

WX152

Bis-Alkenyl Succinimide Ashless Dispersant

Series: Ashless Dispersants

Made with BASF polyisobutylene. Good low-temperature dispersancy and a degree of high-temperature detergency, with good compatibility with detergents and antioxidant/anti-corrosion agents. Also used in quenching oils and fuel additives. Thermal (chlorine-free) process.



ATTRIBUTES **Bis-Succinimide** **Chlorine-Free**

END USES Fuel additives & specialty Engine oils

Technical Parameters

PROPERTY	SPECIFICATION	TEST METHOD
Appearance	Reddish-brown viscous transparent liquid	Visual
Kinematic Viscosity @100 °C, mm ² /s	≤220	GB/T 265
Total Base Number, mg KOH/g	15–30	SH/T 0251
Nitrogen, %	1.15–1.35	SH/T 0224
Color (Diluted)	≤4	GB/T 6540
Mechanical Impurities, %	≤0.08	GB/T 511
Flash Point (Open Cup), °C	≥180	GB/T 267
Water Content, %	≤0.08	GB/T 260
Dispersancy (SDT)	≥55	Appendix

Values are release specifications from the product TDS unless marked typical; the certificate of analysis shipped with each lot is the reference for that lot. Treat rates are guidance and depend on base oil and target performance level — our technical team is available to confirm dosage for your formulation.

Wuxi South Petroleum Additives Co., Ltd.

ADDRESS	TEL	EMAIL	WEB
48 Daqiao Road, Shitangwan, Huishan District, Wuxi, Jiangsu 214185, China	+86 510 8326 0848	sale@wxnfcn.com	www.wxnfcn.cn