

# WX400

## Overbased Calcium Sulfonate Detergent

Series: Sulfonate Detergents

Excellent high-temperature detergency with outstanding acid-neutralizing and rust-preventive performance. Widely used in turbocharged diesel engine oils, marine cylinder oils, crankcase lubricants and premium greases.



ATTRIBUTES Overbased

END USES Greases Marine oils Engine oils

### Technical Parameters

| PROPERTY                                        | SPECIFICATION | TEST METHOD |
|-------------------------------------------------|---------------|-------------|
| Kinematic Viscosity @100 °C, mm <sup>2</sup> /s | ≤150          | GB/T 265    |
| Calcium, %                                      | ≥15           | SH/T 0297   |
| Density @20 °C, g/cm <sup>3</sup>               | 1.10-1.25     | GB/T 2540   |
| Flash Point (Open Cup), °C                      | ≥170          | GB/T 3536   |
| Turbidity, JTU                                  | ≤180          | SH/T 0028   |
| Total Base Number, mg KOH/g                     | ≥395          | SH/T 0251   |

Values are release specifications from the product TDS unless marked typical; the certificate of analysis shipped with each lot is the reference for that lot. Treat rates are guidance and depend on base oil and target performance level — our technical team is available to confirm dosage for your formulation.

#### Wuxi South Petroleum Additives Co., Ltd.

|                                                                           |                   |                 |               |
|---------------------------------------------------------------------------|-------------------|-----------------|---------------|
| ADDRESS                                                                   | TEL               | EMAIL           | WEB           |
| 48 Daqiao Road, Shitangwan, Huishan District, Wuxi, Jiangsu 214185, China | +86 510 8326 0848 | sale@wxnfcn.com | www.wxnfcn.cn |