

WX101

Low-Base Calcium Petroleum Sulfonate Detergent

Series: Sulfonate Detergents

Offers good detergency, dispersancy and rust protection. Used in blending marine lubricants, automotive lubricants and rust-preventive oils.

ATTRIBUTES

Low Base Number

END USES

Industrial & hydraulic oils

Marine oils

Engine oils



Technical Parameters

PROPERTY	SPECIFICATION	TEST METHOD
Kinematic Viscosity @100 °C, mm ² /s	Report	GB/T 265
Calcium, %	2.0-3.0	SH/T 0297
Density @20 °C, g/cm ³	0.90-1.00	GB/T 2540
Flash Point (Open Cup), °C	≥180	GB/T 3536
Turbidity, JTU	Report	SH/T 0028
Total Base Number, mg KOH/g	20-30	SH/T 0251
Water Content, %	≤0.08	GB/T 260
Mechanical Impurities, %	≤0.08	GB/T 511
Active Content, %	≥45	SH/T 0043

Values are release specifications from the product TDS unless marked typical; the certificate of analysis shipped with each lot is the reference for that lot. Treat rates are guidance and depend on base oil and target performance level — our technical team is available to confirm dosage for your formulation.

Wuxi South Petroleum Additives Co., Ltd.

ADDRESS

48 Daqiao Road, Shitangwan, Huishan District, Wuxi, Jiangsu
214185, China

TEL

+86 510 8326 0848

EMAIL

sale@wxnfcn.com

WEB

www.wxnfcn.cn