

WX105

Medium-Base Synthetic Calcium Sulfonate Detergent

Series: Sulfonate Detergents

Provides good acid-neutralizing capability and high-temperature detergency together with a degree of rust protection. Mainly used in blending mid- to high-tier internal combustion engine oils such as CC, CD, SE and SF grades.

ATTRIBUTES Medium Base Number

END USES Engine oils



Technical Parameters

PROPERTY	SPECIFICATION	TEST METHOD
Appearance	Reddish-brown transparent viscous liquid	Visual
Kinematic Viscosity @100 °C, mm ² /s	≤30	GB/T 265
Calcium, %	≥6.5	SH/T 0297
Density @20 °C, g/cm ³	1.10-1.20	GB/T 2540
Flash Point (Open Cup), °C	≥170	GB/T 3536
Turbidity, JTU	≤250	SH/T 0028
Total Base Number, mg KOH/g	≥145	SH/T 0251

Values are release specifications from the product TDS unless marked typical; the certificate of analysis shipped with each lot is the reference for that lot. Treat rates are guidance and depend on base oil and target performance level — our technical team is available to confirm dosage for your formulation.

Wuxi South Petroleum Additives Co., Ltd.

ADDRESS	TEL	EMAIL	WEB
48 Daqiao Road, Shitangwan, Huishan District, Wuxi, Jiangsu 214185, China	+86 510 8326 0848	sale@wxnfcn.com	www.wxnfcn.cn