

WX106B

High-Base Synthetic Calcium Alkylbenzene Sulfonate Detergent

Series: Sulfonate Detergents

Excellent acid-neutralizing capability with good high-temperature detergency. Developed specifically for marine oils, and also used in mid-to high-tier engine oils and heavy-duty diesel engine oils — particularly for engines burning high-sulfur fuels.

ATTRIBUTES

High Base NumberMarine

END USES

Marine oilsEngine oils



Technical Parameters

PROPERTY	SPECIFICATION	TEST METHOD
Appearance	Reddish-brown transparent viscous liquid	Visual
Kinematic Viscosity @100 °C, mm ² /s	≤200	GB/T 265
Calcium, %	≥11.5	SH/T 0297
Density @20 °C, g/cm ³	1.10-1.20	GB/T 2540
Flash Point (Open Cup), °C	≥170	GB/T 3536
Turbidity, JTU	≤250	SH/T 0028
Total Base Number, mg KOH/g	≥300	SH/T 0251

Values are release specifications from the product TDS unless marked typical; the certificate of analysis shipped with each lot is the reference for that lot. Treat rates are guidance and depend on base oil and target performance level — our technical team is available to confirm dosage for your formulation.

Wuxi South Petroleum Additives Co., Ltd.