

WX106D

High-Base Magnesium Sulfonate Detergent

Series: Sulfonate Detergents

Provides good detergency for blending low-ash automotive lubricants; widely used in API GF-5, FA-4 and higher-tier additive packages.

ATTRIBUTES

High Base Number

Magnesium

Low Ash

END USES

Engine oils



Technical Parameters

PROPERTY	SPECIFICATION	TEST METHOD
Kinematic Viscosity @100 °C, mm ² /s	Report	GB/T 265
Magnesium, %	≥8.5	ASTM D4951
Density @20 °C, g/cm ³	≥1.10	GB/T 2540
Flash Point (Open Cup), °C	≥170	GB/T 3536
Total Base Number, mg KOH/g	≥395	SH/T 0251

Values are release specifications from the product TDS unless marked typical; the certificate of analysis shipped with each lot is the reference for that lot. Treat rates are guidance and depend on base oil and target performance level — our technical team is available to confirm dosage for your formulation.

Wuxi South Petroleum Additives Co., Ltd.

ADDRESS

48 Daqiao Road, Shitangwan, Huishan District, Wuxi, Jiangsu
214185, China

TEL

+86 510 8326 0848

EMAIL

sale@wxnfcn.com

WEB

www.wxnfcn.cn