

WX115B

High-Base Sulfurized Calcium Alkylphenate Detergent

Series: Sulfurized Calcium Alkylphenate Detergents

Good high-temperature detergency with strong acid-neutralizing capability and antioxidant/anti-corrosion performance; highly effective at controlling top-ring carbon deposits. Mainly used in marine cylinder oils and mid- to high-tier engine oils.

ATTRIBUTES

High Base Number

Marine

END USES

Marine oils

Engine oils



Technical Parameters

PROPERTY	SPECIFICATION	TEST METHOD
Kinematic Viscosity @100 °C, mm ² /s	≤300	GB/T 265
Total Base Number, mg KOH/g	≥245	SH/T 0251
Calcium, %	≥9.0	SH/T 0297
Mechanical Impurities, %	≤0.1	GB/T 511
Flash Point (Open Cup), °C	≥170	GB/T 267
Sulfur, %	2.9-3.8	SH/T 0303
Water Content, %	≤0.1	SH/T 260

Values are release specifications from the product TDS unless marked typical; the certificate of analysis shipped with each lot is the reference for that lot. Treat rates are guidance and depend on base oil and target performance level — our technical team is available to confirm dosage for your formulation.

Wuxi South Petroleum Additives Co., Ltd.

ADDRESS

48 Daqiao Road, Shitangwan, Huishan District, Wuxi, Jiangsu
214185, China

TEL

+86 510 8326 0848

EMAIL

sale@wxnfcn.com

WEB

www.wxnfcn.cn