

# WX151

## Mono-Alkenyl Succinimide Ashless Dispersant

Series: Ashless Dispersants

Made with BASF polyisobutylene. Excellent control of low-temperature sludge and high-temperature carbon deposit formation, outstanding low-temperature dispersancy, and good solubilization of high-temperature soot. Blended with detergents and antioxidant/anti-corrosion agents for premium gasoline engine oils; also a key raw material for fuel additives. Produced by a thermal (chlorine-free) process, offering better thermal-oxidative stability and dispersancy than chlorination-route products.



ATTRIBUTES

Mono-Succinimide

Chlorine-Free

END USES

Engine oils

Fuel additives & specialty

### Technical Parameters

| PROPERTY                                        | SPECIFICATION                            | TEST METHOD |
|-------------------------------------------------|------------------------------------------|-------------|
| Appearance                                      | Reddish-brown viscous transparent liquid | Visual      |
| Kinematic Viscosity @100 °C, mm <sup>2</sup> /s | ≥220                                     | GB/T 265    |
| Total Base Number, mg KOH/g                     | 45-60                                    | SH/T 0251   |
| Nitrogen, %                                     | ≥2.0                                     | SH/T 0224   |
| Color (Diluted)                                 | ≤3.0                                     | GB/T 6540   |
| Mechanical Impurities, %                        | ≤0.08                                    | GB/T 511    |
| Flash Point (Open Cup), °C                      | ≥180                                     | GB/T 3530   |
| Water Content, %                                | ≤0.08                                    | GB/T 260    |
| Turbidity, JTU                                  | ≤60                                      | SH/T 0028   |

Values are release specifications from the product TDS unless marked typical; the certificate of analysis shipped with each lot is the reference for that lot. Treat rates are guidance and depend on base oil and target performance level — our technical team is available to confirm dosage for your formulation.

#### Wuxi South Petroleum Additives Co., Ltd.

ADDRESS

48 Daqiao Road, Shitangwan, Huishan District, Wuxi, Jiangsu  
214185, China

TEL

+86 510 8326 0848

EMAIL

sale@wxnfcn.com

WEB

www.wxnfcn.cn