

WX152

Bis-Alkenyl Succinimide Ashless Dispersant

Series: Ashless Dispersants

Made with BASF polyisobutylene. Good low-temperature dispersancy and a degree of high-temperature detergency, with good compatibility with detergents and antioxidant/anti-corrosion agents. Also used in quenching oils and fuel additives. Thermal (chlorine-free) process.



ATTRIBUTES

Bis-Succinimide

Chlorine-Free

END USES

Fuel additives & specialty

Engine oils

Technical Parameters

PROPERTY	SPECIFICATION	TEST METHOD
Appearance	Reddish-brown viscous transparent liquid	Visual
Kinematic Viscosity @100 °C, mm ² /s	≤220	GB/T 265
Total Base Number, mg KOH/g	15–30	SH/T 0251
Nitrogen, %	1.15–1.35	SH/T 0224
Color (Diluted)	≤4	GB/T 6540
Mechanical Impurities, %	≤0.08	GB/T 511
Flash Point (Open Cup), °C	≥180	GB/T 267
Water Content, %	≤0.08	GB/T 260
Dispersancy (SDT)	≥55	Appendix

Values are release specifications from the product TDS unless marked typical; the certificate of analysis shipped with each lot is the reference for that lot. Treat rates are guidance and depend on base oil and target performance level — our technical team is available to confirm dosage for your formulation.

Wuxi South Petroleum Additives Co., Ltd.

ADDRESS

48 Daqiao Road, Shitangwan, Huishan District, Wuxi, Jiangsu 214185, China

TEL

+86 510 8326 0848

EMAIL

sale@wxnfcn.com

WEB

www.wxnfcn.cn