

WX208

Zinc Dialkyl Dithiophosphate (Multi-Purpose)

Series: ZDDP Antioxidant & Corrosion Inhibitors

Good antioxidant, anti-corrosion and extreme-pressure anti-wear performance with excellent thermal and hydrolytic stability. Used in blending hydraulic fluids, gear oils, greases and water-based fluids.

ATTRIBUTES

ZDDP

Multi-Purpose

END USES

Industrial & hydraulic oils

Greases



Technical Parameters

PROPERTY	SPECIFICATION	TEST METHOD
Appearance	Amber transparent liquid	Visual
Density @20 °C, g/cm ³	1.10-1.18	GB/T 2540
Kinematic Viscosity @100 °C, mm ² /s	Report	GB/T 265
Sulfur, %	18.0-19.0	SH/T 0303
Phosphorus, %	8.5-9.5	SH/T 0296
Zinc, %	10.0-11.0	SH/T 0226
Flash Point (Open Cup), °C	≥150	GB/T 3536
Color	≤4.0	GB/T 6540
Mechanical Impurities, %	≤0.07	GB/T 511
Water Content, %	≤0.06	GB/T 260

Values are release specifications from the product TDS unless marked typical; the certificate of analysis shipped with each lot is the reference for that lot. Treat rates are guidance and depend on base oil and target performance level — our technical team is available to confirm dosage for your formulation.

Wuxi South Petroleum Additives Co., Ltd.

ADDRESS

48 Daqiao Road, Shitangwan, Huishan District, Wuxi, Jiangsu
214185, China

TEL

+86 510 8326 0848

EMAIL

sale@wxnfcn.com

WEB

www.wxnfcn.cn