

WX105

Medium-Base Synthetic Calcium Sulfonate Detergent, TBN 145

Series: Sulfonate Detergents

Provides good acid-neutralizing capability and high-temperature detergency together with a degree of rust protection. Mainly used in blending mid- to high-tier internal combustion engine oils such as API CC/CD diesel and SE/SF gasoline engine oils.

ATTRIBUTES

Mid TBN

TBN 145

END USES

Engine oils



Technical Parameters

PROPERTY	SPECIFICATION	TEST METHOD
Appearance	Reddish-brown transparent viscous liquid	Visual
Kinematic Viscosity @100 °C, mm ² /s	≤30	GB/T 265
Calcium, wt%	≥6.5	SH/T 0297
Density @20 °C, g/cm ³	1.10-1.20	GB/T 2540
Flash Point (Open Cup), °C	≥170	GB/T 3536
Turbidity, JTU	≤250	SH/T 0028
Total Base Number, mg KOH/g	≥145	SH/T 0251

Values are release specifications from the product TDS unless marked typical; the certificate of analysis shipped with each lot is the reference for that lot. Treat rates are guidance and depend on base oil and target performance level — our technical team is available to confirm dosage for your formulation.

Wuxi South Petroleum Additives Co., Ltd.

ADDRESS

48 Daqiao Road, Shitangwan, Huishan District, Wuxi, Jiangsu
214185, China

TEL

+86 510 8326 0848

EMAIL

sale@wxnfcn.com

WEB

www.wxnfcn.cn