

WX115A

Medium-Base Sulfurized Calcium Phenate, TBN 145

Series: Sulfurized Calcium Phenate Detergents

Very good high-temperature detergency and good oxidation resistance, with a pronounced effect on suppressing top-ring carbon deposit formation in diesel engines. Mainly used in blending mid- to high-tier diesel engine oils.

ATTRIBUTES

Mid TBN

TBN 145

END USES

Engine oils



Technical Parameters

PROPERTY	SPECIFICATION	TEST METHOD
Kinematic Viscosity @100 °C, mm ² /s	≤200	GB/T 265
Total Base Number, mg KOH/g	≥145	SH/T 0251
Calcium, wt%	≥5.0	SH/T 0297
Sediment (mechanical impurities), wt%	≤0.1	GB/T 511
Flash Point (Open Cup), °C	≥170	GB/T 267
Sulfur, wt%	2.3-2.8	SH/T 0303
Water Content, wt%	≤0.1	GB/T 260

Values are release specifications from the product TDS unless marked typical; the certificate of analysis shipped with each lot is the reference for that lot. Treat rates are guidance and depend on base oil and target performance level — our technical team is available to confirm dosage for your formulation.

Wuxi South Petroleum Additives Co., Ltd.

ADDRESS	TEL	EMAIL	WEB
48 Daqiao Road, Shitangwan, Huishan District, Wuxi, Jiangsu 214185, China	+86 510 8326 0848	sale@wxnfcn.com	www.wxnfcn.cn