

# WX161

## High-Molecular-Weight Succinimide Ashless Dispersant

Series: Ashless Dispersants

Based on highly reactive polyisobutylene (HR-PIB). Excellent high-temperature detergency and good low-temperature dispersancy. Produced by a thermal process, it outperforms conventional ashless dispersants in high- and low-temperature dispersancy and soot handling. Chlorine-free. Widely used in mid- to high-tier gasoline and diesel engine oils. Typical treat rate 1%–5%.

ATTRIBUTES

High Molecular Weight

Chlorine-Free

END USES

Engine oils



### Technical Parameters

| PROPERTY                                        | SPECIFICATION                            | TEST METHOD |
|-------------------------------------------------|------------------------------------------|-------------|
| Appearance                                      | Reddish-brown viscous transparent liquid | Visual      |
| Kinematic Viscosity @100 °C, mm <sup>2</sup> /s | 300–500                                  | GB/T 265    |
| Total Base Number, mg KOH/g                     | 15–30                                    | SH/T 0251   |
| Nitrogen, wt%                                   | 1.0–1.1                                  | GB/T 9170   |
| ASTM Color (diluted sample)                     | ≤3.5                                     | GB/T 6540   |
| Sediment (mechanical impurities), wt%           | ≤0.08                                    | GB/T 511    |
| Flash Point (Open Cup), °C                      | ≥180                                     | GB/T 3536   |
| Water Content, wt%                              | ≤0.08                                    | GB/T 260    |

Values are release specifications from the product TDS unless marked typical; the certificate of analysis shipped with each lot is the reference for that lot. Treat rates are guidance and depend on base oil and target performance level — our technical team is available to confirm dosage for your formulation.

#### Wuxi South Petroleum Additives Co., Ltd.

ADDRESS

48 Daqiao Road, Shitangwan, Huishan District, Wuxi, Jiangsu  
214185, China

TEL

+86 510 8326 0848

EMAIL

sale@wxnfcn.com

WEB

www.wxnfcn.cn

Recommended Treat Rate

| PERFORMANCE LEVEL  | TREAT RATE |
|--------------------|------------|
| Typical treat rate | 1%–5%      |

Values are release specifications from the product TDS unless marked typical; the certificate of analysis shipped with each lot is the reference for that lot. Treat rates are guidance and depend on base oil and target performance level — our technical team is available to confirm dosage for your formulation.

Wuxi South Petroleum Additives Co., Ltd.

ADDRESS

48 Daqiao Road, Shitangwan, Huishan District, Wuxi, Jiangsu  
214185, China

TEL

+86 510 8326 0848

EMAIL

sale@wxnfcn.com

WEB

www.wxnfcn.cn