

WX205

Mixed Primary/Secondary ZDDP (C3/C8 alcohols)

Series: ZDDP Antiwear & Antioxidant Additives

Good antioxidant, anti-corrosion and extreme-pressure anti-wear performance. Used in conventional engine oils and industrial lubricants.

ATTRIBUTES

ZDDP

Mixed

END USES

Engine oils

Industrial & hydraulic oils



Technical Parameters

PROPERTY	SPECIFICATION	TEST METHOD
Appearance	Amber transparent liquid	Visual
Density @20 °C, g/cm³	1.10-1.18	GB/T 2540
Kinematic Viscosity @100 °C, mm²/s	Report	GB/T 265
Sulfur, wt%	16.0-18.5	SH/T 0303
Phosphorus, wt%	8.5-9.5	SH/T 0296
Zinc, wt%	9.5-10.8	SH/T 0226
Flash Point (Open Cup), °C	≥180	GB/T 3536
Color	≤4.0	GB/T 6540
Sediment (mechanical impurities), wt%	≤0.07	GB/T 511
Water Content, wt%	≤0.06	GB/T 260
Thermal Decomposition Temperature, °C	≥220	SH/T 0561
pH	≥5.0	—

Values are release specifications from the product TDS unless marked typical; the certificate of analysis shipped with each lot is the reference for that lot. Treat rates are guidance and depend on base oil and target performance level — our technical team is available to confirm dosage for your formulation.

Wuxi South Petroleum Additives Co., Ltd.

ADDRESS

48 Daqiao Road, Shitangwan, Huishan District, Wuxi, Jiangsu
214185, China

TEL

+86 510 8326 0848

EMAIL

sale@wxnfcn.com

WEB

www.wxnfcn.cn