

WX115B

Medium Overbased Sulfurized Calcium Phenate, TBN 245

Series: Sulfurized Calcium Phenate Detergents

Good high-temperature detergency with strong acid-neutralizing capability and antioxidant/anti-corrosion performance; highly effective at controlling top-ring carbon deposits. Mainly used in marine cylinder oils and mid- to high-tier engine oils.

ATTRIBUTES

MOB

TBN 245

Marine

END USES

Marine oils

Engine oils



Technical Parameters

PROPERTY	SPECIFICATION	TEST METHOD
Kinematic Viscosity @100 °C, mm ² /s	≤300	GB/T 265
Total Base Number, mg KOH/g	≥245	SH/T 0251
Calcium, wt%	≥9.0	SH/T 0297
Sediment (mechanical impurities), wt%	≤0.1	GB/T 511
Flash Point (Open Cup), °C	≥170	GB/T 267
Sulfur, wt%	2.9–3.8	SH/T 0303
Water Content, wt%	≤0.1	GB/T 260

Values are release specifications from the product TDS unless marked typical; the certificate of analysis shipped with each lot is the reference for that lot. Treat rates are guidance and depend on base oil and target performance level — our technical team is available to confirm dosage for your formulation.

Wuxi South Petroleum Additives Co., Ltd.