

WX115C

High Overbased Sulfurized Calcium Phenate, TBN 295

Series: Sulfurized Calcium Phenate Detergents

Good high-temperature detergency with strong acid-neutralizing capability and antioxidant/anti-corrosion performance; highly effective at controlling top-ring carbon deposits. Mainly used in marine cylinder oils and mid- to high-tier engine oils.

ATTRIBUTES

HOB

TBN 295

Marine

END USES

Marine oils

Engine oils



Technical Parameters

PROPERTY	SPECIFICATION	TEST METHOD
Kinematic Viscosity @100 °C, mm ² /s	Report	GB/T 265
Total Base Number, mg KOH/g	≥295	SH/T 0251
Calcium, wt%	≥10.0	SH/T 0297
Sediment (mechanical impurities), wt%	≤0.1	GB/T 511
Flash Point (Open Cup), °C	≥170	GB/T 267
Sulfur, wt%	2.5–3.5	SH/T 0303
Water Content, wt%	≤0.1	GB/T 260

Values are release specifications from the product TDS unless marked typical; the certificate of analysis shipped with each lot is the reference for that lot. Treat rates are guidance and depend on base oil and target performance level — our technical team is available to confirm dosage for your formulation.

Wuxi South Petroleum Additives Co., Ltd.

ADDRESS

48 Daqiao Road, Shitangwan, Huishan District, Wuxi, Jiangsu
214185, China

TEL

+86 510 8326 0848

EMAIL

sale@wxnfcn.com

WEB

www.wxnfcn.cn