

WX154B

Borated Succinimide Ashless Dispersant

Series: Ashless Dispersants

A borated ashless dispersant prepared from highly reactive polyisobutylene (Mn = 1000) via a thermal process. Excellent detergency and dispersancy — suppresses piston carbon and varnish formation — with additional antioxidant and anti-wear properties. Improves oil compatibility with fluoroelastomer seals and reduces high-temperature corrosion of copper-lead bearings. Chlorine-free. Used together with detergents it effectively controls low-temperature engine sludge and reduces varnish and carbon deposits on hot components. Typical treat rate 1%–5%.



ATTRIBUTES

Borated

Chlorine-Free

END USES

Engine oils

Technical Parameters

PROPERTY	SPECIFICATION	TEST METHOD
Appearance	Reddish-brown viscous transparent liquid	Visual
Density @20 °C, kg/m ³	890–940	GB/T 1884
Nitrogen, wt%	1.1–1.3	SH/T 2070
Boron, wt%	0.3–0.4	SH/T 0227
Kinematic Viscosity @100 °C, mm ² /s	≤200	GB/T 265
Sediment (mechanical impurities), wt%	≤0.08	GB/T 511
Flash Point (Open Cup), °C	≥180	GB/T 267

Values are release specifications from the product TDS unless marked typical; the certificate of analysis shipped with each lot is the reference for that lot. Treat rates are guidance and depend on base oil and target performance level — our technical team is available to confirm dosage for your formulation.

Wuxi South Petroleum Additives Co., Ltd.

ADDRESS

48 Daqiao Road, Shitangwan, Huishan District, Wuxi, Jiangsu
214185, China

TEL

+86 510 8326 0848

EMAIL

sale@wxnfcn.com

WEB

www.wxnfcn.cn

Recommended Treat Rate

PERFORMANCE LEVEL	TREAT RATE
Typical treat rate	1%–5%

Values are release specifications from the product TDS unless marked typical; the certificate of analysis shipped with each lot is the reference for that lot. Treat rates are guidance and depend on base oil and target performance level — our technical team is available to confirm dosage for your formulation.

Wuxi South Petroleum Additives Co., Ltd.

ADDRESS

48 Daqiao Road, Shitangwan, Huishan District, Wuxi, Jiangsu
214185, China

TEL

+86 510 8326 0848

EMAIL

sale@wxnfcn.com

WEB

www.wxnfcn.cn