

WX203

Zinc Di-(2-ethylhexyl) Dithiophosphate — Primary ZDDP

Series: ZDDP Antiwear & Antioxidant Additives

Excellent antioxidant, anti-corrosion and extreme-pressure anti-wear performance with exceptional thermal stability. Used in mid- to high-tier diesel engine oils.

ATTRIBUTES

ZDDP

Primary

High Thermal Stability

END USES

Engine oils



Technical Parameters

PROPERTY	SPECIFICATION	TEST METHOD
Appearance	Amber transparent liquid	Visual
Density @20 °C, g/cm ³	1.06-1.15	GB/T 2540
Kinematic Viscosity @100 °C, mm ² /s	Report	GB/T 265
Sulfur, wt%	14.0-18	SH/T 0303
Phosphorus, wt%	7.5-8.8	SH/T 0296
Zinc, wt%	9.0-10.5	SH/T 0226
Flash Point (Open Cup), °C	≥180	GB/T 3536
ASTM Color (diluted sample)	≤2.0	GB/T 6540
Sediment (mechanical impurities), wt%	≤0.07	GB/T 511
Water Content, wt%	≤0.03	GB/T 260
Thermal Decomposition Temperature, °C	≥230	SH/T 0561

Values are release specifications from the product TDS unless marked typical; the certificate of analysis shipped with each lot is the reference for that lot. Treat rates are guidance and depend on base oil and target performance level — our technical team is available to confirm dosage for your formulation.

Wuxi South Petroleum Additives Co., Ltd.

ADDRESS

48 Daqiao Road, Shitangwan, Huishan District, Wuxi, Jiangsu
214185, China

TEL

+86 510 8326 0848

EMAIL

sale@wxnfcn.com

WEB

www.wxnfcn.cn