

WX400

High Overbased Calcium Sulfonate Detergent, TBN 400

Series: Sulfonate Detergents

Excellent high-temperature detergency with outstanding acid-neutralizing and rust-preventive performance. Widely used in turbocharged diesel engine oils, marine cylinder oils, crankcase lubricants and premium greases.

ATTRIBUTES

HOB

TBN 400

END USES

Engine oils

Marine oils

Greases



Technical Parameters

PROPERTY	SPECIFICATION	TEST METHOD
Kinematic Viscosity @100 °C, mm ² /s	≤150	GB/T 265
Calcium, wt%	≥15	SH/T 0297
Density @20 °C, g/cm ³	1.10–1.25	GB/T 2540
Flash Point (Open Cup), °C	≥170	GB/T 3536
Turbidity, JTU	≤180	SH/T 0028
Total Base Number, mg KOH/g	≥395	SH/T 0251

Values are release specifications from the product TDS unless marked typical; the certificate of analysis shipped with each lot is the reference for that lot. Treat rates are guidance and depend on base oil and target performance level — our technical team is available to confirm dosage for your formulation.

Wuxi South Petroleum Additives Co., Ltd.

ADDRESS

48 Daqiao Road, Shitangwan, Huishan District, Wuxi, Jiangsu
214185, China

TEL

+86 510 8326 0848

EMAIL

sale@wxnfcn.com

WEB

www.wxnfcn.cn