

WX8057

Liquid Alkylated Diphenylamine Antioxidant

Series: Ashless Antioxidants

Suitable for engine oils, transformer oils, ATF and transmission fluids, slideway oils, quench and heat-transfer oils, and greases.

ATTRIBUTES

AshlessAlkylated Diphenylamine

END USES

Industrial & hydraulic oilsGreasesEngine oils

Technical Parameters

PROPERTY	SPECIFICATION
Appearance	Clear, pale amber to dark amber
Density @25 °C, g/cm ³	0.976
Kinematic Viscosity @40 °C, mm ² /s	281
Nitrogen, wt%	4.6
Flash Point (COC), °C	>185

Recommended Treat Rate

PERFORMANCE LEVEL	TREAT RATE
Lubricating & transformer oils (typical)	0.1–1.0 wt%

Packaging & Storage

For precise treat rate recommendations please contact a company representative. Storage: max blending temperature 70 °C; max storage temperature 50 °C; for long-term storage 25–40 °C is recommended. Keep free of water.

Values are release specifications from the product TDS unless marked typical; the certificate of analysis shipped with each lot is the reference for that lot. Treat rates are guidance and depend on base oil and target performance level — our technical team is available to confirm dosage for your formulation.

Wuxi South Petroleum Additives Co., Ltd.

ADDRESS	TEL	EMAIL	WEB
48 Daqiao Road, Shitangwan, Huishan District, Wuxi, Jiangsu 214185, China	+86 510 8326 0848	sale@wxnfcn.com	www.wxnfcn.cn