

CHAPTER 12

12.1 Reorder so that equations are diagonally dominant:

$$6x_1 - x_2 = 5$$

$$3x_1 + 8x_2 = 11$$

First iteration:

$$x_1 = \frac{5 + x_2}{6} = \frac{5 + 0}{6} = 0.8333$$

$$x_{1,r} = \lambda x_1 + (1 - \lambda)x_1^{old} = 1.25(0.8333) - 0.25(0) = 1.041667$$

$$x_2 = \frac{11 - 3x_1}{8} = \frac{11 - 3(1.041667)}{8} = 0.984375$$

$$x_{2,r} = \lambda x_2 + (1 - \lambda)x_2^{old} = 1.25(0.984375) - 0.25(0) = 1.2305$$

$$\varepsilon_{a,1} = \left| \frac{1.041667 - 0}{1.041667} \right| \times 100\% = 100\% \quad \varepsilon_{a,2} = \left| \frac{1.2305 - 0}{1.2305} \right| \times 100\% = 100\%$$

Second iteration:

$$x_1 = \frac{5 + 1.2305}{6} = 1.0384$$

$$x_{1,r} = 1.25(1.0384) - 0.25(1.041667) = 1.0376$$

$$x_2 = \frac{11 - 3(1.2305)}{8} = 0.9859$$

$$x_{2,r} = 1.25(0.9859) - 0.25(1.2305) = 0.92476$$

$$\varepsilon_{a,1} = \left| \frac{1.0376 - 1.041667}{1.0376} \right| \times 100\% = 0.39\% \quad \varepsilon_{a,2} = \left| \frac{0.92476 - 1.2305}{0.92476} \right| \times 100\% = 33.06\%$$

Third iteration:

$$x_1 = \frac{5 + 0.924759}{6} = 0.98746$$

$$x_{1,r} = 1.25(0.98746) - 0.25(1.037598) = 0.974925$$

$$x_2 = \frac{11 - 3(0.974925)}{8} = 1.009403$$

$$x_{2,r} = 1.25(1.009403) - 0.25(0.924759) = 1.030564$$

$$\varepsilon_{a,1} = \left| \frac{0.974925 - 1.037598}{0.974925} \right| \times 100\% = 6.43\% \quad \varepsilon_{a,2} = \left| \frac{1.030564 - 0.924759}{1.030564} \right| \times 100\% = 10.27\%$$

The exact solution is $x_1 = 1$ and $x_2 = 1$ and the true errors are

$$\varepsilon_{t,1} = \left| \frac{1 - 0.974925}{1} \right| \times 100\% = 2.51\% \quad \varepsilon_{t,2} = \left| \frac{1 - 1.030564}{1} \right| \times 100\% = 3.06\%$$

12.2 The first iteration can be implemented as

$$x_1 = \frac{41 + 0.4x_2}{0.8} = \frac{41 + 0.4(0)}{0.8} = 51.25$$

$$x_2 = \frac{25 + 0.4x_1 + 0.4x_3}{0.8} = \frac{25 + 0.4(51.25) + 0.4(0)}{0.8} = 56.875$$

$$x_3 = \frac{105 + 0.4x_2}{0.8} = \frac{105 + 0.4(56.875)}{0.8} = 159.6875$$

Second iteration:

$$x_1 = \frac{41 + 0.4(56.875)}{0.8} = 79.6875$$

$$x_2 = \frac{25 + 0.4(79.6875) + 0.4(159.6875)}{0.8} = 150.9375$$

$$x_3 = \frac{105 + 0.4(150.9375)}{0.8} = 206.7188$$

The error estimates can be computed as

$$\varepsilon_{a,1} = \left| \frac{79.6875 - 51.25}{79.6875} \right| \times 100\% = 35.69\%$$

$$\varepsilon_{a,2} = \left| \frac{150.9375 - 56.875}{150.9375} \right| \times 100\% = 62.32\%$$

$$\varepsilon_{a,3} = \left| \frac{206.7188 - 159.6875}{206.7188} \right| \times 100\% = 22.75\%$$

The remainder of the calculation proceeds until all the errors fall below the stopping criterion of 5%. The entire computation can be summarized as

iteration	unknown	value	ε_a	maximum ε_a
1	x_1	51.25	100.00%	100.00%
	x_2	56.875	100.00%	
	x_3	159.6875	100.00%	
2	x_1	79.6875	35.69%	62.32%
	x_2	150.9375	62.32%	
	x_3	206.7188	22.75%	
3	x_1	126.7188	37.11%	37.11%
	x_2	197.9688	23.76%	
	x_3	230.2344	10.21%	
4	x_1	150.2344	15.65%	15.65%
	x_2	221.4844	10.62%	
	x_3	241.9922	4.86%	
5	x_1	161.9922	7.26%	7.26%
	x_2	233.2422	5.04%	
	x_3	247.8711	2.37%	
6	x_1	167.8711	3.50%	3.50%
	x_2	239.1211	2.46%	
	x_3	250.8105	1.17%	

Thus, after 6 iterations, the maximum error is 3.5% and we arrive at the result: $x_1 = 167.8711$, $x_2 = 239.1211$ and $x_3 = 250.8105$.

(b) The same computation can be developed with relaxation where $\lambda = 1.2$.

First iteration:

$$x_1 = \frac{41 + 0.4x_2}{0.8} = \frac{41 + 0.4(0)}{0.8} = 51.25$$

Relaxation yields: $x_1 = 1.2(51.25) - 0.2(0) = 61.5$

$$x_2 = \frac{25 + 0.4x_1 + 0.4x_3}{0.8} = \frac{25 + 0.4(61.5) + 0.4(0)}{0.8} = 62$$

Relaxation yields: $x_2 = 1.2(62) - 0.2(0) = 74.4$

$$x_3 = \frac{105 + 0.4x_2}{0.8} = \frac{105 + 0.4(62)}{0.8} = 168.45$$

Relaxation yields: $x_3 = 1.2(168.45) - 0.2(0) = 202.14$

Second iteration:

$$x_1 = \frac{41 + 0.4(62)}{0.8} = 88.45$$

Relaxation yields: $x_1 = 1.2(88.45) - 0.2(61.5) = 93.84$

$$x_2 = \frac{25 + 0.4(93.84) + 0.4(202.14)}{0.8} = 179.24$$

Relaxation yields: $x_2 = 1.2(179.24) - 0.2(74.4) = 200.208$

$$x_3 = \frac{105 + 0.4(200.208)}{0.8} = 231.354$$

Relaxation yields: $x_3 = 1.2(231.354) - 0.2(202.14) = 237.1968$

The error estimates can be computed as

$$\varepsilon_{a,1} = \left| \frac{93.84 - 61.5}{93.84} \right| \times 100\% = 34.46\%$$

$$\varepsilon_{a,2} = \left| \frac{200.208 - 74.4}{200.208} \right| \times 100\% = 62.84\%$$

$$\varepsilon_{a,3} = \left| \frac{237.1968 - 202.14}{237.1968} \right| \times 100\% = 14.78\%$$

The remainder of the calculation proceeds until all the errors fall below the stopping criterion of 5%. The entire computation can be summarized as

iteration	unknown	value	relaxation	ε_a	maximum ε_a
1	x_1	51.25	61.5	100.00%	100.000%
	x_2	62	74.4	100.00%	
	x_3	168.45	202.14	100.00%	
2	x_1	88.45	93.84	34.46%	62.839%
	x_2	179.24	200.208	62.84%	
	x_3	231.354	237.1968	14.78%	
3	x_1	151.354	162.8568	42.38%	42.379%
	x_2	231.2768	237.49056	15.70%	
	x_3	249.99528	252.55498	6.08%	
4	x_1	169.99528	171.42298	5.00%	4.997%
	x_2	243.23898	244.38866	2.82%	
	x_3	253.44433	253.6222	0.42%	

Thus, relaxation speeds up convergence. After 4 iterations, the maximum error is 4.997% and we arrive at the result: $x_1 = 171.423$, $x_2 = 244.389$ and $x_3 = 253.622$.

12.3 The first iteration can be implemented as

$$x_1 = \frac{27 - 2x_2 + x_3}{10} = \frac{27 - 2(0) + 0}{10} = 2.7$$

$$x_2 = \frac{-61.5 + 3x_1 - 2x_3}{-6} = \frac{-61.5 + 3(2.7) - 2(0)}{-6} = 8.9$$

$$x_3 = \frac{-21.5 - x_1 - x_2}{5} = \frac{-21.5 - (2.7) - 8.9}{5} = -6.62$$

Second iteration:

$$x_1 = \frac{27 - 2(8.9) - 6.62}{10} = 0.258$$

$$x_2 = \frac{-61.5 + 3(0.258) - 2(-6.62)}{-6} = 7.914333$$

$$x_3 = \frac{-21.5 - (0.258) - 7.914333}{5} = -5.934467$$

The error estimates can be computed as

$$\varepsilon_{a,1} = \left| \frac{0.258 - 2.7}{0.258} \right| \times 100\% = 947\%$$

$$\varepsilon_{a,2} = \left| \frac{7.914333 - 8.9}{7.914333} \right| \times 100\% = 12.45\%$$

$$\varepsilon_{a,3} = \left| \frac{-5.934467 - (-6.62)}{-5.934467} \right| \times 100\% = 11.55\%$$

Note that because $\varepsilon_{a,1}$ is greater than the stopping criterion, the computation of $\varepsilon_{a,2}$ and $\varepsilon_{a,3}$ is unnecessary for this iteration. The remainder of the calculation proceeds until all the errors fall below the stopping criterion of 5%. The entire computation can be summarized as

iteration	unknown	value	ε_a	maximum ε_a
1	x_1	2.7	100.00%	100%
	x_2	8.9	100.00%	
	x_3	-6.62	100.00%	
2	x_1	0.258	946.51%	946%
	x_2	7.914333	12.45%	
	x_3	-5.93447	11.55%	
3	x_1	0.523687	50.73%	50.73%
	x_2	8.010001	1.19%	
	x_3	-6.00674	1.20%	
4	x_1	0.497326	5.30%	5.30%
	x_2	7.999091	0.14%	
	x_3	-5.99928	0.12%	
5	x_1	0.500253	0.59%	0.59%
	x_2	8.000112	0.01%	
	x_3	-6.00007	0.01%	

Thus, after 5 iterations, the maximum error is 0.59% and we arrive at the result: $x_1 = 0.500253$, $x_2 = 8.000112$ and $x_3 = -6.00007$.

12.4 The first iteration can be implemented as

$$x_1 = \frac{27 - 2x_2 + x_3}{10} = \frac{27 - 2(0) + 0}{10} = 2.7$$

$$x_2 = \frac{-61.5 + 3x_1 - 2x_3}{-6} = \frac{-61.5 + 3(0) - 2(0)}{-6} = 10.25$$

$$x_3 = \frac{-21.5 - x_1 - x_2}{5} = \frac{-21.5 - 0 - 0}{5} = -4.3$$

Second iteration:

$$x_1 = \frac{27 - 2(10.25) - 4.3}{10} = 0.22$$

$$x_2 = \frac{-61.5 + 3(2.7) - 2(-4.3)}{-6} = 7.466667$$

$$x_3 = \frac{-21.5 - (2.7) - 10.25}{5} = -6.89$$

The error estimates can be computed as

$$\varepsilon_{a,1} = \left| \frac{0.22 - 2.7}{0.258} \right| \times 100\% = 1127\%$$

$$\varepsilon_{a,2} = \left| \frac{7.466667 - 10.25}{7.466667} \right| \times 100\% = 37.28\%$$

$$\varepsilon_{a,3} = \left| \frac{-6.89 - (-4.3)}{-6.89} \right| \times 100\% = 37.59\%$$

Note that because $\varepsilon_{a,1}$ is greater than the stopping criterion, the computation of $\varepsilon_{a,2}$ and $\varepsilon_{a,3}$ is unnecessary for this iteration. The remainder of the calculation proceeds until all the errors fall below the stopping criterion of 5%. The entire computation can be summarized as

iteration	unknown	value	ϵ_a	maximum ϵ_a
1	x_1	2.7		
	x_2	10.25		
	x_3	-4.3		
2	x_1	0.22	1127.27%	
	x_2	7.466667	37.28%	
	x_3	-6.89	37.59%	1127.27%
3	x_1	0.517667	57.50%	
	x_2	7.843333	4.80%	
	x_3	-5.83733	18.03%	57.50%
4	x_1	0.5476	5.47%	
	x_2	8.045389	2.51%	
	x_3	-5.9722	2.26%	5.47%
5	x_1	0.493702	10.92%	
	x_2	7.985467	0.75%	
	x_3	-6.0186	0.77%	10.92%
6	x_1	0.501047	1.47%	
	x_2	7.99695	0.14%	
	x_3	-5.99583	0.38%	1.47%

Thus, after 6 iterations, the maximum error is 1.47% and we arrive at the result: $x_1 = 0.501047$, $x_2 = 7.99695$ and $x_3 = -5.99583$.

12.5 The first iteration can be implemented as

$$c_1 = \frac{3800 + 3c_2 + c_3}{15} = \frac{3800 + 3(0) + 0}{15} = 253.3333$$

$$c_2 = \frac{1200 + 3c_1 + 6c_3}{18} = \frac{1200 + 3(253.3333) + 6(0)}{18} = 108.8889$$

$$c_3 = \frac{2350 + 4c_1 + c_2}{12} = \frac{2350 + 4(253.3333) + 108.8889}{12} = 289.3519$$

Second iteration:

$$c_1 = \frac{3800 + 3(108.889) + 289.3519}{15} = 294.4012$$

$$c_2 = \frac{1200 + 3(294.4012) + 6(289.3519)}{18} = 212.1842$$

$$c_3 = \frac{2350 + 4(294.4012) + 212.1842}{12} = 311.6491$$

The error estimates can be computed as

$$\epsilon_{a,1} = \left| \frac{294.4012 - 253.3333}{294.4012} \right| \times 100\% = 13.95\%$$

$$\epsilon_{a,2} = \left| \frac{212.1842 - 108.8889}{212.1842} \right| \times 100\% = 48.68\%$$

$$\epsilon_{a,3} = \left| \frac{311.6491 - 289.3519}{311.6491} \right| \times 100\% = 7.15\%$$

Note that because $\varepsilon_{a,1}$ is greater than the stopping criterion, the computation of $\varepsilon_{a,2}$ and $\varepsilon_{a,3}$ is unnecessary for this iteration. The remainder of the calculation can be summarized as

iteration	unknown	value	ε_a	maximum ε_a
1	x_1	253.3333		
	x_2	108.8889		
	x_3	289.3519		
2	x_1	294.4012	13.95%	
	x_2	212.1842	48.68%	
	x_3	311.6491	7.15%	48.68%
3	x_1	316.5468	7.00%	
	x_2	223.3075	4.98%	
	x_3	319.9579	2.60%	7.00%
4	x_1	319.3254	0.87%	
	x_2	226.5402	1.43%	
	x_3	321.1535	0.37%	1.43%

We can stop at this point as all the approximate errors are less than the 5% stopping criterion. Note that after several more iterations, we arrive at the result: $x_1 = 320.2073$, $x_2 = 227.2021$ and $x_3 = 321.5026$.

12.6 The equations must first be rearranged so that they are diagonally dominant

$$-8x_1 + x_2 - 2x_3 = -20$$

$$2x_1 - 6x_2 - x_3 = -38$$

$$-3x_1 - x_2 + 7x_3 = -34$$

(a) The first iteration can be implemented as

$$x_1 = \frac{-20 - x_2 + 2x_3}{-8} = \frac{-20 - 0 + 2(0)}{-8} = 2.5$$

$$x_2 = \frac{-38 - 2x_1 + x_3}{-6} = \frac{-38 - 2(2.5) + 0}{-6} = 7.166667$$

$$x_3 = \frac{-34 + 3x_1 + x_2}{7} = \frac{-34 + 3(2.5) + 7.166667}{7} = -2.761905$$

Second iteration:

$$x_1 = \frac{-20 - 7.166667 + 2(-2.761905)}{-8} = 4.08631$$

$$x_2 = \frac{-38 - 2x_1 + x_3}{-6} = \frac{-38 - 2(4.08631) + (-2.761905)}{-6} = 8.155754$$

$$x_3 = \frac{-34 + 3x_1 + x_2}{7} = \frac{-34 + 3(4.08631) + 8.155754}{7} = -1.94076$$

The error estimates can be computed as

$$\varepsilon_{a,1} = \left| \frac{4.08631 - 2.5}{4.08631} \right| \times 100\% = 38.82\%$$

$$\varepsilon_{a,2} = \left| \frac{8.155754 - 7.166667}{8.155754} \right| \times 100\% = 12.13\%$$

$$\varepsilon_{a,3} = \left| \frac{-1.94076 - (-2.761905)}{-1.94076} \right| \times 100\% = 42.31\%$$

The remainder of the calculation proceeds until all the errors fall below the stopping criterion of 5%. The entire computation can be summarized as

iteration	unknown	value	ε_a	maximum ε_a
0	x_1	0		
	x_2	0		
	x_3	0		
1	x_1	2.5	100.00%	
	x_2	7.166667	100.00%	
	x_3	-2.7619	100.00%	100.00%
2	x_1	4.08631	38.82%	
	x_2	8.155754	12.13%	
	x_3	-1.94076	42.31%	42.31%
3	x_1	4.004659	2.04%	
	x_2	7.99168	2.05%	
	x_3	-1.99919	2.92%	2.92%

Thus, after 3 iterations, the maximum error is 2.92% and we arrive at the result: $x_1 = 4.004659$, $x_2 = 7.99168$ and $x_3 = -1.99919$.

(b) The same computation can be developed with relaxation where $\lambda = 1.2$.

First iteration:

$$x_1 = \frac{-20 - x_2 + 2x_3}{-8} = \frac{-20 - 0 + 2(0)}{-8} = 2.5$$

Relaxation yields: $x_1 = 1.2(2.5) - 0.2(0) = 3$

$$x_2 = \frac{-38 - 2x_1 + x_3}{-6} = \frac{-38 - 2(3) + 0}{-6} = 7.333333$$

Relaxation yields: $x_2 = 1.2(7.333333) - 0.2(0) = 8.8$

$$x_3 = \frac{-34 + 3x_1 + x_2}{7} = \frac{-34 + 3(3) + 8.8}{7} = -2.3142857$$

Relaxation yields: $x_3 = 1.2(-2.3142857) - 0.2(0) = -2.7771429$

Second iteration:

$$x_1 = \frac{-20 - x_2 + 2x_3}{-8} = \frac{-20 - 8.8 + 2(-2.7771429)}{-8} = 4.2942857$$

Relaxation yields: $x_1 = 1.2(4.2942857) - 0.2(3) = 4.5531429$

$$x_2 = \frac{-38 - 2x_1 + x_3}{-6} = \frac{-38 - 2(4.5531429) - 2.7771429}{-6} = 8.3139048$$

Relaxation yields: $x_2 = 1.2(8.3139048) - 0.2(8.8) = 8.2166857$

$$x_3 = \frac{-34 + 3x_1 + x_2}{7} = \frac{-34 + 3(4.5531429) + 8.2166857}{7} = -1.7319837$$

Relaxation yields: $x_3 = 1.2(-1.7319837) - 0.2(-2.7771429) = -1.5229518$

The error estimates can be computed as

$$\varepsilon_{a,1} = \left| \frac{4.5531429 - 3}{4.5531429} \right| \times 100\% = 34.11\%$$

$$\varepsilon_{a,2} = \left| \frac{8.2166857 - 8.8}{8.2166857} \right| \times 100\% = 7.1\%$$

$$\varepsilon_{a,3} = \left| \frac{-1.5229518 - (-2.7771429)}{-1.5229518} \right| \times 100\% = 82.35\%$$

The remainder of the calculation proceeds until all the errors fall below the stopping criterion of 5%. The entire computation can be summarized as

iteration	unknown	value	relaxation	ε_a	maximum ε_a
1	x_1	2.5	3	100.00%	100.000%
	x_2	7.3333333	8.8	100.00%	
	x_3	-2.314286	-2.777143	100.00%	
2	x_1	4.2942857	4.5531429	34.11%	82.353%
	x_2	8.3139048	8.2166857	7.10%	
	x_3	-1.731984	-1.522952	82.35%	
3	x_1	3.9078237	3.7787598	20.49%	32.257%
	x_2	7.8467453	7.7727572	5.71%	
	x_3	-2.12728	-2.248146	32.26%	
4	x_1	4.0336312	4.0846055	7.49%	19.280%
	x_2	8.0695595	8.12892	4.38%	
	x_3	-1.945323	-1.884759	19.28%	
5	x_1	3.9873047	3.9678445	2.94%	8.068%
	x_2	7.9700747	7.9383056	2.40%	
	x_3	-2.022594	-2.050162	8.07%	
6	x_1	4.0048286	4.0122254	1.11%	3.595%
	x_2	8.0124354	8.0272613	1.11%	
	x_3	-1.990866	-1.979007	3.60%	

Thus, relaxation actually seems to retard convergence. After 6 iterations, the maximum error is 3.595% and we arrive at the result: $x_1 = 4.0122254$, $x_2 = 8.0272613$ and $x_3 = -1.979007$.

12.7 As ordered, none of the sets are guaranteed to converge. However, if Set 1 and 2 are reordered so that they are diagonally dominant, they will converge on the solution of (1, 1, 1).

$$\begin{aligned} \text{Set 1: } \quad & 8x + 3y + z = 12 \\ & 2x + 4y - z = 5 \\ & -6x \quad + 7z = 1 \end{aligned}$$

$$\begin{aligned} \text{Set 2: } \quad & 3x + y - z = 3 \\ & x + 4y - z = 4 \\ & x + y + 5z = 7 \end{aligned}$$

PROPRIETARY MATERIAL. © The McGraw-Hill Companies, Inc. All rights reserved. No part of this Manual may be displayed, reproduced or distributed in any form or by any means, without the prior written permission of the publisher, or used beyond the limited distribution to teachers and educators permitted by McGraw-Hill for their individual course preparation. If you are a student using this Manual, you are using it without permission.

Because it is not diagonally dominant, Set 3 will not converge on the correct solution of (1, 1, 1). For example, if they are ordered as

$$\begin{aligned} -2x + 4y - 5z &= -3 \\ 2y - z &= 1 \\ -x + 3y + 5z &= 7 \end{aligned}$$

For this case, Gauss-Seidel iterations yields

iteration	unknown	value	ε_a	maximum ε_a
1	x_1	1.5	100.00%	
	x_2	0.5	100.00%	
	x_3	1.4	100.00%	100.00%
2	x_1	-1	250.00%	
	x_2	1.2	58.33%	
	x_3	0.48	191.67%	250.00%
3	x_1	2.7	137.04%	
	x_2	0.74	62.16%	
	x_3	1.496	67.91%	137.04%
4	x_1	-0.76	455.26%	
	x_2	1.248	40.71%	
	x_3	0.4992	199.68%	455.26%
5	x_1	2.748	127.66%	
	x_2	0.7496	66.49%	
	x_3	1.49984	66.72%	127.66%
6	x_1	-0.7504	466.20%	
	x_2	1.24992	40.03%	
	x_3	0.499968	199.99%	466.20%
7	x_1	2.74992	127.29%	
	x_2	0.749984	66.66%	
	x_3	1.499994	66.67%	127.29%
8	x_1	-0.75002	466.65%	
	x_2	1.249997	40.00%	
	x_3	0.499999	200.00%	466.65%

Alternatively, they can be ordered as

$$\begin{aligned} -x + 3y + 5z &= 7 \\ 2y - z &= 1 \\ -2x + 4y - 5z &= -3 \end{aligned}$$

For this case, Gauss-Seidel iterations yields

iteration	unknown	value	ε_a	maximum ε_a
1	x_1	-7	100.00%	
	x_2	0.5	100.00%	
	x_3	3.8	100.00%	100.00%
2	x_1	13.5	151.85%	
	x_2	2.4	79.17%	
	x_3	-2.88	231.94%	231.94%
3	x_1	-14.2	195.07%	
	x_2	-0.94	355.32%	
	x_3	5.528	152.10%	355.32%
4	x_1	17.82	179.69%	
	x_2	3.264	128.80%	
	x_3	-3.9168	241.14%	241.14%

5	x_1	-16.792	206.12%	
	x_2	-1.4584	323.81%	
	x_3	6.15008	163.69%	323.81%
6	x_1	19.3752	186.67%	
	x_2	3.57504	140.79%	
	x_3	-4.29005	243.36%	243.36%
7	x_1	-17.7251	209.31%	
	x_2	-1.64502	317.32%	
	x_3	6.374029	167.31%	317.32%
8	x_1	19.93507	188.91%	
	x_2	3.687014	144.62%	
	x_3	-4.42442	244.06%	244.06%

12.8 The equations to be solved are

$$f_1(x, y) = -x^2 + x + 0.5 - y$$

$$f_2(x, y) = x^2 - y - 5xy$$

The partial derivatives can be computed and evaluated at the initial guesses

$$\begin{aligned} \frac{\partial f_{1,0}}{\partial x} &= -2x + 1 = -2(1.2) + 1 = -1.4 & \frac{\partial f_{1,0}}{\partial y} &= -1 \\ \frac{\partial f_{2,0}}{\partial x} &= 2x - 5y = 2(1.2) - 5(1.2) = -3.6 & \frac{\partial f_{2,0}}{\partial y} &= -1 - 5x = -1 - 5(1.2) = -7 \end{aligned}$$

They can then be used to compute the determinant of the Jacobian for the first iteration is

$$-1.4(-7) - (-1)(-3.6) = 6.2$$

The values of the functions can be evaluated at the initial guesses as

$$f_{1,0} = -1.2^2 + 1.2 + 0.5 - 1.2 = -0.94$$

$$f_{2,0} = 1.2^2 - 5(1.2)(1.2) - 1.2 = -6.96$$

These values can be substituted into Eq. (12.12) to give

$$\begin{aligned} x_1 &= 1.2 - \frac{-0.94(-3.6) - (-6.96)(-1)}{6.2} = 1.26129 \\ x_2 &= 1.2 - \frac{-6.96(-1.4) - (-0.94)(-3.6)}{6.2} = 0.174194 \end{aligned}$$

The computation can be repeated until an acceptable accuracy is obtained. The results are summarized as

iteration	x	y	ϵ_{a1}	ϵ_{a2}
0	1.2	1.2		
1	1.26129	0.174194	4.859%	588.889%
2	1.234243	0.211619	2.191%	17.685%
3	1.233319	0.212245	0.075%	0.295%
4	1.233318	0.212245	0.000%	0.000%


12.9 (a) The equations can be set up in a form amenable to plotting as

PROPRIETARY MATERIAL. © The McGraw-Hill Companies, Inc. All rights reserved. No part of this Manual may be displayed, reproduced or distributed in any form or by any means, without the prior written permission of the publisher, or used beyond the limited distribution to teachers and educators permitted by McGraw-Hill for their individual course preparation. If you are a student using this Manual, you are using it without permission.

$$y = x^2 - 1$$

$$y = \sqrt{5 - x^2}$$

These can be plotted as



Thus, a solution seems to lie at about $x = y = 1.6$.

(b) The equations can be solved in a number of different ways. For example, the first equation can be solved for x and the second solved for y . For this case, successive substitution does not work

First iteration:

$$x = \sqrt{5 - y^2} = \sqrt{5 - (1.5)^2} = 1.658312$$

$$y = (1.658312)^2 - 1 = 1.75$$

Second iteration:

$$x = \sqrt{5 - (1.75)^2} = 1.391941$$

$$y = (1.391941)^2 - 1 = 0.9375$$

Third iteration:

$$x = \sqrt{5 - (0.9375)^2} = 2.030048$$

$$y = (2.030048)^2 - 1 = 3.12094$$

Thus, the solution is moving away from the solution that lies at approximately $x = y = 1.6$.

An alternative solution involves solving the second equation for x and the first for y . For this case, successive substitution does work

First iteration:

$$x = \sqrt{y + 1} = \sqrt{1.5 + 1} = 1.581139$$

$$y = \sqrt{5 - x^2} = \sqrt{5 - (1.581139)^2} = 1.581139$$

Second iteration:

PROPRIETARY MATERIAL. © The McGraw-Hill Companies, Inc. All rights reserved. No part of this Manual may be displayed, reproduced or distributed in any form or by any means, without the prior written permission of the publisher, or used beyond the limited distribution to teachers and educators permitted by McGraw-Hill for their individual course preparation. If you are a student using this Manual, you are using it without permission.

$$x = \sqrt{1.581139} = 1.606592$$

$$y = \sqrt{5 - (1.606592)^2} = 1.555269$$

Third iteration:

$$x = \sqrt{5 - (1.555269)^2} = 1.598521$$

$$y = (1.598521)^2 - 1 = 1.563564$$

After several more iterations, the calculation converges on the solution of $x = 1.600485$ and $y = 1.561553$.

(c) The equations to be solved are

$$f_1(x, y) = x^2 - y - 1$$

$$f_2(x, y) = 5 - y^2 - x^2$$

The partial derivatives can be computed and evaluated at the initial guesses

$$\frac{\partial f_{1,0}}{\partial x} = 2x$$

$$\frac{\partial f_{1,0}}{\partial y} = -1$$

$$\frac{\partial f_{2,0}}{\partial x} = -2x$$

$$\frac{\partial f_{2,0}}{\partial y} = -2y$$

They can then be used to compute the determinant of the Jacobian for the first iteration is

$$-1.4(-7) - (-1)(-3.6) = 6.2$$

The values of the functions can be evaluated at the initial guesses as

$$f_{1,0} = -1.2^2 + 1.2 + 0.5 - 1.2 = -0.94$$

$$f_{2,0} = 1.2^2 - 5(1.2)(1.2) - 1.2 = -6.96$$

These values can be substituted into Eq. (12.12) to give

$$x_1 = 1.2 - \frac{-0.94(-3.6) - (-6.96)(-1)}{6.2} = 1.26129$$

$$x_2 = 1.2 - \frac{-6.96(-1.4) - (-0.94)(-3.6)}{6.2} = 0.174194$$

The computation can be repeated until an acceptable accuracy is obtained. The results are summarized as


iteration	x_1	x_2	ϵ_{a1}	ϵ_{a2}
0	1.5	1.5		
1	1.604167	1.5625	6.494%	4.000%
2	1.600489	1.561553	0.230%	0.061%
3	1.600485	1.561553	0.000%	0.000%

12.10 The mass balances can be expressed in matrix form as

$$\begin{bmatrix} 2.8 & 0 & 0 & 0 & 0 & -0.8 & 0 & 0 & 0 & 0 \\ -2 & 2.8 & 0 & 0 & 0 & 0 & -0.8 & 0 & 0 & 0 \\ 0 & -2 & 2.8 & 0 & 0 & 0 & 0 & -0.8 & 0 & 0 \\ 0 & 0 & -2 & 2.8 & 0 & 0 & 0 & 0 & -0.8 & 0 \\ 0 & 0 & 0 & -2 & 2.8 & 0 & 0 & 0 & 0 & -0.8 \\ -0.8 & 0 & 0 & 0 & 0 & 1.8 & -1 & 0 & 0 & 0 \\ 0 & -0.8 & 0 & 0 & 0 & 0 & 1.8 & -1 & 0 & 0 \\ 0 & 0 & -0.8 & 0 & 0 & 0 & 0 & 1.8 & -1 & 0 \\ 0 & 0 & 0 & -0.8 & 0 & 0 & 0 & 0 & 1.8 & -1 \\ 0 & 0 & 0 & 0 & -0.8 & 0 & 0 & 0 & 0 & 1.8 \end{bmatrix} \begin{Bmatrix} c_{G1} \\ c_{G2} \\ c_{G3} \\ c_{G4} \\ c_{G5} \\ c_{L1} \\ c_{L2} \\ c_{L3} \\ c_{L4} \\ c_{L5} \end{Bmatrix} = \begin{Bmatrix} 200 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \\ 10 \end{Bmatrix}$$

These equations can then be solved. The results are tabulated and plotted below:

Reactor	Gas	Liquid
0	200	
1	190.9925	168.4737
2	179.4114	150.4587
3	164.5214	127.2965
4	145.3772	97.51656
5	120.7631	59.22807
6		10



12.11 Substituting centered difference finite differences, the Laplace equation can be written for the node (1, 1) as

$$0 = \frac{T_{21} - 2T_{11} + T_{01}}{\Delta x^2} + \frac{T_{12} - 2T_{11} + T_{10}}{\Delta y^2}$$

Because the grid is square ($\Delta x = \Delta y$), this equation can be expressed as

$$0 = T_{21} - 4T_{11} + T_{01} + T_{12} + T_{10}$$

The boundary node values ($T_{01} = 100$ and $T_{10} = 75$) can be substituted to give

$$4T_{11} - T_{12} - T_{21} = 175$$

The same approach can be written for the other interior nodes. When this is done, the following system of equations results

$$\begin{bmatrix} 4 & -1 & -1 & 0 \\ -1 & 4 & 0 & -1 \\ -1 & 0 & 4 & -1 \\ 0 & -1 & -1 & 4 \end{bmatrix} \begin{Bmatrix} T_{11} \\ T_{12} \\ T_{21} \\ T_{22} \end{Bmatrix} = \begin{Bmatrix} 175 \\ 125 \\ 75 \\ 25 \end{Bmatrix}$$

These equations can be solved using the Gauss-Seidel method. For example, the first iteration would be

$$\begin{aligned} T_{11} &= \frac{175 + T_{12} + T_{21}}{4} = \frac{175 + 0 + 0}{4} = 43.75 \\ T_{12} &= \frac{125 + T_{11} + T_{22}}{4} = \frac{125 + 43.75 + 0}{4} = 42.1875 \\ T_{21} &= \frac{75 + T_{11} + T_{22}}{4} = \frac{75 + 43.75 + 0}{4} = 29.6875 \\ T_{22} &= \frac{25 + T_{12} + T_{21}}{4} = \frac{25 + 42.1875 + 29.6875}{4} = 24.21875 \end{aligned}$$

The computation can be continued as follows:

iteration	unknown	value	ε_a	maximum ε_a
0	x_1	0		
	x_2	0		
	x_3	0		
	x_4	0		
1	x_1	43.75	100.00%	
	x_2	42.1875	100.00%	
	x_3	29.6875	100.00%	
	x_4	24.21875	100.00%	100.00%
2	x_1	61.71875	29.11%	
	x_2	52.73438	20.00%	
	x_3	40.23438	26.21%	
	x_4	29.49219	17.88%	29.11%
3	x_1	66.99219	7.87%	
	x_2	55.37109	4.76%	
	x_3	42.87109	6.15%	
	x_4	30.81055	4.28%	7.87%
4	x_1	68.31055	1.93%	
	x_2	56.03027	1.18%	
	x_3	43.53027	1.51%	
	x_4	31.14014	1.06%	1.93%
5	x_1	68.64014	0.48%	
	x_2	56.19507	0.29%	
	x_3	43.69507	0.38%	
	x_4	31.22253	0.26%	0.48%

Thus, after 5 iterations, the maximum error is 0.48% and we are converging on the final result: $T_{11} = 68.75$, $T_{12} = 56.25$, $T_{21} = 43.75$, and $T_{22} = 31.25$.

12.12

```
function [x,ea,iter] = GaussSeidel(A,b,es,maxit)
% GaussSeidel: Gauss Seidel method
%   x = GaussSeidel(A,b): Gauss Seidel without relaxation
% input:
%   A = coefficient matrix
%   b = right hand side vector
%   es = stop criterion (default = 0.00001%)
```

PROPRIETARY MATERIAL. © The McGraw-Hill Companies, Inc. All rights reserved. No part of this Manual may be displayed, reproduced or distributed in any form or by any means, without the prior written permission of the publisher, or used beyond the limited distribution to teachers and educators permitted by McGraw-Hill for their individual course preparation. If you are a student using this Manual, you are using it without permission.

```

% maxit = max iterations (default = 50)
% output:
% x = solution vector
% ea = maximum relative error (%)
% iter = number of iterations

if nargin<2,error('at least 2 input arguments required'),end
if nargin<3|isempty(es),es=0.00001;end
if nargin<4|isempty(maxit),maxit=50;end
[m,n] = size(A);
if m~=n, error('Matrix A must be square'); end
C = A;
for i = 1:n
    C(i,i) = 0;
    x(i) = 0;
end
x = x';
for i = 1:n
    C(i,1:n) = C(i,1:n)/A(i,i);
end
for i = 1:n
    d(i) = b(i)/A(i,i);
end
iter = 0;
while (1)
    xold = x;
    for i = 1:n
        x(i) = d(i)-C(i,:)*x;
        if x(i) ~= 0
            ea(i) = abs((x(i) - xold(i))/x(i)) * 100;
        end
    end
    iter = iter+1;
    if max(ea)<=es | iter >= maxit, break, end
end
ea=max(ea);

```

Example 12.1:

```

>> clear,clc
>> A=[3 -.1 -.2;.1 7 -.3;.3 -.2 10];
>> b=[7.85;-19.3;71.4];
>> [x,ea,iter] = GaussSeidel(A,b)

```

```

x =
    3.0000
   -2.5000
    7.0000
ea =
    6.4417e-008
iter =
     6

```

Prob. 12.2a:

```

>> clear,clc
>> A=[0.8 -0.4 0;-0.4 0.8 -0.4;0 -0.4 0.8];
>> b=[41;25;105];
>> [x,ea,iter] = GaussSeidel(A,b)

```

```

x =

```



```

173.7500
245.0000
253.7500
ea =
    6.4536e-006
iter =
    25

```

12.13

```

function [x,ea,iter] = GaussSeidelRelax(A,b,lambda,es,maxit)
% GaussSeidel: Gauss Seidel method with relaxation
%   x = GaussSeidel(A,b): Gauss Seidel with relaxation
% input:
%   A = coefficient matrix
%   b = right hand side vector
%   lambda = relation factor (default = 1)
%   es = stop criterion (default = 0.00001%)
%   maxit = max iterations (default = 50)
% output:
%   x = solution vector
%   ea = maximum relative error (%)
%   iter = number of iterations

if nargin<2,error('at least 2 input arguments required'),end
if nargin<3|isempty(lambda),lambda=1;end
if nargin<4|isempty(es),es=0.00001;end
if nargin<5|isempty(maxit),maxit=50;end
[m,n] = size(A);
if m~=n, error('Matrix A must be square'); end
C = A;
for i = 1:n
    C(i,i) = 0;
    x(i) = 0;
end
x = x';
for i = 1:n
    C(i,1:n) = C(i,1:n)/A(i,i);
end
for i = 1:n
    d(i) = b(i)/A(i,i);
end
iter = 0;
while (1)
    xold = x;
    for i = 1:n
        x(i) = d(i)-C(i,:)*x;
        x(i) = lambda*x(i) + (1 - lambda)*xold(i);
        if x(i) ~= 0
            ea(i) = abs((x(i) - xold(i))/x(i)) * 100;
        end
    end
    iter = iter+1;
    if max(ea)<=es | iter >= maxit, break, end
end
ea=max(ea);

```

Example 12.2:

```

>> clear,clc
>> A=[10 -2;-3 12];
>> b=[8;9];

```

```
[x,ea,iter] = GaussSeidelRelax(A,b,1.2,[],2)

x =
    1.0531
    0.9783
ea =
    21.4307
iter =
     2
```

Prob. 12.2b:

```
>> clear,clc
>> A=[0.8 -0.4 0;-0.4 0.8 -0.4;0 -0.4 0.8];
>> b=[41;25;105];
>> [x,ea,iter] = GaussSeidelRelax(A,b,1.2)

x =
    173.7500
    245.0000
    253.7500
ea =
    6.1014e-006
iter =
    12
```

12.14

```
function [x,f,ea,iter]=newtmult(func,x0,es,maxit,varargin)
% newtmult: Newton-Raphson root zeroes nonlinear systems
% [x,f,ea,iter]=newtmult(func,x0,es,maxit,p1,p2,...):
%   uses the Newton-Raphson method to find the roots of
%   a system of nonlinear equations
% input:
%   func = name of function that returns f and J
%   x0 = initial guess
%   es = desired percent relative error (default = 0.0001%)
%   maxit = maximum allowable iterations (default = 50)
%   p1,p2,... = additional parameters used by function
% output:
%   x = vector of roots
%   f = vector of functions evaluated at roots
%   ea = approximate percent relative error (%)
%   iter = number of iterations

if nargin<2,error('at least 2 input arguments required'),end
if nargin<3|isempty(es),es=0.0001;end
if nargin<4|isempty(maxit),maxit=50;end
iter = 0;
x=x0;
while (1)
    [J,f]=func(x,varargin{:});
    dx=J\f;
    x=x-dx;
    iter = iter + 1;
    ea=100*max(abs(dx./x));
    if iter>=maxit|ea<=es, break, end
end

function [J,f]=jfreact(x,varargin)
del=0.000001;
df1dx1=(u(x(1)+del*x(1),x(2))-u(x(1),x(2)))/(del*x(1));
```

```

df1dx2=(u(x(1),x(2)+del*x(2))-u(x(1),x(2)))/(del*x(2));
df2dx1=(v(x(1)+del*x(1),x(2))-v(x(1),x(2)))/(del*x(1));
df2dx2=(v(x(1),x(2)+del*x(2))-v(x(1),x(2)))/(del*x(2));
J=[df1dx1 df1dx2;df2dx1 df2dx2];
f1=u(x(1),x(2));
f2=v(x(1),x(2));
f=[f1;f2];
end

```

Example 12.4: The functions are set up as

```

function f=u(x,y)
f=x^2+x*y-10;
end

function f=v(x,y)
f=y+3*x*y^2-57;
end

>> clear,clc
>> x0=[1.5;3.5];
>> [x,f,ea,iter]=newtmult(@jfreact,x0)

x =
    2.0000
    3.0000
f =
    1.0e-004 *
   -0.0129
   -0.2210
ea =
    1.9494e-005
iter =
     4

```

Prob. 12.8: The functions are set up as

```

function f=u(x,y)
f=-x^2+x+0.5-y;
end

function f=v(x,y)
f=x^2-y-5*x*y;
end

>> clear,clc
>> x0=[1.2;1.2];
>> [x,f,ea,iter]=newtmult(@jfreact,x0)

x =
    1.2333
    0.2122
f =
    1.0e-011 *
   -0.1711
    0.3206
ea =
    1.0523e-010
iter =
     5

```