

Higher-Order unification for free

Reusing the meta-language unification for the object language

Fissore Davide & Enrico Tassi

June 13, 2024

Context

Metaprogramming for type-class resolution

- Our goal:
 - ▶ Type-class solver for Coq in Elpi
- Our problem:
 - ▶ The Elpi's unification algorithm differs from Coq's one
- Our contribution:
 - ▶ Reusing the meta-language unification for the object language

A type-class problem in Coq

```
Instance fin_fin:  $\forall n$ , Finite (fin n). (* r1 *)  
Instance nfact_dec:  $\forall n$  nf, Decision (nfact n nf). (* r2 *)  
Instance forall_dec:  $\forall A$  P, Finite A  $\rightarrow$  (* r3 *)  
  ( $\forall x:A$ , Decision (P x))  $\rightarrow$  Decision ( $\forall x:A$ , P x).
```

```
Goal Decision ( $\forall x$ : fin 7, nfact x 3). (* g *)
```

A type-class problem in Coq

```
Instance fin_fin:  $\forall n$ , Finite (fin n). (* r1 *)
Instance nfact_dec:  $\forall n$  nf, Decision (nfact n nf). (* r2 *)
Instance forall_dec:  $\forall A$  P, Finite A  $\rightarrow$  (* r3 *)
  ( $\forall x:A$ , Decision (P x))  $\rightarrow$  Decision ( $\forall x:A$ , P x).
```

```
Goal Decision ( $\forall x$ : fin 7, nfact x 3). (* g *)
```

- Back-chain to forall_dec with
- $\{A \mapsto \text{fin } 7; P \mapsto \lambda x. (\text{nfact } x \ 3)\}$

A type-class problem in Coq

```
Instance fin_fin:  $\forall n$ , Finite (fin n). (* r1 *)
Instance nfact_dec:  $\forall n$  nf, Decision (nfact n nf). (* r2 *)
Instance forall_dec:  $\forall A$  P, Finite A  $\rightarrow$  (* r3 *)
  ( $\forall x:A$ , Decision (P x))  $\rightarrow$  Decision ( $\forall x:A$ , P x).
```

```
Goal Decision ( $\forall x$ : fin 7, nfact x 3). (* g *)
```

- $\{A \mapsto \text{fin } 7; P \mapsto \lambda x. (\text{nfact } x \ 3)\}$

A type-class problem in Coq

```
Instance fin_fin: ∀n, Finite (fin n).                (* r1 *)
Instance nfact_dec: ∀n nf, Decision (nfact n nf).    (* r2 *)
Instance forall_dec: ∀A P, Finite A →                (* r3 *)
  (∀x:A, Decision (P x)) → Decision (∀x:A, P x).
```

```
Goal Decision (∀x: fin 7, nfact x 3).                (* g *)
```

- $\{A \mapsto \text{fin } 7; P \mapsto \lambda x. (\text{nfact } x \ 3)\}$

- subgoals:

Finite (fin 7) and $(\forall x:A, \text{Decision } ((\lambda x. (\text{nfact } x \ 3)) \ x))$

Coq terms in elpi

Coq	Elpi
$f \cdot a$	<code>app["f", "a"]</code>
$\lambda x. \lambda y. F_{xy}$	<code>lam x\ lam y\ app[uva F [], x, y]</code>
$\lambda x. F_x a$	<code>lam x\ app[uva F [], x, "a"]</code>

Note on unification:

- In coq: $\lambda x. F_x$ unifies with $\lambda x. f \ x \ 3$
- In elpi: “`lam x\app [F, x]`” can’t unify with “`lam x\app [f, x, 3]`”
- But, “`lam x\F x`” unifies with “`lam x\app [f, x, 3]`”

The above type-class problem in elpi

Instance forall_dec: $\forall A\ P, \text{Finite } A \rightarrow$ (* r3 *)
 $(\forall x:A, \text{Decision } (P\ x)) \rightarrow \text{Decision } (\forall x:A, P\ x).$

Goal Decision $(\forall x: \text{fin } 7, \text{nfact } x\ 3).$ (* g *)



The above type-class problem in elpi

Instance forall_dec: $\forall A\ P, \text{Finite } A \rightarrow$ (* r3 *)
 $(\forall x:A, \text{Decision } (P\ x)) \rightarrow \text{Decision } (\forall x:A, P\ x).$

Goal Decision $(\forall x: \text{fin } 7, \text{nfact } x\ 3).$ (* g *)

\downarrow

decision (all A x\ app [P, x]) :- finite A, % r3
pi w\ decision (app [P, w]).

?- decision (all (app ["fin", "7"]) x\ % g
app ["nfact", x, "3"]).

The above type-class problem in elpi

```
decision (all A x\ app [P, x]) :- finite A,           % r3
  pi w\ decision (app [P, w]).
```

```
?- decision (all (app ["fin", "7"]) x\                % g
              app ["nfact", x, "3"]).
```

Solving the goal in elpi

```
decision (all A x\ app [P, x]) :- finite A,           % r3
    pi w\ decision (app [P, w]).
```

```
?- decision (all (app ["fin", "7"]) x\                % g
    app ["nfact", x, "3"] ).
```

Solving the goal in elpi

```
decision (all A x\ app [P, x]) :- finite A,           % r3
    pi w\ decision (app [P, w]).
```

```
?- decision (all (app ["fin", "7"]) x\                % g
    app ["nfact", x, "3"] ).
```

NOTE: Elpi can unify (P x) with app["nfact", x, "3"]

The idea

```
decision (all A x\ P' x) :-                               % r3
  link P' P A,
  finite A,
  pi w\ decision (P' x).
```

```
?- decision (all (app ["fin", "7"]) x\                     % g
               app ["nfact", x, "3"] ).
```

Compilation and simulation

What we propose

① Compilation:

- ▶ Recognize *problematic subterms* p_1, \dots, p_n
- ▶ Replace p_i with fresh unification variables X_i
- ▶ Link p_i with X_i

② Runtime:

- ▶ Unify p_i and X_i only when some conditions hold
- ▶ Decompile remaining links

NOTE: This unification strategy is generalizable to any meta-language when manipulating terms of the object language

Some notations

- \mathbb{P} : the unification problems in the object language (ol)
 - \mathbb{Q} : the unification problems in the target language (ml)
 - step_o : the execution of a unif pb in the ol
 - step_m : the execution of a unif pb in the ml
 - run_o : the run of n steps
 - run_m : the run of n steps
-

- \mathbb{M}, \mathbb{L} : the map store, the link store
- A link in \mathbb{L} is like $X =_\lambda t$
- A mapping in \mathbb{M} is like $\{X \mapsto t\}$

Proven properties

Run Equivalence $\forall \mathbb{P}, \forall n$, if $\mathbb{P} \subseteq \mathcal{L}$

$$\text{run}_o(\mathbb{P}, n) \mapsto \rho \wedge \text{run}_m(\mathbb{P}, n) \mapsto \rho' \Rightarrow \forall s \in \mathbb{P}, \rho s =_o \rho' s$$

Simulation fidelity In the context of run_o and run_m ,

if $\mathbb{P} \subseteq \mathcal{L}$ we have that $\forall p \in 1 \dots n$,

$$\text{step}_o(\mathbb{P}, p, \rho_{p-1}) \mapsto \rho_p \Leftrightarrow \text{step}_m(\mathbb{Q}, p, \sigma_{p-1}, \mathbb{L}_{p-1}) \mapsto (\sigma_p, \mathbb{L}_p)$$

Fidelity recovery In the context of run_o and run_m ,

if $\rho_{p-1} \mathbb{P}_p \subseteq \mathcal{L}$ (even if $\mathbb{P}_p \not\subseteq \mathcal{L}$) then

$$\text{step}_o(\mathbb{P}, p, \rho_{p-1}) \mapsto \rho_p \Leftrightarrow \text{step}_m(\mathbb{Q}, p, \sigma_{p-1}, \mathbb{L}_{p-1}) \mapsto (\sigma_p, \mathbb{L}_p)$$

Problematic subterms recognition: $\diamond\beta$

A HO variable in the pattern fragment:

- X_x becomes λx with mapping $X \mapsto A^1$
- Decompilation: transform the lambda abstraction of the meta language to the lambda abstraction of the object one.
- For example, if $\{A \mapsto (x \setminus f \cdot x \cdot a)\}$, then decompilation produces the following substitution $\{X \mapsto \lambda x. f \cdot x \cdot a\}$

Problematic subterms recognition: $\diamond\eta$

- $\lambda x.s \in \diamond\eta$, if $\exists \rho, \rho(\lambda x.s)$ is an η -redex
- Detection of $\diamond\eta$ terms is not trivial:
 - $\lambda x.f.(A\ x) \in \diamond\eta \quad \rho = \{ A \mapsto \lambda x.x \}$
 - $\lambda x.f.(A\ x) \cdot x \in \diamond\eta \quad \rho = \{ A \mapsto \lambda x.a \}$
 - $\lambda x.f \cdot x.(A\ x) \notin \diamond\eta$
 - $\lambda x.\lambda y.f.(A\ x).(B\ y\ x) \in \diamond\eta \quad \rho = \{ A \mapsto \lambda x.x ; B \mapsto \lambda y.\lambda x.y \}$
- Need of some primitives like `may-contract-to` and `occurs-rigidly`

Problematic subterms recognition: $\diamond\eta$ link progression

- Several conditions: like lhs is assigned to a rigid term, two η -link with same lhs, the rhs becomes outside $\diamond\eta$...
- These conditions guarantee the prefixed properties !
- An example:

$$\begin{aligned}\mathbb{P} &= \{ \lambda x.X \cdot x \simeq_o f \} \\ \mathbb{Q} &= \{ A \simeq_m f \} \\ \mathbb{M} &= \{ X \mapsto B^1 \} \\ \mathbb{L} &= \{ \vdash A =_\eta \lambda x.B_x \} \end{aligned}$$

- After unification of A with f , the lhs of the link is assigned, the link is triggered and $\lambda x.B_x$ is unified with $\lambda x.f \cdot x$
- That is $\{B_x \mapsto f\}$
- Decompilation will assign $\lambda x.f \cdot x$ to X

Problematic subterms recognition: $\diamond \mathcal{L}$

Use of heuristics

Use of CHR

Conclusion

- Takes advantage of the unification capabilities of the meta language at the price of handling problematic sub-terms on the side.
- As a result our encoding takes advantage of indexing data structures and mode analysis for clause filtering.
- It is worth mentioning that we replace terms with variables only when it is strictly needed, leaving the rest of the term structure intact and hence indexable.
- Our approach is flexible enough to accommodate different strategies and heuristics to handle terms outside the pattern fragment