

Operational semantics for Prolog with Cut in Rocq and its application to determinacy analysis

Jane Open Access   

Dummy University Computing Laboratory, [optional: Address], Country

My second affiliation, Country

Joan R. Public¹  

Department of Informatics, Dummy College, [optional: Address], Country

Abstract

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Praesent convallis orci arcu, eu mollis dolor. Aliquam eleifend suscipit lacinia. Maecenas quam mi, porta ut lacinia sed, convallis ac dui. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Suspendisse potenti.

2012 ACM Subject Classification Replace `ccsdsc` macro with valid one

Keywords and phrases Dummy keyword

Digital Object Identifier 10.4230/LIPIcs.CVIT.2016.23

Funding *Jane Open Access:* (Optional) author-specific funding acknowledgements

Joan R. Public: [funding]

Acknowledgements I want to thank ...

1 Introduction

Elpi is a dialect of λ Prolog (see [14, 15, 7, 12]) used as an extension language for the Rocq prover (formerly the Coq proof assistant). Elpi has become an important infrastructure component: several projects and libraries depend on it [13, 3, 4, 19, 8, 9]. Examples include the Hierarchy-Builder library-structuring tool [5] and Derive [17, 18, 11], a program-and-proof synthesis framework with industrial applications at SkyLabs AI.

Starting with version 3, Elpi gained a static analysis for determinacy [10] to help users tame backtracking. Rocq users are familiar with functional programming but not necessarily with logic programming and uncontrolled backtracking is a common source of inefficiency and makes debugging harder. The determinacy checkers identifies predicates that behave like functions, i.e., predicates that commit to their first solution and leave no *choice points* (places where backtracking could resume).

This paper reports our first steps towards a mechanization, in the Rocq prover, of the determinacy analysis from [10]. We focus on the control operator *cut*, which is useful to restrict backtracking but makes the semantic depart from a pure logical reading.

We formalize two operational semantics for Prolog with *cut*. The first is a stack-based semantics that closely models Elpi's implementation and is similar to the semantics mechanized by Pusch in Isabelle/HOL [16] and to the model of Debray and Mishra [6, Sec. 4.3]. This stack-based semantics is a good starting point to study further optimizations used by standard Prolog abstract machines [20, 1], but it makes reasoning about the scope of *cut* difficult. To address that limitation we introduce a tree-based semantics in which the branches pruned by *cut* are explicit and we prove the two semantics equivalent. Using the

¹ Optional footnote, e.g. to mark corresponding author



tree-based semantics we then show that if every rule of a predicate passes the determinacy analysis, the predicate does not leave any choice points.

2 Common code: the language

```

Inductive Tm :=
| Tm_Kp      : Kp -> Tm
| Tm_Kd      : Kd -> Tm
| Tm_V       : V  -> Tm
| Tm_Comb    : Tm -> Tm -> Tm.

Inductive Callable :=
| Callable_Kp   : Kp -> Callable
| Callable_V    : V  -> Callable
| Callable_Comb : Callable -> Tm -> Callable.

Inductive RCallable :=
| RCallable_Kp   : Kp -> RCallable
| RCallable_Comb : RCallable -> Tm -> RCallable.

```

A callable term is a term without a data constructor as functor.
An rcallable is a term with rigid head.

```
Inductive A := cut | call : Callable -> A.
```

An atom is the smallest syntactic unit that can be executed in a prolog program \mathcal{P} .

```
Record R := mkR { head : RCallable; premises : list A }.
```

We exploit the typing system to ensure that the head of a "valid" rule is a term with rigid head.

```

(*simpler than in the code: signatures of preds are hidden*)
Definition program := seq R.

```

A program is made by a list of rules. Rules in \mathcal{P} are indexed by their position in the list. Given a list of rules \mathcal{R} and two indexes i and j , s.t. $i \neq j$ then, \mathcal{R}_i has a higher priority than \mathcal{R}_j .

```

f 1 2.      f 2 3.      r 2 4.
g X X.      % r1
g X Z :- r X Z, !. % r2
g X Z :- f X Y, f Y Z. % r3

```

■ **Figure 1** Small program example

The elpi program above would be translated as a list of 6 elements where the heads and body are translated in the natural way.

Sigma is a substitution mapping variables to their term instantiation.

```
Definition Sigma := {fmap V -> Tm}.
```

The backchaining algorithm is the function \mathcal{B} aims to filter only the rules in the program \mathcal{P} having rules unifying with the current query q in a given substitution σ using the list of modes m . In particular \mathcal{B} returns for each selected rule r a substitution σ' that is the substitution obtained by the unification of the query and the head of r .

$$\mathcal{B} : (\mathcal{P}, \sigma, q) \rightarrow \text{seq}(\sigma * R)$$

3 Semantics intro

We propose two operational semantics for a logic program with cut. The two semantics are based on different syntaxes, the first syntax (called tree) exploits a tree-like structure and is ideal to have a graphical view of its evaluation while the program is being interpreted. The second syntax is the elpi's syntax, we call it therefore elpi. We aim to prove the equivalence of the two semantics together with some interesting lemmas of the cut behavior.

3.1 Tree semantics

```

Inductive tree :=
  | Bot | OK | Dead
  | TA : A -> tree
  | Or  : tree -> Sigma -> tree -> tree
  | And : tree -> seq A -> tree -> tree.

```

In the tree we distinguish 6 main cases: Bot and OK are respectively the standard fail \perp and true \top predicates of prolog. Dead is a special symbol representing a ghost state, that is, a state useful to keep the structure of a tree from an execution to another but that is completely ignored by the interpretation of the program.


TA, standing for tree-atom, is a terminal of the tree containing an atom.

The two recursive cases of a tree are the Or and the And non-terminals. The Or non-terminals $A \vee B_\sigma$ stands for a disjunction between two trees A and B . The second tree branch is decorated with a suspended substitution σ so that, when we backtrack to B , we use σ as initial substitution for B .

The And non-terminal $A \wedge_{B_0} B$ represents of a conjunction of two trees A and B . We call B_0 the reset-point for B and is used to resume the B state in its initial form if some backtracking operation is performed on A . A graphical tree representation is shown in Figure 2a. For the sake of making our graph more compact, the And and Or non-terminals are n-ary (rather than binary), with right-binding priority. We are representing the

The interpretation of a tree is performed by two main routines: **step** and **next_alt** that traverse the tree depth-first, left-to-right.

We get the first to-be-explored terminal in the tree by getting the end of a path. This path is created from a tree traversal starting from the roots and immediately ends if the tree is not neither a disjunction, nor a conjunction: the to-be-explored terminal is the tree itself. Otherwise, if the tree is a disjunction, the path continues on the left- or the right-subtree depending of if the path of the lhs is a dead node. In the case of a conjunction, we look for the path of the lhs. If this path returns a success, we build a path in the rhs, otherwise, we return the lhs. In Figure 2a the first non-explored node is g X.



■ **Figure 2** Tree with first non explored node g X

88 The **step** procedure takes a tree and explores it using the path strategy. A success (i.e.
 89 a tree with path ending with OK) and failed tree (i.e. a tree with path ending with KO or
 90 Dead) is returned as it. The two interesting cases are when the path ends with a call or a
 91 cut.

92 *Call step* In the former case the call node is replaced with a new subtree made by the
 93 rules returned by the \mathcal{B} function. If \mathcal{B} returns a list l , if l is empty then KO tree is returned,
 94 otherwise the call is replaced by right-skewed tree made of n inner Or nodes, where n is
 95 the length of l . The root Or-node has KO as left child. The lhs of the other nodes is a
 96 right-skewed tree of And nodes. The And nodes are again a right-skewed tree containing then
 atoms (either cut or call) taken from the list l .

97 A step in the tree in Figure 2a make a backchain operation over the query g X Y and, in
 98 the program defined in Figure 1, the new tree would be the one in Figure 2b. We have put a
 99 red border around the new generated subtree. It is a disjunction of four subtrees: the first
 100 node is the Dead node (by default), the second is OK, since r1 has no premises, the third
 101 and the fourth contains the premises of respectively r2 and r3.

102 *Cut step* The latter case is delicate since interpreting a cut in a tree has three main
 impacts: at first the cut node is replaced by a OK node, but then we need to cut-away the
 subtrees that are in the scope of the cut: in particular we need to soft-kill the left-siblings of
 the Cut and hard-kill the right-uncles of the the Cut.

107 ► **Definition 1** (Left-siblings (resp. right-sibling)). *Given a node A, the left-siblings (resp.*
 108 *right-sibling) of A are the list of subtrees sharing the same parent of A and that appear on*
 109 *its left (resp. right).*

110 ► **Definition 2** (Right-uncles). *Given a node A, the right-uncles of A are the list of right-sibling*
 111 *of the father of A.*

112 ► **Definition 3** (Soft-kill). *Given a tree t, soft-kill replaces all the leaves of the tree with the*
 113 *node KO except for the leaves that are part of the path p of t.*

114 ► **Definition 4** (Hard-kill). *Given a tree t, hard-kill replaces all the leaves of the tree with the*
 115 *node KO*

116 An example of the impact of the cut is show in Figure 2c. The step routine interprets
 117 the cut if it is at the end of the current path. In the example we have tagged in red the
 118 arrow $!_l$ indicating which sub-trees is soft-killed and $!_r$ indicated which is sub-trees are to be
 119 hard-killed.

3.1.1 Execution example

3.1.2 Valid tree

3.2 Elpi semantics

The Elpi interpreter is based on an operational semantics close to the one picked by Pusch in [16], in turn closely related to the one given by Debray and Mishra in [6, Section 4.3]. Push mechanized the semantics in Isabelle/HOL together with some optimizations that are present in the Warren Abstract Machine [20, 1].

In these operational semantics we need to decorate the cut atom with a list of alternative, morally a pointer to a sub-list of the overall alternatives. An atom in the elpi semantics is defined as follows:

```
Inductive alts :=
  | no_alt
  | more_alt : (Sigma * goals) -> alts -> alts
with goals :=
  | no_goals
  | more_goals : (A * alts) -> goals -> goals .
```


We are completely loosing the tree structure. There are no clean reset points. The backtracking operation is simpler: it is the tail function. The cutr and cutl operations disappears: the alternatives are stored directly in the cutE terminal.

The elpi interpreter is as follows:

```
(*TODO: add system of rules*)
Inductive nur : Sigma -> goals -> alts -> Sigma -> alts -> Type :=
  | StopE s a : nur s nilC a s a
  | CutE s s1 a ca r gl : nur s gl ca s1 r -> nur s ((cutE ca) ::: gl) a s1 r
  | CallE p s s1 a b bs gl r t :
    F u p t s = [:: b & bs ] ->
      nur b.1 (save_goals a gl (a2gs1 p b)) (save_alts a gl ((aa2gs p) bs) ++ a) s1 r ->
      nur s ((callE p t) ::: gl) a s1 r
  | FailE p s s1 s2 t gl a al r :
    F u p t s = [::] -> nur s1 a al s2 r -> nur s ((callE p t) ::: gl) ((s1, a) ::: al) s2 r.
```

The translation of a tree to a list is as follows:

```
Fixpoint t2l (A: tree) s (bt : alts) : alts :=
  match A with
  | OK          => [:: (s, [::])] ]
  | (Bot | Dead) => [::]
  | TA a        => [:: (s, [:: (a, [::])] ) ] ]
  | Or A s1 B    =>
    let lB := t2l B s1 [::] in
    let lA := t2l A s lB in
    add_ca_deep bt (lA ++ lB)
  | And A B0 B    =>
    let lB0 : goals := r2l B0 in
    let lA := t2l A s bt in
    if lA is [:: (s1A, x) & xs] then
      let xz := add_deepG bt lB0 x in
      let xs := add_deep bt lB0 xs in
```



■ **Figure 3** Induction scheme for Theorem 6

```

let xs := make_lB0 xs lB0 in
let lB := t2l B slA (xs ++ bt) in
(make_lB01 lB xz) ++ xs
else [::]
end.

```

► **Theorem 5** (`tree_to_elpi`).

135 $\forall A \sigma_1 B \sigma_2 b \sigma_0, \nu t A \rightarrow$
136 $\text{run}_u \sigma_1 A (\text{Some } \sigma_2) B b \rightarrow$
137 $\exists x xs, t2l A \sigma_1 \emptyset = x :: xs \wedge \text{nur}_u x.1 x.2 xs \sigma_2 (t2l B \sigma_0 \emptyset).$

► **Theorem 6** (`elpi_to_tree`).

138 $\forall \sigma_1 \sigma_2 a na g,$
139 $\text{nur}_u \sigma_1 g a \sigma_2 na \rightarrow$
140 $\forall \sigma_0 t, \nu t t \rightarrow (t2l t \sigma_0 \emptyset) = ((\sigma_1, g) :: a) \rightarrow$
141 $\exists t' n, \text{run}_u \sigma_0 t (\text{Some } \sigma_2) t' n \wedge t2l t' \sigma_0 \emptyset = na.$

142 The proof of Theorem 6 is based on the idea explained in [2, Section 3.3]. An ideal
143 statement for this lemma would be: given a function `l2t` transforming an elpi state to a tree,
144 we would have have that the the execution of an elpi state e is the same as executing `run` on
145 the tree resulting from `l2t(e)`. However, it is difficult to retrieve the strucutre of an elpi state
146 and create a tree from it. This is because, in an elpi state, we have no clear information
147 about the scope of an atom inside the list and, therefore, no evident clue about where this
148 atom should be place in the tree.

149 Our theorem states that, starting from a valid state t which translates to a list of
150 alternatives $(\sigma_1, g) :: a$. If we run in elpi the list of alternatives, then the execution of the
151 tree t returns the same result as the execution in elpi. The proof is performed by induction
152 on the derivations of the elpi execution. We have 4 derivations.

153 We have 4 case to analyse:

154 — References —

- 155 1 Hassan Aït-Kaci. *Warren's Abstract Machine: A Tutorial Reconstruction*. The MIT Press, 08
156 1991. doi:10.7551/mitpress/7160.001.0001.
- 157 2 Yves Bertot. A certified compiler for an imperative language. Technical Report RR-3488,
158 INRIA, September 1998. URL: <https://inria.hal.science/inria-00073199v1>.

- 159 **3** Valentin Blot, Denis Cousineau, Enzo Crance, Louise Dubois de Prisque, Chantal Keller,
160 Assia Mahboubi, and Pierre Vial. Compositional pre-processing for automated reasoning in
161 dependent type theory. In Robbert Krebbers, Dmitriy Traytel, Brigitte Pientka, and Steve
162 Zdancewic, editors, *Proceedings of the 12th ACM SIGPLAN International Conference on*
163 *Certified Programs and Proofs, CPP 2023, Boston, MA, USA, January 16-17, 2023*, pages
164 63–77. ACM, 2023. doi:10.1145/3573105.3575676.
- 165 **4** Cyril Cohen, Enzo Crance, and Assia Mahboubi. TrocQ: Proof transfer for free, with or
166 without univalence. In Stephanie Weirich, editor, *Programming Languages and Systems*, pages
167 239–268. Cham, 2024. Springer Nature Switzerland.
- 168 **5** Cyril Cohen, Kazuhiko Sakaguchi, and Enrico Tassi. Hierarchy Builder: Algebraic hierarchies
169 Made Easy in Coq with Elpi. In *Proceedings of FSCD*, volume 167 of *LIPIcs*, pages 34:1–34:21,
170 2020. URL: [https://drops.dagstuhl.de/entities/document/10.4230/LIPIcs.FSCD.2020.](https://drops.dagstuhl.de/entities/document/10.4230/LIPIcs.FSCD.2020.34)
171 34, doi:10.4230/LIPIcs.FSCD.2020.34.
- 172 **6** Saumya K. Debray and Prateek Mishra. Denotational and operational semantics for prolog. *J.*
173 *Log. Program.*, 5(1):61–91, March 1988. doi:10.1016/0743-1066(88)90007-6.
- 174 **7** Cvetan Dunchev, Ferruccio Guidi, Claudio Sacerdoti Coen, and Enrico Tassi. ELPI: fast,
175 embeddable, λProlog interpreter. In *Proceedings of LPAR*, volume 9450 of *LNCS*, pages
176 460–468. Springer, 2015. URL: <https://inria.hal.science/hal-01176856v1>, doi:10.1007/
177 978-3-662-48899-7_32.
- 178 **8** Davide Fissore and Enrico Tassi. A new Type-Class solver for Coq in Elpi. In *The Coq*
179 *Workshop*, July 2023. URL: <https://inria.hal.science/hal-04467855>.
- 180 **9** Davide Fissore and Enrico Tassi. Higher-order unification for free!: Reusing the meta-
181 language unification for the object language. In *Proceedings of PPDP*, pages 1–13. ACM, 2024.
182 doi:10.1145/3678232.3678233.
- 183 **10** Davide Fissore and Enrico Tassi. Determinacy checking for elpi: an higher-order logic program-
184 ming language with cut. In *Practical Aspects of Declarative Languages: 28th International*
185 *Symposium, PADL 2026, Rennes, France, January 12–13, 2026, Proceedings*, pages 77–95,
186 Berlin, Heidelberg, 2026. Springer-Verlag. doi:10.1007/978-3-032-15981-6_5.
- 187 **11** Benjamin Grégoire, Jean-Christophe L chenet, and Enrico Tassi. Practical and sound equality
188 tests, automatically. In *Proceedings of CPP*, page 167–181. Association for Computing
189 Machinery, 2023. doi:10.1145/3573105.3575683.
- 190 **12** Ferruccio Guidi, Claudio Sacerdoti Coen, and Enrico Tassi. Implementing type theory
191 in higher order constraint logic programming. In *Mathematical Structures in Computer*
192 *Science*, volume 29, pages 1125–1150. Cambridge University Press, 2019. doi:10.1017/
193 S0960129518000427.
- 194 **13** Robbert Krebbers, Luko van der Maas, and Enrico Tassi. Inductive Predicates via Least
195 Fixpoints in Higher-Order Separation Logic. In Yannick Forster and Chantal Keller, editors,
196 *16th International Conference on Interactive Theorem Proving (ITP 2025)*, volume 352 of *Leib-*
197 *niz International Proceedings in Informatics (LIPIcs)*, pages 27:1–27:21, Dagstuhl, Germany,
198 2025. Schloss Dagstuhl – Leibniz-Zentrum f r Informatik. URL: [https://drops.dagstuhl.](https://drops.dagstuhl.de/entities/document/10.4230/LIPIcs.ITP.2025.27)
199 [de/entities/document/10.4230/LIPIcs.ITP.2025.27](https://drops.dagstuhl.de/entities/document/10.4230/LIPIcs.ITP.2025.27), doi:10.4230/LIPIcs.ITP.2025.27.
- 200 **14** Dale Miller. A logic programming language with lambda-abstraction, function variables, and
201 simple unification. In *Extensions of Logic Programming*, pages 253–281. Springer, 1991.
- 202 **15** Dale Miller and Gopalan Nadathur. *Programming with Higher-Order Logic*. Cambridge
203 University Press, 2012.
- 204 **16** Cornelia Pusch. Verification of compiler correctness for the wam. In Gerhard Goos, Juris
205 Hartmanis, Jan van Leeuwen, Joakim von Wright, Jim Grundy, and John Harrison, editors,
206 *Theorem Proving in Higher Order Logics*, pages 347–361, Berlin, Heidelberg, 1996. Springer
207 Berlin Heidelberg.
- 208 **17** Enrico Tassi. Elpi: an extension language for Coq (Metaprogramming Coq in the Elpi λProlog
209 dialect). In *The Fourth International Workshop on Coq for Programming Languages*, January
210 2018. URL: <https://inria.hal.science/hal-01637063>.

- 211 **18** Enrico Tassi. Deriving proved equality tests in Coq-Elpi. In *Proceedings of ITP*, volume 141 of
212 *LIPICs*, pages 29:1–29:18, September 2019. URL: <https://inria.hal.science/hal-01897468>,
213 doi:10.4230/LIPICs.CVIT.2016.23.
- 214 **19** Luko van der Maas. Extending the Iris Proof Mode with inductive predicates using Elpi.
215 Master’s thesis, Radboud University Nijmegen, 2024. doi:10.5281/zenodo.12568604.
- 216 **20** David H.D. Warren. An Abstract Prolog Instruction Set. Technical Report Technical Note 309,
217 SRI International, Artificial Intelligence Center, Computer Science and Technology Division,
218 Menlo Park, CA, USA, October 1983. URL: [https://www.sri.com/wp-content/uploads/](https://www.sri.com/wp-content/uploads/2021/12/641.pdf)
219 [2021/12/641.pdf](https://www.sri.com/wp-content/uploads/2021/12/641.pdf).