

Operational semantics for Prolog with Cut in Rocq and its application to determinacy analysis

Jane Open Access   

Dummy University Computing Laboratory, [optional: Address], Country

My second affiliation, Country

Joan R. Public¹  

Department of Informatics, Dummy College, [optional: Address], Country

Abstract

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Praesent convallis orci arcu, eu mollis dolor. Aliquam eleifend suscipit lacinia. Maecenas quam mi, porta ut lacinia sed, convallis ac dui. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Suspendisse potenti.

2012 ACM Subject Classification Replace `ccsdsc macro with valid one`

Keywords and phrases Dummy keyword

Digital Object Identifier 10.4230/LIPIcs.CVIT.2016.23

Funding *Jane Open Access:* (Optional) author-specific funding acknowledgements

Joan R. Public: [funding]

Acknowledgements I want to thank ...

1 Introduction

ELPI is a dialect of λ PROLOG (see [14, 15, 7, 12]) used as an extension language for the ROCQ prover (formerly the COQ proof assistant). ELPI has become an important infrastructure component: several projects and libraries depend on it [13, 3, 4, 19, 8, 9]. Examples include the Hierarchy-Builder library-structuring tool [5] and Derive [17, 18, 11], a program-and-proof synthesis framework with industrial applications at SkyLabs AI.

Starting with version 3, ELPI gained a static analysis for determinacy [10] to help users tame backtracking. ROCQ users are familiar with functional programming but not necessarily with logic programming and uncontrolled backtracking is a common source of inefficiency and makes debugging harder. The determinacy checkers identifies predicates that behave like functions, i.e., predicates that commit to their first solution and leave no *choice points* (places where backtracking could resume).

This paper reports our first steps towards a mechanization, in the ROCQ prover, of the determinacy analysis from [10]. We focus on the control operator *cut*, which is useful to restrict backtracking but makes the semantic depart from a pure logical reading.

We formalize two operational semantics for PROLOG with cut. The first is a stack-based semantics that closely models ELPI's implementation and is similar to the semantics mechanized by Pusch in ISABELLE/HOL [16] and to the model of Debray and Mishra [6, Sec. 4.3]. This stack-based semantics is a good starting point to study further optimizations used by standard PROLOG abstract machines [20, 1], but it makes reasoning about the scope of *cut* difficult. To address that limitation we introduce a tree-based semantics in which the branches pruned by *cut* are explicit and we prove the two semantics equivalent. Using the

¹ Optional footnote, e.g. to mark corresponding author



© Jane Open Access and Joan R. Public;
licensed under Creative Commons License CC-BY 4.0

42nd Conference on Very Important Topics (CVIT 2016).

Editors: John Q. Open and Joan R. Access; Article No. 23; pp. 23:1–23:9

Leibniz International Proceedings in Informatics



LIPICs Schloss Dagstuhl – Leibniz-Zentrum für Informatik, Dagstuhl Publishing, Germany

```

Inductive P := IP of nat. Inductive D := ID of nat. Inductive V := IV of nat.

Inductive Tm :=
  | Tm_P of P
  | Tm_D of D
  | Tm_V of V
  | Tm_App of Tm & Tm.
Inductive Callable :=
  | Callable_P of P
  | Callable_App of Callable & Tm.

```

■ **Figure 1** Tm and Callable types

tree-based semantics we then show that if every rule of a predicate passes the determinacy analysis, the call to a deterministic predicate does not leave any choice points.

2 Common code: the language

Before going to the two semantics, we show the piece of data structure that are shared by the them. The smallest unit of code that we can use in the language is an atom. The atom inductive (see Type 1) is either a cut or a call. A call carries a callable term (see Figure 1).

A term (Tm) is either a predicate, a datum, a variable or the binary application of a term to another. A Callable is a term accepting predicates only predicates as functors.

Inductive A := cut | call : Callable -> A. (1)

Record R := mkR { head : Callable; premises : list A }. (2)

Record program := { rules : seq R; sig : sigT }. (3)

Definition Sigma := {fmap V -> Tm}. (4)

Definition bc : Unif -> program -> fvS -> Callable ->
Sigma -> (fvS * seq (Sigma * R)) := (5)

A rule (see Type 2) is made a head of type term and a list of premises, the premises are atoms. A program (see Type 3) is made by a list of rules and a mapping from predicates to their signatures. The type sigT is the classic type from the simply typed lambda calculus, i.e. it is either a base type or an arrow. We decorate arrows to know the mode of the lhs type.

A substitution (see Type 4) is a mapping from variables to terms. It is the output of a successful query and is often called the output of a query.

```

Record Unif := {
  unify : Tm -> Tm -> Sigma -> option Sigma;
  matching : Tm -> Tm -> Sigma -> option Sigma;
}.

```

The backchain function (bc, see Type 5) filters the rules in the program that can be used on a given query. It takes: a unificator U which explains how to unify terms up to standard unification (for output terms) or matching (for input terms); a program P to explore and filter; a set S of free variable (fvS) allowing to fresh the program P by renaming the its variables; a query q ; and the substitution σ in which the query q lives. The result of a backchain operation is couple made of an extension of S containing the new variables that have been allocated during the unification phase and a list of filtered rules r accompagnate by their a substitution. This substitution is the result of the unification of q with the head of each rule in r .

In Figure 2, we have an example of a simple ELPI program which will be used in the following section of the paper as an example to show how backtracking and the cut operator works in the semantics we propose. The translation of these rules in the ROCQ representation is straightforward.

```

f 1 2.    f 2 3.    r 2 4.    r 2 8.
g X X.                                % r1
g X Z :- r X Z, !.                  % r2
g X Z :- f X Y, f Y Z.              % r3

```

■ **Figure 2** Small ELPI program example

2.1 The cut operator

The semantics of the cut operator adopted in the ELPI language corresponds to the *hard cut* operator of standard SWI-PROLOG. This operator has two primary purposes. First, it eliminates all alternatives that are created either simultaneously with, or after, the introduction of the cut into the execution state.

To illustrate this high-level description, consider the program shown in Figure 2 and the query $q = g\ 2\ Z$. All three rules for g can be used on the query q . They are tried according to their order of appearance in the program: rule r_1 is tried first, followed by r_2 , and r_3 .

The first rule has no premises and immediately returns the assignment $Z = 2$. However, the computation does not terminate at this point, since two additional unexplored alternatives remain, corresponding to the premises of rules r_2 and r_3 .

The premises of rule r_2 are $r\ 2\ Z, !$. At this stage, the role of the cut becomes apparent. If the premise $r\ 2\ Z$ succeeds, the cut commits to this choice and removes the premises of rule r_3 from the alternative list, as they were generated at the same point as the cut. Moreover, if the call $r\ 2\ Z$ itself produces multiple alternatives, only the first one is committed, while the remaining alternatives are discarded. This is because such alternatives have been created at a deeper depth in the search tree than the cut.

Concretely, the call $r\ 2\ Z$ yields two solutions, assigning Z the values 4 and 8, respectively. The second solution is eliminated by the cut, and only the first assignment is preserved.

3 Semantics intro

We propose two operational semantics for a logic program with cut. The two semantics are based on different syntaxes, the first syntax (called *tree*) exploits a tree-like structure and is ideal both to have a graphical view of its evolution while the state is being interpreted and to prove lemmas over it. The second syntax, called *elpi*, is the ELPI's syntax and has the advantage of reducing the computational cost of cutting and backtracking alternatives by using shared pointers. We aim to prove the equivalence of the two semantics together with some interesting lemmas of the cut behavior.

3.1 Tree semantics

```

Inductive tree :=
| KO | OK | Dead
| TA : A -> tree
| Or  : tree -> Sigma -> tree -> tree
| And : tree -> seq A -> tree -> tree.

```

In the tree we distinguish 6 main cases: *KO*, *OK*, and *Dead* are special meta-symbols representing, respectively, a failed, a successful, and a dead terminal. These symbols are considered meta because they are internal intermediate symbols used to give structure to the

```

Fixpoint is_dead A :=
  match A with
  | Dead => true
  | OK | KO | TA _ => false
  | And A B0 B => is_dead A
  | Or A s B => is_dead A && is_dead B
  end.

Fixpoint path_end A :=
  match A with
  | Dead | OK | KO | TA _ => A
  | Or A _ B =>
    if is_dead A then path_end B
    else path_end A
  | And A B0 B =>
    match path_end A with
    | OK => path_end B
    | A => A
    end
  end.

```

(a) Definition of *is_dead*(b) Definition of *path_end*

tree. While the first two symbols are of immediate understanding, we use *Dead* to represent ghost state, that is, the *Dead* symbol is always ignored by the tree interpreter.

TA (acronym for tree-atom) is the constructor of atoms in the tree.

The two recursive cases of a tree are the *Or* and *And* non-terminals. The *Or* non-terminal $A \vee B_\sigma$ denotes a disjunction between two trees *A* and *B*. The second branch is annotated with a suspended substitution σ so that, upon backtracking to *B*, σ is used as the initial substitution for the execution of *B*.

The *And* non-terminal $A \wedge_{B_0} B$ represents a conjunction of two trees *A* and *B*. We call B_0 the reset point for *B*; it is used to restore the state of *B* to its initial form if a backtracking operation occurs on *A*. Intuitively, let *t2l* be the function flattening a tree in a list of sequents disjunction, in PROLOG-like syntax the tree $A \wedge_{B_0} B$ becomes $(A_1, t2l B); (A_2, B_0); \dots; (A_n, B_0)$ where $t2l(A) = A_1, \dots, A_n$.

A graphical representation of a tree is shown in Figure 4a. To make the graph more compact, the *And* and *Or* non-terminals are n-ary rather than binary, with right-binding priority. The *KO* and *Dead* terminals act as the neutral elements in the *Or* list, while *OK* is the neutral element of the *And* list.

The interpretation of a tree is performed by two main routines: *step* and *next_alt* that traverse the tree depth-first, left-to-right. Then, then *run* inductive makes the transitive closure of step *step* and *next_alt*: it iterates the calls to its auxiliary functions. In Types 7–9 we give the types contrats of these symbols where *fv* is a set of variable names.

Inductive *step_tag* := Expanded | CutBrothers | Failed | Success. (6)


Definition *step* : program -> fvS -> Sigma -> tree -> (fvS * *step_tag* * tree) := (7)

Definition *next_alt* : bool -> tree -> option tree := (8)

Inductive *run* (p : program): fvS -> Sigma -> tree -> option Sigma -> tree -> bool -> Prop := (9)

A particular tree we want to identify is a *is_dead* tree (defined in Figure 3a). This tree has the property to never produce a solution: it is either the *Dead* tree or both branches of *Or* are dead, or the lhs of *And* is dead. In the latter case, we note that *B* can be non-dead, but this is not a problem since the interpreter can run *B* only if *A* is non-dead.

The prolog interpreter explores the state in DFS strategy, it finds the “first-to-be-explored” (ftbe) atom of the tree and then interpretes it. In a non-*is_dead* tree, we get the ftbe node via *path_end*, shown in Figure 3b. The *path_end* is either the tree itself if the tree is a leaf. Otherwise, if the tree is a disjunction, the path continues on the left- or the right-subtree depending of if the the lhs is a *is_dead* tree. In the *Or* case we are clearing ignoring the



■ **Figure 4** Some tree representations

136 dead (ghost) state.

137 In the case of a conjunction, it is more interesting to see what happens. If the *path_end*
 138 *p* of the lhs is a success then we look for the *path_end* in the rhs, otherwise we return *p*. In
 139 Figure 4a the *path_end* of the tree is g X.

140 Below we define two special kind of trees depending on their pathend.

141 **Definition** success A := path_end A == OK. (1)

142 **Definition** failed A := (path_end A == KO) || (path_end A == Dead). (2)

143 3.1.1 The *step* procedure

144 The *step* procedure takes as input a program, a set of free variables (fv), a substitution, and
 145 a tree, and returns an updated set of free variables, a *step_tag*, and an updated tree.

146 Free variables are those variables that appear in a tree; they are used in the backchaining
 147 operation to refresh the variables in the program.

148 The *step_tag* indicates the type of internal tree step that has been performed. **CutBrothers**
 149 denotes the interpretation of a superficial cut, i.e., a cut whose parent nodes are all *And*-nodes.
 150 **Expanded** denotes the interpretation of non-superficial cuts or predicate calls. **Failure** and
 151 **Success** are returned for, respectively, *failed* and *success* trees.

152 The step procedure is intended to interpretate atoms, that is, it returns the identity for
 153 *success* and *failed* tree.

154 **Lemma** success_step u p fv s A: success A -> step u p fv s A = (fv, Success, A). (1)

155 **Lemma** failed_step u p fv s1 A: failed A -> step u p fv s1 A = (fv, Failed, A). (2)

156 Therefore, *step* produces interesting results if the path-end of the input tree is either a
 157 call or a cut.

158 *Call step* The interpretation of a call *c* starts by calling the *bc* function on *c*. The output
 159 list *l* is taken to represent build the new subtree. If *l* is empty then *KO* tree is returned,
 160 otherwise the subtree is a right-skewed tree made of *n* inner *Or* nodes, where *n* is the length
 161 of *l*. The root has *KO* as left child. The lhs of the other nodes is a right-skewed tree of *And*
 162 nodes. The *And* nodes are again a right-skewed tree containing premises of the selected rule.

163 A step in the tree of Figure 4a makes a backchain operation over the query g X Y and, in
 164 the program defined in Figure 2, the new tree would be the one in Figure 4b. We have put a
 165 red border around the new generated subtree. It is a disjunction of four subtrees: the first

if we go right
 in the tree, the
 subst is the one
 in the or...
 dire dei reset
 point

166 node is the *KO* node (by default), the second is *OK*, since r_1 has no premises, the third and
 167 the fourth contains the premises of respectively r_2 and r_3 .

168 *Cut step* The latter case is delicate since interpreting a cut in a tree has three main
 169 impacts: at first it is replaced by the *OK* node, then some special subtrees, in the scope
 170 of the *Cut*, are cut away: in particular we need to soft-kill the left-siblings of the *Cut* and
 171 hard-kill the right-uncles of the the *Cut*.

172 ► **Definition 1** (Left-siblings (resp. right-sibling)). *Given a node A , the left-siblings (resp.*
 173 *right-sibling) of A are the list of subtrees sharing the same parent of A and that appear on*
 174 *its left (resp. right).*

175 ► **Definition 2** (Right-uncles). *Given a node A , the right-uncles of A are the list of right-sibling*
 176 *of the father of A .*

177 ► **Definition 3** (Soft-kill, $!_l$). *Given a successfull tree t , soft-kill replaces all the leaves of the*
 178 *tree with the node *KO* except for the path in t leading to the *OK* node.*

179 ► **Definition 4** (Hard-kill, $!_r$). *Given a tree t , hard-kill replaces all the leaves of the tree with*
 180 *the node *KO**

181 An example of the impact of the cut is show in Figure 4c. The step routine interprets
 182 the cut since it is the node in its path-end. In the example we have 4 arrow tagged with the
 183 $!_l$ or $!_r$ symbols. The $!_l$ arrows go left and soft-kill the pointed subtree, in particular, we can
 184 note that both pointed subtree have a success node, this is beacuse, in order to evaluate the
 185 cut in the figure, we need a successful path leading to it. The $!_l$ procedure will keep the two
 186 *OK* nodes since they are essential to reach the cut, and will kill all the leaves in the other
 187 subtrees, for those specific subtrees, $!_l$ behaves as $!_r$. The $!_r$ procedure, instead, immediately
 188 starts by removing all leaves in the trees pointed by the red arrows.

189 3.1.2 The *next_alt* procedure

190 3.1.3 The *run* inductive

191 3.1.4 Valid tree

192 Reasoning on a the tree semantics allows to identify an invariant that

193 3.2 Elpi semantics

194 TODO: dire che la semantica ad albero è puù faicle per le prove

195 The ELPI interpreter is based on an operational semantics close to the one picked by
 196 Pusch in [16], in turn closely related to the one given by Debray and Mishra in [6, Section
 197 4.3]. Push mechanized the semantics in Isabelle/HOL together with some optimizations that
 198 are present in the Warren Abstract Machine [20, 1].

199 In these operational semantics we need to decorate the cut atom with a list of alternative,
 200 morally a pointer to a sub-list of the overall alternatives. An atom in the elpi semantcis is
 201 defined as follows:

```

Inductive alts :=
  | no_alt
  | more_alt : (Sigma * goals) -> alts -> alts
with goals :=
  | no_goals
  | more_goals : (A * alts) -> goals -> goals .

```

202 We are completely loosing the tree structure. There are no clean reset points. The
 203 backtracking operation is simpler: it is the tail function. The cutr and cutl operations
 204 disappears: the alternatives are stored directly in the cutE terminal.

205 The elpi interpreter is as follows:

```
(*TODO: add system of rules*)
Inductive nur : Sigma -> goals -> alts -> Sigma -> alts -> Type :=
| StopE s a : nur s nilC a s a
| CutE s s1 a ca r gl : nur s gl ca s1 r -> nur s ((cutE ca) ::: gl) a s1 r
| CallE p s s1 a b bs gl r t :
  F u p t s = [:: b & bs ] ->
    nur b.1 (save_goals a gl (a2gs1 p b)) (save_alts a gl ((aa2gs p) bs) ++ a) s1 r ->
    nur s ((callE p t) ::: gl) a s1 r
| FailE p s s1 s2 t gl a al r :
  F u p t s = [::] -> nur s1 a al s2 r -> nur s ((callE p t) ::: gl) ((s1, a) ::: al) s2 r.
```

206 The translation of a tree to a list is as follows:


```
Fixpoint t2l (A: tree) s (bt : alts) : alts :=
match A with
| OK          => [:: (s, [::])]
| (KO | Dead) => [::]
| TA a        => [:: (s, [:: (a, [::])])]
| Or A s1 B    =>
  let lB := t2l B s1 [::] in
  let lA := t2l A s lB in
  add_ca_deep bt (lA ++ lB)
| And A B0 B    =>
  let lB0 : goals := r2l B0 in
  let lA := t2l A s bt in
  if lA is [:: (s1A, x) & xs] then
    let xz := add_deepG bt lB0 x in
    let xs := add_deep bt lB0 xs in
    let xs := make_lB0 xs lB0 in
    let lB := t2l B s1A (xs ++ bt) in
    (make_lB01 lB xz) ++ xs
  else [::]
end.
```

► Theorem 5 (tree_to_elpi).

207 $\forall A \sigma_1 B \sigma_2 b \sigma_0, \forall t A \rightarrow$
 208 $\text{run}_u \sigma_1 A (\text{Some } \sigma_2) B b \rightarrow$
 209 $\exists x xs, t2l A \sigma_1 \emptyset = x :: xs \wedge \text{nur}_u x.1 x.2 xs \sigma_2 (t2l B \sigma_0 \emptyset).$

► Theorem 6 (elpi_to_tree).

210 $\forall \sigma_1 \sigma_2 a na g,$
 211 $\text{nur}_u \sigma_1 g a \sigma_2 na \rightarrow$
 212 $\forall \sigma_0 t, \forall t t \rightarrow (t2l t \sigma_0 \emptyset) = ((\sigma_1, g) :: a) \rightarrow$
 213 $\exists t' n, \text{run}_u \sigma_0 t (\text{Some } \sigma_2) t' n \wedge t2l t' \sigma_0 \emptyset = na.$



■ **Figure 5** Induction scheme for Theorem 6

214 The proof of Theorem 6 is based on the idea explained in [2, Section 3.3]. An ideal
 215 statement for this lemma would be: given a function `12t` transforming an elpi state to a tree,
 216 we would have have that the the execution of an elpi state e is the same as executing `run` on
 217 the tree resulting from `12t(e)`. However, it is difficult to retrieve the strucutre of an elpi state
 218 and create a tree from it. This is because, in an elpi state, we have no clear information
 219 about the scope of an atom inside the list and, therefore, no evident clue about where this
 220 atom should be place in the tree.

221 Our theorem states that, starting from a valid state t which translates to a list of
 222 alternatives $(\sigma_1, g) :: a$. If we run in elpi the list of alternatives, then the execution of the
 223 tree t returns the same result as the execution in elpi. The proof is performed by induction
 224 on the derivations of the elpi execution. We have 4 derivations.

225 We have 4 case to analyse:

226 — References —

- 227 1 Hassan Aït-Kaci. *Warren's Abstract Machine: A Tutorial Reconstruction*. The MIT Press, 08
 228 1991. doi:10.7551/mitpress/7160.001.0001.
- 229 2 Yves Bertot. A certified compiler for an imperative language. Technical Report RR-3488,
 230 INRIA, September 1998. URL: <https://inria.hal.science/inria-00073199v1>.
- 231 3 Valentin Blot, Denis Cousineau, Enzo Crance, Louise Dubois de Prisque, Chantal Keller,
 232 Assia Mahboubi, and Pierre Vial. Compositional pre-processing for automated reasoning in
 233 dependent type theory. In Robbert Krebbers, Dmitriy Traytel, Brigitte Pientka, and Steve
 234 Zdancewic, editors, *Proceedings of the 12th ACM SIGPLAN International Conference on
 235 Certified Programs and Proofs, CPP 2023, Boston, MA, USA, January 16-17, 2023*, pages
 236 63–77. ACM, 2023. doi:10.1145/3573105.3575676.
- 237 4 Cyril Cohen, Enzo Crance, and Assia Mahboubi. Trocq: Proof transfer for free, with or
 238 without univalence. In Stephanie Weirich, editor, *Programming Languages and Systems*, pages
 239 239–268, Cham, 2024. Springer Nature Switzerland.
- 240 5 Cyril Cohen, Kazuhiko Sakaguchi, and Enrico Tassi. Hierarchy Builder: Algebraic hierarchies
 241 Made Easy in Coq with Elpi. In *Proceedings of FSCD*, volume 167 of *LIPICs*, pages 34:1–34:21,
 242 2020. URL: [https://drops.dagstuhl.de/entities/document/10.4230/LIPICs.FSCD.2020.](https://drops.dagstuhl.de/entities/document/10.4230/LIPICs.FSCD.2020.34)
 243 34, doi:10.4230/LIPICs.FSCD.2020.34.
- 244 6 Saumya K. Debray and Prateek Mishra. Denotational and operational semantics for prolog. *J.*
 245 *Log. Program.*, 5(1):61–91, March 1988. doi:10.1016/0743-1066(88)90007-6.
- 246 7 Cvetan Dunchev, Ferruccio Guidi, Claudio Sacerdoti Coen, and Enrico Tassi. ELPI: fast,
 247 embeddable, λ Prolog interpreter. In *Proceedings of LPAR*, volume 9450 of *LNCS*, pages
 248 460–468. Springer, 2015. URL: <https://inria.hal.science/hal-01176856v1>, doi:10.1007/
 249 978-3-662-48899-7_32.
- 250 8 Davide Fissore and Enrico Tassi. A new Type-Class solver for Coq in Elpi. In *The Coq*
 251 *Workshop*, July 2023. URL: <https://inria.hal.science/hal-04467855>.

- 252 9 Davide Fissore and Enrico Tassi. Higher-order unification for free!: Reusing the meta-
253 language unification for the object language. In *Proceedings of PPDP*, pages 1–13. ACM, 2024.
254 doi:10.1145/3678232.3678233.
- 255 10 Davide Fissore and Enrico Tassi. Determinacy checking for elpi: an higher-order logic program-
256 ming language with cut. In *Practical Aspects of Declarative Languages: 28th International*
257 *Symposium, PADL 2026, Rennes, France, January 12–13, 2026, Proceedings*, pages 77–95,
258 Berlin, Heidelberg, 2026. Springer-Verlag. doi:10.1007/978-3-032-15981-6_5.
- 259 11 Benjamin Grégoire, Jean-Christophe Léchenet, and Enrico Tassi. Practical and sound equality
260 tests, automatically. In *Proceedings of CPP*, page 167–181. Association for Computing
261 Machinery, 2023. doi:10.1145/3573105.3575683.
- 262 12 Ferruccio Guidi, Claudio Sacerdoti Coen, and Enrico Tassi. Implementing type theory
263 in higher order constraint logic programming. In *Mathematical Structures in Computer*
264 *Science*, volume 29, pages 1125–1150. Cambridge University Press, 2019. doi:10.1017/
265 S0960129518000427.
- 266 13 Robbert Krebbers, Luko van der Maas, and Enrico Tassi. Inductive Predicates via Least
267 Fixpoints in Higher-Order Separation Logic. In Yannick Forster and Chantal Keller, editors,
268 *16th International Conference on Interactive Theorem Proving (ITP 2025)*, volume 352 of *Leib-*
269 *niz International Proceedings in Informatics (LIPIcs)*, pages 27:1–27:21, Dagstuhl, Germany,
270 2025. Schloss Dagstuhl – Leibniz-Zentrum für Informatik. URL: [https://drops.dagstuhl.](https://drops.dagstuhl.de/entities/document/10.4230/LIPIcs.ITP.2025.27)
271 [de/entities/document/10.4230/LIPIcs.ITP.2025.27](https://drops.dagstuhl.de/entities/document/10.4230/LIPIcs.ITP.2025.27), doi:10.4230/LIPIcs.ITP.2025.27.
- 272 14 Dale Miller. A logic programming language with lambda-abstraction, function variables, and
273 simple unification. In *Extensions of Logic Programming*, pages 253–281. Springer, 1991.
- 274 15 Dale Miller and Gopalan Nadathur. *Programming with Higher-Order Logic*. Cambridge
275 University Press, 2012.
- 276 16 Cornelia Pusch. Verification of compiler correctness for the wam. In Gerhard Goos, Juris
277 Hartmanis, Jan van Leeuwen, Joakim von Wright, Jim Grundy, and John Harrison, editors,
278 *Theorem Proving in Higher Order Logics*, pages 347–361, Berlin, Heidelberg, 1996. Springer
279 Berlin Heidelberg.
- 280 17 Enrico Tassi. Elpi: an extension language for Coq (Metaprogramming Coq in the Elpi λ Prolog
281 dialect). In *The Fourth International Workshop on Coq for Programming Languages*, January
282 2018. URL: <https://inria.hal.science/hal-01637063>.
- 283 18 Enrico Tassi. Deriving proved equality tests in Coq-Elpi. In *Proceedings of ITP*, volume 141 of
284 *LIPIcs*, pages 29:1–29:18, September 2019. URL: <https://inria.hal.science/hal-01897468>,
285 doi:10.4230/LIPIcs.CVIT.2016.23.
- 286 19 Luko van der Maas. Extending the Iris Proof Mode with inductive predicates using Elpi.
287 Master’s thesis, Radboud University Nijmegen, 2024. doi:10.5281/zenodo.12568604.
- 288 20 David H.D. Warren. An Abstract Prolog Instruction Set. Technical Report Technical Note 309,
289 SRI International, Artificial Intelligence Center, Computer Science and Technology Division,
290 Menlo Park, CA, USA, October 1983. URL: [https://www.sri.com/wp-content/uploads/](https://www.sri.com/wp-content/uploads/2021/12/641.pdf)
291 2021/12/641.pdf.