

# Final Presentation

- Fitsum W. Beyene
- Nov 11, 2023



IBM Developer  
SKILLS NETWORK

# Outline

---

- Executive Summary
- Introduction
- Methodology
- Results
- Conclusion
- Appendix

# Executive Summary

---

- Summary of methodologies
  - Data Collection via API, Web Scraping
  - Exploratory Data Analysis (EDA) with Data Visualization
  - EDA with SQL
  - Interactive Map with Folium
  - Dashboards with Plotly Dash
  - Predictive Analysis
- Summary of all results
  - Exploratory Data Analysis results
  - Interactive maps and dashboard
  - Predictive results

# Introduction

---

- Project background and context
  - The aim of this project is to predict if the Falcon 9 first stage will successfully land. SpaceX says on its website that the Falcon 9 rocket launch cost 62 million dollars. Other providers cost upward of 165 million dollars each. The price difference is explained by the fact that SpaceX can reuse the first stage. By determining if the stage will land, we can determine the cost of a launch. This information is interesting for another company if it wants to compete with SpaceX for a rocket launch.
- Problems you want to find answers
  - What are the main characteristics of a successful or failed landing ?
  - What are the effects of each relationship of the rocket variables on the success or failure of a landing ?
  - What are the conditions which will allow SpaceX to achieve the best landing success rate ?

---

- 5

Section 1

# Methodology

# Methodology

---


## Executive Summary

- Data collection methodology:
  - SpaceX REST API
  - Web Scrapping from Wikipedia
- Perform data wrangling
  - Dropping unnecessary columns
  - One Hot Encoding for classification models
- Perform exploratory data analysis (EDA) using visualization and SQL
- Perform interactive visual analytics using Folium and Plotly Dash
- Perform predictive analysis using classification models
  - How to build, tune, evaluate classification models


# Data Collection

---

- Datasets are collected from Rest SpaceX API and webscrapping Wikipedia
  - The information obtained by the API are rocket, launches, payload information.
    - The Space X REST API URL is [api.spacexdata.com/v4/](https://api.spacexdata.com/v4/)



- The information obtained by the webscrapping of Wikipedia are launches, landing, payload information.
  - URL is [https://en.wikipedia.org/w/index.php?title=List\\_of\\_Falcon\\_9\\_and\\_Falcon\\_Heavy\\_launches&oldid=1027686922](https://en.wikipedia.org/w/index.php?title=List_of_Falcon_9_and_Falcon_Heavy_launches&oldid=1027686922)



# Data Collection - SpaceX API

## 1. Getting Response from API

```
spacex_url="https://api.spacexdata.com/v4/launches/past"  
response = requests.get(spacex_url)
```

## 2. Convert Response to JSON File

```
data = response.json()  
data = pd.json_normalize(data)
```

## 3. Transform data

```
getLaunchSite(data)  
getPayloadData(data)  
getCoreData(data)  
getBoosterVersion(data)
```

## 4. Create dictionary with data

```
launch_dict = {'FlightNumber': list(data['flight_number']),  
               'Date': list(data['date']),  
               'BoosterVersion':BoosterVersion,  
               'PayloadMass':PayloadMass,  
               'Orbit':Orbit,  
               'LaunchSite':LaunchSite,  
               'Outcome':Outcome,  
               'Flights':Flights,  
               'GridFins':GridFins,  
               'Reused':Reused,  
               'Legs':Legs,  
               'LandingPad':LandingPad,  
               'Block':Block,  
               'ReusedCount':ReusedCount,  
               'Serial':Serial,  
               'Longitude': Longitude,  
               'Latitude': Latitude}
```

## 5. Create dataframe

```
data = pd.DataFrame.from_dict(launch_dict)
```

## 6. Filter dataframe

```
data_falcon9 = data[data['BoosterVersion']!='Falcon 1']
```

## 7. Export to file

```
data_falcon9.to_csv('dataset_part_1.csv', index=False)
```

[Link to code](#)



# Data Collection - Scraping

## 1. Getting Response from HTML

```
response = requests.get(static_url)
```

## 2. Create BeautifulSoup Object

```
soup = BeautifulSoup(response.text, "html5lib")
```

## 3. Find all tables

```
html_tables = soup.findAll('table')
```

## 4. Get column names

```
for th in first_launch_table.find_all('th'):
    name = extract_column_from_header(th)
    if name is not None and len(name) > 0 :
        column_names.append(name)
```

## 5. Create dictionary

```
launch_dict= dict.fromkeys(column_names)

# Remove an irrelevant column
del launch_dict['Date and time ( )']

# Let's initial the launch_dict with each value to be an empty list
launch_dict['Flight No.'] = []
launch_dict['Launch site'] = []
launch_dict['Payload'] = []
launch_dict['Payload mass'] = []
launch_dict['Orbit'] = []
launch_dict['Customer'] = []
launch_dict['Launch outcome'] = []
# Added some new columns
launch_dict['Version Booster']=[]
launch_dict['Booster landing']=[]
launch_dict['Date']=[]
launch_dict['Time']=[]
```

## 6. Add data to keys

```
extracted_row = 0
#Extract each table
for table_number,table in enumerate(soup.find_all(
    # get table row
    for rows in table.find_all("tr"):
        #check to see if first table heading is a
        if rows.th:
            if rows.th.string:
                flight_number=rows.th.string.stri
                flag=flight_number.isdigit()
```

See notebook for the rest of code

## 7. Create dataframe from dictionary

```
df=pd.DataFrame(launch_dict)
```

## 8. Export to file

```
df.to_csv('spacex_web_scraped.csv', index=False)
```

[Link to code](#)

# Data Wrangling

- In the dataset, there are several cases where the booster did not land successfully.
  - True Ocean, True RTLS, True ASDS means the mission has been successful.
  - False Ocean, False RTLS, False ASDS means the mission was a failure.
- We need to transform string variables into categorical variables where 1 means the mission has been successful and 0 means the mission was a failure.

## 1. Calculate launches number for each site

```
df['LaunchSite'].value_counts()
```

```
CCAFS SLC 40    55
KSC LC 39A      22
VAFB SLC 4E     13
Name: LaunchSite, dtype: int64
```

## 2. Calculate the number and occurrence of each orbit

```
df['Orbit'].value_counts()
```

```
GTO      27
ISS      21
VLEO     14
PO        9
LEO       7
SSO       5
MEO       3
SO        1
ES-L1     1
HEO       1
GEO       1
Name: Orbit, dtype: int64
```

## 3. Calculate number and occurrence of mission outcome per orbit type

```
landing_outcomes = df['Outcome'].value_counts()
landing_outcomes
```

```
True ASDS      41
None None      19
True RTLS      14
False ASDS      6
True Ocean      5
None ASDS       2
False Ocean     2
False RTLS      1
Name: Outcome, dtype: int64
```

## 4. Create landing outcome label from Outcome column

```
landing_class = []
for key,value in df["Outcome"].items():
    if value in bad_outcomes:
        landing_class.append(0)
    else:
        landing_class.append(1)
df['Class']=landing_class
```

## 5. Export to file

```
df.to_csv("dataset_part_2.csv", index=False)
```


[Link to code](#)

# EDA with Data Visualization

---

- Scatter Graphs

- Flight Number vs. Payload Mass
- Flight Number vs. Launch Site
- Payload vs. Launch Site
- Orbit vs. Flight Number
- Payload vs. Orbit Type
- Orbit vs. Payload Mass



*Scatter plots show relationship between variables. This relationship is called the correlation.*

- Bar Graph

- Success rate vs. Orbit


*Bar graphs show the relationship between numeric and categoric variables.*



- Line Graph

- Success rate vs. Year

*Line graphs show data variables and their trends. Line graphs can help to show global behavior and make prediction for unseen data.*



# EDA with SQL

---

- We performed SQL queries to gather and understand data from dataset:
  - Displaying the names of the unique launch sites in the space mission.
  - Display 5 records where launch sites begin with the string 'CCA'
  - Display the total payload mass carried by boosters launched by NASA (CRS).
  - Display average payload mass carried by booster version F9 v1.1.
  - List the date when the first successful landing outcome in ground pad was achieved.
  - List the names of the boosters which have success in drone ship and have payload mass greater than 4000 but less than 6000.
  - List the total number of successful and failure mission outcomes.
  - List the names of the booster\_versions which have carried the maximum payload mass.
  - List the records which will display the month names, failure landing\_outcomes in drone ship, booster versions, launch\_site for the months in year 2015.
  - Rank the count of successful landing\_outcomes between the date 04-06-2010 and 20-03-2017 in descending order.

[Link to code](#)

# Build an Interactive Map with Folium

---

- Folium map object is a map centered on NASA Johnson Space Center at Houston, Texas
  - Red circle at NASA Johnson Space Center's coordinate with label showing its name (*folium.Circle, folium.map.Marker*).
  - Red circles at each launch site coordinates with label showing launch site name (*folium.Circle, folium.map.Marker, folium.features.DivIcon*).
  - The grouping of points in a cluster to display multiple and different information for the same coordinates (*folium.plugins.MarkerCluster*).
  - Markers to show successful and unsuccessful landings. **Green** for successful landing and **Red** for unsuccessful landing. (*folium.map.Marker, folium.Icon*).
  - Markers to show distance between launch site to key locations (railway, highway, coastway, city) and plot a line between them. (*folium.map.Marker, folium.PolyLine, folium.features.DivIcon*)
- These objects are created in order to understand better the problem and the data. We can show easily all launch sites, their surroundings and the number of successful and unsuccessful landings.

# Build a Dashboard with Plotly Dash

---

- Dashboard has dropdown, pie chart, rangeslider and scatter plot components
  - Dropdown allows a user to choose the launch site or all launch sites (*dash\_core\_components.Dropdown*).
  - Pie chart shows the total success and the total failure for the launch site chosen with the dropdown component (*plotly.express.pie*).
  - Rangeslider allows a user to select a payload mass in a fixed range (*dash\_core\_components.RangeSlider*).
  - Scatter chart shows the relationship between two variables, in particular Success vs Payload Mass (*plotly.express.scatter*).

[Link to code](#)

# Predictive Analysis (Classification)

---

- Data preparation
  - Load dataset
  - Normalize data
  - Split data into training and test sets.
- Model preparation
  - Selection of machine learning algorithms
  - Set parameters for each algorithm to GridSearchCV
  - Training GridSearchModel models with training dataset
- Model evaluation
  - Get best hyperparameters for each type of model
  - Compute accuracy for each model with test dataset
  - Plot Confusion Matrix
- Model comparison
  - Comparison of models according to their accuracy
  - The model with the best accuracy will be chosen (see Notebook for result)

# Results

---

- Exploratory data analysis results
- Interactive analytics demo in screenshots
- Predictive analysis results



# Conclusions

---

- The success of a mission can be explained by several factors such as the launch site, the orbit and especially the number of previous launches. Indeed, we can assume that there has been a gain in knowledge between launches that allowed to go from a launch failure to a success.
- The orbits with the best success rates are GEO, HEO, SSO, ES-L1.
- Depending on the orbits, the payload mass can be a criterion to take into account for the success of a mission. Some orbits require a light or heavy payload mass. But generally low weighted payloads perform better than the heavy weighted payloads.
- With the current data, we cannot explain why some launch sites are better than others (KSC LC-39A is the best launch site). To get an answer to this problem, we could obtain atmospheric or other relevant data.
- For this dataset, we choose the Decision Tree Algorithm as the best model even if the test accuracy between all the models used is identical. We choose Decision Tree Algorithm because it has a better train accuracy.

Thank you!

