

1-4 基本的算法结构

魏恒峰

hfwei@nju.edu.cn

2017 年 11 月 06 日

Longest Monotone Subsequence

ES 24.8: Longest Monotone Subsequence

Write a computer program that takes as its input a sequence of distinct integers and returns as its output the length of a longest monotone subsequence.

ES 24.8: Longest Monotone Subsequence

Write a computer program that takes as its input a sequence of distinct integers and returns as its output the length of a longest monotone subsequence.

Understanding this problem:

ES 24.8: Longest Monotone Subsequence

Write a computer program that takes as its input a sequence of distinct integers and returns as its output the length of a longest monotone subsequence.

Understanding this problem:

Subsequence vs. substring

ES 24.8: Longest Monotone Subsequence

Write a computer program that takes as its input a sequence of distinct integers and returns as its output the length of a longest monotone subsequence.

Understanding this problem:

Subsequence vs. substring

Monotone increasing vs. decreasing

ES 24.8: Longest Monotone Subsequence

Write a computer program that takes as its input a sequence of distinct integers and returns as its output the length of a longest monotone subsequence.

Understanding this problem:

Subsequence vs. substring

Monotone increasing vs. decreasing strictly vs. non-strictly

ES 24.8: Longest Monotone Subsequence

Write a computer program that takes as its input a sequence of distinct integers and returns as its output the length of a longest monotone subsequence.

Understanding this problem:

Subsequence vs. substring

Monotone increasing vs. decreasing strictly vs. non-strictly

Longest existence? uniqueness?

ES 24.8: Longest (Strictly) Increasing Subsequence (LIS)

- ▶ Given an integer array $A[0 \dots n - 1]$
- ▶ To find (the length L of) an LIS

0, 8, 4, 12, 2, 10, 6, 14, 1, 9, 5, 13, 3, 11, 7, 15 \implies 0, 2, 6, 9, 11, 15

ES 24.8: Longest (Strictly) Increasing Subsequence (LIS)

- ▶ Given an integer array $A[0 \dots n - 1]$
- ▶ To find (the length L of) an LIS

0, 8, 4, 12, 2, 10, 6, 14, 1, 9, 5, 13, 3, 11, 7, 15 \implies 0, 2, 6, 9, 11, 15

0, 4, 6, 9, 11, 15

学生反馈： 这道题为什么放在 “Pigeonhole Principle” 这一章？

学生反馈： 这道题为什么放在“Pigeonhole Principle”这一章？



学生反馈： 这道题为什么放在 “Pigeonhole Principle” 这一章？



Theorem (Erdős-Szekeres Theorem)

Let n be a positive integer. Every sequence of $n^2 + 1$ distinct integers must contain a monotone subsequence of length $n + 1$.

Q : 这道题与 (强) 数学归纳法有什么关系?

Q : 这道题与 (强) 数学归纳法有什么关系?

B.S. $P(0)$

I.H. $P(0) \cdots P(i-1)$

I.S. $P(0) \cdots P(i-1) \rightarrow P(i)$

Q : 这道题与 (强) 数学归纳法有什么关系?

B.S. $P(0)$

I.H. $P(0) \cdots P(i-1)$

I.S. $P(0) \cdots P(i-1) \rightarrow P(i)$

$P(i)$ 是什么?

$P(i)$: the length of an LIS in $A[0 \cdots i]$.

$P(i)$: the length of an LIS in $A[0 \cdots i]$.

$$L = P(n - 1)$$

$P(i)$: the length of an LIS in $A[0 \cdots i]$.

$$L = P(n - 1)$$

$$P(0) = 1$$

$P(i)$: the length of an LIS in $A[0 \cdots i]$.

$$L = P(n - 1)$$

$$P(0) = 1$$

$$P(0) \cdots P(i - 1) \rightarrow P(i)?$$

$P(i)$: the length of an LIS in $A[0 \cdots i]$.

$$L = P(n - 1)$$

$$P(0) = 1$$

$$P(0) \cdots P(i - 1) \rightarrow P(i)?$$

$$P(i) = \max\{P(i - 1), \max_{\substack{0 \leq j < i \\ A[j] < A[i]}} \{P(j) + 1\}\}$$

$P(i)$: the length of an LIS in $A[0 \cdots i]$.

$$L = P(n - 1)$$

$$P(0) = 1$$

$$P(0) \cdots P(i - 1) \rightarrow P(i)?$$

$$P(i) = \max\{P(i - 1), \max_{\substack{0 \leq j < i \\ A[j] < A[i]}} \{P(j) + 1\}\}$$

$P(i)$: the length of an LIS in $A[0 \cdots i]$.

$$L = P(n - 1)$$

$$P(0) = 1$$

$$P(0) \cdots P(i - 1) \rightarrow P(i)?$$

$$P(i) = \max\{P(i - 1), \max_{\substack{0 \leq j < i \\ A[j] < A[i]}} \{P(j) + 1\}\}$$



$P(i)$: the length of an LIS *ending at* i .

$P(i)$: the length of an LIS *ending at* i .

$$L = \max_{1 \leq i < n} P(i)$$

$P(i)$: the length of an LIS *ending at* i .

$$L = \max_{1 \leq i < n} P(i)$$

$$P(0) = 1$$

$P(i)$: the length of an LIS *ending at* i .

$$L = \max_{1 \leq i < n} P(i)$$

$$P(0) = 1$$

$$P(i) = \max_{\substack{0 \leq j < i \\ A[j] < A[i]}} \{P(j) + 1\}$$

$$P(0) = 1;$$

```
for (int i = 1; i < n; ++i)
```

$$P(i) = \max_{\substack{0 \leq j < i \\ A[j] < A[i]}} \{P(j) + 1\}$$

```
return L = \max_{0 \leq i < n} P(i);
```

$$P(0) = 1;$$

```
for (int i = 1; i < n; ++i)
```


$$P(i) = \max_{\substack{0 \leq j < i \\ A[j] < A[i]}} \{P(j) + 1\}$$

```
return L = \max_{0 \leq i < n} P(i);
```



Flowcharts

How to Argue with Your Girlfriend?



Simulations

DH 2.5: Simulations

Show how to perform the following simulations of some control constructs by others.

(a) “for-do” by “while-do”

```
for (init; cond; inc)
    statement
```

DH 2.5: Simulations

Show how to perform the following simulations of some control constructs by others.

(a) “for-do” by “while-do”

```
for (init; cond; inc)
    statement
```

```
init;
while (cond)
    statement
    inc
```

DH 2.5: Simulations

Show how to perform the following simulations of some control constructs by others.

(a) “for-do” by “while-do”

```
for (init; cond; inc)
    statement
```

```
init;
while (cond)
    statement
    inc
```

Whether to use “while” or “for” is largely a matter of personal preference.

— K&R C Bible

DH 2.5: Simulations

Show how to perform the following simulations of some control constructs by others.

(b) “if-then & if-then-else” by “while-do”

DH 2.5: Simulations

Show how to perform the following simulations of some control constructs by others.

(b) “if-then & if-then-else” by “while-do”

```
if (A)  
  B
```

DH 2.5: Simulations

Show how to perform the following simulations of some control constructs by others.

(b) “if-then & if-then-else” by “while-do”

```
if (A)
  B
```

```
flag = 1
while (A && flag)
  B
  flag = 0
```


DH 2.5: Simulations

Show how to perform the following simulations of some control constructs by others.

(b) “if-then & if-then-else” by “while-do”

```
if (A)
  B
```

```
flag = 1
while (A && flag)
  B
  flag = 0
```

```
if (A)
  B
else
  C
```

DH 2.5: Simulations

Show how to perform the following simulations of some control constructs by others.

(b) “if-then & if-then-else” by “while-do”

```
if (A)
  B
```

```
flag = 1
while (A && flag)
  B
  flag = 0
```

```
if (A)
  B
else
  C
```

```
flag = 1
while (A && flag)
  B
  flag = 0
while ( $\neg$  A && flag)
  B
  flag = 0
```

DH 2.5: Simulations

Simulate the following control constructs by others.

(c) “while-do” by “if-then & goto”

(d) “while-do” by “repeat-until & if-then”

```
while (A)
    B
```

DH 2.5: Simulations

Simulate the following control constructs by others.

(c) “while-do” by “if-then & goto”

(d) “while-do” by “repeat-until & if-then”

```
while (A)
    B
```

```
L: if (A)
    B
    goto loop
```

DH 2.5: Simulations

Simulate the following control constructs by others.

(c) “while-do” by “if-then & goto”

(d) “while-do” by “repeat-until & if-then”

```
while (A)
  B
```

```
L: if (A)
    B
    goto loop
```

```
if (A)
  repeat
    B
  until ( $\neg$  A)
```

DH 2.8: Simulations

Simulate “while-do” by “if-then-else & recursive”.

```
while (A)  
  B
```

DH 2.8: Simulations

Simulate “while-do” by “if-then-else & recursive”.

```
while (A)  
  B
```

```
simulateWhile() {  
  if (A)  
    B  
    simulateWhile();  
  
  return;  
}
```

- (1) A;B
- (2) if-then
- (3) if-then-else
- (4) for-do
- (5) while-do
- (6) repeat-until

- (1) A;B
- (2) if-then
- (3) if-then-else
- (4) for-do
- (5) while-do
- (6) repeat-until

```
repeat
  B
until ( $\neg$  A)
```

- (1) A;B
- (2) if-then
- (3) if-then-else
- (4) for-do
- (5) while-do
- (6) repeat-until

```
repeat  
  B  
until ( $\neg$  A)
```

```
B  
while (A)  
  B
```


- (1) A;B
- (2) if-then
- (3) if-then-else
- (4) for-do
- (5) while-do
- (6) repeat-until

```
repeat  
  B  
until ( $\neg$  A)
```

```
B  
while (A)  
  B
```

Theorem (“On Folk Theorems” (David Harel, 1980))

Any *computable function* can be computed by a “while-do” (and “;”) program (with additional Boolean variables).



Simulations

Bounded iteration vs. Unbounded iteration

DH 2.4: Bounded Iteration

Given a list L of N integers, to produce in S and P the sum of the even numbers in L and the product of the odd ones, respectively.

DH 2.4: Bounded Iteration

Given a list L of N integers, to produce in S and P the sum of the even numbers in L and the product of the odd ones, respectively.

```
int S = 0, P = 1;
for (int i = 0; i < N; ++i) {
    if (L(i) % 2 == 0)
        S += L(i);
    else
        P *= L(i);
}
```

DH 2.4: Bounded Iteration

Given a list L of N integers, to produce in S and P the sum of the even numbers in L and the product of the odd ones, respectively.

```
int S = 0, P = 1;
for (int i = 0; i < N; ++i) {
    if (L(i) % 2 == 0)
        S += L(i);
    else
        P *= L(i);
}
```

DH 2.1: Salary Summation

$N - 1$ vs. N iterations

DH 2.4: Bounded Iteration

Given a list L of N integers, to produce in S and P the sum of the even numbers in L and the product of the odd ones, respectively.

```
int S = 0, P = 1;
for (int i = 0; i < N; ++i) {
    if (L(i) % 2 == 0)
        S += L(i);
    else
        P *= L(i);
}
```

DH 2.1: Salary Summation

$N - 1$ vs. N iterations



DH 2.7: Compute $n!$

Write algorithms that compute $n!$, given a non-negative integer n .

- (a) Using iteration statements.
- (b) Using recursion.

DH 2.7: Compute $n!$

Write algorithms that compute $n!$, given a non-negative integer n .

- (a) Using iteration statements.
- (b) Using recursion.

```
int P = 1;
for (int i = 1; i <= n; ++i) {
    P *= i;
}
```

DH 2.7: Compute $n!$

Write algorithms that compute $n!$, given a non-negative integer n .

- (a) Using iteration statements.
- (b) Using recursion.

```
int P = 1;
for (int i = 1; i <= n; ++i) {
    P *= i;
}
```

```
int recursive-factorial(int n) {
    if (n == 1)
        return 1;
    else n * recursive-factorial(n-1);
}
```

Thank
You!