

Präzisions-Führungselemente

Eléments de guidage de précision

N420

Bundbüchse, bronzeplattiert / Douille avec col, guidage bronze

Werkstoff / matière:

Stahl / acier 18 Ni Cr Mo 5 Bronze / bronze G Sn Pb Bz 10

Härte / trempe:

58 - 60HRc

Härtung / trempage:

einsatzgehärtet / cémenté

Ausführung / éxecution:

geläppt / rectifié

| | | _ | _ | |
|---|---|-----|---|--|
| N | Δ | . 7 | n | |
| | _ | _ | v | |

| d1 | 19/20 | 24/25 | 30/32 | 38/40 | 48/50 | 63 |
|----|-------|-------|-------|-------|-------|-------|
| d2 | 32 | 40 | 48 | 58 | 70 | 85 |
| d3 | 38 | 43 | 51 | 63 | 76 | 93 |
| d4 | 40 | 45 | 54 | 66 | 80 | 95 |
| d6 | 52 | 56 | 66 | 76 | 91 | 108 |
| | M6 | M6 | M8 | M8 | M8 | M8 |
| L | 59 | 70 | 80 | 95 | 115 | 140 |
| L1 | 28 | 32 | 37 | 42 | 48 | 50 |
| d7 | 67,9 | 71,8 | 81,7 | 92,7 | 106,6 | 123,4 |
| b | 22,3 | 23,3 | 25,8 | 28,5 | 32 | 36,3 |
| b1 | 32 | 33,7 | 38 | 42,8 | 48,8 | 56,2 |


N 421

| d1 | 19/20 | 24/25 | 30/32 | 38/40 | 48/50 | 63 | |
|----|-------|-------|-------|-------|-------|----|--|
| L | 40 | 40 | 51 | 61 | 61 | 70 | |
| L1 | 18 | 27 | 37 | 46 | 48 | 50 | |


N 422

| d1 | 19/20 | 24/25 | 30/32 | 38/40 | 48/50 | 63 |
|----|-------|-------|-------|-------|-------|-----|
| L | 50 | 55 | 55 | 67 | 70 | 105 |
| L1 | 27 | 27 | 27 | 30 | 45 | 50 |





N 421



N 422

