

Dr. Mattox Beckman

- Describe the problem that monads attempt to solve.
- Know the three monad laws.
- Know the syntax for declaring monadic operations.
- Be able to give examples using the Maybe and List monads.

Notice the pattern

- Monads are a way of defining computation.
- They are similar to continuations, but even more powerful.
- They are also related to the applicative functors from last time.
- Consider this program....

But what if we have functions like this?

How can we pass a Nothing to it? How can we use what we get from it?

- Applicatives take the values out of the parameters, run them through a function, and then repackage the result for us.
- The functions have no control: the applicative makes all the decisions.
- Monads let the functions themselves decide what should happen.

Introducing Monads

- A *monad* is a container type *m* along with two functions:
 - `return :: a -> m a`
 - `bind :: m a -> (a -> m b) -> m b`
 - In Haskell, bind is written as `>>=`
- These functions must obey three laws:
 - Left identity** `return a >>= f` is the same as `f a`
 - Right identity** `m >>= return` is the same as `m`
 - Associativity** `(m >>= f) >>= g` is the same as `m >>= (\x -> f x >>= g)`

Understanding Return

- The `return` keyword takes an element and puts it into a monad.
- This is a one way trip!
- Very much like `pure` in Applicative.

```
1 return a = Just a
```

Understanding Bind

- All the magic happens in bind.
- `bind :: m a -> (a -> m b) -> m b`
 - The first argument is a monad.
 - The second argument takes a monad, unpacks it, and repackages it with the help of the function argument.
 - Exactly *how* it does that is the magic part.

Bind for Maybe

```
1 Nothing >>= f = Nothing
2 (Just a) >>= f = f a
3 -- Remember that f returns a monad
```

A calculator, with monads

```
1 minc x = x >>= (\xx -> return (xx + 1))
2 madd a b = a >>= (\aa ->
3             b >>= (\bb -> return (aa+bb)))
4 -- but wait!!!
```

- Okay, the above code works, but here's a better way.
- First define functions `lift` to convert a function to monadic form for us!

These are part of Control.Monad

```
1 liftM f a = a >>= (\aa -> return (f aa))
2 liftM2 f a b = a >>= (\aa ->
3                      b >>= (\bb -> return (f aa bb)))
```

Continued

Lifting

```

1 minc = liftM inc
2 madd = liftM2 add
3 msub = liftM2 sub
4 mdiv = a >=> (\aa ->
5             b >=> (\bb ->
6                 if bb == 0 then fail "/0"
7                 else return (dv aa bb)))

```

- fail is another useful monadic function.
- Here it's defined as Nothing.

A monad definition

- Here is the complete monad definition for Maybe

Maybe Monad

```

1 instance Monad Maybe where
2   return = Just
3
4   (>=>) Nothing f = Nothing
5   (>=>) (Just a) f = f a
6
7   fail s = Nothing

```

A list monad

List Monad

```

1 instance Monad [] where
2   return a = [a]
3
4   (>=>) [] f = []
5   (>=>) xs f = concatMap f xs
6
7   fail s = []

```

- Note that we do not have to change *anything* in our lifted calculator example!

More capability

- What is the square root of 4?

Adding nondeterminism

```

1 msqrt a = a >=> (\aa ->
2             let sa = sqrt aa
3             in [-sa,sa])
4
5
6 msqrt [4] >=> minc -- becomes [-1,3]

```

Do notation

- Haskell has a special builtin syntax for monads.

```
1 mdiv a b = do aa <- a
2           bb <- b
3           if bb == 0 then fail "/" else return (dv aa bb)
4
```

- If you only need applicative, it's better to use that than monads.
- Avoid do notation if you can.