

Measure 2: Savings potentials, Normalization, Proportionalization and Creation of Plots and Tables

Marlene Kindler

2025-03-19

Code for the calculation of the savings potential using the results of the LCA-studies. Normalization and Proportionalization is performed as well as the creation of plots and tables. The code needs to be adjusted to the specific measure in the parameter section.

To execute, change:

- Login data for Nextcloud
- Adjust download location
- Adjust upload location
- Adjust URLs for uploading

Load Packages:

```
# install.packages("httr")  
# install.packages("readxl")  
# install.packages("dplyr")  
# install.packages("writexl")  
# install.packages("ggplot2")  
# install.packages("tidyr")  
# install.packages("openxlsx")  
# install.packages("flextable")  
# install.packages("officer")
```

```
library(readxl)  
library(httr)  
library(dplyr)  
library(writexl)  
library(ggplot2)  
library(tidyr)  
library(openxlsx)  
library(flextable)  
library(officer)
```

Parameters

Parameters to be adjusted:

```
measure <- "02" # "02", "03" or "04"  
sheet <- 3 # 3,4 or 5
```

```

# name for columns
name_with <- "with FR"
name_without <- "without FR"
name_SP <- "SP FR"
name_SP_prop <- "prop. SP FR"
name_with_prop <- "prop. with FR"
name_without_prop <- "prop. without FR"
name_with_norm <- "norm. with FR"
name_without_norm <- "norm. without FR"
name_SP_norm <- "norm. SP FR"
# vector with excluded categories due to missing normalization factor
excluded_categories_nf <- c("Climate change: biogenic",
                           "Climate change: fossil",
                           "Climate change: land use and land use change",
                           "Ecotoxicity: freshwater, inorganics",
                           "Ecotoxicity: freshwater, organics",
                           "Human toxicity: carcinogenic, inorganics",
                           "Human toxicity: carcinogenic, organics",
                           "Human toxicity: non-carcinogenic, inorganics",
                           "Human toxicity: non-carcinogenic, organics")
# vector with excluded toxicity categories for Pareto rule
excluded_categories_pr <- c("Human toxicity: carcinogenic",
                           "Human toxicity: non-carcinogenic",
                           "Ecotoxicity: freshwater")

# storage location
location_download <-
"C:/Users/Klene/Documents/Uni_Bremen/WS24_25/Masterarbeit/R/Daten/"
location_upload <-
"C:/Users/Klene/Documents/Uni_Bremen/WS24_25/Masterarbeit/R/Results/"
# Login data for NextCloud
username <- "mkindler@uni-bremen.de" # username
password <- "xxxxxxx" # password
# WebDAV-URL to file
nextcloud_url <- "https://nc.uni-
bremen.de/remote.php/dav/files/mkindler%40uni-
bremen.de/Masterarbeit/Masterarbeit_II/R/Daten/Ergebnisse_LCA_basic.xlsx"
nextcloud_url_2 <- "https://nc.uni-
bremen.de/remote.php/dav/files/mkindler%40uni-
bremen.de/Masterarbeit/Masterarbeit_II/R/Results/"

```

Data preparation

Load data from NextCloud:

```

# download file
response <- GET(nextcloud_url, authenticate(username, password, type =
"basic"))
# Check successful downloading
if (status_code(response) == 200) {
  # Save file
}

```

```

writeBin(content(response, "raw"), paste0(location_download,
"Ergebnisse_LCA_basic.xlsx"))
  cat("The file was successfully downloaded and saved locally.\n")
} else {
  cat("Error downloading the file. Status code: ", status_code(response),
"\n")
}

## The file was successfully downloaded and saved locally.

# Load results data from Excel file
results <- read_excel(paste0(location_download, "Ergebnisse_LCA_basic.xlsx"),
sheet = sheet)
# Check data type: DataFrame
if (is.data.frame(results)) {
  results <- results
} else {
  results <- as.data.frame(results)
}
# Rename columns
results <- results %>%
  rename(
    `impact category` = `Wirkungskategorien`,
    unit = Einheit
  )

# Load normalization factors from Excel file
NF <- read_excel(paste0(location_download, "Ergebnisse_LCA_basic.xlsx"),
sheet = 1)

## New names:
## • `` -> `...2`
## • `` -> `...3`

# Check data type: DataFrame
if (is.data.frame(NF)) {
  NF <- NF
} else {
  NF <- as.data.frame(NF)
}
# Set column names right
NF <- NF[-1, ]
colnames(NF) <- as.character(NF[1, ])
NF <- NF[-1, ]
# Select relevant columns
NF <- NF %>%
  select(`impact category`,
    NF = `normalization factor`\r\n(Matuščík 2024)`)

```

Calculations

Savings potential

Calculation of Savings Potentials:

```
results <- results %>%  
  mutate(!!sym(name_SP) := !!sym(name_without) - !!sym(name_with))
```

Normalization

Calculation of normalized values (to the planetary boundaries (Matušík 2024)):

```
# Join of results and NF according to the impact categories  
results <- left_join(results, NF, by = c("impact category" = "impact  
category"))  
# Convert all columns except the first two into numerical values  
results <- results %>%  
  mutate_at(vars(-1, -2), as.numeric)  
  
# Remove categories without normalization factors  
results_norm <- results %>%  
  filter(!`impact category` %in% excluded_categories_nf)  
  
# Calculation of the normalised values by dividing the column values by the  
normalization factors  
results_norm <- results_norm %>%  
  mutate(  
    across(!c(`impact category`, unit, NF), ~ .x / NF, .names = "norm.  
{.col}")  
  )
```

Determine relevant impact categories

Calculation of proportion of total savings potential of each measure:

```
# Removing the toxicity categories  
results_prop <- results_norm %>%  
  filter(!`impact category` %in% excluded_categories_pr)  
  
# Calculate the sum of each normalized column and divide the values by this  
sum  
results_prop <- results_prop %>%  
  mutate(  
    !!sym(name_without_prop) := !!sym(name_without_norm) /  
sum(abs(!!sym(name_without_norm)), na.rm = TRUE),  
    !!sym(name_with_prop) := !!sym(name_with_norm) /  
sum(abs(!!sym(name_with_norm)), na.rm = TRUE),  
    !!sym(name_SP_prop) := !!sym(name_SP_norm) /  
sum(abs(!!sym(name_SP_norm)), na.rm = TRUE)  
  )  
norm_sum <- sum(abs(results_prop[[name_SP_norm]]))
```

Determine relevant impact categories:

```
# Sort categories by proportion of total savings potential
results_prop <- results_prop %>%
  arrange(desc(abs(!!sym(name_SP_prop))))
# Calculation of the cumulative total and mark categories that contribute to
the sum of 0.8
results_prop <- results_prop %>%
  mutate(
    `cum. sum` = cumsum(abs(!!sym(name_SP_prop))),
    relevant = (`cum. sum` < 0.8) | lag(`cum. sum` < 0.8, default = FALSE)
  )
# Mark at least the highest three impact categories
results_prop$relevant[1:3] <- TRUE
```

Save as csv-file

```
write.csv(results_prop, paste0(location_upload, measure, "_data.csv"),
row.names = FALSE)
```

Plot

```
data_plot <- results_prop %>%
  # Select only relevant categories
  filter(relevant == TRUE) %>%
  # Shorten long category names
  mutate(`impact category` = case_when(
    `impact category` == "Photochemical oxidant formation: human health" ~
"POF",
    `impact category` == "Eutrophication: freshwater" ~ "Eutroph. f.",
    TRUE ~ `impact category`
  )) %>%
  select(`impact category`, name_SP_norm) %>%
  # Arrange descending
  arrange(desc(abs(!!sym(name_SP_norm))))
```

```
## Warning: Using an external vector in selections was deprecated in
tidyselect 1.1.0.
```

```
## i Please use `all_of()` or `any_of()` instead.
```

```
## # Was:
```

```
## data %>% select(name_SP_norm)
```

```
##
```

```
## # Now:
```

```
## data %>% select(all_of(name_SP_norm))
```

```
##
```

```
## See <https://tidyselect.r-lib.org/reference/faq-external-vector.html>.
```

```
## This warning is displayed once every 8 hours.
```

```
## Call `lifecycle::last_lifecycle_warnings()` to see where this warning was
## generated.
```

```
# create cummulative sum
```

```
data_plot <- data_plot %>%
  mutate(
```

```

    cumsum = cumsum(abs(data_plot$`norm. SP FR`/norm_sum))*100
  )

# Define impact categories as factor to ensure order
data_plot$`impact category` <- factor(data_plot$`impact category`, levels =
data_plot$`impact category`)

# max. values for scaling
max_norm <- max(data_plot[[name_SP_norm]])
max_cumsum <- max(data_plot$cumsum)

# Conversion factor
factor <- max_norm / max_cumsum

```

Create plot:

```

ggplot(data_plot, aes(x = `impact category`)) +
  geom_bar(aes(y = !!sym(name_SP_norm)), stat = "identity",
            width = 0.7, fill = "brown", show.legend = FALSE) +
  geom_line(aes(y = cumsum * factor, group = 1), color = "black", size = 1) +
  geom_point(aes(y = cumsum * factor), color = "black", size = 2) +
  geom_hline(yintercept = 0, color = "black", linetype = "solid") +
  geom_hline(yintercept = 80 * factor, color = "grey35", linetype = "solid")
+
  annotate("text", x = 4.3, y = 80 * factor, label = "80%", color = "grey35",
size = 4, hjust = 0, vjust = -1) +
  geom_text(aes(
    y = !!sym(name_SP_norm),
    label = format(!!sym(name_SP_norm), scientific = TRUE, digits = 2)),
    vjust = -0.5, size = 5) +
  scale_y_continuous(
    name = "Savings potentials in % of PB",
    sec.axis = sec_axis(~ . / factor, name = "Cumulative sum in %"),
    expand = expansion(mult = c(0.04, 0.07))
  ) +
  labs(x = "Impact category") +
  theme_classic() +
  theme(
    axis.text.x = element_text(angle = 10, hjust = 1, size = 15),
    axis.text.y.left = element_text(color = "brown", size = 15),
    axis.text.y.right = element_text(color = "black", size = 15),
    axis.title.x = element_text(size = 17),
    axis.title.y.left = element_text(size = 17),
    axis.title.y.right = element_text(size = 17)
  )


```

```

## Warning: Using `size` aesthetic for lines was deprecated in ggplot2 3.4.0.
## i Please use `linewidth` instead.
## This warning is displayed once every 8 hours.

```

```
## Call `lifecycle::last_lifecycle_warnings()` to see where this warning was
## generated.
```



```
# Save plot
ggsave(paste0(location_upload, measure, "_relevant_SP_norm_allin1.png"), dpi
= 600)
```

```
## Saving 5 x 4 in image
```

Tables

Prepare data:

```
# Select relevant columns
results_prop <- results_prop %>%
  select(`impact category`, unit, !!sym(name_without_prop),
  !!sym(name_with_prop),
  !!sym(name_SP_prop))
results_norm <- results_norm %>%
  select(`impact category`, unit, !!sym(name_without_norm),
  !!sym(name_with_norm),
  !!sym(name_SP_norm))
# Join of 'results' and 'results_norm' according to the impact categories
results <- left_join(results, results_norm, by = c("impact category" =
"impact category"))
results <- results %>%
  select(-unit.y) %>%
  rename(unit = unit.x)
# Join of 'results' and 'results_prop' according to the impact categories
```

```

results <- left_join(results, results_prop, by = c("impact category" =
"impact category"))
results <- results %>%
  select(-unit.y) %>%
  rename(unit = unit.x)
# Sort descending according to normalized savings potential
results <- results %>%
  arrange(desc(abs(!!sym(name_SP_norm))))

```

Create tables:

```

# Only results
table_results <- results %>%
  select("impact category", "unit", !!sym(name_without), !!sym(name_with),
!!sym(name_SP)) %>%
  arrange(desc(abs(!!sym(name_SP)))) %>%
  mutate(
    across(-all_of(c("impact category", "unit")), ~ formatC(.x, format = "e",
digits = 2)))
# Create flextable
ft <- flextable(table_results) %>%
  theme_vanilla() %>%
  autofit() %>%
  bold(part = "header") %>%
  border_outer() %>%
  border_inner_h() %>%
  border_inner_v()
# Save as PNG
tf <- tempfile(fileext = ".png")
save_as_image(x = ft, path = paste0(location_upload, measure, "_results",
".png"))

## [1]
"C:/Users/Klene/Documents/Uni_Bremen/WS24_25/Masterarbeit/R/Results/02_result
s.png"

# Saving potentials
table_results <- results %>%
  select(`impact category`, unit, !!sym(name_SP), !!sym(name_SP_norm),
!!sym(name_SP_prop)) %>%
  arrange(desc(abs(!!sym(name_SP_norm)))) %>%
  mutate(
    across(-all_of(c("impact category", "unit")), ~ formatC(.x, format = "e",
digits = 2)))
# Create flextable
ft <- flextable(table_results) %>%
  theme_vanilla() %>%
  autofit() %>%
  bold(part = "header") %>%
  border_outer() %>%
  border_inner_h() %>%
  border_inner_v()

```



```

# Save as PNG
tf <- tempfile(fileext = ".png")
save_as_image(x = ft, path = paste0(location_upload, measure, "_results_SPs",
".png"))

## [1]
"C:/Users/Klene/Documents/Uni_Bremen/WS24_25/Masterarbeit/R/Results/02_results_SPs.png"

# Normalized results
table_results <- results %>%
  select("impact category", "unit", !!sym(name_without_norm),
!!sym(name_with_norm), !!sym(name_SP_norm)) %>%
  arrange(desc(abs(!!sym(name_SP_norm)))) %>%
  mutate(
    across(-all_of(c("impact category", "unit")), ~ formatC(.x, format = "e",
digits = 2)))
# Removing the categories without normalization factors
table_results <- table_results %>%
  filter(!`impact category` %in% excluded_categories_nf)
# Rename columns
table_results <- table_results %>%
  rename(!!sym(name_without) := !!sym(name_without_norm),
!!sym(name_with) := !!sym(name_with_norm),
!!sym(name_SP) := !!sym(name_SP_norm)
)
# Create flextable
ft <- flextable(table_results) %>%
  theme_vanilla() %>%
  autofit() %>%
  bold(part = "header") %>%
  border_outer() %>%
  border_inner_h() %>%
  border_inner_v()
# Save as PNG
tf <- tempfile(fileext = ".png")
save_as_image(x = ft, path = paste0(location_upload, measure,
"_results_norm", ".png"))

## [1]
"C:/Users/Klene/Documents/Uni_Bremen/WS24_25/Masterarbeit/R/Results/02_results_norm.png"

# Proportion data
table_results <- results %>%
  select("impact category", "unit", !!sym(name_without_prop),
!!sym(name_with_prop), !!sym(name_SP_prop)) %>%
  arrange(desc(abs(!!sym(name_SP_prop)))) %>%
  mutate(
    across(-all_of(c("impact category", "unit")), ~ formatC(.x, format = "e",
digits = 2)))
# Removing the categories without normalization factor

```

```

table_results <- table_results %>%
  filter(!`impact category` %in% excluded_categories_nf)
# Removing the toxicity categories
table_results <- table_results %>%
  filter(!`impact category` %in% excluded_categories_pr)
# Rename columns
table_results <- table_results %>%
  rename(!sym(name_without) := !!sym(name_without_prop),
         !!sym(name_with) := !!sym(name_with_prop),
         !!sym(name_SP) := !!sym(name_SP_prop),
         )
# Create flextable
ft <- flextable(table_results) %>%
  theme_vanilla() %>%
  autofit() %>%
  bold(part = "header") %>%
  border_outer() %>%
  border_inner_h() %>%
  border_inner_v()
# Save as PNG
tf <- tempfile(fileext = ".png")
save_as_image(x = ft, path = paste0(location_upload, measure,
"_results_prop", ".png"))

## [1]
"C:/Users/Klene/Documents/Uni_Bremen/WS24_25/Masterarbeit/R/Results/02_results_prop.png"

```

Upload files

```

# # List of Excel files to be uploaded
# files_to_upload <- list.files(path = location_upload, pattern = "\\\\.xlsx$",
full.names = TRUE)
# # Loop over all files and upload
# for (file_path in files_to_upload) {
#   # Creating the file name
#   file_name <- basename(file_path)
#   # Upload file
#   response <- PUT(
#     url = paste0(nextcloud_url_2, file_name),
#     authenticate(username, password),
#     body = upload_file(file_path)
#   )
#   # Check upload status
#   if (status_code(response) == 201) {
#     print(paste(file_name, "was successfully uploaded."))
#   } else if (status_code(response) == 204) {
#     print(paste(file_name, "was successfully replaced (no content
returned)."))
#   } else {
#     print(paste("Error uploading", file_name, ". Status-Code:",
status_code(response)))

```

```

#   }
# }
#
# # List of PNG files to be uploaded
# files_to_upload <- list.files(path = location_upload, pattern = "\\\\.png$",
full.names = TRUE)
# # Loop over all files and upload
# for (file_path in files_to_upload) {
#   # Create the file name
#   file_name <- basename(file_path)
#   # Upload file
#   response <- PUT(
#     url = paste0(nextcloud_url_2, file_name),
#     authenticate(username, password),
#     body = upload_file(file_path)
#   )
#   # Check upload status
#   if (status_code(response) == 201) {
#     print(paste(file_name, "was successfully uploaded."))
#   } else if (status_code(response) == 204) {
#     print(paste(file_name, "was successfully replaced (no content
returned)."))
#   } else {
#     print(paste("Error uploading", file_name, ". Status-Code:",
status_code(response)))
#   }
# }

```