

# **C++ Plus Data Structures**

**Nell Dale**

**David Teague**

**Chapter 10**

**Sorting and Searching Algorithms**

# Sorting means . . .

- The values stored in an array have keys of a type for which the relational operators are defined. (We also assume unique keys.)
- Sorting rearranges the elements into either ascending or descending order within the array. (We'll use ascending order.)


# Straight Selection Sort

values [ 0 ]	36
[ 1 ]	24
[ 2 ]	10
[ 3 ]	6
[ 4 ]	12


**Divides the array into two parts: already sorted, and not yet sorted.**

**On each pass, finds the smallest of the unsorted elements, and swaps it into its correct place, thereby increasing the number of sorted elements by one.**


# Selection Sort: Pass One




# Selection Sort: End Pass One




# Selection Sort: Pass Two



# Selection Sort: End Pass Two




# Selection Sort: Pass Three







# Selection Sort: End Pass Three



# Selection Sort: Pass Four



# Selection Sort: End Pass Four



# Selection Sort:

## How many comparisons?

values [ 0 ]	6
[ 1 ]	10
[ 2 ]	12
[ 3 ]	24
[ 4 ]	36

**4 compares for values[0]**

**3 compares for values[1]**

**2 compares for values[2]**

**1 compare for values[3]**

---

$$= 4 + 3 + 2 + 1$$

# For selection sort in general

- The number of comparisons when the array contains N elements is

$$\text{Sum} = (N-1) + (N-2) + \dots + 2 + 1$$

# Notice that . . .

$$\text{Sum} = (N-1) + (N-2) + \dots + 2 + 1$$

$$+ \text{Sum} = 1 + 2 + \dots + (N-2) + (N-1)$$

---

$$2 * \text{Sum} = N + N + \dots + N + N$$

$$2 * \text{Sum} = N * (N-1)$$

$$\text{Sum} = \frac{N * (N-1)}{2}$$

# For selection sort in general

- The number of comparisons when the array contains N elements is

$$\text{Sum} = (N-1) + (N-2) + \dots + 2 + 1$$

$$\text{Sum} = N * (N-1) / 2$$

$$\text{Sum} = .5 N^2 - .5 N$$

$$\text{Sum} = O(N^2)$$

```
template <class ItemType >
int MinIndex ( ItemType values [ ], int start , int end )
// Post: Function value = index of the smallest value in
//       values [start] .. values [end].
{
    int indexOfMin = start ;
    for ( int index = start + 1 ; index <= end ; index++ )
        if ( values [ index ] < values [ indexOfMin ] )
            indexOfMin = index ;

    return indexOfMin;
}
```



```
template <class ItemType >
void SelectionSort ( ItemType values [ ], int numValues )
// Post: Sorts array values[0 . . numValues-1 ] into ascending
//       order by key
{
    int endIndex = numValues - 1 ;
    for ( int current = 0 ; current < endIndex ; current++ )
        Swap ( values [ current ] ,
                values [ MinIndex ( values, current, endIndex ) ] ) ;
}
```

# Bubble Sort

values [ 0 ]	36
[ 1 ]	24
[ 2 ]	10
[ 3 ]	6
[ 4 ]	12

**Compares neighboring pairs of array elements, starting with the last array element, and swaps neighbors whenever they are not in correct order.**

**On each pass, this causes the smallest element to “bubble up” to its correct place in the array.**

# Bubble Sort

36	36	36	6	6	6
24	24	6	36	36	10
10	6	24	24	10	36
6	10	10	10	24	24
12	12	12	12	12	12

....

```
template <class ItemType >
void BubbleUp ( ItemType values [ ], int start , int end )

// Post: Neighboring elements that were out of order have been
//        swapped between values [start] and values [end],
//        beginning at values [end].
{
    for ( int index = end ; index > start ; index-- )
        if ( values [ index ] < values [ index - 1 ] )
            Swap ( values [ index ], values [ index - 1 ] ) ;
}
```

```
template <class ItemType >  
void BubbleSort ( ItemType values [ ], int numValues )  
// Post: Sorts array values[0 . . numValues-1 ] into ascending  
//       order by key  
{  
    int current = 0 ;  
    while ( current < numValues - 1 )  
    {  
        BubbleUp ( values , current , numValues - 1 ) ;  
        current++ ;  
    }  
}
```

# Modified Bubble Sort

```
template <class ItemType >
int BubbleUp ( ItemType values [ ], int start , int end )
{
    int flag=0;
    for ( int index = end ; index > start ; index-- )
        if ( values [ index ] < values [ index - 1 ] )
        {
            Swap ( values [ index ], values [ index - 1 ] ) ;
            flag++;
        }
    return flag;
}

template <class ItemType >
void BubbleSort ( ItemType values [ ], int numValues )
{
    int current = 0 ;
    while ( (current < numValues - 1) && BubbleUp ( values , current , numValues - 1 ) )
    {
        current++ ;
    }
}
```


# Insertion Sort

values	[ 0 ]	36
	[ 1 ]	24
	[ 2 ]	10
	[ 3 ]	6
	[ 4 ]	12

**One by one, each as yet unsorted array element is inserted into its proper place with respect to the already sorted elements.**

**On each pass, this causes the number of already sorted elements to increase by one.**

# Insertion Sort




**Works like someone who “inserts” one more card at a time into a hand of cards that are already sorted.**

**To insert 12, we need to make room for it by moving first 36 and then 24.**





# Insertion Sort



**Works like someone who “inserts” one more card at a time into a hand of cards that are already sorted.**

**To insert 12, we need to make room for it by moving first 36 and then 24.**


# Insertion Sort



**Works like someone who “inserts” one more card at a time into a hand of cards that are already sorted.**

**To insert 12, we need to make room for it by moving first 36 and then 24.**

# Insertion Sort



**Works like someone who “inserts” one more card at a time into a hand of cards that are already sorted.**

**To insert 12, we need to make room for it by moving first 36 and then 24.**

# Insertion Sort

end =	0	1	2			
values [ 0 ]	36	36	24	24	24	10
[ 1 ]	24	24	36	36	10	24
[ 2 ]	10	10	10	10	36	36
[ 3 ]	6	6	6	6	6	6
[ 4 ]	12	12	12	12	12	12

# Insertion Sort

end = 3

4

[ 0 ]	10	10	10	6	6	6	6
[ 1 ]	24	24	6	10	10	10	10
[ 2 ]	36	6	24	24	24	24	12
[ 3 ]	6	36	36	36	36	12	24
[ 4 ]	12	12	12	12	12	36	36

```

template <class ItemType >
void InsertItem ( ItemType values [ ], int start , int end )

// Post: Elements between values [start] and values [end]
//       have been sorted into ascending order by key.
{
    bool finished = false ;
    int  current = end ;
    bool moreToSearch = ( current != start ) ;
    while ( moreToSearch && !finished )
    {
        if ( values [ current ] < values [ current - 1 ] )
        {
            Swap ( values [ current ], values [ current - 1 ] ) ;
            current-- ;
            moreToSearch = ( current != start ) ;
        }
        else
            finished = true ;
    }
}

```

```
template <class ItemType >
void InsertionSort ( ItemType values [ ], int numValues )
// Post: Sorts array values[0 . . numValues-1 ] into ascending
//       order by key
{
    for ( int count = 1 ; count < numValues ; count++ )

        InsertItem ( values , 0 , count ) ;

}
```

# Insertion Sort

- **Advantages:**
  - **Relatively easy to implement**
  - **Fast when:**
    - ✓ **the data is almost sorted**
    - ✓ **the size of the data is small.**
- **Disadvantages:**
  - **If the data is already sorted in reverse order, each insertion requires a large number of comparisons.**



# Shell Sort

- ♦ **Essentially a segmented insertion sort**
  - **Divides an array into several smaller non-contiguous segments**
  - **The distance between successive elements in one segment is called a “gap”.**
  - **Each segment is sorted within itself using insertion sort.**
  - **Then resegment into larger segments (smaller gaps) and repeat sort.**
  - **Continue until only one segment (gap = 1)**

# Shell Sort

- It works because:
  - It always deals with a small number of elements.
  - Elements are moved a long way through array with each swap and this leaves it more nearly sorted.

# Shell Sort Example

Iteration 1

<b>80</b>	<b>90</b>	<b>50</b>	<b>10</b>	<b>40</b>	<b>31</b>	<b>55</b>	<b>81</b>	<b>9</b>
-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	----------

Gap =  $8/2=4$ . If even number, make it odd by adding 1. Gap=5

<b>80</b>					<b>31</b>			
	<b>90</b>					<b>55</b>		
		<b>50</b>					<b>81</b>	
			<b>10</b>					<b>9</b>
				<b>40</b>				

<b>31</b>					<b>80</b>			
	<b>55</b>					<b>90</b>		
		<b>50</b>					<b>81</b>	
			<b>9</b>					<b>10</b>
				<b>40</b>				

# Shell Sort Example

Iteration 2

31	55	50	9	40	80	90	81	10
----	----	----	---	----	----	----	----	----

Gap =  $5/2+1=3$ .

31			9			90		
	55			40			81	
		50			80			10

9			31			90		
	40			55			81	
		10			50			80

# Shell Sort Example

Iteration 3

9	40	10	31	55	50	90	81	80
---	----	----	----	----	----	----	----	----

Gap =  $3/2=1$ .


9	40	10	31	55	50	90	81	80
---	----	----	----	----	----	----	----	----

9	10	31	40	50	55	80	81	90
---	----	----	----	----	----	----	----	----

# Sorting Algorithms and Average Case Number of Comparisons


## Simple Sorts

- Straight Selection Sort
- Bubble Sort
- Insertion Sort
- Shell Sort



## More Complex Sorts

- Quick Sort
- Merge Sort
- Heap Sort




# Recall that . . .

A heap is a binary tree that satisfies these special **SHAPE** and **ORDER** properties:

- Its shape must be a complete binary tree.
- For each node in the heap, the value stored in that node is greater than or equal to the value in each of its children.


**The largest element  
in a heap is always found in the root node**





# The heap can be stored in an array

	values
[ 0 ]	70
[ 1 ]	60
[ 2 ]	12
[ 3 ]	40
[ 4 ]	30
[ 5 ]	8
[ 6 ]	10




# Heap Sort Approach

**First, make the unsorted array into a heap by satisfying the order property. Then repeat the steps below until there are no more unsorted elements.**


- **Take the root (maximum) element off the heap by swapping it into its correct place in the array at the end of the unsorted elements.**
- **Reheap the remaining unsorted elements.** (This puts the next-largest element into the root position).

# After creating the original heap


	values
[0]	70
[1]	60
[2]	12
[3]	40
[4]	30
[5]	8
[6]	10



# Swap root element into last place in unsorted array




# After swapping root element into its place




# After reheapifying remaining unsorted elements


	values
[ 0 ]	60
[ 1 ]	40
[ 2 ]	12
[ 3 ]	10
[ 4 ]	30
[ 5 ]	8
[ 6 ]	70



# Swap root element into last place in unsorted array




# After swapping root element into its place






# After reheapifying remaining unsorted elements


	values
[ 0 ]	40
[ 1 ]	30
[ 2 ]	12
[ 3 ]	10
[ 4 ]	6
[ 5 ]	60
[ 6 ]	70



# Swap root element into last place in unsorted array




# After swapping root element into its place




# After reheapifying remaining unsorted elements


	values
[ 0 ]	30
[ 1 ]	10
[ 2 ]	12
[ 3 ]	6
[ 4 ]	40
[ 5 ]	60
[ 6 ]	70



# Swap root element into last place in unsorted array




# After swapping root element into its place




# After reheapifying remaining unsorted elements

	values
[0]	12
[1]	10
[2]	6
[3]	30
[4]	40
[5]	60
[6]	70




# Swap root element into last place in unsorted array






# After swapping root element into its place




# After reheapifying remaining unsorted elements

	values
[ 0 ]	10
[ 1 ]	6
[ 2 ]	12
[ 3 ]	30
[ 4 ]	40
[ 5 ]	60
[ 6 ]	70




# Swap root element into last place in unsorted array



# After swapping root element into its place

	values
[ 0 ]	6
[ 1 ]	10
[ 2 ]	12
[ 3 ]	30
[ 4 ]	40
[ 5 ]	60
[ 6 ]	70



**ALL ELEMENTS ARE SORTED**

```

template <class ItemType >
void HeapSort ( ItemType values [ ], int numValues )
// Post: Sorts array values[ 0 .. numValues-1 ] into ascending
//       order by key
{
    int index ;

    // Convert array values[ 0 .. numValues-1 ] into a heap.
    for ( index = numValues/2 - 1 ; index >= 0 ; index-- )
        ReheapDown ( values , index , numValues - 1 ) ;

    // Sort the array.
    for ( index = numValues - 1 ; index >= 1 ; index-- )
    {
        Swap ( values [0] , values [index] );
        ReheapDown ( values , 0 , index - 1 ) ;
    }
}

```

# ReheapDown

```
template< class ItemType >
void ReheapDown ( ItemType values [ ], int root, int bottom )

// Pre: root is the index of a node that may violate the heap
//       order property
// Post: Heap order property is restored between root and bottom
{
    int maxChild ;
    int rightChild ;
    int leftChild ;

    leftChild = root * 2 + 1 ;
    rightChild = root * 2 + 2 ;
```

```
if ( leftChild <= bottom )
```

*// ReheapDown continued*

```
{
```

```
    if ( leftChild == bottom )
```

```
        maxChild = leftChild;
```

```
    else
```

```
    {
```

```
        if ( values [ leftChild ] <= values [ rightChild ] )
```

```
            maxChild = rightChild ;
```

```
        else
```

```
            maxChild = leftChild ;
```

```
    }
```

```
    if ( values [ root ] < values [ maxChild ] )
```

```
    {
```

```
        Swap ( values [ root ] , values [ maxChild ] ) ;
```

```
        ReheapDown ( maxChild, bottom ) ;
```

```
    }
```


```
}
```

```
}
```

# Heap Sort:

## How many comparisons?

In reheap down, an element is compared with its 2 children (and swapped with the larger). But only one element at each level makes this comparison, and a complete binary tree with  $N$  nodes has only  $O(\log_2 N)$  levels.





# Heap Sort of N elements: How many comparisons?


**$(N/2) * O(\log N)$  compares to create original heap**

**$(N-1) * O(\log N)$  compares for the sorting loop**

---

**$= O(N * \log N)$  compares total**

# Using quick sort algorithm



# Before call to function Split

**splitVal = 9**

**GOAL: place splitVal in its proper position with  
all values less than or equal to splitVal on its left  
and all larger values on its right**

<b>9</b>	<b>20</b>	<b>6</b>	<b>18</b>	<b>14</b>	<b>3</b>	<b>60</b>	<b>11</b>
----------	-----------	----------	-----------	-----------	----------	-----------	-----------

**values[first]**


**[last]**

# After call to function Split

**splitVal = 9**

**smaller values  
in left part**

**larger values  
in right part**



values[first]

[last]

**splitVal in correct position**

# After call to function Split

6	3	9	18	14	20	60	11
---	---	---	----	----	----	----	----

3	6	9	11	14	18	20	60
---	---	---	----	----	----	----	----

3	6	9	11	14	18	20	60
---	---	---	----	----	----	----	----

3	6	9	11	14	18	20	60
---	---	---	----	----	----	----	----

## // Recursive quick sort algorithm

```
template <class ItemType >
```

```
void QuickSort ( ItemType values[ ], int first , int last )
```

```
// Pre: first <= last
```

```
// Post: Sorts array values[ first . . last ] into ascending order
```

```
{
```

```
    if ( first < last ) // general case
```

```
    {    int splitPoint ;
```

```
        Split ( values, first, last, splitPoint ) ;
```

```
// values [ first ] . . values[splitPoint - 1 ] <= splitVal
```

```
// values [ splitPoint ] = splitVal
```

```
// values [ splitPoint + 1 ] . . values[ last ] > splitVal
```

```
        QuickSort( values, first, splitPoint - 1 ) ;
```

```
        QuickSort( values, splitPoint + 1, last ) ;
```

```
    }
```

```
};
```

# Quick Sort of N elements: How many comparisons?

- N** For first call, when each of N elements is compared to the split value
- $2 * N/2$**  For the next pair of calls, when N/2 elements in each “half” of the original array are compared to their own split values.
- $4 * N/4$**  For the four calls when N/4 elements in each “quarter” of original array are compared to their own split values.

- .
- .
- .

**HOW MANY SPLITS CAN OCCUR?**

# Quick Sort of N elements: How many splits can occur?

**It depends on the order of the original array elements!**

If each split divides the subarray approximately in half, there will be only  $\log_2 N$  splits, and QuickSort is  $O(N \cdot \log_2 N)$ .

But, if the original array was sorted to begin with, the recursive calls will split up the array into parts of unequal length, with one part empty, and the other part containing all the rest of the array except for split value itself. In this case, there can be as many as  $N-1$  splits, and QuickSort is  $O(N^2)$ .




# Merge Sort Algorithm

**Cut the array in half.**


**Sort the left half.**

**Sort the right half.**

**Merge the two sorted halves into one sorted array.**



# Using Merge Sort Algorithm with $N = 16$



## // Recursive merge sort algorithm

```
template <class ItemType >
void MergeSort ( ItemType values[ ], int first , int last )

// Pre: first <= last
// Post: Array values[ first . . last ] sorted into ascending order.
{
    if ( first < last )                // general case
    {
        int middle = ( first + last ) / 2 ;

        MergeSort ( values, first, middle ) ;

        MergeSort( values, middle + 1, last ) ;

        // now merge two subarrays
        // values [ first . . . middle ] with
        // values [ middle + 1, . . . last ].

        Merge( values, first, middle, middle + 1, last ) ;
    }
}
```

# Merge Sort of N elements: How many comparisons?

The entire array can be subdivided into halves only  $\log_2 N$  times.

Each time it is subdivided, function Merge is called to re-combine the halves. Function Merge uses a temporary array to store the merged elements. Merging is  $O(N)$  because it compares each element in the subarrays.

Copying elements back from the temporary array to the values array is also  $O(N)$ .

**MERGE SORT IS  $O(N \cdot \log_2 N)$ .**

# Sorting Algorithm Comparison

Algorithm Visualization

Algorithm Comparison

# Function `BinarySearch ( )`

- `BinarySearch` takes **sorted** array `info`, and two subscripts, `fromLoc` and `toLoc`, and `item` as arguments. It returns `false` if `item` is not found in the elements `info[fromLoc...toLoc]`. Otherwise, it returns `true`.
- `BinarySearch` is  $O(\log_2 N)$ .

```
found = BinarySearch(info, 25, 0, 14);
```

**item**    **fromLoc**    **toLoc**

**indexes**

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14
---	---	---	---	---	---	---	---	---	---	----	----	----	----	----

**info**

0	2	4	6	8	10	12	14	16	18	20	22	24	26	28
---	---	---	---	---	----	----	----	----	----	----	----	----	----	----

16	18	20	22	24	26	28
----	----	----	----	----	----	----

24	26	28
----	----	----

24
----

**NOTE:**  denotes element examined

```

template<class ItemType>
bool BinarySearch ( ItemType info[ ], ItemType item ,
                  int fromLoc , int toLoc )
    // Pre: info [ fromLoc . . toLoc ] sorted in ascending order
    // Post: Function value = ( item in info [ fromLoc . . toLoc] )
{
    int mid ;
    if ( fromLoc > toLoc )                // base case -- not found
        return false ;
    else {
        mid = ( fromLoc + toLoc ) / 2 ;
        if ( info [ mid ] == item )      // base case-- found at mid
            return true ;
        else if ( item < info [ mid ] )   // search lower half
            return BinarySearch ( info, item, fromLoc, mid-1 ) ;
        else                             // search upper half
            return BinarySearch( info, item, mid + 1, toLoc ) ;
    }
}

```



# Hashing

- is a means used to order and access elements in a list quickly -- the goal is  $O(1)$  time -- by using a function of the key value to identify its location in the list.
- The function of the key value is called a hash function.

**FOR EXAMPLE . . .**

# Using a hash function

	values
[ 0 ]	Empty
[ 1 ]	4501
[ 2 ]	Empty
[ 3 ]	7803
[ 4 ]	Empty
.	.
.	.
.	.
[ 97 ]	Empty
[ 98 ]	2298
[ 99 ]	3699

**HandyParts company makes no more than 100 different parts. But the parts all have four digit numbers.**

**This hash function can be used to store and retrieve parts in an array.**

**$\text{Hash}(\text{key}) = \text{partNum} \% 100$**

# Placing elements in the array

	values
[ 0 ]	Empty
[ 1 ]	4501
[ 2 ]	Empty
[ 3 ]	7803
[ 4 ]	Empty
.	.
.	.
.	.
[ 97 ]	Empty
[ 98 ]	2298
[ 99 ]	3699

Use the hash function

$$\text{Hash}(\text{key}) = \text{partNum} \% 100$$

to place the element with  
part number 5502 in the  
array.

# Placing elements in the array

	values
[ 0 ]	Empty
[ 1 ]	4501
[ 2 ]	5502
[ 3 ]	7803
[ 4 ]	Empty
.	.
.	.
.	.
[ 97 ]	Empty
[ 98 ]	2298
[ 99 ]	3699

Next place part number  
6702 in the array.

$$\text{Hash}(\text{key}) = \text{partNum} \% 100$$

$$6702 \% 100 = 2$$

But values[2] is already  
occupied.

**COLLISION OCCURS**

# How to resolve the collision?

values	
[ 0 ]	Empty
[ 1 ]	4501
[ 2 ]	5502
[ 3 ]	7803
[ 4 ]	Empty
.	.
.	.
.	.
[ 97 ]	Empty
[ 98 ]	2298
[ 99 ]	3699

One way is by linear probing.  
This uses the rehash function

$$(\text{HashValue} + 1) \% 100$$

repeatedly until an empty location  
is found for part number 6702.

# Resolving the collision

	values
[ 0 ]	Empty
[ 1 ]	4501
[ 2 ]	5502
[ 3 ]	7803
[ 4 ]	Empty
.	.
.	.
.	.
[ 97 ]	Empty
[ 98 ]	2298
[ 99 ]	3699

Still looking for a place for 6702  
using the function

$$(\text{HashValue} + 1) \% 100$$

# Collision resolved

values	
[ 0 ]	Empty
[ 1 ]	4501
[ 2 ]	5502
[ 3 ]	7803
[ 4 ]	Empty
.	.
.	.
.	.
[ 97 ]	Empty
[ 98 ]	2298
[ 99 ]	3699

**Part 6702 can be placed at the location with index 4.**

# Collision resolved

values	
[ 0 ]	Empty
[ 1 ]	4501
[ 2 ]	5502
[ 3 ]	7803
[ 4 ]	6702
.	.
.	.
.	.
[ 97 ]	Empty
[ 98 ]	2298
[ 99 ]	3699

**Part 6702 is placed at the location with index 4.**


**Where would the part with number 4598 be placed using linear probing?**



# Radix Sort

## Radix sort

- Is *not* a comparison sort
- Uses a radix-length array of queues of records
- Makes use of the values in digit positions in the keys to select the queue into which a record must be enqueued



# Example of the Radix Sort

- Original Data:  
    {762, 124, 432, 761, 002}
- First Pass(1 digit):  
    { 761, 002, 762, , 432, 124}
- Second Pass(10 digit):  
    {002, 124, 432, 761, 762}
- Third Pass(100 digit) :  
    {002, 124 , 432 , 761, 762}

# Original Array

762
124
432
761
800
402
976
100
001
999

# Queues After First Pass

[0]	[1]	[2]	[3]	[4]	[5]	[6]	[7]	[8]	[9]
800	761	762		124		976			999
100	001	432							
		402							



762
124
432
761
800
402
976
100
001
999

800
100
761
001
762
432
402
124
976
999

# Queues After Second Pass

[0]	[1]	[2]	[3]	[4]	[5]	[6]	[7]	[8]	[9]
800		124	432			761	976		999
100						762			
001									
402									



800
100
761
001
762
432
402
124
976
999



800
100
001
402
124
432
761
762
976
999

# Queues After Third Pass

[0]	[1]	[2]	[3]	[4]	[5]	[6]	[7]	[8]	[9]
001	100			402			761	800	976
	124			432			762		999



800
100
001
402
124
432
761
762
976
999



001
100
124
402
432
761
762
800
976
999

# Array After Third Pass

001
100
124
402
432
761
762
800
976
999