

# Code Quality and Programming Standards

COMSM0086

Dr Simon Lock and Dr Sion Hannuna

# Aim of This Lecture

To try to make you into a better programmer !  
(not just 'coder')

Achieved by considering code quality at two levels:

1. Low-level \*material\* quality of your source code
2. Higher-level \*structural\* quality of the program

# Code Quality

Good code is not just about "correct operation"  
Code may run just fine, but still be BADLY written !

Key questions to ask yourself about your code are:

- How easy is your code for others to understand ?
- How easy is your code for others to change ?
- Does your code support long-term maintenance ?

As a 'coder' you probably don't care about these  
As a 'programmer' you definitely should !

# Example Codebase

Let us consider an example program:


- It runs correctly, without errors
- It is fast and efficient
- It is compact and elegant
- It makes good use of language constructs

Does that sound like high quality code ?

```

#include <stdio.h>
typedef double f;f H=.5,Y=.66,S=-1,I,y=-111;extern"C"{f cos(f),pow(f
,f),atan2(f,f);}struct v{f x,y,z;v(f a=0,f b=0,f c=0):x(a),y(b),z(c)
{}f operator%(v r){return x*r.x+y*r.y+z*r.z;}v operator+(v r){return
v(x+r.x,y+r.y,z+r.z);}v operator*(f s){return v(x*s,y*s,z*s);}W(1,1
,1),P,C,M;f U(f a){return a<0?0:a>1?1:a;}v _(v t){return t*pow(t%t,-
H);}f Q(v c){M=P+c*S;f d=M%M;return d<I?C=c,I=d:0;}f D(v p){I=99;P=p
;f l,u,t;v k;for(const char*b="BCJB@bJBHbJCE[FLL_A[FLMCA[CCTT`T";*b;
++b){k.x+=*b/4&15;int o=*b&3,a=*++b&7;k.y=*b/8&7;v d(o%2*a,o/2*a);!o
?l=a/4%2*-3.14,u=a/2%2*3.14,d=p+k*-H,t=atan2(d.y,d.x),t=t<l?l:t>u?u:
t,Q(k*H+v(cos(t),cos(t-1.57))*(a%2*H+1)):Q(k+d*U((p+k*S)%d/(d%d)));}
return M=Q(v(p.x,-.9,p.z))?(int(p.x+64)^int(p.z+64))/8&1?Y:W:v(Y,Y,1
),pow(I,H)-.45;}v R(v o,v d,f z){for(f u=0,l=1,i=0,a=1;u<97;u+=l=D(o
+d*u))if(l<.01){v p=M,n=_(P+C*S),L=_(v(S,1,2));for(o=o+d*u;++i<6;a-=
U(i/3-D(o+n*i*.3))/pow(2,i));p=p*(U(n%L)*H*Y+Y)*a;p=z?p*Y+R(o+n*.1,d
+n*-2*(d%n),z-1)*H*Y:p;u=pow(U(n%_(L+d*S)),40);return p+p*-u+W*u;}z=
d.z*d.z;return v(z,z,1);} int main(){for(puts("P6 600 220 255");++y<
110;)for(f x=-301;P=R(v(-2,4,25),_(_(v(5,0,2))*++x+_(v(-2,73))*-y+v(
301,-59,-735)),2)*255,x<300;putchar(P.z))putchar(P.x),putchar(P.y);}

```



# Method and Variable Naming

Names we choose greatly impact understandability

How readable is code if the variables are: a, b, c  
(Consider the Ray Tracer code for example !)

There are some general "good name" principles, but  
Everyone has own idea of what makes a good name

Organisations will have own conventions & standards  
Here are the "OOP with Java" naming conventions...

# Naming Conventions

Variable names should describe the data they hold

Method names should describe action they perform

Anything less than 5 chars is probably too short

Anything greater than 20 chars is getting a bit long

Single words are typically not enough to do the job

I favour Verb/Subject pairs as names for methods...



# Examples of Good Method Names

getSurname

setAge

initialiseDataArray

drawNodes

findStringMatches

# Bad Method Names

go

set

calculate

evaluate

enable

# Accepted "Standard" Terms

Sometimes single words `_may_` be acceptable  
IF they are standard terms from the domain  
OR they are self-evident on their own:

`run, draw, clone, delete, multiply, connect, filter`

But why take the risk ?

Does it really hurt to use compound names ?

You can only improve understandability

# Method Complexity

'Divide and Conquer' is an oft touted strategy...  
Split complex code up into simple sub-procedures  
(and sub-sub-procedures)

Avoid massive, hard-to-understand methods  
Particularly with complex loop & decision structures  
These are very hard to understand (and to change)

Big improvements in understandability can be  
achieved by "farming out" code to suitable methods

# Simple "Farming Out" Example

Consider a method to check if two numbers are "close"  
(e.g. 1 and 2 are close, 1 and 8 are not)

A first attempt might look something like this:

(have used "naughty" var names to fit code onto slide)

```
int a = int(random(0, 10));
int b = int(random(0, 10));
System.out.println("Numbers are " + a + " and " + b);
if (((a>b)&&((a-b)<2)) || ((a<b)&&((b-a)<2)) || (a==b)) {
    System.out.println("They are close");
}
else System.out.println("They are NOT close");
```

# A Simpler, Clearer Solution (?)

```
{
    int firstAge = int(random(0, 10));
    int secondAge = int(random(0, 10));
    System.out.println("Ages are " + firstAge + " and " + secondAge);
    if (differenceBetween(firstAge, secondAge) < 2) {
        System.out.println("They are close");
    }
    else System.out.println("They are NOT close");
}

int differenceBetween(int a, int b)
{
    if (a>b) return a-b;
    else return b-a;
}
```

# Minimising Complexity

To minimise complexity, you should try to avoid:

- Very long lines (stretching off side of screen)
- Long methods (stretching off bottom of screen)
- Methods with many parameters (doing too much)
- Deep indentation (many levels of IFs and loops)

Metrics exist to measure control flow complexity

'Cyclomatic Complexity' is one such metric:

[https://en.wikipedia.org/wiki/Cyclomatic\\_complexity](https://en.wikipedia.org/wiki/Cyclomatic_complexity)

# Elegance and Replication

Code should be elegant, versatile and minimal

Nice if we can get one method to do the job of 20 !

(Especially if it is a fraction of the size of those 20)

Achieved by "factoring out" common functionality

Placing that common code in an often-called method

This attitude to programming often referred to as

'DRY' (Don't Repeat Yourself)



# Some "WET" code

```
public void processCommand(String action, Unit unit)
{
    if(action.equals("add")) {
        System.out.println("ID of student to add ?");
        String id = System.in.readLine();
        Student student = cohort.getStudent(id);
        unit.addStudent(student);
    }
    else if(action.equals("remove")) {
        System.out.println("ID of student to remove ?");
        String id = System.in.readLine();
        Student student = cohort.getStudent(id);
        unit.removeStudent(student);
    }
}
```

# DRYer equivalent

```
System.out.println("ID of student to "+ action +" ?");  
String id = System.in.readLine();  
Student student = cohort.getStudent(id);  
if(action.equals("add")) unit.addStudent(student);  
if(action.equals("remove")) unit.removeStudent(student);
```

This seems like a trivial improvement to make  
The question is, why do we still see such WET code !  
(Probably due to lack of time - rather than ability)

# Redundant Code

Whilst we are on the subject of redundant code  
What about code that is never actually used at all ?

Happens from time-to-time during evolutionary dev  
Trying out some ideas in an experimental method  
But never actually calling them from main program

This is fine, but just be careful not to submit it !  
It's easy for checkers to detect this kind of thing ;o)

# Higher Level Structural Considerations

# Structural Cohesion

Classes should be 'cohesive':

"A logical & coherent cluster of data & behaviour"

Our aim is to create classes with a clear purpose

Is

"a tumble dryer...

that also makes coffee"

cohesive ?

# Coupling

Classes should also be distinct and independent  
You should avoid tight coupling between objects



# Cyclic Dependency

It is good to have a clear hierarchy of responsibility


Like management structures in an organisation

Everyone knows who is responsible for what

(when things go wrong we know who to blame ;o)

It is best not to have cyclic loops in these structures

What if your boss was managed by your subordinate !



# Problems with Cyclic Dependencies

Responsibility for features is not clearly defined  
Maintainer has to cycle round the code searching

Often a sign of arbitrary allocation of responsibility  
Developer doesn't have a clear structure in mind  
Implements a feature inside inappropriate class

Cyclic loops are also a type of tight coupling  
(which we have already talked about)




# In case you were wondering...

MVC pattern is NOT an example of cyclic dependency

Dependency is based on the pattern of method calls

The "loop" indicates flow of data, not dependency



# Why is this important ?

You might be wondering why all of this is important  
We are NOT covering these topics "just for interest"

It is important that you adopt professional practices  
We expect you to apply such principles in your work

To encourage you, quality is part of unit assessment  
Marking criteria target ALL the topics covered today

Submit OXO to backboard if you'd like a "trial run"  
Good to get a feel for it (before it actually counts !)