

COMSM1201 : Data Structures & Algorithms

Dr. Neill Campbell
Neill.Campbell@bristol.ac.uk

University of Bristol

November 15, 2021



Table of Contents

N : Recursion

O : Algorithms I - Search

P : Linked Data Structures

Q : ADTs - Collection

R : ADTs - Stacks

S : ADTs - Queues

T : ADTs - Trees

Simple Recursion

- When a function calls itself, this is known as recursion.
- This is an important theme in Computer Science that crops up time & time again.
- Can sometimes lead to very simple and elegant programs.
- Let's look at some toy examples to begin with.

```
1  #include <stdio.h>
2  #include <string.h>
3
4  #define SWAP(A,B) {char temp; temp=A;A=B;B=temp;}
5
6  void strrev(char* s, int n);
7
8  int main(void)
9  {
10     char str[] = "Hello World!";
11     strrev(str, strlen(str));
12     printf("%s\n", str);
13     return 0;
14 }
15
16 /* Iterative Inplace String Reverse */
17 void strrev(char* s, int n)
18 {
19     for(int i=0, j=n-1; i<j; i++, j--){
20         SWAP(s[i], s[j]);
21     }
22 }
```

Execution :

!dlroW olleH

Recursion for *strrev()*

```
1  #include <stdio.h>
2  #include <string.h>
3
4  #define SWAP(A,B) {char temp; temp=A;A=B;B=temp;}
5
6  void strrev(char* s, int start, int end);
7
8  int main(void)
9  {
10     char str[] = "Hello World!";
11     strrev(str, 0, strlen(str)-1);
12     printf("%s\n", str);
13     return 0;
14 }
15
16 /* Recursive : Inplace String Reverse */
17 void strrev(char* s, int start, int end)
18 {
19     if(start >= end){
20         return;
21     }
22     SWAP(s[start], s[end]);
23     strrev(s, start+1, end-1);
24 }
```

Execution :

!dlroW olleH

- We need to change the function prototype.
- This allows us to track both the start and the end of the string.

The Fibonacci Sequence

A well known example of a recursive function is the Fibonacci sequence. The first term is 1, the second term is 1 and each successive term is defined to be the sum of the two previous terms, i.e. :

$\text{fib}(1)$ is 1

$\text{fib}(2)$ is 1

$\text{fib}(n)$ is $\text{fib}(n-1) + \text{fib}(n-2)$

1, 1, 2, 3, 5, 8, 13, 21, ...

Iterative & Recursive Fibonacci

```
1  #include <stdio.h>
2
3  #define MAXFIB 24
4
5  int fibonacci(int n);
6
7  int main(void)
8  {
9
10     for(int i=1; i<=MAXFIB; i++){
11         printf("%d = %d\n", i, fibonacci(i));
12     }
13
14     return 0;
15 }
16
17 int fibonacci(int n)
18 {
19     if(n <= 2){
20         return 1;
21     }
22     int a = 1;
23     int b = 1;
24     int next;
25     for(int i=3; i<=n; i++){
26         next = a + b;
27         a = b;
28         b = next;
29     }
30     return b;
31 }
32 }
```


Execution :

```
1 = 1
2 = 1
3 = 2
4 = 3
5 = 5
6 = 8
7 = 13
8 = 21
9 = 34
10 = 55
11 = 89
12 = 144
13 = 233
14 = 377
15 = 610
16 = 987
17 = 1597
18 = 2584
19 = 4181
20 = 6765
21 = 10946
22 = 17711
23 = 28657
24 = 46368
```

Iterative & Recursive Fibonacci


```
1  #include <stdio.h>
2
3  #define MAXFIB 24
4
5  int fibonacci(int n);
6
7  int main(void)
8  {
9
10     for(int i=1; i<=MAXFIB; i++){
11         printf("%d = %d\n", i, fibonacci(i));
12     }
13
14     return 0;
15 }
16
17
18 int fibonacci(int n)
19 {
20     if(n == 1) return 1;
21     if(n == 2) return 1;
22     return( fibonacci(n-1)+fibonacci(n-2));
23 }
```

It's interesting to see how run-time increases as the length of the sequence is raised.



Maze Escape

The correct route through a maze can be obtained via recursive, rather than iterative, methods.



```
bool explore(int x, int y, char mz[YS][XS])
{
    if mz[y][x] is exit return true;

    Mark mz[y][x] so we don't return here

    if we can go up :
        if(explore(x, y+1, mz)) return true

    if we can go right :
        if(explore(x+1, y, mz)) return true

    Do left & down in a similar manner

    return false; // Failed to find route
}
```


Permuting

- Here we consider the ways to permute a string (or more generally an array)
- Permutations are all possible ways of rearranging the positions of the characters.

Execution :

ABC
ACB
BAC
BCA
CBA
CAB

```
1 // From e.g. http://www.geeksforgeeks.org
2 #include <stdio.h>
3 #include <string.h>
4
5 #define SWAP(A,B) {char temp = *A; *A = *B; *B = temp;}
6
7 void permute(char* a, int s, int e);
8
9 int main()
10 {
11     char str[] = "ABC";
12     int n = strlen(str);
13     permute(str, 0, n-1);
14     return 0;
15 }
16
17 void permute(char* a, int s, int e)
18 {
19     if (s == e){
20         printf("%s\n", a);
21         return;
22     }
23     for (int i = s; i <= e; i++){
24         SWAP((a+s), (a+i)); // Bring one char to the front
25         permute(a, s+1, e);
26         SWAP((a+s), (a+i)); // Backtrack
27     }
28 }
```

Self-test : Power

- Raising a number to a power $n = 2^5$ is the same as multiple multiplications
 $n = 2*2*2*2*2$.
- Or, thinking recursively, $n = 2 * (2^4)$.

```
1  /* Try to write power(a,b) to computer a^b
2  without using any maths functions other than
3  multiplication :
4  Try (1) iterative then (2) recursive
5  (3) Trick that for  $n\%2==0$ ,  $x^n = x^{(n/2)} * x^{(n/2)}$ 
6
7  */
8
9  #include <stdio.h>
10
11 int power(unsigned int a, unsigned int b);
12
13 int main(void)
14 {
15
16     int x = 2;
17     int y = 16;
18
19     printf("%d^%d = %d\n", x, y, power(x,y));
20
21 }
22
23 int power(unsigned int a, unsigned int b)
24 {
25 }
```

Table of Contents

N : Recursion

O : Algorithms I - Search

P : Linked Data Structures

Q : ADTs - Collection

R : ADTs - Stacks

S : ADTs - Queues

T : ADTs - Trees

Sequential Search

- The need to search an array for a particular value is a common problem.
- This is used to delete names from a mailing list, or upgrading the salary of an employee etc.
- The simplest method for searching is called the sequential search.
- Simply move through the array from beginning to end, stopping when you have found the value you require.

```
1  #include <stdio.h>
2  #include <string.h>
3  #include <assert.h>
4
5  #define NOTFOUND -1
6  #define NUMPEOPLE 6
7  typedef struct person{
8      char* name; int age;
9  } person;
10
11 int findAge(const char* name, const person* p, int n);
12
13 int main(void)
14 {
15     person ppl[NUMPEOPLE] = { {"Ackerby", 21}, {"Bloggs", 25},
16                                {"Chumley", 26}, {"Dalton", 25},
17                                {"Eggson", 22}, {"Fulton", 41} };
18
19     assert(findAge("Eggson", ppl, NUMPEOPLE)==22);
20     assert(findAge("Campbell", ppl, NUMPEOPLE)==NOTFOUND);
21     return 0;
22 }
23
24 int findAge(const char* name, const person* p, int n)
25 {
26     for(int j=0; j<n; j++){
27         if(strcmp(name, p[j].name) == 0){
28             return p[j].age;
29         }
30     }
31     return NOTFOUND;
32 }
```

Sequential Search

- Sometimes our list of people may not be random.
- If, for instance, it is sorted, we can use `strcmp()` in a slightly cleverer manner.
- We can stop searching once the search key is alphabetically greater than the item at the current position in the list.
- This halves, on average, the number of comparisons required.

```
1  #include <stdio.h>
2  #include <string.h>
3  #include <assert.h>
4
5  #define NOTFOUND -1
6  #define NUMPEOPLE 6
7  typedef struct person{
8      char* name; int age;
9  } person;
10
11 int findAge(const char* name, const person* p, int n);
12
13 int main(void)
14 {
15     person ppl[NUMPEOPLE] = { {"Ackerby", 21}, {"Bloggs", 25},
16                               {"Chumley", 26}, {"Dalton", 25},
17                               {"Eggson", 22}, {"Fulton", 41} };
18
19     assert(findAge("Eggson", ppl, NUMPEOPLE)==22);
20     assert(findAge("Campbell", ppl, NUMPEOPLE)==NOTFOUND);
21     return 0;
22 }
23
24 int findAge(const char* name, const person* p, int n)
25 {
26     for(int j=0; j<n; j++){
27         int m = strcmp(name, p[j].name);
28         if(m == 0) // Braces!
29             return p[j].age;
30         if(m < 0)
31             return NOTFOUND;
32     }
33     return NOTFOUND;
34 }
```

Binary Search for 101

- Searching small lists doesn't require much computation time.
- However, as lists get longer (e.g. phone directories), sequential searching becomes extremely inefficient.
- A binary search consists of examining the middle element of the array to see if it has the desired value. If not, then half the array may be discarded for the next search.

4	7	19	25	36	37	50	100	101	205	220	270	301	321
↑						↑							↑
							↑			↑			↑
								↑					
									↑				

```
1  #include <stdio.h>
2  #include <stdlib.h>
3  #include <assert.h>
4  #include <time.h>
5  #define NMBS 1000000
6
7  int bin_it(int k, const int* a, int l, int r);
8
9  int main(void)
10 {
11     int a[NMBS];
12     srand(time(NULL));
13
14     // Put even numbers into array
15     for(int i=0; i<NMBS; i++){
16         a[i] = 2*i;
17     }
18
19     // Do many searches for a random number
20     for(int i=0; i<10*NMBS; i++){
21         int n = rand()%NMBS;
22         if((n%2) == 0){
23             assert(bin_it(n, a, 0, NMBS-1) == n/2);
24         }
25         else{ // No odd numbers in this list
26             assert(bin_it(n, a, 0, NMBS-1) < 0);
27         }
28     }
29     return 0;
30 }
```

Iterative v. Recursion Binary Search

```
int bin_it(int k, const int* a, int l, int r)
{
    while(l <= r){
        int m = (l+r)/2;
        if(k == a[m]){
            return m;
        }
        else{
            if (k > a[m]){
                l = m + 1;
            }
            else{
                r = m - 1;
            }
        }
    }
    return -1;
}
```

```
int bin_rec(int k, const int* a, int l, int r)
{
    if(l > r) return -1;
    int m = (l+r)/2;
    if(k == a[m]){
        return m;
    }
    else{
        if (k > a[m]){
            return bin_rec(k, a, m+1, r);
        }
        else{
            return bin_rec(k, a, l, m-1);
        }
    }
}
```

Interpolation Search

- When we look for a word in a dictionary, we don't start in the middle. We make an educated guess as to where to start based on the 1st letter of the word being searched for.
- This idea led to the interpolation search.
- In binary searching, we simply used the middle of an ordered list as a best guess as to where to begin the search.
- Now we use an interpolation involving the key, the start of the list and the end.

$$i = (k - l[0]) / (l[n - 1] - l[0]) * n$$

- when searching for '15' :

0 4 5 9 10 12 15 20
 ↑↑

```
int interp(int k, const int* a, int l, int r)
{
    int m;
    double md;

    while(l <= r){
        md = ((double)(k-a[l])/
              (double)(a[r]-a[l]))*
              (double)(r-l)
              )
            +(double)(l);
        m = 0.5 + md;
        if((m > r) || (m < l)){
            return -1;
        }
        if(k == a[m])
            return m;
        else{
            if (k > a[m]){
                l = m + 1;
            }
            else{
                r = m- 1;
            }
        }
    }
}
```


Algorithmic Complexity

```
1  #include <stdio.h>
2  #include <stdlib.h>
3  #include <time.h>
4
5  #define CSEC (double)(CLOCKS_PER_SEC)
6  #define BIGLOOP 1000000000
7
8  int main(void)
9  {
10
11     clock_t c1 = clock();
12     for(int i=0; i<BIGLOOP; i++){
13         int j = i * 2;
14     }
15     clock_t c2 = clock();
16     printf("%f\n", (double)(c2-c1)/CSEC);
17     return 0;
18 }
19 }
```

- This code on an old Dell laptop took:
 - 3.12 seconds using a non-optimizing compiler -O0
 - 0.00 seconds using an aggressive optimization -O3
- But "wall-clock" time is generally not the thing that excites Computer Scientists.

- Searching and sorting algorithms have a complexity associated with them, called big-O.
- This complexity indicates how, for n numbers, performance deteriorates when n changes.
- Sequential Search : **$O(n)$**
- Binary Search : **$O(\log n)$**
- Interpolation Search : **$O(\log \log n)$**
- We'll discuss the dream of a **$O(1)$** search later in "Hashing".

Binary vs. Interpolation Timing

```
1  #include <stdio.h>
2  #include <stdlib.h>
3  #include <assert.h>
4  #include <time.h>
5
6  int bin_it(int k, const int *a, int l, int r);
7  int bin_rec(int k, const int *a, int l, int r);
8  int interp(int k, const int *a, int l, int r);
9  int* parse_args(int argc, char* argv[], int* n, int* srch);
10
11 int main(int argc, char* argv[])
12 {
13
14     int i, n, srch;
15     int* a;
16     int (*p[3])(int k, const int*a, int l, int r) =
17         {bin_it, bin_rec, interp};
18
19     a = parse_args(argc, argv, &n, &srch);
20
21     srand(time(NULL));
22     for(i=0; i<n; i++){
23         a[i] = 2*i;
24     }
25     for(i=0; i<5000000; i++){
26         assert((*p[srch])(a[rand()%n], a, 0, n-1) >= 0);
27     }
28
29     free(a);
30     return 0;
31 }
32 }
```

Execution :

Binary Search : Iterative

n = 100000 = 0.57

n = 800000 = 0.84

n = 6400000 = 2.20

n = 51200000 = 3.87

Binary Search : Recursive

n = 100000 = 1.23

n = 800000 = 1.79

n = 6400000 = 3.20

n = 51200000 = 4.85

Interpolation

n = 100000 = 0.20

n = 800000 = 0.28

n = 6400000 = 0.50

n = 51200000 = 0.70

Table of Contents

N : Recursion

O : Algorithms I - Search

P : Linked Data Structures

Q : ADTs - Collection

R : ADTs - Stacks

S : ADTs - Queues

T : ADTs - Trees

Linked Data Structures

- Linked data representations are useful when:
 - It is difficult to predict the size and the shape of the data structures in advance.
 - We need to efficiently insert and delete elements.
- To create linked data representations we use pointers to connect separate blocks of storage together. If a given block contains a pointer to a second block, we can follow this pointer there.
- By following pointers one after another, we can travel right along the structure.

```
1  #include <stdio.h>
2  #include <stdlib.h>
3  #include "general.h"
4
5  typedef struct data{
6      int i;
7      struct data* next;
8  } Data;
9
10 Data* allocateData(int i);
11 void printList(Data* l);
12
13 int main(void)
14 {
15     int i;
16     Data* start, *current;
17     start = current = NULL;
18     printf("Enter the first number: ");
19     if(scanf("%i", &i) == 1){
20         start = current = allocateData(i);
21     }
22     else{
23         on_error("Couldn't read an int");
24     }
25
26     printf("Enter more numbers: ");
27     while(scanf("%i", &i) == 1){
28         current->next = allocateData(i);
29         current = current->next;
30     }
31     printList(start);
32     // Should Free List
33     return 0;
34 }
```

Linked Lists

```
Data* allocateData(int i)
{
    Data* p;
    p = (Data*) calloc(1, sizeof(Data));
    p->i = i;
    // Not really required
    p->next = NULL;
    return p;
}

void printList(Data* l)
{
    printf("\n");
    do{
        printf("Number : %i\n", l->i);
        l = l->next;
    }while(l != NULL);
    printf("END\n");
}
```

Searching and Recursive printing:

```
Data* inList(Data* n, int i)
{
    do{
        if(n->i==i){
            return n;
        }
        n = n->next;
    }while(n != NULL);
    return NULL;
}

void printList_r(Data* l)
{
    // Recursive Base-Case
    if(l == NULL) return;

    printf("Number: %i\n", l->i);
    printList_r(l->next);
}
```

Abstract Data Types

- But would we really code something like this **every** time we need flexible data storage ?
- This would be horribly error-prone.
- Build something once, and test it well.
- One example of this is an **Abstract Data Type (ADT)**.
- Each ADT exposes its functionality via an *interface*.
- The user only accesses the data via this interface.
- The user of the ADT doesn't need to understand how the data is being stored (e.g. array vs. linked lists etc.)

Table of Contents

N : Recursion

O : Algorithms I - Search

P : Linked Data Structures

Q : ADTs - Collection

R : ADTs - Stacks

S : ADTs - Queues

T : ADTs - Trees

Collections

- One of the simplest ADTs is the **Collection**.
- This is just a simple place to search for/add/delete data elements.
- Some collections allow duplicate elements and others do not (e.g. Sets).
- Some are ordered (for faster searching) and others unordered.
- Our Collection will be unsorted and will allow duplicates.

```
1  #include "../General/general.h"
2
3  typedef int colltype;
4
5  typedef struct coll coll;
6
7  #include <stdio.h>
8  #include <stdlib.h>
9  #include <assert.h>
10
11 // Create an empty coll
12 coll* coll_init(void);
13 // Add element onto top
14 void coll_add(coll* c, colltype i);
15 // Take element out
16 bool coll_remove(coll* c, colltype d);
17 // Does this exist ?
18 bool coll_isin(coll* c, colltype i);
19 // Return size of coll
20 int coll_size(coll* c);
21 // Clears all space used
22 bool coll_free(coll* c);
```


Collection ADT

- Note that the interface gives you no hints as to the actual underlying implementation of the ADT.
- A user of the ADT doesn't really need to know how it's implemented - ideally.
- The ADT developer could have several **different** implementations.
- Here we'll see *Collection* implemented using:
 - A fixed-size array
 - A dynamic array
 - A linked-list

Fixed/specific.h:

```
1  #pragma once
2
3  #define COLTYPE "Fixed"
4
5  #define FIXESIZE 5000
6  struct coll {
7      // Underlying array
8      colltype a[FIXESIZE];
9      int size;
10 };
```

Collection ADT using a Fixed-size Array

Fixed/fixed.c:

```
1  #include "../coll.h"
2  #include "specific.h"
3
4  coll* coll_init(void)
5  {
6      coll* c = (coll*) nalloc(sizeof(coll), 1);
7      c->size = 0;
8      return c;
9  }
10
11 int coll_size(coll* c)
12 {
13     if(c==NULL){
14         return 0;
15     }
16     return c->size;
17 }
18
19 bool coll_isin(coll* c, colltype d)
20 {
21     for(int i=0; i<coll_size(c); i++){
22         if(c->a[i] == d){
23             return true;
24         }
25     }
26     return false;
27 }
```

```
void coll_add(coll* c, colltype d)
{
    if(c){
        if(c->size >= FIXEDSIZE){
            on_error("Collection overflow");
        }
        c->a[c->size] = d;
        c->size = c->size + 1;
    }
}

bool coll_remove(coll* c, colltype d)
{
    for(int i=0; i<coll_size(c); i++){
        if(c->a[i] == d){
            // Shuffle end of array left one
            for(int j=i; j<coll_size(c); j++){
                c->a[j] = c->a[j+1];
            }
            c->size = c->size - 1;
            return true;
        }
    }
    return false;
}

bool coll_free(coll* c)
{
    free(c);
    return true;
}
```

Collection ADT via an Array (Realloc)

Realloc/specific.h:

```
1  #pragma once
2
3  #define COLLTTYPE "Realloc"
4
5  #define FIXEDSIZE 16
6  #define SCALEFACTOR 2
7  struct coll {
8      // Underlying array
9      colltype* a;
10     int size;
11     int capacity;
12 };
```

Realloc/realloc.c:

```
1  #include "../coll.h"
2  #include "specific.h"
3
4  coll* coll_init(void)
5  {
6      coll* c = (coll*) ncalloc(sizeof(coll), 1);
7      c->a = (colltype*) ncalloc(sizeof(colltype), FIXEDSIZE);
8      c->size = 0;
9      c->capacity = FIXEDSIZE;
10     return c;
11 }
12
13 void coll_add(coll* c, colltype d)
14 {
15     if(c){
16         if(c->size >= c->capacity){
17             c->a = (colltype*) nrealloc(c->a,
18                 sizeof(colltype)*c->capacity*SCALEFACTOR);
19             c->capacity = c->capacity*SCALEFACTOR;
20         }
21         c->a[c->size] = d;
22         c->size = c->size + 1;
23     }
```

Collection ADT via a Linked List

Linked/specific.h:

```
1  #pragma once
2
3  #define COLLYTYPE "Linked"
4
5  struct dataframe {
6      colltype i;
7      struct dataframe* next;
8  };
9  typedef struct dataframe dataframe;
10
11 struct coll {
12     // Underlying array
13     dataframe* start;
14     int size;
15 };
```

Linked/linked.c:

```
#include "../coll.h"
#include "specific.h"

coll* coll_init(void)
{
    coll* c = (coll*) nalloc(sizeof(coll), 1);
    return c;
}

int coll_size(coll* c)
{
    if(c==NULL){
        return 0;
    }
    return c->size;
}

bool coll_isin(coll* c, colltype d)
{
    if(c == NULL || c->start==NULL){
        return false;
    }
    dataframe* f = c->start;
    do{
        if(f->i == d){
            return true;
        }
        f = f->next;
    }while(f != NULL);
    return false;
}
```

Collection ADT via a Linked List II

```
void coll_add(coll* c, colltype d)
{
    if(c){
        dataframe* f = nalloc(sizeof(dataframe), 1);
        f->i = d;
        f->next = c->start;
        c->start = f;
        c->size = c->size + 1;
    }
}

bool coll_free(coll* c)
{
    if(c){
        dataframe* tmp;
        dataframe* p = c->start;
        while(p!=NULL){
            tmp = p->next;
            free(p);
            p = tmp;
        }
        free(c);
    }
    return true;
}
```

```
bool coll_remove(coll* c, colltype d)
{
    dataframe* f1, *f2;
    if((c==NULL) || (c->start==NULL)){
        return false;
    }

    // If Front
    if(c->start->i == d){
        f1 = c->start->next;
        free(c->start);
        c->start = f1;
        c->size = c->size - 1;
        return true;
    }

    f1 = c->start;
    f2 = c->start->next;
    do{
        if(f2->i == d){
            f1->next = f2->next;
            free(f2);
            c->size = c->size - 1;
            return true;
        }
        f1 = f2;
        f2 = f1->next;
    }while(f2 != NULL);
    return false;
}
```

Collection Summary

- Any code using the ADT can be compiled against any of the implementations, e.g. the test (testcoll.c) code.
- The *Collection* interface (coll.h) is never changed.
- There are pros and cons of each implementation:
 - Fixed Array : Simple to implement - can't avoid the problems of it being a fixed-size. Deletion expensive.
 - Realloc Array : Implementation fairly simple. Deletion expensive. Every realloc() is very **expensive**. Need to tune SCALEFACTOR.
 - Linked : Slightly fiddly implementation - fast to delete an element.

Task	Fixed Array	Realloc Array	Linked List
Insert new element	$O(1)$ at end <i>if space</i>	$O(1)$ at end <i>but realloc()</i>	$O(1)$ at front
Search for an element	$O(n)$ <i>brute force</i>	$O(n)$ <i>brute force</i>	$O(n)$ <i>brute force</i>
Search + delete	$O(n) + O(n)$ <i>move left</i>	$O(n) + O(n)$ <i>move left</i>	$O(n) + O(1)$ <i>delete 'free'</i>

- If we had ordered our ADT (ie. the elements were sorted), then the searches could be via a binary / interpolation search, leading to $O(\log n)$ or $O(\log \log n)$ search times.

ADTs Making Coding Simpler

That Linked List code from the previous Chapter again:

```
1  #include "coll.h"
2  #include "Fixed/specific.h"
3
4  int main(void)
5  {
6      coll* c;
7      int i;
8
9      printf("Please type some numbers :");
10     c = coll_init();
11     while(scanf("%i", &i) == 1){
12         coll_add(c, i);
13     }
14     // Do print etc.
15     coll_free(c);
16     return 0;
17 }
```

Table of Contents

N : Recursion

O : Algorithms I - Search

P : Linked Data Structures

Q : ADTs - Collection

R : ADTs - Stacks


S : ADTs - Queues

T : ADTs - Trees


At the highest level of abstraction, ADTs that we can represent using both dynamic structures (pointers) and also fixed structures (arrays) include:

- Collections (Lists)
- Stacks
- Queues
- Sets
- Graphs
- Trees


Binary Trees:




Unidirectional Graph:



The push-down stack:



LIFO (Last in, First out):



- Operations include push and pop.
- In the C run-time system, function calls are implemented using stacks.
- Most recursive algorithms can be re-written using stacks instead.
- But, once again, we are faced with the question : How best to implement such a data type ?

ADT:Stacks Arrays (Realloc) I

stack.h:

```
1  #pragma once
2
3  #include "../General/general.h"
4
5  typedef int stacktype;
6
7  typedef struct stack stack;
8
9  #include <stdio.h>
10 #include <stdlib.h>
11 #include <assert.h>
12 #include <string.h>
13
14 /* Create an empty stack */
15 stack* stack_init(void);
16 /* Add element to top */
17 void stack_push(stack* s, stacktype i);
18 /* Take element from top */
19 bool stack_pop(stack* s, stacktype* d);
20 /* Clears all space used */
21 bool stack_free(stack* s);
22
23 /* Optional? */
24
25 /* Copy top element into d (but don't pop it) */
26 bool stack_peek(stack* s, stacktype* d);
27 /* Make a string version - keep .dot in mind */
28 void stack_tostring(stack* s, char* str);
```

Realloc/specific.h:

```
1  #pragma once
2
3  #define FORMATSTR "%i"
4  #define ELEMSIZE 20
5
6  #define STACKTYPE "Realloc"
7
8  #define FIXEDSIZE 16
9  #define SCALEFACTOR 2
10
11 struct stack {
12     /* Underlying array */
13     stacktype* a;
14     int size;
15     int capacity;
16 };
```

ADT:Stacks Arrays (Realloc) II

Realloc/realloc.c

```
1  #include "../stack.h"
2  #include "specific.h"
3
4  #define DOTFILE 5000
5
6  stack* stack_init(void)
7  {
8      stack *s = (stack*) ncalloc(sizeof(stack), 1);
9      /* Some implementations would allow you to pass
10       a hint about the initial size of the stack */
11      s->a = (stacktype*) ncalloc(sizeof(stacktype), FIXESIZE);
12      s->size = 0;
13      s->capacity = FIXESIZE;
14      return s;
15  }
16
17  void stack_push(stack* s, stacktype d)
18  {
19      if(s==NULL){
20          return;
21      }
22      if(s->size >= s->capacity){
23          s->a = (stacktype*) nrealloc(s->a,
24                                     sizeof(stacktype)*s->capacity*SCALEFACTOR);
25          s->capacity = s->capacity*SCALEFACTOR;
26      }
27      s->a[s->size] = d;
28      s->size = s->size + 1;
29  }
```

```
1  bool stack_pop(stack* s, stacktype* d)
2  {
3      if((s == NULL) || (s->size < 1)){
4          return false;
5      }
6      s->size = s->size - 1;
7      *d = s->a[s->size];
8      return true;
9  }
10
11  bool stack_peek(stack* s, stacktype* d)
12  {
13      if((s==NULL) || (s->size <= 0)){
14          /* Stack is Empty */
15          return false;
16      }
17      *d = s->a[s->size - 1];
18      return true;
19  }
```

ADT:Stacks Arrays (Realloc) III

Realloc/realloc.c

```
1 void stack_tostring(stack* s, char* str)
2 {
3     char tmp[ELEMSIZE];
4     str[0] = '\0';
5     if((s==NULL) || (s->size <1)){
6         return;
7     }
8     for(int i=s->size-1; i>=0; i--){
9         sprintf(tmp, FORMATSTR, s->a[i]);
10        strcat(str, tmp);
11        strcat(str, "|");
12    }
13    str[strlen(str)-1] = '\0';
14 }
15
16 bool stack_free(stack* s)
17 {
18     if(s==NULL){
19         return true;
20     }
21     free(s->a);
22     free(s);
23     return true;
24 }
```

- We need a thorough testing program teststack.c
- See also revstr.c : a version of the string reverse code (for which we already seen an iterative (in-place) and a recursive solution).

ADT:Stacks Linked I

Linked/specific.h

```
1  #pragma once
2
3  #define FORMATSTR "%i"
4  #define ELEMSIZE 20
5  #define STACKTYPE "Linked"
6
7  struct dataframe {
8      stacktype i;
9      struct dataframe* next;
10 };
11 typedef struct dataframe dataframe;
12
13 struct stack {
14     /* Underlying array */
15     dataframe* start;
16     int size;
17 };
```

Linked/linked.c

```
1  #include "../stack.h"
2  #include "specific.h"
3
4  #define DOTFILE 5000
5
6  stack* stack_init(void)
7  {
8      stack* s = (stack*) nalloc(sizeof(stack), 1);
9      return s;
10 }
11
12 void stack_push(stack* s, stacktype d)
13 {
14     if(s){
15         dataframe* f = nalloc(sizeof(dataframe), 1);
16         f->i = d;
17         f->next = s->start;
18         s->start = f;
19         s->size = s->size + 1;
20     }
21 }
```

ADT:Stacks Linked II

```
1  bool stack_pop(stack* s, stacktype* d)
2  {
3      if((s==NULL) || (s->start==NULL)){
4          return false;
5      }
6
7      dataframe* f = s->start->next;
8      *d = s->start->i;
9      free(s->start);
10     s->start = f;
11     s->size = s->size - 1;
12     return true;
13 }
14
15 bool stack_peek(stack* s, stacktype* d)
16 {
17     if((s==NULL) || (s->start==NULL)){
18         return false;
19     }
20     *d = s->start->i;
21     return true;
22 }
```

```
1  void stack_tostring(stack* s, char* str)
2  {
3      char tmp[ELEMSIZE];
4      str[0] = '\0';
5      if((s==NULL) || (s->size < 1)){
6          return;
7      }
8      dataframe* p = s->start;
9      while(p){
10         sprintf(tmp, FORMATSIR, p->i);
11         strcat(str, tmp);
12         strcat(str, "|");
13         p = p->next;
14     }
15     str[strlen(str)-1] = '\0';
16 }
17
18 bool stack_free(stack* s)
19 {
20     if(s){
21         dataframe* p = s->start;
22         while(p!=NULL){
23             dataframe* tmp = p->next;
24             free(p);
25             p = tmp;
26         }
27         free(s);
28     }
29     return true;
30 }
```

Table of Contents

N : Recursion

O : Algorithms I - Search

P : Linked Data Structures

Q : ADTs - Collection

R : ADTs - Stacks

S : ADTs - Queues

T : ADTs - Trees

ADTs : Queues

FIFO (First in, First out):



- Intuitively more “useful” than a stack.
- Think of implementing any kind of service (printer, web etc.)
- Operations include enqueue, dequeue and size.


queue.h

```
1  #pragma once
2
3  #include "../General/general.h"
4
5  typedef int queue_t;
6
7  typedef struct queue queue;
8
9  #include <stdio.h>
10 #include <stdlib.h>
11 #include <string.h>
12 #include <assert.h>
13
14 /* Create an empty queue */
15 queue* queue_init(void);
16 /* Add element on end */
17 void queue_enqueue(queue* q, queue_t v);
18 /* Take element off front */
19 bool queue_dequeue(queue* q, queue_t* d);
20 /* Return size of queue */
21 int queue_size(queue* q);
22 /* Clears all space used */
23 bool queue_free(queue* q);
24
25 /* Helps with visualisation & testing */
26 void queue_tostring(queue* q, char* str);
```

ADTs : Queues (Fixed) I

specific.h

```
1  #pragma once
2
3  #define FORMATSTR "%d"
4  #define ELEMSIZE 20
5
6  #define QUEUETYPE "Fixed"
7
8  #define BOUNDED 5000
9
10 struct queue {
11     /* Underlying array */
12     queuetype a[BOUNDED];
13     int front;
14     int end;
15 };
16
17 #define DOTFILE 5000
```



ADTs : Queues (Fixed) II

fixed.c

```
1  #include "../queue.h"
2  #include "specific.h"
3
4  void __inc(queuetype* p);
5
6  queue* queue_init(void)
7  {
8      queue* q = (queue*) nalloc(sizeof(queue), 1);
9      return q;
10 }
11
12
13 void queue_enqueue(queue* q, queuetype d)
14 {
15     if(q){
16         q->a[q->end] = d;
17         __inc(&q->end);
18         if(q->end == q->front){
19             on_error("Queue too large");
20         }
21     }
22 }
```

```
1  bool queue_dequeue(queue* q, queuetype* d)
2  {
3      if((q==NULL) || (q->front==q->end)){
4          return false;
5      }
6      *d = q->a[q->front];
7      __inc(&q->front);
8      return true;
9  }
10
11 void queue_tostring(queue* q, char* str)
12 {
13     char tmp[ELEMSIZE];
14     str[0] = '\0';
15     if((q==NULL) || (queue_size(q)==0)){
16         return;
17     }
18     for(int i=q->front; i != q->end;){
19         sprintf(tmp, FORMATSTR, q->a[i]);
20         strcat(str, tmp);
21         strcat(str, "|");
22         __inc(&i);
23     }
24     str[strlen(str)-1] = '\0';
25 }
```

ADTs : Queues (Fixed) III

```
1  int queue_size(queue* q)
2  {
3      if(q==NULL){
4          return 0;
5      }
6      if(q->end >= q->front){
7          return q->end - q->front;
8      }
9      return q->end + BOUNDED - q->front;
10 }
11
12 bool queue_free(queue* q)
13 {
14     free(q);
15     return true;
16 }
17
18 void __inc(queuetype* p)
19 {
20     *p = (*p + 1) % BOUNDED;
21 }
```

- We need a thorough testing program
- We'll see queues again for traversing trees
- Simulating a (slow) printer

ADTs : Queues (Linked) I

specific.h

```
1  #pragma once
2
3  #define FORMATSTR "%d"
4  #define ELEMSIZE 20
5
6  #define QUEUETYPE "Linked"
7
8  struct dataframe {
9      queuetype i;
10     struct dataframe* next;
11 };
12 typedef struct dataframe dataframe;
13
14 struct queue {
15     /* Underlying array */
16     dataframe* front;
17     dataframe* end;
18     int size;
19 };
```

linked.c

```
1  #include "../queue.h"
2  #include "specific.h"
3
4  queue* queue_init(void)
5  {
6      queue* q = (queue*) nalloc(sizeof(queue), 1);
7      return q;
8  }
9
10 void queue_enqueue(queue* q, queuetype d)
11 {
12     dataframe* f;
13     if(q == NULL){
14         return;
15     }
16
17     /* Copy the data */
18     f = nalloc(sizeof(dataframe), 1);
19     f->i = d;
20
21     /* 1st one */
22     if(q->front == NULL){
23         q->front = f;
24         q->end = f;
25         q->size = q->size + 1;
26         return;
27     }
28     /* Not 1st */
29     q->end->next = f;
30     q->end = f;
31     q->size = q->size + 1;
32 }
```

ADTs : Queues (Linked) II

```
1  bool queue_dequeue(queue* q, queue_t* d)
2  {
3      dataframe* f;
4      if((q==NULL) || (q->front==NULL) || (q->end==NULL)){
5          return false;
6      }
7      f = q->front->next;
8      *d = q->front->i;
9      free(q->front);
10     q->front = f;
11     q->size = q->size - 1;
12     return true;
13 }
14
15 bool queue_free(queue* q)
16 {
17     if(q){
18         dataframe* tmp;
19         dataframe* p = q->front;
20         while(p!=NULL){
21             tmp = p->next;
22             free(p);
23             p = tmp;
24         }
25         free(q);
26     }
27     return true;
28 }
```

```
1  void queue_tostring(queue* q, char* str)
2  {
3      dataframe *p;
4      char tmp[ELEMSIZE];
5      str[0] = '\0';
6      if((q==NULL) || (q->front == NULL)){
7          return;
8      }
9      p = q->front;
10     while(p){
11         sprintf(tmp, FORMATSTR, p->i);
12         strcat(str, tmp);
13         strcat(str, "|");
14         p = p->next;
15     }
16     str[strlen(str)-1] = '\0';
17 }
18
19 int queue_size(queue* q)
20 {
21     if((q==NULL) || (q->front==NULL)){
22
23         return 0;
24     }
25     return q->size;
26 }
```

Detour : Graphviz

- There exists a nice package, called Graphviz:
`sudo apt install graphviz`
- This allows the visualisation of graphs/dynamic structures using the simple .dot language:

```
digraph {  
    a -> b; b -> c; c -> a;  
}
```
- To create a .pdf:
`dot -Tpdf -o graphviz.pdf examp1.dot`



Table of Contents

N : Recursion

O : Algorithms I - Search

P : Linked Data Structures

Q : ADTs - Collection


R : ADTs - Stacks

S : ADTs - Queues

T : ADTs - Trees

ADTs : Binary Trees

- Binary trees are used extensively in computer science
- Game Trees
- Searching
- Sorting



- Trees drawn upside-down !
- Ancestor relationships: A is the parent of E
- Can refer to left and right children
- In a tree, there is only one path from the root to any child
- A node with no children is a leaf
- Most trees need to be created dynamically
- Empty subtrees are set to NULL

Binary Trees using Arrays ?


- Don't rush to assume a linked data structure must be used to implement trees.
- You could use 1 cell of an array for the first node, the next two cells for its children, the next 4 cells for their children and so on.
- You need to mark which cells are in use & which aren't ...

Counting from cell 1, for a tree with n nodes:

To find	Use	Iff
The root	$A[1]$	A is nonempty
The left child of $A[i]$	$A[2i]$	$2i \leq n$
The parent of $A[i]$	$A[i/2]$	$i > 1$
Is $A[i]$ a leaf ?	True	$2i > n$

Binary Search Trees

In a binary search tree the left-hand tree of a parent contains all keys less than the parent node, and the right-hand side all the keys greater than the parent node.



bst.h

```
1  #include "../General/general.h"
2  #include "../Queue/queue.h"
3
4  #include <stdio.h>
5  #include <stdlib.h>
6  #include <assert.h>
7
8  bst* bst_init(void);
9
10 /* Insert 1 item into the tree */
11 bool bst_insert(bst* b, treetype d);
12
13 /* Return number of nodes in tree */
14 int bst_size(bst* b);
15
16 /* Whether the data d is stored in the tree */
17 bool bst_isin(bst* b, treetype d);
18
19 /* Bulk insert n items from an array a into an initialised tree */
20 bool bst_insertarray(bst* b, treetype* a, int n);
21
22 /* Clear all memory associated with tree, & set pointer to NULL */
23 bool bst_free(bst* b);
24
25 /* Optional ? */
26
27 char* bst_preorder(bst* b);
28 void bst_printlevel(bst* b);
29 /* Create string with tree as ((head)(left)(right)) */
30 char* bst_printlisp(bst* b);
31 /* Use Graphviz via a .dot file */
32 void bst_todot(bst* b, char* dotname);
```

Binary Search Trees : Linked I

specific.h

```
1  #include <string.h>
2
3  typedef int treetype;
4  #define FORMATSIR "%i"
5  #define ELEMSIZE 20
6  #define BSTTYPE "Linked"
7
8  struct dataframe {
9      treetype d;
10     struct dataframe* left;
11     struct dataframe* right;
12 };
13 typedef struct dataframe dataframe;
14
15 struct bst {
16     dataframe* top;
17     /* Data element size, in bytes */
18 };
19 typedef struct bst bst;
```

```
1  /* Based on geekforgeeks.org */
2  dataframe* __insert(dataframe* t, treetype d)
3  {
4      dataframe* f;
5      /* If the tree is empty, return a new frame */
6      if (t == NULL){
7          f = ncalloc(sizeof(dataframe), 1);
8          f->d = d;
9          return f;
10     }
11     /* Otherwise, recurs down the tree */
12     if (d < t->d){
13         t->left = __insert(t->left, d);
14     }
15     else if(d > t->d){
16         t->right = __insert(t->right, d);
17     }
18     /* return the (unchanged) dataframe pointer */
19     return t;
20 }
```

Binary Search Trees : Linked II

```
1 bool __isin(dataframe* t, treetype d)
2 {
3     if(t==NULL){
4         return false;
5     }
6     if(t->d == d){
7         return true;
8     }
9     if(d < t->d){
10        return __isin(t->left, d);
11    }
12    else{
13        return __isin(t->right, d);
14    }
15    return false;
16 }
```

```
1 char* __printlisp(dataframe* t)
2 {
3     char tmp[ELEMSIZE];
4     char *s1, *s2, *p;
5
6     if(t==NULL){
7         /* \0 string */
8         p = nalloc(1,1);
9         return p;
10    }
11    sprintf(tmp, FORMATSTR, t->d);
12    s1 = __printlisp(t->left);
13    s2 = __printlisp(t->right);
14    p = nalloc(strlen(s1)+strlen(s2)+strlen(tmp)+strlen("(")() " ");
15    sprintf(p, "%s(%s)(%s)", tmp, s1, s2);
16    free(s1);
17    free(s2);
18    return p;
19 }
```

Binary Search Trees : Realloc

specific.h

```
1  #include <stdbool.h>
2
3  typedef int treetype;
4  #define FORMATSTR "%i"
5  #define ELEMSIZE 20
6  #define BSTTYPE "Realloc"
7
8  // Probably (2^n) -1
9  #define INITSIZE 31
10 #define SCALEFACTOR 2
11
12 struct dataframe {
13     treetype d;
14     bool invalid;
15 };
16 typedef struct dataframe dataframe;
17
18 struct bst {
19     dataframe* a;
20     int capacity;
21 };
22 typedef struct bst bst;
```

Using a queue for Level-Order traversal:

```
1  void bst_printlevel(bst* b)
2  {
3      treetype n;
4      if((b==NULL) || (! __isvalid(b, 0))){
5          return;
6      }
7      /* Make a queue of cell indices */
8      queue* q = queue_init();
9      queue_enqueue(q, 0);
10     while(queue_dequeue(q, &n) && __isvalid(b, (int)n)){
11         printf(FORMATSTR, b->a[n].d);
12         putchar(' ');
13         queue_enqueue(q, __leftchild((int)n));
14         queue_enqueue(q, __rightchild((int)n));
15     }
```


Binary Search Trees : Complexity

- So, in a nicely balanced tree, insertion, deletion and search are all $O(\log n)$.
- But: if the root of the tree is not well chosen, or the keys to be inserted are ordered, the tree can become a linked list !
- In this case, complexity becomes $O(n)$.
- The tree search performs best when well balanced trees are formed.
- Large body of literature about creating & re-balancing trees - Red-Black trees, Tries, 2-3 trees, AVL trees etc.

Binary Trees : Huffman Compression I

- Often we wish to compress data, to reduce storage requirements, or to speed transmission.
- Text is particularly suited to compression since using one byte per character is wasteful - some letters occur much more frequently.
- Need to give frequently occurring letters short codes, typically a few bits. Less common letters can have long bit patterns.



- To encode the string "BABBAGE":



- Keep a list of characters, ordered by their frequency

Binary Trees : Huffman Compression II

- Use the two least frequent to form a sub-tree, and re-order (sort) the nodes :



- A = 10, B = 0, E = 110, G = 111
- String stored using 13 bits.