

COMSM1201 : Programming in C

Neill.Campbell@bristol.ac.uk

University of Bristol

Built : September 20, 2023



Table of Contents

A: Preamble

B: Hello, World

C: Grammar

D: Flow Control

E: Functions

F: Data Types, Maths and Characters

G: Prettifying (New Types and Aliasing)

H : Constructed Types - 1D Arrays & Structures

I : Strings

J : 2D Arrays & More Types

K : Pointers

L : Advanced Memory Handling

M : Files

About the Course

These course notes were originally based on :

C By Dissection (3rd edition)


Al Kelley and Ira Pohl

because I liked arrays being taught late(r).

I've since changed my mind a little & have re-jigged the notes quite heavily over the years.

Resources

- Free : https://en.wikibooks.org/wiki/C_Programming
- A list of more : <https://www.linuxlinks.com/excellent-free-books-learn-c/>
- Whatever you use, make sure it's **C99** that's being taught, not something else e.g. C11 or C++.
- If you fall in love with C and know you're going to use it for the rest of your life, the reference 'bible' is K&R 2nd edition. It's not a textbook for those new to programming, though.



- Talk to your friends, ask for help, work together.
- Never pass off another persons work as your own.
- Do not pass work to others - either on paper or electronically - even after the submission deadline.
- If someone takes your code and submits it, we need to investigate where it originated - all students involved will be part of this.
- Don't place your code on publicly accessible sites e.g. github - other students may have extensions etc.

History of C



From *Deep C Secrets* by Peter Van Der Linden

- BCPL - Martin Richards
- B - Ken Thomson 1970
- Both of above are *typeless*.
- C - Dennis Ritchie 1972 designed for (& implemented on) a UNIX system.
- K&R C (Kernighan and Ritchie) 1978
- ANSI C
- C99 (COMSM1201)
- C++ Object Oriented Programming (OOP)
- Java (Subset of C++, WWW enabled).

Why C ?

Sep 2023	Sep 2022	Change	Programming Language
1	1		 Python
2	2		 C
3	4	▲	 C++
4	3	▼	 Java
5	5		 C#
6	7	▲	 JavaScript
7	6	▼	 Visual Basic

<https://www.tiobe.com/tiobe-index/>

- One of the most commonly used programming languages according to tiobe.com
- Low-level (c.f. Java)
- Doesn't hide nitty-gritty
- Fast ?
- Large parts common to Java

- Lectured 4 hours per week (Neill & Kira) for weeks 1-12 (barring week 6)
- Programming (C), data structures, algorithms - searching, sorting, string processing, trees etc.

- Weekly (unmarked) exercises that, if completed, should ensure you are able to pass the unit.
- Approximately three/four assignments and one lab test.
- One major project due in early TB2 (35%).
- Hard to gauge timings, so don't make any plans in advance - I'll change it if we're going too fast.

Help with Computers

- Any problems with the computers e.g. installing the correct S/W, accessing lab machines : <http://www.bris.ac.uk/it-services/>
- They are also the people to see about passwords etc.
- This page also links to the rather useful Laptop & Mobile Clinic.

Help with the Unit

- All information is available via the Blackboard site (which will point you to other sites including github.com, MS Teams etc.)
- Online support is given via the Teams Group.
- The main learning resource is our 6 hour of labs per week staffed by TAs.
- TAs are not allowed to write pieces of code for you, nor undertake detailed bug-fixing of your program.

Table of Contents

A: Preamble

B: Hello, World

C: Grammar

D: Flow Control

E: Functions

F: Data Types, Maths and Characters

G: Prettifying (New Types and Aliasing)

H : Constructed Types - 1D Arrays & Structures

I : Strings

J : 2D Arrays & More Types

K : Pointers

L : Advanced Memory Handling

M : Files

Hello World!



Hello World first seen in: Brian Kernighan, *A Tutorial Introduction to the Language B*, 1972

```
1  /* The traditional first program
2  in honour of Dennis Ritchie
3  who invented C at Bell Labs
4  in 1972 */
5
6  #include <stdio.h>
7
8  int main(void)
9  {
10
11     printf("Hello , world!\n");
12     return 0;
13 }
14
```

Execution :

Hello , world!

Dissecting the 1st Program

- Comments are bracketed by the `/*` and `*/` pair.
- `#include <stdio.h>`
Lines that begin with a `#` are called preprocessing directives.
- `int main(void)`
Every program has a function called `main()`
- Statements are grouped using braces,
`{ ... }`
- `printf()` One of the pre-defined library functions being called (invoked) using a single argument the string :
`"Hello, world!\n"`
- The `\n` means print the single character *newline*.
- Notice all declarations and statements are terminated with a semi-colon.
- `return(0)` Instruct the Operating System that the function `main()` has completed successfully.

Area of a Rectangle

```
1  #include <stdio.h>
2
3  int main(void)
4  {
5      // Compute the area of a rectangle
6      int side1, side2, area;
7      side1 = 7;
8      side2 = 8;
9      area = side1 * side2;
10
11     printf("Length of side 1 = %i metres\n", side1);
12     printf("Length of side 2 = %i metres\n", side2);
13     printf("Area of rectangle = %i metres squared\n", area);
14     return 0;
15 }
```

Execution :

Length of side 1 = 7 metres

Length of side 2 = 8 metres

Area of rectangle = 56 metres squared

Dissecting the Area Program

- `//` One line comment.
- `#include <stdio.h>` Always required when using I/O.
- `int side1, side2, area;` *Declaration*
- `side2 = 8;` *Assignment*
- `printf()` has 2 Arguments. The *control string* contains a `%i` to indicate an integer is to be printed.

```
1  preprocessing directives
2
3  int main(void)
4  {
5      declarations
6
7      statements
8  }
```


Arithmetic Operators

- $+$, $-$, $/$, $*$, $\%$
- Addition, Subtraction, Division, Multiplication, Modulus.
- Integer arithmetic discards remainder i.e.
 $1/2$ is 0 , $7/2$ is 3.
- Modulus (Remainder) Arithmetic.
 $7\%4$ is 3, $12\%6$ is 0.
- Only available for integer arithmetic.

The Character Type

```
1 // Demonstration of character arithmetic
2 #include <stdio.h>
3
4 int main(void)
5 {
6     char    c;
7
8     c = 'A';
9     printf("%c ", c);
10    printf("%c\n", c+1);
11    return 0;
12 }
```

Execution :

A B

- The keyword `char` stands for character.
- Used with single quotes i.e. `'A'`, or `'+'`.
- Some keyboards have a second single quote the **back quote** ```
- Note the `%c` conversion format.

Floating Types

```
1  #include <stdio.h>
2
3  int main(void)
4  {
5
6      double x, y;
7
8      x = 1.0;
9      y = 2.0;
10
11     printf("Sum of x & y is %f.\n", x + y);
12
13     return 0;
14
15 }
```

Execution :

Sum of x & y is 3.000000.

- In C there are three common floating types :
 - 1 float
 - 2 double
 - 3 long double
- The *Working Type* is doubles.

The Preprocessor

- A `#` in the first column signifies a preprocessor statement.
- `#include <file.h>` Exchange this line for the entire contents of `file.h`, which is to be found in a standard place.
- `#define PI 3.14159265358979` Replaces all occurrences of `PI` with `3.14159265358979`.
- Include files generally contain other `#define`'s and `#include`'s (amongst other things).

Using printf()

- `printf(fmt-str, arg1, arg2, ...);`

<code>%c</code>	Characters
<code>%i</code>	Integers
<code>%e</code>	Floats/Doubles (Engineering Notation)
<code>%f</code>	Floats/Doubles
<code>%s</code>	Strings

- Fixed-width fields: `printf("F:%7f\n", f);`
F: 3.0001
- Fixed Precision: `printf("F:%.2f\n", f);`
F:3.00

Using scanf()

- Similar to printf() but deals with *input* rather than *output*.
- `scanf(fmt-str, &arg1, &arg2, ...);`
- Note that the *address* of the argument is required.

%c	Characters
%i	Integers
%f	Floats
%lf	Doubles
%s	Strings

- Note doubles handled differently than floats.

While Loops

```
while (test is true) {  
    statement 1;  
    ...  
    statement n;  
}
```

```
1  // Sums are computed.  
2  #include <stdio.h>  
3  
4  int main(void)  
5  {  
6  
7      int cnt = 0;  
8      float sum = 0.0, x;  
9      printf("Input some numbers: ");  
10     while (scanf("%f", &x) == 1) {  
11         cnt = cnt + 1;  
12         sum = sum + x;  
13     }  
14  
15     printf("\n%s%5i\n%s%5f\n\n",  
16           "Count:", cnt, "Sum: ", sum);  
17     return 0;  
18 }
```

Execution :

Input some numbers: 1 5 9 10

Count: 4

Sum: 25.000000

Common Mistakes

- Missing "

```
printf("%c\n, ch);
```

- Missing ;

```
a = a + 1
```

- Missing Address in scanf()

```
scanf("%i", a);
```


Table of Contents

A: Preamble

B: Hello, World

C: Grammar

D: Flow Control

E: Functions

F: Data Types, Maths and Characters

G: Prettifying (New Types and Aliasing)

H : Constructed Types - 1D Arrays & Structures

I : Strings

J : 2D Arrays & More Types

K : Pointers

L : Advanced Memory Handling

M : Files

- C has a grammar/syntax like every other language.
- It has *Keywords*, *Identifiers*, *Constants*, *String Constants*, *Operators* and *Punctuators*.
- Valid Identifiers :
k, `_id`, `iamanidentifier2`, `so_am_i`.
- **Invalid** Identifiers :
`not#me`, `101_south`, `-plus`.
- Constants :
17 (decimal), 017 (octal), 0x17 (hexadecimal).
- String Constant enclosed in double-quotes :
"I am a string"

Operators

- All operators have rules of both *precedence* and *associativity*.
- $1 + 2 * 3$ is the same as $1 + (2 * 3)$ because $*$ has a higher precedence than $+$.
- The associativity of $+$ is left-to-right, thus $1 + 2 + 3$ is equivalent to $(1 + 2) + 3$.
- Increment and decrement operators :
 $i++$; is equivalent to $i = i + 1$;
- May also be prefixed $--i$;

```
1  #include <stdio.h>
2
3  int main(void)
4  {
5      int a, c = 0;
6      a = ++c;
7      int b = c++;
8      printf("%i %i %i\n", a, b, ++c);
9      return 0;
10 }
```

Question : What is the output ?

Assignment

- The = operator has a low precedence and a right-to-left associativity.
- `a = b = c = 0;` is valid and equivalent to :
`a = (b = (c = 0));`
- `i = i + 3;` is the same as `i += 3;`
- Many other operators are possible e.g.
`-=`, `*=`, `/=`.

```
1 // 1st few powers of 2 are printed.
2
3 #include <stdio.h>
4
5 int main(void)
6 {
7     int i = 0, power = 1;
8
9     while (++i <= 10){
10         printf("%5i", power *= 2);
11     }
12     printf("\n");
13     return 0;
14 }
```

Execution :

```
      2      4      8      16      32      64      128      256
512 1024
```

The Standard Library

```
1  #include <stdio.h>
2  #include <stdlib.h>
3
4  int main(void)
5  {
6      printf("Randomly distributed integers are printed.\n"
7            "How many do you want to see? ");
8      int n;
9      if (scanf("%i", &n) == 1){
10         for (int i = 0; i < n; ++i) {
11             if (i % 4 == 0){
12                 printf("\n");
13             }
14             printf("%12i", rand());
15         }
16         printf("\n");
17         return 0;
18     }
19     return 1;
20 }
```

Execution :

```
Randomly distributed integers are printed.
How many do you want to see? 11
```

```
1804289383    846930886    1681692777    1714636915
1957747793    424238335     719885386    1649760492
596516649    1189641421    1025202362
```

- Definitions required for the proper use of many functions such as `rand()` are found in `stdlib.h`.
- Do not mistake these header files for the libraries themselves !

Table of Contents

A: Preamble

B: Hello, World

C: Grammar

D: Flow Control

E: Functions

F: Data Types, Maths and Characters

G: Prettifying (New Types and Aliasing)

H : Constructed Types - 1D Arrays & Structures

I : Strings

J : 2D Arrays & More Types

K : Pointers

L : Advanced Memory Handling

M : Files

Comparisons

<	less than
>	greater than
<=	less than or equal to
>=	greater than or equal to
==	equal to
!=	not equal to
!	not
&&	logical AND
	logical OR

- Any relation is either *true* or *false*.
- Any non-zero value is *true*.
- (a < b) returns the value 0 or 1.
- (i == 5) is a **test** not an **assignment**.
- (!a) is either *true* (1) or *false* (0).
- (a && b) is *true* if both a and b are *true*.
- Single & and | are *bitwise* operators not comparisons - more on this later.

Short-Circuit Evaluation

```
if(x >= 0.0 && sqrt(x) < 10.0){  
    ..... /* Do Something */  
}
```

It's not possible to take the `sqrt()` of a negative number. Here, the `sqrt()` statement is never reached if the first test is *false*. In a logical AND, once any expression is *false*, the whole must be *false*.

The if() Statement

Strictly, you don't need braces if there is only one statement as part of the if :

```
if (expr)
    statement
```

If more than one statement is required :

```
if (expr) {
    statement - 1
    .
    .
    .
    statement - n
}
```

However, we will **always** brace them, even if it's not necessary.

Adding an else statement :

```
if (expr) {
    statement - 1
    .
    .
    .
    statement - n
}
else {
    statement - a
    .
    .
    .
    statement - e
}
```

A Practical Example of if:

```
1  #include <stdio.h>
2
3  int main(void)
4  {
5      int    x, y, z;
6
7      printf("Input three integers: ");
8      if(scanf("%i%i%i", &x, &y, &z) != 3){
9          printf("Didn't get 3 numbers?\n");
10         return 1;
11     }
12     int min;
13     if (x < y){
14         min = x;
15     }
16     // Nasty, dropped braces:
17     else
18         min = y;
19     if (z < min){
20         min = z;
21     }
22     printf("The minimum value is %i\n", min);
23     return 0;
24 }
```

Execution :

Input three integers: 5 7 -4
The minimum value is -4

The while() Statement

```
while(expr)
    statement
```

This, as with the for loop, may execute compound statements :

```
while(expr){
    statement - 1
    .
    .
    statement - n
}
```

However, we will **always** brace them, even if it's not necessary.

```
1 // Simple while countdown
2
3 #include <stdio.h>
4
5 int main(void)
6 {
7
8     int n = 9;
9
10    while(n > 0){
11        printf("%i ", n);
12        n--;
13    }
14    printf("\n");
15    return 0;
16 }
```

Execution :

9 8 7 6 5 4 3 2 1

The for() Loop

This is one of the more complex and heavily used means for controlling execution flow.

```
for( init ; test; loop){  
    statement-1  
    .  
    .  
    .  
    statement-n  
}
```

and may be thought of as :

```
init;  
while(test){  
    statement-1  
    .  
    .  
    .  
    statement-n  
    loop;  
}
```

In the for() loop, note :

- Semi-colons separate the three parts.
- Any (or all) of the three parts could be empty.
- If the test part is empty, it evaluates to *true*.
- `for(;;){ a+=1; }` is an infinite loop.

A Triply-Nested Loop

```
1 // Triples of integers that sum to N
2 #include <stdio.h>
3
4 #define N 7
5
6 int main(void)
7 {
8     int cnt = 0, i, j, k;
9
10    for(i = 0; i <= N; i++){
11        for(j = 0; j <= N; j++){
12            for(k = 0; k <= N; k++){
13                if(i + j + k == N){
14                    ++cnt;
15                    printf("%3i%3i%3i\n", i, j, k);
16                }
17            }
18        }
19    }
20    printf("\nCount: %i\n", cnt);
21    return 0;
22 }
```

Output :

0	0	7
0	1	6
0	2	5
0	3	4
0	4	3
0	5	2
0	6	1
0	7	0

etc.

4	3	0
5	0	2
5	1	1
5	2	0
6	0	1
6	1	0
7	0	0

Count: 36

The Comma Operator

This has the lowest precedence of all the operators in C and associates left-to-right.

```
a = 0 , b = 1;
```

Hence, the for loop may become quite complex :

```
for(sum = 0, i = 1; i <= n; ++i){  
    sum += i;  
}
```

An equivalent, but more difficult to read expression :

```
for(sum = 0 , i = 1; i <= n; ++i, sum += i);
```

Notice the loop has an empty body, hence the semicolon.

The do-while() Loop

```
do {  
    statement -1  
    .  
    .  
    .  
    statement -n  
} while ( test );
```

Unlike the while() loop, the do-while() will always be executed at least once.

```
1  // Simple do-while countdown  
2  
3  #include <stdio.h>  
4  
5  int main(void)  
6  {  
7  
8      int n = 9;  
9  
10     /* This program always prints at least one  
11        number, even if n initialised to 0 */  
12     do{  
13         printf("%i ", n);  
14         n--;  
15     }while(n > 0);  
16     printf("\n");  
17     return 0;  
18 }
```

Execution :

9 8 7 6 5 4 3 2 1

The switch() Statement

```
switch (val) {  
    case 1 :  
        a++;  
        break;  
    case 2 :  
    case 3 :  
        b++;  
        break;  
    default :  
        c++;  
}
```

- The val must be an integer.
- The break statement causes execution to jump out of the loop. No break statement causes execution to 'fall through' to the next line.
- The default label is a catch-all.

The switch() Statement

```
1  /* A Prime number can only be divided
2     exactly by 1 and itself */
3
4  #include <stdio.h>
5
6  int main(void)
7  {
8
9      int i, n;
10     do{
11         printf("Enter a number from 2 - 9 : ");
12         n = scanf("%i", &i);
13     }while( (n!=1) || (i<2) || (i>9) );
14     switch(i){
15         case 2:
16         case 3:
17         case 5:
18         case 7:
19             printf("That's a prime!\n");
20             break;
21         default:
22             printf("That is not a prime!\n");
23     }
24     return 0;
25 }
```

Execution :

Enter a number from 2 - 9 : 1 0 10 3

Enter a number from 2 - 9 : Enter a number

The Conditional (?) Operator

As we have seen, C programmers have a range of techniques available to reduce the amount of typing :

```
expr1 ? expr2 : expr3
```

If `expr1` is *true* then `expr2` is executed, else `expr3` is evaluated.

```
1  #include <stdio.h>
2
3  int main(void)
4  {
5      int    x, y, z;
6
7      printf("Input three integers: ");
8      if (scanf("%i%i%i", &zx, &zy, &zz) != 3){
9          printf("Didn't get 3 numbers?\n");
10         return 1;
11     }
12     int min;
13     min = (x < y) ? x : y;
14     min = (z < min) ? z : min;
15     printf("The minimum value is %i\n", min);
16     return 0;
17 }
```

Table of Contents

A: Preamble

B: Hello, World

C: Grammar

D: Flow Control

E: Functions

F: Data Types, Maths and Characters

G: Prettifying (New Types and Aliasing)

H : Constructed Types - 1D Arrays & Structures

I : Strings

J : 2D Arrays & More Types

K : Pointers

L : Advanced Memory Handling

M : Files

Simple Functions

```
1  #include <stdio.h>
2
3  int min(int a, int b);
4
5  int main(void)
6  {
7
8      int j, k, m;
9
10     printf("Input two integers: ");
11     scanf("%i%i", &j, &k);
12     m = min(j, k);
13     printf("\nOf the two values %i and %i, " \
14           "the minimum is %i.\n\n", j, k, m);
15     return 0;
16 }
17
18
19 int min(int a, int b)
20 {
21     if (a < b)
22         return a;
23     else
24         return b;
25 }
```

Execution :

Input two integers: 5 2

Of the two values 5 and 2, the minimum is 2.

- Execution begins, as normal, in the `main()` function.
- The function *prototype is shown* at the top of the file. This allows the compiler to check the code more thoroughly.
- The function is defined between two braces.
- The function `min()` returns an `int` and takes two `int`'s as arguments. These are copies of `j` and `k`.
- The `return` statement is used to return a value to the calling statement.

Call-by-Value

In the following example, a function is passed an integer using call by value:

```
1  #include <stdio.h>
2
3  void fnc1(int x);
4
5  int main(void)
6  {
7      int x = 1;
8
9      fnc1(x);
10     printf("%i\n", x);
11 }
12
13 void fnc1(int x)
14 {
15     x = x + 1;
16 }
```

Execution :

1

- The function does not change the value of `x` in `main()`, since `x` in the function is effectively only a **copy** of the variable.
- A function which has no return value, is declared `void` and, in other languages, might be termed a *procedure*.
- Most parameters used as arguments to functions in C are copied - this is known as *call-by-value*. We'll see the alternative, *call-by-reference*, later.

Testing

```
1  #include <stdio.h>
2
3  int numfactors(int f);
4
5  int main(void)
6  {
7
8      int n = 12;
9      printf("Number of factors in %i is %i\n", \
10             n, numfactors(n));
11     return 0;
12 }
13
14 int numfactors(int k)
15 {
16
17     int count = 0;
18
19     for(int i=1; i<=k; i++){
20         if( (k%i)==0) {
21             count++;
22         }
23     }
24     return count;
25 }
```

- This is a (not very good) function to compute the number of factors a number has.
- A factor is a number by which a larger (whole/integer) number can be divided.
- 12 has 6 factors: 1, 2, 3, 4, 6 and 12 itself.
- How do we know the program works though ?
- Running it ?
Number of factors in 12 is 6
- We need something more automated.

Pre- and Post-Conditions

```
1  #include <stdio.h>
2  #include <assert.h>
3
4  int numfactors(int f);
5
6  int main(void)
7  {
8
9      int n = 12;
10     printf("Number of factors in %i is %i\n", \
11            n, numfactors(n));
12     return 0;
13 }
14
15 int numfactors(int k)
16 {
17
18     int count = 0;
19
20     assert(k >= 1); // Avoid trying zero
21     for(int i=1; i<=k; i++){
22         if( (k%i)==0) {
23             count++;
24         }
25     }
26     assert(count <= k);
27     return count;
28 }
```

- Pre-conditions check the inputs to functions, typically their arguments.
- Post-conditions check the returns from functions.
- An assert simply states some test that **ought** to be true. If not, the program aborts with an error.
- There's a sense that this is somehow *safer*, but we haven't exactly done much testing on it to ensure the correct answers are returned.

Assert Testing

```
1  #include <stdio.h>
2  #include <assert.h>
3
4  int numfactors(int f);
5
6  int main(void)
7  {
8      assert(numfactors(17) == 2);
9      assert(numfactors(12) == 6);
10     assert(numfactors(6) == 4);
11     assert(numfactors(0) == 0); // ?
12     return 0;
13 }
14
15 int numfactors(int k)
16 {
17
18     int count = 0;
19
20     for(int i=1; i<=k; i++){
21         if( (k%i)==0 ) {
22             count++;
23         }
24     }
25     return count;
26 }
```

- We will use assert testing in this style **every** time we write a function.
- These tests tend to get quite long, so we generally collect them in a function called test() which itself is called from main().
- If there is no error, there is no output from this program.
- By #define'ing NDEBUG before the #include <assert.h>, all assertions are ignored, allowing them to be used during development and switched off later.

Self-test : Multiply

- Write a simple function `int mul(int a, int b)` which multiplies two integers together **without** the use of the multiply symbol in C (i.e. the `*`)
- Use iteration (a loop) to achieve this.
- 7×8 is computed by adding 7, eight times.
- Use `assert()` calls to test it thoroughly - I've given you some to get you started.

```
1  /* Try to write mul(a,b) without using
2     any maths cleverer than addition.    */
3
4  #include <stdio.h>
5  #include <assert.h>
6
7  int mul( int a,  int b);
8  void test(void);
9
10 int main(void)
11 {
12     test();
13
14     return 0;
15 }
16
17 int mul( int a,  int b)
18 {
19     // To be completed
20
21 }
22
23 void test(void)
24 {
25     assert(mul(5,3) == 15);
26     assert(mul(3,5) == 15);
27     assert(mul(0,3) == 0);
28     assert(mul(3,0) == 0);
29     assert(mul(1,8) == 8);
30     assert(mul(8,1) == 8);
31 }
32 }
```

Program Layout

It is normal for the `main()` function to come first in a program :

```
#include <stdio.h>
#include <stdlib.h>

list of function prototypes

int main(void)
{
    . . . . .
}

int f1(int a, int b)
{
    . . . . .
}

int f2(int a, int b)
{
    . . . . .
}
```

However, it is theoretically possible to avoid the need for function prototypes by defining a function before it is used :



```
#include <stdio.h>
#include <stdlib.h>

int f1(int a, int b)
{
    . . . . .
}

int f2(int a, int b)
{
    . . . . .
}

int main(void)
{
    . . . . .
}
```

We will **never** use this second approach - put `main()` first with the prototypes above it.

Replacing Functions with Macros

```
1  #include <stdio.h>
2
3  #define MIN(A, B) ((A)<(B)?(A):(B))
4
5  int main(void)
6  {
7
8      int j, k, m;
9
10     printf("Input two integers: ");
11     scanf("%i%i", &j, &k);
12     m = MIN(j, k);
13     printf("Minimum is %i\n", m);
14     return 0;
15 }
16 }
```

Execution :

```
Input two integers: 5 2
Minimum is 2
```

- There's sometimes a (tiny) time penalty for using functions.
- The contents of the functions are saved onto a special stack, so that when you return to the function, its variables and state can be restored.
- https://en.wikipedia.org/wiki/Call_stack
- Historically, for small functions that needed to be fast, programmers might have `#define` a macro.
- There's a "double evaluation" problem though - what happens if we used `m = MIN(j++, k++)`; ?
- This is expanded to `((j++)<(k++)?(j++):(k++))` which is **not** what was intended.

The inline modifier

- In C99 the inline modifier was introduced
https://en.wikipedia.org/wiki/Inline_function
... serves as a compiler directive that suggests (but does not require) that the compiler substitute the body of the function inline by performing inline expansion, i.e. by inserting the function code at the address of each function call, thereby saving the overhead of a function call.

```
1  #include <stdio.h>
2
3  static inline int min(int a, int b);
4
5  int main(void)
6  {
7
8      int j, k, m;
9
10     printf("Input two integers: ");
11     scanf("%i%i", &j, &k);
12     m = min(j, k);
13     printf("Minimum is %i\n", m);
14     return 0;
15 }
16
17
18 inline int min(int a, int b)
19 {
20     if (a < b)
21         return a;
22     else
23         return b;
24 }
```

Execution :

```
Input two integers: 5 2
Minimum is 2
```

Factorials via Iteration

- A repeated computation is normally achieved via *iteration*, e.g. using `for()`:
- Here we compute the factorial of a number - the factorial of 4, written as $4!$, is simply $4 \times 3 \times 2 \times 1$.
- Obviously, we'd do more assert tests in the full version.

```
1  #include <stdio.h>
2  #include <assert.h>
3
4  int fact(int a);
5
6  int main(void)
7  {
8      assert(fact(4) == 24);
9      assert(fact(1) == 1);
10     assert(fact(0) == 1);
11     assert(fact(10) == 3628800);
12     return 0;
13 }
14
15 int fact(int a)
16 {
17     int i;
18     int tot = 1;
19
20     for(i=1; i<=a; i++){
21         tot *= i;
22     }
23     return tot;
24 }
25
26
27 }
```

Factorials via Recursion (Advanced)

- We could achieve the same result using recursion.
- The factorial of 4 can be thought of as $4 \times 3!$
- A recursive function calls *itself* - there may be many versions of the same function 'alive' at the same time during execution.

```
1  #include <stdio.h>
2  #include <assert.h>
3
4  int fact(int a);
5
6  int main(void)
7  {
8      assert(fact(4) == 24);
9      assert(fact(1) == 1);
10     assert(fact(0) == 1);
11     assert(fact(10) == 3628800);
12     return 0;
13 }
14
15 int fact(int a)
16 {
17     if(a > 0)
18         return (a * fact(a - 1));
19     else
20         return 1;
21 }
22
23
24 }
```

Self-test : Multiply (Advanced)

- Write a simple function `int mul(int a, int b)` which multiplies two integers together **without** the use of the multiply symbol in C (i.e. the `*`)
- Use recursion to achieve this.
- Use `assert()` calls to test it thoroughly.

```
1  /* Try to write mult(a,b) without using
2     any maths cleverer than addition.    */
3
4  #include <stdio.h>
5  #include <assert.h>
6
7  int mul( int a,  int b);
8  void test(void);
9
10 int main(void)
11 {
12     test();
13
14     return 0;
15 }
16
17 int mul( int a,  int b)
18 {
19     // To be completed
20 }
21
22 void test(void)
23 {
24     assert(mul(5,3) == 15);
25     assert(mul(3,5) == 15);
26     assert(mul(0,3) == 0);
27     assert(mul(3,0) == 0);
28     assert(mul(1,8) == 8);
29     assert(mul(8,1) == 8);
30 }
31
32 }
```

Table of Contents

A: Preamble

B: Hello, World

C: Grammar

D: Flow Control

E: Functions

F: Data Types, Maths and Characters

G: Prettifying (New Types and Aliasing)

H : Constructed Types - 1D Arrays & Structures

I : Strings

J : 2D Arrays & More Types

K : Pointers

L : Advanced Memory Handling

M : Files

Fundamental Data types

- [unsigned | signed]
- [long | short]
- [char | int | float | double]
- The use of int implies signed int without the need to state it.
- Likewise unsigned short means unsigned short int.

Type	Minimum size (bits)	Format specifier
char	8	%c
signed char	8	%c (or %hhi for numerical output)
unsigned char	8	%c (or %hhu for numerical output)
short short int signed short signed short int	16	%hi or %hi
unsigned short unsigned short int	16	%hu
int signed signed int	16	Identical for printf : %i or %d For scanf, %d input decimal only For scanf, %i auto-detects format (octal,decimal,hex)
unsigned unsigned int	16	%u
long long int signed long signed long int	32	%ld or %li
unsigned long unsigned long int	32	%lu
long long long long int signed long long signed long long int	64	%lli or %lld
unsigned long long unsigned long long int	64	%llu
float		scanf(): %f, %g, %e, %a
double		%lf, %lg, %le, %la
long double		%Lf, %Lg, %Le, %La

Binary Storage of Numbers

In an unsigned char :

2^7	2^6	2^5	2^4	2^3	2^2	2^1	2^0
0	1	0	0	1	1	0	0

The above represents :

$$1 * 64 + 1 * 8 + 1 * 4 = 76.$$

- Floating operations need not be exact.

```
1  #include <stdio.h>
2
3  int main(void)
4  {
5
6      float d = 0.1;
7      printf("%.12f\n", 3.0*d);
8      return 0;
9  }
```

Execution :

0.3000000004470

- Not all floats are representable so are only approximated.
- Since floats may not be stored exactly, it doesn't make sense to try and compare them:

```
if ( d == 0.3 )
```

- Therefore, we don't allow this by explicitly using the compiler warning flag:
-Wfloat-equal

sizeof()

To find the exact size in bytes of a type on a particular machine, use sizeof(). On a Dell Windows 10 laptop running WSL:

```
1  #include <stdio.h>
2
3  int main(void)
4  {
5
6      printf("char      :%3li\n", sizeof(char));
7      printf("short     :%3li\n", sizeof(short));
8      printf("long      :%3li\n", sizeof(long));
9      printf("unsigned   :%3li\n", sizeof(unsigned));
10     printf("long long  :%3li\n", sizeof(long long));
11     printf("float      :%3li\n", sizeof(float));
12     printf("dbl        :%3li\n", sizeof(double));
13     printf("long dbl   :%3li\n", sizeof(long double));
14     printf("\n");
15
16     return 0;
17 }
```

Execution :

char	:	1
short	:	2
long	:	8
unsigned	:	4
long long	:	8
float	:	4
dbl	:	8
long dbl	:	16

Mathematical Functions

- There are no mathematical functions built into the C language.
- However, there are many functions in the maths library which may be linked in using the **-lm** option with the compiler.
- Functions include :
 `sqrt()` `pow()` `round()`
 `fabs()` `exp()` `log()`
 `sin()` `cos()` `tan()`
- Most take doubles as arguments and return doubles.

Casting

```
1  /* Compute the Volume of a Sphere
2   to the nearest integer */
3  #include <stdio.h>
4  #include <math.h>
5
6  #define PI 3.14159265358979323846
7
8  int main(void)
9  {
10     double r;
11     printf("Enter a radius : ");
12     scanf("%lf", &r);
13     // Make sure radius is positive
14     r = fabs(r);
15     double a = 4.0 / 3.0 * PI * pow(r, (double) 3);
16     printf("Volume of your ball = %f\n", a);
17     printf("Volume of your ball = %.2f\n", a);
18     printf("Volume of your ball = %i\n", (int)a);
19     printf("Volume of your ball = %.0f\n", a);
20     printf("Volume of your ball = %f\n", round(a));
21     return 0;
22 }
```

Execution :

```
Enter a radius : 7.75
Volume of your ball = 1949.816390
Volume of your ball = 1949.82
Volume of your ball = 1949
Volume of your ball = 1950
Volume of your ball = 1950.000000
```

- An explicit type conversion is called a *cast*.
- *If it moves - cast it*. Don't trust the compiler to do it for you !

Storage of Characters

- Characters are stored in the machine as one byte (generally 8-bits storing one of **256** possible values).
- These may be thought of as characters, or very small integers.
- Only a subset of these 256 values are required for the printable characters, space, newline etc.
- Declaration:


```
char c;
```

```
c = 'A';
```

```
or :
```

```
char c1 = 'A', c2 = '*', c3 = ';' ;
```

- The particular integer used to represent a character is dependent on the encoding used. The most common of these, used on most UNIX and PC platforms, is ASCII.



lowercase	'a'	'b'	'c'	...	'z'
ASCII value	97	98	99	...	112
uppercase	'A'	'B'	'C'	...	'Z'
ASCII value	65	66	67	...	90
digit	'0'	'1'	'2'	...	'9'
ASCII value	48	49	50	...	57
other	'&'	'*'	'+'	...	
ASCII value	38	42	43	...	

Using Characters

- When using `printf()` and `scanf()` the formats `%c` and `%i` do very different things :

```
char c = 'a';  
printf("%c\n", c); /* prints : a */  
printf("%i\n", c); /* prints : 97 */
```
- Hard-to-print characters have an escape sequence i.e. to print a newline, the 2 character escape `'\n'` is used.

Escape sequence	Hex value	Character
<code>\a</code>	07	Alert (Beep, Bell)
<code>\b</code>	08	Backspace
<code>\e</code>	1B	Escape character
<code>\f</code>	0C	Formfeed Page Break
<code>\n</code>	0A	Newline (Line Feed)
<code>\r</code>	0D	Carriage Return
<code>\t</code>	09	Horizontal Tab
<code>\v</code>	0B	Vertical Tab
<code>\\</code>	5C	Backslash
<code>\'</code>	27	Apostrophe
<code>\"</code>	22	Double quote
<code>\?</code>	3F	Question mark

Using getchar() and putchar()

```
1 // Outputs characters twice
2
3 #include <stdio.h>
4
5 int main(void)
6 {
7     char c;
8
9     do{
10         c = getchar();
11         putchar(c);
12         putchar(c);
13     }while(c != '!');
14     putchar('\n');
15
16     return 0;
17 }
18 }
```

Execution :

```
abc123!
aabbcc112233!!
```

This has the unfortunate problem of requiring a 'special' character to terminate. More aggressively, the user could terminate by pressing CTRL-C.

```
1 // Outputs characters twice
2
3 #include <stdio.h>
4
5 int main(void)
6 {
7     char c; // char or int ?
8
9     while ((c = getchar()) != EOF) {
10         putchar(c);
11         putchar(c);
12     }
13     putchar('\n');
14
15     return 0;
16 }
17 }
```

Execution :

```
abc123
aabbcc112233
```

The end-of-file constant is defined in `stdio.h`. Although system dependent, `-1` is often used. On the UNIX system this is generated when the end of a file being piped is reached, or when CTRL-D is pressed.

Capitalization

```
1 // Outputs characters twice
2
3 #include <stdio.h>
4
5 #define CAPS ('A' - 'a')
6
7 int main(void)
8 {
9     int c;
10    while ((c = getchar()) != '!'){
11        if (c >= 'a' && c <= 'z'){
12            putchar(c + CAPS);
13        }
14        else{
15            putchar(c);
16        }
17    }
18    putchar('\n');
19    return 0;
21 }
```

Execution :

Hello World!
HELLO WORLD

This is more easily achieved by using some of the definitions found in `ctype.h`.

Macro	true returned if:
<code>isalnum(int c)</code>	Letter or digit
<code>isalpha(int c)</code>	Letter
<code>iscntrl(int c)</code>	Control character
<code>isdigit(int c)</code>	Digit
<code>isgraph(int c)</code>	Printable (not space)
<code>islower(int c)</code>	Lowercase
<code>isprint(int c)</code>	Printable
<code>ispunct(int c)</code>	Punctuation
<code>isspace(int c)</code>	White Space
<code>isupper(int c)</code>	Uppercase
<code>isxdigit(int c)</code>	Hexadecimal
<code>isascii(int c)</code>	ASCII code

ctype.h

Some useful functions are :

Function/Macro	Returns:
int tolower(int c)	Lowercase c
int toupper(int c)	Uppercase c
int toascii(int c)	ASCII code for c

```
1  #include <stdio.h>
2  #include <ctype.h>
3
4  int main(void)
5  {
6
7      int c;
8      while ((c = getchar()) != EOF){
9          if (islower(c)){
10             putchar(toupper(c));
11         }
12         else{
13             putchar(c);
14         }
15     }
16     putchar('\n');
17     return 0;
18 }
```

```
1  #include <stdio.h>
2  #include <ctype.h>
3
4  int main(void)
5  {
6
7      int c;
8      while ((c = getchar()) != EOF){
9          /* toupper() returns non-lowercae
10             chars unaltered */
11             putchar(toupper(c));
12         }
13         putchar('\n');
14         return 0;
15     }
```

Execution :

Hello World!
HELLO WORLD!

Table of Contents

A: Preamble

B: Hello, World

C: Grammar

D: Flow Control

E: Functions

F: Data Types, Maths and Characters

G: Prettifying (New Types and Aliasing)

H : Constructed Types - 1D Arrays & Structures

I : Strings

J : 2D Arrays & More Types

K : Pointers

L : Advanced Memory Handling

M : Files

Enumerated Types

```
enum day { sun, mon, tue, wed, thu, fri, sat};
```

- This creates a user-defined **type** `enum day`.
- The enumerators are constants of type `int`.
- By default the first (`sun`) has the value 0, the second has the value 1 and so on.

- An example of their use:

```
enum day d1;
```

```
...  
d1 = fri;
```

- The default numbering may be changed as well:

```
enum fruit{apple=7, pear, orange=3, lemon};
```
- Use enumerated types as constants to aid readability - they are self-documenting.
- Declare them in a header (`.h`) file.
- Note that the type is `enum day`; the keyword `enum` is not enough.

Typedefs

- Sometimes it is useful to associate a particular name with a certain type, e.g.:
`typedef int colour;`
- Now the type `colour` is synonymous with the type `int`.
- Makes code self-documenting.
- Helps to control complexity when programmers are building complicated or lengthy user-defined types (See Structures later).

Combining typedefs and enums

- Often typedef's are used in conjunction with enumerated types:

```
#include <stdio.h>
#include <assert.h>

enum day {sun,mon,tue,wed,thu,fri,sat};
typedef enum day day;

day find_next_day(day d);

int main(void)
{
    assert(find_next_day(mon)==tue);
    assert(find_next_day(sat)==sun);
    assert(find_next_day(sun)==mon);
    return 0;
}
```

```
day find_next_day(day d)
{
    day next_day;
    switch(d){
        case sun:
            next_day = mon;
            break;
        case mon:
            next_day = tue;
            break;
        case tue:
            next_day = wed;
            break;
        case wed:
            next_day = thu;
            break;
        case thu:
            next_day = fri;
            break;
        case fri:
            next_day = tue;
            break;
        case sat:
            next_day = sun;
            break;
        default:
            printf("I wasn't expecting that !\n");
    }
    return next_day;
}
```

```
enum veg {beet, carrot, pea};  
typedef enum veg veg;  
veg v1, v2;  
v1 = carrot;
```

- We can combine the two operations into one:

```
typedef enum veg {beet,carrot,pea} veg;  
veg v1, v2;  
v1 = carrot;
```

- Assigning:

```
v1 = 10;
```

is very poor programming style !

Booleans

- Before C99 you might have been tempted to define your own Boolean type:

```
1  #include <stdio.h>
2  #include <assert.h>
3
4  typedef enum bool {false, true} bool;
5
6  int main(void)
7  {
8
9      bool b = true;
10     if (b){
11         printf("It's true!\n");
12     }
13     else{
14         printf("It's false!\n");
15     }
16     return 0;
17 }
```

Execution :

It 's true!

- However, we can just use `#include <stdbool.h>`

```
1  #include <stdio.h>
2  #include <stdbool.h>
3  #include <assert.h>
4
5  int main(void)
6  {
7
8      bool b = true;
9      if (b){
10         printf("It's true!\n");
11     }
12     else{
13         printf("It's false!\n");
14     }
15     return 0;
16 }
```

Execution :

It 's true!

Rewrite/complete this code using typedefs and enums to create self-documenting code in any manner you wish.

```
1  #include <stdio.h>
2  #include <assert.h>
3
4  // Argument 1 is temperature
5  // Argument 2 is scale (0=>Celsius, 1=>Fahrenheit)
6  int fvr(double t, int s);
7
8  int main(void)
9  {
10     assert(fvr(37.5, 0)==1);
11     assert(fvr(36.5, 0)==0);
12     assert(fvr(96.5, 1)==0);
13     assert(fvr(99.5, 1)==1);
14     return 0;
15 }
16
17 int fvr(double t, int s)
18 {
19 }
```

Table of Contents

A: Preamble

B: Hello, World

C: Grammar

D: Flow Control

E: Functions

F: Data Types, Maths and Characters

G: Prettifying (New Types and Aliasing)

H : Constructed Types - 1D Arrays & Structures

I : Strings

J : 2D Arrays & More Types

K : Pointers

L : Advanced Memory Handling

M : Files

1D Arrays

- One-Dimensional arrays are declared by a type followed by an identifier with a bracketed constant expression:

```
float x[10];  
int k[ARRAY_SIZE];
```

The following, however, is not valid:

```
float y[i*2];
```

- Arrays are stored in contiguous memory, e.g.:

```
int a[5];
```



- Arrays are indexed **0** to **n-1**.

```
1  #include <stdio.h>  
2  
3  #define N 500  
4  
5  int main(void)  
6  {  
7  
8      /* allocate space a[0]...a[N-1] */  
9      int a[N];  
10     int i, sum = 0;  
11     /* fill array */  
12     for (i = 0; i < N; ++i){  
13         a[i] = 7 + i * i;  
14     }  
15     /* print array */  
16     for (i = 0; i < N; ++i){  
17         printf("a[%i]=%i ", i, a[i]);  
18     }  
19     /* sum elements */  
20     for (i = 0; i < N; ++i){  
21         sum += a[i];  
22     }  
23     /* print sum */  
24     printf("\nsun=%i\n", sum);  
25     return 0;  
26 }
```

1D Arrays : Initialisation

By default, arrays are uninitialised. When they are declared, they may be assigned a value:

```
float x[7] = {-1.1,0.2,2.0,4.4,6.5,0.0,7.7};
```

or,

```
float x[7] = {-1.1, 0.2};
```

the elements 2 ... 6 are set to zero.

Also:

```
int a[] = {3, 8, 9, 1};
```

is valid, the compiler assumes the array size to be 4.

- `a[5] = a[4] + 1;`
- `k[9]++;`
- `n[12+i] = 0;`
- Accessing an array out of bounds will not be identified by the compiler. It may cause an error at run-time. One frequent result is that an entirely unrelated variable is altered.

1D Arrays : Call by Reference

```
1  #include <stdio.h>
2  #include <math.h>
3  #include <assert.h>
4  #define MAX 5
5
6  // Pass array, AND number of elements
7  void set_array(int a[MAX], unsigned int len, int n);
8
9  int main(void)
10 {
11     int x[MAX] = {2, 3, 3, 3, 3};
12     set_array(x, 5, 3); assert(x[0] == 3);
13     x[0] = 5; x[1] = 5; x[2] = 5; x[3] = 5; x[4] = 5;
14     set_array(x, 5, 4); assert(x[2] == 4);
15     set_array(x, 1, 0); assert(x[0] == 0);
16     x[0] = 1; x[1] = 2; x[2] = 3;
17     set_array(x, 3, 2);
18     assert(x[2] == 2); assert(x[3] == 4);
19 }
20
21 // Set all values of array (size len) to n
22 void set_array(int a[MAX], unsigned int len, int n)
23 {
24     if(len == 0){
25         return;
26     }
27     for(unsigned int i=0; i<len; i++){
28         a[i] = n;
29     }
30 }
```

- Here, the array is passed by *Reference* - no copy of the array is made - the function processes the array that was created inside `main()`, despite it apparently having a 'different' name.
- All arrays are passed like this in C - we'll see later when we look at *pointers* why this is the case.

Structures

- A structure type allows the programmer to aggregate components into a single, named variable. Other languages call these *Records* or *Tuples*.
- Each component has individually named members.
- ```
struct employee {
 long id;
 double salary;
 short age;
};
```
- `struct` is a keyword, `employee` is the structure tag name, and `id`, `salary` and `age` are members of the structure.
- A statement of the form :  

```
struct employee e1, e2;
```

 actually creates storage for the variables.
- A member is accessed using the member operator `“.”`
- ```
e1.salary = 35000.2;  
e2.age = 29;
```
- The member name must be unique within the same structure.
- Arrays of structures are possible, i.e.:

```
struct employee team[400];
```

Arrays of Structures

```
#include <stdio.h>
#include <stdbool.h>
#include <stdlib.h>
#include <assert.h>

#define SUITS 4
#define PERSUIT 13
#define DECK (SUITS*PERSUIT)
#define SHUFFLE 3

typedef enum {hearts, diamonds, spades, clubs} suit;

struct card {
    suit st;
    int pips;
};
typedef struct card card;

void shuffle_deck(card d[DECK]);
void init_deck(card d[DECK]);
void print_deck(card d[DECK], int n);
void test(void);

int main(void)
{
    card d[DECK];

    test();
    init_deck(d);
    print_deck(d, 7);
    shuffle_deck(d);
    print_deck(d, 7);
    return 0;
}
```

```
void init_deck(card d[DECK])
{
    for(int i=0; i<DECK; i++){
        // Number 1 .. 13
        d[i].pips = (i%PERSUIT) + 1;
        switch (i/PERSUIT) {
            case hearts: d[i].st = hearts; break;
            case diamonds: d[i].st = diamonds; break;
            case spades: d[i].st = spades; break;
            case clubs: d[i].st = clubs; break;
            // Force an abort ?
            default : assert(false);
        }
    }
}

void shuffle_deck(card d[DECK])
{
    for(int i=0; i<SHUFFLE*DECK; i++){
        int n1 = rand()%DECK;
        int n2 = rand()%DECK;
        card c = d[n1]; d[n1] = d[n2]; d[n2] = c;
    }
}
```

Arrays of Structures

```
void print_deck(card d[DECK], int n)
{
    for(int i=0; i<n; i++){
        switch(d[i].pips){
            case 11:
                printf("Jack");
                break;
            case 12:
                printf("Queen");
                break;
            case 13:
                printf("King");
                break;
            default:
                printf("%2i", d[i].pips);
        }
        switch(d[i].st){
            case hearts :
                printf(" of Hearts\n");
                break;
            case diamonds :
                printf(" of Diamonds\n");
                break;
            case spades:
                printf(" of Spades\n");
                break;
            default :
                printf(" of Clubs\n");
        }
    }
    printf("\n");
}
```

Execution :

```
1 of Hearts
2 of Hearts
3 of Hearts
4 of Hearts
5 of Hearts
6 of Hearts
7 of Hearts

4 of Spades
Jack of Spades
7 of Clubs
9 of Spades
10 of Spades
7 of Hearts
2 of Spades
```

- The print_deck() function is clearly messy ! We can simplify this a little when we understand strings.

Testing

```
void test(void)
{
    int n = 0;
    card d[DECK];
    init_deck(d);
    // Direct assignment
    card c = {hearts, 10};
    // 1st element initialised correctly
    assert(d[9].pips == c.pips);
    assert(d[9].st == c.st);
    for(int i=0; i<1000; i++){
        shuffle_deck(d);
        // Happens 1 time in 52 ?
        if((d[0].st == c.st) && (d[0].pips == c.pips)){
            n++;
        }
    }
    // Is this a reasonable test ?
    assert((n > 10) && (n < 30));
}
```

- Note the direct ability to copy a structure.
- You can't compare them using == though.
- Tricky to think of a good test for shuffle_deck.
- You could also typedef away the array, e.g.:

typedef card deck[DECK];

void shuffle_deck(deck d);

But this hides the fact it's an array (which seems odd?)

Table of Contents

A: Preamble

B: Hello, World

C: Grammar

D: Flow Control

E: Functions

F: Data Types, Maths and Characters

G: Prettifying (New Types and Aliasing)

H : Constructed Types - 1D Arrays & Structures

I : Strings

J : 2D Arrays & More Types

K : Pointers

L : Advanced Memory Handling

M : Files

- Strings are 1D arrays of characters.
- Any character in a string may be accessed as an array element.
- The important difference between strings and ordinary arrays is the **end-of-string sentinel** `'\0'` or null character.
- The string "abc" has a *length* of 3, but its *size* is 4.
- Note `'a'` and `"a"` are different. The first is a character constant, the second is a string with 2 elements `'a'` and `'\0'`.

Initialising Strings :

- `char w[6] = "Hello";`
- `char w[250];`
`w[0] = 'a';`
`w[1] = 'b';`
`w[2] = 'c';`
`w[3] = '\0';`
- `scanf("%s", w);`
Removes leading spaces, reads a string (terminated by a space or EOF). Adds a null character to the end of the string.
- `char w[250] = {'a', 'b', 'c', '\0'};`

Unused Letters and string.h

```
1  #include <stdio.h>
2  #include <stdbool.h>
3  #include <ctype.h>
4
5  #define ALPHASIZE 26
6
7  int main(void)
8  {
9      char s[100] = "The Quick Brown Fox Leaps" \
10                   "Over the Lazy Dog";
11      bool used[ALPHASIZE] = {false};
12      int i = 0;
13      while(s[i]){
14          char c = tolower(s[i]);
15          if(islower(c)){
16              used[c - 'a'] = true;
17          }
18          i++;
19      }
20      for(i=0; i<ALPHASIZE; i++){
21          if(!used[i]){
22              printf("%c has not been used.\n", i+'a');
23          }
24      }
25      return 0;
26  }
```

Execution :

```
j has not been used.
m has not been used.
```

In `#include <string.h>` :

```
char *strcat(char dest[], const char src[]);
int strcmp(const char s1[], const char s2[]);
```

- `strcat()` appends a copy of string `src`, including the terminating null character, to the end of string `dst`.
- `strcmp()` compares two strings byte-by-byte, according to the ordering of your machine's character set. The function returns an integer greater than, equal to, or less than 0, if the string pointed to by `s1` is greater than, equal to, or less than the string pointed to by `s2` respectively.

More string.h

In `#include <string.h>` :

```
char *strcpy(char dst[], const char src[]);  
unsigned strlen(const char s[]);
```

- `strcpy()` copies string `src` to `dst` including the terminating null character, stopping after the null character has been copied.
- `strlen()` returns the number of bytes in `s`, not including the terminating null character.

One way to write the function `strlen()` :

```
1  #include <stdio.h>  
2  #include <assert.h>  
3  
4  unsigned nstrlen(const char s[]);  
5  
6  int main(void)  
7  {  
8      assert(nstrlen("Neill")==5);  
9      assert(nstrlen("")==0);  
10     assert(nstrlen("\n")==1);  
11     assert(nstrlen("abcdef")==nstrlen("fedcba"));  
12     return 0;  
13 }  
14  
15 unsigned nstrlen(const char s[])  
16 {  
17     register unsigned n = 0;  
18  
19     while(s[n] != '\0'){  
20         ++n;  
21     }  
22     return n;  
23 }
```

The snprintf() Function

In `#include <string.h>` : This is very similar to the function `printf()`, except that the output is stored in a string rather than written to the output. It is defined as:

`int snprintf(string, str-size, control-arg, other args);`

For example:

```
int i = 7;
float f = 17.041;
char str[100];
snprintf(str, 100, "%i %f", i, f);
printf("%s\n", str);
```

Outputs : 7 17.041000

This is useful if you need to create a string for passing to another function for further processing.

```
#define SMALLSTR 20
void print_card(char s[BIGSTR], card c)
{
    char pipstr[SMALLSTR];
    char suitstr[SMALLSTR];
    switch(c.pips){
        case 11:
            strcpy(pipstr, "Jack");
            break;
        case 12:
            strcpy(pipstr, "Queen");
            break;
        case 13:
            strcpy(pipstr, "King");
            break;
        default:
            snprintf(pipstr, SMALLSTR, "%2i", c.pips);
    }
    switch(c.st){
        case hearts :
            strcpy(suitstr, "Hearts");
            break;
        case diamonds :
            strcpy(suitstr, "Diamonds");
            break;
        case spades:
            strcpy(suitstr, "Spades");
            break;
        default :
            strcpy(suitstr, "Clubs");
    }
    snprintf(s, BIGSTR, "%s of %s", pipstr, suitstr);
}
```

sprintf() and sscanf()

```
#define FIRSTCARD " 1 of Hearts"
void test(void)
{
    int n = 0;
    char str[BIGSTR];
    card d[DECK];
    init_deck(d);
    // Direct assignment
    print_card(str, d[0]);
    // 1st element initialised correctly
    assert(strcmp(str, FIRSTCARD)==0);
    for(int i=0; i<1000; i++){
        shuffle_deck(d);
        print_card(str, d[0]);
        // Happens 1 time in 52 ?
        if(strcmp(str, FIRSTCARD)==0){
            n++;
        }
    }
    // Is this a reasonable test ?
    assert((n > 10) && (n < 30));
}
```

```
// Simple demo of sscanf (and fgets in passing)
#include <stdio.h>
#include <assert.h>

#define BIGSTR 1000
#define SMLSTR 100
#define DAYSINYEAR 365.2425

#include <stdio.h>

int main(void)
{
    printf("Please type your first name and your age\n");
    char bigstr[BIGSTR];
    fgets(bigstr, BIGSTR, stdin);
    char name[SMLSTR];
    int age;
    // Note no "&" before name : passed by reference already
    assert(sscanf(bigstr, "%s %i\n", name, &age)==2);
    printf("%s, you've lived approximately %.0f days\n",
           name, ((double)(age)+0.5)*DAYSINYEAR);
    return 0;
}
```

Execution :

Please type your first name and your age

Joe 25

Joe, you've lived approximately 9314 days

Table of Contents

A: Preamble

B: Hello, World

C: Grammar

D: Flow Control

E: Functions

F: Data Types, Maths and Characters

G: Prettifying (New Types and Aliasing)

H : Constructed Types - 1D Arrays & Structures

I : Strings

J : 2D Arrays & More Types

K : Pointers

L : Advanced Memory Handling

M : Files

Initializing 2D Arrays

A 2D array is declared as follows:

```
#define ROWS 3  
#define COLS 5  
int a[ROWS][COLS];
```

2D array initialisation :

```
int b[2][3] = {1, 2, 3, 4, 5, 6};  
int b[2][3] = {{1, 2, 3}, {4, 5, 6}};  
int b[ ][3] = {{1, 2, 3}, {4, 5, 6}};
```

Although 2D arrays are stored in a contiguous block of memory, we may think of them as a 2D rectangle of data.

```
int c[3][5] = {{1,2,3,4,5}, {6,7,8,9,10},  
               {11,12,13,14,15}};
```



2D Distance

```
1  #include <stdio.h>
2  #include <math.h>
3
4  #define M 7
5  #define N 9
6
7  void fillarray(int a[M][N]);
8
9  int main(void)
10 {
11     int a[M][N];
12
13     fillarray(a);
14     // Print Array
15     for (int j = 0; j < M; j++){
16         for(int i = 0; i < N; i++){
17             printf("%i ", a[j][i]);
18         }
19         printf("\n");
20     }
21     printf("\n");
22     return 0;
23 }
24
25 void fillarray(int a[M][N])
26 {
27     for (int j = 0; j < M; ++j){
28         double y = ((double)j - ((double)(M-1)/2.0));
29         for(int i = 0; i < N; ++i){ // Column- first
30             double x = ((double)i - ((double)(N-1)/2.0));
31             a[j][i] = round(sqrt(x*x + y*y));
32         }
33     }
34 }
```

Execution :

```
544333445
443222344
432111234
432101234
432111234
443222344
544333445
```

Cards (again!)

```
#define SMALLSTR 20
void print_card(char s[BIGSTR], card c)
{
    // Note the +1 below : zero pips not used, but makes easier coding ?
    char pipenames[PERSUIT+1][SMALLSTR] = {"Zero", "One", "Two", "Three",
                                             "Four", "Five", "Six", "Seven",
                                             "Eight", "Nine", "Ten", "Jack",
                                             "Queen", "King"};

    char suitnames[SUITS][SMALLSTR] = {"Hearts", "Diamonds", "Spades", "Clubs"};
    snprintf(s, BIGSTR, "%s of %s", pipenames[c.pips], suitnames[c.st]);
}
```

- The 2D arrays of characters here have one string per row.
- They are of a fixed-width, sometime called *ragged-right* or *jagged-right* arrays.

Storage Classes

- **auto**

auto int a, b, c;

auto float f;

Because this is the default, it is seldom used.

- **extern**

Tells the compiler to look for the variable elsewhere, possibly another file.

- **register**

Informs the compiler to place the variable in a high-speed memory register if possible, i.e. if there are enough such registers available & the hardware supports this.

```
1  #include <stdio.h>
2  #include <stdlib.h>
3
4  void printstuff(void);
5
6  #define MAXLOOP 20
7
8  int main(void)
9  {
10     int r = rand() % MAXLOOP;
11     for(int i=0; i<r; i++){
12         printstuff();
13     }
14     return 0;
15 }
16
17 void printstuff(void)
18 {
19     static int cnt = 0;
20     printf("You've been here %i times\n", ++cnt);
21 }
```

Execution :

You've been here 1 times

You've been here 2 times

You've been here 3 times

Table of Contents

A: Preamble

B: Hello, World

C: Grammar

D: Flow Control

E: Functions

F: Data Types, Maths and Characters

G: Prettifying (New Types and Aliasing)

H : Constructed Types - 1D Arrays & Structures

I : Strings

J : 2D Arrays & More Types

K : Pointers

L : Advanced Memory Handling

M : Files

Call-by-Value

```
1  #include <stdio.h>
2
3  void changex(int x);
4
5  int main(void)
6  {
7      int x = 1;
8
9      changex(x);
10     printf("%i\n", x);
11     return 0;
12 }
13
14 void changex(int x)
15 {
16     x = x + 1;
17 }
```

Execution :


1

- In the program, the function cannot change the value of `x` as defined in `main()` since a **copy** is made of it.
- To allow a function to modify the value of a variable passed to it we need a mechanism known as **call-by-reference**, which uses the **address** of variables (pointers).

Call-by-Reference


- We have already seen addresses used with `scanf()`. The function call:
`scanf("%i", &v);`
causes the appropriate value to be stored at a particular address in memory.
- If `v` is a variable, then `&v` is its address, or location, in memory.

- `int i, *p;`
- Here `i` is an `int` and `p` is of type *pointer to int*.
- Pointers have a legal range which includes the special address 0 and a set of positive integers which are the machine addresses of a particular system.




The *NULL* Pointer

- `p = NULL;`



- `p = &i;`



Equivalence of i and $*p$

● $i = 5;$



```
1  #include <stdio.h>
2
3  int main(void)
4  {
5
6      int i = 5;
7      int* p = &i;
8      printf("%i\n", *p);
9      i = 17;
10     printf("%i\n", *p);
11     *p = 99;
12     printf("%i\n", i);
13
14     return 0;
15
16 }
```

Execution :

5
17
99

scanf Again

```
1  #include <stdio.h>
2
3  int main(void)
4  {
5
6      int i;
7      int* p;
8
9      p = &i;
10     printf("Please Type a number : ");
11     scanf("%i", &i);
12     printf("%i\n", i);
13     printf("Please Type a number : ");
14     scanf("%i", p);
15     printf("%i\n", i);
16
17     return 0;
18
19 }
```

Execution :

```
Please Type a number : 70
70
Please Type a number : 3
3
```

- In many ways the dereference operator `*` is the inverse of the address operator `&`.

```
float x = 5, y = 8, *p;
p = &x;
y = *p;
```

- What is this equivalent to ?


The *swap* Function

```
1  #include <stdio.h>
2
3  void swap(int* p, int* q);
4
5  int main(void)
6  {
7      int    a = 3, b = 7;
8
9      // 3 7 printed
10     printf("%i %i\n", a, b);
11     swap(&a, &b);
12     // 7 3 printed
13     printf("%i %i\n", a, b);
14     return 0;
15 }
16
17 void swap(int* p, int* q)
18 {
19     int    tmp;
20
21     tmp = *p;
22     *p = *q;
23     *q = tmp;
24 }
```

Execution :

```
3 7
7 3
```

- At beginning of function:



- At end of function:



- Remember that the variables `a` and `b` are not in the scope of `swap()`.

Arrays are Pointers ?

- An array name by itself is simply an address (**Array Decay**).
- For instance:

```
int a[5];  
int *p;
```

declares an array of 5 elements, and `a` is the address of the start of the array.
- Assigning:

```
p = a;
```

is completely valid and the same as:

```
p = &a[0];
```



- To assign `p` to point to the next element, we could either :

```
p = a + 1;  
p = &a[1];
```
- Notice that `p = a + 1` advances the pointer **4** bytes and not 1 byte. This is because an integer is 4 bytes long and `p` is a pointer to an int.
- we can use the pointer `p` is exactly the same way as normal, i.e.:

```
*p = 5;
```

Summing an Array

```
1  #include <stdio.h>
2
3  #define NUM 5
4
5  int sum(int a[]);
6
7  int main(void)
8  {
9
10     int n[NUM] = {10, 12, 6, 7, 2};
11
12     printf("%i\n", sum(n));
13     return 0;
14 }
15
16 int sum(int a[])
17 {
18     int sum = 0;
19
20     for(int i=0; i<NUM; i++){
21         sum += a[i];
22     }
23     return sum;
24 }
```

Execution :

37

```
1  #include <stdio.h>
2
3  #define NUM 5
4
5  int sum(int a[]);
6
7  int main(void)
8  {
9
10     int n[NUM] = {10, 12, 6, 7, 2};
11
12     printf("%i\n", sum(n));
13     return 0;
14 }
15
16 int sum(int a[])
17 {
18     int sum = 0;
19
20     for(int i=0; i<NUM; i++){
21         sum += *(a + i);
22     }
23     return sum;
24 }
```

Execution :

37

```
1  #include <stdio.h>
2
3  #define NUM 5
4
5  int sum(int* p );
6
7  int main(void)
8  {
9
10     int n[NUM] = {10, 12, 6, 7, 2};
11
12     printf("%i\n", sum(n));
13     return 0;
14 }
15
16 int sum(int* p )
17 {
18     int sum = 0;
19
20     for(int i=0; i<NUM; i++){
21         sum += *p;
22         p++;
23     }
24     return sum;
25 }
```

Execution :

37

Pointers to Structures

- By default, structures are passed by value (copied) when used as a parameter to a function.
- But, like any other type, we could pass a pointer instead.
- The complication is that to access the elements of a structure via a pointer, we use the “->” operator, and not the “.”.

```
void print_deck(card d[DECK], int n)
{
    char str[BIGSTR];
    for(int i=0; i<n; i++){
        print_card(str, &d[i]);
        printf("%s\n", str);
    }
    printf("\n");
}

#define SMALLSTR 20
void print_card(char s[BIGSTR], const card* p)
{
    // Note the +1 below : zero pips not used, but makes easier coding ?
    char pipenames[PERSUIT+1][SMALLSTR] = {"Zero", "One", "Two", "Three",
        "Four", "Five", "Six", "Seven",
        "Eight", "Nine", "Ten", "Jack",
        "Queen", "King"};

    char suitnames[SUITS][SMALLSTR] = {"Hearts", "Diamonds", "Spades", "Clubs"};
    snprintf(s, BIGSTR, "%s of %s", pipenames[p->pi], suitnames[p->st]);
}
```

Nested Structures

```
1  #include <stdio.h>
2
3  struct dateofbirth {
4      unsigned char day;
5      unsigned short month;
6      unsigned short year;
7  };
8  typedef struct dateofbirth dob;
9
10 typedef struct {
11     char* name;
12     dob date;
13 } person;
14
15 void print_byval(person b);
16 void print_byref(const person* p);
17
18 int main(void)
19 {
20     person a = {"Gary", {17, 5, 1999}};
21     print_byval(a);
22     print_byref(&a);
23 }
24
25 void print_byval(person b)
26 {
27     printf("%s %hu/%hi/%hi\n", b.name, b.date.day, b.date.month, b.date.year);
28 }
29
30 void print_byref(const person* p)
31 {
32     printf("%s %hu/%hi/%hi\n", p->name, p->date.day, p->date.month, p->date.year);
33 }
```

Execution :

Gary 17/5/1999

Gary 17/5/1999

Table of Contents

A: Preamble

B: Hello, World

C: Grammar

D: Flow Control

E: Functions

F: Data Types, Maths and Characters

G: Prettifying (New Types and Aliasing)

H : Constructed Types - 1D Arrays & Structures

I : Strings

J : 2D Arrays & More Types

K : Pointers

L : Advanced Memory Handling

M : Files

String Constants

```
1 // A FAILED attempt to
2 // convert all 'n' chars to 'N'
3 #include <stdio.h>
4 #include <stdlib.h>
5 #include <string.h>
6 #include <assert.h>
7
8 void nify(char s[]);
9
10 int main(void)
11 {
12
13     nify("neill");
14     return 0;
15 }
16
17 // In-Place : Swaps all 'n' -> 'N'
18 void nify(char s[])
19 {
20     for(int i=0; s[i]; i++){
21         if(s[i] == 'n'){
22             s[i] = 'N';
23         }
24     }
25 }
26 }
```

- This looks (at first) like a sensible attempt to accept a string and change it *in-place* to capitalise all 'n' characters. It crashes though via a segmentation fault.
- With the usual compile flags we get no more information.
- But using:
`clang nify1.c -g3 -fsanitize=undefined -fsanitize=address -o nify1`
we find that

```
s[i] = 'N';
```

is the culprit.
- It turns out that in `main()` we have passed a **constant** string to the function. This is in a part of memory that we have read-only permission.

Local Variables

```
1 // A FAILED attempt to
2 // convert all 'n' chars to 'N'
3 #include <stdio.h>
4 #include <stdlib.h>
5 #include <string.h>
6 #include <assert.h>
7
8 #define LINE 500
9
10 char* nify(char s[]);
11
12 int main(void)
13 {
14
15     char* s1 = nify("inconveniencing");
16     char* s2 = nify("neill");
17     assert(strcmp(s2, "Neill")==0);
18     assert(strcmp(s1, "iNcoNveNieNciNg")==0);
19     return 0;
20 }
21
22
23 // Local copy : Swaps all 'n' -> 'N'
24 char* nify(char s[])
25 {
26     char t[LINE];
27     strcpy(t, s);
28     for(int i=0; t[i]; i++){
29         if(t[i] == 'n'){
30             t[i] = 'N';
31         }
32     }
33     return t;
34 }
```

- Now we try to create a copy of the string, and return a pointer to it.
- With the usual compile flags we're told:
nify2.c: In function 'nify':
nify2.c:33:11: warning: function returns address of local variable [-Wreturn-local-addr]
33 | return t;
- The string t is local to nify().
- What happens in this memory when outside the scope of this function is completely undefined.

Static Variables

```
1 // A FAILED attempt to
2 // convert all 'n' chars to 'N'
3 #include <stdio.h>
4 #include <stdlib.h>
5 #include <string.h>
6 #include <assert.h>
7
8 #define LINE 500
9
10 char* nify(char s[]);
11
12 int main(void)
13 {
14     char* s1 = nify("inconveniencing");
15     char* s2 = nify("neill");
16     assert(strcmp(s2, "Neill")==0);
17     assert(strcmp(s1, "iNcoNveNieNciNg")==0);
18     return 0;
19 }
20
21 // Local copy : Swaps all 'n' -> 'N'
22 char* nify(char s[])
23 {
24     static char t[LINE];
25     strcpy(t, s);
26     for(int i=0; t[i]; i++){
27         if(t[i] == 'n'){
28             t[i] = 'N';
29         }
30     }
31     return t;
32 }
```

- We could just make the local string a static and return it's address couldn't we?
- This only works if we're very careful with the order in which we use the strings.
- This code fails because, in `main()`, by the time we `strcmp(s1, "iNcoNveNieNciNg")` the contents of `s1` have been overwritten by "Neill".
- The pointers `s1` and `s2` are the same.

Using *malloc()*

- We must use `malloc()` instead.
- `void* malloc(int n);`
allocates *n* bytes and returns a pointer to the allocated memory. The memory is not initialized.
- Now, when our function is called, a dedicated chunk of memory is allocated.
- This memory is always in scope until `free()` is used on it.
- We must free the memory somewhere though, otherwise memory leaks develop.
- We will see `calloc()` (and perhaps `realloc()`) later.

```
1  #include <stdlib.h>
2  #include <string.h>
3  #include <assert.h>
4
5  char* nify(char s[]);
6
7  int main(void)
8  {
9      char* s1 = nify("inconveniencing");
10     char* s2 = nify("neill");
11     assert(strcmp(s2, "Neill")==0);
12     assert(strcmp(s1, "iNcoNveNieNciNg")==0);
13     free(s1);
14     free(s2);
15     return 0;
16 }
17
18 // malloc : Swaps all 'n' -> 'N'
19 char* nify(char s[])
20 {
21     int l = strlen(s);
22     char* t = (char*)malloc(l+1);
23     if(t==NULL){
24         exit( EXIT_FAILURE );
25     }
26     strcpy(t, s);
27     for(int i=0; t[i]; i++){
28         if(t[i] == 'n'){
29             t[i] = 'N';
30         }
31     }
32     return t;
33 }
```

Variable Length Arrays

```
1 // This code is not allowed by the -Wvla flag
2 #include <stdio.h>
3 #include <stdlib.h>
4 #include <string.h>
5 #include <assert.h>
6
7 #define WORD 500
8
9 int main(void)
10 {
11     printf("Please type a string :\n");
12     char s[WORD];
13     assert(scanf("%s", s)==1);
14     int n = strlen(s) + 1;
15     char t[n];
16     // Deep copy: character by character
17     strcpy(t, s);
18     printf("%s %s\n", s, t);
19     return 0;
20 }
21
22 }
```

- Here we duplicate a string into *t*.
- This is known as a variable length array.
- However, we will always use the `-Wvla` with the compiler to prevent them.
- There are a number of reasons for this:
 - Some C++ compilers don't accept it.
 - The memory comes off the stack not the heap, and you have no idea if the allocation has worked (it'll just crash if not)
 - <https://nullprogram.com/blog/2019/10/27/>
- None of these is a problem if we use `malloc()`.

Memory Leaks

```
1 // This leaks - but it's not obvious
2 #include <stdio.h>
3 #include <stdlib.h>
4 #include <string.h>
5 #include <assert.h>
6
7 #define WORD 500
8
9 int main(void)
10 {
11
12     printf("Please type a string :\n");
13     char s[WORD];
14     assert(scanf("%s", s)==1);
15     int n = strlen(s);
16     /* malloc() returns a pointer to memory that
17        you have access to. Note forcing cast. */
18     char* t = (char*) malloc(n+1);
19     // If no space, returns NULL
20     assert(t != NULL);
21     // Deep copy: character by character
22     strcpy(t, s);
23     printf("%s %s\n", s, t);
24     return 0;
25 }
26 }
```

- This code appears to work correctly.
- However, it actually **leaks**. The memory allocated was never `free()`'d.
- This is best found by running the program `valgrind`.

```
String String
==474==
==474== HEAP SUMMARY:
==474==    in use at exit: 7 bytes in 1 blocks
==474==    total heap usage: 2 allocs, 1 frees, 1,031 bytes allocated
==474==
==474== LEAK SUMMARY:
==474==    definitely lost: 7 bytes in 1 blocks
```

free()

```
1  #include <stdio.h>
2  #include <stdlib.h>
3  #include <string.h>
4  #include <assert.h>
5
6  #define WORD 500
7
8  int main(void)
9  {
10
11     char s[WORD] = "String";
12     int n = strlen(s);
13     /* malloc() returns a pointer to memory that
14        you have access to. Note forcing cast. */
15     char* t = (char*) malloc(n+1);
16     /* If no space, returns NULL */
17     assert(t != NULL);
18     /* Deep copy: character by character */
19     strcpy(t, s);
20     printf("%s %s\n", s, t);
21     /* All malloc'd memory must be freed
22        to prevent memory leaks */
23     free(t);
24     return 0;
25 }
26 }
```

● This code is now correct.

String String

==475==

==475== HEAP SUMMARY:

==475== in use at exit: 0 bytes in 0 blocks

==475== total heap usage: 2 allocs, 2 frees, 1,031 bytes allocated

==475==

==475== All heap blocks were freed -- no leaks are possible

Structures with Self-Referential Pointers

```
1 // Store a list of numbers
2 #include <stdio.h>
3 #include <stdlib.h>
4 #include <assert.h>
5
6 struct data {
7     int num;
8     struct data* next;
9 };
10 typedef struct data data;
11
12 int main(void)
13 {
14     //      a      b      c
15
16     //      |11 -->|17 -->| 5 . |
17     data c = {5 , NULL};
18     data b = {17, &c};
19     data a = {11, &b};
20
21     // print first number
22     printf("%i\n", a.num);
23     data* p = &a;
24     // Can also get to it via p
25     printf("%i\n", p->num);
26     // Pointer chasing : The Key concept
27     p = p->next;
28     // We're accessing b, without using it's name
29     printf("%i\n", p->num);
30     p = p->next;
31     // And c
32     printf("%i\n", p->num);
33     return 0;
34 }
```

- The structure contains a pointer to a something of it's own type (even before we've fully defined the structure itself).
- Here, if p points to a, then p->next->next points to c.

Linked Lists

```
// Store a list of numbers (length unknown)
#include <stdio.h>
#include <stdlib.h>
#include <assert.h>

#define MAXNUM 20
#define ENDNUM 10

struct data {
    int num;
    struct data* next;
};
typedef struct data data;

void addtolist(data* tail);
void printlist(data* st);

int main(void)
{
    data *p, *start;
    start = p = calloc(1, sizeof(data));
    assert(p);
    p->num = rand()%MAXNUM;
    // Add other numbers to the list
    do{
        addtolist(p);
        p = p->next;
    }while(p->num != ENDNUM);
    printlist(start);
    // Need to free up list - not shown here ...
    return 0;
}
```

```
// Create some new space and store number in it
void addtolist(data* tail)
{
    tail->next = calloc(1, sizeof(data));
    assert(tail);
    tail = tail->next;
    tail->num = rand()%MAXNUM;
}

void printlist(data* st)
{
    while(st != NULL){
        printf("%i ", st->num);
        st = st->next;
    };
    printf("\n");
}
```

Execution :

3 6 17 15 13 15 6 12 9 1 2 7 10

- `calloc()` is similar to `malloc()`, but *clears* the memory it reserves for you. It's passed the number of array cells you wish to create, and the size of each of them.

Table of Contents

A: Preamble

B: Hello, World

C: Grammar

D: Flow Control

E: Functions

F: Data Types, Maths and Characters

G: Prettifying (New Types and Aliasing)

H : Constructed Types - 1D Arrays & Structures

I : Strings

J : 2D Arrays & More Types

K : Pointers

L : Advanced Memory Handling

M : Files

File Properties

- They have a name.
- Until a file is opened nothing can be done with it.
- After use a file must be closed.
- Files may be read, written or appended.
- Conceptually a file may be thought of as a stream of characters.

```
1  /* Creates a file called helloworld.txt
2  in the current filespace and writes to it */
3  #include <stdio.h>
4  #include <stdlib.h>
5
6  int main(void)
7  {
8      // Clobber the file if it exists already
9      FILE* fp = fopen("helloworld.txt", "w");
10     if(fp == NULL){
11         fprintf(stderr, "Cannot open file?\n");
12         exit(EXIT_FAILURE);
13     }
14     fprintf(fp, "Hello World!\n");
15     // fscanf() is also available to read in
16     fclose(fp);
17     return EXIT_SUCCESS;
18 }
```

Reading and Writing

```
1  #include <stdio.h>
2  #include <stdlib.h>
3  #include <string.h>
4  #define BIGSTR 500
5  #define FNAME "helloworld.txt"
6
7  int main(void)
8  {
9      FILE* fp = fopen(FNAME, "w");
10     if(fp == NULL){
11         fprintf(stderr, "Cannot open file %s ?\n", FNAME);
12         exit(EXIT_FAILURE);
13     }
14     fprintf(fp, "Hello World!\n");
15     fclose(fp);
16
17     fp = fopen(FNAME, "r");
18     if(fp == NULL){
19         fprintf(stderr, "Cannot read file %s ?\n", FNAME);
20         exit(EXIT_FAILURE);
21     }
22     char str[BIGSTR];
23     if(fgets(str, BIGSTR, fp) == NULL){
24         fprintf(stderr, "Cannot read 1st line of %s ?\n", FNAME);
25         exit(EXIT_FAILURE);
26     }
27     fclose(fp);
28     // Newline is read too
29     if(strcmp(str, "Hello World!\n")){
30         fprintf(stderr, "1st line of %s not correct?\n", FNAME);
31         exit(EXIT_FAILURE);
32     }
33     return EXIT_SUCCESS;
34 }
```

- If you write a file, it overwrites it from the beginning.
- You must `fclose()` your file pointers otherwise there is a memory leak.
- The statement `exit()` allows you to exit the code **anywhere**, not just in `main`.
- There are three files already open for you: `stdin`, `stdout` and `stderr`.
- Therefore `printf(...)` is just a shorthand for `fprintf(stdout, ...)`
- `fscanf()` could be used instead of `fgets()`.

- To write to screen you'd generally use stdout, so why is there stderr ?
- It's fairly common, when running a program, to want to redirect the output to a file.
- For instance, if you were to type:
 \$ ls > myfile.txt
 this will list all your files into myfile.txt
- The ">" at the prompt redirects the output (or "<" input) to file rather than screen.
- If something went wrong though, the user would never see the message.
- Therefore, stderr exists so that there is a stream to display warnings/errors to the user.

Interlude : argc/v

- A traditional C program has
`int main(int argc, char* argv[]);`
- `argc` is the number of words typed on the command line to execute the program.
- `argv` is an array of **pointers to chars** - i.e. an array of strings.
- This is not a traditional 2D array of characters - it's a 1D array of pointers - each string could be a different length.
- This is sometimes known as a ragged-right or jagged array.

```
1  #include <stdio.h>
2
3  int main(int argc, char* argv[])
4  {
5
6      printf("You typed %i arguments\n", argc);
7      printf("The name of your executable is : %s\n", argv[0]);
8      for(int i=1; i<argc; i++){
9          printf("Argument %d is : %s\n", i, argv[i]);
10     }
11
12     return 0;
13 }
```

Execution :

```
$ ./usingargs -c doof groob
You typed 4 arguments
The name of your executable is : ./usingargs
Argument 1 is : -c
Argument 2 is : doof
Argument 3 is : groob
```

Back to Files : One Character at a Time

```
1 // Some of the functionality of cp
2 #include <stdio.h>
3 #include <stdlib.h>
4
5 int main(int argc, char* argv[])
6 {
7     if(argc != 3){
8         fprintf(stderr, "Usage : %s <filein> <fileout>\n", argv[0]);
9         exit(EXIT_FAILURE);
10    }
11    FILE* fpin = fopen(argv[1], "r");
12    if(!fpin){
13        fprintf(stderr, "Cannot read from %s\n", argv[1]);
14        exit(EXIT_FAILURE);
15    }
16    FILE* fpout = fopen(argv[2], "w");
17    if(!fpout){
18        fprintf(stderr, "Cannot write to %s\n", argv[2]);
19        exit(EXIT_FAILURE);
20    }
21
22    char c;
23    while((c = fgetc(fpin)) != EOF){
24        fputc(c, fpout);
25    }
26    fclose(fpin);
27    fclose(fpout);
28    return EXIT_SUCCESS;
29 }
```

- This is a very basic version of the Linux command cp.
- fgetc() and fputc() are the file equivalents of getchar and putchar.
- How does a C program access arguments typed on the command line ?

Bulk Copying

- Copying one character at a time is very slow for large files.
- `fread()` and `fwrite()` will I/O many characters at once.
- Here we save an entire array to a binary file - another program could read this in later.

```
1  /* Compute some factorials and save them
2     for another program to read back later. */
3  #include <stdio.h>
4  #include <stdlib.h>
5
6  #define FACTS 20
7
8  typedef unsigned long facttype;
9
10 int main(int argc, char* argv[])
11 {
12     if(argc != 2){
13         fprintf(stderr, "Usage : %s <fileout>\n", argv[0]);
14         exit(EXIT_FAILURE);
15     }
16     FILE* fpout = fopen(argv[1], "wb");
17     if(!fpout){
18         fprintf(stderr, "Cannot write to %s\n", argv[1]);
19         exit(EXIT_FAILURE);
20     }
21     facttype facts[FACTS] = {1};
22     for(facttype i=1; i<FACTS; i++){
23         facts[i] = facts[i-1]*i;
24     }
25
26     int n = fwrite(facts, sizeof(facttype), FACTS, fpout);
27     if(n != FACTS){
28         fprintf(stderr, "Cannot write to %s\n", argv[1]);
29         exit(EXIT_FAILURE);
30     }
31     fclose(fpout);
32     return EXIT_SUCCESS;
33 }
```


Window/DOS vs. Unix Text Files

- Text files created on DOS/Windows machines have different line endings than files created on Unix/Linux.
- DOS uses *carriage return* and *line feed* ("\r\n") as a line ending.
- Unix uses just *line feed* ("\n").
- You should generally avoid assuming line endings - use a function that reads entire lines at once such as fgets().
- When you open a file in textmode fopen("file.txt", "rt") some automatic translation may be done on input/output.

```
1  #include <stdio.h>
2  #include <stdlib.h>
3  #include <string.h>
4
5  #define BIGSTR 10000
6
7  int main(int argc, char* argv[])
8  {
9      if(argc != 2){
10         fprintf(stderr, "Usage : %s <file>\n", argv[0]);
11         exit(EXIT_FAILURE);
12     }
13     FILE* fpin = fopen(argv[1], "rb");
14     if(!fpin){
15         fprintf(stderr, "Cannot read %s\n", argv[1]);
16         exit(EXIT_FAILURE);
17     }
18     char str[BIGSTR];
19     if(fgets(str, BIGSTR, fpin)==NULL){
20         fprintf(stderr, "Cannot read %s\n", argv[1]);
21         exit(EXIT_FAILURE);
22     }
23     int n = strlen(str);
24     if(n > 1){
25         if((str[n-1] == '\n') && (str[n-2] == '\r')){
26             printf("Looks like a DOS file?\n");
27         }
28         else{
29             printf("Looks like a Unix file?\n");
30         }
31     }
32     fclose(fpin);
33     return EXIT_SUCCESS;
34 }
```