


# Data Structures and Abstractions with Java™

5<sup>th</sup> Edition



## Java Interlude 4

## Iterators

# What Is an Iterator?

- An object that traverses a collection of data
- During iteration, each data item is considered once
  - Possible to modify item as accessed
- Should implement as a distinct class that interacts with the ADT

# The Java Interface Iterator

```
package java.util;
public interface Iterator<T>
{
    /** Detects whether this iterator has completed its traversal
    and gone beyond the last entry in the collection of data.
    @return True if the iterator has another entry to return. */
    public boolean hasNext();


    /** Retrieves the next entry in the collection and
    advances this iterator by one position.
    @return A reference to the next entry in the iteration,
    if one exists.
    @throws NoSuchElementException if the iterator had reached the
    end already, that is, if hasNext() is false. */
    public T next();

    /** Removes from the collection of data the last entry that
    next() returned. A subsequent call to next() will behave
    as it would have before the removal.
    Precondition: next() has been called, and remove() has not
    been called since then. The collection has not been altered
    during the iteration except by calls to this method.
    @throws IllegalStateException if next() has not been called, or
    if remove() was called already after the last call to next().
    @throws UnsupportedOperationException if the iterator does
    not permit a remove operation. */
    public void remove(); // Optional method
} // end Iterator
```

# The Java Interface `Iterator`

Entries in a collection:

Cursor positions:




© 2019 Pearson Education, Inc.


**FIGURE J4-1 Possible positions of an iterator's cursor within a collection**

# The Java Interface Iterator

(a) Before `next()` executes



(b) After `next()` returns *Jen*



(c) After a subsequent `remove()` deletes *Jen*




**FIGURE J4-2 Effect on a collection's iterator by a call to `next` and subsequent call to `remove`**

# The Interface `Iterable`

```
package java.lang;  
public interface Iterable<T>  
{  
    /** @return An iterator for a collection of objects of type T. */  
    Iterator<T> iterator();  
} // end Iterable
```


## LISTING JI5-2 The interface `java.lang.Iterable`

# Using the Java Interface Iterator



**FIGURE J4-3** The effect of the iterator methods **hasNext** and **next** on a list

# Using the Java Interface Iterator




© 2019 Pearson Education, Inc.

**FIGURE J4-4** The effect of the iterator methods **next** and **remove** on a list



# Using the Java Interface Iterator



© 2019 Pearson Education, Inc.

**FIGURE J4-5 Counting the number of times that Jane appears in a list of names**

# Multiple Iterators

```
Iterator<String> nameIterator = namelist.iterator();
while (nameIterator.hasNext())
{
    String currentName = nameIterator.next();

    int nameCount = 0;

    Iterator<String> countingIterator = namelist.iterator();
    while (countingIterator.hasNext())
    {
        String nextName = countingIterator.next();
        if (currentName.equals(nextName))
            nameCount++;

    } // end while

    System.out.println(currentName + " occurs " + nameCount + " times.");
} // end while
```

## Code that counts the occurrences of each name

## LISTING JI4-3 Java's interface `java.util.ListIterator` (Part 1)

```
package java.util;
public interface ListIterator<T> extends Iterator<T>
{
    /** Detects whether this iterator has gone beyond the last
     *  entry in the list.
     *  @return True if the iterator has another entry to return when
     *  traversing the list forward; otherwise returns false. */
    public boolean hasNext();

    /** Retrieves the next entry in the list and
     *  advances this iterator by one position.
     *  @return A reference to the next entry in the iteration,
     *  if one exists.
     *  @throws NoSuchElementException if the iterator is at the end,
     *  that is, if hasNext() is false. */
    public T next();

    /** Removes from the list the last entry that either next()
     *  or previous() has returned.
     *  Precondition: next() or previous() has been called, but the
     *  iterator's remove() or add() method has not been called
     *  since then. That is, you can call remove only once per
     *  call to next() or previous(). The list has not been altered
     *  during the iteration except by calls to the iterator's
     *  remove(), add(), or set() methods.
     *  @throws IllegalStateException if next() or previous() has not
     *  been called, or if remove() or add() has been called
     *  already after the last call to next() or previous().
     *  @throws UnsupportedOperationException if the iterator does not
     *  permit a remove operation. */
    public void remove(); // Optional method
}
```

These three methods are in the interface **Iterator**; they are duplicated here for reference and to show new behavior for **remove**.

## LISTING JI4-3 Java's interface `java.util.ListIterator` (Part 2)

```
/** Detects whether this iterator has gone before the first
entry in the list.
@return True if the iterator has another entry to visit when
traversing the list backward; otherwise returns false. */
public boolean hasPrevious();

/** Retrieves the previous entry in the list and moves this
iterator back by one position.
@return A reference to the previous entry in the iteration, if
one exists.
@throws NoSuchElementException if the iterator has no previous
entry, that is, if hasPrevious() is false. */
public T previous();

/** Gets the index of the next entry.
@return The index of the list entry that a subsequent call to
next() would return. If next() would not return an entry
because the iterator is at the end of the list, returns
the size of the list. Note that the iterator numbers
the list entries from 0 instead of 1. */
public int nextIndex();

/** Gets the index of the previous entry.
@return The index of the list entry that a subsequent call to
previous() would return. If previous() would not return
an entry because the iterator is at the beginning of the
list, returns -1. Note that the iterator numbers the
list entries from 0 instead of 1. */
public int previousIndex();
```


## LISTING JI4-3 Java's interface `java.util.ListIterator` (Part 3)

```
/** Adds an entry to the list just before the entry, if any,
that next() would have returned before the addition. This
addition is just after the entry, if any, that previous()
would have returned. After the addition, a call to
previous() will return the new entry, but a call to next()
will behave as it would have before the addition.
Further, the addition increases by 1 the values that
nextIndex() and previousIndex() will return.
@param newEntry An object to be added to the list.
@throws ClassCastException if the class of newEntry prevents the
addition to the list.
@throws IllegalArgumentException if some other aspect of
newEntry prevents the addition to the list.
@throws UnsupportedOperationException if the iterator does not
permit an add operation. */
public void add(T newEntry); // Optional method

/** Replaces the last entry in the list that either next()
or previous() has returned.
Precondition: next() or previous() has been called, but the
iterator's remove() or add() method has not been called since then.
@param newEntry An object that is the replacement entry.
@throws ClassCastException if the class of newEntry prevents the
addition to the list.
@throws IllegalArgumentException if some other aspect of newEntry
prevents the addition to the list.
@throws IllegalStateException if next() or previous() has not been called,
or if remove() or add() has been called already
after the last call to next() or previous().
@throws UnsupportedOperationException if the iterator does not permit a set operation. */
public void set(T newEntry); // Optional method
} // end ListIterator
```


# Using the Java Interface `ListIterator`

(a) Before `previous()`



© 2019 Pearson Education, Inc.


(b) After `previous()` returns *Joey*



© 2019 Pearson Education, Inc.

**FIGURE J4-6 The effect of a call to `previous` on a list**

# Using the Java Interface `ListIterator`



© 2019 Pearson Education, Inc.

**FIGURE J4-7** The indices returned by the methods `nextIndex` and `previousIndex`

# The Interface `List` Revisited

- Method `set` replaces entry that either `next` or `previous` just returned.
- Method `add` inserts an entry into list just before iterator's current position
- Method `remove` removes list entry that last call to either `next` or `previous` returned



End

# Java Interlude 4