

# ZLK38AVS Microsemi AcuEdge™ Development Kit for Amazon AVS Preliminary Product Brief

Microsemi's AcuEdge™ ZLK38AVS development kit for Amazon AVS features Microsemi's ZL38063 Timberwolf audio processor. The ZL38063 provides a number of audio enhancements to improve trigger word detection and to enhance Amazon's AVS detection and accuracy. Additionally, the ZL38063 expands the functionality by including 2-way voice communication that provides exceptional speaker phone quality. The kit is designed to help developers quickly and easily prototype and demonstrate high quality voice recognition interfaces. The ZL38063 provides audio enhancements that perform both noise reduction and barge-in processing. The noise reduction allows speech recognition in noisy, real-world condition. Barge-in allows users to interrupt their Alexa device when playing audio.

The ZLK38AVS supports a two microphone configuration for both 180° and 360° audio pick-up. The kit is designed to recognize the Alexa wake word and deliver audio-enhanced speech requests for cloud processing in adverse audio environments.

The ZLK38AVS development kit for Amazon AVS reduces engineering time and costs associated with developing a noise-robust, voice-enabled device.

The ZLK38AVS development kit is compatible with the Amazon AVS application for the Raspberry Pi (RPi).

### **Highlights**

- High-quality stereo acoustic echo canceller for barge-in and full duplex audio
- Fully configurable and scalable solution delivering a two microphone configuration for both 180° and 360° audio pick-up
- Enhanced beam forming technology to enhance audio pick-up in adverse conditions, in presence of noise and outside sound sources
- 2-way full duplex voice communication
- Turnkey designs available as well as all appropriate drivers and documentation, along with worldwide support

### **Applications**

Voice-enabled applications such as:

- Home Gateway/Controller
- Speaker/Sound Bar
- TV/Set-Top Box





## ZLK38AVS Microsemi AcuEdge™ Development Kit for Amazon AVS

### **Preliminary Product Brief**

### Kit Contents

Microsemi AcuEdge™ development kit for Amazon AVS includes the following:

- ZLE38AVS evaluation board
- Pillar (Plastics)
- · Assembly hardware
- Documentation

To make a fully assembled smart speaker demo the following additional components are required (not included in the ZLK380AVS kit)

- Raspberry Pi 3 board
- 2A or greater Micro-USB power supply for the Raspberry Pi 3
- SD memory card for Raspberry Pi
- JBL Clip speaker

### **Fully Assembled Smart Speaker**



### **ZLK38AVS Development Kit Specifications**

### **Physical Characteristics**

Dimensions	70 mm × 66 mm
Operating temperature	–40° C to 85° C

#### **External Interfaces**

Raspberry Pi 3 Header	P2: • I <sup>2</sup> S port • SPI • 8 GPIO	
Audio Header	JMMA1:  • Digital microphones  • Analog out  • 3 GPIO	
SPI Flash Devices	U2: Optional SPI flash component used to store ZL38063 firmware	
USB	J3: Optional USB power and debug port	
Debug Headers	JAIB2/2: Auto tuning headers	
Digital Microphone Headers	JM1-4: Optional header for off-board microphones	

### **Audio Characteristics**

Digital Microphones	4 on-board digital microphones (AKU441): Supports a 2 microphone configuration for 180° and 360° audio pick-up
Analog Output	J1: $2 \times 2.65$ Low cost class D audio amplifier (NCP2820)

### **Connectors**

Stereo 3.5 mm male-to-male audio cable	P1: Audio output	
Micro-USB cable	J3: Optional USB power and debug port	

### **Ordering Information**

Distributor	URL	Part Number	Description
Arrow Electronics	www.arrow.com	ZLK38AVS	Development Kit, for Amazon AVS
Future Electronics	www.futureelectronics.com	ZLK38AVS	Development Kit, for Amazon AVS



#### Microsemi Corporate Headquarters

One Enterprise, Aliso Viejo, CA 92656 USA Within the USA: +1 (800) 713-4113 Outside the USA: +1 (949) 380-6100 Fax: +1 (949) 215-4996 Email: sales.support@microsemi.com www.microsemi.com

©2017 Microsemi Corporation. All rights reserved. Microsemi and the Microsemi logo are registered trademarks of Microsemi Corporation. All other trademarks and service marks are the property of their respective owners. Microsemi Corporation (Nasdaq: MSCC) offers a comprehensive portfolio of semiconductor and system solutions for aerospace & defense, communications, data center and industrial markets. Products include high-performance and radiation-hardened analog mixed-signal integrated circuits, FPGAs, SoCs and ASICs; power management products; timing and synchronization devices and precise time solutions, setting the world's standard for time; voice processing devices; RF solutions; discrete components; enterprise storage and communication solutions, security technologies and scalable anti-tamper products; Ethernet solutions; Power-over-Ethernet ICs and midspans; as well as custom design capabilities and services. Microsemi is headquartered in Aliso Viejo, California and has approximately 4,800 employees globally. Learn more at www.microsemi.com.

Microsemi makes no warranty, representation, or guarantee regarding the information contained herein or the suitability of its products and services for any particular purpose, nor does Microsemi assume any liability whatsoever arising out of the application or use of any product or circuit. The products sold hereunder and any other products sold by Microsemi have been subject to limited testing and should not be used in conjunction with mission-critical equipment or applications. Any performance specifications are believed to be reliable but are not verified, and Buyer must conduct and complete all performance and other testing of the products, alone and together with, or installed in, any end-products. Buyer shall not rely on any data and performance specifications or parameters provided by Microsemi. It is the Buyer's responsibility to independently determine subability of any products and to test and verify the same. The information provided by Microsemi hereunder is provided "as is, where is" and with all faults, and the entire risk associated with such information is entirely with the Buyer. Microsemi does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other IP rights, whether with regard to such information itself or anything described by such information. Information provided in this document is proprietary to Microsemi, and Microsemi reserves the right to make any changes to the information in this document or to any products and services at any time without notice.