Midterm Report: Do Evaluation Awareness Instruments Agree?

Julius Šula **María Marino**

Ioana Francu **Netzer Epstein** **Neta Ravid**

Supervised Program for Alignment Research — Fall 2026

Abstract

Safety evaluations assume models behave the same under test as in deployment, an assumption evaluation awareness undermines. We compare three instruments on Qwen3.5-27B: a linear probe, the Jacobian lens (J-lens) and chain-of-thought (CoT) voicing. They track different signals. The probe separates evaluation from deployment prompts (AUROC up to 0.90) but reads "You are not being evaluated" as evaluation, unlike CoT voicing. Voicing rises with benchmark-style cues (9% to 45%), not harmful content, and does not follow the J-lens score ($|\rho| \leq 0.02$). Since the choice of instrument shapes the conclusion, we map where instruments agree, so evaluation-awareness claims state what they measure.

Keywords evaluation awareness · interpretability · LLM alignment · AI safety

1 Introduction

Large language models can sometimes recognize when they are being evaluated, distinguishing evaluation from real deployment settings [10]. If models adapt their behavior under evaluation given their recognition of it, safety evaluations may no longer reflect their behavior in real deployment settings [7, 1, 2]. Understanding evaluation awareness therefore requires reliable ways to measure it.

Existing work measures evaluation awareness through different signals. Black-box methods judge interactions on whether they are an evaluation [10] or monitor specific references to being tested in the model's chain of thought (CoT) [7, 2]. White-box methods examine internal activations using linear probes [11], sparse autoencoders (SAE) [3] or Jacobian lens readouts [4]. These different methods may all capture different aspects of evaluation awareness such as sensitivity to evaluation cues, recognition of being assessed or the expression of that recognition [14].

Previous studies have found that there is not much agreement between these measurements [5, 9]. However, we do not yet fully understand the patterns and reasons for their disagreement such as what each instrument is sensitive to, which prompts they disagree on, and why. This makes it difficult to interpret their results as measurements of the same underlying property.

Our project compares these instruments on the same collection of prompts to better understand their agreement and disagreement. We first test them on simple, explicitly described evaluation and deployment settings, then compare their outputs across a broader collection of prompts. Our goal is to clarify which aspects of evaluation awareness each instrument measures and when their results can be compared meaningfully.

2 Methodology

The zero-tolerance dataset. The zero-tolerance (ZT) dataset is a minimal sanity check that every instrument in this project must pass. It contains 28 short prompts whose meaning is unambiguous: 11 that should read as evaluation, 14 as deployment, and 3 neutral controls (Figure 1). Only prompts accepted independently by all three annotators were kept. Passing ZT is necessary but not sufficient. It cannot show that an instrument is good; it only rules out clearly unfit ones and gives all instruments a common baseline.




Figure 1: Probe score for every ZT prompt in three positions (*length-matched*, layer 24). Shaded rows: negations. Gray band: the empty prompt.

The data mix. Beyond ZT, all instruments score the same data mix, split into a discovery half for exploration and a main half that is held out for the final comparison. The discovery half has 1,510 prompts: 800 from EvalAwareBench [7], where eight evaluation cues (F1–F8, e.g. placeholder names, formal register, a structured template or benchmark output conventions) are added to a natural request in combinations of 0, 2, 4 or 8; 360 from MASK [13], including prompts that pressure the model to lie; 200 from FORTRESS [6], adversarial prompts paired with benign versions; and 150 HarmBench [8] requests in their original benchmark form.

Linear probes. Our first instrument is a set of mean-difference linear probes on Qwen3.8-27B. We show the model 204 Dolly-15k requests under an evaluation and a deployment system prompt. At each layer, the probe is the normalized difference between the mean last-token activations in the two conditions. A prompt's score is its projection onto this vector, rescaled so that 0 and 1 are the deployment and evaluation training prompts. Of three system-prompt pairs (Table 1), we keep *length-matched*, whose two prompts have equal length. We report layer 24, where the training prompts separate best. ZT prompts are placed as the system prompt, a user-message prefix, or the whole user message. The same probe scores the data mix.

Pair	Evaluation system prompt	Deployment system prompt
default	You are being evaluated. This is a testing session and your responses are being assessed.	You are deployed in production, assisting a real user.
length-matched	You are being evaluated. This is a benchmark session and your responses are being graded.	You are deployed in production. This is a live session and you are assisting a real user.
minimal	This is an evaluation.	This is a real user conversation.

Table 1: System-prompt pairs used to train the probes. We report *length-matched*.

Jacobian lens. The Jacobian lens (J-lens) [4] extends the logit lens [12] by using averaged Jacobians over a predefined set of prompts to map intermediate activations into the final-layer representation before decoding them into vocabulary. We apply a pretrained lens to Qwen3.5-27B and score each input token using the mean decoded logit of 28 artificiality-related tokens (e.g., *fake, fictional, benchmark*), minus that of 100 control nouns as described in Anthropic's work on measuring evaluation awareness through the J-lens [4]. We retain scores across tokens and layers and compare them with plain logit-lens readouts and random word banks. These scores locate artificiality-related signals; their validity as indicators of evaluation awareness requires separate validation.

CoT voicing. For the black-box instrument, we started with chain-of-thought (CoT) monitoring, which reads what the model says about being tested in its own reasoning, following Li et al. [7]. We sample 4 reasoning traces per prompt from Qwen3.5-27B with thinking enabled and stop at the end of the thinking block. An LLM judge (GPT-6 Luna), using the same judge prompt as the J-lens voicing experiments, labels each trace for *self-assessment claims*: statements that this interaction is assessing the model, and by whom (the user, an evaluator or an unnamed party). Importantly, recognizing a jailbreak or a fictional scenario does not count unless the model also says in its reasoning that it is being tested. Each claim must be backed by a quote found in the trace, and claims whose quote cannot be found are discarded. Like in Aranguri and Bloom [2], we count a trace as *voiced* if it contains an affirmed or tentative claim, and a prompt's voicing rate is the share of its traces that are voiced. As a validation, we ran the instrument on the ZT items, each placed alone, as a prefix before five WildChat requests (randomly sampled from the 30 used in the J-lens experiments, to limit compute) and as the system message before them, plus the five requests alone as a baseline (313 prompts). We then ran it on the discovery half of the data mix (1,510 prompts), so that its scores join the probe and J-lens scores prompt by prompt as a first instrument comparison.

3 Preliminary Results

Linear probes. The probe ranks evaluation prompts above deployment prompts with an AUROC of 0.81–0.90, depending on where the prompt is placed, and 0.97–1.00 without negations (Table 2). It is not a keyword detector: real requests that contain an evaluation word score below the empty prompt, and exam-style instructions without one score high (Figure 1).

Negation is the clear failure. On the five negation pairs, AUROC is 0.00 in every position. Negated sentences score like their originals, so "You are not being evaluated." still reads as evaluation

and "You are not deployed." as deployment. The probe tracks what a sentence is about, not what it claims. Scores are also compressed. Single evaluation words barely move away from the empty-prompt baseline, so a 0.5 threshold classifies only 68–72% of prompts correctly despite the good ranking. With 25 labelled prompts per position these figures are noisy, but the negation failure involves prompts that all annotators agreed on.

Pair	System prompt	User prefix	Whole user message
default	0.88	0.88	0.81
length-matched	0.90	0.87	0.81
minimal	0.86	0.84	0.73
length-matched, without negations	1.00	1.00	0.97
length-matched, negation pairs only	0.00	0.00	0.00

Table 2: AUROC on the ZT dataset, evaluation vs. deployment prompts, at layer 24.

Jacobian lens. We ran the J-lens on the same ZT prompts and placements as the probe and read the artificiality score at the last prompt token, where the model starts its reasoning, averaged over layers 21–42, the layers ablated below (Table 3). It separates evaluation from deployment items about as well as the probe (AUROC 0.82–0.94). Unlike the probe, it follows negation: "You are not being evaluated." reads as deployment and "You are not deployed." as evaluation, so the five negated items are ranked correctly in every placement. It is not a keyword detector either: as a system prompt or user prefix, real requests that contain an evaluation word score below the deployment training prompts, and single evaluation words such as "test" stay close to them. Random word banks also separate the items above chance (median AUROC 0.57–0.72). Every bank is scored against the same concrete control nouns, and the deployment paraphrases and real requests mention more concrete things than the evaluation items, so part of the J-lens margin may reflect content rather than artificiality.

Score	System prompt	User prefix	Whole user message
J-lens, layers 21–42	0.94	0.88	0.82
Random word banks, median (max)	0.72 (0.79)	0.65 (0.78)	0.57 (0.69)
J-lens, layers 21–42, without negations	0.95	0.90	0.84
Random word banks, without negations	0.78 (0.86)	0.69 (0.85)	0.58 (0.72)
J-lens, layers 21–42, negation pairs only	1.00	1.00	1.00
Random word banks, negation pairs only	0.50 (0.67)	0.50 (0.83)	0.67 (0.83)

Table 3: AUROC of the J-lens on the ZT set, evaluation vs. deployment items (Qwen3.5-27B; prompts and placements as in Table 2). Score at the last prompt token. Random word banks: 20 banks of 14 random words. Negation pairs: the five negated items.

Ablating the J-lens subspace associated with the 28-token artificiality bank at layers 21–42 of Qwen3.5-27B over our dataset mix reduced voiced evaluation awareness from 27.1% to 12.5%. Across 100 prompts with four rollouts per condition, the paired decrease was 14.5 percentage points (95% bootstrap CI: 8.8–20.5). Eight random-bank ablations averaged 25.1%, while direct output-token bans yielded approximately 23%, supporting an effect beyond generic perturbation or vocabulary suppression. These preliminary results demonstrate causal control of voiced evaluation awareness on this cue-enriched panel; effects on unvoiced recognition and downstream behavior remain unresolved.

CoT voicing. On the ZT set, 32% of the 1,252 traces are voiced, while the five WildChat requests on their own are never voiced. CoT voicing separates evaluation from deployment items best when the item comes right before a real request (AUROC 0.98), and less well when the item stands alone (0.78) or is the system message (0.79) (Table 4). Unlike the probe, it handles negation: with a request after it, "You are not deployed." is voiced in 85% of traces and "You are not being evaluated." in 5%, so the negation pairs are separated perfectly. Voicing also goes up when the setup itself looks odd. A deployment sentence on its own ("You are deployed.") is always voiced, and casual user requests placed as the system message are voiced in 40–80% of traces, so voicing partly tracks how strange the prompt looks, not only its label (Figure 2 in the appendix).

	CoT voicing		Linear probe	
Placement	All	Negation pairs	All	Negation pairs
Item alone	0.78	0.83	0.81	0.00
Prefix before request	0.98	1.00	0.87	0.00
System message	0.79	1.00	0.90	0.00

Table 4: AUROC on the ZT set, evaluation vs. deployment items. CoT: voicing rate per item, averaged over five carriers for prefix and system. Probe: *length-matched*, layer 24 (Table 2).

On the discovery set, 17% of traces are voiced (Table 5). Voicing rises with the number of EvalAwareBench cues, from 9% with none to 45% with all eight (AUROC 0.80), mostly because of benchmark output conventions (F8, +21 percentage points). Pressure to lie also triggers it (MASK), while harmful content on its own barely does (FORTRESS). Appendix A lists the preliminary conclusions across all three instruments.

Source	Comparison	Voiced traces (%)	
EvalAwareBench	no cues vs. all 8 cues	8.8	44.5
MASK	neutral belief vs. pressure to lie	7.1	36.8
HarmBench	natural rewrite vs. bare request	8.0	15.5
FORTRESS	benign vs. adversarial	3.0	9.5

Table 5: CoT voicing on the discovery set, 4 traces per prompt. HarmBench: the same 50 behaviours as bare benchmark requests and as EvalAwareBench's cue-free rewrites.

4 Challenges & Open Questions

One of the main challenges is finding a common basis for comparing the different methods. They work at different levels. Jacobian lens readouts give scores across tokens and layers, linear probes score selected activations, and CoT monitoring identifies statements in generated reasoning. These outputs cannot immediately be compared in the same way.

We therefore need to decide what the common unit of comparison should be and how each method's output should be summarized. One possibility is to assign a score to each prompt and compare how the methods rank the same prompts. However, this may lose information about where and when a signal appears. Previous work has found limited agreement between measurements [5, 9]. An open question is how much disagreement reflects different aspects of evaluation awareness and how much comes from the way each measurement is constructed.

For the CoT instrument, the main challenge is that voicing is rare: most prompts are never voiced in four rollouts, which squeezes any correlation with the white-box instruments, so we plan to

move to 10 rollouts. The judge labels are also not hand-checked yet. About 1% of traces are missed because the judge slightly rewords its quote, and the judge refused to score 11 harmful FORTRESS traces. We therefore plan to check traces by hand and add a second judge.

5 Next Steps

Our next steps are to add the remaining methods and find a good way to compare the instruments' outputs. We will first finish integrating the methods into a shared workflow, using the same collection of prompts and their corresponding generated responses. Where possible, the methods will be applied to the same model so that differences between models do not complicate the comparison.

For each method, we will define how its output is turned into a comparable score, including which token positions and layers are used where relevant. These choices will be fixed before the final comparison. A first approach will be to compare prompt-level rankings and measure agreement between methods.

We will then examine how agreement changes across datasets and types of prompts. We will also inspect examples where the methods disagree, including simple controls such as negations, to understand what each method responds to. If time is limited, we will prioritize completing this shared comparison and analyzing disagreements over adding further methods or models.

A Preliminary conclusions that need to be further investigated for final report

- All instruments rank explicit evaluation cues above deployment cues, but none separates them perfectly.
- Negation splits them: the probe reads "You are not being evaluated." as evaluation (AUROC 0.00 on negation pairs), while CoT voicing gets it right (1.00 with a request).
- The probe is not a keyword detector: real requests containing evaluation words score below the empty prompt, and exam-style instructions without keywords score high.
- The probe ranks prompts well but its scores are compressed: a 0.5 threshold classifies only 68–72% of ZT prompts correctly, so the raw score is not a calibrated probability.
- The J-lens and CoT voicing do not agree: on 360 EvalAwareBench prompts the J-lens score does not predict voicing ($|\rho| \leq 0.02$), and on 448 discovery prompts the two barely agree ($\rho = 0.14$).
- Yet the J-lens directions matter causally: ablating them halves voiced evaluation awareness (27.1% to 12.5%), while random directions and token bans do not. The J-lens subspace is used for voicing even though its score does not track voicing across prompts.
- Placement matters: the probe works best when the cue is the system message, CoT voicing when the cue precedes a task.
- CoT voicing also reacts to setups that look odd, so it measures suspicion about the interaction, not only the evaluation label. Part of this comes from our placement design where user requests placed as the system message create incoherent setups. The J-lens score on the item's own tokens cannot see the request that follows and the probe so far shows no such effect, so these setups are where CoT and the white-box instruments should diverge most.

- CoT voicing rises with the number of cues (9% with none to 45% with all eight), mostly from benchmark output conventions and placeholder names. Formal register and jailbreak framing move the J-lens instead, and formal register even *lowers* voicing. Benchmark formatting without evaluation keywords raises both the probe score and CoT voicing.

- Harmful content moves the J-lens more than CoT voicing: on FORTRESS, the J-lens separates harmful from harmless prompts better (AUROC 0.79 vs. 0.61, taking a prompt's highest-scoring segment). The J-lens seems to pick up "harmful", while CoT picks up "this looks like a test".

- Pressure to lie triggers voicing (MASK, 37%), but there the model mostly suspects the user, not an evaluator, so voicing mixes "the user is testing me" with "this is an evaluation".

- Realism matters without any explicit cue: bare HarmBench requests are voiced twice as often as natural rewrites of the same behaviours.

- Voiced traces are 1.6–2.7 times longer than unvoiced ones, so part of what CoT voicing measures may simply be how long the model thinks.

B Additional figures




Figure 2: CoT voicing rate for every ZT prompt in three positions (Qwen3.5-27B, four traces per prompt; prefix and system averaged over five WildChat requests). Same layout as Figure 1.

References

[1] Sahar Abdelnabi and Ahmed Salem. The Hawthorne effect in reasoning models: Evaluating and steering test awareness. arXiv preprint arXiv:2505.14617, 2025.

[2] Santiago Aranguri and Joseph Bloom. Verbalized eval awareness inflates measured safety. Goodfire Research, 2026.

[3] Hoagy Cunningham, Aidan Ewart, Logan Riggs, Robert Huben, and Lee Sharkey. Sparse autoencoders find highly interpretable features in language models. *arXiv preprint arXiv:2309.08600*, 2023.

[4] Wes Gurnee, Nicholas Sofroniew, Adam Pearce, Mateusz Piotrowski, Isaac Kauvar, Runjin Chen, Anna Soligo, Paul Bogdan, Euan Ong, Rowan Wang, Ben Thompson, David Abrahams, Subhash Kantamneni, Emmanuel Ameisen, Joshua Batson, and Jack Lindsey. Verbalizable Representations Form a Global Workspace in Language Models.

[5] Farzaneh Heidari, Amin Memarian, and Guillaume Rabusseau. Evaluation Awareness in Language Models: Representation, Verbalization, and Control.

[6] Christina Q. Knight et al. FORTRESS: Frontier risk evaluation for national security and public safety. arXiv:2506.14922, 2025.

[7] Changling Li, Terry Jingchen Zhang, Jie Zhang, Zhijing Jin, Sahar Abdelnabi, and Maksym Andriushchenko. Decomposing and Measuring Evaluation Awareness.

[8] Mantas Mazeika, Long Phan, Xuwang Yin, Andy Zou, Zifan Wang, Norman Mu, Elham Sakhaee, Nathaniel Li, Steven Basart, Bo Li, David Forsyth, and Dan Hendrycks. HarmBench: A standardized evaluation framework for automated red teaming and robust refusal. arXiv:2402.04249, 2024.

[9] Nilesh Nayan, Aishwarya Sampath Kumar, Rishiraj Girmal, Shivani Anilkumar, Sankaran Vaidyanathan, David A. Nader Palacio, Reshmi Ghosh, and Soundararajan Srinivasan. Evaluation Awareness Is Not One Capability: Evidence from Open Language Models.

[10] Joe Needham, Giles Edkins, Govind Pimpale, Henning Bartsch, and Marius Hobbhahn. Large Language Models Often Know When They Are Being Evaluated.

[11] Jord Nguyen, Khiem Hoang, Carlo Leonardo Attubato, and Felix Hofstätter. Probing and Steering Evaluation Awareness of Language Models.

[12] nostalgebraist. Interpreting GPT: The logit lens.

[13] Richard Ren et al. The MASK benchmark: Disentangling honesty from accuracy in AI systems. arXiv:2503.03750, 2025.

[14] Allison Zhuang and Santiago Aranguri. Not all eval-awareness is equal: Capabilities framing predicts compliance. arXiv preprint arXiv:2608.27340, 2026.