

PROGRAMMING IN PYTHON I

Data Structures



Andreas Schörgenhumer
Institute for Machine Learning

Copyright Statement

This material, no matter whether in printed or electronic form, may be used for personal and non-commercial educational use only. Any reproduction of this material, no matter whether as a whole or in parts, no matter whether in printed or in electronic form, requires explicit prior acceptance of the authors.

Contact

Andreas Schörgenhumer

Institute for Machine Learning
Johannes Kepler University
Altenberger Str. 69
A-4040 Linz

E-Mail: schoergenhumer@ml.jku.at

Write mails only for personal questions

[Institute ML Homepage](#)

GROUPING VALUES



Motivation

- Often we want to handle a **group of values**
 - E.g.: Group of names, measurements, etc.

Motivation

- Often we want to handle a **group of values**
 - E.g.: Group of names, measurements, etc.
- We could handle each value as separate variable but this would get tedious and complicated:

```
var1 = 1  
var2 = 2  
var3 = 3  
var4 = 4  
...
```

Motivation

- Often we want to handle a **group of values**
 - E.g.: Group of names, measurements, etc.
- We could handle each value as separate variable but this would get tedious and complicated:

```
var1 = 1
var2 = 2
var3 = 3
var4 = 4
...
```

- Instead, we want to have **one variable as reference to the group of values**:

```
var = [1, 2, 3, 4, ...]
```

- We can then retrieve individual values via `var`

Motivation

- Often we want to handle a **group of values**
 - E.g.: Group of names, measurements, etc.
- We could handle each value as separate variable but this would get tedious and complicated:

```
var1 = 1
var2 = 2
var3 = 3
var4 = 4
...
```

- Instead, we want to have **one variable as reference to the group of values**:

```
var = [1, 2, 3, 4, ...]
```

- We can then retrieve individual values via `var`
- Group of values is a **data structure**

DATA STRUCTURES



Data Structures

■ Sequence types

- ☐ **Ordered list** (=sequence) of values
- ☐ Position of values (=index) in sequence is used to access a value
- ☐ Python: List, tuple, string, ...

Data Structures

■ Sequence types

- ☐ **Ordered list** (=sequence) of values
- ☐ Position of values (=index) in sequence is used to access a value
- ☐ Python: List, tuple, string, ...

■ Unordered collections

- ☐ **Unordered set** of unique elements
- ☐ Python: Set

Data Structures

■ Sequence types

- ☐ **Ordered list** (=sequence) of values
- ☐ Position of values (=index) in sequence is used to access a value
- ☐ Python: List, tuple, string, ...

■ Unordered collections

- ☐ **Unordered set** of unique elements
- ☐ Python: Set

■ Mapping types

- ☐ Group of **key-value pairs**
- ☐ Unique keys are used to access values
- ☐ Key-value pairs **might be unordered**
- ☐ Python: Dictionary, ...

Data Structures

■ Sequence types

- ☐ **Ordered list** (=sequence) of values
- ☐ Position of values (=index) in sequence is used to access a value
- ☐ Python: List, tuple, string, ...

■ Unordered collections

- ☐ **Unordered set** of unique elements
- ☐ Python: Set

■ Mapping types

- ☐ Group of **key-value pairs**
- ☐ Unique keys are used to access values
- ☐ Key-value pairs **might be unordered**
- ☐ Python: Dictionary, ...

■ Python takes care of growing data structures for you

Lists (1)

- In Python, a list is the **most versatile sequence type**

Lists (1)

- In Python, a list is the **most versatile sequence type**
- It is created using square brackets containing comma-separated values (=items or elements):

```
my_list = ["some item", "b", 5463, 5.24]
```

Lists (1)

- In Python, a list is the **most versatile sequence type**
- It is created using square brackets containing comma-separated values (=items or elements):

```
my_list = ["some item", "b", 5463, 5.24]
```
- It can contain **items of variable data types**

Lists (1)

- In Python, a list is the **most versatile sequence type**
- It is created using square brackets containing comma-separated values (=items or elements):

```
my_list = ["some item", "b", 5463, 5.24]
```
- It can contain **items of variable data types**
- The **order of items is preserved**

Lists (1)

- In Python, a list is the **most versatile sequence type**
- It is created using square brackets containing comma-separated values (=items or elements):

```
my_list = ["some item", "b", 5463, 5.24]
```
- It can contain **items of variable data types**
- The **order of items is preserved**
- The index of the items is used to access them:

```
my_list[1] # Returns value "b"
```

Lists (1)

- In Python, a list is the **most versatile sequence type**
- It is created using square brackets containing comma-separated values (=items or elements):

```
my_list = ["some item", "b", 5463, 5.24]
```

- It can contain **items of variable data types**
- The **order of items is preserved**
- The index of the items is used to access them:

```
my_list[1] # Returns value "b"
```

- Important: **Indices in Python are integers and start at 0!**

Lists (2)

- Python lists are **mutable**

→ We can add, modify and delete the items in the list

Lists (2)

- Python lists are **mutable**
 - We can add, modify and delete the items in the list
- Python lists can contain all kinds of objects (also mixed)

Lists (2)

- Python lists are **mutable**
 - We can add, modify and delete the items in the list
- Python lists can contain all kinds of objects (also mixed)
- Python lists **can be nested**, i.e., contain other lists:

```
my_list = [23, "367", ["trh", 5], 6.35]  
my_list[2] # Returns ["trh", 5]
```

Tuples

- Another example of a **sequence data type** in Python

Tuples

- Another example of a **sequence data type** in Python
- Tuples are created via a number of values, separated by commas

```
my_tuple = 42, "a string", 346.345  
my_tuple = (42, "a string", 346.345)
```


Tuples

- Another example of a **sequence data type** in Python
- Tuples are created via a number of values, separated by commas

```
my_tuple = 42, "a string", 346.345  
my_tuple = (42, "a string", 346.345)
```

- Tuples are **similar to lists but immutable**
 - Once a tuple is created, it cannot be changed anymore!

```
my_tuple[1] = 5 # This would fail
```
 - It is possible to create tuples with mutable objects, e.g., lists

Sets

- Sets are **unordered** collections of **unique** elements

Sets

- Sets are **unordered** collections of **unique** elements
- In Python, a set is created using `set()` (required for an empty set) or with curly braces that include at least one element:

```
my_set = set() # Creates an empty set  
my_set = {"hi", 12, 123}
```

Sets

- Sets are **unordered** collections of **unique** elements
- In Python, a set is created using `set()` (required for an empty set) or with curly braces that include at least one element:

```
my_set = set() # Creates an empty set  
my_set = {"hi", 12, 123}
```

- Common set operations are supported:
 - ☐ Union: `set1 | set2`
 - ☐ Intersection: `set1 & set2`
 - ☐ Difference: `set1 - set2`
 - ☐ ...

Dictionaries: Motivation

- Imagine you want to implement a phone book, i.e., associate a name with a phone number

Dictionaries: Motivation

- Imagine you want to implement a phone book, i.e., associate a name with a phone number
- You could store the phone number in a list

Dictionaries: Motivation

- Imagine you want to implement a phone book, i.e., associate a name with a phone number
- You could store the phone number in a list
- You have to remember whose number is at which position

Dictionaries: Motivation

- Imagine you want to implement a phone book, i.e., associate a name with a phone number
- You could store the phone number in a list
- You have to remember whose number is at which position
- Could use a second list of names with same order

Dictionaries: Motivation

- Imagine you want to implement a phone book, i.e., associate a name with a phone number
- You could store the phone number in a list
- You have to remember whose number is at which position
- Could use a second list of names with same order
 - Tedious to use and maintain!

Dictionaries: Motivation

- Imagine you want to implement a phone book, i.e., associate a name with a phone number
- You could store the phone number in a list
- You have to remember whose number is at which position
- Could use a second list of names with same order
 - Tedious to use and maintain!
- It would be better to use the names as indices to the phone number, i.e., to have key-value pairs

Dictionaries: Motivation

- Imagine you want to implement a phone book, i.e., associate a name with a phone number
- You could store the phone number in a list
- You have to remember whose number is at which position
- Could use a second list of names with same order
 - Tedious to use and maintain!
- It would be better to use the names as indices to the phone number, i.e., to have key-value pairs
 - This is a map/associative array

Dictionaries in Python (1)

- Python dictionaries are **mappings/associative arrays**
 - Consist of **key-value pairs**, e.g., name → phone number
 - Any **hashable** object can be used as **key**
 - Any object can be used as **value**

Dictionaries in Python (1)

- Python dictionaries are **mappings/associative arrays**
 - Consist of **key-value pairs**, e.g., name → phone number
 - Any **hashable** object can be used as **key**
 - Any object can be used as **value**
- **Mutable** and **ordered**¹ (insertion order is preserved)

¹Since Python version 3.7

Dictionaries in Python (1)

- Python dictionaries are **mappings/associative arrays**
 - Consist of **key-value pairs**, e.g., name → phone number
 - Any **hashable** object can be used as **key**
 - Any object can be used as **value**
- **Mutable** and **ordered**¹ (insertion order is preserved)
- Created with syntax (keys can be anything)

```
my_dict = {key1: value1, key2: value2}
```

or syntax (keys must be identifiers and are automatically converted to type string)

```
my_dict = dict(key1=value1, key2=value2)
```

¹Since Python version 3.7

Dictionaries in Python (2)

- Phone book example (mapping string keys to string values):

```
phone_book = {"sam": "01234", "alex": "98765"}
```

or alternatively:

```
phone_book = dict(sam="01234", alex="98765")
```

Dictionaries in Python (2)

- Phone book example (mapping string keys to string values):

```
phone_book = {"sam": "01234", "alex": "98765"}
```

or alternatively:

```
phone_book = dict(sam="01234", alex="98765")
```

- Now, phone_book contains two entries. Let's use it to get sam's number:

```
phone_book["sam"] # Returns "01234"
```


Dictionaries in Python (2)

- Phone book example (mapping string keys to string values):

```
phone_book = {"sam": "01234", "alex": "98765"}
```

or alternatively:

```
phone_book = dict(sam="01234", alex="98765")
```

- Now, `phone_book` contains two entries. Let's use it to get sam's number:

```
phone_book["sam"] # Returns "01234"
```

- The keys of dictionary entries have to be **unique**

Dictionaries in Python (2)

- Phone book example (mapping string keys to string values):

```
phone_book = {"sam": "01234", "alex": "98765"}
```

or alternatively:

```
phone_book = dict(sam="01234", alex="98765")
```

- Now, phone_book contains two entries. Let's use it to get sam's number:

```
phone_book["sam"] # Returns "01234"
```

- The keys of dictionary entries have to be **unique**
- The following will overwrite the previous number for sam:

```
phone_book["sam"] = "13579"
```

LIST COMPREHENSIONS



List Comprehensions

- Compact way to loop over an iterable (strings, lists, sets, ...), perform (optional) actions on the elements and store the results in a list:

```
lst = [code-to-be-executed for element in iterable]
```

List Comprehensions

- Compact way to loop over an iterable (strings, lists, sets, ...), perform (optional) actions on the elements and store the results in a list:

```
lst = [code-to-be-executed for element in iterable]
```

- Can optionally include conditions during iteration

List Comprehensions

- Compact way to loop over an iterable (strings, lists, sets, ...), perform (optional) actions on the elements and store the results in a list:

```
lst = [code-to-be-executed for element in iterable]
```

- Can optionally include conditions during iteration
- Can also store results in sets and dictionaries, in which case they are called set and dictionary comprehensions

Code Example

```
my_list = ["a", "b", "c"]  
upper_case_list = [item.upper() for item in my_list]
```

- Very compact way instead of a normal for loop (and typically also faster in terms of run-time performance)

SLICING, INDEXING DETAILS AND MORE EXAMPLES



Slicing and Indexing Details

- Python allows to select a range of items in a sequence type, e.g., a list or a string, via **slicing**

Slicing and Indexing Details

- Python allows to select a range of items in a sequence type, e.g., a list or a string, via **slicing**
- Syntax for slicing: `sequence[start:end:stepsize]` with default values if not specified explicitly (0 for start, length of sequence for end, 1 for stepsize)

```
my_list[2:5]    # View on list at indices 2, 3, 4
my_list[2:5:1]  # Same with explicit step size
my_list[2:5:2]  # View on list at indices 2, 4
my_list[::-1]   # Entire list in reverse order
```

Slicing and Indexing Details

- Python allows to select a range of items in a sequence type, e.g., a list or a string, via **slicing**
- Syntax for slicing: `sequence[start:end:stepsize]` with default values if not specified explicitly (0 for start, length of sequence for end, 1 for stepsize)

```
my_list[2:5]    # View on list at indices 2, 3, 4
my_list[2:5:1]  # Same with explicit step size
my_list[2:5:2]  # View on list at indices 2, 4
my_list[::-1]   # Entire list in reverse order
```

- Negative numbers can also be used in indexing (starts from -1 for the last element, -2 for the second-last, etc.)

```
my_list[-2]    # Second-last element in list
```

UNPACKING



Unpacking

- If you have a sequence of values, you cannot only assign this sequence to some variable but also its contents. This is called **unpacking**

```
abc = [1, 2, 3]  # Regular assignment  
a, b, c = [1, 2, 3]  # a -> 1, b -> 2, c -> 3
```

- Can improve code readability (examples see accompanying code file)

OBJECTS, ASSIGNMENTS AND (IM)MUTABILITY



Objects and (Im)Mutability

- Recall: Everything in Python is an **object**

Objects and (Im)Mutability

- Recall: Everything in Python is an **object**
- Some are **immutable** (integers, tuples, etc.) and some are **mutable** (e.g., lists, dicts, etc.)

Objects and (Im)Mutability

- Recall: Everything in Python is an **object**
- Some are **immutable** (integers, tuples, etc.) and some are **mutable** (e.g., lists, dicts, etc.)
- Immutability means that objects cannot be changed, e.g.:

```
x = 3          # Integer object with constant 3
y = ("a", 3)  # 2-tuple object with fixed references
z = "hi"      # String object with fixed "hi"
```

Objects and (Im)Mutability

- Recall: Everything in Python is an **object**
- Some are **immutable** (integers, tuples, etc.) and some are **mutable** (e.g., lists, dicts, etc.)
- Immutability means that objects cannot be changed, e.g.:

```
x = 3           # Integer object with constant 3
y = ("a", 3)    # 2-tuple object with fixed references
z = "hi"        # String object with fixed "hi"
```

- Mutability means that objects can be changed, e.g.:

```
x = [1, 2, 3]   # List object with items 1,2,3
x[0] = 7        # x -> [7, 2, 3]
```

Assignments + Immutability

- An **assignment to an existing object** does not copy the object, it will simply **reference the same object**, e.g.:

```
x = 3    # Integer object  
y = x    # The same integer object
```

Assignments + Immutability

- An **assignment to an existing object** does not copy the object, it will simply **reference the same object**, e.g.:

```
x = 3    # Integer object  
y = x    # The same integer object
```

- x and y reference the same object, the object exists only once in memory

Assignments + Immutability

- An **assignment to an existing object** does not copy the object, it will simply **reference the same object**, e.g.:

```
x = 3    # Integer object  
y = x    # The same integer object
```

- x and y reference the same object, the object exists only once in memory
- Since integers are immutable, there cannot be any side effects in this case

Assignments + Mutability

- Now, consider another example with mutable objects:

```
x = [1, 2, 3] # List object with items 1,2,3  
y = x        # The same list object
```

Assignments + Mutability

- Now, consider another example with mutable objects:

```
x = [1, 2, 3]  # List object with items 1,2,3  
y = x          # The same list object
```

- x and y reference the same object, the object exists only once in memory

Assignments + Mutability

- Now, consider another example with mutable objects:

```
x = [1, 2, 3]  # List object with items 1,2,3  
y = x          # The same list object
```

- x and y reference the same object, the object exists only once in memory
- Since lists are mutable, there can be side effects in this case if you change the object, e.g., via `x[0] = 7`

Assignments + Mutability

- Now, consider another example with mutable objects:

```
x = [1, 2, 3]  # List object with items 1,2,3  
y = x         # The same list object
```

- x and y reference the same object, the object exists only once in memory
- Since lists are mutable, there can be side effects in this case if you change the object, e.g., via `x[0] = 7`
- With this, the list changed; its content is now `[7, 2, 3]`

Assignments + Mutability

- Now, consider another example with mutable objects:

```
x = [1, 2, 3]  # List object with items 1,2,3  
y = x          # The same list object
```

- x and y reference the same object, the object exists only once in memory
- Since lists are mutable, there can be side effects in this case if you change the object, e.g., via `x[0] = 7`
- With this, the list changed; its content is now `[7, 2, 3]`
- Since x and y still reference the same object, this change is visible through both variables (alias effect):

```
x  # List object with items 7,2,3  
y  # The same list object, which means the same  
    items 7,2,3!
```

Consideration of Side Effects

- Side effects are not bad per se, you just have to consider them while programming

Consideration of Side Effects

- Side effects are not bad per se, you just have to consider them while programming
- Often, you actually explicitly want this behavior, e.g., a sorting function that sorts a list **in-place**, i.e., makes changes directly within this list object

Consideration of Side Effects

- Side effects are not bad per se, you just have to consider them while programming
- Often, you actually explicitly want this behavior, e.g., a sorting function that sorts a list **in-place**, i.e., makes changes directly within this list object
- If you do not want this behavior, you can make a copy of your object and perform the changes on the copy, e.g., a sorting function that sorts a list by first copying it, sorting the copy and then returning this copy, leaving the original list unchanged

EXCURSION: LINEAR ARRAY



Excursion: Linear Array (1)

- Goal: We want to store a group of values of a fixed data type
 - E.g., 4 16-bit integer values
- Assumption: Our storage (=memory) consists of 1-byte large blocks with contiguous addresses
 - Byte 1 has address 0, byte 2 has address 1, etc.
- We know we need $m = 4 \cdot 16/8 = 8$ bytes to store our values
 - We can allocate 8 bytes of memory with contiguous addresses, starting at address x

Excursion: Linear Array (2)

Memory:

...	byte	byte	byte	byte	byte	byte	byte	byte	...
-----	------	------	------	------	------	------	------	------	-----

Address: ... 105 106 107 108 109 110 111 112 ...

Memory to store a 16-bit integer:

byte	byte
------	------

Storing 4 16-bit integers in memory:



... 105 106 107 108 109 110 111 112 ...

↑ ↑ ↑ ↑
Addresses of our integers

Excursion: Linear Array (3)

- Given the address of the first byte and the data type bytes (m), we can access one stored value via its index i :
 - 1st integer will be at address $x + 0 * m$
 - 2nd integer will be at address $x + 1 * m$
 - 3rd integer will be at address $x + 2 * m$
 - $(i+1)$ th integer will be at address $x + i * m$
 - Note: Indices here are integers, starting at 0
- In our example: $x = 105$, $m = 2$
- 3rd integer will be at address $x + i * m = 105 + 2 * 2 = 109$
- This is the concept of a **linear array**

Excursion: Linear Array (4)

■ Properties of linear arrays:

- The cost of the indexing operation is independent of the size of the array or the value of the index (in contrast to linked lists²)
 - Allocation of memory takes time and is therefore costly
 - If we want to increase the size of our linear array, we might have to copy the whole array to allocate enough contiguous space
- Increasing the number of elements is costly if done naively

■ In Python, for instance, lists are implemented as linear, variable-length arrays

²Linked lists: <https://realpython.com/linked-lists-python/>