PROGRAMMING IN PYTHON I

Classes: Advanced Topics



Andreas Schörgenhumer Institute for Machine Learning





Copyright Statement

This material, no matter whether in printed or electronic form, may be used for personal and non-commercial educational use only. Any reproduction of this material, no matter whether as a whole or in parts, no matter whether in printed or in electronic form, requires explicit prior acceptance of the authors.

Contact

Andreas Schörgenhumer

Institute for Machine Learning Johannes Kepler University Altenberger Str. 69 A-4040 Linz

E-Mail: schoergenhumer@ml.jku.at

Write mails only for personal questions

Institute ML Homepage

ROOT CLASS OBJECT



Root Class object

Every class in Python extends the root/base class **object**.

Root Class object

- Every class in Python extends the root/base class **object**.
- This means that we inherit everything that is available in object, which are several useful special methods:1

```
☐ __eq__(self, other)
```

- __hash__(self)
- □ __str__(self)
- ___lt__(self, other)
- □ ...

¹No attributes are inherited because object does not have any (instance) attributes.

Root Class object

- Every class in Python extends the root/base class **object**.
- This means that we inherit everything that is available in object, which are several useful special methods:1

```
□ __eq__(self, other)
□ __hash__(self)
□ __str__(self)
□ __lt__(self, other)
□ ...
```

Examples and explanations (for some) are part of the supplementary code file.

¹No attributes are inherited because object does not have any (instance) attributes.

Often, it would be nice to check the instances of our custom classes for equality using the == operator, e.g.:

```
class Dog:
    # Implementation

dog1 = Dog(...)
dog2 = Dog(...)
if dog1 == dog2:
    # Do something
```

Often, it would be nice to check the instances of our custom classes for equality using the == operator, e.g.:

```
class Dog:
    # Implementation

dog1 = Dog(...)
dog2 = Dog(...)
if dog1 == dog2:
    # Do something
```

■ By default, this equality comparison falls back to a reference/identity check (dog1 is dog2).

Often, it would be nice to check the instances of our custom classes for equality using the == operator, e.g.:

```
class Dog:
    # Implementation

dog1 = Dog(...)
dog2 = Dog(...)
if dog1 == dog2:
    # Do something
```

- By default, this equality comparison falls back to a reference/identity check (dog1 is dog2).
- This is the default behavior of the special object method __eq__(self, other), which will be automatically invoked when the == operator is used.

We can override this special method to provide custom behavior for our Dog objects!

```
class Dog:
    def __eq__(self, other):
        if isinstance(other, Dog):
            # Whatever checks we need to perform
            return self.name == other.name and ...
        return NotImplemented # See code file
```

We can override this special method to provide custom behavior for our Dog objects!

```
class Dog:
    def __eq__(self, other):
        if isinstance(other, Dog):
            # Whatever checks we need to perform
            return self.name == other.name and ...
        return NotImplemented # See code file
```

Now, whenever something like some_dog == x is encountered, this is automatically translated into Dog.__eq__(self=some_dog, other=x).

We can override this special method to provide custom behavior for our Dog objects!

```
class Dog:
    def __eq__(self, other):
        if isinstance(other, Dog):
            # Whatever checks we need to perform
            return self.name == other.name and ...
        return NotImplemented # See code file
```

- Now, whenever something like some_dog == x is encountered, this is automatically translated into Dog.__eq__(self=some_dog, other=x).
- This is also called **operator overloading**, since we changed the behavior of our Dog's == operator.

MORE OPERATOR OVERLOADING



More Operator Overloading

There are also some operators we can overload that are not part of object.

More Operator Overloading

- There are also some operators we can overload that are not part of object.
- This means that there is no default support, but we can easily enable it and provide support ourselves.

More Operator Overloading

- There are also some operators we can overload that are not part of object.
- This means that there is no default support, but we can easily enable it and provide support ourselves.
- Some examples:

```
add +: __add__(self, other)
multiply *: __mul__(self, other)
get-indexing []: __getitem__(self, key)
contains in: __contains__(self, item)
```

ENABLING SUPPORT FOR PYTHON FEATURES



Enabling Support for Python Features

- There also exist special methods that enable support for certain Python features.
- Some examples:
 - Iteration (e.g., in for loops): __iter__(self)
 - Context managers (with statement): __enter__(self) and __exit__(self, exc_type, exc_value, traceback)
 - ☐ Making objects callable (like function invocations):
 - __call__(self, ...)

IMPLEMENTATION



Implementation

■ How do we have to implement all these special methods?

Implementation

- How do we have to implement all these special methods?
- Read the specification, which lists the requirements and contains the necessary information!

Implementation

- How do we have to implement all these special methods?
- Read the specification, which lists the requirements and contains the necessary information!
- Useful links:
 - Data model (among other information, listing the specification of special methods):

```
https://docs.python.org/3/reference/datamodel.html
```

- Python's built-in types:
 - https://docs.python.org/3/library/stdtypes.html
- ☐ Glossary (listing important terms):
 - https://docs.python.org/3/glossary.html