

```
1: // <Copyright Owners Albara Mehene & Sean Nishi>
2: // regex_match example
3: #include <boost/regex.hpp>
4: #include <boost/date_time/gregorian/gregorian.hpp>
5: #include <boost/date_time/posix_time/posix_time.hpp>
6: #include <iostream>
7: #include <string>
8: #include <fstream>
9:
10: using boost::gregorian::date;
11: using boost::gregorian::years;
12: using boost::gregorian::months;
13: using boost::gregorian::days;
14: using boost::gregorian::date_duration;
15: using boost::gregorian::date_period;
16: using boost::gregorian::from_simple_string;
17:
18: using boost::posix_time::ptime;
19: using boost::posix_time::hours;
20: using boost::posix_time::minutes;
21: using boost::posix_time::seconds;
22: using boost::posix_time::time_duration;
23:
24:
25: int main(int argc, char* argv[]) {
26:     if (argc != 2) {
27:         std::cout << "ERROR: input only one file" << std::endl;
28:         return -1;
29:     }
30:
31:     // open the input file
32:     std::ifstream logFile;
33:     logFile.open(argv[1]);
34:     // name of file
35:     std::string logName(argv[1]);
36:     std::string outputName = logName + ".rpt";
37:     // create the output file
38:     std::ofstream outputFile;
39:     outputFile.open(outputName.c_str());
40:     // space
41:     std::string line;
42:     date stored_date;
43:     date finished_date;
44:     ptime beginTime;
45:     ptime endTime;
46:     boost::smatch m;
47:     time_duration total_time;
48:     // space
49:     bool s_boot = false;
50:     int lineNum = 1;
51:
52:     // Start of boot: 2014-02-01 14:02:32: (log.c.166) server started
53:     boost::regex Boot_Start(
54:         "([0-9]{4})-([0-9]{2})-([0-9]{2}) "
55:         "([0-9]{2}):([0-9]{2}):([0-9]{2}): "
56:         "\\(log.c.166\\) server started.*");
57:     // If we find the text:
58:     // "2014-01-26 09:58:04.362:INFO:oejs.AbstractConnector:Started
59:     // SelectChannelConnector@0.0.0.0:9080"
60:     boost::regex Boot_End(
61:         "([0-9]{4})-([0-9]{2})-([0-9]{2}) "
```

```
62:      "([0-9]{2}):([0-9]{2}):([0-9]{2}).([0-9]{3}):INFO:"
63:      "oejs.AbstractConnector:Started SelectChannelConnector@0.0.0.0:9080.*");
64:      // Space
65:      boost::regex start_service(
66:          "Starting\\ Service\\.\\.\\.\\. ([a-z]|[A-Z]+).+");
67:      boost::regex end_service(
68:          "Service\\. started\\.\\. successfully\\.\\.\\.\\. "
69:          "([a-z]|[A-Z]+).+\\.\\.\\.\\.([0-9]+).+");
70:      // check if input file is open
71:      if (!logFile.is_open()) {
72:          std::cout << "ERROR: no input log file" << std::endl;
73:          return -1;
74:      } else {
75:          // Go through the loop
76:          while (getline(logFile, line)) {
77:              // search the start regex code
78:              if (regex_search(line, m, Boot_Start)) {
79:                  // store them into date and time
80:                  stored_date = date(stoi(m[1]), stoi(m[2]), stoi(m[3]));
81:                  beginTime = ptime(stored_date,
82:                      time_duration(stoi(m[4]), stoi(m[5]), stoi(m[6])));
83:                  // condition to see if it will fail to go to the next condition
84:                  if (s_boot) {
85:                      s_boot = false;
86:                      outputFile << "**** Incomplete boot ****\n" << std::endl;
87:                  }
88:                  // draw the start into the output file
89:                  outputFile << "=== Device boot ===\n"
90:                      << lineNumber << "(" << logName << "): "
91:                      << m[1] << "-" << m[2] << "-" << m[3]
92:                      << " "
93:                      << m[4] << ":" << m[5] << ":" << m[6]
94:                      << "Boot Start" << std::endl;
95:                  s_boot = true;
96:                  // Then do the same to the end but checking the regex
97:              } else if (regex_search(line, m, Boot_End)) {
98:                  finished_date = date(stoi(m[1]), stoi(m[2]), stoi(m[3]));
99:                  endTime = ptime(stored_date,
100:                      time_duration(stoi(m[4]), stoi(m[5]), stoi(m[6])));
101:                  // output the rest
102:                  outputFile << lineNumber << "(" << logName << "): "
103:                      << m[1] << "-" << m[2] << "-" << m[3]
104:                      << m[4] << ":" << m[5] << ":" << m[6]
105:                      << " Boot Completed" << std::endl;
106:                  total_time = endTime - beginTime;
107:                  outputFile << " "
108:                      << "Boot Time: " << total_time.total_milliseconds()
109:                      << "ms\n" << std::endl;
110:                  s_boot = false;
111:              }
112:              // increment line number to go to next line
113:              lineNumber++;
114:          }
115:          // closing the files
116:          logFile.close();
117:          outputFile.close();
118:      }
119:      return 0;
120: }
```