```
step(currentBsState)
```

```
1: currentContext \leftarrow context[currentBsState]
2: for each state in states[currentContext] do
      tran \leftarrow trOut[state]
3:
      while tran \neq NIL do
4:
        if isEventPresent(currentContext, tran) and isBufferFree(currentContext, tran) then
5:
          newContext \leftarrow createNewContext(currentContex, tran)
6:
          newTransition \leftarrow createNewTransition(currentContext, tran)
7:
          item \leftarrow contextSearch(newContext, ctHashMap)
8:
          if item \neq NIL then
9:
             destinationBsState \leftarrow subValue[item]
10:
             dest[newTransition] \leftarrow destinationBsState
11:
          else
12:
             createNewState(newContext, tran)
13:
14:
             step(destinationBsState)
          end if
15:
        end if
16:
      end while
17:
18: end for
```

takeEventFromBuffer(context,action)

```
1: l \leftarrow link[action]
2: pos \leftarrow index[l]
3: return \ buffer[context][pos]
```

isEventPresent(context,transition)

```
    actionRequest ← actIn[transition]
    eventBuffer ← takeEventFromBuffer(context, actionRequest)
    eventRequest ← event[actionRequest]
    return (actionRequest = NIL or eventBuffer = eventRequest)
```

```
isBufferFree(context, transition)
```

- 1: $actionProduced \leftarrow actOut[transition]$
- 2: while $actionProduced \neq NIL$ do
- 3: $eventBuffer \leftarrow takeEventFromBuffer(context, actionProduced)$
- 4: **if** $eventBuffer \neq NIL$ **then**
- 5: return FALSE
- 6: end if
- 7: $actionProduced \leftarrow next[actionProduced]$
- 8: end while
- 9: return TRUE

createNewContext(context,transition)

- 1: $newContext \leftarrow initializeContext()$
- 2: $state \leftarrow dest[transition]$
- $3: actionRequest \leftarrow actIn[transition]$
- $4: eventRequest \leftarrow event[actionRequest]$
- 5: if $eventRequest \neq NIL$ then
- 6: $eventBuffer \leftarrow NIL$
- 7: end if
- 8: $actionProduced \leftarrow actOut[tran]$
- 9: while $actionProduced \neq NIL$ do
- 10: $l2 \leftarrow link[actionProduced]$
- 11: $pos2 \leftarrow index[l2]$
- 12: $buffer[newContext][pos2] \leftarrow actionProduced$
- 13: $actionProduced \leftarrow next[actionProduced]$
- 14: end while
- 15: return newContext

createNewTransition(context,transition,currentBsState)

- 1: $newTransition \leftarrow initializeTransition()$
- 2: $obs[newTransition] \leftarrow obs[transition]$
- 3: $rel[newTransition] \leftarrow rel[transition]$
- 4: $src[newTransition] \leftarrow currentBsState$
- 5: addTransition(newTransition)
- 6: return newTransition

createNewState(context,transition)

- 1: $destinationBsState \leftarrow initializeState()$
- 2: $context[destinationBsState] \leftarrow context$
- 3: if isFinal(context) then
- 4: $final[destinationBsState] \leftarrow TRUE$
- 5: **else**
- 6: $finale[destinationBsState] \leftarrow FALSE$
- 7: end if
- 8: addState(destinationBsState)
- 9: $dest[transition] \leftarrow destinationBsState$
- 10: addContextToHashMap(context)

```
dfs(state)
```

```
1: color[state] \leftarrow GRAY
2: transitionsIncoming \leftarrow trIn[state]
3: \mathbf{while} \ transitionsIncoming \neq NIL \ \mathbf{do}
4: stateSource \leftarrow scr[transitionsIncoming]
5: \mathbf{if} \ color[stateSource] = WHITE \ \mathbf{then}
6: \mathbf{dfs}[stateSource]
7: \mathbf{end} \ \mathbf{if}
8: transitionsIncoming \leftarrow next[transitionsIncoming]
9: \mathbf{end} \ \mathbf{while}
10: color[state] \leftarrow BLACK
```

prune(network)

```
1: {consideriamo solo reti con un solo automa, infatti il pruning avviene solo sulle
2: network generate dal sistema}
3: autom \leftarrow automatons[network]
4: totalState \leftarrow states[autom]
5: while totalState \neq NIL do
     if final[totalState] = TRUE then
6:
7:
        dfsVisit(totalState)
      end if
8:
      totalState \leftarrow next[totalState]
9:
10: end while
11: while totalStat \neq NIL do
      if color[totalState] = WHITE then
12:
        removeTheState(network, totalState)
13:
      end if
14:
      totalState \leftarrow next[totalState]
15:
16: end while
```

isTransitionObservable(context,transition)

```
1: label \leftarrow NIL
2: currentObservation \leftarrow currentObs[context]
3: {Controllo sulla presenza della lista di osservazioni}
 4: if currentObservation \neq NIL then
      label \leftarrow currentObervation
      transitionLabel \leftarrow obs[tansition]
6:
7:
      idObsarvation \leftarrow id[transitionLabel]
9: if transitionLabel \neq NIL and (label \neq NIL or idLabel \neq idObsarvation) then
      return FALSE
10:
11: else
      return TRUE
12:
13: end if
```