Tensor Flow cheat sheet

Efim Abrikosov

April 29, 2019

1 Data Prepocessing

1.1 Feature columns

tf.feature_column

- tf.feature_column.numeric_column(colname)
- tf.feature_column.bucketized_column(tf.feature_coumn.numeric_column, boundaries_list)

tf.feature_column.crossed_column([tf.feature_coumn.categorical_column list], num_hash_buckets)

- tf.feature_column.categorical_column_with_identity(colname, num_buckets)
- tf.feature_column.categorical_column_with_vocabulary_list(colname, vocabulary_list)
- tf.feature_column.categorical_column_with_hash_bucket()colname, hash_bucket_size)
- \bullet tf.feature_column.embedding_column(tf.feature_column.categorical_column, n_dim)

2 Estimator API

tf.estimator

tf.estimator.Estimator(model_fn, out_dir)

- model_fn is a function that returns tf.estimator.EstimatorSpec given a triple (feature_cols, targets, mode)

Sample signature: tf.estimator.EstimatorSpec(**args)

Arguments list consists of:

- 1. mode, one of the three:
 - tf.estimator.ModeKeys.TRAIN .
 - tf.estimator.ModeKeys.EVAL,
 - tf.estimator.ModeKeys.PREDICT
- 2. predictions_dict
- 3. loss
- $4. train_op$
- $5. \ eval_metrics_ops$
- 6. export_outputs
- model_dir is the name of output directory (string)
- tf.estimator.train_and_evaluate(estimator, train_spec, eval_spec)
 - estimator is an instance of tf.estimator

Sample singature: tf.estimator.[model_name](model_dir, feature_columns, model_params)

- train_spec is an instance of tf.estimator.TrainSpec
 - Sample signature: tf.estimator.TrainSpec(input_fn, max_steps)
- eval_spec is an instance of tf.estimator.EvalSpec

Sample signature: tf.estimator.EvalSpec(input_fn,steps, start_delay_secs, throttle_secs)

• Adding performance metrics

Sample signature: *estimator* = tf.contrib.estimator.add_metrics(*estimator*, rmse)

3 TensorBoard

- filewriter_name = tf.summary.FileWriter(path_name, tf.graph = tf.get_default_graph())
- filewriter_name.close()
- in terminal or with %%bash magic
 - \$ tensorboard --logdir path_name