



ConTeXt

přikazy

CS

ConTeXt

příkazy

cs / český
13. dubna 2017

<code>\AfterPar {...}</code> * BEFEHL
<code>\Alphabeticnumerals {...}</code> * NUMMER
<code>\AMSTEX</code>
<code>\AmSTeX</code>
<code>\And</code>
<code>\abjadnaivenumerals {...}</code> * NUMMER
<code>\abjadnodotnumerals {...}</code> * NUMMER
<code>\abjadnumerals {...}</code> * NUMMER
<code>\activatespacehandler {...}</code> * zap vyp ano fixne
<code>\acute {...}</code> * CHARACTER
<code>\adaptcollector [...]¹ [...,...²...]_{OPT}</code> 1 NAME 2 inherits: \setupcollector
<code>\adaptfontfeature [...]¹ [...,...²...]</code> 1 NAME 2 inherits: \definefontfeature
<code>\adaptpapersize [...]¹,... [...]²,...]_{OPT}</code> 1 inherits: \nastavvelikostpapiru 2 inherits: \nastavvelikostpapiru
<code>\addfeature [...]</code> * NAME
<code>\addfeature {...}</code> * NAME
<code>\addtocommalist {...}¹ \...²</code> 1 TEXT 2 CSNAME

<p><code>\addtoJSreamble {...} {...}</code></p> <p>1 NAME</p> <p>2 CONTENT</p>
<p><code>\addvalue {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\aftersplitstring ... \at ... \to ...</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 CSNAME</p>
<p><code>\aftertestandsplitstring ... \at ... \to ...</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 CSNAME</p>
<p><code>\aktualnicislonaDPisu</code></p>
<p><code>\aktualnidatum [...;...]</code></p> <p style="text-align: center;">OPT</p> <p>* rok mesic den vsedniden y yy Y m mm M d dd D w W mezera _ month:mnem m:mnem d:ord day:ord dd:ord D:ord TEXT znacka day:+ day:++ d:+ d:++ dd:+ dd:++ D:+ D:++ month:jalali m:jalali jalali:to jalali:from</p>
<p><code>\alignbottom</code></p>
<p><code>\aligned [...;...] {...}</code></p> <p>1 vlevo nastred vpravo vrsek spodek radek l c r m t b g</p> <p>2 CONTENT</p>
<p><code>\alignedbox [...;...] \^... {...}</code></p> <p>1 vlevo nastred vpravo vrsek spodek radek l c r m t b g</p> <p>2 CSNAME</p> <p>3 CONTENT</p>
<p><code>\alignedline {...} {...} {...}</code></p> <p>1 vlevo vpravo nastred flushleft flushright center max uvnitr vnejsi innermargin outermargin inneredge outeredge zpetnamezera cutspace levyokraj prav yokraj levahrana pravahrana</p> <p>2 vlevo vpravo nastred flushleft flushright center max uvnitr vnejsi innermargin outermargin inneredge outeredge zpetnamezera cutspace levyokraj prav yokraj levahrana pravahrana</p> <p>3 CONTENT</p>
<p><code>\alignmentcharacter</code></p>
<p><code>\allinputpaths</code></p>
<p><code>\alphabeticnumerals {...}</code></p> <p>* NUMMER</p>

`\alwayscitation [...1...2...] [...]`
OPT

1 odkaz = REFERENCE
 alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
 authornum authoryear
 pred = BEFEHL
 po = BEFEHL
 vlevo = BEFEHL
 vpravo = BEFEHL
 inherits: \setupbtx
 2 REFERENCE

`\alwayscitation [...1] [...2]`
OPT

1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear
 2 REFERENCE

`\alwayscitation [...1...2...] [...2...]`

1 odkaz = REFERENCE
 alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
 authornum authoryear
 pred = BEFEHL
 po = BEFEHL
 vlevo = BEFEHL
 vpravo = BEFEHL
 inherits: \setupbtx
 2 KEY = VALUE

`\alwayscite [...1...2...] [...2]`
OPT

1 odkaz = REFERENCE
 alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
 authornum authoryear
 pred = BEFEHL
 po = BEFEHL
 vlevo = BEFEHL
 vpravo = BEFEHL
 inherits: \setupbtx
 2 REFERENCE

`\alwayscite [...1] [...2]`
OPT

1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear
 2 REFERENCE

`\alwayscite [...1...2...] [...2...]`

1 odkaz = REFERENCE
 alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
 authornum authoryear
 pred = BEFEHL
 po = BEFEHL
 vlevo = BEFEHL
 vpravo = BEFEHL
 inherits: \setupbtx
 2 KEY = VALUE

`\ampersand`

`\anchor [...1] [...2...] [...3...] {...4}`
OPT OPT

1 NAME
 2 inherits: \setuplayer
 3 inherits: \setuplayerinherits: \nastavoramovani
 4 CONTENT

<code>\antikva</code>
<code>\appendetoks ¹ \to \²</code> 1 BEFEHL 2 CSNAME
<code>\appendgvalue {¹} {²}</code> 1 NAME 2 BEFEHL
<code>\appendtocommalist {¹} \²</code> 1 TEXT 2 CSNAME
<code>\appendtoks ¹ \to \²</code> 1 BEFEHL 2 CSNAME
<code>\appendtoksonce ¹ \to \²</code> 1 BEFEHL 2 CSNAME
<code>\appendvalue {¹} {²}</code> 1 NAME 2 BEFEHL
<code>\apply {¹} {²}</code> 1 CONTENT 2 CONTENT
<code>\applyalternativestyle {[*]}</code> * NAME
<code>\applyprocessor {¹} {²}</code> 1 NAME 2 CONTENT
<code>\applytofirstcharacter \¹ {²}</code> 1 CSNAME 2 TEXT
<code>\applytocharacters \¹ {²}</code> 1 CSNAME 2 TEXT
<code>\applytosplitstringchar \¹ {²}</code> 1 CSNAME 2 TEXT

<p><code>\applytosplitstringcharspaced \¹... {²...}</code></p> <p>1 CSNAME</p> <p>2 TEXT</p>
<p><code>\applytosplitstringline \¹... {²...}</code></p> <p>1 CSNAME</p> <p>2 TEXT</p>
<p><code>\applytosplitstringlinespaced \¹... {²...}</code></p> <p>1 CSNAME</p> <p>2 TEXT</p>
<p><code>\applytosplitstringword \¹... {²...}</code></p> <p>1 CSNAME</p> <p>2 TEXT</p>
<p><code>\applytosplitstringwordspaced \¹... {²...}</code></p> <p>1 CSNAME</p> <p>2 TEXT</p>
<p><code>\applytowords \¹... {²...}</code></p> <p>1 CSNAME</p> <p>2 TEXT</p>
<p><code>\arabicdecimals {...}</code></p> <p>* NUMMER</p>
<p><code>\arabicexnumerals {...}</code></p> <p>* NUMMER</p>
<p><code>\arabicnumerals {...}</code></p> <p>* NUMMER</p>
<p><code>\arg {...}</code></p> <p>* CONTENT</p>
<p><code>\asciistr {...}</code></p> <p>* CONTENT</p>
<p><code>\aside [_{OPT}¹...] {²...}</code></p> <p>1 SPRACHE</p> <p>2 CONTENT</p>

`\assignalfadimension {...} \^2... {...} {...} {...}`

1 male stredni velke zadny DIMENSION
2 CSNAME
3 DIMENSION
4 DIMENSION
5 DIMENSION

`\assigndimen \^1... {...}`

1 CSNAME
2 DIMENSION

`\assigndimension {...} \^2... {...} {...} {...}`

1 [-+]male [-+]stredni [-+]velke zadny DIMENSION
2 CSNAME
3 DIMENSION
4 DIMENSION
5 DIMENSION

`\assignifempty \^1... {...}`

1 CSNAME
2 BEFEHL

`\assigntranslation [...,\^1...,\^2...]`

1 SPRACHE = TEXT
2 CSNAME

`\assignvalue {...} \^2... {...} {...} {...}`

1 male stredni velke TEXT
2 CSNAME
3 BEFEHL
4 BEFEHL
5 BEFEHL

`\assignwidth {...} \^2... {...} {...}`

1 prizpusobive siroky DIMENSION
2 CSNAME
3 TEXT
4 DIMENSION

`\assumelongusagecs \^1... {...}`

1 CSNAME
2 CONTENT

`\astype {...}`

* CONTENT

$\backslash\text{attachment}$ $[\overset{1}{\dots}] [\dots,\overset{2}{\dots},\dots]$ <small>OPT</small> <small>OPT</small> 1 NAME 2 inherits: \setupattachment
$\backslash\text{ATTACHMENT}$ $[\overset{1}{\dots}] [\dots,\overset{2}{\dots},\dots]$ <small>OPT</small> <small>OPT</small> 1 NAME 2 inherits: \setupattachment instances: attachment
$\backslash\text{autocap}$ {...} * TEXT
$\backslash\text{autodirhbox}$ $\overset{1}{\dots} \{\overset{2}{\dots}\}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{autodirvbox}$ $\overset{1}{\dots} \{\overset{2}{\dots}\}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{autodirvtop}$ $\overset{1}{\dots} \{\overset{2}{\dots}\}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{autoinsertnextspace}$
$\backslash\text{automathematics}$ {...} * CONTENT
$\backslash\text{autosetups}$ {...,*,...} * NAME
$\backslash\text{autostarttext}$... $\backslash\text{autostoptext}$
$\backslash\text{availablehsize}$
$\backslash\text{averagecharwidth}$
$\backslash\text{BeforePar}$ {...} * BEFEHL
$\backslash\text{Big}$... * CHARACTER
$\backslash\text{Bigg}$... * CHARACTER

\Biggl ... * CHARACTER
\Biggm ... * CHARACTER
\Biggr ... * CHARACTER
\Bigl ... * CHARACTER
\Bigm ... * CHARACTER
\Bigr ... * CHARACTER
\backgroundimage {...} {...} {...} {...} 1 NUMMER 2 DIMENSION 3 DIMENSION 4 BEFEHL
\backgroundimagefill {...} {...} {...} {...} 1 NUMMER 2 DIMENSION 3 DIMENSION 4 BEFEHL
\backgroundline [...] {...} 1 COLOR 2 CONTENT
\bar {...} * CHARACTER
\barevnaalista [...]*...]
* COLOR
\barva [...] {...} 1 COLOR 2 CONTENT

`\BAR {...}`

* CONTENT

instances: nadtrzeno podtrzeno preskrtnuto understrike nadtrzeni podtrzeni preskrtnuti
understrikes underrandom underrandoms underdash underdashes underdot underdots nobar
hiddenbar

`\basegrid [...,*...]`

OPT

* nx = NUMMER
ny = NUMMER
dx = NUMMER
dy = NUMMER
faktor = NUMMER
meritko = NUMMER
xkrok = NUMMER
ykrok = NUMMER
offset = DIMENSION
xoffset = DIMENSION
yoffset = DIMENSION
zarovnani = nastred
jednotka = cm mm in pc pt bp
pismo = STYLE BEFEHL
barva = COLOR

`\baselinebottom`

`\baselineleftbox {...}`

* CONTENT

`\baselinemiddlebox {...}`

* CONTENT

`\baselinerightbox {...}`

* CONTENT

`\bbox {...}`

* CONTENT

`\beforesplitstring 1... \at 2... \to 3...`

1 TEXT
2 TEXT
3 CSNAME

`\beforetestandsplitstring 1... \at 2... \to 3...`

1 TEXT
2 TEXT
3 CSNAME

`\beginBLOCK [...,*...] ... \endBLOCK`

OPT

* + -

`\beginhbox ... \endhbox`

`\beginofshapebox ... \endofshapebox`

<code>\beginvbox ... \endvbox</code>
<code>\beginvtop ... \endvtop</code>
<code>\begstrut ... \endstrut</code>
<code>\bezserifu</code>
<code>\bigbodyfont</code>
<code>\bigg ...</code> * CHARACTER
<code>\bigger</code>
<code>\biggl ...</code> * CHARACTER
<code>\biggm ...</code> * CHARACTER
<code>\biggr ...</code> * CHARACTER
<code>\bigl ...</code> * CHARACTER
<code>\bigm ...</code> * CHARACTER
<code>\bigr ...</code> * CHARACTER
<code>\bigskip</code>
<code>\binom {...} {...}</code> 1 CONTENT 2 CONTENT
<code>\bitmapimage [...,\stackrel{1}{...},...] {...}</code> 1 barva = rgb cmyk seda sirka = DIMENSION vyska = DIMENSION x = NUMMER y = NUMMER 2 NUMMER
<code>\blap {...}</code> * CONTENT

$\backslash\text{bleed} [\dots, \dots, \overset{1}{\dots}, \dots] \{\overset{2}{\dots}\}$ <small>OPT</small> 1 inherits: \setupbleeding 2 CONTENT
$\backslash\text{bleedheight}$
$\backslash\text{bleedwidth}$
$\backslash\text{blockligatures} [\dots]$ * LISTE
$\backslash\text{blockquote} [\overset{1}{\dots}] \{\overset{2}{\dots}\}$ <small>OPT</small> 1 SPRACHE 2 CONTENT
$\backslash\text{bodyfontenvironmentlist}$
$\backslash\text{bodyfontsize}$
$\backslash\text{boldface}$
$\backslash\text{booleanmodevalue} \{\dots\}$ * NAME
$\backslash\text{bottombox} \{\dots\}$ * CONTENT
$\backslash\text{bottomleftbox} \{\dots\}$ * CONTENT
$\backslash\text{bottomrightbox} \{\dots\}$ * CONTENT
$\backslash\text{boxcursor}$
$\backslash\text{boxmarker} \{\overset{1}{\dots}\} \{\overset{2}{\dots}\}$ 1 NAME 2 NUMMER
$\backslash\text{boxofsize} \overset{1}{\dots} \dots \overset{2}{\dots} \dots \{\overset{3}{\dots}\}$ <small>OPT</small> 1 CSNAME 2 DIMENSION 3 CONTENT
$\backslash\text{boxreference} [\dots, \overset{1}{\dots}] \backslash \overset{2}{\dots} \{\overset{3}{\dots}\}$ 1 REFERENCE 2 CSNAME 3 CONTENT

<code>\bpar ... \epar</code>
<code>\bpos {...}</code> * NAME
<code>\breve {...}</code> * CHARACTER
<code>\bTABLE [...,..[*]...,...] ... \eTABLE</code> <small>OPT</small> * inherits: \setupTABLE
<code>\bTABLEbody [...,..[*]...,...] ... \eTABLEbody</code> <small>OPT</small> * inherits: \setupTABLE
<code>\bTABLEfoot [...,..[*]...,...] ... \eTABLEfoot</code> <small>OPT</small> * inherits: \setupTABLE
<code>\bTABLEhead [...,..[*]...,...] ... \eTABLEhead</code> <small>OPT</small> * inherits: \setupTABLE
<code>\bTABLEnext [...,..[*]...,...] ... \eTABLEnext</code> <small>OPT</small> * inherits: \setupTABLE
<code>\bTC [...,..[*]...,...] ... \eTC</code> <small>OPT</small> * inherits: \bTD
<code>\bTD [...,..[*]...,...] ... \eTD</code> <small>OPT</small> * nx = NUMBER * ny = NUMBER * nc = NUMBER * nr = NUMBER * n = NUMBER * m = NUMBER * akce = REFERENCE * inherits: \setupTABLE
<code>\bTDs [...] ... \eTDs</code> * NAME
<code>\bTH [...,..[*]...,...] ... \eTH</code> <small>OPT</small> * inherits: \bTD
<code>\bTN [...,..[*]...,...] ... \eTN</code> <small>OPT</small> * inherits: \bTD
<code>\bTR [...,..[*]...,...] ... \eTR</code> <small>OPT</small> * inherits: \setupTABLE
<code>\bTRs [...] ... \eTRs</code> * NAME

<p><code>\bTX [...[*]...] ... \eTX</code> <small>OPT</small></p> <p>* inherits: \bTD</p>
<p><code>\bTY [...[*]...] ... \eTY</code> <small>OPT</small></p> <p>* inherits: \setupTABLE</p>
<p><code>\bthiddencitation [...]</code></p> <p>* REFERENCE</p>
<p><code>\btxabbreviatedjournal {...}</code></p> <p>* NAME</p>
<p><code>\btxaddjournal [...¹] [...²]</code></p> <p>1 NAME</p> <p>2 NAME</p>
<p><code>\btxalwayscitation [...¹...] [...²]</code> <small>OPT</small></p> <p>1 odkaz = REFERENCE alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear pred = BEFEHL po = BEFEHL vlevo = BEFEHL vpravo = BEFEHL inherits: \setupbtx</p> <p>2 REFERENCE</p>
<p><code>\btxalwayscitation [...¹] [...²]</code> <small>OPT</small></p> <p>1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear</p> <p>2 REFERENCE</p>
<p><code>\btxalwayscitation [...¹...] [...²...] [...³...]</code></p> <p>1 odkaz = REFERENCE alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear pred = BEFEHL po = BEFEHL vlevo = BEFEHL vpravo = BEFEHL inherits: \setupbtx</p> <p>2 KEY = VALUE</p>
<p><code>\btxauthorfield {...}</code></p> <p>* initials firstnames vons surnames juniors</p>
<p><code>\btxdetail {...}</code></p> <p>* address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME</p>
<p><code>\btxdirect {...}</code></p> <p>* address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME</p>

\btxdoif {...} {...}

- 1 address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME
- 2 TRUE

\btxdoifcombiinlistelse {...} {...} {...} {...}

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

\btxdoifelse {...} {...} {...}

- 1 address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME
- 2 TRUE
- 3 FALSE

\btxdoifelsecombiinlist {...} {...} {...} {...}

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

\btxdoifelsesameasprevious {...} {...} {...}

- 1 address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME
- 2 TRUE
- 3 FALSE

\btxdoifelsesameaspreviouschecked {...} {...} {...} {...}

- 1 vzdy dvoustranny
- 2 address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME
- 3 TRUE
- 4 FALSE

\btxdoifelseuservariable {...} {...} {...}

- 1 KEY
- 2 TRUE
- 3 FALSE

\btxdoifnot {...} {...}

- 1 address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME
- 2 TRUE

\btxdoifsameaspreviouselse {...} {...} {...}

- 1 address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME
- 2 TRUE
- 3 FALSE

\btxdoifsameaspreviouscheckedelse {...} {...} {...} {...}

- 1 vzdy dvoustranny
- 2 address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME
- 3 TRUE
- 4 FALSE

\btxdoifuservariableelse {...} {...} {...}

- 1 KEY
- 2 TRUE
- 3 FALSE

\btxexpandedjournal {...}

- * NAME

\btxfield {...}

- * address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME

\btxfieldname {...}

- * address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME

\btxfieldtype {...}

- * address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME

\btxfirstofrange {...}

- * volume pages

\btxflush {...}

- * address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME

\btxflushauthor [...]
OPT {...}

- 1 num normalni normalshort inverted invertedshort
- 2 autor editor

\btxflushauthorinverted {...}

- * autor editor

<p><code>\btxflushauthorinvertedshort {...}</code></p> <p>* autor editor</p>
<p><code>\btxflushauthorname {...}</code></p> <p>* autor editor</p>
<p><code>\btxflushauthornormal {...}</code></p> <p>* autor editor</p>
<p><code>\btxflushauthornormalshort {...}</code></p> <p>* autor editor</p>
<p><code>\btxflushsuffix</code></p>
<p><code>\btxfoundname {...}</code></p> <p>* address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME</p>
<p><code>\btxfoundtype {...}</code></p> <p>* address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME</p>
<p><code>\btxhybridcite [...¹...²...] [...]</code></p> <p style="text-align: center;">OPT</p> <p>1 odkaz = REFERENCE alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear pred = BEFEHL po = BEFEHL vlevo = BEFEHL vpravo = BEFEHL inherits: \setupbtx</p> <p>2 REFERENCE</p>
<p><code>\btxhybridcite [...¹...] [...]</code></p> <p style="text-align: center;">OPT</p> <p>1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear</p> <p>2 REFERENCE</p>
<p><code>\btxhybridcite {...}</code></p> <p>* REFERENCE</p>
<p><code>\btxhybridcite [...¹...²...] [...²...]</code></p> <p>1 odkaz = REFERENCE alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear pred = BEFEHL po = BEFEHL vlevo = BEFEHL vpravo = BEFEHL inherits: \setupbtx</p> <p>2 KEY = VALUE</p>

\btxlistcitation [...¹...²...] [...]

1 odkaz = REFERENCE
alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
authornum authoryear
pred = BEFEHL
po = BEFEHL
vlevo = BEFEHL
vpravo = BEFEHL
inherits: \setupbtx
2 REFERENCE

\btxlistcitation [...¹...] [...²...]

1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear
2 REFERENCE

\btxlistcitation [...¹...²...] [...²...¹...]

1 odkaz = REFERENCE
alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
authornum authoryear
pred = BEFEHL
po = BEFEHL
vlevo = BEFEHL
vpravo = BEFEHL
inherits: \setupbtx
2 KEY = VALUE

\btxloadjournalist [...]

* FILE

\btxoneorrange {...} {...} {...}

1 volume pages
2 TRUE
3 FALSE

\btxremapauthor [...¹...] [...²...]

1 TEXT
2 TEXT

\btxsavejournalist [...]

* FILE

\btxsetup {...}

* NAME

\btxsingularorplural {...¹} {...²} {...³}

1 editor producer director
2 TRUE
3 FALSE

\btxsingularplural {...¹} {...²} {...³}

1 editor producer director
2 TRUE
3 FALSE

$\backslash\text{btxttextcitation} [\dots, \dots, \dots, \dots] [\dots]$

- 1 odkaz = REFERENCE
alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
authornum authoryear
pred = BEFEHL
po = BEFEHL
vlevo = BEFEHL
vpravo = BEFEHL
inherits: \setupbtx
- 2 REFERENCE

$\backslash\text{btxttextcitation} [\dots] [\dots]$

- 1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear
- 2 REFERENCE

$\backslash\text{btxttextcitation} [\dots, \dots, \dots, \dots] [\dots, \dots, \dots, \dots]$

- 1 odkaz = REFERENCE
alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
authornum authoryear
pred = BEFEHL
po = BEFEHL
vlevo = BEFEHL
vpravo = BEFEHL
inherits: \setupbtx
- 2 KEY = VALUE

$\backslash\text{TOOLTIP} [\dots, \dots, \dots, \dots] \{\dots\} \{\dots\}$

- 1 inherits: \setuptooltip
- 2 TEXT
- 3 TEXT

instances:

$\backslash\text{TOOLTIP} [\dots] \{\dots\} \{\dots\}$

- 1 vlevo nastred vpravo
- 2 TEXT
- 3 TEXT

instances:

$\backslash\text{buildmathaccent} \{\dots\} \{\dots\}$

- 1 CHARACTER
- 2 CHARACTER

$\backslash\text{buildtextaccent} \{\dots\} \{\dots\}$

- 1 CHARACTER
- 2 CHARACTER

$\backslash\text{buildtextbottomcomma} \{\dots\}$

- * CHARACTER

$\backslash\text{buildtextbottomdot} \{\dots\}$

- * CHARACTER

<code>\buildtextcedilla {...}</code> * CHARACTER
<code>\buildtextgrave {...}</code> * CHARACTER
<code>\buildtextmacron {...}</code> * CHARACTER
<code>\buildtextognek {...}</code> * CHARACTER
<code>\Caps {...}</code> * TEXT
<code>\Cisla {...}</code> * NUMBER
<code>\CONTEXT</code>
<code>\ConTeXt</code>
<code>\Context</code>
<code>\ConvertConstantAfter \¹... {\²...} {\³...}</code> 1 CSNAME 2 TEXT 3 TEXT
<code>\ConvertToConstant \¹... {\²...} {\³...}</code> 1 CSNAME 2 TEXT 3 TEXT
<code>\camel {...}</code> * TEXT
<code>\catcodetablename</code>
<code>\cbox ¹... {\²...}</code> OPT 1 TEXT 2 CONTENT
<code>\centeraligned {...}</code> * CONTENT

$\backslash\text{centerbox}$ $\overset{1}{\dots}$ $\{\overset{2}{\dots}\}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{centeredbox}$ $\overset{1}{\dots}$ $\{\overset{2}{\dots}\}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{centeredlastline}$
$\backslash\text{centerednextbox}$ $\overset{1}{\dots}$ $\{\overset{2}{\dots}\}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{centerline}$ $\{^*\dots\}$ * CONTENT
$\backslash\text{cernalinka}$ $[\dots\overset{*}{\dots}\dots]$ <small>OPT</small> * inherits: $\backslash\text{nastavcernelinky}$
$\backslash\text{cernelinky}$ $[\dots\overset{*}{\dots}\dots]$ <small>OPT</small> * inherits: $\backslash\text{nastavcernelinky}$
$\backslash\text{cfrac}$ $[\overset{1}{\dots}]$ $\{\overset{2}{\dots}\}$ $\{\overset{3}{\dots}\}$ <small>OPT</small> 1 l c r ll lc lr cl cc cr rl rc rr 2 CONTENT 3 CONTENT
$\backslash\text{cisla}$ $\{^*\dots\}$ * NUMMER
$\backslash\text{cislonadpisu}$ $[\overset{1}{\dots}]$ $[\overset{2}{\dots}]$ <small>OPT</small> 1 ABSCHNITT 2 predchozi aktualni dalsi prvni posledni
$\backslash\text{cislorovnice}$ $[\dots\overset{*}{\dots}\dots]$ <small>OPT</small> * REFERENCE
$\backslash\text{cislostrany}$
$\backslash\text{citace}$ $[\overset{1}{\dots}]$ $\{\overset{2}{\dots}\}$ <small>OPT</small> 1 SPRACHE 2 CONTENT

`\citation [...,\overset{1}{=},...,\overset{2}{=},...] [...]`

OPT

1 odkaz = REFERENCE
alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
authornum authoryear
pred = BEFEHL
po = BEFEHL
vlevo = BEFEHL
vpravo = BEFEHL
inherits: \setupbtx

2 REFERENCE

`\citation [...]\overset{1}{=},...] [...]\overset{2}{=},...]`

OPT

1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear
2 REFERENCE

`\citation {...}`

* REFERENCE

`\citation [...,\overset{1}{=},...,\overset{2}{=},...] [...,\overset{2}{=},...]`

1 odkaz = REFERENCE
alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
authornum authoryear
pred = BEFEHL
po = BEFEHL
vlevo = BEFEHL
vpravo = BEFEHL
inherits: \setupbtx

2 KEY = VALUE

`\cite [...,\overset{1}{=},...,\overset{2}{=},...] [...]`

OPT

1 odkaz = REFERENCE
alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
authornum authoryear
pred = BEFEHL
po = BEFEHL
vlevo = BEFEHL
vpravo = BEFEHL
inherits: \setupbtx

2 REFERENCE

`\cite [...]\overset{1}{=},...] [...]\overset{2}{=},...]`

OPT

1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear
2 REFERENCE

`\cite {...}`

* REFERENCE

`\cite [...,\overset{1}{=},...,\overset{2}{=},...] [...,\overset{2}{=},...]`

1 odkaz = REFERENCE
alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
authornum authoryear
pred = BEFEHL
po = BEFEHL
vlevo = BEFEHL
vpravo = BEFEHL
inherits: \setupbtx

2 KEY = VALUE

$\backslash\text{citovat}$ [¹ ...] { ² ...} <small>OPT</small> 1 SPRACHE 2 CONTENT
$\backslash\text{clap}$ {...} * CONTENT
$\backslash\text{classfont}$ { ¹ ...} { ² ...} 1 NAME 2 FONT
$\backslash\text{cldcommand}$ {...} * BEFEHL
$\backslash\text{cldcontext}$ {...} * BEFEHL
$\backslash\text{cldloadfile}$ {...} * FILE
$\backslash\text{cldprocessfile}$ {...} * FILE
$\backslash\text{cleftarrow}$ { ¹ ...} { ² ...} <small>OPT OPT</small> 1 TEXT 2 TEXT
$\backslash\text{collect}$ {...} * CONTENT
$\backslash\text{collectedtext}$ [..., ¹ ... _{OPT} ,...] [..., ² ... _{OPT} ,...] { ³ ...} { ⁴ ...} 1 inherits: \setupcollector 2 pismo = STYLE BEFEHL barva = COLOR inherits: \nastavoramovani 3 TEXT 4 CONTENT
$\backslash\text{collectexpanded}$ {...} * CONTENT
$\backslash\text{colorcomponents}$ {...} * COLOR
$\backslash\text{colored}$ [..., ¹ ... _{OPT} ,...] { ² ...} 1 inherits: \definujbarvu 2 CONTENT

$\backslash\text{colored}$ [¹ ...] { ² ...} 1 COLOR 2 CONTENT
$\backslash\text{coloronly}$ [¹ ...] { ² ...} 1 COLOR 2 CONTENT
$\backslash\text{columnbreak}$ [... [*] ...] <small>OPT</small> * ano ne nastaveni lokalne sila prvni posledni NUMMER NAME
$\backslash\text{combinepages}$ [¹ ...] [... ² ...] <small>OPT</small> 1 FILE 2 alternativa = a b c horizontalne vertikalne n = NUMMER nx = NUMMER ny = NUMMER start = NUMMER stop = NUMMER vzdalenost = DIMENSION vrsek = BEFEHL spodek = BEFEHL vlevo = BEFEHL vpravo = BEFEHL pred = BEFEHL po = BEFEHL mezi = BEFEHL ramecek = zap vyp pozadi = popredi barevne NAME barvapozadi = COLOR
$\backslash\text{commalistelement}$
$\backslash\text{commalistsentence}$ [... ¹ ...] [... ² ...] <small>OPT</small> 1 TEXT 2 TEXT
$\backslash\text{commalistsize}$
$\backslash\text{comparedimension}$ { ¹ ...} { ² ...} 1 DIMENSION 2 DIMENSION
$\backslash\text{comparedimensioneps}$ { ¹ ...} { ² ...} 1 DIMENSION 2 DIMENSION
$\backslash\text{completebtxrendering}$ [¹ ...] [... ² ...] <small>OPT</small> <small>OPT</small> 1 NAME 2 inherits: \setupbtxrendering
$\backslash\text{uplNyCOMBINEDLIST}$ [... [*] ...] <small>OPT</small> * inherits: \nastavseznam instances:

$\backslash\text{completelist } [\overset{1}{\dots}] [\dots, \dots, \overset{2}{\dots}, \dots]$ <small>OPT</small> 1 LISTE 2 inherits: \nastavseznam
$\backslash\text{completelistofFLOATS } [\dots, \dots, \overset{*}{\dots}, \dots]$ <small>OPT</small> * inherits: \nastavseznam
$\backslash\text{completelistofpublications } [\overset{1}{\dots}] [\dots, \dots, \overset{2}{\dots}, \dots]$ <small>OPT OPT</small> 1 NAME 2 inherits: \setupbt rendering
$\backslash\text{completelistofsorts } [\overset{1}{\dots}] [\dots, \dots, \overset{2}{\dots}, \dots]$ <small>OPT</small> 1 SINGULAR 2 inherits: \nastavtrideni
$\backslash\text{completelistofSORTS } [\dots, \dots, \overset{*}{\dots}, \dots]$ <small>OPT</small> * inherits: \nastavtrideni instances:
$\backslash\text{completelistofsynonyms } [\overset{1}{\dots}] [\dots, \dots, \overset{2}{\dots}, \dots]$ <small>OPT</small> 1 SINGULAR 2 inherits: \nastavsynonyma
$\backslash\text{completelistofSYNONYMS } [\dots, \dots, \overset{*}{\dots}, \dots]$ <small>OPT</small> * inherits: \nastavsynonyma instances:
$\backslash\text{completepagenumber}$
$\backslash\text{completere register } [\overset{1}{\dots}] [\dots, \dots, \overset{2}{\dots}, \dots]$ <small>OPT</small> 1 NAME 2 inherits: \nastavrejstrik
$\backslash\text{upl nyREGISTER } [\dots, \dots, \overset{*}{\dots}, \dots]$ <small>OPT</small> * inherits: \nastavrejstrik instances:
$\backslash\text{complexorsimple } \backslash \dots$ * CSNAME
$\backslash\text{complexorsimpleempty } \backslash \dots$ * CSNAME
$\backslash\text{complexorsimpleempty } \{ \dots \}$ * TEXT CSNAME

<code>\complexorsimple {...}</code> * TEXT CSNAME
<code>\composedcollector {...}</code> * NAME
<code>\composedlayer {...}</code> * NAME
<code>\compresult</code>
<code>\constantdimen \...</code> * CSNAME
<code>\constantdimenargument \...</code> * CSNAME
<code>\constantemptyargument \...</code> * CSNAME
<code>\constantnumber \...</code> * CSNAME
<code>\constantnumberargument \...</code> * CSNAME
<code>\contentreference [...¹,...] [...²_{OPT},...] {...³}</code> 1 REFERENCE 2 inherits: \nastavoramovani 3 CONTENT
<code>\continuednumber {...}</code> * NUMMER
<code>\continueifinputfile {...}</code> * FILE
<code>\convertargument ...¹ \to ...²</code> 1 TEXT 2 CSNAME
<code>\convertcommand \...¹ \to \...²</code> 1 CSNAME 2 CSNAME
<code>\convertedcounter [...¹] [...²_{OPT},...] {...}</code> 1 NAME 2 inherits: \setupcounter

<p>\converteddimen {...} {...}</p> <p>1 DIMENSION</p> <p>2 ex em pt in cm mm sp bp pc dd cc nc</p>
<p>\convertedsubcounter [...]¹ [...]² [...]³...</p> <p> OPT OPT</p> <p>1 NAME</p> <p>2 NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse</p> <p>3 inherits: \setupcounter</p>
<p>\convertmonth {...}</p> <p>* NUMMER</p>
<p>\convertvalue ...¹ \to ...²</p> <p>1 NAME</p> <p>2 CSNAME</p>
<p>\convertvboxtohbox</p>
<p>\copyLABELtext [...]¹ [...]²...</p> <p> OPT</p> <p>1 SPRACHE</p> <p>2 KEY = KEY</p> <p>instances:</p>
<p>\coppages [...]¹ [...]²... [...]³...</p> <p> OPT OPT</p> <p>1 FILE</p> <p>2 znaceni = zap vyp offset = DIMENSION n = NUMMER</p> <p>3 inherits: \setupexternalfigure</p>
<p>\copyparameters [...]¹ [...]² [...]³...</p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 KEY</p>
<p>\copyposition {...}¹ {...}²</p> <p>1 NAME</p> <p>2 NAME</p>
<p>\countersubs [...]¹ [...]²</p> <p> OPT</p> <p>1 NAME</p> <p>2 NUMMER</p>
<p>\counttoken ...¹ \in ...² \to ...³</p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 CSNAME</p>

$\backslash\text{counttokens}$ ¹ ... $\backslash\text{to}$ \backslash ² ... 1 TEXT 2 CSNAME
$\backslash\text{cramped}$ {...} * CONTENT
$\backslash\text{crampedclap}$ {...} * CONTENT
$\backslash\text{crampedllap}$ {...} * CONTENT
$\backslash\text{crampedrlap}$ {...} * CONTENT
$\backslash\text{crightarrow}$ ¹ {...} ² {...} OPT OPT 1 TEXT 2 TEXT
$\backslash\text{crightoverleftarrow}$ ¹ {...} ² {...} OPT OPT 1 TEXT 2 TEXT
$\backslash\text{ctop}$ ¹ ... ² {...} OPT 1 TEXT 2 CONTENT
$\backslash\text{ctxcommand}$ {...} * BEFEHL
$\backslash\text{ctxdirectcommand}$ {...} * BEFEHL
$\backslash\text{ctxdirectlua}$ {...} * BEFEHL
$\backslash\text{ctxfunction}$ {...} * NAME
$\backslash\text{CTXFUNCTIONDEFINITION}$
$\backslash\text{CTXFUNCTION}$
$\backslash\text{ctxlatecommand}$ {...} * BEFEHL

\ctxlatelua {...} * BEFEHL
\ctxloadluafile {...} * FILE
\ctxlua {...} * BEFEHL
\ctxluabuffer [...] <small>OPT</small> * BUFFER
\ctxluacode {...} * BEFEHL
\ctxreport {...} * BEFEHL
\ctxsprint {...} * BEFEHL
\currentassignmentlistkey
\currentassignmentlistvalue
\currentbtxuservariable {...} * KEY
\currentcommalistitem
\currentcomponent
\currentenvironment
\currentfeaturetest
\currentinterface
\currentPOPISEK [...] <small>1</small> [...] <small>2</small> {...} <small>OPT</small> <small>OPT</small> 1 REFERENCE 2 TEXT
\currentlanguage
\currentlistentrydestinationattribute
\currentlistentrylimitedtext {...} * TEXT

<code>\currentlistentrynumber</code>
<code>\currentlistentrypagenumber</code>
<code>\currentlistentryreferenceattribute {...}</code> * <code>cislo text cislostranky vse</code>
<code>\currentlistentrytitle</code>
<code>\currentlistentrytitlerendered</code>
<code>\currentlistsymbol</code>
<code>\currentmainlanguage</code>
<code>\currentmessagetext</code>
<code>\currentmoduleparameter {...}</code> * <code>KEY</code>
<code>\currentoutputstream</code>
<code>\currentproduct</code>
<code>\currentproject</code>
<code>\currentregime</code>
<code>\currentregisterpageuserdata {...}</code> * <code>KEY</code>
<code>\currentresponses</code>
<code>\currenttime [...*,...]</code> <div style="text-align: center; margin-left: 100px;"><small>OPT</small></div> * <code>h m TEXT</code>
<code>\currentvalue</code>
<code>\currentxtablecolumn</code>
<code>\currentxtablerow</code>
<code>\d {...}</code> * <code>CHARACTER</code>
<code>\dalsipodstranka</code>

<p><code>\datasetvariable {...} {...} {...}</code></p> <p>1 NAME</p> <p>2 NAME NUMMER</p> <p>3 KEY realpage</p>
<p><code>\datum [...,¹...,...] [...,²...,...]</code></p> <p><small>OPT</small> <small>OPT</small></p> <p>1 d = NUMMER</p> <p>m = NUMMER</p> <p>y = NUMMER</p> <p>2 inherits: \aktualnidatum</p>
<p><code>\dayoftheweek {...} {...} {...}</code></p> <p>1 NUMMER</p> <p>2 NUMMER</p> <p>3 NUMMER</p>
<p><code>\dayspermonth {...} {...}</code></p> <p>1 NUMMER</p> <p>2 NUMMER</p>
<p><code>\dbinom {...} {...}</code></p> <p>1 CONTENT</p> <p>2 CONTENT</p>
<p><code>\ddot {...}</code></p> <p>* CHARACTER</p>
<p><code>\decrement *...</code></p> <p>* CSNAME</p>
<p><code>\decrementcounter [...] [...²]</code></p> <p><small>OPT</small></p> <p>1 NAME</p> <p>2 NUMMER</p>
<p><code>\decrementedcounter [...]</code></p> <p>* NAME</p>
<p><code>\decrementpagenumber</code></p>
<p><code>\decrementsubpagenumber</code></p>
<p><code>\decrementvalue {...}</code></p> <p>* NAME</p>
<p><code>\decrement cd:parentheses-1</code></p> <p>* CSNAME NUMMER</p>
<p><code>\defaultinterface</code></p>

<code>\defaultobjectpage</code>
<code>\defaultobjectreference</code>
<code>\defcatcodecommand \¹... \²... {\³...}</code> 1 CSNAME 2 CHARACTER NUMMER 3 BEFEHL
<code>\defconvertedargument \¹... {\²...}</code> 1 CSNAME 2 TEXT
<code>\defconvertedcommand \¹... \²...</code> 1 CSNAME 2 CSNAME
<code>\defconvertedvalue \¹... {\²...}</code> 1 CSNAME 2 NAME
<code>\defineactivecharacter ... {\²...}</code> 1 CHARACTER 2 BEFEHL
<code>\definealternativestyle [...,\¹...] [...,\²...] [...,\³...]</code> 1 NAME 2 BEFEHL 3 BEFEHL
<code>\defineanchor [...,\¹...] [...,\²...] [...,\³...,\⁴...,\⁵...] [...,\⁶...,\⁷...,\⁸...]</code> <div style="display: flex; justify-content: space-around; width: 100%;"> OPT OPT </div> 1 NAME 2 NAME 3 inherits: \setupplayer 4 inherits: \setupplayerinherits: \nastavoramovani
<code>\defineattachment [...,\¹...] [...,\²...] [...,\³...,\⁴...,\⁵...]</code> <div style="display: flex; justify-content: space-around; width: 100%;"> OPT OPT </div> 1 NAME 2 NAME 3 inherits: \setupattachment
<code>\defineattribute [...,\¹...] [...,\²...,\³...]</code> <div style="display: flex; justify-content: space-around; width: 100%;"> OPT </div> 1 NAME 2 lokalne globalne public private

\definebackground [¹...] [²...] [³..._{OPT}..._{OPT}]

- 1 NAME
- 2 NAME
- 3 inherits: \nastavpozadi

\definebar [¹...] [²...] [³..._{OPT}..._{OPT}]

- 1 NAME
- 2 NAME
- 3 inherits: \setupbar

\definebodyfontswitch [¹...] [²...]

- 1 NAME
- 2 inherits: \nastavzakladnifont

\definebreakpoint [¹...] [²...] [³..._{OPT}..._{OPT}]

- 1 NAME
- 2 CHARACTER
- 3

typ	=	1 2 3 4 5
nvlevo	=	NUMMER
nvpravo	=	NUMMER
vlevo	=	BEFEHL
stredni	=	BEFEHL
vpravo	=	BEFEHL
range	=	ano ne
language	=	SPRACHE

\definebreakpoints [...]

- * NAME

\definebtx [¹...] [²...] [³..._{OPT}..._{OPT}]

- 1 NAME
- 2 NAME
- 3 inherits: \setupbtx

\definebtxdataset [¹...] [²...] [³..._{OPT}..._{OPT}]

- 1 NAME
- 2 NAME
- 3 inherits: \setupbtxdataset

\definebtxregister [¹...] [²...] [³..._{OPT}..._{OPT}]

- 1 NAME
- 2 NAME
- 3 inherits: \setupbtxregister

\definebtxrendering [¹...] [²...] [³..._{OPT}..._{OPT}]

- 1 NAME
- 2 NAME
- 3 inherits: \setupbtxrendering

```
1  NAME
2  NAME
3  inherits: \setupbutton
```

```
1  NAME
2  NAME
3  inherits: \nastavkapitalky
```

```
1  NAME
2  NAME
3  inherits: \setupcollector
```

```
1  NAME
2  ano ne nastaveni lokalne sila prvi posledni NUMMER
```

```
1  NAME
2  NAME
3  inherits: \setupcombination
```

```
1  NAME
2  NAME
3  inherits: \nastavkomentar
```

* CSNAME

* CSNAME

* TEXT CSNAME

* TEXT CSNAME

```

1  NAME SECTIONBLOCK:NAME
2  NAME PROCESSOR->NAME
3  NAME PROCESSOR->NAME

```

`\definecounter` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupcounter

`\definedataset` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupdataset

`\definedelimitedtext` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupdelimitedtext

`\definedfont` [^{*}...]_{OPT}

- * FONT

`\defineeffect` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupeffect

`\defineexpandable` [¹...] [²...] [³..._{OPT}{...}]

- 1 NUMMER
- 2 CSNAME
- 3 CONTENT

`\defineexternalfigure` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupexternalfigure

`\definefallbackfamily` [¹...] [²...] [³...] [⁴..._{OPT}...]

- 1 NAME
- 2 rm ss tt mm hw cg antikva serif pravidelne bezserifu sans podpora strojopis opis mono rukopisne kaligraficke math matematika
- 3 FONT
- 4

rsc	=	NUMMER
designsize	=	implicitni auto
goodies	=	FILE
range	=	NUMMER NAME
offset	=	NUMMER NAME
check	=	ano ne
sila	=	ano ne
features	=	NAME
tf	=	TEXT
bf	=	TEXT
it	=	TEXT
sl	=	TEXT
bi	=	TEXT
bs	=	TEXT
sc	=	TEXT

`\definefallbackfamily [...]1 [...]2 [...]3 [...]4,...]`
OPT

- 1 NAME
- 2 rm ss tt mm hw cg antikva serif pravidelne bezserifu sans podpora strojopis opis mono rukopisne kaligraficke math matematika
- 3 FONT
- 4 NAME

`\definefieldbody [...]1 [...]2 [...]3,...]`
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupfieldbody

`\definefieldbodyset [...]1 [...]2,...]`

- 1 NAME
- 2 NAME

`\definefieldcategory [...]1 [...]2 [...]3,...]`
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupfieldcategory

`\definefileconstant {...}1 {...}2`

- 1 NAME
- 2 NAME

`\definefilefallback [...]1 [...]2,...]`

- 1 NAME
- 2 FILE

`\definefilesynonym [...]1 [...]2`

- 1 NAME
- 2 FILE

`\definefiller [...]1 [...]2 [...]3,...]`
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupfiller

`\definefirstline [...]1 [...]2 [...]3,...]`
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupfirstline

`\definefittingpage [...]1 [...]2 [...]3,...]`
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupfittingpage

`\definefontalternative [...]`

* NAME

`\definefontfallback [...]1 [...]2 [...]3,...4 [...],...4,...]`
OPT

1 NAME

2 FONT NAME

3 NAME NUMMER

4 rscale = NUMMER
sila = ano ne
check = ano ne
offset = NUMMER NAME

`\definefontfamily [...]1 [...]2 [...]3 [...],...4,...]`
OPT

1 NAME

2 rm ss tt mm hw cg antikva serif pravidelne bezserifu sans podpora strojopis opis mono rukopisne kaligraficke math matematika

3 FONT

4 rscale = NUMMER
designsize = implicitni auto
goodies = FILE
features = NAME
tf = TEXT
bf = TEXT
it = TEXT
sl = TEXT
bi = TEXT
bs = TEXT
sc = TEXT

`\definefontfamilypreset [...]1 [...],...2,...]`

1 NAME

2 inherits: \definefontfamily

`\definefontfamilypreset [...]1 [...]2`

1 NAME

2 NAME

`\definefontfamily [...]1 [...]2 [...]3 [...],...4,...]`
OPT

1 NAME

2 rm ss tt mm hw cg antikva serif pravidelne bezserifu sans podpora strojopis opis mono rukopisne kaligraficke math matematika

3 FONT

4 NAME

`\definefontfeature` [¹...] [²...] [³...,..._{OPT}...]

```

1  NAME
2  NAME
3  language      = NAME
    script       = NAME auto
    mode         = node base auto zadny
    liga         = ano ne
    kern         = ano ne
    extrakerns   = ano ne
    tlig         = ano ne
    trep         = ano ne
    missing      = ano ne
    dummies      = ano ne
    analyze      = ano ne
    unicoding    = ano ne
    expanzen     = NAME
    protrusion   = NAME
    nostackmath  = ano ne
    realdimensions = ano ne
    itlc         = ano ne
    textitalics  = ano ne
    mathitalics  = ano ne
    slant        = NUMMER
    extend       = NUMMER
    dimensions   = NUMMER
    boundingbox  = ano ne
    compose     = ano ne
    char-ligatures = ano ne
    compat-ligatures = ano ne
    goodies      = FILE
    extrafeatures = ano ne
    featureset   = NAME
    colorsheme   = NAME
    postprocessor = NAME
    mathdimensions = NAME
    keepligatures = ano ne auto
    devanagari   = ano ne
    features     = ano ne
    tcom         = ano ne
    anum         = ano ne
    mathsize     = ano ne
    decomposehangul = ano ne
    mathalternatives = ano ne
    mathgaps     = ano ne
    checkmarks   = ano ne
    NAME         = ano ne
    mathnolimitsmode = NUMMER

```

`\definefontfile` [¹...] [²...] [³...,..._{OPT}...]

```

1  NAME
2  FILE
3  features      = NAME
    fallbacks    = NAME
    goodies      = NAME
    designsize   = auto implicitni

```

`\definefontsize` [...]

```

*  NAME

```

`\definefontsolution` [¹...] [²...] [³...,..._{OPT}...]

```

1  NAME
2  NAME
3  inherits: \setupfontsolution

```

`\defineformula` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupformula

`\defineformulaalternative` [¹...] [²...] [³...]

- 1 NAME
- 2 CSNAME
- 3 CSNAME

`\defineformulaframed` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupformulaframed

`\defineframedcontent` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupframedcontent

`\definefrozenfont` [¹...] [²...]

- 1 NAME
- 2 FONT

`\defineglobalcolor` [¹...] [²...₂...]

- 1 NAME
- 2 inherits: \definujbarvu

`\defineglobalcolor` [¹...] [²...]

- 1 NAME
- 2 COLOR

`\definegraphictypesynonym` [¹...] [²...]

- 1 NAME
- 2 NAME

`\definegridsnapping` [¹...] [²...₂...]

- 1 NAME
- 2 lokalne globalne noheight nodepth box max min zadny radek pulradku prvni posledni minvyska maxheight mindepth maxdepth vrsek spodek strut NUMMER minheight:NUMMER maxheight:NUMMER mindepth:NUMMER maxdepth:NUMMER box:NUMMER top:NUMMER bottom:NUMMER offset:NUMMER

`\defineheadalternative` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupheadalternative

`\definehelp [...]1 [...]2 [...]3...`

OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setuphelp

`\definehigh [...]1 [...]2 [...]3...`

OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setuphigh

`\definehighlight [...]1 [...]2 [...]3...`

OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setuphighlight

`\definehspace [...]1 [...]2 [...]3`

OPT

- 1 NAME
- 2 NAME
- 3 DIMENSION

`\definehyphenationfeatures [...]1 [...]2...`

- 1 NAME
- 2 characters = TEXT
hyphens = ano vse TEXT
joiners = ano vse TEXT
rightwords = NUMMER
hyphenmin = NUMMER
lefthyphenmin = NUMMER
righthyphenmin = NUMMER
lefthyphenchar = NUMMER
righthyphenchar = NUMMER
alternativa = original tex hyphenate expanded traditional zadny
pravahrana = tex
rightchars = slovo NUMMER

`\definecharacterkerning [...]1 [...]2 [...]3...`

OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupcharacterkerning

`\definecharacterspacing [...]*`

- * NAME

`\definechemical [...]1 {...}2`

- 1 NAME
- 2 CONTENT

`\definechemicals [...]1 [...]2 [...]3...`

OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupchemical

`\definechemicalsymbol [1.] [2.]`

- 1 NAME
- 2 TEXT

`\defineindentedtext [1.] [2.] [3...3...]`
 OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupindentedtext

`\defineindenting [1.] [2...]`

- 1 NAME
- 2 [-+]male [-+]stredni [-+]velke zadny ne ne prvni dalsi ano vzdy nikdy liche sude normalni reset toggle DIMENSION

`\defineinitial [1.] [2.] [3...3...]`
 OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupinitial

`\defineinsertion [1.] [2.] [3...3...]`
 OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupinsertion

`\defineinteraction [1.] [2.] [3...3...]`
 OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \nastavinterakci

`\defineinteractionbar [1.] [2.] [3...3...]`
 OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \nastavinterakcnilistu

`\defineinterfaceconstant {1.} {2.}`

- 1 NAME
- 2 NAME

`\defineinterfaceelement {1.} {2.}`

- 1 NAME
- 2 NAME

`\defineinterfacevariable {1.} {2.}`

- 1 NAME
- 2 NAME

`\defineinterlinespace` [¹...] [²...] [³..._{OPT}..._{OPT}]

- 1 NAME
- 2 NAME
- 3 inherits: \nastavmeziradkovoumezeru

`\defineintermediatecolor` [¹...] [²..._{OPT}...] [³..._{OPT}..._{OPT}]

- 1 NAME
- 2 COLOR NUMMER
- 3 a = NUMMER
t = NUMMER

`\defineitemgroup` [¹...] [²...] [³..._{OPT}..._{OPT}]

- 1 NAME
- 2 NAME
- 3 inherits: \setupitemgroup

`\defineitems` [¹...] [²...] [³..._{OPT}..._{OPT}]

- 1 NAME
- 2 NAME
- 3 inherits: \nastavpolozky

`\definelabelclass` [¹...] [²..._{OPT}]

- 1 NAME
- 2 NUMMER

`\definelayer` [¹...] [²...] [³..._{OPT}..._{OPT}]

- 1 NAME
- 2 NAME
- 3 inherits: \setuplayer

`\definelayerpreset` [¹...] [²..._{OPT}..._{OPT}]

- 1 NAME
- 2 inherits: \setuplayer

`\definelayerpreset` [¹...] [²...]

- 1 NAME
- 2 NAME

`\definelayout` [¹...] [²...] [³..._{OPT}..._{OPT}]

- 1 NAME
- 2 NAME
- 3 inherits: \nastavvzhled

`\definelinefiller` [¹...] [²...] [³..._{OPT}..._{OPT}]

- 1 NAME
- 2 NAME
- 3 inherits: \setuplinefiller

`\definelinenote [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setuplinenote

`\definelinenumbering [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \nastavcislovaniradku

`\definelines [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \nastavradky

`\definelistalternative [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setuplistalternative

`\definelistextra [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setuplistextra

`\definelow [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setuplow

`\definelowhigh [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setuplowhigh

`\definelowmidhigh [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setuplowmidhigh

`\defineMPinstance [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setupMPinstance

`\definemarginblock` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupmarginblock

`\definemargindata` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupmargindata

`\definemarkers` [...]

- * NAME

`\definemathaccent` ...¹ ...²

- 1 NAME
- 2 CHARACTER

`\definemathalignment` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupmathalignment

`\definemathcases` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupmathcases

`\definemathcommand` [¹...] [²...] [³...] {⁴..._{OPT}..._{OPT}..._{OPT}}

- 1 NAME
- 2 ord op bin rel open close punct alpha uvnitr nothing limop noloop box
- 3 jedna dve
- 4 BEFEHL \...##1 \...##1##2

`\definemathdoubleextensible` [¹...] [²...] [³...] [⁴..._{OPT}...]

- 1 obe vfenced
- 2 NAME
- 3 NUMMER
- 4 NUMMER

`\definemathtics` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupmathtics

```
\definemathextensible [1...] [2...] [3...]
                        OPT
1  reverse matematika text chemistry
2  NAME
3  NUMMER
```

```
\definemathfence [1...] [2...] [3...,...3...,...]
                  OPT          OPT
1  NAME
2  NAME
3  inherits: \setupmathfence
```

```
\definemathfraction [1...] [2...] [3...,...3...,...]
                   OPT          OPT
1  NAME
2  NAME
3  inherits: \setupmathfraction
```

```
\definemathframed [1...] [2...] [3...,...3...,...]
                  OPT          OPT
1  NAME
2  NAME
3  inherits: \setupmathframed
```

```
\definemathmatrix [1...] [2...] [3...,...3...,...]
                  OPT          OPT
1  NAME
2  NAME
3  inherits: \setupmathmatrix
```

```
\definemathornament [1...] [2...] [3...,...3...,...]
                   OPT          OPT
1  NAME
2  NAME
3  inherits: \setupmathornament
```

```
\definemathoverextensible [1...] [2...] [3...]
                        OPT
1  vrsek vfenced
2  NAME
3  NUMMER
```

```
\definemathovertextextensible [1...] [2...] [3...]
                        OPT
1  bothtext
2  NAME
3  NUMMER
```

```
\definemathradical [1...] [2...] [3...,...3...,...]
                  OPT          OPT
1  NAME
2  NAME
3  inherits: \setupmathradical
```



```
\definemathstackers [...]1 [...]2 [...,...]3...,...]  

                                OPT      OPT
```

- 1 NAME
- 2 NAME
- 3 inherits: \setupmathstackers

```
\definemathstyle [...]1 [...]2,...
```

- 1 NAME
- 2 obrazovka text script scriptscript cramped uncramped normalni zhustene male velke

```
\definemathtriplet [...]1 [...]2 [...]3  

                                OPT      OPT
```

- 1 NAME
- 2 NAME
- 3 TEXT

```
\definemathunderextensible [...]1 [...]2 [...]3  

                                OPT
```

- 1 spodek vfenced
- 2 NAME
- 3 NUMMER

```
\definemathundertextextensible [...]1 [...]2 [...]3  

                                OPT
```

- 1 bothtext
- 2 NAME
- 3 NUMMER

```
\definemathunstacked [...]1 [...]2 [...]3  

                                OPT
```

- 1 siroce
- 2 NAME
- 3 NUMMER

```
\definemeasure [...]1 [...]2
```

- 1 NAME
- 2 DIMENSION

```
\definemessageconstant {...}
```

- * NAME

```
\definemixedcolumns [...]1 [...]2 [...,...]3...,...]  

                                OPT      OPT
```

- 1 NAME
- 2 NAME
- 3 inherits: \setupmixedcolumns

```
\definemode [...]1,... [...]2  

                                OPT
```

- 1 NAME
- 2 ano ne drzet

```
\definemultitonecolor [...]1 [...]2 [...]3 [...]4
                                OPT
1  NAME
2  COLOR = NUMMER
3  inherits: \definujbarvu
4  inherits: \definespotcolor
```

```
\definenamecolor [...]1 [...]2
1  NAME
2  inherits: \definujbarvu
```

```
\definenamecolor [...]1 [...]2
1  NAME
2  COLOR
```

```
\definamespace [...]1 [...]2
1  NAME
2  jmeno = TEXT
    parent = TEXT
    pismo = ano ne
    prikaz = ano ne seznam
    setup = ano ne seznam
    set = ano ne seznam
    ramecek = ano ne
```

```
\definennarrower [...]1 [...]2 [...]3
                                OPT      OPT
1  NAME
2  NAME
3  inherits: \nastavzuzeni
```

```
\definernote [...]1 [...]2 [...]3
                                OPT      OPT
1  NAME
2  NAME
3  inherits: \setupnote
```

```
\defineornament [...]1 [...]2 [...]3
                                OPT
1  NAME
2  alternativa = a b
    inherits: \setupcollector
3  pismo = STYLE BEFEHL
    barva = COLOR
    inherits: \nastavoramovani
```

```
\defineornament [...]1 [...]2 [...]3
                                OPT
1  NAME
2  alternativa = a b
    inherits: \setuplayer
3  inherits: \setuplayeredtext
```

```
\defineoutputroutine [...]1 [...]2 [...]3
                                OPT      OPT
1  NAME
2  NAME
3  inherits: \setupoutputroutine
```

<pre>\defineoutputroutinecommand [...,*,...]</pre> <p>* KEY</p>
<pre>\definepage [...¹] [...²]</pre> <p>1 NAME</p> <p>2 REFERENCE</p>
<pre>\definepagebreak [...¹] [...,²,...]</pre> <p>1 NAME</p> <p>2 prazdne zahlavi upati dummy ramecek NUMMER +NUMMER implicitni reset zablockovat ano ne zlom prazdny nastaveni vysokapriorita vlevo vpravo sude liche ctyrnasobny posledni poslednistrana start stop</p>
<pre>\definepagegrid [...¹] [...²]_{OPT} [...,³...]_{OPT},...]</pre> <p>1 NAME</p> <p>2 NAME</p> <p>3 inherits: \setuppagegrid</p>
<pre>\definepagegridarea [...¹] [...²]_{OPT} [...,³...]_{OPT},...]</pre> <p>1 NAME</p> <p>2 NAME</p> <p>3 inherits: \setuppagegridarea</p>
<pre>\definepagegridspan [...¹] [...²]_{OPT} [...,³...]_{OPT},...]</pre> <p>1 NAME</p> <p>2 NAME</p> <p>3 inherits: \setuppagegridspan</p>
<pre>\definepagechecker [...¹] [...²]_{OPT} [...,³...]_{OPT},...]</pre> <p>1 NAME</p> <p>2 NAME</p> <p>3 inherits: \setuppagechecker</p>
<pre>\definepageinjection [...¹] [...²]_{OPT} [...,³...]_{OPT},...]</pre> <p>1 NAME</p> <p>2 NAME</p> <p>3 inherits: \setuppageinjection</p>
<pre>\definepageinjectionalternative [...¹] [...²]_{OPT} [...,³...]_{OPT},...]</pre> <p>1 NAME</p> <p>2 NAME</p> <p>3 inherits: \setuppageinjectionalternative</p>
<pre>\definepageshift [...¹] [...²]_{OPT} [...,³,...]</pre> <p>1 NAME</p> <p>2 horizontalne vertikalne</p> <p>3 DIMENSION</p>

`\definepagestate [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setuppagestate

`\definepairedbox [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setuppairedbox

`\defineparagraph [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setupparagraph

`\defineparallel [...]1 [...]2,...`

1 NAME

2 NAME

`\defineparbuilder [...]*`

* NAME

`\defineplacement [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setupplacement

`\definepositioning [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \nastavumistovani

`\defineprefixset [...]1 [...]2,... [...]3`
OPT

1 NAME SECTIONBLOCK:NAME

2 ABSCHNITT

3 ABSCHNITT

`\defineprocesscolor [...]1 [...]2 [...,...3...,...]`
OPT

1 NAME

2 COLOR

3 inherits: \definujbarvu

`\defineprocessor [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setupprocessor

`\definepushbutton [1...] [2...OPT...]`

- 1 NAME
- 2 inherits: \setupfieldcontentframed

`\definepushsymbol [1...] [2...]`

- 1 NAME
- 2 n r d

`\definerenderingwindow [1...] [2...OPT] [3...OPT...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setuprenderingwindow

`\defineresetset [1...] [2...OPT...] [3...]`

- 1 NAME SECTIONBLOCK:NAME
- 2 NUMMER
- 3 NUMMER

`\definescale [1...] [2...OPT] [3...OPT...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupscale

`\definescript [1...] [2...OPT] [3...OPT...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupscript

`\definesectionlevels [1...] [2...OPT...]`

- 1 NAME
- 2 ABSCHNITT

`\defineselector [1...] [2...OPT...]`

- 1 NAME
- 2 inherits: \setupselector

`\defineseparatorset [1...] [2...OPT...] [3...]`

- 1 NAME SECTIONBLOCK:NAME
- 2 BEFEHL PROCESSOR->BEFEHL
- 3 BEFEHL PROCESSOR->BEFEHL

`\defineshift [1...] [2...OPT] [3...OPT...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupshift

```
1  NAME
2  NAME
3  inherits: \setupsidebar
```

```
1  ano ne
2  SINGULAR
3  NAME
4  CONTENT
```

1	NAME
2	COLOR
3	<p>a = NUMMER zadny normalni multiply rastr prekryv softlight hardlight colordodge colorburn darken lighten difference exclusion hue saturation barevne luminosity</p> <p>t = NUMMER</p> <p>e = TEXT</p> <p>p = NUMMER</p>

```

1  NAME
2  rm ss tt mm hw cg
3  tf bf it sl bi bs sc
4  BEFEHL

```

```
1 NAME
2 NAME
3 inherits: \setupsformula
```

```
1  ano ne
2  SINGULAR
3  NAME
4  TEXT
5  CONTENT
```

```
1  NAME
2  lokalne globalne public private
```

* NAME

* NAME

<pre> \defineTABLEsetup [...] [.,.,.².,.,.] 1 NAME 2 inherits: \setupTABLE </pre>
<pre> \definetabulation [...] [².] [³.,.,.] OPT OPT 1 NAME 2 NAME 3 inherits: \setuptabulation </pre>
<pre> \definetextbackground [...] [².] [³.,.,.³.,.,.] OPT OPT 1 NAME 2 NAME 3 inherits: \setuptextbackground </pre>
<pre> \definetextflow [...] [².] [³.,.,.³.,.,.] OPT OPT 1 NAME 2 NAME 3 inherits: \setuptextflow </pre>
<pre> \definetooltip [...] [².] [³.,.,.³.,.,.] OPT OPT 1 NAME 2 NAME 3 inherits: \setuptooltip </pre>
<pre> \definetransparency [¹.] [².] 1 NAME 2 NUMMER </pre>
<pre> \definetransparency [¹.] [².,.,.².,.,.] 1 NAME 2 a = NUMMER zadny normalni multiply rastr prekryv softlight hardlight colordodge colorburn darken lighten difference exclusion hue saturation barevne luminosity t = NUMMER </pre>
<pre> \definetransparency [¹.] [².] 1 NAME 2 NAME </pre>
<pre> \definetwopasslist {...} * NAME </pre>
<pre> \definetype [¹.] [².] [³.,.,.³.,.,.] OPT OPT 1 NAME 2 NAME 3 inherits: \nastavtype </pre>

```

\definetypesface [...] [...] [...] [...] [...] [...] [...] [...] [...]
1 OPT 2 OPT 3 4 5 6
1 NAME
2 rm ss tt mm hw cg
3 serif sans mono math handwriting calligraphy
4 NAME
5 implicitni dtp
6 rscale = auto NUMMER
  features = NAME
  fallbacks = NAME
  goodies = NAME
  designsize = auto implicitni
  smer = obe

```

```

\definetypescriptprefix [...] [...]
1 NAME
2 TEXT

```

```

\definetypescriptsynonym [...] [...]
1 NAME
2 TEXT

```

```

\definetypesetting [...] [...] [...] [...]
1 OPT 2 OPT 3
1 NAME
2 TEXT
3 inherits: \setuexternalfigure

```

```

\defineunit [...] [...] [...] [...]
1 OPT 2 OPT 3
1 NAME
2 NAME
3 inherits: \setupunit

```

```

\defineviewerlayer [...] [...] [...] [...]
1 OPT 2 OPT 3
1 NAME
2 NAME
3 inherits: \setupviewerlayer

```

```

\definevspace [...] [...] [...]
1 OPT 2 3
1 NAME
2 NAME
3 DIMENSION

```

```

\definevspacing [...] [...]
1 NAME
2 inherits: \vspacing

```

```

\definevspacingamount [...] [...] [...]
1 OPT 2 OPT 3
1 NAME
2 DIMENSION
3 DIMENSION

```



```
\definexable [...] [1...] [2...] [3...OPT...]
```

- 1 NAME
- 2 NAME
- 3 inherits: \setupxtable

```
\definuj [1...] [2...] {3...}
```

- 1 NUMMER
- 2 CSNAME
- 3 CONTENT

```
\definujakcent 1... 2... 3...
```

- 1 CHARACTER
- 2 CHARACTER
- 3 CHARACTER

```
\definujbarvu [1...] [2...OPT...]
```

- 1 NAME
- 2 r = NUMMER
g = NUMMER
b = NUMMER
c = NUMMER
m = NUMMER
y = NUMMER
k = NUMMER
h = NUMMER
s = NUMMER
v = NUMMER
x = NUMMER
a = NUMMER zadny normalni multiply rastr prekryv softlight hardlight colordodge colorburn darken lighten difference
exclusion hue saturation barevne luminosity
t = NUMMER

```
\definujbarvu [1...] [2...]
```

- 1 NAME
- 2 COLOR

```
\definujblok [1...] [2...] [3...OPT...]
```

- 1 NAME
- 2 NAME
- 3 inherits: \nastavblok

```
\definujbloksekce [1...] [2...] [3...OPT...]
```

- 1 NAME
- 2 NAME
- 3 inherits: \nastavbloksekce

```
\definujbuffer [1...] [2...] [3...OPT...]
```

- 1 NAME
- 2 BUFFER
- 3 inherits: \nastavbuffer

`\definujfont [...]1 [...]2 [...,...3...,...]`
OPT

1 NAME

2 FONT

3 inherits: \nastavmeziradkovoumezeru

`\definujfont [...]1 [...]2 [...]3`
OPT

1 NAME

2 FONT

3 NAME

`\definujformatodkazu [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setupreferenceformat

`\definujhbox [...]1 [...]2`

1 NAME

2 DIMENSION

`\definujinterakcnimenu [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \nastavinterakcnimenu

`\definujkombinovanyseznam [...]1 [...,...]2 [...,...3...,...]`
OPT

1 NAME

2 LISTE

3 inherits: \nastavseznam

`\definujkonverzi [...]1 [...]2 [...]3`
OPT

1 SPRACHE

2 NAME

3 CSNAME

`\definujkonverzi [...]1 [...]2 [...,...]3`
OPT

1 SPRACHE

2 NAME

3 TEXT

`\definujnadpis [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 ABSCHNITT

3 inherits: \nastavnadpis

`\definujobrazeksymbol [...]1 [...]2 [...,...3...,...]`
OPT

1 NAME

2 FILE NAME

3 inherits: \externiobraz

`\definujodkaz [...]1 [...]2,...]`

1 NAME

2 REFERENCE

`\definujodstavce [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \nastavodstavce

`\definujopis [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \nastavopis

`\definujoramovani [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \nastavoramovani

`\definujoramovanytext [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setupframedtext

`\definujpaletu [...]1 [...,...2...,...]`

1 NAME

2 NAME = COLOR

`\definujpaletu [...]1 [...]2`

1 NAME

2 NAME

`\definujplvouciobjekt [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 SINGULAR

2 PLURAL

3 inherits: \nastavplvouciobjekt

instances: chemical figure table intermezzo graphic

```
\definujplvouciobjekt [...] [...] [...]
                        OPT      OPT
```

- 1 SINGULAR
- 2 PLURAL
- 3 SINGULAR

instances: chemical figure table intermezzo graphic

```
\definujpodpole [...] [...] [...]...
```

- 1 NAME
- 2 NAME
- 3 NAME

```
\definujpole [...] [...] [...] [...] [...]...
```

- 1 NAME
- 2 radio pod text radek push check signature
- 3 NAME
- 4 NAME
- 5 NAME

```
\definujpopis [...] [...] [...]...3...
                        OPT      OPT
```

- 1 NAME
- 2 NAME
- 3 inherits: \setupdescription

```
\definujpopisek [...] [...] [...]...3...
                        OPT      OPT
```

- 1 NAME
- 2 NAME
- 3 inherits: \setuplabel

```
\definujprekryv [...]...1 [...] [...] [...]
                        OPT
```

- 1 NAME
- 2 NAME
- 3 BEFEHL

```
\definujprikaz ...1 ...2
```

- 1 CHARACTER
- 2 BEFEHL

```
\definujprofil [...] [...] [...]...3...
                        OPT      OPT
```

- 1 NAME
- 2 NAME
- 3 inherits: \setupprofile

```
\definujprogram [...] [...] [...]...3
                        OPT
```

- 1 NAME
- 2 TEXT
- 3 TEXT

`\definujprostredizakladnihofontu` [¹...] [²...] [³...,...³...,...]

OPT

OPT

- 1 NAME
- 2 implicitni DIMENSION
- 3

velky	=	DIMENSION NUMMER
male	=	DIMENSION NUMMER
a	=	DIMENSION NUMMER
b	=	DIMENSION NUMMER
c	=	DIMENSION NUMMER
d	=	DIMENSION NUMMER
text	=	DIMENSION NUMMER
x	=	DIMENSION NUMMER
xx	=	DIMENSION NUMMER
script	=	DIMENSION NUMMER
scriptscript	=	DIMENSION NUMMER
meziradkovamezera	=	DIMENSION
em	=	sklonene kurziva STYLE BEFEHL
*	=	NUMMER

`\definujrejstrik` [¹...] [²...] [³...,...³...,...]

OPT

OPT

- 1 NAME
- 2 NAME
- 3 inherits: \nastavrejstrik

`\definujsablonutabulky` [¹...] [|²...|] [³...] [⁴...]

OPT

OPT

- 1 NAME
- 2 TEMPLATE
- 3 NAME
- 4 NAME

`\definujsekci` [...]

- * NAME

`\definujseznam` [¹...] [²...] [³...,...³...,...]

OPT

OPT

- 1 NAME
- 2 LISTE
- 3 inherits: \nastavseznam

`\definujskupinubarev` [¹...] [²...] [x:y:³z,...]

OPT

- 1 NAME
- 2 seda rgb cmyk spot
- 3 TRIPLET

`\definujstartstop` [¹...] [²...] [³...,...³...,...]

OPT

OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupstartstop

`\definujstyl` [¹...] [²...] [³...,...³...,...]

OPT

OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupstyle

`\definujstylfontu [...1,...] [...2]`

1 NAME

2 NAME

`\definujsymbol [...1] [...2] [...3]`
OPT

1 NAME

2 NAME

3 BEFEHL

`\definujsynonumfontu [...1] [...2] [...3OPT,...3,...]`

1 NAME

2 FONT

3 features = NAME
fallbacks = NAME
goodies = NAME
designsize = auto implicitni

`\definujsynonyma [...1] [...2] [...3OPT] [...4OPT]`

1 SINGULAR

2 PLURAL

3 CSNAME

4 CSNAME

`\definujtabelaci [...1] [...2OPT] [...3OPT /... /]`

1 NAME

2 NAME

3 TEMPLATE

`\definujtext [...1] [...2] [...3OPT] [...4] [...5OPT] [...6OPT] [...7OPT]`

1 NAME

2 vrsek zahlavi text upati spodek

3 text marginalie hrana

4 datum cislostranky BESCHRIFTUNG TEXT BEFEHL

5 datum cislostranky BESCHRIFTUNG TEXT BEFEHL

6 datum cislostranky BESCHRIFTUNG TEXT BEFEHL

7 datum cislostranky BESCHRIFTUNG TEXT BEFEHL

`\definujtrideni [...1] [...2] [...3OPT]`

1 SINGULAR

2 PLURAL

3 zadny CSNAME

`\definujupravu [...1] [...2OPT] [...3OPT,...3,...]`

1 NAME

2 NAME

3 inherits: \nastavupravu

`\definujvelikostpapiru [...]1 [...,...2...,...]`

```
1 NAME
2 sirka      = DIMENSION
  vyska      = DIMENSION
  vrsek      = BEFEHL
  spodek     = BEFEHL
  vlevo      = BEFEHL
  vpravo     = BEFEHL
  vzdalenost = DIMENSION
  stranka    = inherits: \nastavvelikostpapiru
  papir      = inherits: \nastavvelikostpapiru
```

`\definujvelikostpapiru [...]1 [...,...2...] [...,...3...] OPT`

```
1 NAME
2 inherits: \nastavvelikostpapiru
3 inherits: \nastavvelikostpapiru
```

`\definujvycet [...]1 [...]2 [...,...3...,...] OPT OPT`

```
1 NAME
2 NAME
3 inherits: \setupenumeration
```

`\definujzakladnifont [...,...1...] [...,...2...] [...,...3...] [...,...4...,...] OPT OPT`

```
1 NAME implicitni
2 NAME DIMENSION
3 rm ss tt hw cg
4 tf  = FILE
  bf  = FILE
  it  = FILE
  sl  = FILE
  bi  = FILE
  bs  = FILE
  sc  = FILE
  mr  = FILE
  mrlr = FILE
  mrrl = FILE
  mb  = FILE
  mblr = FILE
  mbrl = FILE
```

`\definujzakladnifont [...,...1...] [...,...2...] [...,...3...] [...]4 OPT OPT`

```
1 NAME implicitni
2 NAME DIMENSION
3 rm ss tt hw cg
4 NAME
```

`\definujzasobnikpoli [...]1 [...,...2...] [...,...3...,...] OPT`

```
1 NAME
2 NAME
3 inherits: \setupfieldcategory
```

`\definujznaceni [...]1 [...]2 [...,...3...,...] OPT OPT`

```
1 NAME
2 BESCHRIFTUNG
3 inherits: \nastavznaceni
```

$\backslash\text{definujznak}$ ¹ ... ² ... 1 CHARACTER 2 NUMMER
$\backslash\text{delimited}$ [¹ ...] [² ...] { ³ ...} <small>OPT</small> 1 NAME 2 SPRACHE 3 CONTENT
$\backslash\text{delimitedtext}$ [¹ ...] [² ...] { ³ ...} <small>OPT</small> 1 NAME 2 SPRACHE 3 CONTENT
$\backslash\text{DELIMITEDTEXT}$ [¹ ...] { ² ...} <small>OPT</small> 1 SPRACHE 2 CONTENT instances: citace citovat blockquote speech aside
$\backslash\text{delkaseznamu}$
$\backslash\text{depthofstring}$ {...} * TEXT
$\backslash\text{depthonlybox}$ {...} * CONTENT
$\backslash\text{depthspanningtext}$ { ¹ ...} { ² ...} { ³ ...} 1 TEXT 2 DIMENSION 3 FONT
$\backslash\text{determinenoflines}$ {...} * CONTENT
$\backslash\text{devanagarinumeral}$ s {...} * NUMMER
$\backslash\text{dfrac}$ { ¹ ...} { ² ...} 1 CONTENT 2 CONTENT
$\backslash\text{digits}$ {...} * NUMMER
$\backslash\text{digits}$... * NUMMER

<code>\dimensiontocount {¹...} \²...</code> 1 DIMENSION 2 CSNAME
<code>\directcolor [...]</code> * COLOR
<code>\directcolored [...,[*]...,...]</code> * inherits: \definujbarvu
<code>\directcolored [...]</code> * COLOR
<code>\directconvertedcounter {¹...} {²...}</code> 1 NAME 2 prvni predchozi dalsi posledni cislo
<code>\directdummyparameter {...}</code> * KEY
<code>\directgetboxllx ...</code> * CSNAME NUMBER
<code>\directgetboxlly ...</code> * CSNAME NUMBER
<code>\directhighlight {¹...} {²...}</code> 1 NAME 2 TEXT
<code>\directlocalframed [...¹] {²...}</code> 1 NAME 2 CONTENT
<code>\directluacode {...}</code> * BEFEHL
<code>\directselect {¹...} {²..._{OPT}} {³..._{OPT}} {⁴..._{OPT}} {⁵..._{OPT}} {⁶..._{OPT}}</code> 1 NAME 2 CONTENT 3 CONTENT 4 CONTENT 5 CONTENT 6 CONTENT
<code>\directsetbar {...}</code> * NAME

$\backslash\text{directsetup}$ {...} * NAME
$\backslash\text{directsymbol}$ {... ¹ } {... ² } 1 NAME 2 NAME
$\backslash\text{directvspacing}$ {...,*...} * inherits: \vspacing
$\backslash\text{dis}$ {...} * CONTENT
$\backslash\text{disabledirectives}$ [...,*...]
* NAME
$\backslash\text{disableexperiments}$ [...,*...]
* NAME
$\backslash\text{disablemode}$ [...,*...]
* NAME
$\backslash\text{disableoutputstream}$
$\backslash\text{disableparpositions}$
$\backslash\text{disableregime}$
$\backslash\text{disabletrackers}$ [...,*...]
* NAME
$\backslash\text{displaymath}$ {...} * CONTENT
$\backslash\text{displaymathematics}$ {...} * CONTENT
$\backslash\text{displaymessage}$ {...} * TEXT
$\backslash\text{distributedhsize}$ {... ¹ } {... ² } {... ³ } 1 DIMENSION 2 DIMENSION 3 NUMMER

`\dividedsize {...} {...} {...}`

- 1 DIMENSION
- 2 DIMENSION
- 3 NUMMER

`\doadaptleftskip {...}`

- * ano ne standardni DIMENSION

`\doadaptrightskip {...}`

- * ano ne standardni DIMENSION

`\doaddfeature {...}`

- * NAME

`\doassign [...]1 [...]2...`

- 1 TEXT
- 2 KEY = VALUE

`\doassignempty [...]1 [...]2...`

- 1 TEXT
- 2 KEY = VALUE

`\doboundtext {...}1 {...}2 {...}3`

- 1 TEXT
- 2 DIMENSION
- 3 BEFEHL

`\documentvariable {...}`

- * KEY

`\dodoubleargument \... [...]1 [...]2 [...]3`

- 1 CSNAME
- 2 TEXT
- 3 TEXT

`\dodoubleargumentwithset \... [...]1, [...]2 [...]3`

- 1 CSNAME
- 2 TEXT
- 3 TEXT

`\dodoubleempty \... [...]1 [...]2 [...]3`
OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT

\dodoubleemptywithset \...¹ [...,²...] [...]³
OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT

\dodoublegroupempty \... {..²} {..³}
OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT

\doeassign [...]¹ [...]²

- 1 TEXT
- 2 KEY = VALUE

\doexpandedrecurse {..¹} {..²}

- 1 NUMMER
- 2 BEFEHL

\dogetattribute {...}

- * NAME

\dogetattributeid {...}

- * NAME

\dogetcommacommandelement ...¹ \from ...² \to ...³

- 1 NUMMER
- 2 TEXT
- 3 CSNAME

\dogobbledoubleempty [...]¹ [...]²
OPT OPT

- 1 TEXT
- 2 TEXT

\dogobblesingleempty [...]^{*}
OPT

- * TEXT

\docheckassignment {...}

- * TEXT

\docheckedpagestate {..¹} {..²} {..³} {..⁴} {..⁵} {..⁶} {..⁷}

- 1 REFERENCE
- 2 BEFEHL
- 3 BEFEHL
- 4 BEFEHL
- 5 BEFEHL
- 6 BEFEHL
- 7 BEFEHL

`\docheckedpair {...,*...}`

* TEXT

`\doif {...1} {...2} {...3}`

1 CONTENT

2 CONTENT

3 TRUE

`\doifallcommon {...,1...} {...,2...} {...3}`

2 CONTENT

3 CONTENT

5 TRUE

`\doifallcommonelse {...,1...} {...,2...} {...3} {...4}`

2 CONTENT

3 CONTENT

5 TRUE

6 FALSE

`\doifalldefinedelse {...,1...} {...2} {...3}`

1 NAME

2 TRUE

3 FALSE

`\doifallmodes {...,1...} {...2} {...3}`

1 NAME

2 TRUE

3 FALSE

`\doifallmodeselse {...,1...} {...2} {...3}`

1 NAME

2 TRUE

3 FALSE

`\doifassignmentelse {...1} {...2} {...3}`

1 TEXT

2 TRUE

3 FALSE

`\doifblackelse {...1} {...2} {...3}`

1 COLOR

2 TRUE

3 FALSE

`\doifbothsides {...} {...} {...}`

1 BEFEHL
2 BEFEHL
3 BEFEHL

`\doifbothsidesoverruled {...} {...} {...}`

1 BEFEHL
2 BEFEHL
3 BEFEHL

`\doifboxelse {...} {...} {...} {...}`

1 NAME
2 NAME
3 TRUE
4 FALSE

`\doifbufferelse {...} {...} {...}`

1 BUFFER
2 TRUE
3 FALSE

`\doifcolor {...} {...}`

1 COLOR
2 TRUE

`\doifcolorelse {...} {...} {...}`

1 COLOR
2 TRUE
3 FALSE

`\doifcommandhandler \... {...} {...}`

1 CSNAME
2 NAME
3 TRUE

`\doifcommandhandlerelse \... {...} {...} {...}`

1 CSNAME
2 NAME
3 TRUE
4 FALSE

`\doifcommon {...,1...} {...,2...} {...3}`

2 CONTENT
3 CONTENT
5 TRUE

```
\doifcommonelse {...,1...} {...,2...} {...3} {...4}
```

```
2 CONTENT
```

```
3 CONTENT
```

```
5 TRUE
```

```
6 FALSE
```

```
\doifcontent {...1} {...2} {...3} \...4 {...5}
```

```
1 BEFEHL
```

```
2 BEFEHL
```

```
3 BEFEHL
```

```
4 CSNAME
```

```
5 CONTENT
```

```
\doifconversiondefinedelse {...1} {...2} {...3}
```

```
1 NAME
```

```
2 TRUE
```

```
3 FALSE
```

```
\doifconversionnumberelse {...1} {...2} {...3} {...4}
```

```
1 NAME
```

```
2 NUMMER
```

```
3 TRUE
```

```
4 FALSE
```

```
\doifcounter {...1} {...2}
```

```
1 NAME
```

```
2 TRUE
```

```
\doifcounterelse {...1} {...2} {...3}
```

```
1 NAME
```

```
2 TRUE
```

```
3 FALSE
```

```
\doifcurrentfonthasfeatureelse {...1} {...2} {...3}
```

```
1 NAME
```

```
2 TRUE
```

```
3 FALSE
```

```
\doifdefined {...1} {...2}
```

```
1 NAME
```

```
2 TRUE
```

```
\doifdefinedcounter {...1} {...2}
```

```
1 NAME
```

```
2 TRUE
```

`\doifdefinedcounterelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifdefinedelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifdimensionelse {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifdimenstringelse {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifdocumentargument {...} {...}`

- 1 NAME
- 2 TRUE

`\doifdocumentargumentelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifdocumentfilename {...} {...}`

- 1 NUMMER
- 2 TRUE

`\doifdocumentfilenameelse {...} {...} {...}`

- 1 NUMMER
- 2 TRUE
- 3 FALSE

`\doifdrawingblackelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifelse {...} {...} {...} {...}`

- 1 CONTENT
- 2 CONTENT
- 3 TRUE
- 4 FALSE

`\doifelseallcommon {...,1...} {...,2...} {...} {...4}`

2 CONTENT

3 CONTENT

5 TRUE

6 FALSE

`\doifelsealldefined {...,1...} {...2} {...3}`

1 NAME

2 TRUE

3 FALSE

`\doifelseallmodes {...,1...} {...2} {...3}`

1 NAME

2 TRUE

3 FALSE

`\doifelseassignment {...1} {...2} {...3}`

1 TEXT

2 TRUE

3 FALSE

`\doifelseblack {...1} {...2} {...3}`

1 COLOR

2 TRUE

3 FALSE

`\doifelsebox {...1} {...2} {...3} {...4}`

1 NAME

2 NAME

3 TRUE

4 FALSE

`\doifelsebuffer {...1} {...2} {...3}`

1 BUFFER

2 TRUE

3 FALSE

`\doifelsecolor {...1} {...2} {...3}`

1 COLOR

2 TRUE

3 FALSE

\doifelsecommandhandler \...¹ {...}² {...}³ {...}⁴

- 1 CSNAME
- 2 NAME
- 3 TRUE
- 4 FALSE

\doifelsecommon {...,¹...} {...,²...} {...}³ {...}⁴

- 2 CONTENT
- 3 CONTENT
- 5 TRUE
- 6 FALSE

\doifelseconversiondefined {...}¹ {...}² {...}³

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelseconversionnumber {...}¹ {...}² {...}³ {...}⁴

- 1 NAME
- 2 NUMMER
- 3 TRUE
- 4 FALSE

\doifelsecounter {...}¹ {...}² {...}³

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsecurrentfonthasfeature {...}¹ {...}² {...}³

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsecurrentsortingtonused {...}¹ {...}²

- 1 TRUE
- 2 FALSE

\doifelsecurrentsynonymshown {...}¹ {...}²

- 1 TRUE
- 2 FALSE

\doifelsecurrentsynonymused {...}¹ {...}²

- 1 TRUE
- 2 FALSE

`\doifelsedefined {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsedefinedcounter {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsedimension {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifelsedimenstring {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifelsedocumentargument {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsedocumentfilename {...} {...} {...}`

- 1 NUMMER
- 2 TRUE
- 3 FALSE

`\doifelsedrawingblack {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifelseempty {...} {...} {...}`

- 1 CONTENT
- 2 TRUE
- 3 FALSE

`\doifelseemptyvalue {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelseemptyvariable {...} {...} {...} {...}`

1 NAME
2 KEY
3 TRUE
4 FALSE

`\doifelseenv {...} {...} {...}`

1 KEY
2 TRUE
3 FALSE

`\doifelsefastoptionalcheck {...} {...}`

1 TRUE
2 FALSE

`\doifelsefastoptionalcheckcs \^1 \^2`

1 CSNAME
2 CSNAME

`\doifelsefieldbody {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doifelsefieldcategory {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doifelsefigure {...} {...} {...}`

1 FILE
2 TRUE
3 FALSE

`\doifelsefile {...} {...} {...}`

1 FILE
2 TRUE
3 FALSE

`\doifelsefiledefined {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

\doifelsefileexists {...} {...} {...}

- 1 FILE
- 2 TRUE
- 3 FALSE

\doifelsefirstchar {...} {...} {...} {...}

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

\doifelseflagged {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsefontchar {...} {...} {...} {...}

- 1 FONT
- 2 NUMMER
- 3 TRUE
- 4 FALSE

\doifelsefontpresent {...} {...} {...}

- 1 FONT
- 2 TRUE
- 3 FALSE

\doifelsefontsynonym {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsehasspace {...} {...} {...}

- 1 TEXT
- 2 TRUE
- 3 FALSE

\doifelsehelp {...} {...}

- 1 TRUE
- 2 FALSE

\doifelseincsname {...} {...} {...} {...}

- 1 TEXT
- 2 CSNAME
- 3 TRUE
- 4 FALSE

\doifelseinelement {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelseinputfile {...} {...} {...}

- 1 FILE
- 2 TRUE
- 3 FALSE

\doifelseinsertion {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelseinset {...} {...,²...} {...} {...⁴}

- 1 CONTENT
- 2 CONTENT
- 4 TRUE
- 5 FALSE

\doifelseinstring {...} {...} {...} {...⁴}

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

\doifelseinsymbolset {...} {...} {...} {...}

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

\doifelseintoks {...} {...} {...} {...}

- 1 BEFEHL
- 2 BEFEHL
- 3 TRUE
- 4 FALSE

\doifelseintwopassdata {...} {...} {...} {...}

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

\doifelseitalic {...} {...}

- 1 TRUE
- 2 FALSE

\doifelselanguage {...} {...} {...}

- 1 SPRACHE
- 2 TRUE
- 3 FALSE

\doifelselayerdata {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelselayoutdefined {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelselayoutsomeline {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelselayouttextline {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelseleapyear {...} {...} {...}

- 1 NUMMER
- 2 TRUE
- 3 FALSE

\doifelselist {...} {...} {...}

- 1 LISTE
- 2 TRUE
- 3 FALSE

\doifelselocation {...} {...}

- 1 TRUE
- 2 FALSE

\doifelselocfile {...} {...} {...}

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifelseMPgraphic {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsemainfloatbody {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifelsemarking {...} {...} {...}`

- 1 BESCHRIFTUNG
- 2 TRUE
- 3 FALSE

`\doifelsemeaning \1... \2... {...} {...}`

- 1 CSNAME
- 2 CSNAME
- 3 TRUE
- 4 FALSE

`\doifelsemessage {...} {...} {...} {...}`

- 1 NAME
- 2 NAME NUMMER
- 3 TRUE
- 4 FALSE

`\doifelsemode {...,1...} {...2} {...3}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsenextbgroup {...1} {...2}`

- 1 TRUE
- 2 FALSE

`\doifelsenextbgroupcs \1... \2...`

- 1 CSNAME
- 2 CSNAME

`\doifelsenextchar {...1} {...2} {...3}`

- 1 CHARACTER
- 2 TRUE
- 3 FALSE

`\doifelsenextoptional {...1} {...2}`

- 1 TRUE
- 2 FALSE

`\doifelsenextoptionalcs \1... \2...`

1 CSNAME

2 CSNAME

`\doifelsenextparenthesis {\1...} {\2...}`

1 TRUE

2 FALSE

`\doifelsenonzeropositive {\1...} {\2...} {\3...}`

1 NUMMER

2 TRUE

3 FALSE

`\doifelsenoteonsamepage {\1...} {\2...} {\3...}`

1 NAME

2 TRUE

3 FALSE

`\doifelsenothing {\1...} {\2...} {\3...}`

1 TEXT

2 TRUE

3 FALSE

`\doifelsenumber {\1...} {\2...} {\3...}`

1 TEXT

2 TRUE

3 FALSE

`\doifelseobjectfound {\1...} {\2...} {\3...} {\4...}`

1 NAME

2 NAME

3 TRUE

4 FALSE

`\doifelseobjectreferencefound {\1...} {\2...} {\3...} {\4...}`

1 NAME

2 NAME

3 TRUE

4 FALSE

`\doifelseoddpage {\1...} {\2...}`

1 BEFEHL

2 BEFEHL

`\doifelseoddpagefloat {\1...} {\2...}`

1 TRUE

2 FALSE

\doifelseoldercontext {...} {...} {...}

- 1 NUMMER
- 2 TRUE
- 3 FALSE

\doifelseolderversion {...} {...} {...} {...}

- 1 NUMMER
- 2 NUMMER
- 3 TRUE
- 4 FALSE

\doifelseoverlapping {...} {...} {...} {...}

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

\doifelseoverlay {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelseparallel {...} {...,²...} {...} {...}

- 1 NAME
- 2 NAME vse
- 3 TRUE
- 4 FALSE

\doifelseparentfile {...} {...} {...}

- 1 FILE
- 2 TRUE
- 3 FALSE

\doifelsepath {...} {...} {...}

- 1 PATH
- 2 TRUE
- 3 FALSE

\doifelsepathexists {...} {...} {...}

- 1 PATH
- 2 TRUE
- 3 FALSE

\doifelsepatterns {...} {...} {...}

- 1 SPRACHE
- 2 TRUE
- 3 FALSE

`\doifelseposition {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsepositionaction {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsepositiononpage {...} {...} {...} {...}`

- 1 NAME
- 2 NUMMER
- 3 TRUE
- 4 FALSE

`\doifelsepositionsonsamepage {...,1...} {...2} {...3}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsepositionsonthispage {...,1...} {...2} {...3}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsepositionsused {...1} {...2}`

- 1 TRUE
- 2 FALSE

`\doifelserreferencefound {...} {...} {...}`

- 1 REFERENCE
- 2 TRUE
- 3 FALSE

`\doifelserightpagefloat {...1} {...2}`

- 1 TRUE
- 2 FALSE

`\doifelserighttoleftinbox ...1 {...2} {...3}`

- 1 CSNAME NUMMER
- 2 TRUE
- 3 FALSE

\doifelsesamelinreference {...} {...} {...}

- 1 REFERENCE
- 2 TRUE
- 3 FALSE

\doifelsesamestring {...} {...} {...} {...}

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

\doifelsesetups {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsesomebackground {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsesomespace {...} {...} {...}

- 1 TEXT
- 2 TRUE
- 3 FALSE

\doifelsesomething {...} {...} {...}

- 1 TEXT
- 2 TRUE
- 3 FALSE

\doifelsesometoks \.^{1..} {...} {...}

- 1 CSNAME
- 2 TRUE
- 3 FALSE

\doifelsestringinstring {...} {...} {...} {...}

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

\doifelsestructurelisthasnumber {...} {...}

- 1 TRUE
- 2 FALSE

`\doifelsestructurelisthaspage {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifelsesymboldefined {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsesymbolset {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsetext {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifelsetextflow {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsetextflowcollector {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsetypingfile {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifelseundefined {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelseurldefined {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsevalue {...} {...} {...} {...}`

- 1 NAME
- 2 TEXT
- 3 TRUE
- 4 FALSE

`\doifelsevaluenothing {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsevariable {...} {...} {...} {...}`

- 1 NAME
- 2 KEY
- 3 TRUE
- 4 FALSE

`\doifempty {...} {...}`

- 1 CONTENT
- 2 TRUE

`\doifemptyelse {...} {...} {...}`

- 1 CONTENT
- 2 TRUE
- 3 FALSE

`\doifemptytoks \^1... {...}`

- 1 CSNAME
- 2 TRUE

`\doifemptyvalue {...} {...}`

- 1 NAME
- 2 TRUE

`\doifemptyvalueelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifemptyvariable {...} {...} {...}`

- 1 NAME
- 2 KEY
- 3 TRUE

`\doifemptyvariableelse {...} {...} {...} {...}`

1 NAME
2 KEY
3 TRUE
4 FALSE

`\doifenv {...} {...}`

1 KEY
2 TRUE

`\doifenvelse {...} {...} {...}`

1 KEY
2 TRUE
3 FALSE

`\doiffastoptionalcheckcselect \1 \2`

1 CSNAME
2 CSNAME

`\doiffastoptionalcheckelse {...} {...}`

1 TRUE
2 FALSE

`\doiffieldbodyelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doiffieldcategoryelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doiffigureelse {...} {...} {...}`

1 FILE
2 TRUE
3 FALSE

`\doiffile {...} {...}`

1 FILE
2 TRUE

`\doiffiledefinedelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doiffileelse {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doiffileexistselse {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doiffirstcharelse {...} {...} {...} {...}`

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

`\doifflaggedelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doiffontcharelse {...} {...} {...} {...}`

- 1 FONT
- 2 NUMMER
- 3 TRUE
- 4 FALSE

`\doiffontpresentelse {...} {...} {...}`

- 1 FONT
- 2 TRUE
- 3 FALSE

`\doiffontsynonymelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifhasspaceelse {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifhelpelse {...} {...}`

- 1 TRUE
- 2 FALSE


```
\doifincsnameelse {...} {...} {...} {...}
```

- 1 TEXT
- 2 CSNAME
- 3 TRUE
- 4 FALSE

```
\doifinelementelse {...} {...} {...}
```

- 1 NAME
- 2 TRUE
- 3 FALSE

```
\doifinputfileelse {...} {...} {...}
```

- 1 FILE
- 2 TRUE
- 3 FALSE

```
\doifinsectionelse {...} {...} {...}
```

- 1 NAME
- 2 TRUE
- 3 FALSE

```
\doifinset {...} {...,2...} {...}
```

- 1 CONTENT
- 2 CONTENT
- 4 TRUE

```
\doifinsetelse {...} {...,2...} {...} {...4}
```

- 1 CONTENT
- 2 CONTENT
- 4 TRUE
- 5 FALSE

```
\doifinstring {...} {...2} {...3}
```

- 1 TEXT
- 2 TEXT
- 3 TRUE

```
\doifinstringelse {...} {...2} {...3} {...4}
```

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

\doifinsymbolset {...} {...} {...} {...}

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

\doifinsymbolsetelse {...} {...} {...} {...}

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

\doifintokselse {...} {...} {...} {...}

- 1 BEFEHL
- 2 BEFEHL
- 3 TRUE
- 4 FALSE

\doifintwopassdataelse {...} {...} {...} {...}

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

\doifitalicelse {...} {...}

- 1 TRUE
- 2 FALSE

\doiflanguageelse {...} {...} {...}

- 1 SPRACHE
- 2 TRUE
- 3 FALSE

\doiflayerdataelse {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doiflayoutdefinedelse {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doiflayoutsomelineelse {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doiflayouttextlineelse {.1.} {.2.} {.3.}`

1 NAME
2 TRUE
3 FALSE

`\doifleapyearelse {.1.} {.2.} {.3.}`

1 NUMMER
2 TRUE
3 FALSE

`\doiflistelse {.1.} {.2.} {.3.}`

1 LISTE
2 TRUE
3 FALSE

`\doiflocationelse {.1.} {.2.}`

1 TRUE
2 FALSE

`\doiflocfileelse {.1.} {.2.} {.3.}`

1 FILE
2 TRUE
3 FALSE

`\doifMPgraphicelse {.1.} {.2.} {.3.}`

1 NAME
2 TRUE
3 FALSE

`\doifmainfloatbodyelse {.1.} {.2.}`

1 TRUE
2 FALSE

`\doifmarkingelse {.1.} {.2.} {.3.}`

1 BESCHRIFTUNG
2 TRUE
3 FALSE

`\doifmeaningelse \.1. \.2. {.3.} {.4.}`

1 CSNAME
2 CSNAME
3 TRUE
4 FALSE

`\doifmessageelse {...} {...} {...} {...}`

- 1 NAME
- 2 NAME NUMBER
- 3 TRUE
- 4 FALSE

`\doifmode {...1,...} {...2}`

- 1 NAME
- 2 TRUE

`\doifmodeelse {...1,...} {...2} {...3}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifnextbgroupcselse \...1 \...2..`

- 1 CSNAME
- 2 CSNAME

`\doifnextbgroupelse {...1} {...2}`

- 1 TRUE
- 2 FALSE

`\doifnextcharelse {...1} {...2} {...3}`

- 1 CHARACTER
- 2 TRUE
- 3 FALSE

`\doifnextoptionalcselse \...1 \...2..`

- 1 CSNAME
- 2 CSNAME

`\doifnextoptionalelse {...1} {...2}`

- 1 TRUE
- 2 FALSE

`\doifnextparenthesiselse {...1} {...2}`

- 1 TRUE
- 2 FALSE

`\doifnonzeropositiveelse {...1} {...2} {...3}`

- 1 NUMBER
- 2 TRUE
- 3 FALSE

\doifnot {...} {...} {...}

- 1 CONTENT
- 2 CONTENT
- 3 TRUE

\doifnotallcommon {...,¹...} {...,²...} {...³}

- 2 CONTENT
- 3 CONTENT
- 5 TRUE

\doifnotallmodes {...,¹...} {...²} {...³}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifnotcommandhandler \... {...} {...}

- 1 CSNAME
- 2 NAME
- 3 TRUE

\doifnotcommon {...,¹...} {...,²...} {...³}

- 2 CONTENT
- 3 CONTENT
- 5 TRUE

\doifnotcounter {...} {...}

- 1 NAME
- 2 TRUE

\doifnotdocumentargument {...} {...}

- 1 NAME
- 2 TRUE

\doifnotdocumentfilename {...} {...}

- 1 NUMMER
- 2 TRUE

\doifnotempty {...} {...}

- 1 CONTENT
- 2 TRUE

\doifnotemptyvalue {...} {...}

- 1 NAME
- 2 TRUE

`\doifnotemptyvariable {...} {...} {...}`

1 NAME
2 KEY
3 TRUE

`\doifnotenv {...} {...}`

1 KEY
2 TRUE

`\doifnoteonsamepageelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doifnotescollected {...} {...}`

1 NAME
2 TRUE

`\doifnotfile {...} {...}`

1 FILE
2 TRUE

`\doifnotflagged {...} {...}`

1 NAME
2 TRUE

`\doifnothing {...} {...}`

1 TEXT
2 TRUE

`\doifnothingelse {...} {...} {...}`

1 TEXT
2 TRUE
3 FALSE

`\doifnotinset {...} {...,2...} {...3}`

1 CONTENT
2 CONTENT
3
4 TRUE

`\doifnotinsidesplitfloat {...}`

* TRUE

`\doifnotinstring {...} {...} {...}`

1 TEXT
2 TEXT
3 TRUE

`\doifnotmode {...1,...} {...2}`

1 NAME

2 TRUE

`\doifnotnumber {...1} {...2}`

1 TEXT

2 TRUE

`\doifnotsamestring {...1} {...2} {...3}`

1 TEXT

2 TEXT

3 TRUE

`\doifnotsetups {...1} {...2}`

1 NAME

2 TRUE

`\doifnotvalue {...1} {...2} {...3}`

1 NAME

2 TEXT

3 TRUE

`\doifnotvariable {...1} {...2} {...3}`

1 NAME

2 KEY

3 TRUE

`\doifnumber {...1} {...2}`

1 TEXT

2 TRUE

`\doifnumberelse {...1} {...2} {...3}`

1 TEXT

2 TRUE

3 FALSE

`\doifobjectfoundelse {...1} {...2} {...3} {...4}`

1 NAME

2 NAME

3 TRUE

4 FALSE

`\doifobjectreferencefoundelse {...1} {...2} {...3} {...4}`

1 NAME

2 NAME

3 TRUE

4 FALSE

\doifoddpagelse {¹.} {².}

1 BEFEHL

2 BEFEHL

\doifoddpagefloatelse {¹.} {².}

1 TRUE

2 FALSE

\doifoldercontextelse {¹.} {².} {³.}

1 NUMMER

2 TRUE

3 FALSE

\doifolderversionelse {¹.} {².} {³.} {⁴.}

1 NUMMER

2 NUMMER

3 TRUE

4 FALSE

\doifoverlappingelse {¹.} {².} {³.} {⁴.}

1 NAME

2 NAME

3 TRUE

4 FALSE

\doifoverlayelse {¹.} {².} {³.}

1 NAME

2 TRUE

3 FALSE

\doifparallelelse {¹.} {²...,...} {³.} {⁴.}

1 NAME

2 NAME vse

3 TRUE

4 FALSE

\doifparentfileelse {¹.} {².} {³.}

1 FILE

2 TRUE

3 FALSE

\doifpathelse {¹.} {².} {³.}

1 PATH

2 TRUE

3 FALSE

\doifpathexistselse {...} {...} {...}

- 1 PATH
- 2 TRUE
- 3 FALSE

\doifpatternselect {...} {...} {...}

- 1 SPRACHE
- 2 TRUE
- 3 FALSE

\doifposition {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifpositionaction {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifpositionactionelse {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifpositionelse {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifpositiononpageelse {...} {...} {...} {...}

- 1 NAME
- 2 NUMMER
- 3 TRUE
- 4 FALSE

\doifpositionsonsamepageelse {...,¹...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifpositionsonthispageelse {...,¹...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifpositionsusedelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifreferencefoundelse {...} {...} {...}`

- 1 REFERENCE
- 2 TRUE
- 3 FALSE

`\doifrightpagefloatelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifrighttoleftinboxedelse ... {...} {...}`

- 1 CSNAME NUMMER
- 2 TRUE
- 3 FALSE

`\doifsamelinereferenceelse {...} {...} {...}`

- 1 REFERENCE
- 2 TRUE
- 3 FALSE

`\doifsamestring {...} {...} {...}`

- 1 TEXT
- 2 TEXT
- 3 TRUE

`\doifsamestringelse {...} {...} {...} {...}`

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

`\doifsetups {...} {...}`

- 1 NAME
- 2 TRUE

`\doifsetupself {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifsomebackground {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifsomebackgroundelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifsomespaceelse {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifsomething {...} {...}`

- 1 TEXT
- 2 TRUE

`\doifsomethingelse {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifsometoks \... {...}`

- 1 CSNAME
- 2 TRUE

`\doifsometokselse \... {...} {...}`

- 1 CSNAME
- 2 TRUE
- 3 FALSE

`\doifstringinstringelse {...} {...} {...} {...}`

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

`\doifstructurelisthasnumberelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifstructurelisthaspageelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifsymboldefinedelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

```
\doifsymbolsetelse {...} {...} {...}
```

```
1 NAME  
2 TRUE  
3 FALSE
```

```
\doiftext {...} {...} {...}
```

```
1 TEXT  
2 TRUE  
3 FALSE
```

```
\doiftextelse {...} {...} {...}
```

```
1 TEXT  
2 TRUE  
3 FALSE
```

```
\doiftextflowcollectorelse {...} {...} {...}
```

```
1 NAME  
2 TRUE  
3 FALSE
```

```
\doiftextflowelse {...} {...} {...}
```

```
1 NAME  
2 TRUE  
3 FALSE
```

```
\doiftypingfileelse {...} {...} {...}
```

```
1 FILE  
2 TRUE  
3 FALSE
```

```
\doifundefined {...} {...}
```

```
1 NAME  
2 TRUE
```

```
\doifundefinedcounter {...} {...}
```

```
1 NAME  
2 TRUE
```

```
\doifundefinedelse {...} {...} {...}
```

```
1 NAME  
2 TRUE  
3 FALSE
```

```
\doifurldefinedelse {...} {...} {...}
```

```
1 NAME  
2 TRUE  
3 FALSE
```

`\doifvalue {...} {...} {...}`

- 1 NAME
- 2 TEXT
- 3 TRUE

`\doifvalueelse {...} {...} {...} {...}`

- 1 NAME
- 2 TEXT
- 3 TRUE
- 4 FALSE

`\doifvaluenothing {...} {...}`

- 1 NAME
- 2 TRUE

`\doifvaluenothingelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifvaluesomething {...} {...}`

- 1 NAME
- 2 TRUE

`\doifvariable {...} {...} {...}`

- 1 NAME
- 2 KEY
- 3 TRUE

`\doifvariableelse {...} {...} {...} {...}`

- 1 NAME
- 2 KEY
- 3 TRUE
- 4 FALSE

`\doindentation`

`\dollar`

`\doloop {...}`

- * BEFEHL

`\doloopoverlist {...,1...} {...2}`

- 1 TEXT
- 2 BEFEHL

`\donothing`

<code>\dontconvertfont</code>
<code>\dontleavehmode</code>
<code>\dontpermitspacesbetweengroups</code>
<code>\dopositionaction {.*}</code> * NAME
<code>\doprocesslocalsetups {...,*,...}</code> * NAME
<code>\doquadrupleargument \...¹ [²...] [³...] [⁴...] [⁵...]</code> 1 CSNAME 2 TEXT 3 TEXT 4 TEXT 5 TEXT
<code>\doquadrupleempty \...¹ [²...]_{OPT} [³...]_{OPT} [⁴...]_{OPT} [⁵...]_{OPT}</code> 1 CSNAME 2 TEXT 3 TEXT 4 TEXT 5 TEXT
<code>\doquadruplegroupempty \...¹ {²...}_{OPT} {³...}_{OPT} {⁴...}_{OPT} {⁵...}_{OPT}</code> 1 CSNAME 2 TEXT 3 TEXT 4 TEXT 5 TEXT
<code>\doquintupleargument \...¹ [²...] [³...] [⁴...] [⁵...] [⁶...]</code> 1 CSNAME 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT

`\doquintupleempty \1... [2...] [3...] [4...] [5...] [6...]`
OPT OPT OPT OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT
- 6 TEXT

`\doquintuplegroupempty \1... {2...} {3...} {4...} {5...} {6...}`
OPT OPT OPT OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT
- 6 TEXT

`\dorecurse {1...} {2...}`

- 1 NUMMER
- 2 BEFEHL

`\dorechecknextindentation`

`\dorepeatwithcommand [1...] \2...`

- 1 TEXT NUMMER*TEXT
- 2 CSNAME

`\doreplacefeature {.*...}`

* NAME

`\doresetandafffeature {.*...}`

* NAME

`\doresetattribute {.*...}`

* NAME

`\dorotatebox {1...} \2... {3...}`

- 1 NUMMER
- 2 CSNAME
- 3 CONTENT

`\dosetattribute {1...} {2...}`

- 1 NAME
- 2 NUMMER

`\dosetleftskipadaption {.*...}`

* ano ne standardni DIMENSION

<p><code>\dosetrightrightskipadaption {...}</code></p> <p>* ano ne standardni DIMENSION</p>
<p><code>\dosetupcheckedinterlinespace {...,*=...,...}</code></p> <p>* inherits: \nastavmeziradkovoumezeru</p>
<p><code>\dosetupcheckedinterlinespace {...,*...}</code></p> <p>* zap vyp reset auto male stredni velke NUMMER DIMENSION</p>
<p><code>\dosetupcheckedinterlinespace {...}</code></p> <p>* NAME</p>
<p><code>\doseventupleargument \... [¹... [²... [³... [⁴... [⁵... [⁶... [⁷... [⁸...]]]]]]</code></p> <p>1 CSNAME</p> <p>2 TEXT</p> <p>3 TEXT</p> <p>4 TEXT</p> <p>5 TEXT</p> <p>6 TEXT</p> <p>7 TEXT</p> <p>8 TEXT</p>
<p><code>\doseventupleempty \... [¹... [²... [³... [⁴... [⁵... [⁶... [⁷... [⁸...]]]]]</code> <div> <div>OPT</div> <div>OPT</div> <div>OPT</div> <div>OPT</div> <div>OPT</div> <div>OPT</div> <div>OPT</div> <div>OPT</div> </div> </p> <p>1 CSNAME</p> <p>2 TEXT</p> <p>3 TEXT</p> <p>4 TEXT</p> <p>5 TEXT</p> <p>6 TEXT</p> <p>7 TEXT</p> <p>8 TEXT</p>
<p><code>\dosingleargument \... [¹... [²...]</code></p> <p>1 CSNAME</p> <p>2 TEXT</p>
<p><code>\dosingleempty \... [¹... [²...]</code> <div> <div>OPT</div> </div> </p> <p>1 CSNAME</p> <p>2 TEXT</p>
<p><code>\dosinglegroupempty \... [¹... {²...}</code> <div> <div>OPT</div> </div> </p> <p>1 CSNAME</p> <p>2 TEXT</p>

`\dosixtupleargument \1... [2...] [3...] [4...] [5...] [6...] [7...]`

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT
- 6 TEXT
- 7 TEXT

`\dosixtupleempty \1... [2...] [3...] [4...] [5...] [6...] [7...]`
OPT OPT OPT OPT OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT
- 6 TEXT
- 7 TEXT

`\dostarttagged {1...} {2...} ... \dostoptagged`

- 1 NAME
- 2 NAME

`\dostepwiserecurse {1...} {2...} {3...} {4...}`

- 1 NUMMER
- 2 NUMMER
- 3 [-+]NUMMER
- 4 BEFEHL

`\dosubtractfeature {*...}`

- * NAME

`\dotfskip {*...}`

- * DIMENSION

`\dotoks *...`

- * CSNAME

`\dotripleargument \1... [2...] [3...] [4...]`

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT

`\dotripleargumentwithset \1... [2...2,...] [3...] [4...]`

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT

`\dotripleempty \1... [2...] [3...] [4...]`
OPT OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT

`\dotripleemptywithset \1... [2...2,...] [3...] [4...]`
OPT OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT

`\dotriplegroupempty \1... {2...} {3...} {4...}`
OPT OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT

`\doublebar {...}`

- * TEXT

`\doublebond`

`\doublebrace {...}`

- * TEXT

`\doublebracket {...}`

- * TEXT

`\doubleparent {...}`

- * TEXT

`\dowith {...1,...} {...2}`

- 1 BEFEHL
- 2 BEFEHL

`\dowithnextbox {...1} \2... {...3}`

- 1 BEFEHL
- 2 CSNAME
- 3 CONTENT

`\dowithnextboxcontent {...} {...} \dots {...}`

- 1 BEFEHL
- 2 BEFEHL
- 3 CSNAME
- 4 CONTENT

`\dowithnextboxcontentcs \dots \dots \dots {...}`

- 1 CSNAME
- 2 CSNAME
- 3 CSNAME
- 4 CONTENT

`\dowithnextboxcs \dots \dots {...}`

- 1 CSNAME
- 2 CSNAME
- 3 CONTENT

`\dowithpargument \dots`

- * CSNAME

`\dowithrange {...,1...} \dots`

- 1 NUMMER NUMMER:NUMMER
- 2 CSNAME

`\dowithwargument \dots`

- * CSNAME

`\dpofstring {...}`

- * TEXT

`\dummydigit`

`\dummyparameter {...}`

- * KEY

`\ETEX`

`\EveryLine {...}`

- * BEFEHL

`\EveryPar {...}`

- * BEFEHL

`\edefconvertedargument \dots {...}`

- 1 CSNAME
- 2 TEXT

$\backslash\mathrm{efcmaxheight}$ {...} * NAME
$\backslash\mathrm{efcmaxwidth}$ {...} * NAME
$\backslash\mathrm{efcminheight}$ {...} * NAME
$\backslash\mathrm{efcminwidth}$ {...} * NAME
$\backslash\mathrm{efcparameter}$ {...} {...} 1 NAME 2 KEY
$\backslash\mathrm{effect}$ [...] {...} 1 NAME 2 CONTENT
$\backslash\mathrm{elapsedseconds}$
$\backslash\mathrm{elapsedtime}$
$\backslash\mathrm{eleftrightarrowfill}$ {...} {...} <small>OPT</small> <small>OPT</small> 1 TEXT 2 TEXT
$\backslash\mathrm{eleftharpoonupdownfill}$ {...} {...} <small>OPT</small> <small>OPT</small> 1 TEXT 2 TEXT
$\backslash\mathrm{eleftharpoonupfill}$ {...} {...} <small>OPT</small> <small>OPT</small> 1 TEXT 2 TEXT
$\backslash\mathrm{eleftrightarrowfill}$ {...} {...} <small>OPT</small> <small>OPT</small> 1 TEXT 2 TEXT
$\backslash\mathrm{emphasisboldface}$
$\backslash\mathrm{emphasistypeface}$
$\backslash\mathrm{emptylines}$ [...] <small>OPT</small> * NUMMER
$\backslash\mathrm{emspace}$

<code>\enabledirectives [...,*,...]</code> * NAME
<code>\enableexperiments [...,*,...]</code> * NAME
<code>\enablemode [...,*,...]</code> * NAME
<code>\enableoutputstream [...]</code> * NAME
<code>\enableparpositions</code>
<code>\enableregime [...]</code> * cp1250 cp1251 cp1252 cp1253 cp1254 cp1255 cp1256 cp1257 cp1258 8859-1 8859-2 8859-3 8859-4 8859-9 8859-10 8859-13 8859-14 8859-15 8859-16 utf windows-1250 windows-1251 windows-1252 windows-1253 windows-1254 windows-1255 windows-1256 windows-1257 windows-1258 il1 il2 il3 il4 il5 il6 il7 il8 il9 il10 iso-8859-1 iso-8859-2 iso-8859-3 iso-8859-4 iso-8859-9 iso-8859-10 iso-8859-13 iso-8859-14 iso-8859-15 iso-8859-16 latin1 latin2 latin3 latin4 latin5 latin6 latin7 latin8 latin9 latin10 utf-8 utf8 windows
<code>\enabletrackers [...,*,...]</code> * NAME
<code>\enskip</code>
<code>\enspace</code>
<code>\env {...}</code> * KEY
<code>\envvar {...} {...}</code> 1 KEY 2 BEFEHL
<code>\eoverbarfill {...} {...}</code> <div style="display: flex; justify-content: space-around; width: 100%;"> OPT OPT </div> 1 TEXT 2 TEXT
<code>\eoverbracefill {...} {...}</code> <div style="display: flex; justify-content: space-around; width: 100%;"> OPT OPT </div> 1 TEXT 2 TEXT
<code>\eoverbracketfill {...} {...}</code> <div style="display: flex; justify-content: space-around; width: 100%;"> OPT OPT </div> 1 TEXT 2 TEXT
<code>\eoverparentfill {...} {...}</code> <div style="display: flex; justify-content: space-around; width: 100%;"> OPT OPT </div> 1 TEXT 2 TEXT

$\backslash\text{epos} \{...\}$ * NAME
$\backslash\text{equaldigits} \{...\}$ * TEXT
$\backslash\text{erightarrowfill} \{...\} \{...\}$ <div style="display: flex; justify-content: space-around; width: 100%;"> OPT OPT </div> 1 TEXT 2 TEXT
$\backslash\text{erightharpoondownfill} \{...\} \{...\}$ <div style="display: flex; justify-content: space-around; width: 100%;"> OPT OPT </div> 1 TEXT 2 TEXT
$\backslash\text{erightharpoonupfill} \{...\} \{...\}$ <div style="display: flex; justify-content: space-around; width: 100%;"> OPT OPT </div> 1 TEXT 2 TEXT
$\backslash\text{eTeX}$
$\backslash\text{etwoheadrightarrowfill} \{...\} \{...\}$ <div style="display: flex; justify-content: space-around; width: 100%;"> OPT OPT </div> 1 TEXT 2 TEXT
$\backslash\text{eunderbarfill} \{...\} \{...\}$ <div style="display: flex; justify-content: space-around; width: 100%;"> OPT OPT </div> 1 TEXT 2 TEXT
$\backslash\text{eunderbracefill} \{...\} \{...\}$ <div style="display: flex; justify-content: space-around; width: 100%;"> OPT OPT </div> 1 TEXT 2 TEXT
$\backslash\text{eunderbracketfill} \{...\} \{...\}$ <div style="display: flex; justify-content: space-around; width: 100%;"> OPT OPT </div> 1 TEXT 2 TEXT
$\backslash\text{eunderparentfill} \{...\} \{...\}$ <div style="display: flex; justify-content: space-around; width: 100%;"> OPT OPT </div> 1 TEXT 2 TEXT
$\backslash\text{executeifdefined} \{...\} \{...\}$ 1 NAME 2 BEFEHL
$\backslash\text{exitloop}$
$\backslash\text{exitloopnow}$

<code>\expanded {...}</code> * CONTENT
<code>\expandfontsynonym \¹... {²...}</code> 1 CSNAME 2 NAME
<code>\expandcheckedcsname \¹... {²...} {³...}</code> 1 CSNAME 2 KEY 3 TEXT
<code>\externalfigurecollectionmaxheight {...}</code> * NAME
<code>\externalfigurecollectionmaxwidth {...}</code> * NAME
<code>\externalfigurecollectionminheight {...}</code> * NAME
<code>\externalfigurecollectionminwidth {...}</code> * NAME
<code>\externalfigurecollectionparameter {¹...} {²...}</code> 1 NAME 2 KEY
<code>\externiobraz [¹...] [²...] [³...,..._{OPT}...,..._{OPT}]</code> 1 FILE 2 NAME 3 inherits: \setupeexternalfigure
<code>\fakebox ...</code> * CSNAME NUMBER
<code>\fastdecrement \...</code> * CSNAME
<code>\fastincrement \...</code> * CSNAME
<code>\fastlocalframed [¹...] [²...,...₂...,...₂] {³...}</code> 1 NAME 2 inherits: \nastavoramovani 3 CONTENT

<p><code>\fastscale {...} {...}</code></p> <p>1 NUMMER</p> <p>2 CONTENT</p>
<p><code>\fastsetup {...}</code></p> <p>* NAME</p>
<p><code>\fastsetupwithargument {...} {...}</code></p> <p>1 NAME</p> <p>2 CONTENT</p>
<p><code>\fastsetupwithargumentswapped {...} {...}</code></p> <p>1 CONTENT</p> <p>2 NAME</p>
<p><code>\fastswitchtobodyfont {...}</code></p> <p>* x xx male velke script scriptscript</p>
<p><code>\fastxsxy {...} {...} {...}</code></p> <p>1 NUMMER</p> <p>2 NUMMER</p> <p>3 CONTENT</p>
<p><code>\feature [...] [...]</code></p> <p>1 + - = ! > < more less novy reset implicitni old lokalne</p> <p>2 NAME</p>
<p><code>\feature {...} {...}</code></p> <p>1 + - = ! > < more less novy reset implicitni old lokalne</p> <p>2 NAME</p>
<p><code>\fence</code></p>
<p><code>\fenced [...] {...}</code></p> <p>1 NAME</p> <p>2 CONTENT</p>
<p><code>\FENCE {...}</code></p> <p>* CONTENT</p>
<p><code>\fetchallmarkings [...] [...]</code></p> <p>1 BESCHRIFTUNG</p> <p>2 stranka NAME</p>
<p><code>\fetchallmarks [...]</code></p> <p>* BESCHRIFTUNG</p>

<pre> \fetchmark [...] [²...] OPT 1 BESCHRIFTUNG 2 prvni posledni aktualni predchozi dalsi vrsek spodek implicitni obe vse first:nochek last:nochek previous:nochek next:nochek top:nochek bottom:nochek </pre>
<pre> \fetchmarking [...] [²] [³] 1 BESCHRIFTUNG 2 stranka NAME 3 prvni posledni aktualni predchozi dalsi vrsek spodek implicitni obe vse first:nochek last:nochek previous:nochek next:nochek top:nochek bottom:nochek </pre>
<pre> \fetchonemark [...] [²...] OPT 1 BESCHRIFTUNG 2 prvni posledni aktualni predchozi dalsi vrsek spodek implicitni obe vse first:nochek last:nochek previous:nochek next:nochek top:nochek bottom:nochek </pre>
<pre> \fetchonemarking [...] [²] [³] 1 BESCHRIFTUNG 2 stranka NAME 3 prvni posledni aktualni predchozi dalsi vrsek spodek implicitni obe vse first:nochek last:nochek previous:nochek next:nochek top:nochek bottom:nochek </pre>
<pre> \fetchruntimecommand \¹... {²...} 1 CSNAME 2 FILE </pre>
<pre> \fetchtwomarkings [...] [²] 1 BESCHRIFTUNG 2 stranka NAME </pre>
<pre> \fetchtwomarks [...] * BESCHRIFTUNG </pre>
<pre> \fieldbody [...] [²..._{OPT}...] 1 NAME 2 inherits: \setupfieldbody </pre>
<pre> \fifthoffivearguments {¹...} {²...} {³...} {⁴...} {⁵...} 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT </pre>

<p><code>\fifthofsixarguments {...} {...} {...} {...} {...} {...}</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 TEXT</p> <p>4 TEXT</p> <p>5 TEXT</p> <p>6 TEXT</p>
<code>\figurefilename</code>
<code>\figurefilepath</code>
<code>\figurefiletype</code>
<code>\figurefullname</code>
<code>\figureheight</code>
<code>\figurenaturalheight</code>
<code>\figurenaturalwidth</code>
<p><code>\figuresymbol [...]¹ [...,...²...,...]_{OPT}</code></p> <p>1 FILE NAME</p> <p>2 inherits: \externiobraz</p>
<code>\figurewidth</code>
<p><code>\filename {...}</code></p> <p>* FILE</p>
<p><code>\filledhboxb ...¹ {...}_{OPT}</code></p> <p>1 TEXT</p> <p>2 CONTENT</p>
<p><code>\filledhboxc ...¹ {...}_{OPT}</code></p> <p>1 TEXT</p> <p>2 CONTENT</p>
<p><code>\filledhboxg ...¹ {...}_{OPT}</code></p> <p>1 TEXT</p> <p>2 CONTENT</p>
<p><code>\filledhboxk ...¹ {...}_{OPT}</code></p> <p>1 TEXT</p> <p>2 CONTENT</p>

<pre> \filledhboxm ¹... {²...} OPT 1 TEXT 2 CONTENT </pre>
<pre> \filledhboxr ¹... {²...} OPT 1 TEXT 2 CONTENT </pre>
<pre> \filledhboxy ¹... {²...} OPT 1 TEXT 2 CONTENT </pre>
<pre> \filler [...]</pre> <p>* sym symbol linka sirka mezera NAME</p>
<pre> \filterfromnext {¹...} {²...} {³...} {⁴...} {⁵...} {⁶...} {⁷...} OPT OPT OPT OPT OPT 1 NUMMER 2 NUMMER 3 CONTENT 4 CONTENT 5 CONTENT 6 CONTENT 7 CONTENT 8 CONTENT 9 CONTENT 10 CONTENT 11 CONTENT 12 CONTENT </pre>
<pre> \filterfromvalue {¹...} {²...} {³...} 1 NAME 2 NUMMER 3 NUMMER </pre>
<pre> \filterpages [...¹] [...²,...] [...³,...³,...] OPT 1 FILE 2 sude liche NUMMER NUMMER:NUMMER 3 sirka = DIMENSION n = NUMMER category = NAME </pre>
<pre> \filterreference {[*]...} * implicitni text titul cislo stranka realpage </pre>
<pre> \findtwopassdata {¹...} {²...} 1 NAME 2 NAME </pre>

\finishregisterentry [...]¹ [...,...²...,...]³ [...,...³...,...]
OPT

1 NAME
2 popisek = NAME
keys = TEXT PROCESSOR->TEXT
entries = TEXT PROCESSOR->TEXT
alternativa = TEXT
3 KEY = VALUE

\firstcounter [...]¹ [...]²
OPT

1 NAME
2 NUMMER

\firstcountervalue [...]^{*}

* NAME

\firstcharacter

\firstoffivearguments {...}¹ {...}² {...}³ {...}⁴ {...}⁵

1 TEXT
2 TEXT
3 TEXT
4 TEXT
5 TEXT

\firstoffourarguments {...}¹ {...}² {...}³ {...}⁴

1 TEXT
2 TEXT
3 TEXT
4 TEXT

\firstofoneargument {...}^{*}

* TEXT

\firstofoneunexpanded {...}^{*}

* TEXT

\firstofsixarguments {...}¹ {...}² {...}³ {...}⁴ {...}⁵ {...}⁶

1 TEXT
2 TEXT
3 TEXT
4 TEXT
5 TEXT
6 TEXT

\firstofthreearguments {...}¹ {...}² {...}³

1 TEXT
2 TEXT
3 TEXT

<code>\firstofthreeunexpanded {...} {...} {...}</code> 1 TEXT 2 TEXT 3 TEXT
<code>\firstoftwoarguments {...} {...}</code> 1 TEXT 2 TEXT
<code>\firstoftwounexpanded {...} {...}</code> 1 TEXT 2 TEXT
<code>\firstrealpage</code>
<code>\firstrealpagenumber</code>
<code>\firstsubcountervalue [...] [...]</code> 1 NAME 2 NUMMER
<code>\firstsubpagenumber</code>
<code>\firstuserpage</code>
<code>\firstuserpagenumber</code>
<code>\fitfieldframed [...,\overset{.1}{=},...] {...}</code> <div style="text-align: center; margin-left: 100px;"><small>OPT</small></div> 1 inherits: \nastavoramovani 2 CONTENT
<code>\fittopbaselinegrid {...}</code> * CONTENT
<code>\flag {...}</code> * NAME
<code>\floatuserdataparameter {...}</code> * KEY
<code>\flushboxregister ...</code> * CSNAME NUMBER
<code>\flushcollector [...]</code> * NAME
<code>\flushedrightlastline</code>

\flushlayer [...] * NAME
\flushlocalfloats
\flushnextbox
\flushnotes
\flushoutputstream [...] * NAME
\flushshapebox
\flushtextflow {...} * NAME
\flushtokens [...] * NAME
\flushtoks *... * CSNAME
\fontalternative
\fontbody
\fontclass
\fontclassname {...} {...} 1 NAME 2 FONT
\fontface
\fontfeaturelist [...] [...] 1 NAME 2 TEXT
\fontchar {...} * NAME
\fontcharbyindex {...} * NUMMER
\fontsize
\fontstyle

<p><code>\footnotetext [...¹,...] {²...}</code></p> <p style="text-align: center;">OPT</p> <p>1 REFERENCE</p> <p>2 TEXT</p>
<p><code>\footnotetext [...[*],...] {[*]...}</code></p> <p>* titul = TEXT</p> <p> zalozka = TEXT</p> <p> seznam = TEXT</p> <p> odkaz = REFERENCE</p>
<p><code>\forcecharacterstripping</code></p>
<p><code>\forcelocalfloats</code></p>
<p><code>\forgeteverypar</code></p>
<p><code>\forgetparameters [...¹] [...²...,...]</code></p> <p>1 TEXT</p> <p>2 KEY = VALUE</p>
<p><code>\forgetragged</code></p>
<p><code>\foundbox {¹...} {²...}</code></p> <p>1 NAME</p> <p>2 NAME</p>
<p><code>\fourthoffivearguments {¹...} {²...} {³...} {⁴...} {⁵...}</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 TEXT</p> <p>4 TEXT</p> <p>5 TEXT</p>
<p><code>\fourthoffourarguments {¹...} {²...} {³...} {⁴...}</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 TEXT</p> <p>4 TEXT</p>
<p><code>\fourthofsixarguments {¹...} {²...} {³...} {⁴...} {⁵...} {⁶...}</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 TEXT</p> <p>4 TEXT</p> <p>5 TEXT</p> <p>6 TEXT</p>

$\frac{\dots}{\dots}$ 1 CONTENT 2 CONTENT
$\boxed{\dots}$ * KEY
$\boxed{\dots}$ * KEY
$\dots^1 \dots^2$ 1 CSNAME 2 CSNAME
$\dots^1 \dots^2$ 1 NAME 2 DIMENSION
\dots
$\dots^1 \dots^2$ 1 REFERENCE 2 TEXT
\dots^* * CONTENT
\dots
\dots
\dots^* * NUMBER
$\dots^1 \dots^2$ 1 CSNAME 2 TEXT
$\dots^1 \dots^2$ 1 CSNAME 2 CSNAME
\dots * CSNAME NUMBER
\dots * CSNAME NUMBER

<code>\getbufferdata [...]</code> <div> <div>OPT</div> <div></div> </div>
* BUFFER
<code>\getcommacommandsize [...,*...]</code>
* BEFEHL
<code>\getcommalistsize [...,*...]</code>
* BEFEHL
<code>\getdayoftheweek {...} {...} {...}</code> 1 NUMMER 2 NUMMER 3 NUMMER
<code>\getdayspermonth {...} {...}</code> 1 NUMMER 2 NUMMER
<code>\getdefinedbuffer [...]</code>
* BUFFER
<code>\getdocumentargument {...}</code>
* NAME
<code>\getdocumentargumentdefault {...} {...}</code> 1 NAME 2 TEXT
<code>\getdocumentfilename {...}</code>
* NUMMER
<code>\getdummyparameters [...,*...]</code>
* KEY = VALUE
<code>\getemptyparameters [...¹] [...,*²...]</code> 1 TEXT 2 KEY = VALUE
<code>\getparameters [...¹] [...,*²...]</code> 1 TEXT 2 KEY = VALUE
<code>\getexpandedparameters [...¹] [...,*²...]</code> 1 TEXT 2 KEY = VALUE

<pre> \getfiguredimensions [...] [...²..._{OPT}...] 1 FILE 2 inherits: \setuexternalfigure </pre>
<pre> \getfirstcharacter {...} * TEXT </pre>
<pre> \getfirsttwopassdata {...} * NAME </pre>
<pre> \getfromcommacommand [...¹...] [...²...] 1 BEFEHL 2 NUMMER </pre>
<pre> \getfromcommalist [...¹...] [...²...] 1 BEFEHL 2 NUMMER </pre>
<pre> \getfromtwopassdata {...¹} {...²} 1 NAME 2 NAME </pre>
<pre> \getglyphdirect {...¹} {...²} 1 FONT 2 NUMMER CHARACTER </pre>
<pre> \getglyphstyled {...¹} {...²} 1 FONT 2 NUMMER CHARACTER </pre>
<pre> \getgparameters [...¹] [...²..._{OPT}...] 1 TEXT 2 KEY = VALUE </pre>
<pre> \getlasttwopassdata {...} * NAME </pre>
<pre> \getlocalfloat {...} * NUMMER </pre>
<pre> \getlocalfloats </pre>
<pre> \getMPdrawing </pre>
<pre> \getMPlayer [...¹] [...²..._{OPT}...] {...³} 1 NAME 2 inherits: \nastavoramovani 3 CONTENT </pre>

<pre>\getmessage {...} {...}</pre> <pre>1 NAME</pre> <pre>2 NAME NUMMER</pre>
<pre>\getnamedglyphdirect {...} {...}</pre> <pre>1 FONT</pre> <pre>2 NAME</pre>
<pre>\getnamedglyphstyled {...} {...}</pre> <pre>1 FONT</pre> <pre>2 NAME</pre>
<pre>\getnamedtwopassdatalist \... {...}</pre> <pre>1 CSNAME</pre> <pre>2 NAME</pre>
<pre>\getnaturaldimensions ...</pre> <pre>* CSNAME NUMMER</pre>
<pre>\getnoflines {...}</pre> <pre>* DIMENSION</pre>
<pre>\getobject {...} {...}</pre> <pre>1 NAME</pre> <pre>2 NAME</pre>
<pre>\getobjectdimensions {...} {...}</pre> <pre>1 NAME</pre> <pre>2 NAME</pre>
<pre>\getpaletsize [...]</pre> <pre>* NAME</pre>
<pre>\getparameters [...] [...,...²...,...]</pre> <pre>1 TEXT</pre> <pre>2 KEY = VALUE</pre>
<pre>\getprivatechar {...}</pre> <pre>* NAME</pre>
<pre>\getprivateslot {...}</pre> <pre>* NAME</pre>
<pre>\getrandomcount \... {...} {...}</pre> <pre>1 CSNAME</pre> <pre>2 NUMMER</pre> <pre>3 NUMMER</pre>

`\getrandomdimen \1... {2...} {3...}`

- 1 CSNAME
- 2 DIMENSION
- 3 DIMENSION

`\getrandomfloat \1... {2...} {3...}`

- 1 CSNAME
- 2 NUMMER
- 3 NUMMER

`\getrandomnumber \1... {2...} {3...}`

- 1 CSNAME
- 2 NUMMER
- 3 NUMMER

`\getrandomseed *...`

- * CSNAME

`\getraweparameters [1...] [...,2...,...]`

- 1 TEXT
- 2 KEY = VALUE

`\getrawgparameters [1...] [...,2...,...]`

- 1 TEXT
- 2 KEY = VALUE

`\getrawnoflines {*...}`

- * DIMENSION

`\getrawparameters [1...] [...,2...,...]`

- 1 TEXT
- 2 KEY = VALUE

`\getrawxparameters [1...] [...,2...,...]`

- 1 TEXT
- 2 KEY = VALUE

`\getreference [1...] [2...]`

- 1 implicitni text titul cislo stranka realpage
- 2 REFERENCE

`\getreferenceentry {*...}`

- * implicitni text titul cislo stranka realpage

`\getroundednoflines {*...}`

- * DIMENSION

\getsubstring {...} {...} {...} 1 NUMMER 2 NUMMER 3 TEXT
\gettwopassdata {...} * NAME
\gettwopassdatalist {...} * NAME
\getuvalue {...} * NAME
\getvalue {...} * NAME
\getvariable {...} {...} 1 NAME 2 KEY
\getvariabledefault {...} {...} {...} 1 NAME 2 KEY 3 BEFEHL
\getxparameters [...] [..., ² ...,...] 1 TEXT 2 KEY = VALUE
\globaldisablemode [...,*,...] * NAME
\globalenablemode [...,*,...] * NAME
\globalletempty *.. * CSNAME
\globalpopbox ... * CSNAME NUMMER
\globalpopmacro *.. * CSNAME
\globalpreventmode [...,*,...] * NAME

<code>\globalprocesscommalist [...] \...</code> 1 BEFEHL 2 CSNAME
<code>\globalpushbox ...</code> * CSNAME NUMMER
<code>\globalpushmacro \...</code> * CSNAME
<code>\globalpushreferenceprefix {...} ... \globalpopreferenceprefix</code> * + - TEXT
<code>\globalswapcounts \... \...</code> 1 CSNAME 2 CSNAME
<code>\globalswapdimens \... \...</code> 1 CSNAME 2 CSNAME
<code>\globalswapmacros \... \...</code> 1 CSNAME 2 CSNAME
<code>\globalundefine {...}</code> * NAME
<code>\glyphfontfile {...}</code> * FONT
<code>\gobbledoubleempty [...] [...]</code> <div style="display: flex; justify-content: space-around; width: 100%;"> OPT OPT </div> 1 TEXT 2 TEXT
<code>\gobbleeightarguments {...} {...} {...} {...} {...} {...} {...} {...}</code> 1 CONTENT 2 CONTENT 3 CONTENT 4 CONTENT 5 CONTENT 6 CONTENT 7 CONTENT 8 CONTENT

`\gobblefivearguments {...} {...} {...} {...} {...}`

- 1 CONTENT
- 2 CONTENT
- 3 CONTENT
- 4 CONTENT
- 5 CONTENT

`\gobblefiveoptionals [...] [...] [...] [...] [...]`

- 1 TEXT
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT

`\gobblefourarguments {...} {...} {...} {...}`

- 1 CONTENT
- 2 CONTENT
- 3 CONTENT
- 4 CONTENT

`\gobblefouroptionals [...] [...] [...] [...]`

- 1 TEXT
- 2 TEXT
- 3 TEXT
- 4 TEXT

`\gobbleninearguments {...} {...} {...} {...} {...} {...} {...} {...} {...}`

- 1 CONTENT
- 2 CONTENT
- 3 CONTENT
- 4 CONTENT
- 5 CONTENT
- 6 CONTENT
- 7 CONTENT
- 8 CONTENT
- 9 CONTENT

`\gobbleoneargument {...}`

- * CONTENT

`\gobbleoneoptional [...]`

- * TEXT

\gobblesevenarguments {...} {...} {...} {...} {...} {...} {...}

- 1 CONTENT
- 2 CONTENT
- 3 CONTENT
- 4 CONTENT
- 5 CONTENT
- 6 CONTENT
- 7 CONTENT

\gobblesingleempty [...]

OPT

- * TEXT

\gobblesixarguments {...} {...} {...} {...} {...} {...}

- 1 CONTENT
- 2 CONTENT
- 3 CONTENT
- 4 CONTENT
- 5 CONTENT
- 6 CONTENT

\gobblespacetokens

\gobbletenarguments {...} {...} {...} {...} {...} {...} {...} {...} {...} {...}

- 1 CONTENT
- 2 CONTENT
- 3 CONTENT
- 4 CONTENT
- 5 CONTENT
- 6 CONTENT
- 7 CONTENT
- 8 CONTENT
- 9 CONTENT
- 10 CONTENT

\gobblethreearguments {...} {...} {...}

- 1 CONTENT
- 2 CONTENT
- 3 CONTENT

\gobblethreeoptionals [...] [...] [...]

- 1 TEXT
- 2 TEXT
- 3 TEXT

\gobbletwoarguments {...} {...}

- 1 CONTENT
- 2 CONTENT

<p><code>\gobbletwooptionals [...] [...]</code></p> <p>1 TEXT</p> <p>2 TEXT</p>
<p><code>\gobbleuntil \...</code></p> <p>* CSNAME</p>
<p><code>\gobbleuntilrelax ... \relax</code></p> <p>* CONTENT</p>
<p><code>\grabbufferdata [...] [...] [...] [...]</code></p> <p style="text-align: center;">OPT</p> <p>1 CATEGORY</p> <p>2 NAME</p> <p>3 NAME</p> <p>4 NAME</p>
<p><code>\grabbufferdatadirect {...} {...} {...}</code></p> <p>1 NAME</p> <p>2 NAME</p> <p>3 NAME</p>
<p><code>\grabuntil {...} \^2...</code></p> <p>1 NAME</p> <p>2 CSNAME</p>
<p><code>\grave {...}</code></p> <p>* CHARACTER</p>
<p><code>\grayvalue {...}</code></p> <p>* COLOR</p>
<p><code>\greedystringat ... \at ... \to \^3... \and \^4...</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 CSNAME</p> <p>4 CSNAME</p>
<p><code>\greeknumerals {...}</code></p> <p>* NUMBER</p>
<p><code>\groupedcommand {...} {...}</code></p> <p>1 BEFEHL</p> <p>2 BEFEHL</p>
<p><code>\gsetboxllx \^1 {...}</code></p> <p>1 CSNAME NUMBER</p> <p>2 DIMENSION</p>

<code>\gsetboxlly ... {¹... {²...}}</code> 1 CSNAME NUMBER 2 DIMENSION
<code>\gujaratinumerals {[*]...}</code> * NUMBER
<code>\gurmukhinumerals {[*]...}</code> * NUMBER
<code>\hairspace</code>
<code>\halfwaybox {[*]...}</code> * CONTENT
<code>\handletokens ... \with \²...</code> 1 TEXT 2 CSNAME
<code>\hash</code>
<code>\hat {[*]...}</code> * CHARACTER
<code>\hboxofvbox ...</code> * CSNAME NUMBER
<code>\hboxreference [...¹,...] {²...}</code> 1 REFERENCE 2 CONTENT
<code>\hboxBOX {[*]...}</code> * CONTENT
<code>\hdofstring {[*]...}</code> * TEXT
<code>\headhbox ... {²...}</code> ¹ OPT 1 TEXT 2 CONTENT
<code>\headnumbercontent</code>
<code>\headnumberdistance</code>
<code>\headnumberwidth</code>
<code>\headreferenceattributes</code>

<code>\headsetupspacing</code>
<code>\headtextcontent</code>
<code>\headtextdistance</code>
<code>\headtextwidth</code>
<code>\headvbox</code> ¹ ... { ² ...} <small>OPT</small> 1 TEXT 2 CONTENT
<code>\headwidth</code>
<code>\heightanddepthofstring</code> { [*] ...} * TEXT
<code>\heightofstring</code> { [*] ...} * TEXT
<code>\heightspanningtext</code> { ¹ ...} { ² ...} { ³ ...} 1 TEXT 2 DIMENSION 3 FONT
<code>\HELP</code> [¹ ...] { ² ...} { ³ ...} <small>OPT</small> 1 REFERENCE 2 TEXT 3 TEXT instances: textnapovedy
<code>\hglue</code> ... * DIMENSION
<code>\hiddenbar</code> { [*] ...} * CONTENT
<code>\hiddencitation</code> [[*] ...] * REFERENCE
<code>\hiddencite</code> [[*] ...] * REFERENCE
<code>\highlight</code> [¹ ...] { ² ...} 1 NAME 2 TEXT

$\backslash HIGHLIGHT \{...\}$ * TEXT
$\backslash highordinalstr \{...\}$ * TEXT
$\backslash hilo \overset{OPT}{[...]} \{...\} \{...\}$ 1 vlevo vpravo 2 CONTENT 3 CONTENT
$\backslash himilo \{...\} \{...\} \{...\}$ 1 CONTENT 2 CONTENT 3 CONTENT
$\backslash hl \overset{OPT}{[...]}$ * NUMMER
$\backslash hlavnijazyk [...]$ * SPRACHE
$\backslash hodnotabarvy \{...\}$ * COLOR
$\backslash horizontalgrowingbar [..., ...^*..., ...]$ * inherits: \setuppositionbar
$\backslash horizontalpositionbar [..., ...^*..., ...]$ * inherits: \setuppositionbar
$\backslash hphantom \{...\}$ * CONTENT
$\backslash hpos \{...\} \{...\}$ 1 NAME 2 CONTENT
$\backslash hsizefraction \{...\} \{...\}$ 1 DIMENSION 2 NUMMER
$\backslash hsmash \{...\}$ * CONTENT
$\backslash hsmashbox ...$ * CSNAME NUMMER

<code>\hsmashed {...}</code> * CONTENT
<code>\hspace [...] [...]</code> <div> <div>OPT</div> <div>OPT</div> </div> 1 NAME 2 male stredni velke normalni implicitni zadny .5 1 2 3 speech citovat interquotation citace sentence intersentence NAME
<code>\htdpofstring {...}</code> * TEXT
<code>\htofstring {...}</code> * TEXT
<code>\hyphen</code>
<code>\hyphenatedcoloredword {...}</code> * TEXT
<code>\hyphenatedfile {...}</code> * FILE
<code>\hyphenatedfilename {...}</code> * TEXT
<code>\hyphenatedhbox {...}</code> * CONTENT
<code>\hyphenatedpar {...}</code> * TEXT
<code>\hyphenatedurl {...}</code> * TEXT
<code>\hyphenatedword {...}</code> * TEXT
<code>\CHARACTERKERNING [...] {...}</code> <div> <div>OPT</div> </div> 1 NUMMER 2 TEXT
<code>\chardescription {...}</code> * NUMMER
<code>\charwidthlanguage</code>
<code>\check {...}</code> * CHARACTER

<pre>\checkedfiller {...}</pre> <pre>* sym symbol linka sirka mezero NAME BEFEHL</pre>
<pre>\checkedchar {...} {...}</pre> <pre>1 NUMMER</pre> <pre>2 CHARACTER</pre>
<pre>\checkedstrippedcsname \...</pre> <pre>* CSNAME</pre>
<pre>\checkedstrippedcsname ...</pre> <pre>* TEXT</pre>
<pre>\checkcharacteralign {...}</pre> <pre>* CONTENT</pre>
<pre>\checkinjector [...]</pre> <pre>* NAME</pre>
<pre>\checknextindentation [...]</pre> <pre>* ano ne auto</pre>
<pre>\checknextinjector [...]</pre> <pre>* NAME</pre>
<pre>\checkpage [...] [..., ...²..., ...]</pre> <p style="text-align: center;"><small>OPT</small></p> <pre>1 NAME</pre> <pre>2 inherits: \setuppagechecker</pre>
<pre>\checkparameters [...]</pre> <pre>* TEXT</pre>
<pre>\checkpreviousinjector [...]</pre> <pre>* NAME</pre>
<pre>\checksoundtrack {...}</pre> <pre>* NAME</pre>
<pre>\checktwopassdata {...}</pre> <pre>* NAME</pre>
<pre>\checkvariables [...] [..., ...²..., ...]</pre> <pre>1 NAME</pre> <pre>2 set = BEFEHL</pre> <pre>reset = BEFEHL</pre> <pre>KEY = VALUE</pre>

$\backslash\text{chem}$ $\{...\}^1 \{...\}^2 \{...\}^3$ 1 TEXT 2 TEXT 3 TEXT
$\backslash\text{chemical}$ $[...]^{1}_{\text{OPT}} [...]^{2}_{\text{OPT}} [...]^{3}_{\text{OPT}}$ 1 NAME 2 TEXT 3 TEXT
$\backslash\text{chemicalbottext}$ $\{...\}$ * TEXT
$\backslash\text{chemicalmidtext}$ $\{...\}$ * TEXT
$\backslash\text{chemicalsymbol}$ $[...]$ * NAME
$\backslash\text{chemicaltext}$ $\{...\}$ * TEXT
$\backslash\text{chemicaltoptext}$ $\{...\}$ * TEXT
$\backslash\text{chineseallnumerals}$ $\{...\}$ * NUMMER
$\backslash\text{chinesecapnumerals}$ $\{...\}$ * NUMMER
$\backslash\text{chinesenumerals}$ $\{...\}$ * NUMMER
$\backslash\text{INRSTEX}$
$\backslash\text{ibox}$ $\{...\}$ * CONTENT
$\backslash\text{ifassignment}$ $...^1 \backslash\text{else } ...^2 \backslash\text{fi}$ 1 TRUE 2 FALSE
$\backslash\text{iff}$
$\backslash\text{ifinobject}$ $...^1 \backslash\text{else } ...^2 \backslash\text{fi}$ 1 TRUE 2 FALSE

<pre> \ifinoutputstream .¹. \else .². \fi 1 TRUE 2 FALSE </pre>
<pre> \ifparameters .¹. \else .². \fi 1 TRUE 2 FALSE </pre>
<pre> \iftrialssetting .¹. \else .². \fi 1 TRUE 2 FALSE </pre>
<pre> \ignoreimplicitspaces </pre>
<pre> \ignorevalue {...} * NAME </pre>
<pre> \immediatesavetwopassdata {.¹.} {.².} {.³.} 1 NAME 2 NUMMER 3 CONTENT </pre>
<pre> \impliedby </pre>
<pre> \implies </pre>
<pre> \includemenu [...] * NAME </pre>
<pre> \includeversioninfo {...} * NAME </pre>
<pre> \incrementcounter [.¹.] [.².] OPT 1 NAME 2 NUMMER </pre>
<pre> \incrementedcounter [...] * NAME </pre>
<pre> \incrementpagenumber </pre>
<pre> \incrementsubpagenumber </pre>
<pre> \incrementvalue {...} * NAME </pre>
<pre> \indentation </pre>

<code>\infofont</code>
<code>\infofontbold</code>
<code>\inheritparameter [...]¹ [...]² [...]³</code> 1 TEXT 2 TEXT 3 KEY
<code>\inhibitblank</code>
<code>\initializeboxstack {...}</code> * NAME
<code>\inlinebuffer [...,^{OPT}...]</code> * BUFFER
<code>\inlinedbox {...}</code> * CONTENT
<code>\inlinemath {...}</code> * CONTENT
<code>\inlinemathematics {...}</code> * CONTENT
<code>\inlinemessage {...}</code> * TEXT
<code>\inlineordisplaymath {...}¹ {...}²</code> 1 CONTENT 2 CONTENT
<code>\inlinerrange [...]</code> * REFERENCE
<code>\innerflushshapebox</code>
<code>\input {...}</code> * FILE
<code>\inputfilebarename</code>
<code>\inputfilename</code>
<code>\inputfilerealsuffix</code>
<code>\inputfilesuffix</code>

<pre>\inputgivenfile {...}</pre> <pre>* FILE</pre>
<pre>\input ...</pre> <pre>* FILE</pre>
<pre>\insertpages [...] [...²,...] [...³...]</pre> <p style="text-align: center;">OPT OPT</p> <pre>1 FILE</pre> <pre>2 NUMMER</pre> <pre>3 sirka = DIMENSION</pre> <pre> n = NUMMER</pre> <pre> category = NAME</pre>
<pre>\instalacejazyka [...] [...²...]</pre> <pre>1 NAME</pre> <pre>2 inherits: \nastavjazyk</pre>
<pre>\instalacejazyka [...] [...²]</pre> <pre>1 NAME</pre> <pre>2 SPRACHE</pre>
<pre>\installactionhandler {...}</pre> <pre>* NAME</pre>
<pre>\installactivecharacter ...</pre> <pre>* CHARACTER</pre>
<pre>\installanddefineactivecharacter ¹... {...²}</pre> <pre>1 CHARACTER</pre> <pre>2 BEFEHL</pre>
<pre>\installattributestack \[*]...</pre> <pre>* CSNAME</pre>
<pre>\installautocommandhandler \¹... {...²} \³...</pre> <pre>1 CSNAME</pre> <pre>2 NAME</pre> <pre>3 CSNAME</pre>
<pre>\installautosetuphandler \¹... {...²}</pre> <pre>1 CSNAME</pre> <pre>2 NAME</pre>
<pre>\installbasicautosetuphandler \¹... {...²} \³...</pre> <pre>1 CSNAME</pre> <pre>2 NAME</pre> <pre>3 CSNAME</pre>

\installbasicparameterhandler \... {¹... {²...}}

1 CSNAME

2 NAME

\installbottomframerenderer {¹...} {²...}

1 NAME

2 BEFEHL

\installcommandhandler \... {¹... {²...}} \...³...

1 CSNAME

2 NAME

3 CSNAME

\installcorenamespace {¹...}

* NAME

\installdefinehandler \... {¹... {²...}} \...³...

1 CSNAME

2 NAME

3 CSNAME

\installdefinitionset \... {¹... {²...}}

1 CSNAME

2 NAME

\installdefinitionsetmember \... {¹... {²...}} \...³... {⁴...}

1 CSNAME

2 NAME

3 CSNAME

4 NAME

\installdirectcommandhandler \... {¹... {²...}}

1 CSNAME

2 NAME

\installdirectparameterhandler \... {¹... {²...}}

1 CSNAME

2 NAME

\installdirectparametersethandler \... {¹... {²...}}

1 CSNAME

2 NAME

\installdirectsetuphandler \... {¹... {²...}}

1 CSNAME

2 NAME

<pre>\installdirectstyleandcolorhandler \... {...}</pre> <pre>1 CSNAME</pre> <pre>2 NAME</pre>
<pre>\installframedautocommandhandler \... {...} \...</pre> <pre>1 CSNAME</pre> <pre>2 NAME</pre> <pre>3 CSNAME</pre>
<pre>\installframedcommandhandler \... {...} \...</pre> <pre>1 CSNAME</pre> <pre>2 NAME</pre> <pre>3 CSNAME</pre>
<pre>\installleftframerenderer {...} {...}</pre> <pre>1 NAME</pre> <pre>2 BEFEHL</pre>
<pre>\installnamespace {...}</pre> <pre>* NAME</pre>
<pre>\installoutputroutine \... {...}</pre> <pre>1 CSNAME</pre> <pre>2 BEFEHL</pre>
<pre>\installpagearrangement ... {...}</pre> <pre>1 NAME</pre> <pre>2 BEFEHL</pre>
<pre>\installparameterhandler \... {...}</pre> <pre>1 CSNAME</pre> <pre>2 NAME</pre>
<pre>\installparameterhashhandler \... {...}</pre> <pre>1 CSNAME</pre> <pre>2 NAME</pre>
<pre>\installparametersethandler \... {...}</pre> <pre>1 CSNAME</pre> <pre>2 NAME</pre>
<pre>\installparentinjector \... {...}</pre> <pre>1 CSNAME</pre> <pre>2 NAME</pre>

\installrightframerenderer {...} {...}

- 1 NAME
- 2 BEFEHL

\installrootparameterhandler \... {...}

- 1 CSNAME
- 2 NAME

\installsetuphandler \... {...}

- 1 CSNAME
- 2 NAME

\installsetuponlycommandhandler \... {...}

- 1 CSNAME
- 2 NAME

\installshipoutmethod {...} {...}

- 1 NAME
- 2 BEFEHL

\installsimplecommandhandler \... {...} \...

- 1 CSNAME
- 2 NAME
- 3 CSNAME

\installsimpleframedcommandhandler \... {...} \...

- 1 CSNAME
- 2 NAME
- 3 CSNAME

\installstyleandcolorhandler \... {...}

- 1 CSNAME
- 2 NAME

\installswitchcommandhandler \... {...} \...

- 1 CSNAME
- 2 NAME
- 3 CSNAME

\installswitchsetuphandler \... {...}

- 1 CSNAME
- 2 NAME

\installtexdirective {...} {...} {...}

- 1 NAME
- 2 BEFEHL
- 3 BEFEHL

<pre> \installtexttracker {...} {...} {...} 1 NAME 2 BEFEHL 3 BEFEHL </pre>
<pre> \installtopframerenderer {...} {...} 1 NAME 2 BEFEHL </pre>
<pre> \installunitsseparator {...} {...} 1 NAME 2 BEFEHL </pre>
<pre> \installunitsspace {...} {...} 1 NAME 2 BEFEHL </pre>
<pre> \installversioninfo {...} {...} 1 NAME 2 BEFEHL </pre>
<pre> \integerrounding {...} * NUMMER </pre>
<pre> \interakcnilista [...] [...] OPT OPT 1 NAME 2 inherits: \nastavinterakcnilistu </pre>
<pre> \interakcnitlacitka [..., ...¹..., ...] [..., ...²...] OPT 1 inherits: \nastavinterakcnilistu 2 stranka podstranka REFERENCE </pre>
<pre> \interaktivnimenu [...] [...] OPT 1 NAME 2 inherits: \nastavinterakcnimenu </pre>
<pre> \intertext {...} * TEXT </pre>
<pre> \invokepagehandler {...} {...} 1 normalni zadny NAME 2 CONTENT </pre>
<pre> \istltdir ... * TLT TRT </pre>

\istrtdir ... * TLT TRT
\italiccorrection
\itemtag [...*,...] <small>OPT</small> * REFERENCE
\jazyk [...] * SPRACHE
\LANGUAGE
\jdidolu [...] * DIMENSION
\jdina {.. ¹ .} [.. ² .] 1 CONTENT 2 REFERENCE
\jdinabox {...} [...] 1 CONTENT 2 REFERENCE
\jdinastranu {.. ¹ .} [.. ² .] 1 TEXT 2 REFERENCE
\UNIT {...} * CONTENT instances:
\jobfilename
\jobfilesuffix
\Kap {...} * TEXT
\kaligraficke
\kap {...} * TEXT
\keeplinestogether {...} * NUMMER
\keepunwantedspaces

<p>\kerncharacters [¹...] {²...}</p> <p style="text-align: center;">OPT</p> <p>1 NUMMER</p> <p>2 TEXT</p>
<p>\klonujpole [¹...] [²...] [³...] [...,⁴...]</p> <p>1 NAME</p> <p>2 NAME</p> <p>3 NAME</p> <p>4 NAME</p>
<p>\komentar [¹...] [...,²...²...] {³...}</p> <p style="text-align: center;">OPT OPT</p> <p>1 TEXT</p> <p>2 inherits: \nastavkomentar</p> <p>3 TEXT</p>
<p>\KOMENTAR [¹...] [...,²...²...] {³...}</p> <p style="text-align: center;">OPT OPT</p> <p>1 TEXT</p> <p>2 inherits: \nastavkomentar</p> <p>3 TEXT</p> <p>instances: komentar</p>
<p>\komponenta [...]</p> <p>* FILE</p>
<p>\komponenta ...</p> <p>* FILE</p>
<p>\konvertujcislo {¹...} {²...}</p> <p>1 prazdne implicitni zadny mesic month:mnem pismeno Pismeno pismena Pismena a A Csla slovo words Slovo Slova n N rimskecislice Rimskecislice i I r R KR RK recky Recky g G abjadnumerals abjadnodotnumerals abjadnaivenumerals thainumerals devanagarinumerals gurmurkhinumerals gujaratinnumerals tibetannumerals greeknumerals Greeknumerals arabicnumerals persiannumerals arabicexnumerals arabicdecimals persiandecimals koreannumerals koreanparentnumerals koreancirclenumerals kr kr-p kr-c chinesenumerals chinesecapnumerals chineseallnumerals cn cn-c cn-a sloveniannumerals slovenianNumerals spanishnumerals spanishNumerals mathgreek set_0 set_1 set_2 set_3 continued NAME</p> <p>2 NUMMER</p>
<p>\kopirujpole [¹...] [²...]</p> <p>1 NAME</p> <p>2 NAME</p>
<p>\koreancirclenumerals {...}</p> <p>* NUMMER</p>
<p>\koreannumerals {...}</p> <p>* NUMMER</p>
<p>\koreannumeralsc {...}</p> <p>* NUMMER</p>

<code>\koreannumeralsp {...}</code> * NUMMER
<code>\koreanparentnumerals {...}</code> * NUMMER
<code>\korekcebilehomista {...}</code> * CONTENT
<code>\kurziva</code>
<code>\kurzivnitucne</code>
<code>\LAMSTEX</code>
<code>\LATEX</code>
<code>\LamSTeX</code>
<code>\LaTeX</code>
<code>\LUAJITTEX</code>
<code>\LUATEX</code>
<code>\Lua</code>
<code>\LuajitTeX</code>
<code>\LuaTeX</code>
<code>\LABELjazyk</code> instances:
<code>\LABELtexts {...} {...}</code> 1 KEY 2 TEXT instances:
<code>\languagecharacters {...}</code> * NUMMER
<code>\languageCharacters {...}</code> * NUMMER
<code>\languagecharwidth {...}</code> * SPRACHE

$\backslash\text{lastcounter}$ [¹ ...] [² ...] <small>OPT</small> 1 NAME 2 NUMMER
$\backslash\text{lastcountervalue}$ [...] * NAME
$\backslash\text{lastdigit}$ {...} * NUMMER
$\backslash\text{lastlinewidth}$
$\backslash\text{lastnaturalboxdp}$
$\backslash\text{lastnaturalboxht}$
$\backslash\text{lastnaturalboxwd}$
$\backslash\text{lastpredefinedsymbol}$
$\backslash\text{lastrealpage}$
$\backslash\text{lastrealpagenumber}$
$\backslash\text{lastsubcountervalue}$ [¹ ...] [² ...] 1 NAME 2 NUMMER
$\backslash\text{lastsubpagenumber}$
$\backslash\text{lasttwodigits}$ {...} * NUMMER
$\backslash\text{lastuserpage}$
$\backslash\text{lastuserpagenumber}$
$\backslash\text{lateluacode}$ {...} * BEFEHL
$\backslash\text{layeredtext}$ [... ¹ ... ² ...] [... ³ ... ⁴] <small>OPT</small> <small>OPT</small> 1 inherits: $\backslash\text{setuplayer}$ 2 inherits: $\backslash\text{setuplayeredtext}$ 3 TEXT 4 CONTENT
$\backslash\text{layerheight}$
$\backslash\text{layerwidth}$

<p><code>\lazysavetaggedtwopassdata {...} {...} {...} {...}</code></p> <p>1 NAME</p> <p>2 NUMMER</p> <p>3 NAME</p> <p>4 CONTENT</p>
<p><code>\lazysavetwopassdata {...} {...} {...}</code></p> <p>1 NAME</p> <p>2 NUMMER</p> <p>3 CONTENT</p>
<p><code>\lbox¹ {...}</code> <small>OPT</small></p> <p>1 TEXT</p> <p>2 CONTENT</p>
<p><code>\leftbottombox {...}</code></p> <p>* CONTENT</p>
<p><code>\leftbox {...}</code></p> <p>* CONTENT</p>
<p><code>\lefthbox {...}</code></p> <p>* CONTENT</p>
<p><code>\leftLABELtext {...}</code></p> <p>* KEY</p> <p>instances:</p>
<p><code>\leftline {...}</code></p> <p>* CONTENT</p>
<p><code>\lefttorrighthbox¹ {...}</code> <small>OPT</small></p> <p>1 TEXT</p> <p>2 CONTENT</p>
<p><code>\lefttorrightvbox¹ {...}</code> <small>OPT</small></p> <p>1 TEXT</p> <p>2 CONTENT</p>
<p><code>\lefttorrightvtop¹ {...}</code> <small>OPT</small></p> <p>1 TEXT</p> <p>2 CONTENT</p>
<p><code>\leftskipadaption</code></p>
<p><code>\leftsubguillemot</code></p>

$\backslash\text{lefttopbox}$ {...} * CONTENT
$\backslash\text{lefttoright}$
$\backslash\text{lefttorighthbox}$ ¹ ... { ² ...} OPT 1 TEXT 2 CONTENT
$\backslash\text{lefttorightvbox}$ ¹ ... { ² ...} OPT 1 TEXT 2 CONTENT
$\backslash\text{lefttorightvtop}$ ¹ ... { ² ...} OPT 1 TEXT 2 CONTENT
$\backslash\text{letbeundefined}$ {...} * NAME
$\backslash\text{letcatcodecommand}$ \ ¹ ... ² ... \ ³ ... 1 CSNAME 2 CHARACTER NUMMER 3 CSNAME
$\backslash\text{letcscsname}$ \ ¹ ... \csname ² ... \endcsname 1 CSNAME 2 NAME
$\backslash\text{letcsnamecs}$ \csname ¹ ... \endcsname \ ² ... 1 NAME 2 CSNAME
$\backslash\text{letcsnamecsname}$ \csname ¹ ... \endcsname \csname ² ... \endcsname 1 NAME 2 NAME
$\backslash\text{letdummyparameter}$ { ¹ ...} \ ² ... 1 KEY 2 CSNAME
$\backslash\text{letempty}$ *... * CSNAME
$\backslash\text{letgvalue}$ { ¹ ...} \ ² ... 1 NAME 2 CSNAME

<code>\letgvalueempty {...}</code> * NAME
<code>\letgvalurelax {...}</code> * NAME
<code>\letterampersand</code>
<code>\letterat</code>
<code>\letterbackslash</code>
<code>\letterbar</code>
<code>\letterbgroup</code>
<code>\letterclosebrace</code>
<code>\lettercolon</code>
<code>\letterdollar</code>
<code>\letterdoublequote</code>
<code>\letteregroup</code>
<code>\letterescape</code>
<code>\letterexclamationmark</code>
<code>\letterhash</code>
<code>\letterhat</code>
<code>\letterleftbrace</code>
<code>\letterless</code>
<code>\lettermore</code>
<code>\letteropenbrace</code>
<code>\letterpercent</code>
<code>\letterquestionmark</code>
<code>\letterrightbrace</code>
<code>\lettersinglequote</code>
<code>\letterslash</code>

$\backslash\text{letterspacing}$ [¹ ...] { ² ...} <small>OPT</small> 1 NUMMER 2 TEXT
$\backslash\text{lettertilde}$
$\backslash\text{letterunderscore}$
$\backslash\text{letvalue}$ { ¹ ...} \ ² ... 1 NAME 2 CSNAME
$\backslash\text{letvalueempty}$ {.*} * NAME
$\backslash\text{letvaluerelax}$ {.*} * NAME
$\backslash\text{lfence}$ {.*} * CHARACTER
$\backslash\text{lhbox}$ {.*} * CONTENT
$\backslash\text{limitatelines}$ { ¹ ...} { ² ...} { ³ ...} 1 NUMMER 2 BEFEHL 3 TEXT
$\backslash\text{limitatetext}$ { ¹ ...} { ² ...} { ³ ...} 1 TEXT 2 [-+]DIMENSION 3 BEFEHL
$\backslash\text{limitatetext}$ { ¹ ...} {..., ² ...} { ³ ...} 1 TEXT 2 [-+]DIMENSION 3 BEFEHL
$\backslash\text{limtatefirstline}$ { ¹ ...} { ² ...} { ³ ...} 1 TEXT 2 DIMENSION 3 BEFEHL
$\backslash\text{LINENOTE}$ {.*} * TEXT instances:

`\linespanningtext {...} {...} {...}`

- 1 TEXT
- 2 DIMENSION
- 3 FONT

`\listcitation [...1...] [...2]`
OPT

- 1 odkaz = REFERENCE
alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
authornum authoryear
pred = BEFEHL
po = BEFEHL
vlevo = BEFEHL
vpravo = BEFEHL
inherits: \setupbtx
- 2 REFERENCE

`\listcitation [...1] [...2]`
OPT

- 1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear
- 2 REFERENCE

`\listcitation [...1...] [...2...]`

- 1 odkaz = REFERENCE
alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
authornum authoryear
pred = BEFEHL
po = BEFEHL
vlevo = BEFEHL
vpravo = BEFEHL
inherits: \setupbtx
- 2 KEY = VALUE

`\listcite [...1...] [...2]`
OPT

- 1 odkaz = REFERENCE
alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
authornum authoryear
pred = BEFEHL
po = BEFEHL
vlevo = BEFEHL
vpravo = BEFEHL
inherits: \setupbtx
- 2 REFERENCE

`\listcite [...1] [...2]`
OPT

- 1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear
- 2 REFERENCE

`\listcite [...1...] [...2...]`

- 1 odkaz = REFERENCE
alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
authornum authoryear
pred = BEFEHL
po = BEFEHL
vlevo = BEFEHL
vpravo = BEFEHL
inherits: \setupbtx
- 2 KEY = VALUE

`\listnamespaces`

<code>\llap {...}</code> * CONTENT
<code>\loadanyfile [...]</code> * FILE
<code>\loadanyfileonce [...]</code> * FILE
<code>\loadbtxdefinitionfile [...]</code> * FILE
<code>\loadbtxreplacementfile [...]</code> * FILE
<code>\loadcldfile [...]</code> * FILE
<code>\loadcldfileonce [...]</code> * FILE
<code>\loadfontgoodies [...]</code> * FILE
<code>\loadluafile [...]</code> * FILE
<code>\loadluafileonce [...]</code> * FILE
<code>\loadspellchecklist [¹...] [²...]</code> 1 NAME 2 FILE
<code>\loadtexfile [...]</code> * FILE
<code>\loadtexfileonce [...]</code> * FILE
<code>\loadtypescriptfile [...]</code> * FILE
<code>\localframed [¹] [...,²_{OPT}...,...] {³...}</code> 1 NAME 2 inherits: \nastavoramovani 3 CONTENT

<code>\localframedwithsettings</code> [¹ ...] [² ... <u>...</u> ...] { ³ ...} 1 NAME 2 inherits: \nastavoramovani 3 CONTENT
<code>\localhsize</code>
<code>\localpopbox</code> ... * CSNAME NUMBER
<code>\localpopmacro</code> *... * CSNAME
<code>\localpushbox</code> ... * CSNAME NUMBER
<code>\localpushmacro</code> *... * CSNAME
<code>\localundefine</code> {*...} * NAME
<code>\locatedfilepath</code>
<code>\locatefilepath</code> {*...} * FILE
<code>\locfilename</code> {*...} * FILE
<code>\lomihi</code> { ¹ ...} { ² ...} { ³ ...} 1 CONTENT 2 CONTENT 3 CONTENT
<code>\lowerbox</code> { ¹ ...} \ ² ... { ³ ...} 1 DIMENSION 2 CSNAME 3 CONTENT
<code>\lowercased</code> {*...} * TEXT
<code>\lowercasestring</code> ... ¹ \to \ ² ... 1 TEXT 2 CSNAME
<code>\lowerlefthdoubleninequote</code>

<code>\lowerleftsingleninequote</code>
<code>\lowerrightdoubleninequote</code>
<code>\lowerrightsingleninequote</code>
$\backslash LOWHIGH \overset{OPT}{[.{}^1..]} \{{}^2..\} \{{}^3..\}$ <p>1 vlevo vpravo</p> <p>2 CONTENT</p> <p>3 CONTENT</p>
$\backslash LOWMIDHIGH \{{}^1..\} \{{}^2..\} \{{}^3..\}$ <p>1 CONTENT</p> <p>2 CONTENT</p> <p>3 CONTENT</p>
$\backslash lrtbbox \{{}^1..\} \{{}^2..\} \{{}^3..\} \{{}^4..\} \{{}^5..\}$ <p>1 DIMENSION</p> <p>2 DIMENSION</p> <p>3 DIMENSION</p> <p>4 DIMENSION</p> <p>5 CONTENT</p>
$\backslash ltop \overset{OPT}{.{}^1..} \{{}^2..\}$ <p>1 TEXT</p> <p>2 CONTENT</p>
$\backslash luacode \{{}^*..\}$ <p>* BEFEHL</p>
$\backslash luaconditional \{{}^*..\}$ <p>* CSNAME</p>
$\backslash luaenvironment \{{}^*..\}$ <p>* FILE</p>
$\backslash luaexpanded \{{}^*..\}$ <p>* BEFEHL</p>
$\backslash luafunction \{{}^*..\}$ <p>* BEFEHL</p>
<code>\luajitTeX</code>
<code>\luamajorversion</code>
<code>\luaminorversion</code>

<code>\luaparameterset {...} {...}</code> 1 NAME 2 CONTENT
<code>\luasetup {...}</code> * NAME
<code>\luaTeX</code>
<code>\luaversion</code>
<code>\MESIC {...}</code> * NUMMER
<code>\METAFONT</code>
<code>\METAFUN</code>
<code>\METAPOST</code>
<code>\MetaFont</code>
<code>\MetaFun</code>
<code>\MetaPost</code>
<code>\MKII</code>
<code>\MKIV</code>
<code>\MKIX</code>
<code>\MKVI</code>
<code>\MKXI</code>
<code>\MONTHLONG {...}</code> * NUMMER
<code>\MONTHSHORT {...}</code> * NUMMER
<code>\MPanchor {...}</code> * NAME
<code>\MPbetex {...}</code> * NAME

\MPc {...} * NAME
\MPcode {...} {...} <small>OPT</small> 1 NAME 2 CONTENT
\MPcolor {...} * COLOR
\MPcoloronly {...} * COLOR
\MPcolumn {...} * NAME
\MPd {...} * NAME
\MPdrawing {...} * CONTENT
\MPfontsizehskip {...} * FONT
\MPgetmultipars {...} {...} 1 NAME 2 NAME
\MPgetmultishape {...} {...} 1 NAME 2 NAME
\MPgetposboxes {..., ¹ ...} {... ² } 1 NAME 2 NAME
\MPh {...} * NAME
\MPII
\MPIV
\MPinclusions [<small>OPT</small> ...] <small>OPT</small> {...} {... ³ } 1 + 2 NAME 3 CONTENT

\MPleftskip {...} * NAME
\MPll {...} * NAME
\MPlr {...} * NAME
\MPls {...} * NAME
\MPmenubuttons {...} * NAME
\MPn {...} * NAME
\MPoptions {...} * COLOR
\MPoverlayanchor {...} * NAME
\MPp {...} * NAME
\MPpage {...} * NAME
\MPpardata {...} * NAME
\MPplus {... ¹ } {... ² } {... ³ } 1 NAME 2 NUMMER 3 CONTENT
\MPpos {...} * NAME
\MPpositiongraphic {... ¹ } {..., ² ... _{OPT} ,...} 1 NAME 2 KEY = VALUE
\MPposset {...} * NAME

\MP _r {...} * NAME
\MP _r awvar {...} {...} 1 NAME 2 KEY
\MP _r egion {...} * NAME
\MP _r est {...} {...} 1 NAME 2 CONTENT
\MP _r ightskip {...} * NAME
\MP _r s {...} * NAME
\MP _s tring {...} * NAME
\MP _t ext {...} * NAME
\MP _t ransparency {...} * COLOR
\MP _u l {...} * NAME
\MP _u r {...} * NAME
\MP _V I
\MP _v {...} {...} {...} 1 NAME 2 NUMMER 3 CONTENT
\MP _v ar {...} * KEY
\MP _v ariable {...} * KEY

\MPvv {...} {...} 1 NAME 2 CONTENT
\MPw {...} * NAME
\MPwhd {...} * NAME
\MPx {...} * NAME
\MPxy {...} * NAME
\MPxywhd {...} * NAME
\MPy {...} * NAME
\m [...] <small>OPT</small> 1 NAME 2 CONTENT
\makecharacteractive ... * CHARACTER
\makerawcommalist [... ¹ ,...] \ ² ... 1 BEFEHL 2 CSNAME
\makestrutofbox ... * CSNAME NUMBER
\male
\malekurzivnitucne
\malenormalni
\malesklonene
\malesklonenetucne
\maletucne
\maletucnekurzivni

<code>\maletucnesklonene</code>
<code>\maletype</code>
<code>\maoramovani [...,\overset{1}{...}] \{...\}</code> <small>OPT</small> 1 inherits: \setupmathframed 2 CONTENT
<code>\mapfontsize [...]\[^{2}]{...}</code> 1 DIMENSION 2 DIMENSION
<code>\margindata [...]\[^{2}{...}]{...}\[^{3}{...}]{...}\{...\}</code> <small>OPT</small> <small>OPT</small> 1 NAME 2 odkaz = REFERENCE inherits: \setupmargindata 3 inherits: \setupmarginframed 4 CONTENT
<code>\MARGINDATA [...,\overset{1}{...}]{...}\[^{2}{...}]{...}\{...\}</code> <small>OPT</small> <small>OPT</small> 1 odkaz = REFERENCE inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT instances:
<code>\markcontent [...]\[^{2}{...}]{...}</code> <small>OPT</small> 1 reset vse NAME 2 CONTENT
<code>\markinjector [...]</code> * NAME
<code>\mat {...}</code> * CONTENT
<code>\matematika [...]\[^{2}{...}]{...}</code> <small>OPT</small> 1 NAME 2 CONTENT
<code>\math [...]\[^{2}{...}]{...}</code> <small>OPT</small> 1 NAME 2 CONTENT
<code>\mathbf</code>
<code>\mathbi</code>

$\backslash\text{MATHRADICAL}$ $[\overset{1}{...}] \{ \overset{2}{...} \}$ <div> <div>1</div> <div>TEXT</div> </div> <div> <div>2</div> <div>CONTENT</div> </div>
$\backslash\mathrm{mathrm}$
$\backslash\mathscr{mathscript}$
$\backslash\mathsf{mathsl}$
$\backslash\mathsf{mathss}$
$\backslash\mathtt{text}$ $\overset{1}{...} \{ \overset{2}{...} \}$ <div> <div>1</div> <div>TEXT</div> </div> <div> <div>2</div> <div>TEXT</div> </div>
$\backslash\mathtt{textbf}$ $\overset{1}{...} \{ \overset{2}{...} \}$ <div> <div>1</div> <div>TEXT</div> </div> <div> <div>2</div> <div>TEXT</div> </div>
$\backslash\mathtt{textbi}$ $\overset{1}{...} \{ \overset{2}{...} \}$ <div> <div>1</div> <div>TEXT</div> </div> <div> <div>2</div> <div>TEXT</div> </div>
$\backslash\mathtt{textbs}$ $\overset{1}{...} \{ \overset{2}{...} \}$ <div> <div>1</div> <div>TEXT</div> </div> <div> <div>2</div> <div>TEXT</div> </div>
$\backslash\mathtt{textit}$ $\overset{1}{...} \{ \overset{2}{...} \}$ <div> <div>1</div> <div>TEXT</div> </div> <div> <div>2</div> <div>TEXT</div> </div>
$\backslash\mathtt{textsl}$ $\overset{1}{...} \{ \overset{2}{...} \}$ <div> <div>1</div> <div>TEXT</div> </div> <div> <div>2</div> <div>TEXT</div> </div>
$\backslash\mathtt{texttf}$ $\overset{1}{...} \{ \overset{2}{...} \}$ <div> <div>1</div> <div>TEXT</div> </div> <div> <div>2</div> <div>TEXT</div> </div>
$\backslash\mathtt{tf}$
$\backslash\mathbf{mathtriplet}$ $[\overset{1}{...}] \{ \overset{2}{...} \} \{ \overset{3}{...} \} \{ \overset{4}{...} \}$ <div> <div>1</div> <div>NAME</div> </div> <div> <div>2</div> <div>TEXT</div> </div> <div> <div>3</div> <div>TEXT</div> </div> <div> <div>4</div> <div>TEXT</div> </div>

`\MATHTRIPLET [...]1 {...}2 {...}3 {...}4`
OPT OPT OPT OPT

- 1 NAME
- 2 TEXT
- 3 TEXT
- 4 TEXT

`\mathhtt`

`\MATHUNDEREXTENSIBLE {...}^*`

- * TEXT

`\MATHUNDERTEXTEXTENSIBLE {...}1 {...}2`

- 1 TEXT
- 2 TEXT

`\MATHUNSTACKED`

`\mathupright`

`\mathword ... {...}1`
OPT

- 1 TEXT
- 2 TEXT

`\mathwordbf ... {...}1`
OPT

- 1 TEXT
- 2 TEXT

`\mathwordbi ... {...}1`
OPT

- 1 TEXT
- 2 TEXT

`\mathwordbs ... {...}1`
OPT

- 1 TEXT
- 2 TEXT

`\mathwordit ... {...}1`
OPT

- 1 TEXT
- 2 TEXT

`\mathwordsl ... {...}1`
OPT

- 1 TEXT
- 2 TEXT

`\mathwordtf ... {...}1`
OPT

- 1 TEXT
- 2 TEXT

$\backslash\maxaligned \{...\}$ * CONTENT
$\backslash\mazaramovani [\dots \overset{1}{=} \dots] \{ \overset{2}{\dots} \}$ 1 inherits: $\backslash\mathrm{setupmathframed}$ 2 CONTENT
$\backslash\mbox \{...\}$ * CONTENT
$\backslash\mcframed [\dots \overset{1}{=} \dots] \{ \dots \}$ 1 inherits: $\backslash\mathrm{setupmathframed}$ 2 CONTENT
$\backslash\mathrm{measure} \{...\}$ * NAME
$\backslash\mathrm{measured} \{...\}$ * NAME
$\backslash\mathrm{medskip}$
$\backslash\mathrm{medspace}$
$\backslash\mathrm{mequal} \{ \overset{1}{\dots} \} \{ \overset{2}{\dots} \}$ 1 TEXT 2 TEXT
$\backslash\mathrm{meritko} [\overset{1}{\dots}] [\dots \overset{2}{=} \dots] \{ \overset{3}{\dots} \}$ 1 NAME 2 inherits: $\backslash\mathrm{setupscale}$ 3 CONTENT
$\backslash\mathrm{mesic} \{...\}$ * NUMMER
$\backslash\mathrm{message} \{...\}$ * TEXT
$\backslash\mathrm{metaTeX}$
$\backslash\mathrm{mezera}$
$\backslash\mathrm{mfence} \{...\}$ * CHARACTER
$\backslash\mathrm{mfunction} \{...\}$ * CONTENT

$\backslash\mathrm{functionlabeltext}\{...\}$ * NAME
$\backslash\mathrm{mhbox}\{...\}$ * CONTENT
$\backslash\mathrm{mhookleftarrow}\overset{1}{\{...\}}\overset{2}{\{...\}}$ 1 TEXT 2 TEXT
$\backslash\mathrm{mhookrightarrow}\overset{1}{\{...\}}\overset{2}{\{...\}}$ 1 TEXT 2 TEXT
$\backslash\mathrm{middlealigned}\{...\}$ * CONTENT
$\backslash\mathrm{middlebox}\{...\}$ * CONTENT
$\backslash\mathrm{midhbox}\{...\}$ * CONTENT
$\backslash\mathrm{minimalhbox}\overset{1}{...}\overset{2}{\{...\}}$ 1 TEXT 2 CONTENT
$\backslash\mathrm{mixedcaps}\{...\}$ * TEXT
$\backslash\mathrm{mkvibuffer}\overset{*}{[...]}$ * BUFFER
$\backslash\mathrm{mLeftarrow}\overset{1}{\{...\}}\overset{2}{\{...\}}$ 1 TEXT 2 TEXT
$\backslash\mathrm{mLeftrightarrow}\overset{1}{\{...\}}\overset{2}{\{...\}}$ 1 TEXT 2 TEXT
$\backslash\mathrm{mleftarrow}\overset{1}{\{...\}}\overset{2}{\{...\}}$ 1 TEXT 2 TEXT
$\backslash\mathrm{mleftharpoonupdown}\overset{1}{\{...\}}\overset{2}{\{...\}}$ 1 TEXT 2 TEXT

$\backslash\mleftharpoonup$ $\{\dots\}$ $\{\dots\}$ <small>OPT OPT</small> 1 TEXT 2 TEXT
$\backslash\mleftrightharpoonup$ $\{\dots\}$ $\{\dots\}$ <small>OPT OPT</small> 1 TEXT 2 TEXT
$\backslash\mleftrightharpoons$ $\{\dots\}$ $\{\dots\}$ <small>OPT OPT</small> 1 TEXT 2 TEXT
$\backslash\mmapsto$ $\{\dots\}$ $\{\dots\}$ <small>OPT OPT</small> 1 TEXT 2 TEXT
$\backslash\moduleparameter$ $\{\dots\}$ $\{\dots\}$ 1 FILE 2 KEY
$\backslash\molecule$ $\{.*\}$ * CONTENT
$\backslash\mono$
$\backslash\mononormal$
$\backslash\monotucne$
$\backslash\monthlong$ $\{.*\}$ * NUMMER
$\backslash\monthshort$ $\{.*\}$ * NUMMER
$\backslash\mprandomnumber$
$\backslash\mRrightarrow$ $\{\dots\}$ $\{\dots\}$ <small>OPT OPT</small> 1 TEXT 2 TEXT
$\backslash\mrel$ $\{\dots\}$ $\{\dots\}$ <small>OPT OPT</small> 1 TEXT 2 TEXT
$\backslash\mrightarrow$ $\{\dots\}$ $\{\dots\}$ <small>OPT OPT</small> 1 TEXT 2 TEXT

$\backslash\mathrm{mrightharpoondown} \overset{1}{\{...\}} \overset{2}{\{...\}}$ 1 TEXT 2 TEXT
$\backslash\mathrm{mrightharpoonup} \overset{1}{\{...\}} \overset{2}{\{...\}}$ 1 TEXT 2 TEXT
$\backslash\mathrm{mrightharpoons} \overset{1}{\{...\}} \overset{2}{\{...\}}$ 1 TEXT 2 TEXT
$\backslash\mathrm{mrightharpoonleftarrow} \overset{1}{\{...\}} \overset{2}{\{...\}}$ 1 TEXT 2 TEXT
$\backslash\mathrm{mrizka} [\dots \overset{*}{=} \dots]$ * inherits: \basegrid
$\backslash\mathrm{mtext} \{...\}$ * CONTENT
$\backslash\mathrm{mtriplerel} \overset{1}{\{...\}} \overset{2}{\{...\}}$ 1 TEXT 2 TEXT
$\backslash\mathrm{mtwoheadleftarrow} \overset{1}{\{...\}} \overset{2}{\{...\}}$ 1 TEXT 2 TEXT
$\backslash\mathrm{mtwoheadrightarrow} \overset{1}{\{...\}} \overset{2}{\{...\}}$ 1 TEXT 2 TEXT
$\backslash\mathrm{NormalizeFontHeight} \backslash \overset{1}{...} \overset{2}{\{...\}} \overset{3}{\{...\}} \overset{4}{\{...\}}$ 1 CSNAME 2 TEXT 3 DIMENSION 4 FONT
$\backslash\mathrm{NormalizeFontWidth} \backslash \overset{1}{...} \overset{2}{\{...\}} \overset{3}{\{...\}} \overset{4}{\{...\}}$ 1 CSNAME 2 TEXT 3 DIMENSION 4 FONT

`\NormalizeTextHeight {...} {...} {...}`

- 1 FONT
- 2 DIMENSION
- 3 TEXT

`\NormalizeTextWidth {...} {...} {...}`

- 1 FONT
- 2 DIMENSION
- 3 TEXT

`\nadtrzeni {...}`

- * CONTENT

`\nadtrzeno {...}`

- * CONTENT

`\namedheadnumber {...}`

- * ABSCHNITT

`\namedstructureheadlocation {...}`

- * ABSCHNITT

`\namedstructureuservariable {...} {...}`

- 1 ABSCHNITT
- 2 KEY

`\namedstructurevariable {...} {...}`

- 1 ABSCHNITT
- 2 KEY

`\namedtaggedlabeltexts {...} {...} {...} {...} {...}`

- 1 NAME
- 2 NAME
- 3 NAME
- 4 NAME
- 5 CONTENT

`\nastavbarvu [...]`

- * FILE

`\nastavbarvy [...,...*,...]`

- * status = start stop
- spot = ano ne
- expanzen = ano ne
- faktor = ano ne
- rgb = ano ne
- cmyk = ano ne
- konverze = ano ne vzdy
- pagecolormodel = auto zadny NAME
- barvatextu = COLOR
- intent = overprint knockout zadny

\nastavbilamista [...^{*}...]

OPT

* fixuj fixne prizpusobive radek pulradku quarterline zadny male stredni velke implicitni DIMENSION

\nastavblok [...¹...][...²...]

OPT

1 NAME

2 pred = BEFEHL
po = BEFEHL
vnitrni = BEFEHL
pismo = STYLE BEFEHL
barva = COLOR

\nastavbloksekce [...¹...][...²...]

OPT

1 NAME

2 stranka = inherits: \strana
pred = BEFEHL
po = BEFEHL
cislo = ano ne

\nastavbuffer [...¹...][...²...]

OPT

1 BUFFER

2 pred = BEFEHL
po = BEFEHL

\nastavcernelinky [...^{*}...]

* sirka = max DIMENSION
vyska = max DIMENSION
hloubka = max DIMENSION
vzdalenost = DIMENSION
n = NUMMER
alternativa = a b
pismo = STYLE BEFEHL
barva = COLOR
typ = mp ano ne
mp = NAME

\nastavcislonadpisu [...¹][...²]

1 ABSCHNITT

2 [-+]NUMMER

\nastavcislostrany [...^{*}...]

* inherits: \setupuserpagenumber

\nastavcislovaniodstavcu [...^{*}...]

* status = start stop radek reset
vzdalenost = DIMENSION
pismo = STYLE BEFEHL
barva = COLOR

`\nastavcislovaniradku [...1,...2,...] [...1,...2,...]`
OPT

```
1  NAME
2  start      = NUMMER
   krok       = NUMMER
   metoda     = stranka prvni dalsi
   konverze   = NAME
   pokracovat = ano ne
   misto      = text begin end implicitni vlevo vpravo uvnitr vnejsi ivlevo ivpravo marginalie naokraj
   vzdalenost = DIMENSION
   zarovnani  = uvnitr vnejsi flushleft flushright vlevo vpravo nastred auto
   prikaz     = \...##1
   vlevo      = BEFEHL
   vpravo     = BEFEHL
   marginalie = DIMENSION
   sirka      = marginalie DIMENSION
   pismeno    = STYLE BEFEHL
   barva      = COLOR
```

`\nastavcislovanistran [...*,...*,...]`

```
*  alternativa = jednostranne dvoustranny
   stranka     = inherits: \strana
   strut       = ano ne
   prikaz      = \...##1
   vlevo       = BEFEHL
   vpravo      = BEFEHL
   status      = start stop
   sirka       = DIMENSION
   misto       = zahlavi upati vlevo nastred vpravo ivlevo ivpravo marginalie naokraj naokraj textovahrana
   pismeno     = STYLE BEFEHL
   barva       = COLOR
```

`\nastavcitaci [...*,...*,...]`

```
*  inherits: \setupdelimitedtext
```

`\nastavdeleniplvoucichobjektu [...*,...*,...]`

```
*  pred       = BEFEHL
   po         = BEFEHL
   mezi       = BEFEHL
   radky      = auto NUMMER
   konverze   = NAME
```

`\nastavdelitko [...*,...*,...]`

```
*  znak = normalni siroce
```

`\nastavdolnitexty [...1,...2,...3,...4,...5,...]`
OPT OPT OPT OPT OPT

```
1  text marginalie hrana
2  datum cislostranky BESCHRIFTUNG TEXT BEFEHL
3  datum cislostranky BESCHRIFTUNG TEXT BEFEHL
4  datum cislostranky BESCHRIFTUNG TEXT BEFEHL
5  datum cislostranky BESCHRIFTUNG TEXT BEFEHL
```

`\nastaveni [...]`

```
*  NAME
```

`\nastaveni {...}`

```
*  NAME
```

\nastavhorejsek [...]¹ [...,...²...,...]
OPT

1 text marginalie hrana

2 inherits: \setuplayoutelement

\nastavhornitexty [...]¹ [...]² [...]³ [...]⁴ [...]⁵
OPT OPT OPT OPT OPT

1 text marginalie hrana

2 datum cislostranky BESCHRIFTUNG TEXT BEFEHL

3 datum cislostranky BESCHRIFTUNG TEXT BEFEHL

4 datum cislostranky BESCHRIFTUNG TEXT BEFEHL

5 datum cislostranky BESCHRIFTUNG TEXT BEFEHL

\nastavinterakci [...]¹ [...,...²...,...]
OPT

1 NAME

2 status = start stop
pismeno = STYLE BEFEHL
barva = COLOR
kontrastnibarva = COLOR
titul = TEXT
podtitulek = COLOR
autor = TEXT
datum = TEXT
keyword = TEXT
zaostreni = standardni ramecek sirka minsirka vyska minvyska prizpusobive tight
menu = zap vyp
fieldlayer = auto NAME
pocitat = REFERENCE
klik = ano ne
obrazovka = normalni novy
stranka = ano ne stranka jmeno auto
otevriakci = REFERENCE
zavriakci = REFERENCE
akceotevrenistranky = REFERENCE
akcezavrenistranky = REFERENCE
sadasymbolu = NAME
vyska = DIMENSION
hloubka = DIMENSION
focusoffset = DIMENSION

\nastavinterakci [...]^{*}
OPT

* NAME

\nastavinterakcnilistu [...]¹ [...,...²...,...]
OPT

1 NAME

2 alternativa = a b c d e f g
status = start stop
prikaz = CSNAME
sirka = DIMENSION
vyska = DIMENSION max siroky
hloubka = DIMENSION max
vzdalenost = DIMENSION
krok = male stredni velke
barvapoziadi = COLOR
pismeno = STYLE BEFEHL
barva = COLOR
kontrastnibarva = COLOR
symbol = ano ne
inherits: \nastavoramovani

\nastavinterakcnimenu [...¹,...] [...²,...] OPT

```
1  NAME

2  alternativa      =  vertikalne horizontalne skryte
   category         =  NAME
   levyoffset       =  prekryv ramecek zadny implicitni DIMENSION
   pravyoffset      =  prekryv ramecek zadny implicitni DIMENSION
   offsetvrsku      =  prekryv ramecek zadny implicitni DIMENSION
   offsetspodku     =  prekryv ramecek zadny implicitni DIMENSION
   maxsirka         =  DIMENSION
   maxvyska         =  DIMENSION
   itemalign        =  vlevo nastred vpravo flushleft flushright nizko vysoko nivy
   status           =  start prazdne lokalne
   vlevo            =  BEFEHL
   vpravo           =  BEFEHL
   vzdalenost       =  prekryv DIMENSION
   pred             =  BEFEHL
   po               =  BEFEHL
   mezi             =  BEFEHL
   position         =  ano ne
   stredni          =  BEFEHL
   pismo            =  STYLE BEFEHL
   barva            =  COLOR
   stejnastranka    =  ano ne prazdne zadny normalni implicitni
   kontrastnibarva  =  COLOR
   inherits: \nastavoramovani
```

\nastavinterakcniobrazovku [...^{*},...] OPT

```
*  sirka            =  prizpusobive max tight DIMENSION
   vyska            =  prizpusobive max tight DIMENSION
   zpetnamezera     =  DIMENSION
   horoffset        =  DIMENSION
   offsethlavicky   =  DIMENSION
   svrchnimezera    =  DIMENSION
   volba            =  prizpusobive max jednostranne dvoustranny zalozka auto zadny implicitni fixne nasirku portrait
                     stranka papir
   copies           =  NUMMER
   prodleva         =  zadny NUMMER
```

\nastavjazyk [...¹,...] [...²,...] OPT

```
1  SPRACHE implicitni

2  implicitni       =  SPRACHE
   status           =  start stop
   datum            =  inherits: \aktualnidatum
   patterns         =  FILE
   lefthyphenmin    =  NUMMER
   righthyphenmin   =  NUMMER
   lefthyphenchar   =  NUMMER
   righthyphenchar  =  NUMMER
   setups           =  NAME
   mezerovani       =  siroky zhustene
   font             =  auto
   text             =  TEXT
   limittext        =  TEXT
   hyphen           =  TEXT
   compoundhyphen    =  TEXT
   leftcompoundhyphen =  TEXT
   rightcompoundhyphen =  TEXT
   citovatvlevo     =  BEFEHL
   citovatvpravo    =  BEFEHL
   citacevlevo      =  BEFEHL
   citacevpravo     =  BEFEHL
   leftspeech       =  BEFEHL
   rightspeech      =  BEFEHL
   vetavlevo        =  BEFEHL
   middlespeech     =  BEFEHL
   vetavpravo       =  BEFEHL
   midsentence      =  BEFEHL
   podvetavlevo     =  BEFEHL
   podvetavpravo    =  BEFEHL
   faktor           =  ano ne
```

\nastavkapitalky [...¹,...] [...²,...] OPT

1 NAME
2 titul = ano ne
sc = ano ne
pismoeno = STYLE BEFEHL

\nastavkombinovanyseznam [...¹.] [...²,...] OPT

1 LISTE
2 inherits: \nastavseznam

\nastaveniCOMBINEDLIST [...^{*},...] OPT

* inherits: \nastavseznam

instances:

\nastavkomentar [...¹,...] [...²,...] OPT

1 NAME
2 status = start stop zadny
metoda = normalni skryte
symbol = Comment Napoveda Insert Klavesa Newparagraph Note Odstavec Default
sirka = prizpusobive DIMENSION
vyska = prizpusobive DIMENSION
hloubka = prizpusobive DIMENSION
titul = TEXT
podtitulek = TEXT
autor = TEXT
nx = NUMMER
ny = NUMMER
barva = COLOR
volba = xml max
textlayer = NAME
misto = levahrana pravahrana naokraji levvyokraj pravyokraj text vysoko zadny
vzdalenost = DIMENSION

\nastavkomentarstrany [...^{*},...] OPT

* misto = vlevo vpravo vrsek spodek zadny
status = start stop zadny
offset = DIMENSION
vzdalenost = DIMENSION
sirka = DIMENSION
vyska = DIMENSION

\nastavmarginalnilinky [...¹.] [...²,...] OPT

1 NUMMER
2 inherits: \setupmarginrule

\nastavmeziradkovoumezeru [...¹,...] [...²,...] OPT

1 NAME
2 radek = DIMENSION
vyska = NUMMER
hloubka = NUMMER
minvyska = NUMMER
mindepth = NUMMER
vzdalenost = DIMENSION
vrsek = NUMMER vyska
spodek = NUMMER
natahnout = NUMMER
shrink = NUMMER

\nastavmeziradkovoumezeru [...^{*},...] OPT

* zap vyp reset auto male stredni velke NUMMER DIMENSION

\nastavmeziradkovoumezeru [...]

* NAME

\nastavnadpis [...,¹...] [...,²...,...]
OPT

1 ABSCHNITT

2 frontpartlabel = NAME
bodypartlabel = NAME
appendixlabel = NAME
backpartlabel = NAME
expanzen = ano ne xml
catcodes = NAME
sectionresetset = NAME
sectionseparatorset = NAME
sectionconversionset = NAME
konverze = NAME
sectionstarter = BEFEHL PROCESSOR->BEFEHL
sectionstopper = BEFEHL PROCESSOR->BEFEHL
sectionset = NAME
sectionsegments = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:*
ABSCHNITT:vse
referenceprefix = + - TEXT
pismo = STYLE BEFEHL
barva = COLOR
styltextu = STYLE BEFEHL
barvatextu = COLOR
stylcisla = STYLE BEFEHL
barvacisla = COLOR
propojeni = ABSCHNITT
vlastnicislo = ano ne
beforesection = BEFEHL
aftersection = BEFEHL
insidection = BEFEHL
zvysujicicislo = ano ne seznam prazdne
umistihlavicku = ano ne skryte prazdne
cislo = ano ne
stranka = inherits: \strana
znaceni = stranka reset
zahlavi = start stop vysoko zadny normalni prazdne zadneznaceni NAME
text = start stop vysoko zadny normalni prazdne zadneznaceni NAME
upati = start stop vysoko zadny normalni prazdne zadneznaceni NAME
pred = BEFEHL
po = BEFEHL
mezi = BEFEHL
pokracovat = ano ne
zarovnejtitul = ano ne plvouciobjekt
meziradkovamezera = NAME
interakce = seznam odkaz
internalgrid = NAME
mrizka = normalni standardni ano striktni tolerantni vrsek spodek obe široky prizpusobive prvni
posledni vysoko jedna nizko zadny radek strut box min max nastred NAME
zarovnani = inherits: \nastavzarovnani
tolerance = inherits: \nastavtoleranci
strut = ano ne
zaveseni = radek široky prizpusobive zadny NUMBER
marginalie = DIMENSION
odsadpristi = ano ne auto
alternativa = text odstavec normalni marginalie naokraji vrsek nastred spodek reverse marginalnitext
NAME
misto = NAME
sirka = DIMENSION
numberwidth = DIMENSION
sirkatextu = DIMENSION
vzdalenost = DIMENSION
textdistance = DIMENSION
predchoziprikaz = BEFEHL
prikazpo = BEFEHL
prikaz = \...##1##2
textovyprikaz = \...##1
deeptextcommand = \...##1
ciselnyprikaz = \...##1
deepnumbercommand = \...##1

<p><code>\nastavnadpisy [...,¹...] [...,²...,...]</code> <small>OPT</small></p> <p>1 ABSCHNITT</p> <p>2 inherits: \nastavnadpis</p>
<p><code>\chapter [...,¹...] {...}</code> <small>OPT</small></p> <p>1 REFERENCE</p> <p>2 TEXT</p>
<p><code>\section [...,¹...] {...}</code> <small>OPT</small></p> <p>1 REFERENCE</p> <p>2 TEXT</p>
<p><code>\subject [...,¹...] {...}</code> <small>OPT</small></p> <p>1 REFERENCE</p> <p>2 TEXT</p>
<p><code>\subsection [...,¹...] {...}</code> <small>OPT</small></p> <p>1 REFERENCE</p> <p>2 TEXT</p>
<p><code>\subsubject [...,¹...] {...}</code> <small>OPT</small></p> <p>1 REFERENCE</p> <p>2 TEXT</p>
<p><code>\subsubsection [...,¹...] {...}</code> <small>OPT</small></p> <p>1 REFERENCE</p> <p>2 TEXT</p>
<p><code>\subsubsubject [...,¹...] {...}</code> <small>OPT</small></p> <p>1 REFERENCE</p> <p>2 TEXT</p>
<p><code>\subsubsubsection [...,¹...] {...}</code> <small>OPT</small></p> <p>1 REFERENCE</p> <p>2 TEXT</p>
<p><code>\subsubsubsubject [...,¹...] {...}</code> <small>OPT</small></p> <p>1 REFERENCE</p> <p>2 TEXT</p>
<p><code>\subsubsubsubsection [...,¹...] {...}</code> <small>OPT</small></p> <p>1 REFERENCE</p> <p>2 TEXT</p>
<p><code>\subsubsubsubsubject [...,¹...] {...}</code> <small>OPT</small></p> <p>1 REFERENCE</p> <p>2 TEXT</p>
<p><code>\subsubsubsubsubsection [...,¹...] {...}</code> <small>OPT</small></p> <p>1 REFERENCE</p> <p>2 TEXT</p>
<p><code>\subsubsubsubsubsubject [...,¹...] {...}</code> <small>OPT</small></p> <p>1 REFERENCE</p> <p>2 TEXT</p>

\title [...,¹...] {..²}
OPT

1 REFERENCE

2 TEXT

\nastavodkazovani [...,*...,...]

* status = start stop
expanden = ano ne xml
autofile = ano ne
export = ano ne
vlevo = BEFEHL
vpravo = BEFEHL
sirka = DIMENSION
oboustranne = ano ne
interakce = popis text symbol vse
oddelovac = BEFEHL
prefix = + - TEXT

\nastavodsazovani [...,*...,...]
OPT

* [-+]male [-+]stredni [-+]velke zadny ne ne prvni dalsi ano vzdy nikdy liche sude normalni reset toggle DIMENSION
NAME

\nastavodstavce [...¹] [...,²...] [...,*³...,...]
OPT OPT

1 NAME

2 kazdy NUMMER

3 n = NUMMER
pred = BEFEHL
po = BEFEHL
sirka = DIMENSION
vzdalenost = DIMENSION
vyska = DIMENSION prizpusobive
vrsek = BEFEHL
spodek = BEFEHL
zarovnani = inherits: \nastavzarovnani
vnitrni = BEFEHL
prikaz = BEFEHL
linka = zap vyp
tloustkalinky = DIMENSION
barvalinky = COLOR
pismeno = STYLE BEFEHL
barva = COLOR

\nastavodstavce [...¹] [...,*²...,...]
OPT

1 NAME:NUMMER

2 n = NUMMER
pred = BEFEHL
po = BEFEHL
sirka = DIMENSION
vzdalenost = DIMENSION
vyska = DIMENSION prizpusobive
vrsek = BEFEHL
spodek = BEFEHL
zarovnani = inherits: \nastavzarovnani
vnitrni = BEFEHL
prikaz = BEFEHL
linka = zap vyp
tloustkalinky = DIMENSION
barvalinky = COLOR
pismeno = STYLE BEFEHL
barva = COLOR

\nastavopis [...¹,...] [...²,...]

OPT

```

1  NAME

2  lichyokraj      = DIMENSION
   sudamarginalie = DIMENSION
   marginalie      = ano ne standardni DIMENSION
   volba           = mp lua xml parsed-xml nested tex context zadny NAME
   pismeno         = STYLE BEFEHL
   barva           = COLOR
   zarovnnani      = inherits: \nastavzarovnnani
   radky           = ano ne normalni hyphenated
   mezera          = zap vyp normalni fixne natahnout
   keeptogether    = ano ne
   pred            = BEFEHL
   po              = BEFEHL
   strip           = ano ne NUMMER
   range           = NUMMER NAME
   tab             = ano ne NUMMER
   escape          = ano ne TEXT PROCESSOR->TEXT
   odsadpristi    = ano ne auto
   pokracovat      = ano ne
   start           = NUMMER
   stop            = NUMMER
   krok            = NUMMER
   cislovani       = soubor radek ne
   prazdny         = inherits: \preskoc

```

\nastavoramovani [...¹,...] [...²,...]

OPT

```

1  NAME

2  roh             = pravouhly zaobleny NUMMER
   rohramecku      = pravouhly zaobleny NUMMER
   rohpozadi       = pravouhly zaobleny NUMMER
   polomer         = DIMENSION
   polomerramecku  = DIMENSION
   polomerpozadi   = DIMENSION
   hloubka         = DIMENSION
   hloubkramecku   = DIMENSION
   hloubkapozadi   = DIMENSION
   barvaramecku    = COLOR
   rameceknahore   = zap vyp NAME
   ramecekdole     = zap vyp NAME
   ramecekvlevo    = zap vyp NAME
   ramecekvpravo   = zap vyp NAME
   region          = ano ne
   tloustkalinky   = DIMENSION
   offsetramecku   = DIMENSION
   ramecek         = zap vyp prekryv zadny
   pozadi          = popredi barevne NAME
   offsetpozadi    = ramecek DIMENSION
   component       = NAME
   extras          = BEFEHL
   foregroundstyle  = STYLE BEFEHL
   foregroundcolor  = COLOR
   setups          = NAME
   offset          = implicitni prekryv zadny DIMENSION
   sirka           = lokalne prizpusobive max široky fixne DIMENSION
   vyska           = prizpusobive max široky DIMENSION
   zarovnnani      = inherits: \nastavzarovnnani
   strut           = ano ne zadny lokalne globalne
   autostrut       = ano ne
   misto           = vyska podlehloubky vysoko nizko vrsek nastred spodek radek nivy visici drzet rovnice matematika
                   normalni
   autosirka       = ano ne sila
   radky           = NUMMER
   vrsek           = BEFEHL
   spodek          = BEFEHL
   prazdny         = ano ne
   profile         = NAME
   prazdne         = ano ne
   loffset         = DIMENSION
   roffset         = DIMENSION
   toffset         = DIMENSION
   boffset         = DIMENSION
   orientation     = NUMMER

```

\nastavorez [...,*...]

```
*  status      = start stop
   sirka       = DIMENSION
   vyska       = DIMENSION
   hoffset     = DIMENSION
   voffset     = DIMENSION
   x           = NUMMER
   y           = NUMMER
   nx          = NUMMER
   ny          = NUMMER
   sx          = NUMMER
   sy          = NUMMER
   levyoffset  = DIMENSION
   pravyoffset = DIMENSION
   offsetvrsku = DIMENSION
   offsetspodku = DIMENSION
   mp          = NAME
   n           = NUMMER
   offset      = DIMENSION
```

\nastavotoceni [...,*...]

```
*  misto = prizpusobive siroky podlehloubky vysoko nastred implicitni normalni
   rotace = vlevo vpravo uvnitr vnejsi NUMMER
   inherits: \nastavoramovani
```

\nastavpaletu [...]

```
*  NAME
```

\nastavplvouciobjekt [...¹,...] [...²,...]

```
1  SINGULAR
2  odsadpristi      = ano ne auto
   implicitni      = inherits: \placefloat
   fallback        = inherits: \placefloat
   vnitrni         = BEFEHL
   kriterium       = DIMENSION
   metoda          = NUMMER
   sidemethod      = NUMMER
   textmethod      = NUMMER
   sidealign       = vyska podlehloubky radek pulradku mrizka normalni
   mrizka          = CD:STRING
   lokalne         = ano ne
   prikaz          = \...##1
   availablewidth  = DIMENSION
   availableheight = DIMENSION
   minsirka        = DIMENSION
   maxsirka        = DIMENSION
   misto           = vlevo vpravo nastred flushleft flushright center max uvnitr vnejsi innermargin outermargin
                   inneredge outeredge zpetnamezera cutspace levyokraj pravyokraj levahrana pravahrana
   vzdalenostlevehookraje = DIMENSION
   vzdalenostpravehookraje = DIMENSION
   levyokraj       = DIMENSION
   pravyokraj      = DIMENSION
   innermargin     = DIMENSION
   outermargin     = DIMENSION
   bottombefore    = BEFEHL
   bottomafter     = BEFEHL
   mezerapred      = zadny inherits: \preskoc
   mezeraza        = zadny inherits: \preskoc
   sirka           = DIMENSION
   vyska           = DIMENSION
   offset          = DIMENSION zadny prekryv
   bocnimezerapred = zadny inherits: \preskoc
   bocnimezeraza   = zadny inherits: \preskoc
   marginalie      = DIMENSION
   nvrsek          = DIMENSION
   nspodek         = DIMENSION
   krok            = male stredni velke radek podlehloubky
   nradky          = NUMMER
   cache           = ano ne
```

`\nastavpodcislostrany [...,1*,...]`

* inherits: \setupcounter

`\nastavpole [...,1...] [...,2...] [...,3*,...]OPT [...,4*,...]OPT [...,5*,...]OPT`

1 NAME

2 reset popiscek ramecek horizontalne vertikálne

3 inherits: \setupfieldtotalframed

4 inherits: \setupfieldlabelframed

5 inherits: \setupfieldcontentframed

`\nastavpolozky [...,1...] [...,2*,...]OPT`

1 NAME

2 alternativa = vľavo vpravo vrsek spodek naokraji

sirkatextu = DIMENSION

sirka = DIMENSION

vzdalenost = DIMENSION

symbol = zadny NAME

zarovnani = vľavo nastred vpravo flushleft flushright uvnitr vnejsi marginalie

textalign = vľavo nastred vpravo flushleft flushright uvnitr vnejsi

n = NUMMER

pred = BEFEHL

po = BEFEHL

mezi = BEFEHL

`\nastavpopisek [...,1...] [...,2*,...]OPT`

1 NAME

2 inherits: \setupfloatcaption

`\umistifigure [...,1...] [...,2*,...]OPT {...3} {...4}`

1 split vzdy vľavo vpravo uvnitr vnejsi zpetnamezera cutspace ivľavo ivpravo naokraji levyokraj pravyyokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka zahľavi upati nekde effective

2 REFERENCE

3 TEXT

4 CONTENT

`\umistigraphic [...,1...] [...,2*,...]OPT {...3} {...4}`

1 split vzdy vľavo vpravo uvnitr vnejsi zpetnamezera cutspace ivľavo ivpravo naokraji levyokraj pravyyokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka zahľavi upati nekde effective

2 REFERENCE

3 TEXT

4 CONTENT

`\umistichemical [...,1...] [...,2*,...]OPT {...3} {...4}`

1 split vzdy vľavo vpravo uvnitr vnejsi zpetnamezera cutspace ivľavo ivpravo naokraji levyokraj pravyyokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka zahľavi upati nekde effective

2 REFERENCE

3 TEXT

4 CONTENT

`\umistiintermezzo [...,1...] [...,2...] {...} {...}`
OPT OPT

- 1 split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraj levýokraj pravýokraj leváhrana praváhrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka zahlava upati nekde effective
- 2 REFERENCE
- 3 TEXT
- 4 CONTENT

`\umistitable [...,1...] [...,2...] {...} {...}`
OPT OPT

- 1 split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraj levýokraj pravýokraj leváhrana praváhrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka zahlava upati nekde effective
- 2 REFERENCE
- 3 TEXT
- 4 CONTENT

`\nastavpozadi [...,1...] [...,2==...,...]`
OPT

- 1 NAME
- 2 status = start stop
levyoffset = DIMENSION
pravyoffset = DIMENSION
offsetvrsku = DIMENSION
offsetspodku = DIMENSION
pred = BEFEHL
po = BEFEHL
inherits: \nastavoramovani

`\nastavpozadi [...,1...] [...,2==...,...]`
OPT

- 1 papir stranka levastranka pravastranka text skryte
- 2 status = start stop
inherits: \nastavoramovani

`\nastavprechodstrany [...]`

- * reset auto start nahodny NUMMER

`\nastavpreskok [...,*...]`
OPT

- * inherits: \vspacing

`\nastavprogramy [...,*==...,...]`

- * pismo = STYLE BEFEHL
barva = COLOR

`\nastavradkovani [...]`
OPT

- * fixne zhustene siroky

\nastavradky [...¹,...] [...²,...]

OPT

```
1  NAME
2  volba      = zhustene
   pred       = BEFEHL
   po         = BEFEHL
   mezi       = BEFEHL
   odsazovani = inherits: \nastavodsazovani
   zarovnani  = inherits: \nastavzarovnani
   mezera     = ano zap vyp fixne implicitni
   prikaz     = BEFEHL
   pismeno    = STYLE BEFEHL
   barva      = COLOR
   vlevo     = BEFEHL
   vpravo     = BEFEHL
```

\nastavrejstrik [...¹,...] [...²,...]

OPT

```
1  NAME NAME:NUMBER
2  referencemethod      = vpred
   expanzen             = ano ne xml
   vlastnicislo         = ano ne
   xmlsetup             = NAME
   alternativa          = a b A B
   metoda              = implicitni pred po prvni posledni ch mm zm pm mc zc pc uc
   compress             = ano ne vse
   kriterium            = lokalne text aktualni predchozi vse ABSCHNITT
   pageprefixseparatorset = BEFEHL
   pageprefixconversionset = NAME
   pageprefixstarter    = BEFEHL PROCESSOR->BEFEHL
   pageprefixstopper    = BEFEHL PROCESSOR->BEFEHL
   pageprefixset        = NAME
   pageprefixsegments   = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:*
                        ABSCHNITT:vse
   pageprefixconnector  = BEFEHL
   pageprefix           = ano ne
   pageseparatorset     = NAME
   pageconversionset    = NAME
   pagestarter          = BEFEHL PROCESSOR->BEFEHL
   pagestopper          = BEFEHL PROCESSOR->BEFEHL
   pagesegments         = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:vse
   maxsirka             = DIMENSION
   indikator            = ano ne
   pred                 = BEFEHL
   po                   = BEFEHL
   prikaz               = \...##1
   textovyprikaz        = \...##1
   deeptextcommand      = \...##1
   strankovyprikaz      = \...##1
   vzdalenost           = DIMENSION
   interakce            = text cislostranky
   cislostranky         = ano ne
   symbol               = a n zadny 1 2 BEFEHL
   language             = implicitni DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scn SPRACHE
   pismeno              = STYLE BEFEHL
   barva                = COLOR
   styltextu            = STYLE BEFEHL
   barvatextu           = COLOR
   stylstranky          = STYLE BEFEHL
   barvastranky         = COLOR
   n                    = NUMBER
   rovnovaha            = ano ne
   zarovnani            = inherits: \nastavzarovnani
   numberorder          = cisla
```

\nastavrejstrik [...,¹...] [...,²...] [...,³...,...]
OPT OPT

```

1  NAME
2  NUMMER
3  referencemethod      = vpred
   expanzen             = ano ne xml
   vlastnicislo         = ano ne
   xmlsetup             = NAME
   alternativa          = a b A B
   metoda               = implicitni pred po prvni posledni ch mm zm pm mc zc pc uc
   compress             = ano ne vse
   kriterium            = lokalne text aktualni predchozi vse ABSCHNITT
   pageprefixseparatorset = BEFEHL
   pageprefixconversionset = NAME
   pageprefixstarter    = BEFEHL PROCESSOR->BEFEHL
   pageprefixstopper    = BEFEHL PROCESSOR->BEFEHL
   pageprefixset        = NAME
   pageprefixsegments   = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:*
                        ABSCHNITT:vse
   pageprefixconnector  = BEFEHL
   pageprefix           = ano ne
   pageseparatorset     = NAME
   pageconversionset    = NAME
   pagestarter          = BEFEHL PROCESSOR->BEFEHL
   pagestopper          = BEFEHL PROCESSOR->BEFEHL
   pagesegments         = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:vse
   maxsirka             = DIMENSION
   indikator            = ano ne
   pred                 = BEFEHL
   po                   = BEFEHL
   prikaz               = \...##1
   textovyprikaz        = \...##1
   deeptextcommand      = \...##1
   strankovyprikaz      = \...##1
   vzdalenost           = DIMENSION
   interakce            = text cislostranky
   cislostranky         = ano ne
   symbol               = a n zadny 1 2 BEFEHL
   language             = implicitni DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scen SPRACHE
   pismeno              = STYLE BEFEHL
   barva                = COLOR
   styltextu            = STYLE BEFEHL
   barvatextu           = COLOR
   stylstranky          = STYLE BEFEHL
   barvastranky         = COLOR
   n                    = NUMBER
   rovnovaha            = ano ne
   zarovnnani           = inherits: \nastavzarovnnani
   numberorder          = cisla

```

\nastaveniREGISTER [...,¹...] [...,²...,...]
OPT

```

1  NUMMER
2  inherits: \nastavrejstrik

```

instances:

\nastavsadusymbolu [...*]

```
*  NAME
```

\nastavseznam [...,¹...] [...,²...,...]
OPT

```

1  LISTE

2  status          = start stop
   misto           = zadny zde
   typ             = simple prikaz userdata
   kriterium       = lokalne uvod odkaz SECTIONBLOCK:odkaz vse SECTIONBLOCK:vse text SECTIONBLOCK:text
                   aktualni SECTIONBLOCK:aktualni zde predchozi SECTIONBLOCK:predchozi komponenta ABSCHNITT
                   SECTIONBLOCK:ABSCHNITT

   seznam          = NAME
   sirka           = prizpusobive siroky auto DIMENSION
   vyska           = prizpusobive siroky DIMENSION
   hloubka         = prizpusobive siroky DIMENSION
   symbol          = jedna dve tri zadny implicitni
   popisek         = ano ne zadny NAME
   starter         = BEFEHL
   predel          = BEFEHL
   prikaz          = \...#1#2##3
   ciselnyprikaz   = \...#1
   textovyprikaz   = \...#1
   strankovyprikaz = \...#1
   cislostranky    = ano ne vzdy
   cislonadpisu    = ano ne vzdy
   pred            = BEFEHL
   po              = BEFEHL
   mezi           = BEFEHL
   marginalie      = zadny DIMENSION
   vzdalenost      = zadny DIMENSION
   zarovnejtitul   = ano ne
   numberalign     = vlevo vpravo nastred flushleft flushright uvnitr vnejsi
   zarovnnani      = inherits: \nastavzarovnnani
   zaveseni        = ano ne
   vlevo           = BEFEHL
   vpravo          = BEFEHL
   interakce       = ano ne vse cislo text titul stranka cislooddilu cislostranky
   limittext       = ano ne TEXT
   pismeno         = STYLE BEFEHL
   barva           = COLOR
   stylcisla       = STYLE BEFEHL
   barvacisla      = COLOR
   styltextu       = STYLE BEFEHL
   barvatextu      = COLOR
   stylstranky     = STYLE BEFEHL
   barvastranky    = COLOR
   odkaz           = NUMMER
   extras          = NAME
   order           = prikaz vse titul
   alternativa     = a b c d e f g vlevo vpravo vrsek spodek prikaz zadny interactive odstavec horizontalne
                   vertikalne NAME

   maxsirka        = DIMENSION
   pageprefix      = ano ne
   pageprefixseparatorset = NAME
   pageprefixconversionset = NAME
   pageprefixset   = NAME
   pageprefixsegments = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:*
                   ABSCHNITT:vse
   pageprefixconnector = BEFEHL PROCESSOR->BEFEHL
   pageconversionset = NAME
   pagestarter     = BEFEHL PROCESSOR->BEFEHL
   pagestopper     = BEFEHL PROCESSOR->BEFEHL
   inherits: \setupcounterinherits: \nastavoramovani

```

\nastavsirkucary [...]

* male stredni velke DIMENSION

`\nastavsloupce [...,*...]`

```
*  n          = NUMMER
   vzdalenost = DIMENSION
   volba      = pozadi
   offset     = DIMENSION
   prikaz     = \...##1
   vyska      = DIMENSION
   smer       = vlevo vpravo
   rovnovaha  = ano ne
   zarovnani  = setupalign
   tolerance  = setuptolerance
   prazdny    = inherits: \preskoc
   nvrsek     = NUMMER
   linka      = zap vyp BEFEHL
```

`\nastavspodek [...1][...2...]`
OPT

```
1  text marginalie hrana
2  inherits: \setuplayoutelement
```

`\nastavsynonyma [...1...][...2...]`
OPT

```
1  SINGULAR
2  expanzen      = ano ne xml
   alternativa  = prvni posledni normalni NAME
   dalsi        = BEFEHL
   prikaz       = \...##1##2##3
   textovyprikaz = \...##1
   synonymcommand = \...##1
   language     = implicitni DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scen SPRACHE
   metoda       = implicitni pred po prvni posledni ch mm zm pm mc zc pc uc
   kriterium    = aktualni predchozi lokalne text vse ABSCHNITT
   pismeno      = STYLE BEFEHL
   barva        = COLOR
   styltextu    = STYLE BEFEHL
   barvatextu   = COLOR
   stylsynonyma = STYLE BEFEHL
   barvasynonyma = COLOR
```

`\nastavtabelaci [...1][...2][...3...]`
OPT OPT

```
1  NAME
2  NAME
3  inherits: \setuptabulation
```

`\nastavtabulky [...,*...]`

```
*  text          = DIMENSION max
   split         = ano ne opakovat auto
   ramecek       = zap vyp
   NL            = inherits: \preskoc
   VL            = male stredni velke zadny NUMMER
   HL            = male stredni velke zadny NUMMER
   vzdalenost    = male stredni velke zadny
   zarovnani     = vlevo nastred vpravo
   prikazy       = BEFEHL
   zakladnifont  = inherits: \nastavzakladnifont
   tloustkalinky = DIMENSION
   vyska         = strut NUMMER
   hloubka       = strut NUMMER
   openup        = DIMENSION
```


`\nastavtenkelinky [...,*...]`

```
*   vyska           = max DIMENSION
    hloubka         = max DIMENSION
    pozadi          = barevne
    ramecek         = zap vyp
    tloustkalinky   = DIMENSION
    alternativa     = a b c zadny
    barvapozadi     = COLOR
    barva           = COLOR
    meziradkovamezera = male stredni velke NUMMER
    pred            = BEFEHL
    po              = BEFEHL
    mezi           = BEFEHL
    n              = NUMMER
```

`\nastavtext [...]1 [...,2...]`
OPT

```
1   text marginalie hrana
2   inherits: \setuplayoutelement
```

`\nastavtextovetelinky [...,*...]`

```
*   pred            = BEFEHL
    po              = BEFEHL
    mezi           = BEFEHL
    tloustkalinky   = DIMENSION
    misto           = vlevo naokraji
    pismo           = STYLE BEFEHL
    barva           = COLOR
    barvalinky      = COLOR
    sirka           = DIMENSION
    vyska           = DIMENSION
    vzdalenost      = DIMENSION
    korekcehloubky  = zap vyp
    zakladnifont     = inherits: \nastavzakladnifont
```

`\nastaveniLABELtext [...]1 [...,2...]`
OPT

```
1   SPRACHE
2   KEY = VALUE
```

`instances:`

`\nastavtexttety [...]1 [...]2 [...]3 [...]4 [...]5`
OPT OPT OPT OPT OPT

```
1   text marginalie hrana
2   datum cislostranky BESCHRIFTUNG TEXT BEFEHL
3   datum cislostranky BESCHRIFTUNG TEXT BEFEHL
4   datum cislostranky BESCHRIFTUNG TEXT BEFEHL
5   datum cislostranky BESCHRIFTUNG TEXT BEFEHL
```

`\nastavtextyupati [...]1 [...]2 [...]3 [...]4 [...]5`
OPT OPT OPT OPT OPT

```
1   text marginalie hrana
2   datum cislostranky BESCHRIFTUNG TEXT BEFEHL
3   datum cislostranky BESCHRIFTUNG TEXT BEFEHL
4   datum cislostranky BESCHRIFTUNG TEXT BEFEHL
5   datum cislostranky BESCHRIFTUNG TEXT BEFEHL
```

\nastavtextyzahlavi [...] [...] [...] [...] [...]
OPT OPT OPT OPT OPT

1 text marginalie hrana
2 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
3 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
4 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
5 datum cislostranky BESCHRIFTUNG TEXT BEFEHL

\nastavtoleranci [...,*...]

* horizontalne vertikalne velmistriktni striktni tolerantni velmitolerantni mezera natahnout

\nastavtrideni [...,¹...] [...,²...]
OPT

1 SINGULAR
2 expanzen = ano ne xml
alternativa = prvni posledni normalni NAME
dalsi = BEFEHL
prikaz = \...##1##2##3
textovyprikaz = \...##1
synonymcommand = \...##1
language = implicitni DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scn SPRACHE
metoda = implicitni pred po prvni posledni ch mm zm pm mc zc pc uc
kriterium = aktualni predchozi lokalne text vse ABSCHNITT
pismeno = STYLE BEFEHL
barva = COLOR
styltextu = STYLE BEFEHL
barvatextu = COLOR
stylsynonyma = STYLE BEFEHL
barvasynonyma = COLOR

\nastavtype [...,¹...] [...,²...]
OPT

1 NAME
2 volba = mp lua xml parsed-xml nested tex context zadny NAME
prikaz = CSNAME
vlevo = BEFEHL
vpravo = BEFEHL
tab = ano ne NUMMER
compact = absolutni posledni vse
escape = ano ne TEXT PROCESSOR->TEXT
pismeno = STYLE BEFEHL
barva = COLOR
radky = ano ne normalni hyphenated
mezera = zap vyp normalni fixne natahnout

\nastavumisteniprotejsku [...,*...]

* status = start stop
pred = BEFEHL
po = BEFEHL
mezi = BEFEHL

\nastavumistovani [...,¹...] [...,²...]
OPT

1 NAME
2 offset = ano ne
jednotka = ex em pt in cm mm sp bp pc dd cc nc
status = start prekryv
xoffset = DIMENSION
yoffset = DIMENSION
xkrok = absolutni relativni
ykrok = absolutni relativni
xmeritko = NUMMER
ymeritko = NUMMER
xfaktor = NUMMER
yfaktor = NUMMER
faktor = NUMMER
meritko = NUMMER

\nastavupati [...] [...] ¹ ²
OPT

- 1 text marginalie hrana
- 2 inherits: \setuplayoutelement

\nastavupravu [...] ¹ [...] ² [...] ³
OPT

- 1 NAME
- 2 stranka = inherits: \strana
prikaz = BEFEHL
sirka = DIMENSION
vyska = DIMENSION
zarovnani = inherits: \nastavzarovnani
setups = NAME
vrsek = BEFEHL
spodek = BEFEHL
pred = BEFEHL
po = BEFEHL
misto = vrsek
odkaz = REFERENCE
pagestate = start stop
statuszahlavi = start stop vysoko prazdne zadny normalni
statusupati = start stop vysoko prazdne zadny normalni
statusvrsku = start stop vysoko prazdne zadny normalni
statusspodku = start stop vysoko prazdne zadny normalni
statustextu = start stop vysoko prazdne zadny normalni
oboustranne = ano ne prazdne
pismo = inherits: \value-style
barva = COLOR

\nastavurl [...] ^{*} [...] ¹ ²

- * pismo = STYLE BEFEHL
- barva = COLOR

\nastavusporadani [...] ^{*} [...] ¹ ²

- * zablokovat zrcadleno dvoustranny negativ 90 180 270 reset pozadi normalni 2*16 2*8 2*4 2*2 2**2 2SIDE 2TOP 2UP 2DOWN 2*4*2 2*2*4 2TOPSIDE 2*8*Z 2*6*Z 1*8 1*4 3SIDE TRYPTICHON ZFLYER-8 ZFLYER-10 ZFLYER-12 MAPFLYER-12 DOUBLEWINDOW 1*2-Conference 1*4-Conference 2*2*2 2*2*3 XY NAME

\nastavvelikostpapiru [...] ¹ [...] ² [...] ³ ⁴ ⁵
OPT

- 1 NAME
- 2 vrsek = BEFEHL
spodek = BEFEHL
vlevo = BEFEHL
vpravo = BEFEHL
metoda = normalni zadny NAME
meritko = NUMMER
nx = NUMMER
ny = NUMMER
dx = DIMENSION
dy = DIMENSION
sirka = DIMENSION
vyska = DIMENSION
svrchnimezera = DIMENSION
zpetnamezera = DIMENSION
offset = DIMENSION
stranka = reset nasirku zrcadleno negativ otoceno 90 180 270 NAME
papir = reset nasirku zrcadleno negativ otoceno 90 180 270 NAME
volba = prizpusobive max
vzdalenost = DIMENSION

\nastavvelikostpapiru [...] ¹ [...] ² [...] ³ ⁴ ⁵
OPT OPT

- 1 reset nasirku zrcadleno negativ otoceno 90 180 270 NAME
- 2 reset nasirku zrcadleno negativ otoceno 90 180 270 NAME

```

\nastavvsechnapole [...,1...] [...,2...] [...,3...] [...,4...]
                        OPT      OPT      OPT
1  reset popiscek ramecek horizontalne vertikalne
2  inherits: \setupfieldtotalframed
3  inherits: \setupfieldlabelframed
4  inherits: \setupfieldcontentframed

```

```

\nastavvycty [...,1...] [...,2...]
                        OPT
1  NAME NAME:NUMMER
2  inherits: \setupitemgroup

```

```

\nastaveniitemize [...,1...] [...,2...] [...,3...]
                        OPT      OPT      OPT
1  kazdy NUMMER
2  inherits: \setupitemgroup
3  inherits: \setupitemgroup

```

```

\nastavvyplnovelinky [...,*...]

*  pred      = BEFEHL
   po        = BEFEHL
   n         = NUMMER
   meziradkovamezera = male stredni velke NUMMER
   vzdalenost = DIMENSION
   sirka      = prizpusobive siroky DIMENSION
   oddelovac  = BEFEHL
   pismo      = STYLE BEFEHL
   barva      = COLOR

```

```

\nastavvyplnoveradky [...,*...]

*  pred      = BEFEHL
   po        = BEFEHL
   marginalie = DIMENSION
   sirka      = DIMENSION
   vzdalenost = DIMENSION
   tloustkalinky = DIMENSION
   barva      = COLOR

```

\nastavvzhled [¹...] [²..._{OPT}...]

```

1  NAME

2  status           = start stop normalni opakovat
   marginalie       = DIMENSION
   hrana            = DIMENSION
   vzdalenostokraje = DIMENSION
   vzdalenosthrany  = DIMENSION
   vzdalenostlevehrawy = DIMENSION
   vzdalenostpravehrany = DIMENSION
   vzdalenostlevehookraje = DIMENSION
   vzdalenostpravehookraje = DIMENSION
   vzdalenostvrsku  = DIMENSION
   vzdalenostzahlavi = DIMENSION
   vzdalenostupati  = DIMENSION
   vzdalenostspodku = DIMENSION
   prednastaveni    = NAME
   levyokraj        = DIMENSION
   pravyokraj       = DIMENSION
   levahrana        = DIMENSION
   pravahrana       = DIMENSION
   zahlavi         = DIMENSION
   upati            = DIMENSION
   vrsek            = DIMENSION
   spodek           = DIMENSION
   zpetnamezera     = DIMENSION
   svrchnamezera    = DIMENSION
   setups           = NAME
   cutspace         = DIMENSION
   sirka            = DIMENSION nastred prizpusobive
   bottomspace      = DIMENSION
   radky            = NUMBER
   vyska            = DIMENSION nastred prizpusobive
   horoffset        = DIMENSION
   offsethlavicky   = DIMENSION
   sloupce          = NUMBER
   vzdalenostsloupce = DIMENSION
   metoda           = implicitni normalni NAME
   misto            = vlevo nastred vpravo vrsek spodek jednostranne dvoustranny
   sirkatextu       = DIMENSION
   vyskatextu       = DIMENSION
   nx               = NUMBER
   ny               = NUMBER
   dx               = DIMENSION
   dy               = DIMENSION
   meritko          = NUMBER
   sx               = NUMBER
   sy               = NUMBER
   znaceni          = zap vyp stranka prazdne barevne jedna dve ctyri
   mrizka           = ano ne vyp
   textdistance     = DIMENSION
   alternativa      = implicitni normalni zlom NAME
   clipoffset       = DIMENSION
   cropoffset       = DIMENSION
   trimoffset       = DIMENSION
   bleedoffset      = DIMENSION
   artoffset        = DIMENSION

```

\nastavvzhled [...]

* reset NAME

\nastavzahlavi [¹...] [²..._{OPT}...]

```

1  text marginalie hrana

2  inherits: \setuplayoutelement

```

\nastavzakladnifont [..._{OPT}...]

* DIMENSION NAME globalne reset x xx male velke script scriptscript rm ss tt hw cg antikva serif pravidelne sans bezserifu podpora opis strojopis mono rukopisne kaligraficke

`\nastavzarovnnani [...,*,...]`

* široky siroce spodek vyska radek vysoko nizko nivy flushright flushleft nastred ano ne sirka normalni reset uvnitr vnejsi flushinner flushouter vlevo vpravo center zablockovat posledni end odstavec lefttoright righttoleft l2r r2l tabulka lesshyphenation morehyphenation visici nothanging hz fullhz nohz hyphenated nothyphenated tolerantni velmitolerantni natahnout extremestretch finalni 2*final 3*final 4*final

`\nastavznaceni [...,1...] [...,2...,...]`
OPT

1 BESCHRIFTUNG

2 status = start stop
expanden = ano ne
oddelovac = BEFEHL
filtercommand = \...\##1

`\nastavzuzeni [...,1...] [...,2...,...]`
OPT

1 NAME

2 vlevo = DIMENSION
stredni = DIMENSION
vpravo = DIMENSION
implicitni = [-+]vlevo [-+]nastred [-+]vpravo NUMMER*vlevo NUMMER*nastred NUMMER*vpravo reset
pred = BEFEHL
po = BEFEHL

`\nastrane [...]`

* REFERENCE

`\nastred ...`

* CHARACTER

`\naturalhbox ... {1...2}`
OPT

1 TEXT

2 CONTENT

`\naturalhpack ... {1...2}`
OPT

1 TEXT

2 CONTENT

`\naturalvbox ... {1...2}`
OPT

1 TEXT

2 CONTENT

`\naturalvcenter ... {1...2}`
OPT

1 TEXT

2 CONTENT

`\naturalvpack ... {1...2}`
OPT

1 TEXT

2 CONTENT

`\naturalvtop ... {1...2}`
OPT

1 TEXT

2 CONTENT

<p><code>\naturalwd ...</code></p> <p>* CSNAME NUMBER</p>
<p><code>\negatecolorbox ...</code></p> <p>* CSNAME NUMBER</p>
<p><code>\negated {...}</code></p> <p>* TEXT</p>
<p><code>\negthinspace</code></p>
<p><code>\nejakyradek [...]</code></p> <p>* REFERENCE</p>
<p><code>\nekde {...} {...} [...]</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 REFERENCE</p>
<p><code>\newattribute *...</code></p> <p>* CSNAME</p>
<p><code>\newcatcodetable *...</code></p> <p>* CSNAME</p>
<p><code>\newcounter *...</code></p> <p>* CSNAME</p>
<p><code>\newevery \¹... \²...</code></p> <p>1 CSNAME</p> <p>2 CSNAME</p>
<p><code>\newfrenchspacing</code></p>
<p><code>\newmode {...}</code></p> <p>* NAME</p>
<p><code>\newsignal *...</code></p> <p>* CSNAME</p>
<p><code>\newsystemmode {...}</code></p> <p>* NAME</p>
<p><code>\nextbox</code></p>
<p><code>\nextboxdp</code></p>
<p><code>\nextboxht</code></p>

<code>\nextboxhtdp</code>
<code>\nextboxwd</code>
<code>\nextcounter [...]</code> ¹ <code>[...]</code> ² <small>OPT</small> 1 NAME 2 NUMMER
<code>\nextcountervalue [...]</code> * NAME
<code>\nextdepth</code>
<code>\nextparagraphs</code>
<code>\dalsiPARAGRAPHS</code>
<code>\nextrealpage</code>
<code>\nextrealpagenumber</code>
<code>\nextsubcountervalue [...]</code> ¹ <code>[...]</code> ² 1 NAME 2 NUMMER
<code>\nextsubpagenumber</code>
<code>\nextuserpage</code>
<code>\nextuserpagenumber</code>
<code>\neznamo</code>
<code>\nivy [...]</code> ¹ <code>{...}</code> ² <code>{...}</code> ³ <small>OPT</small> 1 vlevo vpravo 2 CONTENT 3 CONTENT
<code>\nizky {...}</code> * CONTENT
<code>\LOW {...}</code> * CONTENT instances:
<code>\nobar {...}</code> * CONTENT

<code>\nocitation [...]</code> * REFERENCE
<code>\nocitation {...}</code> * REFERENCE
<code>\nocite [...]</code> * REFERENCE
<code>\nocite {...}</code> * REFERENCE
<code>\nodetostring \¹... {²...}</code> 1 CSNAME 2 CONTENT
<code>\nofffigurepages</code>
<code>\noflines</code>
<code>\noflocalfloats</code>
<code>\noindentation</code>
<code>\noitem</code>
<code>\nokap {...}</code> * TEXT
<code>\nonfrenchspacing</code>
<code>\nonmathematics {...}</code> * CONTENT
<code>\normalboldface</code>
<code>\normalframedwithsettings [...,¹...²...] {...}</code> 1 inherits: \nastavoramovani 2 CONTENT
<code>\normalizebodyfontsize \¹... {²...}</code> 1 CSNAME 2 DIMENSION
<code>\normalizedfontsize</code>

`\normalizefontdepth \1... {\2...} {\3...} {\4...}`

- 1 CSNAME
- 2 TEXT
- 3 DIMENSION
- 4 FONT

`\normalizefontheight \1... {\2...} {\3...} {\4...}`

- 1 CSNAME
- 2 TEXT
- 3 DIMENSION
- 4 FONT

`\normalizefontline \1... {\2...} {\3...} {\4...}`

- 1 CSNAME
- 2 TEXT
- 3 DIMENSION
- 4 FONT

`\normalizefontwidth \1... {\2...} {\3...} {\4...}`

- 1 CSNAME
- 2 TEXT
- 3 DIMENSION
- 4 FONT

`\normalizetextdepth {\1...} {\2...} {\3...}`

- 1 FONT
- 2 DIMENSION
- 3 TEXT

`\normalizetextheight {\1...} {\2...} {\3...}`

- 1 FONT
- 2 DIMENSION
- 3 TEXT

`\normalizetextline {\1...} {\2...} {\3...}`

- 1 FONT
- 2 DIMENSION
- 3 TEXT

`\normalizetextwidth {\1...} {\2...} {\3...}`

- 1 FONT
- 2 DIMENSION
- 3 TEXT

`\normalni`

`\normaltypeface`

<code>\notesymbol [...]¹ [...]²</code> <div> <div>OPT</div> <div> 1 NAME 2 REFERENCE </div> </div>
<code>\notragged</code>
<code>\ntimes {...}¹ {...}²</code> <div> 1 TEXT 2 NUMMER </div>
<code>\numberofpoints {...}</code> * DIMENSION
<code>\obeydepth</code>
<code>\objectdepth</code>
<code>\objectheight</code>
<code>\objectmargin</code>
<code>\objectwidth</code>
<code>\obox {...}</code> * CONTENT
<code>\obrazovka [...][*] [...]</code> <div> <div>OPT</div> <div> * inherits: \strana </div> </div>
<code>\odkaz [...]¹, [...] {...}²</code> <div> 1 REFERENCE 2 TEXT </div>
<code>\odkaznastranu [...][*], [...]</code> * REFERENCE
<code>\odkaznatext [...]¹, [...] {...}²</code> <div> 1 REFERENCE 2 TEXT </div>
<code>\odkazujici (...)¹, (...) (...)², (...) [...]³</code> <div> 1 POSITION 2 POSITION 3 REFERENCE </div>
<code>\offset [...]¹, [...]², [...] {...}</code> <div> <div>OPT</div> <div> 1 inherits: \setupoffset 2 CONTENT </div> </div>

<p>\offsetbox [...,¹..._{OPT}...] \²... {³...}</p> <p>1 inherits: \setupoffsetbox</p> <p>2 CSNAME</p> <p>3 CONTENT</p>
<p>\onedigitrounding {...}</p> <p>* NUMMER</p>
<p>\opis [...,¹..._{OPT}...] {²...}</p> <p>1 inherits: \nastavtype</p> <p>2 CONTENT</p>
<p>\opissoubor [...¹...] [...,²..._{OPT}...] {³...}</p> <p>1 NAME</p> <p>2 inherits: \nastavopis</p> <p>3 FILE</p>
<p>\opis [...,¹..._{OPT}...] <<²...>></p> <p>1 inherits: \nastavtype</p> <p>2 ANGLES</p>
<p>\OPIS [...,¹..._{OPT}...] {²...}</p> <p>1 inherits: \nastavtype</p> <p>2 CONTENT</p>
<p>\OPIS [...,¹..._{OPT}...] <<²...>></p> <p>1 inherits: \nastavtype</p> <p>2 ANGLES</p>
<p>\oramovani [...,¹..._{OPT}...] {²...}</p> <p>1 inherits: \nastavoramovani</p> <p>2 CONTENT</p>
<p>\FRAMED [...,¹..._{OPT}...] {²...}</p> <p>1 inherits: \nastavoramovani</p> <p>2 CONTENT</p> <p>instances: unframed fitfieldframed</p>
<p>\oramovanytext [...,¹..._{OPT}...] {²...}</p> <p>1 inherits: \setupframedtext</p> <p>2 CONTENT</p>
<p>\ORAMOVANYTEXT [...,¹..._{OPT}...] {²...}</p> <p>1 inherits: \setupframedtext</p> <p>2 CONTENT</p> <p>instances: oramovanytext</p>

<code>\ordinaldaynumber {...}</code> * NUMBER
<code>\ordinalstr {...}</code> * TEXT
<code>\oref [...]</code> * REFERENCE
<code>\orez [...¹...²...] {...}</code> <small>OPT</small> 1 inherits: \nastavorez 2 CONTENT
<code>\ornamenttext [...¹...²...³...] [...⁴...⁵...] {...} {...}</code> <small>OPT</small> 1 alternativa = a b inherits: \setupcollector 2 pismo = STYLE BEFEHL barva = COLOR inherits: \nastavoramovani 3 TEXT 4 CONTENT
<code>\ornamenttext [...¹] {...²} {...³}</code>
1 NAME 2 TEXT 3 CONTENT
<code>\ornamenttext [...¹...²...³...] [...⁴...⁵...] {...} {...}</code> <small>OPT</small> 1 alternativa = a b inherits: \setupplayer 2 inherits: \setuplayeredtext 3 TEXT 4 CONTENT
<code>\ORNAMENT {...¹} {...²}</code>
1 TEXT 2 CONTENT
<code>\otocit [...¹...²...] {...}</code> <small>OPT</small> 1 inherits: \nastavotoceni 2 CONTENT
<code>\outputfilename</code>
<code>\outputstreambox [...]</code> * NAME
<code>\outputstreamcopy [...]</code> * NAME

<code>\outputstreamunvbox [...]</code> * NAME
<code>\outputstreamunvcopy [...]</code> * NAME
<code>\over [...]</code> * REFERENCE
<code>\overbartext {...} {...}</code> 1 TEXT 2 TEXT
<code>\overbarunderbar {...}</code> * TEXT
<code>\overbrace {...}</code> * TEXT
<code>\overbracetext {...} {...}</code> 1 TEXT 2 TEXT
<code>\overbraceunderbrace {...}</code> * TEXT
<code>\overbracket {...}</code> * TEXT
<code>\overbrackettext {...} {...}</code> 1 TEXT 2 TEXT
<code>\overbracketunderbracket {...}</code> * TEXT
<code>\overlaybutton [...]</code> * REFERENCE
<code>\overlaybutton {...}</code> * REFERENCE
<code>\overlaycolor</code>
<code>\overlaydepth</code>
<code>\overlayfigure {...}</code> * FILE

<code>\overlayheight</code>
<code>\overlaylinecolor</code>
<code>\overlaylinewidth</code>
<code>\overlayoffset</code>
<code>\overlayrollbutton [...] [...]</code> 1 REFERENCE 2 REFERENCE
<code>\overlaywidth</code>
<code>\overleftarrow {...}</code> * TEXT
<code>\overleftharpoondown {...}</code> * TEXT
<code>\overleftharpoonup {...}</code> * TEXT
<code>\overleftrightarrow {...}</code> * TEXT
<code>\overloaderror</code>
<code>\overparent {...}</code> * TEXT
<code>\overparenttext {...} {...}</code> 1 TEXT 2 TEXT
<code>\overparentunderparent {...}</code> * TEXT
<code>\overrightarrow {...}</code> * TEXT
<code>\overrightharpoondown {...}</code> * TEXT
<code>\overrightharpoonup {...}</code> * TEXT

$\backslash\text{overset}$ $\{.^1.\} \{.^2.\}$ 1 TEXT 2 TEXT
$\backslash\text{overtwoheadleftarrow}$ $\{.^*\}$ * TEXT
$\backslash\text{overtwoheadrightarrow}$ $\{.^*\}$ * TEXT
$\backslash\text{oznaceni}$ $(.^1,.^2,.^3,.^4)$ $[.^1,.^2,.^3,.^4]$ $\{.^1,.^2,.^3,.^4\}$ 1 POSITION 2 POSITION 3 inherits: $\backslash\text{nastavoramovani}$ 4 TEXT
$\backslash\text{PDFcolor}$ $\{.^*\}$ * NAME
$\backslash\text{PDFETEX}$
$\backslash\text{PDFTEX}$
$\backslash\text{PICTEX}$
$\backslash\text{PicTeX}$
$\backslash\text{PointsToBigPoints}$ $\{.^1.\} \backslash.^2..$ 1 DIMENSION 2 CSNAME
$\backslash\text{PointsToReal}$ $\{.^1.\} \backslash.^2..$ 1 DIMENSION 2 CSNAME
$\backslash\text{PointsToWholeBigPoints}$ $\{.^1.\} \backslash.^2..$ 1 DIMENSION 2 CSNAME
$\backslash\text{PPCHTEX}$
$\backslash\text{PPCHTeX}$
$\backslash\text{PRAGMA}$
$\backslash\text{PtToCm}$ $\{.^*\}$ * DIMENSION

<p><code>\pagearea</code> [¹...] [²...] [³...] <small>OPT OPT</small></p> <p>1 vrsek zahlavi text upati spodek</p> <p>2 text marginalie hrana</p> <p>3 vlevo vpravo lefttext middletext righttext</p>
<p><code>\pagebreak</code> [...,*...] <small>OPT</small></p> <p>* prazdne zahlavi upati dummy ramecek NUMMER +NUMMER implicitni reset zablockovat ano ne zlom prazdny nastaveni vysokapriorita vlevo vpravo sude liche cytrnasobny posledni poslednistrana start stop NAME</p>
<p><code>\pagefigure</code> [¹...] [...,²...,...] <small>OPT OPT</small></p> <p>1 FILE</p> <p>2 inherits: \setupexternalfigure</p>
<p><code>\pagegridspanwidth</code> {...}</p> <p>* NUMMER</p>
<p><code>\pageinjection</code> [¹...] [...,²...,...] <small>OPT OPT</small></p> <p>1 NAME</p> <p>2 KEY = VALUE</p>
<p><code>\pageinjection</code> [...,¹...,...] [...,²...,...] <small>OPT OPT</small></p> <p>1 inherits: \setuppageinjection</p> <p>2 KEY = VALUE</p>
<p><code>\pagestaterealpage</code> {...} {...}</p> <p>1 NAME</p> <p>2 NAME NUMMER</p>
<p><code>\paletsize</code></p>
<p><code>\PARAGRAPHS</code></p>
<p><code>\pdfactualtext</code> {...} {...}</p> <p>1 CONTENT</p> <p>2 TEXT</p>
<p><code>\pdfbackendactualtext</code> {...} {...}</p> <p>1 CONTENT</p> <p>2 TEXT</p>
<p><code>\pdfbackendcurrentresources</code></p>
<p><code>\pdfbackendsetcatalog</code> {...} {...}</p> <p>1 NAME</p> <p>2 TEXT</p>

<p><code>\pdfbackendsetcolorspace {¹.} {².}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsettextgstate {¹.} {².}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetinfo {¹.} {².}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetname {¹.} {².}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetpageattribute {¹.} {².}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetpageresource {¹.} {².}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetpagesattribute {¹.} {².}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetpattern {¹.} {².}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetshade {¹.} {².}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfcolor {[*].}</code></p> <p>* NAME</p>
<p><code>\pdfTeX</code></p>
<p><code>\pdfTeX</code></p>
<p><code>\percent</code></p>
<p><code>\percentdimen {¹.} {².}</code></p> <p>1 DIMENSION CSNAME</p> <p>2 DIMENSION NUMBER</p>

<code>\permitcaretescape</code>
<code>\permitcircumflexescape</code>
<code>\permitspacesbetweengroups</code>
<code>\persiandecimals {...}</code> * NUMMER
<code>\persiannumerals {...}</code> * NUMMER
<code>\phantom {...}</code> * CONTENT
<code>\phantombox [...,..[*]...,...]</code> * sirka = DIMENSION * vyska = DIMENSION * hloubka = DIMENSION
<code>\pickupgroupedcommand {...¹} {...²} {...³}</code> 1 BEFEHL 2 BEFEHL 3 BEFEHL
<code>\pis [...,..¹...,..._{OPT}] {...²}</code> 1 inherits: \nastavtype 2 CONTENT
<code>\pis [...,..¹...,..._{OPT}] <<...²>></code> 1 inherits: \nastavtype 2 ANGLES
<code>\placeattachments</code>
<code>\placebtxrendering [...¹...] [...,..²...,..._{OPT}]</code> 1 NAME 2 inherits: \setupbtxrendering
<code>\placecitation [...]</code> * REFERENCE
<code>\placecomments</code>
<code>\placecurrentformulanumber</code>
<code>\placedbox {...}</code> * CONTENT

`\placefloat` [¹...] [²...,...] [³...,...] {⁴...} {⁵...}
OPT OPT

- 1 SINGULAR
- 2 split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji levyokraj pravyyokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka zahlavi upati nekde effective
- 3 REFERENCE
- 4 TEXT
- 5 CONTENT

`\placefloatwithsetups` [¹...] [²...,...] [³...,...] {⁴...} {⁵...}
OPT OPT

- 1 NAME
- 2 split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji levyokraj pravyyokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka zahlavi upati nekde effective
- 3 REFERENCE
- 4 TEXT
- 5 CONTENT

`\umistiFLOAT` [¹...,...] [²...,...] {³...} {⁴...}
OPT OPT

- 1 split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji levyokraj pravyyokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka zahlavi upati nekde effective
- 2 REFERENCE
- 3 TEXT
- 4 CONTENT

instances: chemical figure table intermezzo graphic

`\placeframed` [¹...] [²...,..._{OPT},...] {³...}

- 1 NAME
- 2 inherits: \nastavoramovani
- 3 CONTENT

`\placeheadnumber` [...]

- * ABSCHNITT

`\placeheadtext` [...]

- * ABSCHNITT

`\placehelp`

`\placeinitial` [¹...] OPT

- * NAME

`\placelayer` [...]

- * NAME

<p>\placelayeredtext [¹...] [²..._{OPT}...] [³..._{OPT}...] {⁴...} {⁵...}</p> <p>1 NAME</p> <p>2 inherits: \setuplayer</p> <p>3 inherits: \setuplayeredtext</p> <p>4 TEXT</p> <p>5 CONTENT</p>
<p>\placelistofFLOATS [[*]..._{OPT}...]</p> <p>* inherits: \nastavseznam</p>
<p>\placelistofpublications [¹...] [²..._{OPT}...]</p> <p>1 NAME</p> <p>2 inherits: \setupbtxrendering</p>
<p>\placelistofsorts [¹...] [²..._{OPT}...]</p> <p>1 SINGULAR</p> <p>2 inherits: \nastavtrideni</p>
<p>\placelistofSORTS [[*]..._{OPT}...]</p> <p>* inherits: \nastavtrideni</p> <p>instances:</p>
<p>\placelistofsynonyms [¹...] [²..._{OPT}...]</p> <p>1 SINGULAR</p> <p>2 inherits: \nastavsynonyma</p>
<p>\placelistofSYNONYMS [[*]..._{OPT}...]</p> <p>* inherits: \nastavsynonyma</p> <p>instances:</p>
<p>\placelocalnotes [¹...] [²..._{OPT}...]</p> <p>1 NAME</p> <p>2 inherits: \setupnote</p>
<p>\placement [¹...] [²..._{OPT}...] {³...}</p> <p>1 NAME</p> <p>2 inherits: \setupplacement</p> <p>3 CONTENT</p>
<p>\PLACEMENT [¹..._{OPT}...] {²...}</p> <p>1 inherits: \setupplacement</p> <p>2 CONTENT</p>
<p>\placenamedfloat [¹...] [²...]</p> <p>1 NAME</p> <p>2 REFERENCE</p>

<p>\placenedformula [...¹,...] {²...}</p> <p style="text-align: center;">OPT</p> <p>1 + - REFERENCE</p> <p>2 TEXT</p>
<p>\placenames [...¹,...] [...²,...] {³...}</p> <p style="text-align: center;">OPT</p> <p>1 NAME</p> <p>2 inherits: \setupnote</p>
<p>\placepagenumber</p>
<p>\placepairedbox [...¹.] [...²,...] {³...} {⁴...}</p> <p style="text-align: center;">OPT</p> <p>1 NAME</p> <p>2 inherits: \setuppairedbox</p> <p>3 CONTENT</p> <p>4 TEXT</p>
<p>\umistiPAIREDBOX [...¹,...] {²...} {³...}</p> <p style="text-align: center;">OPT</p> <p>1 inherits: \setuppairedbox</p> <p>2 CONTENT</p> <p>3 TEXT</p> <p>instances:</p>
<p>\placeparallel [...¹.] [...²,...] [...³,...] {⁴...}</p> <p style="text-align: center;">OPT</p> <p>1 NAME</p> <p>2 NAME</p> <p>3 inherits: \setupparallel</p>
<p>\placerawlist [...¹.] [...²,...] {³...}</p> <p style="text-align: center;">OPT</p> <p>1 LISTE</p> <p>2 inherits: \nastavseznam</p>
<p>\placereadingwindow [...¹.] [...²,...] {³...}</p> <p style="text-align: center;">OPT</p> <p>1 NAME</p> <p>2 NAME</p>
<p>\plnezneni {...}</p> <p>* NAME</p>
<p>\podtrzeni {...}</p> <p>* CONTENT</p>
<p>\podtrzeno {...}</p> <p>* CONTENT</p>
<p>\pole [...¹.] [...²,...] {³...}</p> <p style="text-align: center;">OPT</p> <p>1 NAME</p> <p>2 TEXT</p>

<p><code>\polozka [...[*]...]</code> <small>OPT</small></p> <p>* REFERENCE</p>
<p><code>\polozky [...¹...²...]</code> <code>{...²}</code> <small>OPT</small></p> <p>1 inherits: \nastavpolozky</p> <p>2 TEXT</p>
<p><code>\popattribute \...</code></p> <p>* CSNAME</p>
<p><code>\POPIS [...¹...]</code> <code>{...²}</code> <code>...³</code> <code>\par</code> <small>OPT</small> <small>OPT</small></p> <p>1 REFERENCE</p> <p>2 TEXT</p> <p>3 CONTENT</p>
<p><code>\popmacro \...</code></p> <p>* CSNAME</p>
<p><code>\popmode [...]</code></p> <p>* NAME</p>
<p><code>\POPISEK [...¹...]</code> <code>{...²}</code> <small>OPT</small> <small>OPT</small></p> <p>1 REFERENCE</p> <p>2 TEXT</p>
<p><code>\popsystemmode {...}</code></p> <p>* NAME</p>
<p><code>\porovnejpaletu [...]</code></p> <p>* NAME</p>
<p><code>\porovnejskupinubarev [...]</code></p> <p>* NAME</p>
<p><code>\positionoverlay {...}</code></p> <p>* NAME</p>
<p><code>\positionregionoverlay {...¹} {...²}</code></p> <p>1 NAME</p> <p>2 NAME</p>
<p><code>\poslaednipodstranka</code></p>
<p><code>\postponenotes</code></p>
<p><code>\pozadi {...}</code></p> <p>* CONTENT</p>

<p><code>\POZADI {...}</code></p> <p>* CONTENT</p> <p>instances: pozadi</p>
<p><code>\pozice [...,¹...,²...] (...²,...) {...³}</code></p> <p><small>OPT</small></p> <p>1 inherits: \nastavumistovani</p> <p>2 POSITION</p> <p>3 CONTENT</p>
<p><code>\poznamka [...¹] [...²]</code></p> <p><small>OPT</small></p> <p>1 NAME</p> <p>2 REFERENCE</p>
<p><code>\NOTE [...¹,...] {...²}</code></p> <p><small>OPT</small></p> <p>1 REFERENCE</p> <p>2 TEXT</p> <p>instances:</p>
<p><code>\NOTE [...,[*]...,...]</code></p> <p>* titul = TEXT</p> <p> zalozka = TEXT</p> <p> seznam = TEXT</p> <p> odkaz = REFERENCE</p> <p>instances:</p>
<p><code>\pravidelne</code></p>
<p><code>\predefinedfont [...]</code></p> <p>* FONT</p>
<p><code>\predefinefont [...¹] [...²]</code></p> <p>1 NAME</p> <p>2 FONT</p>
<p><code>\predefinesymbol [...]</code></p> <p>* NAME</p>
<p><code>\pref {...¹} {...²} [...³]</code></p> <p><small>OPT OPT</small></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 REFERENCE</p>
<p><code>\prefixedpagenumber</code></p>
<p><code>\prelozit [...,[*]...,...]</code></p> <p><small>OPT</small></p> <p>* SPRACHE = TEXT</p>

<pre>\prependetoks ... \to \...</pre> <pre>1 BEFEHL</pre> <pre>2 CSNAME</pre>
<pre>\prependgvalue {...} {...}</pre> <pre>1 NAME</pre> <pre>2 BEFEHL</pre>
<pre>\prependtocommalist {...} \...</pre> <pre>1 TEXT</pre> <pre>2 CSNAME</pre>
<pre>\prependtoks ... \to \...</pre> <pre>1 BEFEHL</pre> <pre>2 CSNAME</pre>
<pre>\prependtoksonce ... \to \...</pre> <pre>1 BEFEHL</pre> <pre>2 CSNAME</pre>
<pre>\prependvalue {...} {...}</pre> <pre>1 NAME</pre> <pre>2 BEFEHL</pre>
<pre>\prepninazakladnifont [...*,...]</pre> <pre>* inherits: \nastavzakladnifont</pre>
<pre>\presetdocument [...,*...,...]</pre> <pre>* inherits: \setupdocument</pre>
<pre>\presetfieldsymbols [...*,...]</pre> <pre>* NAME</pre>
<pre>\presetLABELtext [...]_{OPT} [...,*...,...]</pre> <pre>1 SPRACHE</pre> <pre>2 KEY = VALUE</pre> <p>instances:</p>
<pre>\preskoc [...*,...]_{OPT}</pre> <pre>* inherits: \vspacing</pre>
<pre>\preskrtnuti {...}</pre> <pre>* CONTENT</pre>
<pre>\preskrtnuto {...}</pre> <pre>* CONTENT</pre>

<pre>\pretocommalist {...} \²...</pre> <pre>1 TEXT</pre> <pre>2 CSNAME</pre>
<pre>\prevcounter [...]²...</pre> <pre>1 NAME</pre> <pre>2 NUMMER</pre>
<pre>\prevcountervalue [...]</pre> <pre>* NAME</pre>
<pre>\preventmode [...]*...</pre> <pre>* NAME</pre>
<pre>\prevrealpage</pre>
<pre>\prevrealpagenumber</pre>
<pre>\prevsubcountervalue [...]¹ [...]²...</pre> <pre>1 NAME</pre> <pre>2 NUMMER</pre>
<pre>\prevsubpage</pre>
<pre>\prevsubpagenumber</pre>
<pre>\prevuserpage</pre>
<pre>\prevuserpagenumber</pre>
<pre>\prizpusobivepole [...]¹ [...,...²...,...]</pre> <pre>1 NAME</pre> <pre>2 inherits: \setupfieldbody</pre>
<pre>\prizpusobvzhled [...]¹ [...,...²...,...]</pre> <pre>1 NUMMER</pre> <pre>2 vyska = max DIMENSION</pre> <pre>radky = NUMMER</pre>
<pre>\procent</pre>
<pre>\processaction [...]¹ [...,...²=>...,...]</pre> <pre>1 BEFEHL</pre> <pre>2 APPLY</pre>
<pre>\processallactionsinset [...]¹ [...,...²=>...,...]</pre> <pre>1 BEFEHL</pre> <pre>2 APPLY</pre>

<p><code>\processassignlist [...,¹...] \²...</code></p> <p>1 TEXT</p> <p>2 CSNAME</p>
<p><code>\processassignmentcommand [...,¹...] \²...</code></p> <p>1 KEY = VALUE</p> <p>2 CSNAME</p>
<p><code>\processassignmentlist [...,¹...] \²...</code></p> <p>1 KEY = VALUE</p> <p>2 CSNAME</p>
<p><code>\processbetween {...} \²...</code></p> <p>1 NAME</p> <p>2 CSNAME</p>
<p><code>\processbodyfontenvironmentlist *...</code></p> <p>* CSNAME</p>
<p><code>\processcolorcomponents {...}</code></p> <p>* COLOR</p>
<p><code>\processcommacommand [...,¹...] \²...</code></p> <p>1 BEFEHL</p> <p>2 CSNAME</p>
<p><code>\processcommalist [...,¹...] \²...</code></p> <p>1 BEFEHL</p> <p>2 CSNAME</p>
<p><code>\processcommalistwithparameters [...,¹...] \²...</code></p> <p>1 BEFEHL</p> <p>2 CSNAME</p>
<p><code>\processcontent {...} \²...</code></p> <p>1 NAME</p> <p>2 CSNAME</p>
<p><code>\processfile {...}</code></p> <p>* FILE</p>
<p><code>\processfilemany {...}</code></p> <p>* FILE</p>
<p><code>\processfilenone {...}</code></p> <p>* FILE</p>

<pre>\processfileonce {...}</pre> <pre>* FILE</pre>
<pre>\processfirstactioninset [...]¹ [...,...=>...]²</pre> <pre>1 BEFEHL</pre> <pre>2 APPLY</pre>
<pre>\processisolatedchars {...}¹ \...²</pre> <pre>1 TEXT</pre> <pre>2 CSNAME</pre>
<pre>\processisolatedwords {...}¹ \...²</pre> <pre>1 TEXT</pre> <pre>2 CSNAME</pre>
<pre>\processlinetablebuffer [...][*]</pre> <p style="text-align: center;">OPT</p> <pre>* BUFFER</pre>
<pre>\processlinetablefile {...}[*]</pre> <pre>* FILE</pre>
<pre>\processlist {...}¹ {...}² {...}³ \...⁴</pre> <pre>1 CHARACTER</pre> <pre>2 CHARACTER</pre> <pre>3 TEXT</pre> <pre>4 CSNAME</pre>
<pre>\processMPbuffer [...][*]...]^{OPT}</pre> <pre>* NAME</pre>
<pre>\processMPfigurefile {...}[*]</pre> <pre>* FILE</pre>
<pre>\processmonth {...}¹ {...}² {...}³</pre> <pre>1 NUMMER</pre> <pre>2 NUMMER</pre> <pre>3 BEFEHL</pre>
<pre>\processranges [...]¹,...]² \...</pre> <pre>1 NUMMER NUMMER:NUMMER</pre> <pre>2 CSNAME</pre>
<pre>\processseparatedlist [...]¹ [...]² {...}³</pre> <pre>1 TEXT</pre> <pre>2 TEXT</pre> <pre>3 CSNAME BEFEHL</pre>

<p><code>\processTEXbuffer [...]</code> <small>OPT</small></p> <p>* BUFFER</p>
<p><code>\processtokens {...} {...} {...} {...} {...}</code></p> <p>1 BEFEHL 2 BEFEHL 3 BEFEHL 4 BEFEHL 5 TEXT</p>
<p><code>\processuntil \...</code></p> <p>* CSNAME</p>
<p><code>\processxtablebuffer [...]</code> <small>OPT</small></p> <p>* NAME</p>
<p><code>\processyear {...} {...} {...} {...}</code></p> <p>1 NUMMER 2 BEFEHL 3 BEFEHL 4 BEFEHL</p>
<p><code>\produkt [...]</code></p> <p>* FILE</p>
<p><code>\produkt ...</code></p> <p>* FILE</p>
<p><code>\profiledbox [...]_{OPT} [...,_{OPT}..._{OPT}...] {...}</code></p> <p>1 zadny fixne striktni halffixed quarterfixed eightsfixed NAME 2 inherits: \setupprofile 3 CONTENT</p>
<p><code>\profilegivenbox {...}_{OPT} ..._{OPT}</code></p> <p>1 zadny fixne striktni halffixed quarterfixed eightsfixed NAME 2 CSNAME NUMMER</p>
<p><code>\program [...]</code></p> <p>* NAME</p>
<p><code>\projekt [...]</code></p> <p>* FILE</p>
<p><code>\projekt ...</code></p> <p>* FILE</p>

<p><code>\prostredi [...]</code></p> <p>* FILE</p>
<p><code>\prostredi ...</code></p> <p>* FILE</p>
<p><code>\prvnipodstranka</code></p>
<p><code>\pseudoMixedCapped {...}</code></p> <p>* TEXT</p>
<p><code>\pseudoSmallCapped {...}</code></p> <p>* TEXT</p>
<p><code>\pseudoSmallcapped {...}</code></p> <p>* TEXT</p>
<p><code>\pseudosmallcapped {...}</code></p> <p>* TEXT</p>
<p><code>\purenumber {...}</code></p> <p>* NUMMER</p>
<p><code>\pusharrangedpages ... \poparrangedpages</code></p>
<p><code>\pushattribute \...</code></p> <p>* CSNAME</p>
<p><code>\pushbar [...] ... \popbar</code></p> <p>* NAME</p>
<p><code>\pushbarva [...] ... \popbarva</code></p> <p>* COLOR</p>
<p><code>\pushbutton [.¹...] [.²...]</code></p> <p>1 NAME</p> <p>2 REFERENCE</p>
<p><code>\pushcatcodetable ... \popcatcodetable</code></p>
<p><code>\pushendofline ... \popendofline</code></p>
<p><code>\pushindentation ... \popindentation</code></p>
<p><code>\pushMPdrawing ... \popMPdrawing</code></p>
<p><code>\pushmacro \...</code></p> <p>* CSNAME</p>

<code>\pushmathstyle ... \popmathstyle</code>
<code>\pushmode [...]</code> <code>* NAME</code>
<code>\pushoutputstream [...]</code> <small>OPT</small> <code>* NAME</code>
<code>\pushpath [...]</code> ... <code>\poppath</code> <code>* PATH</code>
<code>\pushpozadi [...]</code> ... <code>\poppozadi</code> <code>* NAME</code>
<code>\pushpunctuation ... \poppunctuation</code>
<code>\pushrandomseed ... \poprandomseed</code>
<code>\pushreferenceprefix {...}</code> ... <code>\popreferenceprefix</code> <code>* + - TEXT</code>
<code>\pushsystemmode {...}</code> <code>* NAME</code>
<code>\qqquad</code>
<code>\quad</code>
<code>\quads [...]</code> <small>OPT</small> <code>* NUMMER</code>
<code>\quitcommalist</code>
<code>\quitprevcommalist</code>
<code>\quittypescriptscanning</code>
<code>\ReadFile {...}</code> <code>* FILE</code>
<code>\Rimskecislice {...}</code> <code>* NUMMER</code>
<code>\radek {...}</code> <code>* CONTENT</code>
<code>\raggedbottom</code>
<code>\raggedcenter</code>

<code>\raggedleft</code>
<code>\raggedright</code>
<code>\raggedwidecenter</code>
<code>\raisebox {¹.} \²... {³.}</code> 1 DIMENSION 2 CSNAME 3 CONTENT
<code>\randomizetext {[*].}</code> * TEXT
<code>\randomnumber {¹.} {².}</code> 1 NUMMER 2 NUMMER
<code>\rawcounter [¹.] [².]</code> <div style="text-align: center;"><small>OPT</small></div> 1 NAME 2 NUMMER
<code>\rawcountervalue [[*].]</code> * NAME
<code>\rawdate [...,[*]...]</code> * inherits: \aktualnidatum
<code>\rawdoifelseinset {¹.} {...,²...} {³.} {⁴.}</code> 1 CONTENT 2 CONTENT 4 TRUE 5 FALSE
<code>\rawdoifinset {¹.} {...,²...} {³.}</code> 1 CONTENT 2 CONTENT 4 TRUE
<code>\rawdoifinsetelse {¹.} {...,²...} {³.} {⁴.}</code> 1 CONTENT 2 CONTENT 4 TRUE 5 FALSE

\rawgetparameters [...]¹ [...,...²...,...]

- 1 TEXT
- 2 KEY = VALUE

\rawprocessaction [...]¹ [...,...²=>...,...]

- 1 BEFEHL
- 2 APPLY

\rawprocesscommacommand [...]¹,... \...²...

- 1 BEFEHL
- 2 CSNAME

\rawprocesscommalist [...]¹,... \...²...

- 1 BEFEHL
- 2 CSNAME

\rawstructurelistuservariable {...}

- * KEY

\rawsubcountervalue [...]¹ [...]²

- 1 NAME
- 2 NUMMER

\rbox ...¹ {...}²
OPT

- 1 TEXT
- 2 CONTENT

\readfile {...}¹ {...}² {...}³

- 1 FILE
- 2 TRUE
- 3 FALSE

\readfixfile {...}¹ {...}² {...}³ {...}⁴

- 1 PATH
- 2 FILE
- 3 TRUE
- 4 FALSE

\readjobfile {...}¹ {...}² {...}³

- 1 FILE
- 2 TRUE
- 3 FALSE

\readlocfile {...}¹ {...}² {...}³

- 1 FILE
- 2 TRUE
- 3 FALSE

<code>\readsetfile {¹...} {²...} {³...} {⁴...}</code> 1 PATH 2 FILE 3 TRUE 4 FALSE
<code>\readsysfile {¹...} {²...} {³...}</code> 1 FILE 2 TRUE 3 FALSE
<code>\readtexfile {¹...} {²...} {³...}</code> 1 FILE 2 TRUE 3 FALSE
<code>\readxmlfile {¹...} {²...} {³...}</code> 1 FILE 2 TRUE 3 FALSE
<code>\realpagenumber</code>
<code>\realSmallCapped {[*]...}</code> * TEXT
<code>\realSmallcapped {[*]...}</code> * TEXT
<code>\realsmallcapped {[*]...}</code> * TEXT
<code>\recursedepth</code>
<code>\recurselevel</code>
<code>\recursestring</code>
<code>\redoconvertfont</code>
<code>\ref [¹...] [²...]</code> 1 implicitni text titul cislo stranka realpage 2 REFERENCE
<code>\REFERENCEFORMAT {¹...} {²...} [³...]</code> <div style="display: flex; justify-content: space-around; width: 100%;"> OPT OPT </div> 1 TEXT 2 TEXT 3 REFERENCE

<code>\referenceprefix</code>
<code>\registerattachment [...]¹ [...,...²...,...]</code> 1 NAME 2 inherits: \setupattachment
<code>\registerctxluafile {...}¹ {...}²</code> 1 FILE 2 NUMMER
<code>\registerexternalfigure [...]¹ [...]² [...,...³...,...]</code> <small>OPT OPT</small> 1 FILE 2 NAME 3 inherits: \setupexternalfigure
<code>\registerfontclass {...}[*]</code> * NAME
<code>\registerhyphenationexception [...]¹ [...]²</code> <small>OPT</small> 1 SPRACHE 2 TEXT
<code>\registerhyphenationpattern [...]¹ [...]²</code> <small>OPT</small> 1 SPRACHE 2 TEXT
<code>\registermenubuttons [...]¹ [...]²</code> 1 NAME 2 TEXT
<code>\registersort [...]¹ [...]²</code> 1 SINGULAR 2 NAME
<code>\registersynonym [...]¹ [...]²</code> 1 SINGULAR 2 NAME
<code>\registerunit [...]¹ [...,...²...,...]</code> <small>OPT</small> 1 prefix jednotka operator suffixe symbol packaged 2 KEY = VALUE
<code>\REGISTER [...]¹ [...+...+...]²</code> <small>OPT</small> 1 TEXT PROCESSOR->TEXT 2 INDEX instances:

\REGISTER [¹ ...] { ² ...} [... ³ ...+...] <div>OPT</div> 1 TEXT PROCESSOR->TEXT 2 TEXT 3 INDEX instances:
\relatemarking [¹ ...] [² ...] 1 BESCHRIFTUNG 2 BESCHRIFTUNG
\relateparameterhandlers { ¹ ...} { ² ...} { ³ ...} { ⁴ ...} 1 NAME 2 NAME 3 NAME 4 NAME
\relaxvalueifundefined {.*...} * NAME
\remainingcharacters
\removebottomthings
\removedepth
\removefromcommalist { ¹ ...} \ ² ... 1 TEXT 2 CSNAME
\removelastskip
\removelastspace
\removemarkedcontent [.*...] * NAME
\removepunctuation
\removesubstring ¹ ... \from ² ... \to \ ³ ... 1 TEXT 2 TEXT 3 CSNAME
\removetoks ¹ ... \from \ ² ... 1 BEFEHL 2 CSNAME
\removeunwantedspaces

<pre>\replacefeature [...]</pre> <pre>* NAME</pre>
<pre>\replacefeature {...}</pre> <pre>* NAME</pre>
<pre>\replaceincommalist \.^{.2.} {...}</pre> <pre>1 CSNAME</pre> <pre>2 NUMMER</pre>
<pre>\replaceword [.^{.1.}] [.^{.2.}] [.^{.3.}]</pre> <pre>1 NAME</pre> <pre>2 TEXT</pre> <pre>3 TEXT</pre>
<pre>\rescan {...}</pre> <pre>* CONTENT</pre>
<pre>\rescanwithsetup {...} {...}</pre> <pre>1 NAME</pre> <pre>2 CONTENT</pre>
<pre>\resetallattributes</pre>
<pre>\resetandaddfeature [...]</pre> <pre>* NAME</pre>
<pre>\resetandaddfeature {...}</pre> <pre>* NAME</pre>
<pre>\resetbar</pre>
<pre>\resetbreakpoints</pre>
<pre>\resetbuffer [...]</pre> <pre>* BUFFER</pre>
<pre>\resetcollector [...]</pre> <pre>* NAME</pre>
<pre>\resetcounter [.^{.1.}] [.^{.2.}]</pre> <div>OPT</div> <pre>1 NAME</pre> <pre>2 NUMMER</pre>
<pre>\resetdigitsmanipulation</pre>
<pre>\resetdirection</pre>

<code>\resetfeature</code>
<code>\resetflag {...}</code> * NAME
<code>\resetfontcolorscheme</code>
<code>\resetfontfallback [...] [¹...] [²...]</code> <small> OPT</small> 1 NAME 2 FONT
<code>\resetfontsolution</code>
<code>\resethyphenationfeatures</code>
<code>\resetcharacteralign</code>
<code>\resetcharacterkerning</code>
<code>\resetcharacterspacing</code>
<code>\resetcharacterstripping</code>
<code>\resetinjector [...]</code> * NAME
<code>\resetinteractionmenu [...]</code> * NAME
<code>\resetitaliccorrection</code>
<code>\resetlayer [...]</code> * NAME
<code>\resetlocalfloats</code>
<code>\resetMPdrawing</code>
<code>\resetMPenvironment</code>
<code>\resetMPinstance [...]</code> * NAME
<code>\resetmarker [...]</code> * NAME
<code>\resetmode {...}</code> * NAME

<code>\resetpagenumber</code>
<code>\resetparallel [...]¹ [...,²...]</code> <small>OPT</small> 1 NAME 2 NAME vse
<code>\resetpath</code>
<code>\resetpenalties \...</code> * CSNAME
<code>\resetprofile</code>
<code>\resetreference [...]</code> * NAME
<code>\resetreplacement</code>
<code>\resetscript</code>
<code>\resetsetups [...]</code> * NAME
<code>\resetshownsynonyms [...]</code> * SINGULAR
<code>\resetsubpagenumber</code>
<code>\resetsymbolset</code>
<code>\resetssystemmode {...}</code> * NAME
<code>\resettimer</code>
<code>\resettrackers</code>
<code>\resettrialtypesetting</code>
<code>\resetusedsortings [...]</code> * SINGULAR
<code>\resetusedsynonyms [...]</code> * SINGULAR
<code>\resetuserpagenumber</code>
<code>\resetvalue {...}</code> * NAME

<code>\resetvisualizers</code>
<code>\resetznaceni [...]</code> * BESCHRIFTUNG
<code>\reshapebox {...}</code> * BEFEHL
<code>\restartcounter [...]</code> <small>¹</small> <small>²</small> <small>³</small> <small>OPT</small> 1 NAME 2 NUMMER 3 NUMMER
<code>\restorebox {...}</code> <small>¹</small> <small>²</small> 1 NAME 2 NAME
<code>\restorecatcodes</code>
<code>\restorecounter [...]</code> * NAME
<code>\restorecurrentattributes {...}</code> * NAME
<code>\restoreendofline</code>
<code>\restoreglobalbodyfont</code>
<code>\reusableMPgraphic {...}</code> <small>¹</small> <small>²</small> <small>OPT</small> 1 NAME 2 KEY = VALUE
<code>\reuseMPgraphic {...}</code> <small>¹</small> <small>²</small> <small>OPT</small> 1 NAME 2 KEY = VALUE
<code>\reuserandomseed</code>
<code>\revivefeature</code>
<code>\rfence {...}</code> * CHARACTER
<code>\rhbox {...}</code> * CONTENT

$\backslash\text{rightbottombox } \{...\}$ * CONTENT
$\backslash\text{rightbox } \{...\}$ * CONTENT
$\backslash\text{righthbox } \{...\}$ * CONTENT
$\backslash\text{rightLABELtext } \{...\}$ * KEY instances:
$\backslash\text{rightline } \{...\}$ * CONTENT
$\backslash\text{rightorleftpageaction } \{...\}^1 \{...\}^2$ 1 BEFEHL 2 BEFEHL
$\backslash\text{rightskipadaption}$
$\backslash\text{rightsubguillemot}$
$\backslash\text{righttopleft}$
$\backslash\text{righttopleftthbox } \dots^1 \{...\}^2$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{righttoplefttvbox } \dots^1 \{...\}^2$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{righttopleftvtop } \dots^1 \{...\}^2$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{righttopbox } \{...\}$ * CONTENT
$\backslash\text{rimskecislice } \{...\}$ * NUMMER
$\backslash\text{rlap } \{...\}$ * CONTENT

<code>\robustaddtocommalist {...} \²...</code> 1 TEXT 2 CSNAME
<code>\robustdoifelseinset {...,¹...} {...,²...} {...} {...⁴}</code> 2 CONTENT 3 CONTENT 5 TRUE 6 FALSE
<code>\robustdoifinsetelse {...,¹...} {...,²...} {...} {...⁴}</code> 2 CONTENT 3 CONTENT 5 TRUE 6 FALSE
<code>\robustpretocommalist {...} \²...</code> 1 TEXT 2 CSNAME
<code>\rollbutton [...,¹...²...³] ... [...]</code> 1 inherits: \setupbutton 2 TEXT 3 REFERENCE
<code>\rollbutton [...¹] [...,²...³...⁴] ... [...]</code> <div style="display: flex; justify-content: space-around; width: 100%;"> <div><small>OPT</small></div> <div><small>OPT</small></div> </div> 1 NAME 2 inherits: \nastavinterakcnimenu 3 TEXT 4 REFERENCE
<code>\rovnice [...,¹...²...] {...}</code> <div style="display: flex; justify-content: space-around; width: 100%;"> <div><small>OPT</small></div> </div> 1 zhustene tight nastred ramecek inherits: \nastavzakladnifont 2 CONTENT
<code>\rozdelplvouciobjekt [...,¹...²...³...] {...} {...}</code> <div style="display: flex; justify-content: space-around; width: 100%;"> <div><small>OPT</small></div> </div> 1 inherits: \nastavdeleniplvoucichobjektu 2 BEFEHL 3 CONTENT
<code>\roztazene [...,¹...²...³...] {...}</code> <div style="display: flex; justify-content: space-around; width: 100%;"> <div><small>OPT</small></div> </div> 1 inherits: \setupstretched 2 TEXT

$\backslash\text{rtop} \overset{1}{...} \{\overset{2}{...}\}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{rukopisne}$
$\backslash\text{ruledhbox} \overset{1}{...} \{\overset{2}{...}\}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{ruledhpack} \overset{1}{...} \{\overset{2}{...}\}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{ruledmbox} \{\dots\}$ * CONTENT
$\backslash\text{ruledtopv} \overset{1}{...} \{\overset{2}{...}\}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{ruledtpack} \overset{1}{...} \{\overset{2}{...}\}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{ruledvbox} \overset{1}{...} \{\overset{2}{...}\}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{ruledvpack} \overset{1}{...} \{\overset{2}{...}\}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{ruledvtop} \overset{1}{...} \{\overset{2}{...}\}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{runMPbuffer} [\overset{*}{...}, \dots]$ <small>OPT</small> * NAME
$\backslash\text{runninghbox} \{\dots\}$ * CONTENT
$\backslash\text{ScaledPointsToBigPoints} \{\overset{1}{...}\} \backslash\overset{2}{...}$ 1 DIMENSION 2 CSNAME

<p><code>\ScaledPointsToWholeBigPoints {¹...} \²...</code></p> <p>1 DIMENSION</p> <p>2 CSNAME</p>
<p><code>\SLOVA {...}</code></p> <p>* TEXT</p>
<p><code>\SLOVO {...}</code></p> <p>* TEXT</p>
<p><code>\Slova {...}</code></p> <p>* TEXT</p>
<p><code>\Slovo {...}</code></p> <p>* TEXT</p>
<p><code>\Smallcapped {...}</code></p> <p>* TEXT</p>
<p><code>\safechar {...}</code></p> <p>* NUMMER</p>
<p><code>\sans</code></p>
<p><code>\sansnormal</code></p>
<p><code>\sanstucne</code></p>
<p><code>\savebarva ... \restorebarva</code></p>
<p><code>\savebox {¹...} {²...} {³...}</code></p> <p>1 NAME</p> <p>2 NAME</p> <p>3 CONTENT</p>
<p><code>\savebtxdataset [_{OPT}¹...] [_{OPT}²...] [_{OPT}³...,...³...,...]</code></p> <p>1 NAME</p> <p>2 FILE</p> <p>3 dataset = NAME</p> <p> typ = bib lua xml</p> <p> soubor = FILE</p> <p> kritérium = vse text uvod odkaz aktualni zde predchozi lokalne komponenta SECTIONBLOCK:vse SECTIONBLOCK:odkaz SECTIONBLOCK:aktualni SECTIONBLOCK:predchozi</p>
<p><code>\savebuffer [...,*...,...]</code></p> <p>* seznam = NAME</p> <p> soubor = FILE</p> <p> prefix = ano ne</p>

\savebuffer [...¹,...] [...²]

- 1 BUFFER
- 2 FILE

\savecounter [...]

- * NAME

\savecurrentattributes {...}

- * NAME

\savenormalmeaning *..

- * CSNAME

\savetaggedtwopassdata {...¹} {...²} {...³} {...⁴}

- 1 NAME
- 2 NUMMER
- 3 NAME
- 4 CONTENT

\savetwopassdata {...¹} {...²} {...³}

- 1 NAME
- 2 NUMMER
- 3 CONTENT

\sbox {...}

- * CONTENT

\SCRIPT

instances:

\secondoffivearguments {...¹} {...²} {...³} {...⁴} {...⁵}

- 1 TEXT
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT

\secondoffourarguments {...¹} {...²} {...³} {...⁴}

- 1 TEXT
- 2 TEXT
- 3 TEXT
- 4 TEXT

`\secondofsixarguments {...} {...} {...} {...} {...} {...}`

- 1 TEXT
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT
- 6 TEXT

`\secondofthreearguments {...} {...} {...}`

- 1 TEXT
- 2 TEXT
- 3 TEXT

`\secondofthreeunexpanded {...} {...} {...}`

- 1 TEXT
- 2 TEXT
- 3 TEXT

`\secondoftwoarguments {...} {...}`

- 1 TEXT
- 2 TEXT

`\secondoftwounexpanded {...} {...}`

- 1 TEXT
- 2 TEXT

`\sedabarva [...] {...}`

- 1 COLOR
- 2 CONTENT

`\vizREGISTER [...] [...] {...}`
OPT

- 1 TEXT PROCESSOR->TEXT
- 2 INDEX
- 3 TEXT PROCESSOR->TEXT

instances:

`\SECTION [...] [...] {...}`
OPT

- 1 REFERENCE
- 2 TEXT

instances: chapter section subsection subsubsection subsubsubsection subsubsubsubsection
title subject subsubject subsubsubject subsubsubsubject subsubsubsubsubject

```
*      titul      = TEXT
      zalozka    = TEXT
      znaceni     = TEXT
      seznam     = TEXT
      odkaz      = REFERENCE
      vlastnicislo = TEXT
```

1	REFERENCE
2	NUMMER
3	TEXT

1	NAME
2	CONTENT
3	CONTENT
4	CONTENT
5	CONTENT
6	CONTENT

* BEFEHL

```
\serializedcommalist
```

\serif

\serifbold

\serifnormal

* NAME

\setbigbodyfont

```
1 CSNAME NUMBER
2 DIMENSION
```

```
1 CSNAME NUMMER
2 DIMENSION
```

\setbreakpoints [...] * reset NAME
\setbuffer [...] ... \endbuffer * NAME
\setcapstrut
\setcatcodetable *... * CSNAME
\setcollector [. ¹ .] [..., ² ... _{OPT} ,...] {. ³ .} 1 NAME 2 inherits: \setupcollector 3 CONTENT
\setcolormodel1 [...] * black bw seda rgb cmyk vse zadny
\setcounter [. ¹ .] [... _{OPT} , ² .] [... ³ .] 1 NAME 2 NUMMER 3 NUMMER
\setcounterown [. ¹ .] [... _{OPT} , ² .] [... ³ .] 1 NAME 2 NUMMER 3 TEXT
\setcurrentfontclass {.*} * NAME
\setdataset [. ¹ .] [... _{OPT} , ² .] [..., ³ ... _{OPT} ,...] 1 NAME 2 NAME 3 KEY = VALUE
\setdefaultpenalties
\setdigitsmanipulation [...] * reset NUMMER
\setdirection [...] * NUMMER
\setdocumentargument {. ¹ .} {. ² .} 1 NAME 2 TEXT

<pre>\setdocumentargumentdefault {...} {...}</pre> <p>1 NAME</p> <p>2 TEXT</p>
<pre>\setdocumentfilename {...} {...}</pre> <p>1 NUMMER</p> <p>2 TEXT</p>
<pre>\setdummyparameter {...} {...}</pre> <p>1 KEY</p> <p>2 BEFEHL</p>
<pre>\setelementexporttag [...] [...] [...] OPT</pre> <p>1 NAME</p> <p>2 export nature pdf</p> <p>3 inline obrazovka mixed</p>
<pre>\setemeasure {...} {...}</pre> <p>1 NAME</p> <p>2 DIMENSION</p>
<pre>\setevalue {...} {...}</pre> <p>1 NAME</p> <p>2 CONTENT</p>
<pre>\setevariable {...} {...} {...}</pre> <p>1 NAME</p> <p>2 KEY</p> <p>3 VALUE</p>
<pre>\setevariables [...] [...] [...] 1 2 3</pre> <p>1 NAME</p> <p>2 set = BEFEHL reset = BEFEHL KEY = VALUE</p>
<pre>\setfirstline [...] OPT</pre> <p>* NAME</p>
<pre>\setflag {...}</pre> <p>* NAME</p>
<pre>\setfont ...</pre> <p>* FONT</p>
<pre>\setfontcolorsheme [...] OPT</pre> <p>* NAME</p>

<code>\setfontfeature {...}</code> * NAME
<code>\setfontsolution [...]</code> * NAME
<code>\setfontstrut</code>
<code>\setfractions</code>
<code>\setgmeasure {...} {...}</code> 1 NAME 2 DIMENSION
<code>\setgvalue {...} {...}</code> 1 NAME 2 CONTENT
<code>\setgvariable {...} {...} {...}</code> 1 NAME 2 KEY 3 VALUE
<code>\setgvariables [...] [...,...²...]</code> 1 NAME 2 set = BEFEHL reset = BEFEHL KEY = VALUE
<code>\sethboxregister ... {...}</code> 1 CSNAME NUMMER 2 CONTENT
<code>\sethyphenatedurlafter {...}</code> * TEXT
<code>\sethyphenatedurlbefore {...}</code> * TEXT
<code>\sethyphenatedurlnormal {...}</code> * TEXT
<code>\sethyphenationfeatures [...,[*]...]</code> <div style="text-align: center; margin-left: 150px;"><small>OPT</small></div> * NAME reset
<code>\setcharacteralign {...} {...}</code> 1 NUMMER 2 TEXT number->TEXT text->TEXT

<pre>\setcharactercasing [...]</pre> <pre>* reset SLOVO slovo Slovo Slova kapitalky Kapitalky zadny nahodny mixed camel kap Kap</pre>
<pre>\setcharactercleaning [...]</pre> <pre>* reset 1</pre>
<pre>\setcharacterkerning [...]</pre> <pre>* reset NAME</pre>
<pre>\setcharacterspacing [...]</pre> <pre>* reset NAME</pre>
<pre>\setcharacterstripping [...]</pre> <pre>* reset 1</pre>
<pre>\setcharstrut {...}</pre> <pre>* TEXT</pre>
<pre>\setinitial [...¹] [...²...]</pre> <div style="display: flex; justify-content: space-around; width: 100%;"> OPT OPT </div> <pre>1 NAME</pre> <pre>2 inherits: \setupinitial</pre>
<pre>\setinjector [...¹] [...²,...] [...³]</pre> <pre>1 NAME</pre> <pre>2 NUMMER</pre> <pre>3 BEFEHL</pre>
<pre>\setinteraction [...]</pre> <pre>* skryte NAME</pre>
<pre>\setinterfacecommand {...¹} {...²}</pre> <pre>1 NAME</pre> <pre>2 NAME</pre>
<pre>\setinterfaceconstant {...¹} {...²}</pre> <pre>1 NAME</pre> <pre>2 NAME</pre>
<pre>\setinterfaceelements {...¹} {...²}</pre> <pre>1 NAME</pre> <pre>2 NAME</pre>
<pre>\setinterfacemessage {...¹} {...²} {...³}</pre> <pre>1 NAME</pre> <pre>2 titul NAME NUMMER</pre> <pre>3 TEXT</pre>

<pre> \setinterfacevariable {...} {...} 1 NAME 2 NAME </pre>
<pre> \setinternalrendering [...] [...] {...} 1 NAME 2 auto embed 3 CONTENT </pre>
<pre> \setitaliccorrection [...] * reset 1 2 </pre>
<pre> \setJSreamble {...} {...} 1 NAME 2 CONTENT </pre>
<pre> \setlayer [...] [...²...] [...³...,...] {...⁴} OPT OPT 1 NAME 2 vlevo vpravo sude liche 3 inherits: \setuplayer 4 CONTENT </pre>
<pre> \setlayerframed [...] [...²...,...] [...³...,...] {...⁴} OPT OPT 1 NAME 2 inherits: \setuplayer 3 inherits: \nastavoramovani 4 CONTENT </pre>
<pre> \setlayerframed [...] [...²...,...] {...³} OPT 1 NAME 2 inherits: \setuplayerinherits: \nastavoramovani 3 CONTENT </pre>
<pre> \setlayertext [...] [...²...,...] [...³...,...] {...⁴} OPT OPT 1 NAME 2 inherits: \setuplayer 3 zarovnani = inherits: \nastavzarovnani sirka = DIMENSION pismo = STYLE BEFEHL barva = COLOR 4 TEXT </pre>
<pre> \setlinefiller [...] * filler NAME </pre>
<pre> \setlocalhsize [...[*]...] OPT * [-+]DIMENSION </pre>

`\setMPlayer [...]1 [...]2 [...,...3...,...]OPT {...}4`

- 1 NAME
- 2 NAME
- 3 inherits: \setupplayer
- 4 CONTENT

`\setMPpositiongraphic {...}1 {...}2 {...,...3...,...}OPT`

- 1 NAME
- 2 NAME
- 3 KEY = VALUE

`\setMPpositiongraphicrange {...}1 {...}2 {...}3 {...,...4...,...}OPT`

- 1 NAME
- 2 NAME
- 3 NAME
- 4 KEY = VALUE

`\setMPtext {...}1 {...}2`

- 1 NAME
- 2 TEXT

`\setMPvariable [...]1 [...]2`

- 1 NAME
- 2 KEY = VALUE

`\setMPvariables [...]1 [...,...2...,...]OPT`

- 1 NAME
- 2 KEY = VALUE

`\setmainbodyfont`

`\setmainparbuilder [...]*`

- * implicitni oneline basic NAME

`\setmarker [...]1 [...]2`

- 1 NAME
- 2 NUMMER

`\setmarking [...]1 {...}2`

- 1 BESCHRIFTUNG
- 2 TEXT

`\setmathstyle {...,*...}`

- * obrazovka text script scriptscript cramped uncramped normalni zhustene male velke NAME

<p><code>\setmeasure {...} {...}</code></p> <p>1 NAME</p> <p>2 DIMENSION</p>
<p><code>\setmessagetext {...} {...}</code></p> <p>1 NAME</p> <p>2 NAME NUMBER</p>
<p><code>\setmode {...}</code></p> <p>* NAME</p>
<p><code>\setnostrut</code></p>
<p><code>\setnote [...]¹ [...,²...] {...}³</code> <small>OPT</small></p> <p>1 NAME</p> <p>2 REFERENCE</p> <p>3 TEXT</p>
<p><code>\setnotetext [...]¹ [...,²...] {...}³</code> <small>OPT</small></p> <p>1 NAME</p> <p>2 REFERENCE</p> <p>3 TEXT</p>
<p><code>\setnotetext [...]¹ [...,²...,...]</code></p> <p>1 NAME</p> <p>2 titul = TEXT zalozka = TEXT seznam = TEXT odkaz = REFERENCE</p>
<p><code>\setnote [...]¹ [...,²...,...]</code></p> <p>1 NAME</p> <p>2 titul = TEXT zalozka = TEXT seznam = TEXT odkaz = REFERENCE</p>
<p><code>\setobject {...}¹ {...}² \... {...}³ {...}⁴</code></p> <p>1 NAME</p> <p>2 NAME</p> <p>3 CSNAME</p> <p>4 CONTENT</p>
<p><code>\setoldstyle</code></p>
<p><code>\setpagegrid [...,¹...,...]² {...}</code> <small>OPT</small></p> <p>1 c = NUMMER r = NUMMER volba = zadny</p> <p>2 CONTENT</p>

\setpagereference {...} {...,²...}

1 NAME

2 REFERENCE

\setpagestate [...]¹ [...]²
OPT

1 NAME

2 NAME NUMBER

\setpagestaterealpageno {...} {...}¹ {...}²

1 NAME

2 NAME NUMBER

\setpenalties \... {...}¹ {...}² {...}³

1 CSNAME

2 NUMBER

3 NUMBER

\setpercentdimen {...} {...}¹ {...}²

1 DIMENSION CSNAME

2 DIMENSION NUMBER

\setposition {...}

* NAME

\setpositionbox {...} \... {...}¹ \... {...}² {...}³

1 NAME

2 CSNAME

3 CONTENT

\setpositiondata {...} {...}¹ {...}² {...}³ {...}⁴

1 NAME

2 DIMENSION

3 DIMENSION

4 DIMENSION

\setpositiondataplus {...} {...}¹ {...}² {...}³ {...}⁴ {...,⁵...}

1 NAME

2 DIMENSION

3 DIMENSION

4 DIMENSION

5 TEXT

\setpositiononly {...}

* NAME

\setpositionplus {...} {...,²...} \... {...⁴}

- 1 NAME
- 2 TEXT
- 3 CSNAME
- 4 CONTENT

\setpositionstrut {...}

- * NAME

\setprofile [...]

- * zadny fixne striktni halffixed quarterfixed eightsfixed NAME

\setrandomseed {...}

- * NUMMER

\setreference [...,¹...] [...,²...,...]

- 1 REFERENCE
- 2 KEY = VALUE

\setreferencedobject {...} {...} \... {...⁴}

- 1 NAME
- 2 NAME
- 3 CSNAME
- 4 CONTENT

\setregisterentry [...¹] [...,²...,...]_{OPT} [...,³...,...]

- 1 NAME
- 2 popisek = NAME
keys = TEXT PROCESSOR->TEXT
entries = TEXT PROCESSOR->TEXT
keys:1 = TEXT
keys:2 = TEXT
keys:3 = TEXT
entries:1 = TEXT
entries:2 = TEXT
entries:3 = TEXT
alternativa = TEXT
- 3 KEY = VALUE

\setreplacement [...]

- * reset NAME

\setrigidcolumnbalance ...

- * CSNAME NUMMER

\setrigidcolumnhsize {...} {...} {...³}

- 1 DIMENSION
- 2 DIMENSION
- 3 NUMMER

<p><code>\setscript [...]</code></p> <p>* hangul hanzi nihongo ethiopic thai test NAME</p>
<p><code>\setsectionblock [¹...] [²...²...]</code> <small>OPT</small></p> <p>1 NAME</p> <p>2 zalozka = TEXT</p>
<p><code>\setsimplecolumnhsize [...[*]...]</code></p> <p>* n = NUMBER</p> <p> sirka = DIMENSION</p> <p> vzdalenost = DIMENSION</p> <p> radky = NUMBER</p>
<p><code>\setsmallbodyfont</code></p>
<p><code>\setsmallcaps</code></p>
<p><code>\setstackbox {¹} {²} {³}</code></p> <p>1 NAME</p> <p>2 NAME</p> <p>3 CONTENT</p>
<p><code>\setstructurepageregister [¹] [...²...] [...³...]</code> <small>OPT</small></p> <p>1 NAME</p> <p>2 popisek = NAME</p> <p> keys = TEXT PROCESSOR->TEXT</p> <p> entries = TEXT PROCESSOR->TEXT</p> <p> keys:1 = TEXT</p> <p> keys:2 = TEXT</p> <p> keys:3 = TEXT</p> <p> entries:1 = TEXT</p> <p> entries:2 = TEXT</p> <p> entries:3 = TEXT</p> <p> alternativa = TEXT</p> <p>3 KEY = VALUE</p>
<p><code>\setstrut</code></p>
<p><code>\setsuperiors</code></p>
<p><code>\setsystemmode {...}</code></p> <p>* NAME</p>
<p><code>\settabular</code></p>
<p><code>\settaggedmetadata [...[*]...]</code></p> <p>* KEY = VALUE</p>

`\setttextcontent [...]1 [...]2 [...]3 [...]4 [...]5`
OPT OPT

- 1 vrsek zahlavi text upati spodek
- 2 text marginalie hrana
- 3 vlevo nastred vpravo
- 4 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
- 5 datum cislostranky BESCHRIFTUNG TEXT BEFEHL

`\settightobject {...}1 {...}2 \... {...}3 {...}4`

- 1 NAME
- 2 NAME
- 3 CSNAME
- 4 CONTENT

`\settightreferencedobject {...}1 {...}2 \... {...}3 {...}4`

- 1 NAME
- 2 NAME
- 3 CSNAME
- 4 CONTENT

`\settightunreferencedobject {...}1 {...}2 \... {...}3 {...}4`

- 1 NAME
- 2 NAME
- 3 CSNAME
- 4 CONTENT

`\settrialtypesetting`

`\setuevalue {...}1 {...}2`

- 1 NAME
- 2 CONTENT

`\setugvalue {...}1 {...}2`

- 1 NAME
- 2 CONTENT

`\setunreferencedobject {...}1 {...}2 \... {...}3 {...}4`

- 1 NAME
- 2 NAME
- 3 CSNAME
- 4 CONTENT

\setupattachment [...,¹...] [...,²...]
OPT

```

1  NAME
2  titul      = TEXT
   podtitulek = TEXT
   autor      = TEXT
   soubor     = FILE
   jmeno      = NAME
   buffer     = BUFFER
   status     = start stop
   metoda     = normalni skryte
   symbol     = Graph Paperclip Pushpin Default
   sirka      = prizpusobive DIMENSION
   vyska      = prizpusobive DIMENSION
   hloubka    = prizpusobive DIMENSION
   barva      = COLOR
   textlayer  = NAME
   misto      = levahrana pravahrana naokraji levyokraj pravyokraj text vysoko zadny
   vzdalenost = DIMENSION

```

\setupbackend [...,^{*}...]

```

*  export      = ano FILE
   xhtml       = FILE
   soubor      = FILE
   intent      = NAME
   mezera      = ano ne
   xmpfile     = FILE
   formatovat  = version implicitni NAME
   uroven      = NUMMER
   volba       = vzdy nikdy
   profile     = FILE

```

\setupbar [...,¹...] [...,²...]
OPT

```

1  NAME
2  barva       = COLOR
   pokracovat  = ano ne vse
   prazdne     = ano ne
   jednotka    = ex em pt in cm mm sp bp pc dd cc nc
   order       = popredi pozadi
   tloustkalinky = DIMENSION
   metoda      = NUMMER
   offset      = NUMMER
   dy          = NUMMER
   max         = NUMMER
   foregroundstyle = STYLE BEFEHL
   foregroundcolor = COLOR
   mp          = NAME
   vlevo       = TEXT
   vpravo      = TEXT

```

\setupbleeding [...,^{*}...]

```

*  sirka       = DIMENSION
   vyska       = DIMENSION
   offset      = DIMENSION
   hoffset     = DIMENSION
   voffset     = DIMENSION
   misto       = t b l r bl lb br rb tl lt tr rt
   natahnout   = ano ne
   stranka     = ano ne

```

\setupbookmark [...,^{*}...]

```

*  sila        = ano ne
   cislo       = ano ne
   numberseparatorset = NAME
   numberconversionset = NAME
   numberstarter = BEFEHL
   numberstopper = BEFEHL
   numbersegments = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:* ABSCHNITT:vse
   sectionblock = ano ne

```

\setupbtx [¹...] [²...,...]

OPT

1 NAME

2 specification = implicitni apa aps NAME
dataset = implicitni NAME
prikaz = \...##1
vlevo = BEFEHL
vpravo = BEFEHL
authorconversion = normalni normalshort normalinverted invertedshort short
etallimit = NUMMER
etaldisplay = NUMMER
etaloption = posledni
predel = initials
interakce = start stop vse
alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
authornum authoryear
sorttype = normalni reverse
compress = ano ne
implicitni = implicitni NAME
pismo = STYLE BEFEHL
barva = COLOR

\setupbtxdataset [¹...,...] [²...,...]

OPT

1 NAME

2 language = SPRACHE

\setupbtxlist [¹...] [²...,...]

OPT

1 NAME

2 inherits: \nastavseznam

\setupbtxregister [¹...,...] [²...,...]

OPT

1 NAME

2 status = start stop
dataset = NAME
field = keyword range cislostranky autor
register = NAME
metoda = once
alternativa = normalshort invertedshort
pismo = STYLE BEFEHL
barva = COLOR

\setupbtxrendering [¹...,...] [²...,...]

OPT

1 NAME

2 statustextu = start stop
pagestate = start stop
oddelovac = BEFEHL
kriterium = predchozi cite zde vse zadny
specification = NAME
titul = TEXT
pred = BEFEHL
po = BEFEHL
dataset = NAME
metoda = dataset sila lokalne globalne zadny
sorttype = short dataset seznam odkaz uzito implicitni cite rejstrik
opakovat = ano ne
group = NAME
cislovani = ano ne num rejstrik tag short stranka

\setupbtx [...]

* NAME

\setupbutton [...¹,...] [...²,...]
OPT

```
1 NAME

2 status          = start stop
  stejnastranka   = ano ne prazdne zadny normalni implicitni
  pismo          = STYLE BEFEHL
  barva           = COLOR
  kontrastnibarva = COLOR
  alternativa     = skryte
  inherits: \nastavoramovani
```

\setupcollector [...¹,...] [...²,...]
OPT

```
1 NAME

2 rotate = vlevo vpravo uvnitr vnejsi NUMMER
  roh    = vlevo nastred vpravo vrsek spodek
  x       = DIMENSION
  y       = DIMENSION
  hoffset = DIMENSION
  voffset = DIMENSION
  misto    = vlevo nastred vpravo vrsek spodek radek l c r m t b g
  status   = start stop
```

\setupcolumnspan [...^{*},...]

```
* n = NUMMER
  inherits: \nastavoramovani
```

\setupcombination [...¹,...] [...²,...]
OPT

```
1 NAME

2 nx      = NUMMER
  ny      = NUMMER
  sirka   = prizpusobive DIMENSION
  vyska   = prizpusobive DIMENSION
  misto    = vlevo nastred vpravo vrsek spodek
  vzdalenost = DIMENSION
  alternativa = popisek text
  zarovnani = inherits: \nastavzarovnani
  pokracovat = ano ne
  pred       = BEFEHL
  po         = BEFEHL
  mezi       = BEFEHL
  pismo      = STYLE BEFEHL
  barva      = COLOR
```

\setupcounter [...¹,...] [...²,...]
OPT

```
1 NAME

2 start          = NUMMER
  counter        = NAME
  metoda         = stranka
  status         = start stop
  zpusob         = bystranka byblock bytext byhlavicka byABSCHNITT
  prefix         = ano ne
  prefixseparatorset = NAME
  prefixconversion = NAME
  prefixconversionset = NAME
  prefixstarter  = BEFEHL PROCESSOR->BEFEHL
  prefixstopper  = BEFEHL PROCESSOR->BEFEHL
  prefixset      = NAME
  prefixsegments = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:* ABSCHNITT:vse
  numberorder    = reverse
  numberseparatorset = NAME
  numberconversion = NAME
  numberconversionset = NAME
  numberstarter  = BEFEHL PROCESSOR->BEFEHL
  numberstopper  = BEFEHL PROCESSOR->BEFEHL
  numbersegments = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse
  typ            = prvni predchozi dalsi posledni cislo
  kriterium      = striktni pozitiv vse
  prefixconnector = BEFEHL PROCESSOR->BEFEHL
```

`\setupdataset [...,1...] [...,2...,...]`
OPT

- 1 NAME
- 2 prodleva = ano ne

`\setupdelimitedtext [...,1...] [...,2...,...]`
OPT

- 1 NAME
- 2
 - pred = BEFEHL
 - po = BEFEHL
 - language = lokalne globalne SPRACHE
 - metoda = font
 - opakovat = ano ne
 - misto = text odstavec marginalie
 - vlevo = BEFEHL
 - stredni = BEFEHL
 - vpravo = BEFEHL
 - nextleft = BEFEHL
 - nextright = BEFEHL
 - mezerapred = inherits: \preskoc
 - mezeraza = inherits: \preskoc
 - levyokraj = ano ne standardni DIMENSION
 - pravyokraj = ano ne standardni DIMENSION
 - odsazovani = inherits: \nastavodsazovani
 - odsadpristi = ano ne auto
 - pismo = STYLE BEFEHL
 - barva = COLOR
 - stylsymboly = STYLE BEFEHL
 - barvasymbolu = COLOR

`\setupdescription [...,1...] [...,2...,...]`
OPT

- 1 NAME
- 2
 - titul = ano ne
 - uroven = NUMMER
 - text = TEXT
 - headcommand = \...##1
 - pred = BEFEHL
 - po = BEFEHL
 - mezi = BEFEHL
 - alternativa = vlevo vpravo naokrajiv vlevo ivpravo marginalie levyokraj pravyokraj innermargin outermargin
semknuto visici vrsek prikaz NAME
 - zarovnnani = inherits: \nastavzarovnnani
 - headalign = inherits: \nastavzarovnnani
 - odsazovani = inherits: \nastavodsazovani
 - obrazovka = ano ne
 - odsadpristi = ano ne auto
 - sirka = prizpusobive siroky radek DIMENSION
 - vzdalenost = zadny DIMENSION
 - zaveseni = prizpusobive siroky zadny marginalie NUMMER
 - closesymbol = BEFEHL
 - closecommand = \...##1
 - expanzen = ano ne xml
 - vzor = TEXT
 - marginalie = ano ne standardni DIMENSION
 - pismo = STYLE BEFEHL
 - barva = COLOR
 - stylhlavicky = STYLE BEFEHL
 - barvahlavicky = COLOR

`\setupdirections [...,*...,...]`

- * bidi = zap vyp lokalne globalne
- metoda = jedna dve implicitni
- fences = ano ne

```
*  pred      = BEFEHL
   po        = BEFEHL
   metadata:author = TEXT
   metadata:title  = TEXT
   metadata:subject = TEXT
   metadata:keywords = TEXT
   KEY          = VALUE
```

```

1  NAME
2  metoda      = zadny prikaz
   natakhnout  = NUMMER
   tloustkalinky = NUMMER
   alternativa = normalni uvnitr vnejsi obe skryte natakhnout

```

```

1  NAME
2  titul          = ano ne
   cislo          = ano ne
   ciselnyprikaz = \...##1
   vzdalenosttitulek = DIMENSION
   styltitulek    = STYLE BEFEHL
   barvatitulek   = COLOR
   titlecommand   = \...##1
   titleleft      = BEFEHL
   titleright     = BEFEHL
   vlevo          = BEFEHL
   vpravo         = BEFEHL
   symbol         = BEFEHL
   starter        = BEFEHL
   predel         = BEFEHL
   propojeni      = NAME
   counter        = NAME
   uroven         = NUMMER
   text           = TEXT
   headcommand    = \...##1
   pred           = BEFEHL
   po             = BEFEHL
   mezi           = BEFEHL
   alternativa    = vlevo vpravo naokraj i vlevo ivpravo marginalie levyokraj pravyokraj innermargin outermargin
                   semknuto visici vrsek prikaz NAME
   zarovnani      = inherits: \nastavzarovnani
   headalign      = inherits: \nastavzarovnani
   odsazovani     = inherits: \nastavodsazovani
   obrazovka      = ano ne
   odsadpristi    = ano ne auto
   sirka          = prizpusobive široky radek DIMENSION
   vzdalenost     = zadny DIMENSION
   zaveseni       = prizpusobive široky zadny marginalie NUMMER
   closesymbol    = BEFEHL
   closecommand   = \...##1
   expanzen       = ano ne xml
   vzor           = TEXT
   marginalie     = ano ne standardni DIMENSION
   pismo          = STYLE BEFEHL
   barva          = COLOR
   stylhlavicky   = STYLE BEFEHL
   barvahlavicky  = COLOR
   inherits: \setupcounter

```

```
*  set      = BEFEHL
   reset    = BEFEHL
   KEY      = VALUE
```

\setupexport [...^{*}...]

```
*   zarovnani      = flushleft nastred flushright normalni
    zakladnifont   = DIMENSION
    sirka          = DIMENSION
    titul          = TEXT
    podtitulek     = TEXT
    autor          = TEXT
    alternativa    = html div
    properties     = ano ne
    hyphen         = ano ne
    cssfile        = FILE
    prvnistranka   = FILE
    poslednistrana = FILE
```

\setupexternalfigure [...¹...] [...²...]
OPT

```
1  NAME

2  sirka          = DIMENSION
    vyska         = DIMENSION
    popisek       = NAME
    stranka       = NUMMER
    objekt        = ano ne
    prefix        = TEXT
    metoda        = pdf mps jpg png jp2 jbig svg eps gif tif mov buffer tex cld auto
    controls      = ano ne
    nahled        = ano ne
    mask          = zadny
    rozliseni     = NUMMER
    barva         = COLOR
    arguments     = TEXT
    opakovat      = ano ne
    faktor        = prizpusobive siroky max auto implicitni
    vfaktor       = prizpusobive siroky max auto implicitni
    sfaktor       = prizpusobive siroky max auto implicitni
    maxsirka      = DIMENSION
    maxvyska      = DIMENSION
    equalwidth    = DIMENSION
    equalheight   = DIMENSION
    meritko       = NUMMER
    xmeritko      = NUMMER
    ymeritko      = NUMMER
    s             = NUMMER
    sx            = NUMMER
    sy            = NUMMER
    radky         = NUMMER
    misto         = lokalne globalne implicitni
    adresar       = PATH
    volba         = test ramecek prazdne
    foregroundcolor = COLOR
    reset         = ano ne
    pozadi        = barevne popredi NAME
    ramecek       = zap vyp
    barvapozadi   = COLOR
    zarovnani     = inherits: \nastavzarovnani
    xmax          = NUMMER
    ymax          = NUMMER
    ramecky       = zap vyp
    interakce     = ano vse zadny odkaz layer zalozka
    zakladnifont  = DIMENSION
    comment       = BEFEHL TEXT
    velikost      = zadny media crop trim art
    cache         = PATH
    resources     = PATH
    obrazovka     = FILE
    konverze      = TEXT
    order         = LISTE
    crossreference = ano ne NUMMER
```

\setupexternalsoundtracks [...^{*}...]

```
*   volba = opakovat
```


`\setupfieldbody [...1,...] [...2,...]`
OPT

- 1 NAME
- 2 category = NAME
inherits: \setupfieldcategory

`\setupfieldcategory [...1,...] [...2,...]`
OPT

- 1 NAME
- 2
 - start = NUMBER
 - pismeno = STYLE BEFEHL
 - barva = COLOR
 - typ = radio pod text radek push check signature
 - values = TEXT
 - implicitni = TEXT
 - barvarameckupole = COLOR
 - barvapozaadipole = COLOR
 - sirka = DIMENSION
 - vyska = DIMENSION
 - hloubka = DIMENSION
 - zarovnani = vlevo nastred vpravo flushleft center flushright
 - n = NUMBER
 - symbol = NAME
 - fieldlayer = NAME
 - volba = pouzeprocteni pozadovane chranene tridene nedostupne nocheck fixne soubor skryte tisknutelne auto
 - klikuvnitr = REFERENCE
 - klikvne = REFERENCE
 - oblastuvnitr = REFERENCE
 - oblastvne = REFERENCE
 - klavesapo = REFERENCE
 - formatovat = REFERENCE
 - validovat = REFERENCE
 - pocitat = REFERENCE
 - focusin = REFERENCE
 - focusout = REFERENCE
 - openpage = REFERENCE
 - closepage = REFERENCE

`\setupfieldcontentframed [...1,...] [...2,...]`
OPT

- 1 NAME
- 2 inherits: \nastavoramovaniinherits: \setupfieldcategory

`\setupfieldlabelframed [...1,...] [...2,...]`
OPT

- 1 NAME
- 2 inherits: \nastavoramovani

`\setupfieldtotalframed [...1,...] [...2,...]`
OPT

- 1 NAME
 - 2
 - pred = BEFEHL
 - po = BEFEHL
 - mezi = BEFEHL
 - vzdalenost = DIMENSION
 - alternativa = reset popisek ramecek horizontalne vertikalne
- inherits: \nastavoramovani

\setupfiller [...¹,...] [...²,...]
OPT

1 NAME

2 levyokraj = DIMENSION
 pravyokraj = DIMENSION
 vlevo = BEFEHL
 vpravo = BEFEHL
 alternativa = symbol natahnout linka mezera
 metoda = lokalne globalne nastred široky
 sirka = DIMENSION
 vyska = DIMENSION
 hloubka = DIMENSION
 offset = DIMENSION
 vzdalenost = DIMENSION
 zarovnani = vlevo vpravo nastred flushleft flushright uvnitr vnejsi
 symbol = BEFEHL
 pismeno = STYLE BEFEHL
 barva = COLOR

\setupfirstline [...¹,...] [...²,...]
OPT

1 NAME

2 n = NUMMER
 alternativa = implicitni radek slovo
 pismeno = STYLE BEFEHL
 barva = COLOR

\setupfittingpage [...¹,...] [...²,...]
OPT

1 NAME

2 pagestate = start stop
 prikaz = \...##1
 marginalie = stranka
 meritko = NUMMER
 papir = auto default NAME
 inherits: \nastavoramovani

\setupfloatcaption [...¹,...] [...²,...]
OPT

1 NAME

2 suffix = BEFEHL
 suffixseparator = BEFEHL
 suffixstopper = BEFEHL
 misto = vlevo vpravo nastred nizko vysoko mrizka prekryv uvnitr vnejsi innermargin outermargin levyokraj
 pravyokraj lefthanging righthanging zaveseni vrsek spodek natahnout zadny implicitni
 prikaz = \...##1
 ciselnyprikaz = \...##1
 textovyprikaz = \...##1
 mezerapred = inherits: \preskoc
 spaceinbetween = inherits: \preskoc
 mezeraza = inherits: \preskoc
 vzdalenost = DIMENSION
 mezi = BEFEHL
 pismeno = STYLE BEFEHL
 barva = COLOR
 offsetvrsku = DIMENSION
 offsetspodku = DIMENSION
 cislo = ano ne zadny
 group = TEXT
 levyokraj = DIMENSION
 pravyokraj = DIMENSION
 innermargin = DIMENSION
 outermargin = DIMENSION
 zarovnani = inherits: \nastavzarovnani
 sirka = prizpusobive max DIMENSION
 minsirka = prizpusobive DIMENSION
 maxsirka = DIMENSION
 inherits: \setupcounter

`\setupfontexpansion [...]1 [...]2...`

```
1 NAME
2 vector = NAME
  faktor = NUMMER
  natahnout = NUMMER
  shrink = NUMMER
  krok = NUMMER
```

`\setupfontprotrusion [...]1 [...]2...`

```
1 NAME
2 vector = NAME
  faktor = NUMMER
  vlevo = NUMMER
  vpravo = NUMMER
```

`\setupfonts [...]*...`

```
* language = ne auto
```

`\setupfontsolution [...]1 [...]2...`
OPT

```
1 NAME
2 goodies = FILE
  solution = NAME
  less = NAME
  more = NAME
  metoda = preroll split normalni reverse nahodny
  kriterium = NUMMER
```

`\setupforms [...]*...`

```
* metoda = XML HTML PDF
  export = ano ne
```

`\setupformula [...]1 [...]2...`
OPT

```
1 NAME
2 misto = vlevo vpravo
  zarovnani = vlevo nastred vpravo flushleft center flushright normalni
  strut = ano ne
  vzdalenost = DIMENSION
  vlevo = BEFEHL
  vpravo = BEFEHL
  mezerapred = inherits: \preskoc
  mezeraza = inherits: \preskoc
  ciselnyprikaz = \...##1
  barva = COLOR
  stylciska = STYLE BEFEHL
  barvaciska = COLOR
  volba = zhustene tight nastred ramecek inherits: \nastavzakladnifont
  marginalie = ano ne standardni DIMENSION
  levyokraj = DIMENSION
  pravyokraj = DIMENSION
  alternativa = NAME
  odsadpristi = ano ne auto
  mrizka = inherits: \snaptogrid
  ramecek = cislo
  inherits: \setupcounter
```

`\setupformulaframed [...]1 [...]2...`
OPT

```
1 NAME
2 inherits: \nastavoramovani
```

`\setupframedcontent [...1,...] [...2,...]`
OPT

1 NAME
2 vlevo = BEFEHL
vpravo = BEFEHL
leftoffser = DIMENSION
pravyoffset = DIMENSION
offsetvrsku = DIMENSION
offsetspodku = DIMENSION
korekceradku = ano ne
inherits: \nastavoramovani

`\setupframedtext [...1,...] [...2,...]`
OPT

1 NAME
2 vlevo = BEFEHL
vpravo = BEFEHL
vnitrni = BEFEHL
misto = vlevo vpravo nastred zadny
korekcehloubky = zap vyp
zakladnifont = inherits: \nastavzakladnifont
odsazovani = inherits: \nastavodsazovani
pismo = STYLE BEFEHL
barva = COLOR
inherits: \nastavoramovaniinherits: \setupplacement

`\setupglobalreferenceprefix [...]`

* + - TEXT

`\setupheadalternative [...1,...] [...2,...]`
OPT

1 NAME
2 alternativa = horizontalne vertikalne nekde
renderingsetup = NAME

`\setuphelp [...1,...] [...2,...]`
OPT

1 NAME
2 inherits: \nastavoramovani

`\setuphigh [...1,...] [...2,...]`
OPT

1 NAME
2 vzdalenost = DIMENSION
up = DIMENSION
pismo = STYLE BEFEHL
barva = COLOR

`\setuphighlight [...1,...] [...2,...]`
OPT

1 NAME
2 prikaz = ano ne
pismo = STYLE BEFEHL
barva = COLOR

`\setuphyphenation [...*,...]`

* metoda = original tex implicitni hyphenate expanded traditional zadny

`\setupcharacterkerning [...1,...] [...2,...]`
OPT

1 NAME
 2 faktor = max NUMMER
 sirka = DIMENSION
 features = NAME
 pismo = STYLE BEFEHL
 barva = COLOR

`\setupcharacterspacing [...1.] [...2.] [...3...]`
OPT

1 NAME
 2 NUMMER
 3 vlevo = NUMMER
 vpravo = NUMMER
 alternativa = 0 1

`\setupchemical [...1,...] [...2...]`
OPT

1 NAME
 2 strut = inherits: \value-strut
 sirka = prizpusobive zadny NUMMER
 vyska = prizpusobive zadny NUMMER
 vlevo = prizpusobive zadny NUMMER
 vpravo = prizpusobive zadny NUMMER
 vrsek = prizpusobive zadny NUMMER
 spodek = prizpusobive zadny NUMMER
 meritko = male stredni velke normalni NUMMER
 rotace = NUMMER
 symzarovnani = auto
 osa = zap vyp
 barvaramecku = COLOR
 tloustkalinky = DIMENSION
 offset = DIMENSION
 jednotka = DIMENSION
 faktor = NUMMER
 ramecek = zap vyp
 barvalinky = COLOR
 zakladnifont = inherits: \nastavzakladnifont
 velikost = male stredni velke
 pismo = STYLE BEFEHL
 barva = COLOR

`\setupchemicalframed [...1,...] [...2...]`
OPT

1 NAME
 2 inherits: \nastavoramovani

`\setupindentedtext [...1,...] [...2...]`
OPT

1 NAME
 2 pred = BEFEHL
 po = BEFEHL
 vzdalenost = DIMENSION
 vzor = TEXT
 text = TEXT
 sirka = prizpusobive siroky DIMENSION
 oddelovac = BEFEHL
 pismo = STYLE BEFEHL
 barva = COLOR
 stylhlavicky = STYLE BEFEHL
 barvahlavicky = COLOR

`\setupinitial [...,1...] [...,2...,...]`
OPT

1 NAME

2 n = NUMMER
 m = NUMMER
 pred = BEFEHL
 vzdalenost = DIMENSION
 hoffset = DIMENSION
 voffset = radek DIMENSION
 pismo = STYLE BEFEHL
 barva = COLOR
 font = FONT
 text = TEXT
 misto = marginalie text
 metoda = prvni posledni auto zadny

`\setupinsertion [...,1...] [...,2...,...]`
OPT

1 NAME

2 misto = stranka text sloupce firstcolumn lastcolumn

`\setupitaliccorrection [...,*...]`

* text vzdy globalne zadny

`\setupitemgroup [...,1] [...,2...] [...,3...] [...,4...,...]`
OPT OPT OPT

1 NAME

2 kazdy NUMMER

3 uvod nahodny pokracovat zhustene autouvod siroky text pred po zadnabila marginalie naokraji naokraji dotextu
 uvolnene prizpusobive nofit odstavec spojeno semknuto predel rozbalene opakovat norepeat reverse sloupce jedna dve
 tri ctyri pet six seven eight nine standardni NUMMER*siroky NUMMER*semknuto horizontalne NAME

4 pred = BEFEHL
 po = BEFEHL
 mezi = BEFEHL
 predhlavickou = BEFEHL
 pohlavicce = BEFEHL
 textvlevo = BEFEHL
 textvpravo = BEFEHL
 vlevo = BEFEHL
 vpravo = BEFEHL
 faktor = NUMMER
 krok = DIMENSION
 sirka = DIMENSION
 vzdalenost = DIMENSION
 marginalie = ano ne standardni DIMENSION
 levyokraj = ano ne standardni DIMENSION
 pravyokraj = ano ne standardni DIMENSION
 zarovnnani = inherits: \nastavzarovnnani
 odsazovani = inherits: \nastavodsazovani
 start = NUMMER
 symzarovnnani = vlevo nastred vpravo flushleft center flushright
 symbol = NAME
 n = NUMMER
 odsadpristi = ano ne auto
 vnitrni = BEFEHL
 prikaz = CSNAME
 polozky = NUMMER
 maxsirka = DIMENSION
 itemalign = vlevo vpravo nastred flushleft flushright uvnitr vnejsi
 alignsymbol = ano ne
 textdistance = male stredni velke zadny mezera DIMENSION
 predelmista = ano ne
 pismo = STYLE BEFEHL
 barva = COLOR
 stylhlavicky = STYLE BEFEHL
 barvahlavicky = COLOR
 stylsnacky = STYLE BEFEHL
 barvaznacky = COLOR
 stylsymboly = STYLE BEFEHL
 barvasymbolu = COLOR
 inherits: \setupcounter

`\setupitemgroup [...1,...] [...2,...]`
OPT

1 NAME NAME:NUMMER

2 pred = BEFEHL
 po = BEFEHL
 mezi = BEFEHL
 predhlavickou = BEFEHL
 pohlavicce = BEFEHL
 textvlevo = BEFEHL
 textvpravo = BEFEHL
 vlevo = BEFEHL
 vpravo = BEFEHL
 faktor = NUMMER
 krok = DIMENSION
 sirka = DIMENSION
 vzdalenost = DIMENSION
 volba = uvod nahodny pokracovat zhustene autouvod široky text pred po zadnabila marginalie naokraji
 naokraji dotextu uvolnene prizpusobive nofit odstavec spojeno semknuto predel rozbalene opakovat
 norepeat reverse sloupce jedna dve tri ctyri pet six seven eight nine standardni NUMMER*siroky
 NUMMER*semknuto horizontalne NAME
 marginalie = ano ne standardni DIMENSION
 levyokraj = ano ne standardni DIMENSION
 pravyokraj = ano ne standardni DIMENSION
 zarovnani = inherits: \nastavzarovnani
 odsazovani = inherits: \nastavodsazovani
 start = NUMMER
 symzarovnani = vlevo vpravo nastred flushleft center flushright
 symbol = NAME
 n = NUMMER
 odsadpristi = ano ne auto
 vnitrni = BEFEHL
 prikaz = CSNAME
 polozky = NUMMER
 maxsirka = DIMENSION
 itemalign = vlevo vpravo nastred flushleft flushright uvnitr vnejsi
 alignsymbol = ano ne
 textdistance = male stredni velke zadny mezera DIMENSION
 predelmista = ano ne
 pismo = STYLE BEFEHL
 barva = COLOR
 stylhlavicky = STYLE BEFEHL
 barvahlavicky = COLOR
 stylsnacky = STYLE BEFEHL
 barvaznacky = COLOR
 stylsymboly = STYLE BEFEHL
 barvasymbolu = COLOR
 inherits: \setupcounter

`\nastaveniITEMGROUP [...1,...] [...2,...] [...3,...]`
OPT OPT OPT

1 kazdy NUMMER

2 inherits: \setupitemgroup

3 inherits: \setupitemgroup

instances: itemize

`\setuplabel [...1,...] [...2,...]`
OPT

```

1  NAME

2  titul           = ano ne
   cislo           = ano ne
   ciselny prikaz  = \...##1
   vzdalenosttitulek = DIMENSION
   stylytitulek    = STYLE BEFEHL
   barvatitulek    = COLOR
   titlecommand    = \...##1
   titleleft       = BEFEHL
   titleright      = BEFEHL
   vlevo           = BEFEHL
   vpravo          = BEFEHL
   symbol          = BEFEHL
   starter         = BEFEHL
   predel          = BEFEHL
   propojeni       = NAME
   counter         = NAME
   uroven          = NUMMER
   text            = TEXT
   headcommand     = \...##1
   pred            = BEFEHL
   po              = BEFEHL
   mezi            = BEFEHL
   alternativa     = vlevo vpravo naokraj ivlevo ivpravo marginalie lev yokraj prav yokraj innermargin outermargin
                     semknuto visici vrsek prikaz dotextu NAME

   zarovnnani      = inherits: \nastavzarovnnani
   headalign       = inherits: \nastavzarovnnani
   odsazovani      = inherits: \nastavodsazovani
   obrazovka       = ano ne
   odsadpristi     = ano ne auto
   sirka           = prizpusobive siroky radek DIMENSION
   vzdalenost      = zadny DIMENSION
   zaveseni        = prizpusobive siroky zadny marginalie NUMMER
   closesymbol     = BEFEHL
   closecommand    = \...##1
   expanzen        = ano ne xml
   referenceprefix = + - TEXT
   vzor            = TEXT
   marginalie      = ano ne standardni DIMENSION
   pismo           = STYLE BEFEHL
   barva           = COLOR
   stylhlavicky    = STYLE BEFEHL
   barvahlavicky   = COLOR
   inherits: \setupcounter

```

`\setuplayer [...1,...] [...2,...]`
OPT

```

1  NAME

2  status          = start stop pokracovat dalsi opakovat
   volba           = test
   stranka         = NUMMER
   sirka           = DIMENSION
   vyska           = DIMENSION
   region          = NAME
   rotace          = vlevo vpravo uvnitr vnejsi NUMMER
   position        = ano ne prekryv
   hoffset         = max DIMENSION
   voffset         = max DIMENSION
   offset          = DIMENSION
   dx              = DIMENSION
   dy              = DIMENSION
   sx              = NUMMER
   sy              = NUMMER
   x               = DIMENSION
   y               = DIMENSION
   roh             = vlevo nastred vpravo vrsek spodek
   misto           = mizka vlevo nastred vpravo vrsek spodek radek l c r m t b g
   radek           = NUMMER
   sloupec         = NUMMER
   smer            = normalni reverse
   oboustranne     = ano ne
   metoda          = prizpusobive prekryv
   opakovat        = ano
   prednastaveni   = lefttop righttop leftbottom rightbottom nastred middletop middlebottom middleleft middleright
                     lefttoleft lefttopright NAME

```


`\setuplayeredtext [...1,...] [...2,...]`
OPT

1 NAME
 2 pismo = STYLE BEFEHL
 barva = COLOR
 inherits: \nastavoramovani

`\setuplayouttext [...1] [...2] [...3,...]`
OPT

1 vrsek zahlavi text upati spodek
 2 text marginalie hrana
 3 status = start stop prazdne vysoko zadny normalni zadneznaceni NAME
 pismo = STYLE BEFEHL
 barva = COLOR
 strut = ano ne
 n = NUMMER
 pred = BEFEHL
 po = BEFEHL
 stylvlevo = STYLE BEFEHL
 stylvpravo = STYLE BEFEHL
 barvavlevo = COLOR
 barvavpravo = COLOR
 sirka = DIMENSION
 sirkavlevo = DIMENSION
 sirkavpravo = DIMENSION

`\setuplinefiller [...1,...] [...2,...]`
OPT

1 NAME
 2 misto = vlevo vpravo obe
 rozsah = vlevo vpravo lokalne
 mp = NAME
 vyska = DIMENSION
 hloubka = DIMENSION
 vzdalenost = DIMENSION
 threshold = DIMENSION
 tloustkalinky = DIMENSION
 pred = BEFEHL
 po = BEFEHL
 barva = COLOR
 styltextu = STYLE BEFEHL
 barvatextu = COLOR
 zarovnani = inherits: \nastavzarovnani

`\setuplinefillers [...1,...] [...2,...]`
OPT

1 NAME
 2 inherits: \setuplinefiller

`\setuplinenote [...1,...] [...2,...]`
OPT

1 NAME
 2 compress = ano ne
 compressmethod = separator predel mezera
 compressseparator = BEFEHL
 compressdistance = DIMENSION
 inherits: \setupnote

`\setuplinetable [...]1 [...]2 [...,...]3 [...,...]`

OPT OPT

```
1 r c
2 liche sude zahlavi NUMMER
3 radky      = prizpusobive NUMMER
  pred       = BEFEHL
  po         = BEFEHL
  mezi       = BEFEHL
  natahnout  = ano ne DIMENSION
  maxsirka   = prizpusobive DIMENSION
  nvlevo     = NUMMER
  n          = NUMMER
  opakovat   = ano ne
  nx         = NUMMER
  sirka      = DIMENSION
  vyska      = prizpusobive radek DIMENSION
  vzdalenost = DIMENSION
  levyoffset = DIMENSION
  pravyoffset = DIMENSION
  zarovnani  = inherits: \nastavzarovnani
  pozadi     = barevne
  barvapozadi = COLOR
  xheight    = max DIMENSION
  xdepth     = max DIMENSION
  pismo     = STYLE BEFEHL
  barva      = COLOR
```

`\setuplistalternative [...]1,... [-,...]2 [...,...]`

OPT

```
1 NAME
2 pred      = BEFEHL
  po        = BEFEHL
  prikaz     = \...##1##2##3
  renderingsetup = NAME
  sirka      = DIMENSION
  vzdalenost = DIMENSION
  natahnout  = DIMENSION
  filler     = BEFEHL
```

`\setuplistextra [...]1,... [-,...]2 [...,...]`

OPT

```
1 NAME
2 pred = BEFEHL
  po   = BEFEHL
```

`\setuplocalfloats [...,...]* [...,...]`

```
* pred = BEFEHL
  po   = BEFEHL
  mezi = BEFEHL
```

`\setuplocalinterlinespace [...]1,... [-,...]2 [...,...]`

OPT

```
1 NAME
2 inherits: \nastavmeziradkovoumezeru
```

`\setuplocalinterlinespace [...]*,... [-,...]* [...,...]`

OPT

```
* zap vyp reset auto male stredni velke NUMMER DIMENSION
```

`\setuplocalinterlinespace [...]* [-,...]* [...,...]`

```
* NAME
```

`\setuplow [...,1...] [...,2...,...]`
OPT

1 NAME
 2 vzdalenost = DIMENSION
 down = DIMENSION
 pismo = STYLE BEFEHL
 barva = COLOR

`\setuplowhigh [...,1...] [...,2...,...]`
OPT

1 NAME
 2 vzdalenost = DIMENSION
 up = DIMENSION
 down = DIMENSION
 pismo = STYLE BEFEHL
 barva = COLOR

`\setuplowmidhigh [...,1...] [...,2...,...]`
OPT

1 NAME
 2 up = DIMENSION
 down = DIMENSION
 pismo = STYLE BEFEHL
 barva = COLOR

`\setupMPgraphics [...,*...,...]`

* barva = lokalne globalne
 mpy = FILE

`\setupMPinstance [...,1...] [...,2...,...]`
OPT

1 NAME
 2 formatovat = metafun mpost
 initializations = ano ne
 setups = NAME
 styltextu = STYLE BEFEHL
 barvatextu = COLOR
 extensions = ano ne
 metoda = binary decimal double scaled implicitni

`\setupMPpage [...,*...,...]`

* inherits: \setupfittingpage

`\setupMPvariables [...,1...] [...,2...,...]`
OPT

1 NAME
 2 KEY = VALUE

`\setupmarginblock [...,1...] [...,2...,...]`
OPT

1 NAME
 2 status = start stop
 sirka = DIMENSION
 pred = BEFEHL
 po = BEFEHL
 mezi = BEFEHL
 zarovnani = inherits: \nastavzarovnani
 pismo = STYLE BEFEHL
 barva = COLOR
 vrsek = BEFEHL
 spodek = BEFEHL
 misto = vlevo vpravo nastred naokraj
 vlevo = BEFEHL
 vpravo = BEFEHL

`\setupmargindata [...1,...] [...2,...]`
OPT

```

1  NAME

2  strut      = ano ne auto kap prizpusobive radek implicitni CHARACTER
   prikaz     = \...##1
   sirka      = DIMENSION
   zarovnani  = inherits: \nastavzarovnani
   anchor     = region text
   misto      = vlevo vpravo uvnitr vnejsi
   metoda    = vrsek radek prvni podlehloubky vyska
   category   = implicitni hrana
   rozsah     = lokalne globalne
   volba      = text odstavec
   marginalie = lokalne normalni marginalie hrana
   vzdalenost = DIMENSION
   hoffset    = DIMENSION
   voffset    = DIMENSION
   dy         = DIMENSION
   bottomspace = DIMENSION
   threshold  = DIMENSION
   radek      = NUMMER
   stack      = ano pokracovat
   pismo     = STYLE BEFEHL
   barva      = COLOR

```

`\setupmarginframed [...1,...] [...2,...]`
OPT

```

1  NAME

2  inherits: \nastavoramovani

```

`\setupmarginrule [...1] [...2,...]`
OPT

```

1  NUMMER

2  inherits: \setupsidebar

```

`\setupmathalignment [...1,...] [...2,...]`
OPT

```

1  NAME

2  n          = NUMMER
   m          = NUMMER
   vzdalenost = DIMENSION
   zarovnani  = vlevo nastred vpravo normalni

```

`\setupmathcases [...1,...] [...2,...]`
OPT

```

1  NAME

2  vlevo      = BEFEHL
   vpravo     = BEFEHL
   strut      = ano ne
   pismo     = STYLE BEFEHL
   vzdalenost = DIMENSION
   numberdistance = DIMENSION

```

`\setupmathematics [...1,...] [...2,...]`
OPT

```

1  NAME

2  openup           = ano ne
   sadasymbolu     = NAME
   functionstyle    = STYLE BEFEHL
   compact          = ano ne
   zarovnani        = l2r r2l
   bidi             = ano ne
   sygreek          = normalni kurziva zadny
   lcgreek          = normalni kurziva zadny
   ucgreek          = normalni kurziva zadny
   italics          = 1 2 3 4 zadny reset
   autopunctuation = ano ne vse
   setups           = NAME
   domain           = NAME reset
   styltextu        = STYLE BEFEHL
   barvatextu        = COLOR
   functioncolor     = COLOR
   integral         = limits nolimits autolimits displaylimits zadny
   stylealternative = NAME
   implicitni       = normalni kurziva
   fraction         = ams ctx

```

`\setupmathfence [...1,...] [...2,...]`
OPT

```

1  NAME

2  prikaz           = ano ne
   vlevo            = NUMMER
   stredni          = NUMMER
   vpravo           = NUMMER
   mathstyle        = obrazovka text script scriptscript cramped uncramped normalni zhustene male velke
   barva            = COLOR
   status           = auto
   faktor           = auto zadny cislo

```

`\setupmathfraction [...1,...] [...2,...]`
OPT

```

1  NAME

2  vzdalenostvrsku = DIMENSION
   vzdalenostspodku = DIMENSION
   marginalie      = DIMENSION
   barva           = COLOR
   strut           = ano ne math tight
   alternativa     = uvnitr vnejsi obe
   linka           = ano ne auto
   vlevo           = NUMMER
   vpravo          = NUMMER
   tloustkalinky   = DIMENSION
   mathstyle       = STYLE BEFEHL
   vzdalenost      = ne zadny prekryv

```

`\setupmathframed [...1,...] [...2,...]`
OPT

```

1  NAME

2  inherits: \nastavoramovani

```

`\setupmathmatrix [...1,...] [...2,...]`
OPT

```

1  NAME

2  vlevo           = BEFEHL
   vpravo          = BEFEHL
   strut           = ano ne NUMMER
   zarovnani       = vlevo nastred vpravo normalni
   pismeno         = STYLE BEFEHL
   vzdalenost      = DIMENSION
   misto           = vrsek spodek vysoko nizko nivvy normalni

```

`\setupmathornament [...,1...] [...,2...,...]`
OPT

1 NAME
 2 alternativa = mp
 barva = COLOR
 mpoffset = DIMENSION
 mp = NAME

`\setupmathradical [...,1...] [...,2...,...]`
OPT

1 NAME
 2 alternativa = implicitni normalni mp
 barva = COLOR
 mpoffset = DIMENSION
 mp = NAME

`\setupmathstackers [...,1...] [...,2...,...]`
OPT

1 NAME
 2 vlevo = BEFEHL
 vpravo = BEFEHL
 topcommand = \...##1
 bottomcommand = \...##1
 middlecommand = \...##1
 mp = NAME
 mpheight = DIMENSION
 mpdepth = DIMENSION
 mpoffset = DIMENSION
 barva = COLOR
 hoffset = DIMENSION
 voffset = DIMENSION
 minvyska = DIMENSION
 mindepth = DIMENSION
 mathclass = rel ord
 offset = min max normalni
 misto = vrsek spodek vysoko nizko nastred NUMBER
 strut = ano ne
 alternativa = normalni implicitni mp
 minsirka = DIMENSION
 vzdalenost = DIMENSION
 moffset = DIMENSION
 order = normalni reverse
 mathlimits = ano ne

`\setupmathstyle [...,*,...]`

* obrazovka text script scriptscript cramped uncramped normalni zhustene male velke NAME

`\setupmixedcolumns [...,1...] [...,2...,...]`
OPT

1 NAME
 2 mrizka = inherits: \definegridsnapping
 tloustkalinky = DIMENSION
 metoda = otr box
 pred = BEFEHL
 po = BEFEHL
 vzdalenost = DIMENSION
 n = NUMMER
 maxvyska = DIMENSION
 maxsirka = DIMENSION
 krok = DIMENSION
 profile = NAME
 zarovnani = inherits: \nastavzarovnani
 setups = NAME
 rovnovaha = ano ne
 splitmethod = zadny fixne
 alternativa = lokalne globalne
 internalgrid = radek pulradku
 oddelovac = linka
 strut = ano ne
 barva = COLOR
 barvalinky = COLOR
 smer = normalni reverse
 inherits: \nastavoramovani

```
\setupmodule [...]1 [...]2...,...]
```

OPT

```
1 FILE
2 test = ano ne
   KEY = VALUE
```

```
\setupnotation [...]1 [...]2...,...]
```

OPT

```
1 NAME
2 titul = ano ne
   cislo = ano ne
   typ = note
   ciselnyprikaz = \...##1
   vzdalenosttitulek = DIMENSION
   styltitulek = STYLE BEFEHL
   barvatitulek = COLOR
   titlecommand = \...##1
   titleleft = BEFEHL
   titleright = BEFEHL
   vlevo = BEFEHL
   vpravo = BEFEHL
   symbol = BEFEHL
   starter = BEFEHL
   predel = BEFEHL
   propojeni = NAME
   counter = NAME
   uroven = NUMMER
   text = TEXT
   headcommand = \...##1
   pred = BEFEHL
   po = BEFEHL
   mezi = BEFEHL
   alternativa = vlevo vpravo naokrajji ivlevo ivpravo marginalie lev yokraj prav yokraj innermargin outermargin
                  semknuto visici vrsek prikaz note NAME
   zarovnnani = inherits: \nastavzarovnnani
   headalign = inherits: \nastavzarovnnani
   odsazovani = inherits: \nastavodsazovani
   obrazovka = ano ne
   odsadpristi = ano ne auto
   sirka = prizpusobive siroky radek DIMENSION
   vzdalenost = zadny DIMENSION
   zaveseni = prizpusobive siroky zadny marginalie NUMMER
   closesymbol = BEFEHL
   closecommand = \...##1
   expanzen = ano ne xml
   referenceprefix = + - TEXT
   vzor = TEXT
   marginalie = ano ne standardni DIMENSION
   pismo = STYLE BEFEHL
   barva = COLOR
   stylhlavicky = STYLE BEFEHL
   barvahlavicky = COLOR
   inherits: \setupcounter
```

```
\setupnotations [...]1 [...]2...,...]
```

OPT

```
1 NAME
2 inherits: \setupnotation
```

\setupnote [...,¹...] [...,²...] OPT

```

1  NAME

2  interakce      = ano ne cislo text vse
   symbolcommand  = \...##1
   textovyprikaz  = \...##1
   indikator      = ano ne
   oddelovactextu = BEFEHL
   sirka          = DIMENSION
   vyska          = DIMENSION
   vzdalenost     = DIMENSION
   rulecommand    = BEFEHL
   linka          = zap vyp normalni vlevo vpravo prikaz odstavec
   split          = tolerantni striktni velmistriktni NUMMER
   faktor         = NUMMER
   misto          = text stranka vysoko spodek zadny sloupce firstcolumn lastcolumn
   dalsi          = BEFEHL
   n              = NUMMER
   barvalinky     = COLOR
   tloustkalinky  = DIMENSION
   setups         = NAME
   meziradkovamezera = NAME
   odstavec       = ano ne
   pred           = BEFEHL
   po             = BEFEHL
   mezi           = BEFEHL
   rozsah         = stranka
   vzdalenostsloupcu = DIMENSION
   pokracovat     = ano ne
   alternativa    = mrizka fixne sloupce note zadny
   kriterium      = stranka
   zakladnifont   = inherits: \nastavzakladnifont
   zarovnnani     = inherits: \nastavzarovnnani
   styltextu      = STYLE BEFEHL
   barvatextu     = COLOR
   anchor         = dalsi
   inherits: \nastavoramovani

```

\setupnotes [...,¹...] [...,²...] OPT

```

1  NAME

2  inherits: \setupnote

```

\setupoffset [...,^{*}...]

```

*  inherits: \setupoffsetbox

```

\setupoffsetbox [...,^{*}...]

```

*  x              = DIMENSION
   y              = DIMENSION
   levyoffset     = DIMENSION
   pravyoffset    = DIMENSION
   offsetvrsku    = DIMENSION
   offsetspodku   = DIMENSION
   metoda        = fixe
   sirka          = DIMENSION
   vyska          = DIMENSION
   hloubka        = DIMENSION
   misto          = vlevo nastred vpravo vrsek spodek radek l c r m t b g

```

\setupoutputroutine [...,¹...] [...,²...] OPT

```

1  NAME

2  KEY = CSNAME

```

\setupoutputroutine [...]

```

*  NAME

```


`\setuppagegrid [...1,...] [...2,...]`
OPT

1 NAME
2 n = NUMMER
nvlevo = NUMMER
nvpravo = NUMMER
sirka = DIMENSION auto
vzdalenost = DIMENSION
radky = NUMMER
maxsirka = DIMENSION
maxvyska = DIMENSION
smer = normalni reverse
stranka = inherits: \strana
inherits: \nastavoramovani

`\setuppagegridarea [...1,...] [...2,...]`
OPT

1 NAME
2 status = start stop opakovat
x = NUMMER
y = NUMMER
nx = NUMMER
ny = NUMMER
pismo = STYLE BEFEHL
barva = COLOR
clipoffset = DIMENSION
pravyoffset = DIMENSION
inherits: \nastavoramovani

`\setuppagegridareatext [...1] [...2]`

1 NAME
2 TEXT

`\setuppagegridlines [...1] [...2] [...3] [...4]`

1 NAME
2 NUMMER
3 NUMMER
4 NUMMER

`\setuppagegridspan [...1,...] [...2,...]`
OPT

1 NAME
2 n = NUMMER
pismo = STYLE BEFEHL
barva = COLOR
pred = BEFEHL
po = BEFEHL
inherits: \nastavoramovani

`\setuppagegridstart [...1] [...2] [...3] [...4]`

1 NAME
2 NUMMER
3 NUMMER
4 NUMMER

`\setuppagechecker [...1,...] [...2,...]`
OPT

1 NAME
2 radky = NUMMER
offset = DIMENSION
metoda = 0 1 2 3
pred = BEFEHL
po = BEFEHL
mezi = BEFEHL

\setuppageinjection [...,¹...] [...,²...,...]
OPT

1 NAME
2 status = predchozi dalsi NUMMER
prodleva = ano ne
alternativa = obrazek buffer setups zadny NAME
stranka = inherits: \strana
pagestate = start stop
n = NUMMER
inherits: \nastavoramovani

\setuppageinjectionalternative [...,¹...] [...,²...,...]
OPT

1 NAME
2 renderingsetup = NAME

\setuppageshift [...,¹...] [...,²...] [...,³...]
OPT OPT

1 stranka papir
2 NAME
3 NAME

\setuppagestate [...,¹...] [...,²...,...]
OPT

1 NAME
2 prodleva = ano ne

\setuppairedbox [...,¹...] [...,²...,...]
OPT

1 NAME
2 pred = BEFEHL
po = BEFEHL
mezi = BEFEHL
misto = vlevo nastred vpravo vrsek spodek vysoko nizko
n = NUMMER
vzdalenost = DIMENSION
zakladnifont = inherits: \nastavzakladnifont
sirka = DIMENSION
vyska = DIMENSION
maxsirka = DIMENSION
maxvyska = DIMENSION
zarovnani = inherits: \nastavzarovnani
pismo = STYLE BEFEHL
barva = COLOR

\nastaveniPAIREDBOX [...,^{*}...,...]

* inherits: \setuppairedbox

instances:

\setuppaper [...,^{*}...,...]

* inherits: \nastavvelikostpapiru

\setupparagraph [...,¹...] [...,²...,...]
OPT

1 NAME
2 pismo = STYLE BEFEHL
barva = COLOR
zarovnani = inherits: \nastavzarovnani
setups = NAME

`\setupparagraphintro [...1,...] [...2]`

1 reset kazdy prvni dalsi
2 BEFEHL

`\setupparallel [...1] [...2,...] [...3...,...]`

1 NAME
2 NAME
3 setups = NAME
start = NUMMER
n = NUMMER
kriterium = vse

`\setupperiods [...*...,...]`

* n = NUMMER
sirka = DIMENSION prizpusobive
vzdalenost = DIMENSION
symbol = BEFEHL

`\setupplacement [...1,...] [...2...,...]`
OPT

1 NAME
2 pred = BEFEHL
po = BEFEHL
vlevo = BEFEHL
vpravo = BEFEHL
mrizka = inherits: \snaptogrid
korekceradku = zap vyp
korekcehloubky = zap vyp
marginalie = ano ne standardni

`\setuppositionbar [...*...,...]`

* pismeno = STYLE BEFEHL
barva = COLOR
n = NUMMER
min = NUMMER
max = NUMMER
text = TEXT
sirka = DIMENSION
vyska = DIMENSION
hloubka = DIMENSION

`\setupprocessor [...1,...] [...2...,...]`
OPT

1 NAME
2 status = start stop
vlevo = BEFEHL
vpravo = BEFEHL
prikaz = \...##1
pismeno = STYLE BEFEHL
barva = COLOR

`\setupprofile [...1,...] [...2...,...]`
OPT

1 NAME
2 vyska = DIMENSION
hloubka = DIMENSION
vzdalenost = DIMENSION
faktor = NUMMER
radky = NUMMER
metoda = striktni fixne zadny

`\setupquotation [...*...,...]`

* inherits: \setupdelimitedtext

\setuprealpagenumber [...,*...,...]

* inherits: \setupcounter

\setupreferenceformat [...,¹...] [...,²...] [...,³...,...]
OPT

1 NAME

2 popisek = * NAME
vlevo = BEFEHL
vpravo = BEFEHL
typ = implicitni text titul cislo stranka realpage
setups = NAME
autocase = ano ne
text = TEXT
pismeno = STYLE BEFEHL
barva = COLOR

\setupreferenceprefix [...]

* + - TEXT

\setupreferencestructureprefix [...¹] [...²] [...,³...,...]
OPT OPT

1 NAME ABSCHNITT

2 implicitni

3 prefix = ano ne
prefixseparatorset = NAME
prefixconversion = NAME
prefixconversionset = NAME
prefixstarter = BEFEHL PROCESSOR->BEFEHL
prefixstopper = BEFEHL PROCESSOR->BEFEHL
prefixset = NAME
prefixsegments = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:* ABSCHNITT:vse
numberconversion = NAME
numberconversionset = NAME
numberstarter = BEFEHL PROCESSOR->BEFEHL
numberstopper = BEFEHL PROCESSOR->BEFEHL
numbersegments = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse
numberseparatorset = NAME
prefixconnector = BEFEHL PROCESSOR->BEFEHL

\setupregisters [...¹] [...,²...,...]
OPT

1 NAME NAME:NUMMER

2 inherits: \nastavrejstrik

\setupregisters [...,¹...] [...,²...] [...,³...,...]
OPT OPT

1 NAME

2 NUMMER

3 inherits: \nastavrejstrik

\setuprenderingwindow [...,¹...] [...,²...,...]
OPT

1 NAME

2 akceotevrenistranky = REFERENCE
akcezavrenistranky = REFERENCE
inherits: \nastavoramovani

\setups [...,*...,...]

* NAME

\setupscale [...¹,...] [...²,...] OPT

```

1  NAME

2  meritko      =  NUMMER
   xmeritko     =  NUMMER
   ymeritko     =  NUMMER
   sirka        =  DIMENSION
   vyska        =  DIMENSION
   hloubka      =  ano ne
   radky        =  NUMMER
   faktor       =  prizpusobive siroky max auto implicitni
   vfaktor      =  prizpusobive siroky max auto implicitni
   sfaktor      =  prizpusobive siroky max auto implicitni
   maxsirka     =  DIMENSION
   maxvyska     =  DIMENSION
   s            =  NUMMER
   sx           =  NUMMER
   sy           =  NUMMER
   equalwidth   =  DIMENSION
   equalheight  =  DIMENSION
   mrizka       =  ano prizpusobive vyska podlehloubky pulradku

```

\setupsript [...¹,...] [...²,...] OPT

```

1  NAME

2  metoda      =  hangul hanzi nihongo ethiopic thai test
   prednastaveni =  NAME
   features     =  auto

```

\setupscripts [...¹,...] [...²,...] OPT

```

1  NAME

2  inherits: \setupsript

```

\setupselector [...¹,...] [...²,...] OPT

```

1  NAME

2  n =  NUMMER
   m =  NUMMER

```

\setupshift [...¹,...] [...²,...] OPT

```

1  NAME

2  pokracovat =  ano ne
   jednotka  =  ex em pt in cm mm sp bp pc dd cc nc
   metoda    =  NUMMER
   dy        =  NUMMER
   zarovnani =  inherits: \nastavzarovnani
   pismeno   =  STYLE BEFEHL
   barva     =  COLOR

```

\setupsidebar [...¹,...] [...²,...] OPT

```

1  NAME

2  tloustkalinky =  DIMENSION
   barvalinky    =  COLOR
   alternativa   =  NUMMER
   offsetvrsku   =  DIMENSION
   offsetspodku  =  DIMENSION
   vzdalenost    =  DIMENSION
   vzdalenostlevehookraje =  DIMENSION
   uroven        =  NUMMER

```

\setupsPELLchecking [...^{*},...] OPT

```

*  status =  start stop
   metoda =  1 2 3
   seznam =  NAME

```

`\setupstartstop [...,1...] [...,2...,...]`
OPT

```
1 NAME
2 pred = BEFEHL
  po = BEFEHL
  mezi = BEFEHL
  setups = NAME
  vlevo = BEFEHL
  vpravo = BEFEHL
  pismo = STYLE BEFEHL
  barva = COLOR
```

`\setupstretched [...,*...,...]`

* inherits: \setupcharacterkerning

`\setupstruts [...]`
OPT

* ano ne auto kap prizpusobive radek implicitni CHARACTER

`\setupstyle [...,1...] [...,2...,...]`
OPT

```
1 NAME
2 metoda = prikaz
  pismo = STYLE BEFEHL
  barva = COLOR
```

`\setupsbformula [...,1...] [...,2...,...]`
OPT

```
1 NAME
2 odsadpristi = ano ne auto
```

`\setups {...,*...}`

* NAME

`\setupTABLE [...,1...] [...,2...] [...,3...,...]`
OPT OPT OPT

```
1 r c x y row column prvni posledni start zahlavi kazdy liche sude jedna NUMMER -NUMMER
2 prvni least kazdy dve liche sude NUMMER -NUMMER
3 extras = BEFEHL
  vlevo = BEFEHL
  vpravo = BEFEHL
  barvahlavicky = COLOR
  stylhlavicky = STYLE BEFEHL
  vzdalenostlevehookraje = DIMENSION
  vzdalenostpravehookraje = DIMENSION
  vzdalenostsloupcu = DIMENSION
  maxsirka = DIMENSION
  setups = NAME
  sirkatextu = DIMENSION lokalne
  split = ano ne opakovat auto
  zahlavi = opakovat
  volba = natahnout tight
  pred = BEFEHL
  po = BEFEHL
  stejnastranka = pred po obe
  spaceinbetween = inherits: \preskoc
  splitoffset = DIMENSION
  aligncharacter = ano ne
  alignmentcharacter = TEXT number->TEXT text->TEXT
  vzdalenost = DIMENSION
  barva = COLOR
  pismo = math STYLE BEFEHL
  inherits: \nastavoramovani
```

`\setupTEXpage [...,*...,...]`

* inherits: \setupfittingpage

`\setuptabulation [...1,...] [...2,...]`
OPT

```

1  NAME

2  formatovat    =  TEMPLATE zadny
   pred         =  BEFEHL
   po           =  BEFEHL
   vzdalenost    =  male stredni velke zadny prazdny podlehloubky mrizka DIMENSION
   zarovnani     =  vlevo nastred vpravo dimension
   linka        =  radek normalni
   barvalinky    =  COLOR
   tloustkalinky =  DIMENSION
   zakladnifont  =  inherits: \nastavzakladnifont
   odsazovani   =  ano ne
   split        =  ano ne opakovat auto
   jednotka     =  DIMENSION
   marginalie    =  DIMENSION
   vnitrni      =  BEFEHL
   EQ           =  BEFEHL
   zahlavi      =  ano opakovat text
   ramecek      =  zap vyp
   titul        =  TEXT
   keptogether  =  ano ne

```

`\setuptagging [...*,...]`

```

*  status = start stop
   metoda = auto

```

`\setuptextbackground [...1,...] [...2,...]`
OPT

```

1  NAME

2  status        =  start stop
   misto         =  text odstavec zadny
   alternativa   =  NUMMER
   mp            =  NAME
   metoda        =  NAME
   pozadi        =  barevne
   barvapozadi   =  COLOR
   roh           =  pravouhly zaobleny
   uroven        =  NUMMER
   offsetpozadi  =  DIMENSION
   pred         =  BEFEHL
   po            =  BEFEHL
   zarovnani     =  inherits: \nastavzarovnani
   pomlcka       =  NUMMER
   polomer       =  DIMENSION
   ramecek       =  zap vyp
   barvaramecku  =  COLOR
   tloustkalinky =  DIMENSION
   voffset       =  DIMENSION
   offsetramecku =  DIMENSION
   levyoffset    =  ano ne standardni DIMENSION
   pravyoffset   =  ano ne standardni DIMENSION
   offsetvrsku   =  male stredni velke radek DIMENSION
   offsetspodku  =  male stredni velke radek DIMENSION
   pismo         =  STYLE BEFEHL
   barva         =  COLOR

```

`\setuptextflow [...1,...] [...2,...]`
OPT

```

1  NAME

2  sirka    =  DIMENSION
   pismo    =  STYLE BEFEHL
   barva    =  COLOR

```

`\setuptooltip [...1,...] [...2,...]`
OPT

```

1  NAME

2  misto = vlevo nastred vpravo
   inherits: \nastavoramovani

```

`\setupunit [...1,...] [...2,...]`
OPT

1 NAME

2 metoda = 1 2 3 4 5 6
 language = SPRACHE
 alternativa = text matematika
 order = reverse normalni
 oddelovac = male stredni velke normalni zadny NAME
 mezera = male stredni velke normalni zadny NAME
 pismo = STYLE BEFEHL
 barva = COLOR

`\setupuserpagenumber [...*,...]`

* viewerprefix = TEXT
 status = start stop zadny drzet prazdne
 inherits: \setupcounter

`\setupversion [...]`

* koncept soubor docasne finalni NAME

`\setupviewerlayer [...*,...]`

* titul = TEXT
 status = start stop
 export = ano ne
 tisknutelne = ano ne
 rozsah = lokalne globalne
 metoda = zadny prikaz

`\setupvspacing [...*,...]`
OPT

* inherits: \vspacing

`\setupwithargument {...1} {...2}`

1 NAME
 2 CONTENT

`\setupwithargumentswapped {...1} {...2}`

1 CONTENT
 2 NAME

`\setupxml [...*,...]`

* implicitni = skryte zadny text
 compress = ano ne

`\setupxtable [...1,...] [...2,...]`
OPT

1 NAME

2 sirkatextu = DIMENSION lokalne
 zakladnifont = inherits: \nastavzakladnifont
 spaceinbetween = inherits: \preskoc
 volba = tight max natahnout sirka vyska fixne
 vyskatextu = DIMENSION
 maxsirka = DIMENSION
 vzdalenostsloupcu = DIMENSION
 vzdalenostlevehookraje = DIMENSION
 vzdalenostpravehookraje = DIMENSION
 zahlavi = opakovat
 upati = opakovat
 tloustkalinky = DIMENSION
 split = ano ne opakovat auto
 splitoffset = DIMENSION
 stejnastranka = pred po obe
 vzdalenost = DIMENSION
 inherits: \nastavoramovani

\setuvalue ¹{...} ²{...}

- 1 NAME
- 2 CONTENT

\setuxvalue ¹{...} ²{...}

- 1 NAME
- 2 CONTENT

\setvalue ¹{...} ²{...}

- 1 NAME
- 2 CONTENT

\setvariable ¹{...} ²{...} ³{...}

- 1 NAME
- 2 KEY
- 3 VALUE

\setvariables [¹...] [²...,...]

- 1 NAME
- 2

set	=	BEFEHL
reset	=	BEFEHL
KEY	=	VALUE

\setvboxregister ¹... ²{...}

- 1 CSNAME NUMBER
- 2 CONTENT

\setvisualizerfont [^{*}...]
OPT

- * FONT

\setvtopregister ¹... ²{...}

- 1 CSNAME NUMBER
- 2 CONTENT

\setwidthof ¹... \to ²...

- 1 TEXT
- 2 CSNAME

\setxmeasure ¹{...} ²{...}

- 1 NAME
- 2 DIMENSION

\setxvalue ¹{...} ²{...}

- 1 NAME
- 2 CONTENT

<pre>\setxvariable {...} {...} {...}</pre> <p>1 NAME</p> <p>2 KEY</p> <p>3 VALUE</p>
<pre>\setxvariables [...] [...,...²...,...]</pre> <p>1 NAME</p> <p>2 set = BEFEHL reset = BEFEHL KEY = VALUE</p>
<pre>\sfrac {...} {...}</pre> <p>1 CONTENT</p> <p>2 CONTENT</p>
<pre>\shapedhbox {...}</pre> <p>* CONTENT</p>
<pre>\SHIFT {...}</pre> <p>* CONTENT</p> <p>instances:</p>
<pre>\showallmakeup</pre>
<pre>\showattributes</pre>
<pre>\showboxes</pre>
<pre>\showbtxdatasetauthors [...,...[*]...,...]</pre> <p style="text-align: center;">OPT</p> <p>* specification = NAME dataset = NAME field = address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME</p>
<pre>\showbtxdatasetauthors [...]</pre> <p style="text-align: center;">OPT</p> <p>* NAME</p>
<pre>\showbtxdatasetcompleteness [...,...[*]...,...]</pre> <p style="text-align: center;">OPT</p> <p>* specification = NAME dataset = NAME field = address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME</p>
<pre>\showbtxdatasetcompleteness [...]</pre> <p style="text-align: center;">OPT</p> <p>* NAME</p>

<pre> \showbtxdatasetfields [...,..[*]...,...] OPT * specification = NAME dataset = NAME field = address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME </pre>
<pre> \showbtxdatasetfields [...] OPT * NAME </pre>
<pre> \showbtxfields [...,..[*]...,...] OPT * rotace = NUMMER specification = NAME </pre>
<pre> \showbtxfields [...] OPT * NAME </pre>
<pre> \showbtxhashedauthors [...] OPT * TEXT </pre>
<pre> \showbtxtables [...] OPT * TEXT </pre>
<pre> \showcolorbar [...] * COLOR </pre>
<pre> \showcolorcomponents [...] * COLOR </pre>
<pre> \showcolorset [...] * COLOR </pre>
<pre> \showcolorstruts </pre>
<pre> \showcounter [...] * NAME </pre>
<pre> \showdirectives </pre>
<pre> \showdirsmargin </pre>
<pre> \showedebuginfo </pre>
<pre> \showexperiments </pre>
<pre> \showfont [...¹] [...,²...] OPT 1 FONT 2 NUMMER </pre>
<pre> \showfontdata </pre>

<code>\showfontkerns</code>
<code>\showfontparameters</code>
<code>\showfontstrip [...*,...]</code> <code>* inherits: \nastavzakladnifont</code>
<code>\showfontstyle [...¹,...]_{OPT} [...²,...]_{OPT} [...³,...]_{OPT} [...⁴,...]_{OPT}</code> <code>1 inherits: \nastavzakladnifont</code> <code>2 rm ss tt mm hw cg</code> <code>3 tf bf it sl bi bs</code> <code>4 vse NUMBER</code>
<code>\showglyphs</code>
<code>\showgridsnapping</code>
<code>\showhelp {...¹} [...²]</code> <code>1 TEXT</code> <code>2 REFERENCE</code>
<code>\showhyphenationtrace [...¹]_{OPT} [...²]</code> <code>1 SPRACHE</code> <code>2 TEXT</code>
<code>\showhyphens {...}</code> <code>* TEXT</code>
<code>\showchardata {...}</code> <code>* TEXT</code>
<code>\showcharratio {...}</code> <code>* TEXT</code>
<code>\showinjector [...*,...]_{OPT}</code> <code>* NAME</code>
<code>\showjustification</code>
<code>\showkerning {...}</code> <code>* TEXT</code>
<code>\showlayoutcomponents</code>
<code>\showligature {...}</code> <code>* TEXT</code>

\showligatures [...] * FONT
\showlogcategories
\showmargins
\showmessage { ¹ .} { ² .} { ³ ...,...} 1 NAME 2 NAME NUMBER 3 TEXT
\showminimalbaseline
\shownextbox \ ¹ ... { ² .} 1 CSNAME 2 CONTENT
\showotfcomposition { ¹ .} { ² .} { ³ .} 1 FONT 2 -1 1 +1 l2r r2l 3 TEXT
\showparentchain \ ¹ ... { ² .} 1 CSNAME 2 NAME
\showsetupsdefinition [...] * NAME
\showtimer {.*} * TEXT
\showtokens [...] * NAME
\showtrackers
\showvalue {.*} * NAME
\showvariable { ¹ .} { ² .} 1 NAME 2 KEY

`\showwarning {...} {...} {...,3...}`

1 NAME

2 NAME NUMBER

3 TEXT

`\schovejbloky [...,1...] [...,2...]`
OPT

1 NAME

2 + -

`\simplealignedbox {...} {...} {...}`

1 DIMENSION

2 vlevo vpravo nastred flushleft flushright uvnitr vnejsi

3 CONTENT

`\simplealignedboxplus {...} {...} {...} {...}`

1 DIMENSION

2 vlevo vpravo nastred flushleft flushright uvnitr vnejsi

3 TEXT

4 CONTENT

`\simplealignedspreadbox {...} {...} {...}`

1 DIMENSION

2 vlevo vpravo nastred flushleft flushright uvnitr vnejsi

3 CONTENT

`\simplegroupedcommand {...} {...}`

1 BEFEHL

2 BEFEHL

`\simplereversealignedbox {...} {...} {...}`

1 DIMENSION

2 vlevo vpravo nastred flushleft flushright uvnitr vnejsi

3 CONTENT

`\simplereversealignedboxplus {...} {...} {...} {...}`

1 DIMENSION

2 vlevo vpravo nastred flushleft flushright uvnitr vnejsi

3 TEXT

4 CONTENT

`\singalcharacteralign {...} {...}`

1 NUMMER

2 NUMMER

`\singlebond`

<p><code>\sixthofsixarguments {...} {...} {...} {...} {...} {...}</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 TEXT</p> <p>4 TEXT</p> <p>5 TEXT</p> <p>6 TEXT</p>
<code>\sklonene</code>
<code>\sklonenetucne</code>
<p><code>\slicepages [...]¹ [...,²...,...]_{OPT} [...,³...,...]_{OPT}</code></p> <p>1 FILE</p> <p>2 offset = DIMENSION hoffset = DIMENSION voffset = DIMENSION sirka = DIMENSION vyska = DIMENSION n = NUMMER</p> <p>3 offset = DIMENSION hoffset = DIMENSION voffset = DIMENSION sirka = DIMENSION vyska = DIMENSION n = NUMMER</p>
<p><code>\sloupec [...,^{OPT}...]</code></p> <p>* inherits: \columnbreak</p>
<p><code>\slovenianNumerals {...}</code></p> <p>* NUMMER</p>
<p><code>\sloveniannumerals {...}</code></p> <p>* NUMMER</p>
<p><code>\slovo {...}</code></p> <p>* TEXT</p>
<p><code>\slovovpravo [...]¹ [...]²</code> _{OPT}</p> <p>1 vpravo DIMENSION</p> <p>2 CONTENT</p>
<code>\smallbodyfont</code>
<p><code>\smallcappedcharacters {...}</code></p> <p>* NUMMER</p>
<p><code>\smallcappedromannumerals {...}</code></p> <p>* NUMMER</p>
<code>\smaller</code>

<code>\smallskip</code>
<code>\smash [...]¹ {...}²</code> <small>OPT</small> 1 <code>w h d t b</code> 2 <code>CONTENT</code>
<code>\smashbox ...</code> * <code>CSNAME NUMMER</code>
<code>\smashboxed ...</code> * <code>CSNAME NUMMER</code>
<code>\smashedhbox ...¹ {...}²</code> <small>OPT</small> 1 <code>TEXT</code> 2 <code>CONTENT</code>
<code>\smashedvbox ...¹ {...}²</code> <small>OPT</small> 1 <code>TEXT</code> 2 <code>CONTENT</code>
<code>\saptogrid [...]¹ \... {...}² {...}³</code> <small>OPT</small> 1 normalni standardni ano striktni tolerantni vrsek spodek obe široky prizpusobive prvni posledni vysoko jedna nizko zadny radek strut box min max nastred NAME 2 <code>CSNAME</code> 3 <code>CONTENT</code>
<code>\saptogrid [...]¹, [...] \... {...}² {...}³</code> <small>OPT</small> 1 <code>inherits: \definegridsnapping</code> 2 <code>CSNAME</code> 3 <code>CONTENT</code>
<code>\someheadnumber [...]¹ [...]²</code> 1 <code>ABSCHNITT</code> 2 predchozi aktualni dalsi prvni posledni
<code>\somekindoftab [...]¹, [...]², [...]³</code> <small>OPT</small> * <code>alternativa = horizontalne vertikalne</code> <code>sirka = DIMENSION</code> <code>vyska = DIMENSION</code> <code>n = NUMMER</code> <code>m = NUMMER</code>
<code>\somalocalfloat</code>
<code>\somenamedheadnumber {...}¹ {...}²</code> 1 <code>ABSCHNITT</code> 2 predchozi aktualni dalsi prvni posledni

`\someplace {1...} {2...} {3...} {4...} {5...} [6...]`

- 1 TEXT
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT
- 6 REFERENCE

`\SORTING [1...] {2...}`
OPT

- 1 NAME
- 2 CONTENT

instances:

`\spanishNumerals {*...}`

- * NUMMER

`\spanishnumerals {*...}`

- * NUMMER

`\speech [1...] {2...}`
OPT

- 1 SPRACHE
- 2 CONTENT

`\splitatasterisk 1... \2... \3...`

- 1 TEXT
- 2 CSNAME
- 3 CSNAME

`\splitatcolon 1... \2... \3...`

- 1 TEXT
- 2 CSNAME
- 3 CSNAME

`\splitatcolons 1... \2... \3...`

- 1 TEXT
- 2 CSNAME
- 3 CSNAME

`\splitatcomma 1... \2... \3...`

- 1 TEXT
- 2 CSNAME
- 3 CSNAME

`\splitdfrac {1...} {2...}`

- 1 CONTENT
- 2 CONTENT

<code>\splitfilename {...}</code> * FILE
<code>\splitfrac {...} {...}</code> 1 CONTENT 2 CONTENT
<code>\splitoffbase</code>
<code>\splitofffull</code>
<code>\splitoffkind</code>
<code>\splitoffname</code>
<code>\splitoffpath</code>
<code>\splitoffroot</code>
<code>\splitofftokens ... \from ... \to ...</code> 1 TEXT 2 TEXT 3 CSNAME
<code>\splitofftype</code>
<code>\splitstring ... \at ... \to ... \and ...</code> 1 TEXT 2 TEXT 3 CSNAME 4 CSNAME
<code>\spreadhbox ...</code> * CSNAME NUMMER
<code>\sqrt [...]¹ {...}²</code> <small>OPT</small> 1 TEXT 2 CONTENT
<code>\stackrel {...} {...}</code> 1 CONTENT 2 CONTENT
<code>\stanovcislonaadpisu [...]</code> * ABSCHNITT

$\backslash\text{stanovcharakteristikuseznamu}$ [..., ¹ ...] [..., ² _{OPT} ...] 1 LISTE 2 inherits: \nastavseznam
$\backslash\text{startalignment}$ [...,*...] ... $\backslash\text{stopalignment}$ * inherits: \nastavzarovnani
$\backslash\text{startallmodes}$ [...,*...] ... $\backslash\text{stopallmodes}$ * NAME
$\backslash\text{startaside}$ [... ¹ ...] [..., ² _{OPT} ...] ... $\backslash\text{stopaside}$ 1 SPRACHE 2 inherits: \startzuzeni
$\backslash\text{startattachment}$ [... ¹ ...] [..., ² _{OPT} ...] ... $\backslash\text{stopattachment}$ 1 NAME 2 inherits: \setupattachment
$\backslash\text{startATTACHMENT}$ [... ¹ ...] [..., ² _{OPT} ...] ... $\backslash\text{stopATTACHMENT}$ 1 NAME 2 inherits: \setupattachment instances: attachment
$\backslash\text{startbar}$ [...*] ... $\backslash\text{stopbar}$ * NAME
$\backslash\text{startbarva}$ [...*] ... $\backslash\text{stopbarva}$ * COLOR
$\backslash\text{startbitmapimage}$ [..., [*] ...] ... $\backslash\text{stopbitmapimage}$ * barva = rgb cmyk seda * sirka = DIMENSION * vyska = DIMENSION * x = NUMMER * y = NUMMER
$\backslash\text{startblockquote}$ [... ¹ ...] [..., ² _{OPT} ...] ... $\backslash\text{stopblockquote}$ 1 SPRACHE 2 inherits: \startzuzeni
$\backslash\text{startbtxrenderingdefinitions}$ [...*] ... $\backslash\text{stopbtxrenderingdefinitions}$ * NAME
$\backslash\text{startbuffer}$ [... [*]] _{OPT} ... $\backslash\text{stopbuffer}$ * NAME
$\backslash\text{startBUFFER}$... $\backslash\text{stopBUFFER}$ instances: skryt

<code>\startcatcodetable *... \stopcatcodetable</code> <code>* CSNAME</code>
<code>\startcenteraligned ... \stopcenteraligned</code>
<code>\startcitace [¹...] [²...] ... \stopcitace</code> <code> OPT OPT</code> <code>1 SPRACHE</code> <code>2 inherits: \startzuzeni</code>
<code>\startcitovat [¹...] ... \stopcitovat</code> <code> OPT</code> <code>* SPRACHE</code>
<code>\startcollect ... \stopcollect</code>
<code>\startcollecting ... \stopcollecting</code>
<code>\startcolorintent [...]\stopcolorintent</code> <code>* knockout overprint zadny</code>
<code>\startcoloronly [...]\stopcoloronly</code> <code>* COLOR</code>
<code>\startcolorset [...]\stopcolorset</code> <code>* NAME</code>
<code>\startcolumnspan [...]\stopcolumnspan</code> <code> [*]</code> <code> OPT</code> <code>* inherits: \setupcolumnspan</code>
<code>\startcombination [¹...] [²...] ... \stopcombination</code> <code> OPT OPT</code> <code>1 NAME</code> <code>2 inherits: \setupcombination</code>
<code>\startcombination [¹...] [²...] ... \stopcombination</code> <code> OPT OPT</code> <code>1 NAME</code> <code>2 N*M</code>
<code>\startcontextcode ... \stopcontextcode</code>
<code>\startcontextdefinitioncode ... \stopcontextdefinitioncode</code>
<code>\startctxfunction ... \stopctxfunction</code> <code>* NAME</code>
<code>\startctxfunctiondefinition ... \stopctxfunctiondefinition</code> <code>* NAME</code>
<code>\startcurrentcolor ... \stopcurrentcolor</code>
<code>\startcurrentlistentrywrapper ... \stopcurrentlistentrywrapper</code>

$\backslash\startdelimited [^{1}] [^{2}] [^{3},...] \dots \backslash\stopdelimited$ $\begin{array}{c} \text{OPT} \qquad \text{OPT} \\ 1 \quad \text{NAME} \\ 2 \quad \text{SPRACHE} \\ 3 \quad \text{inherits: \startzuzeni} \end{array}$
$\backslash\startdelimitedtext [^{1}] [^{2}] [^{3},...] \dots \backslash\stopdelimitedtext$ $\begin{array}{c} \text{OPT} \qquad \text{OPT} \\ 1 \quad \text{NAME} \\ 2 \quad \text{SPRACHE} \\ 3 \quad \text{inherits: \startzuzeni} \end{array}$
$\backslash\startDELIMITEDTEXT [^{1}] [^{2},...] \dots \backslash\stopDELIMITEDTEXT$ $\begin{array}{c} \text{OPT} \qquad \text{OPT} \\ 1 \quad \text{SPRACHE} \\ 2 \quad \text{inherits: \startzuzeni} \end{array}$ <p>instances: citace citovat blockquote speech aside</p>
$\backslash\startdisplaymath \dots \backslash\stopdisplaymath$
$\backslash\startdmath \dots \backslash\stopdmath$
$\backslash\startdocument [^{1},\dots,^{2},...] \dots \backslash\stopdocument$ $\begin{array}{c} \text{OPT} \\ * \quad \text{inherits: \setupdocument} \end{array}$
$\backslash\starteffect [^{*}] \dots \backslash\stopeffect$ $* \quad \text{NAME}$
$\backslash\startEFFECT \dots \backslash\stopEFFECT$
$\backslash\startelement \{^{1}\} [^{2},\dots,^{2},...] \dots \backslash\stopelement$ $\begin{array}{c} \text{OPT} \\ 1 \quad \text{NAME} \\ 2 \quad \text{KEY} = \text{VALUE} \end{array}$
$\backslash\startembeddedxtable [^{1},\dots,^{2},...] \dots \backslash\stopembeddedxtable$ $\begin{array}{c} \text{OPT} \\ * \quad \text{inherits: \setupxtable} \end{array}$
$\backslash\startembeddedxtable [^{*}] \dots \backslash\stopembeddedxtable$ $\begin{array}{c} \text{OPT} \\ * \quad \text{NAME} \end{array}$
$\backslash\startexceptions [^{*}] \dots \backslash\stopexceptions$ $* \quad \text{SPRACHE}$
$\backslash\startexpanded \dots \backslash\stopexpanded$
$\backslash\startexpandedcollect \dots \backslash\stopexpandedcollect$
$\backslash\startextendedcatcodetable \backslash^{*} \dots \backslash\stopextendedcatcodetable$ $* \quad \text{CSNAME}$

<p><code>\startexternalfigurecollection [...]</code> ... <code>\stopexternalfigurecollection</code></p> <p>* NAME</p>
<p><code>\startfittingpage [...]¹ [...,...²...,...]</code> ... <code>\stopfittingpage</code></p> <p><small>OPT</small></p> <p>1 NAME</p> <p>2 inherits: <code>\setupfittingpage</code></p>
<p><code>\startFITTINGPAGE [...,...[*]...,...]</code> ... <code>\stopFITTINGPAGE</code></p> <p><small>OPT</small></p> <p>* inherits: <code>\setupfittingpage</code></p> <p>instances: TEXpage MPpage</p>
<p><code>\startfloatcombination [...,...[*]...,...]</code> ... <code>\stopfloatcombination</code></p> <p><small>OPT</small></p> <p>* inherits: <code>\setupcombination</code></p>
<p><code>\startfloatcombination [...][*]</code> ... <code>\stopfloatcombination</code></p> <p><small>OPT</small></p> <p>* N*M NAME</p>
<p><code>\startPLVOUCIOBJEKTtext [...,...¹...] [...,...²...] {...³...}</code> ... <code>\stopPLVOUCIOBJEKTtext</code></p> <p><small>OPT OPT</small></p> <p>1 split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji levyokraj pravyokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka zahlavi upati nekde effective</p> <p>2 REFERENCE</p> <p>3 TEXT</p>
<p><code>\startfont [...][*]</code> ... <code>\stopfont</code></p> <p><small>OPT</small></p> <p>* FONT</p>
<p><code>\startfontclass [...]</code> ... <code>\stopfontclass</code></p> <p>* kazdy NAME</p>
<p><code>\startfontsolution [...]</code> ... <code>\stopfontsolution</code></p> <p>* NAME</p>
<p><code>\startframedcontent [...][*]</code> ... <code>\stopframedcontent</code></p> <p><small>OPT</small></p> <p>* NAME vyp</p>
<p><code>\startgridsnapping [...][*]</code> ... <code>\stopgridsnapping</code></p> <p><small>OPT</small></p> <p>* normalni standardni ano striktni tolerantni vrsek spodek obe siroky prizpusobive prvnι posledni vysoko jedna nizko zadny radek strut box min max nastred NAME</p>
<p><code>\startgridsnapping [...,...[*]...] ... \stopgridsnapping</code></p> <p><small>OPT</small></p> <p>* inherits: <code>\definegridsnapping</code></p>
<p><code>\starthboxestohbox ... \stophboxestohbox</code></p>
<p><code>\starthboxregister ... \stophboxregister</code></p> <p>* CSNAME NUMBER</p>

$\backslash startHELP$ [...] ... $\backslash stopHELP$ <small>OPT</small> * REFERENCE instances: textnapovedy
$\backslash starthighlight$ [...] ... $\backslash stophighlight$ * NAME
$\backslash startthyphenation$ [...,*...] ... $\backslash stopthyphenation$ * original tex implicitni hyphenate expanded traditional zadny
$\backslash startcharacteralign$ [...] ... $\backslash stopcharacteralign$ <small>OPT</small> * TEXT number->TEXT text->TEXT
$\backslash startcheckedfences$... $\backslash stopcheckedfences$
$\backslash startchemical$ [¹ ...] [..., ² ... ² ...] ... $\backslash stopchemical$ <small>OPT</small> <small>OPT</small> 1 NAME 2 inherits: $\backslash setupchemical$
$\backslash startimath$... $\backslash stopimath$
$\backslash startindentedtext$ [...] ... $\backslash stopindentedtext$ * NAME
$\backslash startINDENTEDTEXT$... $\backslash stopINDENTEDTEXT$
$\backslash startinterakce$ [...] ... $\backslash stopinterakce$ * skryte NAME
$\backslash startinteraktivnimenu$ [...] ... $\backslash stopinteraktivnimenu$ * NAME
$\backslash startinterface$ $\backslash stopinterface$ * vse SPRACHE
$\backslash startintertext$... $\backslash stopintertext$
$\backslash startitemgroup$ [¹ ...] [..., ² ...] [..., ³ ... ³ ...] ... $\backslash stopitemgroup$ <small>OPT</small> <small>OPT</small> 1 NAME 2 inherits: $\backslash setupitemgroup$ 3 inherits: $\backslash setupitemgroup$
$\backslash startITEMGROUP$ [..., ¹ ...] [..., ² ... ² ...] ... $\backslash stopITEMGROUP$ <small>OPT</small> <small>OPT</small> 1 inherits: $\backslash setupitemgroup$ 2 inherits: $\backslash setupitemgroup$ instances: itemize

<pre> \startJSCode ¹...²...³... \stopJSCode 1 NAME 2 uses 3 NAME </pre>
<pre> \startJSreamble ¹...²...³... \stopJSreamble 1 NAME 2 uzito 3 now later </pre>
<pre> \startjdina [...] ... \stopjdina * REFERENCE </pre>
<pre> \startknockout ... \stopknockout </pre>
<pre> \startkomentar [¹...] [²...²...]^{OPT}... \stopkomentar 1 TEXT 2 inherits: \nastavkomentar </pre>
<pre> \startkomentarstranky ... \stopkomentarstranky </pre>
<pre> \startKOMENTAR [¹...] [²...²...]^{OPT}... \stopKOMENTAR 1 TEXT 2 inherits: \nastavkomentar instances: komentar </pre>
<pre> \startkomponenta [...] ... \stopkomponenta * FILE * </pre>
<pre> \startkomponenta \stopkomponenta * FILE * </pre>
<pre> \startkonectabulky [...] ... \stopkonectabulky * NAME </pre>
<pre> \startlayout [...] ... \stoplayout * NAME </pre>
<pre> \startlinealignment [...] ... \stoplinealignment * vlevo nastred vpravo max </pre>
<pre> \startlinecorrection [...[*]...]^{OPT} ... \stoplinecorrection * prazdny inherits: \preskoc </pre>
<pre> \startlinefiller [¹...] [²...²...]^{OPT} ... \stoplinefiller 1 filler NAME 2 inherits: \setuplinefiller </pre>

<p><code>\startLINENOTE [...]{...}</code></p> <p>1 REFERENCE</p> <p>2 TEXT</p> <p>instances:</p>
<p><code>\startlinenumbering [...]¹ [...,²...,...] ... \stoplinenumbering</code></p> <p>1 NAME</p> <p>2 pokračovat = ano ne start = NUMMER krok = NUMMER metoda = stranka prvni dalsi</p>
<p><code>\startlinenumbering [...]¹ [...]² ... \stoplinenumbering</code></p> <p>1 NAME</p> <p>2 pokračovat NUMMER</p>
<p><code>\startlinetable ... \stoplinetable</code></p>
<p><code>\startlinetablebody ... \stoplinetablebody</code></p>
<p><code>\startlinetablecell [...][*] [...]^{OPT} ... \stoplinetablecell</code></p> <p>* inherits: \setuplinetable</p>
<p><code>\startlinetablehead ... \stoplinetablehead</code></p>
<p><code>\startlocalfootnotes ... \stoplocalfootnotes</code></p>
<p><code>\startlocalheadsetup ... \stoplocalheadsetup</code></p>
<p><code>\startlocallinecorrection [...][*] [...]^{OPT} ... \stoplocallinecorrection</code></p> <p>* prazdny inherits: \preskoc</p>
<p><code>\startlocalnotes [...][*] [...] ... \stoplocalnotes</code></p> <p>* NAME</p>
<p><code>\startlocalsetups [...]¹ [...]² ... \stoplocalsetups</code></p> <p>1 mrizka</p> <p>2 NAME</p>
<p><code>\startlocalsetups \stoplocalsetups</code></p> <p>* NAME</p>
<p><code>\startlua ... \stoplua</code></p>
<p><code>\startluacode ... \stopluacode</code></p>
<p><code>\startluaparameterset [...][*] ... \stopluaparameterset</code></p> <p>* NAME</p>

<pre> \startluasetups [...]¹ [...]² ... \stopluasetups OPT 1 mrizka 2 NAME </pre>
<pre> \startluasetups .* ... \stopluasetups * NAME </pre>
<pre> \startMPclip {...} ... \stopMPclip * NAME </pre>
<pre> \startMPcode {...}[*] ... \stopMPcode OPT * NAME </pre>
<pre> \startMPdefinitions {...}[*] ... \stopMPdefinitions OPT * NAME </pre>
<pre> \startMPdrawing [...][*] ... \stopMPdrawing OPT * - </pre>
<pre> \startMPenvironment [...][*] ... \stopMPenvironment OPT * reset globale + </pre>
<pre> \startMPextensions {...,[*]...}^{OPT} ... \stopMPextensions * NAME </pre>
<pre> \startMPinclusions [...]¹ {...}² ... \stopMPinclusions OPT OPT 1 + 2 NAME </pre>
<pre> \startMPinitializations ... \stopMPinitializations </pre>
<pre> \startMPpage [...,[*]...]^{OPT} ... \stopMPpage * inherits: \setupfittingpage </pre>
<pre> \startMPpositiongraphic {...}¹ {...,²...}^{OPT} ... \stopMPpositiongraphic 1 NAME 2 KEY </pre>
<pre> \startMPpositionmethod {...} ... \stopMPpositionmethod * NAME </pre>
<pre> \startMPrun {...}[*] ... \stopMPrun OPT * NAME </pre>
<pre> \startmarginalnilinka [...][*] ... \stopmarginalnilinka OPT * NUMMER </pre>

$\backslash\mathrm{startmarginalnilinka} [\dots,\overset{*}{=}\dots] \dots \backslash\mathrm{stopmarginalnilinka}$ <p><small>OPT</small></p> <p>* inherits: $\backslash\mathrm{setupmarginrule}$</p>
$\backslash\mathrm{startmarginblock} [\overset{*}{\dots}] \dots \backslash\mathrm{stopmarginblock}$ <p><small>OPT</small></p> <p>* NAME</p>
$\backslash\mathrm{startmarkedcontent} [\overset{*}{\dots}] \dots \backslash\mathrm{stopmarkedcontent}$ <p><small>OPT</small></p> <p>* reset vse NAME</p>
$\backslash\mathrm{startMATHALIGNMENT} [\dots,\overset{*}{=}\dots] \dots \backslash\mathrm{stopMATHALIGNMENT}$ <p><small>OPT</small></p> <p>* inherits: $\backslash\mathrm{setupmathalignment}$</p> <p>instances:</p>
$\backslash\mathrm{startMATHCASES} [\dots,\overset{*}{=}\dots] \dots \backslash\mathrm{stopMATHCASES}$ <p><small>OPT</small></p> <p>* inherits: $\backslash\mathrm{setupmathcases}$</p> <p>instances:</p>
$\backslash\mathrm{startMATHMATRIX} [\dots,\overset{*}{=}\dots] \dots \backslash\mathrm{stopMATHMATRIX}$ <p><small>OPT</small></p> <p>* inherits: $\backslash\mathrm{setupmathmatrix}$</p> <p>instances:</p>
$\backslash\mathrm{startmathmode} \dots \backslash\mathrm{stopmathmode}$
$\backslash\mathrm{startmathstyle} [\dots,\overset{*}{\dots}] \dots \backslash\mathrm{stopmathstyle}$ <p>* obrazovka text script scriptscript cramped uncramped normalni zhustene male velke NAME</p>
$\backslash\mathrm{startmatrices} [\dots,\overset{*}{=}\dots] \dots \backslash\mathrm{stopmatrices}$ <p><small>OPT</small></p> <p>* inherits: $\backslash\mathrm{setupmathmatrix}$</p>
$\backslash\mathrm{startmaxaligned} \dots \backslash\mathrm{stopmaxaligned}$
$\backslash\mathrm{startmdformula} [\dots,\overset{*}{\dots}] \dots \backslash\mathrm{stopmdformula}$ <p><small>OPT</small></p> <p>* zhustene tight nastred ramecek inherits: $\backslash\mathrm{nastavzakladnifont}$</p>
$\backslash\mathrm{startmiddlealigned} \dots \backslash\mathrm{stopmiddlealigned}$
$\backslash\mathrm{startmixedcolumns} [\overset{1}{\dots}] [\dots,\overset{2}{=}\dots] \dots \backslash\mathrm{stopmixedcolumns}$ <p><small>OPT</small> <small>OPT</small></p> <p>1 NAME</p> <p>2 inherits: $\backslash\mathrm{setupmixedcolumns}$</p>
$\backslash\mathrm{startMIXEDCOLUMNS} [\dots,\overset{*}{=}\dots] \dots \backslash\mathrm{stopMIXEDCOLUMNS}$ <p><small>OPT</small></p> <p>* inherits: $\backslash\mathrm{setupmixedcolumns}$</p> <p>instances:</p>
$\backslash\mathrm{startmode} [\dots,\overset{*}{\dots}] \dots \backslash\mathrm{stopmode}$ <p>* NAME</p>

$\backslash\text{startmodeset} [\dots^1, \dots] \{\dots^2\} \dots \backslash\text{stopmodeset}$ 1 NAME implicitni 2 CONTENT
$\backslash\text{startmodule} [\dots] \dots \backslash\text{stopmodule}$ * FILE
$\backslash\text{startmoduletestsection} \dots \backslash\text{stopmoduletestsection}$
$\backslash\text{startmodule} \dots \dots \backslash\text{stopmodule}$ * FILE
$\backslash\text{startmpformula} [\dots^*, \dots] \dots \backslash\text{stopmpformula}$ <small>OPT</small> * zhustene tight nastred ramecek inherits: \nastavzakladnifont
$\backslash\text{startnadpis} [\dots^1, \dots] \{\dots^2\} \dots \backslash\text{stopnadpis}$ <small>OPT</small> 1 REFERENCE 2 TEXT
$\backslash\text{startnamedsection} [\dots^1] [\dots, \dots^2, \dots] [\dots, \dots^3, \dots] \dots \backslash\text{stopnamedsection}$ <small>OPT</small> <small>OPT</small> 1 ABSCHNITT 2 titul = TEXT zalozka = TEXT znaceni = TEXT seznam = TEXT odkaz = REFERENCE vlastnicislo = TEXT 3 KEY = VALUE
$\backslash\text{startnamedsubformulas} [\dots^1, \dots] \{\dots^2\} \dots \backslash\text{stopnamedsubformulas}$ <small>OPT</small> 1 + - REFERENCE 2 TEXT
$\backslash\text{startnaproti} \dots \backslash\text{stopnaproti}$
$\backslash\text{startnarrower} [\dots^*, \dots] \dots \backslash\text{stopnarrower}$ <small>OPT</small> * [-+]vlevo [-+]nastred [-+]vpravo NUMMER*vlevo NUMMER*nastred NUMMER*vpravo reset
$\backslash\text{startNARROWER} [\dots^*, \dots] \dots \backslash\text{stopNARROWER}$ <small>OPT</small> * [-+]vlevo [-+]nastred [-+]vpravo NUMMER*vlevo NUMMER*nastred NUMMER*vpravo reset
$\backslash\text{startnegativ} \dots \backslash\text{stopnegativ}$
$\backslash\text{startnicelyfilledbox} [\dots, \dots^*, \dots] \dots \backslash\text{stopnicelyfilledbox}$ <small>OPT</small> * sirka = DIMENSION vyska = DIMENSION offset = DIMENSION strut = ano ne
$\backslash\text{startnointerference} \dots \backslash\text{stopnointerference}$

<code>\startnotallmodes [...,*...] ... \stopnotallmodes</code> <code>* NAME</code>
<code>\startnotext ... \stopnotext</code>
<code>\startnotmode [...,*...] ... \stopnotmode</code> <code>* NAME</code>
<code>\startobrazek [¹...] [²] [...,³...,...] ... \stopobrazek</code> <div style="text-align: center;"><small>OPT</small></div> <code>1 NAME</code> <code>2 FILE</code> <code>3 inherits: \externiobraz</code>
<code>\startodlozit [[*]] ... \stopodlozit</code> <div style="text-align: center;"><small>OPT</small></div> <code>* [-+]NUMBER</code>
<code>\startodstavec [¹] [...,²...,...] ... \stopodstavec</code> <div style="display: flex; justify-content: space-around;"><div><small>OPT</small></div><div><small>OPT</small></div></div> <code>1 NAME</code> <code>2 inherits: \setupparagraph</code>
<code>\startoramovani [¹] [...,²...,...] ... \stoporamovani</code> <div style="display: flex; justify-content: space-around;"><div><small>OPT</small></div><div><small>OPT</small></div></div> <code>1 NAME</code> <code>2 inherits: \nastavoramovani</code>
<code>\startoramovanytext [¹] [...,²...,...] ... \stoporamovanytext</code> <div style="display: flex; justify-content: space-around;"><div><small>OPT</small></div><div><small>OPT</small></div></div> <code>1 vlevo vpravo nastred zadny</code> <code>2 inherits: \setupframedtext</code>
<code>\startORAMOVANYTEXT [¹] [...,²...,...] ... \stopORAMOVANYTEXT</code> <div style="display: flex; justify-content: space-around;"><div><small>OPT</small></div><div><small>OPT</small></div></div> <code>1 vlevo vpravo nastred zadny</code> <code>2 inherits: \setupframedtext</code> <code>instances: oramovanytext</code>
<code>\startoutputstream [...*] ... \stopoutputstream</code> <code>* NAME</code>
<code>\startoverprint ... \stopoverprint</code>
<code>\startpagefigure [¹] [...,²...,...] ... \stoppagefigure</code> <div style="text-align: center;"><small>OPT</small></div> <code>1 FILE</code> <code>2 inherits: \setupexternalfigure</code>
<code>\startpagegrid [¹] [...,²...,...] ... \stoppagegrid</code> <div style="display: flex; justify-content: space-around;"><div><small>OPT</small></div><div><small>OPT</small></div></div> <code>1 NAME</code> <code>2 inherits: \setuppagegrid</code>

<p><code>\startpagegridspan [...]¹ [...]²... \stoppagegridspan</code> <small>OPT</small></p> <p>1 NAME</p> <p>2 inherits: \setuppagegridspan</p>
<p><code>\startPAGEGRID [...][*]... \stopPAGEGRID</code> <small>OPT</small></p> <p>* inherits: \setuppagegrid</p>
<p><code>\startpagelayout [...][*]... \stoppagelayout</code></p> <p>* stranka levestranka pravestranka</p>
<p><code>\startpar [...]¹ [...]²... \stoppar</code> <small>OPT OPT</small></p> <p>1 NAME</p> <p>2 inherits: \setupparagraph</p>
<p><code>\startparagraphs [...][*]... \stopparagraphs</code></p> <p>* NAME</p>
<p><code>\startparagraphscell ... \stopparagraphscell</code></p>
<p><code>\startPARAGRAPHS ... \stopPARAGRAPHS</code></p>
<p><code>\startPARALLEL ... \stopPARALLEL</code></p>
<p><code>\startparbuilder [...][*]... \stopparbuilder</code></p> <p>* implicitni oneline basic NAME</p>
<p><code>\startumistiFLOAT [...]¹ [...]²... \stopumistiFLOAT</code> <small>OPT OPT</small></p> <p>1 titul = TEXT zalozka = TEXT znaceni = TEXT seznam = TEXT misto = split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraj levokraj pravokraj levarana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levestranka pravestranka zhlavi upati nekde effective odkaz = REFERENCE</p> <p>2 KEY = VALUE</p> <p>instances: chemical figure table intermezzo graphic</p>
<p><code>\startumistifigure [...]¹ [...]²... \stopumistifigure</code> <small>OPT OPT</small></p> <p>1 titul = TEXT zalozka = TEXT znaceni = TEXT seznam = TEXT misto = split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraj levokraj pravokraj levarana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levestranka pravestranka zhlavi upati nekde effective odkaz = REFERENCE</p> <p>2 KEY = VALUE</p>

<pre> \startumistigraphic [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] ... \stopumistigraphic OPT OPT 1 titul = TEXT zalozka = TEXT znaceni = TEXT seznam = TEXT misto = split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraj levokraj pravokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka zahlavi upati nekde effective odkaz = REFERENCE 2 KEY = VALUE </pre>
<pre> \startumistichemical [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] ... \stopumistichemical OPT OPT 1 titul = TEXT zalozka = TEXT znaceni = TEXT seznam = TEXT misto = split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraj levokraj pravokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka zahlavi upati nekde effective odkaz = REFERENCE 2 KEY = VALUE </pre>
<pre> \startumistiintermezzo [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] ... \stopumistiintermezzo OPT OPT 1 titul = TEXT zalozka = TEXT znaceni = TEXT seznam = TEXT misto = split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraj levokraj pravokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka zahlavi upati nekde effective odkaz = REFERENCE 2 KEY = VALUE </pre>
<pre> \startumistitable [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] ... \stopumistitable OPT OPT 1 titul = TEXT zalozka = TEXT znaceni = TEXT seznam = TEXT misto = split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraj levokraj pravokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka zahlavi upati nekde effective odkaz = REFERENCE 2 KEY = VALUE </pre>
<pre> \startplacepairedbox [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] ... \stopplacepairedbox OPT OPT 1 NAME 2 inherits: \setuppairedbox </pre>
<pre> \startumistiPAIREDBOX [...,\stackrel{*}{=},...] ... \stopumistiPAIREDBOX OPT * inherits: \setuppairedbox instances: </pre>
<pre> \startpolozka [...,\stackrel{*}{=},...] ... \stoppolozka OPT * REFERENCE </pre>

<pre> \startPOPIS [...,*...,...] ... \stopPOPIS OPT * titul = TEXT zalozka = TEXT seznam = TEXT odkaz = REFERENCE </pre>
<pre> \startPOPIS [...,¹...,...] {...²} ... \stopPOPIS OPT OPT 1 REFERENCE 2 TEXT </pre>
<pre> \startpositioning [...,¹...,...²...,...] ... \stoppositioning OPT OPT 1 NAME 2 inherits: \nastavumistovani </pre>
<pre> \startpositionoverlay {...} ... \stoppositionoverlay * NAME </pre>
<pre> \startpositiv ... \stoppositiv </pre>
<pre> \startpozadi [...,*...,...] ... \stoppozadi OPT * inherits: \nastavpozadi </pre>
<pre> \startPOZADI [...,*...,...] ... \stopPOZADI OPT * inherits: \nastavpozadi instances: pozadi </pre>
<pre> \startNOTE [...,*...,...] ... \stopNOTE OPT * REFERENCE instances: </pre>
<pre> \startNOTE [...,*...,...] ... \stopNOTE OPT * titul = TEXT zalozka = TEXT seznam = TEXT odkaz = REFERENCE instances: </pre>
<pre> \startprekryv ... \stopprekryv </pre>
<pre> \startprocessassignmentcommand [...,*...,...] ... \stopprocessassignmentcommand * KEY = VALUE </pre>
<pre> \startprocessassignmentlist [...,*...,...] ... \stopprocessassignmentlist * KEY = VALUE </pre>
<pre> \startprocesscommacommand [...,*...,...] ... \stopprocesscommacommand * BEFEHL </pre>

\startprocesscommalist [...,*...] ... \stopprocesscommalist * BEFEHL
\startprodukt [...] ... \stopprodukt * FILE *
\startprodukt \stopprodukt * FILE *
\startprojekt [...] ... \stopprojekt * FILE *
\startprojekt \stopprojekt * FILE *
\startprostredi [...] ... \stopprostredi * FILE *
\startprostredi \stopprostredi * FILE *
\startprotectedcolors ... \stopprotectedcolors
\startpublikace [...] [...] ... \stoppublikace <div style="display: flex; justify-content: space-around; width: 100%;"> <small>OPT</small> <small>OPT</small> </div> 1 NAME 2 tag = REFERENCE category = TEXT k = REFERENCE t = TEXT
\startradek [...] * REFERENCE
\startLINES [...] [...] ... \stopLINES <div style="display: flex; justify-content: space-around; width: 100%;"> <small>OPT</small> </div> * inherits: \nastavradky instances:
\startrandomized ... \stoprandomized
\startrawsetups [...] [...] ... \stoprawsetups <div style="display: flex; justify-content: space-around; width: 100%;"> <small>OPT</small> </div> 1 mrizka 2 NAME
\startrawsetups \stoprawsetups * NAME
\startreadingfile ... \stopreadingfile

<pre> \startregime [...] ... \stopregime * inherits: \enableregime </pre>
<pre> \startregister [¹.] [².] [³.] [⁴.] [⁵...+...] OPT OPT 1 NAME 2 NAME 3 TEXT 4 TEXT PROCESSOR->TEXT 5 INDEX </pre>
<pre> \startreusableMPgraphic {¹.} {²...} ... \stopreusableMPgraphic OPT 1 NAME 2 KEY </pre>
<pre> \starttrovnice [...[*]...] ... \stoprovnice OPT * zhustene tight nastred ramecek inherits: \nastavzakladnifont </pre>
<pre> \startROVNICEformula [...[*]...] ... \stopROVNICEformula OPT * zhustene tight nastred ramecek inherits: \nastavzakladnifont instances: sp sd mp md </pre>
<pre> \startrozbalene ... \stoprozbalene </pre>
<pre> \startscript [...] ... \stopscript * hangul hanzi nihongo ethiopic thai test NAME </pre>
<pre> \startsdformula [...[*]...] ... \stopsdformula OPT * zhustene tight nastred ramecek inherits: \nastavzakladnifont </pre>
<pre> \startsectionblock [¹.] [...²...] ... \stopsectionblock OPT 1 NAME 2 zalozka = TEXT inherits: \nastavbloksekce </pre>
<pre> \startsectionblockenvironment [...] ... \stopsectionblockenvironment * NAME </pre>
<pre> \startSECTIONBLOCK [...[*]...] ... \stopSECTIONBLOCK OPT * zalozka = TEXT inherits: \nastavbloksekce instances: </pre>

\startsectionlevel [...¹...] [...²...] [...³...] ... \stopsectionlevel
OPT OPT OPT

1 NAME
 2 titul = TEXT
 zalozka = TEXT
 znaceni = TEXT
 seznam = TEXT
 odkaz = REFERENCE
 vlastnicislo = TEXT
 3 KEY = VALUE

\startSECTION [...¹...] [...²...] ... \stopSECTION
OPT OPT

1 titul = TEXT
 zalozka = TEXT
 znaceni = TEXT
 seznam = TEXT
 odkaz = REFERENCE
 vlastnicislo = TEXT
 2 KEY = VALUE

instances: chapter section subsection subsubsection subsubsubsection subsubsubsubsection
 title subject subsubject subsubsubject subsubsubsubject subsubsubsubsubject

\startchapter [...¹...] [...²...] ... \stopchapter
OPT OPT

1 titul = TEXT
 zalozka = TEXT
 znaceni = TEXT
 seznam = TEXT
 odkaz = REFERENCE
 vlastnicislo = TEXT
 2 KEY = VALUE

\startsection [...¹...] [...²...] ... \stopsection
OPT OPT

1 titul = TEXT
 zalozka = TEXT
 znaceni = TEXT
 seznam = TEXT
 odkaz = REFERENCE
 vlastnicislo = TEXT
 2 KEY = VALUE

\startsubject [...¹...] [...²...] ... \stopsubject
OPT OPT

1 titul = TEXT
 zalozka = TEXT
 znaceni = TEXT
 seznam = TEXT
 odkaz = REFERENCE
 vlastnicislo = TEXT
 2 KEY = VALUE

\startsubsection [...¹...] [...²...] ... \stopsubsection
OPT OPT

1 titul = TEXT
 zalozka = TEXT
 znaceni = TEXT
 seznam = TEXT
 odkaz = REFERENCE
 vlastnicislo = TEXT
 2 KEY = VALUE

$\backslash\text{startsubsubject} [\dots, \dots, \overset{1}{\dots}, \dots] [\dots, \dots, \overset{2}{\dots}, \dots] \dots \backslash\text{stopsubsubject}$
OPT OPT

1 titul = TEXT
 zalozka = TEXT
 znaceni = TEXT
 seznam = TEXT
 odkaz = REFERENCE
 vlastnicislo = TEXT

2 KEY = VALUE

$\backslash\text{startsubsubsection} [\dots, \dots, \overset{1}{\dots}, \dots] [\dots, \dots, \overset{2}{\dots}, \dots] \dots \backslash\text{stopsubsubsection}$
OPT OPT

1 titul = TEXT
 zalozka = TEXT
 znaceni = TEXT
 seznam = TEXT
 odkaz = REFERENCE
 vlastnicislo = TEXT

2 KEY = VALUE

$\backslash\text{startsubsubsubject} [\dots, \dots, \overset{1}{\dots}, \dots] [\dots, \dots, \overset{2}{\dots}, \dots] \dots \backslash\text{stopsubsubsubject}$
OPT OPT

1 titul = TEXT
 zalozka = TEXT
 znaceni = TEXT
 seznam = TEXT
 odkaz = REFERENCE
 vlastnicislo = TEXT

2 KEY = VALUE

$\backslash\text{startsubsubsubsection} [\dots, \dots, \overset{1}{\dots}, \dots] [\dots, \dots, \overset{2}{\dots}, \dots] \dots \backslash\text{stopsubsubsubsection}$
OPT OPT

1 titul = TEXT
 zalozka = TEXT
 znaceni = TEXT
 seznam = TEXT
 odkaz = REFERENCE
 vlastnicislo = TEXT

2 KEY = VALUE

$\backslash\text{startsubsubsubsubject} [\dots, \dots, \overset{1}{\dots}, \dots] [\dots, \dots, \overset{2}{\dots}, \dots] \dots \backslash\text{stopsubsubsubsubject}$
OPT OPT

1 titul = TEXT
 zalozka = TEXT
 znaceni = TEXT
 seznam = TEXT
 odkaz = REFERENCE
 vlastnicislo = TEXT

2 KEY = VALUE

$\backslash\text{startsubsubsubsubsection} [\dots, \dots, \overset{1}{\dots}, \dots] [\dots, \dots, \overset{2}{\dots}, \dots] \dots \backslash\text{stopsubsubsubsubsection}$
OPT OPT

1 titul = TEXT
 zalozka = TEXT
 znaceni = TEXT
 seznam = TEXT
 odkaz = REFERENCE
 vlastnicislo = TEXT

2 KEY = VALUE

$\backslash\text{startsubsubsubsubsubject} [\dots, \dots, \overset{1}{\dots}, \dots] [\dots, \dots, \overset{2}{\dots}, \dots] \dots \backslash\text{stopsubsubsubsubsubject}$
OPT OPT

1 titul = TEXT
 zalozka = TEXT
 znaceni = TEXT
 seznam = TEXT
 odkaz = REFERENCE
 vlastnicislo = TEXT

2 KEY = VALUE

<p><code>\starttitle [...,¹...] [...,²...] ... \stoptitle</code></p> <p style="text-align: center;"><small>OPT OPT</small></p> <p>1 titul = TEXT</p> <p> zalozka = TEXT</p> <p> znaceni = TEXT</p> <p> seznam = TEXT</p> <p> odkaz = REFERENCE</p> <p> vlastnicislo = TEXT</p> <p>2 KEY = VALUE</p>
<p><code>\startitemize [...,¹...] [...,²...] ... \stopitemize</code></p> <p style="text-align: center;"><small>OPT OPT</small></p> <p>1 inherits: \setupitemgroup</p> <p>2 inherits: \setupitemgroup</p>
<p><code>\startsetups [...¹] [...²] ... \stopsetups</code></p> <p style="text-align: center;"><small>OPT</small></p> <p>1 mrizka</p> <p>2 NAME</p>
<p><code>\startsetups ... \stopsetups</code></p> <p>* NAME</p>
<p><code>\startshift [...[*]] ... \stopshift</code></p> <p>* NAME</p>
<p><code>\startsidebar [...¹] [...,²...] ... \stopsidebar</code></p> <p style="text-align: center;"><small>OPT OPT</small></p> <p>1 NAME</p> <p>2 inherits: \setupsidebar</p>
<p><code>\startsimplecolumns [...,[*]...] ... \stopsimplecolumns</code></p> <p style="text-align: center;"><small>OPT</small></p> <p>* inherits: \setsimplecolumnhsize</p>
<p><code>\startskryt ... \stopskryt</code></p>
<p><code>\startsloupce [...,[*]...] ... \stopsloupce</code></p> <p style="text-align: center;"><small>OPT</small></p> <p>* inherits: \nastavsloupce</p>
<p><code>\startspecialitem [...¹] [...,²...] ... \stopspecialitem</code></p> <p style="text-align: center;"><small>OPT OPT</small></p> <p>1 polozka</p> <p>2 REFERENCE</p>
<p><code>\startspecialitem [...[*]] ... \stopspecialitem</code></p> <p>* pod pol</p>
<p><code>\startspecialitem [...¹] {...²} ... \stopspecialitem</code></p> <p>1 sym rozsah mar</p> <p>2 TEXT</p>
<p><code>\startspeech [...,[*]...] ... \stopspeech</code></p> <p style="text-align: center;"><small>OPT</small></p> <p>* inherits: \startzuzeni</p>

$\backslash\mathrm{startspformula} [\dots,\overset{\mathrm{OPT}}{\dots}] \dots \backslash\mathrm{stopspformula}$ * <code>zhustene tight nastred ramecek inherits: \nastavzakladnifont</code>
$\backslash\mathrm{startspread} \dots \backslash\mathrm{stopspread}$
$\backslash\mathrm{start} [\overset{\mathrm{OPT}}{\dots}] \dots \backslash\mathrm{stop}$ * <code>NAME</code>
$\backslash\mathrm{start}\mathrm{STARTSTOP} \dots \backslash\mathrm{stop}\mathrm{STARTSTOP}$
$\backslash\mathrm{startstaticMPfigure} \{\overset{\mathrm{OPT}}{\dots}\} \dots \backslash\mathrm{stopstaticMPfigure}$ * <code>NAME</code>
$\backslash\mathrm{startstaticMPgraphic} \{\overset{1}{\dots}\} \{\overset{2}{\dots},\overset{\mathrm{OPT}}{\dots}\} \dots \backslash\mathrm{stopstaticMPgraphic}$ 1 <code>NAME</code> 2 <code>KEY</code>
$\backslash\mathrm{STARTSTOP} \{\overset{\mathrm{OPT}}{\dots}\}$ * <code>CONTENT</code>
$\backslash\mathrm{startstrictinspectnextcharacter} \dots \backslash\mathrm{stopstrictinspectnextcharacter}$
$\backslash\mathrm{startstructurepageregister} [\overset{1}{\dots}] [\overset{2}{\dots}] [\dots,\overset{3}{\dots},\dots] [\dots,\overset{4}{\dots},\dots]$ 1 <code>NAME</code> 2 <code>NAME</code> 3 <code>popisek = NAME</code> <code>keys = TEXT PROCESSOR->TEXT</code> <code>entries = TEXT PROCESSOR->TEXT</code> <code>keys:1 = TEXT</code> <code>keys:2 = TEXT</code> <code>keys:3 = TEXT</code> <code>entries:1 = TEXT</code> <code>entries:2 = TEXT</code> <code>entries:3 = TEXT</code> <code>alternativa = TEXT</code> 4 <code>KEY = VALUE</code>
$\backslash\mathrm{startstyle} [\dots,\overset{\mathrm{OPT}}{\dots},\dots] \dots \backslash\mathrm{stopstyle}$ * <code>inherits: \setupstyle</code>
$\backslash\mathrm{startstyle} [\overset{\mathrm{OPT}}{\dots}] \dots \backslash\mathrm{stopstyle}$ * <code>NAME FONT</code>
$\backslash\mathrm{start}\mathrm{STYLE} \dots \backslash\mathrm{stop}\mathrm{STYLE}$
$\backslash\mathrm{startsubformulas} [\dots,\overset{\mathrm{OPT}}{\dots},\dots] \dots \backslash\mathrm{stopsubformulas}$ * <code>+ - REFERENCE</code>

<p><code>\startsubjectlevel</code> [¹...] [²...] [³...] ... <code>\stopsubjectlevel</code></p> <p style="text-align: center;">OPT OPT OPT</p> <p>1 NAME</p> <p>2 titul = TEXT zalozka = TEXT znaceni = TEXT seznam = TEXT odkaz = REFERENCE vlastnicislo = TEXT</p> <p>3 KEY = VALUE</p>
<code>\startsubsentence ... \stopsubsentence</code>
<code>\startsubstack ... \stopsubstack</code>
<p><code>\startsymbolset</code> [...] ... <code>\stopsymbolset</code></p> <p>* NAME</p>
<p><code>\startTABLE</code> [...[*]...] ... <code>\stopTABLE</code></p> <p style="text-align: center;">OPT</p> <p>* inherits: <code>\setupTABLE</code></p>
<p><code>\startTABLEbody</code> [...[*]...] ... <code>\stopTABLEbody</code></p> <p style="text-align: center;">OPT</p> <p>* inherits: <code>\setupTABLE</code></p>
<p><code>\startTABLEfoot</code> [...[*]...] ... <code>\stopTABLEfoot</code></p> <p style="text-align: center;">OPT</p> <p>* inherits: <code>\setupTABLE</code></p>
<p><code>\startTABLEhead</code> [...[*]...] ... <code>\stopTABLEhead</code></p> <p style="text-align: center;">OPT</p> <p>* inherits: <code>\setupTABLE</code></p>
<p><code>\startTABLEnext</code> [...[*]...] ... <code>\stopTABLEnext</code></p> <p style="text-align: center;">OPT</p> <p>* inherits: <code>\setupTABLE</code></p>
<p><code>\startTEXpage</code> [...[*]...] ... <code>\stopTEXpage</code></p> <p style="text-align: center;">OPT</p> <p>* inherits: <code>\setupfittingpage</code></p>
<p><code>\starttabelator</code> [/¹/] [...²...] ... <code>\stoptabelator</code></p> <p style="text-align: center;">OPT OPT</p> <p>1 TEMPLATE</p> <p>2 inherits: <code>\nastvtabelaci</code></p>
<p><code>\startTABULATE</code> [¹] [...²...] ... <code>\stopTABULATE</code></p> <p style="text-align: center;">OPT OPT</p> <p>1 NAME</p> <p>2 inherits: <code>\nastvtabelaci</code></p> <p>instances:</p>
<p><code>\starttabulatehead</code> [[*]] ... <code>\stoptabulatehead</code></p> <p style="text-align: center;">OPT</p> <p>* NAME</p>
<p><code>\starttabulatetail</code> [[*]] ... <code>\stoptabulatetail</code></p> <p style="text-align: center;">OPT</p> <p>* NAME</p>

$\backslash startTABULATION$ [¹ ...] [² ... _{OPT} ...] ... \backstopTABULATION 1 NAME 2 inherits: \backsetupTABULATION
\backstartTABULKA [¹ ...] [² ... _{OPT} ...] ... \backstopTABULKA 1 TEMPLATE 2 inherits: \backnastavTABULKY
\backstartTABULKA [¹ ...] [² ... _{OPT} ...] ... \backstopTABULKA 1 NAME 2 inherits: \backnastavTABULKY
\backstartTABULKY [[*] ...] ... \backstopTABULKY * TEMPLATE
\backstartTABULKY [[*] ...] ... \backstopTABULKY * NAME
\backstartTEXCODE ... \backstopTEXCODE
\backstartTEXDEFINITION ¹ ... _{OPT} ² ... _{OPT} ³ ... _{OPT} ⁴ ... _{OPT} ⁵ ... ⁶ ... _{OPT} ... \backstopTEXDEFINITION 1 spaces nospaces 2 globalne 3 unexpanded 4 expanded 5 NAME 6 TEMPLATE
\backstartTEXT ... \backstopTEXT
\backstartTEXTBACKGROUND [¹ ...] [² ... _{OPT} ...] ... \backstopTEXTBACKGROUND 1 NAME 2 inherits: \backsetupTEXTBACKGROUND
$\backstartTEXTBACKGROUNDMANUAL$... $\backstopTEXTBACKGROUNDMANUAL$
\backstartTEXTBACKGROUND [[*] ... _{OPT} ...] ... \backstopTEXTBACKGROUND * inherits: \backsetupTEXTBACKGROUND
\backstartTEXTCOLOR [[*] ...] ... \backstopTEXTCOLOR * COLOR
$\backstartTEXTCOLORINTENT$... \backstopTEXTCOLORINTENT
\backstartTEXTFLOW [[*] ...] ... \backstopTEXTFLOW * NAME

$\backslash\text{starttextnapovedy}$ [$\overset{*}{\dots}$] ... $\backslash\text{stoptextnapovedy}$ <small>OPT</small> * REFERENCE
$\backslash\text{starttextovalinka}$ [$\overset{*}{\dots}$] ... $\backslash\text{stoptextovalinka}$ * TEXT
$\backslash\text{startLABELtext}$ [$\overset{1}{\dots}$] [$\overset{2}{\dots}$] ... $\backslash\text{stopLABELtext}$ <small>OPT</small> 1 SPRACHE 2 KEY instances:
$\backslash\text{starttokens}$ [$\overset{*}{\dots}$] ... $\backslash\text{stoptokens}$ * NAME
$\backslash\text{starttransparent}$ [$\overset{*}{\dots}$] ... $\backslash\text{stoptransparent}$ * COLOR
$\backslash\text{starttypescript}$ [$\overset{1}{\dots},\dots$] [$\overset{2}{\dots},\dots$] [$\overset{3}{\dots},\dots$] ... $\backslash\text{stoptypescript}$ <small>OPT OPT OPT</small> 1 serif sans mono math handwriting calligraphy 2 NAME 3 size jmeno
$\backslash\text{starttypescriptcollection}$ [$\overset{*}{\dots}$] ... $\backslash\text{stoptypescriptcollection}$ * NAME
$\backslash\text{startTYPING}$ [$\dots,\overset{*}{\dots},\dots$] ... $\backslash\text{stopTYPING}$ <small>OPT</small> * inherits: \nastavopis instances:
$\backslash\text{startTYPING}$ [$\dots,\overset{*}{\dots},\dots$] ... $\backslash\text{stopTYPING}$ <small>OPT</small> * pokračovat instances:
$\backslash\text{startumistirovnici}$ [$\dots,\overset{*}{\dots},\dots$] ... $\backslash\text{stopumistirovnici}$ <small>OPT</small> * titul = TEXT * suffix = TEXT * odkaz = + - REFERENCE
$\backslash\text{startumistirovnici}$ [$\dots,\overset{*}{\dots},\dots$] ... $\backslash\text{stopumistirovnici}$ <small>OPT</small> * + - REFERENCE
$\backslash\text{startuniqueMPgraphic}$ [$\overset{1}{\dots}$] [$\overset{2}{\dots},\dots$] ... $\backslash\text{stopuniqueMPgraphic}$ <small>OPT</small> 1 NAME 2 KEY

$\backslash\text{startuniqueMPpagegraphic} \{\overset{1}{\dots}\} \{\overset{2}{\dots},\dots\} \dots \backslash\text{stopuniqueMPpagegraphic}$ <p>1 NAME</p> <p>2 KEY</p>
$\backslash\text{startusableMPgraphic} \{\overset{1}{\dots}\} \{\overset{2}{\dots},\dots\} \dots \backslash\text{stopusableMPgraphic}$ <p>1 NAME</p> <p>2 KEY</p>
$\backslash\text{startuseMPgraphic} \{\overset{1}{\dots}\} \{\overset{2}{\dots},\dots\} \dots \backslash\text{stopuseMPgraphic}$ <p>1 NAME</p> <p>2 KEY</p>
$\backslash\text{startusemathstyleparameter} \backslash* \dots \backslash\text{stopusemathstyleparameter}$ <p>* CSNAME</p>
$\backslash\text{startusingbtxs specification} [\backslash*] \dots \backslash\text{stopusingbtxs specification}$ <p>* NAME</p>
$\backslash\text{startuzky} [\overset{1}{\dots}] [\dots,\dots,\overset{2}{\dots}] \dots \backslash\text{stopuzky}$ <p>1 NAME</p> <p>2 inherits: \nastavzuzeni</p>
$\backslash\text{startuzky} [\dots,\dots,\overset{1}{\dots}] [\dots,\dots,\overset{2}{\dots}] \dots \backslash\text{stopuzky}$ <p>1 inherits: \nastavzuzeni</p> <p>2 [-+]vlevo [-+]nastred [-+]vpravo NUMBER*vlevo NUMBER*nastred NUMBER*vpravo reset</p>
$\backslash\text{startuzky} [\overset{1}{\dots}] [\dots,\dots,\overset{2}{\dots}] \dots \backslash\text{stopuzky}$ <p>1 NAME</p> <p>2 [-+]vlevo [-+]nastred [-+]vpravo NUMBER*vlevo NUMBER*nastred NUMBER*vpravo reset</p>
$\backslash\text{startvboxregister} \dots \dots \backslash\text{stopvboxregister}$ <p>* CSNAME NUMBER</p>
$\backslash\text{startvboxtohbox} \dots \backslash\text{stopvboxtohbox}$
$\backslash\text{startvboxtohboxseparator} \dots \backslash\text{stopvboxtohboxseparator}$
$\backslash\text{startviewerlayer} [\backslash*] \dots \backslash\text{stopviewerlayer}$ <p>* NAME</p>
$\backslash\text{startVIEWERLAYER} \dots \backslash\text{stopVIEWERLAYER}$
$\backslash\text{startvtopregister} \dots \dots \backslash\text{stopvtopregister}$ <p>* CSNAME NUMBER</p>

<pre> \startVYCET [...,*...,...] ... \stopVYCET OPT * titul = TEXT zalozka = TEXT seznam = TEXT odkaz = REFERENCE </pre>
<pre> \startVYCET [...,¹...,...] {²...} ... \stopVYCET OPT OPT 1 REFERENCE 2 TEXT </pre>
<pre> \startxcell [...,¹...] [...,²...,...] ... \stopxcell OPT OPT 1 NAME 2 nx = NUMMER ny = NUMMER nc = NUMMER nr = NUMMER inherits: \setupxtable </pre>
<pre> \startxcellgroup [...,¹...] [...,²...,...] ... \stopxcellgroup OPT OPT 1 NAME 2 inherits: \setupxtable </pre>
<pre> \startxgroup [...,¹...] [...,²...,...] ... \stopxgroup OPT OPT 1 NAME 2 inherits: \setupxtable </pre>
<pre> \startxmldisplayverbatim [...*] ... \stopxmldisplayverbatim * NAME </pre>
<pre> \startxmllineverbatim [...*] ... \stopxmllineverbatim * NAME </pre>
<pre> \startxmlraw ... \stopxmlraw </pre>
<pre> \startxmlsetups [...,¹...] [...,²...] ... \stopxmlsetups OPT 1 mrizka 2 NAME </pre>
<pre> \startxmlsetups ...*... \stopxmlsetups * NAME </pre>
<pre> \startxrow [...,¹...] [...,²...,...] ... \stopxrow OPT OPT 1 NAME 2 inherits: \setupxtable </pre>
<pre> \startxrowgroup [...,¹...] [...,²...,...] ... \stopxrowgroup OPT OPT 1 NAME 2 inherits: \setupxtable </pre>
<pre> \startxtable [...,*...,...] ... \stopxtable OPT * inherits: \setupxtable </pre>

$\backslash\text{startxtablebody} [\dots, \dots, \dots, \dots] \dots \backslash\text{stopxtablebody}$ <small>OPT</small> * inherits: \setupxtable
$\backslash\text{startxtablebody} [\dots] \dots \backslash\text{stopxtablebody}$ <small>OPT</small> * NAME
$\backslash\text{startxtablefoot} [\dots, \dots, \dots, \dots] \dots \backslash\text{stopxtablefoot}$ <small>OPT</small> * inherits: \setupxtable
$\backslash\text{startxtablefoot} [\dots] \dots \backslash\text{stopxtablefoot}$ <small>OPT</small> * NAME
$\backslash\text{startxtablehead} [\dots, \dots, \dots, \dots] \dots \backslash\text{stopxtablehead}$ <small>OPT</small> * inherits: \setupxtable
$\backslash\text{startxtablehead} [\dots] \dots \backslash\text{stopxtablehead}$ <small>OPT</small> * NAME
$\backslash\text{startxtablenext} [\dots, \dots, \dots, \dots] \dots \backslash\text{stopxtablenext}$ <small>OPT</small> * inherits: \setupxtable
$\backslash\text{startxtablenext} [\dots] \dots \backslash\text{stopxtablenext}$ <small>OPT</small> * NAME
$\backslash\text{startXTABLE} [\dots, \dots, \dots, \dots] \dots \backslash\text{stopXTABLE}$ <small>OPT</small> * inherits: \setupxtable
$\backslash\text{startxtable} [\dots] \dots \backslash\text{stopxtable}$ <small>OPT</small> * NAME
$\backslash\text{startzahlavitabulky} [\dots] \dots \backslash\text{stopzahlavitabulky}$ * NAME
$\backslash\text{startzarovnanonastred} \dots \backslash\text{stopzarovnanonastred}$
$\backslash\text{startzarovnanovlevo} \dots \backslash\text{stopzarovnanovlevo}$
$\backslash\text{startzarovnanovpravo} \dots \backslash\text{stopzarovnanovpravo}$
$\backslash\text{startzhustene} [\dots] \dots \backslash\text{stopzhustene}$ <small>OPT</small> * prazdny
$\backslash\text{startzlom} [\dots] [\dots, \dots, \dots, \dots] \dots \backslash\text{stopzlom}$ <small>OPT</small> 1 NAME 2 inherits: \nastavupravu

<p><code>\startMAKEUPzlom [...,*=...,...] ... \stopMAKEUPzlom</code> <small>OPT</small></p> <p>* inherits: \nastavupravu</p> <p>instances:</p>
<p><code>\stopLINENOTE [...]</code></p> <p>* REFERENCE</p> <p>instances:</p>
<p><code>\stopradek [...]</code></p> <p>* REFERENCE</p>
<p><code>\stopregister [...¹] [...²]</code></p> <p>1 NAME</p> <p>2 NAME</p>
<p><code>\stopstructurepageregister [...¹] [...²]</code></p> <p>1 NAME</p> <p>2 NAME</p>
<p><code>\strana [...,*=...,...]</code> <small>OPT</small></p> <p>* inherits: \pagebreak</p>
<p><code>\strictdoifelsenextoptional {...¹} {...²}</code></p> <p>1 TRUE</p> <p>2 FALSE</p>
<p><code>\strictdoifnextoptionalelse {...¹} {...²}</code></p> <p>1 TRUE</p> <p>2 FALSE</p>
<p><code>\stripcharacter ...¹ \from ...² \to ...³</code></p> <p>1 CHARACTER</p> <p>2 TEXT</p> <p>3 CSNAME</p>
<p><code>\strippedcsname *...</code></p> <p>* CSNAME</p>
<p><code>\strippedcsname ...</code></p> <p>* TEXT</p>
<p><code>\stripspaces \from ...¹ \to ...²</code></p> <p>1 TEXT</p> <p>2 CSNAME</p>

<code>\structurelistuservariable {...}</code> * KEY
<code>\structurenumber</code>
<code>\structuretitle</code>
<code>\structureuservariable {...}</code> * KEY
<code>\structurevariable {...}</code> * KEY
<code>\strut</code>
<code>\strutdp</code>
<code>\strutht</code>
<code>\struthtdp</code>
<code>\struttedbox {...}</code> * CONTENT
<code>\strutwd</code>
<code>\style [...¹...²...] {...}</code> 1 inherits: \setupstyle 2 TEXT
<code>\styleinstance [...]</code> * NAME
<code>\style [...¹...] {...²}</code> 1 NAME FONT 2 TEXT
<code>\STYLE {...}</code> * TEXT
<code>\subpagenumber</code>
<code>\subsentence {...}</code> * CONTENT
<code>\substituteincommalist {...¹} {...²} \...³</code> 1 TEXT 2 TEXT 3 CSNAME

<code>\subtractfeature [...]</code> * NAME
<code>\subtractfeature {...}</code> * NAME
<code>\swapcounts \¹... \²...</code> 1 CSNAME 2 CSNAME
<code>\swapdimens \¹... \²...</code> 1 CSNAME 2 CSNAME
<code>\swapface</code>
<code>\swapmacros \¹... \²...</code> 1 CSNAME 2 CSNAME
<code>\swaptypesface</code>
<code>\switchstyleonly [...]</code> * rm ss tt hw cg antikva serif pravidelne sans bezserifu podpora opis strojopis mono rukopisne kaligraficke
<code>\switchstyleonly *</code> * CSNAME
<code>\switchtocolour [...]</code> * COLOR
<code>\switchtointerlinespace [...,¹...] [...,²...]</code> <small>OPT</small> 1 NAME 2 inherits: \nastavmeziradkovoumezeru
<code>\switchtointerlinespace [...,[*]...]</code> <small>OPT</small> * zap vyp reset auto male stredni velke NUMMER DIMENSION
<code>\switchtointerlinespace [...]</code> * NAME
<code>\symbol [¹...] [²...]</code> <small>OPT</small> 1 NAME 2 NAME
<code>\symbolreference [...]</code> * REFERENCE

\symbol {...} * NAME
\synchronizeblank
\synchronizeindenting
\synchronizemarking [¹ ...] [² ...] [³ ...] <small>OPT</small> 1 BESCHRIFTUNG 2 NUMMER 3 drzet
\synchronizeoutputstreams [...,*,...] * NAME
\synchronizestrut {...} * ano ne auto kap prizpusobive radek implicitni CHARACTER
\synchronizewhitespace
\SYNONYM [¹ ...] { ² ...} { ³ ...} <small>OPT</small> 1 NAME 2 TEXT 3 CONTENT instances:
\systemlog {...} {...} {...} 1 FILE 2 TEXT 3 TEXT
\systemlogfirst {...} {...} {...} 1 FILE 2 TEXT 3 TEXT
\systemloglast {...} {...} {...} 1 FILE 2 TEXT 3 TEXT
\systemsetups {...} * NAME
\TABLE
\TaBlE

<code>\TEX</code>
<code>\TeX</code>
<code>\TheNormalizedFontSize</code>
<code>\TransparencyHack</code>
<code>\tabulateautoline</code>
<code>\tabulateautorule</code>
<code>\tabulateline</code>
<code>\tabulaterule</code>
<code>\taggedctxcommand {.*}</code> * BEFEHL
<code>\taggedlabeltexts {.^1.} {.^2.} {.^3.}</code> 1 NAME 2 NAME 3 CONTENT
<code>\tbinom {.^1.} {.^2.}</code> 1 CONTENT 2 CONTENT
<code>\tbox {.*}</code> * CONTENT
<code>\tecka {.*}</code> * CHARACTER
<code>\tecky [.*]</code> <small>OPT</small> * NUMMER
<code>\tecky [...,*...,...]</code> <small>OPT</small> * inherits: \setupperiods
<code>\tenkalinka</code>
<code>\tenkelinky [...,*...,...]</code> <small>OPT</small> * inherits: \nastavtenkelinky
<code>\tequal {.^1.} {.^2.}</code> <small>OPT</small> <small>OPT</small> 1 TEXT 2 TEXT

`\testandsplitstring 1... \at 2... \to 3... \and 4...`

- 1 TEXT
- 2 TEXT
- 3 CSNAME
- 4 CSNAME

`\testcolumn [1...] [2...]`
OPT

- 1 NUMBER
- 2 DIMENSION

`\testfeature {1...} {2...,...}`

- 1 NUMBER
- 2 CONTENT

`\testfeatureonce {1...} {2...,...}`

- 1 NUMBER
- 2 CONTENT

`\testpage [1...] [2...]`
OPT

- 1 NUMBER
- 2 DIMENSION

`\testpageonly [1...] [2...]`
OPT

- 1 NUMBER
- 2 DIMENSION

`\testpagesync [1...] [2...]`
OPT

- 1 NUMBER
- 2 DIMENSION

`\testtokens [...]`

- * NAME

`\tex {...}`

- * CONTENT

`\texdefinition {...}`

- * NAME

`\texsetup {...}`

- * NAME

`\TEXTBACKGROUND {...}`

- * CONTENT

`\textcitation [...1...2...] [...]`

OPT

1 odkaz = REFERENCE
 alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
 authornum authoryear
 pred = BEFEHL
 po = BEFEHL
 vlevo = BEFEHL
 vpravo = BEFEHL
 inherits: \setupbtx

2 REFERENCE

`\textcitation [...1...] [...2]`

OPT

1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear
 2 REFERENCE

`\textcitation [...1...2...] [...2...2...]`

1 odkaz = REFERENCE
 alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
 authornum authoryear
 pred = BEFEHL
 po = BEFEHL
 vlevo = BEFEHL
 vpravo = BEFEHL
 inherits: \setupbtx

2 KEY = VALUE

`\textcite [...1...2...] [...2]`

OPT

1 odkaz = REFERENCE
 alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
 authornum authoryear
 pred = BEFEHL
 po = BEFEHL
 vlevo = BEFEHL
 vpravo = BEFEHL
 inherits: \setupbtx

2 REFERENCE

`\textcite [...1...] [...2]`

OPT

1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear
 2 REFERENCE

`\textcite [...1...2...] [...2...2...]`

1 odkaz = REFERENCE
 alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
 authornum authoryear
 pred = BEFEHL
 po = BEFEHL
 vlevo = BEFEHL
 vpravo = BEFEHL
 inherits: \setupbtx

2 KEY = VALUE

`\textcontrolspace`

`\textflowcollector {...}`

* NAME

`\textmath {...}`

* CONTENT

<code>\textminus</code>
$\text{\textnapovedy} [\overset{1}{...}] \{\overset{2}{...}\} \{\overset{3}{...}\}$ <p>1 REFERENCE</p> <p>2 TEXT</p> <p>3 TEXT</p>
$\text{\textormathchar} \{...\}$ <p>* NUMMER</p>
$\text{\texttovalinka} [\overset{1}{...}] \{\overset{2}{...}\}$ <p>1 vrsek nastred spodek</p> <p>2 TEXT</p>
<code>\textplus</code>
$\text{\text{LABEL}text} \{...\}$ <p>* KEY</p> <p>instances:</p>
<code>\textvisiblespace</code>
$\text{\tfrac} \{\overset{1}{...}\} \{\overset{2}{...}\}$ <p>1 CONTENT</p> <p>2 CONTENT</p>
$\text{\thainumerals} \{...\}$ <p>* NUMMER</p>
$\text{\thefirstcharacter} \{...\}$ <p>* TEXT</p>
$\text{\thenormalizedbodyfontsize} \{...\}$ <p>* DIMENSION</p>
$\text{\theremainingcharacters} \{...\}$ <p>* TEXT</p>
<code>\thickspace</code>
<code>\thinspace</code>
$\text{\thirdoffivearguments} \{\overset{1}{...}\} \{\overset{2}{...}\} \{\overset{3}{...}\} \{\overset{4}{...}\} \{\overset{5}{...}\}$ <p>1 TEXT</p> <p>2 TEXT</p> <p>3 TEXT</p> <p>4 TEXT</p> <p>5 TEXT</p>

`\thirtoffourarguments {...} {...} {...} {...}`

1 TEXT
2 TEXT
3 TEXT
4 TEXT

`\thirdotsixarguments {...} {...} {...} {...} {...} {...}`

1 TEXT
2 TEXT
3 TEXT
4 TEXT
5 TEXT
6 TEXT

`\thirdofthreearguments {...} {...} {...}`

1 TEXT
2 TEXT
3 TEXT

`\thirdofthreeunexpanded {...} {...} {...}`

1 TEXT
2 TEXT
3 TEXT

`\thookleftarrow {...} {...}`
 _{OPT} _{OPT}

1 TEXT
2 TEXT

`\thookrightarrow {...} {...}`
 _{OPT} _{OPT}

1 TEXT
2 TEXT

`\threedigitrounding {...}`

* NUMMER

`\tibetannumerals {...}`

* NUMMER

`\tightlayer [...]`

* NAME

`\tilde {...}`

* CHARACTER

`\tinyfont`

$\backslash\text{tLeftarrow} \overset{1}{\{...\}} \overset{2}{\{...\}}$ 1 TEXT 2 TEXT
$\backslash\text{tLeftrightarrow} \overset{1}{\{...\}} \overset{2}{\{...\}}$ 1 TEXT 2 TEXT
$\backslash\text{tlacitko} [\dots, \overset{1}{\dots}] \overset{2}{\{...\}} [\overset{3}{\dots}]$ 1 inherits: \setupbutton 2 TEXT 3 REFERENCE
$\backslash\text{tlacitkomenu} [\dots, \overset{1}{\dots}] \overset{2}{\{...\}} \overset{3}{\{...\}}$ 1 inherits: \setupbutton 2 TEXT 3 REFERENCE
$\backslash\text{tlacitkomenu} [\overset{1}{\dots}] [\dots, \overset{2}{\dots}] \overset{3}{\{...\}} \overset{4}{\{...\}}$ 1 NAME 2 inherits: \nastavinterakcnimenu 3 TEXT 4 REFERENCE
$\backslash\text{BUTTON} [\dots, \overset{1}{\dots}] \overset{2}{\{...\}} [\overset{3}{\dots}]$ 1 inherits: \setupbutton 2 TEXT 3 REFERENCE instances: button
$\backslash\text{tlap} \{...\}$ * CONTENT
$\backslash\text{tleftarrow} \overset{1}{\{...\}} \overset{2}{\{...\}}$ 1 TEXT 2 TEXT
$\backslash\text{tleftharpoondown} \overset{1}{\{...\}} \overset{2}{\{...\}}$ 1 TEXT 2 TEXT
$\backslash\text{tleftharpoonup} \overset{1}{\{...\}} \overset{2}{\{...\}}$ 1 TEXT 2 TEXT

$\xleftrightarrow{\text{...}}{\text{...}}$ $\xleftrightarrow[\text{OPT}]{\text{...}}{\text{...}}$ 1 TEXT 2 TEXT
$\xharpoonright{\text{...}}{\text{...}}$ $\xharpoonright[\text{OPT}]{\text{...}}{\text{...}}$ 1 TEXT 2 TEXT
\ulcorner
\mapsto $\mapsto[\text{OPT}]{\text{...}}{\text{...}}$ 1 TEXT 2 TEXT
\char"
\linenote
\topbox
\topleftbox
\toplinebox
\toprightbox
\topskippedbox
\rightarrow $\rightarrow[\text{OPT}]{\text{...}}{\text{...}}$ 1 TEXT 2 TEXT
\catcodetables
\tracedfontname
$\text{\traceoutputroutines}$
\tracepositions

`\transparencyparts {...}`

* COLOR

`\transparent [..1..] {..2..}`

1 COLOR

2 CONTENT

`\tref` $\{\dots\}^1$ $\{\dots\}^2$ $[\dots]^3$

1 TEXT

2 TEXT

3 REFERENCE

$$\backslash\mathrm{trel}\quad\{\overset{1}{\dots}\}\quad\{\overset{2}{\dots}\}$$

1 TEXT

2 TEXT

$$\xrightarrow[\text{OPT}]{\text{OPT}} \dots$$

1 TEXT

2 TEXT

$$\backslash\mathrm{trightharpoonowdown} \underset{\mathrm{OPT}}{\{...\}^1} \underset{\mathrm{OPT}}{\{...\}^2}$$

1 TEXT

2 TEXT

$$\backslash\mathrm{trightharpoonup} \mathop{\mathrm{\scriptsize OPT}}^{\scriptsize 1} \mathop{\mathrm{\scriptsize OPT}}^{\scriptsize 2}$$

1 TEXT

2 TEXT

$$\text{\trightleftharpoons} \quad \underset{\text{OPT}}{\{...\}^1} \quad \underset{\text{OPT}}{\{...\}^2}$$

1 TEXT

2 TEXT

$$\text{\trightoverleftarrow}\{\text{\scriptsize OPT}^1\}\{\text{\scriptsize OPT}^2\}$$

1 TEXT

2 TEXT

 $\text{\textbackslashtriplebond}$

```
\truefilename {...}
```

* FILE

`\truefontname {...}`

* FONT

\traggedright

$\backslash\text{ttriplerel} \{\overset{1}{\dots}\} \{\overset{2}{\dots}\}$ $\text{OPT} \quad \text{OPT}$ 1 TEXT 2 TEXT
$\backslash\text{twoheadleftarrow} \{\overset{1}{\dots}\} \{\overset{2}{\dots}\}$ $\text{OPT} \quad \text{OPT}$ 1 TEXT 2 TEXT
$\backslash\text{twoheadrightarrow} \{\overset{1}{\dots}\} \{\overset{2}{\dots}\}$ $\text{OPT} \quad \text{OPT}$ 1 TEXT 2 TEXT
$\backslash\text{tucne}$
$\backslash\text{tucnekurzivni}$
$\backslash\text{tucnesklonene}$
$\backslash\text{tvr damezera}$
$\backslash\text{tvr damezery}$
$\backslash\text{twodigitrounding} \{.*\}$ * NUMBER
$\backslash\text{tx}$
$\backslash\text{txx}$
$\backslash\text{typebuffer} [\overset{1}{\dots}, \dots] [\overset{2}{\dots}, \dots]$ $\text{OPT} \quad \text{OPT}$ 1 BUFFER 2 inherits: $\backslash\text{nastavopis}$
$\backslash\text{opis} \textit{BUFFER} [\dots, \overset{*}{\dots}]$ OPT * inherits: $\backslash\text{nastavopis}$
$\backslash\text{typedefinedbuffer} [\overset{1}{\dots}] [\dots, \overset{2}{\dots}]$ OPT 1 BUFFER 2 inherits: $\backslash\text{nastavopis}$
$\backslash\text{typeface}$
$\backslash\text{typescriptone}$
$\backslash\text{typescriptprefix} \{.*\}$ * NAME
$\backslash\text{typescriptthree}$

<code>\typescripttwo</code>
<code>\typesetbuffer</code> ¹ <code>[...]</code> ² <code>[...,...]</code> <small>OPT OPT</small> 1 * BUFFER 2 inherits: \setupexternalfigure
<code>\typesetfile</code> ¹ <code>[...]</code> ² <code>[...]</code> ³ <code>[...,...]</code> <small>OPT OPT</small> 1 NAME FILE 2 FILE TEXT 3 inherits: \setupexternalfigure
<code>\uconvertnumber</code> { ¹ ...} { ² ...} 1 inherits: \konvertujcislo 2 NUMMER
<code>\uedcatcodecommand</code> \ ¹ ... ² ... { ³ ...} 1 CSNAME 2 CHARACTER NUMMER 3 BEFEHL
<code>\ukazbarvu</code> [[*] ...] * COLOR
<code>\ukazmrizku</code> [[*] ...,...] <small>OPT</small> * reset spodek vrsek zadny vse radky ramecek nonumber vpravo vlevo vnejsi sloupce
<code>\ukaznastaveni</code> [[*] ...,...] <small>OPT</small> * pt bp cm mm dd cc pc nd nc sp in
<code>\ukazpaletu</code> [¹ ...] [² ...,...] <small>OPT</small> 1 NAME 2 horizontalne vertikalne cislo hodnota jmeno
<code>\ukazpodpery</code>
<code>\ukazpostredizakladnihofontu</code> [[*] ...,...] * inherits: \nastavzakladnifont
<code>\ukazramecek</code> [¹ ...,...] ² [² ...,...] <small>OPT OPT</small> 1 vrsek zahlavi text upati spodek 2 levahrana levyokraj text pravyokraj pravahrana
<code>\ukazsadosymbolu</code> [[*] ...] * NAME
<code>\ukazskupinubarev</code> [¹ ...] [² ...,...] <small>OPT</small> 1 NAME 2 horizontalne vertikalne cislo hodnota jmeno

<p><code>\ukazupravu [...]</code> <small>OPT</small></p> <p>* zlom vse boxes glyph fontkern hbox vbox vtop kern glue penalty strut whatsit simple simplehbox simplevbox simplevtop user math kurziva origin reset</p>
<p><code>\ukazvytisk [...¹,...] [...²,...] [...³,...]</code> <small>OPT OPT OPT</small></p> <p>1 inherits: \nastavvelikostpapiu</p> <p>2 inherits: \nastavvelikostpapiu</p> <p>3 inherits: \nastavvzhled</p>
<p><code>\ukazvzhled [...[*],...]</code> <small>OPT</small></p> <p>* pt bp cm mm dd cc pc nd nc sp in</p>
<p><code>\ukazzakladnifont [...[*],...]</code></p> <p>* inherits: \nastavzakladnifont</p>
<p><code>\umistikombinovanyseznam [...¹] [...²,...]</code> <small>OPT</small></p> <p>1 LISTE</p> <p>2 inherits: \nastavseznam</p>
<p><code>\umistiCOMBINEDLIST [...[*],...]</code> <small>OPT</small></p> <p>* inherits: \nastavseznam</p> <p>instances:</p>
<p><code>\umistilokalnipoznamkypodcarou [...[*],...]</code> <small>OPT</small></p> <p>* inherits: \setupnote</p>
<p><code>\umistinadsebe {...¹} {...²}</code></p> <p>1 CONTENT</p> <p>2 CONTENT</p>
<p><code>\umistinamrizku [...¹] {...²}</code> <small>OPT</small></p> <p>1 normalni standardni ano striktni tolerantni vrsek spodek obe široky prizpusobive prvnι posledni vysoko jedna nizko zadny radek strut box min max nastred NAME</p> <p>2 CONTENT</p>
<p><code>\umistinamrizku [...¹,...] {...²}</code> <small>OPT</small></p> <p>1 inherits: \definegridsnapping</p> <p>2 CONTENT</p>
<p><code>\umistipodrovnici [...[*],...]</code> <small>OPT</small></p> <p>* + - REFERENCE</p>
<p><code>\umistipoznamkypodcarou [...[*],...]</code> <small>OPT</small></p> <p>* inherits: \setupnote</p>
<p><code>\umistirejstrik [...¹] [...²,...]</code> <small>OPT</small></p> <p>1 NAME</p> <p>2 inherits: \nastavrejstrik</p>

$\backslash\text{umistiREGISTER} [\dots, \dots \overset{\text{OPT}}{=} \dots, \dots]$ \ast inherits: \nastavrejstrik instances:
$\backslash\text{umistirovnici} [\dots, \dots \overset{\text{OPT}}{=} \dots]$ \ast + - REFERENCE
$\backslash\text{umistiseznam} [\dots, \dots \overset{1}{=} \dots] [\dots, \dots \overset{2}{=} \dots, \dots]$ 1 LISTE 2 inherits: \nastavseznam
$\backslash\text{umistivedlesebe} \{\dots \overset{1}{=} \dots\} \{\dots \overset{2}{=} \dots\}$ 1 CONTENT 2 CONTENT
$\backslash\text{umistizalozky} [\dots, \dots \overset{1}{=} \dots] [\dots, \dots \overset{2}{=} \dots] [\dots, \dots \overset{3}{=} \dots, \dots]$ 1 ABSCHNITT LISTE 2 ABSCHNITT LISTE 3 inherits: \setupbookmark
$\backslash\text{undefinevalue} \{\dots \overset{*}{=} \dots\}$ \ast NAME
$\backslash\text{undepthed} \{\dots \overset{*}{=} \dots\}$ \ast CONTENT
$\backslash\text{underbartext} \{\dots \overset{1}{=} \dots\} \{\dots \overset{2}{=} \dots\}$ 1 TEXT 2 TEXT
$\backslash\text{underbrace} \{\dots \overset{*}{=} \dots\}$ \ast TEXT
$\backslash\text{underbracetext} \{\dots \overset{1}{=} \dots\} \{\dots \overset{2}{=} \dots\}$ 1 TEXT 2 TEXT
$\backslash\text{underbracket} \{\dots \overset{*}{=} \dots\}$ \ast TEXT
$\backslash\text{underbrackettext} \{\dots \overset{1}{=} \dots\} \{\dots \overset{2}{=} \dots\}$ 1 TEXT 2 TEXT
$\backslash\text{underdash} \{\dots \overset{*}{=} \dots\}$ \ast CONTENT

\underdashes {...} * CONTENT
\underdot {...} * CONTENT
\underdots {...} * CONTENT
\underleftarrow {...} * TEXT
\underleftharpoonowdown {...} * TEXT
\underleftharpoonowup {...} * TEXT
\underleftrightharpoonow {...} * TEXT
\underparent {...} * TEXT
\underparenttext {... ¹ } {... ² } 1 TEXT 2 TEXT
\underrandom {...} * CONTENT
\underrandoms {...} * CONTENT
\underrightharpoonow {...} * TEXT
\underrightharpoonowdown {...} * TEXT
\underrightharpoonowup {...} * TEXT
\underset {... ¹ } {... ² } 1 TEXT 2 TEXT

$\backslash\text{understrike}\{\dots\}$ * CONTENT
$\backslash\text{understrikes}\{\dots\}$ * CONTENT
$\backslash\text{undertwoheadleftarrow}\{\dots\}$ * TEXT
$\backslash\text{undertwoheadrightarrow}\{\dots\}$ * TEXT
$\backslash\text{undoassign}[\dots][\dots^2]$ 1 TEXT 2 KEY = VALUE
$\backslash\text{unframed}[\dots,\dots^1,\dots]\{\dots^2\}$ <small>OPT</small> 1 inherits: $\backslash\text{nastavoramovani}$ 2 CONTENT
$\backslash\text{unhhbox}\dots^1\backslash\text{with}\{\dots^2\}$ 1 CSNAME NUMBER 2 BEFEHL
$\backslash\text{unihex}\{\dots\}$ * NUMMER
$\backslash\text{uniqueMPgraphic}\{\dots\}\{\dots,\dots^2,\dots\}$ <small>OPT</small> 1 NAME 2 KEY = VALUE
$\backslash\text{uniqueMPpagegraphic}\{\dots\}\{\dots,\dots^2,\dots\}$ <small>OPT</small> 1 NAME 2 KEY = VALUE
$\backslash\text{unprotect}\dots\backslash\text{protect}$
$\backslash\text{unprotected}\dots^*\backslash\text{par}$ * CONTENT
$\backslash\text{unregisterhyphenationpattern}[\dots^1][\dots^2]$ <small>OPT</small> 1 SPRACHE 2 TEXT
$\backslash\text{unspaceafter}\dots^1\{\dots^2\}$ 1 CSNAME 2 TEXT

$\backslash\text{unspaceargument } \dots \backslash\text{to } \dots$ 1 TEXT 2 CSNAME
$\backslash\text{unspaced } \{ \dots \}$ * TEXT
$\backslash\text{unspacestring } \dots \backslash\text{to } \dots$ 1 TEXT 2 CSNAME
$\backslash\text{untexargument } \{ \dots \} \backslash\text{to } \dots$ 1 TEXT 2 CSNAME
$\backslash\text{untexcommand } \{ \dots \} \backslash\text{to } \dots$ 1 CSNAME 2 CSNAME
$\backslash\text{uppercased } \{ \dots \}$ * TEXT
$\backslash\text{uppercasestring } \dots \backslash\text{to } \dots$ 1 TEXT 2 CSNAME
$\backslash\text{upperlefthdoubleninequote}$
$\backslash\text{upperlefthdoublesixquote}$
$\backslash\text{upperleftsingleninequote}$
$\backslash\text{upperleftsinglesixquote}$
$\backslash\text{upperrighthdoubleninequote}$
$\backslash\text{upperrighthdoublesixquote}$
$\backslash\text{upperrightsingleninequote}$
$\backslash\text{upperrightsinglesixquote}$
$\backslash\text{urcicharakteristikurejstriku } [\dots] [\dots, \dots, \dots]$ 1 NAME 2 language = implicitni DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scن SPRACHE metoda = implicitni pred po prvni posledni ch mm zm pm mc zc pc uc numberorder = cislأ compress = ano ne vse kriterium = lokalne text aktualni predchozi vse ABSCHNITT

\url [...] * NAME
\usealignparameter \... * CSNAME
\useblankparameter \... * CSNAME
\usebodyfont [...,*,...] * inherits: \nastavzakladnifont
\usebodyfontparameter \... * CSNAME
\usebtxdataset [...] [...] [...] [...] [...] <div style="display: flex; justify-content: space-around; font-size: small;"> ¹ OPT ² OPT ³ OPT </div> 1 NAME 2 FILE 3 specification = NAME
\usebtxdefinitions [...] * FILE
\usecolors [...] * FILE
\usecomponent [...] * FILE
\usedummycolorparameter {...} * KEY
\usedummystyleandcolor {...} {...} 1 KEY 2 KEY
\usedummystyleparameter {...} * KEY
\useenvironment [...] * FILE
\useexternalrendering [...] [...] [...] [...] 1 NAME 2 NAME 3 FILE 4 auto embed

<code>\usefigurebase [...]</code> * reset FILE
<code>\usefile [...]¹ [...]² [...]³</code> <div style="text-align: right; margin-right: 100px;"><small>OPT</small></div> 1 NAME 2 FILE 3 TEXT
<code>\usegridparameter *...</code> * CSNAME
<code>\useindentingparameter *...</code> * CSNAME
<code>\useindentnextparameter *...</code> * CSNAME
<code>\useinterlinespaceparameter *...</code> * CSNAME
<code>\uselanguageparameter *...</code> * CSNAME
<code>\uselua module [...]</code> * FILE
<code>\useMPenvironmentbuffer [...]</code> * NAME
<code>\useMPgraphic {...}¹ {...,²...,...}</code> <div style="text-align: right; margin-right: 100px;"><small>OPT</small></div> 1 NAME 2 KEY = VALUE
<code>\useMPlibrary [...]</code> * FILE
<code>\useMPrun {...}¹ {...}²</code> 1 NAME 2 NUMMER
<code>\useMPvariables [...]¹ [...,²...,...]</code> 1 NAME 2 KEY
<code>\usemathstyleparameter *...</code> * CSNAME

* FILE

* CSNAME

* FILE

* CSNAME

* CSNAME

2 NAME

* PATH

3 KEY = VALUE

3 size jmeno

```
*  reset FILE
```

2 FILE

* NUMMER

* TEXT

\utfupper {...} * TEXT
\utilityregisterlength
\uzijadresar [...*,...] * PATH
\uzijbloky [... ¹ ,...] [... ² ,...] [... ³ ,... ³ ,...] <div> <div>OPT</div> <div>OPT</div> </div> 1 NAME 2 + - 3 kriterium = text ABSCHNITT
\uzijexternidokument [... ¹] [... ²] [... ³] <div> <div>OPT</div> </div> 1 NAME 2 FILE 3 TEXT
\uzijexterniobraz [... ¹] [... ²] [... ³] [... ⁴ ,... ⁴ ,...] <div> <div>OPT</div> <div>OPT</div> </div> 1 NAME 2 FILE 3 NAME 4 inherits: \setuexternalfigure
\uzijexternizvuk [... ¹] [... ²]
\uzijJSscripts [... ¹] [... ² ,...] <div> <div>OPT</div> </div> 1 FILE 2 NAME
\uzijmodul [... ¹] [... ² ,...] [... ³ ,... ³ ,...] <div> <div>OPT</div> <div>OPT</div> </div> 1 m p s x t 2 FILE 3 KEY = VALUE
\uzijsymbol [...*] * FILE
\uzijURL [... ¹] [... ²] [... ³] [... ⁴] <div> <div>OPT</div> <div>OPT</div> </div> 1 NAME 2 URL 3 FILE 4 TEXT

<p><code>\uzijurl [...]¹ [...]² [...]³ [...]⁴</code></p> <p>1 NAME</p> <p>2 URL</p> <p>3 FILE</p> <p>4 TEXT</p> <p>OPT OPT</p>
<p><code>\VerboseNumber {...}</code></p> <p>* NUMMER</p>
<p><code>\VSEDNIDEN {...}</code></p> <p>* NUMMER</p>
<p><code>\vboxreference [...]¹, [...]² {...}</code></p> <p>1 REFERENCE</p> <p>2 CONTENT</p>
<p><code>\vec {...}</code></p> <p>* CHARACTER</p>
<p><code>\velke ...</code></p> <p>* CHARACTER</p>
<p><code>\verbatim {...}</code></p> <p>* CONTENT</p>
<p><code>\verbatimstring {...}</code></p> <p>* CONTENT</p>
<p><code>\verbosenummer {...}</code></p> <p>* NUMMER</p>
<p><code>\verticalgrowingbar [...][*]..., ...]</code></p> <p>* inherits: \setuppositionbar</p>
<p><code>\verticalpositionbar [...][*]..., ...]</code></p> <p>* inherits: \setuppositionbar</p>
<p><code>\veryraggedcenter</code></p>
<p><code>\veryraggedleft</code></p>
<p><code>\veryraggedright</code></p>
<p><code>\verze [...][*]</code></p> <p>* koncept soubor docasne finalni NAME</p>
<p><code>\vglue ...[*]</code></p> <p>* DIMENSION</p>

$\backslash\text{viewerlayer}$ [¹ ...] { ² ...} 1 NAME 2 CONTENT
$\backslash\text{vl}$ [¹ ...] _{OPT} * NUMMER
$\backslash\text{vlasovalinka}$
$\backslash\text{vlevo}$... * CHARACTER
$\backslash\text{vphantom}$ { ¹ ...} * CONTENT
$\backslash\text{vpos}$ { ¹ ...} { ² ...} 1 NAME 2 CONTENT
$\backslash\text{vpravo}$... * CHARACTER
$\backslash\text{vradku}$ { ¹ ...} [_{OPT} ² ...] 1 TEXT 2 REFERENCE
$\backslash\text{vsedniden}$ { ¹ ...} * NUMMER
$\backslash\text{vsmash}$ { ¹ ...} * CONTENT
$\backslash\text{vsmashbox}$... * CSNAME NUMMER
$\backslash\text{vsmashed}$ { ¹ ...} * CONTENT
$\backslash\text{vspace}$ [_{OPT} ¹ ...] [_{OPT} ² ...] 1 NAME 2 NAME
$\backslash\text{vspacing}$ [_{OPT} ...*...] * nastaveni stejnastranka max sila enable zablockovat zadnabila zpet prekryv vzdy weak strong implicitni pred mezi po fixne prizpusobive zadny male stredni velke radek pulradku quarterline rovnice bily vyska podlehloubky standardni NUMMER*male NUMMER*stredni NUMMER*velke NUMMER*radek NUMMER*pulradku NUMMER*quarterline NUMMER*rovnice NUMMER*bily NUMMER*vyska NUMMER*podlehloubky category:NUMMER order:NUMMER penalty:NUMMER DIMENSION NAME

$\backslash\text{vyberbloky} [\dots,\overset{1}{\dots}] [\dots,\overset{2}{\dots}] [\dots,\overset{3}{\dots},\dots]$ $\text{OPT} \qquad \text{OPT} \qquad \text{OPT}$ <p>1 NAME</p> <p>2 + -</p> <p>3 kriterium = text ABSCHNITT</p>
$\backslash\text{VYCET} [\dots,\overset{1}{\dots}] \{\dots,\overset{2}{\dots}\} \overset{3}{\dots} \backslash\text{par}$ $\text{OPT} \qquad \text{OPT}$ <p>1 REFERENCE</p> <p>2 TEXT</p> <p>3 CONTENT</p>
$\backslash\text{vyplnenytext} [\dots,\overset{1}{\dots},\dots] \{\dots,\overset{2}{\dots}\} \{\dots,\overset{3}{\dots}\}$ $\text{OPT} \qquad \text{OPT} \qquad \text{OPT}$ <p>1 inherits: \nastavvyplnovelinky</p> <p>2 TEXT</p> <p>3 TEXT</p>
$\backslash\text{vyplnovelinky} [\dots,\overset{1}{\dots},\dots] \{\dots,\overset{2}{\dots}\} \{\dots,\overset{3}{\dots}\}$ $\text{OPT} \qquad \text{OPT} \qquad \text{OPT}$ <p>1 inherits: \nastavvyplnovelinky</p> <p>2 TEXT</p> <p>3 TEXT</p>
$\backslash\text{vyplnovyradek} [\dots,\overset{*}{\dots},\dots]$ <p>* inherits: \nastavvyplnoveradky</p>
$\backslash\text{vysoky} \{\dots,\overset{*}{\dots}\}$ <p>* CONTENT</p>
$\backslash\text{HIGH} \{\dots,\overset{*}{\dots}\}$ <p>* CONTENT</p> <p>instances:</p>
$\backslash\text{WidthSpanningText} \{\dots,\overset{1}{\dots}\} \{\dots,\overset{2}{\dots}\} \{\dots,\overset{3}{\dots}\}$ <p>1 TEXT</p> <p>2 DIMENSION</p> <p>3 FONT</p>
$\backslash\text{wdofstring} \{\dots,\overset{*}{\dots}\}$ <p>* TEXT</p>
$\backslash\text{widthhofstring} \{\dots,\overset{*}{\dots}\}$ <p>* TEXT</p>
$\backslash\text{widthspanningtext} \{\dots,\overset{1}{\dots}\} \{\dots,\overset{2}{\dots}\} \{\dots,\overset{3}{\dots}\}$ <p>1 TEXT</p> <p>2 DIMENSION</p> <p>3 FONT</p>

$\backslash\mathrm{withoutpt}\{\dots\}$ * DIMENSION
$\backslash\mathrm{words}\{\dots\}$ * TEXT
$\backslash\mathrm{wordtonumber}\{\dots\}^1\{\dots\}^2$ 1 jedna dva tri čtyři pět 2 TEXT
$\backslash\mathrm{writedatatolist}\left[\dots\right]^1\left[\dots,\dots\overset{2}{=}\dots,\dots\right]^{\mathrm{OPT}}\left[\dots,\dots\overset{3}{=}\dots,\dots\right]$ 1 LISTE 2 inherits: $\backslash\mathrm{nastavseznam}$ 3 KEY = VALUE
$\backslash\mathrm{writestatus}\{\dots\}^1\{\dots\}^2$ 1 TEXT 2 TEXT
$\backslash\mathrm{XETEX}$
$\backslash\mathrm{XeTeX}$
$\backslash\mathrm{xdefconvertedargument}\backslash\dots\{\dots\}^1\{\dots\}^2$ 1 CSNAME 2 TEXT
$\backslash\mathrm{xequal}\{\dots\}^1_{\mathrm{OPT}}\{\dots\}^2_{\mathrm{OPT}}$ 1 TEXT 2 TEXT
$\backslash\mathrm{xfrac}\{\dots\}^1\{\dots\}^2$ 1 CONTENT 2 CONTENT
$\backslash\mathrm{xhookleftarrow}\{\dots\}^1_{\mathrm{OPT}}\{\dots\}^2_{\mathrm{OPT}}$ 1 TEXT 2 TEXT
$\backslash\mathrm{xhookrightarrow}\{\dots\}^1_{\mathrm{OPT}}\{\dots\}^2_{\mathrm{OPT}}$ 1 TEXT 2 TEXT
$\backslash\mathrm{xLeftarrow}\{\dots\}^1_{\mathrm{OPT}}\{\dots\}^2_{\mathrm{OPT}}$ 1 TEXT 2 TEXT

`\xLeftrightarrow {...} {...}`
OPT OPT

1 TEXT

2 TEXT

`\xleftarrow {...} {...}`
OPT OPT

1 TEXT

2 TEXT

`\xleftharpoonup {...} {...}`
OPT OPT

1 TEXT

2 TEXT

`\xleftharpoonup {...} {...}`
OPT OPT

1 TEXT

2 TEXT

`\xleftrightharpoonup {...} {...}`
OPT OPT

1 TEXT

2 TEXT

`\xleftrightharpoons {...} {...}`
OPT OPT

1 TEXT

2 TEXT

`\xmapsto {...} {...}`
OPT OPT

1 TEXT

2 TEXT

`\xmladdindex {...}`

* NODE

`\xmllaftersetup {...} {...} {...}`

1 NAME

2 SETUP

3 SETUP

`\xmllaftersetup {...} {...}`

1 SETUP

2 SETUP

`\xmlall {...} {...}`

1 NODE

2 LPATH

`\xmlappenddocumentsetup {...} {...}`

1 NAME

2 SETUP

\xmlappendsetup {...}

* SETUP

\xmlapplyselectors {...}

* NODE

\xmlatt {...} {...}

1 NODE

2 NAME

\xmlattdef {...} {...} {...}

1 NODE

2 NAME

3 TEXT

\xmlattribute {...} {...} {...}

1 NODE

2 LPATH

3 NAME

\xmlattributedef {...} {...} {...} {...}

1 NODE

2 LPATH

3 NAME

4 TEXT

\xmlbadinclusions {...}

* NODE

\xmlbeforedocumentsetup {...} {...} {...}

1 NAME

2 SETUP

3 SETUP

\xmlbeforesetup {...} {...}

1 SETUP

2 SETUP

\xmlcommand {...} {...} {...}

1 NODE

2 LPATH

3 XMLSETUP

\xmlconcat {...} {...} {...}

1 NODE

2 LPATH

3 TEXT

`\xmlconcatrange {...} {...} {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 TEXT
- 4 FIRST
- 5 LAST

`\xmlcontext {...} {...}`

- 1 NODE
- 2 LPATH

`\xmlcount {...}`

- * NODE

`\xmldefaulttotext {...}`

- * NODE

`\xmldirectives {...}`

- * NODE

`\xmldirectivesafter {...}`

- * NODE

`\xmldirectivesbefore {...}`

- * NODE

`\xmldisplayverbatim {...}`

- * NODE

`\xmldoif {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 TRUE

`\xmldoifelse {...} {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 TRUE
- 4 FALSE

`\xmldoifelseempty {...} {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 TRUE
- 4 FALSE

`\xmldoifselfempty {...} {...} {...}`

- 1 NODE
- 2 TRUE
- 3 FALSE

`\xmldoifsettext {...} {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 TRUE
- 4 FALSE

`\xmldoifelsevalue {...} {...} {...} {...}`

- 1 CATEGORY
- 2 NAME
- 3 TRUE
- 4 FALSE

`\xmldoifnot {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 TRUE

`\xmldoifnotselfempty {...} {...}`

- 1 NODE
- 2 TRUE

`\xmldoifnottext {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 TRUE

`\xmldoifselfempty {...} {...}`

- 1 NODE
- 2 TRUE

`\xmldoiftext {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 TRUE

`\xmlelement {...} {...}`

- 1 NODE
- 2 NUMMER

`\xmlfilter {...} {...}`

- 1 NODE
- 2 LPATH

<pre> \xmlfirst {...} {...} 1 NODE 2 LPATH </pre>
<pre> \xmlflush {...} * NODE </pre>
<pre> \xmlflushcontext {...} * NODE </pre>
<pre> \xmlflushdocumentsetups {...} {...} 1 NAME 2 SETUP </pre>
<pre> \xmlflushlinewise {...} * NODE </pre>
<pre> \xmlflushpure {...} * NODE </pre>
<pre> \xmlflushspacewise {...} * NODE </pre>
<pre> \xmlflushtext {...} * NODE </pre>
<pre> \xmlchainatt {...} {...} 1 NODE 2 NAME </pre>
<pre> \xmlchainattdef {...} {...} {...} 1 NODE 2 NAME 3 TEXT </pre>
<pre> \xmlchecknamespace {...} {...} 1 NODE 2 NAME </pre>
<pre> \xmlinclude {...} {...} {...} 1 NODE 2 LPATH 3 NAME </pre>
<pre> \xmlinclusion {...} * NODE </pre>

\xmlinclusions {...} * NODE
\xmlinfo {...} * NODE
\xmlinjector {...} * NAME
\xmlinlineverbatim {...} * NODE
\xmlinstalldirective {...} {...} 1 NAME 2 CSNAME
\xmllast {...} {...} 1 NODE 2 LPATH
\xmllastatt
\xmllastmatch
\xmlloadbuffer {...} {...} {...} 1 BUFFER 2 NAME 3 XMLSETUP
\xmlloaddata {...} {...} {...} 1 NAME 2 TEXT 3 XMLSETUP
\xmlloaddirectives {...} * FILE
\xmlloadfile {...} {...} {...} 1 NAME 2 FILE 3 XMLSETUP
\xmlloadonly {...} {...} {...} 1 NAME 2 FILE 3 XMLSETUP

<code>\xmlmain {...}</code> * NAME
<code>\xmlmapvalue {.¹.} {.².} {.³.}</code> 1 CATEGORY 2 NAME 3 TEXT
<code>\xmlname {...}</code> * NODE
<code>\xmlnamespace {...}</code> * NODE
<code>\xmlnonspace {.¹.} {.².}</code> 1 NODE 2 LPATH
<code>\xmlpath {...}</code> * NODE
<code>\xmlpos {...}</code> * NODE
<code>\xmlposition {.¹.} {.².} {.³.}</code> 1 NODE 2 LPATH 3 NUMMER
<code>\xmlprependdocumentsetup {.¹.} {.².}</code> 1 NAME 2 SETUP
<code>\xmlprependsetup {...}</code> * SETUP
<code>\xmlprettyprint {.¹.} {.².}</code> 1 NODE 2 NAME
<code>\xmlprocessbuffer {.¹.} {.².} {.³.}</code> 1 BUFFER 2 NAME 3 XMLSETUP

\xmlprocessdata {...} {...} {...}

- 1 NAME
- 2 TEXT
- 3 XMLSETUP

\xmlprocessfile {...} {...} {...}

- 1 NAME
- 2 FILE
- 3 XMLSETUP

\xmlpure {...} {...}

- 1 NODE
- 2 LPATH

\xmlraw {...}

- * NODE

\xmlrefatt {...} {...}

- 1 NODE
- 2 NAME

\xmlregistereddokumentsetups {...} {...}

- 1 NAME
- 2 SETUP

\xmlregisteredsetups

\xmlregisterns {...} {...}

- 1 NAME
- 2 URL

\xmlremapname {...} {...} {...} {...}

- 1 NODE
- 2 LPATH
- 3 NAME
- 4 NAME

\xmlremapnamespace {...} {...} {...}

- 1 NODE
- 2 NAME
- 3 NAME

\xmlremovedokumentsetup {...} {...}

- 1 NAME
- 2 SETUP

\xmlremovesetup {...} * SETUP
\xmlresetdocumentsetups {...} * NAME
\xmlresetinjectors
\xmlresetsetups {...} * NAME
\xmlsave {...} {...} 1 NODE 2 FILE
\xmlsetentity {...} {...} 1 NAME 2 TEXT
\xmlsetfunction {...} {...} {...} 1 NODE 2 LPATH 3 LUAFUNCTION
\xmlsetinjectors [...,*,...] * NAME
\xmlsetsetup {...} {...} {...} 1 NAME 2 LPATH 3 SETUP
\xmlsetup {...} {...} 1 NODE 2 SETUP
\xmlshow {...} * NODE
\xmlsnippet {...} {...} 1 NODE 2 NUMMER
\xmlstrip {...} {...} 1 NODE 2 LPATH

<pre> \xmlstripnolines {...} {...} 1 NODE 2 LPATH </pre>
<pre> \xmlstripped {...} {...} 1 NODE 2 LPATH </pre>
<pre> \xmlstrippednolines {...} {...} 1 NODE 2 LPATH </pre>
<pre> \xmltag {...} * NODE </pre>
<pre> \xmltexentity {...} {...} 1 NAME 2 TEXT </pre>
<pre> \xmltext {...} {...} 1 NODE 2 LPATH </pre>
<pre> \xmltobuffer {...} {...} {...} 1 NODE 2 LPATH 3 BUFFER </pre>
<pre> \xmltobufferverbose {...} {...} {...} 1 NODE 2 LPATH 3 BUFFER </pre>
<pre> \xmltofile {...} {...} {...} 1 NODE 2 LPATH 3 FILE </pre>
<pre> \xmlvalue {...} {...} {...} 1 CATEGORY 2 NAME 3 TEXT </pre>
<pre> \xmlverbatim {...} * NODE </pre>

1	TEXT
2	TEXT

1	TEXT
2	TEXT

1	TEXT
2	TEXT

1	TEXT
2	TEXT

1	TEXT
2	TEXT

1	TEXT
2	TEXT

1	TEXT
2	TEXT

```
1  CSNAME
2  TEXT
```

1	TEXT
2	TEXT

```
1  TEXT
2  TEXT
```

1	TEXT
2	TEXT

1 CONTENT

2 CONTENT

\xypos {...} * NAME
\Znak {...} * NUMMER
\Znaky {...} * NUMMER
\zadnamezera
\zadnehorniadolniradky
\zadnezahlaviaupati
\zachovejbloky [...; ¹ ...] [...; ² ...] <small>OPT</small> 1 NAME 2 + -
\zalozka [...] ¹ {...} ² <small>OPT</small> 1 ABSCHNITT LISTE 2 TEXT
\zapisdoseznamu [...] ¹ [...; ² ...] ³ {...} ⁴ {...} <small>OPT</small> 1 LISTE 2 inherits: \nastavseznam 3 NUMMER 4 TEXT
\zapismeziseznam [...] ¹ [...; ² ...] ³ {...} <small>OPT</small> 1 LISTE 2 inherits: \nastavseznam 3 BEFEHL
\zaramovani [...; ¹ ...] ² {...} <small>OPT</small> 1 inherits: \nastavoramovani 2 CONTENT
\zarovnanonastred {...} * CONTENT
\zarovnanovlevo {...} * CONTENT
\zarovnanovpravo {...} * CONTENT

<p><code>\zasobnikpoli [...]¹ [...]²,...] [...]³,...]</code></p> <p style="text-align: center;"><small>OPT OPT</small></p> <p>1 NAME</p> <p>2 NAME</p> <p>3 inherits: \setupfieldcategory</p>
<p><code>\ziskejbuffer [...]</code></p> <p style="text-align: center;"><small>OPT</small></p> <p>* BUFFER</p>
<p><code>\ziskatBUFFER</code></p>
<p><code>\ziskejznaceni [...]¹ [...]² [...]³</code></p> <p style="text-align: center;"><small>OPT OPT</small></p> <p>1 BESCHRIFTUNG</p> <p>2 stranka NAME</p> <p>3 prvni posledni aktualni predchozi dalsi vrsek spodek implicitni obe vse first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck</p>
<p><code>\FRACTION {...}¹ {...}²</code></p> <p>1 CONTENT</p> <p>2 CONTENT</p> <p>instances: xfrac xxfrac frac sfrac dfrac binom dbinom tbinom</p>
<p><code>\znaceni (...)¹,...) (...)²,...) [...]³</code></p> <p>1 POSITION</p> <p>2 POSITION</p> <p>3 REFERENCE</p>
<p><code>\znak {...}</code></p> <p>* NUMMER</p>
<p><code>\znaky {...}</code></p> <p>* NUMMER</p>
<p><code>\zpracujbloky [...]¹,...] [...]²,...] [...]³,...]</code></p> <p style="text-align: center;"><small>OPT OPT</small></p> <p>1 NAME</p> <p>2 + -</p> <p>3 kriterium = text ABSCHNITT</p>
<p><code>\zrcadlit {...}</code></p> <p>* CONTENT</p>
<p><code>\zref [...]</code></p> <p>* REFERENCE</p>
<p><code>\zvysit *..</code></p> <p>* CSNAME</p>

```
\zvysit cd:parentheses-1
```

```
* CSNAME NUMMER
```




PRAGMA ADE
Ridderstraat 27
8061GH Hasselt NL
www.pragma-ade.com