



# ConTeXt

commands

# EN



# ConTeXt

## commands

en / english  
July 19, 2016



<code>\AfterPar {...}</code>  *    COMMAND
<code>\Alphabeticnumerals {...}</code>  *    NUMBER
<code>\AMSTEX</code>
<code>\AmSTeX</code>
<code>\And</code>
<code>\abbreviation [...]<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup></code>  1    NAME 2    TEXT 3    CONTENT
<code>\abjadnaivenumerals {...}</code>  *    NUMBER
<code>\abjadnodotnumerals {...}</code>  *    NUMBER
<code>\abjadnumerals {...}</code>  *    NUMBER
<code>\about [...]</code>  *    REFERENCE
<code>\activatespacehandler {...}</code>  *    on <u>off</u> yes fixed
<code>\acute {...}</code>  *    CHARACTER
<code>\adaptcollector [...]<sup>1</sup> [...,...<sup>2</sup>...,...]</code>  1    NAME 2    inherits: \setupcollector
<code>\adaptlayout [...,<sup>1</sup>...] [...,...<sup>2</sup>...,...]</code>  1    NUMBER 2    height = max DIMENSION lines = NUMBER
<code>\adaptpapersize [...,<sup>1</sup>...] [...,<sup>2</sup>...]</code>  1    inherits: \setuppapersize 2    inherits: \setuppapersize

<p><code>\addfeature [...]</code></p> <p>*    NAME</p>
<p><code>\addfeature {...}</code></p> <p>*    NAME</p>
<p><code>\addtocommalist {...} \.^{2..}</code></p> <p>1    TEXT</p> <p>2    CSNAME</p>
<p><code>\addtoJSreamble {...} {...}^{2..}</code></p> <p>1    NAME</p> <p>2    CONTENT</p>
<p><code>\addvalue {...} {...}^{2..}</code></p> <p>1    NAME</p> <p>2    TEXT</p>
<p><code>\aftersplitstring .^{1..} \at .^{2..} \to \.^{3..}</code></p> <p>1    TEXT</p> <p>2    TEXT</p> <p>3    CSNAME</p>
<p><code>\aftertestandsplitstring .^{1..} \at .^{2..} \to \.^{3..}</code></p> <p>1    TEXT</p> <p>2    TEXT</p> <p>3    CSNAME</p>
<p><code>\alignbottom</code></p>
<p><code>\aligned [...,^{1..},...] {...}^{2..}</code></p> <p>1    left middle right top bottom line l c r m t b g</p> <p>2    CONTENT</p>
<p><code>\alignedbox [...,^{1..},...] \.^{2..} {...}^{3..}</code></p> <p>1    left middle right top bottom line l c r m t b g</p> <p>2    CSNAME</p> <p>3    CONTENT</p>
<p><code>\alignedline {...}^{1..} {...}^{2..} {...}^{3..}</code></p> <p>1    left right middle flushleft flushright center max inner outer innermargin outermargin inneredge outeredge backspace cutspace leftmargin rightmargin leftedge rightedge</p> <p>2    left right middle flushleft flushright center max inner outer innermargin outermargin inneredge outeredge backspace cutspace leftmargin rightmargin leftedge rightedge</p> <p>3    CONTENT</p>
<p><code>\alignmentcharacter</code></p>
<p><code>\allinputpaths</code></p>

`\alphabeticnumerals {...}`

\* NUMBER

`\alwayscitation [...1...][...2]`

```
1 reference = REFERENCE
  alternative = default category entry short page num textnum year index tag keywords author authoryears authornum
    authoryear
  before = COMMAND
  after = COMMAND
  left = COMMAND
  right = COMMAND
  inherits: \setupbtx

2 REFERENCE
```

`\alwayscitation [...1...][...2...]`

```
1 reference = REFERENCE
  alternative = default category entry short page num textnum year index tag keywords author authoryears authornum
    authoryear
  before = COMMAND
  after = COMMAND
  left = COMMAND
  right = COMMAND
  inherits: \setupbtx

2 KEY = VALUE
```

`\alwayscitation [...1][...2]`

```
1 default category entry short page num textnum year index tag keywords author authoryears authornum authoryear

2 REFERENCE
```

`\alwayscite [...1...][...2]`

```
1 reference = REFERENCE
  alternative = default category entry short page num textnum year index tag keywords author authoryears authornum
    authoryear
  before = COMMAND
  after = COMMAND
  left = COMMAND
  right = COMMAND
  inherits: \setupbtx

2 REFERENCE
```

`\alwayscite [...1...][...2...]`

```
1 reference = REFERENCE
  alternative = default category entry short page num textnum year index tag keywords author authoryears authornum
    authoryear
  before = COMMAND
  after = COMMAND
  left = COMMAND
  right = COMMAND
  inherits: \setupbtx

2 KEY = VALUE
```

`\alwayscite [...1][...2]`

```
1 default category entry short page num textnum year index tag keywords author authoryears authornum authoryear

2 REFERENCE
```

`\ampersand`

**\anchor** [<sup>1</sup>...] [<sup>2</sup>...<sub>2</sub>...] [<sup>3</sup>...<sub>3</sub>...] {<sup>4</sup>...}

- 1 NAME
- 2 inherits: \setupplayer
- 3 inherits: \setupplayerinherits: \setupframed
- 4 CONTENT

**\appendetoks** <sup>1</sup>... \to \<sup>2</sup>...

- 1 COMMAND
- 2 CSNAME

**\appendgvalue** {<sup>1</sup>...} {<sup>2</sup>...}

- 1 NAME
- 2 COMMAND

**\appendtocommalist** {<sup>1</sup>...} \<sup>2</sup>...

- 1 TEXT
- 2 CSNAME

**\appendtoks** <sup>1</sup>... \to \<sup>2</sup>...

- 1 COMMAND
- 2 CSNAME

**\appendtoksonce** <sup>1</sup>... \to \<sup>2</sup>...

- 1 COMMAND
- 2 CSNAME

**\appendvalue** {<sup>1</sup>...} {<sup>2</sup>...}

- 1 NAME
- 2 COMMAND

**\apply** {<sup>1</sup>...} {<sup>2</sup>...}

- 1 CONTENT
- 2 CONTENT

**\applyalternativestyle** {<sup>\*</sup>...}

- \* NAME

**\applyprocessor** {<sup>1</sup>...} {<sup>2</sup>...}

- 1 NAME
- 2 CONTENT

**\applytocharacters** \<sup>1</sup>... {<sup>2</sup>...}

- 1 CSNAME
- 2 TEXT



`\applytofirstcharacter \1... {2...}`

1 CSNAME

2 TEXT

`\applytosplitstringchar \1... {2...}`

1 CSNAME

2 TEXT

`\applytosplitstringcharspaced \1... {2...}`

1 CSNAME

2 TEXT

`\applytosplitstringline \1... {2...}`

1 CSNAME

2 TEXT

`\applytosplitstringlinespaced \1... {2...}`

1 CSNAME

2 TEXT

`\applytosplitstringword \1... {2...}`

1 CSNAME

2 TEXT

`\applytosplitstringwordspaced \1... {2...}`

1 CSNAME

2 TEXT

`\applytowords \1... {2...}`

1 CSNAME

2 TEXT

`\arabicdecimals {*...}`

\* NUMBER

`\arabicexnumerals {*...}`

\* NUMBER

`\arabicnumerals {*...}`

\* NUMBER

`\arg {*...}`

\* CONTENT

`\asciistr {*...}`

\* CONTENT

`\assignalfadimension {...} \^2... {...} {...} {...}`

1    small medium big none DIMENSION  
2    CSNAME  
3    DIMENSION  
4    DIMENSION  
5    DIMENSION

`\assigndimen \^1... {...}`

1    CSNAME  
2    DIMENSION

`\assigndimension {...} \^2... {...} {...} {...}`

1    [-+]small [-+]medium [-+]big none DIMENSION  
2    CSNAME  
3    DIMENSION  
4    DIMENSION  
5    DIMENSION

`\assignifempty \^1... {...}`

1    CSNAME  
2    COMMAND

`\assigntranslation [...,\^1...,\^2...]\to \^2...`

1    LANGUAGE = TEXT  
2    CSNAME

`\assignvalue {...} \^2... {...} {...} {...}`

1    small medium big TEXT  
2    CSNAME  
3    COMMAND  
4    COMMAND  
5    COMMAND

`\assignwidth {...} \^2... {...} {...}`

1    fit broad DIMENSION  
2    CSNAME  
3    TEXT  
4    DIMENSION

`\assumelongusagecs \^1... {...}`

1    CSNAME  
2    CONTENT

`\astype {...}`

\*    CONTENT

`\at {...} {...} [...]`

- 1 TEXT
- 2 TEXT
- 3 REFERENCE

`\atleftmargin [...]\atleftmargin [...] {...}`

- 1 reference = REFERENCE  
inherits: \setupmargindata
- 2 inherits: \setupmarginframed
- 3 CONTENT

`\atpage [...]`

- \* REFERENCE

`\atrighmargin [...]\atrighmargin [...] {...}`

- 1 reference = REFERENCE  
inherits: \setupmargindata
- 2 inherits: \setupmarginframed
- 3 CONTENT

`\attachment [...] [...]\attachment [...]`

- 1 NAME
- 2 inherits: \setupattachment

`\attachment [...] [...]\attachment [...]`

- 1 NAME
- 2 inherits: \setupattachment

`\autocap {...}`

- \* TEXT

`\autodirhbox ... {...}`

- 1 TEXT
- 2 CONTENT

`\autodirvbox ... {...}`

- 1 TEXT
- 2 CONTENT

`\autodirvtop ... {...}`

- 1 TEXT
- 2 CONTENT

`\autoinsertnextspace`

`\automathematics {...}`

- \* CONTENT

$\backslash\text{autosetups } \{ \dots, \dots \}$ * NAME
$\backslash\text{autostarttext } \dots \backslash\text{autostoptext}$
$\backslash\text{availablehsize}$
$\backslash\text{averagecharwidth}$
$\backslash\text{BeforePar } \{ \dots \}$ * COMMAND
$\backslash\text{Big } \dots$ * CHARACTER
$\backslash\text{Bigg } \dots$ * CHARACTER
$\backslash\text{Biggl } \dots$ * CHARACTER
$\backslash\text{Biggm } \dots$ * CHARACTER
$\backslash\text{Biggr } \dots$ * CHARACTER
$\backslash\text{Bigl } \dots$ * CHARACTER
$\backslash\text{Bigm } \dots$ * CHARACTER
$\backslash\text{Bigr } \dots$ * CHARACTER
$\backslash\text{background } \{ \dots \}$ * CONTENT
$\backslash\text{backgroundimage } \{ \dots^1 \} \{ \dots^2 \} \{ \dots^3 \} \{ \dots^4 \}$ 1 NUMBER 2 DIMENSION 3 DIMENSION 4 COMMAND

`\backgroundimagefill {...} {...} {...} {...}`

- 1 NUMBER
- 2 DIMENSION
- 3 DIMENSION
- 4 COMMAND

`\backgroundline [...] {...}`

- 1 COLOR
- 2 CONTENT

`\background {...}`

- \* CONTENT

`\bar {...}`

- \* CHARACTER

`\bar {...}`

- \* CONTENT

`\basegrid [..., ...*..., ...]`

- \* nx = NUMBER
- ny = NUMBER
- dx = NUMBER
- dy = NUMBER
- factor = NUMBER
- scale = NUMBER
- xstep = NUMBER
- ystep = NUMBER
- offset = DIMENSION
- xoffset = DIMENSION
- yoffset = DIMENSION
- align = middle
- unit = cm mm in pc pt bp
- style = STYLE COMMAND
- color = COLOR

`\baselinebottom`

`\baselineleftbox {...}`

- \* CONTENT

`\baselinemiddlebox {...}`

- \* CONTENT

`\baselinerightbox {...}`

- \* CONTENT

`\bbox {...}`

- \* CONTENT

<code>\beforestrutstring ... \at ... \to \...</code> 1 TEXT 2 TEXT 3 CSNAME
<code>\beforetestandsplitstring ... \at ... \to \...</code> 1 TEXT 2 TEXT 3 CSNAME
<code>\beginblock [...*,...] ... \endblock</code> * + -
<code>\beginofshapebox ... \endofshapebox</code>
<code>\begstrut ... \endstrut</code>
<code>\big ...</code> * CHARACTER
<code>\bigbodyfont</code>
<code>\bigg ...</code> * CHARACTER
<code>\bigger</code>
<code>\biggl ...</code> * CHARACTER
<code>\biggm ...</code> * CHARACTER
<code>\biggr ...</code> * CHARACTER
<code>\bigl ...</code> * CHARACTER
<code>\bigm ...</code> * CHARACTER
<code>\bigr ...</code> * CHARACTER
<code>\bigskip</code>

<p><code>\binom {<sup>1</sup>.} {<sup>2</sup>.}</code></p> <p>1    CONTENT</p> <p>2    CONTENT</p>
<p><code>\bitmapimage [...,<sup>1</sup>...,...] {<sup>2</sup>.}</code></p> <p>1    color    =   rgb cmyk gray</p> <p>     width    =   DIMENSION</p> <p>     height   =   DIMENSION</p> <p>     x        =   NUMBER</p> <p>     y        =   NUMBER</p> <p>2    NUMBER</p>
<p><code>\blackrule [...,*...,...]</code></p> <p>*    inherits: \setupblackrules</p>
<p><code>\blackrules [...,*...,...]</code></p> <p>*    inherits: \setupblackrules</p>
<p><code>\blank [...,*...]</code></p> <p>*    inherits: \vspacing</p>
<p><code>\blap {<sup>*</sup>.}</code></p> <p>*    CONTENT</p>
<p><code>\bleed [...,<sup>1</sup>...,...] {<sup>2</sup>.}</code></p> <p>1    inherits: \setupbleeding</p> <p>2    CONTENT</p>
<code>\bleedheight</code>
<code>\bleedwidth</code>
<p><code>\blockquote {<sup>*</sup>.}</code></p> <p>*    CONTENT</p>
<code>\bodyfontenvironmentlist</code>
<code>\bodyfontsize</code>
<code>\bold</code>
<code>\boldface</code>
<code>\bolditalic</code>
<code>\boldslanted</code>
<p><code>\bookmark [...,<sup>1</sup>.] {<sup>2</sup>.}</code></p> <p>1    SECTION LIST</p> <p>2    TEXT</p>

<code>\booleanmodevalue {...}</code>  *    NAME
<code>\bottombox {...}</code>  *    CONTENT
<code>\bottomleftbox {...}</code>  *    CONTENT
<code>\bottomrightbox {...}</code>  *    CONTENT
<code>\boxcursor</code>
<code>\boxmarker {...} {...}</code>  1    NAME 2    NUMBER
<code>\boxofsize \... ..<sup>2</sup> .. {...<sup>3</sup>}</code>  1    CSNAME 2    DIMENSION 3    CONTENT
<code>\boxreference [...,<sup>1</sup>...] \...<sup>2</sup> {...<sup>3</sup>}</code>  1    REFERENCE 2    CSNAME 3    CONTENT
<code>\bpar ... \epar</code>
<code>\bpos {...}</code>  *    NAME
<code>\breve {...}</code>  *    CHARACTER
<code>\bTABLE [...,<sup>*</sup>...,...] ... \eTABLE</code>  *    inherits: \setupTABLE
<code>\bTABLEbody [...,<sup>*</sup>...,...] ... \eTABLEbody</code>  *    inherits: \setupTABLE
<code>\bTABLEfoot [...,<sup>*</sup>...,...] ... \eTABLEfoot</code>  *    inherits: \setupTABLE
<code>\bTABLEhead [...,<sup>*</sup>...,...] ... \eTABLEhead</code>  *    inherits: \setupTABLE



<p><code>\bTABLEnext [...,*=...,...] ... \eTABLEnext</code></p> <p>* inherits: \setupTABLE</p>
<p><code>\bTC [...,*=...,...] ... \eTC</code></p> <p>* inherits: \bTD</p>
<p><code>\bTD [...,*=...,...] ... \eTD</code></p> <p>* nx = NUMBER ny = NUMBER nc = NUMBER nr = NUMBER n = NUMBER m = NUMBER action = REFERENCE inherits: \setupTABLE</p>
<p><code>\bTDs [...*] ... \eTDs</code></p> <p>* NAME</p>
<p><code>\bTH [...,*=...,...] ... \eTH</code></p> <p>* inherits: \bTD</p>
<p><code>\bTN [...,*=...,...] ... \eTN</code></p> <p>* inherits: \bTD</p>
<p><code>\bTR [...,*=...,...] ... \eTR</code></p> <p>* inherits: \setupTABLE</p>
<p><code>\bTRs [...*] ... \eTRs</code></p> <p>* NAME</p>
<p><code>\bTX [...,*=...,...] ... \eTX</code></p> <p>* inherits: \bTD</p>
<p><code>\bTY [...,*=...,...] ... \eTY</code></p> <p>* inherits: \setupTABLE</p>
<p><code>\bthiddencitation [...*]</code></p> <p>* REFERENCE</p>
<p><code>\btxabbreviatedjournal {...*}</code></p> <p>* NAME</p>
<p><code>\btxaddjournal [...<sup>1</sup>.] [...<sup>2</sup>.]</code></p> <p>1 NAME</p> <p>2 NAME</p>

`\btخالwayscitation [...1...2] [...]`

```
1  reference      = REFERENCE
   alternative    = default category entry short page num textnum year index tag keywords author authoryears authornum
                        authoryear
   before        = COMMAND
   after         = COMMAND
   left         = COMMAND
   right        = COMMAND
   inherits: \setupbtx

2  REFERENCE
```

`\btخالwayscitation [...1...2] [...2...]`

```
1  reference      = REFERENCE
   alternative    = default category entry short page num textnum year index tag keywords author authoryears authornum
                        authoryear
   before        = COMMAND
   after         = COMMAND
   left         = COMMAND
   right        = COMMAND
   inherits: \setupbtx

2  KEY = VALUE
```

`\btخالwayscitation [...1] [...2]`

```
1  default category entry short page num textnum year index tag keywords author authoryears authornum authoryear
2  REFERENCE
```

`\btخالauthorfield {...}`

\* initials firstnames vons surnames juniors

`\btخالdetail {...}`

\* address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language  
month monthfiled nationality note number one two organization pages publisher school series title type volume year  
yearfiled NAME

`\btخالdirect {...}`

\* address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language  
month monthfiled nationality note number one two organization pages publisher school series title type volume year  
yearfiled NAME

`\btخالdoif {...1} {...2}`

```
1  address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language
   month monthfiled nationality note number one two organization pages publisher school series title type volume year
   yearfiled NAME

2  TRUE
```

`\btخالdoifcombiinlistelse {...1} {...2} {...3} {...4}`

```
1  NAME
2  NAME
3  TRUE
4  FALSE
```

`\btخالdoifelse {...1} {...2} {...3}`

```
1  address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language
   month monthfiled nationality note number one two organization pages publisher school series title type volume year
   yearfiled NAME

2  TRUE

3  FALSE
```

\btxdfelsecombiinlist {...} {...} {...} {...}

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

\btxdfelsesameasprevious {...} {...} {...}

- 1 address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language month monthfiled nationality note number one two organization pages publisher school series title type volume year yearfiled NAME
- 2 TRUE
- 3 FALSE

\btxdfelsesameaspreviouschecked {...} {...} {...} {...}

- 1 always doublesided
- 2 address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language month monthfiled nationality note number one two organization pages publisher school series title type volume year yearfiled NAME
- 3 TRUE
- 4 FALSE

\btxdfelseuservariable {...} {...} {...}

- 1 KEY
- 2 TRUE
- 3 FALSE

\btxdfifnot {...} {...}

- 1 address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language month monthfiled nationality note number one two organization pages publisher school series title type volume year yearfiled NAME
- 2 TRUE

\btxdfifsameaspreviouscheckedelse {...} {...} {...} {...}

- 1 always doublesided
- 2 address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language month monthfiled nationality note number one two organization pages publisher school series title type volume year yearfiled NAME
- 3 TRUE
- 4 FALSE

\btxdfifsameaspreviouselse {...} {...} {...}

- 1 address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language month monthfiled nationality note number one two organization pages publisher school series title type volume year yearfiled NAME
- 2 TRUE
- 3 FALSE

\btxdfifuservariableelse {...} {...} {...}

- 1 KEY
- 2 TRUE
- 3 FALSE

\btsexpandedjournal {...}  *   NAME
\btxfield {...}  *   address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language month monthfiled nationality note number one two organization pages publisher school series title type volume year yearfiled NAME
\btxfieldname {...}  *   address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language month monthfiled nationality note number one two organization pages publisher school series title type volume year yearfiled NAME
\btxfieldtype {...}  *   address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language month monthfiled nationality note number one two organization pages publisher school series title type volume year yearfiled NAME
\btxfirstofrange {...}  *   volume pages
\btxflush {...}  *   address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language month monthfiled nationality note number one two organization pages publisher school series title type volume year yearfiled NAME
\btxflushauthor [... <sup>1</sup> ] {... <sup>2</sup> }  1   num normal normalshort inverted invertedshort  2   author editor
\btxflushauthorinverted {...}  *   author editor
\btxflushauthorinvertedshort {...}  *   author editor
\btxflushauthorname {...}  *   author editor
\btxflushauthornormal {...}  *   author editor
\btxflushauthornormalshort {...}  *   author editor
\btxflushsuffix
\btxfoundname {...}  *   address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language month monthfiled nationality note number one two organization pages publisher school series title type volume year yearfiled NAME

`\btxfoundtype {...}`

\* address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language month monthfiled nationality note number one two organization pages publisher school series title type volume year yearfiled NAME

`\btxhybridcite [...1...] [...2]`

```
1 reference = REFERENCE
  alternative = default category entry short page num textnum year index tag keywords author authoryears authornum
               authoryear
  before      = COMMAND
  after       = COMMAND
  left        = COMMAND
  right       = COMMAND
  inherits: \setupbtx

2 REFERENCE
```

`\btxhybridcite [...1...] [...2...]`

```
1 reference = REFERENCE
  alternative = default category entry short page num textnum year index tag keywords author authoryears authornum
               authoryear
  before      = COMMAND
  after       = COMMAND
  left        = COMMAND
  right       = COMMAND
  inherits: \setupbtx

2 KEY = VALUE
```

`\btxhybridcite [...1] [...2]`

```
1 default category entry short page num textnum year index tag keywords author authoryears authornum authoryear
2 REFERENCE
```

`\btxhybridcite {...}`

\* REFERENCE

`\btxlabellanguage`

`\btxlabeltext {...}`

\* KEY

`\btxlistcitation [...1...] [...2]`

```
1 reference = REFERENCE
  alternative = default category entry short page num textnum year index tag keywords author authoryears authornum
               authoryear
  before      = COMMAND
  after       = COMMAND
  left        = COMMAND
  right       = COMMAND
  inherits: \setupbtx

2 REFERENCE
```

`\btxlistcitation [...1...] [...2...]`

```
1 reference = REFERENCE
  alternative = default category entry short page num textnum year index tag keywords author authoryears authornum
               authoryear
  before      = COMMAND
  after       = COMMAND
  left        = COMMAND
  right       = COMMAND
  inherits: \setupbtx

2 KEY = VALUE
```

`\btclistcitation [...]1 [...]2`

1 default category entry short page num textnum year index tag keywords author authoryears authornum authoryear  
2 REFERENCE

`\btloadjournalist [...]*`

\* FILE

`\btoneorrange {...}1 {...}2 {...}3`

1 volume pages  
2 TRUE  
3 FALSE

`\btxremapauthor [...]1 [...]2`

1 TEXT  
2 TEXT

`\btxsavejournalist [...]*`

\* FILE

`\btxsetup {...}`

\* NAME

`\btxsingularorplural {...}1 {...}2 {...}3`

1 editor producer director  
2 TRUE  
3 FALSE

`\btxsingularplural {...}1 {...}2 {...}3`

1 editor producer director  
2 TRUE  
3 FALSE

`\btxttextcitation [...]1 [...]2`

1 reference = REFERENCE  
alternative = default category entry short page num textnum year index tag keywords author authoryears authornum  
authoryear  
before = COMMAND  
after = COMMAND  
left = COMMAND  
right = COMMAND  
inherits: \setupbtx  
2 REFERENCE

`\btxttextcitation [...]1 [...]2`

1 reference = REFERENCE  
alternative = default category entry short page num textnum year index tag keywords author authoryears authornum  
authoryear  
before = COMMAND  
after = COMMAND  
left = COMMAND  
right = COMMAND  
inherits: \setupbtx  
2 KEY = VALUE

$\backslash\text{bttextcitation}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...] 1 default category entry short page num textnum year index tag keywords author authoryears authornum authoryear 2 REFERENCE
$\backslash\text{buildmathaccent}$ {...} {...} 1 CHARACTER 2 CHARACTER
$\backslash\text{buildtextaccent}$ {...} {...} 1 CHARACTER 2 CHARACTER
$\backslash\text{buildtextbottomcomma}$ {...} * CHARACTER
$\backslash\text{buildtextbottomdot}$ {...} * CHARACTER
$\backslash\text{buildtextcedilla}$ {...} * CHARACTER
$\backslash\text{buildtextgrave}$ {...} * CHARACTER
$\backslash\text{buildtextmacron}$ {...} * CHARACTER
$\backslash\text{buildtextognek}$ {...} * CHARACTER
$\backslash\text{button}$ [..., <sup>1</sup> ...,...] {...} [...] 1 inherits: \setupbutton 2 TEXT 3 REFERENCE
$\backslash\text{button}$ [..., <sup>1</sup> ...,...] {...} [...] 1 inherits: \setupbutton 2 TEXT 3 REFERENCE
$\backslash\text{but}$ [ <sup>1</sup> ...] <sup>2</sup> ... \\\ 1 REFERENCE 2 TEXT
$\backslash\text{but}$ [ <sup>1</sup> ...] [..., <sup>2</sup> ,...] 1 REFERENCE 2 REFERENCE

<code>\Caps {...}</code> *    TEXT
<code>\Character {...}</code> *    NUMBER
<code>\Characters {...}</code> *    NUMBER
<code>\CONTEXT</code>
<code>\ConTeXt</code>
<code>\Context</code>
<code>\ConvertConstantAfter \.<sup>1</sup>. {..<sup>2</sup>.} {..<sup>3</sup>.}</code> 1    CSNAME 2    TEXT 3    TEXT
<code>\ConvertToConstant \.<sup>1</sup>. {..<sup>2</sup>.} {..<sup>3</sup>.}</code> 1    CSNAME 2    TEXT 3    TEXT
<code>\calligraphic</code>
<code>\camel {...}</code> *    TEXT
<code>\catcodetablename</code>
<code>\cbox .<sup>1</sup>. {..<sup>2</sup>.}</code> 1    TEXT 2    CONTENT
<code>\centeraligned {...}</code> *    CONTENT
<code>\centerbox .<sup>1</sup>. {..<sup>2</sup>.}</code> 1    TEXT 2    CONTENT
<code>\centeredbox .<sup>1</sup>. {..<sup>2</sup>.}</code> 1    TEXT 2    CONTENT
<code>\centeredlastline</code>



$\backslash\texttt{centerednextbox}$ $\dots$ $\{^1.\dots\}$ 1    TEXT 2    CONTENT
$\backslash\texttt{centerline}$ $\{^*.\dots\}$ *    CONTENT
$\backslash\texttt{cfrac}$ $[^1.\dots]$ $\{^2.\dots\}$ $\{^3.\dots\}$ 1    l c r ll lc lr cl cc cr rl rc rr 2    CONTENT 3    CONTENT
$\backslash\texttt{chapter}$ $[^1.\dots,^1.\dots]$ $\{^2.\dots\}$ 1    REFERENCE 2    TEXT
$\backslash\texttt{character}$ $\{^*.\dots\}$ *    NUMBER
$\backslash\texttt{characterkerning}$ $[^1.\dots]$ $\{^2.\dots\}$ 1    NUMBER 2    TEXT
$\backslash\texttt{characters}$ $\{^*.\dots\}$ *    NUMBER
$\backslash\texttt{chardescription}$ $\{^*.\dots\}$ *    NUMBER
$\backslash\texttt{charwidthlanguage}$
$\backslash\texttt{check}$ $\{^*.\dots\}$ *    CHARACTER
$\backslash\texttt{checkcharacteralign}$ $\{^*.\dots\}$ *    CONTENT
$\backslash\texttt{checkedchar}$ $\{^1.\dots\}$ $\{^2.\dots\}$ 1    NUMBER 2    CHARACTER
$\backslash\texttt{checkedfiller}$ $\{^*.\dots\}$ *    sym symbol rule width space NAME COMMAND
$\backslash\texttt{checkedstrippedcsname}$ $\backslash^*.\dots$ *    CSNAME

\checkedstrippedcsname ... * TEXT
\checkinjector [...]
\checknextindentation [...]
* yes no auto
\checknextinjector [...]
* NAME
\checkpage [ <sup>1</sup> ...] [..., <sup>2</sup> ...,...]
1 NAME 2 inherits: \setuppagechecker
\checkparameters [...]
* TEXT
\checkpreviousinjector [...]
* NAME
\checksoundtrack {...}
* NAME
\checktwopassdata {...}
* NAME
\chem {...} {...} {...}
1 TEXT 2 TEXT 3 TEXT
\chemical [ <sup>1</sup> ...] [..., <sup>2</sup> ...] [..., <sup>3</sup> ...]
1 NAME 2 TEXT 3 TEXT
\chemicalbottext {...}
* TEXT
\chemicalmidtext {...}
* TEXT
\chemicalsymbol [...]
* NAME

`\chemicaltext {...}`

\* TEXT

`\chemicaltoptext {...}`

\* TEXT

`\chineseallnumerals {...}`

\* NUMBER

`\chinesecapnumerals {...}`

\* NUMBER

`\chinesenumerals {...}`

\* NUMBER

`\citation [...1...2...] [...]`

```
1 reference = REFERENCE
  alternative = default category entry short page num textnum year index tag keywords author authoryears authornum
    authoryear
  before = COMMAND
  after = COMMAND
  left = COMMAND
  right = COMMAND
  inherits: \setupbtx

2 REFERENCE
```

`\citation [...1...2...] [...2...]`

```
1 reference = REFERENCE
  alternative = default category entry short page num textnum year index tag keywords author authoryears authornum
    authoryear
  before = COMMAND
  after = COMMAND
  left = COMMAND
  right = COMMAND
  inherits: \setupbtx

2 KEY = VALUE
```

`\citation [...1...] [...2]`

```
1 default category entry short page num textnum year index tag keywords author authoryears authornum authoryear
2 REFERENCE
```

`\citation {...}`

\* REFERENCE

`\cite [...1...2...] [...]`

```
1 reference = REFERENCE
  alternative = default category entry short page num textnum year index tag keywords author authoryears authornum
    authoryear
  before = COMMAND
  after = COMMAND
  left = COMMAND
  right = COMMAND
  inherits: \setupbtx

2 REFERENCE
```

`\cite [...,\sup{1}...,...][...,\sup{2}...,...]`

```
1  reference      = REFERENCE
   alternative    = default category entry short page num textnum year index tag keywords author authoryears authornum
                        authoryear
   before        = COMMAND
   after         = COMMAND
   left          = COMMAND
   right         = COMMAND
   inherits: \setupbtx
2  KEY = VALUE
```

`\cite [...]\sup{1} [...]\sup{2}`

```
1  default category entry short page num textnum year index tag keywords author authoryears authornum authoryear
2  REFERENCE
```

`\cite {...}`

\* REFERENCE

`\clap {...}`

\* CONTENT

`\classfont {...}\sup{1} {...}\sup{2}`

1 NAME

2 FONT

`\cldcommand {...}`

\* COMMAND

`\cldcontext {...}`

\* COMMAND

`\cldloadfile {...}`

\* FILE

`\cldprocessfile {...}`

\* FILE

`\cleftarrow {...}\sup{1} {...}\sup{2}`

1 TEXT

2 TEXT

`\clip [...,\sup{1}...,...]\sup{2} {...}`

1 inherits: \setupclipping

2 CONTENT

`\clonefield [...]\sup{1} [...]\sup{2} [...]\sup{3} [...,\sup{4},...]`

1 NAME

2 NAME

3 NAME

4 NAME

<code>\collect {...}</code> *    CONTENT
<code>\collectedtext [...,\overset{1}{...},...]</code> <code>[...,\overset{2}{...},...]</code> <code>{...}</code> <code>{...}</code> 1    inherits: \setupcollector 2    style   =   STYLE COMMAND color   =   COLOR inherits: \setupframed 3    TEXT 4    CONTENT
<code>\collectexpanded {...}</code> *    CONTENT
<code>\color [...<sup>1</sup>] {...<sup>2</sup>}</code> 1    COLOR 2    CONTENT
<code>\colorbar [...,*,...]</code> *    COLOR
<code>\colorcomponents {...}</code> *    COLOR
<code>\colored [...<sup>1</sup>] {...<sup>2</sup>}</code> 1    COLOR 2    CONTENT
<code>\colored [...,\overset{1}{...},...]</code> <code>{...<sup>2</sup>}</code> 1    inherits: \definecolor 2    CONTENT
<code>\coloronly [...<sup>1</sup>] {...<sup>2</sup>}</code> 1    COLOR 2    CONTENT
<code>\colorvalue {...}</code> *    COLOR
<code>\column [...,*,...]</code> *    inherits: \columnbreak
<code>\columnbreak [...,*,...]</code> *    yes no preference local force first last NUMBER NAME

`\combinepages [...]1 [...,...2...,...]`

1 FILE

2 alternative = a b c horizontal vertical  
n = NUMBER  
nx = NUMBER  
ny = NUMBER  
start = NUMBER  
stop = NUMBER  
distance = DIMENSION  
top = COMMAND  
bottom = COMMAND  
left = COMMAND  
right = COMMAND  
before = COMMAND  
after = COMMAND  
inbetween = COMMAND  
frame = on off  
background = foreground color NAME  
backgroundcolor = COLOR

`\commalistelement`

`\commalistsentence [...]1,... [...]2,...`

1 TEXT  
2 TEXT

`\commalistsize`

`\comment [...]1 [...,...2...,...]{...3}`

1 TEXT  
2 inherits: \setupcomment  
3 TEXT

`\comment [...]1 [...,...2...,...]{...3}`

1 TEXT  
2 inherits: \setupcomment  
3 TEXT

`\comparecolorgroup [...]`

\* NAME

`\comparedimension {...}1 {...}2}`

1 DIMENSION  
2 DIMENSION

`\comparedimensioneps {...}1 {...}2}`

1 DIMENSION  
2 DIMENSION

`\comparepalet [...]`

\* NAME

<code>\completebtxrendering</code> [ <sup>1</sup> ...] [ <sup>2</sup> ...,...] 1 NAME 2 inherits: \setupbtxrendering
<code>\completecombinedlist</code> [...,.. <sup>*</sup> ...,...] * inherits: \setuplist
<code>\completecontent</code> [...,.. <sup>*</sup> ...,...] * inherits: \setuplist
<code>\completeindex</code> [...,.. <sup>*</sup> ...,...] * inherits: \setupregister
<code>\completelist</code> [ <sup>1</sup> ...] [ <sup>2</sup> ...,...] 1 LIST 2 inherits: \setuplist
<code>\completelistofabbreviations</code> [...,.. <sup>*</sup> ...,...] * inherits: \setupsynonyms
<code>\completelistofchemicals</code> [...,.. <sup>*</sup> ...,...] * inherits: \setuplist
<code>\completelistoffigures</code> [...,.. <sup>*</sup> ...,...] * inherits: \setuplist
<code>\completelistoffloats</code> [...,.. <sup>*</sup> ...,...] * inherits: \setuplist
<code>\completelistofgraphics</code> [...,.. <sup>*</sup> ...,...] * inherits: \setuplist
<code>\completelistofintermezzi</code> [...,.. <sup>*</sup> ...,...] * inherits: \setuplist
<code>\completelistoflogos</code> [...,.. <sup>*</sup> ...,...] * inherits: \setupsorting
<code>\completelistofpublications</code> [ <sup>1</sup> ...] [ <sup>2</sup> ...,...] 1 NAME 2 inherits: \setupbtxrendering
<code>\completelistofsorts</code> [ <sup>1</sup> ...] [ <sup>2</sup> ...,...] 1 SINGULAR 2 inherits: \setupsorting
<code>\completelistofsorts</code> [...,.. <sup>*</sup> ...,...] * inherits: \setupsorting

\completelistofsynonyms [ <sup>1</sup> ...] [ <sup>2</sup> ...,...] 1 SINGULAR 2 inherits: \setupsynonyms
\completelistofsynonyms [...,.. <sup>*</sup> ...,...] * inherits: \setupsynonyms
\completelistoftables [...,.. <sup>*</sup> ...,...] * inherits: \setuplist
\completepagenumber
\completeregister [ <sup>1</sup> ...] [ <sup>2</sup> ...,...] 1 NAME 2 inherits: \setupregister
\completeregister [...,.. <sup>*</sup> ...,...] * inherits: \setupregister
\complexorsimpleempty \*... * CSNAME
\complexorsimpleempty {...} * TEXT CSNAME
\complexorsimple \*... * CSNAME
\complexorsimple {...} * TEXT CSNAME
\component [...] * FILE
\component ... * FILE
\composedcollector {...} * NAME
\composedlayer {...} * NAME
\compresult
\com ... \\ * TEXT



<code>\constantdimen \...</code> * CSNAME
<code>\constantdimenargument \...</code> * CSNAME
<code>\constantemptyargument \...</code> * CSNAME
<code>\constantnumber \...</code> * CSNAME
<code>\constantnumberargument \...</code> * CSNAME
<code>\contentreference [...<sup>1</sup>,...] [...<sup>2</sup>...,...]{...<sup>3</sup>}</code> 1 REFERENCE 2 inherits: \setupframed 3 CONTENT
<code>\continuednumber {...}</code> * NUMBER
<code>\continueifinputfile {...}</code> * FILE
<code>\convertargument ...<sup>1</sup> \to ...<sup>2</sup></code> 1 TEXT 2 CSNAME
<code>\convertcommand \...<sup>1</sup> \to ...<sup>2</sup></code> 1 CSNAME 2 CSNAME
<code>\convertedcounter [...<sup>1</sup>.] [...<sup>2</sup>...,...]</code> 1 NAME 2 inherits: \setupcounter
<code>\converteddimen {...<sup>1</sup>.} {...<sup>2</sup>.}</code> 1 DIMENSION 2 ex em pt in cm mm sp bp pc dd cc nc
<code>\convertedsubcounter [...<sup>1</sup>.] [...<sup>2</sup>.] [...<sup>3</sup>...,...]</code> 1 NAME 2 NUMBER NUMBER:NUMBER NUMBER:* NUMBER:all 3 inherits: \setupcounter

<p><code>\convertmonth {...}</code></p> <p>*    NUMBER</p>
<p><code>\convertnumber {...} {...}</code></p> <p>1    empty default none month:mnem character Character characters Characters a A Numbers word words Word Words n N romannumerals Romannumerals i I r R KR RK greek Greek g G abjadnumerals abjadnodotnumerals abjadnaivenumerals thainumerals devanagarinumerals gurmukhinumerals gujaratinnumerals tibetannumerals greeknumerals Greeknumerals arabicnumerals persiannumerals arabicexnumerals arabicdecimals persiandecimals koreannumerals koreanparentnumerals koreancirlenumerals kr kr-p kr-c chinesenumerals chinesecapnumerals chineseallnumerals cn cn-c cn-a sloveniannumerals slovenianNumerals spanishnumerals spanishNumerals mathgreek set_0 set_1 set_2 set_3 continued NAME</p> <p>2    NUMBER</p>
<p><code>\convertvalue ... \to ...</code></p> <p>1    NAME</p> <p>2    CSNAME</p>
<p><code>\convertvboxtohbox</code></p>
<p><code>\copybtxlabeltext [...] [...<sup>2</sup>...]</code></p> <p>1    LANGUAGE</p> <p>2    KEY    =    KEY</p>
<p><code>\copyfield [...] [...]</code></p> <p>1    NAME</p> <p>2    NAME</p>
<p><code>\copyheadtext [...] [...<sup>2</sup>...]</code></p> <p>1    LANGUAGE</p> <p>2    KEY    =    KEY</p>
<p><code>\copylabeltext [...] [...<sup>2</sup>...]</code></p> <p>1    LANGUAGE</p> <p>2    KEY    =    KEY</p>
<p><code>\copylabeltext [...] [...<sup>2</sup>...]</code></p> <p>1    LANGUAGE</p> <p>2    KEY    =    KEY</p>
<p><code>\copymathlabeltext [...] [...<sup>2</sup>...]</code></p> <p>1    LANGUAGE</p> <p>2    KEY    =    KEY</p>
<p><code>\copyoperatorortext [...] [...<sup>2</sup>...]</code></p> <p>1    LANGUAGE</p> <p>2    KEY    =    KEY</p>

`\coppages` [<sup>1</sup>...] [<sup>2</sup>...<sub>2</sub>...] [<sup>3</sup>...<sub>3</sub>...]

1 FILE  
2 marking = on off  
offset = DIMENSION  
n = NUMBER  
3 inherits: \setupexternalfigure

`\copyparameters` [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...]

1 TEXT  
2 TEXT  
3 KEY

`\copyposition` {<sup>1</sup>...} {<sup>2</sup>...}

1 NAME  
2 NAME

`\copprefixtext` [<sup>1</sup>...] [<sup>2</sup>...<sub>2</sub>...]

1 LANGUAGE  
2 KEY = KEY

`\copytaglabeltext` [<sup>1</sup>...] [<sup>2</sup>...<sub>2</sub>...]

1 LANGUAGE  
2 KEY = KEY

`\copyunittext` [<sup>1</sup>...] [<sup>2</sup>...<sub>2</sub>...]

1 LANGUAGE  
2 KEY = KEY

`\correctwhitespace` {<sup>\*</sup>...}

\* CONTENT

`\countersubs` [<sup>1</sup>...] [<sup>2</sup>...]

1 NAME  
2 NUMBER

`\counttoken` <sup>1</sup>... \in <sup>2</sup>... \to \<sup>3</sup>...

1 TEXT  
2 TEXT  
3 CSNAME

`\counttokens` <sup>1</sup>... \to \<sup>2</sup>...

1 TEXT  
2 CSNAME

`\cramped` {<sup>\*</sup>...}

\* CONTENT

$\backslash\text{crampedclap} \{...\}$ *    CONTENT
$\backslash\text{crampedllap} \{...\}$ *    CONTENT
$\backslash\text{crampedrlap} \{...\}$ *    CONTENT
$\backslash\text{crightarrow} \{...\} \{...\}$ 1    TEXT 2    TEXT
$\backslash\text{crightoverleftarrow} \{...\} \{...\}$ 1    TEXT 2    TEXT
$\backslash\text{ctop} \text{ } ^1. \{...\}$ 1    TEXT 2    CONTENT
$\backslash\text{ctxcommand} \{...\}$ *    COMMAND
$\backslash\text{ctxdirectcommand} \{...\}$ *    COMMAND
$\backslash\text{ctxdirectlua} \{...\}$ *    COMMAND
$\backslash\text{ctxfunction} \{...\}$ *    NAME
$\backslash\text{ctxfunctiondefinition}$
$\backslash\text{ctxfunction}$
$\backslash\text{ctxlatecommand} \{...\}$ *    COMMAND
$\backslash\text{ctxlatelua} \{...\}$ *    COMMAND
$\backslash\text{ctxloadluafile} \{...\}$ *    FILE
$\backslash\text{ctxlua} \{...\}$ *    COMMAND

\ctxluabuffer [...] *    BUFFER
\ctxluacode {...} *    COMMAND
\ctxreport {...} *    COMMAND
\ctxsprint {...} *    COMMAND
\currentassignmentlistkey
\currentassignmentlistvalue
\currentbtxuservariable {...} *    KEY
\currentcommalistitem
\currentcomponent
\currentdate [...*,...] *    yes moth day weekday y yy Y m mm M d dd D w W space \_ month:mnem m:mnem d:ord day:ord dd:ord D:ord TEXT
\currentenvironment
\currentfeaturetest
\currentheadnumber
\currentinterface
\currentlabel [... <sup>1</sup> ,... <sup>2</sup> ] {...} 1    REFERENCE 2    TEXT
\currentlanguage
\currentlistentrydestinationattribute
\currentlistentrylimitedtext {...} *    TEXT
\currentlistentrynumber
\currentlistentrypagenumber

\currentlistentryreferenceattribute {...} *    number text pagenumber all
\currentlistentrytitle
\currentlistentrytitlerendered
\currentlistsymbol
\currentmainlanguage
\currentmessagetext
\currentmoduleparameter {...} *    KEY
\currentoutputstream
\currentproduct
\currentproject
\currentregime
\currentregisterpageuserdata {...} *    KEY
\currentresponses
\currenttime [...*,...] *    h m TEXT
\currentvalue
\currentxtablecolumn
\currentxtablerow
\d {...} *    CHARACTER
\d datasetvariable {...} {...} {...} 1    NAME 2    NAME NUMBER 3    KEY realpage

<code>\date [...<sup>1</sup>...<sup>2</sup>...]</code>  1 <code>d = NUMBER</code> <code>m = NUMBER</code> <code>y = NUMBER</code>  2 <code>inherits: \currentdate</code>
<code>\dayoftheweek {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}</code>  1 <code>NUMBER</code>  2 <code>NUMBER</code>  3 <code>NUMBER</code>
<code>\dayspermonth {...<sup>1</sup>} {...<sup>2</sup>}</code>  1 <code>NUMBER</code>  2 <code>NUMBER</code>
<code>\dbinom {...<sup>1</sup>} {...<sup>2</sup>}</code>  1 <code>CONTENT</code>  2 <code>CONTENT</code>
<code>\ddot {...}</code>  * <code>CHARACTER</code>
<code>\decrementcounter [...<sup>1</sup>] [...<sup>2</sup>]</code>  1 <code>NAME</code>  2 <code>NUMBER</code>
<code>\decrementedcounter [...]</code>  * <code>NAME</code>
<code>\decrementpagenumber</code>
<code>\decrementsubpagenumber</code>
<code>\decrementvalue {...}</code>  * <code>NAME</code>
<code>\decrement \...</code>  * <code>CSNAME</code>
<code>\decrement cd:parentheses-1</code>  * <code>CSNAME NUMBER</code>
<code>\defaultinterface</code>
<code>\defaultobjectpage</code>
<code>\defaultobjectreference</code>

`\defcatcodecommand \1... \2... {\3...}`

- 1 CSNAME
- 2 CHARACTER NUMBER
- 3 COMMAND

`\defconvertedargument \1... {\2...}`

- 1 CSNAME
- 2 TEXT

`\defconvertedcommand \1... \2...`

- 1 CSNAME
- 2 CSNAME

`\defconvertedvalue \1... {\2...}`

- 1 CSNAME
- 2 NAME

`\define [1...] \2... {\3...}`

- 1 NUMBER
- 2 CSNAME
- 3 CONTENT

`\defineaccent \1... \2... \3...`

- 1 CHARACTER
- 2 CHARACTER
- 3 CHARACTER

`\defineactivecharacter \1... {\2...}`

- 1 CHARACTER
- 2 COMMAND

`\definealternativestyle [...,1...] [2...] [3...]`

- 1 NAME
- 2 COMMAND
- 3 COMMAND

`\defineanchor [1...] [2...] [...,3...,...] [...,4...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupplayer
- 4 inherits: \setupplayerinherits: \setupframed

`\defineattachment [1...] [2...] [...,3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupattachment



`\defineattribute [.1.] [...,2...]`

1 NAME

2 local global public private

`\definebackground [.1.] [...,2.] [...,3...]`

1 NAME

2 NAME

3 inherits: \setupbackground

`\definebar [.1.] [...,2.] [...,3...]`

1 NAME

2 NAME

3 inherits: \setupbar

`\defineblock [.1.] [...,2.] [...,3...]`

1 NAME

2 NAME

3 inherits: \setupblock

`\definebodyfontenvironment [.1.] [...,2.] [...,3...]`

1 NAME

2 default DIMENSION

3 big = DIMENSION NUMBER  
small = DIMENSION NUMBER  
a = DIMENSION NUMBER  
b = DIMENSION NUMBER  
c = DIMENSION NUMBER  
d = DIMENSION NUMBER  
text = DIMENSION NUMBER  
x = DIMENSION NUMBER  
xx = DIMENSION NUMBER  
script = DIMENSION NUMBER  
scriptscript = DIMENSION NUMBER  
interlinespace = DIMENSION  
em = slanted italic STYLE COMMAND  
\* = NUMBER

`\definebodyfontswitch [.1.] [...,2...]`

1 NAME

2 inherits: \setupbodyfont

`\definebodyfont [...,1...] [...,2...] [...,3...] [...,4...]`

1 NAME default

2 NAME DIMENSION

3 rm ss tt hw cg

4 tf = FILE  
bf = FILE  
it = FILE  
sl = FILE  
bi = FILE  
bs = FILE  
sc = FILE  
mr = FILE  
mrlr = FILE  
mrrl = FILE  
mb = FILE  
mblr = FILE  
mbrl = FILE

`\definebodyfont [...1,...] [...2,...] [...3,...] [...4]`

1 NAME default  
2 NAME DIMENSION  
3 rm ss tt hw cg  
4 NAME

`\definebreakpoint [...1] [...2] [...3,...3,...]`

1 NAME  
2 CHARACTER  
3 type = 1 2 3 4 5  
nleft = NUMBER  
nright = NUMBER  
left = COMMAND  
middle = COMMAND  
right = COMMAND  
language = LANGUAGE

`\definebreakpoints [...*]`

\* NAME

`\definebtx [...1] [...2] [...3,...3,...]`

1 NAME  
2 NAME  
3 inherits: \setupbtx

`\definebtxdataset [...1] [...2] [...3,...3,...]`

1 NAME  
2 NAME  
3 inherits: \setupbtxdataset

`\definebtxregister [...1] [...2] [...3,...3,...]`

1 NAME  
2 NAME  
3 inherits: \setupbtxregister

`\definebtxrendering [...1] [...2] [...3,...3,...]`

1 NAME  
2 NAME  
3 inherits: \setupbtxrendering

`\definebuffer [...1] [...2] [...3,...3,...]`

1 NAME  
2 BUFFER  
3 inherits: \setupbuffer

`\definebutton [...1] [...2] [...3,...3,...]`

1 NAME  
2 NAME  
3 inherits: \setupbutton

`\definecapitals [...]1 [...]2 [...,...3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupcapitals

`\definecharacter ...1 ...2.`

- 1 CHARACTER
- 2 NUMBER

`\definecharacterkerning [...]1 [...]2 [...,...3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupcharacterkerning

`\definecharacterspacing [...]*`

- \* NAME

`\definechemical [...]1 {...}2`

- 1 NAME
- 2 CONTENT

`\definechemicals [...]1 [...]2 [...,...3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupchemical

`\definechemicalsymbol [...]1 [...]2`

- 1 NAME
- 2 TEXT

`\definecollector [...]1 [...]2 [...,...3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupcollector

`\definecolorgroup [...]1 [...]2 [x:y:3z,...]`

- 1 NAME
- 2 gray rgb cmyk spot
- 3 TRIPLET

`\definecolor [1...] [2...3...]`

1 NAME  
2 r = NUMBER  
g = NUMBER  
b = NUMBER  
c = NUMBER  
m = NUMBER  
y = NUMBER  
k = NUMBER  
h = NUMBER  
s = NUMBER  
v = NUMBER  
x = NUMBER  
a = NUMBER none normal multiply screen overlay softlight hardlight colordodge colorburn darken lighten difference  
exclusion hue saturation color luminosity  
t = NUMBER

`\definecolor [1...] [2...]`

1 NAME  
2 COLOR

`\definecolumnbreak [1...] [2...,...]`

1 NAME  
2 yes no preference local force first last NUMBER

`\definecombination [1...] [2...] [3...,...]`

1 NAME  
2 NAME  
3 inherits: \setupcombination

`\definecombinedlist [1...] [2...,...] [3...,...]`

1 NAME  
2 LIST  
3 inherits: \setuplist

`\definecommand 1... 2...`

1 CHARACTER  
2 COMMAND

`\definecomment [1...] [2...] [3...,...]`

1 NAME  
2 NAME  
3 inherits: \setupcomment

`\definecomplexorsimpleempty \*...`

\* CSNAME

`\definecomplexorsimpleempty {*...}`

\* TEXT CSNAME

`\definecomplexorsimple \*...`

\* CSNAME

```
\definecomplexorsimple {...}
```

```
* TEXT CSNAME
```

```
\defineconversionset [...1] [...,2...] [...3]
```

```
1 NAME SECTIONBLOCK:NAME
```

```
2 NAME PROCESSOR->NAME
```

```
3 NAME PROCESSOR->NAME
```

```
\defineconversion [...1] [...2] [...3]
```

```
1 LANGUAGE
```

```
2 NAME
```

```
3 CSNAME
```

```
\defineconversion [...1] [...2] [...,3...]
```

```
1 LANGUAGE
```

```
2 NAME
```

```
3 TEXT
```

```
\definecounter [...1] [...2] [...,3...]
```

```
1 NAME
```

```
2 NAME
```

```
3 inherits: \setupcounter
```

```
\definedataset [...1] [...2] [...,3...]
```

```
1 NAME
```

```
2 NAME
```

```
3 inherits: \setupdataset
```

```
\definedelimitedtext [...1] [...2] [...,3...]
```

```
1 NAME
```

```
2 NAME
```

```
3 inherits: \setupdelimitedtext
```

```
\definedescription [...1] [...2] [...,3...]
```

```
1 NAME
```

```
2 NAME
```

```
3 inherits: \setupdescription
```

```
\definedfont [...]
```

```
* FONT
```

```
\defineeffect [...1] [...2] [...,3...]
```

```
1 NAME
```

```
2 NAME
```

```
3 inherits: \setupeffect
```

```
\defineenumerations [1...] [2...] [3...,...]
```

```
1 NAME
```

```
2 NAME
```

```
3 inherits: \setupenumeration
```

```
\defineexpandable [1...] \2... {3...}
```

```
1 NUMBER
```

```
2 CSNAME
```

```
3 CONTENT
```

```
\defineexternalfigure [1...] [2...] [3...,...]
```

```
1 NAME
```

```
2 NAME
```

```
3 inherits: \setupexternalfigure
```

```
\definefallbackfamily [1...] [2...] [3...] [4...,...]
```

```
1 NAME
```

```
2 rm ss tt mm hw cg roman serif regular sansserif sans support teletype type mono handwritten calligraphic math  
mathematics
```

```
3 FONT
```

```
4 rscale      = NUMBER  
designsize    = default auto  
goodies      = FILE  
range        = NUMBER NAME  
offset       = NUMBER NAME  
check        = yes no  
force        = yes no  
features     = NAME  
tf           = TEXT  
bf           = TEXT  
it           = TEXT  
sl           = TEXT  
bi           = TEXT  
bs           = TEXT  
sc           = TEXT
```

```
\definefallbackfamily [1...] [2...] [3...] [4...,...]
```

```
1 NAME
```

```
2 rm ss tt mm hw cg roman serif regular sansserif sans support teletype type mono handwritten calligraphic math  
mathematics
```

```
3 FONT
```

```
4 NAME
```

```
\definefield [1...] [2...] [3...] [4...,...] [5...]
```

```
1 NAME
```

```
2 radio sub text line push check signature
```

```
3 NAME
```

```
4 NAME
```

```
5 NAME
```

```
\definefieldbody [1...] [2...] [3...,...]
```

```
1 NAME
```

```
2 NAME
```

```
3 inherits: \setupfieldbody
```

`\definefieldbodyset [...]1 [...]2,...]`

1 NAME

2 NAME

`\definefieldcategory [...]1 [...]2 [...]3,...]`

1 NAME

2 NAME

3 inherits: \setupfieldcategory

`\definefieldstack [...]1 [...]2,... [...]3,...]`

1 NAME

2 NAME

3 inherits: \setupfieldcategory

`\definefiguresymbol [...]1 [...]2 [...]3,...]`

1 NAME

2 FILE NAME

3 inherits: \externalfigure

`\definefileconstant {...}1 {...}2`

1 NAME

2 NAME

`\definefilefallback [...]1 [...]2,...]`

1 NAME

2 FILE

`\definefilesynonym [...]1 [...]2`

1 NAME

2 FILE

`\definefiller [...]1 [...]2 [...]3,...]`

1 NAME

2 NAME

3 inherits: \setupfiller

`\definefirstline [...]1 [...]2 [...]3,...]`

1 NAME

2 NAME

3 inherits: \setupfirstline

`\definefittingpage [...]1 [...]2 [...]3,...]`

1 NAME

2 NAME

3 inherits: \setupfittingpage

```
\definefloat [1] [2] [3...]
```

```
1 SINGULAR
2 PLURAL
3 inherits: \setupfloat
```

```
\definefloat [1] [2] [3]
```

```
1 SINGULAR
2 PLURAL
3 SINGULAR
```

```
\definefontalternative [*]
```

```
* NAME
```

```
\definefontfallback [1] [2] [3...] [4...]
```

```
1 NAME
2 FONT NAME
3 NAME NUMBER
4 rscale = NUMBER
  force  = yes no
  check  = yes no
  offset = NUMBER NAME
```

```
\definefontfamilypreset [1] [2...]
```

```
1 NAME
2 inherits: \definefontfamily
```

```
\definefontfamilypreset [1] [2]
```

```
1 NAME
2 NAME
```

```
\definefontfamily [1] [2] [3] [4...]
```

```
1 NAME
2 rm ss tt mm hw cg roman serif regular sansserif sans support teletype type mono handwritten calligraphic math
  mathematics
3 FONT
4 rscale      = NUMBER
  designsize  = default auto
  goodies     = FILE
  features    = NAME
  tf          = TEXT
  bf          = TEXT
  it          = TEXT
  sl          = TEXT
  bi          = TEXT
  bs          = TEXT
  sc          = TEXT
```

```
\definefontfamily [1] [2] [3] [4...]
```

```
1 NAME
2 rm ss tt mm hw cg roman serif regular sansserif sans support teletype type mono handwritten calligraphic math
  mathematics
3 FONT
4 NAME
```



`\definefontfeature [...]1 [...]2 [...,...3...,...]`

1 NAME

2 NAME

3 language = NAME  
script = NAME auto  
mode = node base auto none  
liga = yes no  
kern = yes no  
extrakerns = yes no  
tlig = yes no  
trep = yes no  
missing = yes no  
dummies = yes no  
analyze = yes no  
unicoding = yes no  
expansion = NAME  
protrusion = NAME  
nostackmath = yes no  
realdimensions = yes no  
itlc = yes no  
textitalics = yes no  
mathitalics = yes no  
slant = NUMBER  
extend = NUMBER  
dimensions = NUMBER  
boundingbox = yes no  
compose = yes no  
char-ligatures = yes no  
compat-ligatures = yes no  
goodies = FILE  
extrafeatures = yes no  
featureset = NAME  
colorscheme = NAME  
postprocessor = NAME  
mathdimensions = NAME  
keepligatures = yes no auto  
devanagari = yes no  
features = yes no  
tcom = yes no  
anum = yes no  
mathsize = yes no  
decomposehangul = yes no  
mathalternatives = yes no  
mathgaps = yes no  
NAME = yes no

`\definefontfile [...]1 [...]2 [...,...3...,...]`

1 NAME

2 FILE

3 features = NAME  
fallbacks = NAME  
goodies = NAME  
designsize = auto default

`\definefontsize [...]`

\* NAME

`\definefontsolution [...]1 [...]2 [...,...3...,...]`

1 NAME

2 NAME

3 inherits: \setupfontsolution

`\definefontstyle [...]1,... [...]2`

1 NAME

2 NAME

`\definefontsynonym [1...] [2...] [...,3...,...]`

```
1  NAME
2  FONT
3  features    = NAME
    fallbacks  = NAME
    goodies    = NAME
    designsize = auto default
```

`\definefont [1...] [2...] [...,3...,...]`

```
1  NAME
2  FONT
3  inherits: \setupinterlinespace
```

`\definefont [1...] [2...] [3...]`

```
1  NAME
2  FONT
3  NAME
```

`\defineformula [1...] [2...] [...,3...,...]`

```
1  NAME
2  NAME
3  inherits: \setupformula
```

`\defineformulaalternative [1...] [2...] [3...]`

```
1  NAME
2  CSNAME
3  CSNAME
```

`\defineframed [1...] [2...] [...,3...,...]`

```
1  NAME
2  NAME
3  inherits: \setupframed
```

`\defineframedcontent [1...] [2...] [...,3...,...]`

```
1  NAME
2  NAME
3  inherits: \setupframedcontent
```

`\defineframedtext [1...] [2...] [...,3...,...]`

```
1  NAME
2  NAME
3  inherits: \setupframedtext
```

`\definefrozenfont [1...] [2...]`

```
1  NAME
2  FONT
```

`\defineglobalcolor [...]1 [...,...2...,...]`

1 NAME

2 inherits: \definecolor

`\defineglobalcolor [...]1 [...]2`

1 NAME

2 COLOR

`\definegraphictypesynonym [...]1 [...]2`

1 NAME

2 NAME

`\definegridsnapping [...]1 [...,...2...,...]`

1 NAME

2 local global noheight nodepth box max min none line halflines first last minheight maxheight mindepth maxdepth  
top bottom strut NUMBER minheight:NUMBER maxheight:NUMBER mindepth:NUMBER maxdepth:NUMBER box:NUMBER top:NUMBER  
bottom:NUMBER offset:NUMBER

`\definehbox [...]1 [...]2`

1 NAME

2 DIMENSION

`\definehead [...]1 [...]2 [...,...3...,...]`

1 NAME

2 SECTION

3 inherits: \setuphead

`\defineheadalternative [...]1 [...]2 [...,...3...,...]`

1 NAME

2 NAME

3 inherits: \setupheadalternative

`\definehelp [...]1 [...]2 [...,...3...,...]`

1 NAME

2 NAME

3 inherits: \setuphelp

`\definehigh [...]1 [...]2 [...,...3...,...]`

1 NAME

2 NAME

3 inherits: \setuphigh

`\definehighlight [...]1 [...]2 [...,...3...,...]`

1 NAME

2 NAME

3 inherits: \setuphighlight

```
\definehspace [...] [...] [...]
```

```
1 NAME
2 NAME
3 DIMENSION
```

```
\definehyphenationfeatures [...] [...,...2...,...]
```

```
1 NAME
2 characters      = TEXT
  hyphens         = yes all TEXT
  joiners         = yes all TEXT
  rightwords     = NUMBER
  hyphenmin       = NUMBER
  lefthyphenmin   = NUMBER
  righthyphenmin  = NUMBER
  lefthyphenchar  = NUMBER
  righthyphenchar = NUMBER
  alternative     = original tex hyphenate expanded traditional none
  rightedge       = tex
  rightchars      = word NUMBER
```

```
\defineindentedtext [...] [...] [...,...3...,...]
```

```
1 NAME
2 NAME
3 inherits: \setupindentedtext
```

```
\defineindenting [...] [...,2...,...]
```

```
1 NAME
2 [-+]small [-+]medium [-+]big none no not first next yes always never odd even normal reset toggle DIMENSION
```

```
\defineinitial [...] [...] [...,...3...,...]
```

```
1 NAME
2 NAME
3 inherits: \setupinitial
```

```
\defineinsertion [...] [...] [...,...3...,...]
```

```
1 NAME
2 NAME
3 inherits: \setupinsertion
```

```
\defineinteraction [...] [...] [...,...3...,...]
```

```
1 NAME
2 NAME
3 inherits: \setupinteraction
```

```
\defineinteractionbar [...] [...] [...,...3...,...]
```

```
1 NAME
2 NAME
3 inherits: \setupinteractionbar
```

```
\defineinteractionmenu [...]1 [...]2 [...,...3...,...]
```

```
1 NAME
```

```
2 NAME
```

```
3 inherits: \setupinteractionmenu
```

```
\defineinterfaceconstant {...}1 {...}2
```

```
1 NAME
```

```
2 NAME
```

```
\defineinterfaceelement {...}1 {...}2
```

```
1 NAME
```

```
2 NAME
```

```
\defineinterfacevariable {...}1 {...}2
```

```
1 NAME
```

```
2 NAME
```

```
\defineinterlinespace [...]1 [...]2 [...,...3...,...]
```

```
1 NAME
```

```
2 NAME
```

```
3 inherits: \setupinterlinespace
```

```
\defineintermediatecolor [...]1 [...,2...] [...,...3...,...]
```

```
1 NAME
```

```
2 COLOR NUMBER
```

```
3 a = NUMBER  
t = NUMBER
```

```
\defineitemgroup [...]1 [...]2 [...,...3...,...]
```

```
1 NAME
```

```
2 NAME
```

```
3 inherits: \setupitemgroup
```

```
\defineitems [...]1 [...]2 [...,...3...,...]
```

```
1 NAME
```

```
2 NAME
```

```
3 inherits: \setupitems
```

```
\definelabel [...]1 [...]2 [...,...3...,...]
```

```
1 NAME
```

```
2 NAME
```

```
3 inherits: \setuplabel
```

```
\definelabelclass [...]1 [...]2
```

```
1 NAME
```

```
2 NUMBER
```

**\definelaye**r [<sup>1</sup>...] [<sup>2</sup>...] [...,<sup>3</sup>...,...]

- 1 NAME
- 2 NAME
- 3 inherits: \setuplayer

**\definelaye**rpreset [<sup>1</sup>...] [...,<sup>2</sup>...,...]

- 1 NAME
- 2 inherits: \setuplayer

**\definelaye**rpreset [<sup>1</sup>...] [<sup>2</sup>...]

- 1 NAME
- 2 NAME

**\definelayo**ut [<sup>1</sup>...] [<sup>2</sup>...] [...,<sup>3</sup>...,...]

- 1 NAME
- 2 NAME
- 3 inherits: \setuplayout

**\defineline**note [<sup>1</sup>...] [<sup>2</sup>...] [...,<sup>3</sup>...,...]

- 1 NAME
- 2 NAME
- 3 inherits: \setuplinenote

**\defineline**numbering [<sup>1</sup>...] [<sup>2</sup>...] [...,<sup>3</sup>...,...]

- 1 NAME
- 2 NAME
- 3 inherits: \setuplinenumbering

**\defineline**s [<sup>1</sup>...] [<sup>2</sup>...] [...,<sup>3</sup>...,...]

- 1 NAME
- 2 NAME
- 3 inherits: \setuplines

**\definelist** [<sup>1</sup>...] [<sup>2</sup>...] [...,<sup>3</sup>...,...]

- 1 NAME
- 2 LIST
- 3 inherits: \setuplist

**\definelist**alternative [<sup>1</sup>...] [<sup>2</sup>...] [...,<sup>3</sup>...,...]

- 1 NAME
- 2 NAME
- 3 inherits: \setuplistalternative

**\definelist**extra [<sup>1</sup>...] [<sup>2</sup>...] [...,<sup>3</sup>...,...]

- 1 NAME
- 2 NAME
- 3 inherits: \setuplistextra

`\definelow [1...] [2] [...,3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setuplow

`\definelowhigh [1] [2] [...,3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setuplowhigh

`\definelowmidhigh [1] [2] [...,3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setuplowmidhigh

`\defineMPinstance [1] [2] [...,3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupMPinstance

`\definemakeup [1] [2] [...,3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupmakeup

`\definemarginblock [1] [2] [...,3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupmarginblock

`\definemargindata [1] [2] [...,3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupmargindata

`\definemarker [...]`

- \* NAME

`\definemarking [1] [2] [...,3...,...]`

- 1 NAME
- 2 MARK
- 3 inherits: \setupmarking

`\definemathaccent 1 2`

- 1 NAME
- 2 CHARACTER

```
\definemathalignment [...1] [...2] [...,3...,...]
```

```
1 NAME
```

```
2 NAME
```

```
3 inherits: \setupmathalignment
```

```
\definemathcases [...1] [...2] [...,3...,...]
```

```
1 NAME
```

```
2 NAME
```

```
3 inherits: \setupmathcases
```

```
\definemathcommand [...1] [...2] [...3] {...4}
```

```
1 NAME
```

```
2 ord op bin rel open close punct alpha inner nothing limop nolog box
```

```
3 one two
```

```
4 COMMAND CD:ONEARGUMENT CD:TWOARGUMENTS
```

```
\definemathdoubleextensible [...1] [...2] [...3] [...4]
```

```
1 both vfenced
```

```
2 NAME
```

```
3 NUMBER
```

```
4 NUMBER
```

```
\definemathematics [...1] [...2] [...,3...,...]
```

```
1 NAME
```

```
2 NAME
```

```
3 inherits: \setupmathematics
```

```
\definemathextensible [...1] [...2] [...3]
```

```
1 reverse mathematics text chemistry
```

```
2 NAME
```

```
3 NUMBER
```

```
\definemathfence [...1] [...2] [...,3...,...]
```

```
1 NAME
```

```
2 NAME
```

```
3 inherits: \setupmathfence
```

```
\definemathfraction [...1] [...2] [...,3...,...]
```

```
1 NAME
```

```
2 NAME
```

```
3 inherits: \setupmathfraction
```

```
\definemathframed [...1] [...2] [...,3...,...]
```

```
1 NAME
```

```
2 NAME
```

```
3 inherits: \setupmathframed
```



```
\definemathmatrix [...1] [...2] [...,3...,...]
```

```
1 NAME
```

```
2 NAME
```

```
3 inherits: \setupmathmatrix
```

```
\definemathornament [...1] [...2] [...,3...,...]
```

```
1 NAME
```

```
2 NAME
```

```
3 inherits: \setupmathornament
```

```
\definemathoverextensible [...1] [...2] [...3]
```

```
1 top vfenced
```

```
2 NAME
```

```
3 NUMBER
```

```
\definemathovertextextensible [...1] [...2] [...3]
```

```
1 bothtext
```

```
2 NAME
```

```
3 NUMBER
```

```
\definemathradical [...1] [...2] [...,3...,...]
```

```
1 NAME
```

```
2 NAME
```

```
3 inherits: \setupmathradical
```

```
\definemathstackers [...1] [...2] [...,3...,...]
```

```
1 NAME
```

```
2 NAME
```

```
3 inherits: \setupmathstackers
```

```
\definemathstyle [...1] [...,2...]
```

```
1 NAME
```

```
2 display text script scriptscript cramped uncramped normal packed small big
```

```
\definemathtriplet [...1] [...2] [...3]
```

```
1 NAME
```

```
2 NAME
```

```
3 TEXT
```

```
\definemathunderextensible [...1] [...2] [...3]
```

```
1 bottom vfenced
```

```
2 NAME
```

```
3 NUMBER
```

```
\definemathundertexttextensible [1...] [2...] [3]
```

- 1 bothtext
- 2 NAME
- 3 NUMBER

```
\definemathunstacked [1...] [2...] [3]
```

- 1 wide
- 2 NAME
- 3 NUMBER

```
\definemeasure [1...] [2...]
```

- 1 NAME
- 2 DIMENSION

```
\definemessageconstant {.*}
```

- \* NAME

```
\definemixedcolumns [1...] [2...] [...,3...,...]
```

- 1 NAME
- 2 NAME
- 3 inherits: \setupmixedcolumns

```
\definemode [...,1...] [2...]
```

- 1 NAME
- 2 yes no keep

```
\definemultitonecolor [1...] [...,2...,...] [...,3...,...] [...,4...,...]
```

- 1 NAME
- 2 COLOR = NUMBER
- 3 inherits: \definecolor
- 4 inherits: \definespotcolor

```
\definenamecolor [1...] [...,2...,...]
```

- 1 NAME
- 2 inherits: \definecolor

```
\definenamecolor [1...] [2...]
```

- 1 NAME
- 2 COLOR

```
\definenamespace [1...] [...,2...,...]
```

- 1 NAME
- 2 name = TEXT  
parent = TEXT  
style = yes no  
command = yes no list  
setup = yes no list  
set = yes no list  
frame = yes no

`\definenarrower [...]1 [...]2 [...,...3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupnarrower

`\definernote [...]1 [...]2 [...,...3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupnote

`\defineornament [...]1 [...,...2...,...]2 [...,...3...,...]3`

- 1 NAME
- 2 alternative = a b  
inherits: \setupcollector
- 3 style = STYLE COMMAND  
color = COLOR  
inherits: \setupframed

`\defineornament [...]1 [...,...2...,...]2 [...,...3...,...]3`

- 1 NAME
- 2 alternative = a b  
inherits: \setuplayer
- 3 inherits: \setuplayeredtext

`\defineoutputroutine [...]1 [...]2 [...,...3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupoutputroutine

`\defineoutputroutinecommand [...,*,...]`

- \* KEY

`\defineoverlay [...,1...] [...]2 [...]3`

- 1 NAME
- 2 NAME
- 3 COMMAND

`\definepage [...]1 [...]2`

- 1 NAME
- 2 REFERENCE

`\definepagebreak [...]1 [...,2...]`

- 1 NAME
- 2 empty header footer dummy frame NUMBER +NUMBER default reset disable yes no makeup blank preference bigpreference  
left right even odd quadruple last lastpage start stop

`\definepagechecker [...]1 [...]2 [...,...3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setuppagechecker

```
\definepagegrid [1...] [2...] [...,3...,...]
```

- 1 NAME
- 2 NAME
- 3 inherits: \setuppagegrid

```
\definepagegridarea [1...] [2...] [...,3...,...]
```

- 1 NAME
- 2 NAME
- 3 inherits: \setuppagegridarea

```
\definepagegridspan [1...] [2...] [...,3...,...]
```

- 1 NAME
- 2 NAME
- 3 inherits: \setuppagegridspan

```
\definepageinjection [1...] [2...] [...,3...,...]
```

- 1 NAME
- 2 NAME
- 3 inherits: \setuppageinjection

```
\definepageinjectionalternative [1...] [2...] [...,3...,...]
```

- 1 NAME
- 2 NAME
- 3 inherits: \setuppageinjectionalternative

```
\definepageshift [1...] [2...] [...,3...,...]
```

- 1 NAME
- 2 horizontal vertical
- 3 DIMENSION

```
\definepagestate [1...] [2...] [...,3...,...]
```

- 1 NAME
- 2 NAME
- 3 inherits: \setuppagestate

```
\definepairedbox [1...] [2...] [...,3...,...]
```

- 1 NAME
- 2 NAME
- 3 inherits: \setuppairedbox

```
\definepalet [1...] [...,2...,...]
```

- 1 NAME
- 2 NAME = COLOR

```
\definepalet [1...] [2...]
```

- 1 NAME
- 2 NAME

`\definepapersize [1.] [2...2...]`

```
1  NAME
2  width    = DIMENSION
   height   = DIMENSION
   top      = COMMAND
   bottom   = COMMAND
   left     = COMMAND
   right    = COMMAND
   distance = DIMENSION
   page     = inherits: \setuppapersize
   paper    = inherits: \setuppapersize
```

`\definepapersize [1.] [2...2...] [3...3...]`

```
1  NAME
2  inherits: \setuppapersize
3  inherits: \setuppapersize
```

`\defineparagraph [1.] [2.] [3...3...]`

```
1  NAME
2  NAME
3  inherits: \setupparagraph
```

`\defineparagraphs [1.] [2.] [3...3...]`

```
1  NAME
2  NAME
3  inherits: \setupparagraphs
```

`\defineparallel [1.] [2...2...]`

```
1  NAME
2  NAME
```

`\defineparbuilder [*.]`

```
*  NAME
```

`\defineplacement [1.] [2.] [3...3...]`

```
1  NAME
2  NAME
3  inherits: \setupplacement
```

`\definepositioning [1.] [2.] [3...3...]`

```
1  NAME
2  NAME
3  inherits: \setuppositioning
```

`\defineprefixset [1.] [2...2...] [3.]`

```
1  NAME SECTIONBLOCK:NAME
2  SECTION
3  SECTION
```

`\defineprocesscolor [1...] [2] [...,3...,...]`

- 1 NAME
- 2 COLOR
- 3 inherits: \definecolor

`\defineprocessor [1...] [2] [...,3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupprocessor

`\defineprofile [1...] [2] [...,3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupprofile

`\defineprogram [1...] [2] [3]`

- 1 NAME
- 2 TEXT
- 3 TEXT

`\definepushbutton [1...] [...,2...,...]`

- 1 NAME
- 2 inherits: \setupfieldcontentframed

`\definepushsymbol [1...] [2]`

- 1 NAME
- 2 n r d

`\definereference [1...] [...,2...,...]`

- 1 NAME
- 2 REFERENCE

`\definereferenceformat [1...] [2] [...,3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupreferenceformat

`\defineregister [1...] [2] [...,3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupregister

`\definerenderingwindow [1...] [2] [...,3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setuprenderingwindow

`\defineresetset [1...] [2...,...] [3...]`

- 1 NAME SECTIONBLOCK:NAME
- 2 NUMBER
- 3 NUMBER

`\definescale [1...] [2...] [3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupscale

`\definescript [1...] [2...] [3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupscrip

`\definesection [...]`

- \* NAME

`\definesectionblock [1...] [2...] [3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupsectionblock

`\definesectionlevels [1...] [2...,...]`

- 1 NAME
- 2 SECTION

`\defineselector [1...] [2...,...]`

- 1 NAME
- 2 inherits: \setupselector

`\defineseparatorset [1...] [2...,...] [3...]`

- 1 NAME SECTIONBLOCK:NAME
- 2 COMMAND PROCESSOR->COMMAND
- 3 COMMAND PROCESSOR->COMMAND

`\defineshift [1...] [2...] [3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupshift

`\definesidebar [1...] [2...] [3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupsidebar

`\definesort [...1] [...2] [...3] {...4}`

1    yes no  
2    SINGULAR  
3    NAME  
4    CONTENT

`\definesorting [...1] [...2] [...3]`

1    SINGULAR  
2    PLURAL  
3    none CSNAME

`\definespotcolor [...1] [...2] [...,3...,...]`

1    NAME  
2    COLOR  
3    a = NUMBER none normal multiply screen overlay softlight hardlight colordodge colorburn darken lighten difference  
      exclusion hue saturation color luminosity  
      t = NUMBER  
      e = TEXT  
      p = NUMBER

`\definestartstop [...1] [...2] [...,3...,...]`

1    NAME  
2    NAME  
3    inherits: \setupstartstop

`\definestyle [...1] [...2] [...,3...,...]`

1    NAME  
2    NAME  
3    inherits: \setupstyle

`\definestyleinstance [...1] [...2] [...3] [...4]`

1    NAME  
2    rm ss tt mm hw cg  
3    tf bf it sl bi bs sc  
4    COMMAND

`\definesubfield [...1] [...2] [...,3...]`

1    NAME  
2    NAME  
3    NAME

`\definesubformula [...1] [...2] [...,3...,...]`

1    NAME  
2    NAME  
3    inherits: \setupsubformula



`\definesymbol [1...] [2...] [3...]`

- 1 NAME
- 2 NAME
- 3 COMMAND

`\definesynonym [1...] [2...] [3...] {4...} {5...}`

- 1 yes no
- 2 SINGULAR
- 3 NAME
- 4 TEXT
- 5 CONTENT

`\definesynonyms [1...] [2...] [3...] [4...]`

- 1 SINGULAR
- 2 PLURAL
- 3 CSNAME
- 4 CSNAME

`\definesystemattribute [1...] [2...,...]`

- 1 NAME
- 2 local global public private

`\definesystemconstant {.*}`

- \* NAME

`\definesystemvariable {.*}`

- \* NAME

`\defineTABLEsetup [1...] [...,2...,...]`

- 1 NAME
- 2 inherits: \setupTABLE

`\definetabletemplate [1...] [|2...|] [3...] [4...]`

- 1 NAME
- 2 TEMPLATE
- 3 NAME
- 4 NAME

`\definetabulate [1...] [2...] [|3...|]`

- 1 NAME
- 2 NAME
- 3 TEMPLATE

`\definetabulation [1...] [2...] [...,3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setuptabulation

`\definertext [...1] [...2] [...3] [...4] [...5] [...6] [...7]`

- 1 NAME
- 2 top header text footer bottom
- 3 text margin edge
- 4 date pagenumber MARK TEXT COMMAND
- 5 date pagenumber MARK TEXT COMMAND
- 6 date pagenumber MARK TEXT COMMAND
- 7 date pagenumber MARK TEXT COMMAND

`\definetextbackground [...1] [...2] [...,3...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setuptextbackground

`\definetextflow [...1] [...2] [...,3...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setuptextflow

`\definetooltip [...1] [...2] [...,3...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setuptooltip

`\definetransparency [...1] [...2]`

- 1 NAME
- 2 NUMBER

`\definetransparency [...1] [...,2...]`

- 1 NAME
- 2 a = NUMBER none normal multiply screen overlay softlight hardlight colordodge colorburn darken lighten difference  
exclusion hue saturation color luminosity  
t = NUMBER

`\definetransparency [...1] [...2]`

- 1 NAME
- 2 NAME

`\definetwopasslist {...*}`

- \* NAME

`\definetype [...1] [...2] [...,3...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setuptype

`\definetypeface [...]1 [...]2 [...]3 [...]4 [...]5 [...]6...,...]`

```
1  NAME
2  rm ss tt mm hw cg
3  serif sans mono math handwriting calligraphy
4  NAME
5  default dtp
6  rscale      = auto NUMBER
   features    = NAME
   fallbacks   = NAME
   goodies     = NAME
   designsizes = auto default
   direction   = both
```

`\definetypecriptprefix [...]1 [...]2`

```
1  NAME
2  TEXT
```

`\definetypecriptsynonym [...]1 [...]2`

```
1  NAME
2  TEXT
```

`\definetypeetting [...]1 [...]2 [...]3...,...]`

```
1  NAME
2  TEXT
3  inherits: \setuexternalfigure
```

`\definotyping [...]1 [...]2 [...]3...,...]`

```
1  NAME
2  NAME
3  inherits: \setuptyping
```

`\defineunit [...]1 [...]2 [...]3...,...]`

```
1  NAME
2  NAME
3  inherits: \setupunit
```

`\defineviewerlayer [...]1 [...]2 [...]3...,...]`

```
1  NAME
2  NAME
3  inherits: \setupviewerlayer
```

`\definevspace [...]1 [...]2 [...]3`

```
1  NAME
2  NAME
3  DIMENSION
```

`\definevspacing [...]1 [...]2`

```
1  NAME
2  inherits: \vspacing
```

`\definevspacingamount [...]1 [...]2 [...]3`

- 1 NAME
- 2 DIMENSION
- 3 DIMENSION

`\definetable [...]1 [...]2 [...,3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupxtable

`\delimited [...]1 {...}2`

- 1 NAME
- 2 CONTENT

`\delimitedtext [...]1 {...}2`

- 1 NAME
- 2 CONTENT

`\delimitedtext {...}*`

- \* CONTENT

`\depthofstring {...}*`

- \* TEXT

`\depthonlybox {...}*`

- \* CONTENT

`\depthspanningtext {...}1 {...}2 {...}3`

- 1 TEXT
- 2 DIMENSION
- 3 FONT

`\description [...,1...] {...}2 ...3 \par`

- 1 REFERENCE
- 2 TEXT
- 3 CONTENT

`\determineheadnumber [...]*`

- \* SECTION

`\determinelistcharacteristics [...,1...] [...,2...,...]`

- 1 LIST
- 2 inherits: \setuplist

`\determinenoflines {...}*`

- \* CONTENT

`\determineregistercharacteristics [...]1 [...,...2...,...]`

1 NAME

2 language = default DIN\_5007-1 DIN\_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scn LANGUAGE  
method = default before after first last ch mm zm pm mc zc pc uc  
numberorder = numbers  
compress = yes no all  
criterium = local text current previous all SECTION

`\devanagarinumerals {...}`

\* NUMBER

`\dfrac {...}1 {...}2`

1 CONTENT

2 CONTENT

`\digits {...}`

\* NUMBER

`\digits ...`

\* NUMBER

`\dimensiontount {...}\1...2`

1 DIMENSION

2 CSNAME

`\directcolor [...]`

\* COLOR

`\directcolored [...]`

\* COLOR

`\directcolored [...,...*...,...]`

\* inherits: \definecolor

`\directconvertedcounter {...}1 {...}2`

1 NAME

2 first previous next last number

`\directdummyparameter {...}`

\* KEY

`\directgetboxllx ...`

\* CSNAME NUMBER

`\directgetboxlly ...`

\* CSNAME NUMBER

<code>\directhighlight {...} {...}</code>  1 NAME 2 TEXT
<code>\directlocalframed [...] {...}</code>  1 NAME 2 CONTENT
<code>\directluacode {...}</code>  * COMMAND
<code>\directselect {...} {...} {...} {...} {...} {...}</code>  1 NAME 2 CONTENT 3 CONTENT 4 CONTENT 5 CONTENT 6 CONTENT
<code>\directsetbar {...}</code>  * NAME
<code>\directsetup {...}</code>  * NAME
<code>\directsymbol {...} {...}</code>  1 NAME 2 NAME
<code>\directvspacing {...,*...}</code>  * inherits: \vspacing
<code>\dis {...}</code>  * CONTENT
<code>\disabledirectives [...,*...]</code>  * NAME
<code>\disableexperiments [...,*...]</code>  * NAME
<code>\disablemode [...,*...]</code>  * NAME
<code>\disableoutputstream</code>
<code>\disableparpositions</code>

<code>\disableregime</code>
<code>\disabletrackers [...]*...]</code> *    NAME
<code>\displaymath {...}</code> *    CONTENT
<code>\displaymathematics {...}</code> *    CONTENT
<code>\displaymessage {...}</code> *    TEXT
<code>\distributedhsize {...}^1 {...}^2 {...}^3</code> 1    DIMENSION 2    DIMENSION 3    NUMBER
<code>\dividedsize {...}^1 {...}^2 {...}^3</code> 1    DIMENSION 2    DIMENSION 3    NUMBER
<code>\doadaptleftskip {...}</code> *    yes no standard DIMENSION
<code>\doadaptrightskip {...}</code> *    yes no standard DIMENSION
<code>\doaddfeature {...}</code> *    NAME
<code>\doassign [...]^1 [...]^2..]</code> 1    TEXT 2    KEY = VALUE
<code>\doassignempty [...]^1 [...]^2..]</code> 1    TEXT 2    KEY = VALUE
<code>\doboundtext {...}^1 {...}^2 {...}^3</code> 1    TEXT 2    DIMENSION 3    COMMAND
<code>\docheckassignment {...}</code> *    TEXT

\docheckedpagestate {...} {...} {...} {...} {...} {...} {...}

- 1 REFERENCE
- 2 COMMAND
- 3 COMMAND
- 4 COMMAND
- 5 COMMAND
- 6 COMMAND
- 7 COMMAND

\docheckedpair {...,\*,...}

- \* TEXT

\documentvariable {...}

- \* KEY

\dodoubleargument \<sup>1</sup>... [<sup>2</sup>...] [<sup>3</sup>...]

- 1 CSNAME
- 2 TEXT
- 3 TEXT

\dodoubleargumentwithset \<sup>1</sup>... [...,<sup>2</sup>...] [<sup>3</sup>...]

- 1 CSNAME
- 2 TEXT
- 3 TEXT

\dodoubleempty \<sup>1</sup>... [<sup>2</sup>...] [<sup>3</sup>...]

- 1 CSNAME
- 2 TEXT
- 3 TEXT

\dodoubleemptywithset \<sup>1</sup>... [...,<sup>2</sup>...] [<sup>3</sup>...]

- 1 CSNAME
- 2 TEXT
- 3 TEXT

\dodoublegroupempty \<sup>1</sup>... {...<sup>2</sup>} {...<sup>3</sup>}

- 1 CSNAME
- 2 TEXT
- 3 TEXT

\doeassign [...<sup>1</sup>] [...<sup>2</sup>...]

- 1 TEXT
- 2 KEY = VALUE

\doexpandedrecurse {...<sup>1</sup>} {...<sup>2</sup>}

- 1 NUMBER
- 2 COMMAND



`\dogetattribute {...}`

\* NAME

`\dogetattributeid {...}`

\* NAME

`\dogetcommacommandelement 1... \from 2... \to 3...`

1 NUMBER

2 TEXT

3 CSNAME

`\dogobbledoubleempty [1...] [2...]`

1 TEXT

2 TEXT

`\dogobblesingleempty [...]`

\* TEXT

`\doif {1...} {2...} {3...}`

1 CONTENT

2 CONTENT

3 TRUE

`\doifallcommon {...}`

\* TRUE

`\doifallcommonelse {1...} {2...}`

1 TRUE

2 FALSE

`\doifalldefinedelse {...,1...} {2...} {3...}`

1 NAME

2 TRUE

3 FALSE

`\doifallmodes {...,1...} {2...} {3...}`

1 NAME

2 TRUE

3 FALSE

`\doifallmodeselse {...,1...} {2...} {3...}`

1 NAME

2 TRUE

3 FALSE

`\doifassignmentelse {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifblackelse {...} {...} {...}`

- 1 COLOR
- 2 TRUE
- 3 FALSE

`\doifbothsides {...} {...} {...}`

- 1 COMMAND
- 2 COMMAND
- 3 COMMAND

`\doifbothsidesoverruled {...} {...} {...}`

- 1 COMMAND
- 2 COMMAND
- 3 COMMAND

`\doifboxelse {...} {...} {...} {...}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifbufferelse {...} {...} {...}`

- 1 BUFFER
- 2 TRUE
- 3 FALSE

`\doifcolor {...} {...}`

- 1 COLOR
- 2 TRUE

`\doifcolorelse {...} {...} {...}`

- 1 COLOR
- 2 TRUE
- 3 FALSE

`\doifcommandhandler \... {...} {...}`

- 1 CSNAME
- 2 NAME
- 3 TRUE

```
\doifcommandhandlerelse \1... {2...} {3...} {4...}
```

- 1 CSNAME
- 2 NAME
- 3 TRUE
- 4 FALSE

```
\doifcommon {*...}
```

- \* TRUE

```
\doifcommonelse {1...} {2...}
```

- 1 TRUE
- 2 FALSE

```
\doifcontent {1...} {2...} {3...} \4... {5...}
```

- 1 COMMAND
- 2 COMMAND
- 3 COMMAND
- 4 CSNAME
- 5 CONTENT

```
\doifconversiondefinedelse {1...} {2...} {3...}
```

- 1 NAME
- 2 TRUE
- 3 FALSE

```
\doifconversionnumberelse {1...} {2...} {3...} {4...}
```

- 1 NAME
- 2 NUMBER
- 3 TRUE
- 4 FALSE

```
\doifcounter {1...} {2...}
```

- 1 NAME
- 2 TRUE

```
\doifcounterelse {1...} {2...} {3...}
```

- 1 NAME
- 2 TRUE
- 3 FALSE

```
\doifcurrentfonthasfeatureelse {1...} {2...} {3...}
```

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifdefined {...} {...}`

- 1 NAME
- 2 TRUE

`\doifdefinedcounter {...} {...}`

- 1 NAME
- 2 TRUE

`\doifdefinedcounterelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifdefinedelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifdimensionelse {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifdimenstringelse {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifdocumentargument {...} {...}`

- 1 NAME
- 2 TRUE

`\doifdocumentargumentelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifdocumentfilename {...} {...}`

- 1 NUMBER
- 2 TRUE

`\doifdocumentfilenameelse {...} {...} {...}`

- 1 NUMBER
- 2 TRUE
- 3 FALSE

`\doifdrawingblackelse {...} {...}`

1 TRUE  
2 FALSE

`\doifelse {...} {...} {...} {...}`

1 CONTENT  
2 CONTENT  
3 TRUE  
4 FALSE

`\doifelseallcommon {...} {...}`

1 TRUE  
2 FALSE

`\doifelsealldefined {...,1...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifelseallmodes {...,1...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifelseassignment {...} {...} {...}`

1 TEXT  
2 TRUE  
3 FALSE

`\doifelseblack {...} {...} {...}`

1 COLOR  
2 TRUE  
3 FALSE

`\doifelsebox {...} {...} {...} {...}`

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

`\doifelsebuffer {...} {...} {...}`

1 BUFFER  
2 TRUE  
3 FALSE

\doifelsecolor {...} {...} {...}

- 1 COLOR
- 2 TRUE
- 3 FALSE

\doifelsecommandhandler ^{1} {...} {...} {...}

- 1 CSNAME
- 2 NAME
- 3 TRUE
- 4 FALSE

\doifelsecommon {...} {...}

- 1 TRUE
- 2 FALSE

\doifelseconversiondefined {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelseconversionnumber {...} {...} {...} {...}

- 1 NAME
- 2 NUMBER
- 3 TRUE
- 4 FALSE

\doifelsecounter {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsecurrentfonthasfeature {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsecurrentsortingtongused {...} {...}

- 1 TRUE
- 2 FALSE

\doifelsecurrentsynonymshown {...} {...}

- 1 TRUE
- 2 FALSE

\doifelsecurrentsynonymused {...} {...}

- 1 TRUE
- 2 FALSE

`\doifelsedefined {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsedefinedcounter {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsedimension {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifelsedimenstring {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifelsedocumentargument {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsedocumentfilename {...} {...} {...}`

- 1 NUMBER
- 2 TRUE
- 3 FALSE

`\doifelsedrawingblack {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifelseempty {...} {...} {...}`

- 1 CONTENT
- 2 TRUE
- 3 FALSE

`\doifelseemptyvalue {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelseemptyvariable {...} {...} {...} {...}`

- 1 NAME
- 2 KEY
- 3 TRUE
- 4 FALSE

`\doifelseenv {...} {...} {...}`

- 1 KEY
- 2 TRUE
- 3 FALSE

`\doifelsefastoptionalcheck {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifelsefastoptionalcheckcs \^1 \^2`

- 1 CSNAME
- 2 CSNAME

`\doifelsefieldbody {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsefieldcategory {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsefigure {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifelsefile {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifelsefiledefined {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE



`\doifelsefileexists {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifelsefirstchar {...} {...} {...} {...}`

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

`\doifelseflagged {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsefontchar {...} {...} {...} {...}`

- 1 FONT
- 2 NUMBER
- 3 TRUE
- 4 FALSE

`\doifelsefontpresent {...} {...} {...}`

- 1 FONT
- 2 TRUE
- 3 FALSE

`\doifelsefontsynonym {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsehasspace {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifelsehelp {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifelseincsname {...} {...} {...} {...}`

- 1 TEXT
- 2 CSNAME
- 3 TRUE
- 4 FALSE

`\doifelseinelement {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelseinputfile {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifelseinsertion {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelseinset {...} {...} {...}`

- 1 CONTENT
- 2 TRUE
- 3 FALSE

`\doifelseinstring {...} {...} {...} {...}`

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

`\doifelseinsymbolset {...} {...} {...} {...}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifelseintoks {...} {...} {...} {...}`

- 1 COMMAND
- 2 COMMAND
- 3 TRUE
- 4 FALSE

`\doifelseintwopassdata {...} {...} {...} {...}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifelseitalic {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifelselanguage {...} {...} {...}`

- 1 LANGUAGE
- 2 TRUE
- 3 FALSE

`\doifelselayerdata {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelselayoutdefined {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelselayoutsomeline {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelselayouttextline {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelseleapyear {...} {...} {...}`

- 1 NUMBER
- 2 TRUE
- 3 FALSE

`\doifelselist {...} {...} {...}`

- 1 LIST
- 2 TRUE
- 3 FALSE

`\doifelselocation {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifelselocfile {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifelseMPgraphic {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsemainfloatbody {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifelsemarking {...} {...} {...}`

- 1 MARK
- 2 TRUE
- 3 FALSE

`\doifelsemeaning \1... \2... {...} {...}`

- 1 CSNAME
- 2 CSNAME
- 3 TRUE
- 4 FALSE

`\doifelsemessage {...} {...} {...} {...}`

- 1 NAME
- 2 NAME NUMBER
- 3 TRUE
- 4 FALSE

`\doifelsemode {...,1...} {...2} {...3}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsenextbgroup {...1} {...2}`

- 1 TRUE
- 2 FALSE

`\doifelsenextbgroupcs \1... \2...`

- 1 CSNAME
- 2 CSNAME

`\doifelsenextchar {...1} {...2} {...3}`

- 1 CHARACTER
- 2 TRUE
- 3 FALSE

`\doifelsenextoptional {...1} {...2}`

- 1 TRUE
- 2 FALSE

`\doifelsenextoptionalcs \1... \2...`

1 CSNAME

2 CSNAME

`\doifelsenextparenthesis {\1...} {\2...}`

1 TRUE

2 FALSE

`\doifelsenonzeropositive {\1...} {\2...} {\3...}`

1 NUMBER

2 TRUE

3 FALSE

`\doifelsenoteonsamepage {\1...} {\2...} {\3...}`

1 NAME

2 TRUE

3 FALSE

`\doifelsenothing {\1...} {\2...} {\3...}`

1 TEXT

2 TRUE

3 FALSE

`\doifelsenumber {\1...} {\2...} {\3...}`

1 TEXT

2 TRUE

3 FALSE

`\doifelseobjectfound {\1...} {\2...} {\3...} {\4...}`

1 NAME

2 NAME

3 TRUE

4 FALSE

`\doifelseobjectreferencefound {\1...} {\2...} {\3...} {\4...}`

1 NAME

2 NAME

3 TRUE

4 FALSE

`\doifelseoddpage {\1...} {\2...}`

1 COMMAND

2 COMMAND

`\doifelseoddpagefloat {\1...} {\2...}`

1 TRUE

2 FALSE

`\doifelseoldercontext {...} {...} {...}`

- 1 NUMBER
- 2 TRUE
- 3 FALSE

`\doifelseolderversion {...} {...} {...} {...}`

- 1 NUMBER
- 2 NUMBER
- 3 TRUE
- 4 FALSE

`\doifelseoverlapping {...} {...} {...} {...}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifelseoverlay {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelseparallel {...} {...,2...} {...} {...}`

- 1 NAME
- 2 NAME all
- 3 TRUE
- 4 FALSE

`\doifelseparentfile {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifelsepath {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifelsepathexists {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifelsepatterns {...} {...} {...}`

- 1 LANGUAGE
- 2 TRUE
- 3 FALSE

`\doifelseposition {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsepositionaction {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsepositiononpage {...} {...} {...} {...}`

- 1 NAME
- 2 NUMBER
- 3 TRUE
- 4 FALSE

`\doifelsepositionsonsamepage {...,1...} {...2} {...3}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsepositionsontthispage {...,1...} {...2} {...3}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsepositionsused {...1} {...2}`

- 1 TRUE
- 2 FALSE

`\doifelserreferencefound {...} {...} {...}`

- 1 REFERENCE
- 2 TRUE
- 3 FALSE

`\doifelserightpagefloat {...1} {...2}`

- 1 TRUE
- 2 FALSE

`\doifelserighttoleftinbox ...1 {...2} {...3}`

- 1 CSNAME NUMBER
- 2 TRUE
- 3 FALSE

`\doifelsesamelinereference {...} {...} {...}`

- 1 REFERENCE
- 2 TRUE
- 3 FALSE

`\doifelsesamestring {...} {...} {...} {...}`

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

`\doifelsesetups {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsesomebackground {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsesomespace {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifelsesomething {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifelsesometoks \... {...} {...}`

- 1 CSNAME
- 2 TRUE
- 3 FALSE

`\doifelsestringinstring {...} {...} {...} {...}`

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

`\doifelsestructurelisthasnumber {...} {...}`

- 1 TRUE
- 2 FALSE



`\doifelsestructurelisthaspage {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifelsesymboldefined {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsesymbolset {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsetext {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifelsetextflow {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsetextflowcollector {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsetypingfile {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifelseundefined {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelseurldefined {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsevalue {...} {...} {...} {...}`

- 1 NAME
- 2 TEXT
- 3 TRUE
- 4 FALSE

`\doifelsevaluenothing {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsevariable {...} {...} {...} {...}`

- 1 NAME
- 2 KEY
- 3 TRUE
- 4 FALSE

`\doifempty {...} {...}`

- 1 CONTENT
- 2 TRUE

`\doifemptyelse {...} {...} {...}`

- 1 CONTENT
- 2 TRUE
- 3 FALSE

`\doifemptytoks \^1... {...}`

- 1 CSNAME
- 2 TRUE

`\doifemptyvalue {...} {...}`

- 1 NAME
- 2 TRUE

`\doifemptyvalueelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifemptyvariable {...} {...} {...}`

- 1 NAME
- 2 KEY
- 3 TRUE

`\doifemptyvariableelse {...} {...} {...} {...}`

1 NAME  
2 KEY  
3 TRUE  
4 FALSE

`\doifenv {...} {...}`

1 KEY  
2 TRUE

`\doifenvelse {...} {...} {...}`

1 KEY  
2 TRUE  
3 FALSE

`\doiffastoptionalcheckcelse \1 \2`

1 CSNAME  
2 CSNAME

`\doiffastoptionalcheckelse {...} {...}`

1 TRUE  
2 FALSE

`\doiffielddbbodyelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doiffielddcategoryelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doiffigureelse {...} {...} {...}`

1 FILE  
2 TRUE  
3 FALSE

`\doiffile {...} {...}`

1 FILE  
2 TRUE

`\doiffiledefinedelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doiffileelse {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doiffileexistselse {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doiffirstcharelse {...} {...} {...} {...}`

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

`\doifflaggedelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doiffontcharelse {...} {...} {...} {...}`

- 1 FONT
- 2 NUMBER
- 3 TRUE
- 4 FALSE

`\doiffontpresentelse {...} {...} {...}`

- 1 FONT
- 2 TRUE
- 3 FALSE

`\doiffontsynonymelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifhasspaceelse {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifhelpelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifincsnameelse {1..} {2..} {3..} {4..}`

- 1 TEXT
- 2 CSNAME
- 3 TRUE
- 4 FALSE

`\doifinelementelse {1..} {2..} {3..}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifinputfileelse {1..} {2..} {3..}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifinsertionelse {1..} {2..} {3..}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifinset {1..} {2..}`

- 1 CONTENT
- 2 TRUE

`\doifinsetelse {1..} {2..} {3..}`

- 1 CONTENT
- 2 TRUE
- 3 FALSE

`\doifinstring {1..} {2..} {3..}`

- 1 TEXT
- 2 TEXT
- 3 TRUE

`\doifinstringelse {1..} {2..} {3..} {4..}`

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

`\doifinsymbolset {1..} {2..} {3..} {4..}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifinsymbolsetelse {...} {...} {...} {...}`

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

`\doifintokselsetelse {...} {...} {...} {...}`

1 COMMAND  
2 COMMAND  
3 TRUE  
4 FALSE

`\doifintwopassdataelse {...} {...} {...} {...}`

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

`\doifitalicelsetelse {...} {...}`

1 TRUE  
2 FALSE

`\doiflanguageelsetelse {...} {...} {...}`

1 LANGUAGE  
2 TRUE  
3 FALSE

`\doiflayerdataelsetelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doiflayoutdefinedelsetelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doiflayoutsomelineelsetelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doiflayouttextlineelsetelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifleapyearelse {...} {...} {...}`

- 1 NUMBER
- 2 TRUE
- 3 FALSE

`\doiflistelse {...} {...} {...}`

- 1 LIST
- 2 TRUE
- 3 FALSE

`\doiflocationelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\doiflocfileelse {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifMPgraphicelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifmainfloatbodyelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifmarkingelse {...} {...} {...}`

- 1 MARK
- 2 TRUE
- 3 FALSE

`\doifmeaningelse \1... \2... {...} {...}`

- 1 CSNAME
- 2 CSNAME
- 3 TRUE
- 4 FALSE

`\doifmessageelse {...} {...} {...} {...}`

- 1 NAME
- 2 NAME NUMBER
- 3 TRUE
- 4 FALSE

`\doifmode {...1,...} {...2}`

1 NAME

2 TRUE

`\doifmodeelse {...1,...} {...2} {...3}`

1 NAME

2 TRUE

3 FALSE

`\doifnextbgroupcselse \1.. \2..`

1 CSNAME

2 CSNAME

`\doifnextbgroupelse {...1} {...2}`

1 TRUE

2 FALSE

`\doifnextcharelse {...1} {...2} {...3}`

1 CHARACTER

2 TRUE

3 FALSE

`\doifnextoptionalcselse \1.. \2..`

1 CSNAME

2 CSNAME

`\doifnextoptionalelse {...1} {...2}`

1 TRUE

2 FALSE

`\doifnextparenthesiselse {...1} {...2}`

1 TRUE

2 FALSE

`\doifnonzeropositiveelse {...1} {...2} {...3}`

1 NUMBER

2 TRUE

3 FALSE

`\doifnot {...1} {...2} {...3}`

1 CONTENT

2 CONTENT

3 TRUE

`\doifnotallcommon {...*}`

\* TRUE



`\doifnotallmodes {...1...} {...2} {...3}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifnotcommandhandler \...1 {...2} {...3}`

- 1 CSNAME
- 2 NAME
- 3 TRUE

`\doifnotcommon {...*}`

- \* TRUE

`\doifnotcounter {...1} {...2}`

- 1 NAME
- 2 TRUE

`\doifnotdocumentargument {...1} {...2}`

- 1 NAME
- 2 TRUE

`\doifnotdocumentfilename {...1} {...2}`

- 1 NUMBER
- 2 TRUE

`\doifnotempty {...1} {...2}`

- 1 CONTENT
- 2 TRUE

`\doifnotemptyvalue {...1} {...2}`

- 1 NAME
- 2 TRUE

`\doifnotemptyvariable {...1} {...2} {...3}`

- 1 NAME
- 2 KEY
- 3 TRUE

`\doifnotenv {...1} {...2}`

- 1 KEY
- 2 TRUE

`\doifnoteonsamepageelse {...1} {...2} {...3}`

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifnotescollected {...} {...}

- 1 NAME
- 2 TRUE

\doifnotfile {...} {...}

- 1 FILE
- 2 TRUE

\doifnotflagged {...} {...}

- 1 NAME
- 2 TRUE

\doifnothing {...} {...}

- 1 TEXT
- 2 TRUE

\doifnothingelse {...} {...} {...}

- 1 TEXT
- 2 TRUE
- 3 FALSE

\doifnotinset {...} {...}

- 1 CONTENT
- 2 TRUE

\doifnotinsidesplitfloat {...}

- \* TRUE

\doifnotinstring {...} {...} {...}

- 1 TEXT
- 2 TEXT
- 3 TRUE

\doifnotmode {...,<sup>1</sup>...} {...<sup>2</sup>}

- 1 NAME
- 2 TRUE

\doifnotnumber {...} {...}

- 1 TEXT
- 2 TRUE

\doifnotsamestring {...} {...<sup>2</sup>} {...<sup>3</sup>}

- 1 TEXT
- 2 TEXT
- 3 TRUE

`\doifnotsetups {...} {...}`

- 1 NAME
- 2 TRUE

`\doifnotvalue {...} {...} {...}`

- 1 NAME
- 2 TEXT
- 3 TRUE

`\doifnotvariable {...} {...} {...}`

- 1 NAME
- 2 KEY
- 3 TRUE

`\doifnumber {...} {...}`

- 1 TEXT
- 2 TRUE

`\doifnumberelse {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifobjectfoundelse {...} {...} {...} {...}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifobjectreferencefoundelse {...} {...} {...} {...}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifoddpagelse {...} {...}`

- 1 COMMAND
- 2 COMMAND

`\doifoddpagefloatelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifoldercontextelse {...} {...} {...}`

- 1 NUMBER
- 2 TRUE
- 3 FALSE

`\doifolderversionelse {...} {...} {...} {...}`

- 1 NUMBER
- 2 NUMBER
- 3 TRUE
- 4 FALSE

`\doifoverlappingelse {...} {...} {...} {...}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifoverlayelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifparallelelse {...} {...,2...} {...} {...}`

- 1 NAME
- 2 NAME all
- 3 TRUE
- 4 FALSE

`\doifparentfileelse {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifpathelse {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifpathexistselse {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifpatternseelse {...} {...} {...}`

- 1 LANGUAGE
- 2 TRUE
- 3 FALSE

`\doifposition {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifpositionaction {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifpositionactionelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifpositionelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifpositiononpageelse {...} {...} {...} {...}`

- 1 NAME
- 2 NUMBER
- 3 TRUE
- 4 FALSE

`\doifpositionsonsamepageelse {...,1...} {...2} {...3}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifpositionsonthispageelse {...,1...} {...2} {...3}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifpositionsusedelse {...1} {...2}`

- 1 TRUE
- 2 FALSE

`\doifreferencefoundelse {...1} {...2} {...3}`

- 1 REFERENCE
- 2 TRUE
- 3 FALSE

`\doifrightpagefloatelse {...1} {...2}`

- 1 TRUE
- 2 FALSE

`\doifrighttoleftinboxedelse 1. {2..} {3..}`

- 1 CSNAME NUMBER
- 2 TRUE
- 3 FALSE

`\doifsamelinereferenceelse {1..} {2..} {3..}`

- 1 REFERENCE
- 2 TRUE
- 3 FALSE

`\doifsamestring {1..} {2..} {3..}`

- 1 TEXT
- 2 TEXT
- 3 TRUE

`\doifsamestringelse {1..} {2..} {3..} {4..}`

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

`\doifsetups {1..} {2..}`

- 1 NAME
- 2 TRUE

`\doifsetupselfelse {1..} {2..} {3..}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifsomebackground {1..} {2..} {3..}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifsomebackgroundelse {1..} {2..} {3..}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifsomespaceelse {1..} {2..} {3..}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifsomething {...} {...}`

- 1 TEXT
- 2 TRUE

`\doifsomethingelse {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifsometoks \... {...}`

- 1 CSNAME
- 2 TRUE

`\doifsometokselse \... {...} {...}`

- 1 CSNAME
- 2 TRUE
- 3 FALSE

`\doifstringinstringelse {...} {...} {...} {...}`

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

`\doifstructurelisthasnumberelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifstructurelisthaspageelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifsymboldefinedelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifsymbolsetelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doiftext {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doiftextelse {1.} {2.} {3.}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doiftextflowcollectorelse {1.} {2.} {3.}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doiftextflowelse {1.} {2.} {3.}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doiftypingfileelse {1.} {2.} {3.}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifundefined {1.} {2.}`

- 1 NAME
- 2 TRUE

`\doifundefinedcounter {1.} {2.}`

- 1 NAME
- 2 TRUE

`\doifundefinedelse {1.} {2.} {3.}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifurldefinedelse {1.} {2.} {3.}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifvalue {1.} {2.} {3.}`

- 1 NAME
- 2 TEXT
- 3 TRUE



`\doifvalueelse {...} {...} {...} {...}`

1 NAME  
2 TEXT  
3 TRUE  
4 FALSE

`\doifvaluenothing {...} {...}`

1 NAME  
2 TRUE

`\doifvaluenothingelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifvaluesomething {...} {...}`

1 NAME  
2 TRUE

`\doifvariable {...} {...} {...}`

1 NAME  
2 KEY  
3 TRUE

`\doifvariableelse {...} {...} {...} {...}`

1 NAME  
2 KEY  
3 TRUE  
4 FALSE

`\doindentation`

`\dollar`

`\doloop {...}`

\* COMMAND

`\doloopoverlist {...,1...} {...2}`

1 TEXT  
2 COMMAND

`\donothing`

`\dontconvertfont`

`\dontleavehmode`

`\dontpermitspacesbetweenegroups`

`\dopositionaction {...}`

\* NAME

`\doprocesslocalsetups {...,*...}`

\* NAME

`\doquadrupleargument \1... [2...] [3...] [4...] [5...]`

1 CSNAME

2 TEXT

3 TEXT

4 TEXT

5 TEXT

`\doquadrupleempty \1... [2...] [3...] [4...] [5...]`

1 CSNAME

2 TEXT

3 TEXT

4 TEXT

5 TEXT

`\doquadruplegroupempty \1... {2...} {3...} {4...} {5...}`

1 CSNAME

2 TEXT

3 TEXT

4 TEXT

5 TEXT

`\doquintupleargument \1... [2...] [3...] [4...] [5...] [6...]`

1 CSNAME

2 TEXT

3 TEXT

4 TEXT

5 TEXT

6 TEXT

`\doquintupleempty \1... [2...] [3...] [4...] [5...] [6...]`

1 CSNAME

2 TEXT

3 TEXT

4 TEXT

5 TEXT

6 TEXT

<code>\doquintuplegrouppempty \<sup>1</sup>... {<sup>2</sup>...} {<sup>3</sup>...} {<sup>4</sup>...} {<sup>5</sup>...} {<sup>6</sup>...}</code>  1 CSNAME 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT
<code>\dorechecknextindentation</code>
<code>\dorecurse {<sup>1</sup>...} {<sup>2</sup>...}</code>  1 NUMBER 2 COMMAND
<code>\dorepeatwithcommand [<sup>1</sup>...] \<sup>2</sup>...</code>  1 TEXT NUMBER*TEXT 2 CSNAME
<code>\doreplacefeature {<sup>*</sup>...}</code>  * NAME
<code>\doresetandafffeature {<sup>*</sup>...}</code>  * NAME
<code>\doresetattribute {<sup>*</sup>...}</code>  * NAME
<code>\dorotatebox {<sup>1</sup>...} \<sup>2</sup>... {<sup>3</sup>...}</code>  1 NUMBER 2 CSNAME 3 CONTENT
<code>\dosetattribute {<sup>1</sup>...} {<sup>2</sup>...}</code>  1 NAME 2 NUMBER
<code>\dosetleftskipadaption {<sup>*</sup>...}</code>  * yes no standard DIMENSION
<code>\dosetrighskipadaption {<sup>*</sup>...}</code>  * yes no standard DIMENSION
<code>\dosetupcheckedinterlinespace {...,*=...,...}</code>  * inherits: \setupinterlinespace
<code>\dosetupcheckedinterlinespace {...,*...}</code>  * on off reset auto small medium big NUMBER DIMENSION

```
\dosetupcheckedinterlinespace {...}
```

```
* NAME
```

```
\doseventupleargument \... [.1...] [.2...] [.3...] [.4...] [.5...] [.6...] [.7...] [.8...]
```

```
1 CSNAME  
2 TEXT  
3 TEXT  
4 TEXT  
5 TEXT  
6 TEXT  
7 TEXT  
8 TEXT
```

```
\doseventupleempty \... [.1...] [.2...] [.3...] [.4...] [.5...] [.6...] [.7...] [.8...]
```

```
1 CSNAME  
2 TEXT  
3 TEXT  
4 TEXT  
5 TEXT  
6 TEXT  
7 TEXT  
8 TEXT
```

```
\dosingleargument \... [.1...] [.2...]
```

```
1 CSNAME  
2 TEXT
```

```
\dosingleempty \... [.1...] [.2...]
```

```
1 CSNAME  
2 TEXT
```

```
\dosinglegroupempty \... {.1...} {.2...}
```

```
1 CSNAME  
2 TEXT
```

```
\dosixtupleargument \... [.1...] [.2...] [.3...] [.4...] [.5...] [.6...] [.7...]
```

```
1 CSNAME  
2 TEXT  
3 TEXT  
4 TEXT  
5 TEXT  
6 TEXT  
7 TEXT
```

`\dosixtupleempty \1... [2...] [3] [4] [5] [6] [7]`

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT
- 6 TEXT
- 7 TEXT

`\dostarttagged {1...} {2...} ... \dostoptagged`

- 1 NAME
- 2 NAME

`\dostepwiserecurse {1...} {2...} {3...} {4...}`

- 1 NUMBER
- 2 NUMBER
- 3 [-+]NUMBER
- 4 COMMAND

`\dosubtractfeature {*...}`

- \* NAME

`\dot {*...}`

- \* CHARACTER

`\dotfskip {*...}`

- \* DIMENSION

`\dotoks \*...`

- \* CSNAME

`\dotripleargument \1... [2...] [3] [4]`

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT

`\dotripleargumentwithset \1... [2...,...] [3] [4]`

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT

`\dotripleempty \1... [2...] [3] [4]`

1 CSNAME  
2 TEXT  
3 TEXT  
4 TEXT

`\dotripleemptywithset \1... [2...,...] [3] [4]`

1 CSNAME  
2 TEXT  
3 TEXT  
4 TEXT

`\dotriplegroupempty \1... {2...} {3...} {4...}`

1 CSNAME  
2 TEXT  
3 TEXT  
4 TEXT

`\doublebar {*...}`

\* TEXT

`\doublebond`

`\doublebrace {*...}`

\* TEXT

`\doublebracket {*...}`

\* TEXT

`\doubleparent {*...}`

\* TEXT

`\dowith {1...,...} {2...}`

1 COMMAND  
2 COMMAND

`\dowithnextbox {1...} \2... {3...}`

1 COMMAND  
2 CSNAME  
3 CONTENT

`\dowithnextboxcontent {1...} {2...} \3... {4...}`

1 COMMAND  
2 COMMAND  
3 CSNAME  
4 CONTENT

`\dowithnextboxcontentcs \1... \2... \3... {4...}`

- 1 CSNAME
- 2 CSNAME
- 3 CSNAME
- 4 CONTENT

`\dowithnextboxcs \1... \2... {3...}`

- 1 CSNAME
- 2 CSNAME
- 3 CONTENT

`\dowithpargument \*...`

- \* CSNAME

`\dowithrange {...,1...} \2...`

- 1 NUMBER NUMBER:NUMBER
- 2 CSNAME

`\dowithwargument \*...`

- \* CSNAME

`\dpofstring {*...}`

- \* TEXT

`\dummydigit`

`\dummyparameter {*...}`

- \* KEY

`\ETEX`

`\EveryLine {*...}`

- \* COMMAND

`\EveryPar {*...}`

- \* COMMAND

`\edefconvertedargument \1... {2...}`

- 1 CSNAME
- 2 TEXT

`\efcmxheight {*...}`

- \* NAME

`\efcmxwidth {*...}`

- \* NAME

<code>\efcminheight {...}</code>  *    NAME
<code>\efcminwidth {...}</code>  *    NAME
<code>\efcparameter {...} {...}</code>  1    NAME 2    KEY
<code>\effect [...] {...}</code>  1    NAME 2    CONTENT
<code>\elapsedseconds</code>
<code>\elapsedtime</code>
<code>\leftarrowfill {...} {...}</code>  1    TEXT 2    TEXT
<code>\leftharpoondownfill {...} {...}</code>  1    TEXT 2    TEXT
<code>\leftharpoonupfill {...} {...}</code>  1    TEXT 2    TEXT
<code>\leftrightarrowfill {...} {...}</code>  1    TEXT 2    TEXT
<code>\emphasisboldface</code>
<code>\emphasistypeface</code>
<code>\emptylines [...]</code>  *    NUMBER
<code>\emspace</code>
<code>\enabledirectives [...,*,...]</code>  *    NAME
<code>\enableexperiments [...,*,...]</code>  *    NAME



<p><code>\enablemode [...,*,...]</code></p> <p>* NAME</p>
<p><code>\enableoutputstream [...]</code></p> <p>* NAME</p>
<p><code>\enableparpositions</code></p>
<p><code>\enableregime [...]</code></p> <p>* cp1250 cp1251 cp1252 cp1253 cp1254 cp1255 cp1256 cp1257 cp1258 8859-1 8859-2 8859-3 8859-4 8859-9 8859-10 8859-13 8859-14 8859-15 8859-16 utf windows-1250 windows-1251 windows-1252 windows-1253 windows-1254 windows-1255 windows-1256 windows-1257 windows-1258 il1 il2 il3 il4 il5 il6 il7 il8 il9 il10 iso-8859-1 iso-8859-2 iso-8859-3 iso-8859-4 iso-8859-9 iso-8859-10 iso-8859-13 iso-8859-14 iso-8859-15 iso-8859-16 latin1 latin2 latin3 latin4 latin5 latin6 latin7 latin8 latin9 latin10 utf-8 utf8 windows</p>
<p><code>\enabletrackers [...,*,...]</code></p> <p>* NAME</p>
<p><code>\endnote [...,<sup>1</sup>,...] {...<sup>2</sup>}</code></p> <p>1 REFERENCE</p> <p>2 TEXT</p>
<p><code>\endnote [...,..<sup>*</sup>..<sup>*</sup>,...]</code></p> <p>* title = TEXT</p> <p>bookmark = TEXT</p> <p>list = TEXT</p> <p>reference = REFERENCE</p>
<p><code>\enskip</code></p>
<p><code>\enspace</code></p>
<p><code>\enumeration [...,<sup>1</sup>,...] {...<sup>2</sup>} ...<sup>3</sup> \par</code></p> <p>1 REFERENCE</p> <p>2 TEXT</p> <p>3 CONTENT</p>
<p><code>\env {...}</code></p> <p>* KEY</p>
<p><code>\environment [...]</code></p> <p>* FILE</p>
<p><code>\environment ...</code></p> <p>* FILE</p>
<p><code>\envvar {...} {...<sup>2</sup>}</code></p> <p>1 KEY</p> <p>2 COMMAND</p>

`\eoverbarfill {...} {...}`

1 TEXT

2 TEXT

`\eoverbracefill {...} {...}`

1 TEXT

2 TEXT

`\eoverbracketfill {...} {...}`

1 TEXT

2 TEXT

`\eoverparentfill {...} {...}`

1 TEXT

2 TEXT

`\epos {...}`

\* NAME

`\equaldigits {...}`

\* TEXT

`\erightarrowfill {...} {...}`

1 TEXT

2 TEXT

`\erightharpoondownfill {...} {...}`

1 TEXT

2 TEXT

`\erightharpoonupfill {...} {...}`

1 TEXT

2 TEXT

`\eTeX`

`\ethiopic`

`\etwoheadrightarrowfill {...} {...}`

1 TEXT

2 TEXT

`\eunderbarfill {...} {...}`

1 TEXT

2 TEXT

$\backslash\mathrm{eunderbracefill}\{\ldots\}\{\ldots\}$  1    TEXT 2    TEXT
$\backslash\mathrm{eunderbracketfill}\{\ldots\}\{\ldots\}$  1    TEXT 2    TEXT
$\backslash\mathrm{eunderparentfill}\{\ldots\}\{\ldots\}$  1    TEXT 2    TEXT
$\backslash\mathrm{executeifdefined}\{\ldots\}\{\ldots\}$  1    NAME 2    COMMAND
$\backslash\mathrm{exitloop}$
$\backslash\mathrm{exitloopnow}$
$\backslash\mathrm{expandcheckedcsname}\backslash\ldots\{\ldots\}\{\ldots\}$  1    CSNAME 2    KEY 3    TEXT
$\backslash\mathrm{expanded}\{\ldots\}$  *    CONTENT
$\backslash\mathrm{expandfontsynonym}\backslash\ldots\{\ldots\}$  1    CSNAME 2    NAME
$\backslash\mathrm{externalfigure}[\ldots][\ldots][\ldots,\ldots,\ldots]$  1    FILE 2    NAME 3    inherits: $\backslash\mathrm{setupexternalfigure}$
$\backslash\mathrm{externalfigurecollectionmaxheight}\{\ldots\}$  *    NAME
$\backslash\mathrm{externalfigurecollectionmaxwidth}\{\ldots\}$  *    NAME
$\backslash\mathrm{externalfigurecollectionminheight}\{\ldots\}$  *    NAME
$\backslash\mathrm{externalfigurecollectionminwidth}\{\ldots\}$  *    NAME

<code>\externalfigurecollectionparameter {...} {...}</code>  1 NAME 2 KEY
<code>\fakebox ...</code>  * CSNAME NUMBER
<code>\fastdecrement \...</code>  * CSNAME
<code>\fastincrement \...</code>  * CSNAME
<code>\fastlocalframed [...]<sup>1</sup> [...,...<sup>2</sup>...,...] {...}<sup>3</sup></code>  1 NAME 2 inherits: \setupframed 3 CONTENT
<code>\fastscale {...}<sup>1</sup> {...}<sup>2</sup></code>  1 NUMBER 2 CONTENT
<code>\fastsetup {...}</code>  * NAME
<code>\fastsetupwithargument {...}<sup>1</sup> {...}<sup>2</sup></code>  1 NAME 2 CONTENT
<code>\fastsetupwithargumentswapped {...}<sup>1</sup> {...}<sup>2</sup></code>  1 CONTENT 2 NAME
<code>\fastswitchtobodyfont {...}</code>  * x xx small big script scriptscript
<code>\fastxsxy {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup></code>  1 NUMBER 2 NUMBER 3 CONTENT
<code>\feature [...]<sup>1</sup> [...]<sup>2</sup></code>  1 + - = ! > < more less new reset default old local 2 NAME

<pre> \feature {...} {...}  1  + - = ! &gt; &lt; more less new reset default old local 2  NAME </pre>
<pre> \fence </pre>
<pre> \fenced [...] {...}  1  NAME 2  CONTENT </pre>
<pre> \ fence {...}  *  CONTENT </pre>
<pre> \fetchallmarkings [...] [...]  1  MARK 2  page NAME </pre>
<pre> \fetchallmarks [...]  *  MARK </pre>
<pre> \fetchmark [...] [...]  1  MARK 2  first last current previous next top bottom default both all first:nocheck last:nocheck previous:nocheck next:nocheck    top:nocheck bottom:nocheck </pre>
<pre> \fetchmarking [...] [...] [...]  1  MARK 2  page NAME 3  first last current previous next top bottom default both all first:nocheck last:nocheck previous:nocheck next:nocheck    top:nocheck bottom:nocheck </pre>
<pre> \fetchonemark [...] [...]  1  MARK 2  first last current previous next top bottom default both all first:nocheck last:nocheck previous:nocheck next:nocheck    top:nocheck bottom:nocheck </pre>
<pre> \fetchonemarking [...] [...] [...]  1  MARK 2  page NAME 3  first last current previous next top bottom default both all first:nocheck last:nocheck previous:nocheck next:nocheck    top:nocheck bottom:nocheck </pre>
<pre> \fetchruntinecommand \... {...}  1  CSNAME 2  FILE </pre>
<pre> \fetchtwomarkings [...] [...]  1  MARK 2  page NAME </pre>

\fetchtwomarks [...] * MARK
\field [...] [...] 1 NAME 2 TEXT
\fieldbody [...] [...] 1 NAME 2 inherits: \setupfieldbody
\fieldstack [...] [...] 1 NAME 2 NAME 3 inherits: \setupfieldcategory
\fifthoffivearguments {...} {...} {...} {...} {...} 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT
\fifthofsixarguments {...} {...} {...} {...} {...} {...} 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT
\figurefilename
\figurefilepath
\figurefiletype
\figurefullname
\figureheight
\figurenaturalheight
\figurenaturalwidth
\figuresymbol [...] [...] 1 FILE NAME 2 inherits: \externalfigure

<code>\figurewidth</code>
<code>\filename {...}</code> *    FILE
<code>\filledhboxb <sup>1</sup> {...}</code> 1    TEXT 2    CONTENT
<code>\filledhboxc <sup>1</sup> {...}</code> 1    TEXT 2    CONTENT
<code>\filledhboxg <sup>1</sup> {...}</code> 1    TEXT 2    CONTENT
<code>\filledhboxk <sup>1</sup> {...}</code> 1    TEXT 2    CONTENT
<code>\filledhboxm <sup>1</sup> {...}</code> 1    TEXT 2    CONTENT
<code>\filledhboxr <sup>1</sup> {...}</code> 1    TEXT 2    CONTENT
<code>\filledhboxy <sup>1</sup> {...}</code> 1    TEXT 2    CONTENT
<code>\filler [...]</code> *    sym symbol rule width space NAME
<code>\fillinline [...<sup>*</sup>...]</code> *    inherits: \setupfillinlines
<code>\fillinrules [...<sup>1</sup>...<sup>2</sup>...<sup>3</sup>...] {...} {...}</code> 1    inherits: \setupfillinrules 2    TEXT 3    TEXT
<code>\fillintext [...<sup>1</sup>...<sup>2</sup>...<sup>3</sup>...] {...} {...}</code> 1    inherits: \setupfillinrules 2    TEXT 3    TEXT

\filterfromnext {...} {...}

1 NUMBER

2 NUMBER

\filterfromvalue {...} {...} {...}

1 NAME

2 NUMBER

3 NUMBER

\filterpages [...]<sup>1</sup> [...]<sup>2</sup>,... [...]<sup>3</sup>,...]

1 FILE

2 even odd NUMBER NUMBER:NUMBER

3 width = DIMENSION

category = CD:STRING

n = NUMBER

\filterreference {...}

\* default text title number page realpage

\findtwopassdata {...} {...}

1 NAME

2 NAME

\finishregisterentry [...]<sup>1</sup> [...]<sup>2</sup>,... [...]<sup>3</sup>,...]

1 NAME

2 label = NAME

keys = TEXT PROCESSOR->TEXT

entries = TEXT PROCESSOR->TEXT

alternative = TEXT

3 KEY = VALUE

\firstcharacter

\firstcounter [...]<sup>1</sup> [...]<sup>2</sup>

1 NAME

2 NUMBER

\firstcountervalue [...]<sup>\*</sup>

\* NAME

\firstoffivearguments {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup> {...}<sup>4</sup> {...}<sup>5</sup>

1 TEXT

2 TEXT

3 TEXT

4 TEXT

5 TEXT



\firstoffourarguments {...} {...} {...} {...}

- 1 TEXT
- 2 TEXT
- 3 TEXT
- 4 TEXT

\firstofoneargument {...}

- \* TEXT

\firstofoneunexpanded {...}

- \* TEXT

\firstofsixarguments {...} {...} {...} {...} {...} {...}

- 1 TEXT
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT
- 6 TEXT

\firstofthreearguments {...} {...} {...}

- 1 TEXT
- 2 TEXT
- 3 TEXT

\firstofthreeunexpanded {...} {...} {...}

- 1 TEXT
- 2 TEXT
- 3 TEXT

\firstoftwoarguments {...} {...}

- 1 TEXT
- 2 TEXT

\firstoftwounexpanded {...} {...}

- 1 TEXT
- 2 TEXT

\firstrealpage

\firstrealpagenumber

\firstsubcountervalue [...] [...]

- 1 NAME
- 2 NUMBER

\firstsubpage

<code>\firstsubpagenumber</code>
<code>\firstuserpage</code>
<code>\firstuserpagenumber</code>
<code>\fitfield [.<sup>1</sup>.] [...<sup>2</sup>...,...]</code> 1 NAME 2 inherits: \setupfieldbody
<code>\fitfieldframed [...<sup>1</sup>...,...<sup>2</sup>.] {...}</code> 1 inherits: \setupframed 2 CONTENT
<code>\fittopbaselinegrid {...}</code> * CONTENT
<code>\fixedspace</code>
<code>\fixedspaces</code>
<code>\flag {...}</code> * NAME
<code>\floatuserdataparameter {...}</code> * KEY
<code>\flushcollector [...]</code> * NAME
<code>\flushedrightlastline</code>
<code>\flushlayer [...]</code> * NAME
<code>\flushlocalfloats</code>
<code>\flushnextbox</code>
<code>\flushnotes</code>
<code>\flushoutputstream [...]</code> * NAME
<code>\flushshapebox</code>
<code>\flushtextflow {...}</code> * NAME

\flushtokens [...]  *   NAME
\flushtoks \*...  *   CSNAME
\fontalternative
\fontbody
\fontchar {...}  *   NAME
\fontcharbyindex {...}  *   NUMBER
\fontclass
\fontclassname {...} {...}  1   NAME 2   FONT
\fontface
\fontfeaturelist [... <sup>1</sup> ] [... <sup>2</sup> ]  1   NAME 2   TEXT
\fontsize
\fontstyle
\footnotetext [..., <sup>1</sup> ...] {... <sup>2</sup> }  1   REFERENCE 2   TEXT
\footnotetext [..., <sup>*</sup> ...,...]  *   title       = TEXT bookmark   = TEXT list        = TEXT reference   = REFERENCE
\footnote [..., <sup>1</sup> ...] {... <sup>2</sup> }  1   REFERENCE 2   TEXT
\footnote [..., <sup>*</sup> ...,...]  *   title       = TEXT bookmark   = TEXT list        = TEXT reference   = REFERENCE

<code>\forcecharacterstripping</code>
<code>\forcelocalfloats</code>
<code>\forgeteverypar</code>
<code>\forgetparameters</code> [ <sup>1</sup> ...] [ <sup>2</sup> ... <sub>2</sub> ...] 1 TEXT 2 KEY = VALUE
<code>\forgetragged</code>
<code>\formula</code> [... <sup>1</sup> ,...] {... <sup>2</sup> .} 1 packed tight middle frame inherits: \setupbodyfont 2 CONTENT
<code>\formulanumber</code> [...*,...] * REFERENCE
<code>\foundbox</code> {... <sup>1</sup> .} {... <sup>2</sup> .} 1 NAME 2 NAME
<code>\fourthoffivearguments</code> {... <sup>1</sup> .} {... <sup>2</sup> .} {... <sup>3</sup> .} {... <sup>4</sup> .} {... <sup>5</sup> .} 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT
<code>\fourthoffourarguments</code> {... <sup>1</sup> .} {... <sup>2</sup> .} {... <sup>3</sup> .} {... <sup>4</sup> .} 1 TEXT 2 TEXT 3 TEXT 4 TEXT
<code>\fourthofsixarguments</code> {... <sup>1</sup> .} {... <sup>2</sup> .} {... <sup>3</sup> .} {... <sup>4</sup> .} {... <sup>5</sup> .} {... <sup>6</sup> .} 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT
<code>\frac</code> {... <sup>1</sup> .} {... <sup>2</sup> .} 1 CONTENT 2 CONTENT

$\frac{...}{...}$ 1    CONTENT 2    CONTENT
$\boxed{...,...^1...,...}$ $\{...\}$ 1    inherits: \setupframed 2    CONTENT
$\boxed{\text{dimension}} \{...\}$ *    KEY
$\boxed{\text{parameter}} \{...\}$ *    KEY
$\boxed{\text{text}} [...,...^1...,...] \{...\}$ 1    inherits: \setupframedtext 2    CONTENT
$\boxed{\text{text}} [...,...^1...,...] \{...\}$ 1    inherits: \setupframedtext 2    CONTENT
$\boxed{\text{text}} [...,...^1...,...] \{...\}$ 1    inherits: \setupframed 2    CONTENT
$\frozen{\text{dimension}} \text{ } ^1... \text{ } ^2...$ 1    CSNAME 2    CSNAME
$\frozen{\text{measure}} [^1...] [^2...]$ 1    NAME 2    DIMENSION
$\frenchspacing$
$\text{from } [^*...]$ *    REFERENCE
$\text{fromlinenote } [^1...] \{^2...\}$ 1    REFERENCE 2    TEXT
$\text{frozenhbox } \{^*...\}$ *    CONTENT
$\text{GetPar}$

<code>\GotoPar</code>
<code>\Greeknumpals {...}</code> *    NUMBER
<code>\gdefconvertedargument \<sup>1</sup>... {<sup>2</sup>...}</code> 1    CSNAME 2    TEXT
<code>\gdefconvertedcommand \<sup>1</sup>... \<sup>2</sup>...</code> 1    CSNAME 2    CSNAME
<code>\getboxllx ...</code> *    CSNAME NUMBER
<code>\getboxlly ...</code> *    CSNAME NUMBER
<code>\getbuffer [...]</code> *    BUFFER
<code>\getbufferdata [...]</code> *    BUFFER
<code>\getbuffer</code>
<code>\getcommacommandsize [...*,...]</code> *    COMMAND
<code>\getcommalistsize [...*,...]</code> *    COMMAND
<code>\getdayoftheweek {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...}</code> 1    NUMBER 2    NUMBER 3    NUMBER
<code>\getdayspermonth {<sup>1</sup>...} {<sup>2</sup>...}</code> 1    NUMBER 2    NUMBER
<code>\getdefinedbuffer [...]</code> *    BUFFER
<code>\getdocumentargument {...}</code> *    NAME

<code>\getdocumentargumentdefault {...} {...}</code>  1 NAME 2 TEXT
<code>\getdocumentfilename {...}</code>  * NUMBER
<code>\getdummyparameters [..., ...<sup>2</sup>..., ...]</code>  * KEY = VALUE
<code>\getemptyparameters [...<sup>1</sup>] [..., ...<sup>2</sup>..., ...]</code>  1 TEXT 2 KEY = VALUE
<code>\getparameters [...<sup>1</sup>] [..., ...<sup>2</sup>..., ...]</code>  1 TEXT 2 KEY = VALUE
<code>\getexpandedparameters [...<sup>1</sup>] [..., ...<sup>2</sup>..., ...]</code>  1 TEXT 2 KEY = VALUE
<code>\getfiguredimensions [...<sup>1</sup>] [..., ...<sup>2</sup>..., ...]</code>  1 FILE 2 inherits: \setupexternalfigure
<code>\getfirstcharacter {...}</code>  * TEXT
<code>\getfirsttwopassdata {...}</code>  * NAME
<code>\getfromcommacommand [...<sup>1</sup>, ...] [...<sup>2</sup>]</code>  1 COMMAND 2 NUMBER
<code>\getfromcommalist [...<sup>1</sup>, ...] [...<sup>2</sup>]</code>  1 COMMAND 2 NUMBER
<code>\getfromtwopassdata {...<sup>1</sup>} {...<sup>2</sup>}</code>  1 NAME 2 NAME
<code>\getglyphdirect {...<sup>1</sup>} {...<sup>2</sup>}</code>  1 FONT 2 NUMBER CHARACTER

<code>\getglyphstyled {...} {...}</code>  1    FONT 2    NUMBER CHARACTER
<code>\getgparameters [...]<sup>1</sup> [...,...<sup>2</sup>...,...]</code>  1    TEXT 2    KEY = VALUE
<code>\getlasttwopassdata {...}</code>  *    NAME
<code>\getlocalfloat {...}</code>  *    NUMBER
<code>\getlocalfloats</code>
<code>\getMPdrawing</code>
<code>\getMPlayer [...]<sup>1</sup> [...,...<sup>2</sup>...,...]<sup>3</sup> {...}</code>  1    NAME 2    inherits: \setupframed 3    CONTENT
<code>\getmarking [...]<sup>1</sup> [...]<sup>2</sup> [...]<sup>3</sup></code>  1    MARK 2 <u>page</u> NAME 3    first last current previous next top bottom default both all first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck
<code>\getmessage {...}<sup>1</sup> {...}<sup>2</sup></code>  1    NAME 2    NAME NUMBER
<code>\getnamedglyphdirect {...}<sup>1</sup> {...}<sup>2</sup></code>  1    FONT 2    NAME
<code>\getnamedglyphstyled {...}<sup>1</sup> {...}<sup>2</sup></code>  1    FONT 2    NAME
<code>\getnamedtwopassdatalist \... {...}<sup>1</sup> {...}<sup>2</sup></code>  1    CSNAME 2    NAME
<code>\getnaturaldimensions ...</code>  *    CSNAME NUMBER



<pre>\getnoflines {...}</pre> <pre>*    DIMENSION</pre>
<pre>\getobject {...} {...}</pre> <pre>1    NAME</pre> <pre>2    NAME</pre>
<pre>\getobjectdimensions {...} {...}</pre> <pre>1    NAME</pre> <pre>2    NAME</pre>
<pre>\getpaletsize [...]</pre> <pre>*    NAME</pre>
<pre>\getparameters [...] [...,..<sup>2</sup>...,...]</pre> <pre>1    TEXT</pre> <pre>2    KEY  =  VALUE</pre>
<pre>\getprivateslot {...}</pre> <pre>*    NAME</pre>
<pre>\getrandomcount \... {...} {...}</pre> <pre>1    CSNAME</pre> <pre>2    NUMBER</pre> <pre>3    NUMBER</pre>
<pre>\getrandomdimen \... {...} {...}</pre> <pre>1    CSNAME</pre> <pre>2    DIMENSION</pre> <pre>3    DIMENSION</pre>
<pre>\getrandomfloat \... {...} {...}</pre> <pre>1    CSNAME</pre> <pre>2    NUMBER</pre> <pre>3    NUMBER</pre>
<pre>\getrandomnumber \... {...} {...}</pre> <pre>1    CSNAME</pre> <pre>2    NUMBER</pre> <pre>3    NUMBER</pre>
<pre>\getrandomseed \...</pre> <pre>*    CSNAME</pre>
<pre>\getraweparameters [...<sup>1</sup>] [...,..<sup>2</sup>...,...]</pre> <pre>1    TEXT</pre> <pre>2    KEY  =  VALUE</pre>

\getrawgparameters [<sup>1</sup>...] [<sup>2</sup>...,...]

1 TEXT

2 KEY = VALUE

\getrawnoflines {...}

\* DIMENSION

\getrawparameters [<sup>1</sup>...] [<sup>2</sup>...,...]

1 TEXT

2 KEY = VALUE

\getrawxparameters [<sup>1</sup>...] [<sup>2</sup>...,...]

1 TEXT

2 KEY = VALUE

\getreference [<sup>1</sup>...] [<sup>2</sup>...]

1 default text title number page realpage

2 REFERENCE

\getreferenceentry {...}

\* default text title number page realpage

\getroundednoflines {...}

\* DIMENSION

\getsubstring {...} {...} {...}

1 NUMBER

2 NUMBER

3 TEXT

\gettwopassdata {...}

\* NAME

\gettwopassdatalist {...}

\* NAME

\getuvalue {...}

\* NAME

\getvalue {...}

\* NAME

\getvariable {...} {...}

1 NAME

2 KEY

`\getvariabledefault {...} {...} {...}`

- 1 NAME
- 2 KEY
- 3 COMMAND

`\getxparameters [...] [...,2...,...]`

- 1 TEXT
- 2 KEY = VALUE

`\globaldisablemode [...,*,...]`

- \* NAME

`\globalenablemode [...,*,...]`

- \* NAME

`\globalletempty \*...`

- \* CSNAME

`\globalpopbox ...`

- \* CSNAME NUMBER

`\globalpopmacro \*...`

- \* CSNAME

`\globalpreventmode [...,*,...]`

- \* NAME

`\globalprocesscommalist [...] \*...`

- 1 COMMAND
- 2 CSNAME

`\globalpushbox ...`

- \* CSNAME NUMBER

`\globalpushmacro \*...`

- \* CSNAME

`\globalpushreferenceprefix {...} ... \globalpopreferenceprefix`

- \* + - TEXT

`\globalswapcounts \*... \*...`

- 1 CSNAME
- 2 CSNAME

`\globalswapdimens \*... \*...`

- 1 CSNAME
- 2 CSNAME

`\globalswapmacros \1... \2...`

1 CSNAME

2 CSNAME

`\globalundefine {...}`

\* NAME

`\glyphfontfile {...}`

\* FONT

`\gobbledoubleempty [1...] [2...]`

1 TEXT

2 TEXT

`\gobbleeightarguments {...} {...} {...} {...} {...} {...} {...} {...}`

1 CONTENT

2 CONTENT

3 CONTENT

4 CONTENT

5 CONTENT

6 CONTENT

7 CONTENT

8 CONTENT

`\gobblefivearguments {...} {...} {...} {...} {...}`

1 CONTENT

2 CONTENT

3 CONTENT

4 CONTENT

5 CONTENT

`\gobblefiveoptionals [1...] [2...] [3...] [4...] [5...]`

1 TEXT

2 TEXT

3 TEXT

4 TEXT

5 TEXT

`\gobblefourarguments {...} {...} {...} {...}`

1 CONTENT

2 CONTENT

3 CONTENT

4 CONTENT

`\gobblefouroptionals [...] [...] [...] [...]`

1 TEXT  
2 TEXT  
3 TEXT  
4 TEXT

`\gobbleninearguments {...} {...} {...} {...} {...} {...} {...} {...} {...}`

1 CONTENT  
2 CONTENT  
3 CONTENT  
4 CONTENT  
5 CONTENT  
6 CONTENT  
7 CONTENT  
8 CONTENT  
9 CONTENT

`\gobbleoneargument {...}`

\* CONTENT

`\gobbleoneoptional [...]`

\* TEXT

`\gobblesevenarguments {...} {...} {...} {...} {...} {...} {...}`

1 CONTENT  
2 CONTENT  
3 CONTENT  
4 CONTENT  
5 CONTENT  
6 CONTENT  
7 CONTENT

`\gobblesingleempty [...]`

\* TEXT

`\gobblesixarguments {...} {...} {...} {...} {...} {...}`

1 CONTENT  
2 CONTENT  
3 CONTENT  
4 CONTENT  
5 CONTENT  
6 CONTENT

`\gobblespacetokens`

`\gobbletenarguments {1.} {2.} {3.} {4.} {5.} {6.} {7.} {8.} {9.} {10.}`

- 1    CONTENT
- 2    CONTENT
- 3    CONTENT
- 4    CONTENT
- 5    CONTENT
- 6    CONTENT
- 7    CONTENT
- 8    CONTENT
- 9    CONTENT
- 10   CONTENT

`\gobblethreearguments {1.} {2.} {3.}`

- 1    CONTENT
- 2    CONTENT
- 3    CONTENT

`\gobblethreeoptionals [1.] [2.] [3.]`

- 1    TEXT
- 2    TEXT
- 3    TEXT

`\gobbletwoarguments {1.} {2.}`

- 1    CONTENT
- 2    CONTENT

`\gobbletwooptionals [1.] [2.]`

- 1    TEXT
- 2    TEXT

`\gobbleuntil \...`

- \*    CSNAME

`\gobbleuntilrelax ... \relax`

- \*    CONTENT

`\godown [*.]`

- \*    DIMENSION

`\goto {1.} [2.]`

- 1    CONTENT
- 2    REFERENCE

`\gotobox {1.} [2.]`

- 1    CONTENT
- 2    REFERENCE

<p><code>\gotopage {<sup>1</sup>...} [<sup>2</sup>...]</code></p> <p>1    TEXT</p> <p>2    REFERENCE</p>
<p><code>\got [<sup>1</sup>...] <sup>2</sup>... \\\</code></p> <p>1    REFERENCE</p> <p>2    TEXT</p>
<p><code>\grabbufferdata [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...] [<sup>4</sup>...]</code></p> <p>1    CATEGORY</p> <p>2    NAME</p> <p>3    NAME</p> <p>4    NAME</p>
<p><code>\grabbufferdatadirect {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...}</code></p> <p>1    NAME</p> <p>2    NAME</p> <p>3    NAME</p>
<p><code>\grabuntil {<sup>1</sup>...} \<sup>2</sup>...</code></p> <p>1    NAME</p> <p>2    CSNAME</p>
<p><code>\grave {<sup>*</sup>...}</code></p> <p>*    CHARACTER</p>
<p><code>\graycolor [<sup>1</sup>...] {<sup>2</sup>...}</code></p> <p>1    COLOR</p> <p>2    CONTENT</p>
<p><code>\grayvalue {<sup>*</sup>...}</code></p> <p>*    COLOR</p>
<p><code>\greedystring \at <sup>1</sup>... \at <sup>2</sup>... \to <sup>3</sup>... \and <sup>4</sup>...</code></p> <p>1    TEXT</p> <p>2    TEXT</p> <p>3    CSNAME</p> <p>4    CSNAME</p>
<p><code>\greeknumerals {<sup>*</sup>...}</code></p> <p>*    NUMBER</p>
<p><code>\grid [...,<sup>*</sup>...,...]</code></p> <p>*    inherits: \basegrid</p>

<code>\groupedcommand {...} {...}</code>  1    COMMAND 2    COMMAND
<code>\gsetboxllx <sup>1</sup>... {...}</code>  1    CSNAME NUMBER 2    DIMENSION
<code>\gsetboxlly <sup>1</sup>... {...}</code>  1    CSNAME NUMBER 2    DIMENSION
<code>\gujaratinumerals {...}</code>  *    NUMBER
<code>\gurmukhinumerals {...}</code>  *    NUMBER
<code>\hairline</code>
<code>\hairspace</code>
<code>\halfwaybox {...}</code>  *    CONTENT
<code>\handletokens <sup>1</sup>... \with <sup>2</sup>...</code>  1    TEXT 2    CSNAME
<code>\handwritten</code>
<code>\hangul</code>
<code>\hanzi</code>
<code>\hash</code>
<code>\hat {...}</code>  *    CHARACTER
<code>\hboxofvbox <sup>*</sup>...</code>  *    CSNAME NUMBER
<code>\hboxreference [...<sup>1</sup>,...] {...<sup>2</sup>...}</code>  1    REFERENCE 2    CONTENT



<code>\hboxbox {...}</code> *    CONTENT
<code>\hdofstring {...}</code> *    TEXT
<code>\headhbox .<sup>1</sup>. {...}</code> 1    TEXT 2    CONTENT
<code>\headlanguage</code>
<code>\headnumber [...<sup>1</sup>...] [...<sup>2</sup>...]</code> 1    SECTION 2    previous <u>current</u> next first last
<code>\headnumbercontent</code>
<code>\headnumberdistance</code>
<code>\headnumberwidth</code>
<code>\headreferenceattributes</code>
<code>\headsym {...<sup>1</sup>} [...<sup>2</sup>,...<sup>3</sup>] {...<sup>3</sup>}</code> 1    TEXT 2    REFERENCE 3    TEXT
<code>\headtext {...}</code> *    KEY
<code>\headtextcontent</code>
<code>\headtexts {...<sup>1</sup>} {...<sup>2</sup>}</code> 1    KEY 2    TEXT
<code>\headtextwidth</code>
<code>\headvbox ... {...<sup>1</sup>} {...<sup>2</sup>}</code> 1    TEXT 2    CONTENT
<code>\headwidth</code>
<code>\head ... \par</code> *    TEXT

<code>\heightanddepthofstring {...}</code> * TEXT
<code>\heightofstring {...}</code> * TEXT
<code>\heightspanningtext {...} {...} {...}</code> 1 TEXT 2 DIMENSION 3 FONT
<code>\helptext [...] {...} {...}</code> 1 REFERENCE 2 TEXT 3 TEXT
<code>\help [...] {...} {...}</code> 1 REFERENCE 2 TEXT 3 TEXT
<code>\hglue ...</code> * DIMENSION
<code>\hiddencitation [...]</code> * REFERENCE
<code>\hiddencite [...]</code> * REFERENCE
<code>\hideblocks [...<sup>1</sup>,...] [...<sup>2</sup>,...]</code> 1 NAME 2 + -
<code>\high {...}</code> * CONTENT
<code>\highlight [...] {...}</code> 1 NAME 2 TEXT
<code>\highlight {...}</code> * TEXT
<code>\highordinalstr {...}</code> * TEXT

$\backslash high \{...\}$ *    CONTENT
$\backslash hilo \left[ \begin{smallmatrix} 1 \\ \vdots \end{smallmatrix} \right] \left\{ \begin{smallmatrix} 2 \\ \vdots \end{smallmatrix} \right\} \left\{ \begin{smallmatrix} 3 \\ \vdots \end{smallmatrix} \right\}$ 1    left <u>right</u> 2    CONTENT 3    CONTENT
$\backslash himilo \left\{ \begin{smallmatrix} 1 \\ \vdots \end{smallmatrix} \right\} \left\{ \begin{smallmatrix} 2 \\ \vdots \end{smallmatrix} \right\} \left\{ \begin{smallmatrix} 3 \\ \vdots \end{smallmatrix} \right\}$ 1    CONTENT 2    CONTENT 3    CONTENT
$\backslash hl \left[ \begin{smallmatrix} * \\ \vdots \end{smallmatrix} \right]$ *    NUMBER
$\backslash horizontalgrowingbar \left[ \begin{smallmatrix} \vdots \\ \vdots \\ \vdots \end{smallmatrix} \right] \left[ \begin{smallmatrix} * \\ \vdots \\ \vdots \end{smallmatrix} \right]$ *    inherits: $\backslash setuppositionbar$
$\backslash horizontalpositionbar \left[ \begin{smallmatrix} \vdots \\ \vdots \\ \vdots \end{smallmatrix} \right] \left[ \begin{smallmatrix} * \\ \vdots \\ \vdots \end{smallmatrix} \right]$ *    inherits: $\backslash setuppositionbar$
$\backslash hphantom \{...\}$ *    CONTENT
$\backslash hpos \left\{ \begin{smallmatrix} 1 \\ \vdots \end{smallmatrix} \right\} \left\{ \begin{smallmatrix} 2 \\ \vdots \end{smallmatrix} \right\}$ 1    NAME 2    CONTENT
$\backslash hsizefraction \left\{ \begin{smallmatrix} 1 \\ \vdots \end{smallmatrix} \right\} \left\{ \begin{smallmatrix} 2 \\ \vdots \end{smallmatrix} \right\}$ 1    DIMENSION 2    NUMBER
$\backslash hsmash \{...\}$ *    CONTENT
$\backslash hsmashbox \begin{smallmatrix} * \\ \vdots \end{smallmatrix}$ *    CSNAME NUMBER
$\backslash hsmashed \{...\}$ *    CONTENT
$\backslash hspace \left[ \begin{smallmatrix} 1 \\ \vdots \end{smallmatrix} \right] \left[ \begin{smallmatrix} 2 \\ \vdots \end{smallmatrix} \right]$ 1    NAME 2    small medium big normal <u>default</u> none .5 1 2 3 speech quote interquotation quotation sentence intersentence NAME
$\backslash htdpofstring \{...\}$ *    TEXT

<code>\htofstring {...}</code> *    TEXT
<code>\hyphen</code>
<code>\hyphenatedcoloredword {...}</code> *    TEXT
<code>\hyphenatedfile {...}</code> *    FILE
<code>\hyphenatedfilename {...}</code> *    TEXT
<code>\hyphenatedhbox {...}</code> *    CONTENT
<code>\hyphenatedpar {...}</code> *    TEXT
<code>\hyphenatedurl {...}</code> *    TEXT
<code>\hyphenatedword {...}</code> *    TEXT
<code>\INRSTEX</code>
<code>\ibox {...}</code> *    CONTENT
<code>\ifassignment ...<sup>1</sup> \else ...<sup>2</sup> \fi</code> 1    TRUE 2    FALSE
<code>\iff</code>
<code>\ifinobject ...<sup>1</sup> \else ...<sup>2</sup> \fi</code> 1    TRUE 2    FALSE
<code>\ifinoutputstream ...<sup>1</sup> \else ...<sup>2</sup> \fi</code> 1    TRUE 2    FALSE
<code>\ifparameters ...<sup>1</sup> \else ...<sup>2</sup> \fi</code> 1    TRUE 2    FALSE

<pre> \iftrualtypesetting <sup>1</sup>... \else <sup>2</sup>... \fi  1 TRUE 2 FALSE </pre>
<pre> \ignoreimplicitspaces </pre>
<pre> \ignorevalue {...}  * NAME </pre>
<pre> \immediatesavetwopassdata <sup>1</sup>{...} <sup>2</sup>{...} <sup>3</sup>{...}  1 NAME 2 NUMBER 3 CONTENT </pre>
<pre> \impliedby </pre>
<pre> \implies </pre>
<pre> \in <sup>1</sup>{...} <sup>2</sup>{...} [<sup>3</sup>...]  1 TEXT 2 TEXT 3 REFERENCE </pre>
<pre> \includemenu [...]  * NAME </pre>
<pre> \includeversioninfo {...}  * NAME </pre>
<pre> \incrementcounter [<sup>1</sup>...] [<sup>2</sup>...]  1 NAME 2 NUMBER </pre>
<pre> \incrementedcounter [...]  * NAME </pre>
<pre> \incrementpagenumber </pre>
<pre> \incrementsubpagenumber </pre>
<pre> \incrementvalue {...}  * NAME </pre>
<pre> \increment \*...  * CSNAME </pre>
<pre> \increment cd:parentheses-1  * CSNAME NUMBER </pre>

<code>\indentation</code>
<code>\index [...]<sup>1</sup> [...+...+...]<sup>2</sup></code> 1    TEXT   PROCESSOR->TEXT 2    INDEX
<code>\index [...]<sup>1</sup> {...}<sup>2</sup> [...+...+...]<sup>3</sup></code> 1    TEXT   PROCESSOR->TEXT 2    TEXT 3    INDEX
<code>\infofont</code>
<code>\infofontbold</code>
<code>\inframed [...,...]<sup>1</sup> {...}<sup>2</sup></code> 1    inherits: \setupframed 2    CONTENT
<code>\infull {...}</code> *    NAME
<code>\inheritparameter [...]<sup>1</sup> [...]<sup>2</sup> [...]<sup>3</sup></code> 1    TEXT 2    TEXT 3    KEY
<code>\inhibitblank</code>
<code>\ininner [...,...]<sup>1</sup> [...,...]<sup>2</sup> {...}<sup>3</sup></code> 1    reference = REFERENCE inherits: \setupmargindata 2    inherits: \setupmarginframed 3    CONTENT
<code>\ininneredge [...,...]<sup>1</sup> [...,...]<sup>2</sup> {...}<sup>3</sup></code> 1    reference = REFERENCE inherits: \setupmargindata 2    inherits: \setupmarginframed 3    CONTENT
<code>\ininnermargin [...,...]<sup>1</sup> [...,...]<sup>2</sup> {...}<sup>3</sup></code> 1    reference = REFERENCE inherits: \setupmargindata 2    inherits: \setupmarginframed 3    CONTENT
<code>\initializeboxstack {...}</code> *    NAME

`\inleft [...,\overset{1}{...},...] [...,\overset{2}{...},...] {\overset{3}{...}}`

```
1 reference = REFERENCE
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT
```

`\inleftedge [...,\overset{1}{...},...] [...,\overset{2}{...},...] {\overset{3}{...}}`

```
1 reference = REFERENCE
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT
```

`\inleftmargin [...,\overset{1}{...},...] [...,\overset{2}{...},...] {\overset{3}{...}}`

```
1 reference = REFERENCE
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT
```

`\inline {\overset{1}{...}} [\overset{2}{...}]`

```
1 TEXT
2 REFERENCE
```

`\inlinebuffer [...,*,...]`

```
* BUFFER
```

`\inlinedbox {\overset{*}{...}}`

```
* CONTENT
```

`\inlinemath {\overset{*}{...}}`

```
* CONTENT
```

`\inlinemathematics {\overset{*}{...}}`

```
* CONTENT
```

`\inlinemessage {\overset{*}{...}}`

```
* TEXT
```

`\inlineordisplaymath {\overset{1}{...}} {\overset{2}{...}}`

```
1 CONTENT
2 CONTENT
```

`\inlinerrange [...]`

```
* REFERENCE
```

`\inmargin [...,\overset{1}{...},...] [...,\overset{2}{...},...] {\overset{3}{...}}`

```
1 reference = REFERENCE
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT
```

`\inmfamed [...,\stackrel{1}{=}\dots] {\stackrel{2}{\dots}}`

```
1 inherits: \setupmathframed
2 CONTENT
```

`\innerflushshapebox`

`\inothet [...,\stackrel{1}{=}\dots] [...,\stackrel{2}{=}\dots] {\stackrel{3}{\dots}}`

```
1 reference = REFERENCE
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT
```

`\inouter [...,\stackrel{1}{=}\dots] [...,\stackrel{2}{=}\dots] {\stackrel{3}{\dots}}`

```
1 reference = REFERENCE
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT
```

`\inouteredge [...,\stackrel{1}{=}\dots] [...,\stackrel{2}{=}\dots] {\stackrel{3}{\dots}}`

```
1 reference = REFERENCE
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT
```

`\inoutermargin [...,\stackrel{1}{=}\dots] [...,\stackrel{2}{=}\dots] {\stackrel{3}{\dots}}`

```
1 reference = REFERENCE
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT
```

`\inputfilebarename`

`\inputfilename`

`\inputfilerealsuffix`

`\inputfilesuffix`

`\inputgivenfile {\dots}`

```
* FILE
```

`\input {\dots}`

```
* FILE
```

`\input \dots`

```
* FILE
```



`\inright [...1...] [...2...] {...3}`

```
1 reference = REFERENCE
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT
```

`\inrightedge [...1...] [...2...] {...3}`

```
1 reference = REFERENCE
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT
```

`\inrightmargin [...1...] [...2...] {...3}`

```
1 reference = REFERENCE
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT
```

`\insertpages [...1] [...2,...] [...3...,...]`

```
1 FILE
2 NUMBER
3 width = DIMENSION
  n     = NUMBER
```

`\installactionhandler {...}`

`* NAME`

`\installactivecharacter ...`

`* CHARACTER`

`\installanddefineactivecharacter ...1 {...2}`

```
1 CHARACTER
2 COMMAND
```

`\installattributestack \*...`

`* CSNAME`

`\installautocommandhandler \*1 {...2} \*3...`

```
1 CSNAME
2 NAME
3 CSNAME
```

`\installautosetuphandler \*1 {...2}`

```
1 CSNAME
2 NAME
```

`\installbasicautosetuphandler \... {...} \...`

- 1 CSNAME
- 2 NAME
- 3 CSNAME

`\installbasicparameterhandler \... {...}`

- 1 CSNAME
- 2 NAME

`\installbottomframerenderer {...} {...}`

- 1 NAME
- 2 COMMAND

`\installcommandhandler \... {...} \...`

- 1 CSNAME
- 2 NAME
- 3 CSNAME

`\installcorenamespace {...}`

- \* NAME

`\installdefinehandler \... {...} \...`

- 1 CSNAME
- 2 NAME
- 3 CSNAME

`\installdefinitionset \... {...}`

- 1 CSNAME
- 2 NAME

`\installdefinitionsetmember \... {...} \... {...}`

- 1 CSNAME
- 2 NAME
- 3 CSNAME
- 4 NAME

`\installdirectcommandhandler \... {...}`

- 1 CSNAME
- 2 NAME

`\installdirectparameterhandler \... {...}`

- 1 CSNAME
- 2 NAME

`\installdirectparametersethandler \... {...}`

- 1 CSNAME
- 2 NAME

```
\installdirectsetuphandler \... {...}
```

1 CSNAME

2 NAME

$$\backslash\mathrm{installdirectstyleandcolorhandler}\ \backslash\ldots\{.\ldots\}$$

1 CSNAME

2 NAME

$$\backslash \text{installframedautocommandhandler} \backslash^1 \dots \{ \dots \} \backslash^3$$

1 CSNAME

2 NAME

### 3 CSNAME

$$\backslash \text{installframedcommandhandler} \backslash ^1 \dots \{ \dots \} \backslash ^3 \dots$$

1 CSNAME

2 NAME

### 3 CSNAME

$$\backslash\mathrm{installlanguage} \left[ \dots \right] \left[ \dots, \dots \overset{2}{=} \dots, \dots \right]$$

1 NAME

```
2 inherits: \setuplanguage
```

$$\backslash installlanguage \left[ \dots \right] \left[ \dots \right]$$

1 NAME

## 2 LANGUAGE

$$\backslash installleftframerenderer \{...\} \{...\}$$

1 NAME

## 2 COMMAND

```
\installnamespace {...}
```

\* NAME

$$\backslash\mathrm{installoutputroutine} \backslash^1 \dots \{ \dots \}^2$$

1 CSNAME

## 2 COMMAND

$$\backslash\mathrm{installpagearrangement} \dots \{ \dots \}$$

1 NAME

## 2 COMMAND

```
\installparameterhandler \... {...}
```

1 CSNAME

2 NAME

\installparameterhashhandler \.^{.} {...}

- 1 CSNAME
- 2 NAME

\installparametersethandler \.^{.} {...}

- 1 CSNAME
- 2 NAME

\installparentinjector \.^{.} {...}

- 1 CSNAME
- 2 NAME

\installrightframerenderer {...} {...}

- 1 NAME
- 2 COMMAND

\installrootparameterhandler \.^{.} {...}

- 1 CSNAME
- 2 NAME

\installsetuphandler \.^{.} {...}

- 1 CSNAME
- 2 NAME

\installsetuponlycommandhandler \.^{.} {...}

- 1 CSNAME
- 2 NAME

\installshipoutmethod {...} {...}

- 1 NAME
- 2 COMMAND

\installsimplecommandhandler \.^{.} {...} \.^{.}

- 1 CSNAME
- 2 NAME
- 3 CSNAME

\installsimpleframedcommandhandler \.^{.} {...} \.^{.}

- 1 CSNAME
- 2 NAME
- 3 CSNAME

\installstyleandcolorhandler \.^{.} {...}

- 1 CSNAME
- 2 NAME

`\installswitchcommandhandler \...1 {...}2 \...3`

- 1 CSNAME
- 2 NAME
- 3 CSNAME

`\installswitchsetuphandler \...1 {...}2`

- 1 CSNAME
- 2 NAME

`\installtexdirective {...}1 {...}2 {...}3`

- 1 NAME
- 2 COMMAND
- 3 COMMAND

`\installtextracker {...}1 {...}2 {...}3`

- 1 NAME
- 2 COMMAND
- 3 COMMAND

`\installtopframerenderer {...}1 {...}2`

- 1 NAME
- 2 COMMAND

`\installunitsseparator {...}1 {...}2`

- 1 NAME
- 2 COMMAND

`\installunitsspace {...}1 {...}2`

- 1 NAME
- 2 COMMAND

`\installversioninfo {...}1 {...}2`

- 1 NAME
- 2 COMMAND

`\integerrounding {...}*`

- \* NUMBER

`\interactionbar [...]1 [...,...2...,...]`

- 1 NAME
- 2 inherits: \setupinteractionbar

`\interactionbuttons [...,...1...,...]2 [...,...]`

- 1 inherits: \setupinteractionbar
- 2 page subpage REFERENCE

<code>\interactionmenu [...]<sup>1</sup> [...,<sup>2</sup>...,...]</code>  1 NAME 2 inherits: \setupinteractionmenu
<code>\intertext {...}</code>  * TEXT
<code>\invokepagehandler {...}<sup>1</sup> {...}<sup>2</sup></code>  1 normal none NAME 2 CONTENT
<code>\istltdir ...</code>  * TLT TRT
<code>\istrtdir ...</code>  * TLT TRT
<code>\italic</code>
<code>\italicbold</code>
<code>\italiccorrection</code>
<code>\items [...,<sup>1</sup>...,...]<sup>2</sup> {...}</code>  1 inherits: \setupitems 2 TEXT
<code>\itemtag [...,*,...]</code>  * REFERENCE
<code>\item [...,*,...]</code>  * REFERENCE
<code>\itm [...,*,...]</code>  * REFERENCE
<code>\its</code>
<code>\jobfilename</code>
<code>\jobfilesuffix</code>
<code>\kap {...}</code>  * TEXT
<code>\keepblocks [...,<sup>1</sup>...,...]<sup>2</sup> [...,<sup>2</sup>...,...]</code>  1 NAME 2 + -

<code>\keeplinestogether {...}</code>  *    NUMBER
<code>\keepunwantedspaces</code>
<code>\kerncharacters [...]<sup>1</sup> {...}<sup>2</sup></code>  1    NUMBER 2    TEXT
<code>\koreancirclenumerals {...}</code>  *    NUMBER
<code>\koreannumerals {...}</code>  *    NUMBER
<code>\koreannumeralsc {...}</code>  *    NUMBER
<code>\koreannumeralsp {...}</code>  *    NUMBER
<code>\koreanparentnumerals {...}</code>  *    NUMBER
<code>\LAMSTEX</code>
<code>\LATEX</code>
<code>\LamSTeX</code>
<code>\LaTeX</code>
<code>\LUAJITTEX</code>
<code>\LUATEX</code>
<code>\Lua</code>
<code>\LuajitTeX</code>
<code>\LuaTeX</code>
<code>\labellanguage</code>
<code>\labellanguage</code>
<code>\labeltext {...}</code>  *    KEY

$\backslash\text{labeltexts} \{.^1.\} \{.^2.\}$  1 KEY 2 TEXT
$\backslash\text{labeltexts} \{.^1.\} \{.^2.\}$  1 KEY 2 TEXT
$\backslash\text{labeltext} \{.^*\}$  * KEY
$\backslash\text{label} [...^1,...] \{.^2.\}$  1 REFERENCE 2 TEXT
$\backslash\text{language} [.^*]$  * LANGUAGE
$\backslash\text{languageCharacters} \{.^*\}$  * NUMBER
$\backslash\text{languagecharacters} \{.^*\}$  * NUMBER
$\backslash\text{languagecharwidth} \{.^*\}$  * LANGUAGE
$\backslash\text{language}$
$\backslash\text{lastcounter} [...^1] [...^2]$  1 NAME 2 NUMBER
$\backslash\text{lastcountervalue} [.^*]$  * NAME
$\backslash\text{lastdigit} \{.^*\}$  * NUMBER
$\backslash\text{lastnaturalboxdp}$
$\backslash\text{lastnaturalboxht}$
$\backslash\text{lastnaturalboxwd}$
$\backslash\text{lastpredefinedsymbol}$
$\backslash\text{lastrealpage}$



<code>\lastrealpagenumber</code>
<code>\lastsubcountervalue [...]<sup>1</sup> [...]<sup>2</sup></code> 1 NAME 2 NUMBER
<code>\lastsubpage</code>
<code>\lastsubpagenumber</code>
<code>\lasttwodigits {...}</code> * NUMBER
<code>\lastuserpage</code>
<code>\lastuserpagenumber</code>
<code>\lateluacode {...}</code> * COMMAND
<code>\latin</code>
<code>\layeredtext [...]<sup>1</sup> [...]<sup>2</sup> {...}<sup>3</sup> {...}<sup>4</sup></code> 1 inherits: \setupplayer 2 inherits: \setuplayeredtext 3 TEXT 4 CONTENT
<code>\layerheight</code>
<code>\layerwidth</code>
<code>\lazysavetaggedtwopassdata {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup> {...}<sup>4</sup></code> 1 NAME 2 NUMBER 3 NAME 4 CONTENT
<code>\lazysavetwopassdata {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup></code> 1 NAME 2 NUMBER 3 CONTENT
<code>\lbox ...<sup>1</sup> {...}<sup>2</sup></code> 1 TEXT 2 CONTENT

<code>\left ...</code> * CHARACTER
<code>\leftaligned {...}</code> * CONTENT
<code>\leftbottombox {...}</code> * CONTENT
<code>\leftbox {...}</code> * CONTENT
<code>\lefthbox {...}</code> * CONTENT
<code>\leftheadtext {...}</code> * KEY
<code>\leftlabeltext {...}</code> * KEY
<code>\leftlabeltext {...}</code> * KEY
<code>\leftline {...}</code> * CONTENT
<code>\leftmathlabeltext {...}</code> * KEY
<code>\lefttorrighthbox ...<sup>1</sup> {...<sup>2</sup>}</code> 1 TEXT 2 CONTENT
<code>\lefttorrightvbox ...<sup>1</sup> {...<sup>2</sup>}</code> 1 TEXT 2 CONTENT
<code>\lefttorrightvtop ...<sup>1</sup> {...<sup>2</sup>}</code> 1 TEXT 2 CONTENT
<code>\leftskipadaption</code>
<code>\leftsubguillemot</code>
<code>\lefttopbox {...}</code> * CONTENT

<code>\lefttoright</code>
<code>\lefttorighthbox <sup>1</sup> {...}</code> 1 TEXT 2 CONTENT
<code>\lefttorightvbox <sup>1</sup> {...}</code> 1 TEXT 2 CONTENT
<code>\lefttorightvtop <sup>1</sup> {...}</code> 1 TEXT 2 CONTENT
<code>\letbeundefined {...}</code> * NAME
<code>\letcatcodecommand \<sup>1</sup>... <sup>2</sup>... \<sup>3</sup>...</code> 1 CSNAME 2 CHARACTER NUMBER 3 CSNAME
<code>\letcscsname \<sup>1</sup>... \csname <sup>2</sup>... \endcsname</code> 1 CSNAME 2 NAME
<code>\letcsnamecs \csname <sup>1</sup>... \endcsname \<sup>2</sup>...</code> 1 NAME 2 CSNAME
<code>\letcsnamecsname \csname <sup>1</sup>... \endcsname \csname <sup>2</sup>... \endcsname</code> 1 NAME 2 NAME
<code>\letdummyparameter {...} \<sup>2</sup>...</code> 1 KEY 2 CSNAME
<code>\letempty \*...</code> * CSNAME
<code>\letgvalue {...} \<sup>2</sup>...</code> 1 NAME 2 CSNAME
<code>\letgvalueempty {...}</code> * NAME

<code>\letgvalurelax {...}</code>
<code>* NAME</code>
<code>\letterampersand</code>
<code>\letterat</code>
<code>\letterbackslash</code>
<code>\letterbar</code>
<code>\letterbgroup</code>
<code>\letterclosebrace</code>
<code>\lettercolon</code>
<code>\letterdollar</code>
<code>\letterdoublequote</code>
<code>\letteregroup</code>
<code>\letterescape</code>
<code>\letterexclamationmark</code>
<code>\letterhash</code>
<code>\letterhat</code>
<code>\letterleftbrace</code>
<code>\letterless</code>
<code>\lettermore</code>
<code>\letteropenbrace</code>
<code>\letterpercent</code>
<code>\letterquestionmark</code>
<code>\letterrightbrace</code>
<code>\lettersinglequote</code>
<code>\letterslash</code>

$\backslash$ letterspacing [...] <sup>1</sup> {...} <sup>2</sup> 1    NUMBER 2    TEXT
$\backslash$ lettertilde
$\backslash$ letterunderscore
$\backslash$ letvalue {...} <sup>1</sup> \^ <sup>2</sup> 1    NAME 2    CSNAME
$\backslash$ letvalueempty {...} *    NAME
$\backslash$ letvaluerelax {...} *    NAME
$\backslash$ fence {...} *    CHARACTER
$\backslash$ hbox {...} *    CONTENT
$\backslash$ limitatelines {...} <sup>1</sup> {...} <sup>2</sup> {...} <sup>3</sup> 1    NUMBER 2    COMMAND 3    TEXT
$\backslash$ limitatetext {...} <sup>1</sup> {...} <sup>2</sup> {...} <sup>3</sup> 1    TEXT 2    [-+]DIMENSION 3    COMMAND
$\backslash$ limitatetext {...} <sup>1</sup> {..., <sup>2</sup> ...} <sup>3</sup> {...} 1    TEXT 2    [-+]DIMENSION 3    COMMAND
$\backslash$ limtatefirstline {...} <sup>1</sup> {...} <sup>2</sup> {...} <sup>3</sup> 1    TEXT 2    DIMENSION 3    COMMAND
$\backslash$ line {...} *    CONTENT

`\linenote {...}`

\* TEXT

`\linenote {...}`

\* TEXT

`\linespanningtext {...} {...} {...}`

1 TEXT

2 DIMENSION

3 FONT

`\linewidth`

`\listcitation [...1...] [...2]`

1 reference = REFERENCE  
alternative = default category entry short page num textnum year index tag keywords author authoryears authornum  
authoryear  
before = COMMAND  
after = COMMAND  
left = COMMAND  
right = COMMAND  
inherits: \setupbtx

2 REFERENCE

`\listcitation [...1...] [...2...]`

1 reference = REFERENCE  
alternative = default category entry short page num textnum year index tag keywords author authoryears authornum  
authoryear  
before = COMMAND  
after = COMMAND  
left = COMMAND  
right = COMMAND  
inherits: \setupbtx

2 KEY = VALUE

`\listcitation [...1] [...2]`

1 default category entry short page num textnum year index tag keywords author authoryears authornum authoryear

2 REFERENCE

`\listcite [...1...] [...2]`

1 reference = REFERENCE  
alternative = default category entry short page num textnum year index tag keywords author authoryears authornum  
authoryear  
before = COMMAND  
after = COMMAND  
left = COMMAND  
right = COMMAND  
inherits: \setupbtx

2 REFERENCE

`\listcite [...]{...1...} [...]{...2...}`

```
1  reference      = REFERENCE
   alternative    = default category entry short page num textnum year index tag keywords author authoryears authornum
                        authoryear
   before        = COMMAND
   after         = COMMAND
   left          = COMMAND
   right         = COMMAND
   inherits: \setupbtx
2  KEY = VALUE
```

`\listcite [...]{...1} [...]{...2}`

```
1  default category entry short page num textnum year index tag keywords author authoryears authornum authoryear
2  REFERENCE
```

`\listlength`

`\listnamespaces`

`\llap {...}`

`* CONTENT`

`\loadanyfile [...]`

`* FILE`

`\loadanyfileonce [...]`

`* FILE`

`\loadbtxdefinitionfile [...]`

`* FILE`

`\loadbtxreplacementfile [...]`

`* FILE`

`\loadcldfile [...]`

`* FILE`

`\loadcldfileonce [...]`

`* FILE`

`\loadfontgoodies [...]`

`* FILE`

`\loadluafile [...]`

`* FILE`

`\loadluafileonce [...]`

`* FILE`

<code>\loadspellchecklist [<sup>1</sup>...] [<sup>2</sup>...]</code>  1 NAME 2 FILE
<code>\loadtexfile [...]</code>  * FILE
<code>\loadtexfileonce [...]</code>  * FILE
<code>\loadtypescriptfile [...]</code>  * FILE
<code>\localframed [<sup>1</sup>...] [...,<sup>2</sup>...,...] {<sup>3</sup>...}</code>  1 NAME 2 inherits: \setupframed 3 CONTENT
<code>\localframedwithsettings [<sup>1</sup>...] [...,<sup>2</sup>...,...] {<sup>3</sup>...}</code>  1 NAME 2 inherits: \setupframed 3 CONTENT
<code>\localhsize</code>
<code>\localpopbox ...</code>  * CSNAME NUMBER
<code>\localpopmacro \...</code>  * CSNAME
<code>\localpushbox ...</code>  * CSNAME NUMBER
<code>\localpushmacro \...</code>  * CSNAME
<code>\localundefine {...}</code>  * NAME
<code>\locatedfilepath</code>
<code>\locatefilepath {...}</code>  * FILE
<code>\locfilename {...}</code>  * FILE



$\backslash\text{logo}$ [ <sup>1</sup> ...] { <sup>2</sup> ...} 1 NAME 2 CONTENT
$\backslash\text{lohi}$ [ <sup>1</sup> ...] { <sup>2</sup> ...} { <sup>3</sup> ...} 1 left <u>right</u> 2 CONTENT 3 CONTENT
$\backslash\text{lomihi}$ { <sup>1</sup> ...} { <sup>2</sup> ...} { <sup>3</sup> ...} 1 CONTENT 2 CONTENT 3 CONTENT
$\backslash\text{low}$ { <sup>*</sup> ...} * CONTENT
$\backslash\text{lowerbox}$ { <sup>1</sup> ...} \ <sup>2</sup> ... { <sup>3</sup> ...} 1 DIMENSION 2 CSNAME 3 CONTENT
$\backslash\text{lowercased}$ { <sup>*</sup> ...} * TEXT
$\backslash\text{lowercasestring}$ <sup>1</sup> ... \to \ <sup>2</sup> ... 1 TEXT 2 CSNAME
$\backslash\text{lowerlefthdoubleninequote}$
$\backslash\text{lowerleftsingleninequote}$
$\backslash\text{lowerrighthdoubleninequote}$
$\backslash\text{lowerrightsingleninequote}$
$\backslash\text{lowhigh}$ [ <sup>1</sup> ...] { <sup>2</sup> ...} { <sup>3</sup> ...} 1 left <u>right</u> 2 CONTENT 3 CONTENT
$\backslash\text{lowmidhigh}$ { <sup>1</sup> ...} { <sup>2</sup> ...} { <sup>3</sup> ...} 1 CONTENT 2 CONTENT 3 CONTENT

<code>\low {...}</code> *    CONTENT
<code>\lrbbox {...} {...} {...} {...} {...}</code> 1    DIMENSION 2    DIMENSION 3    DIMENSION 4    DIMENSION 5    CONTENT
<code>\ltop ... {...}</code> 1    TEXT 2    CONTENT
<code>\luacode {...}</code> *    COMMAND
<code>\luaconditional \*</code> *    CSNAME
<code>\luaenvironment ...</code> *    FILE
<code>\luaexpanded {...}</code> *    COMMAND
<code>\luafunction {...}</code> *    COMMAND
<code>\luajitTeX</code>
<code>\luamajorversion</code>
<code>\luaminorversion</code>
<code>\luaparameterset {...} {...}</code> 1    NAME 2    CONTENT
<code>\luasetup {...}</code> *    NAME
<code>\luaTeX</code>
<code>\luaversion</code>
<code>\METAFONT</code>

<code>\METAFUN</code>
<code>\METAPOST</code>
<code>\MetaFont</code>
<code>\MetaFun</code>
<code>\MetaPost</code>
<code>\MKII</code>
<code>\MKIV</code>
<code>\MKIX</code>
<code>\MKVI</code>
<code>\MKXI</code>
<code>\MONTH {...}</code> *    NUMBER
<code>\MONTHLONG {...}</code> *    NUMBER
<code>\MONTHSHORT {...}</code> *    NUMBER
<code>\MPanchor {...}</code> *    NAME
<code>\MPbetex {...}</code> *    NAME
<code>\MPc {...}</code> *    NAME
<code>\MPcode {...} {...}</code> 1    NAME 2    CONTENT
<code>\MPcolor {...}</code> *    COLOR
<code>\MPcoloronly {...}</code> *    COLOR

<code>\MPcolumn {...}</code>  *    NAME
<code>\MPd {...}</code>  *    NAME
<code>\MPdrawing {...}</code>  *    CONTENT
<code>\MPfontsizehskip {...}</code>  *    FONT
<code>\MPgetmultipars {...} {...}</code>  1    NAME 2    NAME
<code>\MPgetmultishape {...} {...}</code>  1    NAME 2    NAME
<code>\MPgetposboxes {...,<sup>1</sup>...} {...<sup>2</sup>}</code>  1    NAME 2    NAME
<code>\MPh {...}</code>  *    NAME
<code>\MPII</code>
<code>\MPIV</code>
<code>\MPinclusions [<sup>1</sup>...] {...<sup>2</sup>} {...<sup>3</sup>}</code>  1    + 2    NAME 3    CONTENT
<code>\MPleftskip {...}</code>  *    NAME
<code>\MPll {...}</code>  *    NAME
<code>\MPlr {...}</code>  *    NAME
<code>\MPls {...}</code>  *    NAME

\MPmenubuttons {...}  *    NAME
\MPn {...}  *    NAME
\MPoptions {...}  *    COLOR
\MPoverlayanchor {...}  *    NAME
\MPp {...}  *    NAME
\MPpage {...}  *    NAME
\MPpardata {...}  *    NAME
\MPplus {... <sup>1</sup> } {... <sup>2</sup> } {... <sup>3</sup> }  1    NAME 2    NUMBER 3    CONTENT
\MPpos {...}  *    NAME
\MPpositiongraphic {... <sup>1</sup> } {...,.. <sup>2</sup> ...,...}  1    NAME 2    KEY = VALUE
\MPposset {...}  *    NAME
\MPpr {...}  *    NAME
\MPrawvar {... <sup>1</sup> } {... <sup>2</sup> }  1    NAME 2    KEY
\MPregion {...}  *    NAME

\MPrest {...} {...}  1    NAME 2    CONTENT
\MPrightskip {...}  *    NAME
\MPrs {...}  *    NAME
\MPstring {...}  *    NAME
\MPtext {...}  *    NAME
\MPtransparency {...}  *    COLOR
\MPul {...}  *    NAME
\MPur {...}  *    NAME
\MPVI
\MPv {...} {...} {...}  1    NAME 2    NUMBER 3    CONTENT
\MPvar {...}  *    KEY
\MPvariable {...}  *    KEY
\MPvv {...} {...}  1    NAME 2    CONTENT
\MPw {...}  *    NAME
\MPx {...}  *    NAME

<code>\MPxy {...}</code>  *    NAME
<code>\MPxywhd {...}</code>  *    NAME
<code>\MPy {...}</code>  *    NAME
<code>\m [...] {...}</code>  1    NAME 2    CONTENT
<code>\mainlanguage [...]</code>  *    LANGUAGE
<code>\makecharacteractive ...</code>  *    CHARACTER
<code>\makerawcommalist [...<sup>1</sup>,...] \<sup>2</sup>...</code>  1    COMMAND 2    CSNAME
<code>\makestrutofbox ...</code>  *    CSNAME NUMBER
<code>\mapfontsize [...] [...]</code>  1    DIMENSION 2    DIMENSION
<code>\margindata [...<sup>1</sup>] [...<sup>2</sup>...,...] [...<sup>3</sup>...,...] {...<sup>4</sup>}</code>  1    NAME 2    reference = REFERENCE inherits: \setupmargindata 3    inherits: \setupmarginframed 4    CONTENT
<code>\margindata [...<sup>1</sup>...,...] [...<sup>2</sup>...,...] {...<sup>3</sup>}</code>  1    reference = REFERENCE inherits: \setupmargindata 2    inherits: \setupmarginframed 3    CONTENT
<code>\margintext [...<sup>1</sup>...,...] [...<sup>2</sup>...,...] {...<sup>3</sup>}</code>  1    reference = REFERENCE inherits: \setupmargindata 2    inherits: \setupmarginframed 3    CONTENT

$\backslash\mathrm{margintitle}$ [... <sup>1</sup> ...] [... <sup>2</sup> ...] {... <sup>3</sup> }  1    reference = REFERENCE inherits: \setupmargindata  2    inherits: \setupmarginframed  3    CONTENT
$\backslash\mathrm{marginword}$ [... <sup>1</sup> ...] [... <sup>2</sup> ...] {... <sup>3</sup> }  1    reference = REFERENCE inherits: \setupmargindata  2    inherits: \setupmarginframed  3    CONTENT
$\backslash\mathrm{markcontent}$ [... <sup>1</sup> ] {... <sup>2</sup> }  1    reset <u>all</u> NAME  2    CONTENT
$\backslash\mathrm{marking}$ (... <sup>1</sup> ,...) (... <sup>2</sup> ,...) [... <sup>3</sup> .]  1    POSITION  2    POSITION  3    REFERENCE
$\backslash\mathrm{markinjector}$ [...*]  *    NAME
$\backslash\mathrm{mar}$ {...*}  *    TEXT
$\backslash\mathrm{mat}$ {...*}  *    CONTENT
$\backslash\mathrm{math}$ [... <sup>1</sup> ] {... <sup>2</sup> }  1    NAME  2    CONTENT
$\backslash\mathrm{mathbf}$
$\backslash\mathrm{mathbi}$
$\backslash\mathrm{mathblackboard}$
$\backslash\mathrm{mathbs}$
$\backslash\mathrm{mathcommand}$ {...*}  *    NAME
$\backslash\mathrm{mathcommand}$ {... <sup>1</sup> } {... <sup>2</sup> }  1    TEXT  2    TEXT



<code>\mathdefault</code>
<code>\mathdoubleextensible {...}</code> *    TEXT
<code>\mathematics [^1.] {^2.}</code> 1    NAME 2    CONTENT
<code>\mathextensible [^1.] {^2.} {^3.}</code> 1    reverse mathematics text chemistry 2    TEXT 3    TEXT
<code>\mathfraktur</code>
<code>\mathframed [...,\stackrel{4}{...}] {^2.}</code> 1    inherits: \setupmathframed 2    CONTENT
<code>\mathfunction {...}</code> *    CONTENT
<code>\mathit</code>
<code>\mathitalic</code>
<code>\mathlabellanguage</code>
<code>\mathlabeltext {...}</code> *    KEY
<code>\mathlabeltexts {^1.} {^2.}</code> 1    KEY 2    TEXT
<code>\mathop {...}</code> *    CONTENT
<code>\mathornament {...}</code> *    CONTENT
<code>\mathoverextensible {...}</code> *    TEXT
<code>\mathovertextextensible {^1.} {^2.}</code> 1    TEXT 2    TEXT

$\sqrt[1]{\dots}$ $\sqrt[2]{\dots}$ 1    TEXT 2    CONTENT
$\mathrm{\dots}$
$\mathscr{\dots}$
$\mathsf{\dots}$
$\mathsfss{\dots}$
$\text{\dots}$ *    TEXT
$\textbf{\dots}$ *    TEXT
$\textit{\dots}$ *    TEXT
$\textbs{\dots}$ *    TEXT
$\texttit{\dots}$ *    TEXT
$\textsl{\dots}$ *    TEXT
$\texttt{\dots}$ *    TEXT
$\mathtt{\dots}$
$\mathop{\dots}\limits^1\mathop{\dots}\limits^2\mathop{\dots}\limits^3\mathop{\dots}\limits^4$ 1    NAME 2    TEXT 3    TEXT 4    TEXT
$\mathop{\dots}\limits^1\mathop{\dots}\limits^2\mathop{\dots}\limits^3\mathop{\dots}\limits^4$ 1    NAME 2    TEXT 3    TEXT 4    TEXT
$\mathtt{\dots}$

$\backslash\mathrm{mathunderextensible}\{...\}$ * TEXT
$\backslash\mathrm{mathundertextextensible}\{...\}^1\{...\}^2$ 1 TEXT 2 TEXT
$\backslash\mathrm{mathunstacked}$
$\backslash\mathrm{mathupright}$
$\backslash\mathrm{mathword}\{...\}$ * TEXT
$\backslash\mathrm{mathwordbf}\{...\}$ * TEXT
$\backslash\mathrm{mathwordbi}\{...\}$ * TEXT
$\backslash\mathrm{mathwordbs}\{...\}$ * TEXT
$\backslash\mathrm{mathwordit}\{...\}$ * TEXT
$\backslash\mathrm{mathwordsl}\{...\}$ * TEXT
$\backslash\mathrm{mathwordtf}\{...\}$ * TEXT
$\backslash\mathrm{maxaligned}\{...\}$ * CONTENT
$\backslash\mathrm{mbox}\{...\}$ * CONTENT
$\backslash\mathrm{mcframed}[...,\dots,\dots]^1\{...\}^2$ 1 inherits: $\backslash\mathrm{setupmathframed}$ 2 CONTENT
$\backslash\mathrm{measure}\{...\}$ * NAME
$\backslash\mathrm{measured}\{...\}$ * NAME

<code>\medskip</code>
<code>\medspace</code>
<code>\menubutton</code> [ <sup>1</sup> ...] [ <sup>2</sup> ... <sup>3</sup> ...] {...} {...} 1 NAME 2 inherits: \setupinteractionmenu 3 TEXT 4 REFERENCE
<code>\menubutton</code> [... <sup>1</sup> ...] {... <sup>2</sup> } {... <sup>3</sup> } 1 inherits: \setupbutton 2 TEXT 3 REFERENCE
<code>\mequal</code> {... <sup>1</sup> } {... <sup>2</sup> } 1 TEXT 2 TEXT
<code>\message</code> {...} * TEXT
<code>\metaTeX</code>
<code>\mfence</code> {...} * CHARACTER
<code>\mframed</code> [... <sup>1</sup> ...] {... <sup>2</sup> } 1 inherits: \setupmathframed 2 CONTENT
<code>\mfunction</code> {...} * CONTENT
<code>\mfunctionlabeltext</code> {...} * NAME
<code>\mhbox</code> {...} * CONTENT
<code>\mhookleftarrow</code> {... <sup>1</sup> } {... <sup>2</sup> } 1 TEXT 2 TEXT
<code>\mhookrightarrow</code> {... <sup>1</sup> } {... <sup>2</sup> } 1 TEXT 2 TEXT

<code>\midaligned {...}</code> *    CONTENT
<code>\middle ...</code> *    CHARACTER
<code>\middlealigned {...}</code> *    CONTENT
<code>\middlebox {...}</code> *    CONTENT
<code>\midhbox {...}</code> *    CONTENT
<code>\minimalhbox <sup>1</sup>... {<sup>2</sup>...}</code> 1    TEXT 2    CONTENT
<code>\mirror {...}</code> *    CONTENT
<code>\mixedcaps {...}</code> *    TEXT
<code>\mkvibuffer [...]</code> *    BUFFER
<code>\mLeftarrow {<sup>1</sup>...} {<sup>2</sup>...}</code> 1    TEXT 2    TEXT
<code>\mLeftrightarrow {<sup>1</sup>...} {<sup>2</sup>...}</code> 1    TEXT 2    TEXT
<code>\mleftarrow {<sup>1</sup>...} {<sup>2</sup>...}</code> 1    TEXT 2    TEXT
<code>\mleftharpoondown {<sup>1</sup>...} {<sup>2</sup>...}</code> 1    TEXT 2    TEXT
<code>\mleftharpoonup {<sup>1</sup>...} {<sup>2</sup>...}</code> 1    TEXT 2    TEXT

$\mleftrightharpoonrightarrow$ $\{...\}^1 \{...\}^2$ 1    TEXT 2    TEXT
$\mleftrightharpoonpoons$ $\{...\}^1 \{...\}^2$ 1    TEXT 2    TEXT
$\mmapsto$ $\{...\}^1 \{...\}^2$ 1    TEXT 2    TEXT
$\moduleparameter$ $\{...\}^1 \{...\}^2$ 1    FILE 2    KEY
$\molecule$ $\{...\}^*$ *    CONTENT
$\mono$
$\monobold$
$\mononormal$
$\month$ $\{...\}^*$ *    NUMBER
$\monthlong$ $\{...\}^*$ *    NUMBER
$\monthshort$ $\{...\}^*$ *    NUMBER
$\mprandomnumber$
$\mRrightarrow$ $\{...\}^1 \{...\}^2$ 1    TEXT 2    TEXT
$\mrel$ $\{...\}^1 \{...\}^2$ 1    TEXT 2    TEXT
$\mrightarrow$ $\{...\}^1 \{...\}^2$ 1    TEXT 2    TEXT

`\mrightharpoondown {...} {...}`

1 TEXT

2 TEXT

`\mrightharpoonup {...} {...}`

1 TEXT

2 TEXT

`\mrightharpoonleft {...} {...}`

1 TEXT

2 TEXT

`\mrightharpoonoverleftarrow {...} {...}`

1 TEXT

2 TEXT

`\mtext {...}`

\* CONTENT

`\mtriplerel {...} {...}`

1 TEXT

2 TEXT

`\mtwoheadleftarrow {...} {...}`

1 TEXT

2 TEXT

`\mtwoheadrightarrow {...} {...}`

1 TEXT

2 TEXT

`\NormalizeFontHeight \... {...} {...} {...}`

1 CSNAME

2 TEXT

3 DIMENSION

4 FONT

`\NormalizeFontWidth \... {...} {...} {...}`

1 CSNAME

2 TEXT

3 DIMENSION

4 FONT

`\NormalizeTextHeight {...} {...} {...}`

1 FONT

2 DIMENSION

3 TEXT

<code>\NormalizeTextWidth {...} {...} {...}</code>  1    FONT 2    DIMENSION 3    TEXT
<code>\Numbers {...}</code>  *    NUMBER
<code>\namedheadnumber {...}</code>  *    SECTION
<code>\namedstructureheadlocation {...}</code>  *    SECTION
<code>\namedstructureuservariable {...} {...}</code>  1    SECTION 2    KEY
<code>\namedstructurevariable {...} {...}</code>  1    SECTION 2    KEY
<code>\namedtaggedlabeltexts {...} {...} {...} {...} {...}</code>  1    NAME 2    NAME 3    NAME 4    NAME 5    CONTENT
<code>\naturalhbox ... {...}</code>  1    TEXT 2    CONTENT
<code>\naturalhpack ... {...}</code>  1    TEXT 2    CONTENT
<code>\naturalvbox ... {...}</code>  1    TEXT 2    CONTENT
<code>\naturalvcenter ... {...}</code>  1    TEXT 2    CONTENT



<code>\naturalvpack ... {<sup>1</sup>...<sup>2</sup>}</code>  1    TEXT 2    CONTENT
<code>\naturalvtop ... {<sup>1</sup>...<sup>2</sup>}</code>  1    TEXT 2    CONTENT
<code>\naturalwd ...</code>  *    CSNAME NUMBER
<code>\negatecolorbox ...</code>  *    CSNAME NUMBER
<code>\negated {...}</code>  *    TEXT
<code>\negthinspace</code>
<code>\newattribute \...</code>  *    CSNAME
<code>\newcatcodetable \...</code>  *    CSNAME
<code>\newcounter \...</code>  *    CSNAME
<code>\newevery \<sup>1</sup>... \<sup>2</sup>...</code>  1    CSNAME 2    CSNAME
<code>\newfrenchspacing</code>
<code>\newmode {...}</code>  *    NAME
<code>\newsignal \...</code>  *    CSNAME
<code>\newsystemmode {...}</code>  *    NAME
<code>\nextbox</code>
<code>\nextboxdp</code>
<code>\nextboxht</code>

<code>\nextboxhtdp</code>
<code>\nextboxwd</code>
<code>\nextcounter [...] [...]</code> 1 NAME 2 NUMBER
<code>\nextcountervalue [...]</code> * NAME
<code>\nextdepth</code>
<code>\nextparagraphs</code>
<code>\nextparagraphs</code>
<code>\nextrealpage</code>
<code>\nextrealpagenumber</code>
<code>\nextsubcountervalue [...] [...]</code> 1 NAME 2 NUMBER
<code>\nextsubpage</code>
<code>\nextsubpagenumber</code>
<code>\nextuserpage</code>
<code>\nextuserpagenumber</code>
<code>\nihongo</code>
<code>\nocitation [...]</code> * REFERENCE
<code>\nocitation {...}</code> * REFERENCE
<code>\nocite [...]</code> * REFERENCE
<code>\nocite {...}</code> * REFERENCE

<code>\nodetostring \<sup>1</sup>... {\<sup>2</sup>...}</code>  1 CSNAME 2 CONTENT
<code>\nofigurepages</code>
<code>\noflines</code>
<code>\noflocalfloats</code>
<code>\noheaderandfooterlines</code>
<code>\noindentation</code>
<code>\nonfrenchspacing</code>
<code>\nonmathematics {\dots}</code>  * CONTENT
<code>\nop \dots \\\</code>  * TEXT
<code>\nop</code>
<code>\normal</code>
<code>\normalboldface</code>
<code>\normalframedwithsettings [...,\dots<sup>1</sup>...,...] {\dots}</code>  1 inherits: \setupframed 2 CONTENT
<code>\normalizebodyfontsize \<sup>1</sup>... {\dots}</code>  1 CSNAME 2 DIMENSION
<code>\normalizedfontsize</code>
<code>\normalizefontdepth \<sup>1</sup>... {\dots} {\dots<sup>3</sup>} {\dots<sup>4</sup>}</code>  1 CSNAME 2 TEXT 3 DIMENSION 4 FONT
<code>\normalizefontheight \<sup>1</sup>... {\dots} {\dots<sup>3</sup>} {\dots<sup>4</sup>}</code>  1 CSNAME 2 TEXT 3 DIMENSION 4 FONT

`\normalizefontline \1... {\2...} {\3...} {\4...}`

- 1 CSNAME
- 2 TEXT
- 3 DIMENSION
- 4 FONT

`\normalizefontwidth \1... {\2...} {\3...} {\4...}`

- 1 CSNAME
- 2 TEXT
- 3 DIMENSION
- 4 FONT

`\normalizetextdepth {\1...} {\2...} {\3...}`

- 1 FONT
- 2 DIMENSION
- 3 TEXT

`\normalizetextheight {\1...} {\2...} {\3...}`

- 1 FONT
- 2 DIMENSION
- 3 TEXT

`\normalizetextline {\1...} {\2...} {\3...}`

- 1 FONT
- 2 DIMENSION
- 3 TEXT

`\normalizetextwidth {\1...} {\2...} {\3...}`

- 1 FONT
- 2 DIMENSION
- 3 TEXT

`\normaltypeface`

`\nospace`

`\note [1...] [2...]`

- 1 NAME
- 2 REFERENCE

`\notesymbol [1...] [2...]`

- 1 NAME
- 2 REFERENCE

`\note [...,1...] {\2...}`

- 1 REFERENCE
- 2 TEXT

$\backslash\text{note}$ [..., $\overset{*}{=}$ ...,...]  *    title        = TEXT *    bookmark    = TEXT *    list         = TEXT *    reference    = REFERENCE
$\backslash\text{notopandbottomlines}$
$\backslash\text{notragged}$
$\backslash\text{notsmallcapped}$ {...}  *    TEXT
$\backslash\text{ntimes}$ {... <sup>1</sup> } {... <sup>2</sup> }  1    TEXT 2    NUMBER
$\backslash\text{numberofpoints}$ {...}  *    DIMENSION
$\backslash\text{numbers}$ {...}  *    NUMBER
$\backslash\text{obeydepth}$
$\backslash\text{objectdepth}$
$\backslash\text{objectheight}$
$\backslash\text{objectmargin}$
$\backslash\text{objectwidth}$
$\backslash\text{obox}$ {...}  *    CONTENT
$\backslash\text{offset}$ [..., $\overset{1}{=}$ ...,... ] {... <sup>2</sup> }  1    inherits: \setupoffset 2    CONTENT
$\backslash\text{offsetbox}$ [..., $\overset{1}{=}$ ...,... ] \dots {... <sup>3</sup> }  1    inherits: \setupoffsetbox 2    CSNAME 3    CONTENT
$\backslash\text{onedigitrounding}$ {...}  *    NUMBER
$\backslash\text{operatorlanguage}$

<code>\operatorortext {...}</code>  *    KEY
<code>\ordinaldaynumber {...}</code>  *    NUMBER
<code>\ordinalstr {...}</code>  *    TEXT
<code>\ornamenttext [...,\overset{1}{...},...] [...,\overset{2}{...},...] {...} {...}</code>  1    alternative = <u>a</u> b inherits: \setupcollector  2    style = STYLE COMMAND color = COLOR inherits: \setupframed  3    TEXT  4    CONTENT
<code>\ornamenttext [...,\overset{1}{...},...] [...,\overset{2}{...},...] {...} {...}</code>  1    alternative = a <u>b</u> inherits: \setupplayer  2    inherits: \setuplayeredtext  3    TEXT  4    CONTENT
<code>\ornamenttext [...] {...} {...}</code>  1    NAME  2    TEXT  3    CONTENT
<code>\ornament {...} {...}</code>  1    TEXT  2    CONTENT
<code>\outputfilename</code>
<code>\outputstreambox [...]</code>  *    NAME
<code>\outputstreamcopy [...]</code>  *    NAME
<code>\outputstreamunvbox [...]</code>  *    NAME
<code>\outputstreamunvcopy [...]</code>  *    NAME



<code>\overlayheight</code>
<code>\overlaylinecolor</code>
<code>\overlaylinewidth</code>
<code>\overlayoffset</code>
<code>\overlayrollbutton [...] [...]</code> 1    REFERENCE 2    REFERENCE
<code>\overlaywidth</code>
<code>\overleftarrow {...}</code> *    TEXT
<code>\overleftharpoondown {...}</code> *    TEXT
<code>\overleftharpoonup {...}</code> *    TEXT
<code>\overleftrightarrow {...}</code> *    TEXT
<code>\overloaderror</code>
<code>\overparent {...}</code> *    TEXT
<code>\overparenttext {...} {...}</code> 1    TEXT 2    TEXT
<code>\overparentunderparent {...}</code> *    TEXT
<code>\overrightarrow {...}</code> *    TEXT
<code>\overrightharpoondown {...}</code> *    TEXT
<code>\overrightharpoonup {...}</code> *    TEXT



$\backslash\overset \{.^1.\} \{.^2.\}$  1    TEXT 2    TEXT
$\backslash\overstrike \{.^*.\}$  *    CONTENT
$\backslash\overstrikes \{.^*.\}$  *    CONTENT
$\backslash\overtwoheadleftarrow \{.^*.\}$  *    TEXT
$\backslash\overtwoheadrightarrow \{.^*.\}$  *    TEXT
$\backslash\PDFcolor \{.^*.\}$  *    NAME
$\backslash\PDFETEX$
$\backslash\PDFTEX$
$\backslash\PICTEX$
$\backslash\PiCTeX$
$\backslash\PointsToBigPoints \{.^1.\} \backslash.^2..$  1    DIMENSION 2    CSNAME
$\backslash\PointsToReal \{.^1.\} \backslash.^2..$  1    DIMENSION 2    CSNAME
$\backslash\PointsToWholeBigPoints \{.^1.\} \backslash.^2..$  1    DIMENSION 2    CSNAME
$\backslash\PPCHTEX$
$\backslash\PPCHTeX$
$\backslash\PRAGMA$
$\backslash\PtToCm \{.^*.\}$  *    DIMENSION

<p><code>\page [...,*,...]</code></p> <p>* inherits: <code>\pagebreak</code></p>
<p><code>\pagearea [...<sup>1</sup>.] [...<sup>2</sup>.] [...<sup>3</sup>.]</code></p> <p>1 top header text footer bottom</p> <p>2 text margin edge</p> <p>3 left right lefttext <u>middletext</u> righttext</p>
<p><code>\pagebreak [...,*,...]</code></p> <p>* empty header footer dummy frame NUMBER +NUMBER default reset disable yes no makeup blank preference bigpreference left right even odd quadruple last lastpage start stop NAME</p>
<p><code>\pagefigure [...<sup>1</sup>.] [...,...<sup>2</sup>...,...]</code></p> <p>1 FILE</p> <p>2 inherits: <code>\setupexternalfigure</code></p>
<p><code>\pagegridspanwidth {...}</code></p> <p>* NUMBER</p>
<p><code>\pageinjection [...<sup>1</sup>.] [...,...<sup>2</sup>...,...]</code></p> <p>1 NAME</p> <p>2 KEY = VALUE</p>
<p><code>\pageinjection [...,...<sup>1</sup>...,...] [...,...<sup>2</sup>...,...]</code></p> <p>1 inherits: <code>\setuppageinjection</code></p> <p>2 KEY = VALUE</p>
<p><code>\pagenumber</code></p>
<p><code>\pagereference [...,*,...]</code></p> <p>* REFERENCE</p>
<p><code>\pagestaterealpage {...<sup>1</sup>.} {...<sup>2</sup>.}</code></p> <p>1 NAME</p> <p>2 NAME NUMBER</p>
<p><code>\paletsize</code></p>
<p><code>\paragraphs</code></p>
<p><code>\part [...<sup>1</sup>,...] {...<sup>2</sup>.}</code></p> <p>1 REFERENCE</p> <p>2 TEXT</p>
<p><code>\pdfactualtext {...<sup>1</sup>.} {...<sup>2</sup>.}</code></p> <p>1 CONTENT</p> <p>2 TEXT</p>

`\pdfbackendactualtext {...} {...}`

1    CONTENT

2    TEXT

`\pdfbackendcurrentresources`

`\pdfbackendsetcatalog {...} {...}`

1    NAME

2    TEXT

`\pdfbackendsetcolorspace {...} {...}`

1    NAME

2    TEXT

`\pdfbackendsettextgstate {...} {...}`

1    NAME

2    TEXT

`\pdfbackendsetinfo {...} {...}`

1    NAME

2    TEXT

`\pdfbackendsetname {...} {...}`

1    NAME

2    TEXT

`\pdfbackendsetpageattribute {...} {...}`

1    NAME

2    TEXT

`\pdfbackendsetpageresource {...} {...}`

1    NAME

2    TEXT

`\pdfbackendsetpagesattribute {...} {...}`

1    NAME

2    TEXT

`\pdfbackendsetpattern {...} {...}`

1    NAME

2    TEXT

`\pdfbackendsetshade {...} {...}`

1    NAME

2    TEXT

`\pdfcolor {...}`

\*    NAME

<code>\pdfTeX</code>
<code>\pdfTeX</code>
<code>\percent</code>
<code>\percentdimen {<sup>1</sup>.<sup>2</sup>.}</code> 1    DIMENSION CSNAME 2    DIMENSION NUMBER
<code>\periods [...]</code> *    NUMBER
<code>\periods [...,...<sup>*</sup>...,...]</code> *    inherits: \setupperiods
<code>\permitcaretescape</code>
<code>\permitcircumflexescape</code>
<code>\permitspacesbetweengroups</code>
<code>\persiandecimals {<sup>*</sup>.<sup>*</sup>.}</code> *    NUMBER
<code>\persiannumerals {<sup>*</sup>.<sup>*</sup>.}</code> *    NUMBER
<code>\phantom {<sup>*</sup>.<sup>*</sup>.}</code> *    CONTENT
<code>\phantombox [...,...<sup>*</sup>...,...]</code> *    width    = DIMENSION *    height   = DIMENSION *    depth    = DIMENSION
<code>\pickupgroupedcommand {<sup>1</sup>.<sup>2</sup>.} {<sup>2</sup>.<sup>3</sup>.} {<sup>3</sup>.<sup>4</sup>.}</code> 1    COMMAND 2    COMMAND 3    COMMAND
<code>\placeattachments</code>
<code>\placebookmarks [...,<sup>1</sup>...] [...,<sup>2</sup>...] [...,<sup>3</sup>...,...]</code> 1    SECTION LIST 2    SECTION LIST 3    inherits: \setupbookmark

`\placebtxrendering [...]1 [...,...2...,...]`

1 NAME

2 inherits: \setupbtxrendering

`\placechemical [...]1,... [...]2,... {...}3 {...}4`

1 split always left right inner outer backspace cutspace inleft inright inmargin leftmargin rightmargin leftedge rightedge innermargin outermargin inneredge outeredge text opposite reset height depth [--]line halfline grid high low fit 90 180 270 nonumber none local here force margin [--]hang hanging tall both middle offset top bottom auto page leftpage rightpage somewhere

2 REFERENCE

3 TEXT

4 CONTENT

`\placecitation [...]`

\* REFERENCE

`\placecombinedlist [...]1 [...,...2...,...]`

1 LIST

2 inherits: \setuplist

`\placecombinedlist [...,...*...,...]`

\* inherits: \setuplist

`\placecomments`

`\placecontent [...,...*...,...]`

\* inherits: \setuplist

`\placecurrentformulanumber`

`\placedbox {...}`

\* CONTENT

`\placefigure [...]1,... [...]2,... {...}3 {...}4`

1 split always left right inner outer backspace cutspace inleft inright inmargin leftmargin rightmargin leftedge rightedge innermargin outermargin inneredge outeredge text opposite reset height depth [--]line halfline grid high low fit 90 180 270 nonumber none local here force margin [--]hang hanging tall both middle offset top bottom auto page leftpage rightpage somewhere

2 REFERENCE

3 TEXT

4 CONTENT

`\placefloat [...]1 [...]2,... [...]3,... {...}4 {...}5`

1 SINGULAR

2 split always left right inner outer backspace cutspace inleft inright inmargin leftmargin rightmargin leftedge rightedge innermargin outermargin inneredge outeredge text opposite reset height depth [--]line halfline grid high low fit 90 180 270 nonumber none local here force margin [--]hang hanging tall both middle offset top bottom auto page leftpage rightpage somewhere

3 REFERENCE

4 TEXT

5 CONTENT

`\placefloatwithsetups [...1] [...2,...] [...3,...] {...4} {...5}`

1 NAME

2 split always left right inner outer backspace cutspace inleft inright inmargin leftmargin rightmargin leftedge  
rightedge innermargin outermargin inneredge outeredge text opposite reset height depth [-+]line halfline grid high  
low fit 90 180 270 nonumber none local here force margin [-+]hang hanging tall both middle offset top bottom auto  
page leftpage rightpage somewhere

3 REFERENCE

4 TEXT

5 CONTENT

`\placefloat [...1,...] [...2,...] {...3} {...4}`

1 split always left right inner outer backspace cutspace inleft inright inmargin leftmargin rightmargin leftedge  
rightedge innermargin outermargin inneredge outeredge text opposite reset height depth [-+]line halfline grid high  
low fit 90 180 270 nonumber none local here force margin [-+]hang hanging tall both middle offset top bottom auto  
page leftpage rightpage somewhere

2 REFERENCE

3 TEXT

4 CONTENT

`\placefootnotes [...*,...]`

\* inherits: \setupnote

`\placeformula [...*,...]`

\* + - REFERENCE

`\placeframed [...1] [...2,...2,...] {...3}`

1 NAME

2 inherits: \setupframed

3 CONTENT

`\placegraphic [...1,...] [...2,...] {...3} {...4}`

1 split always left right inner outer backspace cutspace inleft inright inmargin leftmargin rightmargin leftedge  
rightedge innermargin outermargin inneredge outeredge text opposite reset height depth [-+]line halfline grid high  
low fit 90 180 270 nonumber none local here force margin [-+]hang hanging tall both middle offset top bottom auto  
page leftpage rightpage somewhere

2 REFERENCE

3 TEXT

4 CONTENT

`\placeheadnumber [...*]`

\* SECTION

`\placeheadtext [...*]`

\* SECTION

`\placehelp`

`\placeindex [...*,...]`

\* inherits: \setupregister

`\placeinitial [...]`

\* NAME

`\placeintermezzo [...1,...] [...2,...] {...3} {...4}`

1 split always left right inner outer backspace cutspace inleft inright inmargin leftmargin rightmargin leftedge  
rightedge innermargin outermargin inneredge outeredge text opposite reset height depth [-+]line halfline grid high  
low fit 90 180 270 nonumber none local here force margin [-+]hang hanging tall both middle offset top bottom auto  
page leftpage rightpage somewhere

2 REFERENCE

3 TEXT

4 CONTENT

`\placelayer [...]`

\* NAME

`\placelayeredtext [...1] [...2,...2,...] [...3,...3,...] {...4} {...5}`

1 NAME

2 inherits: \setuplayer

3 inherits: \setuplayeredtext

4 TEXT

5 CONTENT

`\placelegend [...1,...1,...] {...2} {...3}`

1 inherits: \setuppairedbox

2 CONTENT

3 TEXT

`\placelist [...1,...] [...2,...2,...]`

1 LIST

2 inherits: \setuplist

`\placelistofabbreviations [...*,...*,...]`

\* inherits: \setupsynonyms

`\placelistofchemicals [...*,...*,...]`

\* inherits: \setuplist

`\placelistoffigures [...*,...*,...]`

\* inherits: \setuplist

`\placelistoffloats [...*,...*,...]`

\* inherits: \setuplist

`\placelistofgraphics [...*,...*,...]`

\* inherits: \setuplist

`\placelistofintermezzi [...*,...*,...]`

\* inherits: \setuplist

<p><code>\placelistoflogos [...<sup>*</sup>...]</code></p> <p>* inherits: \setupsorting</p>
<p><code>\placelistofpublications [...<sup>1</sup>.] [...<sup>2</sup>...]</code></p> <p>1 NAME</p> <p>2 inherits: \setupbtxrendering</p>
<p><code>\placelistofsorts [...<sup>1</sup>.] [...<sup>2</sup>...]</code></p> <p>1 SINGULAR</p> <p>2 inherits: \setupsorting</p>
<p><code>\placelistofsorts [...<sup>*</sup>...]</code></p> <p>* inherits: \setupsorting</p>
<p><code>\placelistofsynonyms [...<sup>1</sup>.] [...<sup>2</sup>...]</code></p> <p>1 SINGULAR</p> <p>2 inherits: \setupsynonyms</p>
<p><code>\placelistofsynonyms [...<sup>*</sup>...]</code></p> <p>* inherits: \setupsynonyms</p>
<p><code>\placelistoftables [...<sup>*</sup>...]</code></p> <p>* inherits: \setuplist</p>
<p><code>\placelocalfootnotes [...<sup>*</sup>...]</code></p> <p>* inherits: \setupnote</p>
<p><code>\placelocalnotes [...<sup>1</sup>.] [...<sup>2</sup>...]</code></p> <p>1 NAME</p> <p>2 inherits: \setupnote</p>
<p><code>\placement [...<sup>1</sup>.] [...<sup>2</sup>...] {...<sup>3</sup>.}</code></p> <p>1 NAME</p> <p>2 inherits: \setupplacement</p> <p>3 CONTENT</p>
<p><code>\placement [...<sup>1</sup>...] {...<sup>2</sup>.}</code></p> <p>1 inherits: \setupplacement</p> <p>2 CONTENT</p>
<p><code>\placenamefloat [...<sup>1</sup>.] [...<sup>2</sup>.]</code></p> <p>1 NAME</p> <p>2 REFERENCE</p>
<p><code>\placenameformula [...<sup>1</sup>,...] {...<sup>2</sup>.}</code></p> <p>1 + - REFERENCE</p> <p>2 TEXT</p>



`\placenotes [...1,...] [...2,...]`

1 NAME

2 inherits: \setupnote

`\placeongrid [...1] {...2}`

1 normal standard yes strict tolerant top bottom both broad fit first last high one low none line strut box min max  
middle NAME

2 CONTENT

`\placeongrid [...1,...] {...2}`

1 inherits: \definegridsnapping

2 CONTENT

`\placeontopofeachother {...1} {...2}`

1 CONTENT

2 CONTENT

`\placepagenumber`

`\placepairedbox [...1] [...2,...] {...3} {...4}`

1 NAME

2 inherits: \setuppairedbox

3 CONTENT

4 TEXT

`\placepairedbox [...1,...] {...2} {...3}`

1 inherits: \setuppairedbox

2 CONTENT

3 TEXT

`\placeparallel [...1] [...2,...] [...3,...]`

1 NAME

2 NAME

3 inherits: \setupparallel

`\placerawlist [...1] [...2,...]`

1 LIST

2 inherits: \setuplist

`\placeregister [...1] [...2,...]`

1 NAME

2 inherits: \setupregister

`\placeregister [...*,...]`

\* inherits: \setupregister

<p><code>\placereadingwindow [.<sup>1</sup>.] [.<sup>2</sup>.]</code></p> <p>1 NAME</p> <p>2 NAME</p>
<p><code>\placesidebyside {.<sup>1</sup>.} {.<sup>2</sup>.}</code></p> <p>1 CONTENT</p> <p>2 CONTENT</p>
<p><code>\placesubformula [...<sup>*</sup>...]</code></p> <p>* + - REFERENCE</p>
<p><code>\placetable [...<sup>1</sup>...] [...<sup>2</sup>...] {...<sup>3</sup>} {...<sup>4</sup>}</code></p> <p>1 split always left right inner outer backspace cutspace inleft inright inmargin leftmargin rightmargin leftedge rightedge innermargin outermargin inneredge outeredge text opposite reset height depth [--+]line halfline grid high low fit 90 180 270 nonumber none local here force margin [--+]hang hanging tall both middle offset top bottom auto page leftpage rightpage somewhere</p> <p>2 REFERENCE</p> <p>3 TEXT</p> <p>4 CONTENT</p>
<p><code>\popattribute \.*.</code></p> <p>* CSNAME</p>
<p><code>\popmacro \.*.</code></p> <p>* CSNAME</p>
<p><code>\popmode [.*.]</code></p> <p>* NAME</p>
<p><code>\popsystemmode {...}</code></p> <p>* NAME</p>
<p><code>\position [...<sup>1</sup>...<sup>2</sup>...<sup>3</sup>] (...<sup>2</sup>,...) {...<sup>3</sup>}</code></p> <p>1 inherits: \setuppositioning</p> <p>2 POSITION</p> <p>3 CONTENT</p>
<p><code>\positionoverlay {...}</code></p> <p>* NAME</p>
<p><code>\positionregionoverlay {...<sup>1</sup>} {...<sup>2</sup>}</code></p> <p>1 NAME</p> <p>2 NAME</p>
<p><code>\postponenotes</code></p>
<p><code>\predefinedfont [.*.]</code></p> <p>* FONT</p>

<pre>\predefinefont [...] [...]</pre> <pre>1 NAME</pre> <pre>2 FONT</pre>
<pre>\predefinesymbol [...]</pre> <pre>* NAME</pre>
<pre>\prefixedpagenumber</pre>
<pre>\prefixlanguage</pre>
<pre>\prefixtext {...}</pre> <pre>* KEY</pre>
<pre>\prependetoks ... \to ...</pre> <pre>1 COMMAND</pre> <pre>2 CSNAME</pre>
<pre>\prependgvalue {...} {...}</pre> <pre>1 NAME</pre> <pre>2 COMMAND</pre>
<pre>\prependtocommalist {...} \...</pre> <pre>1 TEXT</pre> <pre>2 CSNAME</pre>
<pre>\prependtoks ... \to ...</pre> <pre>1 COMMAND</pre> <pre>2 CSNAME</pre>
<pre>\prependtoksonce ... \to ...</pre> <pre>1 COMMAND</pre> <pre>2 CSNAME</pre>
<pre>\prependvalue {...} {...}</pre> <pre>1 NAME</pre> <pre>2 COMMAND</pre>
<pre>\presetbtxlabeltext [...] [...,...<sup>2</sup>...,...]</pre> <pre>1 LANGUAGE</pre> <pre>2 KEY = VALUE</pre>
<pre>\presetdocument [...,...<sup>*</sup>...,...]</pre> <pre>* inherits: \setupdocument</pre>
<pre>\presetfieldsymbols [...,...<sup>*</sup>...]</pre> <pre>* NAME</pre>

<pre> \presetheadtext [...] [...] 1  LANGUAGE 2  KEY  =  VALUE </pre>
<pre> \presetlabeltext [...] [...] 1  LANGUAGE 2  KEY  =  VALUE </pre>
<pre> \presetlabeltext [...] [...] 1  LANGUAGE 2  KEY  =  VALUE </pre>
<pre> \presetmathlabeltext [...] [...] 1  LANGUAGE 2  KEY  =  VALUE </pre>
<pre> \presetoperatortext [...] [...] 1  LANGUAGE 2  KEY  =  VALUE </pre>
<pre> \presetprefixtext [...] [...] 1  LANGUAGE 2  KEY  =  VALUE </pre>
<pre> \presettaglabeltext [...] [...] 1  LANGUAGE 2  KEY  =  VALUE </pre>
<pre> \presetunittext [...] [...] 1  LANGUAGE 2  KEY  =  VALUE </pre>
<pre> \pretocommalist {...} \... 1  TEXT 2  CSNAME </pre>
<pre> \prevcounter [...] [...] 1  NAME 2  NUMBER </pre>
<pre> \prevcountervalue [...] *  NAME </pre>
<pre> \preventmode [...*,...] *  NAME </pre>
<pre> \prevrealpage </pre>

<code>\prevrealpagenumber</code>
<code>\prevsubcountervalue [...]<sup>1</sup> [...]<sup>2</sup></code> 1 NAME 2 NUMBER
<code>\prevsubpage</code>
<code>\prevsubpagenumber</code>
<code>\prevuserpage</code>
<code>\prevuserpagenumber</code>
<code>\procent</code>
<code>\processaction [...]<sup>1</sup> [...,...=&gt;...]<sup>2</sup></code> 1 COMMAND 2 APPLY
<code>\processallactionsinset [...]<sup>1</sup> [...,...=&gt;...]<sup>2</sup></code> 1 COMMAND 2 APPLY
<code>\processassignlist [...]<sup>1</sup>,... \^<sup>2</sup>...</code> 1 TEXT 2 CSNAME
<code>\processassignmentcommand [...,...<sup>1</sup>...,... \^<sup>2</sup>...</code> 1 KEY = VALUE 2 CSNAME
<code>\processassignmentlist [...,...<sup>1</sup>...,... \^<sup>2</sup>...</code> 1 KEY = VALUE 2 CSNAME
<code>\processbetween {...}<sup>1</sup> \^<sup>2</sup>...</code> 1 NAME 2 CSNAME
<code>\processblocks [...]<sup>1</sup>,... [...]<sup>2</sup>,... [...,...<sup>3</sup>...,...]</code> 1 NAME 2 + - 3 criterium = <u>text</u> SECTION
<code>\processbodyfontenvironmentlist \^*...</code> * CSNAME

<pre>\processcolorcomponents {...}</pre> <pre>*    COLOR</pre>
<pre>\processcommacommand [...,<sup>1</sup>...] \<sup>2</sup>...</pre> <pre>1    COMMAND</pre> <pre>2    CSNAME</pre>
<pre>\processcommalist [...,<sup>1</sup>...] \<sup>2</sup>...</pre> <pre>1    COMMAND</pre> <pre>2    CSNAME</pre>
<pre>\processcommalistwithparameters [...,<sup>1</sup>...] \<sup>2</sup>...</pre> <pre>1    COMMAND</pre> <pre>2    CSNAME</pre>
<pre>\processcontent {...<sup>1</sup>} \<sup>2</sup>...</pre> <pre>1    NAME</pre> <pre>2    CSNAME</pre>
<pre>\processfile {...}</pre> <pre>*    FILE</pre>
<pre>\processfilemany {...}</pre> <pre>*    FILE</pre>
<pre>\processfilenone {...}</pre> <pre>*    FILE</pre>
<pre>\processfileonce {...}</pre> <pre>*    FILE</pre>
<pre>\processfirstactioninset [...<sup>1</sup>] [...,<sup>2</sup>⇒,...]</pre> <pre>1    COMMAND</pre> <pre>2    APPLY</pre>
<pre>\processisolatedchars {...<sup>1</sup>} \<sup>2</sup>...</pre> <pre>1    TEXT</pre> <pre>2    CSNAME</pre>
<pre>\processisolatedwords {...<sup>1</sup>} \<sup>2</sup>...</pre> <pre>1    TEXT</pre> <pre>2    CSNAME</pre>
<pre>\processlinetablebuffer [...]</pre> <pre>*    BUFFER</pre>
<pre>\processlinetablefile {...}</pre> <pre>*    FILE</pre>

\processlist {...} {...} {...} \...

- 1 CHARACTER
- 2 CHARACTER
- 3 TEXT
- 4 CSNAME

\processMPbuffer [...]\*...]

- \* NAME

\processMPfigurefile {...}

- \* FILE

\processmonth {...} {...} {...}

- 1 NUMBER
- 2 NUMBER
- 3 COMMAND

\processranges [...]<sup>1</sup>,... ] \...<sup>2</sup>

- 1 NUMBER NUMBER:NUMBER
- 2 CSNAME

\processseparatedlist [...]<sup>1</sup> [...]<sup>2</sup> {...}<sup>3</sup>

- 1 TEXT
- 2 TEXT
- 3 CSNAME COMMAND

\processTEXbuffer [...]

- \* BUFFER

\processtokens {...} {...} {...} {...} {...}

- 1 COMMAND
- 2 COMMAND
- 3 COMMAND
- 4 COMMAND
- 5 TEXT

\processuntil \...

- \* CSNAME

\processxtablebuffer [...]

- \* NAME

\processyear {...} {...} {...} {...}

- 1 NUMBER
- 2 COMMAND
- 3 COMMAND
- 4 COMMAND

<p><code>\product [...]</code></p> <p>* FILE</p>
<p><code>\product ...</code></p> <p>* FILE</p>
<p><code>\profiledbox [...]<sup>1</sup> [...,...<sup>2</sup>...,...]<sup>3</sup> {...}</code></p> <p>1 none fixed strict halffixed quarterfixed eightsfixed NAME</p> <p>2 inherits: \setupprofile</p> <p>3 CONTENT</p>
<p><code>\profilegivenbox {...}<sup>1</sup> ...<sup>2</sup></code></p> <p>1 none fixed strict halffixed quarterfixed eightsfixed NAME</p> <p>2 CSNAME NUMBER</p>
<p><code>\program [...]</code></p> <p>* NAME</p>
<p><code>\project [...]</code></p> <p>* FILE</p>
<p><code>\project ...</code></p> <p>* FILE</p>
<p><code>\pseudoMixedCapped {...}</code></p> <p>* TEXT</p>
<p><code>\pseudoSmallCapped {...}</code></p> <p>* TEXT</p>
<p><code>\pseudoSmallcapped {...}</code></p> <p>* TEXT</p>
<p><code>\pseudosmallcapped {...}</code></p> <p>* TEXT</p>
<p><code>\psh [...]<sup>1</sup> ...<sup>2</sup> \\</code></p> <p>1 REFERENCE</p> <p>2 TEXT</p>
<p><code>\purenumber {...}</code></p> <p>* NUMBER</p>
<p><code>\pusharrangedpages ... \poparrangedpages</code></p>
<p><code>\pushattribute \...</code></p> <p>* CSNAME</p>



<p><code>\pushbackground [...] ... \popbackground</code></p> <p>* NAME</p>
<p><code>\pushbar [...] ... \popbar</code></p> <p>* NAME</p>
<p><code>\pushbutton [<sup>1</sup>.] [<sup>2</sup>.]</code></p> <p>1 NAME</p> <p>2 REFERENCE</p>
<p><code>\pushcatcodetable ... \popcatcodetable</code></p>
<p><code>\pushcolor [...] ... \popcolor</code></p> <p>* COLOR</p>
<p><code>\pushendofline ... \popendofline</code></p>
<p><code>\pushindentation ... \popindentation</code></p>
<p><code>\pushMPdrawing ... \popMPdrawing</code></p>
<p><code>\pushmacro \*...</code></p> <p>* CSNAME</p>
<p><code>\pushmathstyle ... \popmathstyle</code></p>
<p><code>\pushmode [...]</code></p> <p>* NAME</p>
<p><code>\pushoutputstream [...]</code></p> <p>* NAME</p>
<p><code>\pushpath [...] ... \poppath</code></p> <p>* FILE</p>
<p><code>\pushpunctuation ... \poppunctuation</code></p>
<p><code>\pushrandomseed ... \poprandomseed</code></p>
<p><code>\pushreferenceprefix {...} ... \popreferenceprefix</code></p> <p>* + - TEXT</p>
<p><code>\pushsystemmode {...}</code></p> <p>* NAME</p>
<p><code>\qqquad</code></p>
<p><code>\quad</code></p>

<code>\quitcommalist</code>
<code>\quitprevcommalist</code>
<code>\quittypescriptscanning</code>
<code>\quotation {...}</code> *    CONTENT
<code>\quote {...}</code> *    CONTENT
<code>\ReadFile {...}</code> *    FILE
<code>\Romannumerals {...}</code> *    NUMBER
<code>\raggedbottom</code>
<code>\raggedcenter</code>
<code>\raggedleft</code>
<code>\raggedright</code>
<code>\raggedwidecenter</code>
<code>\raisebox {...} \^{.2} {...}</code> 1    DIMENSION 2    CSNAME 3    CONTENT
<code>\randomizetext {...}</code> *    TEXT
<code>\randomnumber {...} {...}</code> 1    NUMBER 2    NUMBER
<code>\ran {...}</code> *    TEXT
<code>\rawcounter [...]<sup>1</sup> [...]<sup>2</sup></code> 1    NAME 2    NUMBER
<code>\rawcountervalue [...]</code> *    NAME

<pre>\rawdate [...,*,...]</pre> <p>* inherits: \currentdate</p>
<pre>\rawdoifelseinset {...} {...} {...}</pre> <p>1 CONTENT</p> <p>2 TRUE</p> <p>3 FALSE</p>
<pre>\rawdoifinset {...} {...}</pre> <p>1 CONTENT</p> <p>2 TRUE</p>
<pre>\rawdoifinsetelse {...} {...} {...}</pre> <p>1 CONTENT</p> <p>2 TRUE</p> <p>3 FALSE</p>
<pre>\rawgetparameters [...]<sup>1</sup> [...,...<sup>2</sup>...,...]</pre> <p>1 TEXT</p> <p>2 KEY = VALUE</p>
<pre>\rawprocessaction [...]<sup>1</sup> [...,...<sup>2</sup>&gt;...,...]</pre> <p>1 COMMAND</p> <p>2 APPLY</p>
<pre>\rawprocesscommacommand [...]<sup>1</sup>,... \...<sup>2</sup>..</pre> <p>1 COMMAND</p> <p>2 CSNAME</p>
<pre>\rawprocesscommalist [...]<sup>1</sup>,... \...<sup>2</sup>..</pre> <p>1 COMMAND</p> <p>2 CSNAME</p>
<pre>\rawstructurelistuservariable {...}</pre> <p>* KEY</p>
<pre>\rawsubcountervalue [...]<sup>1</sup> [...]<sup>2</sup></pre> <p>1 NAME</p> <p>2 NUMBER</p>
<pre>\raw [...]<sup>1</sup> ... \\<sup>2</sup></pre> <p>1 REFERENCE</p> <p>2 TEXT</p>
<pre>\rbox ...<sup>1</sup> {...}<sup>2</sup></pre> <p>1 TEXT</p> <p>2 CONTENT</p>

\readfile {...} {...} {...}

- 1 FILE
- 2 TRUE
- 3 FALSE

\readfixfile {...} {...} {...} {...}

- 1 FILE
- 2 FILE
- 3 TRUE
- 4 FALSE

\readjobfile {...} {...} {...}

- 1 FILE
- 2 TRUE
- 3 FALSE

\readlocfile {...} {...} {...}

- 1 FILE
- 2 TRUE
- 3 FALSE

\readsetfile {...} {...} {...} {...}

- 1 FILE
- 2 FILE
- 3 TRUE
- 4 FALSE

\readsysfile {...} {...} {...}

- 1 FILE
- 2 TRUE
- 3 FALSE

\readtexfile {...} {...} {...}

- 1 FILE
- 2 TRUE
- 3 FALSE

\readxmlfile {...} {...} {...}

- 1 FILE
- 2 TRUE
- 3 FALSE

\realpagenumber

\realSmallCapped {...}

- \* TEXT

<code>\realSmallcapped {...}</code> * TEXT
<code>\realSmallcapped {...}</code> * TEXT
<code>\recursedepth</code>
<code>\recurselevel</code>
<code>\recursestring</code>
<code>\redoconvertfont</code>
<code>\ref [.<sup>1</sup>.] [.<sup>2</sup>.]</code> 1 default text title number page realpage 2 REFERENCE
<code>\reference [...,<sup>1</sup>...] {.<sup>2</sup>.}</code> 1 REFERENCE 2 TEXT
<code>\referenceformat {.<sup>1</sup>.} {.<sup>2</sup>.} [.<sup>3</sup>.]</code> 1 TEXT 2 TEXT 3 REFERENCE
<code>\referenceprefix</code>
<code>\referring (...,<sup>1</sup>...) (...,<sup>2</sup>...) [.<sup>3</sup>.]</code> 1 POSITION 2 POSITION 3 REFERENCE
<code>\registerattachment [.<sup>1</sup>.] [...,<sup>2</sup>...,...]</code> 1 NAME 2 inherits: \setupattachment
<code>\registerctxluafile {.<sup>1</sup>.} {.<sup>2</sup>.}</code> 1 FILE 2 NUMBER
<code>\registerexternalfigure [.<sup>1</sup>.] [.<sup>2</sup>.] [...,<sup>3</sup>...,...]</code> 1 FILE 2 NAME 3 inherits: \setupexternalfigure

<pre>\registerfontclass {...}</pre> <p>*    NAME</p>
<pre>\registerhyphenationexception [...] [...]</pre> <p>1    LANGUAGE</p> <p>2    TEXT</p>
<pre>\registerhyphenationpattern [...] [...]</pre> <p>1    LANGUAGE</p> <p>2    TEXT</p>
<pre>\registermenubuttons [...] [...]</pre> <p>1    NAME</p> <p>2    TEXT</p>
<pre>\registersort [...] [...]</pre> <p>1    SINGULAR</p> <p>2    NAME</p>
<pre>\registersynonym [...] [...]</pre> <p>1    SINGULAR</p> <p>2    NAME</p>
<pre>\registerunit [...] [...,...<sup>2</sup>...,...]</pre> <p>1    prefix <u>unit</u> operator suffixe symbol packaged</p> <p>2    KEY = VALUE</p>
<pre>\register [...] [...] [...+...+...]</pre> <p>1    TEXT PROCESSOR-&gt;TEXT</p> <p>2    INDEX</p>
<pre>\register [...] [...] {...} [...] [...+...+...]</pre> <p>1    TEXT PROCESSOR-&gt;TEXT</p> <p>2    TEXT</p> <p>3    INDEX</p>
<pre>\regular</pre>
<pre>\relatemarking [...] [...]</pre> <p>1    MARK</p> <p>2    MARK</p>
<pre>\relateparameterhandlers {...} {...} {...} {...}</pre> <p>1    NAME</p> <p>2    NAME</p> <p>3    NAME</p> <p>4    NAME</p>

<code>\relaxvalueifundefined {...}</code>  *    NAME
<code>\remainingcharacters</code>
<code>\remark (...<sup>1</sup>,...) (...<sup>2</sup>,...) [...<sup>3</sup>,...<sup>3</sup>,...] {...<sup>4</sup>}</code>  1    POSITION 2    POSITION 3    inherits: \setupframed 4    TEXT
<code>\removebottomthings</code>
<code>\removedepth</code>
<code>\removefromcommalist {...<sup>1</sup>} \...<sup>2</sup>.</code>  1    TEXT 2    CSNAME
<code>\removelastskip</code>
<code>\removelastspace</code>
<code>\removemarkedcontent [...]</code>  *    NAME
<code>\removepunctuation</code>
<code>\removesubstring ...<sup>1</sup> \from ...<sup>2</sup> \to \...<sup>3</sup>.</code>  1    TEXT 2    TEXT 3    CSNAME
<code>\removetoks ...<sup>1</sup> \from \...<sup>2</sup>.</code>  1    COMMAND 2    CSNAME
<code>\removeunwantedspaces</code>
<code>\replacefeature [...]</code>  *    NAME
<code>\replacefeature {...}</code>  *    NAME
<code>\replaceincommalist \...<sup>1</sup> {...<sup>2</sup>}</code>  1    CSNAME 2    NUMBER

<pre>\replaceword [...] [...] [...]</pre> <pre>1 NAME</pre> <pre>2 TEXT</pre> <pre>3 TEXT</pre>
<pre>\rescan {...}</pre> <pre>* CONTENT</pre>
<pre>\rescanwithsetup [...] [...]</pre> <pre>1 NAME</pre> <pre>2 CONTENT</pre>
<pre>\resetallattributes</pre>
<pre>\resetandaddfeature [...] [...]</pre> <pre>* NAME</pre>
<pre>\resetandaddfeature {...}</pre> <pre>* NAME</pre>
<pre>\resetbreakpoints</pre>
<pre>\resetbuffer [...] [...]</pre> <pre>* BUFFER</pre>
<pre>\resetcharacteralign</pre>
<pre>\resetcharacterkerning</pre>
<pre>\resetcharacterspacing</pre>
<pre>\resetcharacterstripping</pre>
<pre>\resetcollector [...] [...]</pre> <pre>* NAME</pre>
<pre>\resetcounter [...] [...]</pre> <pre>1 NAME</pre> <pre>2 NUMBER</pre>
<pre>\resetdigitsmanipulation</pre>
<pre>\resetdirection</pre>
<pre>\resetfeature</pre>
<pre>\resetflag {...}</pre> <pre>* NAME</pre>



<code>\resetfontcolorsheme</code>
<code>\resetfontfallback [...] [...]</code> 1    NAME 2    FONT
<code>\resetfontsolution</code>
<code>\resethyphenationfeatures</code>
<code>\resetinjector [...]</code> *    NAME
<code>\resetinteractionmenu [...]</code> *    NAME
<code>\resetitaliccorrection</code>
<code>\resetlayer [...]</code> *    NAME
<code>\resetlocalfloats</code>
<code>\resetMPdrawing</code>
<code>\resetMPenvironment</code>
<code>\resetMPinstance [...]</code> *    NAME
<code>\resetmarker [...]</code> *    NAME
<code>\resetmarking [...]</code> *    MARK
<code>\resetmode {...}</code> *    NAME
<code>\resetpagenumber</code>
<code>\resetparallel [...] [...,<sup>2</sup>...]</code> 1    NAME 2    NAME <u>all</u>
<code>\resetpath</code>
<code>\resetpenalties \.*.</code> *    CSNAME

<code>\resetprofile</code>
<code>\resetreference [...]</code> *    NAME
<code>\resetreplacement</code>
<code>\resetscript</code>
<code>\resetsetups [...]</code> *    NAME
<code>\resetshownsynonyms [...]</code> *    SINGULAR
<code>\resetsubpagenumber</code>
<code>\resetsymbolset</code>
<code>\resetssystemmode {...}</code> *    NAME
<code>\resettimer</code>
<code>\resettrackers</code>
<code>\resettrialtypesetting</code>
<code>\resetusedsortings [...]</code> *    SINGULAR
<code>\resetusedsynonyms [...]</code> *    SINGULAR
<code>\resetuserpagenumber</code>
<code>\resetvalue {...}</code> *    NAME
<code>\resetvisualizers</code>
<code>\reshapebox {...}</code> *    COMMAND
<code>\restartcounter [.¹.] [.².] [.³.]</code> 1    NAME 2    NUMBER 3    NUMBER

$\backslash\text{restorebox}$ $\{.^1.\}$ $\{.^2.\}$  1 NAME 2 NAME
$\backslash\text{restorecatcodes}$
$\backslash\text{restorecounter}$ $[.^*.]$  * NAME
$\backslash\text{restorecurrentattributes}$ $\{.^*.\}$  * NAME
$\backslash\text{restoreendofline}$
$\backslash\text{restoreglobalbodyfont}$
$\backslash\text{reusableMPgraphic}$ $\{.^1.\}$ $\{.^2.\}$ $\{.^2.\}$  1 NAME 2 KEY = VALUE
$\backslash\text{reuseMPgraphic}$ $\{.^1.\}$ $\{.^2.\}$ $\{.^2.\}$  1 NAME 2 KEY = VALUE
$\backslash\text{reuserandomseed}$
$\backslash\text{revivefeature}$
$\backslash\text{rfence}$ $\{.^*.\}$  * CHARACTER
$\backslash\text{rhbox}$ $\{.^*.\}$  * CONTENT
$\backslash\text{right}$ $.^*$  * CHARACTER
$\backslash\text{rightaligned}$ $\{.^*.\}$  * CONTENT
$\backslash\text{rightbottombox}$ $\{.^*.\}$  * CONTENT
$\backslash\text{rightbox}$ $\{.^*.\}$  * CONTENT
$\backslash\text{righthbox}$ $\{.^*.\}$  * CONTENT

$\backslash\mathrm{rightheadtext}\{...\}$ * KEY
$\backslash\mathrm{rightlabeltext}\{...\}$ * KEY
$\backslash\mathrm{rightlabeltext}\{...\}$ * KEY
$\backslash\mathrm{rightline}\{...\}$ * CONTENT
$\backslash\mathrm{rightmathlabeltext}\{...\}$ * KEY
$\backslash\mathrm{rightorleftpageaction}\{.^1.\}\{.^2.\}$ 1 COMMAND 2 COMMAND
$\backslash\mathrm{rightskipadaption}$
$\backslash\mathrm{rightsubguillemot}$
$\backslash\mathrm{righttopleft}$
$\backslash\mathrm{righttopleftthbox}\{.^1.\}\{.^2.\}$ 1 TEXT 2 CONTENT
$\backslash\mathrm{righttopleftvbox}\{.^1.\}\{.^2.\}$ 1 TEXT 2 CONTENT
$\backslash\mathrm{righttopleftvtop}\{.^1.\}\{.^2.\}$ 1 TEXT 2 CONTENT
$\backslash\mathrm{righttopbox}\{...\}$ * CONTENT
$\backslash\mathrm{rlap}\{...\}$ * CONTENT
$\backslash\mathrm{robustaddtocommalist}\{.^1.\}\backslash.^2.$ 1 TEXT 2 CSNAME

`\robustdoifelseinset {...} {...}`

- 1 TRUE
- 2 FALSE

`\robustdoifinsetelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\robustpretocommalist {...} \^...`

- 1 TEXT
- 2 CSNAME

`\rob [...]1 ... \^`

- 1 REFERENCE
- 2 TEXT

`\rollbutton [...]1 [...,...2...,...] ... [...]4`

- 1 NAME
- 2 inherits: \setupinteractionmenu
- 3 TEXT
- 4 REFERENCE

`\rollbutton [...,...1...,...] ... [...]3`

- 1 inherits: \setupbutton
- 2 TEXT
- 3 REFERENCE

`\roman`

`\romannumerals {...}`

- \* NUMBER

`\rotate [...,...1...,...] {...}2`

- 1 inherits: \setuprotate
- 2 CONTENT

`\rtop ...1 {...}2`

- 1 TEXT
- 2 CONTENT

`\ruledhbox ...1 {...}2`

- 1 TEXT
- 2 CONTENT

`\ruledhpack ...1 {...}2`

- 1 TEXT
- 2 CONTENT

<code>\ruledmbox {...}</code>  *    CONTENT
<code>\ruledtopv <sup>1</sup>... {...}</code>  1    TEXT 2    CONTENT
<code>\ruledtpack <sup>1</sup>... {...}</code>  1    TEXT 2    CONTENT
<code>\ruledvbox <sup>1</sup>... {...}</code>  1    TEXT 2    CONTENT
<code>\ruledvpack <sup>1</sup>... {...}</code>  1    TEXT 2    CONTENT
<code>\ruledvtop <sup>1</sup>... {...}</code>  1    TEXT 2    CONTENT
<code>\rul <sup>*</sup>... \\\</code>  *    TEXT
<code>\runMPbuffer [...*,...]</code>  *    NAME
<code>\ScaledPointsToBigPoints {...} \<sup>2</sup>...</code>  1    DIMENSION 2    CSNAME
<code>\ScaledPointsToWholeBigPoints {...} \<sup>2</sup>...</code>  1    DIMENSION 2    CSNAME
<code>\SmallCapped {...}</code>  *    TEXT
<code>\Smallcapped {...}</code>  *    TEXT
<code>\safechar {...}</code>  *    NUMBER
<code>\sans</code>

<code>\sansbold</code>
<code>\sansnormal</code>
<code>\sansserif</code>
<code>\savebox {<sup>1</sup>.} {<sup>2</sup>.} {<sup>3</sup>.}</code>  1 NAME  2 NAME  3 CONTENT
<code>\savebtxdataset [<sup>1</sup>.] [<sup>2</sup>.] [<sup>3</sup>...]</code>  1 NAME  2 FILE  3 dataset = NAME type = bib lua xml file = FILE criterium = all text intro reference current here previous local component SECTIONBLOCK:all SECTIONBLOCK:reference SECTIONBLOCK:current SECTIONBLOCK:previous
<code>\savebuffer [...<sup>1</sup>,...] [<sup>2</sup>.]</code>  1 BUFFER  2 FILE
<code>\savebuffer [...<sup>*</sup>...]</code>  * list = NAME file = FILE prefix = <u>yes</u> no
<code>\savecolor ... \restorecolor</code>
<code>\savecounter [...]</code>  * NAME
<code>\savecurrentattributes {<sup>*</sup>.}</code>  * NAME
<code>\savenormalmeaning \<sup>*</sup>...</code>  * CSNAME
<code>\savetaggedtwopassdata {<sup>1</sup>.} {<sup>2</sup>.} {<sup>3</sup>.} {<sup>4</sup>.}</code>  1 NAME  2 NUMBER  3 NAME  4 CONTENT
<code>\savetwopassdata {<sup>1</sup>.} {<sup>2</sup>.} {<sup>3</sup>.}</code>  1 NAME  2 NUMBER  3 CONTENT

`\sbox {...}`

\* CONTENT

`\scale [...1] [...2...3] {...}`

1 NAME

2 inherits: \setupscale

3 CONTENT

`\screen [...*,...]`

\* inherits: \page

`\script`

`\secondoffivearguments {...1} {...2} {...3} {...4} {...5}`

1 TEXT

2 TEXT

3 TEXT

4 TEXT

5 TEXT

`\secondoffourarguments {...1} {...2} {...3} {...4}`

1 TEXT

2 TEXT

3 TEXT

4 TEXT

`\secondofsixarguments {...1} {...2} {...3} {...4} {...5} {...6}`

1 TEXT

2 TEXT

3 TEXT

4 TEXT

5 TEXT

6 TEXT

`\secondofthreearguments {...1} {...2} {...3}`

1 TEXT

2 TEXT

3 TEXT

`\secondofthreeunexpanded {...1} {...2} {...3}`

1 TEXT

2 TEXT

3 TEXT

`\secondoftwoarguments {...1} {...2}`

1 TEXT

2 TEXT



`\secondoftwounexpanded {...} {...}`

- 1 TEXT
- 2 TEXT

`\section [...,1...] {...2}`

- 1 REFERENCE
- 2 TEXT

`\section [...,1...] {...2}`

- 1 REFERENCE
- 2 TEXT

`\section [...,1...] {...2} {...3}`

- 1 REFERENCE
- 2 NUMBER
- 3 TEXT

`\section [...,*...] [...,*...]`

`* title = TEXT`  
`bookmark = TEXT`  
`marking = TEXT`  
`list = TEXT`  
`reference = REFERENCE`  
`ownnumber = TEXT`

`\seeindex [...1] [...+...2+...] {...3}`

- 1 TEXT PROCESSOR->TEXT
- 2 INDEX
- 3 TEXT PROCESSOR->TEXT

`\seeregister [...1] [...+...2+...] {...3}`

- 1 TEXT PROCESSOR->TEXT
- 2 INDEX
- 3 TEXT PROCESSOR->TEXT

`\select {...} {...} {...} {...} {...} {...}`

- 1 NAME
- 2 CONTENT
- 3 CONTENT
- 4 CONTENT
- 5 CONTENT
- 6 CONTENT

`\selectblocks [...,1...] [...,2...] [...,3...]`

- 1 NAME
- 2 + -
- 3 criterium = text SECTION

\serializecommalist [...,*,...]  *   COMMAND
\serializedcommalist
\serif
\serifbold
\serifnormal
\setbar [...]  *   NAME
\setbigbodyfont
\setboxllx <sup>1</sup> ... { <sup>2</sup> ...}  1   CSNAME NUMBER 2   DIMENSION
\setboxlly <sup>1</sup> ... { <sup>2</sup> ...}  1   CSNAME NUMBER 2   DIMENSION
\setbreakpoints [...]  *   reset NAME
\setbuffer [...] ... \endbuffer  *   NAME
\setcapstrut
\setcatcodetable \*...  *   CSNAME
\setcharacteralign { <sup>1</sup> ...} { <sup>2</sup> ...}  1   NUMBER 2   TEXT number->TEXT text->TEXT
\setcharactercasing [...]  *   reset WORD word Word Words capital Capital none random mixed camel cap Cap
\setcharactercleaning [...]  *   reset 1
\setcharacterkerning [...]  *   reset NAME

`\setcharacterspacing [...]`

\* reset NAME

`\setcharacterstripping [...]`

\* reset 1

`\setcharstrut {...}`

\* TEXT

`\setcollector [...]1 [...,...2...,...]3 {...}`

1 NAME

2 inherits: \setupcollector

3 CONTENT

`\setcolormodel [...]`

\* black bw gray rgb cmyk all none

`\setcounter [...]1 [...]2 [...]3`

1 NAME

2 NUMBER

3 NUMBER

`\setcounterown [...]1 [...]2 [...]3`

1 NAME

2 NUMBER

3 TEXT

`\setcurrentfontclass {...}`

\* NAME

`\setdataset [...]1 [...]2 [...,...3...,...]`

1 NAME

2 NAME

3 KEY = VALUE

`\setdefaultpenalties`

`\setdigitsmanipulation [...]`

\* reset NUMBER

`\setdirection [...]`

\* NUMBER

`\setdocumentargument {...}1 {...}2`

1 NAME

2 TEXT

`\setdocumentargumentdefault {...} {...}`

- 1 NAME
- 2 TEXT

`\setdocumentfilename {...} {...}`

- 1 NUMBER
- 2 TEXT

`\setdummyparameter {...} {...}`

- 1 KEY
- 2 COMMAND

`\setelementexporttag [...] [...] [...]`

- 1 NAME
- 2 `export` nature pdf
- 3 inline display mixed

`\setemeasure {...} {...}`

- 1 NAME
- 2 DIMENSION

`\setevalue {...} {...}`

- 1 NAME
- 2 CONTENT

`\setevariable {...} {...} {...}`

- 1 NAME
- 2 KEY
- 3 VALUE

`\setevariables [...] [..., ...2..., ...]`

- 1 NAME
- 2 `set` = COMMAND  
`reset` = COMMAND  
KEY = VALUE

`\setfirstline [...]`

- \* NAME

`\setflag {...}`

- \* NAME

`\setfont ...`

- \* FONT

`\setfontcolorsheme [...]`

- \* NAME

<pre>\setfontfeature {...}</pre> <p>* NAME</p>
<pre>\setfontsolution [...]</pre> <p>* NAME</p>
<pre>\setfontstrut</pre>
<pre>\setgmeasure {...} {...}</pre> <p>1 NAME</p> <p>2 DIMENSION</p>
<pre>\setgvalue {...} {...}</pre> <p>1 NAME</p> <p>2 CONTENT</p>
<pre>\setgvariable {...} {...} {...}</pre> <p>1 NAME</p> <p>2 KEY</p> <p>3 VALUE</p>
<pre>\setgvariables [...] [...,\underline{...},...]</pre> <p>1 NAME</p> <p>2 set = COMMAND reset = COMMAND KEY = VALUE</p>
<pre>\sethyphenatedurlafter {...}</pre> <p>* TEXT</p>
<pre>\sethyphenatedurlbefore {...}</pre> <p>* TEXT</p>
<pre>\sethyphenatedurlnormal {...}</pre> <p>* TEXT</p>
<pre>\sethyphenationfeatures [...,*,...]</pre> <p>* NAME reset</p>
<pre>\setinitial [...] [...,\underline{...},...]</pre> <p>1 NAME</p> <p>2 inherits: \setupinitial</p>
<pre>\setinjector [...] [...,\underline{...}] [...]</pre> <p>1 NAME</p> <p>2 NUMBER</p> <p>3 COMMAND</p>

<pre> \setinteraction [...]  *   hidden NAME </pre>
<pre> \setinterfacecommand {...} {...}  1   NAME 2   NAME </pre>
<pre> \setinterfaceconstant {...} {...}  1   NAME 2   NAME </pre>
<pre> \setinterfaceelements {...} {...}  1   NAME 2   NAME </pre>
<pre> \setinterfacemessage {...} {...} {...}  1   NAME 2   title NAME NUMBER 3   TEXT </pre>
<pre> \setinterfacevariable {...} {...}  1   NAME 2   NAME </pre>
<pre> \setinternalrendering [...] [...] {...}  1   NAME 2   auto embed 3   CONTENT </pre>
<pre> \setitaliccorrection [...]  *   reset 1 2 </pre>
<pre> \setJSreamble {...} {...}  1   NAME 2   CONTENT </pre>
<pre> \setlayer [...] [...] [...,..<sup>3</sup>...,..] {...<sup>4</sup>}  1   NAME 2   left right even odd 3   inherits: \setuplayer 4   CONTENT </pre>
<pre> \setlayerframed [...] [...] [...,..<sup>2</sup>...,..] [...,..<sup>3</sup>...,..] {...<sup>4</sup>}  1   NAME 2   inherits: \setuplayer 3   inherits: \setupframed 4   CONTENT </pre>

**\setlayerframed** [<sup>1</sup>...] [<sup>2</sup>...<sup>2</sup>...<sup>2</sup>...] {<sup>3</sup>...}

- 1 NAME
- 2 inherits: \setuplayerinherits: \setupframed
- 3 CONTENT

**\setlayertext** [<sup>1</sup>...] [<sup>2</sup>...<sup>2</sup>...<sup>2</sup>...] [<sup>3</sup>...<sup>3</sup>...<sup>3</sup>...] {<sup>4</sup>...}

- 1 NAME
- 2 inherits: \setuplayer
- 3 align = inherits: \setupalign  
width = DIMENSION  
style = STYLE COMMAND  
color = COLOR
- 4 TEXT

**\setlocalhsize** [<sup>\*</sup>...]

- \* [-+]DIMENSION

**\setMPlayer** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...<sup>3</sup>...<sup>3</sup>...] {<sup>4</sup>...}

- 1 NAME
- 2 NAME
- 3 inherits: \setuplayer
- 4 CONTENT

**\setMPpositiongraphic** {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...<sup>3</sup>...<sup>3</sup>...}

- 1 NAME
- 2 NAME
- 3 KEY = VALUE

**\setMPpositiongraphicrange** {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...} {<sup>4</sup>...<sup>4</sup>...<sup>4</sup>...}

- 1 NAME
- 2 NAME
- 3 NAME
- 4 KEY = VALUE

**\setMPtext** {<sup>1</sup>...} {<sup>2</sup>...}

- 1 NAME
- 2 TEXT

**\setMPvariable** [<sup>1</sup>...] [<sup>2</sup>...<sup>2</sup>...]

- 1 NAME
- 2 KEY = VALUE

**\setMPvariables** [<sup>1</sup>...] [<sup>2</sup>...<sup>2</sup>...<sup>2</sup>...]

- 1 NAME
- 2 KEY = VALUE

**\setmainbodyfont**

`\setmainparbuilder [...]`

\* default oneline basic NAME

`\setmarker [...]1 [...]2`

1 NAME

2 NUMBER

`\setmarking [...]1 {...}2`

1 MARK

2 TEXT

`\setmathstyle {...,*,...}`

\* display text script scriptscript cramped uncramped normal packed small big NAME

`\setmeasure {...}1 {...}2`

1 NAME

2 DIMENSION

`\setmessagetext {...}1 {...}2`

1 NAME

2 NAME NUMBER

`\setmode {...}`

\* NAME

`\setnostrut`

`\setnotetext [...]1 [...,2...] {...}3`

1 NAME

2 REFERENCE

3 TEXT

`\setnotetext [...]1 [...,2...] {...}`

1 NAME

2 title = TEXT  
bookmark = TEXT  
list = TEXT  
reference = REFERENCE

`\setnote [...]1 [...,2...] {...}3`

1 NAME

2 REFERENCE

3 TEXT

`\setnote [...]1 [...,2...] {...}`

1 NAME

2 title = TEXT  
bookmark = TEXT  
list = TEXT  
reference = REFERENCE



`\setobject {...} {...} \... {...}`

- 1 NAME
- 2 NAME
- 3 CSNAME
- 4 CONTENT

`\setoldstyle`

`\setpagegrid [...1...,...2] {...}`

- 1 c = NUMBER
- r = NUMBER
- option = none
- 2 CONTENT

`\setpagereference {...1} {...2,...}`

- 1 NAME
- 2 REFERENCE

`\setpagestate [...1] [...2]`

- 1 NAME
- 2 NAME NUMBER

`\setpagestaterealpageno {...1} {...2}`

- 1 NAME
- 2 NAME NUMBER

`\setpenalties \... {...2} {...3}`

- 1 CSNAME
- 2 NUMBER
- 3 NUMBER

`\setpercentdimen {...1} {...2}`

- 1 DIMENSION CSNAME
- 2 DIMENSION NUMBER

`\setposition {...*}`

- \* NAME

`\setpositionbox {...1} \...2 {...3}`

- 1 NAME
- 2 CSNAME
- 3 CONTENT

`\setpositiondata {...1} {...2} {...3} {...4}`

- 1 NAME
- 2 DIMENSION
- 3 DIMENSION
- 4 DIMENSION

\setpositiondataplus {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} {...<sup>4</sup>} {...,<sup>5</sup>...}

- 1 NAME
- 2 DIMENSION
- 3 DIMENSION
- 4 DIMENSION
- 5 TEXT

\setpositiononly {...}

- \* NAME

\setpositionplus {...<sup>1</sup>} {...,<sup>2</sup>...} \...<sup>3</sup> {...<sup>4</sup>}

- 1 NAME
- 2 TEXT
- 3 CSNAME
- 4 CONTENT

\setpositionstrut {...}

- \* NAME

\setprofile [...]

- \* none fixed strict halffixed quarterfixed eightsfixed NAME

\setrandomseed {...}

- \* NUMBER

\setreference [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

- 1 REFERENCE
- 2 KEY = VALUE

\setreferencedobject {...<sup>1</sup>} {...<sup>2</sup>} \...<sup>3</sup> {...<sup>4</sup>}

- 1 NAME
- 2 NAME
- 3 CSNAME
- 4 CONTENT

\setregisterentry [...<sup>1</sup>] [...,<sup>2</sup>...,...]<sup>3</sup> [...,<sup>3</sup>...,...]

- 1 NAME
- 2 label = NAME  
keys = TEXT PROCESSOR->TEXT  
entries = TEXT PROCESSOR->TEXT  
keys:1 = TEXT  
keys:2 = TEXT  
keys:3 = TEXT  
entries:1 = TEXT  
entries:2 = TEXT  
entries:3 = TEXT  
alternative = TEXT
- 3 KEY = VALUE

\setreplacement [...]

- \* reset NAME

<pre> \setrigidcolumnbalance ...  * CSNAME NUMBER </pre>
<pre> \setrigidcolumnhsize {...} {...} {...}  1 DIMENSION 2 DIMENSION 3 NUMBER </pre>
<pre> \setscript [...]  * hangul hanzi nihongo ethiopic thai test NAME </pre>
<pre> \setsectionblock [...] [..., ...<sup>2</sup>..., ...]  1 NAME  2 bookmark = TEXT </pre>
<pre> \setsimplecolumnhsize [..., ...<sup>*</sup>..., ...]  * n      = NUMBER   width  = DIMENSION   distance = DIMENSION   lines  = NUMBER </pre>
<pre> \setsmallbodyfont </pre>
<pre> \setsmallcaps </pre>
<pre> \setstackbox {...} {...<sup>2</sup>} {...<sup>3</sup>}  1 NAME 2 NAME 3 CONTENT </pre>
<pre> \setstructurepageregister [...] [..., ...<sup>2</sup>..., ...] [..., ...<sup>3</sup>..., ...]  1 NAME  2 label      = NAME   keys       = TEXT PROCESSOR-&gt;TEXT   entries     = TEXT PROCESSOR-&gt;TEXT   keys:1      = TEXT   keys:2      = TEXT   keys:3      = TEXT   entries:1   = TEXT   entries:2   = TEXT   entries:3   = TEXT   alternative = TEXT  3 KEY = VALUE </pre>
<pre> \setstrut </pre>
<pre> \setsuperiors </pre>
<pre> \setsystemmode {...}  * NAME </pre>
<pre> \settabular </pre>

`\settaggedmetadata [...,*...]`

\* KEY = VALUE

`\settextcontent [...] [...] [...] [...] [...]`

1 top header text footer bottom  
2 text margin edge  
3 left middle right  
4 date pagenumber MARK TEXT COMMAND  
5 date pagenumber MARK TEXT COMMAND

`\settightobject {...} {...} \... {...}`

1 NAME  
2 NAME  
3 CSNAME  
4 CONTENT

`\settightreferencedobject {...} {...} \... {...}`

1 NAME  
2 NAME  
3 CSNAME  
4 CONTENT

`\settightunreferencedobject {...} {...} \... {...}`

1 NAME  
2 NAME  
3 CSNAME  
4 CONTENT

`\settrialtypesetting`

`\setuevalue {...} {...}`

1 NAME  
2 CONTENT

`\setugvalue {...} {...}`

1 NAME  
2 CONTENT

`\setunreferencedobject {...} {...} \... {...}`

1 NAME  
2 NAME  
3 CSNAME  
4 CONTENT

`\setupalign [...,*...]`

\* broad wide bottom height line high low lohi flushright flushleft middle yes no width normal reset inner outer  
flushinner flushouter left right center disable last end paragraph lefttoright righttoleft l2r r2l table lessshyphenation  
morehyphenation hanging nothanging hz fullhz nohz hyphenated nothyphenated tolerant verytolerant stretch extremestretch  
final 2\*final 3\*final 4\*final

`\setuparranging [...,*...]`

\*    disable mirrored doublesided negative 90 180 270 reset background normal 2\*16 2\*8 2\*4 2\*2 2\*\*2 2SIDE 2TOP 2UP  
2DOWN 2\*4\*2 2\*2\*4 2TOPSIDE 2\*8\*Z 2\*6\*Z 1\*8 1\*4 3SIDE TRYPTICHON ZFLYER-8 ZFLYER-10 ZFLYER-12 MAPFLYER-12 DOUBLEWINDOW  
1\*2-Conference 1\*4-Conference 2\*2\*2 2\*2\*3 XY NAME

`\setupattachment [...,1...] [...,2...]`

1    NAME

2    title        = TEXT  
     subtitle    = TEXT  
     author      = TEXT  
     file        = FILE  
     name        = NAME  
     buffer      = BUFFER  
     state       = start stop  
     method      = normal hidden  
     symbol      = Graph Paperclip Pushpin Default  
     width       = fit DIMENSION  
     height      = fit DIMENSION  
     depth       = fit DIMENSION  
     color       = COLOR  
     textlayer   = NAME  
     location    = leftedge rightedge inmargin leftmargin rightmargin text high none  
     distance    = DIMENSION

`\setupbackend [...,*...]`

\*    export      = yes FILE  
     xhtml      = FILE  
     file        = FILE  
     intent      = NAME  
     space       = yes no  
     xmpfile     = FILE  
     format      = version default NAME  
     level       = NUMBER  
     option      = always never  
     profile     = FILE

`\setupbackground [...,1...] [...,2...]`

1    NAME

2    state        = start stop  
     leftoffset   = DIMENSION  
     rightoffset = DIMENSION  
     topoffset    = DIMENSION  
     bottomoffset = DIMENSION  
     before       = COMMAND  
     after        = COMMAND  
     inherits: \setupframed

`\setupbackgrounds [...,1...] [...,2...] [...,3...]`

1    top header text footer bottom

2    leftedge leftmargin text rightmargin rightedge

3    inherits: \setupframed

`\setupbackgrounds [...,1...] [...,2...]`

1    paper page leftpage rightpage text hidden

2    state = start stop  
     inherits: \setupframed

`\setupbar [...1,...] [...2,...]`

1 NAME

2 color = COLOR  
continue = yes no all  
unit = ex em pt in cm mm sp bp pc dd cc nc  
order = foreground background  
rulethickness = DIMENSION  
method = NUMBER  
offset = NUMBER  
dy = NUMBER  
max = NUMBER  
foregroundstyle = STYLE COMMAND  
foregroundcolor = COLOR  
mp = NAME

`\setupblackrules [...*,...]`

\* width = max DIMENSION  
height = max DIMENSION  
depth = max DIMENSION  
distance = DIMENSION  
n = NUMBER  
alternative = a b  
style = STYLE COMMAND  
color = COLOR  
type = mp yes no  
mp = NAME

`\setupblank [...*,...]`

\* inherits: \vspacing

`\setupbleeding [...*,...]`

\* width = DIMENSION  
height = DIMENSION  
offset = DIMENSION  
hoffset = DIMENSION  
voffset = DIMENSION  
location = t b l r bl lb br rb tl lt tr rt  
stretch = yes no  
page = yes no

`\setupblock [...1,...] [...2,...]`

1 NAME

2 before = COMMAND  
after = COMMAND  
inner = COMMAND  
style = STYLE COMMAND  
color = COLOR

`\setupbodyfont [...*,...]`

\* DIMENSION NAME global reset x xx small big script scriptscript rm ss tt hw cg roman serif regular sans sansserif support type teletype mono handwritten calligraphic

`\setupbookmark [...*,...]`

\* force = yes no  
number = yes no  
numberseparatorset = NAME  
numberconversionset = NAME  
numberstarter = COMMAND  
numberstopper = COMMAND  
numbersegments = NUMBER NUMBER:NUMBER NUMBER:\* NUMBER:all SECTION SECTION:SECTION SECTION:\* SECTION:all  
sectionblock = yes no

`\setupbottom [...]1 [...,...2...,...]`

- 1 text margin edge
- 2 inherits: \setuplayoutelement

`\setupbottomtexts [...]1 [...]2 [...]3 [...]4 [...]5`

- 1 text margin edge
- 2 date pagenumber MARK TEXT COMMAND
- 3 date pagenumber MARK TEXT COMMAND
- 4 date pagenumber MARK TEXT COMMAND
- 5 date pagenumber MARK TEXT COMMAND

`\setupbtxdataset [...]1,...] [...,...2...,...]`

- 1 NAME
- 2 language = LANGUAGE

`\setupbtxlabeltext [...]1 [...,...2...,...]`

- 1 LANGUAGE
- 2 KEY = VALUE

`\setupbtxlist [...]1 [...,...2...,...]`

- 1 NAME
- 2 inherits: \setuplist

`\setupbtxregister [...]1,...] [...,...2...,...]`

- 1 NAME
- 2 state = start stop  
dataset = NAME  
field = keyword range pagenumber author  
register = NAME  
method = once  
alternative = normalshort invertedshort  
style = STYLE COMMAND  
color = COLOR

`\setupbtxrendering [...]1,...] [...,...2...,...]`

- 1 NAME
- 2 textstate = start stop  
pagestate = start stop  
separator = COMMAND  
criterion = previous cite here all none  
specification = NAME  
title = TEXT  
before = COMMAND  
after = COMMAND  
dataset = NAME  
method = dataset force local global none  
sorttype = short dataset list reference used default cite index  
repeat = yes no  
group = NAME  
numbering = yes no num index tag short page

`\setupbtx [...]1 [...,...2...,...]`

```
1  NAME

2  specification = default apa aps NAME
   dataset      = default NAME
   command      = CD:ONEARGUMENT
   left         = COMMAND
   right        = COMMAND
   authorconversion = normal normalshort normalinverted invertedshort short
   etallimit    = NUMBER
   etaldisplay   = NUMBER
   etaloption    = last
   stopper      = initials
   interaction   = start stop all
   alternative   = default category entry short page num textnum year index tag keywords author authoryears
                  authornum authoryear
   sorttype     = normal reverse
   compress     = yes no
   default      = default NAME
   style        = STYLE COMMAND
   color        = COLOR
```

`\setupbtx [...]`

`* NAME`

`\setupbuffer [...]1,...] [...,...2...,...]`

```
1  BUFFER

2  before = COMMAND
   after  = COMMAND
```

`\setupbutton [...]1,...] [...,...2...,...]`

```
1  NAME

2  state      = start stop
   samepage   = yes no empty none normal default
   style      = STYLE COMMAND
   color      = COLOR
   contrastcolor = COLOR
   alternative = hidden
   inherits: \setupframed
```

`\setupcapitals [...]1,...] [...,...2...,...]`

```
1  NAME

2  title = yes no
   sc    = yes no
   style = STYLE COMMAND
```

`\setupcaption [...]1,...] [...,...2...,...]`

```
1  NAME

2  inherits: \setupfloatcaption
```

`\setupcharacterkerning [...]1,...] [...,...2...,...]`

```
1  NAME

2  factor = max NUMBER
   width  = DIMENSION
   features = NAME
   style  = STYLE COMMAND
   color  = COLOR
```



`\setupcharacterspacing [...1.] [...2.] [...,3...]`

```
1 NAME
2 NUMBER
3 left      = NUMBER
  right     = NUMBER
  alternative = 0 1
```

`\setupchemical [...1,...] [...,2...]`

```
1 NAME
2 strut      = inherits: \value-strut
  width      = fit none NUMBER
  height     = fit none NUMBER
  left       = fit none NUMBER
  right      = fit none NUMBER
  top        = fit none NUMBER
  bottom     = fit none NUMBER
  scale      = small medium big normal NUMBER
  rotation   = NUMBER
  symalign   = auto
  axis       = on off
  framecolor = COLOR
  rulethickness = DIMENSION
  offset     = DIMENSION
  unit       = DIMENSION
  factor     = NUMBER
  frame      = on off
  rulecolor  = COLOR
  bodyfont   = inherits: \setupbodyfont
  size       = small medium big
  style      = STYLE COMMAND
  color      = COLOR
```

`\setupchemicalframed [...1,...] [...,2...]`

```
1 NAME
2 inherits: \setupframed
```

`\setupclipping [...,*...]`

```
* state      = start stop
  width      = DIMENSION
  height     = DIMENSION
  hoffset    = DIMENSION
  voffset    = DIMENSION
  x          = NUMBER
  y          = NUMBER
  nx         = NUMBER
  ny         = NUMBER
  sx         = NUMBER
  sy         = NUMBER
  leftoffset = DIMENSION
  rightoffset = DIMENSION
  topoffset  = DIMENSION
  bottomoffset = DIMENSION
  mp         = NAME
  n          = NUMBER
  offset     = DIMENSION
```

`\setupcollector [...1,...] [...,2...]`

```
1 NAME
2 rotation = left right inner outer NUMBER
  corner   = left middle right top bottom
  x        = DIMENSION
  y        = DIMENSION
  hoffset  = DIMENSION
  voffset  = DIMENSION
  location = left middle right top bottom line l c r m t b g
  state    = start stop
```

`\setupcolor [...]`

\* FILE

`\setupcolors [...,*...]`

\* state = start stop  
spot = yes no  
expansion = yes no  
factor = yes no  
rgb = yes no  
cmyk = yes no  
conversion = yes no always  
pagecolormodel = auto none NAME  
textcolor = COLOR  
intent = overprint knockout none

`\setupcolumns [...,*...]`

\* n = NUMBER  
distance = DIMENSION  
option = background  
offset = DIMENSION  
command = CD:ONEARGUMENT  
height = DIMENSION  
direction = left right  
balance = yes no  
align = setupalign  
tolerance = setuptolerance  
blank = inherits: \blank  
ntop = NUMBER  
rule = on off COMMAND

`\setupcolumnspan [...,*...]`

\* n = NUMBER  
inherits: \setupframed

`\setupcombination [...,1...] [...,2...]`

1 NAME  
2 nx = NUMBER  
ny = NUMBER  
width = fit DIMENSION  
height = fit DIMENSION  
location = left middle right top bottom  
distance = DIMENSION  
alternative = label text  
align = inherits: \setupalign  
continue = yes no  
before = COMMAND  
after = COMMAND  
inbetween = COMMAND  
style = STYLE COMMAND  
color = COLOR

`\setupcombinedlist [...,1] [...,2...]`

1 LIST  
2 inherits: \setuplist

`\setupcombinedlist [...,*...]`

\* inherits: \setuplist

`\setupcomment [...,1...] [...,2...,...]`

```
1  NAME

2  state      = start stop none
   method     = normal hidden
   symbol     = Comment Help Insert Key Newparagraph Note Paragraph Default
   width      = fit DIMENSION
   height     = fit DIMENSION
   depth      = fit DIMENSION
   title      = TEXT
   subtitle   = TEXT
   author     = TEXT
   nx         = NUMBER
   ny         = NUMBER
   color      = COLOR
   option     = xml max
   textlayer  = NAME
   location   = leftedge rightedge inmargin leftmargin rightmargin text high none
   distance   = DIMENSION
```

`\setupcontent [...,*...,...]`

`* inherits: \setuplist`

`\setupcounter [...,1...] [...,2...,...]`

```
1  NAME

2  start      = NUMBER
   counter    = NAME
   method     = page
   state      = start stop
   way        = bypage byblock bytext byhead bySECTION
   prefix     = yes no
   prefixseparatorset = NAME
   prefixconversion = NAME
   prefixconversionset = NAME
   prefixstarter = COMMAND PROCESSOR->COMMAND
   prefixstopper = COMMAND PROCESSOR->COMMAND
   prefixset   = NAME
   prefixsegments = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:all SECTION SECTION:SECTION SECTION:* SECTION:all
   numberorder = reverse
   numberseparatorset = NAME
   numberconversion = NAME
   numberconversionset = NAME
   numberstarter = COMMAND PROCESSOR->COMMAND
   numberstopper = COMMAND PROCESSOR->COMMAND
   numbersegments = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:all
   type        = first previous next last number
   criterium   = strict positive all
   prefixconnector = COMMAND PROCESSOR->COMMAND
```

`\setupdataset [...,*...,...]`

`* delay = yes no`

`\setupdelimitedtext [...1,...] [...2...,...]`

```
1  NAME
2  before      = COMMAND
   after       = COMMAND
   language    = LANGUAGE
   method      = font
   repeat      = yes no
   location    = text paragraph margin
   left        = COMMAND
   middle      = COMMAND
   right       = COMMAND
   nextleft    = COMMAND
   nextright   = COMMAND
   spacebefore = inherits: \blank
   spaceafter  = inherits: \blank
   leftmargin  = yes no standard DIMENSION
   rightmargin = yes no standard DIMENSION
   indenting   = inherits: \setupindenting
   indentnext  = yes no auto
   style       = STYLE COMMAND
   color       = COLOR
   symstyle    = STYLE COMMAND
   symcolor    = COLOR
```

`\setupdescription [...1,...] [...2...,...]`

```
1  NAME
2  title       = yes no
   level       = NUMBER
   text        = TEXT
   headcommand = CD:ONEARGUMENT
   before      = COMMAND
   after       = COMMAND
   inbetween   = COMMAND
   alternative  = left right inmargin inleft inright margin leftmargin rightmargin innermargin outermargin serried
                  hanging top command NAME
   align        = inherits: \setupalign
   headalign    = inherits: \setupalign
   indenting    = inherits: \setupindenting
   display      = yes no
   indentnext   = yes no auto
   width        = fit broad line DIMENSION
   distance     = none DIMENSION
   hang         = fit broad none margin NUMBER
   closesymbol  = COMMAND
   closecommand = CD:ONEARGUMENT
   expansion    = yes no xml
   sample       = TEXT
   margin       = yes no standard DIMENSION
   style        = STYLE COMMAND
   color        = COLOR
   headstyle    = STYLE COMMAND
   headcolor    = COLOR
```

`\setupdirections [...*...,...]`

```
*  bidi      = on off local global
   method     = one two default
   fences     = yes no
```

`\setupdocument [...*...,...]`

```
*  before      = COMMAND
   after       = COMMAND
   metadata:author = TEXT
   metadata:title  = TEXT
   metadata:subject = TEXT
   metadata:keywords = TEXT
   KEY          = VALUE
```

`\setupeffect [...,1...] [...,2...,...]`

```
1 NAME
2 method      = none command
  stretch     = NUMBER
  rulethickness = NUMBER
  alternative   = normal inner outer both hidden stretch
```

`\setupenumeration [...,1...] [...,2...,...]`

```
1 NAME
2 title      = yes no
  number     = yes no
  numbercommand = CD:ONEARGUMENT
  titledistance = DIMENSION
  titlestyle  = STYLE COMMAND
  titlecolor  = COLOR
  titlecommand = CD:ONEARGUMENT
  titleleft   = COMMAND
  titleright  = COMMAND
  left        = COMMAND
  right       = COMMAND
  symbol      = COMMAND
  starter     = COMMAND
  stopper     = COMMAND
  coupling    = NAME
  counter     = NAME
  level       = NUMBER
  text        = TEXT
  headcommand = CD:ONEARGUMENT
  before      = COMMAND
  after       = COMMAND
  inbetween   = COMMAND
  alternative  = left right inmargin inleft inright margin leftmargin rightmargin innermargin outermargin serried
                hanging top command NAME
  align       = inherits: \setupalign
  headalign   = inherits: \setupalign
  indenting   = inherits: \setupindenting
  display     = yes no
  indentnext  = yes no auto
  width       = fit broad line DIMENSION
  distance    = none DIMENSION
  hang        = fit broad none margin NUMBER
  closesymbol = COMMAND
  closecommand = CD:ONEARGUMENT
  expansion   = yes no xml
  sample      = TEXT
  margin      = yes no standard DIMENSION
  style       = STYLE COMMAND
  color       = COLOR
  headstyle   = STYLE COMMAND
  headcolor   = COLOR
  inherits: \setupcounter
```

`\setupenv [...,*...,...]`

```
* set    = COMMAND
  reset  = COMMAND
  KEY    = VALUE
```

`\setupexport [...,*...,...]`

```
* align      = flushleft middle flushright normal
  bodyfont    = DIMENSION
  width       = DIMENSION
  title       = TEXT
  subtitle    = TEXT
  author      = TEXT
  alternative  = html div
  properties  = yes no
  hyphen      = yes no
  cssfile     = FILE
  firstpage   = FILE
  lastpage    = FILE
```

`\setupexternalfigure [...1,...] [...2...,...]`

```
1  NAME
2  width          = DIMENSION
   height         = DIMENSION
   label          = NAME
   page           = NUMBER
   object         = yes no
   prefix         = TEXT
   method         = pdf mps jpg png jp2 jbig svg eps gif tif mov buffer tex cld auto
   controls       = yes no
   preview        = yes no
   mask           = none
   resolution     = NUMBER
   color          = COLOR
   arguments      = CD:STRING
   repeat         = yes no
   factor         = fit broad max auto default
   hfactor        = fit broad max auto default
   wfactor        = fit broad max auto default
   maxwidth       = DIMENSION
   maxheight      = DIMENSION
   equalwidth     = DIMENSION
   equalheight    = DIMENSION
   scale          = NUMBER
   xscale         = NUMBER
   yscale         = NUMBER
   s              = NUMBER
   sx             = NUMBER
   sy             = NUMBER
   lines          = NUMBER
   location       = local global default
   directory      = PATH
   option         = test frame empty
   foregroundcolor = COLOR
   reset          = yes no
   background     = color foreground NAME
   frame          = on off
   backgroundcolor = COLOR
   align          = inherits: \setupalign
   xmax           = NUMBER
   ymax           = NUMBER
   frames         = on off
   interaction     = yes all none reference layer bookmark
   bodyfont       = DIMENSION
   comment        = COMMAND TEXT
   size           = none media crop trim art
   cache          = PATH
   resources      = PATH
   display        = FILE
   conversion     = TEXT
   order          = LIST
   crossreference = yes no NUMBER
```

`\setupexternalsoundtracks [...*...,...]`

\* option = repeat

`\setupfield [...1] [...2,...] [...3...,...] [...4...,...] [...5...,...]`

```
1  NAME
2  reset label frame horizontal vertical
3  inherits: \setupfieldtotalframed
4  inherits: \setupfieldlabelframed
5  inherits: \setupfieldcontentframed
```

`\setupfieldbody [...1,...] [...2...,...]`

```
1  NAME
2  category = NAME
   inherits: \setupfieldcategory
```

`\setupfieldcategory [...1,...] [...2...]`

```

1  NAME
2  start          = NUMBER
   style          = STYLE COMMAND
   color          = COLOR
   type           = radio sub text line push check signature
   values         = TEXT
   default        = TEXT
   fieldframecolor = COLOR
   fieldbackgroundcolor = COLOR
   width          = DIMENSION
   height         = DIMENSION
   depth         = DIMENSION
   align          = left middle right flushleft center flushright
   n              = NUMBER
   symbol         = NAME
   fieldlayer     = NAME
   option         = readonly required protected sorted unavailable nocheck fixed file hidden printable auto
   clickin        = REFERENCE
   clickout       = REFERENCE
   regionin       = REFERENCE
   regionout      = REFERENCE
   afterkey       = REFERENCE
   format         = REFERENCE
   validate       = REFERENCE
   calculate      = REFERENCE
   focusin        = REFERENCE
   focusout       = REFERENCE
   openpage       = REFERENCE
   closepage      = REFERENCE

```

`\setupfieldcontentframed [...1,...] [...2...]`

```

1  NAME
2  inherits: \setupframedinherits: \setupfieldcategory

```

`\setupfieldlabelframed [...1,...] [...2...]`

```

1  NAME
2  inherits: \setupframed

```

`\setupfields [...1,...] [...2...] [...3...] [...4...]`

```

1  reset label frame horizontal vertical
2  inherits: \setupfieldtotalframed
3  inherits: \setupfieldlabelframed
4  inherits: \setupfieldcontentframed

```

`\setupfieldtotalframed [...1,...] [...2...]`

```

1  NAME
2  before      = COMMAND
   after       = COMMAND
   inbetween   = COMMAND
   distance    = DIMENSION
   alternative = reset label frame horizontal vertical
   inherits: \setupframed

```

`\setupfiller [...1,...] [...2...,...]`

```
1  NAME

2  leftmargin   = DIMENSION
   rightmargin  = DIMENSION
   left         = COMMAND
   right        = COMMAND
   alternative  = symbol stretch rule space
   method       = local global middle broad
   width        = DIMENSION
   height       = DIMENSION
   depth        = DIMENSION
   offset       = DIMENSION
   distance     = DIMENSION
   align        = left right middle flushleft flushright inner outer
   symbol       = COMMAND
   style        = STYLE COMMAND
   color        = COLOR
```

`\setupfillinlines [...*...,...]`

```
*  before      = COMMAND
   after       = COMMAND
   margin      = DIMENSION
   width       = DIMENSION
   distance    = DIMENSION
   rulethickness = DIMENSION
   color       = COLOR
```

`\setupfillinrules [...*...,...]`

```
*  before      = COMMAND
   after       = COMMAND
   n           = NUMBER
   interlinespace = small medium big NUMBER
   distance    = DIMENSION
   width       = fit broad DIMENSION
   separator   = COMMAND
   style       = STYLE COMMAND
   color       = COLOR
```

`\setupfirstline [...1,...] [...2...,...]`

```
1  NAME

2  n           = NUMBER
   alternative = default line word
   style      = STYLE COMMAND
   color      = COLOR
```

`\setupfittingpage [...1,...] [...2...,...]`

```
1  NAME

2  pagestate = start stop
   command   = CD:ONEARGUMENT
   margin    = page
   scale     = NUMBER
   paper     = auto default NAME
   inherits: \setupframed
```



`\setupfloat [...1,...] [...2,...]`

```

1 SINGULAR

2 indentnext      = yes no auto
  default         = inherits: \placefloat
  fallback        = inherits: \placefloat
  inner           = COMMAND
  criterium       = DIMENSION
  method          = NUMBER
  sidemethod      = NUMBER
  textmethod      = NUMBER
  sidealign       = height depth line halfline grid normal
  local           = yes no
  command         = CD:ONEARGUMENT
  availablewidth  = DIMENSION
  availableheight = DIMENSION
  minwidth        = DIMENSION
  maxwidth        = DIMENSION
  location        = left right middle flushleft flushright center max inner outer innermargin outermargin
                  inneredge outeredge backspace cutspace leftmargin rightmargin leftedge rightedge

  leftmargindistance = DIMENSION
  rightmargindistance = DIMENSION
  leftmargin         = DIMENSION
  rightmargin        = DIMENSION
  innermargin        = DIMENSION
  outermargin        = DIMENSION
  bottombefore       = COMMAND
  bottomafter        = COMMAND
  spacebefore        = none inherits: \blank
  spaceafter         = none inherits: \blank
  width              = DIMENSION
  height             = DIMENSION
  offset             = DIMENSION none overlay
  sidespacebefore    = none inherits: \blank
  sidespaceafter     = none inherits: \blank
  margin             = DIMENSION
  ntop               = DIMENSION
  nbottom            = DIMENSION
  step               = small medium big line depth
  nlines             = NUMBER
  cache              = yes no

```

`\setupfloatcaption [...1,...] [...2,...]`

```

1 NAME

2 suffix          = COMMAND
  suffixseparator = COMMAND
  suffixstopper   = COMMAND
  location        = left right middle low high grid overlay inner outer innermargin outermargin leftmargin rightmargin
                  lefthanging righthanging hang top bottom stretch none default

  command         = CD:ONEARGUMENT
  numbercommand    = CD:ONEARGUMENT
  textcommand      = CD:ONEARGUMENT
  spacebefore      = inherits: \blank
  spaceinbetween   = inherits: \blank
  spaceafter       = inherits: \blank
  distance         = DIMENSION
  inbetween        = COMMAND
  style            = STYLE COMMAND
  color            = COLOR
  topoffset        = DIMENSION
  bottomoffset     = DIMENSION
  number           = yes no none
  group           = TEXT
  leftmargin       = DIMENSION
  rightmargin      = DIMENSION
  innermargin      = DIMENSION
  outermargin      = DIMENSION
  align            = inherits: \setupalign
  width            = fit max DIMENSION
  minwidth         = fit DIMENSION
  maxwidth         = DIMENSION
  inherits:        \setupcounter

```

```
\setupfloatsplitting [...,*...,...]
```

```
* before      = COMMAND
  after       = COMMAND
  inbetween    = COMMAND
  lines       = auto NUMBER
  conversion   = NAME
```

```
\setupfontexpansion [...1.] [...,2...,...]
```

```
1  NAME

2  vector      = NAME
   factor      = NUMBER
   stretch    = NUMBER
   shrink      = NUMBER
   step        = NUMBER
```

```
\setupfontprotrusion [...1.] [...,2...,...]
```

```
1  NAME

2  vector      = NAME
   factor      = NUMBER
   left        = NUMBER
   right       = NUMBER
```

```
\setupfonts [...,*...,...]
```

```
* language = no auto
```

```
\setupfontsolution [...,1...] [...,2...,...]
```

```
1  NAME

2  goodies      = FILE
   solution     = NAME
   less         = NAME
   more         = NAME
   method       = preroll split normal reverse random
   criterium    = NUMBER
```

```
\setupfooter [...1.] [...,2...,...]
```

```
1  text margin edge

2  inherits: \setuplayoutelement
```

```
\setupfootertexts [...1.] [...2.] [...3.] [...4.] [...5.]
```

```
1  text margin edge

2  date pagenumber MARK TEXT COMMAND

3  date pagenumber MARK TEXT COMMAND

4  date pagenumber MARK TEXT COMMAND

5  date pagenumber MARK TEXT COMMAND
```

```
\setupforms [...,*...,...]
```

```
* method = XML HTML PDF
  export  = yes no
```

`\setupformula [...1,...] [...2...,...]`

```

1  NAME
2  location      = left right
    align        = left middle right flushleft center flushright normal
    strut        = yes no
    distance     = DIMENSION
    left         = COMMAND
    right        = COMMAND
    spacebefore  = inherits: \blank
    spaceafter   = inherits: \blank
    numbercommand = CD:ONEARGUMENT
    color        = COLOR
    numberstyle  = STYLE COMMAND
    numbercolor  = COLOR
    option       = middle
    margin       = yes no standard DIMENSION
    leftmargin   = DIMENSION
    rightmargin  = DIMENSION
    alternative  = NAME
    indentnext   = yes no auto
    grid         = inherits: \suptogrid
    inherits: \setupcounter

```

`\setupframed [...1,...] [...2...,...]`

```

1  NAME
2  corner          = rectangular round NUMBER
    framecorner    = rectangular round NUMBER
    backgroundcorner = rectangular round NUMBER
    radius         = DIMENSION
    frameradius    = DIMENSION
    backgroundradius = DIMENSION
    depth          = DIMENSION
    frameddepth    = DIMENSION
    backgrounddepth = DIMENSION
    framecolor     = COLOR
    topframe       = on off NAME
    bottomframe    = on off NAME
    leftframe      = on off NAME
    rightframe     = on off NAME
    region         = yes no
    rulethickness  = DIMENSION
    frameoffset    = DIMENSION
    frame          = on off overlay none
    background     = foreground color NAME
    backgroundoffset = frame DIMENSION
    component      = NAME
    extras         = COMMAND
    foregroundstyle = STYLE COMMAND
    foregroundcolor = COLOR
    setups         = NAME
    offset         = default overlay none DIMENSION
    width          = local fit max broad fixed DIMENSION
    height         = fit max broad DIMENSION
    align          = inherits: \setupalign
    strut          = yes no none local global
    autostrut      = yes no
    location       = height depth high low top middle bottom line lohi hanging keep mathematics normal
    autowidth      = yes no force
    lines          = NUMBER
    top            = COMMAND
    bottom         = COMMAND
    blank          = yes no
    profile        = NAME
    empty          = yes no
    loffset        = DIMENSION
    roffset        = DIMENSION
    toffset        = DIMENSION
    boffset        = DIMENSION
    orientation    = NUMBER

```

`\setupframedcontent [...1,...] [...2...,...]`

1 NAME

2 left = COMMAND  
right = COMMAND  
leftoffset = DIMENSION  
rightoffset = DIMENSION  
topoffset = DIMENSION  
bottomoffset = DIMENSION  
linecorrection = yes no  
inherits: \setupframed

`\setupframedtext [...1,...] [...2...,...]`

1 NAME

2 left = COMMAND  
right = COMMAND  
inner = COMMAND  
location = left right middle none  
depthcorrection = on off  
bodyfont = inherits: \setupbodyfont  
indenting = inherits: \setupindenting  
style = STYLE COMMAND  
color = COLOR  
inherits: \setupframedinherits: \setupplacement

`\setupglobalreferenceprefix [...*]`

\* + - TEXT

`\setuphead [...1,...] [...2,...]`

```

1 SECTION
2 frontpartlabel      = NAME
  bodypartlabel       = NAME
  appendixlabel       = NAME
  backpartlabel       = NAME
  expansion           = yes no xml
  catcodes            = NAME
  sectionresetset     = NAME
  sectionseparatorset = NAME
  sectionconversionset = NAME
  conversion          = NAME
  sectionstarter      = COMMAND PROCESSOR->COMMAND
  sectionstopper      = COMMAND PROCESSOR->COMMAND
  sectionset          = NAME
  sectionsegments     = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:all SECTION SECTION:SECTION SECTION:* SECTION:all
  referenceprefix     = + - TEXT
  style               = STYLE COMMAND
  color               = COLOR
  textstyle           = STYLE COMMAND
  textcolor           = COLOR
  numberstyle         = STYLE COMMAND
  numbercolor         = COLOR
  coupling            = SECTION
  ownnumber           = yes no
  beforesection       = COMMAND
  aftersection        = COMMAND
  insidesection       = COMMAND
  incrementnumber     = yes no list empty
  placehead           = yes no hidden empty
  number              = yes no
  page                = inherits: \page
  marking             = page reset
  header              =
  header              = start stop high none normal empty nomarking NAME
  text                = start stop high none normal empty nomarking NAME
  footer              = start stop high none normal empty nomarking NAME
  before              = COMMAND
  after               = COMMAND
  inbetween           = COMMAND
  continue            = yes no
  aligntitle          = yes no float
  interlinespace      = NAME
  interaction          = list reference
  internalgrid        = NAME
  grid                = normal standard yes strict tolerant top bottom both broad fit first last high one low
                      none line strut box min max middle NAME
  align               = inherits: \setupalign
  tolerance           = inherits: \setuptolerance
  strut               = yes no
  hang                = line broad fit none NUMBER
  margin              = DIMENSION
  indentnext          = yes no auto
  alternative          = text paragraph normal margin inmargin top middle bottom reverse NAME
  width               = DIMENSION
  numberwidth         = DIMENSION
  textwidth           = DIMENSION
  distance            = DIMENSION
  commandbefore       = COMMAND
  commandafter        = COMMAND
  command             = CD:TWOARGUMENTS
  textcommand         = CD:ONEARGUMENT
  deeptextcommand     = CD:ONEARGUMENT
  numbercommand       = CD:ONEARGUMENT
  deepnumbercommand   = CD:ONEARGUMENT

```

`\setupheadalternative [...1,...] [...2,...]`

```

1 NAME
2 alternative      = horizontal vertical
  renderingsetup  = NAME

```

`\setupheader [...1] [...2,...]`

```

1 text margin edge
2 inherits: \setuplayoutelement

```

`\setupheadertexts [...1] [...2] [...3] [...4] [...5]`

```
1 text margin edge
2 date pagenumber MARK TEXT COMMAND
3 date pagenumber MARK TEXT COMMAND
4 date pagenumber MARK TEXT COMMAND
5 date pagenumber MARK TEXT COMMAND
```

`\setupheadnumber [...1] [...2]`

```
1 SECTION
2 [-+]NUMBER
```

`\setupheadtext [...1] [...,2...]`

```
1 LANGUAGE
2 KEY = VALUE
```

`\setuphelp [...,1...] [...,2...]`

```
1 NAME
2 inherits: \setupframed
```

`\setuphigh [...,1...] [...,2...]`

```
1 NAME
2 distance = DIMENSION
  up       = DIMENSION
  style    = STYLE COMMAND
  color    = COLOR
```

`\setuphighlight [...,1...] [...,2...]`

```
1 NAME
2 command = yes no
  style   = STYLE COMMAND
  color   = COLOR
```

`\setuphyphenation [...,*...]`

```
* method = original tex default hyphenate expanded traditional none
```

`\setuphyphenmark [...,*...]`

```
* sign = normal wide
```

`\setupindentedtext [...,1...] [...,2...]`

```
1 NAME
2 before = COMMAND
  after  = COMMAND
  distance = DIMENSION
  sample = TEXT
  text   = TEXT
  width  = fit broad DIMENSION
  separator = COMMAND
  style   = STYLE COMMAND
  color   = COLOR
  headstyle = STYLE COMMAND
  headcolor = COLOR
```

`\setupindenting [...,*...]`

```
* [-+]small [-+]medium [-+]big none no not first next yes always never odd even normal reset toggle DIMENSION NAME
```

`\setupindex [...1,...] [...2...]`

1 NUMBER  
2 inherits: \setupregister

`\setupinitial [...1,...] [...2...]`

1 NAME  
2 n = NUMBER  
m = NUMBER  
before = COMMAND  
distance = DIMENSION  
hoffset = DIMENSION  
voffset = line DIMENSION  
style = STYLE COMMAND  
color = COLOR  
font = FONT  
text = TEXT  
location = margin text  
method = first last auto none

`\setupinsertion [...1,...] [...2...]`

1 NAME  
2 location = page text columns firstcolumn lastcolumn

`\setupinteractionbar [...1,...] [...2...]`

1 NAME  
2 alternative = a b c d e f g  
state = start stop  
command = CSNAME  
width = DIMENSION  
height = DIMENSION max broad  
depth = DIMENSION max  
distance = DIMENSION  
step = small medium big  
backgroundcolor = COLOR  
style = STYLE COMMAND  
color = COLOR  
contrastcolor = COLOR  
symbol = yes no  
inherits: \setupframed

`\setupinteractionmenu [...1,...] [...2...]`

1 NAME  
2 alternative = vertical horizontal hidden  
category = NAME  
leftoffset = overlay frame none default DIMENSION  
rightoffset = overlay frame none default DIMENSION  
topoffset = overlay frame none default DIMENSION  
bottomoffset = overlay frame none default DIMENSION  
maxwidth = DIMENSION  
maxheight = DIMENSION  
itemalign = left middle right flushleft flushright low high lohi  
state = start empty local  
left = COMMAND  
right = COMMAND  
distance = overlay DIMENSION  
before = COMMAND  
after = COMMAND  
inbetween = COMMAND  
position = yes no  
middle = COMMAND  
style = STYLE COMMAND  
color = COLOR  
samepage = yes no empty none normal default  
contrastcolor = COLOR  
inherits: \setupframed

\setupinteractionscreen [...,\*...]

\* width = fit max tight DIMENSION  
height = fit max tight DIMENSION  
backspace = DIMENSION  
horoffset = DIMENSION  
veroffset = DIMENSION  
topspace = DIMENSION  
option = fit max singlesided doublesided bookmark auto none default fixed landscape portrait page paper  
copies = NUMBER  
delay = none NUMBER

\setupinteraction [...,<sup>1</sup>...] [...,<sup>2</sup>...]

1 NAME  
2 state = start stop  
style = STYLE COMMAND  
color = COLOR  
contrastcolor = COLOR  
title = TEXT  
subtitle = COLOR  
author = TEXT  
date = TEXT  
keyword = TEXT  
focus = standard frame width minwidth height minheight fit tight  
menu = on off  
fieldlayer = auto NAME  
calculate = REFERENCE  
click = yes no  
display = normal new  
page = yes no page name auto  
openaction = REFERENCE  
closeaction = REFERENCE  
openpageaction = REFERENCE  
closepageaction = REFERENCE  
symbolset = NAME  
height = DIMENSION  
depth = DIMENSION  
focusoffset = DIMENSION

\setupinteraction [...]

\* NAME

\setupinterlinespace [...,<sup>1</sup>...] [...,<sup>2</sup>...]

1 NAME  
2 line = DIMENSION  
height = NUMBER  
depth = NUMBER  
minheight = NUMBER  
mindepth = NUMBER  
distance = DIMENSION  
top = NUMBER height  
bottom = NUMBER  
stretch = NUMBER  
shrink = NUMBER

\setupinterlinespace [...,\*...]

\* on off reset auto small medium big NUMBER DIMENSION

\setupinterlinespace [...]

\* NAME

\setupitaliccorrection [...,\*...]

\* text always global none



`\setupitemgroup [...]1 [...]2,... [...]3,... [...]4,...=...]`

1 NAME

2 each NUMBER

3 intro random continue packed autointro broad text before after nowwhite margin inmargin atmargin intext loose fit  
nofit paragraph joinedup serried stopper unpacked repeat norepeat reverse columns one two three four five six  
seven eight nine standard NUMBER\*broad NUMBER\*serried horizontal NAME

4 before = COMMAND  
after = COMMAND  
inbetween = COMMAND  
beforehead = COMMAND  
afterhead = COMMAND  
lefttext = COMMAND  
righttext = COMMAND  
left = COMMAND  
right = COMMAND  
factor = NUMBER  
step = DIMENSION  
width = DIMENSION  
distance = DIMENSION  
margin = yes no standard DIMENSION  
leftmargin = yes no standard DIMENSION  
rightmargin = yes no standard DIMENSION  
align = inherits: \setupalign  
indenting =  
start = NUMBER  
symalign = left middle right flushleft center flushright  
symbol = NAME  
n = NUMBER  
indentnext = yes no auto  
inner = COMMAND  
command = CSNAME  
items = NUMBER  
maxwidth = DIMENSION  
itemalign = left right middle flushleft flushright inner outer  
alignsymbol = yes no  
textdistance = small medium big none space DIMENSION  
placestopper = yes no  
style = STYLE COMMAND  
color = COLOR  
headstyle = STYLE COMMAND  
headcolor = COLOR  
marstyle = STYLE COMMAND  
marcolor = COLOR  
symstyle = STYLE COMMAND  
symcolor = COLOR  
inherits: \setupcounter

`\setupitemgroup [...1,...] [...2,...,...]`

```

1  NAME NAME:NUMBER

2  before      = COMMAND
   after       = COMMAND
   inbetween   = COMMAND
   beforehead  = COMMAND
   afterhead   = COMMAND
   lefttext    = COMMAND
   righttext   = COMMAND
   left        = COMMAND
   right       = COMMAND
   factor      = NUMBER
   step        = DIMENSION
   width       = DIMENSION
   distance    = DIMENSION
   option      = intro random continue packed autointro broad text before after nowwhite margin inmargin atmargin
                intext loose fit nofit paragraph joinedup serried stopper unpacked repeat norepeat reverse
                columns one two three four five six seven eight nine standard NUMBER*broad NUMBER*serried horizontal
                NAME
   margin      = yes no standard DIMENSION
   leftmargin  = yes no standard DIMENSION
   rightmargin = yes no standard DIMENSION
   align       = inherits: \setupalign
   indenting   =
   start       = NUMBER
   symalign    = left middle right flushleft center flushright
   symbol      = NAME
   n          = NUMBER
   indentnext  = yes no auto
   inner       = COMMAND
   command     = CSNAME
   items       = NUMBER
   maxwidth    = DIMENSION
   itemalign   = left right middle flushleft flushright inner outer
   alignsymbol = yes no
   textdistance = small medium big none space DIMENSION
   placestopper = yes no
   style       = STYLE COMMAND
   color       = COLOR
   headstyle   = STYLE COMMAND
   headcolor   = COLOR
   marstyle    = STYLE COMMAND
   marcolor    = COLOR
   symstyle    = STYLE COMMAND
   symcolor    = COLOR
   inherits: \setupcounter

```

`\setupitems [...1,...] [...2,...,...]`

```

1  NAME

2  alternative = left right top bottom inmargin
   textwidth  = DIMENSION
   width      = DIMENSION
   distance   = DIMENSION
   symbol     = none NAME
   align      = left middle right flushleft flushright inner outer margin
   textalign  = left middle right flushleft flushright inner outer
   n         = NUMBER
   before     = COMMAND
   after      = COMMAND
   inbetween  = COMMAND

```

`\setuplabel [...1,...] [...2...]`

```

1  NAME
2  title      = yes no
   number     = yes no
   numbercommand = CD:ONEARGUMENT
   titledistance = DIMENSION
   titlestyle  = STYLE COMMAND
   titlecolor  = COLOR
   titlecommand = CD:ONEARGUMENT
   titleleft   = COMMAND
   titleright  = COMMAND
   left        = COMMAND
   right       = COMMAND
   symbol      = COMMAND
   starter     = COMMAND
   stopper     = COMMAND
   coupling    = NAME
   counter     = NAME
   level       = NUMBER
   text        = TEXT
   headcommand = CD:ONEARGUMENT
   before      = COMMAND
   after       = COMMAND
   inbetween   = COMMAND
   alternative  = left right inmargin inleft inright margin leftmargin rightmargin innermargin outermargin serried
                  hanging top command intext NAME
   align       = inherits: \setupalign
   headalign   = inherits: \setupalign
   indenting   = inherits: \setupindenting
   display     = yes no
   indentnext  = yes no auto
   width       = fit broad line DIMENSION
   distance    = none DIMENSION
   hang        = fit broad none margin NUMBER
   closesymbol = COMMAND
   closecommand = CD:ONEARGUMENT
   expansion   = yes no xml
   sample      = TEXT
   margin      = yes no standard DIMENSION
   style       = STYLE COMMAND
   color       = COLOR
   headstyle   = STYLE COMMAND
   headcolor   = COLOR
   inherits: \setupcounter

```

`\setuplabeltext [...1] [...2...]`

```

1  LANGUAGE
2  KEY = VALUE

```

`\setuplabeltext [...1] [...2...]`

```

1  LANGUAGE
2  KEY = VALUE

```

`\setuplanguage [...]1 [...,...2...,...]`

```

1  LANGUAGE default
2  default          = LANGUAGE
   state           = start stop
   date            = inherits: \currentdate
   patterns        = FILE
   factor          = yes no
   lefthyphenmin   = NUMBER
   righthyphenmin   = NUMBER
   lefthyphenchar   = NUMBER
   righthyphenchar  = NUMBER
   setups          = NAME
   spacing         = broad packed
   font            = auto
   text            = TEXT
   limitttext      = TEXT
   hyphen          = TEXT
   compoundhyphen   = TEXT
   leftcompoundhyphen = TEXT
   rightcompoundhyphen = TEXT
   leftquote       = COMMAND
   rightquote      = COMMAND
   leftquotation    = COMMAND
   rightquotation   = COMMAND
   leftspeech      = COMMAND
   rightspeech     = COMMAND
   leftsentence    = COMMAND
   middlespeech    = COMMAND
   rightsentence   = COMMAND
   midsentence     = COMMAND
   leftsubsentence = COMMAND
   rightsubsentence = COMMAND

```

`\setupplayer [...]1,... [...,...2...,...]`

```

1  NAME
2  state          = start stop continue next repeat
   option         = test
   page           = NUMBER
   width          = DIMENSION
   height         = DIMENSION
   region         = NAME
   rotation       = left right inner outer NUMBER
   position       = yes no overlay
   hoffset        = max DIMENSION
   voffset        = max DIMENSION
   offset         = DIMENSION
   dx             = DIMENSION
   dy             = DIMENSION
   sx             = NUMBER
   sy             = NUMBER
   x              = DIMENSION
   y              = DIMENSION
   corner         = left middle right top bottom
   location       = grid left middle right top bottom line l c r m t b g
   line           = NUMBER
   column         = NUMBER
   direction      = normal reverse
   doublesided    = yes no
   method         = fit overlay
   repeat         = yes
   preset         = lefttop righttop leftbottom rightbottom middle middletop middlebottom middleleft middleright
                  lefttopleft lefttopright NAME

```

`\setuplayeredtext [...]1,... [...,...2...,...]`

```

1  NAME
2  style = STYLE COMMAND
   color = COLOR
   inherits: \setupframed

```

`\setuplayouttext` [<sup>1</sup>...] [<sup>2</sup>...] [...,<sup>3</sup>...,...]

```

1 top header text footer bottom
2 text margin edge
3 state      = start stop empty high none normal nomarking NAME
  style      = STYLE COMMAND
  color      = COLOR
  strut      = yes no
  n          = NUMBER
  before     = COMMAND
  after      = COMMAND
  leftstyle  = STYLE COMMAND
  rightstyle = STYLE COMMAND
  leftcolor  = COLOR
  rightcolor = COLOR
  width      = DIMENSION
  leftwidth  = DIMENSION
  rightwidth = DIMENSION

```

`\setuplayout` [<sup>1</sup>...] [...,<sup>2</sup>...,...]

```

1 NAME
2 state      = start stop normal repeat
  margin     = DIMENSION
  edge       = DIMENSION
  margindistance = DIMENSION
  edgedistance = DIMENSION
  leftedgedistance = DIMENSION
  rightedgedistance = DIMENSION
  leftmargindistance = DIMENSION
  rightmargindistance = DIMENSION
  topdistance = DIMENSION
  headerdistance = DIMENSION
  footerdistance = DIMENSION
  bottomdistance = DIMENSION
  preset      = NAME
  leftmargin  = DIMENSION
  rightmargin = DIMENSION
  leftedge    = DIMENSION
  rightedge   = DIMENSION
  header      = DIMENSION
  footer      = DIMENSION
  top         = DIMENSION
  bottom      = DIMENSION
  backspace   = DIMENSION
  topspace    = DIMENSION
  setups      = NAME
  cutspace    = DIMENSION
  width       = DIMENSION middle fit
  bottomspace = DIMENSION
  lines       = NUMBER
  height      = DIMENSION middle fit
  horoffset   = DIMENSION
  veroffset   = DIMENSION
  columns     = NUMBER
  columndistance = DIMENSION
  method      = default normal NAME
  location    = left middle right top bottom singlesided doublesided
  textwidth   = DIMENSION
  textheight  = DIMENSION
  nx          = NUMBER
  ny          = NUMBER
  dx          = DIMENSION
  dy          = DIMENSION
  scale       = NUMBER
  sx          = NUMBER
  sy          = NUMBER
  marking     = on off page empty color
  grid        = yes no off
  textdistance = DIMENSION
  alternative  = default normal makeup NAME
  clipoffset  = DIMENSION
  cropoffset  = DIMENSION
  trimoffset  = DIMENSION
  bleedoffset = DIMENSION
  artoffset   = DIMENSION

```

`\setuplayout [...]`

\* reset NAME

`\setuplegend [...,..1...,...]`

\* inherits: \setuppairedbox

`\setuplinenote [...,1...] [...,..2...,...]`

1 NAME

2 compress = yes no  
compressmethod = separator stopper space  
compressseparator = COMMAND  
compressdistance = DIMENSION  
inherits: \setupnote

`\setuplinenumbering [...,1...] [...,..2...,...]`

1 NAME

2 start = NUMBER  
step = NUMBER  
method = page first next  
conversion = NAME  
continue = yes no  
location = text begin end default left right inner outer inleft inright margin inmargin  
distance = DIMENSION  
align = inner outer flushleft flushright left right middle auto  
command = CD:ONEARGUMENT  
left = COMMAND  
right = COMMAND  
margin = DIMENSION  
width = margin DIMENSION  
style = STYLE COMMAND  
color = COLOR

`\setuplines [...,1...] [...,..2...,...]`

1 NAME

2 option = packed  
before = COMMAND  
after = COMMAND  
inbetween = COMMAND  
indenting = inherits: \setupindenting  
align = inherits: \setupalign  
space = yes on off fixed default  
command = COMMAND  
style = STYLE COMMAND  
color = COLOR  
left = COMMAND  
right = COMMAND

```
\setuplinetable [...]1 [...]2 [...,...]3 [...,...]
```

```
1 r c
```

```
2 odd even header NUMBER
```

```
3 lines          = fit NUMBER
  before         = COMMAND
  after          = COMMAND
  inbetween      = COMMAND
  stretch       = yes no DIMENSION
  maxwidth       = fit DIMENSION
  nleft          = NUMBER
  n              = NUMBER
  repeat         = yes no
  nx             = NUMBER
  width          = DIMENSION
  height         = fit line DIMENSION
  distance       = DIMENSION
  leftoffset     = DIMENSION
  rightoffset    = DIMENSION
  align          = inherits: \setupalign
  background     = color
  backgroundcolor = COLOR
  xheight        = max DIMENSION
  xdepth         = max DIMENSION
  style          = STYLE COMMAND
  color          = COLOR
```

```
\setuplinewidth [...]
```

```
* small medium big DIMENSION
```

\setuplist [...,<sup>1</sup>...] [...,<sup>2</sup>...]

```

1  LIST
2  state           = start stop
   location        = none here
   type            = simple command userdata
   criterium       = local intro reference SECTIONBLOCK:reference all SECTIONBLOCK:all text SECTIONBLOCK:text
                   current SECTIONBLOCK:current here previous SECTIONBLOCK:previous component SECTION
                   SECTIONBLOCK:SECTION
   list            = NAME
   width           = fit broad auto DIMENSION
   height          = fit broad DIMENSION
   depth           = fit broad DIMENSION
   symbol          = one two three none default
   label           = yes no none NAME
   starter         = COMMAND
   stopper         = COMMAND
   command         = CD:THREEARGUMENT
   numbercommand   = CD:ONEARGUMENT
   textcommand     = CD:ONEARGUMENT
   pagecommand     = CD:ONEARGUMENT
   pagenumber      = yes no always
   headnumber      = yes no always
   before          = COMMAND
   after           = COMMAND
   inbetween       = COMMAND
   margin          = none DIMENSION
   distance        = none DIMENSION
   aligntitle      = yes no
   numberalign     = left right middle flushleft flushright inner outer
   align           = inherits: \setupalign
   hang            = yes no
   left            = COMMAND
   right           = COMMAND
   interaction     = yes no all number text title page sectionnumber pagenumber
   limittext       = yes no TEXT
   style           = STYLE COMMAND
   color           = COLOR
   numberstyle     = STYLE COMMAND
   numbercolor     = COLOR
   textstyle       = STYLE COMMAND
   textcolor       = COLOR
   pagestyle       = STYLE COMMAND
   pagecolor       = COLOR
   reference       = NUMBER
   extras          = NAME
   order           = command all title
   alternative     = a b c d e f g left right top bottom command none interactive paragraph horizontal
                   vertical NAME
   maxwidth        = DIMENSION
   pageprefix      = yes no
   pageprefixseparatorset = NAME
   pageprefixconversionset = NAME
   pageprefixset   = NAME
   pageprefixsegments = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:all SECTION SECTION:SECTION SECTION:* SECTION:all
   pageprefixconnector = COMMAND PROCESSOR->COMMAND
   pageconversionset = NAME
   pagestarter     = COMMAND PROCESSOR->COMMAND
   pagestopper     = COMMAND PROCESSOR->COMMAND
   inherits: \setupcounterinherits: \setupframed

```

\setuplistalternative [...,<sup>1</sup>...] [...,<sup>2</sup>...]

```

1  NAME
2  before          = COMMAND
   after           = COMMAND
   command         = CD:THREEARGUMENTS
   renderingsetup  = NAME
   width           = DIMENSION
   distance        = DIMENSION
   stretch        = DIMENSION
   filler          = COMMAND

```



`\setuplistextra [...,1...] [...,2...,...]`

1 NAME  
2 before = COMMAND  
after = COMMAND

`\setuplocalfloats [...,*...,...]`

\* before = COMMAND  
after = COMMAND  
inbetween = COMMAND

`\setuplocalinterlinespace [...,1...] [...,2...,...]`

1 NAME  
2 inherits: \setupinterlinespace

`\setuplocalinterlinespace [...,*...]`

\* on off reset auto small medium big NUMBER DIMENSION

`\setuplocalinterlinespace [...*...]`

\* NAME

`\setuplow [...,1...] [...,2...,...]`

1 NAME  
2 distance = DIMENSION  
down = DIMENSION  
style = STYLE COMMAND  
color = COLOR

`\setuplowhigh [...,1...] [...,2...,...]`

1 NAME  
2 distance = DIMENSION  
up = DIMENSION  
down = DIMENSION  
style = STYLE COMMAND  
color = COLOR

`\setuplowmidhigh [...,1...] [...,2...,...]`

1 NAME  
2 up = DIMENSION  
down = DIMENSION  
style = STYLE COMMAND  
color = COLOR

`\setupMPgraphics [...,*...,...]`

\* color = local global  
mpy = FILE

`\setupMPinstance [...,1...] [...,2...,...]`

1 NAME  
2 format = metafun mpost  
initializations = yes no  
setups = NAME  
textstyle = STYLE COMMAND  
textcolor = COLOR  
extensions = yes no  
method = binary decimal double scaled default

```
\setupMPpage [...1...*...]
```

```
* inherits: \setupfittingpage
```

```
\setupMPvariables [...1] [...2...]
```

```
1 NAME
```

```
2 KEY = VALUE
```

```
\setupmakeup [...1...] [...2...]
```

```
1 NAME
```

```
2 page      = inherits: \page
  command   = COMMAND
  width      = DIMENSION
  height     = DIMENSION
  align      = inherits: \setupalign
  setups     = NAME
  top        = COMMAND
  bottom     = COMMAND
  before     = COMMAND
  after      = COMMAND
  location   = top
  reference  = REFERENCE
  pagestate  = start stop
  headerstate = start stop high empty none normal
  footerstate = start stop high empty none normal
  topstate   = start stop high empty none normal
  bottomstate = start stop high empty none normal
  textstate  = start stop high empty none normal
  doublesided = yes no empty
  style      = inherits: \value-style
  color      = COLOR
```

```
\setupmarginblock [...1...] [...2...]
```

```
1 NAME
```

```
2 state      = start stop
  width      = DIMENSION
  before     = COMMAND
  after      = COMMAND
  inbetween  = COMMAND
  align      = inherits: \setupalign
  style      = STYLE COMMAND
  color      = COLOR
  top        = COMMAND
  bottom     = COMMAND
  location   = left right middle inmargin
  left       = COMMAND
  right      = COMMAND
```

`\setupmargindata [...1,...] [...2,...]`

```
1 NAME
2 strut      = yes no auto cap fit line default CHARACTER
  command    = CD:ONEARGUMENT
  width      = DIMENSION
  align      = inherits: \setupalign
  anchor     = region text
  location   = left right inner outer
  method     = top line first depth height
  category   = default edge
  scope      = local global
  option     = text paragraph
  margin     = local normal margin edge
  distance   = DIMENSION
  hoffset    = DIMENSION
  voffset    = DIMENSION
  dy         = DIMENSION
  bottomspace = DIMENSION
  threshold  = DIMENSION
  line       = NUMBER
  stack      = yes continue
  style      = STYLE COMMAND
  color      = COLOR
```

`\setupmarginframed [...1,...] [...2,...]`

```
1 NAME
2 inherits: \setupframed
```

`\setupmarginrule [...1] [...2,...]`

```
1 NUMBER
2 inherits: \setupsidebar
```

`\setupmarginrules [...1] [...2,...]`

```
1 NUMBER
2 inherits: \setupmarginrule
```

`\setupmarking [...1,...] [...2,...]`

```
1 MARK
2 state      = start stop
  expansion  = yes no
  separator  = COMMAND
  filtercommand = CD:ONEARGUMENT
```

`\setupmathalignment [...1,...] [...2,...]`

```
1 NAME
2 n          = NUMBER
  m          = NUMBER
  distance   = DIMENSION
  align      = left middle right normal
```

`\setupmathcases [...1,...] [...2,...]`

```
1 NAME
2 left       = COMMAND
  right      = COMMAND
  strut      = yes no
  style      = STYLE COMMAND
  distance   = DIMENSION
  numberdistance = DIMENSION
```

`\setupmathematics [...1,...] [...2,...]`

```

1  NAME

2  openup           = yes no
   symbolset       = NAME
   functionstyle    = STYLE COMMAND
   compact         = yes no
   align           = l2r r2l
   bidi           = yes no
   sygreek         = normal italic none
   lcgreek         = normal italic none
   ucgreek         = normal italic none
   italics         = 1 2 3 4 none reset
   autopunctuation = yes no all
   setups          = NAME
   domain          = NAME reset
   textstyle       = STYLE COMMAND
   textcolor       = COLOR
   functioncolor   =
   integral        = limits nolimits autolimits displaylimits none
   stylealternative = LIST
   default         = normal italic

```

`\setupmathfence [...1,...] [...2,...]`

```

1  NAME

2  command = yes no
   left    = NUMBER
   middle  = NUMBER
   right   = NUMBER
   mathstyle = display text script scriptscript cramped uncramped normal packed small big
   color    = COLOR
   state    = auto

```

`\setupmathfraction [...1,...] [...2,...]`

```

1  NAME

2  topdistance    = DIMENSION
   bottomdistance = DIMENSION
   margin        = DIMENSION
   color         = COLOR
   strut         = yes no math tight
   alternative    = inner outer both
   rule          = yes no auto
   left          = NUMBER
   right         = NUMBER
   rulethickness = DIMENSION
   mathstyle     = STYLE COMMAND
   distance      = no none overlay

```

`\setupmathframed [...1,...] [...2,...]`

```

1  NAME

2  inherits: \setupframed

```

`\setupmathlabeltext [...1] [...2,...]`

```

1  LANGUAGE

2  KEY = VALUE

```

`\setupmathmatrix [...1,...] [...2,...]`

```

1  NAME

2  left    = COMMAND
   right   = COMMAND
   strut   = yes no NUMBER
   align   = left middle right normal
   style   = STYLE COMMAND
   distance = DIMENSION
   location = top bottom high low lohi normal

```

`\setupmathornament [...1,...] [...2.,...]`

```
1  NAME
2  alternative = mp
   color      = COLOR
   mppoffset  = DIMENSION
   mp         = NAME
```

`\setupmathradical [...1,...] [...2.,...]`

```
1  NAME
2  alternative = default normal mp
   color      = COLOR
   mppoffset  = DIMENSION
   mp         = NAME
```

`\setupmathstackers [...1,...] [...2.,...]`

```
1  NAME
2  left        = COMMAND
   right       = COMMAND
   topcommand  = CD:ONEARGUMENT
   bottomcommand = CD:ONEARGUMENT
   middlecommand = CD:ONEARGUMENT
   mp          = NAME
   mpheight    = DIMENSION
   mpdepth     = DIMENSION
   mppoffset   = DIMENSION
   color       = COLOR
   hoffset     = DIMENSION
   voffset     = DIMENSION
   minheight   = DIMENSION
   mindepth    = DIMENSION
   mathclass   = rel ord
   offset      = min max normal
   location    = top bottom high low middle NUMBER
   strut       = yes no
   alternative = normal default mp
   minwidth    = DIMENSION
   distance    = DIMENSION
   moffset     = DIMENSION
   order       = normal reverse
   mathlimits  = yes no
```

`\setupmathstyle [...*,...]`

\* display text script scriptscript cramped uncramped normal packed small big NAME

`\setupmixedcolumns [...1,...] [...2.,...]`

```
1  NAME
2  grid          = inherits: \setupgrid
   rulethickness = DIMENSION
   method        = otr box
   before        = COMMAND
   after         = COMMAND
   distance      = DIMENSION
   n             = NUMBER
   maxheight     = DIMENSION
   maxwidth      = DIMENSION
   step          = DIMENSION
   profile       = NAME
   align         = inherits: \setupalign
   setups        = NAME
   balance       = yes no
   splitmethod   = none fixed
   alternative    = local global
   internalgrid  = line halfline
   separator     = rule
   strut         = yes no
   color         = COLOR
   rulecolor     = COLOR
   direction     = normal reverse
   inherits:    \setupframed
```

`\setupmodule [...]1 [...,...2...,...]`

```
1  FILE
2  test  = yes no
    KEY  = VALUE
```

`\setupnarrower [...]1,... [...,...2...,...]`

```
1  NAME
2  left   = DIMENSION
    middle = DIMENSION
    right  = DIMENSION
    default = [-+]left [-+]middle [-+]right NUMBER*left NUMBER*middle NUMBER*right reset
    before = COMMAND
    after  = COMMAND
```

`\setupnotation [...]1,... [...,...2...,...]`

```
1  NAME
2  title      = yes no
    number    = yes no
    type      = note
    numbercommand = CD:ONEARGUMENT
    titledistance = DIMENSION
    titlestyle  = STYLE COMMAND
    titlecolor  = COLOR
    titlecommand = CD:ONEARGUMENT
    titleleft   = COMMAND
    titleright  = COMMAND
    left        = COMMAND
    right       = COMMAND
    symbol      = COMMAND
    starter     = COMMAND
    stopper     = COMMAND
    coupling    = NAME
    counter     = NAME
    level       = NUMBER
    text        = TEXT
    headcommand = CD:ONEARGUMENT
    before      = COMMAND
    after       = COMMAND
    inbetween   = COMMAND
    alternative  = left right inmargin inleft inright margin leftmargin rightmargin innermargin outermargin serried
                  hanging top command note NAME
    align       = inherits: \setupalign
    headalign   = inherits: \setupalign
    indenting   = inherits: \setupindenting
    display     = yes no
    indentnext  = yes no auto
    width       = fit broad line DIMENSION
    distance    = none DIMENSION
    hang        = fit broad none margin NUMBER
    closesymbol = COMMAND
    closecommand = CD:ONEARGUMENT
    expansion   = yes no xml
    sample      = TEXT
    margin      = yes no standard DIMENSION
    style       = STYLE COMMAND
    color       = COLOR
    headstyle   = STYLE COMMAND
    headcolor   = COLOR
    inherits: \setupcounter
```

`\setupnote [...1,...] [...2,...]`

```
1  NAME

2  interaction      = yes no number text all
   symbolcommand   = CD:ONEARGUMENT
   textcommand     = CD:ONEARGUMENT
   indicator       = yes no
   textseparator   = COMMAND
   width           = DIMENSION
   height          = DIMENSION
   distance        = DIMENSION
   rulecommand     = COMMAND
   rule            = on off normal left right command paragraph
   split           = tolerant strict verystrict NUMBER
   factor          = NUMBER
   location        = text page high bottom none columns firstcolumn lastcolumn
   next            = COMMAND
   n               = NUMBER
   rulecolor       = COLOR
   rulethickness   = DIMENSION
   setups          = NAME
   interlinespace  = NAME
   paragraph       = yes no
   before          = COMMAND
   after           = cd.command
   inbetween       = COMMAND
   scope           = page
   columndistance = DIMENSION
   continue        = yes no
   alternative     = grid fixed columns note none
   criterium       = page
   bodyfont        = inherits: \setupbodyfont
   align           = inherits: \setupalign
   textstyle       = STYLE COMMAND
   textcolor       = COLOR
   anchor          = next
   inherits: \setupframed
```

`\setupoffset [...*,...]`

\* inherits: \setupoffsetbox

`\setupoffsetbox [...*,...]`

```
*  x      = DIMENSION
   y      = DIMENSION
   leftoffset = DIMENSION
   rightoffset = DIMENSION
   topoffset  = DIMENSION
   bottomoffset = DIMENSION
   method    = fixed
   width     = DIMENSION
   height    = DIMENSION
   depth     = DIMENSION
   location  = left middle right top bottom line l c r m t b g
```

`\setupoperatortext [...1] [...2,...]`

```
1  LANGUAGE
2  KEY = VALUE
```

`\setupoppositeplacing [...*,...]`

```
*  state    = start stop
   before   = COMMAND
   after    = COMMAND
   inbetween = COMMAND
```

`\setupoutputroutine [...1] [...2,...]`

```
1  NAME
2  KEY = CSNAME
```

`\setupoutputroutine [...]`

\* NAME

`\setuppagechecker [...1,...] [...2,...,...]`

1 NAME

2 lines = NUMBER  
offset = DIMENSION  
method = 0 1 2 3  
before = COMMAND  
after = COMMAND  
inbetween = COMMAND

`\setuppagecomment [...,*...,...]`

\* location = left right top bottom none  
state = start stop none  
offset = DIMENSION  
distance = DIMENSION  
width = DIMENSION  
height = DIMENSION

`\setuppagegrid [...1,...] [...2,...,...]`

1 NAME

2 n = NUMBER  
nleft = NUMBER  
nright = NUMBER  
width = DIMENSION auto  
distance = DIMENSION  
lines = NUMBER  
maxwidth = DIMENSION  
maxheight = DIMENSION  
direction = normal reverse  
page = inherits: \page  
inherits: \setupframed

`\setuppagegridarea [...1,...] [...2,...,...]`

1 NAME

2 state = start stop repeat  
x = NUMBER  
y = NUMBER  
nx = NUMBER  
ny = NUMBER  
style = STYLE COMMAND  
color = COLOR  
clipoffset = DIMENSION  
rightoffset = DIMENSION  
inherits: \setupframed

`\setuppagegridareatext [...1] [...2]`

1 NAME

2 TEXT

`\setuppagegridlines [...1] [...2] [...3] [...4]`

1 NAME

2 NUMBER

3 NUMBER

4 NUMBER



`\setuppagegridspan [...1,...] [...2.,...]`

```
1 NAME
2 n      = NUMBER
  style  = STYLE COMMAND
  color  = COLOR
  before = COMMAND
  after  = COMMAND
  inherits: \setupframed
```

`\setuppagegridstart [...1] [...2] [...3] [...4]`

```
1 NAME
2 NUMBER
3 NUMBER
4 NUMBER
```

`\setuppageinjection [...1,...] [...2.,...]`

```
1 NAME
2 state      = previous next NUMBER
  delay      = yes no
  alternative = figure buffer setups none NAME
  page       = inherits: \page
  pagestate  = start stop
  n          = NUMBER
  inherits: \setupframed
```

`\setuppageinjectionalternative [...1,...] [...2.,...]`

```
1 NAME
2 renderingsetup = NAME
```

`\setuppagenumber [...*.,...]`

```
* inherits: \setupuserpagenumber
```

`\setuppagenumbering [...*.,...]`

```
* alternative = singlesided doublesided
  page       = inherits: \page
  strut      = yes no
  command    = CD:ONEARGUMENT
  left       = COMMAND
  right      = COMMAND
  state      = start stop
  width      = DIMENSION
  location   = header footer left middle right inleft inright margin inmargin atmargin marginedge
  style      = STYLE COMMAND
  color      = COLOR
```

`\setuppageshift [...1] [...2] [...3]`

```
1 page paper
2 NAME
3 NAME
```

`\setuppagestate [...*.,...]`

```
* delay = yes no
```

`\setuppagetransitions [...*.]`

```
* reset auto start random NUMBER
```

`\setuppairedbox [...1,...] [...2,...]`

```
1  NAME
2  before    = COMMAND
   after     = COMMAND
   inbetween = COMMAND
   location  = left middle right top bottom high low
   n         = NUMBER
   distance  = DIMENSION
   bodyfont  = inherits: \setupbodyfont
   width     = DIMENSION
   height    = DIMENSION
   maxwidth  = DIMENSION
   maxheight = DIMENSION
   align     = inherits: \setupalign
   style     = STYLE COMMAND
   color     = COLOR
```

`\setuppairedbox [...*,...]`

\* inherits: \setuppairedbox

`\setuppalet [...]`

\* NAME

`\setuppaper [...*,...]`

\* inherits: \setuppapersize

`\setuppapersize [...1,...] [...2,...]`

```
1  reset landscape mirrored negative rotated 90 180 270 NAME
2  reset landscape mirrored negative rotated 90 180 270 NAME
```

`\setuppapersize [...1,...] [...2,...]`

```
1  NAME
2  top      = COMMAND
   bottom   = COMMAND
   left     = COMMAND
   right    = COMMAND
   method   = normal none NAME
   scale    = NUMBER
   nx       = NUMBER
   ny       = NUMBER
   dx       = DIMENSION
   dy       = DIMENSION
   width    = DIMENSION
   height   = DIMENSION
   topspace = DIMENSION
   backspace = DIMENSION
   offset   = DIMENSION
   page     = reset landscape mirrored negative rotated 90 180 270 NAME
   paper    = reset landscape mirrored negative rotated 90 180 270 NAME
   option   = fit max
   distance = DIMENSION
```

`\setupparagraph [...1,...] [...2,...]`

```
1  NAME
2  style    = STYLE COMMAND
   color    = COLOR
   align    = inherits: \setupalign
   setups   = NAME
```

`\setupparagraphintro [...1,...] [...2,...]`

```
1  reset each first next
2  COMMAND
```

`\setupparagraphnumbering [...,..*...,...]`

```
* state      = start stop line reset
distance    = DIMENSION
style       = STYLE COMMAND
color       = COLOR
```

`\setupparagraphs [...1.] [...,2...] [...,3...,...]`

```
1 NAME
2 each NUMBER
3 n          = NUMBER
  before     = COMMAND
  after      = COMMAND
  width      = DIMENSION
  distance   = DIMENSION
  height     = DIMENSION fit
  top        = COMMAND
  bottom     = COMMAND
  align      = inherits: \setupalign
  inner      = COMMAND
  command    = COMMAND
  rule       = on off
  rulethickness = DIMENSION
  rulecolor  = COLOR
  style      = STYLE COMMAND
  color      = COLOR
```

`\setupparagraphs [...1.] [...,2...,...]`

```
1 NAME:NUMBER
2 n          = NUMBER
  before     = COMMAND
  after      = COMMAND
  width      = DIMENSION
  distance   = DIMENSION
  height     = DIMENSION fit
  top        = COMMAND
  bottom     = COMMAND
  align      = inherits: \setupalign
  inner      = COMMAND
  command    = COMMAND
  rule       = on off
  rulethickness = DIMENSION
  rulecolor  = COLOR
  style      = STYLE COMMAND
  color      = COLOR
```

`\setupparallel [...1.] [...,2...] [...,3...,...]`

```
1 NAME
2 NAME
3 setups     = NAME
  start      = NUMBER
  n          = NUMBER
  criterium  = all
```

`\setupperiods [...,*...,...]`

```
* n          = NUMBER
width        = DIMENSION fit
distance     = DIMENSION
symbol       = COMMAND
```

`\setupplacement [...1,...] [...2,...]`

```
1  NAME

2  before      = COMMAND
   after       = COMMAND
   left        = COMMAND
   right       = COMMAND
   grid        = inherits: \suptogrid
   linecorrection = on off
   depthcorrection = on off
   margin      = yes no standard
```

`\setuppositionbar [...*,...]`

```
*  style = STYLE COMMAND
   color = COLOR
   n     = NUMBER
   min   = NUMBER
   max   = NUMBER
   text  = TEXT
   width = DIMENSION
   height = DIMENSION
   depth = DIMENSION
```

`\setuppositioning [...1,...] [...2,...]`

```
1  NAME

2  offset = yes no
   unit   = ex em pt in cm mm sp bp pc dd cc nc
   state  = start overlay
   xoffset = DIMENSION
   yoffset = DIMENSION
   xstep   = absolute relative
   ystep   = absolute relative
   xscale  = NUMBER
   yscale  = NUMBER
   xfactor = NUMBER
   yfactor = NUMBER
   factor  = NUMBER
   scale   = NUMBER
```

`\setupprefixtext [...1,...] [...2,...]`

```
1  LANGUAGE

2  KEY = VALUE
```

`\setupprocessor [...1,...] [...2,...]`

```
1  NAME

2  state = start stop
   left  = COMMAND
   right = COMMAND
   command = CD:ONEARGUMENT
   style  = STYLE COMMAND
   color  = COLOR
```

`\setupprofile [...1,...] [...2,...]`

```
1  NAME

2  height = DIMENSION
   depth  = DIMENSION
   distance = DIMENSION
   factor = NUMBER
   lines  = NUMBER
   method = strict fixed none
```

`\setupprograms [...*,...]`

```
*  style = STYLE COMMAND
   color = COLOR
```

**\setupquotation** [...<sup>\*</sup>...]

\* inherits: \setupdelimitedtext

**\setupquote** [...<sup>\*</sup>...]

\* inherits: \setupdelimitedtext

**\setuprealpagenumber** [...<sup>\*</sup>...]

\* inherits: \setupcounter

**\setupreferenceformat** [...<sup>1</sup>...] [...<sup>2</sup>...]

1 NAME  
2 label = \* NAME  
left = COMMAND  
right = COMMAND  
type = default text title number page realpage  
setups = NAME  
autocase = yes no  
text = TEXT  
style = STYLE COMMAND  
color = COLOR

**\setupreferenceprefix** [...]

\* + - TEXT

**\setupreferencestructureprefix** [...<sup>1</sup>] [...<sup>2</sup>] [...<sup>3</sup>...]

1 NAME SECTION  
2 default  
3 prefix = yes no  
prefixseparatorset = NAME  
prefixconversion = NAME  
prefixconversionset = NAME  
prefixstarter = COMMAND PROCESSOR->COMMAND  
prefixstopper = COMMAND PROCESSOR->COMMAND  
prefixset = NAME  
prefixsegments = NUMBER NUMBER:NUMBER NUMBER:\* NUMBER:all SECTION SECTION:SECTION SECTION:\* SECTION:all  
numberconversion = NAME  
numberconversionset = NAME  
numberstarter = COMMAND PROCESSOR->COMMAND  
numberstopper = COMMAND PROCESSOR->COMMAND  
numbersegments = NUMBER NUMBER:NUMBER NUMBER:\* NUMBER:all  
numberseparatorset = NAME  
prefixconnector = COMMAND PROCESSOR->COMMAND

**\setupreferencing** [...<sup>\*</sup>...]

\* state = start stop  
expansion = yes no xml  
autofile = yes no  
export = yes no  
left = COMMAND  
right = COMMAND  
width = DIMENSION  
doublesided = yes no  
interaction = label text symbol all  
separator = COMMAND  
prefix = + - TEXT

**\setupregister** [...<sup>1</sup>...] [...<sup>2</sup>...]

1 NUMBER  
2 inherits: \setupregister

\setupregister [...,<sup>1</sup>...] [...,<sup>2</sup>...] [...,<sup>3</sup>...,...]

1 NAME

2 NUMBER

3   referencemethod           = forward  
     expansion               = yes no xml  
     ownnumber               = yes no  
     xmlsetup                 = NAME  
     alternative             = a b A B  
     method                  = default before after first last ch mm zm pm mc zc pc uc  
     compress                = yes no all  
     criterium               = local text current previous all SECTION  
     pageprefixseparatorset   = COMMAND  
     pageprefixconversionset  = NAME  
     pageprefixstarter       = COMMAND PROCESSOR->COMMAND  
     pageprefixstopper       = COMMAND PROCESSOR->COMMAND  
     pageprefixset           = NAME  
     pageprefixsegments      = NUMBER NUMBER:NUMBER NUMBER:\* NUMBER:all SECTION SECTION:SECTION SECTION:\* SECTION:all  
     pageprefixconnector     = COMMAND  
     pageprefix              = yes no  
     pageseparatorset        = NAME  
     pageconversionset       = NAME  
     pagestarter             = COMMAND PROCESSOR->COMMAND  
     pagestopper             = COMMAND PROCESSOR->COMMAND  
     pagesegments            = NUMBER NUMBER:NUMBER NUMBER:\* NUMBER:all  
     maxwidth                = DIMENSION  
     indicator               = yes no  
     before                  = COMMAND  
     after                   = COMMAND  
     command                 = CD:ONEARGUMENT  
     textcommand             = CD:ONEARGUMENT  
     deeptextcommand         = CD:ONEARGUMENT  
     pagecommand             = CD:ONEARGUMENT  
     distance                = DIMENSION  
     interaction             = text pagenumber  
     pagenumber              = yes no  
     symbol                  = a n none 1 2 COMMAND  
     language                = default DIN\_5007-1 DIN\_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-sc9 LANGUAGE  
     style                   = STYLE COMMAND  
     color                   = COLOR  
     textstyle               = STYLE COMMAND  
     textcolor               = COLOR  
     pagestyle               = STYLE COMMAND  
     pagecolor               = COLOR  
     n                        = NUMBER  
     balance                 = yes no  
     align                   = inherits: \setupalign  
     numberorder             = numbers

`\setupregister [...]1 [...,...2...,...]`

```
1 NAME:NUMBER
2 referencemethod = forward
  expansion = yes no xml
  ownnumber = yes no
  xmlsetup = NAME
  alternative = a b A B
  method = default before after first last ch mm zm pm mc zc pc uc
  compress = yes no all
  criterium = local text current previous all SECTION
  pageprefixseparatorset = COMMAND
  pageprefixconversionset = NAME
  pageprefixstarter = COMMAND PROCESSOR->COMMAND
  pageprefixstopper = COMMAND PROCESSOR->COMMAND
  pageprefixset = NAME
  pageprefixsegments = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:all SECTION SECTION:SECTION SECTION:* SECTION:all
  pageprefixconnector = COMMAND
  pageprefix = yes no
  pageseparatorset = NAME
  pageconversionset = NAME
  pagestarter = COMMAND PROCESSOR->COMMAND
  pagestopper = COMMAND PROCESSOR->COMMAND
  pagesegments = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:all
  maxwidth = DIMENSION
  indicator = yes no
  before = COMMAND
  after = COMMAND
  command = CD:ONEARGUMENT
  textcommand = CD:ONEARGUMENT
  deeptextcommand = CD:ONEARGUMENT
  pagecommand = CD:ONEARGUMENT
  distance = DIMENSION
  interaction = text pagenumber
  pagenumber = yes no
  symbol = a n none 1 2 COMMAND
  language = default DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scN LANGUAGE
  style = STYLE COMMAND
  color = COLOR
  textstyle = STYLE COMMAND
  textcolor = COLOR
  pagestyle = STYLE COMMAND
  pagecolor = COLOR
  n = NUMBER
  balance = yes no
  align = inherits: \setupalign
  numberorder = numbers
```

`\setuprenderingwindow [...]1,... [...,...2...,...]`

```
1 NAME
2 openpageaction = REFERENCE
  closepageaction = REFERENCE
  inherits: \setupframed
```

`\setuprotate [...,...*...,...]`

```
* location = fit broad depth high middle default normal
  rotation = left right inner outer NUMBER
  inherits: \setupframed
```

`\setupscale [...1,...] [...2,...]`

```
1 NAME
2 scale      = NUMBER
  xscale     = NUMBER
  yscale     = NUMBER
  width      = DIMENSION
  height     = DIMENSION
  depth      = yes no
  lines      = NUMBER
  factor     = fit broad max auto default
  hfactor    = fit broad max auto default
  wfactor    = fit broad max auto default
  maxwidth   = DIMENSION
  maxheight  = DIMENSION
  s          = NUMBER
  sx         = NUMBER
  sy         = NUMBER
  equalwidth = DIMENSION
  equalheight = DIMENSION
  grid       = yes fit height depth halfline
```

`\setupscrip [...1,...] [...2,...]`

```
1 NAME
2 method     = hangul hanzi nihongo ethiopic thai test
  preset     = NAME
  features   = auto
```

`\setupsectionblock [...1,...] [...2,...]`

```
1 NAME
2 page       = inherits: \page
  before     = COMMAND
  after      = COMMAND
  number     = yes no
```

`\setupselector [...1] [...2,...]`

```
1 NAME
2 n = NUMBER
  m = NUMBER
```

`\setupshift [...1,...] [...2,...]`

```
1 NAME
2 continue   = yes no
  unit       = ex em pt in cm mm sp bp pc dd cc nc
  method     = NUMBER
  dy         = NUMBER
  align      = inherits: \setupalign
  style      = STYLE COMMAND
  color      = COLOR
```

`\setupsidebar [...1,...] [...2,...]`

```
1 NAME
2 rulethickness = DIMENSION
  rulecolor    = COLOR
  alternative   = NUMBER
  topoffset    = DIMENSION
  bottomoffset = DIMENSION
  distance     = DIMENSION
  leftmargindistance = DIMENSION
  level        = NUMBER
```



`\setupsorting [...,1...] [...,2...,...]`

```
1 SINGULAR
2 expansion      = yes no xml
  alternative    = first last normal NAME
  next           = COMMAND
  command        = CD:THREEARGUMENTS
  textcommand    = CD:ONEARGUMENT
  synonymcommand = CD:ONEARGUMENT
  language       = default DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scn LANGUAGE
  method         = default before after first last ch mm zm pm mc zc pc uc
  criterium      = current previous local text all SECTION
  style          = STYLE COMMAND
  color          = COLOR
  textstyle      = STYLE COMMAND
  textcolor      = COLOR
  synonymstyle    = STYLE COMMAND
  synonymcolor    = COLOR
```

`\setupspacing [...]`

\* fixed packed broad

`\setupspellchecking [...,*...,...]`

```
* state = start stop
  method = 1 2 3
  list   = NAME
```

`\setupstartstop [...,1...] [...,2...,...]`

```
1 NAME
2 before = COMMAND
  after  = COMMAND
  inbetween = COMMAND
  setups = NAME
  left   = COMMAND
  right  = COMMAND
  style  = STYLE COMMAND
  color  = COLOR
```

`\setupstretched [...,*...,...]`

\* inherits: \setupcharacterkerning

`\setupstruts [...]`

\* yes no auto cap fit line default CHARACTER

`\setupstyle [...,1...] [...,2...,...]`

```
1 NAME
2 method = command
  style  = STYLE COMMAND
  color  = COLOR
```

`\setupsubformula [...,1...] [...,2...,...]`

```
1 NAME
2 indentnext = yes no auto
```

`\setupsubpagenumber [...,*...,...]`

\* inherits: \setupcounter

`\setupsymbolset [...]`

\* NAME

`\setupsynonyms [...,1...] [...,2...,...]`

1 SINGULAR

2 expansion = yes no xml  
alternative = first last normal NAME  
next = COMMAND  
command = CD:THREEARGUMENTS  
textcommand = CD:ONEARGUMENT  
synonymcommand = CD:ONEARGUMENT  
language = default DIN\_5007-1 DIN\_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scn LANGUAGE  
method = default before after first last ch mm zm pm mc zc pc uc  
criterium = current previous local text all SECTION  
style = STYLE COMMAND  
color = COLOR  
textstyle = STYLE COMMAND  
textcolor = COLOR  
synonymstyle = STYLE COMMAND  
synonymcolor = COLOR

`\setups [...,*,...]`

\* NAME

`\setups {...,*,...}`

\* NAME

`\setupTABLE [...,1...] [...,2...] [...,3...,...]`

1 r c x y row column first last start header each odd even one NUMBER -NUMBER

2 first least each two odd even NUMBER -NUMBER

3 extras = COMMAND  
left = COMMAND  
right = COMMAND  
headcolor = COLOR  
headstyle = STYLE COMMAND  
leftmargindistance = DIMENSION  
rightmargindistance = DIMENSION  
columnndistance = DIMENSION  
maxwidth = DIMENSION  
setups = NAME  
textwidth = DIMENSION local  
split = yes no repeat auto  
header = repeat  
option = stretch tight  
before = COMMAND  
after = COMMAND  
samepage = before after both  
spaceinbetween = inherits: \blank  
splitoffset = DIMENSION  
aligncharacter = yes no  
alignmentcharacter = TEXT  
distance = DIMENSION  
color = COLOR  
style = STYLE COMMAND  
inherits: \setupframed

`\setupTEXpage [...,*...,...]`

\* inherits: \setupfittingpage

`\setuptables [...,*...]`

```
* text      = DIMENSION max
  split     = yes no repeat auto
  frame     = on off
  NL        = inherits: \blank
  VL        = small medium big none NUMBER
  HL        = small medium big none NUMBER
  distance  = small medium big none
  align     = left middle right
  commands  = COMMAND
  bodyfont  = inherits: \setupbodyfont
  rulethickness = DIMENSION
  height    = strut NUMBER
  depth     = strut NUMBER
```

`\setuptabulate [...]1 [...]2 [...,*...]3...`

```
1 NAME
2 NAME
3 inherits: \setuptabulation
```

`\setuptabulation [...]1 [...]2 [...,*...]3...`

```
1 NAME
2 format      = TEMPLATE none
  before      = COMMAND
  after       = COMMAND
  distance    = small medium big none blank depth grid DIMENSION
  align       = left middle right dimension
  rule        = line normal
  rulecolor   = COLOR
  rulethickness = DIMENSION
  bodyfont    = inherits: \setupbodyfont
  indenting   = yes no
  split       = yes no repeat auto
  unit        = DIMENSION
  margin      = DIMENSION
  inner       = COMMAND
  EQ          = COMMAND
  header      = yes repeat text
  frame       = on off
  title       = TEXT
  keeptogether = yes no
```

`\setuptagging [...,*...]`

```
* state = start stop
  method = auto
```

`\setuptaglabeltext [...]1 [...,*...]2...`

```
1 LANGUAGE
2 KEY = VALUE
```

`\setuptext [...]1 [...,*...]2...`

```
1 text margin edge
2 inherits: \setuplayoutelement
```

`\setuptextbackground [...1,...] [...2...,...]`

```
1  NAME
2  state      = start stop
   location   = text paragraph none
   alternative = NUMBER
   mp         = NAME
   method     = NAME
   background = color
   backgroundcolor = COLOR
   corner     = rectangular round
   level      = NUMBER
   backgroundoffset = DIMENSION
   before     = COMMAND
   after      = COMMAND
   align      = inherits: \setupalign
   dash       = NUMBER
   radius     = DIMENSION
   frame      = on off
   framecolor = COLOR
   rulethickness = DIMENSION
   voffset    = DIMENSION
   frameoffset = DIMENSION
   leftoffset = yes no standard DIMENSION
   rightoffset = yes no standard DIMENSION
   topoffset  = small medium big line DIMENSION
   bottomoffset = small medium big line DIMENSION
   style      = STYLE COMMAND
   color      = COLOR
```

`\setuptextflow [...1,...] [...2...,...]`

```
1  NAME
2  width = DIMENSION
   style = STYLE COMMAND
   color = COLOR
```

`\setuptextrules [...*...,...]`

```
*  before      = COMMAND
   after       = COMMAND
   inbetween   = COMMAND
   rulethickness = DIMENSION
   location    = left inmargin
   style       = STYLE COMMAND
   color       = COLOR
   rulecolor   = COLOR
   width       = DIMENSION
   height      = DIMENSION
   distance    = DIMENSION
   depthcorrection = on off
   bodyfont    = inherits: \setupbodyfont
```

`\setuptexttexts [...1] [...2] [...3] [...4] [...5]`

```
1  text margin edge
2  date pagenumber MARK TEXT COMMAND
3  date pagenumber MARK TEXT COMMAND
4  date pagenumber MARK TEXT COMMAND
5  date pagenumber MARK TEXT COMMAND
```

`\setupthinrules` [...,<sup>1</sup>...,...]

\* `height` = max DIMENSION  
\* `depth` = max DIMENSION  
\* `background` = color  
\* `frame` = on off  
\* `rulethickness` = DIMENSION  
\* `alternative` = a b c none  
\* `backgroundcolor` = COLOR  
\* `color` = COLOR  
\* `interlinespace` = small medium big NUMBER  
\* `before` = COMMAND  
\* `after` = COMMAND  
\* `inbetween` = COMMAND  
\* `n` = NUMBER

`\setuptolerance` [...,<sup>1</sup>...,...]

\* horizontal vertical veryststrict strict tolerant verytolerant space stretch

`\setuptooltip` [...,<sup>1</sup>...,...] [...,<sup>2</sup>...,...]

1 NAME  
2 `location` = left middle right  
\* `inherits:` \setupframed

`\setuptop` [...<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 `text` margin edge  
2 `inherits:` \setuplayoutelement

`\setuptotexts` [...<sup>1</sup>...] [...<sup>2</sup>...] [...<sup>3</sup>...] [...<sup>4</sup>...] [...<sup>5</sup>...]

1 `text` margin edge  
2 `date` `pagenumber` MARK TEXT COMMAND  
3 `date` `pagenumber` MARK TEXT COMMAND  
4 `date` `pagenumber` MARK TEXT COMMAND  
5 `date` `pagenumber` MARK TEXT COMMAND

`\setuptype` [...,<sup>1</sup>...,...] [...,<sup>2</sup>...,...]

1 NAME  
2 `option` = mp lua xml parsed-xml nested tex context none NAME  
\* `command` = CSNAME  
\* `left` = COMMAND  
\* `right` = COMMAND  
\* `tab` = yes no NUMBER  
\* `compact` = absolute last all  
\* `escape` = yes no TEXT PROCESSOR->TEXT  
\* `style` = STYLE COMMAND  
\* `color` = COLOR  
\* `lines` = yes no normal hyphenated  
\* `space` = on off normal fixed stretch

`\setuptyping [...,*...]`

```
* oddmargin      = DIMENSION
  evenmargin     = DIMENSION
  margin         = yes no standard DIMENSION
  option         = mp lua xml parsed-xml nested tex context none NAME
  style          = STYLE COMMAND
  color          = COLOR
  align          = inherits: \setupalign
  lines          = yes no normal hyphenated
  space          = on off normal fixed stretch
  kepttogether   = yes no
  before         = COMMAND
  after          = COMMAND
  strip          = yes no NUMBER
  range          = NUMBER NAME
  tab            = yes no NUMBER
  escape         = yes no TEXT PROCESSOR->TEXT
  indentnext     = yes no auto
  continue       = yes no
  start          = NUMBER
  stop           = NUMBER
  step           = NUMBER
  numbering      = file line no
  blank          = inherits: \blank
```

`\setupunit [...,1...] [...,2...]`

```
1 NAME
2 method      = 1 2 3 4 5 6
  language     = LANGUAGE
  alternative   = text mathematics
  order        = reverse normal
  separator    = small medium big normal none NAME
  space        = small medium big normal none NAME
  style        = STYLE COMMAND
  color        = COLOR
```

`\setupunittext [...,1...] [...,2...]`

```
1 LANGUAGE
2 KEY = VALUE
```

`\setupurl [...,*...]`

```
* style = STYLE COMMAND
  color = COLOR
```

`\setupuserpagenumber [...,*...]`

```
* viewerprefix = TEXT
  state         = start stop none keep empty
  inherits: \setupcounter
```

`\setupversion [...]`

```
* concept file temporary final NAME
```

`\setupviewerlayer [...,*...]`

```
* title      = TEXT
  state       = start stop
  export      = yes no
  printable   = yes no
  scope       = local global
  method      = none command
```

`\setupvspacing [...,*...]`

```
* inherits: \vspacing
```

`\setupwhitespace [...]*...]`

\* fix fixed flexible line halfline quarterline none small medium big default DIMENSION

`\setupwithargument {...} {...}^1`

1 NAME

2 CONTENT

`\setupwithargumentswapped {...} {...}^1`

1 CONTENT

2 NAME

`\setupxml [...]*...=...]`

\* default = hidden none text  
compress = yes no

`\setupxtable [...]*^1...] [...]*^2...]`

1 NAME

2 textwidth = DIMENSION local  
bodyfont = inherits: \setupbodyfont  
spaceinbetween = inherits: \blank  
option = tight max stretch width height fixed  
textheight = DIMENSION  
maxwidth = DIMENSION  
columnndistance = DIMENSION  
leftmargindistance = DIMENSION  
rightmargindistance = DIMENSION  
header = repeat  
footer = repeat  
rulethickness = DIMENSION  
split = yes no repeat auto  
splitoffset = DIMENSION  
samepage = before after both  
distance = DIMENSION  
inherits: \setupframed

`\setup [...]*...`

\* NAME

`\setup {...}^*`

\* NAME

`\setuvalue {...} {...}^1`

1 NAME

2 CONTENT

`\setuxvalue {...} {...}^1`

1 NAME

2 CONTENT

`\setvalue {...} {...}^1`

1 NAME

2 CONTENT

`\setvariable {...} {...} {...}`

- 1 NAME
- 2 KEY
- 3 VALUE

`\setvariables [...] [...,...2...,...]`

- 1 NAME
- 2 set = COMMAND  
reset = COMMAND  
KEY = VALUE

`\setvisualizerfont [...]`

- \* FONT

`\setwidthof ... \to ...2`

- 1 TEXT
- 2 CSNAME

`\setxmeasure {...} {...}`

- 1 NAME
- 2 DIMENSION

`\setxvalue {...} {...}`

- 1 NAME
- 2 CONTENT

`\setxvariable {...} {...} {...}`

- 1 NAME
- 2 KEY
- 3 VALUE

`\setxvariables [...] [...,...2...,...]`

- 1 NAME
- 2 set = COMMAND  
reset = COMMAND  
KEY = VALUE

`\sfrac {...} {...}`

- 1 CONTENT
- 2 CONTENT

`\shapedhbox {...}`

- \* CONTENT

`\shiftdown {...}`

- \* CONTENT

`\shiftup {...}`

- \* CONTENT



<pre>\shift {...}</pre> <p>* CONTENT</p>
<pre>\showallmakeup</pre>
<pre>\showattributes</pre>
<pre>\showbodyfont [...,*,...]</pre> <p>* inherits: \setupbodyfont</p>
<pre>\showbodyfontenvironment [...,*,...]</pre> <p>* inherits: \setupbodyfont</p>
<pre>\showboxes</pre>
<pre>\showbtxdatasetauthors [...,*=...,...]</pre> <p>* specification = NAME dataset = NAME field = address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language month monthfiled nationality note number one two organization pages publisher school series title type volume year yearfiled NAME</p>
<pre>\showbtxdatasetauthors [...]</pre> <p>* NAME</p>
<pre>\showbtxdatasetcompleteness [...,*=...,...]</pre> <p>* specification = NAME dataset = NAME field = address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language month monthfiled nationality note number one two organization pages publisher school series title type volume year yearfiled NAME</p>
<pre>\showbtxdatasetcompleteness [...]</pre> <p>* NAME</p>
<pre>\showbtxdatasetfields [...,*=...,...]</pre> <p>* specification = NAME dataset = NAME field = address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language month monthfiled nationality note number one two organization pages publisher school series title type volume year yearfiled NAME</p>
<pre>\showbtxdatasetfields [...]</pre> <p>* NAME</p>
<pre>\showbtxfields [...,*=...,...]</pre> <p>* rotation = NUMBER specification = NAME</p>
<pre>\showbtxfields [...]</pre> <p>* NAME</p>
<pre>\showbtxhashedauthors [...]</pre> <p>* TEXT</p>

\showbtxtables [...] * TEXT
\showchardata {...} * TEXT
\showcharratio {...} * TEXT
\showcolor [...] * COLOR
\showcolorbar [...] * COLOR
\showcolorcomponents [...] * COLOR
\showcolorgroup [...] <sup>1</sup> [...] <sup>2</sup> ,...] 1 NAME 2 <u>horizontal</u> vertical number value name
\showcolorset [...] * COLOR
\showcolorstruts
\showcounter [...] * NAME
\showdirectives
\showdirsinmargin
\showedebuginfo
\showexperiments
\showfont [...] <sup>1</sup> [...] <sup>2</sup> ,...] 1 FONT 2 NUMBER
\showfontdata
\showfontkerns
\showfontparameters

<code>\showfontstrip [...,*,...]</code>  <code>* inherits: \setupbodyfont</code>
<code>\showfontstyle [...,<sup>1</sup>,...] [...,<sup>2</sup>,...] [...,<sup>3</sup>,...] [...,<sup>4</sup>,...]</code>  <code>1 inherits: \setupbodyfont</code> <code>2 rm ss tt mm hw cg</code> <code>3 tf bf it sl bi bs</code> <code>4 all NUMBER</code>
<code>\showframe [...,<sup>1</sup>,...] [...,<sup>2</sup>,...]</code>  <code>1 top header text footer bottom</code> <code>2 leftedge leftmargin text rightmargin rightedge</code>
<code>\showglyphs</code>
<code>\showgrid [...,*,...]</code>  <code>* reset <u>bottom</u> top none <u>all</u> lines frame nonumber <u>right</u> left outer <u>columns</u></code>
<code>\showgridsnapping</code>
<code>\showhelp {...} [...]</code>  <code>1 TEXT</code> <code>2 REFERENCE</code>
<code>\showhyphenationtrace [...]<sup>1</sup> [...]<sup>2</sup></code>  <code>1 LANGUAGE</code> <code>2 TEXT</code>
<code>\showhyphens {...}</code>  <code>* TEXT</code>
<code>\showinjector [...,*,...]</code>  <code>* NAME</code>
<code>\showjustification</code>
<code>\showkerning {...}</code>  <code>* TEXT</code>
<code>\showlayout [...,*,...]</code>  <code>* <u>pt</u> <u>bp</u> <u>cm</u> mm dd cc pc nd nc sp in</code>
<code>\showlayoutcomponents</code>
<code>\showligature {...}</code>  <code>* TEXT</code>

<code>\showligatures [...]</code>  * <code>FONT</code>
<code>\showlogcategories</code>
<code>\showmakeup [...]</code>  * <code>makeup</code> all boxes glyph fontkern hbox vbox vtop kern glue penalty strut whatsit simple simplehbox simplevbox simplevtop user math italic origin reset
<code>\showmargins</code>
<code>\showmessage {...} {...} {...,  1    NAME  2    NAME NUMBER  3    TEXT </code>
<code>\showminimalbaseline</code>
<code>\shownextbox \... {...}</code>  1    CSNAME 2    CONTENT
<code>\showotfcomposition {...} {...} {...}</code>  1    FONT 2    -1 1 +1 l2r r2l 3    TEXT
<code>\showpalet [...] [...,  1    NAME  2    <u>horizontal</u> vertical number value name </code>
<code>\showparentchain \... {...}</code>  1    CSNAME 2    NAME
<code>\showprint [...,<sup>1</sup>...] [...,<sup>2</sup>...] [...,<sup>3</sup>...,...]</code>  1    inherits: \setuppapersize 2    inherits: \setuppapersize 3    inherits: \setuplayout
<code>\showsetups [...,*,...]</code>  * <code>pt bp <u>cm</u> mm dd cc pc nd nc sp in</code>
<code>\showsetupsdefinition [...]</code>  *    NAME
<code>\showstruts</code>

<code>\showsymbolset [...]</code>  *    NAME
<code>\showtimer {...}</code>  *    TEXT
<code>\showtokens [...]</code>  *    NAME
<code>\showtrackers</code>
<code>\showvalue {...}</code>  *    NAME
<code>\showvariable {...} {...}</code>  1    NAME 2    KEY
<code>\showwarning {...} {...} {..., ...}</code>  1    NAME 2    NAME NUMBER 3    TEXT
<code>\simplealignedbox {...} {...} {...}</code>  1    DIMENSION 2    left right middle flushleft flushright inner outer 3    CONTENT
<code>\simplealignedboxplus {...} {...} {...} {...}</code>  1    DIMENSION 2    left right middle flushleft flushright inner outer 3    TEXT 4    CONTENT
<code>\simplealignedspreadbox {...} {...} {...}</code>  1    DIMENSION 2    left right middle flushleft flushright inner outer 3    CONTENT
<code>\simplegroupedcommand {...} {...}</code>  1    COMMAND 2    COMMAND
<code>\simplereversealignedbox {...} {...} {...}</code>  1    DIMENSION 2    left right middle flushleft flushright inner outer 3    CONTENT

`\simplereversealignedboxplus {...} {...} {...} {...}`

- 1 DIMENSION
- 2 left right middle flushleft flushright inner outer
- 3 TEXT
- 4 CONTENT

`\singalcharacteralign {...} {...}`

- 1 NUMBER
- 2 NUMBER

`\singlebond`

`\sixthofsixarguments {...} {...} {...} {...} {...} {...}`

- 1 TEXT
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT
- 6 TEXT

`\slanted`

`\slantedbold`

`\slicepages [...]1 [...]2 [...]3 [...]`

- 1 FILE
- 2 offset = DIMENSION  
hoffset = DIMENSION  
voffset = DIMENSION  
width = DIMENSION  
height = DIMENSION  
n = NUMBER
- 3 offset = DIMENSION  
hoffset = DIMENSION  
voffset = DIMENSION  
width = DIMENSION  
height = DIMENSION  
n = NUMBER

`\slovenianNumerals {...}`

- \* NUMBER

`\sloveniannumerals {...}`

- \* NUMBER

`\small`

`\smallbodyfont`

`\smallbold`

`\smallbolditalic`

<code>\smallboldslanted</code>
<code>\smallcapped {...}</code> * TEXT
<code>\smallcappedcharacters {...}</code> * NUMBER
<code>\smallcappedromannumerals {...}</code> * NUMBER
<code>\smaller</code>
<code>\smallitalicbold</code>
<code>\smallnormal</code>
<code>\smallskip</code>
<code>\smallslanted</code>
<code>\smallslantedbold</code>
<code>\smalltype</code>
<code>\smash [.^.] {...}</code> 1 w h d t b 2 CONTENT
<code>\smashbox ...</code> * CSNAME NUMBER
<code>\smashboxed ...</code> * CSNAME NUMBER
<code>\smashedhbox .^.. {...}</code> 1 TEXT 2 CONTENT
<code>\smashedvbox .^.. {...}</code> 1 TEXT 2 CONTENT
<code>\snaptogrid [.^.] \.^.. {...}</code> 1 normal standard yes strict tolerant top bottom both broad fit first last high one low none line strut box min max middle NAME 2 CSNAME 3 CONTENT

`\snaptogrid [...1,...] \... {...3}`

1 inherits: \definegridsnapping  
2 CSNAME  
3 CONTENT

`\someheadnumber [...1] [...2]`

1 SECTION  
2 previous current next first last

`\somekindoftab [...*...]`

\* alternative = horizontal vertical  
width = DIMENSION  
height = DIMENSION  
n = NUMBER  
m = NUMBER

`\someline [...*]`

\* REFERENCE

`\somelocalfloat`

`\somenamedheadnumber {...1} {...2}`

1 SECTION  
2 previous current next first last

`\someplace {...1} {...2} {...3} {...4} {...5} [...6]`

1 TEXT  
2 TEXT  
3 TEXT  
4 TEXT  
5 TEXT  
6 REFERENCE

`\somewhere {...1} {...2} [...3]`

1 TEXT  
2 TEXT  
3 REFERENCE

`\sorting [...1] {...2}`

1 NAME  
2 CONTENT

`\space`

`\spanishNumerals {...*}`

\* NUMBER

`\spanishnumerals {...*}`

\* NUMBER



<code>\speech {...}</code> *    CONTENT
<code>\splitdfrac {...} {...}</code> 1    CONTENT 2    CONTENT
<code>\splitfilename {...}</code> *    FILE
<code>\splitfloat [...,\stackrel{1}{...}] {...} {...}</code> 1    inherits: \setupfloatsplitting 2    COMMAND 3    CONTENT
<code>\splitfrac {...} {...}</code> 1    CONTENT 2    CONTENT
<code>\splitoffbase</code>
<code>\splitofffull</code>
<code>\splitoffkind</code>
<code>\splitoffname</code>
<code>\splitoffpath</code>
<code>\splitoffroot</code>
<code>\splitofftokens ... \from ... \to ...</code> 1    TEXT 2    TEXT 3    CSNAME
<code>\splitofftype</code>
<code>\splitstring ... \at ... \to ... \and ...</code> 1    TEXT 2    TEXT 3    CSNAME 4    CSNAME
<code>\spreadhbox ...</code> *    CSNAME NUMBER

$\backslash\mathrm{sqrt}$ [...] {...} <div> <div>1</div> <div>TEXT</div> </div> <div> <div>2</div> <div>CONTENT</div> </div>
$\backslash\mathrm{stackrel}$ {...} {...} <div> <div>1</div> <div>CONTENT</div> </div> <div> <div>2</div> <div>CONTENT</div> </div>
$\backslash\mathrm{startalign}$ [...,*...,...] ... $\backslash\mathrm{stopalign}$ <div> <div>*</div> <div>inherits: <math>\backslash\mathrm{setupmathalignment}</math></div> </div>
$\backslash\mathrm{startalignment}$ [...,*...,...] ... $\backslash\mathrm{stopalignment}$ <div> <div>*</div> <div>inherits: <math>\backslash\mathrm{setupalign}</math></div> </div>
$\backslash\mathrm{startallmodes}$ [...,*...,...] ... $\backslash\mathrm{stopallmodes}$ <div> <div>*</div> <div>NAME</div> </div>
$\backslash\mathrm{startappendices}$ [...,*...,...] ... $\backslash\mathrm{stopappendices}$ <div> <div>*</div> <div>bookmark = TEXT</div> <div>inherits: <math>\backslash\mathrm{setupsectionblock}</math></div> </div>
$\backslash\mathrm{startattachment}$ [...] [...,*...,...] ... $\backslash\mathrm{stopattachment}$ <div> <div>1</div> <div>NAME</div> </div> <div> <div>2</div> <div>inherits: <math>\backslash\mathrm{setupattachment}</math></div> </div>
$\backslash\mathrm{startattachment}$ [...] [...,*...,...] ... $\backslash\mathrm{stopattachment}$ <div> <div>1</div> <div>NAME</div> </div> <div> <div>2</div> <div>inherits: <math>\backslash\mathrm{setupattachment}</math></div> </div>
$\backslash\mathrm{startbackground}$ [...,*...,...] ... $\backslash\mathrm{stopbackground}$ <div> <div>*</div> <div>inherits: <math>\backslash\mathrm{setupbackground}</math></div> </div>
$\backslash\mathrm{startbackground}$ [...,*...,...] ... $\backslash\mathrm{stopbackground}$ <div> <div>*</div> <div>inherits: <math>\backslash\mathrm{setupbackground}</math></div> </div>
$\backslash\mathrm{startbackmatter}$ [...,*...,...] ... $\backslash\mathrm{stopbackmatter}$ <div> <div>*</div> <div>bookmark = TEXT</div> <div>inherits: <math>\backslash\mathrm{setupsectionblock}</math></div> </div>
$\backslash\mathrm{startbar}$ [...] ... $\backslash\mathrm{stopbar}$ <div> <div>*</div> <div>NAME</div> </div>
$\backslash\mathrm{startbitmapimage}$ [...,*...,...] ... $\backslash\mathrm{stopbitmapimage}$ <div> <div>*</div> <div>color = rgb cmyk gray</div> <div>width = DIMENSION</div> <div>height = DIMENSION</div> <div>x = NUMBER</div> <div>y = NUMBER</div> </div>

$\backslash\text{startblockquote} [\dots^* \dots] \dots \backslash\text{stopblockquote}$  * inherits: $\backslash\text{startnarrower}$
$\backslash\text{startbodymatter} [\dots^* \dots] \dots \backslash\text{stopbodymatter}$  * bookmark = TEXT inherits: $\backslash\text{setupsectionblock}$
$\backslash\text{startboxedcolumns} [\dots^* \dots] \dots \backslash\text{stopboxedcolumns}$  * inherits: $\backslash\text{setupmixedcolumns}$
$\backslash\text{startbtxlabeltext} [\dots^1] [\dots^2] \dots \backslash\text{stopbtxlabeltext}$  1 LANGUAGE 2 KEY
$\backslash\text{startbtxrenderingdefinitions} [\dots^*] \dots \backslash\text{stopbtxrenderingdefinitions}$  * NAME
$\backslash\text{startbuffer} [\dots^*] \dots \backslash\text{stopbuffer}$  * NAME
$\backslash\text{startbuffer} \dots \backslash\text{stopbuffer}$
$\backslash\text{startbut} [\dots^*] \dots \backslash\text{stopbut}$  * REFERENCE
$\backslash\text{startcases} [\dots^* \dots] \dots \backslash\text{stopcases}$  * inherits: $\backslash\text{setupmathcases}$
$\backslash\text{startcatcodetable} \backslash \dots^* \dots \backslash\text{stopcatcodetable}$  * CSNAME
$\backslash\text{startcentraligned} \dots \backslash\text{stopcentraligned}$
$\backslash\text{startchapter} [\dots^1 \dots] [\dots^2 \dots] \dots \backslash\text{stopchapter}$  1 title = TEXT bookmark = TEXT marking = TEXT list = TEXT reference = REFERENCE ownnumber = TEXT  2 KEY = VALUE
$\backslash\text{startcharacteralign} [\dots^*] \dots \backslash\text{stopcharacteralign}$  * TEXT number->TEXT text->TEXT
$\backslash\text{startcheckedfences} \dots \backslash\text{stopcheckedfences}$
$\backslash\text{startchemical} [\dots^1] [\dots^2 \dots] \dots \backslash\text{stopchemical}$  1 NAME 2 inherits: $\backslash\text{setupchemical}$

<code>\startcollect ... \stopcollect</code>
<code>\startcollecting ... \stopcollecting</code>
<code>\startcolor [...] ... \stopcolor</code> <code>*    COLOR</code>
<code>\startcolorintent [...] ... \stopcolorintent</code> <code>*    knockout overprint none</code>
<code>\startcoloronly [...] ... \stopcoloronly</code> <code>*    COLOR</code>
<code>\startcolorset [...] ... \stopcolorset</code> <code>*    NAME</code>
<code>\startcolumns [...,..<sup>1</sup>...,...] ... \stopcolumns</code> <code>*    inherits: \setupcolumns</code>
<code>\startcolumnspan [...,..<sup>1</sup>...,...] ... \stopcolumnspan</code> <code>*    inherits: \setupcolumnspan</code>
<code>\startcombination [<sup>1</sup>...] [<sup>2</sup>...] ... \stopcombination</code> <code>1    NAME</code> <code>2    N*M</code>
<code>\startcombination [<sup>1</sup>...] [...,..<sup>2</sup>...,...] ... \stopcombination</code> <code>1    NAME</code> <code>2    inherits: \setupcombination</code>
<code>\startcomment [<sup>1</sup>...] [...,..<sup>2</sup>...,...] ... \stopcomment</code> <code>1    TEXT</code> <code>2    inherits: \setupcomment</code>
<code>\startcomment [<sup>1</sup>...] [...,..<sup>2</sup>...,...] ... \stopcomment</code> <code>1    TEXT</code> <code>2    inherits: \setupcomment</code>
<code>\startcomponent [...] ... \stopcomponent</code> <code>*    FILE *</code>
<code>\startcomponent ... ... \stopcomponent</code> <code>*    FILE *</code>
<code>\startcom ... \stopcom</code>
<code>\startcontextcode ... \stopcontextcode</code>

<code>\startcontextdefinitioncode ... \stopcontextdefinitioncode</code>
<code>\startctxfunction ... \stopctxfunction</code> <code>* NAME</code>
<code>\startctxfunctiondefinition ... \stopctxfunctiondefinition</code> <code>* NAME</code>
<code>\startcurrentcolor ... \stopcurrentcolor</code>
<code>\startcurrentlistentrywrapper ... \stopcurrentlistentrywrapper</code>
<code>\startdelimited [...] [...] ... \stopdelimited</code> <code>1 NAME</code> <code>2 inherits: \startnarrower</code>
<code>\startdelimitedtext [...] [...] ... \stopdelimitedtext</code> <code>1 NAME</code> <code>2 inherits: \startnarrower</code>
<code>\startdelimitedtext [...] ... \stopdelimitedtext</code> <code>* inherits: \startnarrower</code>
<code>\startdescription [..., ...*..., ...] ... \stopdescription</code> <code>* title = TEXT</code> <code>bookmark = TEXT</code> <code>list = TEXT</code> <code>reference = REFERENCE</code>
<code>\startdescription [...,<sup>1</sup>...] {.<sup>2</sup>.} ... \stopdescription</code> <code>1 REFERENCE</code> <code>2 TEXT</code>
<code>\startdisplaymath ... \stopdisplaymath</code>
<code>\startdmath ... \stopdmath</code>
<code>\startdocument [..., ...*..., ...] ... \stopdocument</code> <code>* inherits: \setupdocument</code>
<code>\starteffect [...] ... \stopeffect</code> <code>* NAME</code>
<code>\starteffect ... \stopeffect</code>
<code>\startembeddedxtable [..., ...*..., ...] ... \stopembeddedxtable</code> <code>* inherits: \setupxtable</code>
<code>\startembeddedxtable [...] ... \stopembeddedxtable</code> <code>* NAME</code>

`\startendnote [...,*=...,...] ... \stopendnote`

\* title = TEXT  
bookmark = TEXT  
list = TEXT  
reference = REFERENCE

`\startendnote [...,*...] ... \stopendnote`

\* REFERENCE

`\startenumeration [...,*=...,...] ... \stopenumeration`

\* title = TEXT  
bookmark = TEXT  
list = TEXT  
reference = REFERENCE

`\startenumeration [...,1...,...] {...2.} ... \stopenumeration`

1 REFERENCE

2 TEXT

`\startenvironment [...*] ... \stopenvironment`

\* FILE \*

`\startenvironment ...* ... \stopenvironment`

\* FILE \*

`\startexceptions [...*] ... \stopexceptions`

\* LANGUAGE

`\startexpanded ... \stopexpanded`

`\startexpandedcollect ... \stopexpandedcollect`

`\startextendedcatcodetable \... ... \stopextendedcatcodetable`

\* CSNAME

`\startexternalfigurecollection [...*] ... \stopexternalfigurecollection`

\* NAME

`\startfact [...1] [...,*2...,...] ... \stopfact`

1 NAME

2 inherits: \setuptabulate

`\startfigure [...1] [...2] [...,*3...,...] ... \stopfigure`

1 NAME

2 FILE

3 inherits: \externalfigure

`\startfiguretext [...1,...] [...2,...] {...3} ... \stopfiguretext`

- 1 split always left right inner outer backspace cutspace inleft inright inmargin leftmargin rightmargin leftedge rightedge innermargin outermargin inneredge outeredge text opposite reset height depth [-+]line halfline grid high low fit 90 180 270 nonumber none local here force margin [-+]hang hanging tall both middle offset top bottom auto page leftpage rightpage somewhere
- 2 REFERENCE
- 3 TEXT

`\startfittingpage [...1] [...2,...,...] ... \stopfittingpage`

- 1 NAME
- 2 inherits: \setupfittingpage

`\startfittingpage [...*,...,...] ... \stopfittingpage`

- \* inherits: \setupfittingpage

`\startfloatcombination [...*] ... \stopfloatcombination`

- \* N\*M NAME

`\startfloatcombination [...*,...,...] ... \stopfloatcombination`

- \* inherits: \setupcombination

`\startfloattext [...1,...] [...2,...] {...3} ... \stopfloattext`

- 1 split always left right inner outer backspace cutspace inleft inright inmargin leftmargin rightmargin leftedge rightedge innermargin outermargin inneredge outeredge text opposite reset height depth [-+]line halfline grid high low fit 90 180 270 nonumber none local here force margin [-+]hang hanging tall both middle offset top bottom auto page leftpage rightpage somewhere
- 2 REFERENCE
- 3 TEXT

`\startfont [...*] ... \stopfont`

- \* FONT

`\startfontclass [...*] ... \stopfontclass`

- \* each NAME

`\startfontsolution [...*] ... \stopfontsolution`

- \* NAME

`\startfootnote [...*,...,...] ... \stopfootnote`

- \* title = TEXT
- \* bookmark = TEXT
- \* list = TEXT
- \* reference = REFERENCE

`\startfootnote [...*,...] ... \stopfootnote`

- \* REFERENCE

`\startformula [...*,...] ... \stopformula`

- \* packed tight middle frame inherits: \setupbodyfont

$\backslash\text{startformulas} [\dots^*,\dots] \dots \backslash\text{stopformulas}$ *    + - REFERENCE
$\backslash\text{startformulaformula} [\dots^*,\dots] \dots \backslash\text{stopformulaformula}$ *    packed tight middle frame inherits: $\backslash\text{setupbodyfont}$
$\backslash\text{startframed} [.^1.] [\dots,\dots^2,\dots] \dots \backslash\text{stopframed}$ 1    NAME 2    inherits: $\backslash\text{setupframed}$
$\backslash\text{startframedcontent} [.^*.] \dots \backslash\text{stopframedcontent}$ *    NAME off
$\backslash\text{startframedtext} [.^1.] [\dots,\dots^2,\dots] \dots \backslash\text{stopframedtext}$ 1    left right middle none 2    inherits: $\backslash\text{setupframedtext}$
$\backslash\text{startframedtext} [.^1.] [\dots,\dots^2,\dots] \dots \backslash\text{stopframedtext}$ 1    left right middle none 2    inherits: $\backslash\text{setupframedtext}$
$\backslash\text{startfrontmatter} [\dots,\dots^*,\dots] \dots \backslash\text{stopfrontmatter}$ *    bookmark = TEXT inherits: $\backslash\text{setupsectionblock}$
$\backslash\text{startgoto} [.^*.] \dots \backslash\text{stopgoto}$ *    REFERENCE
$\backslash\text{startgot} [.^*.] \dots \backslash\text{stopgot}$ *    REFERENCE
$\backslash\text{startgraphicstext} [\dots^1,\dots] [\dots^2,\dots] \{\dots^3\} \dots \backslash\text{stopgraphicstext}$ 1    split always left right inner outer backspace cutspace inleft inright inmargin leftmargin rightmargin leftedge rightedge innermargin outermargin inneredge outeredge text opposite reset height depth [-+]line halfline grid high low fit 90 180 270 nonumber none local here force margin [-+]hang hanging tall both middle offset top bottom auto page leftpage rightpage somewhere 2    REFERENCE 3    TEXT
$\backslash\text{startgridsnapping} [.^*.] \dots \backslash\text{stopgridsnapping}$ *    normal standard yes strict tolerant top bottom both broad fit first last high one low none line strut box min max middle NAME
$\backslash\text{startgridsnapping} [\dots^*,\dots] \dots \backslash\text{stopgridsnapping}$ *    inherits: $\backslash\text{definegridsnapping}$
$\backslash\text{starthboxestohbox} \dots \backslash\text{stophboxestohbox}$



<code>\starthead [...,<sup>1</sup>...] {...} ... \stophead</code>  1    REFERENCE 2    TEXT
<code>\starheadtext [...<sup>1</sup>] [...<sup>2</sup>] ... \stopheadtext</code>  1    LANGUAGE 2    KEY
<code>\starhelptext [...<sup>*</sup>] ... \stophelptext</code>  *    REFERENCE
<code>\starthelp [...<sup>*</sup>] ... \stophelp</code>  *    REFERENCE
<code>\starthiding ... \stophiding</code>
<code>\starthighlight [...<sup>*</sup>] ... \stophighlight</code>  *    NAME
<code>\starthyphenation [...,<sup>*</sup>...] ... \stophyphenation</code>  *    original tex <u>default</u> hyphenate expanded traditional none
<code>\startimath ... \stopimath</code>
<code>\startindentedtext [...<sup>*</sup>] ... \stopindentedtext</code>  *    NAME
<code>\startindentedtext ... \stopindentedtext</code>
<code>\startinteraction [...<sup>*</sup>] ... \stopinteraction</code>  *    hidden NAME
<code>\startinteractionmenu [...<sup>*</sup>] ... \stopinteractionmenu</code>  *    NAME
<code>\startinterface ... .. \stopinterface</code>  *    all LANGUAGE
<code>\startintermezzotext [...,<sup>1</sup>...] [...,<sup>2</sup>...] {...<sup>3</sup>} ... \stopintermezzotext</code>  1    split always left right inner outer backspace cutspace inleft inright inmargin leftmargin rightmargin leftedge rightedge innermargin outermargin inneredge outeredge text opposite reset height depth [-+]line halflines grid high low fit 90 180 270 nonumber none local here force margin [-+]hang hanging tall both middle offset top bottom auto page leftpage rightpage somewhere 2    REFERENCE 3    TEXT
<code>\startintertext ... \stopintertext</code>

<code>\startitem [...,*...] ... \stopitem</code>  *   REFERENCE
<code>\startitemgroup [...<sup>1</sup>] [...<sup>2</sup>,...] [...<sup>3</sup>,...,...] ... \stopitemgroup</code>  1   NAME 2   inherits: \setupitemgroup 3   inherits: \setupitemgroup
<code>\startitemgroup [...<sup>1</sup>,...] [...<sup>2</sup>,...,...] ... \stopitemgroup</code>  1   inherits: \setupitemgroup 2   inherits: \setupitemgroup
<code>\startitemize [...<sup>1</sup>,...] [...<sup>2</sup>,...,...] ... \stopitemize</code>  1   inherits: \setupitemgroup 2   inherits: \setupitemgroup
<code>\startJScode ...<sup>1</sup> ...<sup>2</sup> ...<sup>3</sup> ... \stopJScode</code>  1   NAME 2   uses 3   NAME
<code>\startJSpreamble ...<sup>1</sup> ...<sup>2</sup> ...<sup>3</sup> ... \stopJSpreamble</code>  1   NAME 2   used 3   now later
<code>\startknockout ... \stopknockout</code>
<code>\startLUA [...,*...] ... \stopLUA</code>  *   inherits: \setuptyping
<code>\startlua [...,*...] ... \stoplua</code>  *   continue
<code>\startlabeltext [...<sup>1</sup>] [...<sup>2</sup>] ... \stoplabeltext</code>  1   LANGUAGE 2   KEY
<code>\startlabeltext [...<sup>1</sup>] [...<sup>2</sup>] ... \stoplabeltext</code>  1   LANGUAGE 2   KEY
<code>\startlayout [...*] ... \stoplayout</code>  *   NAME
<code>\startleftaligned ... \stopleftaligned</code>

$\backslash\text{startlegend}$ [ <sup>1</sup> ...] [ <sub>...</sub> <sup>2</sup> ...] ... $\backslash\text{stoplegend}$ 1 NAME 2 inherits: $\backslash\text{setuptabulate}$
$\backslash\text{startline}$ [...] * REFERENCE
$\backslash\text{startlinealignment}$ [...] $\backslash\text{stoplinealignment}$ * left middle right max
$\backslash\text{startlinecorrection}$ [... <sup>*</sup> ...] $\backslash\text{stoplinecorrection}$ * blank inherits: $\backslash\text{blank}$
$\backslash\text{startlinenote}$ [ <sup>1</sup> ...] { <sub>...</sub> <sup>2</sup> } 1 REFERENCE 2 TEXT
$\backslash\text{startlinenote}$ [ <sup>1</sup> ...] { <sub>...</sub> <sup>2</sup> } 1 REFERENCE 2 TEXT
$\backslash\text{startlinenumbering}$ [ <sup>1</sup> ...] [ <sub>...</sub> <sup>2</sup> ...] ... $\backslash\text{stoplinenumbering}$ 1 NAME 2 inherits: $\backslash\text{setuplinenumbering}$
$\backslash\text{startlinenumbering}$ [ <sup>1</sup> ...] [ <sub>...</sub> <sup>2</sup> ...] ... $\backslash\text{stoplinenumbering}$ 1 NAME 2 continue NUMBER
$\backslash\text{startlines}$ [ <sub>...</sub> <sup>*</sup> ...] ... $\backslash\text{stoplines}$ * inherits: $\backslash\text{setuplines}$
$\backslash\text{startlines}$ [ <sub>...</sub> <sup>*</sup> ...] ... $\backslash\text{stoplines}$ * inherits: $\backslash\text{setuplines}$
$\backslash\text{startlinetable}$ ... $\backslash\text{stoplinetable}$
$\backslash\text{startlinetablebody}$ ... $\backslash\text{stoplinetablebody}$
$\backslash\text{startlinetablecell}$ [ <sub>...</sub> <sup>*</sup> ...] ... $\backslash\text{stoplinetablecell}$ * inherits: $\backslash\text{setuplinetable}$
$\backslash\text{startlinetablehead}$ ... $\backslash\text{stoplinetablehead}$
$\backslash\text{startlocalfootnotes}$ ... $\backslash\text{stoplocalfootnotes}$
$\backslash\text{startlocalheadsetup}$ ... $\backslash\text{stoplocalheadsetup}$

<pre> \startlocallinecorrection [...,*...] ... \stoplocallinecorrection  *   blank inherits: \blank </pre>
<pre> \startlocalnotes [...,*...] ... \stoplocalnotes  *   NAME </pre>
<pre> \startlocalsetups [...<sup>1</sup>.] [...<sup>2</sup>.] ... \stoplocalsetups  1   grid 2   NAME </pre>
<pre> \startlocalsetups .* ... \stoplocalsetups  *   NAME </pre>
<pre> \startlua ... \stoplua </pre>
<pre> \startluacode ... \stopluacode </pre>
<pre> \startluaparameterset [...] ... \stopluaparameterset  *   NAME </pre>
<pre> \startluasetups [...<sup>1</sup>.] [...<sup>2</sup>.] ... \stopluasetups  1   grid 2   NAME </pre>
<pre> \startluasetups .* ... \stopluasetups  *   NAME </pre>
<pre> \startMPclip {...} ... \stopMPclip  *   NAME </pre>
<pre> \startMPcode {...} ... \stopMPcode  *   NAME </pre>
<pre> \startMPdefinitions {...} ... \stopMPdefinitions  *   NAME </pre>
<pre> \startMPdrawing [...] ... \stopMPdrawing  *   - </pre>
<pre> \startMPenvironment [...] ... \stopMPenvironment  *   reset global + </pre>
<pre> \startMPextensions {...,*...} ... \stopMPextensions  *   NAME </pre>
<pre> \startMPinclusions [...<sup>1</sup>.] {...<sup>2</sup>.} ... \stopMPinclusions  1   + 2   NAME </pre>

<code>\startMPinitializations ... \stopMPinitializations</code>
<code>\startMPpage [...,*...,...] ... \stopMPpage</code> <code>* inherits: \setupfittingpage</code>
<code>\startMPpositiongraphic {...} {...,<sup>2</sup>...} ... \stopMPpositiongraphic</code> <code>1 NAME</code> <code>2 KEY</code>
<code>\startMPpositionmethod {...} ... \stopMPpositionmethod</code> <code>* NAME</code>
<code>\startMPrun {...} ... \stopMPrun</code> <code>* NAME</code>
<code>\startMP [...,*...,...] ... \stopMP</code> <code>* inherits: \setuptyping</code>
<code>\startMP [...,*...] ... \stopMP</code> <code>* continue</code>
<code>\startmakeup [...] [...,<sup>2</sup>...,...] ... \stopmakeup</code> <code>1 NAME</code> <code>2 inherits: \setupmakeup</code>
<code>\startmakeupmakeup [...,*...,...] ... \stopmakeupmakeup</code> <code>* inherits: \setupmakeup</code>  <code>instances: standard page text middle</code>
<code>\startmarginblock [...] ... \stopmarginblock</code> <code>* NAME</code>
<code>\startmarginrule [...] ... \stopmarginrule</code> <code>* NUMBER</code>
<code>\startmarginrule [...,*...,...] ... \stopmarginrule</code> <code>* inherits: \setupmarginrule</code>
<code>\startmarkedcontent [...] ... \stopmarkedcontent</code> <code>* reset <u>all</u> NAME</code>
<code>\startmathalignment [...,*...,...] ... \stopmathalignment</code> <code>* inherits: \setupmathalignment</code>
<code>\startmathalignment [...,*...,...] ... \stopmathalignment</code> <code>* inherits: \setupmathalignment</code>

$\backslash\mathrm{startmathcases} [\dots^* \dots] \dots \backslash\mathrm{stopmathcases}$ $\ast$ inherits: $\backslash\mathrm{setupmathcases}$
$\backslash\mathrm{startmathcases} [\dots^* \dots] \dots \backslash\mathrm{stopmathcases}$ $\ast$ inherits: $\backslash\mathrm{setupmathcases}$
$\backslash\mathrm{startmathlabeltext} [.^1.] [.^2.] \dots \backslash\mathrm{stopmathlabeltext}$ 1 LANGUAGE 2 KEY
$\backslash\mathrm{startmathmatrix} [\dots^* \dots] \dots \backslash\mathrm{stopmathmatrix}$ $\ast$ inherits: $\backslash\mathrm{setupmathmatrix}$
$\backslash\mathrm{startmathmatrix} [\dots^* \dots] \dots \backslash\mathrm{stopmathmatrix}$ $\ast$ inherits: $\backslash\mathrm{setupmathmatrix}$
$\backslash\mathrm{startmathmode} \dots \backslash\mathrm{stopmathmode}$
$\backslash\mathrm{startmathstyle} [\dots^* \dots] \dots \backslash\mathrm{stopmathstyle}$ $\ast$ display text script scriptscript cramped uncramped normal packed small big NAME
$\backslash\mathrm{startmatrices} [\dots^* \dots] \dots \backslash\mathrm{stopmatrices}$ $\ast$ inherits: $\backslash\mathrm{setupmathmatrix}$
$\backslash\mathrm{startmatrix} [\dots^* \dots] \dots \backslash\mathrm{stopmatrix}$ $\ast$ inherits: $\backslash\mathrm{setupmathmatrix}$
$\backslash\mathrm{startmaxaligned} \dots \backslash\mathrm{stopmaxaligned}$
$\backslash\mathrm{startmdformula} [\dots^* \dots] \dots \backslash\mathrm{stopmdformula}$ $\ast$ packed tight middle frame inherits: $\backslash\mathrm{setupbodyfont}$
$\backslash\mathrm{startmidaligned} \dots \backslash\mathrm{stopmidaligned}$
$\backslash\mathrm{startmiddlealigned} \dots \backslash\mathrm{stopmiddlealigned}$
$\backslash\mathrm{startmixedcolumns} [.^1.] [\dots.^2. \dots] \dots \backslash\mathrm{stopmixedcolumns}$ 1 NAME 2 inherits: $\backslash\mathrm{setupmixedcolumns}$
$\backslash\mathrm{startmixedcolumns} [\dots^* \dots] \dots \backslash\mathrm{stopmixedcolumns}$ $\ast$ inherits: $\backslash\mathrm{setupmixedcolumns}$
$\backslash\mathrm{startmode} [\dots^* \dots] \dots \backslash\mathrm{stopmode}$ $\ast$ NAME

`\startmodeset [...1,...] {...2} ... \stopmodeset`

1 NAME default

2 CONTENT

`\startmoduletestsection ... \stopmoduletestsection`

`\startmodule [...*] ... \stopmodule`

\* FILE

`\startmodule ...* ... \stopmodule`

\* FILE

`\startmpformula [...*,...] ... \stopmpformula`

\* packed tight middle frame inherits: \setupbodyfont

`\startnamedsection [...1] [...2,...] [...3,...] ... \stopnamedsection`

1 SECTION

2 title = TEXT  
bookmark = TEXT  
marking = TEXT  
list = TEXT  
reference = REFERENCE  
ownnumber = TEXT

3 KEY = VALUE

`\startnamedsubformulas [...1,...] {...2} ... \stopnamedsubformulas`

1 + - REFERENCE

2 TEXT

`\startnarrower [...*,...] ... \stopnarrower`

\* [-+]left [-+]middle [-+]right NUMBER\*left NUMBER\*middle NUMBER\*right reset

`\startnarrower [...*,...] ... \stopnarrower`

\* [-+]left [-+]middle [-+]right NUMBER\*left NUMBER\*middle NUMBER\*right reset

`\startnarrow [...1] [...2,...] ... \stopnarrow`

1 NAME

2 inherits: \setupnarrower

`\startnarrow [...1] [...2,...] ... \stopnarrow`

1 NAME

2 [-+]left [-+]middle [-+]right NUMBER\*left NUMBER\*middle NUMBER\*right reset

`\startnarrow [...1,...] [...2,...] ... \stopnarrow`

1 inherits: \setupnarrower

2 [-+]left [-+]middle [-+]right NUMBER\*left NUMBER\*middle NUMBER\*right reset

`\startnegative ... \stopnegative`

<pre> \startnicelyfilledbox [...,*=...,...] ... \stopnicelyfilledbox  *   width   = DIMENSION     height  = DIMENSION     offset  = DIMENSION     strut   = <u>yes</u> no </pre>
<pre> \startnointerference ... \stopnointerference </pre>
<pre> \startnop ... \stopnop </pre>
<pre> \startnotallmodes [...,*,...] ... \stopnotallmodes  *   NAME </pre>
<pre> \startnotext ... \stopnotext </pre>
<pre> \startnote [...,*=...,...] ... \stopnote  *   title      = TEXT     bookmark   = TEXT     list       = TEXT     reference   = REFERENCE </pre>
<pre> \startnote [...,*,...] ... \stopnote  *   REFERENCE </pre>
<pre> \startnotmode [...,*,...] ... \stopnotmode  *   NAME </pre>
<pre> \startoperator<sup>1</sup>text [...<sup>2</sup>] [...] ... \stopoperator<sup>2</sup>text  1   LANGUAGE 2   KEY </pre>
<pre> \startopposite ... \stopopposite </pre>
<pre> \startoutputstream [...] ... \stopoutputstream  *   NAME </pre>
<pre> \startoverlay ... \stopoverlay </pre>
<pre> \startoverprint ... \stopoverprint </pre>
<pre> \startPARSEDXML [...,*=...,...] ... \stopPARSEDXML  *   inherits: \setuptyping </pre>
<pre> \startPARSEDXML [...,*,...] ... \stopPARSEDXML  *   continue </pre>
<pre> \startpacked [...] ... \stoppacked  *   blank </pre>
<pre> \startpagecomment ... \stoppagecomment </pre>



`\startpagefigure [1...] [...2...] ... \stoppagefigure`

1 FILE

2 inherits: \setupexternalfigure

`\startpagegrid [1...] [...2...] ... \stoppagegrid`

1 NAME

2 inherits: \setuppagegrid

`\startpagegridspan [1...] [...2...] ... \stoppagegridspan`

1 NAME

2 inherits: \setuppagegridspan

`\startpagegrid [...*...] ... \stoppagegrid`

\* inherits: \setuppagegrid

`\startpagelayout [...*] ... \stoppagelayout`

\* page leftpage rightpage

`\startpar [1...] [...2...] ... \stoppar`

1 NAME

2 inherits: \setupparagraph

`\startparagraph [1...] [...2...] ... \stopparagraph`

1 NAME

2 inherits: \setupparagraph

`\startparagraphs [...*] ... \stopparagraphs`

\* NAME

`\startparagraphscell ... \stopparagraphscell`

`\startparagraphs ... \stopparagraphs`

`\startparallel ... \stopparallel`

`\startparbuilder [...*] ... \stopparbuilder`

\* default oneline basic NAME

`\startpart [...1...] [...2...] ... \stoppart`

1 title = TEXT  
bookmark = TEXT  
marking = TEXT  
list = TEXT  
reference = REFERENCE  
ownnumber = TEXT

2 KEY = VALUE

`\startplacechemical [...,\stackrel{1}{...},...] [...,\stackrel{2}{...},...] ... \stopplacechemical`

```
1 title      = TEXT
  bookmark   = TEXT
  marking    = TEXT
  list       = TEXT
  location   = split always left right inner outer backspace cutspace inleft inright inmargin leftmargin rightmargin
              leftedge rightedge innermargin outermargin inneredge outeredge text opposite reset height depth
              [-+]line halfline grid high low fit 90 180 270 nonumber none local here force margin [-+]hang
              hanging tall both middle offset top bottom auto page leftpage rightpage somewhere
  reference  = REFERENCE

2 KEY = VALUE
```

`\startplacefigure [...,\stackrel{1}{...},...] [...,\stackrel{2}{...},...] ... \stopplacefigure`

```
1 title      = TEXT
  bookmark   = TEXT
  marking    = TEXT
  list       = TEXT
  location   = split always left right inner outer backspace cutspace inleft inright inmargin leftmargin rightmargin
              leftedge rightedge innermargin outermargin inneredge outeredge text opposite reset height depth
              [-+]line halfline grid high low fit 90 180 270 nonumber none local here force margin [-+]hang
              hanging tall both middle offset top bottom auto page leftpage rightpage somewhere
  reference  = REFERENCE

2 KEY = VALUE
```

`\startplacefloat [...,\stackrel{1}{...},...] [...,\stackrel{2}{...},...] [...,\stackrel{3}{...},...] ... \stopplacefloat`

```
1 SINGULAR

2 title      = TEXT
  bookmark   = TEXT
  marking    = TEXT
  list       = TEXT
  location   = split always left right inner outer backspace cutspace inleft inright inmargin leftmargin rightmargin
              leftedge rightedge innermargin outermargin inneredge outeredge text opposite reset height depth
              [-+]line halfline grid high low fit 90 180 270 nonumber none local here force margin [-+]hang
              hanging tall both middle offset top bottom auto page leftpage rightpage somewhere
  reference  = REFERENCE

3 KEY = VALUE
```

`\startplacefloat [...,\stackrel{1}{...},...] [...,\stackrel{2}{...},...] ... \stopplacefloat`

```
1 title      = TEXT
  bookmark   = TEXT
  marking    = TEXT
  list       = TEXT
  location   = split always left right inner outer backspace cutspace inleft inright inmargin leftmargin rightmargin
              leftedge rightedge innermargin outermargin inneredge outeredge text opposite reset height depth
              [-+]line halfline grid high low fit 90 180 270 nonumber none local here force margin [-+]hang
              hanging tall both middle offset top bottom auto page leftpage rightpage somewhere
  reference  = REFERENCE

2 KEY = VALUE
```

`\startplaceformula [...,\stackrel{*}{...},...] ... \stopplaceformula`

```
* title      = TEXT
  suffix     = TEXT
  reference  = + - TEXT
```

`\startplaceformula [...,*...] ... \stopplaceformula`

```
* + - REFERENCE
```

`\startplacegraphic [...1...] [...2...] ... \stopplacegraphic`

```
1 title      = TEXT
  bookmark   = TEXT
  marking    = TEXT
  list       = TEXT
  location   = split always left right inner outer backspace cutspace inleft inright inmargin leftmargin rightmargin
              leftedge rightedge innermargin outermargin inneredge outeredge text opposite reset height depth
              [--]line halfline grid high low fit 90 180 270 nonumber none local here force margin [--]hang
              hanging tall both middle offset top bottom auto page leftpage rightpage somewhere
  reference  = REFERENCE

2 KEY = VALUE
```

`\startplaceintermezzo [...1...] [...2...] ... \stopplaceintermezzo`

```
1 title      = TEXT
  bookmark   = TEXT
  marking    = TEXT
  list       = TEXT
  location   = split always left right inner outer backspace cutspace inleft inright inmargin leftmargin rightmargin
              leftedge rightedge innermargin outermargin inneredge outeredge text opposite reset height depth
              [--]line halfline grid high low fit 90 180 270 nonumber none local here force margin [--]hang
              hanging tall both middle offset top bottom auto page leftpage rightpage somewhere
  reference  = REFERENCE

2 KEY = VALUE
```

`\startplacelegend [...*...] ... \stopplacelegend`

`* inherits: \setuppairedbox`

`\startplacepairedbox [1...] [...2...] ... \stopplacepairedbox`

```
1 NAME

2 inherits: \setuppairedbox
```

`\startplacepairedbox [...*...] ... \stopplacepairedbox`

`* inherits: \setuppairedbox`

`\startplacetable [...1...] [...2...] ... \stopplacetable`

```
1 title      = TEXT
  bookmark   = TEXT
  marking    = TEXT
  list       = TEXT
  location   = split always left right inner outer backspace cutspace inleft inright inmargin leftmargin rightmargin
              leftedge rightedge innermargin outermargin inneredge outeredge text opposite reset height depth
              [--]line halfline grid high low fit 90 180 270 nonumber none local here force margin [--]hang
              hanging tall both middle offset top bottom auto page leftpage rightpage somewhere
  reference  = REFERENCE

2 KEY = VALUE
```

`\startpositioning [1...] [...2...] ... \stoppositioning`

```
1 NAME

2 inherits: \setuppositioning
```

`\startpositionoverlay {...} ... \stoppositionoverlay`

`* NAME`

`\startpositive ... \stoppositive`

`\startpostponing [...] ... \stoppostponing`

`* [--]NUMBER`

<pre> \startprefixtext [...] [...] ... \stopprefixtext  1  LANGUAGE 2  KEY </pre>
<pre> \startprocessassignmentcommand [...,.*...,...] ... \stopprocessassignmentcommand  *  KEY = VALUE </pre>
<pre> \startprocessassignmentlist [...,.*...,...] ... \stopprocessassignmentlist  *  KEY = VALUE </pre>
<pre> \startprocesscommacommand [...,*...] ... \stopprocesscommacommand  *  COMMAND </pre>
<pre> \startprocesscommalist [...,*...] ... \stopprocesscommalist  *  COMMAND </pre>
<pre> \startproduct [...] ... \stopproduct  *  FILE * </pre>
<pre> \startproduct ... ... \stopproduct  *  FILE * </pre>
<pre> \startproject [...] ... \stopproject  *  FILE * </pre>
<pre> \startproject ... ... \stopproject  *  FILE * </pre>
<pre> \startprotectedcolors ... \stopprotectedcolors </pre>
<pre> \startpsh [...] ... \stoppsh  *  REFERENCE </pre>
<pre> \startpublication [.¹.] [...,.*²...,...] ... \stoppublication  1  NAME 2  tag      = REFERENCE    category = TEXT    k        = REFERENCE    t        = TEXT </pre>
<pre> \startquotation [...,*...] ... \stopquotation  *  inherits: \startnarrower </pre>
<pre> \startquote ... \stopquote </pre>
<pre> \starandomized ... \stoprandomized </pre>

```
1  grid
2  NAME
```

\* NAME

## \* REFERENCE

```
* inherits: \enableregime
```

```

1  NAME
2  NAME
3  TEXT
4  TEXT PROCESSOR->TEXT
5  INDEX

```

```
1  NAME
2  KEY
```

## \* REFERENCE

```
* hangul hanzi nihongo ethiopic thai test NAME
```

\* packed tight middle frame inherits: \setupbodyfont

```
1  title      = TEXT
   bookmark   = TEXT
   marking    = TEXT
   list       = TEXT
   reference  = REFERENCE
   ownnumber  = TEXT

2  KEY = VALUE
```

<pre> \startsectionblock [...<sup>1</sup>] [...<sup>2</sup>...,...] ... \stopsectionblock  1  NAME  2  bookmark = TEXT     inherits: \setupsectionblock </pre>
<pre> \startsectionblockenvironment [...<sup>*</sup>] ... \stopsectionblockenvironment  *  NAME </pre>
<pre> \startsectionblock [...<sup>*</sup>...,...] ... \stopsectionblock  *  bookmark = TEXT     inherits: \setupsectionblock </pre>
<pre> \startsectionlevel [...<sup>1</sup>.] [...<sup>2</sup>...,...] [...<sup>3</sup>...,...] ... \stopsectionlevel  1  NAME  2  title      = TEXT     bookmark  = TEXT     marking   = TEXT     list      = TEXT     reference = REFERENCE     ownnumber = TEXT  3  KEY = VALUE </pre>
<pre> \startsection [...<sup>1</sup>...,...] [...<sup>2</sup>...,...] ... \stopsection  1  title      = TEXT     bookmark  = TEXT     marking   = TEXT     list      = TEXT     reference = REFERENCE     ownnumber = TEXT  2  KEY = VALUE </pre>
<pre> \startsetups [...<sup>1</sup>.] [...<sup>2</sup>.] ... \stopsetups  1  grid  2  NAME </pre>
<pre> \startsetups ... .. \stopsetups  *  NAME </pre>
<pre> \startshift [...<sup>*</sup>.] ... \stopshift  *  NAME </pre>
<pre> \startsidebar [...<sup>1</sup>.] [...<sup>2</sup>...,...] ... \stopsidebar  1  NAME  2  inherits: \setupsidebar </pre>
<pre> \startsimplecolumns [...<sup>*</sup>...,...] ... \stopsimplecolumns  *  inherits: \setsimplecolumnhsize </pre>
<pre> \startspecialitem [...<sup>1</sup>.] [...<sup>2</sup>,...] ... \stopspecialitem  1  <u>item</u>  2  REFERENCE </pre>

`\startspecialitem [...]1 {...}2 ... \stopspecialitem`

1 sym ran mar

2 TEXT

`\startspecialitem [...]* ... \stopspecialitem`

\* sub its

`\startspeech [...,*...] ... \stopspeech`

\* inherits: \startnarrower

`\startspformula [...,*...] ... \stopspformula`

\* packed tight middle frame inherits: \setupbodyfont

`\startspread ... \stopspread`

`\start [...]* ... \stop`

\* NAME

`\startstartstop ... \stopstartstop`

`\startstaticMPfigure {...}* ... \stopstaticMPfigure`

\* NAME

`\startstaticMPgraphic {...}1 {...,2...} ... \stopstaticMPgraphic`

1 NAME

2 KEY

`\startstop {...}*`

\* CONTENT

`\startstrictinspectnextcharacter ... \stopstrictinspectnextcharacter`

`\startstructurepageregister [...]1 [...]2 [...,3...,...] [...,4...,...]`

1 NAME

2 NAME

3 label = NAME  
keys = TEXT PROCESSOR->TEXT  
entries = TEXT PROCESSOR->TEXT  
keys:1 = TEXT  
keys:2 = TEXT  
keys:3 = TEXT  
entries:1 = TEXT  
entries:2 = TEXT  
entries:3 = TEXT  
alternative = TEXT

4 KEY = VALUE

`\startstyle ... \stopstyle`

`\startstyle [...]* ... \stopstyle`

\* NAME FONT

`\startstyle [...,..1...,...] ... \stopstyle`

`* inherits: \setupstyle`

`\startsubformulas [...,..*...,...] ... \stopsubformulas`

`* + - REFERENCE`

`\startsubject [...,..1...,...] [...,..2...,...] ... \stopsubject`

1 title = TEXT  
bookmark = TEXT  
marking = TEXT  
list = TEXT  
reference = REFERENCE  
ownnumber = TEXT

2 KEY = VALUE

`\startsubjectlevel [...,..1...,...] [...,..2...,...] [...,..3...,...] ... \stopsubjectlevel`

1 NAME

2 title = TEXT  
bookmark = TEXT  
marking = TEXT  
list = TEXT  
reference = REFERENCE  
ownnumber = TEXT

3 KEY = VALUE

`\startsubsection [...,..1...,...] [...,..2...,...] ... \stopsubsection`

1 title = TEXT  
bookmark = TEXT  
marking = TEXT  
list = TEXT  
reference = REFERENCE  
ownnumber = TEXT

2 KEY = VALUE

`\startsubsentence ... \stopsubsentence`

`\startsubstack ... \stopsubstack`

`\startsubsubject [...,..1...,...] [...,..2...,...] ... \stopsubsubject`

1 title = TEXT  
bookmark = TEXT  
marking = TEXT  
list = TEXT  
reference = REFERENCE  
ownnumber = TEXT

2 KEY = VALUE

`\startsubsubsection [...,..1...,...] [...,..2...,...] ... \stopsubsubsection`

1 title = TEXT  
bookmark = TEXT  
marking = TEXT  
list = TEXT  
reference = REFERENCE  
ownnumber = TEXT

2 KEY = VALUE



`\startsubsubsubject [...,\subscript{1}...,...]\stopsubsubsubject`

```
1 title      = TEXT
  bookmark   = TEXT
  marking     = TEXT
  list        = TEXT
  reference   = REFERENCE
  ownnumber   = TEXT
```

```
2 KEY = VALUE
```

`\startsubsubsubsection [...,\subscript{1}...,...]\stopsubsubsubsection`

```
1 title      = TEXT
  bookmark   = TEXT
  marking     = TEXT
  list        = TEXT
  reference   = REFERENCE
  ownnumber   = TEXT
```

```
2 KEY = VALUE
```

`\startsubsubsubsubject [...,\subscript{1}...,...]\stopsubsubsubsubject`

```
1 title      = TEXT
  bookmark   = TEXT
  marking     = TEXT
  list        = TEXT
  reference   = REFERENCE
  ownnumber   = TEXT
```

```
2 KEY = VALUE
```

`\startsubsubsubsubsection [...,\subscript{1}...,...]\stopsubsubsubsubsection`

```
1 title      = TEXT
  bookmark   = TEXT
  marking     = TEXT
  list        = TEXT
  reference   = REFERENCE
  ownnumber   = TEXT
```

```
2 KEY = VALUE
```

`\startsubsubsubsubsubject [...,\subscript{1}...,...]\stopsubsubsubsubsubject`

```
1 title      = TEXT
  bookmark   = TEXT
  marking     = TEXT
  list        = TEXT
  reference   = REFERENCE
  ownnumber   = TEXT
```

```
2 KEY = VALUE
```

`\startsymbolset [...] \stopsymbolset`

```
* NAME
```

`\startTABLE [...,\superscript{1}...,...]\stopTABLE`

```
* inherits: \setupTABLE
```

`\startTABLEbody [...,\superscript{1}...,...]\stopTABLEbody`

```
* inherits: \setupTABLE
```

`\startTABLEfoot [...,\superscript{1}...,...]\stopTABLEfoot`

```
* inherits: \setupTABLE
```

<code>\startTABLEhead [...,\stackrel{...}{...}] ... \stopTABLEhead</code> <code>* inherits: \setupTABLE</code>
<code>\startTABLEnext [...,\stackrel{...}{...}] ... \stopTABLEnext</code> <code>* inherits: \setupTABLE</code>
<code>\startTEXpage [...,\stackrel{...}{...}] ... \stopTEXpage</code> <code>* inherits: \setupfittingpage</code>
<code>\startTEX [...,\stackrel{...}{...}] ... \stopTEX</code> <code>* inherits: \setuptyping</code>
<code>\startTEX [...,\stackrel{...}{...}] ... \stopTEX</code> <code>* continue</code>
<code>\starttablehead [...,\stackrel{...}{...}] ... \stoptablehead</code> <code>* NAME</code>
<code>\starttables [...,\stackrel{...}{...}] ... \stoptables</code> <code>* TEMPLATE</code>
<code>\starttables [...,\stackrel{...}{...}] ... \stoptables</code> <code>* NAME</code>
<code>\starttabletail [...,\stackrel{...}{...}] ... \stoptabletail</code> <code>* NAME</code>
<code>\starttabletext [...,\stackrel{1}{...}] [...,\stackrel{2}{...}] {\stackrel{3}{...}} ... \stoptabletext</code> 1 split always left right inner outer backspace cutspace inleft inright inmargin leftmargin rightmargin leftedge rightedge innermargin outermargin inneredge outeredge text opposite reset height depth [-+]line halfline grid high low fit 90 180 270 nonumber none local here force margin [-+]hang hanging tall both middle offset top bottom auto page leftpage rightpage somewhere 2 REFERENCE 3 TEXT
<code>\starttable [...,\stackrel{1}{...}] [...,\stackrel{2}{...}] ... \stoptable</code> 1 TEMPLATE 2 inherits: \setuptables
<code>\starttable [...,\stackrel{1}{...}] [...,\stackrel{2}{...}] ... \stoptable</code> 1 NAME 2 inherits: \setuptables
<code>\starttabulate [...,\stackrel{1}{...}] [...,\stackrel{2}{...}] ... \stoptabulate</code> 1 TEMPLATE 2 inherits: \setuptabulate
<code>\starttabulatehead [...,\stackrel{...}{...}] ... \stoptabulatehead</code> <code>* NAME</code>

<code>\starttabulatetail [...] ... \stoptabulatetail</code> <code>* NAME</code>
<code>\starttabulate [<sup>1</sup>.] [...,<sup>2</sup>...,...] ... \stoptabulate</code> <code>1 NAME</code> <code>2 inherits: \setuptabulate</code>
<code>\starttabulation [<sup>1</sup>.] [...,<sup>2</sup>...,...] ... \stoptabulation</code> <code>1 NAME</code> <code>2 inherits: \setuptabulation</code>
<code>\starttaglabeltext [<sup>1</sup>.] [<sup>2</sup>.] ... \stoptaglabeltext</code> <code>1 LANGUAGE</code> <code>2 KEY</code>
<code>\starttexcode ... \stoptexcode</code>
<code>\starttexdefinition <sup>1</sup>... <sup>2</sup>... <sup>3</sup>... <sup>4</sup>... <sup>5</sup>... <sup>6</sup>... ... \stoptexdefinition</code> <code>1 spaces nospaces</code> <code>2 global</code> <code>3 unexpanded</code> <code>4 expanded</code> <code>5 NAME</code> <code>6 TEMPLATE</code>
<code>\starttext ... \stoptext</code>
<code>\starttextbackground [<sup>1</sup>.] [...,<sup>2</sup>...,...] ... \stoptextbackground</code> <code>1 NAME</code> <code>2 inherits: \setuptextbackground</code>
<code>\starttextbackgroundmanual ... \stoptextbackgroundmanual</code>
<code>\starttextbackground [...,<sup>*</sup>...,...] ... \stoptextbackground</code> <code>* inherits: \setuptextbackground</code>
<code>\starttextcolor [...] ... \stoptextcolor</code> <code>* COLOR</code>
<code>\starttextcolorintent ... \stoptextcolorintent</code>
<code>\starttextflow [...] ... \stoptextflow</code> <code>* NAME</code>
<code>\starttextrule {...} ... \stoptextrule</code> <code>* TEXT</code>

`\starttitle [...1...] [...2...] ... \stoptitle`

1 title = TEXT  
bookmark = TEXT  
marking = TEXT  
list = TEXT  
reference = REFERENCE  
ownnumber = TEXT

2 KEY = VALUE

`\starttokens [...] ... \stoptokens`

\* NAME

`\starttransparent [...] ... \stoptransparent`

\* COLOR

`\starttxt ... \stoptxt`

`\starttypescript [...1...] [...2...] [...3...] ... \stoptypescript`

1 serif sans mono math handwriting calligraphy

2 NAME

3 size name

`\starttypescriptcollection [...] ... \stoptypescriptcollection`

\* NAME

`\starttyping [...*...] ... \stoptyping`

\* inherits: \setuptyping

`\starttyping [...*...] ... \stoptyping`

\* continue

`\starttyping [...*...] ... \stoptyping`

\* inherits: \setuptyping

`\starttyping [...*...] ... \stoptyping`

\* continue

`\startuniqueMPgraphic {...1} {...2...} ... \stopuniqueMPgraphic`

1 NAME

2 KEY

`\startuniqueMPpagegraphic {...1} {...2...} ... \stopuniqueMPpagegraphic`

1 NAME

2 KEY

`\startunittext [...1] [...2] ... \stopunittext`

1 LANGUAGE

2 KEY

`\startunpacked ... \stopunpacked`

```
1  NAME
2  KEY
```

```
1  NAME
2  KEY
```

\* CSNAME

\* NAME

\startvboxtohboxseparator ... \stopvboxtohboxseparator

\* NAME

```
* inherits: \setuptyping
```

```
* continue
```

```
1  NAME
2  nx  =  NUMBER
   ny  =  NUMBER
   nc  =  NUMBER
   nr  =  NUMBER
   inherits: \setupxtable
```

```
1  NAME
2  inherits: \setupxtable
```

```
1  NAME
2  inherits: \setupxtable
```

\* NAME

\* NAME

<code>\startxmlraw ... \stopxmlraw</code>
<code>\startxmlsetups [...] [...] ... \stopxmlsetups</code> 1 <code>grid</code> 2 <code>NAME</code>
<code>\startxmlsetups ... .. \stopxmlsetups</code> * <code>NAME</code>
<code>\startxrow [...] [...] ... \stopxrow</code> 1 <code>NAME</code> 2 <code>inherits: \setupxtable</code>
<code>\startxrowgroup [...] [...] ... \stopxrowgroup</code> 1 <code>NAME</code> 2 <code>inherits: \setupxtable</code>
<code>\startxtablebody [..., ...*..., ...] ... \stopxtablebody</code> * <code>inherits: \setupxtable</code>
<code>\startxtablebody [...] ... \stopxtablebody</code> * <code>NAME</code>
<code>\startxtablefoot [..., ...*..., ...] ... \stopxtablefoot</code> * <code>inherits: \setupxtable</code>
<code>\startxtablefoot [...] ... \stopxtablefoot</code> * <code>NAME</code>
<code>\startxtablehead [..., ...*..., ...] ... \stopxtablehead</code> * <code>inherits: \setupxtable</code>
<code>\startxtablehead [...] ... \stopxtablehead</code> * <code>NAME</code>
<code>\startxtablenext [..., ...*..., ...] ... \stopxtablenext</code> * <code>inherits: \setupxtable</code>
<code>\startxtablenext [...] ... \stopxtablenext</code> * <code>NAME</code>
<code>\startxtable [..., ...*..., ...] ... \stopxtable</code> * <code>inherits: \setupxtable</code>
<code>\startxtable [..., ...*..., ...] ... \stopxtable</code> * <code>inherits: \setupxtable</code>

<code>\startxtable [...]</code> ... <code>\stopxtable</code>  *    NAME
<code>\stopline [...]</code>  *    REFERENCE
<code>\stoplinenote [...]</code>  *    REFERENCE
<code>\stoplinenote [...]</code>  *    REFERENCE
<code>\stopregister [...]</code> <code>[...]</code>  1    NAME 2    NAME
<code>\stopstructurepageregister [...]</code> <code>[...]</code>  1    NAME 2    NAME
<code>\stretched [...]</code> <code>...<sup>1</sup>...</code> <code>{...<sup>2</sup>}</code>  1    inherits: <code>\setupstretched</code> 2    TEXT
<code>\strictdoifelsenextoptional {...}</code> <code>{...<sup>2</sup>}</code>  1    TRUE 2    FALSE
<code>\strictdoifnextoptionalelse {...}</code> <code>{...<sup>2</sup>}</code>  1    TRUE 2    FALSE
<code>\stripcharacter ...<sup>1</sup></code> <code>\from ...<sup>2</sup></code> <code>\to ...<sup>3</sup></code>  1    CHARACTER 2    TEXT 3    CSNAME
<code>\strippedcsname \...</code>  *    CSNAME
<code>\strippedcsname ...</code>  *    TEXT
<code>\stripspaces \from ...<sup>1</sup></code> <code>\to ...<sup>2</sup></code>  1    TEXT 2    CSNAME

<code>\structurelistuservariable {...}</code> * KEY
<code>\structurenumber</code>
<code>\structuretitle</code>
<code>\structureuservariable {...}</code> * KEY
<code>\structurevariable {...}</code> * KEY
<code>\strut</code>
<code>\strutdp</code>
<code>\strutht</code>
<code>\struthtdp</code>
<code>\struttedbox {...}</code> * CONTENT
<code>\strutwd</code>
<code>\styleinstance [...]</code> * NAME
<code>\style {...}</code> * TEXT
<code>\style [...<sup>1</sup>] {...<sup>2</sup>}</code> 1 NAME FONT 2 TEXT
<code>\style [...,<sup>1</sup>...<sup>2</sup>] {...}</code> 1 inherits: \setupstyle 2 TEXT
<code>\subject [...,<sup>1</sup>...] {...<sup>2</sup>}</code> 1 REFERENCE 2 TEXT
<code>\subpagenumber</code>
<code>\subsection [...,<sup>1</sup>...] {...<sup>2</sup>}</code> 1 REFERENCE 2 TEXT



<code>\subsentence {...}</code>  *    CONTENT
<code>\substituteincommalist {...} {...} \...</code>  1    TEXT 2    TEXT 3    CSNAME
<code>\subsubject [...,<sup>1</sup>...] {...}</code>  1    REFERENCE 2    TEXT
<code>\subsubsection [...,<sup>1</sup>...] {...<sup>2</sup>}</code>  1    REFERENCE 2    TEXT
<code>\subsubsubject [...,<sup>1</sup>...] {...<sup>2</sup>}</code>  1    REFERENCE 2    TEXT
<code>\subsubsubsection [...,<sup>1</sup>...] {...<sup>2</sup>}</code>  1    REFERENCE 2    TEXT
<code>\subsubsubsubject [...,<sup>1</sup>...] {...<sup>2</sup>}</code>  1    REFERENCE 2    TEXT
<code>\subsubsubsubsection [...,<sup>1</sup>...] {...<sup>2</sup>}</code>  1    REFERENCE 2    TEXT
<code>\subsubsubsubsubject [...,<sup>1</sup>...] {...<sup>2</sup>}</code>  1    REFERENCE 2    TEXT
<code>\subsubsubsubsubsection [...,<sup>1</sup>...] {...<sup>2</sup>}</code>  1    REFERENCE 2    TEXT
<code>\subsubtractfeature [...]</code>  *    NAME
<code>\subsubtractfeature {...}</code>  *    NAME
<code>\sub</code>
<code>\swapcounts \... \...</code>  1    CSNAME 2    CSNAME

<code>\swapdimens \<sup>1</sup> \<sup>2</sup></code>  1 CSNAME 2 CSNAME
<code>\swapface</code>
<code>\swapmacros \<sup>1</sup> \<sup>2</sup></code>  1 CSNAME 2 CSNAME
<code>\swaptypeface</code>
<code>\switchstyleonly [...]</code>  * rm ss tt hw cg roman serif regular sans sansserif support type teletype mono handwritten calligraphic
<code>\switchstyleonly \*</code>  * CSNAME
<code>\switchtobodyfont [...*,...]</code>  * inherits: \setupbodyfont
<code>\switchtocolour [...]</code>  * COLOR
<code>\switchtointerlinespace [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]</code>  1 NAME 2 inherits: \setupinterlinespace
<code>\switchtointerlinespace [...*,...]</code>  * on off reset auto small medium big NUMBER DIMENSION
<code>\switchtointerlinespace [...]</code>  * NAME
<code>\symbolreference [...]</code>  * REFERENCE
<code>\symbol [...<sup>1</sup>] [...<sup>2</sup>]</code>  1 NAME 2 NAME
<code>\symbol {...}</code>  * NAME
<code>\sym {...}</code>  * TEXT
<code>\synchronizeblank</code>

<code>\synchronizeindenting</code>
<code>\synchronizemarking [...]<sup>1</sup> [...]<sup>2</sup> [...]<sup>3</sup></code> 1    MARK 2    NUMBER 3    keep
<code>\synchronizeoutputstreams [...,*,...]</code> *    NAME
<code>\synchronizestrut {...<sup>*</sup>}</code> *    yes no auto cap fit line default CHARACTER
<code>\synchronizewhitespace</code>
<code>\synonym [...]<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup></code> 1    NAME 2    TEXT 3    CONTENT
<code>\systemlog {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup></code> 1    FILE 2    TEXT 3    TEXT
<code>\systemlogfirst {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup></code> 1    FILE 2    TEXT 3    TEXT
<code>\systemloglast {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup></code> 1    FILE 2    TEXT 3    TEXT
<code>\systemsetups {...<sup>*</sup>}</code> *    NAME
<code>\TABLE</code>
<code>\TaBlE</code>
<code>\TEX</code>
<code>\TeX</code>
<code>\TheNormalizedFontSize</code>

<code>\TransparencyHack</code>
<code>\tabulateautoline</code>
<code>\tabulateautorule</code>
<code>\tabulateline</code>
<code>\tabulaterule</code>
<code>\taggedctxcommand {...}</code> *    COMMAND
<code>\taggedlabeltexts {...} {...} {...}</code> 1    NAME 2    NAME 3    CONTENT
<code>\taglabellanguage</code>
<code>\taglabeltext {...}</code> *    KEY
<code>\tbinom {...} {...}</code> 1    CONTENT 2    CONTENT
<code>\tbox {...}</code> *    CONTENT
<code>\tequal {...} {...}</code> 1    TEXT 2    TEXT
<code>\testandsplitstring .<sup>1</sup>. \at .<sup>2</sup>. \to \<sup>3</sup>. \and \<sup>4</sup>.</code> 1    TEXT 2    TEXT 3    CSNAME 4    CSNAME
<code>\testcolumn [...] [...]</code> 1    NUMBER 2    DIMENSION
<code>\testfeature {...}</code> *    NUMBER

<pre> \testfeatureonce {...}  *   NUMBER </pre>
<pre> \testpage [...] [...]  1   NUMBER 2   DIMENSION </pre>
<pre> \testpageonly [...] [...]  1   NUMBER 2   DIMENSION </pre>
<pre> \testpagesync [...] [...]  1   NUMBER 2   DIMENSION </pre>
<pre> \testtokens [...]  *   NAME </pre>
<pre> \tex {...}  *   CONTENT </pre>
<pre> \texdefinition {...}  *   NAME </pre>
<pre> \texsetup {...}  *   NAME </pre>
<pre> \textbackground {...}  *   CONTENT </pre>
<pre> \textcitation [...,\u{1}...,...] [...]  1   reference    = REFERENCE     alternative  = default category entry short page num textnum year index tag keywords author authoryears authornum                   authoryear     before       = COMMAND     after        = COMMAND     left         = COMMAND     right        = COMMAND     inherits:    \setupbtx  2   REFERENCE </pre>
<pre> \textcitation [...,\u{1}...,...] [...,\u{2}...,...]  1   reference    = REFERENCE     alternative  = default category entry short page num textnum year index tag keywords author authoryears authornum                   authoryear     before       = COMMAND     after        = COMMAND     left         = COMMAND     right        = COMMAND     inherits:    \setupbtx  2   KEY = VALUE </pre>

`\textcitation [...]1 [...]2`

1 default category entry short page num textnum year index tag keywords author authoryears authornum authoryear  
2 REFERENCE

`\textcite [...]1 [...]2`

1 reference = REFERENCE  
alternative = default category entry short page num textnum year index tag keywords author authoryears authornum  
authoryear  
before = COMMAND  
after = COMMAND  
left = COMMAND  
right = COMMAND  
inherits: \setupbtx  
2 REFERENCE

`\textcite [...]1 [...]2`

1 reference = REFERENCE  
alternative = default category entry short page num textnum year index tag keywords author authoryears authornum  
authoryear  
before = COMMAND  
after = COMMAND  
left = COMMAND  
right = COMMAND  
inherits: \setupbtx  
2 KEY = VALUE

`\textcite [...]1 [...]2`

1 default category entry short page num textnum year index tag keywords author authoryears authornum authoryear  
2 REFERENCE

`\textcontrolspace`

`\textflowcollector {...}`

\* NAME

`\textmath {...}`

\* CONTENT

`\textminus`

`\textormathchar {...}`

\* NUMBER

`\textplus`

`\textreference [...]1 [...]2`

1 REFERENCE  
2 TEXT

`\textrule [...]1 [...]2`

1 top middle bottom  
2 TEXT

`\textvisiblespace`

$\backslash\mathrm{tfrac}\{\dots\}\{\dots\}$  1    CONTENT 2    CONTENT
$\backslash\mathrm{thai}$
$\backslash\mathrm{thainumerals}\{\dots\}$  *    NUMBER
$\backslash\mathrm{thefirstcharacter}\{\dots\}$  *    TEXT
$\backslash\mathrm{thenormalizedbodyfontsize}\{\dots\}$  *    DIMENSION
$\backslash\mathrm{theremainingcharacters}\{\dots\}$  *    TEXT
$\backslash\mathrm{thickspace}$
$\backslash\mathrm{thinrule}$
$\backslash\mathrm{thinrules}\left[\dots,\dots^*\dots,\dots\right]$  *    inherits: $\backslash\mathrm{setupthinrules}$
$\backslash\mathrm{thinspace}$
$\backslash\mathrm{thirdoffivearguments}\{\dots\}\{\dots\}\{\dots\}\{\dots\}\{\dots\}$  1    TEXT 2    TEXT 3    TEXT 4    TEXT 5    TEXT
$\backslash\mathrm{thirdoffourarguments}\{\dots\}\{\dots\}\{\dots\}\{\dots\}$  1    TEXT 2    TEXT 3    TEXT 4    TEXT
$\backslash\mathrm{thirdofsixarguments}\{\dots\}\{\dots\}\{\dots\}\{\dots\}\{\dots\}\{\dots\}$  1    TEXT 2    TEXT 3    TEXT 4    TEXT 5    TEXT 6    TEXT

`\thirdofthreearguments {...} {...} {...}`

- 1 TEXT
- 2 TEXT
- 3 TEXT

`\thirdofthreeunexpanded {...} {...} {...}`

- 1 TEXT
- 2 TEXT
- 3 TEXT

`\thookleftarrow {...} {...}`

- 1 TEXT
- 2 TEXT

`\thookrightarrow {...} {...}`

- 1 TEXT
- 2 TEXT

`\threedigitrounding {...}`

- \* NUMBER

`\tibetannumerals {...}`

- \* NUMBER

`\tightlayer [...]`

- \* NAME

`\tilde {...}`

- \* CHARACTER

`\tinyfont`

`\title [...,1...] {...}`

- 1 REFERENCE
- 2 TEXT

`\tleftarrow {...} {...}`

- 1 TEXT
- 2 TEXT

`\tleftrightarrow {...} {...}`

- 1 TEXT
- 2 TEXT

`\tlap {...}`

- \* CONTENT



`\tleftarrow {...} {...}`

1 TEXT

2 TEXT

`\tleftharpoondown {...} {...}`

1 TEXT

2 TEXT

`\tleftharpoonup {...} {...}`

1 TEXT

2 TEXT

`\tleftrightarrow {...} {...}`

1 TEXT

2 TEXT

`\tleftrightharpoons {...} {...}`

1 TEXT

2 TEXT

`\tmapsto {...} {...}`

1 TEXT

2 TEXT

`\tochar {...}`

\* NAME

`\tolinenote [...]`

\* REFERENCE

`\tooltip [...1...] {...} {...}`

1 inherits: \setuptooltip

2 TEXT

3 TEXT

`\tooltip [...1] {...} {...}`

1 left middle right

2 TEXT

3 TEXT

`\tooltip [...1...] {...} {...}`

1 inherits: \setuptooltip

2 TEXT

3 TEXT

<code>\tooltip [...]{...}{...}</code>  1    left middle right 2    TEXT 3    TEXT
<code>\topbox {...}</code>  *    CONTENT
<code>\topleftbox {...}</code>  *    CONTENT
<code>\toplinebox {...}</code>  *    CONTENT
<code>\toprightbox {...}</code>  *    CONTENT
<code>\topskippedbox {...}</code>  *    CONTENT
<code>\tRightarrow {...}{...}</code>  1    TEXT 2    TEXT
<code>\tracecatcodetables</code>
<code>\tracedfontname {...}</code>  *    FONT
<code>\traceoutputroutines</code>
<code>\tracepositions</code>
<code>\translate [...]*...]</code>  *    LANGUAGE    =    TEXT
<code>\transparencycomponents {...}</code>  *    COLOR
<code>\transparent [...]{...}</code>  1    COLOR 2    CONTENT
<code>\trel {...}{...}</code>  1    TEXT 2    TEXT

$\rightarrow$ $\text{\trightarrow}$ {...} {...} 1    TEXT 2    TEXT
$\downarrow$ $\text{\trightharpoonowdown}$ {...} {...}
$\uparrow$ $\text{\trightharpoonoup}$ {...} {...}
$\rightleftarrows$ $\text{\trightleftatharpoons}$ {...} {...}
$\overrightarrow{\leftarrow}$ $\text{\trightoverleftarrow}$ {...} {...}
$\equiv$ $\text{\triplebond}$
$\text{\truefilename}$ {...} *    FILE
$\text{\truefontname}$ {...} *    FONT
$\text{\ttraggedright}$
$\text{\ttriplerel}$ {...} {...}
$\twoheadleftarrow$ $\text{\ttwoheadleftarrow}$ {...} {...}
$\twoheadrightarrow$ $\text{\ttwoheadrightarrow}$ {...} {...}
$\text{\twodigitrounding}$ {...}
$\text{\tx}$

<p><code>\txt ... \</code></p> <p>* TEXT</p>
<p><code>\txt {...} [...<sup>2</sup>,...]</code></p> <p>1 TEXT</p> <p>2 REFERENCE</p>
<p><code>\txx</code></p>
<p><code>\typebuffer [...<sup>1</sup>,...] [...<sup>2</sup>,...]</code></p> <p>1 BUFFER</p> <p>2 inherits: \setuptyping</p>
<p><code>\typebuffer [...<sup>*</sup>,...]</code></p> <p>* inherits: \setuptyping</p>
<p><code>\typedefinedbuffer [...<sup>1</sup>] [...<sup>2</sup>,...]</code></p> <p>1 BUFFER</p> <p>2 inherits: \setuptyping</p>
<p><code>\typeface</code></p>
<p><code>\typefile [...<sup>1</sup>] [...<sup>2</sup>,...] {...<sup>3</sup>}</code></p> <p>1 NAME</p> <p>2 inherits: \setuptyping</p> <p>3 FILE</p>
<p><code>\typescriptone</code></p>
<p><code>\typescriptprefix {...}</code></p> <p>* NAME</p>
<p><code>\typescriptthree</code></p>
<p><code>\typescripttwo</code></p>
<p><code>\typesetbuffer [...<sup>1</sup>] [...<sup>2</sup>,...]</code></p> <p>1 * BUFFER</p> <p>2 inherits: \setupexternalfigure</p>
<p><code>\typesetfile [...<sup>1</sup>] [...<sup>2</sup>] [...<sup>3</sup>,...]</code></p> <p>1 NAME FILE</p> <p>2 FILE TEXT</p> <p>3 inherits: \setupexternalfigure</p>
<p><code>\type [...<sup>1</sup>,...] {...<sup>2</sup>}</code></p> <p>1 inherits: \setuptype</p> <p>2 CONTENT</p>

$\backslash type [\dots\overset{1}{=}\dots] <<\overset{2}{\dots}>$ 1 inherits: $\backslash setuptype$ 2 ANGLES
$\backslash type [\dots\overset{1}{=}\dots] \{\overset{2}{\dots}\}$ 1 inherits: $\backslash setuptype$ 2 CONTENT
$\backslash type [\dots\overset{1}{=}\dots] <<\overset{2}{\dots}>$ 1 inherits: $\backslash setuptype$ 2 ANGLES
$\backslash typ [\dots\overset{1}{=}\dots] \{\overset{2}{\dots}\}$ 1 inherits: $\backslash setuptype$ 2 CONTENT
$\backslash typ [\dots\overset{1}{=}\dots] <<\overset{2}{\dots}>$ 1 inherits: $\backslash setuptype$ 2 ANGLES
$\backslash uconvertnumber \{\overset{1}{\dots}\} \{\overset{2}{\dots}\}$ 1 inherits: $\backslash convertnumber$ 2 NUMBER
$\backslash uedcatcodecommand \overset{1}{\dots} \overset{2}{\dots} \{\overset{3}{\dots}\}$ 1 CSNAME 2 CHARACTER NUMBER 3 COMMAND
$\backslash undefinevalue \{\dots\}$ * NAME
$\backslash undepthed \{\dots\}$ * CONTENT
$\backslash underbar \{\dots\}$ * CONTENT
$\backslash underbars \{\dots\}$ * CONTENT
$\backslash underbartext \{\overset{1}{\dots}\} \{\overset{2}{\dots}\}$ 1 TEXT 2 TEXT
$\backslash underbrace \{\dots\}$ * TEXT

$$\underbrace{\text{...}}^{.1} \underbrace{\text{...}}^{.2}$$

1 TEXT

2 TEXT

`\underbracket {.*.}`

\* TEXT

`\underbrackettext {..1..} {..2..}`

1 TEXT

2 TEXT

$$\backslash\underdash \{.\!.\!.\}$$

\* CONTENT

`\underdashes {...}`

\* CONTENT

 $\backslash\mathrm{underdot} \{.\!.\!. \}$ 

\* CONTENT

 $\backslash\mathrm{underdotes}\{.\!.\!.\}^*$ 

\* CONTENT

 $\underleftarrow{\{...\}}$ 

\* TEXT

 $\underleftarrow{\hspace{1cm}} \{...\}$ 

\* TEXT

 $\underleftarrow{\hspace{1.5cm}} \{...\}$ 

\* TEXT

 $\underleftrightarrow{...}$ 

\* TEXT

`\underparent {...}`

\* TEXT

`\underparenttext {..1..} {..2..}`

1 TEXT

2 TEXT

`\underrandom {.*}`

\* CONTENT

`\underrandoms {...}`

\* CONTENT

$\rightarrow$ <code>\underrightarrow {...}</code> * TEXT
$\downarrow$ <code>\underrightharpoondown {...}</code> * TEXT
$\uparrow$ <code>\underrightharpoonup {...}</code> * TEXT
$\underset{\text{TEXT}}{\text{TEXT}}$ <code>\underset {...} {...}</code> 1 TEXT 2 TEXT
<del>CONTENT</del> <code>\understrike {...}</code> * CONTENT
<del>CONTENT</del> <code>\understrikes {...}</code> * CONTENT
$\leftarrow$ <code>\undertwoheadleftarrow {...}</code> * TEXT
$\rightarrow$ <code>\undertwoheadrightarrow {...}</code> * TEXT
$\text{KEY} = \text{VALUE}$ <code>\undoassign [...] [...=...]</code> 1 TEXT 2 KEY = VALUE
$\text{CONTENT}$ <code>\unframed [...,\overset{1}{...},...] {...}</code> 1 inherits: \setupframed 2 CONTENT
$\text{CSNAME NUMBER}$ <code>\unhhbox ... \with {...}</code> 1 CSNAME NUMBER 2 COMMAND
$\text{NUMBER}$ <code>\unihex {...}</code> * NUMBER
$\text{KEY} = \text{VALUE}$ <code>\uniqueMPgraphic {...} {...,\overset{2}{...},...}</code> 1 NAME 2 KEY = VALUE
$\text{KEY} = \text{VALUE}$ <code>\uniqueMPpagegraphic {...} {...,\overset{2}{...},...}</code> 1 NAME 2 KEY = VALUE

<code>\unit {...}</code> *    CONTENT
<code>\unitlanguage</code>
<code>\unittext {...}</code> *    KEY
<code>\unit {...}</code> *    CONTENT
<code>\unknown</code>
<code>\unprotect ... \protect</code>
<code>\unprotected ... \par</code> *    CONTENT
<code>\unregisterhyphenationpattern [...] [...]</code> 1    LANGUAGE 2    TEXT
<code>\unspaceafter ... {...}</code> 1    CSNAME 2    TEXT
<code>\unspaceargument ... \to ...</code> 1    TEXT 2    CSNAME
<code>\unspaced {...}</code> *    TEXT
<code>\unspacestring ... \to ...</code> 1    TEXT 2    CSNAME
<code>\untexargument {...} \to ...</code> 1    TEXT 2    CSNAME
<code>\untexcommand {...} \to ...</code> 1    CSNAME 2    CSNAME
<code>\uppercased {...}</code> *    TEXT



<code>\uppercasestring <sup>1</sup>... \to <sup>2</sup>...</code> 1 TEXT 2 CSNAME
<code>\upperlefthdoubleninequote</code>
<code>\upperlefthdoublesixquote</code>
<code>\upperleftsingleninequote</code>
<code>\upperleftsinglesixquote</code>
<code>\upperrighthdoubleninequote</code>
<code>\upperrighthdoublesixquote</code>
<code>\upperrightsingleninequote</code>
<code>\upperrightsinglesixquote</code>
<code>\url [...]</code> * NAME
<code>\usealignparameter \*</code> * CSNAME
<code>\useblankparameter \*</code> * CSNAME
<code>\useblocks [...<sup>1</sup>,...] [...<sup>2</sup>,...] [...<sup>3</sup>,...,...]</code> 1 NAME 2 + - 3 criterium = <u>text</u> SECTION
<code>\usebodyfont [...*,...]</code> * inherits: \setupbodyfont
<code>\usebodyfontparameter \*</code> * CSNAME
<code>\usebtxdataset [...<sup>1</sup>] [...<sup>2</sup>] [...<sup>3</sup>,...,...]</code> 1 NAME 2 FILE 3 specification = NAME
<code>\usebtdefinitions [...*]</code> * FILE

<pre>\usecolors [...]</pre> <p>* FILE</p>
<pre>\usecomponent [...]</pre> <p>* FILE</p>
<pre>\usedummycolorparameter {...}</pre> <p>* KEY</p>
<pre>\usedummystyleandcolor {...} {...}</pre> <p>1 KEY</p> <p>2 KEY</p>
<pre>\usedummystyleparameter {...}</pre> <p>* KEY</p>
<pre>\useenvironment [...]</pre> <p>* FILE</p>
<pre>\useexternaldocument [...<sup>1</sup>] [...<sup>2</sup>] [...<sup>3</sup>]</pre> <p>1 NAME</p> <p>2 FILE</p> <p>3 TEXT</p>
<pre>\useexternalfigure [...<sup>1</sup>] [...<sup>2</sup>] [...<sup>3</sup>] [...,<sup>4</sup>...,...]</pre> <p>1 NAME</p> <p>2 FILE</p> <p>3 NAME</p> <p>4 inherits: \setupexternalfigure</p>
<pre>\useexternalrendering [...<sup>1</sup>] [...<sup>2</sup>] [...<sup>3</sup>] [...<sup>4</sup>]</pre> <p>1 NAME</p> <p>2 NAME</p> <p>3 FILE</p> <p>4 auto embed</p>
<pre>\useexternalsoundtrack [...<sup>1</sup>] [...<sup>2</sup>]</pre> <p>1 NAME</p> <p>2 FILE</p>
<pre>\usefigurebase [...]</pre> <p>* reset FILE</p>
<pre>\usefile [...<sup>1</sup>] [...<sup>2</sup>] [...<sup>3</sup>]</pre> <p>1 NAME</p> <p>2 FILE</p> <p>3 TEXT</p>

<pre>\usegridparameter \*..</pre> <pre>* CSNAME</pre>
<pre>\useindentingparameter \*..</pre> <pre>* CSNAME</pre>
<pre>\useindentnextparameter \*..</pre> <pre>* CSNAME</pre>
<pre>\useinterlinespaceparameter \*..</pre> <pre>* CSNAME</pre>
<pre>\useJSscripts [...]<sup>1</sup> [...,<sup>2</sup>...]</pre> <pre>1 FILE</pre> <pre>2 NAME</pre>
<pre>\uselanguageparameter \*..</pre> <pre>* CSNAME</pre>
<pre>\uselua module [...]</pre> <pre>* FILE</pre>
<pre>\useMPenvironmentbuffer [...]</pre> <pre>* NAME</pre>
<pre>\useMPgraphic {...}<sup>1</sup> {...,<sup>2</sup>...}</pre> <pre>1 NAME</pre> <pre>2 KEY = VALUE</pre>
<pre>\useMPlibrary [...]</pre> <pre>* FILE</pre>
<pre>\useMPrun {...}<sup>1</sup> {...}<sup>2</sup></pre> <pre>1 NAME</pre> <pre>2 NUMBER</pre>
<pre>\useMPvariables [...]<sup>1</sup> [...,<sup>2</sup>...]</pre> <pre>1 NAME</pre> <pre>2 KEY</pre>
<pre>\usemathstyleparameter \*..</pre> <pre>* CSNAME</pre>
<pre>\usemodule [...]<sup>1</sup> [...,<sup>2</sup>...]<sup>3</sup> [...,<sup>3</sup>...]</pre> <pre>1 m p s x t</pre> <pre>2 FILE</pre> <pre>3 KEY = VALUE</pre>

<pre>\usepath [...,*,...]</pre> <pre>* FILE</pre>
<pre>\useproduct [...]</pre> <pre>* FILE</pre>
<pre>\useprofileparameter \...</pre> <pre>* CSNAME</pre>
<pre>\useproject [...]</pre> <pre>* FILE</pre>
<pre>\userreferenceparameter \...</pre> <pre>* CSNAME</pre>
<pre>\userpagenumber</pre>
<pre>\usesetupsp parameter \...</pre> <pre>* CSNAME</pre>
<pre>\usestaticMPfigure [...,\<sup>1</sup>...,...] [\<sup>2</sup>...]</pre> <pre>1 inherits: \setupscale</pre> <pre>2 NAME</pre>
<pre>\usesubpath [...,*,...]</pre> <pre>* FILE</pre>
<pre>\usesymbols [...]</pre> <pre>* FILE</pre>
<pre>\usetexmodule [\<sup>1</sup>...] [\<sup>2</sup>...,...] [\<sup>3</sup>...,...]</pre> <pre>1 m p s x t</pre> <pre>2 FILE</pre> <pre>3 KEY = VALUE</pre>
<pre>\usetypescript [\<sup>1</sup>...] [\<sup>2</sup>...] [\<sup>3</sup>...]</pre> <pre>1 serif sans mono math handwriting calligraphy casual all</pre> <pre>2 NAME fallback default dtp simple</pre> <pre>3 size name</pre>
<pre>\usetypescriptfile [\<sup>*</sup>...]</pre> <pre>* reset FILE</pre>
<pre>\useURL [\<sup>1</sup>...] [\<sup>2</sup>...] [\<sup>3</sup>...] [\<sup>4</sup>...]</pre> <pre>1 NAME</pre> <pre>2 URL</pre> <pre>3 FILE</pre> <pre>4 TEXT</pre>

\useurl [...] <sup>1</sup> [...] <sup>2</sup> [...] <sup>3</sup> [...] <sup>4</sup>  1 NAME 2 URL 3 FILE 4 TEXT
\usezipfile [...] <sup>1</sup> [...] <sup>2</sup>  1 FILE 2 FILE
\utfchar {...}  * NUMBER
\utflower {...}  * TEXT
\utfupper {...}  * TEXT
\utilityregisterlength
\VerboseNumber {...}  * NUMBER
\ vboxreference [...] <sup>1</sup> , [...] <sup>2</sup> {...}  1 REFERENCE 2 CONTENT
\vec {...}  * CHARACTER
\verbatim {...}  * CONTENT
\verbatimstring {...}  * CONTENT
\verbozenumber {...}  * NUMBER
\version [...]  * concept file temporary final NAME
\verticalgrowingbar [...] <sup>*</sup> [...]  * inherits: \setuppositionbar
\verticalpositionbar [...] <sup>*</sup> [...]  * inherits: \setuppositionbar

<code>\veryraggedcenter</code>
<code>\veryraggedleft</code>
<code>\veryraggedright</code>
<code>\vglue ...</code> * DIMENSION
<code>\viewerlayer [...]{...}</code> 1 NAME 2 CONTENT
<code>\vl [...]</code> * NUMBER
<code>\vphantom {...}</code> * CONTENT
<code>\vpos {...}{...}</code> 1 NAME 2 CONTENT
<code>\vsmash {...}</code> * CONTENT
<code>\vsmashbox ...</code> * CSNAME NUMBER
<code>\vsmashed {...}</code> * CONTENT
<code>\vspace [...]{...}</code> 1 NAME 2 NAME
<code>\vspacing [...]{...}</code> * preference samepage max force enable disable nowhite back overlay always weak strong default before inbetween after fixed flexible none small medium big line halfline quarterline formula white height depth standard NUMBER*small NUMBER*medium NUMBER*big NUMBER*line NUMBER*halfline NUMBER*quarterline NUMBER*formula NUMBER*white NUMBER*height NUMBER*depth category:NUMBER order:NUMBER penalty:NUMBER DIMENSION NAME
<code>\WEEKDAY {...}</code> * NUMBER
<code>\WidthSpanningText {...}{...}{...}</code> 1 TEXT 2 DIMENSION 3 FONT

<p><code>\WORD {...}</code></p> <p>* TEXT</p>
<p><code>\WORDS {...}</code></p> <p>* TEXT</p>
<p><code>\Word {...}</code></p> <p>* TEXT</p>
<p><code>\Words {...}</code></p> <p>* TEXT</p>
<p><code>\wdofstring {...}</code></p> <p>* TEXT</p>
<p><code>\weekday {...}</code></p> <p>* NUMBER</p>
<p><code>\widthofstring {...}</code></p> <p>* TEXT</p>
<p><code>\widthspanningtext {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}</code></p> <p>1 TEXT</p> <p>2 DIMENSION</p> <p>3 FONT</p>
<p><code>\withoutpt {...}</code></p> <p>* DIMENSION</p>
<p><code>\word {...}</code></p> <p>* TEXT</p>
<p><code>\wordright [...<sup>1</sup>] {...<sup>2</sup>}</code></p> <p>1 right DIMENSION</p> <p>2 CONTENT</p>
<p><code>\words {...}</code></p> <p>* TEXT</p>
<p><code>\wordtonumber {...<sup>1</sup>} {...<sup>2</sup>}</code></p> <p>1 one two three four five</p> <p>2 TEXT</p>
<p><code>\writebetweenlist [...<sup>1</sup>] [...,<sup>2</sup>...,...] {...<sup>3</sup>}</code></p> <p>1 LIST</p> <p>2 inherits: \setuplist</p> <p>3 COMMAND</p>

`\writedatatolist [...]1 [...,...2...,...]2 [...,...3...,...]3`

1 LIST  
2 inherits: \setuplist  
3 KEY = VALUE

`\writestatus {...}1 {...}2`

1 TEXT  
2 TEXT

`\writetolist [...]1 [...,...2...,...]2 {...}3 {...}4`

1 LIST  
2 inherits: \setuplist  
3 NUMBER  
4 TEXT

`\XETEX`

`\XeTeX`

`\xdefconvertedargument \...1 {...}2`

1 CSNAME  
2 TEXT

`\xequal {...}1 {...}2`

1 TEXT  
2 TEXT

`\xfrac {...}1 {...}2`

1 CONTENT  
2 CONTENT

`\xhookleftarrow {...}1 {...}2`

1 TEXT  
2 TEXT

`\xhookrightarrow {...}1 {...}2`

1 TEXT  
2 TEXT

`\xLeftarrow {...}1 {...}2`

1 TEXT  
2 TEXT

`\xLeftrightarrow {...}1 {...}2`

1 TEXT  
2 TEXT



`\xleftarrow {...} {...}`

1 TEXT

2 TEXT

`\xleftharpoondown {...} {...}`

1 TEXT

2 TEXT

`\xleftharpoonup {...} {...}`

1 TEXT

2 TEXT

`\xleftrightharrow {...} {...}`

1 TEXT

2 TEXT

`\xleftrightharpoons {...} {...}`

1 TEXT

2 TEXT

`\xmapsto {...} {...}`

1 TEXT

2 TEXT

`\xmladdindex {...}`

\* NODE

`\xmllafterdocumentsetup {...} {...} {...}`

1 NAME

2 SETUP

3 SETUP

`\xmllaftersetup {...} {...}`

1 SETUP

2 SETUP

`\xmlall {...} {...}`

1 NODE

2 LPATH

`\xmlappenddocumentsetup {...} {...}`

1 NAME

2 SETUP

`\xmlappendsetup {...}`

\* SETUP

\xmlapplyselectors {...}

\* NODE

\xmlatt {...} {...}

1 NODE

2 NAME

\xmlattdef {...} {...} {...}

1 NODE

2 NAME

3 TEXT

\xmlattribute {...} {...} {...}

1 NODE

2 LPATH

3 NAME

\xmlattributedef {...} {...} {...} {...}

1 NODE

2 LPATH

3 NAME

4 TEXT

\xmlbadinclusions {...}

\* NODE

\xmlbeforedocumentsetup {...} {...} {...}

1 NAME

2 SETUP

3 SETUP

\xmlbeforesetup {...} {...}

1 SETUP

2 SETUP

\xmlchainatt {...} {...}

1 NODE

2 NAME

\xmlchainattdef {...} {...} {...}

1 NODE

2 NAME

3 TEXT

\xmlchecknamespace {...} {...}

1 NODE

2 NAME

`\xmlcommand {...} {...} {...}`

- 1    NODE
- 2    LPATH
- 3    XMLSETUP

`\xmlconcat {...} {...} {...}`

- 1    NODE
- 2    LPATH
- 3    TEXT

`\xmlconcatrange {...} {...} {...} {...} {...}`

- 1    NODE
- 2    LPATH
- 3    TEXT
- 4    FIRST
- 5    LAST

`\xmlcontext {...} {...}`

- 1    NODE
- 2    LPATH

`\xmlcount {...}`

- \*    NODE

`\xmldefaulttotext {...}`

- \*    NODE

`\xmldirectives {...}`

- \*    NODE

`\xmldirectivesafter {...}`

- \*    NODE

`\xmldirectivesbefore {...}`

- \*    NODE

`\xmldisplayverbatim {...}`

- \*    NODE

`\xmldoif {...} {...} {...}`

- 1    NODE
- 2    LPATH
- 3    TRUE

`\xmldoifelse {...} {...} {...} {...}`

- 1    NODE
- 2    LPATH
- 3    TRUE
- 4    FALSE

`\xmldoifelseempty {...} {...} {...} {...}`

- 1    NODE
- 2    LPATH
- 3    TRUE
- 4    FALSE

`\xmldoifelseselfempty {...} {...} {...}`

- 1    NODE
- 2    TRUE
- 3    FALSE

`\xmldoifelsetext {...} {...} {...} {...}`

- 1    NODE
- 2    LPATH
- 3    TRUE
- 4    FALSE

`\xmldoifelsevalue {...} {...} {...} {...}`

- 1    CATEGORY
- 2    NAME
- 3    TRUE
- 4    FALSE

`\xmldoifnot {...} {...} {...}`

- 1    NODE
- 2    LPATH
- 3    TRUE

`\xmldoifnotselfempty {...} {...}`

- 1    NODE
- 2    TRUE

`\xmldoifnottext {...} {...} {...}`

- 1    NODE
- 2    LPATH
- 3    TRUE

`\xmldoifselfempty {...} {...}`

- 1    NODE
- 2    TRUE

`\xmldoiftext {...} {...} {...}`

- 1    NODE
- 2    LPATH
- 3    TRUE

`\xmlelement {...} {...}`

- 1    NODE
- 2    NUMBER

`\xmlfilter {...} {...}`

- 1    NODE
- 2    LPATH

`\xmlfirst {...} {...}`

- 1    NODE
- 2    LPATH

`\xmlflush {...}`

- \*    NODE

`\xmlflushcontext {...}`

- \*    NODE

`\xmlflushdocumentsetups {...} {...}`

- 1    NAME
- 2    SETUP

`\xmlflushlinewise {...}`

- \*    NODE

`\xmlflushpure {...}`

- \*    NODE

`\xmlflushspacewise {...}`

- \*    NODE

`\xmlflushtext {...}`

- \*    NODE

`\xmlinclude {...} {...} {...}`

- 1    NODE
- 2    LPATH
- 3    NAME

`\xmlinclusion {...}`

- \*    NODE

\xmlinclusions {...}  *    NODE
\xmlinfo {...}  *    NODE
\xmlinjector {...}  *    NAME
\xmlinlineverbatim {...}  *    NODE
\xmlinstalldirective {...} {...}  1    NAME 2    CSNAME
\xmllast {...} {...}  1    NODE 2    LPATH
\xmllastatt
\xmllastmatch
\xmlloadbuffer {...} {...} {...}  1    BUFFER 2    NAME 3    XMLSETUP
\xmlloaddata {...} {...} {...}  1    NAME 2    TEXT 3    XMLSETUP
\xmlloaddirectives {...}  *    FILE
\xmlloadfile {...} {...} {...}  1    NAME 2    FILE 3    XMLSETUP
\xmlloadonly {...} {...} {...}  1    NAME 2    FILE 3    XMLSETUP

\xmlmain {...}  *    NAME
\xmlmapvalue {...} {...} {...}  1    CATEGORY 2    NAME 3    TEXT
\xmlname {...}  *    NODE
\xmlnamespace {...}  *    NODE
\xmlnonspace {...} {...}  1    NODE 2    LPATH
\xmlpath {...}  *    NODE
\xmlpos {...}  *    NODE
\xmlposition {...} {...} {...}  1    NODE 2    LPATH 3    NUMBER
\xmlprependdocumentsetup {...} {...}  1    NAME 2    SETUP
\xmlprependsetup {...}  *    SETUP
\xmlprettyprint {...} {...}  1    NODE 2    NAME
\xmlprocessbuffer {...} {...} {...}  1    BUFFER 2    NAME 3    XMLSETUP

\xmlprocessdata {...} {...} {...}

- 1 NAME
- 2 TEXT
- 3 XMLSETUP

\xmlprocessfile {...} {...} {...}

- 1 NAME
- 2 FILE
- 3 XMLSETUP

\xmlpure {...} {...}

- 1 NODE
- 2 LPATH

\xmlraw {...}

- \* NODE

\xmlrefatt {...} {...}

- 1 NODE
- 2 NAME

\xmlregistereddokumentsetups {...} {...}

- 1 NAME
- 2 SETUP

\xmlregisteredsetups

\xmlregisterns {...} {...}

- 1 NAME
- 2 URL

\xmlremapname {...} {...} {...} {...}

- 1 NODE
- 2 LPATH
- 3 NAME
- 4 NAME

\xmlremapnamespace {...} {...} {...}

- 1 NODE
- 2 NAME
- 3 NAME

\xmlremovedokumentsetup {...} {...}

- 1 NAME
- 2 SETUP



\xmlremovesetup {...}

\* SETUP

\xmlresetdocumentsetups {...}

\* NAME

\xmlresetinjectors

\xmlresetsetups {...}

\* NAME

\xmlsave {...} {...}

1 NODE

2 FILE

\xmlsetentity {...} {...}

1 NAME

2 TEXT

\xmlsetfunction {...} {...} {...}

1 NODE

2 LPATH

3 LUAFUNCTION

\xmlsetinjectors [...,\*,...]

\* NAME

\xmlsetsetup {...} {...} {...}

1 NAME

2 LPATH

3 SETUP

\xmlsetup {...} {...}

1 NODE

2 SETUP

\xmlshow {...}

\* NODE

\xmlsnippet {...} {...}

1 NODE

2 NUMBER

\xmlstrip {...} {...}

1 NODE

2 LPATH

`\xmlstripnolines {...} {...}`

- 1 NODE
- 2 LPATH

`\xmlstripped {...} {...}`

- 1 NODE
- 2 LPATH

`\xmlstrippednolines {...} {...}`

- 1 NODE
- 2 LPATH

`\xmltag {...}`

- \* NODE

`\xmltexentity {...} {...}`

- 1 NAME
- 2 TEXT

`\xmltext {...} {...}`

- 1 NODE
- 2 LPATH

`\xmltobuffer {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 BUFFER

`\xmltobufferverbose {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 BUFFER

`\xmltofile {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 FILE

`\xmlvalue {...} {...} {...}`

- 1 CATEGORY
- 2 NAME
- 3 TEXT

`\xmlverbatim {...}`

- \* NODE

`\xrightarrow {...} {...}`

1 TEXT

2 TEXT

`\xrel {...} {...}`

1 TEXT

2 TEXT

`\xrightarrow {...} {...}`

1 TEXT

2 TEXT

`\xrightarrow[...]{...}`

1 TEXT

2 TEXT

`\xrightarrowup {...} {...}`

1 TEXT

2 TEXT

`\xleftrightarrow {...} {...}`

1 TEXT

2 TEXT

`\xrightarrowleftarrow {...} {...}`

1 TEXT

2 TEXT

`\xsplitstring \^... {...}`

1 CSNAME

2 TEXT

`\xtriplerel {...} {...}`

1 TEXT

2 TEXT

`\xtwoheadleftarrow {...} {...}`

1 TEXT

2 TEXT

`\xtwoheadrightarrow {...} {...}`

1 TEXT

2 TEXT

`\xxfrac {...} {...}`

1 CONTENT

2 CONTENT

`\xypos {...}`

\* NAME



The background is an abstract composition of various geometric shapes, primarily rectangles and squares, in shades of green and grey. The shapes are layered and overlap, creating a sense of depth and movement. The colors are muted, with a palette of light green, dark green, and grey. The overall effect is a modern, minimalist design.

**PRAGMA ADE**  
**Ridderstraat 27**  
**8061GH Hasselt NL**  
**[www.pragma-ade.com](http://www.pragma-ade.com)**