

new minivas

in luametateX

Introduction

Here I will discuss some of the new primitives in Lua_T_EX and LuaMeta_T_EX, the later being a successor that permits the Con_T_EXt folks to experiment with new features. The order is arbitrary. When you compare Lua_T_EX with pdf_T_EX, there are actually quite some differences. Some primitives that pdf_T_EX introduced have been dropped in Lua_T_EX because they can be done better in Lua. Others have been promoted to core primitives that no longer have a pdf prefix. Then there are lots of new primitives, some introduce new concepts, some are a side effect of for instance new math font technologies, and then there are those that are handy extensions to the macro language. The LuaMeta_T_EX engine drops quite some primitives, like those related to pdf_T_EX specific f(r)ont or backend features. It also adds some new primitives, mostly concerning the macro language.

We also discuss the primitives that fit into the macro programming scope that are present in traditional _T_EX and ε -_T_EX but there are for sure better of explanations out there already. Primitives that relate to typesetting, like those controlling math, fonts, boxes, attributes, directions, catcodes, Lua (functions) etc are not discussed or discussed in less detail here.

There are for instance primitives to create aliases to low level registers like counters and dimensions, as well as other (semi-numeric) quantities like characters, but normally these are wrapped into high level macros so that definitions can't clash too much. Numbers, dimensions etc can be advanced, multiplied and divided and there is a simple expression mechanism to deal with them. We don't go into these details here: it's mostly an overview of what the engine provides. If you are new to _T_EX, you need to play a while with its mixed bag of typesetting and programming features in order to understand the difference between this macro language and other languages you might be familiar with.

1	\	4	26	\catcode	11
2	\-	4	27	\catcodetable	11
3	\/	4	28	\cdef	11
4	\advance	5	29	\cdefcsname	12
5	\advanceby	5	30	\chardef	12
6	\afterassigned	5	31	\constant	12
7	\afterassignment	5	32	\constrained	12
8	\aftergroup	5	33	\count	12
9	\aftergrouped	6	34	\countdef	12
10	\aliased	6	35	\csactive	13
11	\alignmark	7	36	\csname	13
12	\aligntab	7	37	\csstring	13
13	\associateunit	7	38	\currentgrouplevel	13
14	\atendoffile	8	39	\currentgrouptype	14
15	\atendoffiled	8	40	\currentifbranch	14
16	\atendofgroup	8	41	\currentiflevel	14
17	\atendofgrouped	8	42	\currentiftype	15
18	\attribute	9	43	\currentloopiterator	15
19	\attributedef	9	44	\currentloopnesting	16
20	\batchmode	9	45	\currentstacksize	16
21	\begincsname	9	46	\def	16
22	\begingroup	9	47	\defcsname	17
23	\beginlocalcontrol	9	48	\deferred	17
24	\beginmathgroup	10	49	\detokened	17
25	\beginsimplegroup	10	50	\detokenize	18

51	<code>\detokenized</code>	18	100	<code>\explicititaliccorrection</code>	29
52	<code>\dimen</code>	18	101	<code>\explicitspace</code>	29
53	<code>\dimendef</code>	18	102	<code>\fi</code>	30
54	<code>\dimensiondef</code>	19	103	<code>\float</code>	30
55	<code>\dimexpr</code>	19	104	<code>\floatdef</code>	31
56	<code>\dimexpression</code>	19	105	<code>\floatexpr</code>	31
57	<code>\directlua</code>	19	106	<code>\font</code>	31
58	<code>\divide</code>	19	107	<code>\formatname</code>	31
59	<code>\divideby</code>	19	108	<code>\frozen</code>	31
60	<code>\edef</code>	20	109	<code>\futurecsname</code>	32
61	<code>\edefcsname</code>	20	110	<code>\futuredef</code>	32
62	<code>\edivide</code>	20	111	<code>\futureexpand</code>	32
63	<code>\edivideby</code>	21	112	<code>\futureexpandis</code>	33
64	<code>\else</code>	21	113	<code>\futureexpandisap</code>	33
65	<code>\end</code>	21	114	<code>\futurelet</code>	33
66	<code>\endcsname</code>	21	115	<code>\gdef</code>	34
67	<code>\endgroup</code>	21	116	<code>\gdefcsname</code>	34
68	<code>\endinput</code>	21	117	<code>\glet</code>	34
69	<code>\endlinechar</code>	22	118	<code>\gletcsname</code>	34
70	<code>\endlocalcontrol</code>	22	119	<code>\glettonothing</code>	34
71	<code>\endmathgroup</code>	22	120	<code>\global</code>	34
72	<code>\endsimplegroup</code>	22	121	<code>\globaldefs</code>	35
73	<code>\enforced</code>	22	122	<code>\glueexpr</code>	35
74	<code>\eofinput</code>	23	123	<code>\glueshrink</code>	35
75	<code>\errmessage</code>	23	124	<code>\glueshrinkorder</code>	35
76	<code>\errorstopmode</code>	23	125	<code>\gluespecdef</code>	35
77	<code>\escapechar</code>	23	126	<code>\gluestretch</code>	35
78	<code>\etoks</code>	23	127	<code>\gluestretchorder</code>	35
79	<code>\etoksapp</code>	23	128	<code>\glyph</code>	35
80	<code>\etokspre</code>	23	129	<code>\gtoksapp</code>	36
81	<code>\eufactor</code>	23	130	<code>\gtokspre</code>	36
82	<code>\everyeof</code>	24	131	<code>\if</code>	36
83	<code>\everyjob</code>	24	132	<code>\ifabsdim</code>	36
84	<code>\expand</code>	24	133	<code>\ifabsfloat</code>	37
85	<code>\expandactive</code>	24	134	<code>\ifabsnum</code>	37
86	<code>\expandafter</code>	24	135	<code>\ifarguments</code>	37
87	<code>\expandafterpars</code>	25	136	<code>\ifboolean</code>	38
88	<code>\expandafterspaces</code>	25	137	<code>\ifcase</code>	38
89	<code>\expandcstoken</code>	25	138	<code>\ifcat</code>	38
90	<code>\expanded</code>	26	139	<code>\ifchkdim</code>	38
91	<code>\expandedafter</code>	26	140	<code>\ifchkdimension</code>	38
92	<code>\expandeddetokenize</code>	27	141	<code>\ifchknum</code>	39
93	<code>\expandedendless</code>	27	142	<code>\ifchknumber</code>	39
94	<code>\expandedloop</code>	27	143	<code>\ifcmpdim</code>	39
95	<code>\expandedrepeat</code>	28	144	<code>\ifcmpnum</code>	39
96	<code>\expandparameter</code>	28	145	<code>\ifcondition</code>	40
97	<code>\expandtoken</code>	28	146	<code>\ifcsname</code>	41
98	<code>\expandtoks</code>	29	147	<code>\ifcstok</code>	41
99	<code>\explicitdiscretionary</code>	29	148	<code>\ifdefined</code>	41

149	<code>\ifdim</code>	42	198	<code>\inputlineno</code>	53
150	<code>\ifdimexpression</code>	42	199	<code>\instance</code>	53
151	<code>\ifdimval</code>	42	200	<code>\integerdef</code>	53
152	<code>\ifempty</code>	42	201	<code>\interactionmode</code>	53
153	<code>\iffalse</code>	43	202	<code>\jobname</code>	53
154	<code>\ifflags</code>	43	203	<code>\lastarguments</code>	54
155	<code>\iffloat</code>	43	204	<code>\lastloopiterator</code>	54
156	<code>\iffontchar</code>	43	205	<code>\lastnamedcs</code>	54
157	<code>\ifhaschar</code>	43	206	<code>\letcharcode</code>	55
158	<code>\ifhastok</code>	44	207	<code>\letcsname</code>	55
159	<code>\ifhastoks</code>	44	208	<code>\letfrozen</code>	55
160	<code>\ifhasxtoks</code>	44	209	<code>\letprotected</code>	55
161	<code>\ifhbox</code>	45	210	<code>\lettolastnamedcs</code>	56
162	<code>\ifhmode</code>	45	211	<code>\lettonothing</code>	56
163	<code>\iffinalignment</code>	45	212	<code>\localcontrol</code>	56
164	<code>\ifincsname</code>	45	213	<code>\localcontrolled</code>	57
165	<code>\ifinner</code>	45	214	<code>\localcontrolledendless</code>	57
166	<code>\ifintervaldim</code>	46	215	<code>\localcontrolledloop</code>	57
167	<code>\ifintervalfloat</code>	46	216	<code>\localcontrolledrepeat</code>	58
168	<code>\ifintervalnum</code>	46	217	<code>\long</code>	58
169	<code>\iflastnamedcs</code>	46	218	<code>\lowercase</code>	58
170	<code>\ifmathparameter</code>	46	219	<code>\luaescapestring</code>	58
171	<code>\ifmathstyle</code>	46	220	<code>\luatexbanner</code>	58
172	<code>\ifmmode</code>	47	221	<code>\luatexrevision</code>	59
173	<code>\ifnum</code>	47	222	<code>\luatexversion</code>	59
174	<code>\ifnumexpression</code>	47	223	<code>\mathgroupingmode</code>	59
175	<code>\ifnumval</code>	48	224	<code>\meaning</code>	59
176	<code>\ifodd</code>	48	225	<code>\meaningasis</code>	59
177	<code>\ifparameter</code>	48	226	<code>\meaningful</code>	59
178	<code>\ifrelax</code>	48	227	<code>\meaningfull</code>	59
179	<code>\iftok</code>	48	228	<code>\meaningless</code>	60
180	<code>\iftrue</code>	49	229	<code>\meaningless</code>	60
181	<code>\ifvbox</code>	49	230	<code>\mugluespecdef</code>	60
182	<code>\ifvmode</code>	49	231	<code>\multiply</code>	60
183	<code>\ifvoid</code>	49	232	<code>\multiplyby</code>	60
184	<code>\ifx</code>	49	233	<code>\nonstopmode</code>	60
185	<code>\ifzerodim</code>	50	234	<code>\norelax</code>	60
186	<code>\ifzerofloat</code>	50	235	<code>\nospaces</code>	61
187	<code>\ifzeronum</code>	50	236	<code>\number</code>	61
188	<code>\ignorearguments</code>	50	237	<code>\numericsscale</code>	61
189	<code>\ignorenestedupto</code>	51	238	<code>\numericsscaled</code>	61
190	<code>\ignorepars</code>	51	239	<code>\numexpr</code>	62
191	<code>\ignorereset</code>	51	240	<code>\numexpression</code>	62
192	<code>\ignorespaces</code>	52	241	<code>\or</code>	63
193	<code>\ignoreupto</code>	52	242	<code>\orelse</code>	63
194	<code>\immediate</code>	52	243	<code>\orunless</code>	64
195	<code>\immutable</code>	52	244	<code>\outer</code>	64
196	<code>\initcatcodetable</code>	52	245	<code>\parameterdef</code>	64
197	<code>\input</code>	52	246	<code>\parameterindex</code>	65

247	<code>\parametermark</code>	65	273	<code>\the</code>	71
248	<code>\parametermode</code>	65	274	<code>\thewithoutunit</code>	71
249	<code>\positdef</code>	65	275	<code>\todimension</code>	72
250	<code>\previousloopiterator</code>	66	276	<code>\tohexadecimal</code>	72
251	<code>\protected</code>	66	277	<code>\tointeger</code>	72
252	<code>\protecteddetokenize</code>	66	278	<code>\tokenized</code>	72
253	<code>\protectedexpandeddetokenize</code>	66	279	<code>\toksapp</code>	72
254	<code>\pxdimen</code>	66	280	<code>\tokspre</code>	73
255	<code>\quitloop</code>	67	281	<code>\tolerant</code>	73
256	<code>\quitloopnow</code>	67	282	<code>\toscaled</code>	74
257	<code>\rdivide</code>	67	283	<code>\tosparsedimension</code>	74
258	<code>\rdivideby</code>	67	284	<code>\tosparsescaled</code>	74
259	<code>\relax</code>	67	285	<code>\unexpanded</code>	74
260	<code>\retained</code>	68	286	<code>\unexpandedendless</code>	74
261	<code>\retokenized</code>	69	287	<code>\unexpandedloop</code>	74
262	<code>\romannumeral</code>	69	288	<code>\unexpandedrepeat</code>	75
263	<code>\savecatcodetable</code>	70	289	<code>\unless</code>	75
264	<code>\scantextokens</code>	70	290	<code>\unletfrozen</code>	76
265	<code>\scantokens</code>	70	291	<code>\unletprotected</code>	76
266	<code>\scrollmode</code>	70	292	<code>\untraced</code>	76
267	<code>\semiexpand</code>	70	293	<code>\uppercase</code>	77
268	<code>\semiexpanded</code>	70	294	<code>\xdef</code>	77
269	<code>\semiprotected</code>	70	295	<code>\xdefcsname</code>	77
270	<code>\skip</code>	71	296	<code>\xtoks</code>	77
271	<code>\string</code>	71	297	<code>\xtoksapp</code>	77
272	<code>\swapcsvalues</code>	71	298	<code>\xtokspre</code>	77

In this document the section titles that discuss the original \TeX and $\varepsilon\text{\TeX}$ primitives have a different color those explaining the \LuaTeX and \LuaMetaTeX primitives.

Primitives that extend typesetting related functionality, provide control over subsystems (like math), allocate additional data types and resources, deal with fonts and languages, manipulate boxes and glyphs, etc. are hardly discussed here. Math for instance is a topic of its own. In this document we concentrate on the programming aspects.

Primitives

1 `\`

This original \TeX primitive is equivalent to the more verbose `\explicit space`.

2 `\-`

This original \TeX primitive is equivalent to the more verbose `\explicit discretionary`.

3 `\/`

This original \TeX primitive is equivalent to the more verbose `\explicit italic correction`.

4 \advance

Advances the given register by an also given value:

```
\advance\scratchdimen      10pt
\advance\scratchdimen      by 3pt
\advance\scratchcounterone \zerocount
\advance\scratchcounterone \scratchcountertwo
```

The by keyword is optional.

5 \advanceby

This is slightly more efficient variant of \advance that doesn't look for by and therefore, if one is missing, doesn't need to push back the last seen token. Using \advance with by is nearly as efficient but takes more tokens.

6 \afterassigned

The \afterassignment primitive stores a token to be injected (and thereby expanded) after an assignment has happened. Unlike \aftergroup, multiple calls are not accumulated, and changing that would be too incompatible. This is why we have \afterassigned, which can be used to inject a bunch of tokens. But in order to be consistent this one is also not accumulative.

```
\afterassigned{done}%
\afterassigned{{\bf done}}%
\scratchcounter=123
```

results in: **done** being typeset.

7 \afterassignment

The token following \afterassignment, a traditional T_EX primitive, is saved and gets injected (and then expanded) after a following assignment took place.

```
\afterassignment !\def\MyMacro {} \quad
\afterassignment !\let\MyMacro ? \quad
\afterassignment !\scratchcounter 123 \quad
\afterassignment !%
\afterassignment ?\advance\scratchcounter by 1
```

The \afterassignments are not accumulated, the last one wins:

! ! ! ?

8 \aftergroup

The traditional T_EX \aftergroup primitive stores the next token and expands that after the group has been closed.

Multiple \aftergroups are combined:

```
before{ ! \aftergroup a\aftergroup f\aftergroup t\aftergroup e\aftergroup r}
```

before ! after

9 \aftergrouped

The in itself powerful \aftergroup primitives works quite well, even if you need to do more than one thing: you can either use it multiple times, or you can define a macro that does multiple things and apply that after the group. However, you can avoid that by using this primitive which takes a list of tokens.

```
regular
\bgrou
\aftergrouped{regular}%
\bf bold
\egrou
```

Because it happens after the group, we're no longer typesetting in bold.

regular **bold** regular

10 \aliased

This primitive is part of the overload protection subsystem where control sequences can be tagged.

```
\permanent\def\foo{F00}
      \let\of\foo
\aliased \let\oof\foo

\meaningasis\foo
\meaningasis\of
\meaningasis\oof
```

gives:

```
\permanent \def \foo {F00}
\def \of {F00}
\permanent \def \oof {F00}
```

When a something is \let the 'permanent', 'primitive' and 'immutable' flags are removed but the \aliased prefix retains them.

```
\let\relaxed\relax

\meaningasis\relax
\meaningasis\relaxed
```

So in this example the \relaxed alias is not flagged as primitive:

```
\primitive \relax
\relax
```

11 `\alignmark`

When you have the `#` not set up as macro parameter character `cq`. align mark, you can use this primitive instead. The same rules apply with respect to multiple such tokens in (nested) macros and alignments.

12 `\aligntab`

When you have the `&` not set up as align tab, you can use this primitive instead. The same rules apply with respect to multiple such tokens in (nested) macros and alignments.

13 `\associateunit`

The $\text{T}_{\text{E}}\text{X}$ engine comes with some build in units, like `pt` (fixed) and `em` (adaptive). On top of that a macro package can add additional units, which is what we do in $\text{ConT}_{\text{E}}\text{Xt}$. In figure 1 we show the current repertoire.




Figure 1 Available units

When this primitive is used in a context where a number is expected it returns the origin of the unit (in the color legend running from 1 upto 4). A new unit is defined as:

```
\newdimen\MyDimenZA \MyDimenZA=10pt
\protected\def\MyDimenAB{\dimexpr\hsize/2\relax}
\associateunit za \MyDimenZA
\associateunit zb \MyMacroZB
```

Possible associations are: macros that expand to a dimension, internal dimension registers, register dimensions (`\dimendef`, direct dimensions (`\dimensiondef`) and Lua functions that return a dimension.

One can run into scanning ahead issues where $\text{T}_{\text{E}}\text{X}$ expects a unit and a user unit gets expanded. This is why for instance in $\text{ConT}_{\text{E}}\text{Xt}$ we define the `ma` unit as:

```
\protected\def\mathaxisunit{\scaledmathaxis\mathstyle\norelax}
\associateunit ma \mathaxisunit % or \newuserunit \mathaxisunit ma
```


So that it can be used in rule specifications that themselves look ahead for keywords and therefore are normally terminated by a `\relax`. Adding the extra `\norelax` will make the scanner see one that doesn't get fed back into the input. Of course a macro package has to manage extra units in order to avoid conflicts.

14 `\atendoffile`

The `\everyeof` primitive is kind of useless because you don't know if a file (which can be a tokenlist processed as pseudo file) itself includes a file, which then results in nested application of this token register. One way around this is:

```
\atendoffile\SomeCommand
```

This acts on files the same way as `\atendofgroup` does. Multiple calls will be accumulated and are bound to the current file.

15 `\atendoffiled`

This is the multi token variant of `\atendoffile`. Multiple invocations are accumulated and by default prepended to the existing list. As with grouping this permits proper nesting. You can force an append by the optional keyword `reverse`.

16 `\atendofgroup`

The token provided will be injected just before the group ends. Because these tokens are collected, you need to be aware of possible interference between them. However, normally this is managed by the macro package.

```
\bgroup
\atendofgroup\unskip
\atendofgroup )%
( but it works okay
\egroup
```

Of course these effects can also be achieved by combining (extra) grouping with `\aftergroup` calls, so this is more a convenience primitives than a real necessity: (but it works okay), as proven here.

17 `\atendofgrouped`

This is the multi token variant of `\atendofgroup`. Of course the next example is somewhat naive when it comes to spacing and so, but it shows the purpose.

```
\bgroup
\atendofgrouped{\bf QED}%
\atendofgrouped{ (indeed) }%
This sometimes looks nicer.
\egroup
```

Multiple invocations are accumulated: This sometimes looks nicer. **QED (indeed)**.

18 `\attribute`

The following sets an `attribute(register)` value:

```
\attribute 999 = 123
```

An attribute is unset by assigning -2147483647 to it. A user needs to be aware of attributes being used now and in the future of a macro package and setting them this way is very likely going to interfere.

19 `\attributedef`

This primitive can be used to relate a control sequence to an attribute register and can be used to implement a mechanism for defining unique ones that won't interfere. As with other registers: leave management to the macro package in order to avoid unwanted side effects!

20 `\batchmode`

This command disables (error) messages which can save some runtime in situations where T_EX's character-by-character log output impacts runtime. It only makes sense in automated workflows where one doesn't look at the log anyway.

21 `\begincsname`

The next code creates a control sequence token from the given serialized tokens:

```
\csname mymacro\endcsname
```

When `\mymacro` is not defined a control sequence will be created with the meaning `\relax`. A side effect is that a test for its existence might fail because it now exists. The next sequence will *not* create an control sequence:

```
\begincsname mymacro\endcsname
```

This actually is kind of equivalent to:

```
\ifcsname mymacro\endcsname
  \csname mymacro\endcsname
\fi
```

22 `\begingroup`

This primitive starts a group and has to be ended with `\endgroup`. See `\beginsimplegroup` for more info.

23 `\beginlocalcontrol`

Once T_EX is initialized it will enter the main loop. In there certain commands trigger a function that itself can trigger further scanning and functions. In LuaMetaT_EX we can have local main loops and we can either enter it from the Lua end (which we don't discuss here) or at the T_EX end using this primitive.

```

\scratchcounter100

\edef\whatever{
  a
  \beginlocalcontrol
    \advance\scratchcounter 10
  b
  \endlocalcontrol
  \beginlocalcontrol
    c
  \endlocalcontrol
  d
  \advance\scratchcounter 10
}

\the\scratchcounter
\whatever
\the\scratchcounter

```

A bit of close reading probably gives an impression of what happens here:

```

b c

110 a d 120

```

The local loop can actually result in material being injected in the current node list. However, where normally assignments are not taking place in an `\edef`, here they are applied just fine. Basically we have a local \TeX job, be it that it shares all variables with the parent loop.

24 `\beginmathgroup`

In math mode grouping with `\begingroup` and `\endgroup` in some cases works as expected, but because the math input is converted in a list that gets processed later some settings can become persistent, like changes in style or family. The engine therefore provides the alternatives `\beginmathgroup` and `\endmathgroup` that restore some properties.

25 `\beginsimplegroup`

The original \TeX engine distinguishes two kind of grouping that at the user end show up as:

```

\begingroup \endgroup
\bggroup \egroup { }

```

where the last two pairs are equivalent unless the scanner explicitly wants to see a left and/or right brace and not an equivalent. For the sake of simplify we use the aliases here. It is not possible to mix these pairs, so:

```

\bggroup xxx\endgroup
\begingroup xxx\egroup

```

will in both cases issue an error. This can make it somewhat hard to write generic grouping macros without somewhat dirty trickery. The way out is to use the generic group opener `\beginsimplegroup`.

Internally LuaMetaTeX is aware of what group it currently is dealing with and there we distinguish:

simple group	<code>\bgroup</code>	<code>\egroup</code>
semi simple group	<code>\begingroup</code>	<code>\endgroup \endsimplegroup</code>
also simple group	<code>\beginsimplegroup</code>	<code>\egroup \endgroup \endsimplegroup</code>
math simple group	<code>\beginmathgroup</code>	<code>\endmathgroup</code>

This means that you can say:

```
\beginsimplegroup xxx\endsimplegroup
\beginsimplegroup xxx\endgroup
\beginsimplegroup xxx\egroup
```

So a group started with `\beginsimplegroup` can be finished in three ways which means that the user (or calling macro) doesn't have to take into account what kind of grouping was used to start with. Normally usage of this primitive is hidden in macros and not something the user has to be aware of.

26 \catcode

Every character can be put in a category, but this is typically something that the macro package manages because changes can affect behavior. Also, once passed as an argument, the catcode of a character is frozen. There are 16 different values:

<code>\escapecatcode</code>	0	<code>\begingroupcatcode</code>	1
<code>\endgroupcatcode</code>	2	<code>\mathshifcatcode</code>	3
<code>\alignmentcatcode</code>	4	<code>\endoflinecatcode</code>	5
<code>\parametercatcode</code>	6	<code>\superscriptcatcode</code>	7
<code>\subscriptcatcode</code>	8	<code>\ignorecatcode</code>	9
<code>\spacecatcode</code>	10	<code>\lettercatcode</code>	11
<code>\othercatcode</code>	12	<code>\activecatcode</code>	13
<code>\commentcatcode</code>	14	<code>\invalidcatcode</code>	15

The first column shows the constant that ConTeXt provides and the name indicates the purpose. Here are two examples:

```
\catcode123=\begingroupcatcode
\catcode125=\endgroupcatcode
```

27 \catcodetable

The catcode table with the given index will become active.

28 \cdef

This primitive is like `\edef` but in some usage scenarios is slightly more efficient because (delayed) expansion is ignored which in turn saves building a temporary token list.

```
\edef\FooA{this is foo} \meaningfull\FooA\cr\lf
\cdef\FooB{this is foo} \meaningfull\FooB\par
```

```
macro:this is foo
constant macro:this is foo
```

29 `\cdefcsname`

This primitive is like `\edefcsame` but in some usage scenarios is slightly more efficient because (delayed) expansion is ignored which in turn saves building a temporary token list.

```
\edefcsname FooA\endcsname{this is foo} \meaningasis\FooA\crlf
\cdefcsname FooB\endcsname{this is foo} \meaningasis\FooB\par

\def \FooA {this is foo}
\constant \def \FooB {this is foo}
```

30 `\chardef`

The following definition relates a control sequence to a specific character:

```
\chardef\copyrightsign"A9
```

However, because in a context where a number is expected, such a `\chardef` is seen as valid number, there was a time when this primitive was used to define constants without overflowing the by then limited pool of count registers. In ε -T_EX aware engines this was less needed, and in LuaMetaT_EX we have `\integerdef` as a more natural candidate.

31 `\constant`

This prefix tags a macro (without arguments) as being constant. The main consequence is that in some cases expansion gets delayed which gives a little performance boost and less (temporary) memory usage, for instance in `\csname` like scenarios.

32 `\constrained`

See previous section about `\retained`.

33 `\count`

This accesses a count register by index. This is kind of ‘not done’ unless you do it local and make sure that it doesn't influence macros that you call.

```
\count4023=10
```

In standard T_EX the first 10 counters are special because they get reported to the console, and `\count0` is then assumed to be the page counter.

34 `\countdef`

This primitive relates a control sequence to a count register. Compare this to the example in the previous section.

```
\countdef\MyCounter4023
\MyCounter=10
```

However, this is also ‘not done’. Instead one should use the allocator that the macro package provides.

```
\newcount\MyCounter
\MyCounter=10
```

In LuaMetaTeX we also have integers that don't rely on registers. These are assigned by the primitive `\integerdef`:

```
\integerdef\MyCounterA 10
```

Or better `\newinteger`.

```
\newinteger\MyCounterB
\MyCounterN10
```

There is a lowlevel manual on registers.

35 \csactive

Because LuaTeX (and LuaMetaTeX) are Unicode engines active characters are implemented a bit differently. They don't occupy a eight bit range of characters but are stored as control sequence with a special prefix `U+FFFF` which never shows up in documents. The `\csstring` primitive injects the name of a control sequence without leading escape character, the `\csactive` injects the internal name of the following (either of not active) character. As we cannot display the prefix: `\csactive~` will inject the utf sequences for `U+FFFF` and `U+007E`, so here we get the bytes `EFBFBF7E`. Basically the next token is preceded by `\string`, so when you don't provide a character you are in for a surprise.

36 \csname

This original TeX primitive starts the construction of a control sequence reference. It does a lookup and when no sequence with than name is found, it will create a hash entry and defaults its meaning to `\relax`.

`\csname` letters and other characters `\endcsname`

37 \csstring

This primitive returns the name of the control sequence given without the leading escape character (normally a backslash). Of course you could strip that character with a simple helper but this is more natural.

```
\csstring\mymacro
```

We get the name, not the meaning: `mymacro`.

38 \currentgrouplevel

The next example gives: `[1] [2] [3] [2] [1]`.

```
[\the\currentgrouplevel] \bgroup
  [\the\currentgrouplevel] \bgroup
    [\the\currentgrouplevel]
      \egroup [\the\currentgrouplevel]
\egroup [\the\currentgrouplevel]
```

39 \currentgrouptype

The next example gives: [22] [1] [22] [1] [1] [23] [1] [1].

```
[\the\currentgrouptype] \bgroup
  [\the\currentgrouptype] \begingroup
    [\the\currentgrouptype]
  \endgroup [\the\currentgrouptype]
  [\the\currentgrouptype] \beginmathgroup
    [\the\currentgrouptype]
  \endmathgroup [\the\currentgrouptype]
[\the\currentgrouptype] \egroup
```

The possible values depend in the engine and for LuaMetaTeX they are:

0 bottomlevel	9 output	18 mathoperator	27 mathnumber
1 simple	10 mathsubformula	19 mathradical	28 localbox
2 hbox	11 mathstack	20 mathchoice	29 splitoff
3 adjustedhbox	12 mathcomponent	21 alsosimple	30 splitkeep
4 vbox	13 discretionary	22 semisimple	31 preamble
5 vtop	14 insert	23 mathsimple	32 alignset
6 hbox	15 vadjust	24 mathfence	33 finishrow
7 align	16 vcenter	25 mathinline	34 lua
8 noalign	17 mathfraction	26 mathdisplay	

40 \currentifbranch

The next example gives: [0] [1] [-1] [1] [0].

```
[\the\currentifbranch] \iftrue
  [\the\currentifbranch] \iffalse
    [\the\currentifbranch]
  \else
    [\the\currentifbranch]
  \fi [\the\currentifbranch]
\fi [\the\currentifbranch]
```

So when in the ‘then’ branch we get plus one and when in the ‘else’ branch we end up with a minus one.

41 \currentiflevel

The next example gives: [0] [1][2] [3] [2] [1] [0].

```
[\the\currentiflevel] \iftrue
  [\the\currentiflevel]\iftrue
    [\the\currentiflevel] \iftrue
      [\the\currentiflevel]
      \fi [\the\currentiflevel]
    \fi [\the\currentiflevel]
  \fi [\the\currentiflevel]
```

42 \currentifttype

The next example gives: [-1] [25][25] [25] [25] [25] [-1].

```
[\the\currentifttype] \iftrue
  [\the\currentifttype]\iftrue
    [\the\currentifttype] \iftrue
      [\the\currentifttype]
      \fi [\the\currentifttype]
    \fi [\the\currentifttype]
  \fi [\the\currentifttype]
```

The values are engine dependent:

0 char	7 absfloat	14 odd	21 vbox	28 chknunber
1 cat	8 zerofloat	15 vmode	22 tok	29 numval
2 num	9 intervalfloat	16 hmode	23 cstoken	30 cmpnum
3 absnum	10 dim	17 mmode	24 x	31 chkdim
4 zeronum	11 absdim	18 inner	25 true	32 chkdimension
5 intervalnum	12 zerodim	19 void	26 false	33 dimval
6 float	13 intervaldim	20 hbox	27 chknum	34 cmpdim

43 \currentloopiterator

Here we show the different expanded loop variants:

```
\edef\testA{\expandedloop 1 10 1{!}}
\edef\testB{\expandedrepeat 10 {!}}
\edef\testC{\expandedendless {\ifnum\currentloopiterator>10 \quitloop\else !\fi}}
\edef\testD{\expandedendless {\ifnum#I>10 \quitloop\else !\fi}}
```

All these give the same result:

```
\def \testA {!!!!!!!!!!!!}
\def \testB {!!!!!!!!!!!!}
\def \testC {!!!!!!!!!!!!}
\def \testD {!!!!!!!!!!!!}
```

The **#I** is a shortcut to the current loop iterator; other shortcuts are **#P** for the parent iterator value and **#G** for the grand parent.

44 `\currentloopnesting`

This integer reports how many nested loops are currently active. Of course in practice the value only has meaning when you know at what outer level your nested loop started.

45 `\currentstacksize`

This is more diagnostic feature than a useful one but we show it anyway. There is some basic overhead when we enter a group:

```
\bgroup [\the\currentstacksize]
  \bgroup [\the\currentstacksize]
    \bgroup [\the\currentstacksize]
      [\the\currentstacksize] \egroup
    [\the\currentstacksize] \egroup
  [\the\currentstacksize] \egroup
```

[57] [58] [59] [59] [58] [57]

As soon as we define something or change a value, the stack gets populated by information needed for recovery after the group ends.

```
\bgroup [\the\currentstacksize]
  \scratchcounter 1
  \bgroup [\the\currentstacksize]
    \scratchdimen 1pt
    \scratchdimen 2pt
    \bgroup [\the\currentstacksize]
      \scratchcounter 2
      \scratchcounter 3
      [\the\currentstacksize] \egroup
    [\the\currentstacksize] \egroup
  [\the\currentstacksize] \egroup
```

[57] [59] [61] [62] [60] [58]

The stack also keeps some state information, for instance when a box is being built. In LuaMetaTeX that is quite a bit more than in other engines but it is compensated by more efficient save stack handling elsewhere.

```
\hbox \bgroup [\the\currentstacksize]
  \hbox \bgroup [\the\currentstacksize]
    \hbox \bgroup [\the\currentstacksize]
      [\the\currentstacksize] \egroup
    [\the\currentstacksize] \egroup
  [\the\currentstacksize] \egroup
```

[65] [74] [83] [83] [74] [65]

46 `\def`

This is the main definition command, as in:

```
\def\foo{l me}
```

with companions like `\gdef`, `\edef`, `\xdef`, etc. and variants like:

```
\def\foo#1{... #1...}
```

where the hash is used in the preamble and for referencing. More about that can be found in the low level manual about macros.

47 `\defcsname`

We now get a series of log clutter avoidance primitives. It's fine if you argue that they are not really needed, just don't use them.

```
\expandafter\def\csname MyMacro:1\endcsname{...}
\defcsname MyMacro:1\endcsname{...}
```

The fact that \TeX has three (expanded and global) companions can be seen as a signal that less verbosity makes sense. It's just that macro packages use plenty of `\csname`'s.

48 `\deferred`

This is mostly a compatibility prefix and it can be checked at the Lua end when there is a Lua based assignment going on. It is the counterpart of `\immediate`. In the traditional engines a `\write` is normally deferred (turned into a node) and can be handled `\immediate`, while a `\special` does the opposite.

49 `\detokened`

The following token will be serialized into characters with category ‘other’.

```
\toks0{123}
\def\foo{let's be \relax'd}
\def\oof#1{let's see #1}
\detokened\toks0
\detokened\foo
\detokened\oof
\detokened\setbox
\detokened X
```

Gives:

```
123
let's be \relax 'd
\oof
\setbox
X
```

Macros with arguments are not shown.

50 `\detokenize`

This ε -TeX primitive turns the content of the provides list will become characters, kind of verbatim.

```
\expandafter\let\expandafter\temp\detokenize{1} \meaning\temp
\expandafter\let\expandafter\temp\detokenize{A} \meaning\temp
```

the character U+0031 1

the character U+0041 A

51 `\detokenized`

The following (single) token will be serialized into characters with category ‘other’.

```
\toks0{123}
\def\foo{let's be \relax'd}
\def\oof#1{let's see #1}
\detokenized\toks0
\detokenized\foo
\detokenized\oof
\detokenized\setbox
\detokenized X
```

Gives:

```
\toks 0
\foo
\oof
\setbox
X
```

It is one of these new primitives that complement others like `\detokened` and such, and they are often mostly useful in experiments of some low level magic, which made them stay.

52 `\dimen`

Like `\count` this is a register accessor which is described in more detail in a low level manual.

```
\dimen0=10pt
```

While TeX has some assumptions with respect to the first ten count registers (as well as the one that holds the output, normally 255), all dimension registers are treated equal. However, you need to be aware of clashes with other usage. Therefore you can best use the predefined scratch registers or define dedicate ones with the `\newdimen` macro.

53 `\dimendef`

This primitive is used by the `\newdimen` macro when it relates a control sequence with a specific register. Only use it when you know what you're doing.

54 `\dimensiondef`

A variant of `\integerdef` is:

```
\dimensiondef\MyDimen = 1234pt
```

The properties are comparable to the ones described in the section `\integerdef`.

55 `\dimexpr`

This primitive is similar to `\numexpr` but operates on dimensions instead. Integer quantities are interpreted as dimensions in scaled points.

```
\the\dimexpr (1pt + 2pt - 5pt) * 10 / 2 \relax
```

gives: -10.0pt. You can mix in symbolic integers and dimensions. This doesn't work:

because the engine scans for a dimension and only for an integer (or equivalent) after a `*` or `/`.

56 `\dimexpression`

This command is like `\numexpression` but results in a dimension instead of an integer. Where `\dimexpr` doesn't like `2 * 10pt` this expression primitive is quite happy with it.

57 `\directlua`

This is the low level interface to Lua:

Gives: "Greetings from the lua end!" as expected. In Lua we have access to all kind of internals of the engine. In LuaMetaTeX the interfaces have been polished and extended compared to LuaTeX. Although many primitives and mechanisms were added to the TeX frontend, the main extension interface remains Lua. More information can be found in documents that come with ConTeXt, in presentations and in articles.

58 `\divide`

The `\divide` operation can be applied to integers, dimensions, float, attribute and glue quantities. There are subtle rounding differences between the divisions in expressions and `\divide`:

```
\scratchcounter 1049 \numexpr\scratchcounter / 10\relax : 105
\scratchcounter 1049 \numexpr\scratchcounter : 10\relax : 104
\scratchcounter 1049 \divide\scratchcounter by 10      : 104
```

The `:` divider in `\dimexpr` is something that we introduced in LuaTeX.

59 `\divideby`

This is slightly more efficient variant of `\divide` that doesn't look for `by`. See previous section.

60 \edef

This is the expanded version of \def.

```
\def \foo{foo}      \meaning\foo
\def \of{\foo\foo} \meaning\of
\edef\oof{\foo\foo} \meaning\oof
```

Because \foo is unprotected it will expand inside the body definition:

```
macro:foo
macro:\foo \foo
macro:foofoo
```

61 \edefcsname

This is the companion of \edef:

```
\expandafter\edef\csname MyMacro:1\endcsname{...}
\edefcsname MyMacro:1\endcsname{...}
```

62 \edivide

When expressions were introduced the decision was made to round the divisions which is incompatible with the way \divide works. The expression scanners in LuaMetaTeX compensates that by providing a : for integer division. The \ edivide does the opposite: it rounds the way expressions do.

```
\the\dimexpr .4999pt : 2 \relax      =.24994pt
\the\dimexpr .4999pt / 2 \relax      =.24995pt
\scratchdimen.4999pt \divide \scratchdimen 2 \the\scratchdimen=.24994pt
\scratchdimen.4999pt \edivide\scratchdimen 2 \the\scratchdimen=.24995pt

\the\numexpr 1001 : 2 \relax          =500
\the\numexpr 1001 / 2 \relax          =501
\scratchcounter1001 \divide \scratchcounter 2 \the\scratchcounter=500
\scratchcounter1001 \edivide\scratchcounter 2 \the\scratchcounter=501
```

Keep in mind that with dimensions we have a fractional part so we actually rounding applies to the fraction. For that reason we also provide \rdivide.

```
0.24994pt=.24994pt
0.24995pt=.24995pt
0.24994pt=.24994pt
0.24995pt=.24995pt
```

```
500=500
501=501
500=500
501=501
```

63 `\edivideby`

This the by-less variant of `\edivide`.

64 `\else`

This traditional primitive is part of the condition testing mechanism. When a condition matches, \TeX will continue till it sees an `\else` or `\or` or `\orelse` (to be discussed later). It will then do a fast skipping pass till it sees an `\fi`.

65 `\end`

This ends a \TeX run, unless of course this primitive is redefined.

66 `\endcsname`

This primitive is used in combination with `\csname`, `\ifcsname` and `\beginscname` where its end the scanning for the to be constructed control sequence token.

67 `\endgroup`

This is the companion of the `\begingroup` primitive that opens a group. See `\beginsimplegroup` for more info.

68 `\endinput`

The engine can be in different input modes: reading from file, reading from a token list, expanding a macro, processing something that comes back from Lua, etc. This primitive quits reading from file:

```
this is seen
\endinput
here we're already quit
```

There is a catch. This is what the above gives:

```
this is seen
but how about this:
```

```
this is seen
before \endinput after
here we're already quit
```

Here we get:

```
this is seen before after
```

Because a token list is one line, the following works okay:

```
\def\quitrn{\ifsomething \endinput \fi}
```

but in a file you'd have to do this when you quit in a conditional:

```
\ifsomething
  \expandafter \endinput
\fi
```

While the one-liner works as expected:

```
\ifsomething \endinput \fi
```

69 **\endlinechar**

This is an internal integer register. When set to positive value the character with that code point will be appended to the line. The current value is 13. Here is an example:

```
\endlinechar\hyphenasciicode
line 1
line 2
```

line 1-line 2-

If the character is active, the property is honored and the command kicks in. The maximum value is 127 (the maximum character code a single byte utf character can carry.)

70 **\endlocalcontrol**

See **\beginlocalcontrol**.

71 **\endmathgroup**

This primitive is the counterpart of **\beginmathgroup**.

72 **\endsimplegroup**

This one ends a simple group, see **\beginsimplegroup** for an explanation about grouping primitives.

73 **\enforced**

The engine can be set up to prevent overloading of primitives and macros defined as **\permanent** or **\immutable**. However, a macro package might want to get around this in controlled situations, which is why we have a **\enforced** prefix. This prefix is interpreted differently in so called ‘ini’ mode when macro definitions can be dumped in the format. Internally they get an **always** flag as indicator that in these places an overload is possible.

```
\permanent\def\foo{original}

\def\oof           {\def\foo{fails}}
\def\oof{\enforced\def\foo{succeeds}}
```

Of course this only has an effect when overload protection is enabled.

74 `\eofinput`

This is a variant on `\input` that takes a token list as first argument. That list is expanded when the file ends. It has companion primitives `\atendoffile` (single token) and `\atendoffiled` (multiple tokens).

75 `\errmessage`

This primitive expects a token list and shows its expansion on the console and/or in the log file, depending on how \TeX is configured. After that it will enter the error state and either goes on or waits for input, again depending on how \TeX is configured. For the record: we don't use this primitive in \ConTeXt .

76 `\errorstopmode`

This directive stops at every opportunity to interact. In \ConTeXt we overload the actions in a callback and quit the run because we can assume that a successful outcome is unlikely.

77 `\escapechar`

This internal integer has the code point of the character that get prepended to a control sequence when it is serialized (for instance in tracing or messages).

78 `\etoks`

This assigns an expanded token list to a token register:

```
\def\temp{less stuff}
\etoks\scratchtoks{a bit \temp}
```

The original value of the register is lost.

79 `\etoksapp`

A variant of `\toksapp` is the following: it expands the to be appended content.

```
\def\temp{more stuff}
\etoksapp\scratchtoks{some \temp}
```

80 `\etokspre`

A variant of `\tokspre` is the following: it expands the to be prepended content.

```
\def\temp{less stuff}
\etokspre\scratchtoks{a bit \temp}
```

81 `\eufactor`

When we introduced the `es` (2.5cm) and `ts` (2.5mm) units as metric variants of the `in` we also added the `eu` factor. One `eu` equals one tenth of a `es` times the `\eufactor`. The `ts` is a convenient offset in

test files, the `es` a convenient ones for layouts and image dimensions and the `eu` permits definitions that scale nicely without the need for dimensions. They also were a prelude to what later became possible with `\associateunit`.

82 `\everyeof`

The content of this token list is injected when a file ends but it can only be used reliably when one is really sure that no other file is loaded in the process. So in the end it is of no real use in a more complex macro package.

83 `\everyjob`

This token list register is injected at the start of a job, or more precisely, just before the main control loop starts.

84 `\expand`

Beware, this is not a prefix but a directive to ignore the protected characters of the following macro.

```
\protected \def \testa{\the\scratchcounter}
      \edef\testb{\testa}
      \edef\testc{\expand\testa}
```

The meaning of the three macros is:

```
protected macro:\the \scratchcounter
macro:\testa
macro:123
```

85 `\expandactive`

This a bit of an outlier and mostly there for completeness.

```

\meaningasis~
\edef\foo{~}          \meaningasis\foo
\edef\foo{\expandactive~} \meaningasis\foo
```

There seems to be no difference but the real meaning of the first `\foo` is ‘active character 126’ while the second `\foo` ‘protected call ’ is.

```
\protected \def ~ {\nobreakspace }
\def \foo {~}
\def \foo {~}
```

Of course the definition of the active tilde is ConT_EXt specific and situation dependent.

86 `\expandafter`

This original T_EX primitive stores the next token, does a one level expansion of what follows it, which actually can be an not expandable token, and reinjects the stored token in the input. Like:

```
\expandafter\let\csname my weird macro name\endcsname{m w m n}
```

Without `\expandafter` the `\csname` primitive would have been let to the left brace (effectively then a begin group). Actually in this particular case the control sequence with the weird name is injected and when it didn't yet exist it will get the meaning `\relax` so we sort of have two assignments in a row then.

87 `\expandafterpars`

Here is another gobble: the next token is reinjected after following spaces and par tokens have been read. So:

```
[\expandafterpars 1 2]
[\expandafterpars 3
4]
[\expandafterpars 5
6]
```

gives us: [12] [34] [56], because empty lines are like `\par` and therefore ignored.

88 `\expandafterspaces`

This is a gobble: the next token is reinjected after following spaces have been read. Here is a simple example:

```
[\expandafterspaces 1 2]
[\expandafterspaces 3
4]
[\expandafterspaces 5
6]
```

We get this typeset: [12] [34] [5

6], because a newline normally is configured to be a space (and leading spaces in a line are normally being ignored anyway).

89 `\expandcstoken`

The rationale behind this primitive is that when we `\let` a single token like a character it is hard to compare that with something similar, stored in a macro. This primitive pushes back a single token alias created by `\let` into the input.

```
\let\tempA + \meaning\tempA
```

```
\let\tempB X \meaning\tempB \crlf
\let\tempC $ \meaning\tempC \par
```

```
\edef\temp      {\tempA} \doifelse{\temp}{+}{Y}{N} \meaning\temp \crlf
\edef\temp      {\tempB} \doifelse{\temp}{X}{Y}{N} \meaning\temp \crlf
\edef\temp      {\tempC} \doifelse{\temp}{X}{Y}{N} \meaning\temp \par
```

```

\edef\temp{\expandcstoken\tempA} \doifelse{\temp}{+}{Y}{N} \meaning\temp \crlf
\edef\temp{\expandcstoken\tempB} \doifelse{\temp}{X}{Y}{N} \meaning\temp \crlf
\edef\temp{\expandcstoken\tempC} \doifelse{\temp}{$}{Y}{N} \meaning\temp \par

\doifelse{\expandcstoken\tempA}{+}{Y}{N}
\doifelse{\expandcstoken\tempB}{X}{Y}{N}
\doifelse{\expandcstoken\tempC}{$}{Y}{N} \par

```

The meaning of the `\let` macros shows that we have a shortcut to a character with (in this case) catcode letter, other (here ‘other character’ gets abbreviated to ‘character’), math shift etc.

the character U+002B ‘plus sign’

the letter U+0058 X

math shift character U+0024 ‘dollar sign’

N macro:\tempA

N macro:\tempB

N macro:\tempC

Y macro:+

Y macro:X

Y macro:\$

Y Y Y

Here we use the ConT_EXt macro `\doifelse` which can be implemented in different ways, but the only property relevant to the user is that the expanded content of the two arguments is compared.

90 \expanded

This primitive complements the two expansion related primitives mentioned in the previous two sections. This time the content will be expanded and then pushed back into the input. Protected macros will not be expanded, so you can use this primitive to expand the arguments in a call. In ConT_EXt you need to use `\normalexpanded` because we already had a macro with that name. We give some examples:

```

\def\A{!}
\def\B#1{\string#1} \B{\A}
\def\B#1{\string#1} \normalexpanded{\noexpand\B{\A}}
\protected\def\B#1{\string#1} \B{\A}

\A
!
\A

```

91 \expandedafter

The following two lines are equivalent:

```

\def\foo{123}
\expandafter[\expandafter[\expandafter\secondofthreearguments\foo]]

```

```
\expandedafter{[[\secondofthreearguments]\foo]}
```

In ConT_EXt MkIV the number of times that one has multiple `\expandafters` is much larger than in ConT_EXt LMTX thanks to some of the new features in LuaMetaT_EX, and this primitive is not really used yet in the core code.

```
[[2]]
```

```
[[2]]
```

92 `\expandeddetokenize`

This is a companion to `\detokenize` that expands its argument:

```
\def\foo{12#H3}
\def\oof{\foo}
\detokenize      {\foo} \detokenize      {\oof}
\expandeddetokenize{\foo} \expandeddetokenize{\oof}
\edef\ofo{\expandeddetokenize{\foo}} \meaningless\ofo
\edef\ofo{\expandeddetokenize{\oof}} \meaningless\ofo
```

This is a bit more convenient than

```
\detokenize \expandafter {\normalexpanded {\foo}}
```

kind of solutions. We get:

```
\foo \oof
12#3 12#3
12#3
12#3
```

93 `\expandedendless`

This one loops forever but because the loop counter is not set you need to find a way to quit it.

94 `\expandedloop`

This variant of the previously introduced `\localcontrolledloop` doesn't enter a local branch but immediately does its work. This means that it can be used inside an expansion context like `\edef`.

```
\edef\whatever
  {\expandedloop 1 10 1
    {\scratchcounter=\the\currentloopiterator\relax}}

\meaningasis\whatever
```

```
\def \whatever {\scratchcounter =1\relax \scratchcounter =2\relax \scratchcounter =3\relax \scratchcounter
=4\relax \scratchcounter =5\relax \scratchcounter =6\relax \scratchcounter =7\relax \scratchcounter =8\relax
\scratchcounter =9\relax \scratchcounter =10\relax }
```

95 `\expandedrepeat`

This one takes one instead of three arguments which is sometimes more convenient.

96 `\expandparameter`

This primitive is a predecessor of `\parameterdef` so we stick to a simple example.

```
\def\foo#1#2%
  {\integerdef\MyIndexOne\parameterindex\plusone % 1
   \integerdef\MyIndexTwo\parameterindex\plustwo % 2
   \oof{P}\oof{Q}\oof{R}\norelax}

\def\oof#1%
  {<1:\expandparameter\MyIndexOne><1:\expandparameter\MyIndexOne>%
   #1%
   <2:\expandparameter\MyIndexTwo><2:\expandparameter\MyIndexTwo>}

\foo{A}{B}
```

In principle the whole parameter stack can be accessed but often one never knows if a specific macro is called nested. The original idea behind this primitive was tracing but it can also be used to avoid passing parameters along a chain of calls.

```
<1:A><1:A>P<2:B><2:B><1:A><1:A>Q<2:B><2:B><1:A><1:A>R<2:B><2:B>
```

97 `\expandtoken`

This primitive creates a token with a specific combination of catcode and character code. Because it assumes some knowledge of $\text{T}_{\text{E}}\text{X}$ we can show it using some `\expandafter` magic:

```
\expandafter\let\expandafter\temp\expandtoken 11 `X \meaning\temp
\expandafter\let\expandafter\temp\expandtoken 12 `X \meaning\temp
```

The meanings are:

```
the letter U+0058 X
the character U+0058 X
```

Using other catcodes is possible but the results of injecting them into the input directly (or here by injecting `\temp`) can be unexpected because of what $\text{T}_{\text{E}}\text{X}$ expects. You can get messages you normally won't get, for instance about unexpected alignment interference, which is a side effect of $\text{T}_{\text{E}}\text{X}$ using some catcode/character combinations as signals and there is no reason to change those internals. That said:

```
\xdef\tempA{\expandtoken 9 `X} \meaning\tempA
\xdef\tempB{\expandtoken 10 `X} \meaning\tempB
\xdef\tempC{\expandtoken 11 `X} \meaning\tempC
\xdef\tempD{\expandtoken 12 `X} \meaning\tempD
```

are all valid and from the meaning you cannot really deduce what's in there:

```
macro:X
```

```
macro:X
macro:X
macro:X
```

But you can be assured that:

```
[AB: \ifx\tempA\tempB Y\else N\fi]
[AC: \ifx\tempA\tempC Y\else N\fi]
[AD: \ifx\tempA\tempD Y\else N\fi]
[BC: \ifx\tempB\tempC Y\else N\fi]
[BD: \ifx\tempB\tempD Y\else N\fi]
[CD: \ifx\tempC\tempD Y\else N\fi]
```

makes clear that they're different: [AB: N] [AC: N] [AD: N] [BC: N] [BD: N] [CD: N], and in case you wonder, the characters with catcode 10 are spaces, while those with code 9 are ignored.

98 \expandtoks

This is a more efficient equivalent of \the applied to a token register, so:

```
\scratchtoks{just some tokens}
\edef\TestA{[\the \scratchtoks]}
\edef\TestB{[\expandtoks\scratchtoks]}
[\the \scratchtoks] [\TestA] \meaning\TestA
[\expandtoks\scratchtoks] [\TestB] \meaning\TestB
```

does the expected:

```
[just some tokens] [[just some tokens]] macro:[just some tokens]
[just some tokens] [[just some tokens]] macro:[just some tokens]
```

The \expandtoken primitive avoid a copy into the input when there is no need for it.

99 \explicitdiscretionary

This is the verbose alias for one of T_EX's single character control sequences: \-.

100 \explicititaliccorrection

This is the verbose alias for one of T_EX's single character control sequences: \/. Italic correction is a character property specific to T_EX and the concept is not present in modern font technologies. There is a callback that hooks into this command so that a macro package can provide its own solution to this (or alternatively it can assign values to the italic correction field).

101 \explicitspace

This is the verbose alias for one of T_EX's single character control sequences: \. A space is inserted with properties according the space related variables. There is look-back involved in order to deal with space factors.

When \nospaces is set to 1 no spaces are inserted, when its value is 2 a zero space is inserted.

102 \fi

This traditional primitive is part of the condition testing mechanism and ends a test. So, we have:

```
\ifsomething ... \else ... \fi
\ifsomething ... \or ... \or ... \else ... \fi
\ifsomething ... \orelse \ifsomething ... \else ... \fi
\ifsomething ... \or ... \orelse \ifsomething ... \else ... \fi
```

The \orelse is new in LuaMetaTeX and a continuation like we find in other programming languages (see later section).

103 \float

In addition to integers and dimensions, which are fixed 16.16 integer floats we also have ‘native’ floats, based on 32 bit posit unums.

```
\float0 = 123.456          \the\float0
\float2 = 123.456          \the\float0
\advance \float0 by 123.456 \the\float0
\advance \float0 by \float2 \the\float0
\divideby\float0 3         \the\float0
```

They come with the same kind of support as the other numeric data types:

```
123.45600032806396484
123.45600032806396484
246.91200065612792969
370.36800384521484375
123.45600128173828125
```

We leave the subtle differences between floats and dimensions to the user to investigate:

```
\dimen00 = 123.456pt       \the\dimen0
\dimen02 = 123.456pt       \the\dimen0
\advance \dimen0 by 123.456pt \the\dimen0
\advance \dimen0 by \dimen2  \the\dimen0
\divideby\dimen0 3         \the\dimen0
```

The nature of posits is that they are more accurate around zero (or smaller numbers in general).

```
123.456pt
123.456pt
246.91199pt
370.36798pt
123.456pt
```

This also works:

```
\float0=123.456e4
\float2=123.456    \multiply\float2 by 10000
\the\float0
```

\the\float2

The values are (as expected) the same:

```
1234560
1234560
```

104 \floatdef

This primitive defines a symbolic (macro) alias to a float register, just like `\countdef` and friends do.

105 \floatexpr

This is the companion of `\numexpr`, `\dimexpr` etc.

```
\scratchcounter 200
\the \floatexpr 123.456/456.123 \relax
\the \floatexpr 1.2*\scratchcounter \relax
\the \floatexpr \scratchcounter/3 \relax
\number\floatexpr \scratchcounter/3 \relax
```

Watch the difference between `\the` and `\number`:

```
0.27066383324563503265
240
66.666666984558105469
67
```

106 \font

This primitive is either a symbolic reference to the current font or in the perspective of an assignment is used to trigger a font definitions with a given name (cs) and specification. In LuaMetaTeX the assignment will trigger a callback that then handles the definition; in addition to the filename an optional size specifier is checked (at or scaled).

In LuaMetaTeX *all* font loading is delegated to Lua, and there is no loading code built in the engine. Also, instead of `\font` in ConTeXt one uses dedicated and more advanced font definition commands.

107 \formatname

It is in the name: `cont-en`, but we cheat here by only showing the filename and not the full path, which in a ConTeXt setup can span more than a line in this paragraph.

108 \frozen

You can define a macro as being frozen:

```
\frozen\def\MyMacro{...}
```

When you redefine this macro you get an error:

! You can't redefine a frozen macro.

This is a prefix like `\global` and it can be combined with other prefixes.¹

109 `\futurecsname`

In order to make the repertoire of `def`, `let` and `futurelet` primitives complete we also have:

```
\futurecsname MyMacro:1\endcsname\MyAction
```

110 `\futuredef`

We elaborate on the example of using `\futurelet` in the previous section. Compare that one with the next:

```
\def\MySpecialToken{[]
\def\DoWhatever{\ifx\NextToken\MySpecialToken YES\else NOP\fi : }
\futurelet\NextToken\DoWhatever [A]\crlf
\futurelet\NextToken\DoWhatever (A)\par
```

This time we get:

NOP: [A]

NOP: (A)

It is for that reason that we now also have `\futuredef`:

```
\def\MySpecialToken{[]
\def\DoWhatever{\ifx\NextToken\MySpecialToken YES\else NOP\fi : }
\futuredef\NextToken\DoWhatever [A]\crlf
\futuredef\NextToken\DoWhatever (A)\par
```

So we're back to what we want:

YES: [A]

NOP: (A)

111 `\futureexpand`

This primitive can be used as an alternative to a `\futurelet` approach, which is where the name comes from.²

```
\def\variantone<#1>{(#1)}
\def\varianttwo#1{[#1]}
\futureexpand<\variantone\varianttwo<one>
\futureexpand<\variantone\varianttwo{two}
```

So, the next token determines which of the two variants is taken:

¹ The `\outer` and `\long` prefixes are no-ops in LuaMetaTeX and LuaTeX can be configured to ignore them.

² In the engine primitives that have similar behavior are grouped in commands that are then dealt with together, code wise.

(one) [two]

Because we look ahead there is some magic involved: spaces are ignored but when we have no match they are pushed back into the input. The next variant demonstrates this:

```
\def\variantone<#1>{(#1)}
\def\varianttwo{}
\def\temp{\futureexpand<\variantone\varianttwo}
[\temp <one>]
[\temp {two}]
[\expandafter\temp\space <one>]
[\expandafter\temp\space {two}]
```

This gives us:

[(one)] [two] [(one)] [two]

112 \futureexpandis

We assume that the previous section is read. This variant will not push back spaces, which permits a consistent approach i.e. the user can assume that macro always gobbles the spaces.

```
\def\variantone<#1>{(#1)}
\def\varianttwo{}
\def\temp{\futureexpandis<\variantone\varianttwo}
[\temp <one>]
[\temp {two}]
[\expandafter\temp\space <one>]
[\expandafter\temp\space {two}]
```

So, here no spaces are pushed back. This is in the name of this primitive means ‘ignore spaces’, but having that added to the name would have made the primitive even more verbose (after all, we also don't have `\expandeddef` but `\edef` and no `\globalexpandeddef` but `\xdef`).

[(one)] [two] [(one)] [two]

113 \futureexpandisap

This primitive is like the one in the previous section but also ignores par tokens, so `isap` means ‘ignore spaces and paragraphs’.

114 \futurelet

The original \TeX primitive `\futurelet` can be used to create an alias to a next token, push it back into the input and then expand a given token.

```
\let\MySpecialTokenL[
\let\MySpecialTokenR] % nicer for checker
\def\DoWhatever{\ifx\NextToken\MySpecialTokenL YES\else NOP\fi : }
\futurelet\NextToken\DoWhatever [A]\crlf
\futurelet\NextToken\DoWhatever (A)\par
```

This is typically the kind of primitive that most users will never use because it expects a sane follow up handler (here `\DoWhatever`) and therefore is related to user interfacing.

YES: [A]

NOP: (A)

115 `\gdef`

The is the global companion of `\def`.

116 `\gdefcsname`

As with standard \TeX we also define global ones:

```
\expandafter\gdef\csname MyMacro:1\endcsname{...}
      \gdefcsname MyMacro:1\endcsname{...}
```

117 `\glet`

This is the global companion of `\let`. The fact that it is not an original primitive is probably due to the expectation for it not it not being used (as) often (as in $\text{Con}\text{\TeX}$ t).

118 `\gletcsname`

Naturally $\text{LuaMeta}\text{\TeX}$ also provides a global variant:

```
\expandafter\global\expandafter\let\csname MyMacro:1\endcsname\relax
\expandafter      \glet\csname MyMacro:1\endcsname\relax
      \gletcsname MyMacro:1\endcsname\relax
```

So, here we save even more.

119 `\glettonothing`

This is the global companion of `\lettonothing`.

120 `\global`

This is one of the original prefixes that can be used when we define a macro of change some register.

```
\bgroup
      \def\MyMacroA{a}
\global\def\MyMacroB{a}
      \gdef\MyMacroC{a}
\egroup
```

The macro defined in the first line is forgotten when the groups is left. The second and third definition are both global and these definitions are retained.

121 `\globaldefs`

When set to a positive value, this internal integer will force all definitions to be global, and in a complex macro package that is not something a user will do unless it is very controlled.

122 `\glueexpr`

This is a more extensive variant of `\dimexpr` that also handles the optional stretch and shrink components.

123 `\glueshrink`

This returns the shrink component of a glue quantity. The result is a dimension so you need to apply `\the` when applicable.

124 `\glueshrinkorder`

This returns the shrink order of a glue quantity. The result is a integer so you need to apply `\the` when applicable.

125 `\gluespecdef`

A variant of `\integerdef` and `\dimensiondef` is:

```
\gluespecdef\MyGlue = 3pt plus 2pt minus 1pt
```

The properties are comparable to the ones described in the previous sections.

126 `\gluestretch`

This returns the stretch component of a glue quantity. The result is a dimension so you need to apply `\the` when applicable.

127 `\gluestretchorder`

This returns the stretch order of a glue quantity. The result is a integer so you need to apply `\the` when applicable.


128 `\glyph`

This is a more extensive variant of `\char` that permits setting some properties if the injected character node.

```
\ruledhbox{\glyph
  scale 2000 xscale 9000 yscale 1200
  slant 700 weight 200
  xoffset 10pt yoffset -5pt left 10pt right 20pt
  123}
\quad
```

```
\ruledhbox{\glyph
  scale 2000 xscale 9000 yscale 1200
  slant 700 weight 200
  125}
```

In addition one can specify font (symbol), id (valid font id number), an options (bit set) and raise.



When no parameters are set, the current ones are used. More details and examples of usage can be found in the ConT_EXt distribution.

129 \gtoksapp

This is the global variant of \toksapp.

130 \gtokspre

This is the global variant of \tokspre.

131 \if

This traditional T_EX conditional checks if two character codes are the same. In order to understand unexpanded results it is good to know that internally T_EX groups primitives in a way that serves the implementation. Each primitive has a command code and a character code, but only for real characters the name character code makes sense. This condition only really tests for character codes when we have a character, in all other cases, the result is true.

```
\def\A{A}\def\B{B} \chardef\C=`C \chardef\D=`D \def\AA{AA}

[\if AA YES \else NOP \fi] [\if AB YES \else NOP \fi]
[\if \A\B YES \else NOP \fi] [\if \A\A YES \else NOP \fi]
[\if \C\D YES \else NOP \fi] [\if \C\C YES \else NOP \fi]
[\if \count\dimen YES \else NOP \fi] [\if \AA\A YES \else NOP \fi]
```

The last example demonstrates that the tokens get expanded, which is why we get the extra A:

```
[ YES ] [NOP ] [NOP ] [YES ] [YES ] [YES ] [YES ] [AYES ]
```

132 \ifabsdim

This test will negate negative dimensions before comparison, as in:

```
\def\TestA#1{\ifdim #1<2pt too small\orelse\ifdim #1>4pt too large\else okay\fi}
\def\TestB#1{\ifabsdim#1<2pt too small\orelse\ifabsdim#1>4pt too large\else okay\fi}

\TestA {1pt}\quad\TestA {3pt}\quad\TestA {5pt}\crlf
\TestB {1pt}\quad\TestB {3pt}\quad\TestB {5pt}\crlf
\TestB{-1pt}\quad\TestB{-3pt}\quad\TestB{-5pt}\par
```

So we get this:

```
too small  okay  too large
too small  okay  too large
too small  okay  too large
```

133 \ifabsfloat

This test will negate negative floats before comparison, as in:

```
\def\TestA#1{\iffloat #1<2.46 small\orelse\iffloat #1>4.68 large\else medium\fi}
\def\TestB#1{\ifabsfloat#1<2.46 small\orelse\ifabsfloat#1>4.68 large\else medium\fi}

\TestA {1.23}\quad\TestA {3.45}\quad\TestA {5.67}\crlf
\TestB {1.23}\quad\TestB {3.45}\quad\TestB {5.67}\crlf
\TestB {-1.23}\quad\TestB {-3.45}\quad\TestB {-5.67}\par
```

So we get this:

```
small  medium  large
small  medium  large
small  medium  large
```

134 \ifabsnum

This test will negate negative numbers before comparison, as in:

```
\def\TestA#1{\ifnum #1<100 too small\orelse\ifnum #1>200 too large\else okay\fi}
\def\TestB#1{\ifabsnum#1<100 too small\orelse\ifabsnum#1>200 too large\else okay\fi}

\TestA {10}\quad\TestA {150}\quad\TestA {210}\crlf
\TestB {10}\quad\TestB {150}\quad\TestB {210}\crlf
\TestB {-10}\quad\TestB {-150}\quad\TestB {-210}\par
```

Here we get the same result each time:

```
too small  okay  too large
too small  okay  too large
too small  okay  too large
```

135 \ifarguments

This is a variant of \ifcase where the selector is the number of arguments picked up. For example:

```
\def\MyMacro#1#2#3{\ifarguments\0\or1\or2\or3\else ?\fi} \MyMacro{A}{B}{C}
\def\MyMacro#1#0#3{\ifarguments\0\or1\or2\or3\else ?\fi} \MyMacro{A}{B}{C}
\def\MyMacro#1#-#2{\ifarguments\0\or1\or2\or3\else ?\fi} \MyMacro{A}{B}{C}\par
```

Watch the non counted, ignored, argument in the last case. Normally this test will be used in combination with \ignorearguments.

136 \ifboolean

This tests a number (register or equivalent) and any nonzero value represents true, which is nicer than using an `\unless\ifcase`.

137 \ifcase

This numeric T_EX conditional takes a counter (literal, register, shortcut to a character, internal quantity) and goes to the branch that matches.

```
\ifcase 3 zero\or one\or two\or three\or four\else five or more\fi
```

Indeed: three equals three. In later sections we will see some LuaMetaT_EX primitives that behave like an `\ifcase`.

138 \ifcat

Another traditional T_EX primitive: what happens with what gets read in depends on the catcode of a character, think of characters marked to start math mode, or alphabetic characters (letters) versus other characters (like punctuation).

```
\def\A{A}\def\B{,} \chardef\C=`C \chardef\D=`, \def\AA{AA}

[\ifcat $! YES \else NOP \fi] [\ifcat () YES \else NOP \fi]
[\ifcat AA YES \else NOP \fi] [\ifcat AB YES \else NOP \fi]
[\ifcat \A\B YES \else NOP \fi] [\ifcat \A\A YES \else NOP \fi]
[\ifcat \C\D YES \else NOP \fi] [\ifcat \C\C YES \else NOP \fi]
[\ifcat \count\dimen YES \else NOP \fi] [\ifcat \AA\A YES \else NOP \fi]
```

Close reading is needed here:

```
[NOP ] [ YES ] [ YES ] [ YES ] [NOP ] [YES ] [YES ] [YES ] [YES ] [AYES ]
```

This traditional T_EX condition as well as the one in the previous section are hardly used in ConT_EXt, if only because they expand what follows and we seldom need to compare characters.

139 \ifchkdim

A variant on the checker in the previous section is a dimension checker:

```
\ifchkdim oeps \or okay\else error\fi\quad
\ifchkdim 12 \or okay\else error\fi\quad
\ifchkdim 12pt \or okay\else error\fi\quad
\ifchkdim 12pt or more\or okay\else error\fi
```

We get:

```
error error okay okay
```

140 \ifchkdimension

CONtrary to `\ifchkdim` this test doesn't accept trailing crap:

```

\ifchkdimension oeps      \or okay\else error\fi\quad
\ifchkdimension 12        \or okay\else error\fi\quad
\ifchkdimension 12pt      \or okay\else error\fi\quad
\ifchkdimension 12pt or more\or okay\else error\fi

```

reports:

```
error error okay error
```

141 \ifchknum

In ConT_EXt there are quite some cases where a variable can have a number or a keyword indicating a symbolic name of a number or maybe even some special treatment. Checking if a valid number is given is possible to some extend, but a native checker makes much sense too. So here is one:

```

\ifchknum oeps      \or okay\else error\fi\quad
\ifchknum 12        \or okay\else error\fi\quad
\ifchknum 12pt      \or okay\else error\fi\quad
\ifchknum 12pt or more\or okay\else error\fi

```

The result is as expected:

```
error okay okay okay
```

142 \ifchknumber

This check is more restrictive than \ifchknum discussed in the previous section:

```

\ifchknumber oeps      \or okay\else error\fi\quad
\ifchknumber 12        \or okay\else error\fi\quad
\ifchknumber 12pt      \or okay\else error\fi\quad
\ifchknumber 12pt or more\or okay\else error\fi

```

Here we get:

```
error okay error error
```

143 \ifcmpdim

This conditional compares two dimensions and the resulting \ifcase reflects their relation:

```

[1pt 2pt : \ifcmpdim 1pt 2pt less\or equal\or more\fi]\quad
[1pt 1pt : \ifcmpdim 1pt 1pt less\or equal\or more\fi]\quad
[2pt 1pt : \ifcmpdim 2pt 1pt less\or equal\or more\fi]

```

This gives:

```
[1pt 2pt : less] [1pt 1pt : equal] [2pt 1pt : more]
```

144 \ifcmpnum

This conditional compares two numbers and the resulting \ifcase reflects their relation:


```
[1 2 : \ifcmpnum 1 2 less\or equal\or more\fi]\quad
[1 1 : \ifcmpnum 1 1 less\or equal\or more\fi]\quad
[2 1 : \ifcmpnum 2 1 less\or equal\or more\fi]
```

This gives:

```
[1 2 : less] [1 1 : equal] [2 1 : more]
```

145 \ifcondition

The conditionals in \TeX are hard coded as primitives and although it might look like `\newif` creates one, it actually just defined three macros.

```
\newif\ifMyTest
\meaning\MyTesttrue \crlf
\meaning\MyTestfalse \crlf
\meaning\ifMyTest \crlf \MyTesttrue
\meaning\ifMyTest \par
```

```
protected macro:\always \let \ifMyTest \iftrue
protected macro:\always \let \ifMyTest \iffalse
\iffalse
\iftrue
```

This means that when you say:

```
\ifMytest ... \else ... \fi
```

You actually have one of:

```
\iftrue ... \else ... \fi
\iffalse ... \else ... \fi
```

and because these are proper conditions nesting them like:

```
\ifnum\scratchcounter > 0 \ifMyTest A\else B\fi \fi
```

will work out well too. This is not true for macros, so for instance:

```
\scratchcounter = 1
\unexpanded\def\ifMyTest{\iftrue}
\ifnum\scratchcounter > 0 \ifMyTest A\else B\fi \fi
```

will make a run fail with an error (or simply loop forever, depending on your code). This is where `\ifcondition` enters the picture:

```
\def\MyTest{\iftrue} \scratchcounter0
\ifnum\scratchcounter > 0
  \ifcondition\MyTest A\else B\fi
\else
  x
\fi
```

This primitive is seen as a proper condition when $\text{T}_{\text{E}}\text{X}$ is in “fast skipping unused branches” mode but when it is expanding a branch, it checks if the next expanded token is a proper tests and if so, it deals with that test, otherwise it fails. The main condition here is that the `\MyTest` macro expands to a proper true or false test, so, a definition like:

```
\def\MyTest{\ifnum\scratchcounter<10 }
```

is also okay. Now, is that neat or not?

146 \ifcsname

This is an ε - $\text{T}_{\text{E}}\text{X}$ conditional that complements the one on the previous section:

```
\expandafter\ifx\csname MyMacro\endcsname\relax ... \else ... \fi
\ifcsname MyMacro\endcsname ... \else ... \fi
```

Here the first one has the side effect of defining the macro and defaulting it to `\relax`, while the second one doesn't do that. Juts think of checking a few million different names: the first one will deplete the hash table and probably string space too.

In $\text{LuaMetaT}_{\text{E}}\text{X}$ the construction stops when there is no letter or other character seen ($\text{T}_{\text{E}}\text{X}$ expands on the go so expandable macros are dealt with). Instead of an error message, the match is simply false and all tokens till the `\endcsname` are gobbled.

147 \ifcstok

A variant on the primitive mentioned in the previous section is one that operates on lists and macros:

```
\def\A{a} \def\B{b} \def\C{a}
```

This:

```
\ifcstok\A\B Y\else N\fi\space
\ifcstok\A\C Y\else N\fi\space
\ifcstok\A\c Y\else N\fi\space
\ifcstok\A\c Y\else N\fi
```

will give us: N Y Y Y.

148 \ifdefined

In traditional $\text{T}_{\text{E}}\text{X}$ checking for a macro to exist was a bit tricky and therefore ε - $\text{T}_{\text{E}}\text{X}$ introduced a convenient conditional. We can do this:

```
\ifx\MyMacro\undefined ... \else ... \fi
```

but that assumes that `\undefined` is indeed undefined. Another test often seen was this:

```
\expandafter\ifx\csname MyMacro\endcsname\relax ... \else ... \fi
```

Instead of comparing with `\undefined` we need to check with `\relax` because the control sequence is defined when not yet present and defaults to `\relax`. This is not pretty.

149 \ifdim

Dimensions can be compared with this traditional T_EX primitive.

```
\scratchdimen=1pt \scratchcounter=65536
```

```
\ifdim\scratchdimen=\scratchcounter sp YES \else NOP\fi
\ifdim\scratchdimen=1 pt YES \else NOP\fi
```

The units are mandate:

YES YES

150 \ifdimexpression

The companion of the previous primitive is:

This matches when the result is non zero, and you can mix calculations and tests as with normal expressions. Contrary to the number variant units can be used and precision kicks in.

151 \ifdimval

This conditional is a variant on \ifchkdir and provides some more detailed information about the value:

```
[-12pt : \ifdimval -12pt\or negative\or zero\or positive\else error\fi]\quad
[0pt : \ifdimval 0pt\or negative\or zero\or positive\else error\fi]\quad
[12pt : \ifdimval 12pt\or negative\or zero\or positive\else error\fi]\quad
[oeps : \ifdimval oeps\or negative\or zero\or positive\else error\fi]
```

This gives:

```
[-12pt : negative] [0pt : zero] [12pt : positive] [oeps : error]
```

152 \ifempty

This conditional checks if a control sequence is empty:

```
is \ifempty\MyMacro \else not \fi empty
```

It is basically a shortcut of:

```
is \ifx\MyMacro\empty \else not \fi empty
```

with:

```
\def\empty{}
```

Of course this is not empty at all:

```
\def\notempty#1{}
```

153 \iffalse

Here we have a traditional \TeX conditional that is always false (therefore the same is true for any macro that is \let to this primitive).

154 \ifflags

This test primitive relates to the various flags that one can set on a control sequence in the perspective of overload protection and classification.

```
\protected\untraced\tolerant\def\foo[#1]{...#1...}
\permanent\constant           \def\oof{okay}
```

flag	\foo	\oof	flag	\foo	\oof
frozen	N	N	permanent	N	Y
immutable	N	N	mutable	N	N
noaligned	N	N	instance	N	N
untraced	Y	N	global	N	N
tolerant	Y	N	constant	N	Y
protected	Y	N	semiprotected	N	N

Instead of checking against a prefix you can test against a bitset made from:

0x1	frozen	0x2	permanent	0x4	immutable	0x8	primitive
0x10	mutable	0x20	noaligned	0x40	instance	0x80	untraced
0x100	global	0x200	tolerant	0x400	protected	0x800	overloaded
0x1000	aliased	0x2000	immediate	0x4000	conditional	0x8000	value
0x10000	semiprotected	0x20000	inherited	0x40000	constant	0x80000	deferred

155 \iffloat

This test does for floats what \ifnum , \ifdim do for numbers and dimensions: comparing two of them.

156 \iffontchar

This is an $\varepsilon\text{-TeX}$ conditional. It takes a font identifier and a character number. In modern fonts simply checking could not be enough because complex font features can swap in other ones and their index can be anything. Also, a font mechanism can provide fallback fonts and characters, so don't rely on this one too much. It just reports true when the font passed to the frontend has a slot filled.

157 \ifhaschar

This one is a simplified variant of the above:

```
\ifhaschar !{this ! works} yes \else no \fi
```

and indeed we get: yes! Of course the spaces in this this example code are normally not present in such a test.

158 \ifhastok

This conditional looks for occurrences in token lists where each argument has to be a proper list.

```
\def\scratchtoks{x}

\ifhastoks{yz}      {xyz} Y\else N\fi\quad
\ifhastoks\scratchtoks {xyz} Y\else N\fi
```

We get:

Y Y

159 \ifhastoks

This test compares two token lists. When a macro is passed it's meaning gets used.

```
\def\x {x}
\def\xyz{xyz}

(\ifhastoks {x} {xyz}Y\else N\fi)\quad
(\ifhastoks {\x} {xyz}Y\else N\fi)\quad
(\ifhastoks \x {xyz}Y\else N\fi)\quad
(\ifhastoks {y} {xyz}Y\else N\fi)\quad
(\ifhastoks {yz} {xyz}Y\else N\fi)\quad
(\ifhastoks {yz} {\xyz}Y\else N\fi)
```

(Y) (N) (Y) (Y) (Y) (N)

160 \ifhasxtoks

This primitive is like the one in the previous section but this time the given lists are expanded.

```
\def\x {x}
\def\xyz{\x yz}

(\ifhasxtoks {x} {xyz}Y\else N\fi)\quad
(\ifhasxtoks {\x} {xyz}Y\else N\fi)\quad
(\ifhasxtoks \x {xyz}Y\else N\fi)\quad
(\ifhasxtoks {y} {xyz}Y\else N\fi)\quad
(\ifhasxtoks {yz} {xyz}Y\else N\fi)\quad
(\ifhasxtoks {yz} {\xyz}Y\else N\fi)
```

(Y) (Y) (Y) (Y) (Y) (Y)

This primitive has some special properties.

```
\edef\+{\expandtoken 9 `+}

\ifhasxtoks {xy} {xyz}Y\else N\fi\quad
\ifhasxtoks {x\+y} {xyz}Y\else N\fi
```

Here the first argument has a token that has category code ‘ignore’ which means that such a character will be skipped when seen. So the result is:

Y Y

This permits checks like these:

```
\edef\,{\expandtoken 9 ` ,}

\ifhasxtoks{\,x\,} {,x,y,z,}Y\else N\fi\quad
\ifhasxtoks{\,y\,} {,x,y,z,}Y\else N\fi\quad
\ifhasxtoks{\,z\,} {,x,y,z,}Y\else N\fi\quad
\ifhasxtoks{\,x\,} {,xy,z,}Y\else N\fi
```

I admit that it needs a bit of a twisted mind to come up with this, but it works ok:

Y Y Y N

161 \ifhbox

This traditional conditional checks if a given box register or internal box variable represents a horizontal box,

162 \ifhmode

This traditional conditional checks we are in (restricted) horizontal mode.

163 \iffinalignment

As the name indicates, this primitive tests for being in an alignment. Roughly spoken, the engine is either in a state of align, handling text or dealing with math.

164 \ifincsname

This conditional is sort of obsolete and can be used to check if we're inside a \csgname or \ifcsgname construction. It's not used in ConT_EXt.

165 \ifinner

This traditional one can be confusing. It is true when we are in restricted horizontal mode (a box), internal vertical mode (a box), or inline math mode.

```
test \ifhmode \ifinner INNER\fi HMODE\fi\crlf
\hbox{test \ifhmode \ifinner INNER \fi HMODE\fi} \par

\ifvmode \ifinner INNER\fi VMODE \fi\crlf
\ vbox{\ifvmode \ifinner INNER \fi VMODE\fi} \crlf
\ vbox{\ifinner INNER \ifvmode VMODE \fi \fi} \par
```

Watch the last line: because we typeset INNER we enter horizontal mode:

```
test HMODE
test INNER HMODE
```

VMODE
 INNER VMODE
 INNER

166 `\ifintervalldim`

This conditional is true when the intervals around the values of two dimensions overlap. The first dimension determines the interval.

```
[\ifintervalldim1pt 20pt 21pt \else no \fi overlap]
[\ifintervalldim1pt 18pt 20pt \else no \fi overlap]
```

So here: [overlap] [no overlap]

167 `\ifintervalfloat`

This one does with floats what we described under `\ifintervalldim`.

168 `\ifintervalnum`

This one does with integers what we described under `\ifintervalldim`.

169 `\iflastnamedcs`

When a `\csname` is constructed and succeeds the last one is remembered and can be accessed with `\lastnamedcs`. It can however be an undefined one. That state can be checked with this primitive. Of course it also works with the `\ifcurname` and `\begincurname` variants.

170 `\ifmathparameter`

This is an `\ifcase` where the value depends on if the given math parameter is zero, (0), set (1), or unset (2).

```
\ifmathparameter\Umathpunctclosespacing\displaystyle
  zero      \or
  nonzero   \or
  unset     \fi
```

171 `\ifmathstyle`

This is a variant of `\ifcase` where the number is one of the seven possible styles: display, text, cramped text, script, cramped script, script script, cramped script script.

```
\ifmathstyle
  display
\or
  text
\or
  cramped text
```

\else

normally smaller than text

\fi

172 \ifmmode

This traditional conditional checks we are in (inline or display) math mode mode.

173 \ifnum

This is a frequently used conditional: it compares two numbers where a number is anything that can be seen as such.

`\scratchcounter=65 \chardef\A=65`

`\ifnum65=`A` YES `\else` NOP`\fi`

`\ifnum\scratchcounter=65` YES `\else` NOP`\fi`

`\ifnum\scratchcounter=\A` YES `\else` NOP`\fi`

Unless a number is an unexpandable token it ends with a space or `\relax`, so when you end up in the true branch, you'd better check if T_EX could determine where the number ends.

YES YES YES

On top of these ascii combinations, the engine also accepts some Unicode characters. This brings the full repertoire to:

character		operation
0x003C	<	less
0x003D	=	equal
0x003E	>	more
0x2208	∈	element of
0x2209	∉	not element of
0x2260	≠	!= not equal
0x2264	≤	!> less equal
0x2265	≥	!< greater equal
0x2270	⩵	not less equal
0x2271	⩵	not greater equal

This also applied to `\ifdim` although in the case of element we discard the fractional part (read: divide the numeric representation by 65536).

174 \ifnumexpression

Here is an example of a conditional using expressions:

This matches when the result is non zero, and you can mix calculations and tests as with normal expressions.

175 \ifnumval

This conditional is a variant on \ifchknm. This time we get some more detail about the value:

```
[-12 : \ifnumval -12\or negative\or zero\or positive\else error\fi]\quad
[0 : \ifnumval 0\or negative\or zero\or positive\else error\fi]\quad
[12 : \ifnumval 12\or negative\or zero\or positive\else error\fi]\quad
[oeps : \ifnumval oeps\or negative\or zero\or positive\else error\fi]
```

This gives:

```
[-12 : negative] [0 : zero] [12 : positive] [oeps : error]
```

176 \ifodd

One reason for this condition to be around is that in a double sided layout we need test for being on an odd or even page. It scans for a number the same was as other primitives,

```
\ifodd65 YES \else NO\fi &
\ifodd`B YES \else NO\fi .
```

So: YES & NO.

177 \ifparameter

In a macro body #1 is a reference to a parameter. You can check if one is set using a dedicated parameter condition:

```
\tolerant\def\foo[#1]#*[#2]%
  {\ifparameter#1\or one\else no one\fi\enspace
  \ifparameter#2\or two\else no two\fi\emspace}
```

```
\foo
\foo[1]
\foo[1][2]
```

We get:

```
no one no two  one no two  one two
```

178 \ifrelax

This is a convenient shortcut for \ifx\relax and the motivation for adding this one is (as with some others) to get less tracing.

179 \iftok

When you want to compare two arguments, the usual way to do this is the following:

```
\edef\tempA{#1}
\edef\tempb{#2}
```

```

\ifx\tempA\tempB
  the same
\else
  different
\fi

```

This works quite well but the fact that we need to define two macros can be considered a bit of a nuisance. It also makes macros that use this method to be not so called ‘fully expandable’. The next one avoids both issues:

```

\iftok{#1}{#2}
  the same
\else
  different
\fi

```

Instead of direct list you can also pass registers, so given:

```

\scratchtoks{a}%
\toks0{a}%

```

This:

```

\iftok 0 \scratchtoks      Y\else N\fi\space
\iftok{a}\scratchtoks     Y\else N\fi\space
\iftok\scratchtoks\scratchtoks Y\else N\fi

```

gives: Y Y Y.

180 \iftrue

Here we have a traditional T_EX conditional that is always true (therefore the same is true for any macro that is \let to this primitive).

181 \ifvbox

This traditional conditional checks if a given box register or internal box variable represents a vertical box,

182 \ifvmode

This traditional conditional checks we are in (internal) vertical mode.

183 \ifvoid

This traditional conditional checks if a given box register or internal box variable has any content.

184 \ifx

We use this traditional T_EX conditional a lot in ConT_EXt. Contrary to \if the two tokens that are compared are not expanded. This makes it possible to compare the meaning of two macros. Depending

on the need, these macros can have their content expanded or not. A different number of parameters results in false.

Control sequences are identical when they have the same command code and character code. Because a `\let` macro is just a reference, both let macros are the same and equal to `\relax`:

```
\let\one\relax \let\two\relax
```

The same is true for other definitions that result in the same (primitive) or meaning encoded in the character field (think of `\chardefs` and so).

185 `\ifzerodim`

This tests for a dimen (dimension) being zero so we have:

```
\ifdim<dimension>=0pt
\ifzerodim<dimension>
\ifcase<dimension register>
```

186 `\ifzerofloat`

As the name indicated, this tests for a zero float value.

```
[\scratchfloat\zerofloat \ifzerofloat\scratchfloat \else not \fi zero]
[\scratchfloat\plusone \ifzerofloat\scratchfloat \else not \fi zero]
[\scratchfloat 0.01 \ifzerofloat\scratchfloat \else not \fi zero]
[\scratchfloat 0.0e0 \ifzerofloat\scratchfloat \else not \fi zero]
[\scratchfloat \zeropoint\ifzerofloat\scratchfloat \else not \fi zero]
```

So: [zero] [not zero] [not zero] [zero] [zero]

187 `\ifzeronum`

This tests for a number (integer) being zero so we have these variants now:

```
\ifnum<integer or equivalent>=0
\ifzeronum<integer or equivalent>
\ifcase<integer or equivalent>
```

188 `\ignorearguments`

This primitive will quit argument scanning and start expansion of the body of a macro. The number of grabbed arguments can be tested as follows:

```
\def\MyMacro[#1][#2][#3]%
{\ifarguments zero\or one\or two\or three \else hm\fi}

\MyMacro \ignorearguments \quad
\MyMacro [1]\ignorearguments \quad
\MyMacro [1][2]\ignorearguments \quad
\MyMacro [1][2][3]\ignorearguments \par
```

zero one two three

Todo: explain optional delimiters.

189 \ignorenestedupto

This primitive gobbles following tokens and can deal with nested ‘environments’, for example:

```
\def\startfoo{\ignorenestedupto\startfoo\stopfoo}
```

```
(before
\startfoo
  test \startfoo test \stopfoo
  {test \startfoo test \stopfoo}
\stopfoo
after)
```

delivers:

(before after)

190 \ignorepars

This is a variant of \ignorespaces: following spaces *and* \par equivalent tokens are ignored, so for instance:

```
one + \ignorepars
```

```
two = \ignorepars \par
```

```
three
```

renders as: one + two = three. Traditionally T_EX has been sensitive to \par tokens in some of its building blocks. This has to do with the fact that it could indicate a runaway argument which in the times of slower machines and terminals was best to catch early. In LuaMetaT_EX we no longer have long macros and the mechanisms that are sensitive can be told to accept \par tokens (and ConT_EXt set them such that this is the case).

191 \ignorerest

An example shows what this primitive does:

```
\tolerant\def\foo[#1]#*[#2]%
{1234
  \ifparameter#1\or\else
    \expandafter\ignorerest
  \fi
  /#1/
  \ifparameter#2\or\else
    \expandafter\ignorerest
  \fi
  /#2/ }
```

```
\foo test \foo[456] test \foo[456][789] test
```

As this likely makes most sense in conditionals you need to make sure the current state is properly finished. Because `\expandafter` bumps the input state, here we actually quit two levels; this is because so called ‘backed up text’ is intercepted by this primitive.

```
1234 test 1234 /456/ test 1234 /456/ /789/ test
```

192 `\ignorespaces`

This traditional \TeX primitive signals the scanner to ignore the following spaces, if any. We mention it because we show a companion in the next section.

193 `\ignoreupto`

This ignores everything upto the given token, so

```
\ignoreupto \foo not this but\foo only this
```

will give: only this.

194 `\immediate`

This one has no effect unless you intercept it at the Lua end and act upon it. In original \TeX `immediate` is used in combination with `read from` and `write to file` operations. So, this is an old primitive with a new meaning.

195 `\immutable`

This prefix flags what follows as being frozen and is usually applied to for instance `\integerdef`'d control sequences. In that respect it is like `\permanent` but it makes it possible to distinguish quantities from macros.

196 `\initcatcodetable`

This initializes the catcode table with the given index.

197 `\input`

There are several ways to use this primitive:

```
\input test
\input {test}
\input "test"
\input 'test'
```

When no suffix is given, \TeX will assume the suffix is `.tex`. The second one is normally used.

198 \inputlineno

This integer holds the current linenumber but it is not always reliable.

199 \instance

This prefix flags a macro as an instance which is mostly relevant when a macro package want to categorize macros.

200 \integerdef

You can alias to a count (integer) register with \countdef:

```
\countdef\MyCount134
```

Afterwards the next two are equivalent:

```
\MyCount = 99
```

```
\count1234 = 99
```

where \MyCount can be a bit more efficient because no index needs to be scanned. However, in terms of storage the value (here 99) is always in the register so \MyCount has to get there. This indirectness has the benefit that directly setting the value is reflected in the indirect accessor.

```
\integerdef\MyCount = 99
```

This primitive also defines a numeric equivalent but this time the number is stored with the equivalent. This means that:

```
\let\MyCopyOfCount = \MyCount
```

will store the *current* value of \MyCount in \MyCopyOfCount and changing either of them is not reflected in the other.

The usual \advance, \multiply and \divide can be used with these integers and they behave like any number. But compared to registers they are actually more a constant.

201 \interactionmode

This internal integer can be used to set or query the current interaction mode:

\batchmode	0	omits all stops and terminal output
\nonstopmode	1	omits all stops
\scrollmode	2	omits error stops
\errorstopmode	3	stops at every opportunity to interact

202 \jobname

This gives the current job name without suffix: `primitives`.

203 \lastarguments

```

\def\MyMacro    #1{\the\lastarguments (#1) }           \MyMacro{1}      \crlf
\def\MyMacro    #1#2{\the\lastarguments (#1) (#2)}     \MyMacro{1}{2}      \crlf
\def\MyMacro#1#2#3{\the\lastarguments (#1) (#2) (#3)} \MyMacro{1}{2}{3} \par

\def\MyMacro    #1{(#1)                \the\lastarguments} \MyMacro{1}      \crlf
\def\MyMacro    #1#2{(#1) (#2)         \the\lastarguments} \MyMacro{1}{2}    \crlf
\def\MyMacro#1#2#3{(#1) (#2) (#3) \the\lastarguments} \MyMacro{1}{2}{3} \par

```

The value of `\lastarguments` can only be trusted in the expansion until another macro is seen and expanded. For instance in these examples, as soon as a character (like the left parenthesis) is seen, horizontal mode is entered and `\everypar` is expanded which in turn can involve macros. You can see that in the second block (that is: unless we changed `\everypar` in the meantime).

```

1(1)
2(1) (2)
3(1) (2) (3)

```

```

(1) 0
(1) (2) 2
(1) (2) (3) 3

```

204 \lastloopiterator

In addition to `\currentloopiterator` we have a variant that stores the value in case an unexpanded loop is used:

```

\localcontrolledrepeat 8 { [\the\currentloopiterator\eq\the\lastloopiterator] }
\expandedrepeat        8 { [\the\currentloopiterator\eq\the\lastloopiterator] }
\unexpandedrepeat      8 { [\the\currentloopiterator\ne\the\lastloopiterator] }

[1=1] [2=2] [3=3] [4=4] [5=5] [6=6] [7=7] [8=8]
[1=1] [2=2] [3=3] [4=4] [5=5] [6=6] [7=7] [8=8]
[0≠1] [0≠2] [0≠3] [0≠4] [0≠5] [0≠6] [0≠7] [0≠8]

```

205 \lastnamedcs

The example code in the previous section has some redundancy, in the sense that there to be looked up control sequence name `mymacro` is assembled twice. This is no big deal in a traditional eight bit \TeX but in a Unicode engine multi-byte sequences demand some more processing (although it is unlikely that control sequences have many multi-byte utf8 characters).

```

\ifcsname mymacro\endcsname
  \csname mymacro\endcsname
\fi

```

Instead we can say:

```

\ifcsname mymacro\endcsname
  \lastnamedcs

```

`\fi`

Although there can be some performance benefits another advantage is that it uses less tokens and parsing. It might even look nicer.

206 `\letcharcode`

Assigning a meaning to an active character can sometimes be a bit cumbersome; think of using some documented uppercase magic that one tends to forget as it's used only a few times and then never looked at again. So we have this:

```
{\letcharcode 65 1 \catcode 65 13 A : \meaning A}\crlf
{\letcharcode 65 2 \catcode 65 13 A : \meaning A}\par
```

here we define A as an active charcter with meaning 1 in the first line and 2 in the second.

```
1 : the character U+0031 1
2 : the character U+0032 2
```

Normally one will assign a control sequence:

```
{\letcharcode 66 \bf \catcode 66 13 {B bold}: \meaning B}\crlf
{\letcharcode 73 \it \catcode 73 13 {I italic}: \meaning I}\par
```

Of course `\bf` and `\it` are ConT_EXt specific commands:

```
bold: protected macro:\ifmmode \expandafter \mathbf \else \expandafter \normalbf \fi
italic: protected macro:\ifmmode \expandafter \mathit \else \expandafter \normalit \fi
```

207 `\letcsname`

It is easy to see that we save two tokens when we use this primitive. As with the `..defcs..` variants it also saves a push back of the composed macro name.

```
\expandafter\let\csname MyMacro:1\endcsname\relax
\letcsname MyMacro:1\endcsname\relax
```

208 `\letfrozen`

You can explicitly freeze an unfrozen macro:

```
\def\MyMacro{...}
\letfrozen\MyMacro
```

A redefinition will now give:

! You can't redefine a frozen macro.

209 `\letprotected`

Say that you have these definitions:


```

\def \MyMacroA{alpha}
\protected \def \MyMacroB{beta}
\edef \MyMacroC{\MyMacroA\MyMacroB}
\letprotected \MyMacroA
\edef \MyMacroD{\MyMacroA\MyMacroB}
\meaning \MyMacroC\cr\l f
\meaning \MyMacroD\par

```

The typeset meaning in this example is:

```

macro:alpha\MyMacroB
macro:\MyMacroA \MyMacroB

```

210 \lettolastnamedcs

The `\lastnamedcs` primitive is somewhat special as it is a (possible) reference to a control sequence which is why we have a dedicated variant of `\let`.

```

\csname relax\endcsname\let \foo\lastnamedcs \meaning\foo
\csname relax\endcsname\expandafter\let\expandafter \oof\lastnamedcs \meaning\oof
\csname relax\endcsname\lettolastnamedcs \ofo \meaning\ofo

```

These give the following where the first one obviously is not doing what we want and the second one is kind of cumbersome.

```

\lastnamedcs
\relax
\relax

```

211 \lettonothing

This one let's a control sequence to nothing. Assuming that `\empty` is indeed empty, these two lines are equivalent.

```

\let \foo\empty
\lettonothing\oof

```

212 \localcontrol

This primitive takes a single token:

```

\edef\testa{\scratchcounter123 \the\scratchcounter}
\edef\testc{\testa \the\scratchcounter}
\edef\testd{\localcontrol\testa \the\scratchcounter}

```

The three meanings are:

```

123

\testa macro:\scratchcounter 123 123
\testc macro:\scratchcounter 123 123123
\testd macro:123

```

The `\localcontrol` makes that the following token gets expanded so we don't see the yet to be expanded assignment show up in the macro body.

213 `\localcontrolled`

The previously described local control feature comes with two extra helpers. The `\localcontrolled` primitive takes a token list and wraps this into a local control sidetrack. For example:

```
\edef\testa{\scratchcounter123 \the\scratchcounter}
\edef\testb{\localcontrolled{\scratchcounter123}\the\scratchcounter}
```

The two meanings are:

```
\testa macro:\scratchcounter 123 123
\testb macro:123
```

The assignment is applied immediately in the expanded definition.

214 `\localcontrolledendless`

As the name indicates this will loop forever. You need to explicitly quit the loop with `\quitloop` or `\quitloopnow`. The first quitter aborts the loop at the start of a next iteration, the second one tries to exit immediately, but is sensitive for interference with for instance nested conditionals.

215 `\localcontrolledloop`

As with more of the primitives discussed here, there is a manual in the 'lowlevel' subset that goes into more detail. So, here a simple example has to do:

```
\localcontrolledloop 1 100 1 {%
  \ifnum\currentloopiterator>6\relax
    \quitloop
  \else
    [\number\currentloopnesting:\number\currentloopiterator]
    \localcontrolledloop 1 8 1 {%
      (\number\currentloopnesting:\number\currentloopiterator)
    }\par
  \fi
}
```

Here we see the main loop primitive being used nested. The code shows how we can `\quitloop` and have access to the `\currentloopiterator` as well as the nesting depth `\currentloopnesting`.

```
[1:1] (2:1) (2:2) (2:3) (2:4) (2:5) (2:6) (2:7) (2:8)
[1:2] (2:1) (2:2) (2:3) (2:4) (2:5) (2:6) (2:7) (2:8)
[1:3] (2:1) (2:2) (2:3) (2:4) (2:5) (2:6) (2:7) (2:8)
[1:4] (2:1) (2:2) (2:3) (2:4) (2:5) (2:6) (2:7) (2:8)
[1:5] (2:1) (2:2) (2:3) (2:4) (2:5) (2:6) (2:7) (2:8)
[1:6] (2:1) (2:2) (2:3) (2:4) (2:5) (2:6) (2:7) (2:8)
```

Be aware of the fact that `\quitloop` will end the loop at the *next* iteration so any content after it will show up. Normally this one will be issued in a condition and we want to end that properly. Also keep in mind that because we use local control (a nested \TeX expansion loop) anything you feed back can be injected out of order.

The three numbers can be separated by an equal sign which is a trick to avoid look ahead issues that can result from multiple serialized numbers without spaces that indicate the end of sequence of digits.

216 `\localcontrolledrepeat`

This one takes one instead three arguments which looks a bit better in simple looping.

217 `\long`

This original prefix gave the macro being defined the property that it could not have `\par` (or the often equivalent empty lines) in its arguments. It was mostly a protection against a forgotten right curly brace, resulting in a so called run-away argument. That mattered on a paper terminal or slow system where such a situation should be caught early. In $\text{Lua}\TeX$ it was already optional, and in $\text{LuaMeta}\TeX$ we dropped this feature completely (so that we could introduce others).

218 `\lowercase`

This token processor converts character tokens to their lowercase counterparts as defined per `\lc-code`. In order to permit dirty tricks active characters are also processed. We don't really use this primitive in $\text{Con}\TeX$ t, but for consistency we let it respond to `\expand`:³

```
\edef          \foo          {\lowercase{tex TeX \TEX}} \meaningless\foo
\lowercase{\edef\foo          {tex TeX \TEX}} \meaningless\foo
\edef          \foo{\expand\lowercase{tex TeX \TEX}} \meaningless\foo
```

Watch how `\lowercase` is not expandable but can be forced to. Of course, as the logo macro is protected the \TeX logo remains mixed case.

```
\lowercase {tex TeX \TEX }
tex tex \TEX
tex tex \TEX
```

219 `\luaescapestring`

This command converts the given (token) list into something that is acceptable for Lua. It is inherited from $\text{Lua}\TeX$ and not used in $\text{Con}\TeX$ t.

```
\directlua { tex.print ("luaescapestring {\tt This is a "test".}) }
```

Results in: This is a "test". (Watch the grouping.)

220 `\luatexbanner`

This gives: This is $\text{LuaMeta}\TeX$, Version 2.10.11.

³ Instead of providing `\lowercased` and `\uppercased` primitives that would clash with macros anyway.

221 `\luatexrevision`

This is an integer. The current value is: 10.

222 `\luatexversion`

This is an integer. The current value is: 210.

223 `\mathgroupingmode`

Normally a `{ }` or `\bgroup-\egroup` pair in math create a math list. However, users are accustomed to using it also for grouping and then a list being created might not be what a user wants. As an alternative to the more verbose `\begingroup-\endgroup` or even less sensitive `\beginmathgroup-\endmathgroup` you can set the math grouping mode to a non zero value which makes curly braces (and the aliases) behave as expected.

224 `\meaning`

We start with a primitive that will be used in the following sections. The reported meaning can look a bit different than the one reported by other engines which is a side effect of additional properties and more extensive argument parsing.

```
\tolerant\permanent\protected\gdef\foo[#1]#*[#2]{(#1)(#2)} \meaning\foo
```

```
tolerant protected macro:[#1]#*[#2]->(#1)(#2)
```

225 `\meaningasis`

Although it is not really round trip with the original due to information being lost this primitive tries to return an equivalent definition.

```
\tolerant\permanent\protected\gdef\foo[#1]#*[#2]{(#1)(#2)} \meaningasis\foo
```

```
\permanent \tolerant \protected \def \foo [#1]#*[#2]{(#1)(#2)}
```

226 `\meaningful`

This one reports a bit less than `\meaningful`.

```
\tolerant\permanent\protected\gdef\foo[#1]#*[#2]{(#1)(#2)} \meaningful\foo
```

```
permanent tolerant protected macro
```

227 `\meaningfull`

This one reports a bit more than `\meaning`.

```
\tolerant\permanent\protected\gdef\foo[#1]#*[#2]{(#1)(#2)} \meaningfull\foo
```

```
permanent tolerant protected macro:[#1]#*[#2]->(#1)(#2)
```

228 \meaningles

This one reports a bit less than \meaningless.

```
\tolerant\permanent\protected\gdef\foo[#1]#*[#2]{(#1)(#2)} \meaningles\foo
[#1]#*[#2]
```

229 \meaningless

This one reports a bit less than \meaning.

```
\tolerant\permanent\protected\gdef\foo[#1]#*[#2]{(#1)(#2)} \meaningless\foo
[#1]#*[#2]->(#1)(#2)
```

230 \mugluespecdef

A variant of \gluespecdef that expects mu units is:

```
\mugluespecdef\MyGlue = 3mu plus 2mu minus 1mu
```

The properties are comparable to the ones described in the previous sections.

231 \multiply

The given quantity is multiplied by the given integer (that can be preceded by the keyword ‘by’, like:

```
\scratchdimen=10pt \multiply\scratchdimen by 3
```

232 \multiplyby

This is slightly more efficient variant of \multiply that doesn't look for by. See previous section.

233 \nonstopmode

This directive omits all stops.

234 \norelax

The rationale for this command can be shown by a few examples:

```
\dimen0 1pt \dimen2 1pt \dimen4 2pt
\edef\testa{\ifdim\dimen0=\dimen2\norelax N\else Y\fi}
\edef\testb{\ifdim\dimen0=\dimen2\relax N\else Y\fi}
\edef\testc{\ifdim\dimen0=\dimen4\norelax N\else Y\fi}
\edef\testd{\ifdim\dimen0=\dimen4\relax N\else Y\fi}
\edef\teste{\norelax}
```

The five meanings are:

```

\testa macro:N
\testb macro:\relax N
\testc macro:Y
\testd macro:Y
\teste macro:

```

So, the `\norelax` acts like `\relax` but is not pushed back as usual (in some cases).

235 `\nospaces`

When `\nospaces` is set to 1 no spaces are inserted, when its value is 2 a zero space is inserted. The default value is 0 which means that spaces become glue with properties depending on the font, specific parameters and/or space factors determined preceding characters.

236 `\number`

This \TeX primitive serializes the next token into a number, assuming that it is indeed a number, like

```

\number`A
\number65
\number\scratchcounter

```

For counters and such the `\the` primitive does the same, but when you're not sure if what follows is a verbose number or (for instance) a counter the `\number` primitive is a safer bet, because `\the 65` will not work.

237 `\numeralscale`

This primitive can best be explained by a few examples:

```

\the\numeralscale 1323
\the\numeralscale 1323.0
\the\numeralscale 1.323
\the\numeralscale 13.23

```

In several places \TeX uses a scale but due to the lack of floats it then uses 1000 as 1.0 replacement. This primitive can be used for ‘real’ scales:

```

1323000
1323000
1323
13230

```

238 `\numeralscaled`

This is a variant if `\numeralscale`:

```

\scratchcounter 1000
\the\numeralscaled 1323 \scratchcounter
\the\numeralscaled 1323.0 \scratchcounter

```

```
\the\numericscaled 1.323 \scratchcounter
\the\numericscaled 13.23 \scratchcounter
```

The second number gets multiplied by the first fraction:

```
1323000
1323000
1323
13230
```

239 \numexpr

This primitive was introduced by ε -TeX and supports a simple expression syntax:

```
\the\numexpr 10 * (1 + 2 - 5) / 2 \relax
```

gives: -10. You can mix in symbolic integers and dimensions.

240 \numexpression

The normal `\numexpr` primitive understands the `+`, `-`, `*` and `/` operators but in LuaMetaTeX we also can use `:` for a non rounded integer division (think of Lua's `//`). if you want more than that, you can use the new expression primitive where you can use the following operators.

add	<code>+</code>	
subtract	<code>-</code>	
multiply	<code>*</code>	
divide	<code>/</code> <code>:</code>	
mod	<code>%</code>	<code>mod</code>
band	<code>&</code>	<code>band</code>
bxor	<code>^</code>	<code>bxor</code>
bor	<code> </code> <code>v</code>	<code>bor</code>
and	<code>&&</code>	<code>and</code>
or	<code> </code>	<code>or</code>
setbit	<code><undecided></code>	<code>bset</code>
resetbit	<code><undecided></code>	<code>breset</code>
left	<code><<</code>	
right	<code>>></code>	
less	<code><</code>	
lessequal	<code><=</code>	
equal	<code>=</code> <code>==</code>	
moreequal	<code>>=</code>	
more	<code>></code>	
unequal	<code><></code> <code>!=</code> <code>~=</code>	
not	<code>!</code> <code>~</code>	<code>not</code>

An example of the verbose bitwise operators is:

```
\scratchcounter = \numexpression
"00000 bor "00001 bor "00020 bor "00400 bor "08000 bor "F0000
\relax
```

In the table you might have notices that some operators have equivalents. This makes the scanner a bit less sensitive for catcode regimes.

When `\tracingexpressions` is set to one or higher the intermediate ‘reverse polish notation’ stack that is used for the calculation is shown, for instance:

```
4:8: {numexpression rpn: 2 5 > 4 5 > and}
```

When you want the output on your console, you need to say:

```
\tracingexpressions 1
\tracingonline      1
```

241 `\or`

This traditional primitive is part of the condition testing mechanism and relates to an `\ifcase` test (or a similar test to be introduced in later sections). Depending on the value, \TeX will do a fast scanning till the right `\or` is seen, then it will continue expanding till it sees a `\or` or `\else` or `\orelse` (to be discussed later). It will then do a fast skipping pass till it sees an `\fi`.

242 `\orelse`

This primitive provides a convenient way to flatten your conditional tests. So instead of

```
\ifnum\scratchcounter<-10
  too small
\else\ifnum\scratchcounter>10
  too large
\else
  just right
\fi\fi
```

You can say this:

```
\ifnum\scratchcounter<-10
  too small
\orelse\ifnum\scratchcounter>10
  too large
\else
  just right
\fi
```

You can mix tests and even the case variants will work in most cases⁴

```
\ifcase\scratchcounter      zero
\or                        one
\or                        two
\orelse\ifnum\scratchcounter<10 less than ten
\else                      ten or more
```

⁴ I just play safe because there are corner cases that might not work yet.

`\fi`

Performance wise there are no real benefits although in principle there is a bit less housekeeping involved than with nested checks. However you might like this:

```
\ifnum\scratchcounter<-10
  \expandafter\toosmall
\orelse\ifnum\scratchcounter>10
  \expandafter\toolarge
\else
  \expandafter\justright
\fi
```

over:

```
\ifnum\scratchcounter<-10
  \expandafter\toosmall
\else\ifnum\scratchcounter>10
  \expandafter\expandafter\expandafter\toolarge
\else
  \expandafter\expandafter\expandafter\justright
\fi\fi
```

or the more ConT_EXt specific:

```
\ifnum\scratchcounter<-10
  \expandafter\toosmall
\else\ifnum\scratchcounter>10
  \doubleexpandafter\toolarge
\else
  \doubleexpandafter\justright
\fi\fi
```

But then, some T_EXies like complex and obscure code and throwing away working old code that took ages to perfect and get working and also showed that one masters T_EX might hurt.

243 \orunless

This is the negated variant of `\orelse` (prefixing that one with `\unless` doesn't work well).

244 \outer

An outer macro is one that can only be used at the outer level. This property is no longer supported. Like `\long`, the `\outer` prefix is now an no-op (and we don't expect this to have unfortunate side effects).

245 \parameterdef

Here is an example of binding a variable to a parameter. The alternative is of course to use an `\edef`.

```
\def\foo#1#2%
```

```

{\parameterdef\MyIndexOne\plusone % 1
 \parameterdef\MyIndexTwo\plustwo % 2
 \oof{P}\oof{Q}\oof{R}\norelax}

\def\oof#1%
 {<1:\MyIndexOne><1:\MyIndexOne>%
  #1%
  <2:\MyIndexTwo><2:\MyIndexTwo>}

\foo{A}{B}

```

The outcome is:

```
<1:A><1:A>P<2:B><2:B><1:A><1:A>Q<2:B><2:B><1:A><1:A>R<2:B><2:B>
```

246 \parameterindex

This gives the zero based position on the parameter stack. One reason for introducing \parameterdef is that the position remains abstract so there we don't need to use \parameterindex.

247 \parametermark

This is an equivalent for #.

248 \parametermode

Setting this internal integer to a positive value (best use 1 because future versions might use bit set) will enable the usage of # for escaped in the main text and body of macros.

249 \positdef

The engine uses 32 bit integers for various purposes and has no (real) concept of a floating point quantity. We get around this by providing a floating point data type based on 32 bit unums (posits). These have the advantage over native floats of more precision in the lower ranges but at the cost of a software implementation.

The \positdef primitive is the floating point variant of \integerdef and \dimensiondef: an efficient way to implement named quantities other than registers.

```

\positdef      \MyFloatA 5.678
\positdef      \MyFloatB 567.8
[\the\MyFloatA] [\todimension\MyFloatA] [\tointeger\MyFloatA]
[\the\MyFloatB] [\todimension\MyFloatB] [\tointeger\MyFloatB]

```

For practical reasons we can map posit (or float) onto an integer or dimension:

```
[5.6780000030994415283] [5.678pt] [6]
[567.8000030517578125] [567.80005pt] [568]
```

250 `\previousloopiterator`

```

\edef\testA{
  \expandedrepeat 2 {%
    \expandedrepeat 3 {%
      (\the\previousloopiterator1:\the\currentloopiterator)
    }%
  }%
}
\edef\testB{
  \expandedrepeat 2 {%
    \expandedrepeat 3 {%
      (#P:#I) % #G is two levels up
    }%
  }%
}

```

These give the same result:

```

\def \testA { (1:1) (1:2) (1:3) (2:1) (2:2) (2:3) }
\def \testB { (1:1) (1:2) (1:3) (2:1) (2:2) (2:3) }

```

The number indicates the number of levels we go up the loop chain.

251 `\protected`

A protected macro is one that doesn't get expanded unless it is time to do so. For instance, inside an `\edef` it just stays what it is. It often makes sense to pass macros as-is to (multi-pass) file (for tables of contents).

In ConT_EXt we use either `\protected` or `\unexpanded` because the later was the command we used to achieve the same results before ε -T_EX introduced this protection primitive. Originally the `\protected` macro was also defined but it has been dropped.

252 `\protecteddetokenize`

This is a variant of `\protecteddetokenize` that uses some escapes encoded as body parameters, like `#H` for a hash.

253 `\protectedexpandeddetokenize`

This is a variant of `\expandeddetokenize` that uses some escapes encoded as body parameters, like `#H` for a hash.

254 `\pxdimen`

The current numeric value of this dimension is 65781, 1.00374pt: one bp. We kept it around because it was introduced in pdfT_EX and made it into LuaT_EX, where it relates to the resolution of included images. In ConT_EXt it is not used.

255 \quitloop

There are several loop primitives and they can be quit with `\quitloop` at the next the *next* iteration. An immediate quit is possible with `\quitloopnow`. An example is given with `\localcontrolledloop`.

256 \quitloopnow

There are several loop primitives and they can be quit with `\quitloopnow` at the spot.

257 \rdivide

This is variant of `\divide` that rounds the result. For integers the result is the same as `\edivide`.

```
\the\dimexpr .4999pt : 2 \relax =.24994pt
\the\dimexpr .4999pt / 2 \relax =.24995pt
\scratchdimen.4999pt \divide \scratchdimen 2 \the\scratchdimen =.24994pt
\scratchdimen.4999pt \edivide\scratchdimen 2 \the\scratchdimen =.24995pt
\scratchdimen 4999pt \rdivide\scratchdimen 2 \the\scratchdimen =2500.0pt
\scratchdimen 5000pt \rdivide\scratchdimen 2 \the\scratchdimen =2500.0pt
```

```
\the\numexpr 1001 : 2 \relax =500
\the\numexpr 1001 / 2 \relax =501
\scratchcounter1001 \divide \scratchcounter 2 \the\scratchcounter=500
\scratchcounter1001 \edivide\scratchcounter 2 \the\scratchcounter=501
\scratchcounter1001 \rdivide\scratchcounter 2 \the\scratchcounter=501
```

```
0.24994pt=.24994pt
0.24995pt=.24995pt
0.24994pt=.24994pt
0.24995pt=.24995pt
2500.0pt=2500.0pt
2500.0pt=2500.0pt
```

```
500=500
501=501
500=500
501=501
501=501
```

258 \rdivideby

This is the by-less companion to `\rdivide`.

259 \relax

This primitive does nothing and is often used to end a verbose number or dimension in a comparison, for example:

```
\ifnum \scratchcounter = 123\relax
```

which prevents a lookahead. A variant would be:

```
\ifnum \scratchcounter = 123 %
```

assuming that spaces are not ignored. Another application is finishing an expression like `\numexpr` or `\dimexpr`. It is also used to prevent lookahead in cases like:

```
\vrule height 3pt depth 2pt width 5pt\relax
\hskip 5pt plus 3pt minus 2pt\relax
```

Because `\relax` is not expandable the following:

```
\edef\foo{\relax} \meaningfull\foo
\edef\oof{\norelax} \meaningfull\oof
```

gives this:

macro:\relax

macro:

A `\norelax` disappears here but in the previously mentioned scenarios it has the same function as `\relax`. It will not be pushed back either in cases where a lookahead demands that.

260 \retained

When a value is assigned inside a group \TeX pushes the current value on the save stack in order to be able to restore the original value after the group has ended. You can reach over a group by using the `\global` prefix. A mix between local and global assignments can be achieved with the `\retained` primitive.

```
\MyDim 15pt \bgroup \the\MyDim \space
\bgroup
  \bgroup
    \bgroup \advance\MyDim10pt \the\MyDim \egroup\space
    \bgroup \advance\MyDim10pt \the\MyDim \egroup\space
  \egroup
  \bgroup
    \bgroup \advance\MyDim10pt \the\MyDim \egroup\space
    \bgroup \advance\MyDim10pt \the\MyDim \egroup\space
  \egroup
\egroup
\egroup \the\MyDim

\MyDim 15pt \bgroup \the\MyDim \space
\bgroup
  \bgroup
    \bgroup \global\advance\MyDim10pt \the\MyDim \egroup\space
    \bgroup \global\advance\MyDim10pt \the\MyDim \egroup\space
  \egroup
  \bgroup
    \bgroup \global\advance\MyDim10pt \the\MyDim \egroup\space
    \bgroup \global\advance\MyDim10pt \the\MyDim \egroup\space
```

```

\egroup
\egroup
\egroup \the\MyDim

\MyDim 15pt \bgroup \the\MyDim \space
\constrained\MyDim\zeropoint
\group
  \bgroup \retained\advance\MyDim10pt \the\MyDim \egroup\space
  \bgroup \retained\advance\MyDim10pt \the\MyDim \egroup\space
\egroup
\group
  \bgroup \retained\advance\MyDim10pt \the\MyDim \egroup\space
  \bgroup \retained\advance\MyDim10pt \the\MyDim \egroup\space
\egroup
\egroup \the\MyDim

```

These lines result in:

```

15.0pt 25.0pt 25.0pt 25.0pt 25.0pt 15.0pt
15.0pt 25.0pt 35.0pt 45.0pt 55.0pt 55.0pt
15.0pt 10.0pt 20.0pt 30.0pt 40.0pt 15.0pt

```

Because LuaMetaTeX avoids redundant stack entries and reassignments this mechanism is a bit fragile but the `\constrained` prefix makes sure that we do have a stack entry. If it is needed depends on the usage pattern.

261 \retokenized

This is a companion of `\tokenized` that accepts a catcode table, so the whole repertoire is:

```

\tokenized                                {test $x$ test: current}
\tokenized catcodetable \ctxcatcodes {test $x$ test: context}
\tokenized catcodetable \vrbcategories {test $x$ test: verbatim}
\retokenized \ctxcatcodes {test $x$ test: context}
\retokenized \vrbcategories {test $x$ test: verbatim}

```

Here we pass the numbers known to ConTeXt and get:

```

test x test: current
test x test: context
test $x$ test: verbatim
test x test: context
test $x$ test: verbatim

```

262 \romannumeral

This converts a number into a sequence of characters representing a roman numeral. Because the Romans had no zero, a zero will give no output, a fact that is sometimes used for hacks and showing off ones macro coding capabilities. A large number will for sure result in a long string because after thousand we start duplicating.

263 `\savecatcodetable`

This primitive stores the currently set catcodes in the current table.

264 `\scantextokens`

This primitive scans the input as if it comes from a file. In the next examples the `\detokenize` primitive turns tokenized code into verbatim code that is similar to what is read from a file.

```
\edef\whatever{\detokenize{This is {\bf bold} and this is not.}}
\detokenize {This is {\bf bold} and this is not.}\crlf
\scantextokens{This is {\bf bold} and this is not.}\crlf
\scantextokens{\whatever}\crlf
\scantextokens\expandafter{\whatever}\par
```

This primitive does not have the end-of-file side effects of its precursor `\scantokens`.

This is `{\bf bold}` and this is not.

This is **bold** and this is not.

This is `{\bf bold}` and this is not.

This is **bold** and this is not.

265 `\scantokens`

Just forget about this ε -TeX primitive, just take the one in the next section.

266 `\scrollmode`

This directive omits error stops.

267 `\semiexpand`

This command expands the next macro when it is protected with `\semprotected`. See that primitive there for an example.

268 `\semiexpanded`

This command expands the tokens in the given list including the macros protected by with `\semprotected`. See that primitive there for an example.

269 `\semiprotected`

The working of this prefix can best be explained with an example. We define a few macros first:

```
\def\TestA{A}
\semiprotected\def\TestB{B}
\protected\def\TestC{C}

\edef\TestD{\TestA      \TestB      \TestC}
```

```

\edef\TestE{\TestA\semiexpand\TestB\semiexpand\TestC}
\edef\TestF{\TestA\expand \TestB\expand \TestC}

\edef\TestG{\normalexpanded {\TestA\TestB\TestC}}
\edef\TestH{\normalsemiexpanded{\TestA\TestB\TestC}}

```

The meaning of the macros that are made from the other three are:

Here we use the `\normal`... variants because (currently) we still have the macro with the `\expanded` in the ConT_EXt core.

```

A\TestB \TestC
AB\TestC
ABC
A\TestB \TestC
AB\TestC

```

270 \skip

This is the accessor for an indexed glue register.

271 \string

We mention this original primitive because of the one in the next section. It expands the next token or control sequence as if it was just entered, so normally a control sequence becomes a backslash followed by characters and a space.

272 \swapcsvalues

Because we mention some `def` and `let` primitives here, it makes sense to also mention a primitive that will swap two values (meanings). This one has to be used with care. Of course that what gets swapped has to be of the same type (or at least similar enough not to cause issues). Registers for instance store their values in the token, but as soon as we are dealing with token lists we also need to keep an eye on reference counting. So, to some extent this is an experimental feature.

273 \the

The `\the` primitive serializes the following token, when applicable: integers, dimensions, token registers, special quantities, etc. The catcodes of the result will be according to the current settings, so in `\the\dimen0`, the `pt` will have catcode ‘letter’ and the number and period will become ‘other’.

274 \thewithoutunit

The `\the` primitive, when applied to a dimension variable, adds a `pt` unit. because dimensions are the only traditional unit with a fractional part they are sometimes used as pseudo floats in which case `\thewithoutunit` can be used to avoid the unit. This is more convenient than stripping it off afterwards (via an expandable macro).

275 \todimension

The following code gives this: 1234.0pt and like its numeric counterparts accepts anything that resembles a number this one goes beyond (user, internal or pseudo) registers values too.

```
\scratchdimen = 1234pt \todimension\scratchdimen
```

276 \tohexadecimal

The following code gives this: 4D2 with uppercase letters.

```
\scratchcounter = 1234 \tohexadecimal\scratchcounter
```

277 \tointeger

The following code gives this: 1234 and is equivalent to \number.

```
\scratchcounter = 1234 \tointeger\scratchcounter
```

278 \tokenized

Just as \expanded has a counterpart \unexpanded, it makes sense to give \detokenize a companion:

```
\edef\foo{\detokenize{\inframed{foo}}}  
\edef\oof{\detokenize{\inframed{oof}}}
```

```
\meaning\foo \crlf \dontleavehmode\foo
```

```
\edef\foo{\tokenized{\foo\foo}}
```

```
\meaning\foo \crlf \dontleavehmode\foo
```

```
\dontleavehmode\tokenized{\foo\oof}
```

```
macro:\inframed {foo}
```

```
\inframed {foo}
```

```
macro:\inframed {foo}\inframed {foo}
```

foo	foo
-----	-----

foo	foo	oof
-----	-----	-----

This primitive is similar to:

```
\def\tokenized#1{\scantextokens\expandafter{\normalexpanded{#1}}}
```

and should be more efficient, not that it matters much as we don't use it that much (if at all).

279 \toksapp

One way to append something to a token list is the following:

```
\scratchtoks\expandafter{\the\scratchtoks more stuff}
```

This works all right, but it involves a copy of what is already in `\scratchtoks`. This is seldom a real issue unless we have large token lists and many appends. This is why LuaTeX introduced:

```
\toksapp\scratchtoks{more stuff}
\toksapp\scratchtoksone\scratchtokstwo
```

At some point, when working on LuaMetaTeX, I realized that primitives like this one and the next appenders and prependers to be discussed were always on the radar of Taco and me. Some were even implemented in what we called eetex: extended ε -TeX, and we even found back the prototypes, dating from pre-pdfTeX times.

280 \tokspre

Where appending something is easy because of the possible `\expandafter` trickery a prepend would involve more work, either using temporary token registers and/or using a mixture of the (no)expansion added by ε -TeX, but all are kind of inefficient and cumbersome.

```
\tokspre\scratchtoks{less stuff}
\tokspre\scratchtoksone\scratchtokstwo
```

This prepends the token list that is provided.

281 \tolerant

This prefix tags the following macro as being tolerant with respect to the expected arguments. It only makes sense when delimited arguments are used or when braces are mandate.

```
\tolerant\def\foo[#1]*[#2]{(#1)(#2)}
```

This definition makes `\foo` tolerant for various calls:

```
\foo \foo[1] \foo [1] \foo[1] [2] \foo [1] [2]
```

these give: `()(1)()(1)()(1)(2) (1)(2)`. The spaces after the first call disappear because the macro name parser gobbles it, while in the second case the `#*` gobbles them. Here is a variant:

```
\tolerant\def\foo[#1]#[#2]{!#1!#2!}
```

```
\foo[?] x
\foo[?] [?] x
```

```
\tolerant\def\foo[#1]*[#2]{!#1!#2!}
```

```
\foo[?] x
\foo[?] [?] x
```

We now get the following:

```
!?! x !?! x
```

```
!?!x !?! x
```

Here the `#`, remembers that spaces were gobbles and they will be put back when there is no further match. These are just a few examples of this tolerant feature. More details can be found in the lowlevel manuals.

282 `\toscaled`

The following code gives this: 1234.0 is similar to `\todimension` but omits the `pt` so that we don't need to revert to some nasty stripping code.

```
\scratchdimen = 1234pt \toscaled\scratchdimen
```

283 `\tosparsedimension`

The following code gives this: 1234pt where ‘sparse’ indicates that redundant trailing zeros are not shown.

```
\scratchdimen = 1234pt \tosparsedimension\scratchdimen
```

284 `\tosparsescaled`

The following code gives this: 1234 where ‘sparse’ means that redundant trailing zeros are omitted.

```
\scratchdimen = 1234pt \tosparsescaled\scratchdimen
```

285 `\unexpanded`

This is an ϵ -T_EX enhancement. The content will not be expanded in a context where expansion is happening, like in an `\edef`. In ConT_EXt you need to use `\normalunexpanded` because we already had a macro with that name.

```
\def \A{!} \meaning\A
\def \B{?} \meaning\B
\edef\C{\A\B} \meaning\C
\edef\C{\normalunexpanded{\A}\B} \meaning\C
```

```
macro:!
macro:?
macro:!?
macro:\A ?
```

286 `\unexpandedendless`

This one loops forever so you need to quit explicitly.

287 `\unexpandedloop`

As follow up on `\expandedloop` we now show its counterpart:

```
\edef\whatever
```

```
{\unexpandedloop 1 10 1
  {\scratchcounter=\the\currentloopiterator\relax}}
```

```
\meaningasis\whatever
```

```
\def \whatever {\scratchcounter =0\relax \scratchcounter =0\relax \scratchcounter =0\relax \scratchcounter
=0\relax \scratchcounter =0\relax \scratchcounter =0\relax \scratchcounter =0\relax \scratchcounter =0\relax
\scratchcounter =0\relax \scratchcounter =0\relax }
```

The difference between the (un)expanded loops and a local controlled one is shown here. Watch the out of order injection of A's.

```
\edef\TestA{\localcontrolledloop 1 5 1 {A}} % out of order
\edef\TestB{\expandedloop 1 5 1 {B}}
\edef\TestC{\unexpandedloop 1 5 1 {C\relax}}
```

AAAAA

We show the effective definition as well as the outcome of using them

```
\meaningasis\TestA
\meaningasis\TestB
\meaningasis\TestC
```

```
A: \TestA
B: \TestB
C: \TestC
```

```
\def \TestA {}
\def \TestB {BBBBB}
\def \TestC {C\relax C\relax C\relax C\relax C\relax }
```

```
A:
B: BBBBB
C: CCCCC
```

Watch how because it is empty `\TestA` has become a constant macro because that's what deep down empty boils down to.

288 \unexpandedrepeat

This one takes one instead of three arguments which looks better in simple loops.

289 \unless

This ε -T_EX prefix will negate the test (when applicable).

```
\ifx\one\two YES\else NO\fi
\unless\ifx\one\two NO\else YES\fi
```

This primitive is hardly used in ConT_EXt and we probably could get rid of these few cases.

290 \unletfrozen

A frozen macro cannot be redefined: you get an error. But as nothing in T_EX is set in stone, you can do this:

```
\frozen\def\MyMacro{...}
\unletfrozen\MyMacro
```

and `\MyMacro` is no longer protected from overloading. It is still undecided to what extent ConT_EXt will use this feature.

291 \unletprotected

The complementary operation of `\letprotected` can be used to unprotect a macro, so that it gets expandable.

```
\def \MyMacroA{alpha}
\protected \def \MyMacroB{beta}
\edef \MyMacroC{\MyMacroA\MyMacroB}
\unletprotected \MyMacroB
\edef \MyMacroD{\MyMacroA\MyMacroB}
\meaning \MyMacroC\crlf
\meaning \MyMacroD\par
```

Compare this with the example in the previous section:

```
macro:alpha\MyMacroB
macro:alphabeta
```

292 \untraced

Related to the meaning providers is the `\untraced` prefix. It marks a macro as to be reported by name only. It makes the macro look like a primitive.

```
\def\foo{}
\untraced\def\oof{}

\scratchtoks{\foo\foo\oof\oof}

\tracingall \the\scratchtoks \tracingnone
```

This will show up in the log as follows:

```
1:4: {\the}
1:5: \foo ->
1:5: \foo ->
1:5: \oof
1:5: \oof
```

This is again a trick to avoid too much clutter in a log. Often it doesn't matter to users what the meaning of a macro is (if they trace at all).⁵

⁵ An earlier variant could also hide the expansion completely but that was just confusing.

293 `\uppercase`

See its counterpart `\lowercase` for an explanation.

294 `\xdef`

This is an alternative for `\global\edef`:

```
\xdef\MyMacro{...}
```

295 `\xdefcsname`

This is the companion of `\xdef`:

```
\expandafter\xdef\csname MyMacro:1\endcsname{...}
      \xdefcsname MyMacro:1\endcsname{...}
```

296 `\xtoks`

This is the global variant of `\etoks`.

297 `\xtoksapp`

This is the global variant of `\etoksapp`.

298 `\xtokspre`

This is the global variant of `\etokspre`.

Obsolete

The LuaMetaTeX engine has more than its LuaTeX ancestor but it also has less. Because in the end the local control mechanism performed quite okay I decided to drop the `\immediateassignment` and `\immediateassigned` variants. They sort of used the same trick so there isn't much to gain and it was less generic (read: error prone).

Syntax

1 accent

t `\accent`
 $[xoffset\ dimension][yoffset\ dimension] integer character$

2 aftersomething

l `\afterassigned`
 $\{tokens\}$
t `\afterassignment`
 $token$
t `\aftergroup`
 $token$
l `\aftergrouped`
 $\{tokens\}$
l `\atendoffile`
 $token$
l `\atendoffiled`
 $[reverse]\{tokens\}$
l `\atendofgroup`
 $token$
l `\atendofgrouped`
 $\{tokens\}$

3 alignmenttab

l `\aligntab`

4 arithmetic

t `\advance`
 $quantity [by] quantity$
l `\advanceby`
 $quantity quantity$
t `\divide`
 $quantity [by] quantity$
l `\divideby`
 $quantity quantity$
l `\edivide`
 $quantity quantity$
l `\edivideby`
 $quantity quantity$
t `\multiply`
 $quantity [by] quantity$

l `\multiplyby`
 $quantity quantity$
l `\rdivide`
 $quantity quantity$
l `\rdivideby`
 $quantity quantity$

5 association

l `\associateunit`
 $\backslash cs [=] integer$
 $> \backslash cs : integer$

6 auxiliary

l `\insertmode`
 $integer$
 $: integer$
e `\interactionmode`
 $integer$
 $: integer$
t `\prevdepth`
 $dimension$
 $: dimension$
t `\prevgraf`
 $integer$
 $: integer$
t `\spacefactor`
 $integer$
 $: integer$

7 begingroup

t `\begingroup`
l `\beginmathgroup`
l `\beginsimplegroup`

8 beginlocal

l `\beginlocalcontrol`
l `\expandedendless`
 $\{tokens\}$
l `\expandedloop`
 $integer integer integer \{tokens\}$
l `\expandedrepeat`
 $integer \{tokens\}$

```

l \localcontrol
    tokens\endlocalcontrol
l \localcontrolled
    {tokens}
l \localcontrolledendless
    {tokens}
l \localcontrolledloop
    see \expandedloop
l \localcontrolledrepeat
    integer {tokens}
l \unexpandedendless
    {tokens}
l \unexpandedloop
    see \expandedloop
l \unexpandedrepeat
    integer {tokens}

```

9 beginparagraph

```

t \indent
t \noindent
l \parattribute
    integer [=] integer
l \quitvmode
l \snapshotpar
    cardinal
    : integer
l \undent
l \wrapuppar
    [reverse] {tokens}

```

10 boundary

```

l \boundary
    [=] integer
l \mathboundary
    [=] integer
l \noboundary
l \optionalboundary
    [=] integer
l \pageboundary
    [=] integer
l \protrusionboundary
    [=] integer
l \wordboundary

```

11 boxproperty

```

l \boxadapt
    ( index | box ) [=] integer
    > ( index | box ) : dimension
l \boxanchor
    see \boxadapt
l \boxanchors
    ( index | box ) [=] integer integer
    > ( index | box ) : integer
l \boxattribute
    ( index | box ) integer [=] integer
    > ( index | box ) integer : integer
l \boxdirection
    see \boxadapt
l \boxfreeze
    ( index | box )
    > ( index | box ) : integer
l \boxgeometry
    see \boxadapt
l \boxlimitate
    see \boxfreeze
l \boxorientation
    see \boxadapt
l \boxrepack
    see \boxfreeze
l \boxshift
    ( index | box ) [=] dimension
    > ( index | box ) : dimension
l \boxshrink
    see \boxfreeze
l \boxsource
    see \boxadapt
l \boxstretch
    see \boxfreeze
l \boxtarget
    see \boxadapt
l \boxtotal
    see \boxfreeze
l \boxvadjust
    ( index | box ) {tokens}
    > ( index | box ) : cardinal
l \boxxmove
    see \boxshift
l \boxxoffset
    see \boxshift
l \boxymove
    see \boxshift

```


l \boxyoffset
 see \boxshift
t \dp
 see \boxshift
t \ht
 see \boxshift
t \wd
 see \boxshift

12 caseshift

t \lowercase
 {tokens}
t \uppercase
 {tokens}

13 catcodetable

l \initcatcodetable
 integer
l \savecatcodetable
 integer

14 charnumber

t \char
 integer
l \glyph
 [xoffset dimension] [yoffset
 dimension] [scale integer] [xscale
 integer] [yscale integer] [left
 dimension] [right dimension] [raise
 dimension] [options integer] [font
 integer] [id integer] integer

15 combinetoks

l \etoks
 toks {tokens}
l \etoksapp
 toks {tokens}
l \etokspre
 toks {tokens}
l \gtoksapp
 toks {tokens}
l \gtokspre
 toks {tokens}

l \toksapp
 toks {tokens}
l \tokspre
 toks {tokens}
l \xtoks
 toks {tokens}
l \xtoksapp
 toks {tokens}
l \xtokspre
 toks {tokens}

16 convert

l \csactive
 > token : tokens
l \csstring
 > token : tokens
l \detokened
 > (\cs | {tokens} | toks) : tokens
l \detokenized
 > {tokens} : tokens
l \directlua
 > {tokens} : tokens
l \expanded
 > {tokens} : tokens
t \fontname
 > (font | integer) : tokens
l \fontspecifiedname
 > (font | integer) : tokens
l \formatname
 : tokens
t \jobname
 : tokens
l \luabytocode
 > integer : tokens
l \luaescapestring
 > {tokens} : tokens
l \luafunction
 > integer : tokens
l \luatexbanner
 : tokens
t \meaning
 > token : tokens
l \meaningasis
 > token : tokens
l \meaningful
 > token : tokens
l \meaningfull
 > token : tokens

```

l \meaningles
  > token : tokens
l \meaningless
  > token : tokens
t \number
  > integer : tokens
t \romannumeral
  > integer : tokens
l \semiexpanded
  > {tokens} : tokens
t \string
  > token : tokens
l \tocharacter
  > integer : tokens
l \todimension
  > dimension : tokens
l \tohexadecimal
  > integer : tokens
l \tointeger
  > integer : tokens
l \tomathstyle
  > mathstyle : tokens
l \toscaled
  > dimension : tokens
l \tosparsedimension
  > dimension : tokens
l \tosparsescaled
  > dimension : tokens

```

17 csname

```

l \begincsname
  tokens\endcsname
t \csname
  tokens\endcsname
l \futurecsname
  tokens\endcsname
l \lastnamedcs

```

18 def

```

l \cdef
  \cs [preamble] {tokens}
l \cdefcsname
  tokens\endcsname [preamble] {tokens}
t \def
  \cs [preamble] {tokens}
l \defcsname
  tokens\endcsname [preamble] {tokens}

```

```

t \edef
  \cs [preamble] {tokens}
l \edefcsname
  tokens\endcsname [preamble] {tokens}
t \gdef
  \cs [preamble] {tokens}
l \gdefcsname
  tokens\endcsname [preamble] {tokens}
t \xdef
  \cs [preamble] {tokens}
l \xdefcsname
  tokens\endcsname [preamble] {tokens}

```

19 definecharcode

```

l \Udelcode
  integer [=] integer
  > integer : integer
l \Umathcode
  integer [=] integer
  > integer : integer
l \amcode
  integer [=] integer
  > integer : integer
t \catcode
  integer [=] integer
  > integer : integer
t \delcode
  integer [=] integer
  > integer : integer
l \hccode
  integer [=] integer
  > integer : integer
l \hmcode
  integer [=] integer
  > integer : integer
t \lccode
  integer [=] integer
  > integer : integer
t \mathcode
  integer [=] integer
  > integer : integer
t \sfcode
  integer [=] integer
  > integer : integer
t \uccode
  integer [=] integer
  > integer : integer

```

20 definefamily

t `\scriptfont`
 family (*font* | *integer*)
 > *family*: *integer*

t `\scriptscriptfont`
 see `\scriptfont`

t `\textfont`
 see `\scriptfont`

21 definefont

t `\font`
 `\cs ({filename} | filename) [(at
 dimension | scaled integer)]`
 : *tokens*

22 delimiternumber

l `\Udelimiter`
 integer integer integer

t `\delimiter`
 integer

23 discretionary

t `\-`

l `\automaticdiscretionary`

t `\discretionary`
 [*penalty*] [*postword*] [*preword*]
 [*break*] [*nobreak*] [*options*] [*class*]
 {*tokens*} {*tokens*} {*tokens*}

l `\explicitdiscretionary`

24 endcsname

t `\endcsname`

25 endgroup

t `\endgroup`

l `\endmathgroup`

l `\endsimplegroup`

26 endjob

t `\dump`

t `\end`

27 endllocal

l `\endllocalcontrol`

28 endparagraph

t `\par`

29 endtemplate

l `\aligncontent`

t `\cr`

t `\crr`

t `\noalign`
 {*tokens*}

t `\omit`

t `\span`

30 equationnumber

t `\eqno`
 {*tokens*}

t `\legno`
 {*tokens*}

31 expandafter

l `\expand`
 token

l `\expandactive`
 token

t `\expandafter`
 token token

l `\expandafterpars`
 token

l `\expandafterspaces`
 token

l `\expandcstoken`
 token

l `\expandedafter`
 token {*tokens*}

l `\expandparameter`
 integer

l `\expandtoken`
 token

l \expandtoks
 { *tokens* }
l \futureexpand
 token token token
l \futureexpandis
 TODO
l \futureexpandisap
 TODO
l \semiexpand
 token
e \unless

32 explicit space

**t **
l \explicit space
 TODO

33 fontproperty

l \cfcode
 (*font* | *integer*) *integer* [=] *integer*
 > (*font* | *integer*) *integer* : *integer*
l \efcode
 see \cfcode
t \fontdimen
 (*font* | *integer*) *integer* [=] *dimension*
 > (*font* | *integer*) *integer* : *dimension*
t \hyphenchar
 (*font* | *integer*) [=] *integer*
 > (*font* | *integer*) : *integer*
l \lpcode
 see \fontdimen
l \rpcode
 see \fontdimen
l \scaledfontdimen
 see \hyphenchar
t \skewchar
 see \hyphenchar

34 getmark

t \botmark
e \botmarks
 integer
l \currentmarks
 integer

t \firstmark
e \firstmarks
 integer
t \splitbotmark
e \splitbotmarks
 integer
t \splitfirstmark
e \splitfirstmarks
 integer
t \topmark
e \topmarks
 integer

35 halign

t \halign
 [*attr integer integer*] [*callback integer*] [*discard*] [*noskips*]
 [*reverse*] [*to dimension*] [*spread dimension*] { *tokens* }

36 hmove

t \moveleft
 dimension box
t \moveright
 dimension box

37 hrule

t \hrule
 [*attr integer* [=] *integer*] [*width dimension*] [*height dimension*] [*depth dimension*] [*left dimension*] [*right dimension*] [*top dimension*] [*bottom dimension*] [*xoffset dimension*] [*yoffset dimension*] [*font integer*] [*fam integer*] [*char integer*]
l \nohrule
 see \hrule
l \virtualhrule
 [*attr integer* [=] *integer*] [*width dimension*] [*height dimension*] [*depth dimension*] [*left dimension*] [*right dimension*] [*top dimension*] [*bottom dimension*] [*xoffset dimension*] [*yoffset dimension*]

38 hskip

t \hfil
t \hfill
t \hfilneg
t \hskip
 $\text{dimension} \left[\begin{array}{l} \text{plus} \\ (\text{dimension} \mid \text{fi}[n^*l]) \end{array} \right] \left[\begin{array}{l} \text{minus} \\ (\text{dimension} \mid \text{fi}[n^*l]) \end{array} \right]$
t \hss

39 hyphenation

l \hjcode
 $\text{integer} [=] \text{integer}$
t \hyphenation
 $\{ \text{tokens} \}$
l \hyphenationmin
 $[=] \text{integer}$
t \patterns
 $\{ \text{tokens} \}$
l \postexhyphenchar
 $[=] \text{integer}$
l \posthyphenchar
 $[=] \text{integer}$
l \preexhyphenchar
 $[=] \text{integer}$
l \prehyphenchar
 $[=] \text{integer}$

40 iftest

t \else
t \fi
t \if
l \ifabsdim
 dimension
 $(! \mid < \mid = \mid > \mid \in \mid \notin \mid \neq \mid \leq \mid \geq \mid \neq \mid \neq)$
 dimension
l \ifabsfloat
 $\text{float} (! \mid < \mid = \mid > \mid \in \mid \notin \mid \neq \mid \leq \mid \geq \mid \neq \mid \neq)$
 float
l \ifabsnum
 integer
 $(! \mid < \mid = \mid > \mid \in \mid \notin \mid \neq \mid \leq \mid \geq \mid \neq \mid \neq)$
 integer
l \ifarguments
l \ifboolean
 integer

t \ifcase
 integer
t \ifcat
 token
l \ifchkdim
 $\text{tokens} \backslash \text{or}$
l \ifchkdimension
 $\text{tokens} \backslash \text{or}$
l \ifchknum
 $\text{tokens} \backslash \text{or}$
l \ifchknumber
 $\text{tokens} \backslash \text{or}$
l \ifcmpdim
 $\text{dimension} \text{ dimension}$
l \ifcmpnum
 $\text{integer} \text{ integer}$
l \ifcondition
 $\backslash \text{if} \dots$
e \ifcsname
 $\text{tokens} \backslash \text{endcsname}$
l \ifcstok
 $\text{tokens} \backslash \text{relax}$
e \ifdefined
 token
t \ifdim
 see $\backslash \text{ifabsdim}$
l \ifdimexpression
 $\text{tokens} \backslash \text{relax}$
l \ifdimval
 $\text{tokens} \backslash \text{or}$
l \ifempty
 $(\text{token} \mid \{ \text{tokens} \})$
t \iffalse
l \ifflags
 $\backslash \text{cs}$
l \ifffloat
 see $\backslash \text{ifabsfloat}$
e \iffontchar
 $\text{integer} \text{ integer}$
l \ifhaschar
 $\text{token} \{ \text{tokens} \}$
l \ifhastok
 $\text{token} \{ \text{tokens} \}$
l \ifhastoks
 $\text{tokens} \backslash \text{relax}$
l \ifhasxtoks
 $\text{tokens} \backslash \text{relax}$
t \ifhbox
 $(\text{index} \mid \text{box})$

t \ifhmode
l \iffinalalignment
l \ifincsname
 tokens\endcsname
t \ifinner
l \ifinsert
 integer
l \ifintervalldim
 dimension dimension dimension
l \ifintervalfloat
 integer integer integer
l \ifintervalnum
 float float float
l \iflastnamedcs
l \ifmathparameter
 integer
l \ifmathstyle
 mathstyle
t \ifmmode
t \ifnum
 see \ifabsnum
l \ifnumexpression
 tokens\relax
l \ifnumval
 tokens\or
t \ifodd
 integer
l \ifparameter
 parameter\or
l \ifparameters
l \ifrelax
 token
l \iftok
 tokens\relax
t \iftrue
t \ifvbox
 see \ifhbox
t \ifvmode
t \ifvoid
 see \ifhbox
t \ifx
 token
l \ifzerodim
 dimension
l \ifzerofloat
 float
l \ifzeronum
 integer
t \or

l \orelse
l \orunless

41 ignoresomething

l \ignorearguments
l \ignorenestedupto
 token
l \ignorepars
l \ignorereset
t \ignorespaces
l \ignoreupto
 token

42 input

t \endinput
t \eofinput
 { *tokens* } ({ filename } | filename)
t \input
 ({ filename } | filename)
l \quitloop
l \quitloopnow
l \retokenized
 [catcodetable] { *tokens* }
l \scantextokens
 { *tokens* }
e \scantokens
 { *tokens* }
l \tokenized
 { *tokens* }

43 insert

t \insert
 integer

44 interaction

t \batchmode
t \errorstopmode
t \nonstopmode
t \scrollmode

45 internaldimension

t \boxmaxdepth
 [=] *dimension*

```

: dimension
t \delimitershortfall
    [=] dimension
    : dimension
t \displayindent
    [=] dimension
    : dimension
t \displaywidth
    [=] dimension
    : dimension
t \emergencyextrastretch
    [=] dimension
    : dimension
t \emergencystretch
    [=] dimension
    : dimension
l \glyphxoffset
    [=] dimension
    : dimension
l \glyphyoffset
    [=] dimension
    : dimension
t \hangindent
    [=] dimension
    : dimension
t \hfuzz
    [=] dimension
    : dimension
t \hsize
    [=] dimension
    : dimension
l \ignoredepthcriterion
    [=] dimension
    : dimension
t \lineskiplimit
    [=] dimension
    : dimension
t \mathsurround
    [=] dimension
    : dimension
t \maxdepth
    [=] dimension
    : dimension
t \nulldelimiterspace
    [=] dimension
    : dimension
t \overfullrule
    [=] dimension
    : dimension

```

```

l \pageextragoal
    [=] dimension
    : dimension
t \parindent
    [=] dimension
    : dimension
t \predisplaysize
    [=] dimension
    : dimension
l \pxdimen
    [=] dimension
    : dimension
t \scriptspace
    [=] dimension
    : dimension
l \shortinlinemaththreshold
    [=] dimension
    : dimension
t \splitmaxdepth
    [=] dimension
    : dimension
l \tabsize
    [=] dimension
    : dimension
t \vfuzz
    [=] dimension
    : dimension
t \vsize
    [=] dimension
    : dimension

```

46 internalglue

```

t \abovedisplayshortskip
    [=] glue
    : glue
t \abovedisplayskip
    [=] glue
    : glue
l \additionalpageskip
    [=] glue
    : glue
t \baselineskip
    [=] glue
    : glue
t \belowdisplayshortskip
    [=] glue
    : glue

```

t \belowdisplayskip
 [=] *glue*
 : *glue*
l \emergencyleftskip
 [=] *glue*
 : *glue*
l \emergencyrightskip
 [=] *glue*
 : *glue*
l \initialpageskip
 [=] *glue*
 : *glue*
l \initialtopskip
 [=] *glue*
 : *glue*
t \leftskip
 [=] *glue*
 : *glue*
t \lineskip
 [=] *glue*
 : *glue*
l \mathsurroundskip
 [=] *glue*
 : *glue*
l \maththreshold
 [=] *glue*
 : *glue*
l \parfillleftskip
 [=] *glue*
 : *glue*
l \parfillrightskip
 [=] *glue*
 : *glue*
t \parfillskip
 [=] *glue*
 : *glue*
l \parinitleftskip
 [=] *glue*
 : *glue*
l \parinitrightskip
 [=] *glue*
 : *glue*
t \parskip
 [=] *glue*
 : *glue*
t \rightskip
 [=] *glue*
 : *glue*

t \spaceskip
 [=] *glue*
 : *glue*
t \splittopskip
 [=] *glue*
 : *glue*
t \tabskip
 [=] *glue*
 : *glue*
t \topskip
 [=] *glue*
 : *glue*
t \xspaceskip
 [=] *glue*
 : *glue*

47 internalinteger

t \adjdemerits
 [=] *integer*
 : *integer*
l \adjustspacing
 [=] *integer*
 : *integer*
l \adjustspacingshrink
 [=] *integer*
 : *integer*
l \adjustspacingstep
 [=] *integer*
 : *integer*
l \adjustspacingstretch
 [=] *integer*
 : *integer*
l \alignmentcellsource
 [=] *integer*
 : *integer*
l \alignmentwrapsource
 [=] *integer*
 : *integer*
l \automatichyphenpenalty
 [=] *integer*
 : *integer*
l \automigrationmode
 [=] *integer*
 : *integer*
l \autoparagraphmode
 [=] *integer*
 : *integer*

t \binoppenalty [=] integer : integer	l \exceptionpenalty [=] integer : integer
t \brokenpenalty [=] integer : integer	t \exhyphenchar [=] integer : integer
l \catcodetable [=] integer : integer	t \exhyphenpenalty [=] integer : integer
t \clubpenalty [=] integer : integer	l \explicithyphenpenalty [=] integer : integer
t \day [=] integer : integer	t \fam [=] integer : integer
t \defaultthyphenchar [=] integer : integer	t \finalhyphendemerits [=] integer : integer
t \defaultskewchar [=] integer : integer	l \firstvalidlanguage [=] integer : integer
t \delimiterfactor [=] integer : integer	t \floatingpenalty [=] integer : integer
l \discretionaryoptions [=] integer : integer	t \globaldefs [=] integer : integer
t \displaywidowpenalty [=] integer : integer	l \glyphdatafield [=] integer : integer
t \doubleadjdemerits [=] integer : integer	l \glyphoptions [=] integer : integer
t \doublehyphendemerits [=] integer : integer	l \glyphscale [=] integer : integer
t \endlinechar [=] integer : integer	l \glyphscriptfield [=] integer : integer
t \errorcontextlines [=] integer : integer	l \glyphscriptscale [=] integer : integer
t \escapechar [=] integer : integer	l \glyphscriptscriptscale [=] integer : integer
l \eufactor [=] integer : integer	l \glyphslant [=] integer : integer

l \glyphstatefield [=] <i>integer</i> : <i>integer</i>	l \linebreakoptional [=] <i>integer</i> : <i>integer</i>
l \glyphtextscale [=] <i>integer</i> : <i>integer</i>	l \linebreakpasses [=] <i>integer</i> : <i>integer</i>
l \glyphweight [=] <i>integer</i> : <i>integer</i>	l \linedirection [=] <i>integer</i> : <i>integer</i>
l \glyphxscale [=] <i>integer</i> : <i>integer</i>	t \linepenalty [=] <i>integer</i> : <i>integer</i>
l \glyphyscale [=] <i>integer</i> : <i>integer</i>	l \localbrokenpenalty [=] <i>integer</i> : <i>integer</i>
t \hangafter [=] <i>integer</i> : <i>integer</i>	l \localinterlinepenalty [=] <i>integer</i> : <i>integer</i>
t \hbadness [=] <i>integer</i> : <i>integer</i>	l \localpretolerance [=] <i>integer</i> : <i>integer</i>
t \holdinginserts [=] <i>integer</i> : <i>integer</i>	l \localtolerance [=] <i>integer</i> : <i>integer</i>
l \holdingmigrations [=] <i>integer</i> : <i>integer</i>	t \looseness [=] <i>integer</i> : <i>integer</i>
l \hyphenationmode [=] <i>integer</i> : <i>integer</i>	l \luacopyinputnodes [=] <i>integer</i> : <i>integer</i>
t \hyphenpenalty [=] <i>integer</i> : <i>integer</i>	l \mathbeginclass [=] <i>integer</i> : <i>integer</i>
t \interlinepenalty [=] <i>integer</i> : <i>integer</i>	l \mathcheckfencesmode [=] <i>integer</i> : <i>integer</i>
t \language [=] <i>integer</i> : <i>integer</i>	l \mathdictgroup [=] <i>integer</i> : <i>integer</i>
e \lastlinefit [=] <i>integer</i> : <i>integer</i>	l \mathdictproperties [=] <i>integer</i> : <i>integer</i>
t \lefthyphenmin [=] <i>integer</i> : <i>integer</i>	l \mathdirection [=] <i>integer</i> : <i>integer</i>
l \linebreakcriterion [=] <i>integer</i> : <i>integer</i>	l \mathdisplaymode [=] <i>integer</i> : <i>integer</i>

\mathdisplaypenaltyfactor [=] integer : integer	\mathrulesmode [=] integer : integer
\mathdisplayskipmode [=] integer : integer	\mathscriptsmode [=] integer : integer
\mathdoublescriptmode [=] integer : integer	\mathslackmode [=] integer : integer
\mathendclass [=] integer : integer	\mathspacingmode [=] integer : integer
\matheqnogapstep [=] integer : integer	\mathsurroundmode [=] integer : integer
\mathfontcontrol [=] integer : integer	\mathtolerance [=] integer : integer
\mathgluemode [=] integer : integer	t \maxdeadcycles [=] integer : integer
\mathgroupingmode [=] integer : integer	t \month [=] integer : integer
\mathinlinepenaltyfactor [=] integer : integer	t \newlinechar [=] integer : integer
\mathleftclass [=] integer : integer	\normalizelinemode [=] integer : integer
\mathlimitsmode [=] integer : integer	\normalizeparmode [=] integer : integer
\mathnolimitsmode [=] integer : integer	\nospaces [=] integer : integer
\mathpenaltiesmode [=] integer : integer	\orphanpenalty [=] integer : integer
\mathpretolerance [=] integer : integer	\outputbox [=] integer : integer
\mathrightclass [=] integer : integer	t \outputpenalty [=] integer : integer
\mathrulesfam [=] integer : integer	\overloadmode [=] integer : integer

l <code>\parametermode</code> <code>[=] integer</code> <code>: integer</code>	t <code>\righthyphenmin</code> <code>[=] integer</code> <code>: integer</code>
l <code>\pardirection</code> <code>[=] integer</code> <code>: integer</code>	e <code>\savingshyphcodes</code> <code>[=] integer</code> <code>: integer</code>
t <code>\pausing</code> <code>[=] integer</code> <code>: integer</code>	e <code>\savingsdiscards</code> <code>[=] integer</code> <code>: integer</code>
t <code>\postdisplaypenalty</code> <code>[=] integer</code> <code>: integer</code>	l <code>\setfontid</code> <code>[=] integer</code> <code>: integer</code>
l <code>\postinlinepenalty</code> <code>[=] integer</code> <code>: integer</code>	t <code>\setlanguage</code> <code>[=] integer</code> <code>: integer</code>
l <code>\postshortinlinepenalty</code> <code>[=] integer</code> <code>: integer</code>	l <code>\shapingpenaltiesmode</code> <code>[=] integer</code> <code>: integer</code>
l <code>\prebinoppenalty</code> <code>[=] integer</code> <code>: integer</code>	l <code>\shapingpenalty</code> <code>[=] integer</code> <code>: integer</code>
e <code>\predisplaydirection</code> <code>[=] integer</code> <code>: integer</code>	l <code>\shortinlineorphanpenalty</code> <code>[=] integer</code> <code>: integer</code>
l <code>\predisplaygapfactor</code> <code>[=] integer</code> <code>: integer</code>	t <code>\showboxbreadth</code> <code>[=] integer</code> <code>: integer</code>
t <code>\predisplaypenalty</code> <code>[=] integer</code> <code>: integer</code>	t <code>\showboxdepth</code> <code>[=] integer</code> <code>: integer</code>
l <code>\preinlinepenalty</code> <code>[=] integer</code> <code>: integer</code>	t <code>\shownodedetails</code> <code>[=] integer</code> <code>: integer</code>
l <code>\prerelpenalty</code> <code>[=] integer</code> <code>: integer</code>	l <code>\singlelinepenalty</code> <code>[=] integer</code> <code>: integer</code>
l <code>\preshortinlinepenalty</code> <code>[=] integer</code> <code>: integer</code>	l <code>\spacefactormode</code> <code>[=] integer</code> <code>: integer</code>
t <code>\pretolerance</code> <code>[=] integer</code> <code>: integer</code>	l <code>\spacefactorshrinklimit</code> <code>[=] integer</code> <code>: integer</code>
l <code>\protrudechars</code> <code>[=] integer</code> <code>: integer</code>	l <code>\spacefactorstretchlimit</code> <code>[=] integer</code> <code>: integer</code>
t <code>\relpenalty</code> <code>[=] integer</code> <code>: integer</code>	l <code>\supmarkmode</code> <code>[=] integer</code> <code>: integer</code>

l <code>\textdirection</code>	t <code>\tracinglostchars</code>
<code>[=] integer</code>	<code>[=] integer</code>
<code>: integer</code>	<code>: integer</code>
t <code>\time</code>	t <code>\tracingmacros</code>
<code>[=] integer</code>	<code>[=] integer</code>
<code>: integer</code>	<code>: integer</code>
t <code>\tolerance</code>	l <code>\tracingmarks</code>
<code>[=] integer</code>	<code>[=] integer</code>
<code>: integer</code>	<code>: integer</code>
l <code>\tracingadjusts</code>	l <code>\tracingmath</code>
<code>[=] integer</code>	<code>[=] integer</code>
<code>: integer</code>	<code>: integer</code>
l <code>\tracingalignments</code>	e <code>\tracingnesting</code>
<code>[=] integer</code>	<code>[=] integer</code>
<code>: integer</code>	<code>: integer</code>
e <code>\tracingassigns</code>	l <code>\tracingnodes</code>
<code>[=] integer</code>	<code>[=] integer</code>
<code>: integer</code>	<code>: integer</code>
t <code>\tracingcommands</code>	t <code>\tracingonline</code>
<code>[=] integer</code>	<code>[=] integer</code>
<code>: integer</code>	<code>: integer</code>
l <code>\tracingexpressions</code>	t <code>\tracingoutput</code>
<code>[=] integer</code>	<code>[=] integer</code>
<code>: integer</code>	<code>: integer</code>
l <code>\tracingfonts</code>	t <code>\tracingpages</code>
<code>[=] integer</code>	<code>[=] integer</code>
<code>: integer</code>	<code>: integer</code>
l <code>\tracingfullboxes</code>	t <code>\tracingparagraphs</code>
<code>[=] integer</code>	<code>[=] integer</code>
<code>: integer</code>	<code>: integer</code>
e <code>\tracinggroups</code>	l <code>\tracingpasses</code>
<code>[=] integer</code>	<code>[=] integer</code>
<code>: integer</code>	<code>: integer</code>
l <code>\tracinghyphenation</code>	l <code>\tracingpenalties</code>
<code>[=] integer</code>	<code>[=] integer</code>
<code>: integer</code>	<code>: integer</code>
e <code>\tracingifs</code>	t <code>\tracingrestores</code>
<code>[=] integer</code>	<code>[=] integer</code>
<code>: integer</code>	<code>: integer</code>
l <code>\tracinginserts</code>	t <code>\tracingstats</code>
<code>[=] integer</code>	<code>[=] integer</code>
<code>: integer</code>	<code>: integer</code>
l <code>\tracinglevels</code>	t <code>\uchyph</code>
<code>[=] integer</code>	<code>[=] integer</code>
<code>: integer</code>	<code>: integer</code>
l <code>\tracinglists</code>	l <code>\variablefam</code>
<code>[=] integer</code>	<code>[=] integer</code>
<code>: integer</code>	<code>: integer</code>

t \vbadness
 [=] *integer*
 : *integer*

t \widowpenalty
 [=] *integer*
 : *integer*

t \year
 [=] *integer*
 : *integer*

48 internalmuglue

t \medmuskip
 [=] *muglue*
 : *muglue*

l \pettymuskip
 [=] *muglue*
 : *muglue*

t \thickmuskip
 [=] *muglue*
 : *muglue*

t \thinmuskip
 [=] *muglue*
 : *muglue*

l \tinymuskip
 [=] *muglue*
 : *muglue*

49 internaltoks

t \errhelp
 [=] *toks*
 : *toks*

l \everybeforepar
 [=] *toks*
 : *toks*

t \everycr
 [=] *toks*
 : *toks*

t \everydisplay
 [=] *toks*
 : *toks*

e \everyeof
 [=] *toks*
 : *toks*

t \everyhbox
 [=] *toks*
 : *toks*

t \everyjob
 [=] *toks*
 : *toks*

t \everymath
 [=] *toks*
 : *toks*

l \everymathatom
 [=] *toks*
 : *toks*

t \everypar
 [=] *toks*
 : *toks*

l \everytab
 [=] *toks*
 : *toks*

t \everyvbox
 [=] *toks*
 : *toks*

t \output
 [=] *toks*
 : *toks*

50 italiccorrection

**t **
l \explicititaliccorrection
 TODO

51 kern

t \hkern
 dimension

t \kern
 dimension

t \vkern
 dimension

52 leader

t \cleaders
 (*box* | *rule* | *glyph*) *glue*

l \gleaders
 see \cleaders

t \leaders
 see \cleaders

l \uleaders
 [*callback integer*] (*box* | *rule* | *glyph*)
 glue

t \xleaders
see \cleaders

53 legacy

t \shipout
{ *tokens* }

54 let

l \futuredef
 \cs \cs
t \futurelet
 \cs [=] \cs
l \glet
 \cs
l \gletcsname
 tokens\endcsname
l \glettonothing
 \cs
t \let
 \cs
l \letcharcode
 \cs
l \letcsname
 tokens\endcsname
l \letfrozen
 \cs
l \letprotected
 \cs
l \lettolastramedcs
 \cs
l \lettonothing
 \cs
l \swapcsvalues
 \cs \cs
l \unletfrozen
 \cs
l \unletprotected
 \cs

55 localbox

l \localleftbox
 box
l \localmiddlebox
 box
l \localrightbox
 box

56 luafunctioncall

l \luabytecodecall
 integer
l \luafunctioncall
 integer

57 makebox

t \box
 (*index* | *box*)
t \copy
 see \box
l \dbox
 [*target integer*] [*to dimension*]
 [*adapt*] [*attr integer integer*]
 [*anchor integer*] [*axis integer*]
 [*shift dimension*] [*spread dimension*]
 [*source integer*] [*direction integer*]
 [*delay*] [*orientation integer*]
 [*xoffset dimension*] [*xmove dimension*]
 [*yoffset dimension*] [*ymove dimension*] [*reverse*] [*retain*]
 [*container*] [*class integer*] { *tokens* }
l \dpack
 see \dbox
l \dsplit
 [*attr*] [*to*] [*upto*] { *tokens* }
t \hbox
 see \dbox
l \hpack
 see \dbox
l \insertbox
 integer
l \insertcopy
 integer
t \lastbox
l \localleftboxbox
l \localmiddleboxbox
l \localrightboxbox
l \tpack
 see \dbox
l \tsplit
 see \dsplit
t \vbox
 see \dbox
l \vpack
 see \dbox

t `\vsplit`
 see `\dsplit`
t `\vtop`
 see `\dbox`

58 mark

l `\clearmarks`
 integer
l `\flushmarks`
t `\mark`
 { *tokens* }
e `\marks`
 integer { *tokens* }

59 mathaccent

l `\Umathaccent`
 [*attr integer integer*] [*center*]
 [*class integer*] [*exact*] [*source*
 integer] [*stretch*] [*shrink*]
 [*fraction integer*] [*fixed*]
 [*keepbase*] [*nooverflow*] [*base*]
 (*both* [*fixed*] *character* [*fixed*]
 character | *bottom* [*fixed*]
 character | *top* [*fixed*]
 character | *overlay*
 character | *character*)
t `\mathaccent`
 { *tokens* }

60 mathcharnumber

l `\Umathchar`
 integer
t `\mathchar`
 integer
l `\mathclass`
 integer
l `\mathdictionary`
 integer mathchar

61 mathchoice

t `\mathchoice`
 { *tokens* } { *tokens* } { *tokens* } { *tokens* }
l `\mathdiscretionary`
 [*class integer*] { *tokens* } { *tokens* }

 { *tokens* }
l `\mathstack`
 { *tokens* }

62 mathcomponent

l `\mathatom`
 [*attr integer integer*] [*all integer*]
 [*leftclass integer*] [*limits*]
 [*rightclass integer*] [*class integer*]
 [*unpack*] [*unroll*] [*single*] [*source*
 integer] [*textfont*] [*mathfont*]
 [*options integer*] [*nolimits*]
 [*nooverflow*] [*void*] [*phantom*]
 [*integer*]
t `\mathbin`
 { *tokens* }
t `\mathclose`
 { *tokens* }
t `\mathinner`
 { *tokens* }
t `\mathop`
 { *tokens* }
t `\mathopen`
 { *tokens* }
t `\mathord`
 { *tokens* }
t `\mathpunct`
 { *tokens* }
t `\mathrel`
 { *tokens* }
t `\overline`
 { *tokens* }
t `\underline`
 { *tokens* }

63 mathfence

l `\Uleft`
 [*auto*] [*attr integer integer*] [*axis*]
 [*bottom dimension*] [*depth dimension*]
 [*factor integer*] [*height dimension*]
 [*noaxis*] [*nocheck*] [*nolimits*]
 [*nooverflow*] [*leftclass integer*]
 [*limits*] [*exact*] [*void*] [*phantom*]
 [*class integer*] [*rightclass integer*]
 [*scale*] [*source integer*] [*top*]
 delimiter

l `\Umiddle`
 see `\Uleft`
l `\Uoperator`
 see `\Uleft`
l `\Uright`
 see `\Uleft`
l `\Uvextensible`
 see `\Uleft`
t `\left`
 see `\Uleft`
t `\middle`
 see `\Uleft`
t `\right`
 see `\Uleft`

64 `mathfraction`

l `\Uabove`
 $dimension$ [attr integer integer]
 [class integer] [center] [exact]
 [proportional] [noaxis]
 [nooverflow] [style *mathstyle*]
 [source integer] [hfactor integer]
 [vfactor integer] [font] [thickness
 $dimension$]
l `\Uabovewithdelims`
 delimiter delimiter $dimension$ [attr
 integer integer] [class integer]
 [center] [exact] [proportional]
 [noaxis] [nooverflow] [style
 $mathstyle$] [source integer] [hfactor
 integer] [vfactor integer] [font]
 [thickness $dimension$]
l `\Uatop`
 see `\Uabove`
l `\Uatopwithdelims`
 see `\Uabovewithdelims`
l `\Uover`
 [attr integer integer] [class
 integer] [center] [exact]
 [proportional] [noaxis]
 [nooverflow] [style *mathstyle*]
 [source integer] [hfactor integer]
 [vfactor integer] [font] [thickness
 $dimension$]
l `\Uoverwithdelims`
 delimiter delimiter [attr integer
 integer] [class integer] [center]
 [exact] [proportional] [noaxis]

[nooverflow] [style *mathstyle*]
 [source integer] [hfactor integer]
 [vfactor integer] [font] [thickness
 $dimension$]
l `\Uskewed`
 delimiter [attr integer integer]
 [class integer] [center] [exact]
 [proportional] [noaxis]
 [nooverflow] [style *mathstyle*]
 [source integer] [hfactor integer]
 [vfactor integer] [font] [thickness
 $dimension$]
l `\Uskewedwithdelims`
 delimiter delimiter delimiter [attr
 integer integer] [class integer]
 [center] [exact] [proportional]
 [noaxis] [nooverflow] [style
 $mathstyle$] [source integer] [hfactor
 integer] [vfactor integer] [font]
 [thickness $dimension$]
l `\Ustretched`
 see `\Uskewed`
l `\Ustretchedwithdelims`
 see `\Uskewedwithdelims`
t `\above`
 $dimension$
t `\abovewithdelims`
 delimiter delimiter $dimension$
t `\atop`
 $dimension$
t `\atopwithdelims`
 delimiter delimiter $dimension$
t `\over`
t `\overwithdelims`
 delimiter delimiter

65 `mathmodifier`

l `\Umathadapttleft`
l `\Umathadapttright`
l `\Umathlimits`
l `\Umathnoaxis`
l `\Umathnolimits`
l `\Umathopenupdepth`
 $dimension$
l `\Umathopenupheight`
 $dimension$
l `\Umathphantom`

```

\Umathsource
  [nucleus] integer
\Umathuseaxis
\Umathvoid
\displaylimits
\limits
\nolimits

```

66 mathparameter

```

\Umathaccentbasedepth
  mathstyle [=] dimension
> mathstyle: dimension
\Umathaccentbaseheight
  mathstyle [=] dimension
> mathstyle: dimension
\Umathaccentbottomovershoot
  mathstyle [=] dimension
> mathstyle: dimension
\Umathaccentbottomshiftdown
  mathstyle [=] dimension
> mathstyle: dimension
\Umathaccentextendmargin
  mathstyle [=] dimension
> mathstyle: dimension
\Umathaccentssuperscriptdrop
  mathstyle [=] dimension
> mathstyle: dimension
\Umathaccentssuperscriptpercent
  mathstyle [=] integer
> mathstyle: integer
\Umathaccenttopovershoot
  mathstyle [=] dimension
> mathstyle: dimension
\Umathaccenttopshiftup
  mathstyle [=] dimension
> mathstyle: dimension
\Umathaccentvariant
  [=] mathstyle
: mathstyle
\Umathaxis
  mathstyle [=] dimension
> mathstyle: dimension
\Umathbottomaccentvariant
  [=] mathstyle
: mathstyle
\Umathconnectoroverlapmin
  mathstyle [=] dimension
> mathstyle: dimension

```

```

\Umathdegreevariant
  [=] mathstyle
: mathstyle
\Umathdelimiterextendmargin
  mathstyle [=] dimension
> mathstyle: dimension
\Umathdelimiterovertvariant
  [=] mathstyle
: mathstyle
\Umathdelimiterpercent
  mathstyle [=] integer
> mathstyle: integer
\Umathdelimitershortfall
  mathstyle [=] dimension
> mathstyle: dimension
\Umathdelimiterundervariant
  [=] mathstyle
: mathstyle
\Umathdenominatorvariant
  [=] mathstyle
: mathstyle
\Umathexheight
  mathstyle [=] dimension
> mathstyle: dimension
\Umathextrasubpresshift
  mathstyle [=] dimension
> mathstyle: dimension
\Umathextrasubprespace
  mathstyle [=] dimension
> mathstyle: dimension
\Umathextrasubshift
  mathstyle [=] dimension
> mathstyle: dimension
\Umathextrasubspace
  mathstyle [=] dimension
> mathstyle: dimension
\Umathextrasuppresshift
  mathstyle [=] dimension
> mathstyle: dimension
\Umathextrasupprespace
  mathstyle [=] dimension
> mathstyle: dimension
\Umathextrasupshift
  mathstyle [=] dimension
> mathstyle: dimension
\Umathextrasupspace
  mathstyle [=] dimension
> mathstyle: dimension

```

<pre> \Umathflattenedaccentbasedepth mathstyle [=] dimension > mathstyle: dimension \Umathflattenedaccentbaseheight mathstyle [=] dimension > mathstyle: dimension \Umathflattenedaccentbottomshiftdown mathstyle [=] dimension > mathstyle: dimension \Umathflattenedaccenttopshiftup mathstyle [=] dimension > mathstyle: dimension \Umathfractiondelsize mathstyle [=] dimension > mathstyle: dimension \Umathfractiondenomdown mathstyle [=] dimension > mathstyle: dimension \Umathfractiondenomvgap mathstyle [=] dimension > mathstyle: dimension \Umathfractionnumup mathstyle [=] dimension > mathstyle: dimension \Umathfractionnumvgap mathstyle [=] dimension > mathstyle: dimension \Umathfractionrule mathstyle [=] dimension > mathstyle: dimension \Umathfractionvariant [=] mathstyle : mathstyle \Umathhextensiblevariant [=] mathstyle : mathstyle \Umathlimitabovebgap mathstyle [=] dimension > mathstyle: dimension \Umathlimitabovekern mathstyle [=] dimension > mathstyle: dimension \Umathlimitabovevgap mathstyle [=] dimension > mathstyle: dimension \Umathlimitbelowbgap mathstyle [=] dimension > mathstyle: dimension </pre>	<pre> \Umathlimitbelowkern mathstyle [=] dimension > mathstyle: dimension \Umathlimitbelowvgap mathstyle [=] dimension > mathstyle: dimension \Umathnolimitsubfactor mathstyle [=] integer > mathstyle: integer \Umathnolimitsupfactor mathstyle [=] integer > mathstyle: integer \Umathnumeratorvariant [=] mathstyle : mathstyle \Umathoperatorsize mathstyle [=] dimension > mathstyle: dimension \Umathoverbarkern mathstyle [=] dimension > mathstyle: dimension \Umathoverbarrule mathstyle [=] dimension > mathstyle: dimension \Umathoverbarvgap mathstyle [=] dimension > mathstyle: dimension \Umathoverdelimiterbgap mathstyle [=] dimension > mathstyle: dimension \Umathoverdelimitervariant [=] mathstyle : mathstyle \Umathoverdelimitervgap mathstyle [=] dimension > mathstyle: dimension \Umathoverlayaccentvariant [=] mathstyle : mathstyle \Umathoverlinevariant [=] mathstyle : mathstyle \Umathpresubshiftdistance mathstyle [=] dimension > mathstyle: dimension \Umathpresupshiftdistance mathstyle [=] dimension > mathstyle: dimension </pre>
--	--

```

\Umathprimeraise
  mathstyle [=] dimension
  > mathstyle: dimension
\Umathprimeraisecomposed
  mathstyle [=] dimension
  > mathstyle: dimension
\Umathprimeshifteddrop
  mathstyle [=] dimension
  > mathstyle: dimension
\Umathprimeshiftup
  mathstyle [=] dimension
  > mathstyle: dimension
\Umathprimespaceafter
  mathstyle [=] dimension
  > mathstyle: dimension
\Umathprimevariant
  [=] mathstyle
  : mathstyle
\Umathprimewidth
  mathstyle [=] dimension
  > mathstyle: dimension
\Umathquad
  mathstyle [=] dimension
  > mathstyle: dimension
\Umathradicaldegreeafter
  mathstyle [=] dimension
  > mathstyle: dimension
\Umathradicaldegreebefore
  mathstyle [=] dimension
  > mathstyle: dimension
\Umathradicaldegreeraise
  mathstyle [=] dimension
  > mathstyle: dimension
\Umathradicalextensibleafter
  mathstyle [=] dimension
  > mathstyle: dimension
\Umathradicalextensiblebefore
  mathstyle [=] dimension
  > mathstyle: dimension
\Umathradicalkern
  mathstyle [=] dimension
  > mathstyle: dimension
\Umathradicalrule
  mathstyle [=] dimension
  > mathstyle: dimension
\Umathradicalvariant
  [=] mathstyle
  : mathstyle
\Umathradicalvgap
  mathstyle [=] dimension
  > mathstyle: dimension
\Umathruleddepth
  mathstyle [=] dimension
  > mathstyle: dimension
\Umathruleheight
  mathstyle [=] dimension
  > mathstyle: dimension
\Umathskeweddelimitertolerance
  mathstyle [=] dimension
  > mathstyle: dimension
\Umathskewedfractionhgap
  mathstyle [=] dimension
  > mathstyle: dimension
\Umathskewedfractionvgap
  mathstyle [=] dimension
  > mathstyle: dimension
\Umathspaceafterscript
  mathstyle [=] dimension
  > mathstyle: dimension
\Umathspacebeforescript
  mathstyle [=] dimension
  > mathstyle: dimension
\Umathstackdenomdown
  mathstyle [=] dimension
  > mathstyle: dimension
\Umathstacknumup
  mathstyle [=] dimension
  > mathstyle: dimension
\Umathstackvariant
  [=] mathstyle
  : mathstyle
\Umathstackvgap
  mathstyle [=] dimension
  > mathstyle: dimension
\Umathsubscriptvariant
  [=] mathstyle
  : mathstyle
\Umathsubshiftdistance
  mathstyle [=] dimension
  > mathstyle: dimension
\Umathsubshiftdown
  mathstyle [=] dimension
  > mathstyle: dimension
\Umathsubshiftdrop
  mathstyle [=] dimension
  > mathstyle: dimension

```

```

\Umathsubsupshiftdown
  mathstyle [=] dimension
  > mathstyle: dimension
\Umathsubsupvgap
  mathstyle [=] dimension
  > mathstyle: dimension
\Umathsubtopmax
  mathstyle [=] dimension
  > mathstyle: dimension
\Umathsupbottommin
  mathstyle [=] dimension
  > mathstyle: dimension
\Umathsuperscriptvariant
  mathstyle [=] dimension
  > mathstyle: dimension
\Umathsupshiftdistance
  mathstyle [=] dimension
  > mathstyle: dimension
\Umathsupshiftdrop
  mathstyle [=] dimension
  > mathstyle: dimension
\Umathsupshiftup
  mathstyle [=] dimension
  > mathstyle: dimension
\Umathsupsubbottommax
  mathstyle [=] dimension
  > mathstyle: dimension
\Umathtopaccentvariant
  [=] mathstyle
  : mathstyle
\Umathunderbarkern
  mathstyle [=] dimension
  > mathstyle: dimension
\Umathunderbarrule
  mathstyle [=] dimension
  > mathstyle: dimension
\Umathunderbarvgap
  mathstyle [=] dimension
  > mathstyle: dimension
\Umathunderdelimiterbgap
  mathstyle [=] dimension
  > mathstyle: dimension
\Umathunderdelimitervariant
  [=] mathstyle
  : mathstyle
\Umathunderdelimitervgap
  mathstyle [=] dimension
  > mathstyle: dimension

\Umathunderlinevariant
  [=] mathstyle
  : mathstyle
\Umathvextensiblevariant
  [=] mathstyle
  : mathstyle
\Umathxscale
  mathstyle [=] integer
  > mathstyle: integer
\Umathyscale
  mathstyle [=] integer
  > mathstyle: integer
\copymathatomrule
  integer integer
\copymathparent
  integer integer
\copymathspacing
  integer integer
\letmathatomrule
  integer integer integer integer integer
\letmathparent
  integer integer
\letmathspacing
  see \letmathatomrule
\resetmathspacing
\setdefaultmathcodes
\setmathatomrule
  integer integer mathstyle integer integer
\setmathdisplaypostpenalty
  integer [=] integer
\setmathdisplayprepenalty
  integer [=] integer
\setmathignore
  mathparameter integer
\setmathoptions
  integer [=] integer
\setmathpostpenalty
  integer [=] integer
\setmathprepenalty
  integer [=] integer
\setmathspacing
  integer integer mathstyle glue

67 mathradical

\Udelimited
  [attr integer integer] [bottom]

```

```

[ exact ] [ top ] [ style mathstyle ]
[ source integer ] [ stretch ] [ shrink ]
[ width dimension ] [ height dimension ]
[ depth dimension ] [ left ] [ middle ]
[ right ] [ nooverflow ] delimiter
delimiter [ delimiter ] [ delimiter ]
( mathatom | { tokens } )
l \Udelimiterover
[ attr integer integer ] [ bottom ]
[ exact ] [ top ] [ style mathstyle ]
[ source integer ] [ stretch ] [ shrink ]
[ width dimension ] [ height dimension ]
[ depth dimension ] [ left ] [ middle ]
[ right ] [ nooverflow ] delimiter
[ delimiter ] [ delimiter ]
( mathatom | { tokens } )
l \Udelimiterunder
see \Udelimiterover
l \Uhexensible
see \Udelimiterover
l \Uoverdelimiter
see \Udelimiterover
l \Uradical
see \Udelimiterover
l \Uroot
[ attr integer integer ] [ bottom ]
[ exact ] [ top ] [ style mathstyle ]
[ source integer ] [ stretch ] [ shrink ]
[ width dimension ] [ height dimension ]
[ depth dimension ] [ left ] [ middle ]
[ right ] [ nooverflow ] delimiter
[ delimiter ] [ delimiter ]
( mathatom | { tokens } )
( mathatom | { tokens } )
l \Urooted
[ attr integer integer ] [ bottom ]
[ exact ] [ top ] [ style mathstyle ]
[ source integer ] [ stretch ] [ shrink ]
[ width dimension ] [ height dimension ]
[ depth dimension ] [ left ] [ middle ]
[ right ] [ nooverflow ] delimiter
delimiter [ delimiter ] [ delimiter ]
( mathatom | { tokens } )
( mathatom | { tokens } )
l \Underdelimiter
see \Udelimiterover
t \radical
see \Uroot

```

68 mathscript

```

l \noatomruling
t \nonscript
l \nosubprescript
l \nosubscript
l \nosuperprescript
l \nosuperscript
l \primescript
( mathatom | { tokens } )
l \shiftedsubprescript
see \primescript
l \shiftedsubscript
see \primescript
l \shiftedsuperprescript
see \primescript
l \shiftedsuperscript
see \primescript
l \subprescript
see \primescript
l \subscript
see \primescript
l \superprescript
see \primescript
l \superscript
see \primescript

```

69 mathshiftcs

```

l \Ustartdisplaymath
l \Ustartmath
l \Ustartmathmode
l \Ustopdisplaymath
l \Ustopmath
l \Ustopmathmode

```

70 mathstyle

```

l \allcrampedstyles
l \alldisplaystyles
l \allmainstyles
l \allmathstyles
l \allscriptscriptstyles
l \allscriptstyles
l \allsplitstyles
l \alltextstyles
l \alluncrampedstyles
l \allunsplitstyles

```

```

l \crampeddisplaystyle
l \crampedscriptscriptstyle
l \crampedscriptstyle
l \crampedtextstyle
t \displaystyle
l \givenmathstyle
    mathstyle
l \scaledmathstyle
    integer
    > mathstyle : integer
t \scriptscriptstyle
t \scriptstyle
t \textstyle

```

71 message

```

t \errmessage
    { tokens }
t \message
    { tokens }

```

72 mkern

```

t \mkern
    dimension

```

73 mskip

```

l \mathatomskip
    muglue
t \mskip
    muglue

```

74 noexpand

```

t \noexpand
    token

```

75 pageproperty

```

t \deadcycles
    [=] integer
    : integer
l \insertdepth
    integer [=] dimension
    > integer : dimension
l \insertdistance
    integer [=] dimension

```

```

    > integer : dimension
l \insertheight
    integer [=] dimension
    > integer : dimension
l \insertheights
    [=] dimension
    : dimension
l \insertlimit
    integer [=] dimension
    > integer : dimension
l \insertmaxdepth
    integer [=] dimension
    > integer : dimension
l \insertmultiplier
    integer [=] integer
    > integer : integer
t \insertpenalties
    [=] integer
    : integer
l \insertpenalty
    integer [=] integer
    > integer : integer
l \insertstorage
    integer [=] integer
    > integer : integer
l \insertstoring
    [=] integer
    : integer
l \insertwidth
    integer [=] dimension
    > integer : dimension
l \pagedepth
    [=] dimension
    : dimension
l \pageexcess
    [=] dimension
    : dimension
t \pagefillllstretch
    [=] dimension
    : dimension
t \pagefillstretch
    [=] dimension
    : dimension
t \pagefilstretch
    [=] dimension
    : dimension
l \pagefistretch
    [=] dimension
    : dimension

```

t \pagegoal
 [=] *dimension*
 : *dimension*

l \pagelastdepth
 [=] *dimension*
 : *dimension*

l \pagelastfillllstretch
 [=] *dimension*
 : *dimension*

l \pagelastfillstretch
 [=] *dimension*
 : *dimension*

l \pagelastfilstretch
 [=] *dimension*
 : *dimension*

l \pagelastheight
 [=] *dimension*
 : *dimension*

l \pagelastshrink
 [=] *dimension*
 : *dimension*

l \pagelaststretch
 [=] *dimension*
 : *dimension*

t \pageshrink
 [=] *dimension*
 : *dimension*

t \pagestretch
 [=] *dimension*
 : *dimension*

t \pagetotal
 [=] *dimension*
 : *dimension*

l \pagevsize
 [=] *dimension*
 : *dimension*

76 parameter

l \alignmark
l \parametermark

77 penalty

l \hpenalty
 integer

t \penalty
 integer

l \vpenalty
 integer

78 prefix

l \aliased
l \constant
l \constrained
l \deferred
l \enforced
l \frozen
t \global
l \immediate
l \immutable
l \inherited
l \instance
t \long
l \mutable
l \noaligned
t \outer
l \overloaded
l \permanent
e \protected
l \retained
l \semiprotected
l \tolerant
l \untraced

79 register

l \attribute
 (*index* | *box*) [=] *integer*
 > (*index* | *box*) : *integer*

t \count
 see \attribute

t \dimen
 (*index* | *box*) [=] *dimension*
 > (*index* | *box*) : *dimension*

l \float
 (*index* | *box*) [=] *float*
 > (*index* | *box*) : *float*

t \muskip
 (*index* | *box*) [=] *muglue*
 > (*index* | *box*) : *muglue*

t \skip
 (*index* | *box*) [=] *glue*
 > (*index* | *box*) : *glue*

t `\toks`
 (*index* | *box*) [=] {*tokens*}
 > (*index* | *box*) : {*tokens*}

80 relax

l `\norelax`
t `\relax`

81 removeitem

t `\unboundary`
t `\unkern`
t `\unpenalty`
t `\unskip`

82 setbox

t `\setbox`
 (*index* | *box*) [=]

83 setfont

t `\nullfont`

84 shorthanddef

l `\Umathchardef`
 \cs *integer*
l `\Umathdictdef`
 \cs *integer integer*
l `\attributedef`
 \cs *integer*
t `\chardef`
 \cs *integer*
t `\countdef`
 \cs *integer*
t `\dimendef`
 \cs *integer*
l `\dimensiondef`
 \cs *integer*
l `\floatdef`
 \cs *integer*
l `\fontspecdef`
 \cs (*font* | *integer*)
l `\gluespecdef`
 \cs *integer*

l `\integerdef`
 \cs *integer*
l `\luadef`
 \cs *integer*
t `\mathchardef`
 \cs *integer*
l `\mugluespecdef`
 \cs *integer*
t `\muskipdef`
 \cs *integer*
l `\parameterdef`
 \cs *integer*
l `\positdef`
 \cs *integer*
t `\skipdef`
 \cs *integer*
t `\toksdef`
 \cs *integer*

85 someitem

t `\badness`
 [=] *integer*
 : *integer*
e `\currentgrouplevel`
 [=] *integer*
 : *integer*
e `\currentgrouptype`
 [=] *integer*
 : *integer*
e `\currentifbranch`
 [=] *integer*
 : *integer*
e `\currentiflevel`
 [=] *integer*
 : *integer*
e `\currentifttype`
 [=] *integer*
 : *integer*
l `\currentloopiterator`
 [=] *integer*
 : *integer*
l `\currentloopnesting`
 [=] *integer*
 : *integer*
e `\currentstacksize`
 [=] *integer*
 : *integer*

```

e \dimexpr
    tokens\relax [=] dimension
    > tokens\relax: dimension
l \dimexpression
    tokens\relax [=] dimension
    > tokens\relax: dimension
l \floatexpr
    tokens\relax [=] float
    > tokens\relax: float
l \fontcharba
    integer [=] dimension
    > integer: dimension
e \fontcharbp
    integer [=] dimension
    > integer: dimension
e \fontcharht
    integer [=] dimension
    > integer: dimension
e \fontcharic
    integer [=] dimension
    > integer: dimension
l \fontcharta
    integer [=] dimension
    > integer: dimension
e \fontcharwd
    integer [=] dimension
    > integer: dimension
l \fontid
    ( font | integer ) [=] integer
    > ( font | integer ) : integer
l \fontmathcontrol
    see \fontid
l \fontspecid
    see \fontid
l \fontspecifiedsize
    see \fontid
l \fontspecscale
    see \fontid
l \fontspecslant
    see \fontid
l \fontspecweight
    see \fontid
l \fontspecxscale
    see \fontid
l \fontspecyscale
    see \fontid
l \fonttextcontrol
    see \fontid

e \glueexpr
    tokens\relax [=] glue
    > tokens\relax: glue
e \glueshrink
    glue [=] dimension
    > glue: dimension
e \glueshrinkorder
    glue [=] dimension
    > glue: dimension
e \gluestretch
    glue [=] integer
    > glue: integer
e \gluestretchorder
    glue [=] integer
    > glue: integer
e \gluetomu
    glue [=] glue
    > glue: glue
l \glyphxscaled
    [=] integer
    : integer
l \glyphyscaled
    [=] integer
    : integer
l \indexofcharacter
    integer [=] integer
    > integer: integer
l \indexofregister
    integer [=] integer
    > integer: integer
t \inputlineno
    [=] integer
    : integer
l \insertprogress
    integer [=] dimension
    > integer: dimension
l \lastarguments
    [=] integer
    : integer
l \lastatomclass
    [=] integer
    : integer
l \lastboundary
    [=] integer
    : integer
l \lastchkdimension
    [=] dimension
    : dimension

```

```

l \lastchknumber
    [=] integer
    : integer
t \lastkern
    [=] dimension
    : dimension
l \lastleftclass
    [=] integer
    : integer
l \lastloopiterator
    [=] integer
    : integer
l \lastnodesubtype
    [=] integer
    : integer
e \lastnodetype
    [=] integer
    : integer
l \lastpageextra
    [=] dimension
    : dimension
l \lastparcontext
    [=] integer
    : integer
t \lastpenalty
    [=] integer
    : integer
l \lastrightclass
    [=] integer
    : integer
t \lastskip
    [=] glue
    : glue
l \leftmarginkern
    [=] dimension
    : dimension
l \luatexrevision
    [=] {tokens}
    : {tokens}
l \luatexversion
    [=] {tokens}
    : {tokens}
l \mathatombglue
    [=] glue
    : glue
l \mathcharclass
    integer [=] integer
    > integer : integer

l \mathcharfam
    integer [=] integer
    > integer : integer
l \mathcharslot
    integer [=] integer
    > integer : integer
l \mathmainstyle
    [=] integer
    : integer
l \mathscale
    [=] integer
    : integer
l \mathstackstyle
    [=] integer
    : integer
l \mathstyle
    [=] integer
    : integer
l \mathstylefontid
    [=] integer
    : integer
e \muexpr
    tokens\relax [=] muglue
    > tokens\relax : muglue
e \mutoglue
    muglue [=] glue
    > muglue : glue
l \nestedloopiterator
    [=] integer
    : integer
l \numericsscale
    (integer | float) [=] integer
    > (integer | float) : integer
l \numericsscaled
    see \numericsscale
e \numexpr
    tokens\relax [=] integer
    > tokens\relax : integer
l \numexpression
    tokens\relax [=] integer
    > tokens\relax : integer
l \overshoot
    [=] dimension
    : dimension
l \parametercount
    [=] integer
    : integer
l \parameterindex
    [=] integer

```

```

: integer
e \parshapedimen
  integer [=] dimension
  > integer: dimension
e \parshapeindent
  integer [=] dimension
  > integer: dimension
e \parshapelength
  [=] dimension
  : dimension
l \previousloopiterator
  [=] integer
  : integer
l \rightmarginkern
  [=] dimension
  : dimension
l \scaledemwidth
  (font | integer) [=] dimension
  > (font | integer): dimension
l \scaledexheight
  see \scaledemwidth
l \scaledextraspaces
  see \scaledemwidth
l \scaledfontcharba
  integer [=] dimension
  > integer: dimension
l \scaledfontcharbp
  integer [=] dimension
  > integer: dimension
l \scaledfontcharht
  integer [=] dimension
  > integer: dimension
l \scaledfontcharic
  integer [=] dimension
  > integer: dimension
l \scaledfontcharta
  integer [=] dimension
  > integer: dimension
l \scaledfontcharwd
  integer [=] dimension
  > integer: dimension
l \scaledinterwordshrink
  see \scaledemwidth
l \scaledinterwordspace
  see \scaledemwidth
l \scaledinterwordstretch
  see \scaledemwidth
l \scaledmathaxis
  mathstyle [=] dimension

```

```

  > mathstyle: dimension
l \scaledmathemwidth
  mathstyle [=] dimension
  > mathstyle: dimension
l \scaledmathexheight
  mathstyle [=] dimension
  > mathstyle: dimension
l \scaledslantperpoint
  see \scaledemwidth

```

86 specification

```

e \clubpenalties
  [options] integer n * (integer)
  : integer
e \displaywidowpenalties
  see \clubpenalties
e \interlinepenalties
  see \clubpenalties
l \mathbackwardpenalties
  see \clubpenalties
l \mathforwardpenalties
  see \clubpenalties
l \orphanpenalties
  see \clubpenalties
l \parpasses
  [options] n * ([adjdemerits integer]
  [adjustspacing integer]
  [adjustspacingstep integer]
  [adjustspacingshrink integer]
  [adjustspacingstretch integer]
  [badness integer] [classes integer]
  [callback integer]
  [doubleadjdemerits integer]
  [doublehyphenemerits integer]
  [emergencystretch dimension]
  [extrahyphenpenalty integer]
  [finalhyphenemerits integer]
  [identifier integer]
  [ifadjustspacing integer] [looseness
  integer] [linebreakcriterion
  integer] [linebreakoptional integer]
  [linepenalty integer] [next]
  [orphanpenalty integer] [quit]
  [skip] [threshold dimension]
  [tolerance integer])
  : integer
t \parshape
  [options] integer n * (dimension

```

dimension)
 : *integer*
e `\widowpenalties`
 see `\clubpenalties`

87 the

e `\detokenize`
 { *tokens* }
l `\expandeddetokenize`
 { *tokens* }
l `\protecteddetokenize`
 { *tokens* }
l `\protectedexpandeddetokenize`
 { *tokens* }
t `\the`
 dimension
l `\thewithoutunit`
 quantity
e `\unexpanded`
 { *tokens* }

88 unhbox

t `\unhbox`
 integer
t `\unhcopy`
 integer
l `\unhpack`
 integer

89 unvbox

l `\insertunbox`
 integer
l `\insertuncopy`
 integer
e `\pagediscards`
e `\splitdiscards`
t `\unvbox`
 integer
t `\unvcopy`
 integer
l `\unvpack`
 integer

90 vadjust

t `\vadjust`
 [*pre*] [*post*] [*baseline*] [*before*]
 [*index integer*] [*after*] [*attr*
 integer integer] [*depth*
 (*after* | *before* | *check* | *last*)]
 { *tokens* }

91 valign

t `\valign`
 [*attr integer integer*] [*callback*
 integer] [*discard*] [*noskips*]
 [*reverse*] [*to dimension*] [*spread*
 dimension] { *tokens* }

92 vcenter

t `\vcenter`
 [*target integer*] [*to dimension*]
 [*adapt*] [*attr integer integer*]
 [*anchor integer*] [*axis integer*]
 [*shift dimension*] [*spread dimension*]
 [*source integer*] [*direction integer*]
 [*delay*] [*orientation integer*]
 [*xoffset dimension*] [*xmove*
 dimension] [*yoffset dimension*]
 [*ymove dimension*] [*reverse*] [*retain*]
 [*container*] [*class integer*] { *tokens* }

93 vmove

t `\lower`
 dimension box
t `\raise`
 dimension box

94 vrule

l `\novrule`
 [*attr integer* [=] *integer*] [*width*
 dimension] [*height dimension*] [*depth*
 dimension] [*left dimension*] [*right*
 dimension] [*top dimension*] [*bottom*
 dimension] [*xoffset dimension*]
 [*yoffset dimension*] [*font integer*]

[*fam integer*] [*char integer*]

l \srule
 see \novrule

l \virtualvrule
 [*attr integer* [=] *integer*] [*width dimension*] [*height dimension*] [*depth dimension*] [*left dimension*] [*right dimension*] [*top dimension*] [*bottom dimension*] [*xoffset dimension*] [*yoffset dimension*]

t \vrule
 see \novrule

95 vskip

t \vfil

t \vfill

t \vfilneg

t \vskip
 dimension [*plus* (*dimension* | *fi*[*n*l*]))] [*minus* (*dimension* | *fi*[*n*l*]))]

t \vss

96 xray

t \show
 token

t \showbox
 (*index* | *box*)

e \showgroups

e \showifs

t \showlists

e \showstack

t \showthe
 quantity

e \showtokens
 { *tokens* }

Rationale

Some words about the why and how it came. One of the early adopters of ConT_EXt was Taco Hoekwater and we spent numerous trips to T_EX meetings all over the globe. He was also the only one I knew who had read the T_EX sources. Because ConT_EXt has always been on the edge of what is possible and at that time we both used it for rather advanced rendering, we also ran into the limitations. I'm not talking of T_EX features here. Naturally old school T_EX is not really geared for dealing with images of all kind, colors in all kind of color spaces, highly interactive documents, input methods like xml, etc. The nice thing is that it offers some escapes, like specials and writes and later execution of programs that opened up lots of possibilities, so in practice there were no real limitations to what one could do. But coming up with a consistent and extensible (multi lingual) user interface was non trivial, because it had an impact in memory usage and performance. A lot could be done given some programming, as ConT_EXt MkII proves, but it was not always pretty under the hood. The move to LuaT_EX and MkIV transferred some action to Lua, and because LuaT_EX effectively was a ConT_EXt related project, we could easily keep them in sync.

Our traveling together, meeting several times per year, and eventually email and intense LuaT_EX developments (lots of Skype sessions) for a couple of years, gave us enough opportunity to discuss all kind of nice features not present in the engine. The previous century we discussed lots of them, rejected some, stayed with others, and I admit that forgot about most of the arguments already. Some that we did was already explored in e_et_ex, some of those ended up in LuaT_EX, and eventually what we have in LuaMetaT_EX can be seen as the result of years of programming in T_EX, improving macros, getting more performance and efficiency out of existing ConT_EXt code and inspiration that we got out of the ConT_EXt community, a demanding lot, always willing to experiment with us.

Once I decided to work on LuaMetaT_EX and bind its source to the ConT_EXt distribution so that we can be sure that it won't get messed up and might interfere with the ConT_EXt expectations, some more primitives saw their way into it. It is very easy to come up with all kind of bells and whistles but it is equally easy to hurt performance of an engine and what might go unnoticed in simple tests can really affect a macro package that depends on stability. So, what I did was mostly looking at the ConT_EXt code and wondering how to make some of the low level macros look more natural, also because I know that there are users who look into these sources. We spend a lot of time making them look consistent and nice and the nicer the better. Getting a better performance was seldom an argument because much is already as fast as can be so there is not that much to gain, but less clutter in tracing was an argument for some new primitives. Also, the fact that we soon might need to fall back on our phones to use T_EX a smaller memory footprint and less byte shuffling also was a consideration. The LuaMetaT_EX memory footprint is somewhat smaller than the LuaT_EX footprint. By binding LuaMetaT_EX to ConT_EXt we can also guarantee that the combinations works as expected.

I'm aware of the fact that ConT_EXt is in a somewhat unique position. First of all it has always been kind of cutting edge so its users are willing to experiment. There are users who immediately update and run tests, so bugs can and will be fixed fast. Already for a long time the community has a convenient infrastructure for updating and the build farm for generating binaries (also for other engines) is running smoothly.

Then there is the ConT_EXt user interface that is quite consistent and permits extensions with staying backward compatible. Sometimes users run into old manuals or examples and then complain that ConT_EXt is not compatible but that then involves obsolete technology: we no longer need font and input encodings and font definitions are different for OpenType fonts. We always had an abstract backend model, but nowadays pdf is kind of dominant and drives a lot of expectations. So, some of the MkII commands are gone and MkIV has some more. Also, as MetaPost evolved that department

in ConT_EXt also evolved. Think of it like cars: soon all are electric so one cannot expect a hole to poor in some fluid but gets a (often incompatible) plug instead. And buttons became touch panels. There is no need to use much force to steer or brake. Navigation is different, as are many controls. And do we need to steer ourselves a decade from now?

So, just look at T_EX and ConT_EXt in the same way. A system from the nineties in the previous century differs from one three decades later. Demands differ, input differs, resources change, editing and processing moves on, and so on. Manuals, although still being written are seldom read from cover to cover because online searching replaced them. And who buys books about programming? So Lua-MetaT_EX, while still being T_EX also moves on, as do the way we do our low level coding. This makes sense because the original T_EX ecosystem was not made with a huge and complex macro package in mind, that just happened. An author was supposed to make a style for each document. An often used argument for using another macro package over ConT_EXt was that the later evolved and other macro packages would work the same forever and not change from the perspective of the user. In retrospect those arguments were somewhat strange because the world, computers, users etc. do change. Standards come and go, as do software politics and preferences. In many aspects the T_EX community is not different from other large software projects, operating system wars, library devotees, programming language addicts, paradigm shifts. But, don't worry, if you don't like LuaMetaT_EX and its new primitives, just forget about them. The other engines will be there forever and are a safe bet, although LuaT_EX already stirred up the pot I guess. But keep in mind that new features in the latest greatest ConT_EXt version will more and more rely on LuaMetaT_EX being used; after all that is where it's made for. And this manual might help understand its users why, where and how the low level code differs between MkII, MkIV and LMTX.

Can we expect more new primitives than the ones introduced here? Given the amount of time I spent on experimenting and considering what made sense and what not, the answer probably is “no”, or at least “not that much”. As in the past no user ever requested the kind of primitives that were added, I don't expect users to come up with requests in the future either. Of course, those more closely related to ConT_EXt development look at it from the other end. Because it's there where the low level action really is, demands might still evolve.

Basically there are two areas where the engine can evolve: the programming part and the rendering. In this manual we focus on the programming and writing the manual sort of influences how details get filled in. Rendering is more complex because there heuristics and usage plays a more dominant role. Good examples are the math, par and page builder. They were extended and features were added over time but improved rendering came later. Not all extensions are critical, some are there (and got added) in order to write more readable code but there is only so much one can do in that area. Occasionally a feature pops up that is a side effect of a challenge. No matter what gets added it might not affect complexity too much and definitely not impact performance significantly!

Hans Hagen
Hasselt NL

To be checked primitives

additionalpageskip	crampedscriptscriptstyle
adjustspacing	crampedscriptstyle
adjustspacingshrink	crampedtextstyle
adjustspacingstep	currentmarks
adjustspacingstretch	dbox
aligncontent	discretionaryoptions
alignmentcellsource	dpack
alignmentwrapsource	dsplit
allcrampedstyles	efcode
alldisplaystyles	emergencyleftskip
allmainstyles	emergencyrightskip
allscriptscriptstyles	everybeforepar
allscriptstyles	everytab
allsplitstyles	exceptionpenalty
alltextstyles	explicithyphenpenalty
alluncrampedstyles	firstvalidlanguage
allunsplitstyles	flushmarks
amcode	fontcharba
automaticdiscretionary	fontcharta
automatichyphenpenalty	fontid
automigrationmode	fontspecdef
autoparagraphmode	fontspecid
boundary	fontspecifiedname
boxadapt	fontspecifiedsize
boxanchor	fontspecscale
boxanchors	fontspecslant
boxattribute	fontspecweight
boxdirection	fontspecxscale
boxfreeze	fontspecyscale
boxgeometry	fonttextcontrol
boxlimitate	gleaders
boxorientation	glyphdatafield
boxrepack	glyphoptions
boxshift	glyphscale
boxshrink	glyphscriptfield
boxsource	glyphscriptscale
boxstretch	glyphscriptscriptscale
boxtarget	glyphslant
boxtotal	glyphstatefield
boxvadjust	glyphtextscale
boxxmove	glyphweight
boxxoffset	glyphxoffset
boxymove	glyphxscale
boxyoffset	glyphxscaled
cfcode	glyphyoffset
clearmarks	glyphyscale
crampeddisplaystyle	glyphyscaled

hccode	localleftbox
hjcode	localleftboxbox
hmcode	localmiddlebox
holdingmigrations	localmiddleboxbox
hpack	localpretolerance
hpenalty	localrightbox
hyphenationmin	localrightboxbox
hyphenationmode	localtolerance
ifinsert	lpcode
ifparameters	luabytecode
ignoreddepthcriterion	luabytecodecall
indexofcharacter	luacopyinputnodes
indexofregister	luadef
inherited	luafunction
initialpageskip	luafunctioncall
initialtopskip	mutable
insertbox	nestedloopiterator
insertcopy	noaligned
insertdepth	noatomruling
insertdistance	noboundary
insertheight	nohrule
insertheights	normalizelinemode
insertlimit	normalizeparmode
insertmaxdepth	nosubprescript
insertmode	nosubscript
insertmultiplier	nosuperprescript
insertpenalty	nosuperscript
insertprogress	novrule
insertstorage	optionalboundary
insertstoring	orphanpenalties
insertunbox	orphanpenalty
insertuncopy	outputbox
insertwidth	overloaded
lastatomclass	overloadmode
lastboundary	overshoot
lastchkdimension	pageboundary
lastchknumber	pagedepth
lastleftclass	pageexcess
lastnodesubtype	pageextragoal
lastpageextra	pagefistretch
lastparcontext	pagelastdepth
lastrightclass	pagelastfillllstretch
leftmarginkern	pagelastfillstretch
linebreakcriterion	pagelastfilstretch
linebreakoptional	pagelastheight
linebreakpasses	pagelastshrink
linedirection	pagelaststretch
localbrokenpenalty	pagevsize
localinterlinepenalty	parametercount

parattribute	shiftedsuperprescript
pardirection	shiftedsuperscript
parfillleftskip	shortinlineorphanpenalty
parfillrightskip	singlelinepenalty
parinitleftskip	snapshotpar
parinitrightskip	spacefactormode
parpasses	spacefactorshrinklimit
pettymuskip	spacefactorstretchlimit
postexhyphenchar	srule
posthyphenchar	subprescript
postinlinepenalty	subscript
postshortinlinepenalty	superprescript
prebinoppenalty	superscript
predisplaygapfactor	supmarkmode
preexhyphenchar	tabsize
prehyphenchar	texdirection
preinlinepenalty	tinymuskip
prerelpenalty	tocharacter
preshortinlinepenalty	tpack
primescript	tracingadjusts
protrudechars	tracingalignments
protrusionboundary	tracingfonts
quitvmode	tracingfullboxes
rightmarginkern	tracinghyphenation
rpcode	tracinginserts
scaledemwidth	tracinglevels
scaledexheight	tracinglists
scaledextraspaces	tracingmarks
scaledfontcharba	tracingnodes
scaledfontchardp	tracingpasses
scaledfontcharht	tracingpenalties
scaledfontcharic	tsplit
scaledfontcharta	uleaders
scaledfontcharwd	undent
scaledfontdimen	unhpack
scaledinterwordshrink	unvpack
scaledinterwordspace	variablefam
scaledinterwordstretch	virtualhrule
scaledslantperpoint	virtualvrule
setfontid	vpack
shapingpenaltiesmode	vpenalty
shapingpenalty	wordboundary
shiftedsubprescript	wrapuppar
shiftedsubscript	

Indexed primitives

edivide

-

/

advance

advanceby

afterassigned

afterassignment

aftergroup

aftergrouped

aliased

alignmark

aligntab

associateunit

atendoffile

atendoffiled

atendofgroup

atendofgrouped

attribute

attributedef

batchmode

begincsname

begingroup

beginlocalcontrol

beginmathgroup

beginsimplegroup

catcode

catcodetable

cdef

cdefcsname

char

chardef

constant

constrained

count

countdef

csactive

csname

csstring

currentgrouplevel

currentgrouptype

currentifbranch

currentiflevel

currentifttype

currentloopiterator

currentloopnesting

currentstacksize

def

defcsname

deferred

detokened

detokenize

detokenized

dimen

dimendef

dimensiondef

dimexpr

dimexpression

directlua

divide

divideby

edef

edefcsame

edefcsname

edivide

edivideby

else

end

endcsname

endgroup

endinput

endlinechar

endlocalcontrol

endmathgroup

endsimplegroup

enforced

eofinput

errmessage

errorstopmode

escapechar

etoks

etoksapp

etokspre

eufactor

everyeof

everyjob

everypar

expand

expandactive

expandafter

expandafterpars

expandafterspaces

expandcstoken

expanded

expandedafter	ifchkdimension
expandeddetokenize	ifchknum
expandedendless	ifchknumber
expandedloop	ifcmpdim
expandedrepeat	ifcmpnum
expandparameter	ifcondition
expandtoken	ifcsname
expandtoks	ifcstok
explicitdiscretionary	ifdefined
explicititaliccorrection	ifdim
explicitSPACE	ifdimexpression
fi	ifdimval
float	ifempty
floatdef	iffalse
floatexpr	ifflags
font	iffloat
formatname	iffontchar
frozen	ifhaschar
futurecsname	ifhastok
futuredef	ifhastoks
futureexpand	ifhasxtoks
futureexpandis	ifhbox
futureexpandisap	ifhmode
futurelet	iffinalignment
gdef	ifincsname
gdefcsname	ifinner
glet	ifintervaldim
gletcsname	ifintervalfloat
glettonothing	ifintervalnum
global	iflastnamedcs
globaldefs	ifmathparameter
glueexpr	ifmathstyle
glueshrink	ifmmode
glueshrinkorder	ifnum
gluespecdef	ifnumexpression
gluestretch	ifnumval
gluestretchorder	ifodd
glyph	ifparameter
gtoksapp	ifrelax
gtokspre	iftok
if	iftrue
ifabsdim	ifvbox
ifabsfloat	ifvmode
ifabsnum	ifvoid
ifarguments	ifx
ifboolean	ifzerodim
ifcase	ifzerofloat
ifcat	ifzeronum
ifchkdim	ignorearguments

ignorenestedupto	norelax
ignorepars	normalunexpanded
ignorereset	nospaces
ignorespaces	number
ignoreupto	numericsscale
immediate	numericsscaled
immediateassigned	numexpr
immediateassignment	numexpression
immutable	or
initcatcodetable	orelse
input	orunless
inputlineno	outer
instance	par
integerdef	parameterdef
interactionmode	parameterindex
jobname	parametermark
lastarguments	parametermode
lastloopiterator	permanent
lastnamedcs	positdef
lccode	previousloopiterator
let	protected
letcharcode	protecteddetokenize
letcsname	protectedexpandeddetokenize
letfrozen	pxdimen
letprotected	quitloop
lettolastnamedcs	quitloopnow
lettonothing	rdivide
localcontrol	rdivideby
localcontrolled	relax
localcontrolledendless	retained
localcontrolledloop	retokenized
localcontrolledrepeat	romannumeral
long	savecatcodetable
lowercase	scantexttokens
luaescapestring	scantokens
luatexbanner	scrollmode
luatexrevision	semiexpand
luatexversion	semiexpanded
mathgroupingmode	semiprotected
meaning	semprotected
meaningasis	skip
meaningful	special
meaningfull	string
meaningles	swapcsvalues
meaningless	the
mugluespecdef	thewithoutunit
multiply	todimension
multiplyby	tohexadecimal
nonstopmode	tointeger

tokenized	unless
toksapp	unletfrozen
tokspre	unletprotected
tolerant	untraced
toscaled	uppercase
tosparsedimension	write
tosparsescaled	xdef
tracingexpressions	xdefcsname
unexpanded	xtoks
unexpandedendless	xtoksapp
unexpandedloop	xtokspre
unexpandedrepeat	