

# ConTeXt

comenzile

# RO



# ConTeXt

## comenzile

ro / română  
28 iunie 2019



<code>\AfterPar {...}</code> *    BEFEHL
<code>\Alphabeticnumerals {...}</code> *    NUMMER
<code>\AMSTEX</code>
<code>\AmSTeX</code>
<code>\And</code>
<code>\abjadnaivenumerals {...}</code> *    NUMMER
<code>\abjadnodotnumerals {...}</code> *    NUMMER
<code>\abjadnumerals {...}</code> *    NUMMER
<code>\activatespacehandler {...}</code> *    on dezactivat da fixat
<code>\acute {...}</code> *    CHARACTER
<code>\adaptcollector [...<sup>1</sup>] [...<sup>2</sup>...,...]</code> 1    NAME <span style="float:right">OPT</span> 2    inherits: \setupcollector
<code>\adapteazaaspect [...<sup>1</sup>...] [...<sup>2</sup>...,...]</code> 1    NUMMER <span style="float:right">OPT</span> 2    inaltime = max DIMENSION linii        = NUMMER
<code>\adaptfontfeature [...<sup>1</sup>] [...<sup>2</sup>...,...]</code> 1    NAME 2    inherits: \definefontfeature
<code>\adaptpapersize [...<sup>1</sup>...] [...<sup>2</sup>...,...]</code> 1    inherits: \seteazadimensiunihartie <span style="float:right">OPT</span> 2    inherits: \seteazadimensiunihartie
<code>\addfeature [...]</code> *    NAME
<code>\addfeature {...}</code> *    NAME
<code>\addfontpath [...*,...]</code> *    PATH
<code>\addtocommalist {...<sup>1</sup>} \^<sup>2</sup>...</code> 1    TEXT 2    CSNAME

<p><code>\addtoJSreamble {...} {...}</code></p> <p>1 NAME</p> <p>2 CONTENT</p>
<p><code>\addvalue {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\adubuffer [...,*...]</code></p> <p>* BUFFER OPT</p>
<p><code>\getBUFFER</code></p>
<p><code>\adumarcaje [...]<sup>1</sup> [...]<sup>2</sup> [...]<sup>3</sup></code></p> <p>1 BESCHRIFTUNG OPT OPT</p> <p>2 pagina NAME</p> <p>3 primul ultim curent precedent urmatorul sus subsol implicit ambele tot first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck</p>
<p><code>\afiseazaaspect [...,*...]</code></p> <p>* pt bp cm mm dd cc pc <del>nd</del><sup>OPT</sup> nc sp in</p>
<p><code>\afiseazaculoare [...]</code></p> <p>* COLOR</p>
<p><code>\afiseazafonttext [...,*...]</code></p> <p>* inherits: \seteazafonttext</p>
<p><code>\afiseazagrid [...,*...]</code></p> <p>* reset subsol sus <del>ni</del><sup>OPT</sup>funul tot linii incadrat nonumber dreapta stanga extern intern coloane</p>
<p><code>\afiseazagrupculoare [...]<sup>1</sup> [...]<sup>2</sup>,...]</code></p> <p>1 NAME OPT</p> <p>2 orizontal vertical numar valoare nume</p>
<p><code>\afiseazamakeup [...]</code></p> <p>* marcaj reset boxes <del>tot</del><sup>OPT</sup> hbox vbox vtop kern glue penalty fontkern strut whatsit glyph simple simplehbox simplevbox simplevtop user math italic origin discretionary expansion linie spatiu adancime</p>
<p><code>\afiseazamediufonttext [...,*...]</code></p> <p>* inherits: \seteazafonttext</p>
<p><code>\afiseazapaleta [...]<sup>1</sup> [...]<sup>2</sup>,...]</code></p> <p>1 NAME OPT</p> <p>2 orizontal vertical numar valoare nume</p>
<p><code>\afiseazarama [...]<sup>1</sup>,... [...]<sup>2</sup>,...]</code></p> <p>1 sus antet text <del>sub</del><sup>OPT</sup>subsol OPT</p> <p>2 bordurastanga marginestanga text marginedreapta borduradreapta</p>
<p><code>\afiseazasetari [...,*...]</code></p> <p>* pt bp cm mm dd cc pc <del>nd</del><sup>OPT</sup> nc sp in</p>
<p><code>\afiseazasetsimboluri [...]</code></p> <p>* NAME</p>
<p><code>\afiseazastruts</code></p>

<p><code>\afiseazatiparire [...<sup>1</sup>,...] [...<sup>2</sup>,...] [...<sup>3</sup>,...]</code></p> <p>1 inherits: \seteazadimensiuni<sup>gT</sup>hartie OPT OPT</p> <p>2 inherits: \seteazadimensiunihartie</p> <p>3 inherits: \seteazaaspect</p>
<p><code>\aftersplitstring ... \at ... \to ...</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 CSNAME</p>
<p><code>\aftertestandsplitstring ... \at ... \to ...</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 CSNAME</p>
<p><code>\aldin</code></p>
<p><code>\aldininclinat</code></p>
<p><code>\aldinitalic</code></p>
<p><code>\alignbottom</code></p>
<p><code>\aligned [...<sup>1</sup>,...] {...<sup>2</sup>}</code></p> <p>1 stanga centru dreapta sus subsol linie l c r m t b g</p> <p>2 CONTENT</p>
<p><code>\alignedbox [...<sup>1</sup>,...] ...<sup>2</sup> {...<sup>3</sup>}</code></p> <p>1 stanga centru dreapta sus subsol linie l c r m t b g</p> <p>2 CSNAME</p> <p>3 CONTENT</p>
<p><code>\alignedline {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}</code></p> <p>1 stanga dreapta centru flushleft flushright center max intern extern innermargin outermargin inneredge outeredge spatiuspate cutspace marginestanga marginedreapta bordurastanga borduradreapta</p> <p>2 stanga dreapta centru flushleft flushright center max intern extern innermargin outermargin inneredge outeredge spatiuspate cutspace marginestanga marginedreapta bordurastanga borduradreapta</p> <p>3 CONTENT</p>
<p><code>\alignhere</code></p>
<p><code>\alignmentcharacter</code></p>
<p><code>\aliniatcentru {...}</code></p> <p>* CONTENT</p>
<p><code>\aliniatdreapta {...}</code></p> <p>* CONTENT</p>
<p><code>\aliniatstanga {...}</code></p> <p>* CONTENT</p>
<p><code>\allinputpaths</code></p>
<p><code>\alphabeticnumerals {...}</code></p> <p>* NUMMER</p>

**\alwayscitation** [ $\dots^1\dots$ ] [ $\dots^2$ ]

```
1  referinta = REFERENCEOPT
   alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
               authoryear
   inainte   = BEFEHL
   dupa      = BEFEHL
   stanga    = BEFEHL
   dreapta   = BEFEHL
   inherits: \setupbtx
2  REFERENCE
```

**\alwayscitation** [ $\dots^1$ ] [ $\dots^2$ ]

```
1  implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear
2  REFERENCE
```

**\alwayscitation** [ $\dots^1\dots$ ] [ $\dots^2\dots$ ]

```
1  referinta = REFERENCE
   alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
               authoryear
   inainte   = BEFEHL
   dupa      = BEFEHL
   stanga    = BEFEHL
   dreapta   = BEFEHL
   inherits: \setupbtx
2  KEY = VALUE
```

**\alwayscite** [ $\dots^1\dots$ ] [ $\dots^2$ ]

```
1  referinta = REFERENCE
   alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
               authoryear
   inainte   = BEFEHL
   dupa      = BEFEHL
   stanga    = BEFEHL
   dreapta   = BEFEHL
   inherits: \setupbtx
2  REFERENCE
```

**\alwayscite** [ $\dots^1$ ] [ $\dots^2$ ]

```
1  implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear
2  REFERENCE
```

**\alwayscite** [ $\dots^1\dots$ ] [ $\dots^2\dots$ ]

```
1  referinta = REFERENCE
   alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
               authoryear
   inainte   = BEFEHL
   dupa      = BEFEHL
   stanga    = BEFEHL
   dreapta   = BEFEHL
   inherits: \setupbtx
2  KEY = VALUE
```

**\ampersand**

**\anchor** [ $\dots^1$ ] [ $\dots^2\dots$ ] [ $\dots^3\dots$ ] [ $\dots^4$ ]

```
1  NAME
   OPT
2  inherits: \setuplayer
3  inherits: \setuplayerinherits: \seteazainconjurat
4  CONTENT
```

**\appendetoks**  $\dots^1$  \to  $\dots^2$

```
1  BEFEHL
2  CSNAME
```

**\appendgvalue** [ $\dots^1$ ] [ $\dots^2$ ]

```
1  NAME
2  BEFEHL
```



<code>\appendtocommalist {...} \^2...</code> 1 TEXT 2 CSNAME
<code>\appendtoks \^1... \to \^2...</code> 1 BEFEHL 2 CSNAME
<code>\appendtoksonce \^1... \to \^2...</code> 1 BEFEHL 2 CSNAME
<code>\appendvalue {...} {...}</code> 1 NAME 2 BEFEHL
<code>\apply {...} {...}</code> 1 CONTENT 2 CONTENT
<code>\applyalternativestyle {...}</code> * NAME
<code>\applyprocessor {...} {...}</code> 1 NAME 2 CONTENT
<code>\applytocharacters \^1... {...}</code> 1 CSNAME 2 TEXT
<code>\applytofirstcharacter \^1... {...}</code> 1 CSNAME 2 TEXT
<code>\applytosplitstringchar \^1... {...}</code> 1 CSNAME 2 TEXT
<code>\applytosplitstringcharspaced \^1... {...}</code> 1 CSNAME 2 TEXT
<code>\applytosplitstringline \^1... {...}</code> 1 CSNAME 2 TEXT
<code>\applytosplitstringlinespaced \^1... {...}</code> 1 CSNAME 2 TEXT
<code>\applytosplitstringword \^1... {...}</code> 1 CSNAME 2 TEXT
<code>\applytosplitstringwordspaced \^1... {...}</code> 1 CSNAME 2 TEXT

<code>\applytowords \<sup>1</sup>... {<sup>2</sup>...}</code> 1 CSNAME 2 TEXT
<code>\arabicdecimals {<sup>*</sup>...}</code> * NUMBER
<code>\arabicexnumerals {<sup>*</sup>...}</code> * NUMBER
<code>\arabicnumerals {<sup>*</sup>...}</code> * NUMBER
<code>\arg {<sup>*</sup>...}</code> * CONTENT
<code>\asciistr {<sup>*</sup>...}</code> * CONTENT
<code>\ascundeblocuri [...,<sup>1</sup>...] [...,<sup>2</sup>...]</code> 1 NAME 2 NAME <small>OPT</small>
<code>\assignfadiimension {<sup>1</sup>...} \<sup>2</sup>... {<sup>3</sup>...} {<sup>4</sup>...} {<sup>5</sup>...}</code> 1 mic mediu mare niciunul DIMENSION 2 CSNAME 3 DIMENSION 4 DIMENSION 5 DIMENSION
<code>\assigndimen \<sup>1</sup>... {<sup>2</sup>...}</code> 1 CSNAME 2 DIMENSION
<code>\assigndimension {<sup>1</sup>...} \<sup>2</sup>... {<sup>3</sup>...} {<sup>4</sup>...} {<sup>5</sup>...}</code> 1 [-+]mic [-+]mediu [-+]mare niciunul DIMENSION 2 CSNAME 3 DIMENSION 4 DIMENSION 5 DIMENSION
<code>\assignifempty \<sup>1</sup>... {<sup>2</sup>...}</code> 1 CSNAME 2 BEFEHL
<code>\assigntranslation [...,<sup>1</sup>...,...] \to \<sup>2</sup>...</code> 1 SPRACHE = TEXT 2 CSNAME
<code>\assignvalue {<sup>1</sup>...} \<sup>2</sup>... {<sup>3</sup>...} {<sup>4</sup>...} {<sup>5</sup>...}</code> 1 mic mediu mare TEXT 2 CSNAME 3 BEFEHL 4 BEFEHL 5 BEFEHL
<code>\assignwidth {<sup>1</sup>...} \<sup>2</sup>... {<sup>3</sup>...} {<sup>4</sup>...}</code> 1 ajustat broad DIMENSION 2 CSNAME 3 TEXT 4 DIMENSION

$\backslash$ assumelongusagecs $\overset{1}{\dots} \{\overset{2}{\dots}\}$ 1 CSNAME 2 CONTENT
$\backslash$ astype $\{\dots\}$ * CONTENT
$\backslash$ ATTACHMENT $[\overset{1}{\dots}] [\dots, \overset{2}{\dots}, \dots]$ 1 NAME OPT OPT 2 inherits: \setupattachment instances: attachment
$\backslash$ attachment $[\overset{1}{\dots}] [\dots, \overset{2}{\dots}, \dots]$ 1 NAME OPT OPT 2 inherits: \setupattachment
$\backslash$ autocap $\{\dots\}$ * TEXT
$\backslash$ autodirhbox $\overset{1}{\dots} \{\overset{2}{\dots}\}$ 1 TEXT OPT 2 CONTENT
$\backslash$ autodirvbox $\overset{1}{\dots} \{\overset{2}{\dots}\}$ 1 TEXT OPT 2 CONTENT
$\backslash$ autodirvtop $\overset{1}{\dots} \{\overset{2}{\dots}\}$ 1 TEXT OPT 2 CONTENT
$\backslash$ autoinsertnextspace
$\backslash$ autointegral $\{\overset{1}{\dots}\} \{\overset{2}{\dots}\} \{\overset{3}{\dots}\}$ 1 TEXT 2 TEXT 3 TEXT
$\backslash$ automathematics $\{\dots\}$ * CONTENT
$\backslash$ autopagestaterealpage $\{\dots\}$ * NAME
$\backslash$ autopagestaterealpageorder $\{\dots\}$ * NAME
$\backslash$ autosetups $\{\dots, \dots\}$ * NAME
$\backslash$ autostarttext ... $\backslash$ autostoptext
$\backslash$ availablehsize
$\backslash$ averagecharwidth
$\backslash$ BeforePar $\{\dots\}$ * BEFEHL

\Big ... * CHARACTER
\Bigg ... * CHARACTER
\Biggl ... * CHARACTER
\Biggm ... * CHARACTER
\Biggr ... * CHARACTER
\Bigl ... * CHARACTER
\Bigm ... * CHARACTER
\Bigr ... * CHARACTER
\backgroundimage {...} {...} {...} {...} 1 NUMBER 2 DIMENSION 3 DIMENSION 4 BEFEHL
\backgroundimagefill {...} {...} {...} {...} 1 NUMBER 2 DIMENSION 3 DIMENSION 4 BEFEHL
\backgroundline [...] {...} 1 COLOR 2 CONTENT
\bar {...} * CHARACTER
\baraculoare [...,*...] * COLOR
\barainteractiune [... <sup>1</sup> ] [... <sup>2</sup> ...,...] 1 NAME OPT OPT 2 inherits: \seteazabarainteractiune
\BAR {...} * CONTENT instances: overbar underbar overstrike understrike overbars underbars overstrikes understrikes underrandom underrandoms underdash underdashes underdot underdots nobar hiddenbar
\hiddenbar {...} * CONTENT

$\backslash nobar \{...\}$ *    CONTENT
$\backslash overbar \{...\}$ *    CONTENT
$\backslash overbars \{...\}$ *    CONTENT
$\backslash overstrike \{...\}$ *    CONTENT
$\backslash overstrikes \{...\}$ *    CONTENT
$\backslash underbar \{...\}$ *    CONTENT
$\backslash underbars \{...\}$ *    CONTENT
$\backslash underdash \{...\}$ *    CONTENT
$\backslash underdashes \{...\}$ *    CONTENT
$\backslash underdot \{...\}$ *    CONTENT
$\backslash underdots \{...\}$ *    CONTENT
$\backslash underrandom \{...\}$ *    CONTENT
$\backslash underrandoms \{...\}$ *    CONTENT
$\backslash understrike \{...\}$ *    CONTENT
$\backslash understrikes \{...\}$ *    CONTENT

<pre> \basegrid [...,..*=...,...] *   nx           = NUMMER     ny           = NUMMER     dx           = NUMMER     dy           = NUMMER     factor       = NUMMER     scala        = NUMMER     xstep        = NUMMER     ystep        = NUMMER     offset       = DIMENSION     xoffset      = DIMENSION     yoffset      = DIMENSION     aliniere     = centru     unitate      = cm mm in pc pt bp     stil         = STYLE BEFEHL     culoare      = COLOR     culoarerigla = COLOR     grosimerigla = DIMENSION </pre>
<pre> \baselinebottom </pre>
<pre> \baselineleftbox {...} *   CONTENT </pre>
<pre> \baselinemiddlebox {...} *   CONTENT </pre>
<pre> \baselinerightbox {...} *   CONTENT </pre>
<pre> \bbordermatrix {...} *   CONTENT </pre>
<pre> \bbox {...} *   CONTENT </pre>
<pre> \beforesplitstring ... \at ... \to ... 1   TEXT 2   TEXT 3   CSNAME </pre>
<pre> \beforetestandsplitstring ... \at ... \to ... 1   TEXT 2   TEXT 3   CSNAME </pre>
<pre> \beginBLOCK [...,<sup>1</sup>...] [...,<sup>2</sup>...] ... \endBLOCK 1   + - NAME      OPT      OPT 2   KEY = VALUE </pre>
<pre> \beginhbox ... \endhbox </pre>
<pre> \beginofshapebox ... \endofshapebox </pre>
<pre> \beginvbox ... \endvbox </pre>
<pre> \beginvtop ... \endvtop </pre>
<pre> \begstrut ... \endstrut </pre>
<pre> \bigbodyfont </pre>

<code>\bigg ...</code> * CHARACTER
<code>\bigger</code>
<code>\biggl ...</code> * CHARACTER
<code>\biggm ...</code> * CHARACTER
<code>\biggr ...</code> * CHARACTER
<code>\bigl ...</code> * CHARACTER
<code>\bigm ...</code> * CHARACTER
<code>\bigr ...</code> * CHARACTER
<code>\bigskip</code>
<code>\bitmapimage [...,<sup>1</sup>...,<sup>2</sup>...] {...}</code> 1 culoare = rgb cmyk gri latime = DIMENSION inaltime = DIMENSION x = NUMMER y = NUMMER 2 NUMMER
<code>\blanc [...,*,...]</code> * preferinta <sup>OPT</sup> aceeasipagina max fortat enable dezactivat faraalb impachetat inapot overlay totdeauna weak strong implicit inainte intre dupa fixat flexibil niciunul mic mediu mare linie jumatatelinie quarterline formula alb inaltime adancime standard NUMMER*mic NUMMER*mediu NUMMER*mare NUMMER*linie NUMMER*jumatatelinie NUMMER*quarterline NUMMER*formula NUMMER*alb NUMMER*inaltime NUMMER*adancime category:NUMMER order:NUMMER penalty:NUMMER DIMENSION NAME
<code>\blap {...}</code> * CONTENT
<code>\bleed [...,<sup>1</sup>...,<sup>2</sup>...] {...}</code> 1 inherits: \setupbleeding 2 CONTENT
<code>\bleedheight</code>
<code>\bleedwidth</code>
<code>\blockligatures [...,*,...]</code> * TEXT
<code>\blocksynctexfile [...,*,...]</code> * FILE
<code>\blockuservariable {...}</code> * KEY

<code>\bodyfontenvironmentlist</code>
<code>\bodyfontsize</code>
<code>\boldface</code>
<code>\booleanmodevalue {...}</code> *    NAME
<code>\bordermatrix {...}</code> *    CONTENT
<code>\bottombox {...}</code> *    CONTENT
<code>\bottomleftbox {...}</code> *    CONTENT
<code>\bottomrightbox {...}</code> *    CONTENT
<code>\boxcursor</code>
<code>\boxmarker {...} {...}</code> 1    NAME 2    NUMMER
<code>\boxofsize \... ..<sup>1</sup> ...<sup>2</sup> .. {...}<sup>3</sup></code> 1    CSNAME                    OPT 2    DIMENSION 3    CONTENT
<code>\boxreference [...,<sup>1</sup>...] \...<sup>2</sup> {...}<sup>3</sup></code> 1    REFERENCE 2    CSNAME 3    CONTENT
<code>\bpar ... \epar</code>
<code>\bpos {...}</code> *    NAME
<code>\breakhere</code>
<code>\breve {...}</code> *    CHARACTER
<code>\bTABLE [...,<sup>*</sup>...,...] ... \eTABLE</code> *    inherits: \setupTABLE
<code>\bTABLEbody [...,<sup>*</sup>...,...] ... \eTABLEbody</code> *    inherits: \setupTABLE
<code>\bTABLEfoot [...,<sup>*</sup>...,...] ... \eTABLEfoot</code> *    inherits: \setupTABLE



\TABLEhead [...,.*=...,...] ... \eTABLEhead * inherits: \setupTABLE
\TABLEnext [...,.*=...,...] ... \eTABLEnext * inherits: \setupTABLE
\BTC [...,.*=...,...] ... \eTC * inherits: \BTD
\bTD [...,.*=...,...] ... \eTD * nx = <sup>OPT</sup> NUMBER ny = NUMBER nc = NUMBER nr = NUMBER n = NUMBER m = NUMBER actiune = REFERENCE inherits: \setupTABLE
\bTDs [...*] ... \eTDs * NAME
\bTH [...,.*=...,...] ... \eTH * inherits: \BTD
\bTN [...,.*=...,...] ... \eTN * inherits: \BTD
\bTR [...,.*=...,...] ... \eTR * inherits: \ <sup>OPT</sup> setupTABLE
\bTRs [...*] ... \eTRs * NAME
\bTX [...,.*=...,...] ... \eTX * inherits: \BTD
\bTY [...,.*=...,...] ... \eTY * inherits: \ <sup>OPT</sup> setupTABLE
\btxabbreviatedjournal {...*} * NAME
\btxaddjournal [... <sup>1</sup> .] [... <sup>2</sup> .] 1 NAME 2 NAME
\btxalwayscitation [...,.* <sup>1</sup> =...,...] [... <sup>2</sup> .] 1 referinta = REFERENCE <sup>OPT</sup> alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authorityyear inainte = BEFEHL dupa = BEFEHL stanga = BEFEHL dreapta = BEFEHL inherits: \setupbtx 2 REFERENCE
\btxalwayscitation [... <sup>1</sup> .] [... <sup>2</sup> .] 1 implicit category entry <sup>OPT</sup> short pagina num textnum an index tag keywords autor authoryears authornum authorityyear 2 REFERENCE

```

\btخالwayscitation [...,..1...,...] [...,..2...,...]
1  referinta    = REFERENCE
   alternativ    = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
                   authoryear
   inainte      = BEFEHL
   dupa         = BEFEHL
   stanga       = BEFEHL
   dreapta      = BEFEHL
   inherits: \setupbtX
2  KEY = VALUE

```

```

\btXauthorfield {...}
*  initials firstnames vons surnames juniors

```

```

\btXdetail {...}
*  address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language
   luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an
   yearfiled NAME

```

```

\btXdirect {...}
*  address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language
   luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an
   yearfiled NAME

```

```

\btXdoif {...} {...}
1  address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language
   luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an
   yearfiled NAME
2  TRUE

```

```

\btXdoifcombiinlistelse {...} {...} {...} {...}
1  NAME
2  NAME
3  TRUE
4  FALSE

```

```

\btXdoifelse {...} {...} {...}
1  address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language
   luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an
   yearfiled NAME
2  TRUE
3  FALSE

```

```

\btXdoifelsecombiinlist {...} {...} {...} {...}
1  NAME
2  NAME
3  TRUE
4  FALSE

```

```

\btXdoifelsesameasprevious {...} {...} {...}
1  address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language
   luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an
   yearfiled NAME
2  TRUE
3  FALSE

```

```

\btXdoifelsesameaspreviouschecked {...} {...} {...} {...}
1  totdeauna douafete
2  address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language
   luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an
   yearfiled NAME
3  TRUE
4  FALSE

```

```

\btXdoifelseuservariable {...} {...} {...}
1  KEY
2  TRUE
3  FALSE

```

<pre> \btxdoifnot {.^1.} {.^2.} 1  address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language    luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an    yearfiled NAME 2  TRUE </pre>
<pre> \btxdoifsameaspreviouscheckedelse {.^1.} {.^2.} {.^3.} {.^4.} 1  totdeauna douafete 2  address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language    luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an    yearfiled NAME 3  TRUE 4  FALSE </pre>
<pre> \btxdoifsameaspreviouselse {.^1.} {.^2.} {.^3.} 1  address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language    luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an    yearfiled NAME 2  TRUE 3  FALSE </pre>
<pre> \btxdoifuservariableelse {.^1.} {.^2.} {.^3.} 1  KEY 2  TRUE 3  FALSE </pre>
<pre> \btxexpandedjournal {.^*} *  NAME </pre>
<pre> \btxfield {.^*} *  address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language    luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an    yearfiled NAME </pre>
<pre> \btxfieldname {.^*} *  address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language    luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an    yearfiled NAME </pre>
<pre> \btxfieldtype {.^*} *  address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language    luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an    yearfiled NAME </pre>
<pre> \btxfirstofrange {.^*} *  volume pages </pre>
<pre> \btxflush {.^*} *  address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language    luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an    yearfiled NAME </pre>
<pre> \btxflushauthor [.^1.] {.^2.} 1  num normal normalsh<sup>OPT</sup>t inverted invertedshort 2  autor editor </pre>
<pre> \btxflushauthorinverted {.^*} *  autor editor </pre>
<pre> \btxflushauthorinvertedshort {.^*} *  autor editor </pre>
<pre> \btxflushauthorname {.^*} *  autor editor </pre>

\btxflushauthornormal {...} * autor editor
\btxflushauthornormalshort {...} * autor editor
\btxflushsuffix
\btxfoundname {...} * address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME
\btxfoundtype {...} * address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME
\btxhiddencitation [...] * REFERENCE
\btxhybridcite [... <sup>1</sup> ... <sup>2</sup> ...] [...] 1 referinta = REFERENCE <sup>OPT</sup> alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear inainte = BEFEHL dupa = BEFEHL stanga = BEFEHL dreapta = BEFEHL inherits: \setupbtx 2 REFERENCE
\btxhybridcite [... <sup>1</sup> ...] [... <sup>2</sup> ...] 1 implicit category <sup>OPT</sup> entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear 2 REFERENCE
\btxhybridcite {...} * REFERENCE
\btxhybridcite [... <sup>1</sup> ... <sup>2</sup> ...] [... <sup>2</sup> ... <sup>1</sup> ...] 1 referinta = REFERENCE alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear inainte = BEFEHL dupa = BEFEHL stanga = BEFEHL dreapta = BEFEHL inherits: \setupbtx 2 KEY = VALUE
\btxlistcitation [... <sup>1</sup> ... <sup>2</sup> ...] [...] 1 referinta = REFERENCE <sup>OPT</sup> alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear inainte = BEFEHL dupa = BEFEHL stanga = BEFEHL dreapta = BEFEHL inherits: \setupbtx 2 REFERENCE
\btxlistcitation [... <sup>1</sup> ...] [... <sup>2</sup> ...] 1 implicit category <sup>OPT</sup> entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear 2 REFERENCE

\btxlistcitation [...<sup>1</sup>...] [...<sup>2</sup>...]

```
1  referinta  = REFERENCE
   alternativ  = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
               authoryear
   inainte    = BEFEHL
   dupa       = BEFEHL
   stanga     = BEFEHL
   dreapta    = BEFEHL
   inherits: \setupbtx
2  KEY = VALUE
```

\btxloadjournalist [...]

\* FILE

\btxoneorrange {...} {...} {...}

```
1  volume pages
2  TRUE
3  FALSE
```

\btxremapauthor [...<sup>1</sup>] [...<sup>2</sup>]

```
1  TEXT
2  TEXT
```

\btxsavjournalist [...]

\* FILE

\btxsetup {...}

\* NAME

\btxsingularorplural {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

```
1  editor producer director
2  TRUE
3  FALSE
```

\btxsingularplural {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

```
1  editor producer director
2  TRUE
3  FALSE
```

\btxttextcitation [...<sup>1</sup>...] [...<sup>2</sup>]

```
1  referinta  = REFERENCEOPT
   alternativ  = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
               authoryear
   inainte    = BEFEHL
   dupa       = BEFEHL
   stanga     = BEFEHL
   dreapta    = BEFEHL
   inherits: \setupbtx
2  REFERENCE
```

\btxttextcitation [...<sup>1</sup>] [...<sup>2</sup>]

```
1  implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear
2  REFERENCE
```

\btxttextcitation [...<sup>1</sup>...] [...<sup>2</sup>...]

```
1  referinta  = REFERENCE
   alternativ  = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
               authoryear
   inainte    = BEFEHL
   dupa       = BEFEHL
   stanga     = BEFEHL
   dreapta    = BEFEHL
   inherits: \setupbtx
2  KEY = VALUE
```

$\backslash\text{buildmathaccent} \{.^1.\} \{.^2.\}$ 1 CHARACTER 2 CHARACTER
$\backslash\text{buildtextaccent} \{.^1.\} \{.^2.\}$ 1 CHARACTER 2 CHARACTER
$\backslash\text{buildtextbottomcomma} \{.^*.\}$ * CHARACTER
$\backslash\text{buildtextbottomdot} \{.^*.\}$ * CHARACTER
$\backslash\text{buildtextcedilla} \{.^*.\}$ * CHARACTER
$\backslash\text{buildtextgrave} \{.^*.\}$ * CHARACTER
$\backslash\text{buildtextmacron} \{.^*.\}$ * CHARACTER
$\backslash\text{buildtextognek} \{.^*.\}$ * CHARACTER
$\backslash\text{butoaneinteractiune} [^1, \dots, ^1, \dots] [^2, \dots]$ 1 inherits: $\backslash\text{seteazabarainteractiune}$ 2 pagina subpagina REFERENCE
$\backslash\text{buton} [^1, \dots, ^1, \dots] \{.^2.\} [.^3.]$ 1 inherits: $\backslash\text{setupbutton}$ 2 TEXT 3 REFERENCE
$\backslash\text{butonmeniu} [^1, \dots, ^1, \dots] \{.^2.\} \{.^3.\}$ 1 inherits: $\backslash\text{setupbutton}$ 2 TEXT 3 REFERENCE
$\backslash\text{butonmeniu} [.^1.] [^2, \dots, ^2, \dots] \{.^3.\} \{.^4.\}$ 1 NAME 2 inherits: $\backslash\text{seteazameniuinteractiune}$ 3 TEXT 4 REFERENCE
$\backslash\text{BUTTON} [^1, \dots, ^1, \dots] \{.^2.\} [.^3.]$ 1 inherits: $\backslash\text{setupbutton}$ 2 TEXT 3 REFERENCE instances: button
$\backslash\text{Caps} \{.^*.\}$ * TEXT
$\backslash\text{CONTEXT}$
$\backslash\text{ConTeXt}$
$\backslash\text{Context}$

<code>\ConvertConstantAfter \.<sup>1</sup>... {..<sup>2</sup>...} {..<sup>3</sup>...}</code> 1 CSNAME 2 TEXT 3 TEXT
<code>\ConvertToConstant \.<sup>1</sup>... {..<sup>2</sup>...} {..<sup>3</sup>...}</code> 1 CSNAME 2 TEXT 3 TEXT
<code>\CUVANT {..<sup>*</sup>...}</code> * TEXT
<code>\CUVINTE {..<sup>*</sup>...}</code> * TEXT
<code>\Cuvant {..<sup>*</sup>...}</code> * TEXT
<code>\Cuvinte {..<sup>*</sup>...}</code> * TEXT
<code>\caligrafic</code>
<code>\camel {..<sup>*</sup>...}</code> * TEXT
<code>\camp [...]<sup>1</sup> [...]<sup>2</sup></code> 1 NAME OPT 2 TEXT
<code>\catcodetablename</code>
<code>\cbox .<sup>1</sup>... {..<sup>2</sup>...}</code> 1 TEXT OPT 2 CONTENT
<code>\centraligned {..<sup>*</sup>...}</code> * CONTENT
<code>\centerbox .<sup>1</sup>... {..<sup>2</sup>...}</code> 1 TEXT OPT 2 CONTENT
<code>\centeredbox .<sup>1</sup>... {..<sup>2</sup>...}</code> 1 TEXT OPT 2 CONTENT
<code>\centeredlastline</code>
<code>\centerednextbox .<sup>1</sup>... {..<sup>2</sup>...}</code> 1 TEXT OPT 2 CONTENT
<code>\centerline {..<sup>*</sup>...}</code> * CONTENT
<code>\centru .<sup>*</sup>...</code> * CHARACTER

$\backslash\mathrm{cfrac}$ [ <sup>1</sup> ...] { <sup>2</sup> ...} { <sup>3</sup> ...} 1 l c r l <sup>P</sup> l <sup>F</sup> c l <sup>r</sup> c l c c c r l r c r r 2 CONTENT 3 CONTENT
$\backslash\mathrm{CHARACTERKERNING}$ [ <sup>1</sup> ...] { <sup>2</sup> ...} 1 NUMMER OPT 2 TEXT
$\backslash\mathrm{chardescription}$ {...} * NUMMER
$\backslash\mathrm{charwidthlanguage}$
$\backslash\mathrm{check}$ {...} * CHARACTER
$\backslash\mathrm{checkcharacteralign}$ {...} * CONTENT
$\backslash\mathrm{checkedblank}$ [...,*,...] * inherits: \blanc
$\backslash\mathrm{checkedchar}$ { <sup>1</sup> ...} { <sup>2</sup> ...} 1 NUMMER 2 CHARACTER
$\backslash\mathrm{checkedfiller}$ {...} * sym simbol rigla latime spatiu NAME BEFEHL
$\backslash\mathrm{checkedstrippedcsname}$ \*.. * CSNAME
$\backslash\mathrm{checkedstrippedcsname}$ *.. * TEXT
$\backslash\mathrm{checkinjector}$ [...] * NAME
$\backslash\mathrm{checknextindentation}$ [...] * da nu auto
$\backslash\mathrm{checknextinjector}$ [...] * NAME
$\backslash\mathrm{checkpage}$ [ <sup>1</sup> ...] [..., <sup>2</sup> ...,...] 1 NAME OPT 2 inherits: \setuppagechecker
$\backslash\mathrm{checkparameters}$ [...] * TEXT
$\backslash\mathrm{checkpreviousinjector}$ [...] * NAME
$\backslash\mathrm{checksoundtrack}$ {...} * NAME



<pre>\checktwopassdata {...} * NAME</pre>
<pre>\checkvariables [...]<sup>1</sup> [...,...<sup>2</sup>...,...]</pre> <pre>1 NAME 2 set = BEFEHL reset = BEFEHL KEY = VALUE</pre>
<pre>\chem {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup></pre> <pre>1 TEXT 2 TEXT 3 TEXT</pre>
<pre>\chemical [...]<sup>1</sup> [...,...<sup>2</sup>...,...]<sup>3</sup> [...,...]<sup>3</sup></pre> <pre>1 NAME OPT OPT 2 TEXT 3 TEXT</pre>
<pre>\chemicalbottext {...} * TEXT</pre>
<pre>\chemicalmidtext {...} * TEXT</pre>
<pre>\chemicalsymbol [...]</pre> <pre>* NAME</pre>
<pre>\chemicaltext {...} * TEXT</pre>
<pre>\chemicaltoptext {...} * TEXT</pre>
<pre>\chineseallnumerals {...} * NUMMER</pre>
<pre>\chineseapnumerals {...} * NUMMER</pre>
<pre>\chinesenumerals {...} * NUMMER</pre>
<pre>\citation [...,...<sup>1</sup>...,...]<sup>2</sup> [...]</pre> <pre>1 referinta = REFERENCE alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear inainte = BEFEHL dupa = BEFEHL stanga = BEFEHL dreapta = BEFEHL inherits: \setupbtx 2 REFERENCE</pre>
<pre>\citation [...]<sup>1</sup> [...]<sup>2</sup></pre> <pre>1 implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear 2 REFERENCE</pre>
<pre>\citation {...} * REFERENCE</pre>

`\citation [...,\sup{1}...,...]` `[...,\sup{2}...,...]`

```
1  referinta = REFERENCE
   alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
               authoryear
   inainte   = BEFEHL
   dupa      = BEFEHL
   stanga    = BEFEHL
   dreapta   = BEFEHL
   inherits: \setupbtx
2  KEY = VALUE
```

`\cite [...,\sup{1}...,...]` `[...,\sup{2}...]`

```
1  referinta opt = REFERENCE
   alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
               authoryear
   inainte   = BEFEHL
   dupa      = BEFEHL
   stanga    = BEFEHL
   dreapta   = BEFEHL
   inherits: \setupbtx
2  REFERENCE
```

`\cite [...,\sup{1}...]` `[...,\sup{2}...]`

```
1  implicitopt category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear
2  REFERENCE
```

`\cite {...}`

\* REFERENCE

`\cite [...,\sup{1}...,...]` `[...,\sup{2}...,...]`

```
1  referinta = REFERENCE
   alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
               authoryear
   inainte   = BEFEHL
   dupa      = BEFEHL
   stanga    = BEFEHL
   dreapta   = BEFEHL
   inherits: \setupbtx
2  KEY = VALUE
```

`\clap {...}`

\* CONTENT

`\classfont [...,\sup{1}...] [...,\sup{2}...]`

```
1  NAME
2  FONT
```

`\cldcommand {...}`

\* BEFEHL

`\cldcontext {...}`

\* BEFEHL

`\cldloadfile {...}`

\* FILE

`\cldprocessfile {...}`

\* FILE

`\clip [...,\sup{1}...,...]` `{...,\sup{2}...}`

```
1  inherits: \seteazaclipping
2  CONTENT
```

`\clippedoverlayimage {...}`

\* FILE

<p><code>\cloneazacamp [...]<sup>1</sup> [...]<sup>2</sup> [...]<sup>3</sup> [...]<sup>4</sup>,...]</code></p> <p>1 NAME</p> <p>2 NAME</p> <p>3 NAME</p> <p>4 NAME</p>
<p><code>\collect {...}</code></p> <p>* CONTENT</p>
<p><code>\collectedtext [...]<sup>1</sup>,...<sup>1</sup>,...<sup>1</sup>] [...]<sup>2</sup>,...<sup>2</sup>,...<sup>2</sup>] {...}<sup>3</sup> {...}<sup>4</sup></code></p> <p>1 inherits: \setupcollect<sup>OFF</sup> <sup>OPT</sup></p> <p>2 stil = STYLE BEFEHL</p> <p>culoare = COLOR</p> <p>inherits: \seteazainconjurat</p> <p>3 TEXT</p> <p>4 CONTENT</p>
<p><code>\collectexpanded {...}</code></p> <p>* CONTENT</p>
<p><code>\coloana [...]<sup>*</sup>,...]</code></p> <p>* inherits: \columnbreak<sup>OFF</sup></p>
<p><code>\colorcomponents {...}</code></p> <p>* COLOR</p>
<p><code>\colored [...]<sup>1</sup>,...<sup>1</sup>,...<sup>1</sup>] {...}<sup>2</sup></code></p> <p>1 inherits: \definesteculoare</p> <p>2 CONTENT</p>
<p><code>\colored [...]<sup>1</sup>] {...}<sup>2</sup></code></p> <p>1 COLOR</p> <p>2 CONTENT</p>
<p><code>\coloronly [...]<sup>1</sup>] {...}<sup>2</sup></code></p> <p>1 COLOR</p> <p>2 CONTENT</p>
<p><code>\columnbreak [...]<sup>*</sup>,...]</code></p> <p>* da nu preferinta local fortat primul ultim NUMMER NAME</p>
<p><code>\columnsetspanwidth {...}</code></p> <p>* NUMMER</p>
<p><code>\combinepages [...]<sup>1</sup> [...]<sup>2</sup>,...<sup>2</sup>,...<sup>2</sup></code></p> <p>1 FILE <sup>OPT</sup></p> <p>2 alternativ = a b c orizontal vertical</p> <p>n = NUMMER</p> <p>nx = NUMMER</p> <p>ny = NUMMER</p> <p>start = NUMMER</p> <p>stop = NUMMER</p> <p>distanta = DIMENSION</p> <p>sus = BEFEHL</p> <p>jos = BEFEHL</p> <p>stanga = BEFEHL</p> <p>dreapta = BEFEHL</p> <p>inainte = BEFEHL</p> <p>dupa = BEFEHL</p> <p>intre = BEFEHL</p> <p>frame = on dezactivat</p> <p>fundal = primplan culoare NAME</p> <p>culoarefundal = COLOR</p>

$\backslash\text{COMMENT} [\text{...}] [\text{...},\text{...},\text{...}] \{\text{...}\}$ 1    TEXT            OPT            OPT 2    inherits: \seteazacommentariu 3    TEXT instances: comment
$\backslash\text{comment} [\text{...}] [\text{...},\text{...},\text{...}] \{\text{...}\}$ 1    TEXT            OPT            OPT 2    inherits: \seteazacommentariu 3    TEXT
$\backslash\text{commalistelement}$
$\backslash\text{commalistsentence} [\text{...},\text{...}] [\text{...},\text{...}]$ 1    TEXT                            OPT 2    TEXT
$\backslash\text{commalistsize}$
$\backslash\text{comparagrupculoare} [\text{...}]$ *    NAME
$\backslash\text{comparapaleta} [\text{...}]$ *    NAME
$\backslash\text{comparedimension} \{\text{...}\} \{\text{...}\}$ 1    DIMENSION 2    DIMENSION
$\backslash\text{comparedimensioneps} \{\text{...}\} \{\text{...}\}$ 1    DIMENSION 2    DIMENSION
$\backslash\text{completeazanumarpagina}$
$\backslash\text{completebtxrendering} [\text{...}] [\text{...},\text{...},\text{...}]$ 1    NAME                            OPT            OPT 2    inherits: \setupbtxrendering
$\backslash\text{completCOMBINEDLIST} [\text{...},\text{...},\text{...}]$ *    inherits: \seteazalistacombinata <sup>OPT</sup> instances: content
$\backslash\text{completcontent} [\text{...},\text{...},\text{...}]$ *    inherits: \seteazalistacombinata <sup>OPT</sup>
$\backslash\text{completelist} [\text{...}] [\text{...},\text{...},\text{...}]$ 1    LISTE                            OPT 2    inherits: \seteazalista
$\backslash\text{completelistofFLOATS} [\text{...},\text{...},\text{...}]$ *    inherits: \seteazalista            OPT instances: chemicals figures tables intermezzi graphics
$\backslash\text{completelistofchemicals} [\text{...},\text{...},\text{...}]$ *    inherits: \seteazalista            OPT
$\backslash\text{completelistoffigures} [\text{...},\text{...},\text{...}]$ *    inherits: \seteazalista            OPT

<code>\completelistofgraphics [...,..<sup>*</sup>...,...]</code> <code>* inherits: \seteazalista</code> <small>OPT</small>
<code>\completelistofintermezzi [...,..<sup>*</sup>...,...]</code> <code>* inherits: \seteazalista</code> <small>OPT</small>
<code>\completelistoftables [...,..<sup>*</sup>...,...]</code> <code>* inherits: \seteazalista</code> <small>OPT</small>
<code>\completelistofpublications [...<sup>1</sup>...] [...,..<sup>2</sup>...,...]</code> <code>1 NAME</code> <small>OPT</small> <small>OPT</small> <code>2 inherits: \setupbt rendering</code>
<code>\completelistofsorts [...<sup>1</sup>...] [...,..<sup>2</sup>...,...]</code> <code>1 SINGULAR</code> <small>OPT</small> <code>2 inherits: \seteazasortare</code>
<code>\completelistofSORTS [...,..<sup>*</sup>...,...]</code> <code>* inherits: \seteazasortare</code> <small>OPT</small> <code>instances: logos</code>
<code>\completelistoflogos [...,..<sup>*</sup>...,...]</code> <code>* inherits: \seteazasortare</code> <small>OPT</small>
<code>\completelistofsynonyms [...<sup>1</sup>...] [...,..<sup>2</sup>...,...]</code> <code>1 SINGULAR</code> <small>OPT</small> <code>2 inherits: \seteazasinonime</code>
<code>\completelistofSYNONYMS [...,..<sup>*</sup>...,...]</code> <code>* inherits: \seteazasinonime</code> <small>OPT</small> <code>instances: abbreviations</code>
<code>\completelistofabbreviations [...,..<sup>*</sup>...,...]</code> <code>* inherits: \seteazasinonime</code> <small>OPT</small>
<code>\completeregister [...<sup>1</sup>...] [...,..<sup>2</sup>...,...]</code> <code>1 NAME</code> <small>OPT</small> <code>2 inherits: \seteazaregistru</code>
<code>\completREGISTER [...,..<sup>*</sup>...,...]</code> <code>* inherits: \seteazaregistru</code> <small>OPT</small> <code>instances: index</code>
<code>\completindex [...,..<sup>*</sup>...,...]</code> <code>* inherits: \seteazaregistru</code> <small>OPT</small>
<code>\complexorsimple \*..</code> <code>* CSNAME</code>
<code>\complexorsimpleempty \*..</code> <code>* CSNAME</code>
<code>\complexorsimpleempty {...}</code> <code>* TEXT CSNAME</code>
<code>\complexorsimple {...}</code> <code>* TEXT CSNAME</code>

\componenta [...] * FILE
\componenta ... * FILE
\composedcollector {...} * NAME
\composedlayer {...} * NAME
\compresult
\constantdimen \... * CSNAME
\constantdimenargument \... * CSNAME
\constantemptyargument \... * CSNAME
\constantnumber \... * CSNAME
\constantnumberargument \... * CSNAME
\contentreference [..., <sup>1</sup> ...] [..., <sup>2</sup> <sub>OPT</sub> ...,...] {... <sup>3</sup> } 1 REFERENCE 2 inherits: \seteazainconjurat 3 CONTENT
\continuednumber {...} * NUMMER
\continueifinputfile {...} * FILE
\convertargument ... <sup>1</sup> \to ... <sup>2</sup> 1 TEXT 2 CSNAME
\convertcommand \... <sup>1</sup> \to ... <sup>2</sup> 1 CSNAME 2 CSNAME
\convertedcounter [...] <sup>1</sup> [..., <sup>2</sup> <sub>OPT</sub> ...,...] 1 NAME 2 inherits: \setupcounter
\converteddimen {...} <sup>1</sup> {...} <sup>2</sup> 1 DIMENSION 2 ex em pt in cm mm sp bp pc dd cc nc

<p><b>\convertedsubcounter</b> [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...<sub>3</sub>...]</p> <p>1 NAME OPT OPT</p> <p>2 NUMMER NUMMER:NUMMER NUMMER:* NUMMER:tot</p> <p>3 inherits: \setupcounter</p>
<p><b>\converttestenunar</b> {<sup>1</sup>...} {<sup>2</sup>...}</p> <p>1 gol implicit niciunul luna month:mnem caracter Carac<sup>ter</sup> caractere Caractere a A Numere cuvant words Cuvant Cuvinte n N numereromane Numereromane i I r R KR RK grec Grec g G abjadnumerals abjadnodotnumerals abjadnaivenumerals thainumerals devanagarinumerals gurmurkhinumerals gujaratinnumerals tibetannumerals greeknumerals Greeknumerals arabicnumerals persiannumerals arabicexnumerals arabicdecimals persiandecimals koreannumerals koreanparentnumerals koreancircclenumberals kr kr-p kr-c chinesenumerals chinesecapnumerals chineseallnumerals cn cn-c cn-a sloveniannumerals slovenianNumerals spanishnumerals spanishNumerals mathgreek set_0 set_1 set_2 set_3 continued NAME</p> <p>2 NUMMER</p>
<p><b>\convertmonth</b> {...}</p> <p>* NUMMER</p>
<p><b>\convertvalue</b> <sup>1</sup>... \to \sup&gt;2...</p> <p>1 NAME</p> <p>2 CSNAME</p>
<p><b>\convertvboxtohbox</b></p>
<p><b>\copiazacamp</b> [<sup>1</sup>...] [<sup>2</sup>...]</p> <p>1 NAME</p> <p>2 NAME</p>
<p><b>\copyboxfromcache</b> {<sup>1</sup>...} {<sup>2</sup>...} <sup>3</sup>...</p> <p>1 NAME</p> <p>2 NUMMER TEXT</p> <p>3 CSNAME NUMMER</p>
<p><b>\copyLABELtext</b> [<sup>1</sup>...] [<sup>2</sup>...<sub>2</sub>...]</p> <p>1 SPRACHE OPT</p> <p>2 KEY = KEY</p> <p>instances: head label mathlabel taglabel unit operator prefix suffix btxlabel</p>
<p><b>\copybtxlabeltext</b> [<sup>1</sup>...] [<sup>2</sup>...<sub>2</sub>...]</p> <p>1 SPRACHE OPT</p> <p>2 KEY = KEY</p>
<p><b>\copyheadtext</b> [<sup>1</sup>...] [<sup>2</sup>...<sub>2</sub>...]</p> <p>1 SPRACHE OPT</p> <p>2 KEY = KEY</p>
<p><b>\copylabeltext</b> [<sup>1</sup>...] [<sup>2</sup>...<sub>2</sub>...]</p> <p>1 SPRACHE OPT</p> <p>2 KEY = KEY</p>
<p><b>\copymathlabeltext</b> [<sup>1</sup>...] [<sup>2</sup>...<sub>2</sub>...]</p> <p>1 SPRACHE OPT</p> <p>2 KEY = KEY</p>
<p><b>\copyoperatortext</b> [<sup>1</sup>...] [<sup>2</sup>...<sub>2</sub>...]</p> <p>1 SPRACHE OPT</p> <p>2 KEY = KEY</p>
<p><b>\copyprefixtext</b> [<sup>1</sup>...] [<sup>2</sup>...<sub>2</sub>...]</p> <p>1 SPRACHE OPT</p> <p>2 KEY = KEY</p>

$\backslash\text{copysuffixtext}$ [ <sup>1</sup> ...] [ <sup>2</sup> ... <sup>2</sup> ...] 1 SPRACHE OPT 2 KEY = KEY
$\backslash\text{copytaglabeltext}$ [ <sup>1</sup> ...] [ <sup>2</sup> ... <sup>2</sup> ...] 1 SPRACHE OPT 2 KEY = KEY
$\backslash\text{copyunittext}$ [ <sup>1</sup> ...] [ <sup>2</sup> ... <sup>2</sup> ...] 1 SPRACHE OPT 2 KEY = KEY
$\backslash\text{copypages}$ [ <sup>1</sup> ...] [ <sup>2</sup> ... <sup>2</sup> ...] <sup>3</sup> [ <sup>3</sup> ... <sup>3</sup> ...] 1 FILE OPT OPT 2 marcaje = on dezactivat offset = DIMENSION n = NUMMER 3 inherits: \setupexternalfigure
$\backslash\text{copyparameters}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...] [ <sup>3</sup> ...] 1 TEXT 2 TEXT 3 KEY
$\backslash\text{copyposition}$ { <sup>1</sup> ...} { <sup>2</sup> ...} 1 NAME 2 NAME
$\backslash\text{copysetups}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...] 1 NAME 2 NAME
$\backslash\text{corecteazaspatalb}$ { <sup>*</sup> ...} * CONTENT
$\backslash\text{countersubs}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...] 1 NAME OPT 2 NUMMER
$\backslash\text{counttoken}$ <sup>1</sup> ... \in <sup>2</sup> ... \to <sup>3</sup> ... 1 TEXT 2 TEXT 3 CSNAME
$\backslash\text{counttokens}$ <sup>1</sup> ... \to <sup>2</sup> ... 1 TEXT 2 CSNAME
$\backslash\text{cramped}$ { <sup>*</sup> ...} * CONTENT
$\backslash\text{crampedclap}$ { <sup>*</sup> ...} * CONTENT
$\backslash\text{crampedllap}$ { <sup>*</sup> ...} * CONTENT
$\backslash\text{crampedrlap}$ { <sup>*</sup> ...} * CONTENT



$\backslash\text{ctop}$ <sup>1</sup> ... { <sup>2</sup> ...} 1 TEXT <sup>OPT</sup> 2 CONTENT
$\backslash\text{ctxcommand}$ { <sup>*</sup> ...} * BEFEHL
$\backslash\text{ctxdirectcommand}$ { <sup>*</sup> ...} * BEFEHL
$\backslash\text{ctxdirectlua}$ { <sup>*</sup> ...} * BEFEHL
$\backslash\text{ctxfunction}$ { <sup>*</sup> ...} * NAME
$\backslash\text{CTXFUNCTIONDEFINITION}$
$\backslash\text{CTXFUNCTION}$
$\backslash\text{ctxlatecommand}$ { <sup>*</sup> ...} * BEFEHL
$\backslash\text{ctxlatelua}$ { <sup>*</sup> ...} * BEFEHL
$\backslash\text{ctxloadluafile}$ { <sup>*</sup> ...} * FILE
$\backslash\text{ctxlua}$ { <sup>*</sup> ...} * BEFEHL
$\backslash\text{ctxluabuffer}$ [ <sup>*</sup> ...] * BUFFER <sup>OPT</sup>
$\backslash\text{ctxluacode}$ { <sup>*</sup> ...} * BEFEHL
$\backslash\text{ctxreport}$ { <sup>*</sup> ...} * BEFEHL
$\backslash\text{ctxsprint}$ { <sup>*</sup> ...} * BEFEHL
$\backslash\text{culoare}$ [ <sup>1</sup> ...] { <sup>2</sup> ...} 1 COLOR 2 CONTENT
$\backslash\text{culoaregri}$ [ <sup>1</sup> ...] { <sup>2</sup> ...} 1 COLOR 2 CONTENT
$\backslash\text{currentassignmentlistkey}$
$\backslash\text{currentassignmentlistvalue}$

\currentbtxuservariable {...} * KEY
\currentcommalistitem
\currentcomponent
\currentenvironment
\currentfeaturetest
\currentinterface
\currentETICHETA [..., <sup>1</sup> ...] {... <sup>2</sup> } 1 REFERENCE OPT OPT 2 TEXT
\currentlanguage
\currentlistentrydestinationattribute
\currentlistentrylimitedtext {...} * TEXT
\currentlistentrynumber
\currentlistentrypagenumber
\currentlistentryreferenceattribute {...} * numar text numarpagina tot
\currentlistentrytitle
\currentlistentrytitlerendered
\currentlistsymbol
\currentmainlanguage
\currentmessagetext
\currentmoduleparameter {...} * KEY
\currentoutputstream
\currentproduct
\currentproject
\currentregime
\currentregisterpageuserdata {...} * KEY

<code>\currentresponses</code>
<code>\currenttime [...*,...]</code> <code>* h m TEXT</code> <small>OPT</small>
<code>\currentvalue</code>
<code>\currentxtablecolumn</code>
<code>\currentxtablerow</code>
<code>\cuvant {...}</code> <code>* TEXT</code>
<code>\cuvantdreapta [...<sup>1</sup>] {...<sup>2</sup>}</code> <code>1 dreapta DIMENSION</code> <small>OPT</small> <code>2 CONTENT</code>
<code>\d {...}</code> <code>* CHARACTER</code>
<code>\data [...<sup>1</sup>,...<sup>2</sup>,...]</code> <code>1 d = NUMMER</code> <small>OPT</small> <code>m = NUMMER</code> <code>y = NUMMER</code> <code>2 inherits: \datacurenta</code>
<code>\datacurenta [...*,...]</code> <code>* an luna zi zisaptamana y yy Y m mm M d dd D w W spatiu \ month:mnem m:mnem d:ord day:ord dd:ord D:ord TEXT</code> <code>referinta day:+ day:++ d:+ d:++ dd:+ dd:++ D:+ D:++ month:jalali m:jalali jalali:to jalali:from</code>
<code>\datasetvariable {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}</code> <code>1 NAME</code> <code>2 NAME NUMMER</code> <code>3 KEY realpage</code>
<code>\dayoftheweek {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}</code> <code>1 NUMMER</code> <code>2 NUMMER</code> <code>3 NUMMER</code>
<code>\dayspermonth {...<sup>1</sup>} {...<sup>2</sup>}</code> <code>1 NUMMER</code> <code>2 NUMMER</code>
<code>\dddots {...}</code> <code>* CHARACTER</code>
<code>\ddots {...}</code> <code>* CHARACTER</code>
<code>\decrement \*...</code> <code>* CSNAME</code>
<code>\decrementcounter [...<sup>1</sup>] [...<sup>2</sup>]</code> <code>1 NAME</code> <small>OPT</small> <code>2 NUMMER</code>

\decrementedcounter [...] * NAME
\decrementpagenumber
\decrementsubpagenumber
\decrementvalue {...} * NAME
\decrement (...;...) * CSNAME NUMBER
\defaultinterface
\defaultobjectpage
\defaultobjectreference
\defcatcodecommand \ <sup>1</sup> ... \ <sup>2</sup> ... {\ <sup>3</sup> ...} 1 CSNAME 2 CHARACTER NUMBER 3 BEFEHL
\defconvertedargument \ <sup>1</sup> ... {\ <sup>2</sup> ...} 1 CSNAME 2 TEXT
\defconvertedcommand \ <sup>1</sup> ... \ <sup>2</sup> ... 1 CSNAME 2 CSNAME
\defconvertedvalue \ <sup>1</sup> ... {\ <sup>2</sup> ...} 1 CSNAME 2 NAME
\defineactivecharacter \ <sup>1</sup> ... {\ <sup>2</sup> ...} 1 CHARACTER 2 BEFEHL
\definealternativestyle [...,\ <sup>1</sup> ...] [\ <sup>2</sup> ...] [\ <sup>3</sup> ...] 1 NAME 2 BEFEHL 3 BEFEHL
\defineanchor [\ <sup>1</sup> ...] [\ <sup>2</sup> ...] [...,\ <sup>3</sup> ...,\ <sup>3</sup> ...] [...,\ <sup>4</sup> ...,\ <sup>4</sup> ...] 1 NAME 2 NAME 3 inherits: \setupplayer 4 inherits: \setupplayerinherits: \seteazainconjurat
\defineattachment [\ <sup>1</sup> ...] [\ <sup>2</sup> ...] [...,\ <sup>3</sup> ...,\ <sup>3</sup> ...] 1 NAME 2 NAME 3 inherits: \setupattachment
\defineattribute [\ <sup>1</sup> ...] [...,\ <sup>2</sup> ...] 1 NAME 2 local global public private pickup

```
\definebackground [...]1 [...]2 [...,...3...,...]3
1 NAME OPT OPT
2 NAME
3 inherits: \seteazafundal
```

```
\definebar [...]1 [...]2 [...,...3...,...]3
1 NAME OPT OPT
2 NAME
3 inherits: \setupbar
```

```
\definebodyfontswitch [...]1 [...,2...]2
1 NAME
2 inherits: \seteazafonttext
```

```
\definebreakpoint [...]1 [...]2 [...,...3...,...]3
1 NAME OPT
2 CHARACTER
3 type = 1 2 3 4 5
nstanga = NUMMER
ndreapta = NUMMER
stanga = BEFEHL
mijloc = BEFEHL
dreapta = BEFEHL
range = da nu
language = SPRACHE
```

```
\definebreakpoints [...]*
* NAME
```

```
\definebtx [...]1 [...]2 [...,...3...,...]3
1 NAME OPT OPT
2 NAME
3 inherits: \setupbtx
```

```
\definebtxdataset [...]1 [...]2 [...,...3...,...]3
1 NAME OPT OPT
2 NAME
3 inherits: \setupbtxdataset
```

```
\definebtxregister [...]1 [...]2 [...,...3...,...]3
1 NAME OPT OPT
2 NAME
3 inherits: \setupbtxregister
```

```
\definebtxrendering [...]1 [...]2 [...,...3...,...]3
1 NAME OPT OPT
2 NAME
3 inherits: \setupbtxrendering
```

```
\definebutton [...]1 [...]2 [...,...3...,...]3
1 NAME OPT OPT
2 NAME
3 inherits: \setupbutton
```

```
\definecapitals [...]1 [...]2 [...,...3...,...]3
1 NAME OPT OPT
2 NAME
3 inherits: \seteazamajuscule
```

```
\definecharacterkerning [...]1 [...]2 [...,...3...,...]3
1 NAME OPT OPT
2 NAME
3 inherits: \setupcharacterkerning
```

<code>\definecharacterspacing [...]</code> <code>* NAME</code>
<code>\definechemical [...] {...}</code> <code>1 NAME</code> <code>2 CONTENT</code>
<code>\definechemicals [...] [...]<sup>2</sup> [...,...<sup>3</sup>...,...]</code> <code>1 NAME</code> <code>2 NAME</code> <code>3 inherits: \setupchemical</code>
<code>\definechemicalsymbol [...] [...]</code> <code>1 NAME</code> <code>2 TEXT</code>
<code>\definecollector [...] [...]<sup>2</sup> [...,...<sup>3</sup>...,...]</code> <code>1 NAME</code> <code>2 NAME</code> <code>3 inherits: \setupcollector</code>
<code>\definecolumnbreak [...]<sup>1</sup> [...,<sup>2</sup>...]</code> <code>1 NAME</code> <code>2 da nu preferinta local fortat primul ultim NUMMER</code>
<code>\definecolumnset [...] [...]<sup>2</sup> [...,...<sup>3</sup>...,...]</code> <code>1 NAME</code> <code>2 NAME</code> <code>3 inherits: \setupcolumnset</code>
<code>\definecolumnsetarea [...] [...]<sup>2</sup> [...,...<sup>3</sup>...,...]</code> <code>1 NAME</code> <code>2 NAME</code> <code>3 inherits: \setupcolumnsetarea</code>
<code>\definecolumnsetspan [...] [...]<sup>2</sup> [...,...<sup>3</sup>...,...]</code> <code>1 NAME</code> <code>2 NAME</code> <code>3 inherits: \setupcolumnsetspan</code>
<code>\definecombination [...] [...]<sup>2</sup> [...,...<sup>3</sup>...,...]</code> <code>1 NAME</code> <code>2 NAME</code> <code>3 inherits: \setupcombination</code>
<code>\definecomment [...] [...]<sup>2</sup> [...,...<sup>3</sup>...,...]</code> <code>1 NAME</code> <code>2 NAME</code> <code>3 inherits: \seteazacomentariu</code>
<code>\definecomplexorsimple \...</code> <code>* CSNAME</code>
<code>\definecomplexorsimpleempty \...</code> <code>* CSNAME</code>
<code>\definecomplexorsimpleempty {...}</code> <code>* TEXT CSNAME</code>
<code>\definecomplexorsimple {...}</code> <code>* TEXT CSNAME</code>

```
\defineconversionset [...] [...] [...]
1 NAME SECTIONBLOCK:NAME
2 NAME PROCESSOR->NAME
3 NAME PROCESSOR->NAME
```

```
\definecounter [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupcounter
```

```
\definedataset [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupdataset
```

```
\definedelimitedtext [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupdelimitedtext
```

```
\definedfont [...]
* FONT
```

```
\defineeffect [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupeffect
```

```
\defineexpandable [...] \^ [...] { [...] }
1 NUMMER
2 CSNAME
3 CONTENT
```

```
\defineexternalfigure [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupexternalfigure
```

```
\definefacingfloat [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupfacingfloat
```

```
\definefallbackfamily [...] [...] [...] [...]
1 NAME
2 rm ss tt mm hw cg roman serif regular sansserif sans suport teletype type mono scrismatematica caligrafic math
3 FONT
4 rscale = NUMMER
designsize = implicit auto
goodies = FILE
range = NUMMER NAME
offset = NUMMER NAME
check = da nu
fortat = da nu
features = NAME
tf = TEXT
bf = TEXT
it = TEXT
sl = TEXT
bi = TEXT
bs = TEXT
sc = TEXT
```

`\definefallbackfamily [...]1 [...]2 [...]3 [...]4,...]`

```
1 NAME OPT
2 rm ss tt mm hw cg roman serif regular sansserif sans suport teletype type mono scrismathematica manual caligrafic math
3 FONT
4 NAME
```

`\definefieldbody [...]1 [...]2 [...]3,...]`

```
1 NAME OPT OPT
2 NAME
3 inherits: \setupfieldbody
```

`\definefieldbodyset [...]1 [...]2,...]`

```
1 NAME
2 NAME
```

`\definefieldcategory [...]1 [...]2 [...]3,...]`

```
1 NAME OPT OPT
2 NAME
3 inherits: \setupfieldcategory
```

`\definefileconstant {...}1 {...}2`

```
1 NAME
2 NAME
```

`\definefilefallback [...]1 [...]2,...]`

```
1 NAME
2 FILE
```

`\definefilesynonym [...]1 [...]2`

```
1 NAME
2 FILE
```

`\definefiller [...]1 [...]2 [...]3,...]`

```
1 NAME OPT OPT
2 NAME
3 inherits: \setupfiller
```

`\definefirstline [...]1 [...]2 [...]3,...]`

```
1 NAME OPT OPT
2 NAME
3 inherits: \setupfirstline
```

`\definefittingpage [...]1 [...]2 [...]3,...]`

```
1 NAME OPT OPT
2 NAME
3 inherits: \setupfittingpage
```

`\definefontalternative [...]*`

```
* NAME
```

`\definefontfallback [...]1 [...]2 [...]3,...]4 [...]5,...]`

```
1 NAME OPT
2 FONT NAME
3 NAME NUMMER
4 rscale = NUMMER
  fortat = da nu
  check = da nu
  offset = NUMMER NAME
  target = NUMMER NAME
  features = NAME
  factor = NUMMER
  metoda = lowercase uppercase
```



```

\definefontfamily [...] [...] [...] [...] [...]
1  NAME
2  rm ss tt mm hw cg roman serif regular sansserif sans suport teletype type mono scrismatematica
3  FONT
4  rscale      = NUMBER
   designsizes = implicit auto
   goodies     = FILE
   features    = NAME
   tf          = TEXT
   bf          = TEXT
   it          = TEXT
   sl          = TEXT
   bi          = TEXT
   bs          = TEXT
   sc          = TEXT

```

```

\definefontfamilypreset [...] [...]
1  NAME
2  inherits: \definefontfamily

```

```

\definefontfamilypreset [...] [...]
1  NAME
2  NAME

```

```

\definefontfamily [...] [...] [...] [...] [...]
1  NAME
2  rm ss tt mm hw cg roman serif regular sansserif sans suport teletype type mono scrismatematica
3  FONT
4  NAME

```

**\definefontfeature** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...<sup>3</sup>...,...]

```
1  NAME                                OPT
2  NAME
3  language      = NAME
   script        = NAME auto
   mode          = node base auto niciunul
   liga          = da nu
   kern          = da nu
   extrakerns    = da nu
   tlig          = da nu
   trep          = da nu
   missing       = da nu
   dummies       = da nu
   analyze       = da nu
   unicoding     = da nu
   expansiune    = NAME
   protrusion    = NAME
   nostackmath   = da nu
   realdimensions = da nu
   itlc          = da nu
   textitalics   = da nu
   mathitalics   = da nu
   slant         = NUMMER
   extend        = NUMMER
   dimensions    = NUMMER
   boundingbox    = da nu fundal incadrat gol COLOR
   compose       = da nu
   char-ligatures = da nu
   compat-ligatures = da nu
   goodies       = FILE
   extrafeatures = da nu
   featureset    = NAME
   colorscheme   = NAME
   postprocessor = NAME
   mathdimensions = NAME
   keepligatures = da nu auto
   devanagari    = da nu
   features      = da nu
   tcom          = da nu
   anum          = da nu
   mathsize      = da nu
   decomposehangul = da nu
   mathalternatives = da nu
   mathgaps      = da nu
   checkmarks    = da nu
   NAME          = da nu
   mathnolimitsmode = NUMMER
   blockligatures = da nu
```

**\definefontfile** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...<sup>3</sup>...,...]

```
1  NAME                                OPT
2  FILE
3  features      = NAME
   fallbacks    = NAME
   goodies       = NAME
   designsize    = auto implicit
```

**\definefontsize** [...]

```
*  NAME
```

**\definefontsolution** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...<sup>3</sup>...,...]

```
1  NAME                                OPT      OPT
2  NAME
3  inherits: \setupfontsolution
```

**\defineformula** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...<sup>3</sup>...,...]

```
1  NAME                                OPT      OPT
2  NAME
3  inherits: \setupformula
```

**\defineformulaalternative** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...]

```
1  NAME
2  CSNAME
3  CSNAME
```

```
\defineformulaframed [...] [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupformulaframed
```

```
\defineframedcontent [...] [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupframedcontent
```

```
\defineframedtable [...] [...]
1 NAME OPT
2 NAME
```

```
\definefrozenfont [...] [...]
1 NAME
2 FONT
```

```
\defineglobalcolor [...] [...] [...]
1 NAME
2 inherits: \definesteculoare
```

```
\defineglobalcolor [...] [...]
1 NAME
2 COLOR
```

```
\definegraphicstypesynonym [...] [...]
1 NAME
2 NAME
```

```
\definegridsnapping [...] [...] [...]
1 NAME
2 local global noheight nodepth box max min niciunul linie jumatatelinie primul ultim inaltime minima maxheight
mindepth maxdepth sus subsol strut NUMMER minheight:NUMMER maxheight:NUMMER mindepth:NUMMER maxdepth:NUMMER
box:NUMMER top:NUMMER bottom:NUMMER offset:NUMMER
```

```
\defineheadalternative [...] [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupheadalternative
```

```
\definehelp [...] [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setuphelp
```

```
\definehigh [...] [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setuphigh
```

```
\definehighlight [...] [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setuphighlight
```

```
\definehspace [...] [...] [...]
1 NAME OPT
2 NAME
3 DIMENSION
```

```

\definehyphenationfeatures [...] [...2...]
1 NAME
2 characters = TEXT
   hyphens   = da tot TEXT
   joiners    = da tot TEXT
   rightwords = NUMMER
   hyphenmin  = NUMMER
   lefthyphenmin = NUMMER
   righthyphenmin = NUMMER
   lefthyphenchar = NUMMER
   righthyphenchar = NUMMER
   alternativ  = original tex hyphenate expanded traditional niciunul
   borduradreapta = tex
   rightchars  = cuvant NUMMER

```

```

\defineindentedtext [...] [...2] [...3...]
1 NAME
2 NAME
3 inherits: \setupindentedtext

```

```

\defineindenting [...] [...2,...]
1 NAME
2 [-+]mic [-+]mediu [-+]mare niciunul nu nu primul urmatorul da totdeauna niciodata impar par normal reset toggle
   DIMENSION

```

```

\defineinitial [...] [...2] [...3...]
1 NAME
2 NAME
3 inherits: \setupinitial

```

```

\defineinsertion [...] [...2] [...3...]
1 NAME
2 NAME
3 inherits: \setupinsertion

```

```

\defineinteraction [...] [...2] [...3...]
1 NAME
2 NAME
3 inherits: \seteazainteractiunea

```

```

\defineinteractionbar [...] [...2] [...3...]
1 NAME
2 NAME
3 inherits: \seteazabarainteractiune

```

```

\defineinterfaceconstant {...} {...2}
1 NAME
2 NAME

```

```

\defineinterfaceelement {...} {...2}
1 NAME
2 NAME

```

```

\defineinterfacevariable {...} {...2}
1 NAME
2 NAME

```

```

\defineinterlinespace [...] [...2] [...3...]
1 NAME
2 NAME
3 inherits: \seteazaspatiuinterliniar

```

```

\defineintermediatecolor [...] [...2,...] [...3...]
1 NAME
2 COLOR NUMMER
3 a = NUMMER
   t = NUMMER

```

<pre> \defineitemgroup [...] [...] [...] [...] 1  NAME                      OPT      OPT 2  NAME 3  inherits: \setupitemgroup </pre>
<pre> \defineitems [...] [...] [...] [...] 1  NAME                      OPT      OPT 2  NAME 3  inherits: \seteazaelemente </pre>
<pre> \definelabelclass [...] [...] 1  NAME                      OPT 2  NUMMER </pre>
<pre> \definelayer [...] [...] [...] 1  NAME                      OPT      OPT 2  NAME 3  inherits: \setuplayer </pre>
<pre> \definelayerpreset [...] [...] 1  NAME 2  inherits: \setuplayer </pre>
<pre> \definelayerpreset [...] [...] 1  NAME 2  NAME </pre>
<pre> \definelayout [...] [...] [...] 1  NAME                      OPT      OPT 2  NAME 3  inherits: \seteazaaspect </pre>
<pre> \definelinefiller [...] [...] [...] 1  NAME                      OPT      OPT 2  NAME 3  inherits: \setuplinefiller </pre>
<pre> \definelinenote [...] [...] [...] 1  NAME                      OPT      OPT 2  NAME 3  inherits: \setuplinenote </pre>
<pre> \definelinenumbering [...] [...] [...] 1  NAME                      OPT      OPT 2  NAME 3  inherits: \seteazanumerotarelinii </pre>
<pre> \definelines [...] [...] [...] 1  NAME                      OPT      OPT 2  NAME 3  inherits: \seteazalinii </pre>
<pre> \definelistalternative [...] [...] [...] 1  NAME                      OPT      OPT 2  NAME 3  inherits: \setuplistalternative </pre>
<pre> \definelistextra [...] [...] [...] 1  NAME                      OPT      OPT 2  NAME 3  inherits: \setuplistextra </pre>

<pre> \definelow [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...<sub>=</sub>...,...] 1  NAME                OPT          OPT 2  NAME 3  inherits: \setuplow </pre>
<pre> \definelowhigh [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...<sub>=</sub>...,...] 1  NAME                OPT          OPT 2  NAME 3  inherits: \setuplowhigh </pre>
<pre> \definelowmidhigh [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...<sub>=</sub>...,...] 1  NAME                OPT          OPT 2  NAME 3  inherits: \setuplowmidhigh </pre>
<pre> \defineMPinstance [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...<sub>=</sub>...,...] 1  NAME                OPT          OPT 2  NAME 3  inherits: \setupMPinstance </pre>
<pre> \definemarginblock [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...<sub>=</sub>...,...] 1  NAME                OPT          OPT 2  NAME 3  inherits: \setupmarginblock </pre>
<pre> \definemargindata [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...<sub>=</sub>...,...] 1  NAME                OPT          OPT 2  NAME 3  inherits: \setupmargindata </pre>
<pre> \definemarker [...]  *  NAME </pre>
<pre> \definemathaccent <sup>1</sup>... <sup>2</sup>... 1  NAME 2  CHARACTER </pre>
<pre> \definemathalignment [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...<sub>=</sub>...,...] 1  NAME                OPT          OPT 2  NAME 3  inherits: \setupmathalignment </pre>
<pre> \definemathcases [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...<sub>=</sub>...,...] 1  NAME                OPT          OPT 2  NAME 3  inherits: \setupmathcases </pre>
<pre> \definemathcommand [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...] {<sup>4</sup>...} 1  NAME                OPT          OPT    OPT 2  ord op bin rel open close punct alpha intern nothing limop nolog box 3  unu doi 4  BEFEHL \...##1 \...##1##2 </pre>
<pre> \definemathdouble [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...] [<sup>4</sup>...] 1  ambele vfenced NAME 2  NAME 3  NUMMER 4  NUMMER </pre>
<pre> \definemathdoubleextensible [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...] [<sup>4</sup>...] 1  ambele vfenced                OPT 2  NAME 3  NUMMER 4  NUMMER </pre>

<pre> \definemathe<sup>1</sup>matics [...]<sup>2</sup> [...]<sup>3</sup> [...,...,...</pre> <pre> 1 NAME OPT OPT 2 NAME 3 inherits: \setupmathematics</pre>
<pre> \definemathextensible [...]<sup>1</sup> [...]<sup>2</sup> [...]<sup>3</sup></pre> <pre> 1 reverse matematica text chemistry 2 NAME 3 NUMMER</pre>
<pre> \definemathfence [...]<sup>1</sup> [...]<sup>2</sup> [...,...,<sup>3</sup>...,...</pre> <pre> 1 NAME OPT OPT 2 NAME 3 inherits: \setupmathfence</pre>
<pre> \definemathfraction [...]<sup>1</sup> [...]<sup>2</sup> [...,...,<sup>3</sup>...,...</pre> <pre> 1 NAME OPT OPT 2 NAME 3 inherits: \setupmathfraction</pre>
<pre> \definemathframed [...]<sup>1</sup> [...]<sup>2</sup> [...,...,<sup>3</sup>...,...</pre> <pre> 1 NAME OPT OPT 2 NAME 3 inherits: \setupmathframed</pre>
<pre> \definemathmatrix [...]<sup>1</sup> [...]<sup>2</sup> [...,...,<sup>3</sup>...,...</pre> <pre> 1 NAME OPT OPT 2 NAME 3 inherits: \setupmathmatrix</pre>
<pre> \definemathornament [...]<sup>1</sup> [...]<sup>2</sup> [...,...,<sup>3</sup>...,...</pre> <pre> 1 NAME OPT OPT 2 NAME 3 inherits: \setupmathornament</pre>
<pre> \definemathover [...]<sup>1</sup> [...]<sup>2</sup> [...]<sup>3</sup></pre> <pre> 1 sus vfenced NAME 2 NAME 3 NUMMER</pre>
<pre> \definemathoverextensible [...]<sup>1</sup> [...]<sup>2</sup> [...]<sup>3</sup></pre> <pre> 1 sus vfenced OPT 2 NAME 3 NUMMER</pre>
<pre> \definemathovertexttextensible [...]<sup>1</sup> [...]<sup>2</sup> [...]<sup>3</sup></pre> <pre> 1 bothtext OPT 2 NAME 3 NUMMER</pre>
<pre> \definemathradical [...]<sup>1</sup> [...]<sup>2</sup> [...,...,<sup>3</sup>...,...</pre> <pre> 1 NAME OPT OPT 2 NAME 3 inherits: \setupmathradical</pre>
<pre> \definemathstackers [...]<sup>1</sup> [...]<sup>2</sup> [...,...,<sup>3</sup>...,...</pre> <pre> 1 NAME OPT OPT 2 NAME 3 inherits: \setupmathstackers</pre>
<pre> \definemathstyle [...]<sup>1</sup> [...]<sup>2</sup>,...</pre> <pre> 1 NAME 2 display text script scriptscript cramped uncramped normal impachetat mic mare</pre>

<pre> \definemathtriplet [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...] 1  NAME              OPT              OPT 2  NAME 3  TEXT </pre>
<pre> \definemathunder [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...] 1  subsol vfenced NAME 2  NAME 3  NUMMER </pre>
<pre> \definemathunderextensible [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...] 1  subsol vfenced              OPT 2  NAME 3  NUMMER </pre>
<pre> \definemathundertexttextensible [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...] 1  bothtext              OPT 2  NAME 3  NUMMER </pre>
<pre> \definemathunstacked [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...] 1  larg              OPT 2  NAME 3  NUMMER </pre>
<pre> \definemeasure [<sup>1</sup>...] [<sup>2</sup>...] 1  NAME 2  DIMENSION </pre>
<pre> \definemessageconstant {...} *  NAME </pre>
<pre> \definemixedcolumns [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...<sup>3</sup>...,...] 1  NAME              OPT              OPT 2  NAME 3  inherits: \setupmixedcolumns </pre>
<pre> \definemode [...,<sup>1</sup>...] [<sup>2</sup>...] 1  NAME              OPT 2  da nu mentine </pre>
<pre> \definemultitonecolor [<sup>1</sup>...] [...,<sup>2</sup>...,...<sup>3</sup>...,...<sup>4</sup>...,...] 1  NAME              OPT 2  COLOR = NUMMER 3  inherits: \definesteculoare 4  inherits: \definespotcolor </pre>
<pre> \definenamecolor [<sup>1</sup>...] [...,<sup>2</sup>...,...<sup>2</sup>...,...] 1  NAME 2  inherits: \definesteculoare </pre>
<pre> \definenamecolor [<sup>1</sup>...] [<sup>2</sup>...] 1  NAME 2  COLOR </pre>
<pre> \definenamespace [<sup>1</sup>...] [...,<sup>2</sup>...,...<sup>2</sup>...,...] 1  NAME 2  nume      = TEXT    parent    = TEXT    stil      = da nu    comanda   = da nu lista    setup     = da nu lista    set       = da nu lista    frame     = da nu </pre>



<pre> \definenaarrower [...] [...] [...] 1 NAME 2 NAME 3 inherits: \seteazaingust </pre>
<pre> \definenote [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setupnote </pre>
<pre> \defineornament [...] [...] [...] 1 NAME 2 alternativ = a b   inherits: \setupcollector 3 stil = STYLE BEFEHL   culoare = COLOR   inherits: \seteazainconjurat </pre>
<pre> \defineornament [...] [...] [...] 1 NAME 2 alternativ = a b   inherits: \setuplayer 3 inherits: \setuplayeredtext </pre>
<pre> \defineoutputroutine [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setupoutputroutine </pre>
<pre> \defineoutputroutinecommand [...,*...] * KEY </pre>
<pre> \definepage [...] [...] 1 NAME 2 REFERENCE </pre>
<pre> \definepagebreak [...] [...] 1 NAME 2 gol antet subsol dummy incadrat NUMMER +NUMMER implicit reset dezactivat da nu marcaj blank preferinta preferintamare   stanga dreapta par impar cvadрупul ultim ultimpagina start stop </pre>
<pre> \definepagechecker [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setuppagechecker </pre>
<pre> \definepagecolumns [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setuppagecolumns </pre>
<pre> \definepageinjection [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setuppageinjection </pre>
<pre> \definepageinjectionalternative [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setuppageinjectionalternative </pre>
<pre> \definepageshift [...] [...] [...] 1 NAME 2 orizontal vertical 3 DIMENSION </pre>

<pre> \definepagestate [...] [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setuppagestate </pre>
<pre> \definepairedbox [...] [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setuppairedbox </pre>
<pre> \defineparagraph [...] [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupparagraph </pre>
<pre> \defineparallel [...] [...] 1 NAME 2 NAME </pre>
<pre> \defineparbuilder [...] * NAME </pre>
<pre> \defineperiodkerning [...] [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupperiodkerning </pre>
<pre> \defineplacement [...] [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupplacement </pre>
<pre> \definepositioning [...] [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setarepozitie </pre>
<pre> \defineprefixset [...] [...] [...] 1 NAME SECTIONBLOCK:NAME OPT 2 ABSCHNITT 3 ABSCHNITT </pre>
<pre> \defineprocesscolor [...] [...] [...] [...] 1 NAME OPT 2 COLOR 3 inherits: \definesteculoare </pre>
<pre> \defineprocessor [...] [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupprocessor </pre>
<pre> \definepushbutton [...] [...] [...] [...] 1 NAME OPT 2 inherits: \setupfieldcontentframed </pre>
<pre> \definepushsymbol [...] [...] 1 NAME 2 n r d </pre>
<pre> \definerenderingwindow [...] [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setuprenderingwindow </pre>

```
\defineresetset [...] [...] [...]
1 NAME SECTIONBLOCK:NAME OPT
2 NUMMER
3 NUMMER
```

```
\defineruby [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupruby
```

```
\definescale [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupscale
```

```
\definescript [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupscript
```

```
\definesectionlevels [...] [...]
1 NAME
2 ABSCHNITT
```

```
\defineselector [...] [...]
1 NAME OPT
2 inherits: \setupselector
```

```
\defineseparatorset [...] [...] [...]
1 NAME SECTIONBLOCK:NAME OPT
2 BEFEHL PROCESSOR->BEFEHL
3 BEFEHL PROCESSOR->BEFEHL
```

```
\defineshift [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupshift
```

```
\definesidebar [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupsidebar
```

```
\definesort [...] [...] [...] {...}
1 da nu OPT
2 SINGULAR
3 NAME
4 CONTENT
```

```
\definespotcolor [...] [...] [...]
1 NAME
2 COLOR
3 a = NUMMER niciunul normal multiply ecran overlay softlight hardlight colordodge colorburn darken lighten
    difference exclusion hue saturation culoare luminosity
    t = NUMMER
    e = TEXT
    p = NUMMER
```

```
\defineste [...] [...] [...]
1 NUMMER OPT
2 CSNAME
3 CONTENT
```

**\definesteaccent** <sup>1</sup>... <sup>2</sup>... <sup>3</sup>...

- 1 CHARACTER
- 2 CHARACTER
- 3 CHARACTER

**\definesteantet** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...]

- 1 NAME
- 2 ABSCHNITT
- 3 inherits: \seteazatitlu

**\definestebloc** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...]

- 1 NAME
- 2 NAME
- 3 inherits: \seteazabloc

**\definesteblocsectiune** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...]

- 1 NAME
- 2 NAME
- 3 inherits: \seteazablocsectiune

**\definestebuffer** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...]

- 1 NAME
- 2 BUFFER
- 3 inherits: \seteazabuffer

**\definestecamp** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...] [<sup>4</sup>...,...] [<sup>5</sup>...]

- 1 NAME
- 2 radio sub text linie push check signature
- 3 NAME
- 4 NAME
- 5 NAME

**\definestecaracter** <sup>1</sup>... <sup>2</sup>...

- 1 CHARACTER
- 2 NUMMER

**\definestecomanda** <sup>1</sup>... <sup>2</sup>...

- 1 CHARACTER
- 2 BEFEHL

**\definesteconversie** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...]

- 1 SPRACHE
- 2 NAME
- 3 CSNAME

**\definesteconversie** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...]

- 1 SPRACHE
- 2 NAME
- 3 TEXT

**\definesteculoare** [<sup>1</sup>...] [<sup>2</sup>...,...]

- 1 NAME
- 2 r = NUMMER
- g = NUMMER
- b = NUMMER
- c = NUMMER
- m = NUMMER
- y = NUMMER
- k = NUMMER
- h = NUMMER
- s = NUMMER
- v = NUMMER
- x = NUMMER
- a = NUMMER niciunul normal multiply ecran overlay softlight hardlight colordodge colorburn darken lighten difference exclusion hue saturation culoare luminosity
- t = NUMMER

**\definesteculoare** [<sup>1</sup>...] [<sup>2</sup>...]

- 1 NAME
- 2 COLOR

**\definestedescriere** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...<sup>3</sup>...,...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupdescription

**\definestedimensiunehartie** [<sup>1</sup>...] [<sup>2</sup>...,...<sup>2</sup>...,...]

- 1 NAME
- 2 latime = DIMENSION  
inaltime = DIMENSION  
sus = BEFEHL  
jos = BEFEHL  
stanga = BEFEHL  
dreapta = BEFEHL  
distanta = DIMENSION  
pagina = inherits: \seteazadimensiunihartie  
hartie = inherits: \seteazadimensiunihartie

**\definestedimensiunehartie** [<sup>1</sup>...] [<sup>2</sup>...,...<sup>2</sup>...] [<sup>3</sup>...,...<sup>3</sup>...,...]

- 1 NAME
- 2 inherits: \seteazadimensiunihartie
- 3 inherits: \seteazadimensiunihartie

**\definesteenumerare** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...<sup>3</sup>...,...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupenumeration

**\definesteeticheta** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...<sup>3</sup>...,...]

- 1 NAME
- 2 NAME
- 3 inherits: \setuplabel

**\definestefloat** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...<sup>3</sup>...,...]

- 1 SINGULAR
  - 2 SINGULAR PLURAL
  - 3 inherits: \seteazafloat
- instances: chemical figure table intermezzo graphic

**\definestefloat** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...]

- 1 SINGULAR
  - 2 PLURAL
  - 3 SINGULAR
- instances: chemical figure table intermezzo graphic

**\definestefont** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...<sup>3</sup>...,...]

- 1 NAME
- 2 FONT
- 3 inherits: \seteazaspatiuinterliniar

```

\definestefonttext [...] [...] [...] [...]
1 NAME implicit
2 NAME DIMENSION
3 rm ss tt hw cg
4 tf = FILE
bf = FILE
it = FILE
sl = FILE
bi = FILE
bs = FILE
sc = FILE
mr = FILE
mrlr = FILE
mrrl = FILE
mb = FILE
mblr = FILE
mbrl = FILE

```

```

\definestefonttext [...] [...] [...] [...]
1 NAME implicit
2 NAME DIMENSION
3 rm ss tt hw cg
4 NAME

```

```

\definestefont [...] [...] [...]
1 NAME
2 FONT
3 NAME

```

```

\definesteformatreferinte [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupreferenceformat

```

```

\definestegrupculori [...] [...] [x:y:z,...]
1 NAME
2 gri rgb cmyk spot
3 TRIPLET

```

```

\definestehbox [...] [...]
1 NAME
2 DIMENSION

```

```

\definesteinconjurare [...] [...] [...]
1 NAME
2 NAME
3 inherits: \seteazainconjurat

```

```

\definestelista [...] [...] [...]
1 NAME
2 LISTE
3 inherits: \seteazalista

```

```

\definestelistacombinata [...] [...] [...]
1 NAME
2 LISTE
3 inherits: \seteazalistacombinata

```

```

\definestemakeup [...] [...] [...]
1 NAME
2 NAME
3 inherits: \seteazamakeup

```

```

\definestemarcaje [...] [...] [...]
1 NAME
2 BESCHRIFTUNG
3 inherits: \seteazamarcaje

```

```

\definestemediulfonttext [...] [...] [...]
1 NAME OPT OPT
2 implicit DIMENSION
3 mare = DIMENSION NUMBER
mic = DIMENSION NUMBER
a = DIMENSION NUMBER
b = DIMENSION NUMBER
c = DIMENSION NUMBER
d = DIMENSION NUMBER
text = DIMENSION NUMBER
x = DIMENSION NUMBER
xx = DIMENSION NUMBER
script = DIMENSION NUMBER
scriptscript = DIMENSION NUMBER
spatiereinterliniara = DIMENSION
em = inclinat italic STYLE BEFEHL
* = NUMBER

```

```

\definestemeniuiinteractiune [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \seteazameniuiinteractiune

```

```

\definesteoverlay [...] [...] [...]
1 NAME OPT
2 NAME
3 BEFEHL

```

```

\definestepaleta [...] [...]
1 NAME
2 NAME = COLOR

```

```

\definestepaleta [...] [...]
1 NAME
2 NAME

```

```

\definesteparagraf [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \seteazaparagrafe

```

```

\definesteprofil [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupprofile

```

```

\definesteprogram [...] [...] [...]
1 NAME OPT
2 TEXT
3 TEXT

```

```

\definestereferinte [...] [...]
1 NAME
2 REFERENCE

```

```

\definesteregistru [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \seteazaregistru

```

```

\definestesablontabel [...] [...] [...]
1 NAME OPT OPT
2 TEMPLATE
3 NAME
4 NAME

```

<pre> \definestesectione [...] *   NAME </pre>
<pre> \definestesimbol [...] [...] [...] 1   NAME          OPT 2   NAME 3   BEFEHL </pre>
<pre> \definestesimbolfigura [...] [...] [...] [...] 1   NAME          OPT 2   FILE NAME 3   inherits: \figuraexterna </pre>
<pre> \definestesinonim [...] [...] [...] [...] 1   SINGULAR          OPT      OPT 2   PLURAL 3   CSNAME 4   CSNAME </pre>
<pre> \definestesinonimfont [...] [...] [...] [...] 1   NAME          OPT 2   FONT 3   features      = NAME    fallbacks     = NAME    goodies        = NAME    designsize     = auto implicit </pre>
<pre> \definestesortare [...] [...] [...] 1   SINGULAR          OPT 2   PLURAL 3   niciunul CSNAME </pre>
<pre> \definestestartstop [...] [...] [...] [...] 1   NAME          OPT      OPT 2   NAME 3   inherits: \setupstartstop </pre>
<pre> \definestestil [...] [...] [...] [...] 1   NAME          OPT      OPT 2   NAME 3   inherits: \setupstyle </pre>
<pre> \definestestilfont [...] [...] [...] 1   NAME 2   NAME </pre>
<pre> \definestestivacampuri [...] [...] [...] [...] 1   NAME          OPT 2   NAME 3   inherits: \setupfieldcategory </pre>
<pre> \definestesubcamp [...] [...] [...] [...] 1   NAME 2   NAME 3   NAME </pre>
<pre> \definestetabulatori [...] [...] [...] [...] 1   NAME          OPT      OPT 2   NAME 3   TEMPLATE </pre>



<pre> \definestetext [...] [...] [...] [...] [...] [...] [...] 1  NAME 2  sus antet text subsol subsol 3  text margine bordura 4  data numarpagina BESCHRIFTUNG TEXT BEFEHL 5  data numarpagina BESCHRIFTUNG TEXT BEFEHL 6  data numarpagina BESCHRIFTUNG TEXT BEFEHL 7  data numarpagina BESCHRIFTUNG TEXT BEFEHL </pre>
<pre> \definestetexteinconjugate [...] [...] [...] 1  NAME 2  inherits: \setupframedtext </pre>
<pre> \definestetextinconjurat [...] [...] [...] 1  NAME 2  NAME 3  inherits: \setupframedtext </pre>
<pre> \definestetyping [...] [...] [...] 1  NAME 2  NAME 3  inherits: \seteazatyping </pre>
<pre> \definestyleinstance [...] [...] [...] 1  NAME 2  rm ss tt mm hw cg 3  tf bf it sl bi bs sc 4  BEFEHL </pre>
<pre> \definesubformula [...] [...] [...] 1  NAME 2  NAME 3  inherits: \setupsubformula </pre>
<pre> \definesynonym [...] [...] [...] {...} {...} 1  da nu 2  SINGULAR 3  NAME 4  TEXT 5  CONTENT </pre>
<pre> \definesystemattribute [...] [...] 1  NAME 2  local global public private pickup </pre>
<pre> \definesystemconstant {...} *  NAME </pre>
<pre> \definesystemvariable {...} *  NAME </pre>
<pre> \defineTABLEsetup [...] [...] 1  NAME 2  inherits: \setupTABLE </pre>
<pre> \definetabulation [...] [...] [...] 1  NAME 2  NAME 3  inherits: \setuptabulation </pre>
<pre> \definetextbackground [...] [...] [...] 1  NAME 2  NAME 3  inherits: \setuptextbackground </pre>

<pre> \definetextflow [...] [...] [...] [...] 1  NAME 2  NAME 3  inherits: \setuptextflow </pre>
<pre> \definetokenlist [...] *  NAME </pre>
<pre> \definetooltip [...] [...] [...] [...] 1  NAME 2  NAME 3  inherits: \setuptooltip </pre>
<pre> \definetransparency [...] [...] 1  NAME 2  NUMMER </pre>
<pre> \definetransparency [...] [...] 1  NAME 2  a = NUMMER niciunul normal multiply ecran overlay softlight hardlight colordodge colorburn darken lighten     difference exclusion hue saturation culoare luminosity     t = NUMMER </pre>
<pre> \definetransparency [...] [...] 1  NAME 2  NAME </pre>
<pre> \definetwopasslist {...} *  NAME </pre>
<pre> \definetype [...] [...] [...] [...] 1  NAME 2  NAME 3  inherits: \seteazatype </pre>
<pre> \definetypeface [...] [...] [...] [...] [...] [...] [...] 1  NAME 2  rm ss tt mm hw cg 3  serif sans mono math handwriting calligraphy 4  NAME 5  implicit dtp 6  rscale      = auto NUMMER    features    = NAME    fallbacks   = NAME    goodies     = NAME    designsize  = auto implicit    directie    = ambele </pre>
<pre> \definetypescriptprefix [...] [...] 1  NAME 2  TEXT </pre>
<pre> \definetypescriptsynonym [...] [...] 1  NAME 2  TEXT </pre>
<pre> \definetypesetting [...] [...] [...] [...] 1  NAME 2  TEXT 3  inherits: \setupexternalfigure </pre>
<pre> \defineunit [...] [...] [...] [...] 1  NAME 2  NAME 3  inherits: \setupunit </pre>

<code>\defineuserdata [...]<sup>1</sup> [...]<sup>2</sup> [...,...<sup>3</sup>...,...]</code> 1 NAME OPT OPT 2 NAME 3 inherits: \setupuserdata
<code>\defineuserdataalternative [...]<sup>1</sup> [...]<sup>2</sup> [...,...<sup>3</sup>...,...]</code> 1 NAME OPT OPT 2 NAME 3 inherits: \setupuserdataalternative
<code>\defineviewerlayer [...]<sup>1</sup> [...]<sup>2</sup> [...,...<sup>3</sup>...,...]</code> 1 NAME OPT OPT 2 NAME 3 inherits: \setupviewerlayer
<code>\definevspace [...]<sup>1</sup> [...]<sup>2</sup> [...]<sup>3</sup></code> 1 NAME OPT 2 NAME 3 DIMENSION
<code>\definevspacing [...]<sup>1</sup> [...]<sup>2</sup></code> 1 NAME 2 inherits: \vspacing
<code>\definevspacingamount [...]<sup>1</sup> [...]<sup>2</sup> [...]<sup>3</sup></code> 1 NAME OPT OPT 2 DIMENSION 3 DIMENSION
<code>\definetable [...]<sup>1</sup> [...]<sup>2</sup> [...,...<sup>3</sup>...,...]</code> 1 NAME OPT OPT 2 NAME 3 inherits: \setupxtable
<code>\delimited [...]<sup>1</sup> [...]<sup>2</sup> {...}<sup>3</sup></code> 1 NAME OPT 2 SPRACHE 3 CONTENT
<code>\delimitedtext [...]<sup>1</sup> [...]<sup>2</sup> {...}<sup>3</sup></code> 1 NAME OPT 2 SPRACHE 3 CONTENT
<code>\DELIMITEDTEXT [...]<sup>1</sup> {...}<sup>2</sup></code> 1 SPRACHE OPT 2 CONTENT instances: quotation quote blockquote speech aside
<code>\aside [...]<sup>1</sup> {...}<sup>2</sup></code> 1 SPRACHE OPT 2 CONTENT
<code>\blockquote [...]<sup>1</sup> {...}<sup>2</sup></code> 1 SPRACHE OPT 2 CONTENT
<code>\quotation [...]<sup>1</sup> {...}<sup>2</sup></code> 1 SPRACHE OPT 2 CONTENT
<code>\quote [...]<sup>1</sup> {...}<sup>2</sup></code> 1 SPRACHE OPT 2 CONTENT

<code>\speech [...] {...}</code> 1    SPRACHE <small>OPT</small> 2    CONTENT
<code>\depthofstring {...}</code> *    TEXT
<code>\depthonlybox {...}</code> *    CONTENT
<code>\depthspanningtext {...} {...} {...}</code> 1    TEXT 2    DIMENSION 3    FONT
<code>\depthstrut</code>
<code>\DESCRIERE [...,<sup>1</sup>...] {...<sup>2</sup>} ...<sup>3</sup> \par</code> 1    REFERENCE <small>OPT</small> <small>OPT</small> 2    TEXT 3    CONTENT
<code>\despre [...]</code> *    REFERENCE
<code>\determinacaracteristicilelistei [...,<sup>1</sup>...] [...,<sup>2</sup>...<sup>2</sup>...]</code> 1    LISTE 2    inherits: \seteazalista <small>OPT</small>
<code>\determinacaracteristiciregistru [...] [...,<sup>2</sup>...<sup>2</sup>...]</code> 1    NAME <small>OPT</small> 2    language    = implicit DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scn SPRACHE metoda        = implicit inainte dupa primul ultim ch mm zm pm mc zc pc uc numberorder   = numere compress       = da nu tot criteriu       = local text curent precedent tot ABSCHNITT
<code>\determinanumartitlu [...]</code> *    ABSCHNITT
<code>\determinenoflines {...}</code> *    CONTENT
<code>\devanagarinumerals {...}</code> *    NUMMER
<code>\digits {...}</code> *    NUMMER
<code>\digits ...</code> *    NUMMER
<code>\dimensiontocount {...} \<sup>2</sup>...</code> 1    DIMENSION 2    CSNAME
<code>\din [...]</code> *    REFERENCE

\directboxfromcache {...} {...} 1 NAME 2 NUMMER TEXT
\directcolor [...] * COLOR
\directcolored [...]{...}{...} * inherits: \definesteculoare
\directcolored [...] * COLOR
\directconvertedcounter {...} {...} 1 NAME 2 primul precedent urmatorul ultim numar
\directcopyboxfromcache {...} {...} 1 NAME 2 NUMMER TEXT
\directdummysparameter {...} * KEY
\directgetboxllx ... * CSNAME NUMMER
\directgetboxlly ... * CSNAME NUMMER
\directhighlight {...} {...} 1 NAME 2 TEXT
\directlocalframed [...]{...} 1 NAME 2 CONTENT
\directluacode {...} * BEFEHL
\directselect {...} {...} {...} {...} {...} {...} 1 NAME 2 CONTENT 3 CONTENT 4 CONTENT 5 CONTENT 6 CONTENT
\directsetbar {...} * NAME
\directsetup {...} * NAME
\directsymbol {...} {...} 1 NAME 2 NAME

$\backslash\mathrm{directvspacing}\{...,*,...\}$ * inherits: $\backslash\mathrm{vspacing}$
$\backslash\mathrm{dis}\{...\}$ * CONTENT
$\backslash\mathrm{disabledirectives}\{...,*,...\}$ * NAME
$\backslash\mathrm{disableexperiments}\{...,*,...\}$ * NAME
$\backslash\mathrm{disablemode}\{...,*,...\}$ * NAME
$\backslash\mathrm{disableoutputstream}$
$\backslash\mathrm{disableparpositions}$
$\backslash\mathrm{disableregime}$
$\backslash\mathrm{disabletrackers}\{...,*,...\}$ * NAME
$\backslash\mathrm{displaymath}\{...\}$ * CONTENT
$\backslash\mathrm{displaymathematics}\{...\}$ * CONTENT
$\backslash\mathrm{displaymessage}\{...\}$ * TEXT
$\backslash\mathrm{distributedhsize}\{...\}^1\{...\}^2\{...\}^3$ 1 DIMENSION 2 DIMENSION 3 NUMMER
$\backslash\mathrm{dividedsize}\{...\}^1\{...\}^2\{...\}^3$ 1 DIMENSION 2 DIMENSION 3 NUMMER
$\backslash\mathrm{doadaptleftskip}\{...\}$ * da nu standard DIMENSION
$\backslash\mathrm{doadaptrightskip}\{...\}$ * da nu standard DIMENSION
$\backslash\mathrm{doaddfeature}\{...,*,...\}$ * NAME
$\backslash\mathrm{doassign}\{...\}^1\{...\}^2$ 1 TEXT 2 KEY = VALUE

<code>\doassignempty [.<sup>1</sup>.] [..<sup>2</sup>..]</code> 1 TEXT 2 KEY = VALUE
<code>\doboundtext {...} {...} {...}</code> 1 TEXT 2 DIMENSION 3 BEFEHL
<code>\docheckassignment {...}</code> * TEXT
<code>\docheckedpagestate {.<sup>1</sup>.} {..<sup>2</sup>.} {...} {..<sup>4</sup>.} {..<sup>5</sup>.} {..<sup>6</sup>.} {..<sup>7</sup>.}</code> 1 REFERENCE 2 BEFEHL 3 BEFEHL 4 BEFEHL 5 BEFEHL 6 BEFEHL 7 BEFEHL
<code>\docheckedpair {...,*...}</code> * TEXT
<code>\documentvariable {...}</code> * KEY
<code>\dodoubleargument \.<sup>1</sup>. [..<sup>2</sup>.] [..<sup>3</sup>.]</code> 1 CSNAME 2 TEXT 3 TEXT
<code>\dodoubleargumentwithset \.<sup>1</sup>. [...,<sup>2</sup>...] [..<sup>3</sup>.]</code> 1 CSNAME 2 TEXT 3 TEXT
<code>\dodoubleempty \.<sup>1</sup>. [<sup>2</sup>...] [<sup>3</sup>...]</code> 1 CSNAME OPT OPT 2 TEXT 3 TEXT
<code>\dodoubleemptywithset \.<sup>1</sup>. [...,<sup>2</sup>...] [<sup>3</sup>...]</code> 1 CSNAME OPT OPT 2 TEXT 3 TEXT
<code>\dodoublegroupempty \.<sup>1</sup>. {..<sup>2</sup>.} {..<sup>3</sup>.}</code> 1 CSNAME OPT OPT 2 TEXT 3 TEXT
<code>\doeassign [.<sup>1</sup>.] [..<sup>2</sup>..]</code> 1 TEXT 2 KEY = VALUE
<code>\doexpandedrecurse {...} {..<sup>2</sup>.}</code> 1 NUMMER 2 BEFEHL
<code>\dofastloops {...} \.<sup>2</sup>.</code> 1 NUMMER 2 CSNAME

\dogetattribute {...} * NAME
\dogetattributeid {...} * NAME
\dogetcommacommandelement <sup>1</sup> ... \from <sup>2</sup> ... \to <sup>3</sup> ... 1 NUMBER 2 TEXT 3 CSNAME
\dogobbledoubleempty [ <sup>1</sup> ...] [ <sup>2</sup> ...] 1 TEXT OPT OPT 2 TEXT
\dogobblesingleempty [...] * TEXT OPT
\doif {... <sup>1</sup> } {... <sup>2</sup> } {... <sup>3</sup> } 1 CONTENT 2 CONTENT 3 TRUE
\doifallcommon {..., <sup>1</sup> ...} {..., <sup>2</sup> ...} {... <sup>3</sup> } 1 TEXT 2 TEXT 3 TRUE
\doifallcommonelse {..., <sup>1</sup> ...} {..., <sup>2</sup> ...} {... <sup>3</sup> } {... <sup>4</sup> } 1 TEXT 2 TEXT 3 TRUE 4 FALSE
\doifalldefinedelse {..., <sup>1</sup> ...} {... <sup>2</sup> } {... <sup>3</sup> } 1 NAME 2 TRUE 3 FALSE
\doifallmodes {..., <sup>1</sup> ...} {... <sup>2</sup> } {... <sup>3</sup> } 1 NAME 2 TRUE 3 FALSE
\doifallmodeselse {..., <sup>1</sup> ...} {... <sup>2</sup> } {... <sup>3</sup> } 1 NAME 2 TRUE 3 FALSE
\doifassignmentelse {... <sup>1</sup> } {... <sup>2</sup> } {... <sup>3</sup> } 1 TEXT 2 TRUE 3 FALSE
\doifassignmentelsecs {... <sup>1</sup> } \ <sup>2</sup> ... \ <sup>3</sup> ... 1 TEXT 2 CSNAME 3 CSNAME
\doifblackelse {... <sup>1</sup> } {... <sup>2</sup> } {... <sup>3</sup> } 1 COLOR 2 TRUE 3 FALSE



`\doifbothsides {...} {...} {...}`

1 BEFEHL  
2 BEFEHL  
3 BEFEHL

`\doifbothsidesoverruled {...} {...} {...}`

1 BEFEHL  
2 BEFEHL  
3 BEFEHL

`\doifboxelse {...} {...} {...} {...}`

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

`\doifbufferelse {...} {...} {...}`

1 BUFFER  
2 TRUE  
3 FALSE

`\doifcolor {...} {...}`

1 COLOR  
2 TRUE

`\doifcolorelse {...} {...} {...}`

1 COLOR  
2 TRUE  
3 FALSE

`\doifcommandhandler \... {...} {...}`

1 CSNAME  
2 NAME  
3 TRUE

`\doifcommandhandlerelse \... {...} {...} {...}`

1 CSNAME  
2 NAME  
3 TRUE  
4 FALSE

`\doifcommon {...,1...} {...,2...} {...3}`

1 TEXT  
2 TEXT  
3 TRUE

`\doifcommonelse {...,1...} {...,2...} {...3} {...4}`

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

`\doifcontent {...} {...} {...} \...4 {...5}`

1 BEFEHL  
2 BEFEHL  
3 BEFEHL  
4 CSNAME  
5 CONTENT

`\doifconversiondefinedelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

\doifconversionnumberelse {...} {...} {...} {...}

1 NAME  
2 NUMMER  
3 TRUE  
4 FALSE

\doifcounter {...} {...}

1 NAME  
2 TRUE

\doifcounterelse {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifcurrentfonthasfeatureelse {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifdefined {...} {...}

1 NAME  
2 TRUE

\doifdefinedcounter {...} {...}

1 NAME  
2 TRUE

\doifdefinedcounterelse {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifdefinedelse {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifdimensionelse {...} {...} {...}

1 TEXT  
2 TRUE  
3 FALSE

\doifdimenstringelse {...} {...} {...}

1 TEXT  
2 TRUE  
3 FALSE

\doifdocumentargument {...} {...}

1 NAME  
2 TRUE

\doifdocumentargumentelse {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifdocumentfilename {...} {...}

1 NUMMER  
2 TRUE

`\doifdocumentfilenameelse {...} {...} {...}`

1    NUMBER  
2    TRUE  
3    FALSE

`\doifdocumentvariable {...} {...}`

1    KEY  
2    TRUE

`\doifdocumentvariableelse {...} {...} {...}`

1    KEY  
2    TRUE  
3    FALSE

`\doifdrawingblackelse {...} {...}`

1    TRUE  
2    FALSE

`\doifelse {...} {...} {...} {...}`

1    CONTENT  
2    CONTENT  
3    TRUE  
4    FALSE

`\doifelseallcommon {...,1...} {...,2...} {...} {...4}`

1    TEXT  
2    TEXT  
3    TRUE  
4    FALSE

`\doifelsealldefined {...,1...} {...} {...}`

1    NAME  
2    TRUE  
3    FALSE

`\doifelseallmodes {...,1...} {...} {...}`

1    NAME  
2    TRUE  
3    FALSE

`\doifelseassignment {...} {...} {...}`

1    TEXT  
2    TRUE  
3    FALSE

`\doifelseassignmentcs {...} \2... \3...`

1    TEXT  
2    CSNAME  
3    CSNAME

`\doifelseblack {...} {...} {...}`

1    COLOR  
2    TRUE  
3    FALSE

`\doifelsebox {...} {...} {...} {...}`

1    NAME  
2    NAME  
3    TRUE  
4    FALSE

\doifelseboxincache {...} {...} {...} {...}

1 NAME  
2 NUMMER TEXT  
3 TRUE  
4 FALSE

\doifelsebuffer {...} {...} {...}

1 BUFFER  
2 TRUE  
3 FALSE

\doifelsecolor {...} {...} {...}

1 COLOR  
2 TRUE  
3 FALSE

\doifelsecommandhandler \... {...} {...} {...}

1 CSNAME  
2 NAME  
3 TRUE  
4 FALSE

\doifelsecommon {...,<sup>1</sup>...} {...,<sup>2</sup>...} {...} {...<sup>4</sup>}

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

\doifelseconversiondefined {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelseconversionnumber {...} {...} {...} {...<sup>4</sup>}

1 NAME  
2 NUMMER  
3 TRUE  
4 FALSE

\doifelsecounter {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsecurrentfonthasfeature {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsecurrentsortingtonused {...} {...}

1 TRUE  
2 FALSE

\doifelsecurrentsynonymshown {...} {...}

1 TRUE  
2 FALSE

\doifelsecurrentsynonymused {...} {...}

1 TRUE  
2 FALSE

\doifelsedefined {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsedefinedcounter {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsedimension {...} {...} {...}

1 TEXT  
2 TRUE  
3 FALSE

\doifelsedimenstring {...} {...} {...}

1 TEXT  
2 TRUE  
3 FALSE

\doifelsedocumentargument {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsedocumentfilename {...} {...} {...}

1 NUMBER  
2 TRUE  
3 FALSE

\doifelsedocumentvariable {...} {...} {...}

1 KEY  
2 TRUE  
3 FALSE

\doifelsedrawingblack {...} {...}

1 TRUE  
2 FALSE

\doifelseempty {...} {...} {...}

1 CONTENT  
2 TRUE  
3 FALSE

\doifelseemptyvalue {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelseemptyvariable {...} {...} {...} {...}

1 NAME  
2 KEY  
3 TRUE  
4 FALSE

\doifelseenv {...} {...} {...}

1 KEY  
2 TRUE  
3 FALSE

\doifelsefastoptionalcheck {...} {...}

1 TRUE  
2 FALSE

\doifelsefastoptionalcheckcs \... \...

1 CSNAME  
2 CSNAME

`\doifelsefieldbody {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifelsefieldcategory {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifelsefigure {...} {...} {...}`

1 FILE  
2 TRUE  
3 FALSE

`\doifelsefile {...} {...} {...}`

1 FILE  
2 TRUE  
3 FALSE

`\doifelsefiledefined {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifelsefileexists {...} {...} {...}`

1 FILE  
2 TRUE  
3 FALSE

`\doifelsefirstchar {...} {...} {...} {...}`

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

`\doifelseflagged {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifelsefontchar {...} {...} {...} {...}`

1 FONT  
2 NUMBER  
3 TRUE  
4 FALSE

`\doifelsefontfeature {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifelsefontpresent {...} {...} {...}`

1 FONT  
2 TRUE  
3 FALSE

`\doifelsefontsynonym {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

\doifelseframed \<sup>1</sup>... {<sup>2</sup>...} {<sup>3</sup>...}

1 CSNAME  
2 TRUE  
3 FALSE

\doifelsehasspace {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...}

1 TEXT  
2 TRUE  
3 FALSE

\doifelsehelp {<sup>1</sup>...} {<sup>2</sup>...}

1 TRUE  
2 FALSE

\doifelseincsname {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...} {<sup>4</sup>...}

1 TEXT  
2 CSNAME  
3 TRUE  
4 FALSE

\doifelseinelement {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...}

1 NAME  
2 TRUE  
3 FALSE

\doifelseinputfile {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...}

1 FILE  
2 TRUE  
3 FALSE

\doifelseinsertion {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...}

1 NAME  
2 TRUE  
3 FALSE

\doifelseinset {<sup>1</sup>...} {<sup>2</sup>...,...} {<sup>3</sup>...} {<sup>4</sup>...}

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

\doifelseinstring {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...} {<sup>4</sup>...}

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

\doifelseinsymbolset {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...} {<sup>4</sup>...}

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

\doifelseintoks {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...} {<sup>4</sup>...}

1 BEFEHL  
2 BEFEHL  
3 TRUE  
4 FALSE

\doifelseintwopassdata {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...} {<sup>4</sup>...}

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

\doifelseitalic {...} {...}

1 TRUE  
2 FALSE

\doifelselanguage {...} {...} {...}

1 SPRACHE  
2 TRUE  
3 FALSE

\doifelselayerdata {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelselayoutdefined {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelselayoutsomeline {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelselayouttextline {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelseleapyear {...} {...} {...}

1 NUMMER  
2 TRUE  
3 FALSE

\doifelselist {...} {...} {...}

1 LISTE  
2 TRUE  
3 FALSE

\doifelselocation {...} {...}

1 TRUE  
2 FALSE

\doifelselocfile {...} {...} {...}

1 FILE  
2 TRUE  
3 FALSE

\doifelseMPgraphic {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsemainfloatbody {...} {...}

1 TRUE  
2 FALSE

\doifelsemarkedpage {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE



\doifelsemarking {...} {...} {...} 1    BESCHRIFTUNG 2    TRUE 3    FALSE
\doifelsemeaning \ <sup>1</sup> ... \ <sup>2</sup> ... {...} {...} 1    CSNAME 2    CSNAME 3    TRUE 4    FALSE
\doifelsemessage {...} {...} {...} {...} 1    NAME 2    NAME NUMMER 3    TRUE 4    FALSE
\doifelsemode {..., <sup>1</sup> ...} {...} {...} 1    NAME 2    TRUE 3    FALSE
\doifelsenextbgroup {...} {...} 1    TRUE 2    FALSE
\doifelsenextbgroupcs \ <sup>1</sup> ... \ <sup>2</sup> ... 1    CSNAME 2    CSNAME
\doifelsenextchar {...} {...} {...} 1    CHARACTER 2    TRUE 3    FALSE
\doifelsenextoptional {...} {...} 1    TRUE 2    FALSE
\doifelsenextoptionalcs \ <sup>1</sup> ... \ <sup>2</sup> ... 1    CSNAME 2    CSNAME
\doifelsenextparenthesis {...} {...} 1    TRUE 2    FALSE
\doifelsenonzeropositive {...} {...} {...} 1    NUMMER 2    TRUE 3    FALSE
\doifelsenoteonsamepage {...} {...} {...} 1    NAME 2    TRUE 3    FALSE
\doifelsenothing {...} {...} {...} 1    TEXT 2    TRUE 3    FALSE

<pre> \doifelsenumber {...} {...} {...} 1  TEXT 2  TRUE 3  FALSE </pre>
<pre> \doifelseobjectfound {...} {...} {...} {...} 1  NAME 2  NAME 3  TRUE 4  FALSE </pre>
<pre> \doifelseobjectreferencefound {...} {...} {...} {...} 1  NAME 2  NAME 3  TRUE 4  FALSE </pre>
<pre> \doifelseoddpagel {^1} {^2} 1  BEFEHL 2  BEFEHL </pre>
<pre> \doifelseoddpagelfloat {...} {...} 1  TRUE 2  FALSE </pre>
<pre> \doifelseoldercontext {...} {...} {...} 1  NUMMER 2  TRUE 3  FALSE </pre>
<pre> \doifelseolderversion {...} {...} {...} {...} 1  NUMMER 2  NUMMER 3  TRUE 4  FALSE </pre>
<pre> \doifelseoverlapping {...} {...} {...} {...} 1  NAME 2  NAME 3  TRUE 4  FALSE </pre>
<pre> \doifelseoverlay {...} {...} {...} 1  NAME 2  TRUE 3  FALSE </pre>
<pre> \doifelseparallel {...} {...^2,...} {...} {...} 1  NAME 2  NAME tot 3  TRUE 4  FALSE </pre>
<pre> \doifelseparentfile {...} {...} {...} 1  FILE 2  TRUE 3  FALSE </pre>
<pre> \doifelsepath {...} {...} {...} 1  PATH 2  TRUE 3  FALSE </pre>

\doifelsepathexists {...} {...} {...}

1 PATH  
2 TRUE  
3 FALSE

\doifelsepatterns {...} {...} {...}

1 SPRACHE  
2 TRUE  
3 FALSE

\doifelseposition {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsepositionaction {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsepositiononpage {...} {...} {...} {...}

1 NAME  
2 NUMMER  
3 TRUE  
4 FALSE

\doifelsepositionsonsamepage {...,<sup>1</sup>...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsepositionsonthispage {...,<sup>1</sup>...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsepositionsused {...} {...}

1 TRUE  
2 FALSE

\doifelserreferencefound {...} {...} {...}

1 REFERENCE  
2 TRUE  
3 FALSE

\doifelserrightpage {...} {...}

1 TRUE  
2 FALSE

\doifelserrightpagefloat {...} {...}

1 TRUE  
2 FALSE

\doifelserrighttoleftinbox ...<sup>1</sup> {...} {...}

1 CSNAME NUMMER  
2 TRUE  
3 FALSE

\doifelsesamelinereference {...} {...} {...}

1 REFERENCE  
2 TRUE  
3 FALSE

```
\doifelsesamestring {...} {...} {...} {...}
1 TEXT
2 TEXT
3 TRUE
4 FALSE
```

```
\doifelsesetups {...} {...} {...}
1 NAME
2 TRUE
3 FALSE
```

```
\doifelsesomebackground {...} {...} {...}
1 NAME
2 TRUE
3 FALSE
```

```
\doifelsesomespace {...} {...} {...}
1 TEXT
2 TRUE
3 FALSE
```

```
\doifelsesomething {...} {...} {...}
1 TEXT
2 TRUE
3 FALSE
```

```
\doifelsesometoks \... {...} {...}
1 CSNAME
2 TRUE
3 FALSE
```

```
\doifelsestringinstring {...} {...} {...} {...}
1 TEXT
2 TEXT
3 TRUE
4 FALSE
```

```
\doifelsestructurelisthasnumber {...} {...}
1 TRUE
2 FALSE
```

```
\doifelsestructurelisthaspage {...} {...}
1 TRUE
2 FALSE
```

```
\doifelsesymboldefined {...} {...} {...}
1 NAME
2 TRUE
3 FALSE
```

```
\doifelsesymbolset {...} {...} {...}
1 NAME
2 TRUE
3 FALSE
```

```
\doifelsetext {...} {...} {...}
1 TEXT
2 TRUE
3 FALSE
```

```
\doifelsetextflow {...} {...} {...}
1 NAME
2 TRUE
3 FALSE
```

<pre> \doifsettextflowcollector {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifsettopofpage {...} {...} 1 TRUE 2 FALSE </pre>
<pre> \doifsettypingfile {...} {...} {...} 1 FILE 2 TRUE 3 FALSE </pre>
<pre> \doifelseundefined {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifelseurldefined {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifelsevalue {...} {...} {...} {...} 1 NAME 2 TEXT 3 TRUE 4 FALSE </pre>
<pre> \doifelsevaluenothing {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifelsevariable {...} {...} {...} {...} 1 NAME 2 KEY 3 TRUE 4 FALSE </pre>
<pre> \doifempty {...} {...} 1 CONTENT 2 TRUE </pre>
<pre> \doifemptyelse {...} {...} {...} 1 CONTENT 2 TRUE 3 FALSE </pre>
<pre> \doifemptytoks \... {...} 1 CSNAME 2 TRUE </pre>
<pre> \doifemptyvalue {...} {...} 1 NAME 2 TRUE </pre>
<pre> \doifemptyvalueelse {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>

`\doifemptyvariable {...} {...} {...}`

1 NAME  
2 KEY  
3 TRUE

`\doifemptyvariableelse {...} {...} {...} {...}`

1 NAME  
2 KEY  
3 TRUE  
4 FALSE

`\doifenv {...} {...}`

1 KEY  
2 TRUE

`\doifenvelse {...} {...} {...}`

1 KEY  
2 TRUE  
3 FALSE

`\doiffastoptionalcheckcselse \1... \2...`

1 CSNAME  
2 CSNAME

`\doiffastoptionalcheckelse {...} {...}`

1 TRUE  
2 FALSE

`\doiffielddbbodyelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doiffielddcategoryelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doiffigureelse {...} {...} {...}`

1 FILE  
2 TRUE  
3 FALSE

`\doiffile {...} {...}`

1 FILE  
2 TRUE

`\doiffiledefinedelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doiffileelse {...} {...} {...}`

1 FILE  
2 TRUE  
3 FALSE

`\doiffileexistselse {...} {...} {...}`

1 FILE  
2 TRUE  
3 FALSE

```
\doiffirstcharelse {...} {...} {...} {...}
1 TEXT
2 TEXT
3 TRUE
4 FALSE
```

```
\doiffaggedelse {...} {...} {...}
1 NAME
2 TRUE
3 FALSE
```

```
\doiffontcharelse {...} {...} {...} {...}
1 FONT
2 NUMMER
3 TRUE
4 FALSE
```

```
\doiffontfeatureelse {...} {...} {...}
1 NAME
2 TRUE
3 FALSE
```

```
\doiffontpresentelse {...} {...} {...}
1 FONT
2 TRUE
3 FALSE
```

```
\doiffontsynonymelse {...} {...} {...}
1 NAME
2 TRUE
3 FALSE
```

```
\doifhasspaceelse {...} {...} {...}
1 TEXT
2 TRUE
3 FALSE
```

```
\doifhelpelse {...} {...}
1 TRUE
2 FALSE
```

```
\doifincsnameelse {...} {...} {...} {...}
1 TEXT
2 CSNAME
3 TRUE
4 FALSE
```

```
\doifinelementelse {...} {...} {...}
1 NAME
2 TRUE
3 FALSE
```

```
\doifinputfileelse {...} {...} {...}
1 FILE
2 TRUE
3 FALSE
```

```
\doifinsertionelse {...} {...} {...}
1 NAME
2 TRUE
3 FALSE
```

`\doifinset {...} {...,2...} {...3}`

1 TEXT  
2 TEXT  
3 TRUE

`\doifinsetelse {...} {...,2...} {...} {...4}`

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

`\doifinstring {...} {...2} {...3}`

1 TEXT  
2 TEXT  
3 TRUE

`\doifinstringelse {...} {...2} {...} {...4}`

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

`\doifinsymbolset {...} {...} {...} {...4}`

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

`\doifinsymbolsetelse {...} {...} {...} {...4}`

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

`\doifintokselse {...} {...} {...} {...4}`

1 BEFEHL  
2 BEFEHL  
3 TRUE  
4 FALSE

`\doifintwopassdataelse {...} {...} {...} {...4}`

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

`\doifitalicelse {...} {...}`

1 TRUE  
2 FALSE

`\doiflanguageelse {...} {...2} {...3}`

1 SPRACHE  
2 TRUE  
3 FALSE

`\doiflayerdataelse {...1} {...2} {...3}`

1 NAME  
2 TRUE  
3 FALSE

`\doiflayoutdefinedelse {...} {...2} {...3}`

1 NAME  
2 TRUE  
3 FALSE



`\doiflayoutsomelineelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doiflayouttextlineelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifleapyearelse {...} {...} {...}`

1 NUMBER  
2 TRUE  
3 FALSE

`\doiflistelse {...} {...} {...}`

1 LISTE  
2 TRUE  
3 FALSE

`\doiflocationelse {...} {...}`

1 TRUE  
2 FALSE

`\doiflocfileelse {...} {...} {...}`

1 FILE  
2 TRUE  
3 FALSE

`\doifMPgraphicelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifmainfloatbodyelse {...} {...}`

1 TRUE  
2 FALSE

`\doifmarkingelse {...} {...} {...}`

1 BESCHRIFTUNG  
2 TRUE  
3 FALSE

`\doifmeaningelse \... \... {...} {...}`

1 CSNAME  
2 CSNAME  
3 TRUE  
4 FALSE

`\doifmessageelse {...} {...} {...} {...}`

1 NAME  
2 NAME NUMBER  
3 TRUE  
4 FALSE

`\doifmode {...,1...} {...2}`

1 NAME  
2 TRUE

`\doifmodeelse {...,1...} {...2} {...3}`

1 NAME  
2 TRUE  
3 FALSE

<pre> \doifnextbgroupcselse \<sup>1</sup>... \<sup>2</sup>... 1 CSNAME 2 CSNAME </pre>
<pre> \doifnextbgroupelse {<sup>1</sup>...} {<sup>2</sup>...} 1 TRUE 2 FALSE </pre>
<pre> \doifnextcharelse {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...} 1 CHARACTER 2 TRUE 3 FALSE </pre>
<pre> \doifnextoptionalcselse \<sup>1</sup>... \<sup>2</sup>... 1 CSNAME 2 CSNAME </pre>
<pre> \doifnextoptionalelse {<sup>1</sup>...} {<sup>2</sup>...} 1 TRUE 2 FALSE </pre>
<pre> \doifnextparenthesiselse {<sup>1</sup>...} {<sup>2</sup>...} 1 TRUE 2 FALSE </pre>
<pre> \doifnonzeropositiveelse {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...} 1 NUMMER 2 TRUE 3 FALSE </pre>
<pre> \doifnot {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...} 1 CONTENT 2 CONTENT 3 TRUE </pre>
<pre> \doifnotallcommon {...,<sup>1</sup>...} {...,<sup>2</sup>...} {...,<sup>3</sup>...} 1 TEXT 2 TEXT 3 TRUE </pre>
<pre> \doifnotallmodes {...,<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifnotcommandhandler \<sup>1</sup>... {<sup>2</sup>...} {<sup>3</sup>...} 1 CSNAME 2 NAME 3 TRUE </pre>
<pre> \doifnotcommon {...,<sup>1</sup>...} {...,<sup>2</sup>...} {...,<sup>3</sup>...} 1 TEXT 2 TEXT 3 TRUE </pre>
<pre> \doifnotcounter {<sup>1</sup>...} {<sup>2</sup>...} 1 NAME 2 TRUE </pre>
<pre> \doifnotdocumentargument {<sup>1</sup>...} {<sup>2</sup>...} 1 NAME 2 TRUE </pre>

<pre> \doifnotdocumentfilename {...} {...} 1  NUMMER 2  TRUE </pre>
<pre> \doifnotdocumentvariable {...} {...} 1  KEY 2  TRUE </pre>
<pre> \doifnotempty {...} {...} 1  CONTENT 2  TRUE </pre>
<pre> \doifnotemptyvalue {...} {...} 1  NAME 2  TRUE </pre>
<pre> \doifnotemptyvariable {...} {...} {...} 1  NAME 2  KEY 3  TRUE </pre>
<pre> \doifnotenv {...} {...} 1  KEY 2  TRUE </pre>
<pre> \doifnoteonsamepageelse {...} {...} {...} 1  NAME 2  TRUE 3  FALSE </pre>
<pre> \doifnotescollected {...} {...} 1  NAME 2  TRUE </pre>
<pre> \doifnotfile {...} {...} 1  FILE 2  TRUE </pre>
<pre> \doifnotflagged {...} {...} 1  NAME 2  TRUE </pre>
<pre> \doifnothing {...} {...} 1  TEXT 2  TRUE </pre>
<pre> \doifnothingelse {...} {...} {...} 1  TEXT 2  TRUE 3  FALSE </pre>
<pre> \doifnotinset {...} {...<sup>2</sup>,...} {...<sup>3</sup>} 1  TEXT 2  TEXT 3  TRUE </pre>
<pre> \doifnotinsidesplitfloat {...} *  TRUE </pre>
<pre> \doifnotinstring {...} {...} {...} 1  TEXT 2  TEXT 3  TRUE </pre>

<pre> \doifnotmode {...<sup>1</sup>,...} {...<sup>2</sup>} 1  NAME 2  TRUE </pre>
<pre> \doifnotnumber {...<sup>1</sup>} {...<sup>2</sup>} 1  TEXT 2  TRUE </pre>
<pre> \doifnotsamestring {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} 1  TEXT 2  TEXT 3  TRUE </pre>
<pre> \doifnotsetups {...<sup>1</sup>} {...<sup>2</sup>} 1  NAME 2  TRUE </pre>
<pre> \doifnotvalue {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} 1  NAME 2  TEXT 3  TRUE </pre>
<pre> \doifnotvariable {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} 1  NAME 2  KEY 3  TRUE </pre>
<pre> \doifnumber {...<sup>1</sup>} {...<sup>2</sup>} 1  TEXT 2  TRUE </pre>
<pre> \doifnumberelse {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} 1  TEXT 2  TRUE 3  FALSE </pre>
<pre> \doifobjectfoundelse {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} {...<sup>4</sup>} 1  NAME 2  NAME 3  TRUE 4  FALSE </pre>
<pre> \doifobjectreferencefoundelse {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} {...<sup>4</sup>} 1  NAME 2  NAME 3  TRUE 4  FALSE </pre>
<pre> \doifoddpageelse {...<sup>1</sup>} {...<sup>2</sup>} 1  BEFEHL 2  BEFEHL </pre>
<pre> \doifoddpagefloatelse {...<sup>1</sup>} {...<sup>2</sup>} 1  TRUE 2  FALSE </pre>
<pre> \doifoldercontextelse {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} 1  NUMMER 2  TRUE 3  FALSE </pre>

```
\doifolderversionelse {...} {...} {...} {...}
1  NUMMER
2  NUMMER
3  TRUE
4  FALSE
```

```
\doifoverlappingelse {...} {...} {...} {...}
1  NAME
2  NAME
3  TRUE
4  FALSE
```

```
\doifoverlayelse {...} {...} {...}
1  NAME
2  TRUE
3  FALSE
```

```
\doifparallelelse {...} {...,2...} {...} {...}
1  NAME
2  NAME tot
3  TRUE
4  FALSE
```

```
\doifparentfileelse {...} {...} {...}
1  FILE
2  TRUE
3  FALSE
```

```
\doifpathelse {...} {...} {...}
1  PATH
2  TRUE
3  FALSE
```

```
\doifpathexistselse {...} {...} {...}
1  PATH
2  TRUE
3  FALSE
```

```
\doifpatternselse {...} {...} {...}
1  SPRACHE
2  TRUE
3  FALSE
```

```
\doifposition {...} {...} {...}
1  NAME
2  TRUE
3  FALSE
```

```
\doifpositionaction {...} {...} {...}
1  NAME
2  TRUE
3  FALSE
```

```
\doifpositionactionelse {...} {...} {...}
1  NAME
2  TRUE
3  FALSE
```

```
\doifpositionelse {...} {...} {...}
1  NAME
2  TRUE
3  FALSE
```

\doifpositiononpageelse {...} {...} {...} {...}

1 NAME  
2 NUMMER  
3 TRUE  
4 FALSE

\doifpositionsonsamepageelse {...,<sup>1</sup>...} {...<sup>2</sup>} {...<sup>3</sup>}

1 NAME  
2 TRUE  
3 FALSE

\doifpositionsonthispageelse {...,<sup>1</sup>...} {...<sup>2</sup>} {...<sup>3</sup>}

1 NAME  
2 TRUE  
3 FALSE

\doifpositionsusedelse {...<sup>1</sup>} {...<sup>2</sup>}

1 TRUE  
2 FALSE

\doifreferencefoundelse {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

1 REFERENCE  
2 TRUE  
3 FALSE

\doifrightpagefloatelse {...<sup>1</sup>} {...<sup>2</sup>}

1 TRUE  
2 FALSE

\doifrighttoleftinboxelse ...<sup>1</sup> {...<sup>2</sup>} {...<sup>3</sup>}

1 CSNAME NUMMER  
2 TRUE  
3 FALSE

\doifsamelinereferenceelse {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

1 REFERENCE  
2 TRUE  
3 FALSE

\doifsamestring {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

1 TEXT  
2 TEXT  
3 TRUE

\doifsamestringelse {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} {...<sup>4</sup>}

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

\doifsetups {...<sup>1</sup>} {...<sup>2</sup>}

1 NAME  
2 TRUE

\doifsetupselse {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

1 NAME  
2 TRUE  
3 FALSE

\doifsomebackground {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

1 NAME  
2 TRUE  
3 FALSE

`\doifsomebackgroundelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifsomespaceelse {...} {...} {...}`

1 TEXT  
2 TRUE  
3 FALSE

`\doifsomething {...} {...}`

1 TEXT  
2 TRUE

`\doifsomethingelse {...} {...} {...}`

1 TEXT  
2 TRUE  
3 FALSE

`\doifsometoks \... {...}`

1 CSNAME  
2 TRUE

`\doifsometokselse \... {...} {...}`

1 CSNAME  
2 TRUE  
3 FALSE

`\doifstringinstringelse {...} {...} {...} {...}`

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

`\doifstructurelisthasnumberelse {...} {...}`

1 TRUE  
2 FALSE

`\doifstructurelisthaspageelse {...} {...}`

1 TRUE  
2 FALSE

`\doifsymboldefinedelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifsymbolsetelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doiftext {...} {...} {...}`

1 TEXT  
2 TRUE  
3 FALSE

`\doiftextelse {...} {...} {...}`

1 TEXT  
2 TRUE  
3 FALSE

`\doiftextflowcollectorelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doiftextflowelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doiftopofpageelse {...} {...}`

1 TRUE  
2 FALSE

`\doiftypingfileelse {...} {...} {...}`

1 FILE  
2 TRUE  
3 FALSE

`\doifundefined {...} {...}`

1 NAME  
2 TRUE

`\doifundefinedcounter {...} {...}`

1 NAME  
2 TRUE

`\doifundefinedelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifunknownfontfeature {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifurldefinedelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifvalue {...} {...} {...}`

1 NAME  
2 TEXT  
3 TRUE

`\doifvalueelse {...} {...} {...} {...}`

1 NAME  
2 TEXT  
3 TRUE  
4 FALSE

`\doifvaluenothing {...} {...}`

1 NAME  
2 TRUE

`\doifvaluenothingelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE



<pre> \doifvaluesomething {...} {...} 1  NAME 2  TRUE </pre>
<pre> \doifvariable {...} {...} {...} 1  NAME 2  KEY 3  TRUE </pre>
<pre> \doifvariableelse {...} {...} {...} {...} 1  NAME 2  KEY 3  TRUE 4  FALSE </pre>
<pre> \doindentation </pre>
<pre> \dollar </pre>
<pre> \doloop {...} *  BEFEHL </pre>
<pre> \doloopoverlist {...,<sup>1</sup>...} {...<sup>2</sup>} 1  TEXT 2  BEFEHL </pre>
<pre> \donothing </pre>
<pre> \dontconvertfont </pre>
<pre> \dontleavehmode </pre>
<pre> \dontpermitspacesbetweenegroups </pre>
<pre> \dopositionaction {...} *  NAME </pre>
<pre> \doprocesslocalsetups {...,<sup>*</sup>...} *  NAME </pre>
<pre> \doquadrupleargument \<sup>1</sup>... [<sup>2</sup>...] [<sup>3</sup>...] [<sup>4</sup>...] [<sup>5</sup>...] 1  CSNAME 2  TEXT 3  TEXT 4  TEXT 5  TEXT </pre>
<pre> \doquadrupleempty \<sup>1</sup>... [<sup>2</sup>...] [<sup>3</sup>...] [<sup>4</sup>...] [<sup>5</sup>...] 1  CSNAME          OPT      OPT      OPT      OPT 2  TEXT 3  TEXT 4  TEXT 5  TEXT </pre>
<pre> \doquadruplegroupempty \<sup>1</sup>... {<sup>2</sup>...} {<sup>3</sup>...} {<sup>4</sup>...} {<sup>5</sup>...} 1  CSNAME          OPT      OPT      OPT      OPT 2  TEXT 3  TEXT 4  TEXT 5  TEXT </pre>

<p><code>\doquintupleargument \<sup>1</sup>... [<sup>2</sup>...] [<sup>3</sup>...] [<sup>4</sup>...] [<sup>5</sup>...] [<sup>6</sup>...]</code></p> <p>1 CSNAME 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT</p>
<p><code>\doquintupleempty \<sup>1</sup>... [<sup>2</sup>...] [<sup>3</sup>...] [<sup>4</sup>...] [<sup>5</sup>...] [<sup>6</sup>...]</code></p> <p>1 CSNAME 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT</p>
<p><code>\doquintuplegroupempty \<sup>1</sup>... {<sup>2</sup>...} {<sup>3</sup>...} {<sup>4</sup>...} {<sup>5</sup>...} {<sup>6</sup>...}</code></p> <p>1 CSNAME 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT</p>
<p><code>\dorechecknextindentation</code></p>
<p><code>\dorecurse {<sup>1</sup>...} {<sup>2</sup>...}</code></p> <p>1 NUMBER 2 BEFEHL</p>
<p><code>\dorepeatwithcommand [<sup>1</sup>...] \<sup>2</sup>...</code></p> <p>1 TEXT NUMBER*TEXT 2 CSNAME</p>
<p><code>\doreplacefeature {...,*...}</code></p> <p>* NAME</p>
<p><code>\doresetandafffeature {...,*...}</code></p> <p>* NAME</p>
<p><code>\doresetattribute {<sup>*</sup>...}</code></p> <p>* NAME</p>
<p><code>\dorotatebox {<sup>1</sup>...} \<sup>2</sup>... {<sup>3</sup>...}</code></p> <p>1 NUMBER 2 CSNAME 3 CONTENT</p>
<p><code>\dosetattribute {<sup>1</sup>...} {<sup>2</sup>...}</code></p> <p>1 NAME 2 NUMBER</p>
<p><code>\dosetleftskipadaption {<sup>*</sup>...}</code></p> <p>* da nu standard DIMENSION</p>
<p><code>\dosetrighskipadaption {<sup>*</sup>...}</code></p> <p>* da nu standard DIMENSION</p>
<p><code>\dosetupcheckedinterlinespace {...,*...}</code></p> <p>* inherits: \seteazaspatiuinterliniar</p>
<p><code>\dosetupcheckedinterlinespace {...,*...}</code></p> <p>* on dezactivat reset auto mic mediu mare NUMBER DIMENSION</p>

\* NAME

1	CSNAME
2	TEXT
3	TEXT
4	TEXT
5	TEXT
6	TEXT
7	TEXT
8	TEXT

1	CSNAME
2	TEXT
3	TEXT
4	TEXT
5	TEXT
6	TEXT
7	TEXT
8	TEXT

```

1 CSNAME
2 TEXT

```

```
1 CSNAME
2 TEXT
```

```
1 CSNAME
2 TEXT
```

1	CSNAME
2	TEXT
3	TEXT
4	TEXT
5	TEXT
6	TEXT
7	TEXT

1	CSNAME
2	TEXT
3	TEXT
4	TEXT
5	TEXT
6	TEXT
7	TEXT

1	NAME
2	NAME

- 1 NUMMER
- 2 NUMMER
- 3 [-+] NUMMER
- 4 BEFEHL

\* NAME

`\dotfskip {...}`

\* DIMENSION

`\dotoks \...`

\* CSNAME

`\dotripleargument \1... [2...] [3] [4]`

1 CSNAME

2 TEXT

3 TEXT

4 TEXT

`\dotripleargumentwithset \1... [...,2...] [3] [4]`

1 CSNAME

2 TEXT

3 TEXT

4 TEXT

`\dotripleempty \1... [2] [3] [4]`

1 CSNAME

OPT

OPT

OPT

2 TEXT

3 TEXT

4 TEXT

`\dotripleemptywithset \1... [...,2...] [3] [4]`

1 CSNAME

OPT

OPT

OPT

2 TEXT

3 TEXT

4 TEXT

`\dotriplegroupempty \1... {2...} {3...} {4...}`

1 CSNAME

OPT

OPT

OPT

2 TEXT

3 TEXT

4 TEXT

`\doublebond`

`\dowith {...,1...} {2...}`

1 BEFEHL

2 BEFEHL

`\dowithnextbox {1...} \2... {3...}`

1 BEFEHL

2 CSNAME

3 CONTENT

`\dowithnextboxcontent {1...} {2...} \3... {4...}`

1 BEFEHL

2 BEFEHL

3 CSNAME

4 CONTENT

`\dowithnextboxcontentcs \1... \2... \3... {4...}`

1 CSNAME

2 CSNAME

3 CSNAME

4 CONTENT

`\dowithnextboxcs \1... \2... {3...}`

1 CSNAME

2 CSNAME

3 CONTENT

<code>\dowithpargument \*..</code> <code>* CSNAME</code>
<code>\dowithrange {...<sup>1</sup>,...} \*..<sup>2</sup></code> <code>1 NUMBER NUMBER:NUMBER</code> <code>2 CSNAME</code>
<code>\dowithwargument \*..</code> <code>* CSNAME</code>
<code>\dpofstring {...}</code> <code>* TEXT</code>
<code>\dreapta ...</code> <code>* CHARACTER</code>
<code>\dummydigit</code>
<code>\dummyparameter {...}</code> <code>* KEY</code>
<code>\dute {...<sup>1</sup>} [...<sup>2</sup>]</code> <code>1 CONTENT</code> <code>2 REFERENCE</code>
<code>\dutebox {...<sup>1</sup>} [...<sup>2</sup>]</code> <code>1 CONTENT</code> <code>2 REFERENCE</code>
<code>\dutepagina {...<sup>1</sup>} [...<sup>2</sup>]</code> <code>1 TEXT</code> <code>2 REFERENCE</code>
<code>\ETEX</code>
<code>\EveryLine {...}</code> <code>* BEFEHL</code>
<code>\EveryPar {...}</code> <code>* BEFEHL</code>
<code>\ecran [...<sup>*</sup>,...]</code> <code>* inherits: <sup>QPT</sup>\pagina</code>
<code>\edefconvertedargument \*..<sup>1</sup> {...<sup>2</sup>}</code> <code>1 CSNAME</code> <code>2 TEXT</code>
<code>\efcmxheight {...}</code> <code>* NAME</code>
<code>\efcmxwidth {...}</code> <code>* NAME</code>
<code>\efcminheight {...}</code> <code>* NAME</code>

<code>\efcminwidth {...}</code> <code>* NAME</code>
<code>\efcparameter {...} {...}</code> <code>1 NAME</code> <code>2 KEY</code>
<code>\effect [...]{...}</code> <code>1 NAME</code> <code>2 CONTENT</code>
<code>\elapsedseconds</code>
<code>\elapsedtime</code>
<code>\element [...,*...]</code> <code>* REFERENCE OPT</code>
<code>\em</code>
<code>\emphasisboldface</code>
<code>\emphasistypeface</code>
<code>\emptylines [...*...]</code> <code>* NUMMER OPT</code>
<code>\emspace</code>
<code>\enabledirectives [...,*...]</code> <code>* NAME</code>
<code>\enableexperiments [...,*...]</code> <code>* NAME</code>
<code>\enablemode [...,*...]</code> <code>* NAME</code>
<code>\enableoutputstream [...]</code> <code>* NAME</code>
<code>\enableparpositions</code>
<code>\enableregime [...]</code> <code>* cp1250 cp1251 cp1252 cp1253 cp1254 cp1255 cp1256 cp1257 cp1258 8859-1 8859-2 8859-3 8859-4 8859-9 8859-10 8859-13 8859-14 8859-15 8859-16 utf windows-1250 windows-1251 windows-1252 windows-1253 windows-1254 windows-1255 windows-1256 windows-1257 windows-1258 il1 il2 il3 il4 il5 il6 il7 il8 il9 il10 iso-8859-1 iso-8859-2 iso-8859-3 iso-8859-4 iso-8859-9 iso-8859-10 iso-8859-13 iso-8859-14 iso-8859-15 iso-8859-16 latin1 latin2 latin3 latin4 latin5 latin6 latin7 latin8 latin9 latin10 utf-8 utf8 windows</code>
<code>\enabletrackers [...,*...]</code> <code>* NAME</code>
<code>\enskip</code>
<code>\enspace</code>

$\backslash$ ENUMERARE [... <sup>1</sup> ,...] {... <sup>2</sup> } ... <sup>3</sup> \par 1    REFERENCE            OPT            OPT 2    TEXT 3    CONTENT
$\backslash$ env {...} *    KEY
$\backslash$ envvar {... <sup>1</sup> } {... <sup>2</sup> } 1    KEY 2    BEFEHL
$\backslash$ epos {...} *    NAME
$\backslash$ equaldigits {...} *    TEXT
$\backslash$ eTeX
$\backslash$ ETICHETA [... <sup>1</sup> ,...] {... <sup>2</sup> } 1    REFERENCE            OPT            OPT 2    TEXT
$\backslash$ executeifdefined {... <sup>1</sup> } {... <sup>2</sup> } 1    NAME 2    BEFEHL
$\backslash$ exitloop
$\backslash$ exitloopnow
$\backslash$ expandcheckedcsname \... {... <sup>2</sup> } {... <sup>3</sup> } 1    CSNAME 2    KEY 3    TEXT
$\backslash$ expanded {...} *    CONTENT
$\backslash$ expandeddoif {... <sup>1</sup> } {... <sup>2</sup> } {... <sup>3</sup> } 1    CONTENT 2    CONTENT 3    TRUE
$\backslash$ expandeddoifelse {... <sup>1</sup> } {... <sup>2</sup> } {... <sup>3</sup> } {... <sup>4</sup> } 1    CONTENT 2    CONTENT 3    TRUE 4    FALSE
$\backslash$ expandeddoifnot {... <sup>1</sup> } {... <sup>2</sup> } {... <sup>3</sup> } 1    CONTENT 2    CONTENT 3    TRUE
$\backslash$ expandfontsynonym \... {... <sup>2</sup> } 1    CSNAME 2    NAME

<pre> \expdoif {...} {...} {...} 1  CONTENT 2  CONTENT 3  TRUE </pre>
<pre> \expdoifcommonelse {...,<sup>1</sup>...} {...,<sup>2</sup>...} {...} {...<sup>4</sup>} 1  TEXT 2  TEXT 3  TRUE 4  FALSE </pre>
<pre> \expdoifelse {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} {...<sup>4</sup>} 1  CONTENT 2  CONTENT 3  TRUE 4  FALSE </pre>
<pre> \expdoifelsecommon {...,<sup>1</sup>...} {...,<sup>2</sup>...} {...} {...<sup>4</sup>} 1  TEXT 2  TEXT 3  TRUE 4  FALSE </pre>
<pre> \expdoifelseinset {...<sup>1</sup>} {...,<sup>2</sup>...} {...<sup>3</sup>} {...<sup>4</sup>} 1  TEXT 2  TEXT 3  TRUE 4  FALSE </pre>
<pre> \expdoifinsetelse {...<sup>1</sup>} {...,<sup>2</sup>...} {...<sup>3</sup>} {...<sup>4</sup>} 1  TEXT 2  TEXT 3  TRUE 4  FALSE </pre>
<pre> \expdoifnot {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} 1  CONTENT 2  CONTENT 3  TRUE </pre>
<pre> \externalfigurecollectionmaxheight {...} *  NAME </pre>
<pre> \externalfigurecollectionmaxwidth {...} *  NAME </pre>
<pre> \externalfigurecollectionminheight {...} *  NAME </pre>
<pre> \externalfigurecollectionminwidth {...} *  NAME </pre>
<pre> \externalfigurecollectionparameter {...<sup>1</sup>} {...<sup>2</sup>} 1  NAME 2  KEY </pre>
<pre> \fakebox ... *  CSNAME NUMBER </pre>
<pre> \faraliniiantetsisubsol </pre>
<pre> \faraliniisussijos </pre>



<code>\faraspatiu</code>
<code>\fastdecrement \...</code> <code>* CSNAME</code>
<code>\fastincrement \...</code> <code>* CSNAME</code>
<code>\fastlocalframed [...]<sup>1</sup> [...,<sup>2</sup>...,...]<sup>3</sup> {...}</code> <code>1 NAME</code> <code>2 inherits: \seteazainconjurat</code> <code>3 CONTENT</code>
<code>\fastloopfinal</code>
<code>\fastloopindex</code>
<code>\fastscale {...}<sup>1</sup> {...}<sup>2</sup></code> <code>1 NUMMER</code> <code>2 CONTENT</code>
<code>\fastsetup {...}</code> <code>* NAME</code>
<code>\fastsetupwithargument {...}<sup>1</sup> {...}<sup>2</sup></code> <code>1 NAME</code> <code>2 CONTENT</code>
<code>\fastsetupwithargumentswapped {...}<sup>1</sup> {...}<sup>2</sup></code> <code>1 CONTENT</code> <code>2 NAME</code>
<code>\fastswitchtobodyfont {...}</code> <code>* x xx mic mare script scriptscript</code>
<code>\fastsxsy {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup></code> <code>1 NUMMER</code> <code>2 NUMMER</code> <code>3 CONTENT</code>
<code>\feature [...]<sup>1</sup> [...,<sup>2</sup>...]</code> <code>1 + - = ! &gt; &lt; more less nou reset implicit old local</code> <code>2 NAME</code>
<code>\feature {...}<sup>1</sup> {...,<sup>2</sup>...}</code> <code>1 + - = ! &gt; &lt; more less nou reset implicit old local</code> <code>2 NAME</code>
<code>\fence</code>
<code>\fenced [...]<sup>1</sup> {...}<sup>2</sup></code> <code>1 NAME</code> <code>2 CONTENT</code>
<code>\FENCE {...}</code> <code>* CONTENT</code>

\fetchallmarkings [ <sup>1</sup> ...] [ <sup>2</sup> ...] 1 BESCHRIFTUNG 2 pagina NAME
\fetchallmarks [...] * BESCHRIFTUNG
\fetchmark [ <sup>1</sup> ...] [ <sup>2</sup> ...] 1 BESCHRIFTUNG OPT 2 primul ultim curent precedent urmatorul sus subsol implicit ambele tot first:nochek last:nochek previous:nochek next:nochek top:nochek bottom:nochek
\fetchmarking [ <sup>1</sup> ...] [ <sup>2</sup> ...] [ <sup>3</sup> ...] 1 BESCHRIFTUNG 2 pagina NAME 3 primul ultim curent precedent urmatorul sus subsol implicit ambele tot first:nochek last:nochek previous:nochek next:nochek top:nochek bottom:nochek
\fetchonemark [ <sup>1</sup> ...] [ <sup>2</sup> ...] 1 BESCHRIFTUNG OPT 2 primul ultim curent precedent urmatorul sus subsol implicit ambele tot first:nochek last:nochek previous:nochek next:nochek top:nochek bottom:nochek
\fetchonemarking [ <sup>1</sup> ...] [ <sup>2</sup> ...] [ <sup>3</sup> ...] 1 BESCHRIFTUNG 2 pagina NAME 3 primul ultim curent precedent urmatorul sus subsol implicit ambele tot first:nochek last:nochek previous:nochek next:nochek top:nochek bottom:nochek
\fetchruntimecommand \ <sup>1</sup> ... { <sup>2</sup> ...} 1 CSNAME 2 FILE
\fetchtwomarkings [ <sup>1</sup> ...] [ <sup>2</sup> ...] 1 BESCHRIFTUNG 2 pagina NAME
\fetchtwomarks [...] * BESCHRIFTUNG
\fieldbody [ <sup>1</sup> ...] [ <sup>2</sup> ... <sub>OPT</sub> ...] 1 NAME 2 inherits: \setupfieldbody
\fifthoffivearguments { <sup>1</sup> ...} { <sup>2</sup> ...} { <sup>3</sup> ...} { <sup>4</sup> ...} { <sup>5</sup> ...} 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT
\fifthofsixarguments { <sup>1</sup> ...} { <sup>2</sup> ...} { <sup>3</sup> ...} { <sup>4</sup> ...} { <sup>5</sup> ...} { <sup>6</sup> ...} 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT
\figuraexterna [ <sup>1</sup> ...] [ <sup>2</sup> ...] [ <sup>3</sup> ... <sub>OPT</sub> ... <sub>OPT</sub> ...] 1 FILE OPT 2 NAME 3 inherits: \setuexternalfigure

<code>\figurefilename</code>
<code>\figurefilepath</code>
<code>\figurefiletype</code>
<code>\figurefullname</code>
<code>\figureheight</code>
<code>\figurenaturalheight</code>
<code>\figurenaturalwidth</code>
<code>\figuresymbol [...]</code> $[...,\overset{2}{=}\dots, ...]$ 1 FILE NAME OPT 2 inherits: \figuraexterna
<code>\figurewidth</code>
<code>\filename {...}</code> * FILE
<code>\filledhboxb</code> $\overset{1}{...} \{\overset{2}{...}\}$ 1 TEXT OPT 2 CONTENT
<code>\filledhboxc</code> $\overset{1}{...} \{\overset{2}{...}\}$ 1 TEXT OPT 2 CONTENT
<code>\filledhboxg</code> $\overset{1}{...} \{\overset{2}{...}\}$ 1 TEXT OPT 2 CONTENT
<code>\filledhboxk</code> $\overset{1}{...} \{\overset{2}{...}\}$ 1 TEXT OPT 2 CONTENT
<code>\filledhboxm</code> $\overset{1}{...} \{\overset{2}{...}\}$ 1 TEXT OPT 2 CONTENT
<code>\filledhboxr</code> $\overset{1}{...} \{\overset{2}{...}\}$ 1 TEXT OPT 2 CONTENT
<code>\filledhboxy</code> $\overset{1}{...} \{\overset{2}{...}\}$ 1 TEXT OPT 2 CONTENT
<code>\filler [...]</code> * sym simbol rigla latime spatiu NAME
<code>\fillupto [...]</code> $\{\overset{2}{...}\}$ 1 sym simbol rigla latime spatiu NAME 2 TEXT

<pre> \filterfromnext {...} {...} {...} {...} {...} {...} {...} 1  NUMBER 2  NUMBER 3  CONTENT 4  CONTENT 5  CONTENT 6  CONTENT 7  CONTENT </pre>
<pre> \filterfromvalue {...} {...} {...} 1  NAME 2  NUMBER 3  NUMBER </pre>
<pre> \filterpages [...]<sup>1</sup> [...,<sup>2</sup>...] [...,<sup>3</sup>...,...]<sup>OPT</sup> 1  FILE 2  par impar NUMBER NUMBER:NUMBER 3  latime    = DIMENSION    n         = NUMBER    category  = NAME </pre>
<pre> \filterreference {...} *  implicit text titlu numar pagina realpage </pre>
<pre> \findtwopassdata {...} {...} 1  NAME 2  NAME </pre>
<pre> \finishregisterentry [...]<sup>1</sup> [...,<sup>2</sup>...,...]<sup>2</sup> [...,<sup>3</sup>...,...]<sup>OPT</sup> 1  NAME 2  eticheta  = NAME    keys      = TEXT PROCESSOR-&gt;TEXT    entries    = TEXT PROCESSOR-&gt;TEXT    alternativ = TEXT 3  KEY = VALUE </pre>
<pre> \firdepar </pre>
<pre> \firstcharacter </pre>
<pre> \firstcounter [...]<sup>1</sup> [...]<sup>2</sup><sup>OPT</sup> 1  NAME 2  NUMBER </pre>
<pre> \firstcountervalue [...]<sup>*</sup> *  NAME </pre>
<pre> \firstinlist [...,<sup>*</sup>...] *  BEFEHL </pre>
<pre> \firstoffivearguments {...} {...} {...} {...} {...} 1  TEXT 2  TEXT 3  TEXT 4  TEXT 5  TEXT </pre>
<pre> \firstoffourarguments {...} {...} {...} {...} 1  TEXT 2  TEXT 3  TEXT 4  TEXT </pre>

\firstofoneargument {...} * TEXT
\firstofoneunexpanded {...} * TEXT
\firstofsixarguments {...} {...} {...} {...} {...} {...} 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT
\firstofthreearguments {...} {...} {...} 1 TEXT 2 TEXT 3 TEXT
\firstofthreeunexpanded {...} {...} {...} 1 TEXT 2 TEXT 3 TEXT
\firstoftwoarguments {...} {...} 1 TEXT 2 TEXT
\firstoftwounexpanded {...} {...} 1 TEXT 2 TEXT
\firstrealpage
\firstrealpagenumber
\firstsubcountervalue [... <sup>1</sup> ...] [... <sup>2</sup> ] 1 NAME 2 NUMMER
\firstsubpagenumber
\firstuserpage
\firstuserpagenumber
\fitfieldframed [... <sup>1</sup> ...] {... <sup>2</sup> } 1 inherits: \seteazainconjunctat 2 CONTENT
\fittopbaselinegrid {...} * CONTENT
\flag {...} * NAME
\floatuserdataparameter {...} * KEY

\flushbox {...} {...} 1 NAME 2 NAME
\flushboxregister ... * CSNAME NUMBER
\flushcollector [...] * NAME
\flushedrightlastline
\flushlayer [...] * NAME
\flushlocalfloats
\flushnextbox
\flushnotes
\flushoutputstream [...] * NAME
\flushshapebox
\flushtextflow {...} * NAME
\flushtokens [...] * NAME
\flushtoks \*... * CSNAME
\folosestebloc [... <sup>1</sup> ,...] [... <sup>2</sup> ,...] [... <sup>3</sup> ,... <sup>3</sup> ,...] 1 NAME 2 NAME 3 criteriu = text ABSCHNITT
\folosestedirector [... <sup>*</sup> ,...] * PATH
\folosestedocumentextern [... <sup>1</sup> ] [... <sup>2</sup> ] [... <sup>3</sup> ] 1 NAME 2 FILE 3 TEXT
\folosestefiguraexterna [... <sup>1</sup> ] [... <sup>2</sup> ] [... <sup>3</sup> ] [... <sup>4</sup> ,... <sup>4</sup> ,...] 1 NAME 2 FILE 3 NAME 4 inherits: \setupexternalfigure
\folosestemodul [... <sup>1</sup> ] [... <sup>2</sup> ,...] [... <sup>3</sup> ,... <sup>3</sup> ,...] 1 m p s x t 2 FILE 3 KEY = VALUE

\folosestemuzicaexterna [...] [...] 1 NAME 2 FILE
\folosestescriptJS [...] [...] 1 FILE 2 NAME
\folosestesimboluri [...] * FILE
\folosesteURL [...] [...] [...] [...] 1 NAME 2 URL 3 FILE 4 TEXT
\folosesteurl [...] [...] [...] [...] 1 NAME 2 URL 3 FILE 4 TEXT
\fontalternative
\fontbody
\fontchar {...} * NAME
\fontcharbyindex {...} * NUMMER
\fontclass
\fontclassname {...} {...} 1 NAME 2 FONT
\fontface
\fontfeaturelist [...] [...] 1 NAME 2 TEXT
\fontsize
\fontstyle
\footnotetext [...] [...] [...] [...] 1 REFERENCE 2 TEXT
\footnotetext [..., ..., ..., ...] * titlu = TEXT semncarte = TEXT lista = TEXT referinta = REFERENCE
\forcecharacterstripping

<code>\forcelocalfloats</code>
<code>\forgeteverypar</code>
<code>\forgetparameters [. <sup>1</sup>.] [...,..<sup>2</sup>...,...]</code> 1 TEXT 2 KEY = VALUE
<code>\forgetparskip</code>
<code>\forgetragged</code>
<code>\formula [...,<sup>1</sup>...] {..<sup>2</sup>.}</code> 1 <small>offset</small> <code>impachetat tight centru incadrat adancime linie jumatatelinie -linie -jumatatelinie inherits: \seteazafonttext</code> 2 CONTENT
<code>\foundbox {..<sup>1</sup>.} {..<sup>2</sup>.}</code> 1 NAME 2 NAME
<code>\fourthoffivearguments {..<sup>1</sup>.} {..<sup>2</sup>.} {..<sup>3</sup>.} {..<sup>4</sup>.} {..<sup>5</sup>.}</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT
<code>\fourthoffourarguments {..<sup>1</sup>.} {..<sup>2</sup>.} {..<sup>3</sup>.} {..<sup>4</sup>.}</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT
<code>\fourthofsixarguments {..<sup>1</sup>.} {..<sup>2</sup>.} {..<sup>3</sup>.} {..<sup>4</sup>.} {..<sup>5</sup>.} {..<sup>6</sup>.}</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT
<code>\FRACTION {..<sup>1</sup>.} {..<sup>2</sup>.}</code> 1 CONTENT 2 CONTENT instances: <code>xfrac xxfrac frac sfrac dfrac binom dbinom tbinom</code>
<code>\binom {..<sup>1</sup>.} {..<sup>2</sup>.}</code> 1 CONTENT 2 CONTENT
<code>\dbinom {..<sup>1</sup>.} {..<sup>2</sup>.}</code> 1 CONTENT 2 CONTENT
<code>\dfrac {..<sup>1</sup>.} {..<sup>2</sup>.}</code> 1 CONTENT 2 CONTENT
<code>\frac {..<sup>1</sup>.} {..<sup>2</sup>.}</code> 1 CONTENT 2 CONTENT



$\backslash sfrac \{...\} \{...\}$ 1    CONTENT 2    CONTENT
$\backslash tbinom \{...\} \{...\}$ 1    CONTENT 2    CONTENT
$\backslash xfrac \{...\} \{...\}$ 1    CONTENT 2    CONTENT
$\backslash xxfrac \{...\} \{...\}$ 1    CONTENT 2    CONTENT
$\backslash framed \left[ ..., \dots \stackrel{1}{=} \dots \right] \{...\}$ 1    inherits: $\backslash seteaazainconjurat$ 2    CONTENT
$\backslash frameddimension \{...\}$ *    KEY
$\backslash framedparameter \{...\}$ *    KEY
$\backslash FRAMED \left[ ..., \dots \stackrel{1}{=} \dots \right] \{...\}$ 1    inherits: $\backslash seteaazainconjurat$ 2    CONTENT instances: <code>unframed fitfieldframed</code>
$\backslash fitfieldframed \left[ ..., \dots \stackrel{1}{=} \dots \right] \{...\}$ 1    inherits: $\backslash seteaazainconjurat$ 2    CONTENT
$\backslash unframed \left[ ..., \dots \stackrel{1}{=} \dots \right] \{...\}$ 1    inherits: $\backslash seteaazainconjurat$ 2    CONTENT
$\backslash freezedimenmacro \stackrel{1}{\backslash} \dots \stackrel{2}{\backslash} \dots$ 1    CSNAME 2    CSNAME
$\backslash freezemeasure \left[ \dots \right] \left[ \dots \right]$ 1    NAME 2    DIMENSION
$\backslash frenchspacing$
$\backslash fromlinenote \left[ \dots \right] \{...\}$ 1    REFERENCE 2    TEXT
$\backslash frozenhbox \{...\}$ *    CONTENT
$\backslash frule \dots \stackrel{*}{\dots} \dots \backslash relax$ *    width <sub>⌊</sub> DIMENSION height <sub>⌊</sub> DIMENSION depth <sub>⌊</sub> DIMENSION radius <sub>⌊</sub> DIMENSION line <sub>⌊</sub> DIMENSION type <sub>⌊</sub> TEXT data <sub>⌊</sub> TEXT name <sub>⌊</sub> TEXT

\fundal {...} *   CONTENT
\FUNDAL {...} *   CONTENT instances: fundal
\GetPar
\GotoPar
\Greeknumerals {...} *   NUMMER
\gdefconvertedargument \ <sup>1</sup> ... {\ <sup>2</sup> ...} 1   CSNAME 2   TEXT
\gdefconvertedcommand \ <sup>1</sup> ... \ <sup>2</sup> .. 1   CSNAME 2   CSNAME
\getboxfromcache {\ <sup>1</sup> ...} {\ <sup>2</sup> ...} \ <sup>3</sup> .. 1   NAME 2   NUMMER TEXT 3   CSNAME NUMMER
\getboxllx ... *   CSNAME NUMMER
\getboxlly ... *   CSNAME NUMMER
\getbufferdata [...] *   BUFFER                   OPT
\getcommacommandsize [...,*,...] *   BEFEHL
\getcommalistsize [...,*,...] *   BEFEHL
\getdayoftheweek {\ <sup>1</sup> ...} {\ <sup>2</sup> ...} {\ <sup>3</sup> ...} 1   NUMMER 2   NUMMER 3   NUMMER
\getdayspermonth {\ <sup>1</sup> ...} {\ <sup>2</sup> ...} 1   NUMMER 2   NUMMER
\getdefinedbuffer [...] *   BUFFER
\getdocumentargument {...} *   NAME

<code>\getdocumentargumentdefault {...} {...}</code> 1 NAME 2 TEXT
<code>\getdocumentfilename {...}</code> * NUMMER
<code>\getdummyparameters [...,..<sup>2</sup>...,...]</code> * KEY = VALUE
<code>\getemptyparameters [...] [...,..<sup>2</sup>...,...]</code> 1 TEXT 2 KEY = VALUE
<code>\getparameters [...] [...,..<sup>2</sup>...,...]</code> 1 TEXT 2 KEY = VALUE
<code>\getexpandedparameters [...] [...,..<sup>2</sup>...,...]</code> 1 TEXT 2 KEY = VALUE
<code>\getfiguredimensions [...] [...,..<sup>2</sup>...,...]</code> 1 FILE 2 inherits: \setupexternalfigure
<code>\getfirstcharacter {...}</code> * TEXT
<code>\getfirsttwopassdata {...}</code> * NAME
<code>\getfromcommacommand [...,<sup>1</sup>...] [...<sup>2</sup>]</code> 1 BEFEHL 2 NUMMER
<code>\getfromcommalist [...,<sup>1</sup>...] [...<sup>2</sup>]</code> 1 BEFEHL 2 NUMMER
<code>\getfromtwopassdata {...} {...}</code> 1 NAME 2 NAME
<code>\getglyphdirect {...} {...}</code> 1 FONT 2 NUMMER CHARACTER
<code>\getglyphstyled {...} {...}</code> 1 FONT 2 NUMMER CHARACTER
<code>\getgparameters [...] [...,..<sup>2</sup>...,...]</code> 1 TEXT 2 KEY = VALUE
<code>\getinlineuserdata</code>
<code>\getlasttwopassdata {...}</code> * NAME

\getlocalfloat {...} *   NUMBER
\getlocalfloats
\getMPdrawing
\getMPlayer [ <sup>1</sup> ...] [ <sup>2</sup> ... <sub>OPT</sub> ...] {...} 1   NAME 2   inherits: \seteazainconjurat 3   CONTENT
\getmessage { <sup>1</sup> ...} { <sup>2</sup> ...} 1   NAME 2   NAME NUMBER
\getnamedglyphdirect { <sup>1</sup> ...} { <sup>2</sup> ...} 1   FONT 2   NAME
\getnamedglyphstyled { <sup>1</sup> ...} { <sup>2</sup> ...} 1   FONT 2   NAME
\getnamedtwopassdatalist \ <sup>1</sup> ... { <sup>2</sup> ...} 1   CSNAME 2   NAME
\getnaturaldimensions ... *   CSNAME NUMBER
\getnoflines {...} *   DIMENSION
\getobject { <sup>1</sup> ...} { <sup>2</sup> ...} 1   NAME 2   NAME
\getobjectdimensions { <sup>1</sup> ...} { <sup>2</sup> ...} 1   NAME 2   NAME
\getpaletsize [...] *   NAME
\getparameters [ <sup>1</sup> ...] [ <sup>2</sup> ... <sub>...</sub> ...] 1   TEXT 2   KEY = VALUE
\getprivatechar {...} *   NAME
\getprivateslot {...} *   NAME
\getrandomcount \ <sup>1</sup> ... { <sup>2</sup> ...} { <sup>3</sup> ...} 1   CSNAME 2   NUMBER 3   NUMBER

<pre> \getrandomdimen \<sup>1</sup>... {<sup>2</sup>...} {<sup>3</sup>...} 1 CSNAME 2 DIMENSION 3 DIMENSION </pre>
<pre> \getrandomfloat \<sup>1</sup>... {<sup>2</sup>...} {<sup>3</sup>...} 1 CSNAME 2 NUMMER 3 NUMMER </pre>
<pre> \getrandomnumber \<sup>1</sup>... {<sup>2</sup>...} {<sup>3</sup>...} 1 CSNAME 2 NUMMER 3 NUMMER </pre>
<pre> \getrandomseed \*... * CSNAME </pre>
<pre> \getraweparameters [<sup>1</sup>...] [...,<sup>2</sup>...,...] 1 TEXT 2 KEY = VALUE </pre>
<pre> \getrawgparameters [<sup>1</sup>...] [...,<sup>2</sup>...,...] 1 TEXT 2 KEY = VALUE </pre>
<pre> \getrawnoflines {*...} * DIMENSION </pre>
<pre> \getrawparameters [<sup>1</sup>...] [...,<sup>2</sup>...,...] 1 TEXT 2 KEY = VALUE </pre>
<pre> \getrawxparameters [<sup>1</sup>...] [...,<sup>2</sup>...,...] 1 TEXT 2 KEY = VALUE </pre>
<pre> \getreference [<sup>1</sup>...] [<sup>2</sup>...] 1 implicit text titlu numar pagina realpage 2 REFERENCE </pre>
<pre> \getreferenceentry {*...} * implicit text titlu numar pagina realpage </pre>
<pre> \getroundednoflines {*...} * DIMENSION </pre>
<pre> \getsubstring {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...} 1 NUMMER 2 NUMMER 3 TEXT </pre>
<pre> \gettokenlist [...] * NAME </pre>
<pre> \gettwopassdata {*...} * NAME </pre>
<pre> \gettwopassdatalist {*...} * NAME </pre>

<code>\getuserdata</code>
<code>\getuvalue {...}</code> *    NAME
<code>\getvalue {...}</code> *    NAME
<code>\getvariable {...} {...}</code> 1    NAME 2    KEY
<code>\getvariabledefault {...} {...} {...}</code> 1    NAME 2    KEY 3    BEFEHL
<code>\getxparameters [...] [...,...<sup>2</sup>...,...]</code> 1    TEXT 2    KEY = VALUE
<code>\globaldisablemode [...,*,...]</code> *    NAME
<code>\globalenablemode [...,*,...]</code> *    NAME
<code>\globalletempty \...</code> *    CSNAME
<code>\globalpopbox ...</code> *    CSNAME NUMBER
<code>\globalpopmacro \...</code> *    CSNAME
<code>\globalpreventmode [...,*,...]</code> *    NAME
<code>\globalprocesscommalist [...] \...</code> 1    BEFEHL 2    CSNAME
<code>\globalpushbox ...</code> *    CSNAME NUMBER
<code>\globalpushmacro \...</code> *    CSNAME
<code>\globalpushreferenceprefix {...} ... \globalpopreferenceprefix</code> *    + - TEXT
<code>\globalswapcounts \... \...</code> 1    CSNAME 2    CSNAME
<code>\globalswapdimens \... \...</code> 1    CSNAME 2    CSNAME

`\globalswapmacros \1... \2...`

1 CSNAME  
2 CSNAME

`\globalundefine {...}`

\* NAME

`\glyphfontfile {...}`

\* FONT

`\gobbledoubleempty [1...] [2...]`

1 TEXT  
2 TEXT

OPT OPT

`\gobbleeightarguments {...} {...} {...} {...} {...} {...} {...} {...}`

1 CONTENT  
2 CONTENT  
3 CONTENT  
4 CONTENT  
5 CONTENT  
6 CONTENT  
7 CONTENT  
8 CONTENT

`\gobblefivearguments {...} {...} {...} {...} {...}`

1 CONTENT  
2 CONTENT  
3 CONTENT  
4 CONTENT  
5 CONTENT

`\gobblefiveoptionals [1...] [2...] [3...] [4...] [5...]`

1 TEXT  
2 TEXT  
3 TEXT  
4 TEXT  
5 TEXT

`\gobblefourarguments {...} {...} {...} {...}`

1 CONTENT  
2 CONTENT  
3 CONTENT  
4 CONTENT

`\gobblefouroptionals [1...] [2...] [3...] [4...]`

1 TEXT  
2 TEXT  
3 TEXT  
4 TEXT

`\gobbleninearguments {...} {...} {...} {...} {...} {...} {...} {...} {...}`

1 CONTENT  
2 CONTENT  
3 CONTENT  
4 CONTENT  
5 CONTENT  
6 CONTENT  
7 CONTENT  
8 CONTENT  
9 CONTENT

`\gobbleoneargument {...}`

\* CONTENT

`\gobbleoneoptional [*...]`

\* TEXT

\gobblesevenarguments {...} {...} {...} {...} {...} {...} {...}

1 CONTENT  
2 CONTENT  
3 CONTENT  
4 CONTENT  
5 CONTENT  
6 CONTENT  
7 CONTENT

\gobblesingleempty [...]

\* TEXT OPT

\gobblesixarguments {...} {...} {...} {...} {...} {...}

1 CONTENT  
2 CONTENT  
3 CONTENT  
4 CONTENT  
5 CONTENT  
6 CONTENT

\gobblespacetokens

\gobbletenarguments {...} {...} {...} {...} {...} {...} {...} {...} {...} {...}

1 CONTENT  
2 CONTENT  
3 CONTENT  
4 CONTENT  
5 CONTENT  
6 CONTENT  
7 CONTENT  
8 CONTENT  
9 CONTENT  
10 CONTENT

\gobblethreearguments {...} {...} {...}

1 CONTENT  
2 CONTENT  
3 CONTENT

\gobblethreeoptionals [...] [...] [...]

1 TEXT  
2 TEXT  
3 TEXT

\gobbletwoarguments {...} {...}

1 CONTENT  
2 CONTENT

\gobbletwooptionals [...] [...]

1 TEXT  
2 TEXT

\gobbleuntil \...

\* CSNAME

\gobbleuntilrelax ... \relax

\* CONTENT

\grabbufferdata [...] [...] [...] [...]

1 CATEGORY OPT  
2 NAME  
3 NAME  
4 NAME



<code>\grabbufferdatadirect {...} {...} {...}</code> 1 NAME 2 NAME 3 NAME
<code>\grabuntil {...} \^2..</code> 1 NAME 2 CSNAME
<code>\grave {...}</code> * CHARACTER
<code>\grayvalue {...}</code> * COLOR
<code>\greedystring ... \at \^2.. \to \^3.. \and \^4..</code> 1 TEXT 2 TEXT 3 CSNAME 4 CSNAME
<code>\greeknumerals {...}</code> * NUMMER
<code>\grid [..., ...=..., ...]</code> * inherits: \basegrid <sup>OPT</sup>
<code>\grosimelinie</code>
<code>\groupedcommand {...} {...}</code> 1 BEFEHL 2 BEFEHL
<code>\gsetboxllx \^1. {...}</code> 1 CSNAME NUMBER 2 DIMENSION
<code>\gsetboxlly \^1. {...}</code> 1 CSNAME NUMBER 2 DIMENSION
<code>\gujaratinumerals {...}</code> * NUMMER
<code>\gurmukhinumerals {...}</code> * NUMMER
<code>\hairspace</code>
<code>\halflinestrut</code>
<code>\halfstrut</code>
<code>\halfwaybox {...}</code> * CONTENT
<code>\handletokens \^1. \with \^2..</code> 1 TEXT 2 CSNAME

<code>\hash</code>
<code>\hat {...}</code> * CHARACTER
<code>\hboxofvbox ...</code> * CSNAME NUMBER
<code>\hboxreference [...<sup>1</sup>,...] {...<sup>2</sup>}</code> 1 REFERENCE 2 CONTENT
<code>\hboxBOX {...}</code> * CONTENT
<code>\hdofstring {...}</code> * TEXT
<code>\headhbox ...<sup>1</sup> {...<sup>2</sup>}</code> 1 TEXT OPT 2 CONTENT
<code>\headnumbercontent</code>
<code>\headnumberdistance</code>
<code>\headnumberwidth</code>
<code>\headreferenceattributes</code>
<code>\headsetupspacing</code>
<code>\headtextcontent</code>
<code>\headtextdistance</code>
<code>\headtextwidth</code>
<code>\headvbox ...<sup>1</sup> {...<sup>2</sup>}</code> 1 TEXT OPT 2 CONTENT
<code>\headwidth</code>
<code>\heightanddepthofstring {...}</code> * TEXT
<code>\heightofstring {...}</code> * TEXT
<code>\heightspanningtext {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}</code> 1 TEXT 2 DIMENSION 3 FONT

$\backslash$ HELP [...] {...} {...} 1 REFERENCE 2 TEXT 3 TEXT instances: helptext
$\backslash$ helptext [...] {...} {...} 1 REFERENCE OPT 2 TEXT 3 TEXT
$\backslash$ hglue ... * DIMENSION
$\backslash$ hiddencitation [...]
$\backslash$ hiddencite [...]
$\backslash$ highlight [...] {...} 1 NAME 2 TEXT
$\backslash$ HIGHLIGHT {...} * TEXT
$\backslash$ highordinalstr {...} * TEXT
$\backslash$ hilo [...] {...} {...} 1 stanga <sup>OR</sup> dreapta 2 CONTENT 3 CONTENT
$\backslash$ himilo {...} {...} {...} 1 CONTENT 2 CONTENT 3 CONTENT
$\backslash$ hl [...]
$\backslash$ horizontalgrowingbar [...,...*=...] * inherits: \setuppositionbar
$\backslash$ horizontalpositionbar [...,...*=...] * inherits: \setuppositionbar
$\backslash$ hphantom {...} * CONTENT
$\backslash$ hpos [...] {...} 1 NAME 2 CONTENT
$\backslash$ hsizefraction [...] {...} 1 DIMENSION 2 NUMMER

<code>\hsmash {...}</code> *    CONTENT
<code>\hsmashbox ...</code> *    CSNAME NUMBER
<code>\hsmashed {...}</code> *    CONTENT
<code>\hspace [...<sup>1</sup>] [...<sup>2</sup>]</code> 1    NAME        OPT        OPT 2    mic mediu mare normal implicit niciunul .5 1 2 3 speech minicitat interquotation citat sentence intersentence final NAME
<code>\htdpofstring {...}</code> *    TEXT
<code>\htofstring {...}</code> *    TEXT
<code>\hyphen</code>
<code>\hyphenatedcoloredword {...}</code> *    TEXT
<code>\hyphenatedfile {...}</code> *    FILE
<code>\hyphenatedfilename {...}</code> *    TEXT
<code>\hyphenatedhbox {...}</code> *    CONTENT
<code>\hyphenatedpar {...}</code> *    TEXT
<code>\hyphenatedurl {...}</code> *    TEXT
<code>\hyphenatedword {...}</code> *    TEXT
<code>\INRSTEX</code>
<code>\ibox {...}</code> *    CONTENT
<code>\ifassignment ... \else ... \fi</code> 1    TRUE 2    FALSE
<code>\iff</code>
<code>\ifinobject ... \else ... \fi</code> 1    TRUE 2    FALSE

<code>\ifinoutputstream .<sup>1</sup>. \else .<sup>2</sup>. \fi</code> 1 TRUE 2 FALSE
<code>\ifparameters .<sup>1</sup>. \else .<sup>2</sup>. \fi</code> 1 TRUE 2 FALSE
<code>\iftrialeasetting .<sup>1</sup>. \else .<sup>2</sup>. \fi</code> 1 TRUE 2 FALSE
<code>\ignoreimplicitspaces</code>
<code>\ignoretagsinexport [...,*,...]</code> * NAME
<code>\ignorevalue {...}</code> * NAME
<code>\immediatesavetwopassdata {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}</code> 1 NAME 2 NUMBER 3 CONTENT
<code>\impartefloat [...,<sup>1</sup>...,...] {...<sup>2</sup>} {...<sup>3</sup>}</code> 1 inherits: \seteazaimpartefloat 2 BEFEHL 3 CONTENT
<code>\impliedby</code>
<code>\implies</code>
<code>\in {...<sup>1</sup>} {...<sup>2</sup>} [...<sup>3</sup>]</code> 1 TEXT <sup>OPT</sup> OPT 2 TEXT 3 REFERENCE
<code>\inalt {...}</code> * CONTENT
<code>\HIGH {...}</code> * CONTENT instances: unitshigh
<code>\unitshigh {...}</code> * CONTENT
<code>\inclinat</code>
<code>\inclinataldin</code>
<code>\includemenu [...]</code> * NAME
<code>\includeversioninfo {...}</code> * NAME

$\backslash\text{increment } \dots$ * CSNAME
$\backslash\text{incrementcounter } [\dots] [\dots]$ 1 NAME OPT 2 NUMBER
$\backslash\text{incrementedcounter } [\dots]$ * NAME
$\backslash\text{incrementpagenumber}$
$\backslash\text{incrementsubpagenumber}$
$\backslash\text{incrementvalue } \{\dots\}$ * NAME
$\backslash\text{increment } (\dots, \dots)$ * CSNAME NUMBER
$\backslash\text{indentation}$
$\backslash\text{infofont}$
$\backslash\text{infofontbold}$
$\backslash\text{inframed } [\dots, \dots] \{\dots\}$ 1 inherits: \setea <sup>2</sup> \inconjurat 2 CONTENT
$\backslash\text{inheritparameter } [\dots] [\dots] [\dots]$ 1 TEXT 2 TEXT 3 KEY
$\backslash\text{inhibitblank}$
$\backslash\text{initializeboxstack } \{\dots\}$ * NAME
$\backslash\text{injos } [\dots]$ * DIMENSION
$\backslash\text{inlinebuffer } [\dots, \dots]$ * BUFFER OPT
$\backslash\text{inlinedbox } \{\dots\}$ * CONTENT
$\backslash\text{inlinemath } \{\dots\}$ * CONTENT
$\backslash\text{inlinemathematics } \{\dots\}$ * CONTENT
$\backslash\text{inlinemessage } \{\dots\}$ * TEXT

$\backslash inlineordisplaymath \{.^1.\} \{.^2.\}$ 1    CONTENT 2    CONTENT
$\backslash inlineprettyprintbuffer \{.^1.\} \{.^2.\}$ 1    BUFFER 2    mp lua xml parsed-xml nested tex context niciunul NAME
$\backslash inlinerange [...]$ *    REFERENCE
$\backslash inline \{.^1.\} [.^2.]$ 1    TEXT            OPT 2    REFERENCE
$\backslash innerflushshapebox$
$\backslash input \{.^*\}$ *    FILE
$\backslash inputfilebarename$
$\backslash inputfilename$
$\backslash inputfilerealsuffix$
$\backslash inputfilesuffix$
$\backslash inputgivenfile \{.^*\}$ *    FILE
$\backslash input ...$ *    FILE
$\backslash insertpages [.^1.] [...,.^2,...] [...,.^3,...]$ 1    FILE                    OPT                    OPT 2    NUMBER 3    latime    =    DIMENSION n            =    NUMMER category    =    NAME
$\backslash instalarelimba [.^1.] [...,.^2,...]$ 1    NAME 2    inherits: \setarelimba
$\backslash instalarelimba [.^1.] [.^2.]$ 1    NAME 2    SPRACHE
$\backslash installactionhandler \{.^*\}$ *    NAME
$\backslash installactivecharacter ...$ *    CHARACTER
$\backslash installanddefineactivecharacter .^1. \{.^2.\}$ 1    CHARACTER 2    BEFEHL

\installattributestack \*.. * CSNAME
\installautocommandhandler \... { <sup>1</sup> ...} \... 1 CSNAME 2 NAME 3 CSNAME
\installautosetuphandler \... { <sup>1</sup> ...} 1 CSNAME 2 NAME
\installbasicautosetuphandler \... { <sup>1</sup> ...} \... 1 CSNAME 2 NAME 3 CSNAME
\installbasicparameterhandler \... { <sup>1</sup> ...} 1 CSNAME 2 NAME
\installbottomframerenderer { <sup>1</sup> ...} { <sup>2</sup> ...} 1 NAME 2 BEFEHL
\installcommandhandler \... { <sup>1</sup> ...} \... 1 CSNAME 2 NAME 3 CSNAME
\installcorenamespace { <sup>1</sup> ...} * NAME
\installdefinehandler \... { <sup>1</sup> ...} \... 1 CSNAME 2 NAME 3 CSNAME
\installdefinitionset \... { <sup>1</sup> ...} 1 CSNAME 2 NAME
\installdefinitionsetmember \... { <sup>1</sup> ...} \... { <sup>2</sup> ...} 1 CSNAME 2 NAME 3 CSNAME 4 NAME
\installdirectcommandhandler \... { <sup>1</sup> ...} 1 CSNAME 2 NAME
\installdirectparameterhandler \... { <sup>1</sup> ...} 1 CSNAME 2 NAME
\installdirectparametersethandler \... { <sup>1</sup> ...} 1 CSNAME 2 NAME
\installdirectsetuphandler \... { <sup>1</sup> ...} 1 CSNAME 2 NAME



<pre> \installdirectstyleandcolorhandler \... {...} 1 CSNAME 2 NAME </pre>
<pre> \installframedautocommandhandler \... {...} \... 1 CSNAME 2 NAME 3 CSNAME </pre>
<pre> \installframedcommandhandler \... {...} \... 1 CSNAME 2 NAME 3 CSNAME </pre>
<pre> \installglobalmacrostack \*... * CSNAME </pre>
<pre> \installleftframerenderer {...} {...} 1 NAME 2 BEFEHL </pre>
<pre> \installmacrostack \*... * CSNAME </pre>
<pre> \installnamespace {...} * NAME </pre>
<pre> \installoutputroutine \... {...} 1 CSNAME 2 BEFEHL </pre>
<pre> \installpagearrangement ... {...} 1 NAME 2 BEFEHL </pre>
<pre> \installparameterhandler \... {...} 1 CSNAME 2 NAME </pre>
<pre> \installparameterhashhandler \... {...} 1 CSNAME 2 NAME </pre>
<pre> \installparametersethandler \... {...} 1 CSNAME 2 NAME </pre>
<pre> \installparentinjector \... {...} 1 CSNAME 2 NAME </pre>
<pre> \installrightframerenderer {...} {...} 1 NAME 2 BEFEHL </pre>
<pre> \installrootparameterhandler \... {...} 1 CSNAME 2 NAME </pre>

<code>\installsetuphandler \<sup>1</sup>... {<sup>2</sup>...}</code> 1 CSNAME 2 NAME
<code>\installsetuponlycommandhandler \<sup>1</sup>... {<sup>2</sup>...}</code> 1 CSNAME 2 NAME
<code>\installshipoutmethod {<sup>1</sup>...} {<sup>2</sup>...}</code> 1 NAME 2 BEFEHL
<code>\installsimplecommandhandler \<sup>1</sup>... {<sup>2</sup>...} \<sup>3</sup>...</code> 1 CSNAME 2 NAME 3 CSNAME
<code>\installsimpleframedcommandhandler \<sup>1</sup>... {<sup>2</sup>...} \<sup>3</sup>...</code> 1 CSNAME 2 NAME 3 CSNAME
<code>\installstyleandcolorhandler \<sup>1</sup>... {<sup>2</sup>...}</code> 1 CSNAME 2 NAME
<code>\installswitchcommandhandler \<sup>1</sup>... {<sup>2</sup>...} \<sup>3</sup>...</code> 1 CSNAME 2 NAME 3 CSNAME
<code>\installswitchsetuphandler \<sup>1</sup>... {<sup>2</sup>...}</code> 1 CSNAME 2 NAME
<code>\installtexdirective {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...}</code> 1 NAME 2 BEFEHL 3 BEFEHL
<code>\installtextracker {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...}</code> 1 NAME 2 BEFEHL 3 BEFEHL
<code>\installtopframerenderer {<sup>1</sup>...} {<sup>2</sup>...}</code> 1 NAME 2 BEFEHL
<code>\installunitsseparator {<sup>1</sup>...} {<sup>2</sup>...}</code> 1 NAME 2 BEFEHL
<code>\installunitsspace {<sup>1</sup>...} {<sup>2</sup>...}</code> 1 NAME 2 BEFEHL
<code>\installversioninfo {<sup>1</sup>...} {<sup>2</sup>...}</code> 1 NAME 2 BEFEHL
<code>\integerrounding {<sup>*</sup>...}</code> * NUMMER

<code>\intertext {...}</code> * TEXT
<code>\intins [...,<sup>1</sup>...,<sup>2</sup>...] {...}</code> 1 inherits: \setupstretched 2 TEXT
<code>\invokepagehandler {...} {...}</code> 1 normal niciunul NAME 2 CONTENT
<code>\istltdir ...</code> * TLT TRT
<code>\istrtdir ...</code> * TLT TRT
<code>\italic</code>
<code>\italicaldin</code>
<code>\italiccorrection</code>
<code>\italicface</code>
<code>\itemtag [...,*,...]</code> * REFERENCE <small>OPT</small>
<code>\jobfilename</code>
<code>\jobfilesuffix</code>
<code>\jos {...}</code> * CONTENT
<code>\jossus [...<sup>1</sup>] {...<sup>2</sup>} {...<sup>3</sup>}</code> 1 stanga dreapta 2 CONTENT 3 CONTENT
<code>\LOW {...}</code> * CONTENT instances: unitslow
<code>\unitslow {...}</code> * CONTENT
<code>\Kap {...}</code> * TEXT
<code>\kap {...}</code> * TEXT
<code>\keeplinestogether {...}</code> * NUMMER
<code>\keepunwantedspaces</code>

$\backslash\text{kerncharacters}$ [ <sup>1</sup> ...] { <sup>2</sup> ...} 1    NUMBER                    OPT 2    TEXT
$\backslash\text{koreancirclednumerals}$ {...} *    NUMBER
$\backslash\text{koreannumerals}$ {...} *    NUMBER
$\backslash\text{koreannumeralsc}$ {...} *    NUMBER
$\backslash\text{koreannumeralsp}$ {...} *    NUMBER
$\backslash\text{koreanparentnumerals}$ {...} *    NUMBER
$\backslash\text{LAMSTEX}$
$\backslash\text{LATEX}$
$\backslash\text{LamSTeX}$
$\backslash\text{LaTeX}$
$\backslash\text{Litera}$ {...} *    NUMBER
$\backslash\text{Litere}$ {...} *    NUMBER
$\backslash\text{LUAJITTEX}$
$\backslash\text{LUAMETATEX}$
$\backslash\text{LUATEX}$
$\backslash\text{LUNA}$ {...} *    NUMBER
$\backslash\text{Lua}$
$\backslash\text{LuajitTeX}$
$\backslash\text{LuaMetaTeX}$
$\backslash\text{LuaTeX}$
$\backslash\text{la}$ { <sup>1</sup> ...} { <sup>2</sup> ...} [ <sup>3</sup> ...] 1    TEXT <sup>PPT</sup> OPT 2    TEXT 3    REFERENCE

<code>\LABELlimba</code> instances: head label mathlabel taglabel unit operator prefix suffix btxlabel
<code>\btxlabellimba</code>
<code>\headlimba</code>
<code>\labellimba</code>
<code>\mathlabellimba</code>
<code>\operatorlimba</code>
<code>\prefixlimba</code>
<code>\suffixlimba</code>
<code>\taglabellimba</code>
<code>\unitlimba</code>
<code>\LABELtexts {...} {...}</code> 1 KEY 2 TEXT instances: head label mathlabel
<code>\headtexts {...} {...}</code> 1 KEY 2 TEXT
<code>\labeltexts {...} {...}</code> 1 KEY 2 TEXT
<code>\mathlabeltexts {...} {...}</code> 1 KEY 2 TEXT
<code>\languageCharacters {...}</code> * NUMMER
<code>\languagecharacters {...}</code> * NUMMER
<code>\languagecharwidth {...}</code> * SPRACHE
<code>\lapagina [...]</code> * REFERENCE
<code>\lastcounter [...] [...]</code> 1 NAME OPT 2 NUMMER
<code>\lastcountervalue [...]</code> * NAME

<code>\lastdigit {...}</code> *    NUMMER
<code>\lastlinewidth</code>
<code>\lastnaturalboxdp</code>
<code>\lastnaturalboxht</code>
<code>\lastnaturalboxwd</code>
<code>\lastpredefinedsymbol</code>
<code>\lastrealpage</code>
<code>\lastrealpagenumber</code>
<code>\lastsubcountervalue [...]<sup>1</sup> [...]<sup>2</sup></code> 1    NAME 2    NUMMER
<code>\lastsubpagenumber</code>
<code>\lasttwodigits {...}</code> *    NUMMER
<code>\lastuserpage</code>
<code>\lastuserpagenumber</code>
<code>\lateluacode {...}</code> *    BEFEHL
<code>\layeredtext [...]<sup>1</sup> [...]<sup>2</sup> {...}<sup>3</sup> {...}<sup>4</sup></code> 1    inherits: \setuplayer <sup>PT</sup> 2    inherits: \setuplayeredtext 3    TEXT 4    CONTENT
<code>\layerheight</code>
<code>\layerwidth</code>
<code>\lazysavetaggedtwopassdata {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup> {...}<sup>4</sup></code> 1    NAME 2    NUMMER 3    NAME 4    CONTENT
<code>\lazysavetwopassdata {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup></code> 1    NAME 2    NUMMER 3    CONTENT
<code>\lbox ... {...}<sup>1</sup></code> 1    TEXT <sup>OPT</sup> 2    CONTENT

$\backslash\text{leftbottombox}$ {...} *    CONTENT
$\backslash\text{leftbox}$ {...} *    CONTENT
$\backslash\text{lefthbox}$ {...} *    CONTENT
$\backslash\text{leftLABELtext}$ {...} *    KEY instances: head label mathlabel
$\backslash\text{leftheadtext}$ {...} *    KEY
$\backslash\text{leftlabeltext}$ {...} *    KEY
$\backslash\text{leftmathlabeltext}$ {...} *    KEY
$\backslash\text{leftline}$ {...} *    CONTENT
$\backslash\text{lefttorrighthbox}$ <sup>1</sup> ... { <sup>2</sup> ...} 1    TEXT                    OPT 2    CONTENT
$\backslash\text{lefttorrightvbox}$ <sup>1</sup> ... { <sup>2</sup> ...} 1    TEXT                    OPT 2    CONTENT
$\backslash\text{lefttorrightvtop}$ <sup>1</sup> ... { <sup>2</sup> ...} 1    TEXT                    OPT 2    CONTENT
$\backslash\text{leftskipadaption}$
$\backslash\text{leftsubguillemot}$
$\backslash\text{lefttopbox}$ {...} *    CONTENT
$\backslash\text{lefttoright}$
$\backslash\text{lefttorrighthbox}$ <sup>1</sup> ... { <sup>2</sup> ...} 1    TEXT                    OPT 2    CONTENT
$\backslash\text{lefttorrightvbox}$ <sup>1</sup> ... { <sup>2</sup> ...} 1    TEXT                    OPT 2    CONTENT
$\backslash\text{lefttorrightvtop}$ <sup>1</sup> ... { <sup>2</sup> ...} 1    TEXT                    OPT 2    CONTENT

<code>\letbeundefined {...}</code> <code>*    NAME</code>
<code>\letcatcodecommand \<sup>1</sup>... \<sup>2</sup>... \<sup>3</sup>...</code> <code>1    CSNAME</code> <code>2    CHARACTER NUMBER</code> <code>3    CSNAME</code>
<code>\letcscsname \<sup>1</sup>... \csname \<sup>2</sup>... \endcsname</code> <code>1    CSNAME</code> <code>2    NAME</code>
<code>\letcsnamecs \csname \<sup>1</sup>... \endcsname \<sup>2</sup>...</code> <code>1    NAME</code> <code>2    CSNAME</code>
<code>\letcsnamecsname \csname \<sup>1</sup>... \endcsname \csname \<sup>2</sup>... \endcsname</code> <code>1    NAME</code> <code>2    NAME</code>
<code>\letdummyparameter {\<sup>1</sup>...} \<sup>2</sup>...</code> <code>1    KEY</code> <code>2    CSNAME</code>
<code>\letempty \<sup>*</sup>...</code> <code>*    CSNAME</code>
<code>\letgvalue {\<sup>1</sup>...} \<sup>2</sup>...</code> <code>1    NAME</code> <code>2    CSNAME</code>
<code>\letgvalueempty {...}</code> <code>*    NAME</code>
<code>\letgvalurelax {...}</code> <code>*    NAME</code>
<code>\letterampersand</code>
<code>\letterat</code>
<code>\letterbackslash</code>
<code>\letterbar</code>
<code>\letterbgroup</code>
<code>\letterclosebrace</code>
<code>\lettercolon</code>
<code>\letterdollar</code>
<code>\letterdoublequote</code>
<code>\letterereggroup</code>



<code>\letterescape</code>
<code>\letterexclamationmark</code>
<code>\letterhash</code>
<code>\letterhat</code>
<code>\letterleftbrace</code>
<code>\letterleftbracket</code>
<code>\letterleftparenthesis</code>
<code>\letterless</code>
<code>\lettermore</code>
<code>\letteropenbrace</code>
<code>\letterpercent</code>
<code>\letterquestionmark</code>
<code>\letterrightbrace</code>
<code>\letterrightbracket</code>
<code>\letterrightparenthesis</code>
<code>\lettersinglequote</code>
<code>\letterslash</code>
<code>\letterspacing [...]<sup>1</sup> {...}<sup>2</sup></code> 1    NUMBER                    OPT 2    TEXT
<code>\lettertilde</code>
<code>\letterunderscore</code>
<code>\letvalue {...} \<sup>2</sup>...</code> 1    NAME 2    CSNAME
<code>\letvalueempty {...}</code> *    NAME
<code>\letvaluerelax {...}</code> *    NAME
<code>\lfence {...}</code> *    CHARACTER

<code>\lhbox {...}</code> *    CONTENT
<code>\limba [...]</code> *    SPRACHE
<code>\limbapricipala [...]</code> *    SPRACHE
<code>\LANGUAGE</code>
<code>\limitatefirstline {...} {...} {...}</code> 1    TEXT 2    DIMENSION 3    BEFEHL
<code>\limitatelines {...} {...} {...}</code> 1    NUMMER 2    BEFEHL 3    TEXT
<code>\limitatetext {...} {...} {...}</code> 1    TEXT 2    [-+]DIMENSION 3    BEFEHL
<code>\limitatetext {...} {...<sup>2</sup>,...} {...}</code> 1    TEXT 2    [-+]DIMENSION 3    BEFEHL
<code>\linebox {...}</code> *    CONTENT
<code>\LINENOTE {...}</code> *    TEXT instances: linenote
<code>\linenote {...}</code> *    TEXT
<code>\linespanningtext {...} {...} {...}</code> 1    TEXT 2    DIMENSION 3    FONT
<code>\linie {...}</code> *    CONTENT
<code>\linieneagra [...,..<sup>*</sup>...,...]</code> *    inherits: \seteazalin <sup>HT</sup> inegre
<code>\liniesubtire</code>
<code>\linieumplere [...,..<sup>*</sup>...,...]</code> *    inherits: \seteazalini <sup>HT</sup> umplere
<code>\liniinegre [...,..<sup>*</sup>...,...]</code> *    inherits: \seteazalin <sup>HT</sup> inegre

```
\liniisubtiri [...*...]
* inherits: \seteazalinisubtire
```

```
\listcitation [...1...] [...2]
1 referinta = REFERENCE
  alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
               authoryear
  inainte   = BEFEHL
  dupa      = BEFEHL
  stanga    = BEFEHL
  dreapta   = BEFEHL
  inherits: \setupbtx
2 REFERENCE
```

```
\listcitation [...1] [...2]
1 implicit categoryOPT entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear
2 REFERENCE
```

```
\listcitation [...1...] [...2...]
1 referinta = REFERENCE
  alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
               authoryear
  inainte   = BEFEHL
  dupa      = BEFEHL
  stanga    = BEFEHL
  dreapta   = BEFEHL
  inherits: \setupbtx
2 KEY = VALUE
```

```
\listcite [...1...] [...2]
1 referinta = REFERENCE
  alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
               authoryear
  inainte   = BEFEHL
  dupa      = BEFEHL
  stanga    = BEFEHL
  dreapta   = BEFEHL
  inherits: \setupbtx
2 REFERENCE
```

```
\listcite [...1] [...2]
1 implicit categoryOPT entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear
2 REFERENCE
```

```
\listcite [...1...] [...2...]
1 referinta = REFERENCE
  alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
               authoryear
  inainte   = BEFEHL
  dupa      = BEFEHL
  stanga    = BEFEHL
  dreapta   = BEFEHL
  inherits: \setupbtx
2 KEY = VALUE
```

```
\listnamespaces
```

```
\litera {...}
* NUMMER
```

```
\litere {...}
* NUMMER
```

```
\llap {...}
* CONTENT
```

\loadanyfile [...] * FILE
\loadanyfileonce [...] * FILE
\loadbtxdefinitionfile [...] * FILE
\loadbtxreplacementfile [...] * FILE
\loadcldfile [...] * FILE
\loadcldfileonce [...] * FILE
\loadfontgoodies [...] * FILE
\loadluafile [...] * FILE
\loadluafileonce [...] * FILE
\loadspellchecklist [ <sup>1</sup> ...] [ <sup>2</sup> ...] 1 NAME 2 FILE
\loadtexfile [...] * FILE
\loadtexfileonce [...] * FILE
\loadtypescriptfile [...] * FILE
\localframed [ <sup>1</sup> ] [..., <sup>2</sup> ...,...]{ <sup>3</sup> ...} 1 NAME OPT 2 inherits: \seteazainconjurat 3 CONTENT
\localframedwithsettings [ <sup>1</sup> ] [..., <sup>2</sup> ...,...]{ <sup>3</sup> ...} 1 NAME 2 inherits: \seteazainconjurat 3 CONTENT
\localhsize
\localpopbox ... * CSNAME NUMBER
\localpopmacro \*... * CSNAME

$\backslash\text{localpushbox}$ $\dots$ $\ast$ CSNAME NUMBER
$\backslash\text{localpushmacro}$ $\backslash\dots$ $\ast$ CSNAME
$\backslash\text{localundefine}$ $\{\dots\}$ $\ast$ NAME
$\backslash\text{locatedfilepath}$
$\backslash\text{locatefilepath}$ $\{\dots\}$ $\ast$ FILE
$\backslash\text{locfilename}$ $\{\dots\}$ $\ast$ FILE
$\backslash\text{lomihi}$ $\{\dots\}$ $\{\dots\}$ $\{\dots\}$ 1 CONTENT 2 CONTENT 3 CONTENT
$\backslash\text{lowerbox}$ $\{\dots\}$ $\backslash\dots$ $\{\dots\}$ 1 DIMENSION 2 CSNAME 3 CONTENT
$\backslash\text{lowercased}$ $\{\dots\}$ $\ast$ TEXT
$\backslash\text{lowercasestring}$ $\dots$ $\backslash\text{to}$ $\backslash\dots$ 1 TEXT 2 CSNAME
$\backslash\text{lowerlefthdoubleninequote}$
$\backslash\text{lowerleftsingleninequote}$
$\backslash\text{lowerrighthdoubleninequote}$
$\backslash\text{lowerrightsingleninequote}$
$\backslash\text{LOWHIGH}$ $[\dots]$ $\{\dots\}$ $\{\dots\}$ 1 stanga dreapta 2 CONTENT 3 CONTENT
$\backslash\text{LOWMIDHIGH}$ $\{\dots\}$ $\{\dots\}$ $\{\dots\}$ 1 CONTENT 2 CONTENT 3 CONTENT
$\backslash\text{lrtbbox}$ $\{\dots\}$ $\{\dots\}$ $\{\dots\}$ $\{\dots\}$ $\{\dots\}$ 1 DIMENSION 2 DIMENSION 3 DIMENSION 4 DIMENSION 5 CONTENT

<code>\ltop ... {<sup>1</sup>...<sup>2</sup>}</code> 1    TEXT <sup>OPT</sup> 2    CONTENT
<code>\luacode {...}</code> *    BEFEHL
<code>\luaconditional \*..</code> *    CSNAME
<code>\luaenvironment ...</code> *    FILE
<code>\luaexpanded {...}</code> *    BEFEHL
<code>\luaexpr {...}</code> *    CONTENT
<code>\luafunction {...}</code> *    BEFEHL
<code>\luajitTeX</code>
<code>\luamajorversion</code>
<code>\luametaTeX</code>
<code>\luaminorversion</code>
<code>\luaparameterset {<sup>1</sup>...} {<sup>2</sup>...}</code> 1    NAME 2    CONTENT
<code>\luasetup {...}</code> *    NAME
<code>\luaTeX</code>
<code>\luaversion</code>
<code>\luna {...}</code> *    NUMMER
<code>\lungimelista</code>
<code>\METAFONT</code>
<code>\METAFUN</code>
<code>\METAPOST</code>
<code>\MetaFont</code>
<code>\MetaFun</code>

<code>\MetaPost</code>
<code>\MKII</code>
<code>\MKIV</code>
<code>\MKIX</code>
<code>\MKVI</code>
<code>\MKXI</code>
<code>\MONTHLONG {...}</code> *    NUMBER
<code>\MONTHSHORT {...}</code> *    NUMBER
<code>\MPanchor {...}</code> *    NAME
<code>\MPbetex {...}</code> *    NAME
<code>\MPc {...}</code> *    NAME
<code>\MPcode {...} {...}</code> 1    NAME        OPT 2    CONTENT
<code>\MPcolor {...}</code> *    COLOR
<code>\MPcoloronly {...}</code> *    COLOR
<code>\MPcolumn {...}</code> *    NAME
<code>\MPd {...}</code> *    NAME
<code>\MPdrawing {...}</code> *    CONTENT
<code>\MPfontsizehskip {...}</code> *    FONT
<code>\MPgetmultipars {...} {...}</code> 1    NAME 2    NAME
<code>\MPgetmultishape {...} {...}</code> 1    NAME 2    NAME

\MPgetposboxes {... <sup>1</sup> ,...} {... <sup>2</sup> } 1 NAME 2 NAME
\MPH {...} * NAME
\MPII
\MPIV
\MPinclusions [... <sup>1</sup> ] {... <sup>2</sup> } {... <sup>3</sup> } 1 + OPT OPT 2 NAME 3 CONTENT
\MPlleftskip {...} * NAME
\MPl1 {...} * NAME
\MPlr {...} * NAME
\MPls {...} * NAME
\MPmenubuttons {...} * NAME
\MPn {...} * NAME
\MPOptions {...} * COLOR
\MPOverlayanchor {...} * NAME
\MPP {...} * NAME
\MPPage {...} * NAME
\MPPardata {...} * NAME
\MPPplus {... <sup>1</sup> } {... <sup>2</sup> } {... <sup>3</sup> } 1 NAME 2 NUMMER 3 CONTENT
\MPPos {...} * NAME



$\backslash$ MPpositiongraphic {...} {... <sup>2</sup> ...,...} 1 NAME 2 KEY = VALUE
$\backslash$ MPposset {...} * NAME
$\backslash$ MPr {...} * NAME
$\backslash$ MPrawvar {...} {...} 1 NAME 2 KEY
$\backslash$ MPregion {...} * NAME
$\backslash$ MPrest {...} {...} 1 NAME 2 CONTENT
$\backslash$ MPrightskip {...} * NAME
$\backslash$ MPrs {...} * NAME
$\backslash$ MPstring {...} * NAME
$\backslash$ MPtext {...} * NAME
$\backslash$ MPtransparency {...} * COLOR
$\backslash$ MPul {...} * NAME
$\backslash$ MPur {...} * NAME
$\backslash$ MPVI
$\backslash$ MPv {...} {...} {...} 1 NAME 2 NUMMER 3 CONTENT
$\backslash$ MPvar {...} * KEY
$\backslash$ MPvariable {...} * KEY
$\backslash$ MPvv {...} {...} 1 NAME 2 CONTENT

\MPw {...} * NAME
\MPwhd {...} * NAME
\MPx {...} * NAME
\MPxy {...} * NAME
\MPxywhd {...} * NAME
\MPy {...} * NAME
\m [... <sup>1</sup> ] {... <sup>2</sup> } 1 NAME 2 CONTENT
\makecharacteractive ... * CHARACTER
\makerawcommalist [... <sup>1</sup> ,...] \ <sup>2</sup> ... 1 BEFEHL 2 CSNAME
\makestrutofbox ... * CSNAME NUMBER
\mapfontsize [... <sup>1</sup> ] [... <sup>2</sup> ] 1 DIMENSION 2 DIMENSION
\marcaje (... <sup>1</sup> ,...) (... <sup>2</sup> ,...) [... <sup>3</sup> ] 1 POSITION 2 POSITION 3 REFERENCE
\mare ... * CHARACTER
\margindata [... <sup>1</sup> ] [... <sup>2</sup> ... <sup>OPT</sup> ,...] [... <sup>3</sup> ... <sup>OPT</sup> ,...] {... <sup>4</sup> } 1 NAME 2 referinta = REFERENCE inherits: \setupmargindata 3 inherits: \setupmarginframed 4 CONTENT
\MARGINDATA [... <sup>1</sup> ... <sup>OPT</sup> ,...] [... <sup>2</sup> ... <sup>OPT</sup> ,...] {... <sup>3</sup> } 1 referinta = REFERENCE inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT instances: inleftmargin inrightmargin inoutermargin ininnermargin inleftedge inrightedge inouteredge ininneredge atleftmargin atrightmargin inleft inright inouter ininner inmargin inother margintext

```
\atleftmargin [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] {\stackrel{3}{...}}
1 referinta = REFERENCEOPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT
```

```
\atrightrightmargin [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] {\stackrel{3}{...}}
1 referinta = REFERENCEOPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT
```

```
\ininner [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] {\stackrel{3}{...}}
1 referinta = REFERENCEOPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT
```

```
\ininneredge [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] {\stackrel{3}{...}}
1 referinta = REFERENCEOPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT
```

```
\ininnermargin [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] {\stackrel{3}{...}}
1 referinta = REFERENCEOPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT
```

```
\inleft [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] {\stackrel{3}{...}}
1 referinta = REFERENCEOPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT
```

```
\inleftedge [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] {\stackrel{3}{...}}
1 referinta = REFERENCEOPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT
```

```
\inleftmargin [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] {\stackrel{3}{...}}
1 referinta = REFERENCEOPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT
```

```
\inmargin [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] {\stackrel{3}{...}}
1 referinta = REFERENCEOPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT
```

```
\inothert [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] {\stackrel{3}{...}}
1 referinta = REFERENCEOPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT
```

```
\inouter [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] {\stackrel{3}{...}}
1 referinta = REFERENCEOPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT
```

$\backslash\text{inouteredge}$ [ $\dots\overset{1}{=}\dots$ ] [ $\dots\overset{2}{=}\dots$ ] {...} 1    referinta = REFERENCE <sup>OPT</sup> inherits: \setupmargindata 2    inherits: \setupmarginframed 3    CONTENT
$\backslash\text{inoutermargin}$ [ $\dots\overset{1}{=}\dots$ ] [ $\dots\overset{2}{=}\dots$ ] {...} 1    referinta = REFERENCE <sup>OPT</sup> inherits: \setupmargindata 2    inherits: \setupmarginframed 3    CONTENT
$\backslash\text{inright}$ [ $\dots\overset{1}{=}\dots$ ] [ $\dots\overset{2}{=}\dots$ ] {...} 1    referinta = REFERENCE <sup>OPT</sup> inherits: \setupmargindata 2    inherits: \setupmarginframed 3    CONTENT
$\backslash\text{inrightedge}$ [ $\dots\overset{1}{=}\dots$ ] [ $\dots\overset{2}{=}\dots$ ] {...} 1    referinta = REFERENCE <sup>OPT</sup> inherits: \setupmargindata 2    inherits: \setupmarginframed 3    CONTENT
$\backslash\text{inrightmargin}$ [ $\dots\overset{1}{=}\dots$ ] [ $\dots\overset{2}{=}\dots$ ] {...} 1    referinta = REFERENCE <sup>OPT</sup> inherits: \setupmargindata 2    inherits: \setupmarginframed 3    CONTENT
$\backslash\text{margintext}$ [ $\dots\overset{1}{=}\dots$ ] [ $\dots\overset{2}{=}\dots$ ] {...} 1    referinta = REFERENCE <sup>OPT</sup> inherits: \setupmargindata 2    inherits: \setupmarginframed 3    CONTENT
$\backslash\text{markcontent}$ [ $\overset{1}{\dots}$ ] {...} 1    reset tot NAME <sup>OPT</sup> 2    CONTENT
$\backslash\text{markedpages}$ [...] *    NAME
$\backslash\text{markinjector}$ [...] *    NAME
$\backslash\text{markpage}$ [ $\overset{1}{\dots}$ ] [ $\dots\overset{2}{=}\dots$ ] 1    NAME <sup>OPT</sup> 2    [-+]NUMBER
$\backslash\text{mat}$ {...} *    CONTENT
$\backslash\text{matematica}$ [ $\overset{1}{\dots}$ ] {...} 1    NAME <sup>OPT</sup> 2    CONTENT
$\backslash\text{math}$ [ $\overset{1}{\dots}$ ] {...} 1    NAME <sup>OPT</sup> 2    CONTENT
$\backslash\text{mathbf}$

<code>\mathbi</code>
<code>\mathblackboard</code>
<code>\mathbs</code>
$\backslash\text{MATHCOMMAND}$ $\{\dots\}^1\{\dots\}^2$ 1    TEXT                    OPT            OPT 2    TEXT
<code>\mathdefault</code>
$\backslash\text{mathdouble}$ $[\dots]^1\{\dots\}^2\{\dots\}^3\{\dots\}^4$ 1    ambele vfenced <sup>OPT</sup> 2    NUMMER 3    TEXT 4    TEXT
$\backslash\text{MATHDOUBLEEXTENSIBLE}$ $\{\dots\}^1\{\dots\}^2$ 1    TEXT 2    TEXT instances: doublebar doublebrace doubleparent doublebracket overbarunderbar overbraceunderbrace overparentunderparent overbracketunderbracket
$\backslash\text{doublebar}$ $\{\dots\}^1\{\dots\}^2$ 1    TEXT 2    TEXT
$\backslash\text{doublebrace}$ $\{\dots\}^1\{\dots\}^2$ 1    TEXT 2    TEXT
$\backslash\text{doublebracket}$ $\{\dots\}^1\{\dots\}^2$ 1    TEXT 2    TEXT
$\backslash\text{doubleparent}$ $\{\dots\}^1\{\dots\}^2$ 1    TEXT 2    TEXT
$\backslash\text{overbarunderbar}$ $\{\dots\}^1\{\dots\}^2$ 1    TEXT 2    TEXT
$\backslash\text{overbraceunderbrace}$ $\{\dots\}^1\{\dots\}^2$ 1    TEXT 2    TEXT
$\backslash\text{overbracketunderbracket}$ $\{\dots\}^1\{\dots\}^2$ 1    TEXT 2    TEXT
$\backslash\text{overparentunderparent}$ $\{\dots\}^1\{\dots\}^2$ 1    TEXT 2    TEXT

`\MATHEXTENSIBLE {...} {...}`

1 TEXT

OPT

OPT

2 TEXT

instances: xrel xequal xleftarrow xrightarrow xleftrightharrow xLeftarrow xRightarrow  
xleftrightharpoon xtwoheadleftarrow xtwoheadrightarrow xmapsto xhookleftarrow xhookrightarrow  
xleftharpoondown xleftharpoonup xrightarpoon xrightarpoonup xrightoverleftarrow  
xleftrightharpoons xrightleftharpoons xtriplerel mrel mequal mleftarrow mrightarrow mleftrightharpoon  
mLeftarrow mRightarrow mLefttrightharpoon mtwoheadleftarrow mtwoheadrightarrow mmapsto mhookleftarrow  
mhookrightarrow mleftharpoondown mleftharpoonup mrightarpoon mrightarpoonup mrightoverleftarrow  
mleftrightharpoons mrightleftharpoons mtriplerel eleftrightarrowfill erightarrowfill eleftrightarrowfill  
etwoheadrightarrowfill eleftharpoondownfill eleftharpoonupfill erightharpoondownfill  
erightharpoonupfill eoverbarfill eunderbarfill eoverbracefill eunderbracefill eoverparentfill  
eunderparentfill eoverbracketfill eunderbracketfill trel tequal tmapsto tleftarrow trightarrow  
tleftrightarrow tLeftarrow tRightarrow tleftrightharpoon ttwoheadleftarrow ttwoheadrightarrow  
thookleftarrow thookrightarrow tleftharpoondown tleftharpoonup trightharpoondown trightharpoonup  
trightoverleftarrow tleftrightharpoons trightleftharpoons ttriplerel cleftarrow crightarrow  
crightoverleftarrow

`\cleftarrow {...} {...}`

1 TEXT

OPT

OPT

2 TEXT

`\crightarrow {...} {...}`

1 TEXT

OPT

OPT

2 TEXT

`\crightoverleftarrow {...} {...}`

1 TEXT

OPT

OPT

2 TEXT

`\eleftrightarrowfill {...} {...}`

1 TEXT

OPT

OPT

2 TEXT

`\eleftharpoondownfill {...} {...}`

1 TEXT

OPT

OPT

2 TEXT

`\eleftharpoonupfill {...} {...}`

1 TEXT

OPT

OPT

2 TEXT

`\eleftrightarrowfill {...} {...}`

1 TEXT

OPT

OPT

2 TEXT

`\eoverbarfill {...} {...}`

1 TEXT

OPT

OPT

2 TEXT

`\eoverbracefill {...} {...}`

1 TEXT

OPT

OPT

2 TEXT

`\eoverbracketfill {...} {...}`

1 TEXT

OPT

OPT

2 TEXT

`\eoverparentfill {...} {...}`

1 TEXT

OPT

OPT

2 TEXT

$$\rightarrowfill \{...\} \{...\}$$

1	TEXT	OPT	OPT
---	------	-----	-----

2 TEXT

$$\text{\texttt{\textbackslash erightharpoonowdownfill}} \{...\} \{...\}$$

1	TEXT	OPT	OPT
---	------	-----	-----

1	TEXT
2	TEXT

$$\text{\textbackslash erightharpoonupupfill} \{...\} \{...\}$$

1	TEXT	OPT	OPT
---	------	-----	-----

2 TEXT

$$\etwoheadrightarrowfill \{...\} \{...\}$$

1	TEXT	OPT	OPT
---	------	-----	-----

2 TEXT

$$\text{\eunderbarfill } \{...\}^{\text{\eunderbarfill}} \{...\}^{\text{\eunderbarfill}}$$

1	TEXT	OPT	OPT
---	------	-----	-----

2 TEXT

$$\backslash eunderbracefill \{...\} \{...\}$$

1	TEXT	OPT	OPT
---	------	-----	-----

```
1 TEXT
2 TEXT
```

$$\underbrace{\hspace{1cm}}^{\scriptscriptstyle{1}} \underbrace{\hspace{1cm}}^{\scriptscriptstyle{2}}$$

1	TEXT	OPT	OPT
---	------	-----	-----

```
1  TEXT
2  TEXT
```

$$\text{\eunderparentfill } \{...\}^1 \{...\}^2$$

1	TEXT	OPT	OPT
---	------	-----	-----

1 TEXT  
2 TEXT

$$\backslash mequal \{.\overset{1}{.}\} \{.\overset{2}{.}\}$$

1	TEXT	OPT	OPT
---	------	-----	-----

2 TEXT

 $\hookrightarrow \{...\}^1 \{...\}^2$ 

1	TEXT	OPT	OPT
---	------	-----	-----

2 TEXT

 $\hookrightarrow \{...\} \{...\}$ 

1	TEXT	OPT	OPT
---	------	-----	-----

```
1  TEXT
2  TEXT
```

$$\backslash mLeftarrow \{...\} \{...\}$$

1	TEXT	OPT	OPT
---	------	-----	-----

2 TEXT

$$\mathrel{\mathop{\rightarrow}\limits^{\cdot}\!\!\!\rightarrow} \{...\} \{...\}$$

1	TEXT	OPT	OPT
---	------	-----	-----

2 TEXT

$$\mleftarrow{\dots}\{\dots\}$$

1	TEYT	OPT	OPT
---	------	-----	-----

1 TEXT  
2 TEXT

 $\leftharpoonown \{...\} \{...\}$ 

1	TEXT	OPT	OPT
1	TEXT	OPT	OPT

2 TEXT

$\mleftharpoonup \{...\} \{...\}$ 1    TEXT                    OPT            OPT 2    TEXT
$\mleftrightharpoonup \{...\} \{...\}$ 1    TEXT                    OPT            OPT 2    TEXT
$\mleftrightharpoons \{...\} \{...\}$ 1    TEXT                    OPT            OPT 2    TEXT
$\mmapsto \{...\} \{...\}$ 1    TEXT                    OPT            OPT 2    TEXT
$\mRrightarrow \{...\} \{...\}$ 1    TEXT                    OPT            OPT 2    TEXT
$\mrel \{...\} \{...\}$ 1    TEXT    OPT            OPT 2    TEXT
$\mrightarrow \{...\} \{...\}$ 1    TEXT                    OPT            OPT 2    TEXT
$\mrightharpoondown \{...\} \{...\}$ 1    TEXT                    OPT            OPT 2    TEXT
$\mrightharpoonup \{...\} \{...\}$ 1    TEXT                    OPT            OPT 2    TEXT
$\mrightharpoons \{...\} \{...\}$ 1    TEXT                    OPT            OPT 2    TEXT
$\mrightharpoonleft \{...\} \{...\}$ 1    TEXT                    OPT            OPT 2    TEXT
$\mrightharpoonright \{...\} \{...\}$ 1    TEXT                    OPT            OPT 2    TEXT
$\mrightarrowtail \{...\} \{...\}$ 1    TEXT                    OPT            OPT 2    TEXT
$\mtwoheadleftarrow \{...\} \{...\}$ 1    TEXT                    OPT            OPT 2    TEXT
$\mtwoheadrightarrow \{...\} \{...\}$ 1    TEXT                    OPT            OPT 2    TEXT
$\tequal \{...\} \{...\}$ 1    TEXT                    OPT            OPT 2    TEXT



$\hookleftarrow$ $\{...\}^{1}\{...\}^{2}$ 1    TEXT                    OPT            OPT 2    TEXT
$\hookrightarrow$ $\{...\}^{1}\{...\}^{2}$ 1    TEXT                    OPT            OPT 2    TEXT
$\leftarrow$ $\{...\}^{1}\{...\}^{2}$ 1    TEXT                    OPT            OPT 2    TEXT
$\leftrightarrow$ $\{...\}^{1}\{...\}^{2}$ 1    TEXT                    OPT            OPT 2    TEXT
$\rightarrow$ $\{...\}^{1}\{...\}^{2}$ 1    TEXT                    OPT            OPT 2    TEXT
$\leftharpoonup$ $\{...\}^{1}\{...\}^{2}$ 1    TEXT                    OPT            OPT 2    TEXT
$\leftharpoonup$ $\{...\}^{1}\{...\}^{2}$ 1    TEXT                    OPT            OPT 2    TEXT
$\leftrightharpoonup$ $\{...\}^{1}\{...\}^{2}$ 1    TEXT                    OPT            OPT 2    TEXT
$\leftrightharpoons$ $\{...\}^{1}\{...\}^{2}$ 1    TEXT                    OPT            OPT 2    TEXT
$\mapsto$ $\{...\}^{1}\{...\}^{2}$ 1    TEXT                    OPT            OPT 2    TEXT
$\rightarrow$ $\{...\}^{1}\{...\}^{2}$ 1    TEXT                    OPT            OPT 2    TEXT
$\rel$ $\{...\}^{1}\{...\}^{2}$ 1    TEXT    OPT            OPT 2    TEXT
$\rightarrow$ $\{...\}^{1}\{...\}^{2}$ 1    TEXT                    OPT            OPT 2    TEXT
$\rightharpoonup$ $\{...\}^{1}\{...\}^{2}$ 1    TEXT                    OPT            OPT 2    TEXT
$\rightharpoonup$ $\{...\}^{1}\{...\}^{2}$ 1    TEXT                    OPT            OPT 2    TEXT
$\rightharpoonup$ $\{...\}^{1}\{...\}^{2}$ 1    TEXT                    OPT            OPT 2    TEXT

$\backtrightlefttharpoons$ $\{...\}^1\{...\}^2$ 1    TEXT                      OPT              OPT 2    TEXT
$\rightarrowoverleftarrow{\hspace{1cm}}$ $\{...\}^1\{...\}^2$ 1    TEXT                      OPT              OPT 2    TEXT
$\triplebarrel$ $\{...\}^1\{...\}^2$ 1    TEXT                      OPT              OPT 2    TEXT
$\twoheadleftarrow$ $\{...\}^1\{...\}^2$ 1    TEXT                      OPT              OPT 2    TEXT
$\twoheadrightarrow$ $\{...\}^1\{...\}^2$ 1    TEXT                      OPT              OPT 2    TEXT
$\xequal$ $\{...\}^1\{...\}^2$ 1    TEXT                      OPT              OPT 2    TEXT
$\hookrightarrow$ $\{...\}^1\{...\}^2$ 1    TEXT                      OPT              OPT 2    TEXT
$\hookrightarrow$ $\{...\}^1\{...\}^2$ 1    TEXT                      OPT              OPT 2    TEXT
$\xleftarrow{\hspace{1cm}}$ $\{...\}^1\{...\}^2$ 1    TEXT                      OPT              OPT 2    TEXT
$\xleftrightarrow{\hspace{1cm}}$ $\{...\}^1\{...\}^2$ 1    TEXT                      OPT              OPT 2    TEXT
$\xleftarrow{\hspace{1cm}}$ $\{...\}^1\{...\}^2$ 1    TEXT                      OPT              OPT 2    TEXT
$\xleftharpoonup{\hspace{1cm}}$ $\{...\}^1\{...\}^2$ 1    TEXT                      OPT              OPT 2    TEXT
$\xleftharpoonup{\hspace{1cm}}$ $\{...\}^1\{...\}^2$ 1    TEXT                      OPT              OPT 2    TEXT
$\xleftrightarrow{\hspace{1cm}}$ $\{...\}^1\{...\}^2$ 1    TEXT                      OPT              OPT 2    TEXT
$\xleftrightharpoons{\hspace{1cm}}$ $\{...\}^1\{...\}^2$ 1    TEXT                      OPT              OPT 2    TEXT

1	TEXT	OPT	OPT
2	TEXT		

1	TEXT	OPT	OPT
2	TEXT		

```

1  TEXT  OPT      OPT
2  TEXT

```

1	TEXT	OPT	OPT
2	TEXT		

1	TEXT	OPT	OPT
2	TEXT		

1	TEXT	OPT	OPT
2	TEXT		

1	TEXT	OPT	OPT
2	TEXT		

1	TEXT	OPT	OPT
2	TEXT		

1	TEXT	OPT	OPT
2	TEXT		

1	TEXT	OPT	OPT
2	TEXT		

1	TEXT	OPT	OPT
2	TEXT		

 $\mathfrak{f}$ 

```

1 inherits: \setupmathframednpf
2 CONTENT

```

```
1 inherits: \setupmathframedOPT
2 CONTENT
```

```
1 inherits: \setupOPTmathframed
2 CONTENT
```

$\mframed$ [ $\dots$ $\stackrel{1}{=}$ $\dots$ ] $\{\dots\}$ 1 inherits: $\text{\setupmathframed}$ 2 CONTENT
$\mathfunction$ $\{\dots\}$ * CONTENT
$\mathit$
$\mathit$
$\mathMATRIX$ $\{\dots\}$ * CONTENT
$\mathop$ $\{\dots\}$ * CONTENT
$\mathORNAMENT$ $\{\dots\}$ * CONTENT
$\mathover$ [ $\dots$ ] $\{\dots\}$ $\{\dots\}$ 1 sus $\text{\vfenced}$ <sup>OPT</sup> 2 NUMBER 3 TEXT
$\mathOVEREXTENSIBLE$ $\{\dots\}$ * TEXT
$\mathOVERTEXTEXTENSIBLE$ $\{\dots\}$ $\{\dots\}$ 1 TEXT 2 TEXT instances:
$\mathRADICAL$ [ $\dots$ ] $\{\dots\}$ 1 TEXT <sup>OPT</sup> 2 CONTENT
$\mathrm$
$\mathscript$
$\mathsl$
$\mathss$
$\mathtext$ $\dots$ $\{\dots\}$ 1 TEXT <sup>OPT</sup> 2 TEXT
$\mathtextbf$ $\dots$ $\{\dots\}$ 1 TEXT <sup>OPT</sup> 2 TEXT
$\mathtextbi$ $\dots$ $\{\dots\}$ 1 TEXT <sup>OPT</sup> 2 TEXT

$\backslash\mathtextbs \dots^{.1}\{...\}$ 1    TEXT            OPT 2    TEXT
$\backslash\mathtextit \dots^{.1}\{...\}$ 1    TEXT            OPT 2    TEXT
$\backslash\mathtextsl \dots^{.1}\{...\}$ 1    TEXT            OPT 2    TEXT
$\backslash\mathtexttf \dots^{.1}\{...\}$ 1    TEXT            OPT 2    TEXT
$\backslash\mathtf$
$\backslash\mathtripler [\dots]^1\{...\}^2\{...\}^3\{...\}^4$ 1    NAME            OPT            OPT            OPT            OPT 2    TEXT 3    TEXT 4    TEXT
$\backslash\mathtriplet [\dots]^1\{...\}^2\{...\}^3\{...\}^4$ 1    NAME            OPT            OPT            OPT            OPT 2    TEXT 3    TEXT 4    TEXT
$\backslash\mathtt$
$\backslash\mathunder [\dots]^1\{...\}^2\{...\}^3$ 1    subsol    vfence $\mathbb{F}$ 2    NUMMER 3    TEXT
$\backslash\mathunderextensible \{...\}^*$ *    TEXT
$\backslash\mathunderextextensible \{...\}^1\{...\}^2$ 1    TEXT 2    TEXT instances:
$\backslash\mathunstacked$
$\backslash\mathupright$
$\backslash\mathword \dots^{.1}\{...\}^2$ 1    TEXT            OPT 2    TEXT
$\backslash\mathwordbf \dots^{.1}\{...\}^2$ 1    TEXT            OPT 2    TEXT
$\backslash\mathwordbi \dots^{.1}\{...\}^2$ 1    TEXT            OPT 2    TEXT

$\backslash\mathrm{mathwordbs} \mathrel{\mathop{\cdot}\limits^1} \dots \{\mathrel{\mathop{\cdot}\limits^2} \dots\}$ 1    TEXT            OPT 2    TEXT
$\backslash\mathrm{mathwordit} \mathrel{\mathop{\cdot}\limits^1} \dots \{\mathrel{\mathop{\cdot}\limits^2} \dots\}$ 1    TEXT            OPT 2    TEXT
$\backslash\mathrm{mathwordsl} \mathrel{\mathop{\cdot}\limits^1} \dots \{\mathrel{\mathop{\cdot}\limits^2} \dots\}$ 1    TEXT            OPT 2    TEXT
$\backslash\mathrm{mathwordtf} \mathrel{\mathop{\cdot}\limits^1} \dots \{\mathrel{\mathop{\cdot}\limits^2} \dots\}$ 1    TEXT            OPT 2    TEXT
$\backslash\mathrm{maxaligned} \{.*\}$ *    CONTENT
$\backslash\mathrm{mbox} \{.*\}$ *    CONTENT
$\backslash\mathrm{measure} \{.*\}$ *    NAME
$\backslash\mathrm{measured} \{.*\}$ *    NAME
$\backslash\mathrm{mediu} [.*]$ *    FILE
$\backslash\mathrm{mediu} \mathrel{\mathop{\cdot}\limits^*}$ *    FILE
$\backslash\mathrm{medskip}$
$\backslash\mathrm{medspace}$
$\backslash\mathrm{menuinteractiune} [.\mathrel{\mathop{\cdot}\limits^1}] [\dots\mathrel{\mathop{\cdot}\limits^2}\dots]$ 1    NAME                    OPT 2    inherits: \seteazameniinteractiune
$\backslash\mathrm{message} \{.*\}$ *    TEXT
$\backslash\mathrm{mfence} \{.*\}$ *    CHARACTER
$\backslash\mathrm{mfunction} \{.*\}$ *    CONTENT
$\backslash\mathrm{mfunctionlabeltext} \{.*\}$ *    NAME
$\backslash\mathrm{mhbox} \{.*\}$ *    CONTENT
$\backslash\mathrm{mic}$

<code>\micaldin</code>
<code>\micaldininclinat</code>
<code>\micinclinat</code>
<code>\micinclinataldin</code>
<code>\micitalicaldin</code>
<code>\micnormal</code>
<code>\mictype</code>
<code>\middlealigned {...}</code> *    CONTENT
<code>\middlebox {...}</code> *    CONTENT
<code>\midhbox {...}</code> *    CONTENT
<code>\midsubsentence</code>
<code>\minimalhbox <sup>1</sup>... {<sup>2</sup>...}</code> 1    TEXT            OPT 2    CONTENT
<code>\mixedcaps {...}</code> *    TEXT
<code>\mkvibuffer [...]</code> *    BUFFER            OPT
<code>\moduleparameter {...} {...}</code> 1    FILE 2    KEY
<code>\molecule {...}</code> *    CONTENT
<code>\mono</code>
<code>\monoaldin</code>
<code>\mononormal</code>
<code>\monthlong {...}</code> *    NUMMER
<code>\monthshort {...}</code> *    NUMMER
<code>\mprandomnumber</code>

<code>\mtext {...}</code> *   CONTENT
<code>\NormalizeFontHeight \<sup>1</sup>... {<sup>2</sup>...} {<sup>3</sup>...} {<sup>4</sup>...}</code> 1   CSNAME 2   TEXT 3   DIMENSION 4   FONT
<code>\NormalizeFontWidth \<sup>1</sup>... {<sup>2</sup>...} {<sup>3</sup>...} {<sup>4</sup>...}</code> 1   CSNAME 2   TEXT 3   DIMENSION 4   FONT
<code>\NormalizeTextHeight {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...}</code> 1   FONT 2   DIMENSION 3   TEXT
<code>\NormalizeTextWidth {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...}</code> 1   FONT 2   DIMENSION 3   TEXT
<code>\Numere {...}</code> *   NUMMER
<code>\Numereromane {...}</code> *   NUMMER
<code>\namedheadnumber {...}</code> *   ABSCHNITT
<code>\namedstructureheadlocation {...}</code> *   ABSCHNITT
<code>\namedstructureuservariable {<sup>1</sup>...} {<sup>2</sup>...}</code> 1   ABSCHNITT 2   KEY
<code>\namedstructurevariable {<sup>1</sup>...} {<sup>2</sup>...}</code> 1   ABSCHNITT 2   KEY
<code>\namedtaggedlabeltexts {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...} {<sup>4</sup>...} {<sup>5</sup>...}</code> 1   NAME 2   NAME 3   NAME 4   NAME 5   CONTENT
<code>\naturalhbox <sup>1</sup>... {<sup>2</sup>...}</code> 1   TEXT           OPT 2   CONTENT
<code>\naturalhpack <sup>1</sup>... {<sup>2</sup>...}</code> 1   TEXT           OPT 2   CONTENT
<code>\naturalvbox <sup>1</sup>... {<sup>2</sup>...}</code> 1   TEXT           OPT 2   CONTENT



$\backslash\text{naturalvcenter}$ $\overset{1}{\dots} \{\overset{2}{\dots}\}$ 1 TEXT OPT 2 CONTENT
$\backslash\text{naturalvpack}$ $\overset{1}{\dots} \{\overset{2}{\dots}\}$ 1 TEXT OPT 2 CONTENT
$\backslash\text{naturalvtop}$ $\overset{1}{\dots} \{\overset{2}{\dots}\}$ 1 TEXT OPT 2 CONTENT
$\backslash\text{naturalwd}$ $\dots$ * CSNAME NUMBER
$\backslash\text{necunoscut}$
$\backslash\text{negatecolorbox}$ $\dots$ * CSNAME NUMBER
$\backslash\text{negated}$ $\{\dots\}$ * TEXT
$\backslash\text{negemspace}$
$\backslash\text{negenspace}$
$\backslash\text{negthinspace}$
$\backslash\text{newattribute}$ $\backslash\dots$ * CSNAME
$\backslash\text{newcatcodetable}$ $\backslash\dots$ * CSNAME
$\backslash\text{newcounter}$ $\backslash\dots$ * CSNAME
$\backslash\text{newevery}$ $\overset{1}{\backslash\dots} \overset{2}{\backslash\dots}$ 1 CSNAME 2 CSNAME
$\backslash\text{newfrenchspacing}$
$\backslash\text{newmode}$ $\{\dots\}$ * NAME
$\backslash\text{newsignal}$ $\backslash\dots$ * CSNAME
$\backslash\text{newsystemmode}$ $\{\dots\}$ * NAME
$\backslash\text{nextbox}$
$\backslash\text{nextboxdp}$



<code>\noflocalfloats</code>
<code>\noheightstrut</code>
<code>\noindentation</code>
<code>\noitem</code>
<code>\nokap {...}</code> <code>* TEXT</code>
<code>\nonfrenchspacing</code>
<code>\nonmathematics {...}</code> <code>* CONTENT</code>
<code>\normal</code>
<code>\normalboldface</code>
<code>\normalframedwithsettings [...<sup>1</sup>...<sup>2</sup>...] {...}</code> <code>1 inherits: \seteazainconjurat</code> <code>2 CONTENT</code>
<code>\normalitalicface</code>
<code>\normalizebodyfontsize \<sup>1</sup>... {<sup>2</sup>...}</code> <code>1 CSNAME</code> <code>2 DIMENSION</code>
<code>\normalizedfontsize</code>
<code>\normalizefontdepth \<sup>1</sup>... {<sup>2</sup>...} {<sup>3</sup>...} {<sup>4</sup>...}</code> <code>1 CSNAME</code> <code>2 TEXT</code> <code>3 DIMENSION</code> <code>4 FONT</code>
<code>\normalizefontheight \<sup>1</sup>... {<sup>2</sup>...} {<sup>3</sup>...} {<sup>4</sup>...}</code> <code>1 CSNAME</code> <code>2 TEXT</code> <code>3 DIMENSION</code> <code>4 FONT</code>
<code>\normalizefontline \<sup>1</sup>... {<sup>2</sup>...} {<sup>3</sup>...} {<sup>4</sup>...}</code> <code>1 CSNAME</code> <code>2 TEXT</code> <code>3 DIMENSION</code> <code>4 FONT</code>
<code>\normalizefontwidth \<sup>1</sup>... {<sup>2</sup>...} {<sup>3</sup>...} {<sup>4</sup>...}</code> <code>1 CSNAME</code> <code>2 TEXT</code> <code>3 DIMENSION</code> <code>4 FONT</code>
<code>\normalizetextdepth {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...}</code> <code>1 FONT</code> <code>2 DIMENSION</code> <code>3 TEXT</code>

<code>\normalizetextheight {...} {...} {...}</code> 1 FONT 2 DIMENSION 3 TEXT
<code>\normalizetextline {...} {...} {...}</code> 1 FONT 2 DIMENSION 3 TEXT
<code>\normalizetextwidth {...} {...} {...}</code> 1 FONT 2 DIMENSION 3 TEXT
<code>\normalslantedface</code>
<code>\normaltypeface</code>
<code>\nota [...<sup>1</sup>] [...<sup>2</sup>]</code> 1 NAME OPT 2 REFERENCE
<code>\NOTE [...,<sup>1</sup>...] {...<sup>2</sup>}</code> 1 REFERENCE <sup>PT</sup> 2 TEXT instances: footnote endnote
<code>\NOTE [...,<sup>*</sup>...] [...]</code> * titlu = TEXT semncarte = TEXT lista = TEXT referinta = REFERENCE instances: footnote endnote
<code>\endnote [...,<sup>*</sup>...] [...]</code> * titlu = TEXT semncarte = TEXT lista = TEXT referinta = REFERENCE
<code>\footnote [...,<sup>*</sup>...] [...]</code> * titlu = TEXT semncarte = TEXT lista = TEXT referinta = REFERENCE
<code>\endnote [...,<sup>1</sup>...] {...<sup>2</sup>}</code> 1 REFERENCE OPT 2 TEXT
<code>\footnote [...,<sup>1</sup>...] {...<sup>2</sup>}</code> 1 REFERENCE OPT 2 TEXT
<code>\notesymbol [...<sup>1</sup>] [...<sup>2</sup>]</code> 1 NAME OPT 2 REFERENCE
<code>\notragged</code>

<code>\ntimes {...} {...}</code> 1 TEXT 2 NUMMER
<code>\numarformula [...,*,...]</code> * REFERENCE OPT
<code>\numarpagina</code>
<code>\numartitlu [...] [...]</code> 1 ABSCHNITT OPT 2 precedent curent urmatorul primul ultim
<code>\numartitlucurent</code>
<code>\numberofpoints {...}</code> * DIMENSION
<code>\numere {...}</code> * NUMMER
<code>\numereromane {...}</code> * NUMMER
<code>\obeydepth</code>
<code>\objectdepth</code>
<code>\objectheight</code>
<code>\objectmargin</code>
<code>\objectwidth</code>
<code>\obox {...}</code> * CONTENT
<code>\offset [...,*,...] {...}</code> 1 inherits: \setupoffset OPT 2 CONTENT
<code>\offsetbox [...,*,...] \^... {...}</code> 1 inherits: \setupoffsetbox OPT 2 CSNAME 3 CONTENT
<code>\olinie [...]</code> * REFERENCE
<code>\onedigitrounding {...}</code> * NUMMER
<code>\ordinaldaynumber {...}</code> * NUMMER
<code>\ordinalstr {...}</code> * TEXT

$\backslash\text{ornamenttext}$ [ $\dots$ , $\dots$ , $\overset{1}{=}\dots$ , $\dots$ ] [ $\dots$ , $\dots$ , $\overset{2}{=}\dots$ , $\dots$ ] $\{\dots\}$ $\{\dots\}$ 1    alternativ = a b inherits: \setupcollector 2    stil       = STYLE BEFEHL culoare = COLOR inherits: \seteazainconjurat 3    TEXT 4    CONTENT
$\backslash\text{ornamenttext}$ [ $\overset{1}{.}\dots$ ] $\{\overset{2}{.}\dots\}$ $\{\overset{3}{.}\dots\}$ 1    NAME 2    TEXT 3    CONTENT
$\backslash\text{ornamenttext}$ [ $\dots$ , $\dots$ , $\overset{1}{=}\dots$ , $\dots$ ] [ $\dots$ , $\dots$ , $\overset{2}{=}\dots$ , $\dots$ ] $\{\dots\}$ $\{\dots\}$ 1    alternativ = a b inherits: \setupplayer 2    inherits: \setuplayeredtext 3    TEXT 4    CONTENT
$\backslash\text{ORNAMENT}$ $\{\overset{1}{.}\dots\}$ $\{\overset{2}{.}\dots\}$ 1    TEXT 2    CONTENT
$\backslash\text{outputfilename}$
$\backslash\text{outputstreambox}$ [ $\dots$ ] *    NAME
$\backslash\text{outputstreamcopy}$ [ $\dots$ ] *    NAME
$\backslash\text{outputstreamunvbox}$ [ $\dots$ ] *    NAME
$\backslash\text{outputstreamunvcopy}$ [ $\dots$ ] *    NAME
$\backslash\text{over}$ [ $\dots$ ] *    REFERENCE
$\backslash\text{overlaybutton}$ [ $\dots$ ] *    REFERENCE
$\backslash\text{overlaybutton}$ $\{\dots\}$ *    REFERENCE
$\backslash\text{overlaycolor}$
$\backslash\text{overlaydepth}$
$\backslash\text{overlayfigure}$ $\{\dots\}$ *    FILE
$\backslash\text{overlayheight}$
$\backslash\text{overlayimage}$ $\{\dots\}$ *    FILE

<code>\overlaylinecolor</code>
<code>\overlaylinewidth</code>
<code>\overlayoffset</code>
<code>\overlayrollbutton [...] [...]</code> 1    REFERENCE 2    REFERENCE
<code>\overlaywidth</code>
<code>\overloaderror</code>
<code>\overset {...} {...}</code> 1    TEXT 2    TEXT
<code>\PDFcolor {...}</code> *    NAME
<code>\PDFETEX</code>
<code>\PDFTEX</code>
<code>\PICTEX</code>
<code>\PiCTeX</code>
<code>\PointsToBigPoints {...} \^...</code> 1    DIMENSION 2    CSNAME
<code>\PointsToReal {...} \^...</code> 1    DIMENSION 2    CSNAME
<code>\PointsToWholeBigPoints {...} \^...</code> 1    DIMENSION 2    CSNAME
<code>\PPCHTEX</code>
<code>\PPCHTeX</code>
<code>\PRAGMA</code>
<code>\PtToCm {...}</code> *    DIMENSION
<code>\pagearea [...] [...] [...]</code> 1    sus antet text subsof subsofT 2    text margine bordura 3    stanga dreapta lefttext middletext righttext

<p><b>\pagebreak</b> [...,*,...]</p> <p>* gol antet subsof<sup>OPT</sup>dummy incadrat NUMMER +NUMMER implicit reset dezactivat da nu marcaj blank preferinta preferintamare stanga dreapta par impar cvadрупul ultim ultimpagina start stop NAME</p>
<p><b>\pagefigure</b> [...]<sup>1.</sup> [...,...]<sup>2.</sup> [...,...]</p> <p>1 FILE <sup>OPT</sup></p> <p>2 offset = implicit overlay niciunul DIMENSION</p>
<p><b>\pageinjection</b> [...]<sup>1.</sup> [...,...]<sup>2.</sup> [...,...]</p> <p>1 NAME <sup>OPT</sup> <sup>OPT</sup></p> <p>2 KEY = VALUE</p>
<p><b>\pageinjection</b> [...,...]<sup>1.</sup> [...,...]<sup>2.</sup> [...,...]</p> <p>1 inherits: \setuppageinjection<sup>OPT</sup> <sup>OPT</sup></p> <p>2 KEY = VALUE</p>
<p><b>\pagestaterealpage</b> {...}<sup>1.</sup> {...}<sup>2.</sup></p> <p>1 NAME</p> <p>2 NAME NUMMER</p>
<p><b>\pagestaterealpageorder</b> {...}<sup>1.</sup> {...}<sup>2.</sup></p> <p>1 NAME</p> <p>2 NAME NUMMER</p>
<p><b>\pagina</b> [...,*,...]</p> <p>* inherits: \<sup>OPT</sup>pagebreak</p>
<p><b>\paletsize</b></p>
<p><b>\PARAGRAPHS</b></p>
<p><b>\pastreazablocuri</b> [...,...]<sup>1.</sup> [...,...]<sup>2.</sup></p> <p>1 NAME <sup>OPT</sup></p> <p>2 NAME</p>
<p><b>\pdfactualtext</b> {...}<sup>1.</sup> {...}<sup>2.</sup></p> <p>1 CONTENT</p> <p>2 TEXT</p>
<p><b>\pdfbackendactualtext</b> {...}<sup>1.</sup> {...}<sup>2.</sup></p> <p>1 CONTENT</p> <p>2 TEXT</p>
<p><b>\pdfbackendcurrentresources</b></p>
<p><b>\pdfbackendsetcatalog</b> {...}<sup>1.</sup> {...}<sup>2.</sup></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><b>\pdfbackendsetcolorspace</b> {...}<sup>1.</sup> {...}<sup>2.</sup></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><b>\pdfbackendsettextgstate</b> {...}<sup>1.</sup> {...}<sup>2.</sup></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><b>\pdfbackendsetinfo</b> {...}<sup>1.</sup> {...}<sup>2.</sup></p> <p>1 NAME</p> <p>2 TEXT</p>



<p><code>\pdfbackendsetname {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetpageattribute {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetpageresource {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetpagesattribute {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetpattern {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetshade {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfcolor {...}</code></p> <p>* NAME</p>
<p><code>\pdfeTeX</code></p>
<p><code>\pdfTeX</code></p>
<p><code>\pelung {...}</code></p> <p>* NAME</p>
<p><code>\percent</code></p>
<p><code>\percentdimen {...} {...}</code></p> <p>1 DIMENSION CSNAME</p> <p>2 DIMENSION NUMBER</p>
<p><code>\permitcaretescape</code></p>
<p><code>\permitcircumflexescape</code></p>
<p><code>\permitspacesbetweengroups</code></p>
<p><code>\persiandecimals {...}</code></p> <p>* NUMBER</p>
<p><code>\persiannumerals {...}</code></p> <p>* NUMBER</p>
<p><code>\phantom {...}</code></p> <p>* CONTENT</p>

```
*  latime      =  DIMENSION
   inaltime   =  DIMENSION
   inaltime   =  DIMENSION
```

1 BEFEHL  
2 BEFEHL  
3 BEFEHL

```
1  NAME                                OPT          OPT
2  inherits: \setupbtrendering
```

## \* REFERENCE

\* CONTENT

```

1 SINGULAR                                OPT      OPT
2 split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin marginestanga
   marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime
   adancime [--]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine
   [--]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva
   effective antet subsol
3 REFERENCE
4 TEXT
5 CONTENT

```

```

1 NAME                                OPT      OPT
2 split totdeauna stanga dreapta intern extern spatiuspace cutspace instanga indreapta inmargin marginestanga
marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime
adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine
[-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva
effective antet subsol
3 REFERENCE
4 TEXT
5 CONTENT

```

instances: chemical figure table intermezzo graphic

`\punechemical [...,1...] [...,2...] {...} {...}`

1 split totdeauna stangă<sup>OPT</sup> dreapta<sup>OPT</sup> intern extern spatiuspace cutspace instanga indreapta inmargin marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva effective antet subsol

2 REFERENCE

3 TEXT

4 CONTENT

`\punefigure [...,1...] [...,2...] {...} {...}`

1 split totdeauna stangă<sup>OPT</sup> dreapta<sup>OPT</sup> intern extern spatiuspace cutspace instanga indreapta inmargin marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva effective antet subsol

2 REFERENCE

3 TEXT

4 CONTENT

`\punegraphic [...,1...] [...,2...] {...} {...}`

1 split totdeauna stangă<sup>OPT</sup> dreapta<sup>OPT</sup> intern extern spatiuspace cutspace instanga indreapta inmargin marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva effective antet subsol

2 REFERENCE

3 TEXT

4 CONTENT

`\puneintermezzo [...,1...] [...,2...] {...} {...}`

1 split totdeauna stangă<sup>OPT</sup> dreapta<sup>OPT</sup> intern extern spatiuspace cutspace instanga indreapta inmargin marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva effective antet subsol

2 REFERENCE

3 TEXT

4 CONTENT

`\punetable [...,1...] [...,2...] {...} {...}`

1 split totdeauna stangă<sup>OPT</sup> dreapta<sup>OPT</sup> intern extern spatiuspace cutspace instanga indreapta inmargin marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva effective antet subsol

2 REFERENCE

3 TEXT

4 CONTENT

`\placeframed [...]1 [...,2...] {...}`

1 NAME<sup>OPT</sup>

2 inherits: \seteazainconjurat

3 CONTENT

`\placeheadnumber [...]`

\* ABSCHNITT

`\placeheadtext [...]`

\* ABSCHNITT

`\placehelp`

`\placeinitial [...]`

\* NAME<sup>OPT</sup>

`\placelayer [...]`

\* NAME

$\backslash\text{placelayeredtext}$ [ <sup>1</sup> ...] [ <sup>2</sup> ... <sup>*</sup> ...] <sub>OPT</sub> [ <sup>3</sup> ... <sup>*</sup> ...] <sub>OPT</sub> { <sup>4</sup> ...} { <sup>5</sup> ...} 1 NAME 2 inherits: \setuplayer 3 inherits: \setuplayeredtext 4 TEXT 5 CONTENT
$\backslash\text{placelistofFLOATS}$ [ <sup>*</sup> ... <sup>*</sup> ...] <sub>OPT</sub> * inherits: \seteazalista instances: chemicals figures tables intermezzi graphics
$\backslash\text{placelistofchemicals}$ [ <sup>*</sup> ... <sup>*</sup> ...] <sub>OPT</sub> * inherits: \seteazalista
$\backslash\text{placelistoffigures}$ [ <sup>*</sup> ... <sup>*</sup> ...] <sub>OPT</sub> * inherits: \seteazalista
$\backslash\text{placelistofgraphics}$ [ <sup>*</sup> ... <sup>*</sup> ...] <sub>OPT</sub> * inherits: \seteazalista
$\backslash\text{placelistofintermezzi}$ [ <sup>*</sup> ... <sup>*</sup> ...] <sub>OPT</sub> * inherits: \seteazalista
$\backslash\text{placelistoftables}$ [ <sup>*</sup> ... <sup>*</sup> ...] <sub>OPT</sub> * inherits: \seteazalista
$\backslash\text{placelistofpublications}$ [ <sup>1</sup> ...] [ <sup>2</sup> ... <sup>*</sup> ...] <sub>OPT</sub> 1 NAME 2 inherits: \setupbtxrendering
$\backslash\text{placelistofsorts}$ [ <sup>1</sup> ...] [ <sup>2</sup> ... <sup>*</sup> ...] <sub>OPT</sub> 1 SINGULAR 2 inherits: \seteazasortare
$\backslash\text{placelistofSORTS}$ [ <sup>*</sup> ... <sup>*</sup> ...] <sub>OPT</sub> * inherits: \seteazasortare instances: logos
$\backslash\text{placelistoflogos}$ [ <sup>*</sup> ... <sup>*</sup> ...] <sub>OPT</sub> * inherits: \seteazasortare
$\backslash\text{placelistofsynonyms}$ [ <sup>1</sup> ...] [ <sup>2</sup> ... <sup>*</sup> ...] <sub>OPT</sub> 1 SINGULAR 2 inherits: \seteazasinonime
$\backslash\text{placelistofSYNONYMS}$ [ <sup>*</sup> ... <sup>*</sup> ...] <sub>OPT</sub> * inherits: \seteazasinonime instances: abbreviations
$\backslash\text{placelistofabbreviations}$ [ <sup>*</sup> ... <sup>*</sup> ...] <sub>OPT</sub> * inherits: \seteazasinonime
$\backslash\text{placelocalnotes}$ [ <sup>1</sup> ...] [ <sup>2</sup> ... <sup>*</sup> ...] <sub>OPT</sub> 1 NAME 2 inherits: \setupnote
$\backslash\text{placement}$ [ <sup>1</sup> ...] [ <sup>2</sup> ... <sup>*</sup> ...] <sub>OPT</sub> { <sup>3</sup> ...} 1 NAME 2 inherits: \setupplacement 3 CONTENT

$\backslash\text{PLACEMENT}$ [... <sup>1</sup> ... <sup>2</sup> ...] {...} 1 inherits: \setupplacement 2 CONTENT
$\backslash\text{placenamefloat}$ [... <sup>1</sup> ] [... <sup>2</sup> ] 1 NAME 2 REFERENCE
$\backslash\text{placenameformula}$ [... <sup>1</sup> ... <sup>2</sup> ...] {... <sup>3</sup> } {... <sup>4</sup> } 1 + - REFERENCE OPT OPT 2 TEXT 3 TEXT
$\backslash\text{placenotes}$ [... <sup>1</sup> ... <sup>2</sup> ...] 1 NAME OPT 2 inherits: \setupnote
$\backslash\text{placepairedbox}$ [... <sup>1</sup> ] [... <sup>2</sup> ... <sup>3</sup> ...] {... <sup>4</sup> } {... <sup>5</sup> } 1 NAME OPT 2 inherits: \setuppairedbox 3 CONTENT 4 TEXT
$\backslash\text{punePAIREDBOX}$ [... <sup>1</sup> ... <sup>2</sup> ...] {... <sup>3</sup> } {... <sup>4</sup> } 1 inherits: \setuppairedbox 2 CONTENT 3 TEXT instances: legend
$\backslash\text{punelegend}$ [... <sup>1</sup> ... <sup>2</sup> ...] {... <sup>3</sup> } {... <sup>4</sup> } 1 inherits: \setuppairedbox OPT 2 CONTENT 3 TEXT
$\backslash\text{placeparallel}$ [... <sup>1</sup> ] [... <sup>2</sup> ... <sup>3</sup> ...] [... <sup>4</sup> ... <sup>5</sup> ...] 1 NAME OPT 2 NAME 3 inherits: \setupparallel
$\backslash\text{placerawlist}$ [... <sup>1</sup> ] [... <sup>2</sup> ... <sup>3</sup> ...] 1 LISTE OPT 2 inherits: \seteazalista
$\backslash\text{placereadingwindow}$ [... <sup>1</sup> ] [... <sup>2</sup> ] 1 NAME OPT 2 NAME
$\backslash\text{plaseazapegrid}$ [... <sup>1</sup> ] {... <sup>2</sup> } 1 normal standard da Strict tolerant sus subsol ambele broad ajustat primul ultim inalt unu jos niciunul linie strut box min max centru math math:linie math:jumatatelinie math:-line math:-halfline NAME 2 CONTENT
$\backslash\text{plaseazapegrid}$ [... <sup>1</sup> ... <sup>2</sup> ...] {... <sup>3</sup> } 1 inherits: \definegridsmapping 2 CONTENT
$\backslash\text{plaseazasemnecarte}$ [... <sup>1</sup> ... <sup>2</sup> ...] [... <sup>3</sup> ... <sup>4</sup> ...] [... <sup>5</sup> ... <sup>6</sup> ...] 1 ABSCHNITT LISTE OPT OPT OPT 2 ABSCHNITT LISTE 3 inherits: \setupbookmark
$\backslash\text{popattribute}$ \*... * CSNAME

<p><code>\popmacro \*...</code></p> <p>* CSNAME</p>
<p><code>\popmode [...]</code></p> <p>* NAME</p>
<p><code>\popsystemmode {...}</code></p> <p>* NAME</p>
<p><code>\positionoverlay {...}</code></p> <p>* NAME</p>
<p><code>\positionregionoverlay {...} {...}</code></p> <p>1 NAME</p> <p>2 NAME</p>
<p><code>\postponenotes</code></p>
<p><code>\potrivestecamp [...]<sup>1</sup> [...,...<sup>2</sup>...,...]</code></p> <p>1 NAME</p> <p>2 inherits: \setupfieldbody</p>
<p><code>\pozitie [...,...<sup>1</sup>...,...]<sup>1</sup> (...,...<sup>2</sup>...) {...}<sup>3</sup></code></p> <p>1 inherits: \setarepozitie<sup>OPT</sup></p> <p>2 POSITION</p> <p>3 CONTENT</p>
<p><code>\predefinedfont [...]</code></p> <p>* FONT</p>
<p><code>\predefinefont [...]<sup>1</sup> [...]<sup>2</sup></code></p> <p>1 NAME</p> <p>2 FONT</p>
<p><code>\predefinesymbol [...]</code></p> <p>* NAME</p>
<p><code>\prefixedpagenumber</code></p>
<p><code>\prependetoks ... \to \<sup>2</sup>...</code></p> <p>1 BEFEHL</p> <p>2 CSNAME</p>
<p><code>\prependgvalue {...}<sup>1</sup> {...}<sup>2</sup></code></p> <p>1 NAME</p> <p>2 BEFEHL</p>
<p><code>\prependtocommalist {...}<sup>1</sup> \<sup>2</sup>...</code></p> <p>1 TEXT</p> <p>2 CSNAME</p>
<p><code>\prependtoks ... \to \<sup>2</sup>...</code></p> <p>1 BEFEHL</p> <p>2 CSNAME</p>
<p><code>\prependtoksonce ... \to \<sup>2</sup>...</code></p> <p>1 BEFEHL</p> <p>2 CSNAME</p>

<pre> \prependvalue {...} {...} 1 NAME 2 BEFEHL </pre>
<pre> \prerollblank [...,*...] * inherits: \blanc </pre>
<pre> \presetdocument [...,*...] * inherits: \setupdocument </pre>
<pre> \presetfieldsymbols [...,*...] * NAME </pre>
<pre> \presetLABELtext [...<sup>1</sup>...] [...<sup>2</sup>...] 1 SPRACHE OPT 2 KEY = VALUE instances: head label mathlabel taglabel unit operator prefix suffix btxlabel </pre>
<pre> \presetbtxlabeltext [...<sup>1</sup>...] [...<sup>2</sup>...] 1 SPRACHE OPT 2 KEY = VALUE </pre>
<pre> \presetheadtext [...<sup>1</sup>...] [...<sup>2</sup>...] 1 SPRACHE OPT 2 KEY = VALUE </pre>
<pre> \presetlabeltext [...<sup>1</sup>...] [...<sup>2</sup>...] 1 SPRACHE OPT 2 KEY = VALUE </pre>
<pre> \presetmathlabeltext [...<sup>1</sup>...] [...<sup>2</sup>...] 1 SPRACHE OPT 2 KEY = VALUE </pre>
<pre> \presetoperatortext [...<sup>1</sup>...] [...<sup>2</sup>...] 1 SPRACHE OPT 2 KEY = VALUE </pre>
<pre> \presetprefixtext [...<sup>1</sup>...] [...<sup>2</sup>...] 1 SPRACHE OPT 2 KEY = VALUE </pre>
<pre> \presetsuffixtext [...<sup>1</sup>...] [...<sup>2</sup>...] 1 SPRACHE OPT 2 KEY = VALUE </pre>
<pre> \presettaglabeltext [...<sup>1</sup>...] [...<sup>2</sup>...] 1 SPRACHE OPT 2 KEY = VALUE </pre>
<pre> \presetunittext [...<sup>1</sup>...] [...<sup>2</sup>...] 1 SPRACHE OPT 2 KEY = VALUE </pre>
<pre> \pretocommalist {...} \<sup>2</sup>... 1 TEXT 2 CSNAME </pre>
<pre> \prettyprintbuffer {...} {...} 1 BUFFER 2 mp lua xml parsed-xml nested tex context niciunul NAME </pre>

<pre> \prevcounter [...] [<sup>1</sup>...] [<sup>2</sup>...] 1  NAME                      OPT 2  NUMMER </pre>
<pre> \prevcountervalue [...] *  NAME </pre>
<pre> \preventmode [...,*...] *  NAME </pre>
<pre> \prevrealpage </pre>
<pre> \prevrealpagenumber </pre>
<pre> \prevsubcountervalue [<sup>1</sup>...] [<sup>2</sup>...] 1  NAME 2  NUMMER </pre>
<pre> \prevsubpage </pre>
<pre> \prevsubpagenumber </pre>
<pre> \prevuserpage </pre>
<pre> \prevuserpagenumber </pre>
<pre> \primasubpagina </pre>
<pre> \procent </pre>
<pre> \proceseazabloc [...,<sup>1</sup>...] [...,<sup>2</sup>...] [...,<sup>3</sup>...] 1  NAME                      OPT          OPT 2  NAME 3  criteriu = text ABSCHNITT </pre>
<pre> \processaction [<sup>1</sup>...] [...,<sup>2</sup>=&gt;...] 1  BEFEHL 2  APPLY </pre>
<pre> \processallactionsinset [<sup>1</sup>...] [...,<sup>2</sup>=&gt;...] 1  BEFEHL 2  APPLY </pre>
<pre> \processassignlist [...,<sup>1</sup>...] \<sup>2</sup>... 1  TEXT 2  CSNAME </pre>
<pre> \processassignmentcommand [...,<sup>1</sup>...] \<sup>2</sup>... 1  KEY = VALUE 2  CSNAME </pre>
<pre> \processassignmentlist [...,<sup>1</sup>...] \<sup>2</sup>... 1  KEY = VALUE 2  CSNAME </pre>
<pre> \processbetween {<sup>1</sup>...} \<sup>2</sup>... 1  NAME 2  CSNAME </pre>



<pre> \processbodyfontenvironmentlist \*. * CSNAME </pre>
<pre> \processcolorcomponents {...} * COLOR </pre>
<pre> \processcommaccommand [...,<sup>1</sup>...] \<sup>2</sup>... 1 BEFEHL 2 CSNAME </pre>
<pre> \processcommalist [...,<sup>1</sup>...] \<sup>2</sup>... 1 BEFEHL 2 CSNAME </pre>
<pre> \processcommalistwithparameters [...,<sup>1</sup>...] \<sup>2</sup>... 1 BEFEHL 2 CSNAME </pre>
<pre> \processcontent {...} \<sup>2</sup>... 1 NAME 2 CSNAME </pre>
<pre> \processfile {...} * FILE </pre>
<pre> \processfilemany {...} * FILE </pre>
<pre> \processfilenone {...} * FILE </pre>
<pre> \processfileonce {...} * FILE </pre>
<pre> \processfirstactioninset [...<sup>1</sup>] [...,<sup>2</sup>...=&gt;...,...] 1 BEFEHL 2 APPLY </pre>
<pre> \processisolatedchars {...} \<sup>2</sup>... 1 TEXT 2 CSNAME </pre>
<pre> \processisolatedwords {...} \<sup>2</sup>... 1 TEXT 2 CSNAME </pre>
<pre> \processlinetablebuffer [...<sup>*</sup>] * BUFFER OPT </pre>
<pre> \processlinetablefile {...} * FILE </pre>
<pre> \processlist {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} \<sup>4</sup>... 1 CHARACTER 2 CHARACTER 3 TEXT 4 CSNAME </pre>
<pre> \processMPbuffer [...<sup>*</sup>...] * NAME OPT </pre>

<p><code>\processMPfigurefile {...}</code></p> <p>* FILE</p>
<p><code>\processmonth {...} {...} {...}</code></p> <p>1 NUMBER</p> <p>2 NUMBER</p> <p>3 BEFEHL</p>
<p><code>\processranges [...<sup>1</sup>,...] \<sup>2</sup>...</code></p> <p>1 NUMBER NUMBER:NUMBER</p> <p>2 CSNAME</p>
<p><code>\processseparatedlist [...<sup>1</sup>] [...<sup>2</sup>] {...<sup>3</sup>}</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 CSNAME BEFEHL</p>
<p><code>\processTEXbuffer [...<sup>*</sup>]</code></p> <p>* BUFFER <small>OPT</small></p>
<p><code>\processtokens {...} {...} {...} {...} {...}</code></p> <p>1 BEFEHL</p> <p>2 BEFEHL</p> <p>3 BEFEHL</p> <p>4 BEFEHL</p> <p>5 TEXT</p>
<p><code>\processuntil \<sup>*</sup>...</code></p> <p>* CSNAME</p>
<p><code>\processxtablebuffer [...<sup>*</sup>]</code></p> <p>* NAME <small>OPT</small></p>
<p><code>\processyear {...} {...<sup>2</sup>} {...<sup>3</sup>} {...<sup>4</sup>}</code></p> <p>1 NUMBER</p> <p>2 BEFEHL</p> <p>3 BEFEHL</p> <p>4 BEFEHL</p>
<p><code>\produs [...<sup>*</sup>]</code></p> <p>* FILE</p>
<p><code>\produs \<sup>*</sup>...</code></p> <p>* FILE</p>
<p><code>\profiledbox [...<sup>1</sup>] [...<sup>2</sup>,...<sup>2</sup>,...] {...<sup>3</sup>}</code></p> <p>1 niciunul fixat strict halfixed quarterfixed eightsfixed NAME</p> <p>2 inherits: \setupprofile</p> <p>3 CONTENT</p>
<p><code>\profilegivenbox {...} \<sup>2</sup>...</code></p> <p>1 niciunul fixat strict halfixed quarterfixed eightsfixed NAME</p> <p>2 CSNAME NUMBER</p>
<p><code>\program [...<sup>*</sup>]</code></p> <p>* NAME</p>
<p><code>\proiect [...<sup>*</sup>]</code></p> <p>* FILE</p>

<p><code>\proiect ...</code>  * FILE</p>
<p><code>\pseudoMixedCapped {...}</code>  * TEXT</p>
<p><code>\pseudoSmallCapped {...}</code>  * TEXT</p>
<p><code>\pseudoSmallcapped {...}</code>  * TEXT</p>
<p><code>\pseudosmallcapped {...}</code>  * TEXT</p>
<p><code>\puncte {...}</code>  * CHARACTER</p>
<p><code>\puncte [...]</code>  * NUMMER OPT</p>
<p><code>\puncte [...*...]</code>  * inherits: \setupperiods</p>
<p><code>\punedeasuprafiecareia {...} {...}</code>  1 CONTENT  2 CONTENT</p>
<p><code>\punefatainfata {...} {...}</code>  1 CONTENT  2 CONTENT</p>
<p><code>\puneformula [...<sup>1</sup>...] {...<sup>2</sup>}</code>  1 + - REFERENCE OPT OPT  2 TEXT</p>
<p><code>\punelista [...<sup>1</sup>...] [...<sup>2</sup>...]</code>  1 LISTE OPT  2 inherits: \seteazalista</p>
<p><code>\punelistacombinata [...<sup>1</sup>] [...<sup>2</sup>...]</code>  1 LISTE OPT  2 inherits: \seteazalistacombinata</p>
<p><code>\puneCOMBINEDLIST [...*...]</code>  * inherits: \seteazalistacombinata OPT  <b>instances: content</b></p>
<p><code>\punecontent [...*...]</code>  * inherits: \seteazalistacombinata OPT</p>
<p><code>\punenotesubsol [...*...]</code>  * inherits: \setupnote OPT</p>
<p><code>\punenotesubsollocale [...*...]</code>  * inherits: \setupnote OPT</p>
<p><code>\punenumarpagina</code></p>

<p><code>\puneregistru [...]<sup>1</sup> [...,...<sup>2</sup>...,...]</code></p> <p>1 NAME OPT</p> <p>2 inherits: \seteazaregistru</p>
<p><code>\puneREGISTER [...,...<sup>*</sup>...,...]</code></p> <p>* inherits: \seteazaregi<sup>OPT</sup>stru</p> <p>instances: index</p>
<p><code>\puneindex [...,...<sup>*</sup>...,...]</code></p> <p>* inherits: \seteaza<sup>OPT</sup>registru</p>
<p><code>\punesubformula [...,...<sup>1</sup>...] {...<sup>2</sup>}</code></p> <p>1 + - REFERENCE OPT OPT</p> <p>2 TEXT</p>
<p><code>\purenumber {...<sup>*</sup>}</code></p> <p>* NUMMER</p>
<p><code>\pusharrangedpages ... \poparrangedpages</code></p>
<p><code>\pushattribute \...<sup>*</sup></code></p> <p>* CSNAME</p>
<p><code>\pushbar [...]<sup>*</sup> ... \popbar</code></p> <p>* NAME</p>
<p><code>\pushbutton [...]<sup>1</sup> [...]<sup>2</sup></code></p> <p>1 NAME</p> <p>2 REFERENCE</p>
<p><code>\pushcatcodetable ... \popcatcodetable</code></p>
<p><code>\pushculoare [...]<sup>*</sup> ... \popculoare</code></p> <p>* COLOR</p>
<p><code>\pushendofline ... \popendofline</code></p>
<p><code>\pushfundal [...]<sup>*</sup> ... \popfundal</code></p> <p>* NAME</p>
<p><code>\pushindentation ... \popindentation</code></p>
<p><code>\pushMPdrawing ... \popMPdrawing</code></p>
<p><code>\pushmacro \...<sup>*</sup></code></p> <p>* CSNAME</p>
<p><code>\pushmathstyle ... \popmathstyle</code></p>
<p><code>\pushmode [...]<sup>*</sup></code></p> <p>* NAME</p>
<p><code>\pushoutputstream [...]<sup>*</sup></code></p> <p>* NAME OPT</p>
<p><code>\pushpath [...]<sup>*</sup> ... \poppath</code></p> <p>* PATH</p>

<code>\pushpunctuation ... \poppunctuation</code>
<code>\pushrandomseed ... \poprandomseed</code>
<code>\pushreferenceprefix {...} ... \popreferenceprefix</code> <code>* + - TEXT</code>
<code>\pushsystemmode {...}</code> <code>* NAME</code>
<code>\putboxincache {...} {...} ...</code> <code>1 NAME</code> <code>2 NUMMER TEXT</code> <code>3 CSNAME NUMMER</code>
<code>\putnextboxincache {...} {...} \... {...}</code> <code>1 NAME</code> <code>2 NUMMER TEXT</code> <code>3 CSNAME</code> <code>4 CONTENT</code>
<code>\qqquad</code>
<code>\quad</code>
<code>\quads [...]</code> <code>* NUMMER <small>OPT</small></code>
<code>\quarterstrut</code>
<code>\quitcommalist</code>
<code>\quitprevcommalist</code>
<code>\quittypescriptscanning</code>
<code>\ReadFile {...}</code> <code>* FILE</code>
<code>\raggedbottom</code>
<code>\raggedcenter</code>
<code>\raggedleft</code>
<code>\raggedright</code>
<code>\raggedwidecenter</code>
<code>\raisebox {...} \... {...}</code> <code>1 DIMENSION</code> <code>2 CSNAME</code> <code>3 CONTENT</code>
<code>\randomizetext {...}</code> <code>* TEXT</code>

\randomnumber {...} {...} 1    NUMMER 2    NUMMER
\rawcounter [...] <sup>1</sup> [...] <sup>2</sup> 1    NAME                    OPT 2    NUMMER
\rawcountervalue [...] *    NAME
\rawdate [...,*] *    inherits: \datacurenta
\rawdoifelseinset {...} <sup>1</sup> {..., <sup>2</sup> ...} {...} <sup>3</sup> {...} <sup>4</sup> 1    TEXT 2    TEXT 3    TRUE 4    FALSE
\rawdoifinset {...} <sup>1</sup> {..., <sup>2</sup> ...} {...} <sup>3</sup> 1    TEXT 2    TEXT 3    TRUE
\rawdoifinsetelse {...} <sup>1</sup> {..., <sup>2</sup> ...} {...} <sup>3</sup> {...} <sup>4</sup> 1    TEXT 2    TEXT 3    TRUE 4    FALSE
\rawgetparameters [...] <sup>1</sup> [..., <sup>2</sup> ...,...] 1    TEXT 2    KEY = VALUE
\rawprocessaction [...] <sup>1</sup> [..., <sup>2</sup> ...=>...,...] 1    BEFEHL 2    APPLY
\rawprocesscommacommand [..., <sup>1</sup> ...] \^ <sup>2</sup> .. 1    BEFEHL 2    CSNAME
\rawprocesscommalist [..., <sup>1</sup> ...] \^ <sup>2</sup> .. 1    BEFEHL 2    CSNAME
\rawstructurelistuservariable {...} *    KEY
\rawsubcountervalue [...] <sup>1</sup> [...] <sup>2</sup> 1    NAME 2    NUMMER
\rbox ... <sup>1</sup> {...} <sup>2</sup> 1    TEXT <sup>OPT</sup> 2    CONTENT
\readfile {...} <sup>1</sup> {...} <sup>2</sup> {...} <sup>3</sup> 1    FILE 2    TRUE 3    FALSE

<code>\readfixfile {<sup>1</sup>..} {<sup>2</sup>..} {<sup>3</sup>..} {<sup>4</sup>..}</code> 1    PATH 2    FILE 3    TRUE 4    FALSE
<code>\readjobfile {<sup>1</sup>..} {<sup>2</sup>..} {<sup>3</sup>..}</code> 1    FILE 2    TRUE 3    FALSE
<code>\readlocfile {<sup>1</sup>..} {<sup>2</sup>..} {<sup>3</sup>..}</code> 1    FILE 2    TRUE 3    FALSE
<code>\readsetfile {<sup>1</sup>..} {<sup>2</sup>..} {<sup>3</sup>..} {<sup>4</sup>..}</code> 1    PATH 2    FILE 3    TRUE 4    FALSE
<code>\readsysfile {<sup>1</sup>..} {<sup>2</sup>..} {<sup>3</sup>..}</code> 1    FILE 2    TRUE 3    FALSE
<code>\readtexfile {<sup>1</sup>..} {<sup>2</sup>..} {<sup>3</sup>..}</code> 1    FILE 2    TRUE 3    FALSE
<code>\readxmlfile {<sup>1</sup>..} {<sup>2</sup>..} {<sup>3</sup>..}</code> 1    FILE 2    TRUE 3    FALSE
<code>\realpagenumber</code>
<code>\realSmallCapped {<sup>*</sup>..}</code> *    TEXT
<code>\realSmallcapped {<sup>*</sup>..}</code> *    TEXT
<code>\realsmallcapped {<sup>*</sup>..}</code> *    TEXT
<code>\recursedepth</code>
<code>\recurselevel</code>
<code>\recursestring</code>
<code>\redoconvertfont</code>
<code>\ref [<sup>1</sup>..] [<sup>2</sup>..]</code> 1    implicit text titlu numar pagina realpage 2    REFERENCE

<code>\REFERENCEFORMAT {...} {...} [...]</code> 1    TEXT                    OPT            OPT 2    TEXT 3    REFERENCE
<code>\referenceprefix</code>
<code>\referinta [...,<sup>1</sup>...] {..<sup>2</sup>.}</code> 1    REFERENCE 2    TEXT
<code>\referintapagina [...,*...]</code> *    REFERENCE
<code>\referintatext [...,<sup>1</sup>...] {..<sup>2</sup>.}</code> 1    REFERENCE 2    TEXT
<code>\referring (...,<sup>1</sup>...) (...,<sup>2</sup>...) [...<sup>3</sup>]</code> 1    POSITION 2    POSITION 3    REFERENCE
<code>\reflexie {...}</code> *    CONTENT
<code>\registerattachment [...<sup>1</sup>] [...,<sup>2</sup>...,...]</code> 1    NAME 2    inherits: \setupattachment
<code>\registerctxluafile {...} {..<sup>2</sup>.}</code> 1    FILE 2    NUMMER
<code>\registerexternalfigure [...<sup>1</sup>] [...<sup>2</sup>] [...,<sup>3</sup>...,...]</code> 1    FILE                                    OPT                    OPT 2    NAME 3    inherits: \setupexternalfigure
<code>\registerfontclass {...}</code> *    NAME
<code>\registerhyphenationexception [...<sup>1</sup>] [...<sup>2</sup>]</code> 1    SPRACHE                                    OPT 2    TEXT
<code>\registerhyphenationpattern [...<sup>1</sup>] [...<sup>2</sup>]</code> 1    SPRACHE                                    OPT 2    TEXT
<code>\registermenubuttons [...<sup>1</sup>] [...<sup>2</sup>]</code> 1    NAME 2    TEXT
<code>\registersort [...<sup>1</sup>] [...<sup>2</sup>]</code> 1    SINGULAR 2    NAME
<code>\registersynonym [...<sup>1</sup>] [...<sup>2</sup>]</code> 1    SINGULAR 2    NAME



<pre> \registerunit [...]<sup>1</sup> [...,...<sup>2</sup>...,...] 1  prefix unitate operator suffixe simbol packaged 2  KEY = VALUE </pre>
<pre> \REGISTER [...]<sup>1</sup> {...+...<sup>2</sup>+...} 1  TEXT PROCESSOR-&gt;TEXT 2  INDEX instances: index </pre>
<pre> \index [...]<sup>1</sup> {...+...<sup>2</sup>+...} 1  TEXT PROCESSOR-&gt;TEXT 2  INDEX </pre>
<pre> \REGISTER [...]<sup>1</sup> {...}<sup>2</sup> {...+...<sup>3</sup>+...} 1  TEXT PROCESSOR-&gt;TEXT 2  TEXT 3  INDEX instances: index </pre>
<pre> \index [...]<sup>1</sup> {...}<sup>2</sup> {...+...<sup>3</sup>+...} 1  TEXT PROCESSOR-&gt;TEXT 2  TEXT 3  INDEX </pre>
<pre> \regular </pre>
<pre> \relatemarking [...]<sup>1</sup> [...]<sup>2</sup> 1  BESCHRIFTUNG 2  BESCHRIFTUNG </pre>
<pre> \relateparameterhandlers {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup> {...}<sup>4</sup> 1  NAME 2  NAME 3  NAME 4  NAME </pre>
<pre> \relaxvalueifundefined {...} *  NAME </pre>
<pre> \remainingcharacters </pre>
<pre> \remarca (...,<sup>1</sup>...) (...<sup>2</sup>,...) [...,...<sup>3</sup>...,...]<sup>4</sup> {...} 1  POSITION 2  POSITION 3  OPT 4  inherits: \setezainconjurat 5  TEXT </pre>
<pre> \removebottomthings </pre>
<pre> \removedepth </pre>
<pre> \removefromcommalist {...}<sup>1</sup> \...<sup>2</sup> 1  TEXT 2  CSNAME </pre>
<pre> \removelastskip </pre>
<pre> \removelastspace </pre>
<pre> \removemarkedcontent [...]<sup>*</sup> *  NAME </pre>

<code>\removepunctuation</code>
<code>\removesubstring <sup>1</sup>... \from <sup>2</sup>... \to <sup>3</sup>...</code> 1 TEXT 2 TEXT 3 CSNAME
<code>\removetoks <sup>1</sup>... \from <sup>2</sup>...</code> 1 BEFEHL 2 CSNAME
<code>\removeunwantedspaces</code>
<code>\replacefeature [...]</code> * NAME
<code>\replacefeature {...}</code> * NAME
<code>\replaceincommalist \<sup>1</sup>... {<sup>2</sup>...}</code> 1 CSNAME 2 NUMMER
<code>\replaceword [<sup>1</sup>...] [<sup>2</sup>] [<sup>3</sup>]</code> 1 NAME 2 TEXT 3 TEXT
<code>\rescan {...}</code> * CONTENT
<code>\rescanwithsetup {<sup>1</sup>...} {<sup>2</sup>...}</code> 1 NAME 2 CONTENT
<code>\resetallattributes</code>
<code>\resetandaddfeature [...]</code> * NAME
<code>\resetandaddfeature {...}</code> * NAME
<code>\resetbar</code>
<code>\resetboxesincache {...}</code> * NAME
<code>\resetbreakpoints</code>
<code>\resetbuffer [...]</code> * BUFFER
<code>\resetcharacteralign</code>
<code>\resetcharacterkerning</code>
<code>\resetcharacterspacing</code>

<code>\resetcharacterstripping</code>
<code>\resetcollector [...]</code> *   NAME
<code>\resetcounter [...] [...]</code> 1   NAME                   OPT 2   NUMMER
<code>\resetdigitsmanipulation</code>
<code>\resetdirection</code>
<code>\reseteazamarcaje [...]</code> *   BESCHRIFTUNG
<code>\resetfeature</code>
<code>\resetflag {...}</code> *   NAME
<code>\resetfontcolorscheme</code>
<code>\resetfontfallback [...] [...]</code> 1   NAME                   OPT 2   FONT
<code>\resetfontsolution</code>
<code>\resethyphenationfeatures</code>
<code>\resetinjector [...]</code> *   NAME
<code>\resetinteractionmenu [...]</code> *   NAME
<code>\resetitaliccorrection</code>
<code>\resetlayer [...]</code> *   NAME
<code>\resetlocalfloats</code>
<code>\resetMPdrawing</code>
<code>\resetMPenvironment</code>
<code>\resetMPinstance [...]</code> *   NAME
<code>\resetmarker [...]</code> *   NAME
<code>\resetmode {...}</code> *   NAME



\resetvalue {...} *   NAME
\resetvisualizers
\reshapebox {...} *   BEFEHL
\resolvedglyphdirect {...} {...} 1   FONT 2   e:NAME x:NUMMER d:NUMMER s:NUMMER i:NUMMER n:NAME c:NAME u:NAME a:NAME
\resolvedglyphstyled {...} {...} 1   FONT 2   e:NAME x:NUMMER d:NUMMER s:NUMMER i:NUMMER n:NAME c:NAME u:NAME a:NAME
\restartcounter [...] [...] [...] 1   NAME                               OPT 2   NUMMER 3   NUMMER
\restorebox {...} {...} 1   NAME 2   NAME
\restorecatcodes
\restorecounter [...] *   NAME
\restorecurrentattributes {...} *   NAME
\restoreendofline
\restoreglobalbodyfont
\reusableMPgraphic {...} {...}... <sup>2</sup> ... 1   NAME                               OPT 2   KEY   =   VALUE
\reuseMPgraphic {...} {...}... <sup>2</sup> ... 1   NAME                               OPT 2   KEY   =   VALUE
\reuserandomseed
\revivefeature
\rfence {...} *   CHARACTER
\rhbox {...} *   CONTENT
\rightbottombox {...} *   CONTENT

$\backslash\mathrm{rightbox}\{...\}$ *    CONTENT
$\backslash\mathrm{righthbox}\{...\}$ *    CONTENT
$\backslash\mathrm{rightLABELtext}\{...\}$ *    KEY instances: head label mathlabel
$\backslash\mathrm{rightheadtext}\{...\}$ *    KEY
$\backslash\mathrm{rightlabeltext}\{...\}$ *    KEY
$\backslash\mathrm{rightmathlabeltext}\{...\}$ *    KEY
$\backslash\mathrm{rightline}\{...\}$ *    CONTENT
$\backslash\mathrm{rightorleftpageaction}\{.^1.\}\{.^2.\}$ 1    BEFEHL 2    BEFEHL
$\backslash\mathrm{rightpageorder}$
$\backslash\mathrm{rightskipadaption}$
$\backslash\mathrm{rightsubguillemot}$
$\backslash\mathrm{righttopleft}$
$\backslash\mathrm{righttopleftthbox}\{.^1.\}\{.^2.\}$ 1    TEXT                    OPT 2    CONTENT
$\backslash\mathrm{righttopleftvbox}\{.^1.\}\{.^2.\}$ 1    TEXT                    OPT 2    CONTENT
$\backslash\mathrm{righttopleftvtop}\{.^1.\}\{.^2.\}$ 1    TEXT                    OPT 2    CONTENT
$\backslash\mathrm{righttopbox}\{...\}$ *    CONTENT
$\backslash\mathrm{riglertext}\{.^1.\}\{.^2.\}$ 1    sus centru subSol    OPT 2    TEXT
$\backslash\mathrm{rigleumplere}\{...,\overset{1}{\pm}...,\dots\}\{.^2.\}\{.^3.\}$ 1    inherits: \seteazarigleumplere    OPT    OPT 2    TEXT 3    TEXT

<code>\ring {...}</code> * CHARACTER
<code>\rlap {...}</code> * CONTENT
<code>\robustaddtocommalist {...} \^{.2.}</code> 1 TEXT 2 CSNAME
<code>\robustdoifelseinset {...} {...^{.2.},...} {...^{.3.}} {...^{.4.}}</code> 1 TEXT 2 TEXT 3 TRUE 4 FALSE
<code>\robustdoifinsetelse {...} {...^{.2.},...} {...^{.3.}} {...^{.4.}}</code> 1 TEXT 2 TEXT 3 TRUE 4 FALSE
<code>\robustpretocommalist {...} \^{.2.}</code> 1 TEXT 2 CSNAME
<code>\rollbutton [...^{.1.},...^{.2.}] \^{.3.}</code> 1 inherits: \setupbutton 2 TEXT 3 REFERENCE
<code>\rollbutton [...^{.1.}] [...^{.2.},...^{.3.}] \^{.4.}</code> 1 NAME OPT OPT 2 inherits: \seteazameniuiinteractiune 3 TEXT 4 REFERENCE
<code>\roman</code>
<code>\roteste [...^{.1.},...^{.2.}] {...^{.2.}}</code> 1 inherits: \seteazameniuiinteractiune 2 CONTENT
<code>\rtop \^{.1.} {...^{.2.}}</code> 1 TEXT OPT 2 CONTENT
<code>\ruby [...^{.1.}] {...^{.2.}} {...^{.3.}}</code> 1 NAME OPT 2 TEXT 3 TEXT
<code>\ruledhbox \^{.1.} {...^{.2.}}</code> 1 TEXT OPT 2 CONTENT
<code>\ruledhpack \^{.1.} {...^{.2.}}</code> 1 TEXT OPT 2 CONTENT
<code>\ruledmbox {...}</code> * CONTENT

<code>\ruledtopv</code> <sup>1</sup> ... { <sup>2</sup> ...} 1 TEXT OPT 2 CONTENT
<code>\ruledtpack</code> <sup>1</sup> ... { <sup>2</sup> ...} 1 TEXT OPT 2 CONTENT
<code>\ruledvbox</code> <sup>1</sup> ... { <sup>2</sup> ...} 1 TEXT OPT 2 CONTENT
<code>\ruledvpack</code> <sup>1</sup> ... { <sup>2</sup> ...} 1 TEXT OPT 2 CONTENT
<code>\ruledvtop</code> <sup>1</sup> ... { <sup>2</sup> ...} 1 TEXT OPT 2 CONTENT
<code>\runMPbuffer</code> [...,*...] * NAME OPT
<code>\runninghbox</code> {*...} * CONTENT
<code>\ScaledPointsToBigPoints</code> { <sup>1</sup> ...} \ <sup>2</sup> ... 1 DIMENSION 2 CSNAME
<code>\ScaledPointsToWholeBigPoints</code> { <sup>1</sup> ...} \ <sup>2</sup> ... 1 DIMENSION 2 CSNAME
<code>\Smallcapped</code> {*...} * TEXT
<code>\safechar</code> {*...} * NUMMER
<code>\samplefile</code> {*...} * FILE
<code>\sans</code>
<code>\sansaldin</code>
<code>\sansnormal</code>
<code>\sansserif</code>
<code>\savebox</code> { <sup>1</sup> ...} { <sup>2</sup> ...} { <sup>3</sup> ...} 1 NAME 2 NAME 3 CONTENT



<pre> \savebtxdataset [...] [...] [...] [...] 1  NAME          OPT      OPT      OPT 2  FILE 3  dataset      = NAME    type         = bib lua xml    fisier       = FILE    criteriu     = tot text intro referinta curent aici precedent local componenta SECTIONBLOCK:tot SECTIONBLOCK:referinta                   SECTIONBLOCK:curent SECTIONBLOCK:precedent </pre>
<pre> \savebuffer [...] [...] *  lista      = NAME    fisier     = FILE    prefix     = da nu </pre>
<pre> \savebuffer [...] [...] 1  BUFFER 2  FILE </pre>
<pre> \savecounter [...] *  NAME </pre>
<pre> \saveculoare ... \restoreculoare </pre>
<pre> \savecurrentattributes {...} *  NAME </pre>
<pre> \savenormalmeaning \... *  CSNAME </pre>
<pre> \savetaggedtwopassdata {...} {...} {...} {...} 1  NAME 2  NUMMER 3  NAME 4  CONTENT </pre>
<pre> \savetwopassdata {...} {...} {...} 1  NAME 2  NUMMER 3  CONTENT </pre>
<pre> \sbox {...} *  CONTENT </pre>
<pre> \scala [...] [...] [...] [...] 1  NAME      OPT      OPT 2  inherits: \setupscale 3  CONTENT </pre>
<pre> \scriebuffer [...] [...] [...] 1  BUFFER      OPT      OPT 2  inherits: \seteazatyping </pre>
<pre> \typeBUFFER [...] [...] *  inherits: \seteazatyping </pre>
<pre> \scrieinlista [...] [...] [...] [...] 1  LISTE      OPT 2  inherits: \seteazalista 3  NUMMER 4  TEXT </pre>

<pre> \scrieintreliste [...] [...] <sup>2</sup> [...] <sup>3</sup> 1  LISTE 2  inherits: \seteazalista 3  BEFEHL </pre>
<pre> \SCRIPT instances: hangul hanzi nihongo ethiopic thai latin test </pre>
<pre> \ethiopic </pre>
<pre> \hangul </pre>
<pre> \hanzi </pre>
<pre> \latin </pre>
<pre> \nihongo </pre>
<pre> \test </pre>
<pre> \thai </pre>
<pre> \scrismanual </pre>
<pre> \secondoffivearguments {...} {...} {...} {...} {...} 1  TEXT 2  TEXT 3  TEXT 4  TEXT 5  TEXT </pre>
<pre> \secondoffourarguments {...} {...} {...} {...} 1  TEXT 2  TEXT 3  TEXT 4  TEXT </pre>
<pre> \secondofsixarguments {...} {...} {...} {...} {...} {...} 1  TEXT 2  TEXT 3  TEXT 4  TEXT 5  TEXT 6  TEXT </pre>
<pre> \secondofthreearguments {...} {...} {...} 1  TEXT 2  TEXT 3  TEXT </pre>
<pre> \secondofthreeunexpanded {...} {...} {...} 1  TEXT 2  TEXT 3  TEXT </pre>
<pre> \secondoftwoarguments {...} {...} 1  TEXT 2  TEXT </pre>

`\secondoftwounexpanded {...} {...}`

1 TEXT  
2 TEXT

`\SECTION [...,1...] {...}`

1 REFERENCE <sup>OPT</sup>  
2 TEXT

instances: part chapter section subsection subsubsection subsubsubsection subsubsubsubsection  
title subject subsubject subsubsubject subsubsubsubject subsubsubsubsubject

`\SECTION [...,*...,...]`

\* titlu = TEXT  
semncarte = TEXT  
marcaje = TEXT  
lista = TEXT  
referinta = REFERENCE  
numarpropriu = TEXT

instances: part chapter section subsection subsubsection subsubsubsection subsubsubsubsection  
title subject subsubject subsubsubject subsubsubsubject subsubsubsubsubject

`\chapter [...,*...,...]`

\* titlu = TEXT  
semncarte = TEXT  
marcaje = TEXT  
lista = TEXT  
referinta = REFERENCE  
numarpropriu = TEXT

`\part [...,*...,...]`

\* titlu = TEXT  
semncarte = TEXT  
marcaje = TEXT  
lista = TEXT  
referinta = REFERENCE  
numarpropriu = TEXT

`\section [...,*...,...]`

\* titlu = TEXT  
semncarte = TEXT  
marcaje = TEXT  
lista = TEXT  
referinta = REFERENCE  
numarpropriu = TEXT

`\subject [...,*...,...]`

\* titlu = TEXT  
semncarte = TEXT  
marcaje = TEXT  
lista = TEXT  
referinta = REFERENCE  
numarpropriu = TEXT

`\subsection [...,*...,...]`

\* titlu = TEXT  
semncarte = TEXT  
marcaje = TEXT  
lista = TEXT  
referinta = REFERENCE  
numarpropriu = TEXT

`\subsubject [...,*...,...]`

\* titlu = TEXT  
semncarte = TEXT  
marcaje = TEXT  
lista = TEXT  
referinta = REFERENCE  
numarpropriu = TEXT

`\subsubsection [...,.*,...]`

\* titlu = TEXT  
semncarte = TEXT  
marcaje = TEXT  
lista = TEXT  
referinta = REFERENCE  
numarpropriu = TEXT

`\subsubsubject [...,.*,...]`

\* titlu = TEXT  
semncarte = TEXT  
marcaje = TEXT  
lista = TEXT  
referinta = REFERENCE  
numarpropriu = TEXT

`\subsubsubsection [...,.*,...]`

\* titlu = TEXT  
semncarte = TEXT  
marcaje = TEXT  
lista = TEXT  
referinta = REFERENCE  
numarpropriu = TEXT

`\subsubsubsubject [...,.*,...]`

\* titlu = TEXT  
semncarte = TEXT  
marcaje = TEXT  
lista = TEXT  
referinta = REFERENCE  
numarpropriu = TEXT

`\subsubsubsubsection [...,.*,...]`

\* titlu = TEXT  
semncarte = TEXT  
marcaje = TEXT  
lista = TEXT  
referinta = REFERENCE  
numarpropriu = TEXT

`\subsubsubsubsubject [...,.*,...]`

\* titlu = TEXT  
semncarte = TEXT  
marcaje = TEXT  
lista = TEXT  
referinta = REFERENCE  
numarpropriu = TEXT

`\title [...,.*,...]`

\* titlu = TEXT  
semncarte = TEXT  
marcaje = TEXT  
lista = TEXT  
referinta = REFERENCE  
numarpropriu = TEXT

`\chapter [...,1...] {2...}`

1 REFERENCE OPT  
2 TEXT

`\SECTION [...,1...] {2...} {3...}`

1 REFERENCE OPT  
2 NUMMER  
3 TEXT

instances: part chapter section subsection subsubsection subsubsubsection subsubsubsubsection  
title subject subsubject subsubsubject subsubsubsubject subsubsubsubsubject

<code>\chapter [...,<sup>1</sup>...] {...} {...}</code> 1    REFERENCE <small>OPT</small> 2    NUMMER 3    TEXT
<code>\part [...,<sup>1</sup>...] {...} {...}</code> 1    REFERENCE <sup>PT</sup> 2    NUMMER 3    TEXT
<code>\section [...,<sup>1</sup>...] {...} {...}</code> 1    REFERENCE <small>OPT</small> 2    NUMMER 3    TEXT
<code>\subject [...,<sup>1</sup>...] {...} {...}</code> 1    REFERENCE <small>OPT</small> 2    NUMMER 3    TEXT
<code>\subsection [...,<sup>1</sup>...] {...} {...}</code> 1    REFERENCE <small>OPT</small> 2    NUMMER 3    TEXT
<code>\subsubject [...,<sup>1</sup>...] {...} {...}</code> 1    REFERENCE <small>OPT</small> 2    NUMMER 3    TEXT
<code>\subsubsection [...,<sup>1</sup>...] {...} {...}</code> 1    REFERENCE <small>OPT</small> 2    NUMMER 3    TEXT
<code>\subsubsubject [...,<sup>1</sup>...] {...} {...}</code> 1    REFERENCE <small>OPT</small> 2    NUMMER 3    TEXT
<code>\subsubsubsection [...,<sup>1</sup>...] {...} {...}</code> 1    REFERENCE <small>OPT</small> 2    NUMMER 3    TEXT
<code>\subsubsubsubject [...,<sup>1</sup>...] {...} {...}</code> 1    REFERENCE <small>OPT</small> 2    NUMMER 3    TEXT
<code>\subsubsubsubsection [...,<sup>1</sup>...] {...} {...}</code> 1    REFERENCE <small>OPT</small> 2    NUMMER 3    TEXT
<code>\subsubsubsubsubject [...,<sup>1</sup>...] {...} {...}</code> 1    REFERENCE <small>OPT</small> 2    NUMMER 3    TEXT
<code>\subsubsubsubsubsection [...,<sup>1</sup>...] {...} {...}</code> 1    REFERENCE <small>OPT</small> 2    NUMMER 3    TEXT
<code>\subsubsubsubsubsubject [...,<sup>1</sup>...] {...} {...}</code> 1    REFERENCE <small>OPT</small> 2    NUMMER 3    TEXT
<code>\title [...,<sup>1</sup>...] {...} {...}</code> 1    REFERENCE <small>OPT</small> 2    NUMMER 3    TEXT

<pre> \part [...,<sup>1</sup>...] {<sup>2</sup>.} 1  REFERENCE<sup>PT</sup> 2  TEXT </pre>
<pre> \section [...,<sup>1</sup>...] {<sup>2</sup>.} 1  REFERENCE<sup>OPT</sup> 2  TEXT </pre>
<pre> \subject [...,<sup>1</sup>...] {<sup>2</sup>.} 1  REFERENCE<sup>OPT</sup> 2  TEXT </pre>
<pre> \subsection [...,<sup>1</sup>...] {<sup>2</sup>.} 1  REFERENCE<sup>OPT</sup> 2  TEXT </pre>
<pre> \subsubject [...,<sup>1</sup>...] {<sup>2</sup>.} 1  REFERENCE<sup>OPT</sup> 2  TEXT </pre>
<pre> \subsubsection [...,<sup>1</sup>...] {<sup>2</sup>.} 1  REFERENCE<sup>OPT</sup> 2  TEXT </pre>
<pre> \subsubsubject [...,<sup>1</sup>...] {<sup>2</sup>.} 1  REFERENCE<sup>OPT</sup> 2  TEXT </pre>
<pre> \subsubsubsection [...,<sup>1</sup>...] {<sup>2</sup>.} 1  REFERENCE<sup>OPT</sup> 2  TEXT </pre>
<pre> \subsubsubsubject [...,<sup>1</sup>...] {<sup>2</sup>.} 1  REFERENCE<sup>OPT</sup> 2  TEXT </pre>
<pre> \subsubsubsubsection [...,<sup>1</sup>...] {<sup>2</sup>.} 1  REFERENCE<sup>OPT</sup> 2  TEXT </pre>
<pre> \subsubsubsubsubject [...,<sup>1</sup>...] {<sup>2</sup>.} 1  REFERENCE<sup>OPT</sup> 2  TEXT </pre>
<pre> \subsubsubsubsubsection [...,<sup>1</sup>...] {<sup>2</sup>.} 1  REFERENCE<sup>OPT</sup> 2  TEXT </pre>
<pre> \subsubsubsubsubsubject [...,<sup>1</sup>...] {<sup>2</sup>.} 1  REFERENCE<sup>OPT</sup> 2  TEXT </pre>
<pre> \title [...,<sup>1</sup>...] {<sup>2</sup>.} 1  REFERENCE<sup>OPT</sup> 2  TEXT </pre>
<pre> \veziREGISTER [...<sup>1</sup>] {...+<sup>2</sup>+...} {<sup>3</sup>.} 1  TEXT PROCESSOR-&gt;TEXT 2  INDEX 3  TEXT PROCESSOR-&gt;TEXT <b>instances:</b> index </pre>
<pre> \veziindex [...<sup>1</sup>] {...+<sup>2</sup>+...} {<sup>3</sup>.} 1  TEXT PROCESSOR-&gt;TEXT 2  INDEX 3  TEXT PROCESSOR-&gt;TEXT </pre>

```
\select {...} {...} {...} {...} {...} {...}
1  NAME          OPT      OPT      OPT      OPT      OPT
2  CONTENT
3  CONTENT
4  CONTENT
5  CONTENT
6  CONTENT
```

```
\selecteazablocuri [...,1...] [...,2...] [...,3...,...]
1  NAME          OPT      OPT
2  NAME
3  criteriu = text ABSCHNITT
```

```
\semncarte [...]1 {...}2
1  ABSCHNITT LISTE
2  TEXT
```

```
\serializecommalist [...,*...]
*  BEFEHL
```

```
\serializedcommalist
```

```
\serif
```

```
\serifbold
```

```
\serifnormal
```

```
\setare [...]*
*  NAME
```

```
\setareitemization [...,1...] [...,2...,...]
1  NAME NAME:NUMMER OPT
2  inherits: \setupitemgroup
```

```
\setarelimba [...]1 [...,2...,...]
1  SPRACHE implicitOPT
2  implicit          = SPRACHE
   stare             = start stop
   data              = inherits: \datacurenta
   time              = inherits: \currenttime
   patterns          = FILE
   lefthyphenmin     = NUMMER
   righthyphenmin    = NUMMER
   lefthyphenchar    = NUMMER
   righthyphenchar   = NUMMER
   setups            = NAME
   spatiere          = broad impachetat
   font              = auto NAME
   bidi              = stanga dreapta l2r r2l
   text              = TEXT
   limittext         = TEXT
   hyphen            = TEXT
   compoundhyphen    = TEXT
   leftcompoundhyphen = TEXT
   rightcompoundhyphen = TEXT
   minicitatstanga   = BEFEHL
   minicitatdreapta  = BEFEHL
   citatstanga       = BEFEHL
   citatdreapta      = BEFEHL
   leftspeech        = BEFEHL
   rightspeech       = BEFEHL
   propozitiestanga  = BEFEHL
   middlespeech      = BEFEHL
   propozitiedreapta = BEFEHL
   midsentence       = BEFEHL
   subpropozitiestanga = BEFEHL
   subpropozitiedreapta = BEFEHL
   factor            = da nu
```

```

\setarepozie [..1...][...2...]
1 NAME OPT
2 offset = da nu
   unite = ex em pt in cm mm sp bp pc dd cc nc
   stare = start overlay
   xoffset = DIMENSION
   yoffset = DIMENSION
   xstep = absolut relativ
   ystep = absolut relativ
   xscala = NUMMER
   yscala = NUMMER
   xfactor = NUMMER
   yfactor = NUMMER
   factor = NUMMER
   scala = NUMMER

```

```

\setare {...}
* NAME

```

```

\setautopagestaterealpageno {...}
* NAME

```

```

\setbar [...]
* NAME

```

```

\setbigbodyfont

```

```

\setboxllx 1... {2...}
1 CSNAME NUMMER
2 DIMENSION

```

```

\setboxlly 1... {2...}
1 CSNAME NUMMER
2 DIMENSION

```

```

\setbreakpoints [...]
* reset NAME

```

```

\setbuffer [...] ... \endbuffer
* NAME

```

```

\setcapstrut

```

```

\setcatcodetable \*...
* CSNAME

```

```

\setcharacteralign {1...} {2...}
1 NUMMER
2 TEXT number->TEXT text->TEXT

```

```

\setcharacteraligndetail {1...} {2...} {3...} {4...}
1 NUMMER
2 TEXT number->TEXT text->TEXT
3 DIMENSION
4 DIMENSION

```

```

\setcharactercasing [...]
* reset CUVANT cuvânt Cuvant Cuvinte majuscula Majuscula niciunul aleator mixed camel cap Cap

```

```

\setcharactercleaning [...]
* reset 1

```



<pre> \setcharacterkerning [...] *   reset NAME </pre>
<pre> \setcharacterspacing [...] *   reset NAME </pre>
<pre> \setcharacterstripping [...] *   reset 1 </pre>
<pre> \setcharstrut {...} *   TEXT </pre>
<pre> \setcollector [.<sup>1</sup>.] [...,<sup>2</sup>...,...<sup>3</sup>.] {...} 1   NAME                      OPT 2   inherits: \setupcollector 3   CONTENT </pre>
<pre> \setcolormodel [.<sup>1</sup>.] *   black bw gri rgb cmyk tot niciunul </pre>
<pre> \setcounter [.<sup>1</sup>.] [...<sup>2</sup>.] [...<sup>3</sup>.] 1   NAME                      OPT 2   NUMMER 3   NUMMER </pre>
<pre> \setcounterown [.<sup>1</sup>.] [...<sup>2</sup>.] [...<sup>3</sup>.] 1   NAME                      OPT 2   NUMMER 3   TEXT </pre>
<pre> \setcurrentfontclass {...} *   NAME </pre>
<pre> \setdataset [.<sup>1</sup>.] [...<sup>2</sup>.] [...,<sup>3</sup>...,...<sup>3</sup>.] 1   NAME                      OPT 2   NAME 3   KEY = VALUE </pre>
<pre> \setdefaultpenalties </pre>
<pre> \setdigitsmanipulation [.<sup>1</sup>.] *   reset NUMMER </pre>
<pre> \setdirection [.<sup>1</sup>.] *   NUMMER </pre>
<pre> \setdocumentargument {.<sup>1</sup>.} {.<sup>2</sup>.} 1   NAME 2   TEXT </pre>
<pre> \setdocumentargumentdefault {.<sup>1</sup>.} {.<sup>2</sup>.} 1   NAME 2   TEXT </pre>
<pre> \setdocumentfilename {.<sup>1</sup>.} {.<sup>2</sup>.} 1   NUMMER 2   TEXT </pre>

`\setdummyparameter {...} {...}`

- 1 KEY
- 2 BEFEHL

`\setezaaliniat [...,*...]`

- \* [-+]mic [-+]mediu [-+]mare niciunul nu nu primul urmatorul da totdeauna niciodata impar par normal reset toggle  
DIMENSION NAME

`\setezaalinieria [...,*...]`

- \* broad larg subsol inaltime linie inalt jos lohi flushright flushleft centru da nu latime normal reset intern  
extern flushinner flushouter stanga dreapta center dezactivat ultim end paragraf lefttoright righttoleft l2r  
r2l tabelul lesshyphenation morehyphenation suspendat nothanging hz fullhz nohz despsilabe nedespsilabe tolerant  
foartetolerant dilatata extremestretch final 1\*final 2\*final 3\*final 4\*final more 1\*more 2\*more

`\setezaantet [...]RT [...,*...]`

- 1 text margine bordura
- 2 inherits: \setuplayouttext

`\setezaaranjareapag [...,*...]`

- \* dezactivat oglindit douafete negativ 90 180 270 reset fundal normal 2\*16 2\*8 2\*4 2\*2 2\*\*2 2SIDE 2TOP 2UP 2DOWN  
2\*4\*2 2\*2\*4 2TOPSIDE 2\*8\*Z 2\*6\*Z 1\*8 1\*4 3SIDE TRYPTICHON ZFLYER-8 ZFLYER-10 ZFLYER-12 MAPFLYER-12 DOUBLEWINDOW  
1\*2-Conference 1\*4-Conference 2\*2\*2 2\*2\*3 XY NAME

```

\setezaaspect [...]1 [...]2...
1 NAME OPT
2 stare = start stop normal repetat
  margine = DIMENSION
  bordura = DIMENSION
  distantamargine = DIMENSION
  distantabordura = DIMENSION
  distantabordurastanga = DIMENSION
  distantacoltdreapta = DIMENSION
  distantamarginestanga = DIMENSION
  distantamarginedreapta = DIMENSION
  distantasus = DIMENSION
  distantaantet = DIMENSION
  distantasubsol = DIMENSION
  distantajos = DIMENSION
  preset = NAME
  marginestanga = DIMENSION
  marginedreapta = DIMENSION
  bordurastanga = DIMENSION
  borduradreapta = DIMENSION
  antet = DIMENSION
  subsol = DIMENSION
  sus = DIMENSION
  jos = DIMENSION
  spatiuspate = DIMENSION
  spatiusus = DIMENSION
  setups = NAME
  cutspace = DIMENSION
  latime = DIMENSION centru ajustat
  spatiujos = DIMENSION
  linii = NUMMER
  inaltime = DIMENSION centru ajustat
  offsetoriz = DIMENSION
  veroffset = DIMENSION
  coloane = NUMMER
  distantacoloane = DIMENSION
  metoda = implicit normal NAME
  locatie = stanga centru dreapta sus subsol ofata douafete
  latimetext = DIMENSION
  inaltimetext = DIMENSION
  nx = NUMMER
  ny = NUMMER
  dx = DIMENSION
  dy = DIMENSION
  scala = NUMMER
  sx = NUMMER
  sy = NUMMER
  marcaje = on dezactivat pagina gol culoare unu doi patru
  grid = da nu dezactivat
  textdistance = DIMENSION
  alternativ = implicit normal marcaj NAME
  clipoffset = DIMENSION
  cropoffset = DIMENSION auto
  trimoffset = DIMENSION
  bleedoffset = DIMENSION
  artoffset = DIMENSION

```

```

\setezaaspect [...]

```

```

* reset NAME

```

```

\seteazabarainteractiune [...]1 [...]2...
1 NAME OPT

```

```

2 alternativ = a b c d e f g
  stare = start stop
  comanda = CSNAME
  latime = DIMENSION
  inaltime = DIMENSION max broad
  inaltime = DIMENSION max
  distanta = DIMENSION
  pas = mic mediu mare
  culoarefundal = COLOR
  stil = STYLE BEFEHL
  culoare = COLOR
  culoarecontrast = COLOR
  simbol = da nu
  inherits: \seteazainconjurat

```

**\seteazablanc** [...,\*,...]

\* inherits: \blanc OPT

**\seteazabloc** [...,<sup>1</sup>,...] [...,..<sup>2</sup>...,...]

1 NAME OPT  
2 inainte = BEFEHL  
dupa = BEFEHL  
stanga = BEFEHL  
dreapta = BEFEHL  
alternativ = paragraf text  
intern = BEFEHL  
setups = NAME  
alinieri = stanga dreapta centru flushleft flushright intern extern  
stil = STYLE BEFEHL  
culoare = COLOR

**\seteazablocsectione** [...,<sup>1</sup>,...] [...,..<sup>2</sup>...,...]

1 NAME OPT  
2 pagina = inherits: \pagina  
inainte = BEFEHL  
dupa = BEFEHL  
numar = da nu

**\seteazabuffer** [...,<sup>1</sup>,...] [...,..<sup>2</sup>...,...]

1 BUFFER OPT  
2 inainte = BEFEHL  
dupa = BEFEHL  
strip = da nu

**\seteazacamp** [...,<sup>1</sup>] [...,..<sup>2</sup>,...] [...,..<sup>3</sup>...,...] [...,..<sup>4</sup>...,...] [...,..<sup>5</sup>...,...]

1 NAME OPT  
2 reset eticheta incadrat orizontal vertical  
3 inherits: \setupfieldtotalframed  
4 inherits: \setupfieldlabelframed  
5 inherits: \setupfieldcontentframed

**\seteazacampuri** [...,<sup>1</sup>,...] [...,..<sup>2</sup>...,...] [...,..<sup>3</sup>...,...] [...,..<sup>4</sup>...,...]

1 reset eticheta incadrat<sup>OPT</sup> orizontal vertical<sup>OPT</sup>  
2 inherits: \setupfieldtotalframed  
3 inherits: \setupfieldlabelframed  
4 inherits: \setupfieldcontentframed

**\seteazaclipping** [...,..<sup>\*</sup>...,...]

\* stare = start stop  
latime = DIMENSION  
inaltime = DIMENSION  
hoffset = DIMENSION  
voffset = DIMENSION  
x = NUMMER  
y = NUMMER  
nx = NUMMER  
ny = NUMMER  
sx = NUMMER  
sy = NUMMER  
offsetstanga = DIMENSION  
offsetdreapta = DIMENSION  
offsetsus = DIMENSION  
offsetjos = DIMENSION  
mp = NAME  
n = NUMMER  
offset = DIMENSION

\seteazacoloane [...,.\*=.,...]

\* n = NUMMER  
distanta = DIMENSION  
optiune = fundal  
offset = DIMENSION  
comanda = \...##1  
inaltime = DIMENSION  
directie = stanga dreapta  
balanta = da nu  
aliniere = inherits: \  
toleranta = inherits: \  
blanc = inherits: \blanc  
nsus = NUMMER  
rigla = on dezactivat BEFEHL

\seteazacommentariu [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME OPT  
2 stare = start stop niciunul  
metoda = normal ascuns  
simbol = Comment Ajutor Insert Cheie Newparagraph Note Paragraf Default  
latime = ajustat DIMENSION  
inaltime = ajustat DIMENSION  
inaltime = ajustat DIMENSION  
titlu = TEXT  
subtitlu = TEXT  
autor = TEXT  
nx = NUMMER  
ny = NUMMER  
culoare = COLOR  
optiune = xml max  
textlayer = NAME  
locatie = bordurastanga borduradreapta inmarginemarginestanga marginedreapta text inalt niciunul  
distanta = DIMENSION  
spatiu = da  
buffer = BUFFER

\seteazacommentariupagina [...,.\*=.,...]

\* locatie = stanga dreapta sus subsol niciunul  
stare = start stop niciunul  
offset = DIMENSION  
distanta = DIMENSION  
latime = DIMENSION  
inaltime = DIMENSION

\seteazaculoare [...]

\* FILE

\seteazaculori [...,.\*=.,...]

\* stare = start stop  
spot = da nu  
expansiune = da nu  
factor = da nu  
rgb = da nu  
cmyk = da nu  
conversie = da nu totdeauna  
pagecolormodel = auto niciunul NAME  
culoaretext = COLOR  
intent = overprint knockout niciunul

`\seteazadimensiunihartie [...]1 [...]2...`

```
1  NAME                      OPT
2  sus                       = BEFEHL
   jos                       = BEFEHL
   stanga                    = BEFEHL
   dreapta                   = BEFEHL
   metoda                    = normal niciunul NAME
   scala                     = NUMMER
   nx                        = NUMMER
   ny                        = NUMMER
   dx                        = DIMENSION
   dy                        = DIMENSION
   latime                    = DIMENSION
   inaltime                  = DIMENSION
   spatiusus                 = DIMENSION
   spatiuspate               = DIMENSION
   offset                    = DIMENSION
   pagina                    = reset vedere oglindit negativ rotat 90 180 270 NAME
   hartie                    = reset vedere oglindit negativ rotat 90 180 270 NAME
   optiune                   = ajustat max
   distanta                  = DIMENSION
```

`\seteazadimensiunihartie [...]1 [...]2...`

```
1  reset vedere oglindit negativ rotat 90 180 270OPTNAME
2  reset vedere oglindit negativ rotat 90 180 270 NAME
```

`\seteazaecraninteractiune [...]*...`

```
*  latime                    = ajustat max tight DIMENSION
   inaltime                  = ajustat max tight DIMENSION
   spatiuspate               = DIMENSION
   offsetoriz                = DIMENSION
   veroffset                 = DIMENSION
   spatiusus                 = DIMENSION
   optiune                   = ajustat max ofata douafete semncarte auto niciunul implicit fixat vedere portrait pagina foaie
                              attachment layer titlu nomenclar
   copies                    = NUMMER
   print                     = LISTE
   intarziere                = niciunul NUMMER
```

`\seteazaelemente [...]1 [...]2...`

```
1  NAME                      OPT
2  alternativ                 = stanga dreapta sus subsol inmarginie
   latimetext                = DIMENSION
   latime                    = DIMENSION
   distanta                  = DIMENSION
   simbol                    = niciunul NAME
   aliniere                  = stanga centru dreapta flushleft flushright intern extern margine
   textalign                 = stanga centru dreapta flushleft flushright intern extern
   n                         = NUMMER
   inainte                   = BEFEHL
   dupa                      = BEFEHL
   intre                     = BEFEHL
```

`\seteazaenumerare [...]1 [...]2...`

```
1  NAME                      OPT
2  inherits: \setupenumeration
```

**\seteazafloat** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```

1 SINGULAR OPT
2 aliniaturmator = da nu auto
implicit = inherits: \placefloat
fallback = inherits: \placefloat
intern = BEFEHL
criteriu = DIMENSION
metoda = NUMMER
sidemethod = NUMMER
textmethod = NUMMER
sidealign = inaltime adancime linie jumatatelinie grila normal
grid = inherits: \snaptogrid
local = da nu
comanda = \...##1
availablewidth = DIMENSION
availableheight = DIMENSION
latimeminima = DIMENSION
latimemaxima = DIMENSION
locatie = stanga dreapta centru flushleft flushright center max intern extern innermargin outermargin
inneredge outeredge spatuspace cutspace marginestanga marginedreapta borduradreapta
borduradreapta
distantamarginestanga = DIMENSION
distantamarginedreapta = DIMENSION
marginestanga = DIMENSION
marginedreapta = DIMENSION
innermargin = DIMENSION
outermargin = DIMENSION
bottombefore = BEFEHL
bottomafter = BEFEHL
expansiune = da nu xml
referenceprefix = + - TEXT
xmlsetup = NAME
catcodes = NAME
freeregion = da nu
spatiuinainte = niciunul inherits: \blanc
spatiudupa = niciunul inherits: \blanc
latime = DIMENSION
inaltime = DIMENSION
offset = DIMENSION niciunul overlay
spatiulateralainte = niciunul inherits: \blanc
spatiulateraldupa = niciunul inherits: \blanc
spacebefore = niciunul inherits: \blanc
spaceafterside = niciunul inherits: \blanc
sidethreshold = old dimension
margine = DIMENSION
nsus = NUMMER
njos = NUMMER
pas = mic mediu mare linie adancime
nlinii = NUMMER
cache = da nu
compress = da nu
compressdistance = DIMENSION
inherits: \seteazainconjurat

```

**\seteazafloats** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```

1 SINGULAR OPT
2 inherits: \seteazafloat

```

**\seteazafonttext** [...\*,...]

```

* DIMENSION NAME global rset x xx mic mare script scriptscript rm ss tt hw cg roman serif regular sans sansserif
suport type teletype mono scrismmanual caligrafic

```

**\seteazaformulare** [...<sup>\*</sup>,...]

```

* metoda = XML HTML PDF
export = da nu

```

**\seteazaformule** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```

1 NAME OPT
2 inherits: \setupformula

```

`\seteazafundal [...,1...] [...,2...,...]`

1 NAME OPT  
2 stare = start stop  
offsetstanga = DIMENSION  
offsetdreapta = DIMENSION  
offsetsus = DIMENSION  
offsetjos = DIMENSION  
inainte = BEFEHL  
dupa = BEFEHL  
inherits: \seteazainconjurat

`\seteazafundaluri [...,1...] [...,2...] [...,3...,...]`

1 sus antet text subsol subsol OPT  
2 bordurastanga marginestanga text marginedreapta borduradreapta  
3 inherits: \seteazainconjurat

`\seteazafundaluri [...,1...] [...,2...,...]`

1 foaie pagina paginastanga<sup>OPT</sup> paginadreapta text ascuns  
2 stare = start stop  
inherits: \seteazainconjurat

`\seteazagrosimelinie [...]`

\* mic mediu mare DIMENSION

`\seteazaimpartireafloat [...,*...,...]`

\* inainte = BEFEHL  
dupa = BEFEHL  
intre = BEFEHL  
linii = auto NUMMER  
conversie = NAME



\seteazainconjurat [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```

1  NAME                      OPT
2  colt                      = rectangular rotund NUMMER
   coltframe                 = rectangular rotund NUMMER
   coltfundal                 = rectangular rotund NUMMER
   raza                      = DIMENSION
   razaframe                  = DIMENSION
   razafundal                 = DIMENSION
   inaltime                   = DIMENSION
   adancimeframe              = DIMENSION
   adancimefundal             = DIMENSION
   culoareframe               = COLOR
   framesus                   = on dezactivat mic NAME
   framejos                   = on dezactivat mic NAME
   framestanga                = on dezactivat mic NAME
   framedreapta               = on dezactivat mic NAME
   region                     = da nu
   grosimerigla               = DIMENSION
   offsetframe                = DIMENSION
   frame                      = on dezactivat overlay mic closed niciunul
   fundal                     = primplan culoare NAME
   offsetfundal               = incadrat DIMENSION
   component                  = NAME
   extras                     = BEFEHL
   foregroundstyle            = STYLE BEFEHL
   foregroundcolor            = COLOR
   setups                     = NAME
   offset                     = implicit overlay niciunul DIMENSION
   latime                     = local ajustat max broad fixat DIMENSION
   inaltime                   = ajustat max broad DIMENSION
   inaltimeminima             = DIMENSION
   aliniere                   = inherits: \seteazaalinierea
   strut                      = da nu niciunul local global
   autostrut                  = da nu
   locatie                    = inaltime adancime inalt jos sus centru subsol linie lohi suspendat mentine formula matematica
                               normal
   autolatime                 = da nu fortat
   linii                      = NUMMER
   sus                        = BEFEHL
   jos                        = BEFEHL
   blanc                      = da nu
   profile                    = NAME
   gol                        = da nu
   loffset                    = DIMENSION
   roffset                    = DIMENSION
   toffset                    = DIMENSION
   boffset                    = DIMENSION
   orientation                 = NUMMER

```

\seteazaingust [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```

1  NAME                      OPT
2  stanga                    = DIMENSION
   mijloc                    = DIMENSION
   dreapta                   = DIMENSION
   implicit                   = [-+]stanga [-+]centru [-+]dreapta NUMMER*stanga NUMMER*centru NUMMER*dreapta reset
   inainte                   = BEFEHL
   dupa                      = BEFEHL

```

**\seteazainteractiunea** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1	NAME	OPT
2	stare	= start stop
	stil	= STYLE BEFEHL
	culoare	= COLOR
	culoarecontrast	= COLOR
	titlu	= TEXT
	subtitlu	= COLOR
	autor	= TEXT
	data	= TEXT
	keyword	= TEXT
	focus	= standard incadrat latime latimeminima inaltime inaltimeminima ajustat tight
	menu	= on dezactivat
	fieldlayer	= auto NAME
	calculeaza	= REFERENCE
	click	= da nu
	display	= normal nou
	pagina	= da nu pagina nume auto
	actiunedeschidere	= REFERENCE
	actiuneinchidere	= REFERENCE
	actiunedeschiderepagina	= REFERENCE
	actiuneinchiderepagina	= REFERENCE
	setsimbol	= NAME
	inaltime	= DIMENSION
	inaltime	= DIMENSION
	focusoffset	= DIMENSION

**\seteazainteractiunea** [...]

*	NAME	OPT
---	------	-----

**\seteazajos** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1	text	margin <sup>OPT</sup>	border
2	inherits: \setuplayouttext		

**\seteazalegenda** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1	NAME	OPT
2	suffix	= BEFEHL
	suffixseparator	= BEFEHL
	suffixstopper	= BEFEHL
	locatie	= stanga dreapta centru jos inalt grila linii overlay intern extern innermargin outermargin marginestanga marginedreapta lefthanging righthanging suspenda sus subsol dilatat tolerant foartetolerant niciunul implicit
	comanda	= \...##1
	comandanumar	= \...##1
	comandatext	= \...##1
	spatiuinainte	= inherits: \blanc
	spaceinbetween	= inherits: \blanc
	spatiudupa	= inherits: \blanc
	distanta	= DIMENSION
	stiltitlu	= STYLE BEFEHL
	culoaretitlu	= COLOR
	headseparator	= TEXT
	intre	= BEFEHL
	stil	= STYLE BEFEHL
	culoare	= COLOR
	offsetsus	= DIMENSION
	offsetjos	= DIMENSION
	numar	= da nu niciunul
	group	= TEXT
	marginestanga	= DIMENSION
	marginedreapta	= DIMENSION
	innermargin	= DIMENSION
	outermargin	= DIMENSION
	alinie	= inherits: \seteazaalinie
	latime	= ajustat max DIMENSION
	latimeminima	= ajustat DIMENSION
	latimemaxima	= DIMENSION
	inherits: \setupcounterinherits: \seteazainconjurat	

**\seteazalegende** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1	NAME	OPT
2	inherits: \seteazalegenda	

```
\seteazaliniesilabe [...,.*,...]
*   semn = normal larg
```

```
\seteazaliniesubtire [...,.*,...]
*   inalttime      = max DIMENSION
    inalttime      = max DIMENSION
    fundal         = culoare
    frame          = on dezactivat
    grosimerigla    = DIMENSION
    alternativ       = a b c niciunul
    culoarefundal   = COLOR
    culoare         = COLOR
    spatiereinterliniara = mic mediu mare NUMMER
    inainte         = BEFEHL
    dupa            = BEFEHL
    intre           = BEFEHL
    n               = NUMMER
```

```
\seteazalinii [...,1...] [...,.*2...]
1   NAME          OPT
2   optiune       = impachetat
    inainte       = BEFEHL
    dupa          = BEFEHL
    intre         = BEFEHL
    aliniat       = inherits: \seteazaaliniat
    aliniere      = inherits: \seteazaalinierea
    spatiu        = da on dezactivat fixat implicit
    comanda       = BEFEHL
    stil          = STYLE BEFEHL
    culoare       = COLOR
    stanga        = BEFEHL
    dreapta       = BEFEHL
```

```
\seteazaliniimargine [...,1] [...,.*2...]
1   NUMMER        OPT
2   inherits: \setupmarginrule
```

```
\seteazaliniinegre [...,.*,...]
*   latime        = max DIMENSION
    inalttime      = max DIMENSION
    inalttime      = max DIMENSION
    distanta       = DIMENSION
    n              = NUMMER
    alternativ      = a b
    stil           = STYLE BEFEHL
    culoare        = COLOR
    type           = mp da nu
    mp             = NAME
```

```
\seteazaliniiumplere [...,.*,...]
*   inainte       = BEFEHL
    dupa          = BEFEHL
    margine        = DIMENSION
    latime         = DIMENSION
    distanta       = DIMENSION
    grosimerigla   = DIMENSION
    culoare        = COLOR
```

```

\seteazalista [...,1...] [...,2...,...]
1  LISTE
2  stare = start stop
   locatie = niciunul aici
   type = simple comanda userdata
   criteriu = local intro referinta SECTIONBLOCK:referinta tot SECTIONBLOCK:tot text SECTIONBLOCK:text
             curent SECTIONBLOCK:curent aici precedent SECTIONBLOCK:precedent componenta ABSCHNITT
             SECTIONBLOCK:ABSCHNITT
   lista = NAME
   latime = ajustat broad DIMENSION
   inaltime = ajustat broad DIMENSION
   inaltime = ajustat broad DIMENSION
   simbol = unu doi trei niciunul implicit
   eticheta = da nu niciunul NAME
   starter = BEFEHL
   stopper = BEFEHL
   comanda = \...#1#2#3
   comandanumar = \...#1
   comandatext = \...#1
   comandapagina = \...#1
   numarpagina = da nu totdeauna
   numartitlu = da nu totdeauna
   inainte = BEFEHL
   dupa = BEFEHL
   intre = BEFEHL
   margine = niciunul DIMENSION
   distanta = niciunul DIMENSION
   alinieretitlu = da nu
   numberalign = stanga dreapta centru flushleft flushright intern extern
   aliniere = inherits: \seteazaalinierea
   suspenda = da nu
   stanga = BEFEHL
   dreapta = BEFEHL
   interactiune = da nu tot numar text titlu pagina numarsetiune numarpagina
   limittext = da nu TEXT
   stil = STYLE BEFEHL
   culoare = COLOR
   stilnumar = STYLE BEFEHL
   culoarenumar = COLOR
   stiltext = STYLE BEFEHL
   culoaretex = COLOR
   stilpagina = STYLE BEFEHL
   culoarepagina = COLOR
   referinta = NUMMER
   extras = NAME
   order = comanda tot titlu
   alternativ = a b c d e f g stanga dreapta sus subsol comanda niciunul interactive paragraf orizontal
              vertical NAME
   latimemaxima = DIMENSION
   pageprefix = da nu
   pageprefixseparatorset = NAME
   pageprefixconversionset = NAME
   pageprefixset = NAME
   pageprefixsegments = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:tot ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:*
                       ABSCHNITT:tot curent
   pageprefixconnector = BEFEHL PROCESSOR->BEFEHL
   pageconversionset = NAME
   pagestarter = BEFEHL PROCESSOR->BEFEHL
   pagestopper = BEFEHL PROCESSOR->BEFEHL
   inherits: \setupcounterinherits: \seteazainconjurat

```

```

\seteazalistacombinata [...,1] [...,2...,...]
1  LISTE
2  criteriu = local intro referinta SECTIONBLOCK:referinta tot SECTIONBLOCK:tot text SECTIONBLOCK:text curent
            SECTIONBLOCK:curent aici precedent SECTIONBLOCK:precedent componenta ABSCHNITT SECTIONBLOCK:ABSCHNITT
   referinta = NUMMER
   extras = NAME
   order = comanda tot titlu
   alternativ = a b c d e f g stanga dreapta sus subsol comanda niciunul interactive paragraf orizontal vertical
              NAME

```

```

\setareCOMBINEDLIST [...,*...,...]
* inherits: \seteazalistacombinata
instances: content

```

```

\setarecontent [...,*...,...]
* inherits: \seteazalistacombinata

```

`\seteazamajuscule [...,1...] [...,2...,...]`

1 NAME OPT  
2 titlu = da nu  
sc = da nu  
stil = STYLE BEFEHL

`\seteazamakeup [...,1...] [...,2...,...]`

1 NAME OPT  
2 pagina = inherits: \pagina  
comanda = BEFEHL  
latime = DIMENSION  
inaltime = DIMENSION  
aliniera = inherits: \seteazaaliniera  
setups = NAME  
sus = BEFEHL  
jos = BEFEHL  
inainte = BEFEHL  
dupa = BEFEHL  
locatie = sus  
referinta = REFERENCE  
pagestate = start stop  
stareantet = start stop inalt gol niciunul normal  
staresubsol = start stop inalt gol niciunul normal  
staresus = start stop inalt gol niciunul normal  
starejos = start stop inalt gol niciunul normal  
staretext = start stop inalt gol niciunul normal  
douafete = da nu gol  
stil = STYLE BEFEHL  
culoare = COLOR

`\seteazamarcaje [...,1...] [...,2...,...]`

1 BESCHRIFTUNG OPT  
2 stare = start stop  
expansiune = da nu  
separator = BEFEHL  
filtercommand = \...##1

`\seteazameniuiinteractiune [...,1...] [...,2...,...]`

1 NAME OPT  
2 alternativ = vertical orizontal ascuns  
category = NAME  
offsetstanga = overlay incadrat niciunul implicit DIMENSION  
offsetdreapta = overlay incadrat niciunul implicit DIMENSION  
offsetsus = overlay incadrat niciunul implicit DIMENSION  
offsetjos = overlay incadrat niciunul implicit DIMENSION  
latimemaxima = DIMENSION  
inaltimemaxima = DIMENSION  
itemalign = stanga centru dreapta flushleft flushright jos inalt lohi  
stare = start gol local  
stanga = BEFEHL  
dreapta = BEFEHL  
distanta = overlay DIMENSION  
inainte = BEFEHL  
dupa = BEFEHL  
intre = BEFEHL  
pozitie = da nu  
mijloc = BEFEHL  
stil = STYLE BEFEHL  
culoare = COLOR  
aceeasipagina = da nu gol niciunul normal implicit  
culoarecontrast = COLOR  
inherits: \seteazainconjurat

`\seteazaminicitat [...,*...,...]`

\* inherits: \setupdelimitedtext

`\seteazanumarpagina [...,*...,...]`

\* inherits: \setuppagenumber

`\seteazanumarsubpagina [...,*...,...]`

\* inherits: \setupcounter

\seteazanumartitlu [...]<sup>1</sup> [...]<sup>2</sup>

1 ABSCHNITT  
2 [-+]NUMMER

\seteazanumerotarelinii [...]<sup>1</sup>,...<sup>2</sup> [...],...<sup>2</sup>,...]

1 NAME OPT  
2 start = NUMMER  
pas = NUMMER  
metoda = pagina primul urmatorul  
conversie = NAME  
continua = da nu  
locatie = text begin end implicit stanga dreapta intern extern instanga indreapta margine inmargine  
distanta = DIMENSION  
aliniere = intern extern flushleft flushright stanga dreapta centru auto  
comanda = \...##1  
stanga = BEFEHL  
dreapta = BEFEHL  
margine = DIMENSION  
latime = margine DIMENSION  
stil = STYLE BEFEHL  
culoare = COLOR

\seteazanumerotarepagina [...],...<sup>\*</sup>,...]

\* alternativ = ofata douafete  
pagina = inherits: \pagina  
strut = da nu  
comanda = \...##1  
stanga = BEFEHL  
dreapta = BEFEHL  
stare = start stop  
latime = DIMENSION  
locatie = antet subsol stanga centru dreapta instanga indreapta margine inmargine lamargine marginebordura  
stil = STYLE BEFEHL  
culoare = COLOR

\seteazanumerotareparagrafe [...],...<sup>\*</sup>,...]

\* stare = start stop linie reset  
distanta = DIMENSION  
stil = STYLE BEFEHL  
culoare = COLOR

\seteazapaleta [...]

\* NAME

\seteazaparagrafe [...]<sup>1</sup> [...],...<sup>2</sup> [...],...<sup>3</sup>,...]

1 NAME OPT OPT  
2 fiecare NUMMER  
3 n = NUMMER  
inainte = BEFEHL  
dupa = BEFEHL  
latime = DIMENSION  
distanta = DIMENSION  
inaltime = DIMENSION ajustat  
sus = BEFEHL  
jos = BEFEHL  
aliniere = inherits: \seteazaalinierea  
intern = BEFEHL  
comanda = BEFEHL  
rigla = on dezactivat  
grosimerigla = DIMENSION  
culoarerigla = COLOR  
stil = STYLE BEFEHL  
culoare = COLOR

**\seteazaparafrage** [<sup>1</sup>...] [<sup>2</sup>...,...]

```
1  NAME:NUMMER          OPT
2  n                    =  NUMMER
   inainte              =  BEFEHL
   dupa                  =  BEFEHL
   latime                =  DIMENSION
   distanta              =  DIMENSION
   inaltime              =  DIMENSION ajustat
   sus                   =  BEFEHL
   jos                   =  BEFEHL
   aliniere              =  inherits: \seteazaalinierea
   intern                =  BEFEHL
   comanda               =  BEFEHL
   rigla                 =  on dezactivat
   grosimerigla          =  DIMENSION
   culoarerigla          =  COLOR
   stil                  =  STYLE BEFEHL
   culoare               =  COLOR
```

**\seteazaplasareaopozita** [...,\*...]

```
*  stare                =  start stop
   inainte              =  BEFEHL
   dupa                  =  BEFEHL
   intre                =  BEFEHL
```

**\seteazaprograme** [...,\*...]

```
*  stil                 =  STYLE BEFEHL
   culoare              =  COLOR
```

**\seteazareferinte** [...,\*...]

```
*  stare                =  start stop
   expansiune           =  da nu xml
   autofile             =  da nu
   export               =  da nu
   stanga               =  BEFEHL
   dreapta              =  BEFEHL
   latime               =  DIMENSION
   douafete             =  da nu
   interactiune         =  eticheta text simbol tot
   separator            =  BEFEHL
   prefix               =  + - TEXT
```

\seteazaregistru [<sup>1</sup>...] [<sup>2</sup>...,...]

1	NAME NAME:NUMMER	OPT	
2	referencemethod	=	avans
	expansiune	=	da nu xml
	numarpropriu	=	da nu
	xmlsetup	=	NAME
	alternativ	=	a b A B
	metoda	=	implicit inainte dupa primul ultim ch mm zm pm mc zc pc uc
	compress	=	da nu tot
	check	=	da nu
	criteriu	=	local text curent precedent tot ABSCHNITT
	pageprefixseparatorset	=	BEFEHL
	pageprefixconversionset	=	NAME
	pageprefixstarter	=	BEFEHL PROCESSOR->BEFEHL
	pageprefixstopper	=	BEFEHL PROCESSOR->BEFEHL
	pageprefixset	=	NAME
	pageprefixsegments	=	NUMMER NUMMER:NUMMER NUMMER:* NUMMER:tot ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:* ABSCHNITT:tot curent
	pageprefixconnector	=	BEFEHL
	pageprefix	=	da nu
	pageseparatorset	=	NAME
	pageconversionset	=	NAME
	pagestarter	=	BEFEHL PROCESSOR->BEFEHL
	pagestopper	=	BEFEHL PROCESSOR->BEFEHL
	pagesegments	=	NUMMER NUMMER:NUMMER NUMMER:* NUMMER:tot
	latimemaxima	=	DIMENSION
	indicator	=	da nu
	inainte	=	BEFEHL
	dupa	=	BEFEHL
	comanda	=	\...##1
	comandatext	=	\...##1
	deeptextcommand	=	\...##1
	comandapagina	=	\...##1
	distanta	=	DIMENSION
	interactiune	=	text numarpagina
	numarpagina	=	da nu
	simbol	=	a n niciunul 1 2 BEFEHL
	language	=	implicit DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scn SPRACHE
	stil	=	STYLE BEFEHL
	culoare	=	COLOR
	stiltext	=	STYLE BEFEHL
	culoaretext	=	COLOR
	stilpagina	=	STYLE BEFEHL
	culoarepagina	=	COLOR
	pageleft	=	BEFEHL
	pageright	=	BEFEHL
	n	=	NUMMER
	balanta	=	da nu
	alinie	=	inherits: \seteazaalinie
	numberorder	=	numere



\seteazaregistru [...,<sup>1</sup>...] [...,<sup>2</sup>...] [...,<sup>3</sup>...,...]

```
1 NAME OPT OPT
2 NUMMER
3 referencemethod = avans
  expansiune = da nu xml
  numarpropriu = da nu
  xmlsetup = NAME
  alternativ = a b A B
  metoda = implicit inainte dupa primul ultim ch mm zm pm mc zc pc uc
  compress = da nu tot impachetat
  check = da nu
  criteriu = local text curent precedent tot ABSCHNITT
  pageprefixseparatorset = BEFEHL
  pageprefixconversionset = NAME
  pageprefixstarter = BEFEHL PROCESSOR->BEFEHL
  pageprefixstopper = BEFEHL PROCESSOR->BEFEHL
  pageprefixset = NAME
  pageprefixsegments = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:tot ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:*
                        ABSCHNITT:tot curent

  pageprefixconnector = BEFEHL
  pageprefix = da nu
  pageseparatorset = NAME
  pageconversionset = NAME
  pagestarter = BEFEHL PROCESSOR->BEFEHL
  pagestopper = BEFEHL PROCESSOR->BEFEHL
  pagesegments = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:tot
  latimemaxima = DIMENSION
  indicator = da nu
  inainte = BEFEHL
  dupa = BEFEHL
  comanda = \...##1
  comandatext = \...##1
  deeptextcommand = \...##1
  comandapagina = \...##1
  distanta = DIMENSION
  interactiune = text numarpagina
  numarpagina = da nu
  simbol = a n niciunul 1 2 BEFEHL
  language = implicit DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scen SPRACHE
  stil = STYLE BEFEHL
  culoare = COLOR
  stiltext = STYLE BEFEHL
  culoarettext = COLOR
  stilpagina = STYLE BEFEHL
  culoarepagina = COLOR
  pageleft = BEFEHL
  pageright = BEFEHL
  n = NUMBER
  balanta = da nu
  aliniere = inherits: \seteazaalinierea
  numberorder = numere
```

\setareREGISTER [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

```
1 NUMMER OPT
2 inherits: \seteazaregistru
instances: index
```

\setareindex [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

```
1 NUMMER OPT
2 inherits: \seteazaregistru
```

\seteazarigletext [...,<sup>\*</sup>...,...]

```
* inainte = BEFEHL
  dupa = BEFEHL
  intre = BEFEHL
  grosimerigla = DIMENSION
  locatie = stanga inmarginie
  stil = STYLE BEFEHL
  culoare = COLOR
  culoarerigla = COLOR
  latime = DIMENSION
  inaltime = DIMENSION
  distanta = DIMENSION
  corectieadancime = on dezactivat
  fonttext = inherits: \seteazafonttext
```

**\seteazarigleumplere** [...,..<sup>\*</sup>...,...]

\*    inainte                = BEFEHL  
     dupa                 = BEFEHL  
     n                     = NUMBER  
     spatiereinterliniara = mic mediu mare NUMBER  
     distanta              = DIMENSION  
     latime                = ajustat broad DIMENSION  
     separator            = BEFEHL  
     stil                  = STYLE BEFEHL  
     culoare              = COLOR

**\seteazarotare** [...,..<sup>\*</sup>...,...]

\*    locatie = ajustat broad adancime inalt centru implicit normal  
     rotatie = stanga dreapta intern extern NUMBER  
     inherits: \seteazainconjurat

**\seteazasimbol** [...]

\*    NAME

**\seteazasinonime** [...,<sup>1</sup>...] [...,..<sup>2</sup>...,...]

1    SINGULAR                OPT  
2    expansiune              = da nu xml  
     alternativ               = primul ultim normal NAME  
     urmatorul               = BEFEHL  
     comanda                = \...##1##2##3  
     comandatext            = \...##1  
     synonymcommand        = \...##1  
     language               = implicit DIN\_5007-1 DIN\_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scن SPRACHE  
     metoda                 = implicit inainte dupa primul ultim ch mm zm pm mc zc pc uc  
     criteriu                = curent precedent local text tot ABSCHNITT  
     stil                    = STYLE BEFEHL  
     culoare                = COLOR  
     stiltext                = STYLE BEFEHL  
     culoaretext            = COLOR  
     stilsinonim            = STYLE BEFEHL  
     culoaresinonim        = COLOR

**\seteazasortare** [...,<sup>1</sup>...] [...,..<sup>2</sup>...,...]

1    SINGULAR                OPT  
2    expansiune              = da nu xml  
     alternativ               = primul ultim normal NAME  
     urmatorul               = BEFEHL  
     comanda                = \...##1##2##3  
     comandatext            = \...##1  
     synonymcommand        = \...##1  
     language               = implicit DIN\_5007-1 DIN\_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scن SPRACHE  
     metoda                 = implicit inainte dupa primul ultim ch mm zm pm mc zc pc uc  
     criteriu                = curent precedent local text tot ABSCHNITT  
     stil                    = STYLE BEFEHL  
     culoare                = COLOR  
     stiltext                = STYLE BEFEHL  
     culoaretext            = COLOR  
     stilsinonim            = STYLE BEFEHL  
     culoaresinonim        = COLOR

**\seteazaspatiu** [...]

\*    fixat impachetat <sup>OPT</sup> broad

**\seteazaspatialb** [...,<sup>\*</sup>...]

\*    fix fixat flexibil linie <sup>OPT</sup> jumatatelinie quarterline niciunul mic mediu mare implicit DIMENSION

```

\seteazaspatiuiinterliniar [...] [...]
1 NAME OPT
2 linie = DIMENSION
  inalttime = NUMMER
  inalttime = NUMMER
  inalttimeminima = NUMMER
  mindepth = NUMMER
  distanta = DIMENSION
  sus = NUMMER inalttime
  jos = NUMMER
  dilatat = NUMMER
  shrink = NUMMER

```

```

\seteazaspatiuiinterliniar [...]
* on dezactivat reset auto mic mediu mare NUMMER DIMENSION

```

```

\seteazaspatiuiinterliniar [...]
* NAME

```

```

\seteazasubsol [...]
1 text margine bordura
2 inherits: \setuplayouttext

```

```

\seteazasus [...]
1 text margine bordura
2 inherits: \setuplayouttext

```

```

\seteazatabele [...]
* text = DIMENSION max
  split = da nu repetat auto
  frame = on dezactivat
  NL = inherits: \blanc
  VL = mic mediu mare niciunul NUMMER
  HL = mic mediu mare niciunul NUMMER
  distanta = mic mediu mare niciunul
  aliniere = stanga centru dreapta
  comenzi = BEFEHL
  fonttext = inherits: \seteazafonttext
  grosimerigla = DIMENSION
  inalttime = strut NUMMER
  inalttime = strut NUMMER
  openup = DIMENSION

```

```

\seteazatabulatori [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setuptabulation

```

```

\seteazatext [...]
1 text margine bordura
2 inherits: \setuplayouttext

```

```

\seteazatexteantet [...] [...] [...] [...] [...]
1 text margine bordura OPT OPT OPT OPT OPT
2 data numarpagina BESCHRIFTUNG TEXT BEFEHL
3 data numarpagina BESCHRIFTUNG TEXT BEFEHL
4 data numarpagina BESCHRIFTUNG TEXT BEFEHL
5 data numarpagina BESCHRIFTUNG TEXT BEFEHL

```

```

\seteazatextejos [...] [...] [...] [...] [...]
1 text margine bordura OPT OPT OPT OPT OPT
2 data numarpagina BESCHRIFTUNG TEXT BEFEHL
3 data numarpagina BESCHRIFTUNG TEXT BEFEHL
4 data numarpagina BESCHRIFTUNG TEXT BEFEHL
5 data numarpagina BESCHRIFTUNG TEXT BEFEHL

```

```
\seteazatextesubsol [...1] [...2] [...3] [...4] [...5]
1 text margine bordura OPT OPT OPT OPT OPT
2 data numarpagina BESCHRIFTUNG TEXT BEFEHL
3 data numarpagina BESCHRIFTUNG TEXT BEFEHL
4 data numarpagina BESCHRIFTUNG TEXT BEFEHL
5 data numarpagina BESCHRIFTUNG TEXT BEFEHL
```

```
\seteazatextesus [...1] [...2] [...3] [...4] [...5]
1 text margine bordura OPT OPT OPT OPT OPT
2 data numarpagina BESCHRIFTUNG TEXT BEFEHL
3 data numarpagina BESCHRIFTUNG TEXT BEFEHL
4 data numarpagina BESCHRIFTUNG TEXT BEFEHL
5 data numarpagina BESCHRIFTUNG TEXT BEFEHL
```

```
\seteazatextetext [...1] [...2] [...3] [...4] [...5]
1 text margine bordura OPT OPT OPT OPT OPT
2 data numarpagina BESCHRIFTUNG TEXT BEFEHL
3 data numarpagina BESCHRIFTUNG TEXT BEFEHL
4 data numarpagina BESCHRIFTUNG TEXT BEFEHL
5 data numarpagina BESCHRIFTUNG TEXT BEFEHL
```

```
\setareLABELtext [...1] [...,2...,...]
1 SPRACHE OPT
2 KEY = VALUE
instances: head label mathlabel taglabel unit operator prefix suffix btxlabel
```

```
\setarebtxlabeltext [...1] [...,2...,...]
1 SPRACHE OPT
2 KEY = VALUE
```

```
\setareheadtext [...1] [...,2...,...]
1 SPRACHE OPT
2 KEY = VALUE
```

```
\setarelabeltext [...1] [...,2...,...]
1 SPRACHE OPT
2 KEY = VALUE
```

```
\setaremathlabeltext [...1] [...,2...,...]
1 SPRACHE OPT
2 KEY = VALUE
```

```
\setareoperatortext [...1] [...,2...,...]
1 SPRACHE OPT
2 KEY = VALUE
```

```
\setareprefixtext [...1] [...,2...,...]
1 SPRACHE OPT
2 KEY = VALUE
```

```
\setaresuffixtext [...1] [...,2...,...]
1 SPRACHE OPT
2 KEY = VALUE
```

```
\setaretaglabeltext [...1] [...,2...,...]
1 SPRACHE OPT
2 KEY = VALUE
```

```
\setareunittext [...1] [...,2...,...]
1 SPRACHE OPT
2 KEY = VALUE
```

\seteazatitlu [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```

1  ABSCHNITT          OPT
2  frontpartlabel     = NAME
   bodypartlabel      = NAME
   appendixlabel      = NAME
   backpartlabel      = NAME
   expansiune         = da nu xml
   catcodes           = NAME
   sectionresetset    = NAME
   sectionseparatorset = NAME
   sectionconversionset = NAME
   conversie          = NAME
   sectionstarter     = BEFEHL PROCESSOR->BEFEHL
   sectionstopper      = BEFEHL PROCESSOR->BEFEHL
   sectionset         = NAME
   sectionsegments    = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:tot ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:*
                        ABSCHNITT:tot curent

   referenceprefix    = + - TEXT
   stil               = STYLE BEFEHL
   culoare            = COLOR
   stiltext           = STYLE BEFEHL
   culoaretext        = COLOR
   stilnumar          = STYLE BEFEHL
   culoarenumar       = COLOR
   cuplare            = ABSCHNITT
   numarpropriu       = da nu
   beforesection      = BEFEHL
   aftersection       = BEFEHL
   insidesection      = BEFEHL
   numarincrement     = da nu lista gol
   punetitlu          = da nu ascuns gol sectiune
   numar             = da nu
   pagina             = inherits: \pagina
   marcaje            = pagina reset
   antet              = start stop inalt niciunul normal gol faramarcare NAME
   text               = start stop inalt niciunul normal gol faramarcare NAME
   subsol             = start stop inalt niciunul normal gol faramarcare NAME
   inainte            = BEFEHL
   dupa               = BEFEHL
   intre              = BEFEHL
   continua           = da nu
   alinieretitlu      = da nu obiectmobil
   spatiereinterliniara = NAME
   interactiune       = lista referinta
   internalgrid       = NAME
   grid               = normal standard da strict tolerant sus subsol ambele broad ajustat primul ultim inalt unu
                        jos niciunul linie strut box min max centru math math:linie math:jumatatelinie math:-line
                        math:-halfline NAME

   aliniere           = inherits: \seteazaalinierea
   toleranta          = inherits: \seteazatoleranta
   strut              = da nu
   suspenda           = linie broad ajustat niciunul NUMMER
   margine            = DIMENSION
   aliniaturmator     = da nu auto
   alternativ          = text paragraf normal margine inmargine sus centru subsol reverse textmarginal NAME
   latime             = DIMENSION
   numberwidth        = DIMENSION
   latimetext         = DIMENSION
   distanta           = DIMENSION
   textdistance       = DIMENSION
   comandainainte     = BEFEHL
   comandadupa        = BEFEHL
   comanda            = \...##1##2
   comandatext        = \...##1
   deeptextcommand    = \...##1
   comandanumar       = \...##1
   deepnumbercommand  = \...##1
   locatie            = NAME
   criteriu           = strict pozitiv tot

```

\seteazatitluri [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```

1  ABSCHNITT          OPT
2  inherits: \seteazatitlu

```

\seteazatoleranta [...\*,...]

\* orizontal vertical foarteststrict strict tolerant foartetolerant spatiu dilatat

**\seteazatranzitiepagina** [<sup>1</sup>...]

\* reset auto start aleator NUMBER

**\seteazatype** [<sup>1</sup>...,...]<sup>2</sup> [<sup>2</sup>...,...]

1 NAME OPT  
2 optiune = mp lua xml parsed-xml nested tex context niciunul NAME  
comanda = CSNAME  
stanga = BEFEHL  
dreapta = BEFEHL  
tab = da nu NUMBER  
compact = absolut ultim tot  
escape = da nu TEXT PROCESSOR->TEXT  
stil = STYLE BEFEHL  
culoare = COLOR  
linii = da nu normal despsilabe  
spatiu = on dezactivat normal fixat dilatat

**\seteazatyping** [<sup>1</sup>...,...]<sup>2</sup> [<sup>2</sup>...,...]

1 NAME OPT  
2 margineimpara = DIMENSION  
marginepara = DIMENSION  
margine = da nu standard DIMENSION  
optiune = mp lua xml parsed-xml nested tex context niciunul NAME  
stil = STYLE BEFEHL  
culoare = COLOR  
alinie = inherits: \seteazaalinie  
linii = da nu normal despsilabe  
spatiu = on dezactivat normal fixat dilatat  
keeptogether = da nu  
inainte = BEFEHL  
dupa = BEFEHL  
strip = da nu NUMBER  
range = NUMMER NAME  
tab = da nu NUMBER  
escape = da nu TEXT PROCESSOR->TEXT  
aliniaturmator = da nu auto  
continua = da nu  
start = NUMMER  
stop = NUMMER  
pas = NUMMER  
numerotare = fisier linie nu  
blanc = inherits: \blanc

**\seteazaurl** [<sup>1</sup>...,...<sup>\*</sup>...,...]

\* stil = STYLE BEFEHL  
culoare = COLOR

**\setelementexporttag** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...]

1 NAME OPT  
2 export nature pdf  
3 inline display mixed

**\setemeasure** {<sup>1</sup>...} {<sup>2</sup>...}

1 NAME  
2 DIMENSION

**\setevalue** {<sup>1</sup>...} {<sup>2</sup>...}

1 NAME  
2 CONTENT

**\setevariable** {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...}

1 NAME  
2 KEY  
3 VALUE

**\setevariables** [<sup>1</sup>...] [<sup>2</sup>...,...]

1 NAME  
2 set = BEFEHL  
reset = BEFEHL  
KEY = VALUE

* NAME	OPT
--------	-----

\setfirstpasscharacteralign

\* NAME

\* FONT

\* NAME

\* NAME

\* NAME

\setfontstrut

```
* hangul hanzi nihongo ethiopic thai test NAME
```

1	NAME
2	DIMENSION

1	NAME
2	CONTENT

1	NAME
2	KEY
3	VALUE

```

1  NAME
2  set      =  BEFEHL
   reset    =  BEFEHL
   KEY      =  VALUE

```

```

1 CSNAME NUMMER
2 CONTENT

```

\* TEXT

\* TEXT

\* TEXT

```
* NAME reset OPT
```

<code>\setinitial [...]<sup>1</sup> [...,...<sup>2</sup>...,...]</code> 1 NAME OPT OPT 2 inherits: \setupinitial
<code>\setinjector [...]<sup>1</sup> [...,...<sup>2</sup>,...] [...]<sup>3</sup></code> 1 NAME 2 NUMMER 3 BEFEHL
<code>\setinteraction [...]</code> * ascuns NAME
<code>\setinterfacecommand {...}<sup>1</sup> {...}<sup>2</sup></code> 1 NAME 2 NAME
<code>\setinterfaceconstant {...}<sup>1</sup> {...}<sup>2</sup></code> 1 NAME 2 NAME
<code>\setinterfaceelement {...}<sup>1</sup> {...}<sup>2</sup></code> 1 NAME 2 NAME
<code>\setinterfacemessage {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup></code> 1 NAME 2 titlu NAME NUMMER 3 TEXT
<code>\setinterfacevariable {...}<sup>1</sup> {...}<sup>2</sup></code> 1 NAME 2 NAME
<code>\setinternalrendering [...]<sup>1</sup> [...]<sup>2</sup> {...}<sup>3</sup></code> 1 NAME 2 auto embed 3 CONTENT
<code>\setitaliccorrection [...]</code> * reset 1 2
<code>\setJSreamble {...}<sup>1</sup> {...}<sup>2</sup></code> 1 NAME 2 CONTENT
<code>\setlayer [...]<sup>1</sup> [...]<sup>2</sup> [...,...<sup>3</sup>...,...]<sup>3</sup> {...}<sup>4</sup></code> 1 NAME OPT OPT 2 stanga dreapta par impar 3 inherits: \setuplayer 4 CONTENT
<code>\setlayerframed [...]<sup>1</sup> [...,...<sup>2</sup>...,...]<sup>2</sup> [...,...<sup>3</sup>...,...]<sup>3</sup> {...}<sup>4</sup></code> 1 NAME OPT OPT 2 inherits: \setuplayer 3 inherits: \seteazainconjurat 4 CONTENT
<code>\setlayerframed [...]<sup>1</sup> [...,...<sup>2</sup>...,...]<sup>2</sup> {...}<sup>3</sup></code> 1 NAME OPT 2 inherits: \setuplayerinherits: \seteazainconjurat 3 CONTENT



<pre> \setlayertext [...<sup>1</sup>] [...<sup>2</sup>...<sup>3</sup>...] [...<sup>4</sup>...] {...} 1  NAME 2  inherits: \setuplayer 3  aliniere = inherits: \setezaalinierea    latime  = DIMENSION    stil    = STYLE BEFEHL    culoare = COLOR 4  TEXT </pre>
<pre> \setlinefiller [...] *  filler NAME </pre>
<pre> \setlocalhsize [...] *  [-+]DIMENSION OPT </pre>
<pre> \setlocalscript [...] *  hangul hanzi nihongo ethiopic thai test NAME </pre>
<pre> \setMPlayer [...<sup>1</sup>] [...<sup>2</sup>] [...<sup>3</sup>...<sup>4</sup>...] {...} 1  NAME 2  NAME 3  inherits: \setuplayer 4  CONTENT </pre>
<pre> \setMPpositiongraphic {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>...<sup>4</sup>...] 1  NAME 2  NAME 3  KEY = VALUE </pre>
<pre> \setMPpositiongraphicrange {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} {...<sup>4</sup>...<sup>5</sup>...] 1  NAME 2  NAME 3  NAME 4  KEY = VALUE </pre>
<pre> \setMPtext {...<sup>1</sup>} {...<sup>2</sup>} 1  NAME 2  TEXT </pre>
<pre> \setMPvariable [...<sup>1</sup>] [...<sup>2</sup>...] 1  NAME 2  KEY = VALUE </pre>
<pre> \setMPvariables [...<sup>1</sup>] [...<sup>2</sup>...<sup>3</sup>...] 1  NAME 2  KEY = VALUE </pre>
<pre> \setmainbodyfont </pre>
<pre> \setmainparbuilder [...] *  implicit oneline basic NAME </pre>
<pre> \setmarker [...<sup>1</sup>] [...<sup>2</sup>] 1  NAME 2  NUMMER </pre>
<pre> \setmarking [...<sup>1</sup>] {...<sup>2</sup>} 1  BESCHRIFTUNG 2  TEXT </pre>
<pre> \setmathstyle {...,*...} *  display text script scriptscript cramped uncramped normal impachetat mic mare NAME </pre>

<pre> \setmeasure {...} {...} 1  NAME 2  DIMENSION </pre>
<pre> \setmessagetext {...} {...} 1  NAME 2  NAME NUMBER </pre>
<pre> \setmode {...} *  NAME </pre>
<pre> \setnostrut </pre>
<pre> \setnote [...]<sup>1</sup> [...,<sup>2</sup>...] {...}<sup>3</sup> 1  NAME 2  REFERENCE 3  TEXT </pre>
<pre> \setnotetext [...]<sup>1</sup> [...,<sup>2</sup>...] {...}<sup>3</sup> 1  NAME 2  REFERENCE 3  TEXT </pre>
<pre> \setnotetext [...]<sup>1</sup> [...,<sup>2</sup>...] 1  NAME 2  titlu      = TEXT    semncarte = TEXT    lista     = TEXT    referinta = REFERENCE </pre>
<pre> \setnote [...]<sup>1</sup> [...,<sup>2</sup>...] 1  NAME 2  titlu      = TEXT    semncarte = TEXT    lista     = TEXT    referinta = REFERENCE </pre>
<pre> \setobject {...}<sup>1</sup> {...}<sup>2</sup> \... {...}<sup>3</sup> {...}<sup>4</sup> 1  NAME 2  NAME 3  CSNAME 4  CONTENT </pre>
<pre> \setoldstyle </pre>
<pre> \setpagereference {...}<sup>1</sup> [...,<sup>2</sup>...] 1  NAME 2  REFERENCE </pre>
<pre> \setpagestate [...]<sup>1</sup> [...]<sup>2</sup> 1  NAME 2  NAME NUMBER </pre>
<pre> \setpagestaterealpageno {...}<sup>1</sup> {...}<sup>2</sup> 1  NAME 2  NAME NUMBER </pre>
<pre> \setpenalties \... {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup> 1  CSNAME 2  NUMMER 3  NUMMER </pre>

`\setpercentdimen {...} {...}`

- 1 DIMENSION CSNAME
- 2 DIMENSION NUMMER

`\setperiodkerning [...]`

- \* reset NAME

`\setposition {...}`

- \* NAME

`\setpositionbox {...} \^2... {...}`

- 1 NAME
- 2 CSNAME
- 3 CONTENT

`\setpositiondata {...} {...} {...} {...}`

- 1 NAME
- 2 DIMENSION
- 3 DIMENSION
- 4 DIMENSION

`\setpositiondataplus {...} {...} {...} {...} {...,5...}`

- 1 NAME
- 2 DIMENSION
- 3 DIMENSION
- 4 DIMENSION
- 5 TEXT

`\setpositiononly {...}`

- \* NAME

`\setpositionplus {...} {...,2...} \^3... {...}`

- 1 NAME
- 2 TEXT
- 3 CSNAME
- 4 CONTENT

`\setpositionstrut {...}`

- \* NAME

`\setprofile [...]`

- \* niciunul fixat strict halffixed quarterfixed eightsfixed NAME

`\setrandomseed {...}`

- \* NUMMER

`\setreference [...,1...] [...,2...,...]`

- 1 REFERENCE
- 2 KEY = VALUE

`\setreferencedobject {...} {...} \^3... {...}`

- 1 NAME
- 2 NAME
- 3 CSNAME
- 4 CONTENT

<pre> \setregisterentry [...] [...] [...] 1  NAME 2  eticheta    = NAME     keys       = TEXT PROCESSOR-&gt;TEXT     entries    = TEXT PROCESSOR-&gt;TEXT     keys:1     = TEXT     keys:2     = TEXT     keys:3     = TEXT     entries:1  = TEXT     entries:2  = TEXT     entries:3  = TEXT     alternativ  = TEXT 3  KEY = VALUE </pre>
<pre> \setreplacement [...] *  reset NAME </pre>
<pre> \setrigidcolumnbalance ... *  CSNAME NUMMER </pre>
<pre> \setrigidcolumnhsize {...} {...} {...} 1  DIMENSION 2  DIMENSION 3  NUMMER </pre>
<pre> \setscript [...] *  hangul hanzi nihongo ethiopic thai test NAME </pre>
<pre> \setsecondpasscharacteralign </pre>
<pre> \setsectionblock [...] [...] 1  NAME 2  semncarte = TEXT </pre>
<pre> \setsimplecolumnhsize [...,...*,...] *  n      = NUMMER     latime = DIMENSION     distanta = DIMENSION     linii  = NUMMER </pre>
<pre> \setsmallbodyfont </pre>
<pre> \setsmallcaps </pre>
<pre> \setstackbox {...} {...} {...} 1  NAME 2  NAME 3  CONTENT </pre>
<pre> \setstructurepageregister [...] [...] [...] 1  NAME 2  eticheta    = NAME     keys       = TEXT PROCESSOR-&gt;TEXT     entries    = TEXT PROCESSOR-&gt;TEXT     keys:1     = TEXT     keys:2     = TEXT     keys:3     = TEXT     entries:1  = TEXT     entries:2  = TEXT     entries:3  = TEXT     alternativ  = TEXT 3  KEY = VALUE </pre>
<pre> \setstrut </pre>

<code>\setsuperiors</code>
<code>\setsystemmode {...}</code> *    NAME
<code>\settabular</code>
<code>\settaggedmetadata [...,*...,...]</code> *    KEY   =   VALUE
<code>\settextcontent [...<sup>1</sup>.] [...<sup>2</sup>.] [...<sup>3</sup>.] [...<sup>4</sup>.] [...<sup>5</sup>.]</code> 1    sus antet text subsol subsol                    OPT                    OPT 2    text margine bordura 3    stanga centru dreapta 4    data numarpagina BESCHRIFTUNG TEXT BEFEHL 5    data numarpagina BESCHRIFTUNG TEXT BEFEHL
<code>\settightobject {...<sup>1</sup>.} {...<sup>2</sup>.} \... {...<sup>4</sup>.}</code> 1    NAME 2    NAME 3    CSNAME 4    CONTENT
<code>\settightreferencedobject {...<sup>1</sup>.} {...<sup>2</sup>.} \... {...<sup>4</sup>.}</code> 1    NAME 2    NAME 3    CSNAME 4    CONTENT
<code>\settightstrut</code>
<code>\settightunreferencedobject {...<sup>1</sup>.} {...<sup>2</sup>.} \... {...<sup>4</sup>.}</code> 1    NAME 2    NAME 3    CSNAME 4    CONTENT
<code>\settokenlist [...<sup>1</sup>.] {...<sup>2</sup>.}</code> 1    NAME 2    TEXT
<code>\settrialtypesetting</code>
<code>\setuevalue {...<sup>1</sup>.} {...<sup>2</sup>.}</code> 1    NAME 2    CONTENT
<code>\setugvalue {...<sup>1</sup>.} {...<sup>2</sup>.}</code> 1    NAME 2    CONTENT
<code>\setunreferencedobject {...<sup>1</sup>.} {...<sup>2</sup>.} \... {...<sup>4</sup>.}</code> 1    NAME 2    NAME 3    CSNAME 4    CONTENT
<code>\setupalternativestyles [...,*...,...]</code> *    metoda   =   normal auto

\setupattachment [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
2 titlu = TEXT  
subtitlu = TEXT  
autor = TEXT  
fisier = FILE  
nume = NAME  
buffer = BUFFER  
stare = start stop  
metoda = normal ascuns  
simbol = Graph Paperclip Pushpin Default  
latime = ajustat DIMENSION  
inaltime = ajustat DIMENSION  
inaltime = ajustat DIMENSION  
culoare = COLOR  
textlayer = NAME  
locatie = bordurastanga borduradreaapta inmarginestanga marginedreaapta text inalt niciunul  
distanta = DIMENSION

\setupattachments [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
2 inherits: \setupattachment

\setupbackend [...<sup>\*</sup>,...]

\* export = da FILE  
xhtml = FILE  
fisier = FILE  
intent = Coated\_FOGRA39\_(ISO\_12647-2:2004) GRACoL2006\_Coated1v2.icc ISO\_Coated\_v2\_300 ISO\_Coated\_v2\_(ECI)  
ISOnewspaper26v4 ISOnewspaper26v4\_gr ISO\_Uncoated ISO\_Uncoated\_Yellowish ISO\_Web\_Coated Japan\_Color\_2001\_Coated  
Japan\_Color\_2002\_Newspaper Japan\_Web\_Coated\_(Ad) SNAP\_2007 SWOP2006\_Coated3v2.icc SWOP2006\_Coated5v2.icc  
Uncoated\_FOGRA29\_(ISO\_12647-2:2004) Web\_Coated\_FOGRA28\_(ISO\_12647-2:2004) PSR\_LWC\_PLUS\_V2\_PT PSR\_LWC\_STD\_V2\_PT  
PSR\_SC\_PLUS\_V2\_PT PSR\_SC\_STD\_V2\_PT PSRgravureMF  
spatiu = da nu  
xmpfile = FILE  
format = version implicit PDF/X-1a:2001 PDF/X-1a:2003 PDF/X-3:2002 PDF/X-3:2003 PDF/X-4 PDF/X-4p PDF/X-5g  
PDF/X-5pg PDF/X-5n PDF/A-1a:2005 PDF/A-1b:2005 PDF/A-2a PDF/A-3a PDF/UA-1  
nivel = NUMMER  
optiune = totdeauna niciodata  
profile = FILE

\setupbar [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
2 culoare = COLOR  
continua = da nu tot  
gol = da nu  
unitate = ex em pt in cm mm sp bp pc dd cc nc  
order = primplan fundal  
grosimerigla = DIMENSION  
metoda = NUMMER  
offset = NUMMER  
dy = NUMMER  
max = NUMMER  
foregroundstyle = STYLE BEFEHL  
foregroundcolor = COLOR  
mp = NAME  
stanga = TEXT  
dreapta = TEXT

\setupbars [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
2 inherits: \setupbar

\setupbleeding [...<sup>\*</sup>,...]

\* latime = DIMENSION  
inaltime = DIMENSION  
offset = DIMENSION  
hoffset = DIMENSION  
voffset = DIMENSION  
locatie = t b l r bl lb br rb tl lt tr rt  
dilatata = da nu  
pagina = da nu

```

\setupbookmark [...,..1...,...]
*   fortat           = da nu
    numar           = da nu
    numberseparatorset = NAME
    numberconversionset = NAME
    numberstarter    = BEFEHL
    numberstopper    = BEFEHL
    numbersegments   = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:tot ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:* ABSCHNITT:tot
    sectionblock     = da nu

```

```

\setupbtx [...,..1...] [...,..2...,...]
1   NAME             OPT
2   specification     = implicit apa aps NAME
    dataset           = implicit NAME
    comanda           = \...##1
    stanga            = BEFEHL
    dreapta           = BEFEHL
    authorconversion   = normal normalshort normalinverted invertedshort short
    etallimit         = NUMBER
    etaldisplay       = NUMBER
    etaloption        = ultim
    stopper           = initials
    interactiune      = start stop numar text pagina tot
    alternativ         = implicit category entry short pagina num textnum an index tag keywords autor authoryears
                      authornum authoryear
    sorttype          = normal reverse
    compress          = da nu
    implicit          = implicit NAME
    stil              = STYLE BEFEHL
    culoare           = COLOR

```

```

\setupbtxdataset [...,..1...] [...,..2...,...]
1   NAME             OPT
2   language         = SPRACHE

```

```

\setupbtxlist [...,..1...] [...,..2...,...]
1   NAME             OPT
2   inherits: \seteazalista

```

```

\setupbtxregister [...,..1...] [...,..2...,...]
1   NAME             OPT
2   stare            = start stop
    dataset          = NAME
    field            = keyword range numarpagina autor
    register         = NAME
    metoda           = once
    alternativ        = normalshort invertedshort
    stil             = STYLE BEFEHL
    culoare          = COLOR

```

```

\setupbtxrendering [...,..1...] [...,..2...,...]
1   NAME             OPT
2   staretext        = start stop
    pagestate        = start stop
    separator        = BEFEHL
    criteriu         = precedent cite aici tot niciunul
    filter           = TEXT
    specification     = NAME
    titlu            = TEXT
    inainte          = BEFEHL
    dupa             = BEFEHL
    dataset          = NAME
    metoda           = dataset fortat local global niciunul
    sorttype         = short dataset lista referinta folosit implicit cite index
    repeta           = da nu
    group            = NAME
    numerotare       = da nu num index tag short pagina

```

```

\setupbtx [...,..1...]
*   NAME

```

**\setupbutton** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME OPT  
2 stare = start stop  
aceeasipagina = da nu gol niciunul normal implicit  
stil = STYLE BEFEHL  
culoare = COLOR  
culoarecontrast = COLOR  
alternativ = ascuns  
inherits: \seteazainconjurat

**\setupcharacteralign** [...,<sup>\*</sup>...,...]

\* latimestanga = DIMENSION  
marginedreapta = DIMENSION  
leftsample = TEXT  
rightsample = TEXT  
character = TEXT number->TEXT text->TEXT

**\setupcharacterkerning** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME OPT  
2 factor = max NUMMER  
latime = DIMENSION  
features = NAME  
stil = STYLE BEFEHL  
culoare = COLOR

**\setupcharacterspacing** [...<sup>1</sup>] [...<sup>2</sup>] [...,<sup>3</sup>...,...]

1 NAME OPT  
2 NUMMER  
3 stanga = NUMMER  
dreapta = NUMMER  
alternativ = 0 1

**\setupchemical** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME OPT  
2 strut = da nu auto cap ajustat linie implicit CHARACTER  
latime = ajustat niciunul NUMMER  
inaltime = ajustat niciunul NUMMER  
stanga = ajustat niciunul NUMMER  
dreapta = ajustat niciunul NUMMER  
sus = ajustat niciunul NUMMER  
jos = ajustat niciunul NUMMER  
scala = mic mediu mare normal NUMMER  
rotatie = NUMMER  
symaliniere = auto  
axa = on dezactivat  
culoareframe = COLOR  
grosimerigla = DIMENSION  
offset = DIMENSION  
unitate = DIMENSION  
factor = NUMMER  
frame = on dezactivat  
culoarerigla = COLOR  
fonttext = inherits: \seteazafonttext  
dimensiune = mic mediu mare  
stil = STYLE BEFEHL  
culoare = COLOR

**\setupchemicalframed** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME OPT  
2 inherits: \seteazainconjurat

**\setupcollector** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME OPT  
2 rotatie = stanga dreapta intern extern NUMMER  
colt = stanga centru dreapta sus subsol  
x = DIMENSION  
y = DIMENSION  
hoffset = DIMENSION  
voffset = DIMENSION  
locatie = stanga centru dreapta sus subsol linie l c r m t b g  
stare = start stop



**\setupcolumnset** [...<sup>1</sup>...] [...<sup>2</sup>...]

1 NAME NAME:NUMBER OPT  
2 n = NUMBER  
nstanga = NUMBER  
ndreapta = NUMBER  
latime = DIMENSION auto  
distanta = DIMENSION  
linii = NUMBER  
latimemaxima = DIMENSION  
inaltimemaxima = DIMENSION  
directie = normal reverse  
pagina = inherits: \pagina  
inherits: \seteazainconjurat

**\setupcolumnsetarea** [...<sup>1</sup>...] [...<sup>2</sup>...]

1 NAME OPT  
2 stare = start stop repetat  
x = NUMBER  
y = NUMBER  
nx = NUMBER  
ny = NUMBER  
stil = STYLE BEFEHL  
culoare = COLOR  
clipoffset = DIMENSION  
offsetdreapta = DIMENSION  
inherits: \seteazainconjurat

**\setupcolumnsetareatext** [...<sup>1</sup>] [...<sup>2</sup>]

1 NAME  
2 TEXT

**\setupcolumnsetlines** [...<sup>1</sup>] [...<sup>2</sup>] [...<sup>3</sup>] [...<sup>4</sup>]

1 NAME  
2 NUMMER  
3 NUMMER  
4 NUMMER

**\setupcolumnsetspan** [...<sup>1</sup>...] [...<sup>2</sup>...]

1 NAME OPT  
2 n = NUMBER  
stil = STYLE BEFEHL  
culoare = COLOR  
inainte = BEFEHL  
dupa = BEFEHL  
inherits: \seteazainconjurat

**\setupcolumnsetstart** [...<sup>1</sup>] [...<sup>2</sup>] [...<sup>3</sup>] [...<sup>4</sup>]

1 NAME  
2 NUMMER  
3 NUMMER  
4 NUMMER

**\setupcolumnspan** [...<sup>\*</sup>...]

\* n = NUMMER  
inherits: \seteazainconjurat

**\setupcombination** [...<sup>1</sup>...] [...<sup>2</sup>...]

1 NAME OPT  
2 nx = NUMBER  
ny = NUMBER  
latime = ajustat DIMENSION  
inaltime = ajustat DIMENSION  
locatie = stanga centru dreapta sus subsol  
distanta = DIMENSION  
alternativ = eticheta text  
alinie = inherits: \seteazaalinie  
continua = da nu  
inainte = BEFEHL  
dupa = BEFEHL  
intre = BEFEHL  
stil = STYLE BEFEHL  
culoare = COLOR

\setupcounter [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

```
1 NAME OPT
2 start = NUMBER
  counter = NAME
  metoda = pagina
  stare = start stop
  mod = bypagina byblock bytext byantet byABSCHNITT
  prefix = da nu
  prefixseparatorset = NAME
  prefixconversion = NAME
  prefixconversionset = NAME
  prefixstarter = BEFEHL PROCESSOR->BEFEHL
  prefixstopper = BEFEHL PROCESSOR->BEFEHL
  prefixset = NAME
  prefixsegments = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:tot ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:* ABSCHNITT:tot
    curent
  numberorder = reverse
  numberseparatorset = NAME
  numberconversion = NAME
  numberconversionset = NAME
  numberstarter = BEFEHL PROCESSOR->BEFEHL
  numberstopper = BEFEHL PROCESSOR->BEFEHL
  numbersegments = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:tot
  type = primul precedent urmatorul ultim numar
  criteriu = strict pozitiv tot
  prefixconnector = BEFEHL PROCESSOR->BEFEHL
```

\setupdataset [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

```
1 NAME OPT
2 intarziere = da nu
```

\setupdelimitedtext [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

```
1 NAME NAME:NUMBER OPT
2 inainte = BEFEHL
  dupa = BEFEHL
  language = local global SPRACHE
  metoda = font
  repeta = da nu
  locatie = text paragraf margine
  stanga = BEFEHL
  mijloc = BEFEHL
  dreapta = BEFEHL
  nextleft = BEFEHL
  nextright = BEFEHL
  spatiuinainte = inherits: \blanc
  spatiudupa = inherits: \blanc
  marginestanga = da nu standard DIMENSION
  marginedreapta = da nu standard DIMENSION
  aliniat = inherits: \seteazaaliniat
  aliniaturmator = da nu auto
  stil = STYLE BEFEHL
  culoare = COLOR
  stilsimbol = STYLE BEFEHL
  culoaresimbol = COLOR
```

**\setupdescription** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
 2 titlu = da nu  
 nivel = NUMBER  
 text = TEXT  
 headcommand = \...##1  
 inainte = BEFEHL  
 dupa = BEFEHL  
 intre = BEFEHL  
 alternativ = stanga dreapta inmargine instanga indreapta margine marginestanga marginedreapta innermargin  
 outermargin serried suspendat sus gol comanda NAME  
 aliniere = inherits: \seteazaalinierea  
 headalign = inherits: \seteazaalinierea  
 aliniat = inherits: \seteazaaliniat  
 display = da nu  
 aliniaturmator = da nu auto  
 latime = ajustat broad linie DIMENSION  
 distanta = niciunul DIMENSION  
 dilatat = NUMBER  
 shrink = NUMBER  
 suspenda = ajustat broad niciunul margine NUMBER  
 closesymbol = BEFEHL  
 closecommand = \...##1  
 expansiune = da nu xml  
 referenceprefix = + - TEXT  
 exemplu = TEXT  
 margine = da nu standard DIMENSION  
 stil = STYLE BEFEHL  
 culoare = COLOR  
 stiltitlu = STYLE BEFEHL  
 culoaretitlu = COLOR  
 alinieretitlu = da nu

**\setupdirections** [...<sup>\*</sup>,...]

\* bidi = on dezactivat local global  
 metoda = unu doi implicit  
 fences = da nu  
 break = ambele inainte

**\setupdocument** [...<sup>\*</sup>,...]

\* inainte = BEFEHL  
 dupa = BEFEHL  
 metadata:author = TEXT  
 metadata:title = TEXT  
 metadata:subject = TEXT  
 metadata:keywords = TEXT  
 KEY = VALUE

**\setupeffect** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
 2 metoda = niciunul comanda  
 dilatat = NUMBER  
 grosimerigla = DIMENSION  
 alternativ = normal intern extern ambele ascuns dilatat

\setupenumeration [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

```

1  NAME                                OPT
2  titlu                               = da nu
   numar                               = da nu
   comandanumar                        = \...##1
   distantatitlu                       = DIMENSION
   stiltitlu                           = STYLE BEFEHL
   culoaretitlu                        = COLOR
   titlecommand                        = \...##1
   titleleft                           = BEFEHL
   titleright                          = BEFEHL
   stanga                              = BEFEHL
   dreapta                             = BEFEHL
   simbol                              = BEFEHL
   starter                             = BEFEHL
   stopper                             = BEFEHL
   cuplare                             = NAME
   counter                             = NAME
   nivel                               = NUMMER
   text                                = TEXT
   headcommand                         = \...##1
   inainte                             = BEFEHL
   dupa                                = BEFEHL
   intre                               = BEFEHL
   alternativ                           = stanga dreapta inmargin instanga indreapta margine marginestanga marginedreapta innermargin
                                     outermargin serried suspendat sus gol comanda NAME
   aliniere                            = inherits: \seteazaalinierea
   headalign                           = inherits: \seteazaalinierea
   aliniat                             = inherits: \seteazaaliniat
   display                             = da nu
   aliniaturmator                      = da nu auto
   latime                              = ajustat broad linie DIMENSION
   distanta                            = niciunul DIMENSION
   dilatat                             = NUMMER
   shrink                              = NUMMER
   suspenda                            = ajustat broad niciunul margine NUMMER
   closesymbol                         = BEFEHL
   closecommand                        = \...##1
   expansiune                          = da nu xml
   referenceprefix                     = + - TEXT
   exemplu                             = TEXT
   margine                             = da nu standard DIMENSION
   stil                                = STYLE BEFEHL
   culoare                              = COLOR
   stiltitlu                           = STYLE BEFEHL
   culoaretitlu                        = COLOR
   alinieretitlu                       = da nu
   inherits: \setupcounter

```

\setupenv [...,\*...,...]

```

*  set      = BEFEHL
   reset    = BEFEHL
   KEY      = VALUE

```

\setupexport [...,\*...,...]

```

*  aliniere      = flushleft centru flushright normal
   fonttext      = DIMENSION
   latime        = DIMENSION
   titlu         = TEXT
   subtitlu      = TEXT
   autor         = TEXT
   alternativ     = html div
   properties    = da nu
   hyphen        = da nu
   cssfile       = FILE
   primapagina   = FILE
   ultimapagina  = FILE

```

`\setupexternalfigure [...,1...] [...,2...,...]`

```

1  NAME                                OPT
2  latime                             = DIMENSION
   inaltime                           = DIMENSION
   eticheta                            = NAME
   pagina                             = NUMMER
   obiect                              = da nu
   prefix                             = TEXT
   metoda                             = pdf mps jpg png jp2 jbig svg eps gif tif mov buffer tex cld auto
   controale                           = da nu
   previzualizare                     = da nu
   mask                               = niciunul
   rezolutie                           = NUMMER
   culoare                             = COLOR
   arguments                           = TEXT
   repeta                              = da nu
   factor                             = ajustat broad max auto implicit
   hfactor                             = ajustat broad max auto implicit
   factorw                             = ajustat broad max auto implicit
   latimemaxima                       = DIMENSION
   inaltimemaxima                     = DIMENSION
   equalwidth                         = DIMENSION
   equalheight                        = DIMENSION
   scala                              = NUMMER
   xscala                             = NUMMER
   yscala                             = NUMMER
   s                                  = NUMMER
   sx                                 = NUMMER
   sy                                 = NUMMER
   linii                              = NUMMER
   locatie                             = local global implicit
   director                           = PATH
   optiune                             = test incadrat gol
   foregroundcolor                    = COLOR
   reset                              = da nu
   fundal                             = culoare primplan NAME
   frame                              = on dezactivat
   culoarefundal                      = COLOR
   xmax                               = NUMMER
   ymax                               = NUMMER
   frames                             = on dezactivat
   interactiune                       = da tot niciunul referinta layer semncarte
   fonttext                           = DIMENSION
   comment                             = BEFEHL TEXT
   dimensiune                         = niciunul media crop trim art
   cache                              = PATH
   resources                          = PATH
   display                            = FILE
   conversie                           = TEXT
   order                              = LISTE
   crossreference                     = da nu NUMMER
   transform                          = auto NUMMER
   userpassword                       = TEXT
   ownerpassword                      = TEXT

```

`\setupexternalsoundtracks [...,*...,...]`

`* optiune = repetat`

`\setupfacingfloat [...,1...] [...,2...,...]`

```

1  NAME                                OPT
2  intre                             = BEFEHL
   pagina                             = inherits: \pagina
   spaceinbetween                     = inherits: \blanc
   stil                               = STYLE BEFEHL
   culoare                             = COLOR
   inherits: \seteazainconjurat

```

`\setupfieldbody [...,1...] [...,2...,...]`

```

1  NAME                                OPT
2  category = NAME
   inherits: \setupfieldcategory

```

**\setupfieldcategory** [...<sup>1</sup>,...] [...<sup>2</sup>...]

```

1  NAME                      OPT
2  start                     =  NUMMER
   stil                      =  STYLE BEFEHL
   culoare                   =  COLOR
   type                      =  radio sub text linie push check signature
   values                    =  TEXT
   implicit                  =  TEXT
   culoareframecamp          =  COLOR
   culoarefundalcamp         =  COLOR
   latime                    =  DIMENSION
   inaltime                  =  DIMENSION
   inaltime                  =  DIMENSION
   aliniere                  =  stanga centru dreapta flushleft center flushright
   n                         =  NUMMER
   simbol                    =  NAME
   fieldlayer                =  NAME
   optiune                   =  readonly obligatoriu protejat sortat nedisponibil nocheck fixat fisier ascuns tiparibil auto
   clickintru                =  REFERENCE
   clickies                  =  REFERENCE
   regiuneintrare            =  REFERENCE
   regiuneiesire             =  REFERENCE
   dupatasta                 =  REFERENCE
   format                    =  REFERENCE
   verifica                  =  REFERENCE
   calculeaza                =  REFERENCE
   focusin                   =  REFERENCE
   focusout                  =  REFERENCE
   openpage                  =  REFERENCE
   closepage                 =  REFERENCE

```

**\setupfieldcontentframed** [...<sup>1</sup>,...] [...<sup>2</sup>...]

```

1  NAME                      OPT
2  inherits: \seteazainconjuratinherits: \setupfieldcategory

```

**\setupfieldlabelframed** [...<sup>1</sup>,...] [...<sup>2</sup>...]

```

1  NAME                      OPT
2  inherits: \seteazainconjurat

```

**\setupfieldtotalframed** [...<sup>1</sup>,...] [...<sup>2</sup>...]

```

1  NAME                      OPT
2  inainte                   =  BEFEHL
   dupa                      =  BEFEHL
   intre                     =  BEFEHL
   distanta                  =  DIMENSION
   alternativ                  =  reset eticheta incadrat orizontal vertical
   inherits: \seteazainconjurat

```

**\setupfiller** [...<sup>1</sup>,...] [...<sup>2</sup>...]

```

1  NAME                      OPT
2  marginestanga             =  DIMENSION
   marginedreapta           =  DIMENSION
   stanga                    =  BEFEHL
   dreapta                   =  BEFEHL
   alternativ                  =  simbol dilatat rigla spatiu
   metoda                    =  local global centru broad
   latime                    =  DIMENSION
   inaltime                  =  DIMENSION
   inaltime                  =  DIMENSION
   offset                    =  DIMENSION
   distanta                  =  DIMENSION
   aliniere                  =  stanga dreapta centru flushleft flushright intern extern
   simbol                    =  BEFEHL
   stil                      =  STYLE BEFEHL
   culoare                   =  COLOR

```

**\setupfirstline** [...<sup>1</sup>,...] [...<sup>2</sup>...]

```

1  NAME                      OPT
2  n                         =  NUMMER
   alternativ                  =  implicit linie cuvant
   stil                      =  STYLE BEFEHL
   culoare                   =  COLOR

```

\setupfittingpage [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
2 pagestate = start stop  
comanda = \...##1  
margine = pagina  
scala = NUMMER  
hartie = auto implicit NAME  
inherits: \setezainconjurat

\setupfloatframed [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
2 inherits: \setezainconjurat

\setupfontexpansion [...<sup>1</sup>] [...<sup>2</sup>,...]

1 NAME  
2 vector = NAME  
factor = NUMMER  
dilatat = NUMMER  
shrink = NUMMER  
pas = NUMMER

\setupfontprotrusion [...<sup>1</sup>] [...<sup>2</sup>,...]

1 NAME  
2 vector = NAME  
factor = NUMMER  
stanga = NUMMER  
dreapta = NUMMER

\setupfonts [...<sup>\*</sup>,...]

\* language = nu auto

\setupfontsolution [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
2 goodies = FILE  
solution = NAME  
less = NAME  
more = NAME  
metoda = preroll split normal reverse aleator  
criteriu = NUMMER

\setupformula [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
2 locatie = stanga dreapta  
alinie = stanga centru dreapta flushleft center flushright normal  
split = da nu pagina  
strut = da nu  
distanta = DIMENSION  
stanga = BEFEHL  
dreapta = BEFEHL  
spatiuinainte = inherits: \blanc  
spatiudupa = inherits: \blanc  
comandanumar = \...##1  
culoare = COLOR  
stilnumar = STYLE BEFEHL  
culoarenumar = COLOR  
optiune = impachetat tight centru incadrat adancime linie jumatatelinie -linie -jumatatelinie inherits: \setezafonttext  
margine = da nu standard DIMENSION  
marginestanga = DIMENSION  
marginedreapta = DIMENSION  
alternativ = NAME  
aliniaturmator = da nu auto  
grid = inherits: \snaptogrid  
frame = numar  
suspenda = niciunul auto  
expansiune = da nu xml  
referenceprefix = + - TEXT  
xmlsetup = NAME  
catcodes = NAME  
inherits: \setupcounter

**\setupformulaframed** [<sup>1</sup>...,...] [<sup>2</sup>...,...]

- 1 NAME OPT
- 2 inherits: \seteazainconjurat

**\setupframedcontent** [<sup>1</sup>...,...] [<sup>2</sup>...,...]

- 1 NAME OPT
- 2 stanga = BEFEHL
- dreapta = BEFEHL
- leftoffser = DIMENSION
- offsetdreapta = DIMENSION
- offsetsus = DIMENSION
- offsetjos = DIMENSION
- corectielinie = da nu
- inherits: \seteazainconjurat

**\setupframedtable** [<sup>1</sup>...] [<sup>2</sup>...,...]

- 1 NAME OPT
- 2 inainte = BEFEHL
- dupa = BEFEHL
- intre = BEFEHL
- distanta = DIMENSION
- inherits: \seteazainconjurat

**\setupframedtablecolumn** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...]

- 1 NAME OPT
- 2 NUMMER fiecare
- 3 inherits: \seteazainconjurat

**\setupframedtablerow** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...]

- 1 NAME OPT
- 2 NUMMER fiecare
- 3 inherits: \seteazainconjurat

**\setupframedtext** [<sup>1</sup>...,...] [<sup>2</sup>...,...]

- 1 NAME OPT
- 2 stanga = BEFEHL
- dreapta = BEFEHL
- intern = BEFEHL
- locatie = stanga dreapta centru niciunul
- corectieadancime = on dezactivat
- fonttext = inherits: \seteazafonttext
- aliniat = inherits: \seteazaaliniat
- stil = STYLE BEFEHL
- culoare = COLOR
- inherits: \seteazainconjuratinherits: \setupplacement

**\setupglobalreferenceprefix** [...]

- \* + - TEXT

**\setupheadalternative** [<sup>1</sup>...,...] [<sup>2</sup>...,...]

- 1 NAME OPT
- 2 alternativ = orizontal vertical undeva
- renderingsetup = NAME

**\setuphelp** [<sup>1</sup>...,...] [<sup>2</sup>...,...]

- 1 NAME OPT
- 2 inherits: \seteazainconjurat

**\setuphigh** [<sup>1</sup>...,...] [<sup>2</sup>...,...]

- 1 NAME OPT
- 2 distanta = DIMENSION
- up = DIMENSION
- stil = STYLE BEFEHL
- culoare = COLOR



`\setuphighlight [...1,...] [...2,...]`

1 NAME OPT  
2 comanda = da nu  
stil = STYLE BEFEHL  
culoare = COLOR

`\setuphyphenation [...*,...]`

\* metoda = original tex implicit hyphenate expanded traditional niciunul

`\setupindentedtext [...1,...] [...2,...]`

1 NAME OPT  
2 inainte = BEFEHL  
dupa = BEFEHL  
distanta = DIMENSION  
exemplu = TEXT  
text = TEXT  
latime = ajustat broad DIMENSION  
separator = BEFEHL  
stil = STYLE BEFEHL  
culoare = COLOR  
stiltitlu = STYLE BEFEHL  
culoaretitlu = COLOR

`\setupinitial [...1,...] [...2,...]`

1 NAME OPT  
2 n = NUMMER  
m = NUMMER  
inainte = BEFEHL  
distanta = DIMENSION  
hoffset = DIMENSION  
voffset = linie DIMENSION  
stil = STYLE BEFEHL  
culoare = COLOR  
font = FONT  
text = TEXT  
locatie = margine text  
metoda = primul ultim auto niciunul

`\setupinsertion [...1,...] [...2,...]`

1 NAME OPT  
2 locatie = pagina text coloane firstcolumn lastcolumn

`\setupitaliccorrection [...*,...]`

\* text totdeauna global niciunul

```

\setupitemgroup [...]1 [...]2 [...]3 [...]4
1 NAME OPT OPT OPT
2 fiecare NUMMER
3 intro aleator continuu impachetat autointro broad text inainte dupa faraalb margine inmargine lamargine intext
larg ajustat nofit paragraf unit serried stopper nostopper despachetat repetat norepeat reverse coloane unu doi
trei patru cinci six seven eight nine standard NUMMER*broad NUMMER*serried orizontal NAME
4 inainte = BEFEHL
dupa = BEFEHL
intre = BEFEHL
inaintetitlu = BEFEHL
dupatitlu = BEFEHL
textstanga = BEFEHL
textdreapta = BEFEHL
stanga = BEFEHL
dreapta = BEFEHL
factor = NUMMER
pas = DIMENSION
latime = DIMENSION
distanta = DIMENSION
margine = da nu standard DIMENSION
marginestanga = da nu standard DIMENSION
marginedreapta = da nu standard DIMENSION
distantamarginestanga = da nu standard DIMENSION
distantamarginedreapta = da nu standard DIMENSION
aliniere = inherits: \seteazaalinierea
aliniat = inherits: \seteazaaliniat
start = NUMMER
symaliniere = stanga centru dreapta flushleft center flushright
simbol = NAME
n = NUMMER
aliniaturmator = da nu auto
intern = BEFEHL
comanda = CSNAME
elemente = NUMMER
latimemaxima = DIMENSION
itemalign = stanga dreapta centru flushleft flushright intern extern
alignsymbol = da nu
textdistance = mic mediu mare niciunul spatiu DIMENSION
punestopper = da nu
stil = STYLE BEFEHL
culoare = COLOR
stiltitlu = STYLE BEFEHL
culoaretitlu = COLOR
stilmarcaj = STYLE BEFEHL
culoaremarcaj = COLOR
stilsimbol = STYLE BEFEHL
culoaresimbol = COLOR
grid = inherits: \definegridsnapping
inherits: \setupcounter

```

**\setupitemgroup** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```

1  NAME NAME:NUMBER      OPT
2  inainte                = BEFEHL
   dupa                   = BEFEHL
   intre                  = BEFEHL
   inaintetitlu           = BEFEHL
   dupatitlu              = BEFEHL
   textstanga             = BEFEHL
   textdreapta            = BEFEHL
   stanga                 = BEFEHL
   dreapta                = BEFEHL
   factor                 = NUMBER
   pas                    = DIMENSION
   latime                 = DIMENSION
   distanta               = DIMENSION
   optiune                = intro aleator continuu impachetat autointro broad text inainte dupa faraalb margine inmargine
                           lamargine intext larg ajustat nofit paragraf unit serried stopper despachetat repetat norepeat
                           reverse coloane unu doi trei patru cinci six seven eight nine standard NUMBER*broad NUMBER*serried
                           orizontal NAME
   margine                = da nu standard DIMENSION
   marginestanga          = da nu standard DIMENSION
   marginedreapta         = da nu standard DIMENSION
   aliniere               = inherits: \seteazaalinierea
   aliniat                = inherits: \seteazaaliniat
   start                  = NUMBER
   symaliniere            = stanga centru dreapta flushleft center flushright
   simbol                 = NAME
   n                      = NUMBER
   aliniaturmator         = da nu auto
   intern                 = BEFEHL
   comanda                = CSNAME
   elemente               = NUMBER
   latimemaxima           = DIMENSION
   itemalign              = stanga dreapta centru flushleft flushright intern extern
   alignsymbol            = da nu
   textdistance           = mic mediu mare niciunul spatiu DIMENSION
   punestopper            = da nu
   stil                   = STYLE BEFEHL
   culoare                = COLOR
   stiltitlu              = STYLE BEFEHL
   culoaretitlu           = COLOR
   stilmarcaj             = STYLE BEFEHL
   culoaremarcaj          = COLOR
   stilsimbol             = STYLE BEFEHL
   culoaresimbol          = COLOR
   grid                   = inherits: \definegridsnapping
inherits: \setupcounter

```

**\setareITEMGROUP** [...<sup>1</sup>,...] [...<sup>2</sup>,...] [...<sup>3</sup>,...]

```

1  fiecare NUMBER      OPT      OPT      OPT
2  inherits: \setupitemgroup
3  inherits: \setupitemgroup
instances: itemize

```

**\setareitemize** [...<sup>1</sup>,...] [...<sup>2</sup>,...] [...<sup>3</sup>,...]

```

1  fiecare NUMBER      OPT      OPT      OPT
2  inherits: \setupitemgroup
3  inherits: \setupitemgroup

```

**\setuplabel** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```

1  NAME          OPT
2  titlu          = da nu
   numar          = da nu
   comandanumar   = \...##1
   distantatitlu  = DIMENSION
   stiltitlu       = STYLE BEFEHL
   culoaretitlu   = COLOR
   titlecommand   = \...##1
   titleleft      = BEFEHL
   titleright     = BEFEHL
   stanga         = BEFEHL
   dreapta        = BEFEHL
   simbol         = BEFEHL
   starter        = BEFEHL
   stopper        = BEFEHL
   cuplare        = NAME
   counter        = NAME
   nivel          = NUMMER
   text           = TEXT
   headcommand    = \...##1
   inainte        = BEFEHL
   dupa           = BEFEHL
   intre          = BEFEHL
   alternativ      = stanga dreapta inmargin instanga indreapta margine marginestanga marginedreapta innermargin
                   outermargin serried suspendat sus gol comanda intext NAME
   aliniere       = inherits: \seteazaalinierea
   headalign      = inherits: \seteazaalinierea
   aliniat        = inherits: \seteazaaliniat
   display        = da nu
   aliniaturmator = da nu auto
   latime         = ajustat broad linie DIMENSION
   distanta       = niciunul DIMENSION
   dilatat        = NUMMER
   shrink         = NUMMER
   suspenda       = ajustat broad niciunul margine NUMMER
   closesymbol    = BEFEHL
   closecommand   = \...##1
   expansiune     = da nu xml
   referenceprefix = + - TEXT
   exemplu        = TEXT
   margine        = da nu standard DIMENSION
   stil           = STYLE BEFEHL
   culoare        = COLOR
   stiltitlu      = STYLE BEFEHL
   culoaretitlu   = COLOR
   alinieretitlu  = da nu
   inherits: \setupcounter

```

**\setuplayer** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```

1  NAME          OPT
2  stare         = start stop continuu urmatorul repetat
   optiune       = test
   pagina        = NUMMER
   latime        = DIMENSION
   inaltime      = DIMENSION
   region        = NAME
   rotatie       = stanga dreapta intern extern NUMMER
   pozitie       = da nu overlay
   hoffset       = max DIMENSION
   voffset       = max DIMENSION
   offset        = DIMENSION
   dx            = DIMENSION
   dy            = DIMENSION
   sx            = NUMMER
   sy            = NUMMER
   x             = DIMENSION
   y             = DIMENSION
   colt          = stanga centru dreapta sus subsol
   locatie       = grila stanga centru dreapta sus subsol linie l c r m t b g
   linie         = NUMMER
   coloana       = NUMMER
   directie      = normal reverse
   douafete      = da nu
   metoda        = ajustat overlay
   repeta        = da
   preset        = lefttop righttop leftbottom rightbottom centru middletop middlebottom middleleft middleright lefttoleft
                   lefttopright NAME

```

`\setuplayeredtext [...1,...] [...2,...]`

```
1 NAME OPT
2 stil = STYLE BEFEHL
  culoare = COLOR
  inherits: \seteazainconjurat
```

`\setuplayouttext [...1] [...2] [...3,...]`

```
1 sus antet text subsol subsolOPT
2 text margine bordura
3 stare = start stop gol inalt niciunul normal faramarcare NAME
  stil = STYLE BEFEHL
  culoare = COLOR
  strut = da nu
  n = NUMMER
  inainte = BEFEHL
  dupa = BEFEHL
  stilstanga = STYLE BEFEHL
  stildreapta = STYLE BEFEHL
  culoarestanga = COLOR
  culoaredreapta = COLOR
  latime = DIMENSION
  latimestanga = DIMENSION
  marginedreapta = DIMENSION
```

`\setuplinefiller [...1,...] [...2,...]`

```
1 NAME OPT
2 locatie = stanga dreapta ambele
  scop = stanga dreapta local
  mp = NAME
  inaltime = DIMENSION
  inaltime = DIMENSION
  distanta = DIMENSION
  threshold = DIMENSION
  grosimerigla = DIMENSION
  inainte = BEFEHL
  dupa = BEFEHL
  culoare = COLOR
  stiltext = STYLE BEFEHL
  culoaretext = COLOR
  aliniere = inherits: \seteazaalinierea
```

`\setuplinefillers [...1,...] [...2,...]`

```
1 NAME OPT
2 inherits: \setuplinefiller
```

`\setuplinenote [...1,...] [...2,...]`

```
1 NAME OPT
2 compress = da nu
  compressmethod = separator stopper spatiu
  compressseparator = BEFEHL
  compressdistance = DIMENSION
  inherits: \setupnote
```

**\setuplinetable** [...<sup>1</sup>] [...<sup>2</sup>] [...,...<sup>3</sup>...,...]

```

1  r c          OPT      OPT
2  impar par antet NUMBER
3  linii        = ajustat NUMBER
   inainte      = BEFEHL
   dupa         = BEFEHL
   intre       = BEFEHL
   dilatata    = da nu DIMENSION
   latimemaxima = ajustat DIMENSION
   nstanga     = NUMBER
   n           = NUMBER
   repeta      = da nu
   nx          = NUMBER
   latime      = DIMENSION
   inaltime    = ajustat linie DIMENSION
   distanta    = DIMENSION
   offsetstanga = DIMENSION
   offsetdreapta = DIMENSION
   aliniere    = inherits: \seteazaalinierea
   fundal      = culoare
   culoarefundal = COLOR
   xheight     = max DIMENSION
   xdepth      = max DIMENSION
   stil        = STYLE BEFEHL
   culoare     = COLOR

```

**\setuplistalternative** [...<sup>1</sup>,...] [...,...<sup>2</sup>...,...]

```

1  NAME          OPT
2  inainte      = BEFEHL
   dupa         = BEFEHL
   comanda      = \...##1##2##3
   renderingsetup = NAME
   latime       = DIMENSION
   distanta     = DIMENSION
   dilatata    = DIMENSION
   filler       = BEFEHL

```

**\setuplistextra** [...<sup>1</sup>,...] [...,...<sup>2</sup>...,...]

```

1  NAME          OPT
2  inainte = BEFEHL
   dupa    = BEFEHL

```

**\setuplocalfloats** [...,...<sup>\*</sup>...,...]

```

*  inainte = BEFEHL
   dupa    = BEFEHL
   intre   = BEFEHL

```

**\setuplocalinterlinespace** [...<sup>1</sup>,...] [...,...<sup>2</sup>...,...]

```

1  NAME          OPT
2  inherits: \seteazaspatiuinterliniar

```

**\setuplocalinterlinespace** [...,<sup>\*</sup>...]

```

*  on dezactivat reset auto mic mediu mare OPT NUMBER DIMENSION

```

**\setuplocalinterlinespace** [...<sup>\*</sup>]

```

*  NAME

```

**\setuplow** [...<sup>1</sup>,...] [...,...<sup>2</sup>...,...]

```

1  NAME          OPT
2  distanta = DIMENSION
   down     = DIMENSION
   stil     = STYLE BEFEHL
   culoare  = COLOR

```

`\setuplowhigh [...1,...] [...2,...]`

1 NAME OPT  
2 distanta = DIMENSION  
up = DIMENSION  
down = DIMENSION  
stil = STYLE BEFEHL  
culoare = COLOR

`\setuplowmidhigh [...1,...] [...2,...]`

1 NAME OPT  
2 up = DIMENSION  
down = DIMENSION  
stil = STYLE BEFEHL  
culoare = COLOR

`\setupMPgraphics [...*,...]`

\* culoare = local global  
mpy = FILE

`\setupMPinstance [...1,...] [...2,...]`

1 NAME OPT  
2 format = metafun mpost  
initializations = da nu  
setups = NAME  
stiltext = STYLE BEFEHL  
culoaretext = COLOR  
extensions = da nu  
metoda = binary decimal double scaled implicit

`\setupMPpage [...*,...]`

\* inherits: \setupfittingpage

`\setupMPvariables [...1] [...2,...]`

1 NAME OPT  
2 KEY = VALUE

`\setupmarginblock [...1,...] [...2,...]`

1 NAME OPT  
2 stare = start stop  
latime = DIMENSION  
inainte = BEFEHL  
dupa = BEFEHL  
intre = BEFEHL  
aliniera = inherits: \seteazaaliniera  
stil = STYLE BEFEHL  
culoare = COLOR  
sus = BEFEHL  
jos = BEFEHL  
locatie = stanga dreapta centru inmarginie  
stanga = BEFEHL  
dreapta = BEFEHL

```

\setupmargindata [...1,...] [...2,...]
1  NAME                      OPT
2  strut                    = da nu auto cap ajustat linie implicit CHARACTER
    comanda                = \...#1
    latime                 = DIMENSION
    aliniere               = inherits: \seteazaalinierea
    anchor                 = region text
    locatie                = stanga dreapta intern extern
    metoda                 = sus linie primul adancime inaltime
    category               = implicit bordura
    scop                   = local global
    optiune                = text paragraf
    margine                = local normal margine bordura
    distanta               = DIMENSION
    hoffset                = DIMENSION
    voffset                = DIMENSION
    dy                     = DIMENSION
    spatiu jos             = DIMENSION
    threshold              = DIMENSION
    linie                  = NUMMER
    stack                  = da continuu
    stil                   = STYLE BEFEHL
    culoare                = COLOR

```

```

\setupmarginframed [...1,...] [...2,...]
1  NAME                      OPT
2  inherits: \seteazainconjurat

```

```

\setupmarginrule [...1,...] [...2,...]
1  NUMMER                    OPT
2  inherits: \setupsidebar

```

```

\setupmathalignment [...1,...] [...2,...]
1  NAME                      OPT
2  n                        = NUMMER
    m                      = NUMMER
    distanta               = DIMENSION
    numar                 = auto
    separator              = TEXT
    aliniere               = stanga centru dreapta normal
    locatie                = sus center subsol normal
    grid                   = math nu

```

```

\setupmathcases [...1,...] [...2,...]
1  NAME                      OPT
2  stanga                  = BEFEHL
    dreapta                = BEFEHL
    strut                  = da nu
    stil                   = STYLE BEFEHL
    distanta               = DIMENSION
    numberdistance         = DIMENSION

```



`\setupmathematics [...1,...] [...2,...]`

```

1 NAME OPT
2 openup = da nu
  setsymbol = NAME
  functionstyle = STYLE BEFEHL
  compact = da nu
  aliniere = l2r r2l righttoleft
  bidi = da nu
  sygreek = normal italic niciunul
  lcgreek = normal italic niciunul
  ucgreek = normal italic niciunul
  italics = 1 2 3 4 niciunul reset
  autopunctuation = da nu tot comma yes,semicolon comma,semicolon all,semicolon
  setups = NAME
  domain = NAME reset
  stiltext = STYLE BEFEHL
  culoaretext = COLOR
  functioncolor = COLOR
  integral = limits nolimits autolimits displaylimits niciunul
  stylealternative = NAME
  implicit = normal italic
  fraction = ams ctx
  ampersand = normal
  collapsing = 1 2 3 niciunul reset
  kernpairs = da nu

```

`\setupmathfence [...1,...] [...2,...]`

```

1 NAME OPT
2 comanda = da nu
  stanga = NUMMER
  mijloc = NUMMER
  dreapta = NUMMER
  mathstyle = display text script scriptscript cramped uncramped normal impachetat mic mare
  culoare = COLOR
  stare = auto
  metoda = auto
  dimensiune = NUMMER
  factor = niciunul auto NUMMER
  mathclass = NUMMER

```

`\setupmathfraction [...1,...] [...2,...]`

```

1 NAME OPT
2 distantasus = DIMENSION
  distantajos = DIMENSION
  margine = DIMENSION
  culoare = COLOR
  strut = da nu math tight
  alternativ = intern extern ambele
  rigla = da nu auto
  stanga = NUMMER
  dreapta = NUMMER
  grosimerigla = DIMENSION
  mathstyle = STYLE BEFEHL
  distanta = nu niciunul overlay
  inlinethreshold = auto NUMMER
  displaythreshold = auto NUMMER
  fences = NAME

```

`\setupmathfractions [...1,...] [...2,...]`

```

1 NAME OPT
2 inherits: \setupmathfraction

```

`\setupmathframed [...1,...] [...2,...]`

```

1 NAME OPT
2 inherits: \seteazainconjurat

```

```

\setupmathmatrix [...1,...] [...2,...]
1  NAME                      OPT
2  stanga                    = BEFEHL
   dreapta                  = BEFEHL
   strut                     = da nu NUMMER
   aliniere                  = stanga centru dreapta normal
   stil                      = STYLE BEFEHL
   distanta                  = DIMENSION
   simplecommand             = TEXT
   locatie                   = sus subsol inalt jos lohi normal

```

```

\setupmathornament [...1,...] [...2,...]
1  NAME                      OPT
2  alternativ                  = mp
   culoare                   = COLOR
   mpoffset                   = DIMENSION
   mp                         = NAME

```

```

\setupmathradical [...1,...] [...2,...]
1  NAME                      OPT
2  alternativ                  = implicit normal mp
   culoare                   = COLOR
   mpoffset                   = DIMENSION
   mp                         = NAME

```

```

\setupmathstackers [...1,...] [...2,...]
1  NAME                      OPT
2  stanga                    = BEFEHL
   dreapta                  = BEFEHL
   topcommand                = \...##1
   bottomcommand             = \...##1
   middlecommand             = \...##1
   mp                        = NAME
   mpheight                  = DIMENSION
   mpdepth                   = DIMENSION
   mpoffset                   = DIMENSION
   culoare                   = COLOR
   hoffset                   = DIMENSION
   voffset                   = DIMENSION
   inaltiminima              = DIMENSION
   mindepth                  = DIMENSION
   mathclass                  = rel ord
   offset                    = min max normal
   locatie                   = sus subsol inalt jos centru NUMMER
   strut                     = da nu
   alternativ                  = normal implicit mp
   latiminima                = DIMENSION
   distanta                  = DIMENSION
   moffset                   = DIMENSION
   order                      = normal reverse
   mathlimits                 = da nu

```

```

\setupmathstyle [...*,...]
*  display text script scriptscript cramped uncramped normal impachetat mic mare NAME

```

```
\setupmixedcolumns [...1,...] [...2,...]
```

```
1 NAME OPT
2 grid = inherits: \definegridsnapping
  grosimerigla = DIMENSION
  metoda = otr box
  inainte = BEFEHL
  dupa = BEFEHL
  distanta = DIMENSION
  n = NUMMER
  inaltimemaxima = DIMENSION
  latimemaxima = DIMENSION
  pas = DIMENSION
  profile = NAME
  aliniere = inherits: \seteazaalinierea
  setups = NAME
  balanta = da nu
  splitmethod = niciunul fixat
  alternativ = local global
  internalgrid = linie jumatatelinie
  separator = rigla
  strut = da nu
  culoare = COLOR
  culoarerigla = COLOR
  directie = normal reverse
  inherits: \seteazainconjurat
```

```
\setupmodule [...1] [...2,...]
```

```
1 FILE OPT
2 test = da nu
  KEY = VALUE
```

`\setupnotation [...1,...] [...2,...]`

```

1  NAME                      OPT
2  titlu                     = da nu
   numar                     = da nu
   type                       = note
   comandanumar              = \...##1
   distantatitlu             = DIMENSION
   stiltitlu                  = STYLE BEFEHL
   culoaretitlu               = COLOR
   titlecommand               = \...##1
   titleleft                  = BEFEHL
   titleright                  = BEFEHL
   stanga                     = BEFEHL
   dreapta                    = BEFEHL
   simbol                     = BEFEHL
   starter                    = BEFEHL
   stopper                     = BEFEHL
   cuplare                     = NAME
   counter                     = NAME
   nivel                      = NUMMER
   text                       = TEXT
   headcommand                = \...##1
   inainte                     = BEFEHL
   dupa                       = BEFEHL
   intre                      = BEFEHL
   alternativ                  = stanga dreapta inmargine instanga indreapta margine marginestanga marginedreapta innermargin
                                outermargin serried suspendat sus comanda note NAME
   aliniere                    = inherits: \seteazaalinierea
   headalign                   = inherits: \seteazaalinierea
   aliniat                     = inherits: \seteazaaliniat
   display                     = da nu
   aliniaturmator              = da nu auto
   latime                      = ajustat broad linie DIMENSION
   distanta                    = niciunul DIMENSION
   dilatat                     = NUMMER
   shrink                      = NUMMER
   suspenda                    = ajustat broad niciunul margine NUMMER
   closesymbol                 = BEFEHL
   closecommand                = \...##1
   expansiune                  = da nu xml
   referenceprefix             = + - TEXT
   exemplu                     = TEXT
   margine                     = da nu standard DIMENSION
   stil                        = STYLE BEFEHL
   culoare                     = COLOR
   stiltitlu                    = STYLE BEFEHL
   culoaretitlu                = COLOR
   alinieretitlu               = da nu
   inherits: \setupcounter

```

`\setupnotations [...1,...] [...2,...]`

```

1  NAME                      OPT
2  inherits: \setupnotation

```

**\setupnote** [ $\dots$ , $\dots$ ]<sup>1</sup> [ $\dots$ , $\dots$ ]<sup>2</sup> $\dots$ , $\dots$ ]

```

1  NAME          OPT
2  interactiune   = da nu numar text tot
   symbolcommand  = \...##1
   comandatext    = \...##1
   indicator      = da nu
   separator      = BEFEHL
   latime         = DIMENSION
   inaltime       = DIMENSION
   distanta       = DIMENSION
   rulecommand    = BEFEHL
   rigla          = on dezactivat normal stanga dreapta comanda paragraf
   split          = tolerant strict foartestric NUMBER
   factor         = NUMBER
   locatie        = text pagina inalt subsol niciunul coloane firstcolumn lastcolumn
   urmatorul      = BEFEHL
   n              = NUMBER
   culoarerigla   = COLOR
   grosimerigla   = DIMENSION
   setups         = NAME
   spatiereinterliniara = NAME
   paragraf       = da nu
   inainte        = BEFEHL
   dupa           = BEFEHL
   intre          = BEFEHL
   scop           = pagina
   distantacoloane = DIMENSION
   continua       = da nu
   alternativ      = grila fixat coloane note niciunul
   criteriu       = pagina
   fonttext       = inherits: \seteazafonttext
   aliniere       = inherits: \seteazaalinierea
   stiltext       = STYLE BEFEHL
   culoaretex     = COLOR
   anchor         = urmatorul
   spatiuinainte  = inherits: \blanc
   spaceinbetween = inherits: \blanc
   inherits: \seteazainconjurat

```

**\setupnotes** [ $\dots$ , $\dots$ ]<sup>1</sup> [ $\dots$ , $\dots$ ]<sup>2</sup> $\dots$ , $\dots$ ]

```

1  NAME          OPT
2  inherits: \setupnote

```

**\setupoffset** [ $\dots$ , $\dots$ ]<sup>\*</sup> $\dots$ , $\dots$ ]

```

*  inherits: \setupoffsetbox

```

**\setupoffsetbox** [ $\dots$ , $\dots$ ]<sup>\*</sup> $\dots$ , $\dots$ ]

```

*  x              = DIMENSION
   y              = DIMENSION
   offsetstanga   = DIMENSION
   offsetdreapta  = DIMENSION
   offsetsus      = DIMENSION
   offsetjos      = DIMENSION
   metoda        = fixat
   latime         = DIMENSION
   inaltime       = DIMENSION
   inaltime       = DIMENSION
   locatie        = stanga centru dreapta sus subsol linie l c r m t b g

```

**\setupoutputroutine** [ $\dots$ ]<sup>1</sup> [ $\dots$ , $\dots$ ]<sup>2</sup> $\dots$ , $\dots$ ]

```

1  NAME          OPT
2  KEY = CSNAME

```

**\setupoutputroutine** [ $\dots$ ]<sup>\*</sup>

```

*  NAME

```

**\setuppagechecker** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME OPT  
2 linii = NUMMER  
offset = DIMENSION  
metoda = 0 1 2 3  
inainte = BEFEHL  
dupa = BEFEHL  
intre = BEFEHL

**\setuppagecolumns** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME OPT  
2 separator = NAME  
directie = normal reverse  
distanta = DIMENSION  
n = NUMMER  
latimemaxima = DIMENSION  
alinie = inherits: \setezaalinie  
blanc = inherits: \blanc  
culoare = COLOR  
setups = NAME  
pagina = inherits: \pagina  
inherits: \seteazainconjurat

**\setuppageinjection** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME OPT  
2 stare = precedent urmatorul NUMMER  
intarziere = da nu  
alternativ = figura buffer setups niciunul NAME  
pagina = inherits: \pagina  
pagestate = start stop  
n = NUMMER  
inherits: \seteazainconjurat

**\setuppageinjectionalternative** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME OPT  
2 renderingsetup = NAME

**\setuppageshift** [...<sup>1</sup>...] [...<sup>2</sup>...] [...<sup>3</sup>...]

1 pagina foaie OPT OPT  
2 NAME  
3 NAME

**\setuppagestate** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME OPT  
2 intarziere = da nu

**\setuppairedbox** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME OPT  
2 inainte = BEFEHL  
dupa = BEFEHL  
intre = BEFEHL  
locatie = stanga centru dreapta sus subsol inalt jos  
n = NUMMER  
distanta = DIMENSION  
fonttext = inherits: \seteazafonttext  
latime = DIMENSION  
inaltime = DIMENSION  
latimemaxima = DIMENSION  
inaltimemaxima = DIMENSION  
alinie = inherits: \setezaalinie  
stil = STYLE BEFEHL  
culoare = COLOR

**\setarePAIREDBOX** [...,<sup>\*</sup>...,...]

\* inherits: \setuppairedbox  
instances: legend

**\setarelegend** [...,<sup>\*</sup>...,...]

\* inherits: \setuppairedbox

```
\setuppaper [...,..*...,...]
* inherits: \seteazadimensiunihartie
```

```
\setupparagraph [...,1...] [...,..2...,...]
1 NAME OPT
2 stil = STYLE BEFEHL
culoare = COLOR
alinieri = inherits: \seteazaalinieria
setups = NAME
```

```
\setupparagraphintro [...,1...] [...,2]
1 reset fiecare primul urmatorul
2 BEFEHL
```

```
\setupparallel [...,1] [...,2,...] [...,..3...,...]
1 NAME
2 NAME
3 setups = NAME
start = NUMMER
n = NUMMER
criteriu = tot
```

```
\setupperiodkerning [...,1,...] [...,..2...,...]
1 NAME OPT
2 factor = NUMMER
```

```
\setupperiods [...,..*...,...]
* n = NUMMER
latime = DIMENSION ajustat
distanta = DIMENSION
simbol = BEFEHL
```

```
\setupplacement [...,1,...] [...,..2...,...]
1 NAME OPT
2 inainte = BEFEHL
dupa = BEFEHL
stanga = BEFEHL
dreapta = BEFEHL
grid = inherits: \snaptogrid
corectielinie = on dezactivat
corectieadancime = on dezactivat
margine = da nu standard
```

```
\setuppositionbar [...,..*...,...]
* stil = STYLE BEFEHL
culoare = COLOR
n = NUMMER
min = NUMMER
max = NUMMER
text = TEXT
latime = DIMENSION
inaltime = DIMENSION
inaltime = DIMENSION
```

```
\setupprocessor [...,1,...] [...,..2...,...]
1 NAME OPT
2 stare = start stop
stanga = BEFEHL
dreapta = BEFEHL
comanda = \...##1
stil = STYLE BEFEHL
culoare = COLOR
```

\setupprofile [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME OPT  
2 inalttime = DIMENSION  
inalttime = DIMENSION  
distanta = DIMENSION  
factor = NUMMER  
linii = NUMMER  
metoda = strict fixat niciunul

\setupquotation [...,<sup>\*</sup>...,...]

\* inherits: \setupdelimitedtext

\setuprealpagenumber [...,<sup>\*</sup>...,...]

\* inherits: \setupcounter

\setupreferenceformat [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME OPT  
2 eticheta = \* NAME  
stanga = BEFEHL  
dreapta = BEFEHL  
type = implicit text titlu numar pagina realpage  
setups = NAME  
autocase = da nu  
text = TEXT  
stil = STYLE BEFEHL  
culoare = COLOR

\setupreferenceprefix [...]

\* + - TEXT

\setupreferencestructureprefix [...<sup>1</sup>...] [...<sup>2</sup>...] [...,<sup>3</sup>...,...]

1 NAME ABSCHNITT OPT OPT  
2 implicit  
3 prefix = da nu  
prefixseparatorset = NAME  
prefixconversion = NAME  
prefixconversionset = NAME  
prefixstarter = BEFEHL PROCESSOR->BEFEHL  
prefixstopper = BEFEHL PROCESSOR->BEFEHL  
prefixset = NAME  
prefixsegments = NUMMER NUMMER:NUMMER NUMMER:\* NUMMER:tot ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:\* ABSCHNITT:tot  
curent  
numberconversion = NAME  
numberconversionset = NAME  
numberstarter = BEFEHL PROCESSOR->BEFEHL  
numberstopper = BEFEHL PROCESSOR->BEFEHL  
numbersegments = NUMMER NUMMER:NUMMER NUMMER:\* NUMMER:tot  
numberseparatorset = NAME  
prefixconnector = BEFEHL PROCESSOR->BEFEHL

\setupregisters [...<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME NAME:NUMMER OPT  
2 inherits: \seteazaregistru

\setupregisters [...,<sup>1</sup>...] [...,<sup>2</sup>...] [...,<sup>3</sup>...,...]

1 NAME OPT OPT  
2 NUMMER  
3 inherits: \seteazaregistru

\setuprenderingwindow [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME OPT  
2 actiunedeschiderepagina = REFERENCE  
actiuneinchiderepagina = REFERENCE  
inherits: \seteazainconjurat



```

\setuppruby [...1,...] [...2,...]
1  NAME          OPT
2  locatie      = sus stanga dreapta niciunul
   aliniere     = auto flushleft centru flushright
   dilatat      = da nu
   hoffset      = DIMENSION
   voffset      = DIMENSION
   distanta     = niciunul DIMENSION
   stanga       = BEFEHL
   dreapta      = BEFEHL
   stil         = STYLE BEFEHL
   culoare      = COLOR

```

```

\setups [...*,...]
*  NAME

```

```

\setupscale [...1,...] [...2,...]
1  NAME          OPT
2  scala          = NUMMER
   xscala         = NUMMER
   yscala         = NUMMER
   latime         = DIMENSION
   inaltime       = DIMENSION
   inaltime       = da nu
   linii          = NUMMER
   factor         = ajustat broad max min auto implicit
   hfactor        = ajustat broad max min auto implicit
   factorw        = ajustat broad max min auto implicit
   latimemaxima   = DIMENSION
   inaltimemaxima = DIMENSION
   s              = NUMMER
   sx             = NUMMER
   sy             = NUMMER
   equalwidth     = DIMENSION
   equalheight    = DIMENSION
   grid           = da ajustat inaltime adancime jumatatelinie

```

```

\setupscript [...1,...] [...2,...]
1  NAME          OPT
2  metoda        = hangul hanzi nihongo ethiopic thai test
   preset        = NAME
   features      = auto

```

```

\setupscripts [...1,...] [...2,...]
1  NAME          OPT
2  inherits: \setupscript

```

```

\setupselector [...1,...] [...2,...]
1  NAME
2  n = NUMMER
   m = NUMMER

```

```

\setupshift [...1,...] [...2,...]
1  NAME          OPT
2  continua      = da nu
   unitate       = ex em pt in cm mm sp bp pc dd cc nc
   metoda        = NUMMER
   dy            = NUMMER
   aliniere      = inherits: \seteazaalinierea
   stil          = STYLE BEFEHL
   culoare       = COLOR

```

```

\setupsidebar [...1,...] [...2,...]
1  NAME          OPT
2  grosimerigla   = DIMENSION
   culoarerigla   = COLOR
   alternativ      = NUMMER
   offsetsus      = DIMENSION
   offsetjos      = DIMENSION
   distanta       = DIMENSION
   distantamarginestanga = DIMENSION
   nivel          = NUMMER

```

`\setupspellchecking [...,*...]`

\* stare = start stop  
metoda = 1 2 3  
lista = NAME

`\setupstartstop [...,1...] [...,2...]`

1 NAME OPT  
2 inainte = BEFEHL  
dupa = BEFEHL  
intre = BEFEHL  
setups = NAME  
stanga = BEFEHL  
dreapta = BEFEHL  
stil = STYLE BEFEHL  
culoare = COLOR

`\setupstretched [...,*...]`

\* inherits: \setupcharacterkerning

`\setupstruts [...]`

\* da nu auto cap OPTajustat linie implicit CHARACTER

`\setupstyle [...,1...] [...,2...]`

1 NAME OPT  
2 metoda = comanda  
stil = STYLE BEFEHL  
culoare = COLOR

`\setupsubformula [...,1...] [...,2...]`

1 NAME OPT  
2 aliniaturmator = da nu auto

`\setupsubformulas [...,1...] [...,2...]`

1 NAME OPT  
2 inherits: \setupsubformula

`\setupsynctex [...,*...]`

\* stare = start stop  
metoda = min max

`\setups {...,*...}`

\* NAME

```

\setupTABLE [...1,...] [...2,...] [...3,...]
1  r c x y rand colona primul uOPTltim start antet fiecare impar par unu NUMMER -NUMMER
2  primul least fiecare doi impar par NUMMER -NUMMER
3  extras          = BEFEHL
   stanga          = BEFEHL
   dreapta         = BEFEHL
   culoaretitlu    = COLOR
   stiltitlu       = STYLE BEFEHL
   distantamarginestanga = DIMENSION
   distantamarginedreapta = DIMENSION
   distantacoloane = DIMENSION
   latimemaxima    = DIMENSION
   setups          = NAME
   latimetext       = DIMENSION local
   split           = da nu repetat auto
   antet           = repetat
   optiune         = dilatat tight
   inainte         = BEFEHL
   dupa            = BEFEHL
   aceeasipagina   = inainte dupa ambele
   spaceinbetween  = inherits: \blanc
   splitoffset     = DIMENSION
   aliniazacaracter = da nu
   alierecaracter  = TEXT number->TEXT text->TEXT
   distanta        = DIMENSION
   culoare         = COLOR
   stil            = math STYLE BEFEHL
   inherits: \seteazainconjurat

```

```

\setupTEXpage [...*,...]
* inherits: \setupfittingpage

```

```

\setuptabulation [...1,...] [...2,...]
1  NAME          OPT
2  format        = TEMPLATE niciunul
   inainte       = BEFEHL
   dupa          = BEFEHL
   distanta      = mic mediu mare niciunul blank adancime grila DIMENSION
   blanc         = preferinta aceeasipagina max fortat enable dezactivat faraalb impachetat inapot overlay
                  totdeauna weak strong implicit inainte intre dupa fixat flexibil niciunul mic mediu mare
                  linie jumatatelinie quarterline formula alb inaltime adancime standard NUMMER*mic NUMMER*mediu
                  NUMMER*mare NUMMER*linie NUMMER*jumatatelinie NUMMER*quarterline NUMMER*formula NUMMER*alb
                  NUMMER*inaltime NUMMER*adancime category:NUMMER order:NUMMER penalty:NUMMER DIMENSION NAME
   stiltitlu     = STYLE BEFEHL
   culoaretitlu  = COLOR
   fundal        = NAME
   culoarefundal = COLOR
   foregroundstyle = STYLE BEFEHL
   foregroundcolor = COLOR
   aliniere      = stanga centru dreapta dimension
   rigla         = linie normal
   culoarerigla  = COLOR
   grosimerigla  = DIMENSION
   fonttext      = inherits: \seteazafonttext
   aliniat       = da nu
   split         = da nu repetat auto
   unitate       = DIMENSION
   margine       = DIMENSION
   intern        = BEFEHL
   EQ            = BEFEHL
   antet         = da repetat text
   frame         = on dezactivat
   titlu         = TEXT
   kepttogether  = da nu

```

```

\setuptagging [...*,...]
* stare = start stop
  metoda = auto

```

`\setuptextbackground [...,1...] [...,2...,...]`

```
1 NAME OPT
2 stare = start stop
  locatie = text paragraf totdeauna niciunul
  criteriu = NUMMER
  alternativ = NUMMER
  mp = NAME
  metoda = NAME
  fundal = culoare
  culoarefundal = COLOR
  colt = rectangular rotund
  nivel = NUMMER
  offsetfundal = DIMENSION
  inainte = BEFEHL
  dupa = BEFEHL
  aliniere = inherits: \seteazaalinierea
  dash = NUMMER
  raza = DIMENSION
  frame = on dezactivat
  culoareframe = COLOR
  grosimerigla = DIMENSION
  voffset = DIMENSION
  offsetframe = DIMENSION
  offsetstanga = da nu standard DIMENSION
  offsetdreapta = da nu standard DIMENSION
  offsetsus = mic mediu mare linie DIMENSION
  offsetjos = mic mediu mare linie DIMENSION
  stil = STYLE BEFEHL
  culoare = COLOR
```

`\setuptextflow [...,1...] [...,2...,...]`

```
1 NAME OPT
2 latime = DIMENSION
  stil = STYLE BEFEHL
  culoare = COLOR
```

`\setuptooltip [...,1...] [...,2...,...]`

```
1 NAME OPT
2 locatie = stanga centru dreapta
  inherits: \seteazainconjurat
```

`\setupunit [...,1...] [...,2...,...]`

```
1 NAME OPT
2 metoda = 1 2 3 4 5 6
  language = SPRACHE
  alternativ = text matematica
  order = reverse normal
  separator = mic mediu mare normal niciunul NAME
  spatiu = mic mediu mare normal niciunul NAME
  stil = STYLE BEFEHL
  culoare = COLOR
```

`\setupuserdata [...,1...] [...,2...,...]`

```
1 NAME OPT
2 inainte = BEFEHL
  dupa = BEFEHL
  aliniere = inherits: \seteazaalinierea
  setups = NAME
  stil = STYLE BEFEHL
  culoare = COLOR
  alternativ = implicit NAME
  KEY = VALUE
```

`\setupuserdataalternative [...,1...] [...,2...,...]`

```
1 NAME OPT
2 renderingsetup = NAME
  KEY = VALUE
```

`\setupuserpagenumber [...,*...,...]`

```
* viewerprefix = TEXT
  stare = start stop niciunul mentine gol
  inherits: \setupcounter
```

```
\setupversion [...]  
*   concept fisier temporar final NAME
```

```
\setupviewerlayer [...,*=...,...]  
*   titlu       = TEXT  
    stare       = start stop  
    export      = da nu  
    tiparibil   = da nu  
    scop        = local global  
    metoda      = niciunul comanda
```

```
\setupvspacing [...,*=...,...]  
*   inherits: \vspacing OPT
```

```
\setupwithargument {...} {...}  
1   NAME  
2   CONTENT
```

```
\setupwithargumentswapped {...} {...}  
1   CONTENT  
2   NAME
```

```
\setupxml [...,*=...,...]  
*   implicit    = ascuns niciunul text  
    compress    = da nu
```

```
\setupxtable [...,1,...] [...,*=2...,...]  
1   NAME OPT  
2   latimetext      = DIMENSION local  
    fonttext        = inherits: \seteazafonttext  
    spaceinbetween  = inherits: \blanc  
    optiune          = tight max dilatat latime inaltime fixat  
    inaltimetext     = DIMENSION  
    latimemaxima     = DIMENSION  
    distantacoloane  = DIMENSION  
    distantamarginestanga = DIMENSION  
    distantamarginedreapta = DIMENSION  
    antet            = repetat  
    subsol           = repetat  
    grosimerigla     = DIMENSION  
    split            = da nu repetat auto  
    splitoffset      = DIMENSION  
    aceeasipagina    = inainte dupa ambele  
    distanta         = DIMENSION  
    aliniazacaracter = da nu  
    alignmentleftsample = TEXT  
    alignmentrightsample = TEXT  
    alignmentleftwidth = DIMENSION  
    alignmentrightwidth = DIMENSION  
    alierecaracter   = TEXT  
    inherits: \seteazainconjurat
```

```
\setuvalue {...} {...}  
1   NAME  
2   CONTENT
```

```
\setuxvalue {...} {...}  
1   NAME  
2   CONTENT
```

```
\setvalue {...} {...}  
1   NAME  
2   CONTENT
```

```
\setvariable {...} {...} {...}  
1   NAME  
2   KEY  
3   VALUE
```

**\setvariables** [<sup>1</sup>...] [<sup>2</sup>...]

1 NAME  
2 set = BEFEHL  
reset = BEFEHL  
KEY = VALUE

**\setvboxregister** <sup>1</sup>... {<sup>2</sup>...}

1 CSNAME NUMMER  
2 CONTENT

**\setvisualizerfont** [<sup>\*</sup>...]

\* FONT OPT

**\setvtopregister** <sup>1</sup>... {<sup>2</sup>...}

1 CSNAME NUMMER  
2 CONTENT

**\setwidthof** <sup>1</sup>... \to \<sup>2</sup>...

1 TEXT  
2 CSNAME

**\setxmeasure** {<sup>1</sup>...} {<sup>2</sup>...}

1 NAME  
2 DIMENSION

**\setxvalue** {<sup>1</sup>...} {<sup>2</sup>...}

1 NAME  
2 CONTENT

**\setxvariable** {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...}

1 NAME  
2 KEY  
3 VALUE

**\setxvariables** [<sup>1</sup>...] [<sup>2</sup>...]

1 NAME  
2 set = BEFEHL  
reset = BEFEHL  
KEY = VALUE

**\shapedhbox** {<sup>\*</sup>...}

\* CONTENT

**\shiftbox** {<sup>1</sup>...}

1 CONTENT

**\SHIFT** {<sup>\*</sup>...}

\* CONTENT  
instances: shiftup shiftdown

**\shiftdown** {<sup>\*</sup>...}

\* CONTENT

**\shiftup** {<sup>\*</sup>...}

\* CONTENT

**\showallmakeup**

**\showattributes**

<code>\showboxes</code>
<pre> \showbtxdatasetauthors [...,.*,...] *  specification = NAME          OPT     dataset      = NAME     field        = address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution                   journal language luna monthfiled nationality note numar unu doi organization pages publisher                   school series titlu type volume an yearfiled NAME </pre>
<pre> \showbtxdatasetauthors [...] *  NAME          OPT </pre>
<pre> \showbtxdatasetcompleteness [...,.*,...] *  specification = NAME          OPT     dataset      = NAME     field        = address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution                   journal language luna monthfiled nationality note numar unu doi organization pages publisher                   school series titlu type volume an yearfiled NAME </pre>
<pre> \showbtxdatasetcompleteness [...] *  NAME          OPT </pre>
<pre> \showbtxdatasetfields [...,.*,...] *  specification = NAME          OPT     dataset      = NAME     field        = address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution                   journal language luna monthfiled nationality note numar unu doi organization pages publisher                   school series titlu type volume an yearfiled NAME </pre>
<pre> \showbtxdatasetfields [...] *  NAME          OPT </pre>
<pre> \showbtxfields [...,.*,...] *  rotatie      = NUMMER<sup>OPT</sup>     specification = NAME </pre>
<pre> \showbtxfields [...] *  NAME          OPT </pre>
<pre> \showbtxhashedauthors [...] *  TEXT          OPT </pre>
<pre> \showbtxtables [...] *  TEXT          OPT </pre>
<pre> \showchardata {...} *  TEXT </pre>
<pre> \showcharratio {...} *  TEXT </pre>
<pre> \showcolorbar [...] *  COLOR </pre>
<pre> \showcolorcomponents [...] *  COLOR </pre>
<pre> \showcolorset [...] *  COLOR </pre>

<code>\showcolorstruts</code>
<code>\showcounter [...]</code> <code>* NAME</code>
<code>\showdirectives</code>
<code>\showdirlsinmargin</code>
<code>\showedebuginfo</code>
<code>\showexperiments</code>
<code>\showfont [...]</code> <code>[...<sup>2</sup>,...]</code> <code>1 FONT</code> <code>OPT</code> <code>2 NUMMER</code>
<code>\showfontdata</code>
<code>\showfontexpansion</code>
<code>\showfontitalics</code>
<code>\showfontkerns</code>
<code>\showfontparameters</code>
<code>\showfontstrip [...*,...]</code> <code>* inherits: \seteazafonttext</code>
<code>\showfontstyle [...<sup>1</sup>,...]</code> <code>[...<sup>2</sup>,...]</code> <code>[...<sup>3</sup>,...]</code> <code>[...<sup>4</sup>,...]</code> <code>1 inherits: \seteazafont<sup>OPT</sup>text</code> <code>OPT</code> <code>OPT</code> <code>OPT</code> <code>2 rm ss tt mm hw cg</code> <code>3 tf bf it sl bi bs</code> <code>4 tot NUMMER</code>
<code>\showglyphdata</code>
<code>\showglyphs</code>
<code>\showgridsnapping</code>
<code>\showhelp {...}</code> <code>[...<sup>2</sup>]</code> <code>1 TEXT</code> <code>2 REFERENCE</code>
<code>\showhyphenationtrace [...<sup>1</sup>]</code> <code>[...<sup>2</sup>]</code> <code>1 SPRACHE</code> <code>OPT</code> <code>2 TEXT</code>
<code>\showhyphens {...}</code> <code>* TEXT</code>
<code>\showinjector [...*,...]</code> <code>* NAME</code> <code>OPT</code>



<code>\showjustification</code>
<code>\showkerning {...}</code> *    TEXT
<code>\showlayoutcomponents</code>
<code>\showligature {...}</code> *    TEXT
<code>\showligatures [...]</code> *    FONT
<code>\showlogcategories</code>
<code>\showmargins</code>
<code>\showmessage {...} {...} {...,<sup>3</sup>...}</code> 1    NAME 2    NAME NUMBER 3    TEXT
<code>\showminimalbaseline</code>
<code>\shownextbox \<sup>1</sup>... {<sup>2</sup>...}</code> 1    CSNAME 2    CONTENT
<code>\showotfcomposition {...} {...} {<sup>3</sup>...}</code> 1    FONT 2    -1 1 +1 12r r2l 3    TEXT
<code>\showparentchain \<sup>1</sup>... {<sup>2</sup>...}</code> 1    CSNAME 2    NAME
<code>\showsetupsdefinition [...]</code> *    NAME
<code>\showtimer {...}</code> *    TEXT
<code>\showtokens [...]</code> *    NAME
<code>\showtrackers</code>
<code>\showvalue {...}</code> *    NAME
<code>\showvariable {<sup>1</sup>...} {<sup>2</sup>...}</code> 1    NAME 2    KEY

<code>\showwarning {...} {...} {...,<sup>3</sup>...}</code> 1 NAME 2 NAME NUMMER 3 TEXT
<code>\signalrightpage</code>
<code>\simbol [...]<sup>1</sup> [...]<sup>2</sup></code> 1 NAME <small>OPT</small> 2 NAME
<code>\simbol {...}</code> * NAME
<code>\simplealignedbox {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup></code> 1 DIMENSION 2 stanga dreapta centru flushleft flushright intern extern 3 CONTENT
<code>\simplealignedboxplus {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup> {...}<sup>4</sup></code> 1 DIMENSION 2 stanga dreapta centru flushleft flushright intern extern 3 TEXT 4 CONTENT
<code>\simplealignedspreadbox {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup></code> 1 DIMENSION 2 stanga dreapta centru flushleft flushright intern extern 3 CONTENT
<code>\simplegroupedcommand {...}<sup>1</sup> {...}<sup>2</sup></code> 1 BEFEHL 2 BEFEHL
<code>\simplereversealignedbox {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup></code> 1 DIMENSION 2 stanga dreapta centru flushleft flushright intern extern 3 CONTENT
<code>\simplereversealignedboxplus {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup> {...}<sup>4</sup></code> 1 DIMENSION 2 stanga dreapta centru flushleft flushright intern extern 3 TEXT 4 CONTENT
<code>\singalcharacteralign {...}<sup>1</sup> {...}<sup>2</sup></code> 1 NUMMER 2 NUMMER
<code>\singlebond</code>
<code>\sixthofsixarguments {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup> {...}<sup>4</sup> {...}<sup>5</sup> {...}<sup>6</sup></code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT
<code>\slantedface</code>

$\backslash$ slicepages [ <sup>1</sup> ...] [ <sup>2</sup> ... <sub>OPT</sub> ...] [ <sup>3</sup> ... <sub>OPT</sub> ...] 1 FILE 2 offset = DIMENSION hoffset = DIMENSION voffset = DIMENSION latime = DIMENSION inaltime = DIMENSION n = NUMBER 3 offset = DIMENSION hoffset = DIMENSION voffset = DIMENSION latime = DIMENSION inaltime = DIMENSION n = NUMBER
$\backslash$ slovenianNumerals {...} * NUMBER
$\backslash$ sloveniannumerals {...} * NUMBER
$\backslash$ smallbodyfont
$\backslash$ smallcappedcharacters {...} * NUMBER
$\backslash$ smallcappedromannumerals {...} * NUMBER
$\backslash$ smaller
$\backslash$ smallskip
$\backslash$ smash [ <sup>1</sup> ...] { <sup>2</sup> ...} 1 w h d t <sub>OPT</sub> 2 CONTENT
$\backslash$ smashbox ... * CSNAME NUMBER
$\backslash$ smashboxed ... * CSNAME NUMBER
$\backslash$ smashedhbox <sup>1</sup> ... { <sup>2</sup> ...} 1 TEXT <sub>OPT</sub> 2 CONTENT
$\backslash$ smashedvbox <sup>1</sup> ... { <sup>2</sup> ...} 1 TEXT <sub>OPT</sub> 2 CONTENT
$\backslash$ snaptogrid [ <sup>1</sup> ...] \ <sup>2</sup> ... { <sup>3</sup> ...} 1 normal standard <sub>OPT</sub> box min max centru math math:linie math:jumatatelinie math:-line math:-halfline NAME 2 CSNAME 3 CONTENT
$\backslash$ snaptogrid [... <sup>1</sup> ...] \ <sup>2</sup> ... { <sup>3</sup> ...} 1 inherits: \define <sub>OPT</sub> gridsnapping 2 CSNAME 3 CONTENT

\someheadnumber [...] [...] 1    ABSCHNITT 2    precedent curent urmatorul primul ultim
\somekindoftab [..., ... <sup>*</sup> ..., ...] *    alternativ    =    orizontal <sup>OPT</sup> vertical latime       =    DIMENSION inaltime    =    DIMENSION n            =    NUMMER m            =    NUMMER
\somelocalfloat
\somenamedheadnumber {...} {...} 1    ABSCHNITT 2    precedent curent urmatorul primul ultim
\someplace {...} {...} {...} {...} {...} [...] 1    TEXT 2    TEXT 3    TEXT 4    TEXT 5    TEXT 6    REFERENCE
\SORTING [... <sup>1</sup> ] {... <sup>2</sup> } 1    NAME <sup>OPT</sup> 2    CONTENT instances: logo
\logo [... <sup>1</sup> ] {... <sup>2</sup> } 1    NAME <sup>OPT</sup> 2    CONTENT
\spaceddigits {...} *    NUMMER
\spaceddigitismethod
\spaceddigitsseparator
\spaceddigitssymbol
\spanishNumerals {...} *    NUMMER
\spanishnumerals {...} *    NUMMER
\spatiifixate
\spatiu
\spatiufixat
\splitatasterisk ... \ <sup>2</sup> ... \ <sup>3</sup> ... 1    TEXT 2    CSNAME 3    CSNAME

$\backslash\text{splitatcolon } \dots \text{ }^1 \backslash \dots \text{ }^2 \backslash \dots \text{ }^3$ 1 TEXT 2 CSNAME 3 CSNAME
$\backslash\text{splitatcolons } \dots \text{ }^1 \backslash \dots \text{ }^2 \backslash \dots \text{ }^3$ 1 TEXT 2 CSNAME 3 CSNAME
$\backslash\text{splitatcomma } \dots \text{ }^1 \backslash \dots \text{ }^2 \backslash \dots \text{ }^3$ 1 TEXT 2 CSNAME 3 CSNAME
$\backslash\text{splitatperiod } \dots \text{ }^1 \backslash \dots \text{ }^2 \backslash \dots \text{ }^3$ 1 TEXT 2 CSNAME 3 CSNAME
$\backslash\text{splitdfrac } \{ \dots \}^1 \{ \dots \}^2$ 1 CONTENT 2 CONTENT
$\backslash\text{splitfilename } \{ \dots \}^*$ * FILE
$\backslash\text{splitfrac } \{ \dots \}^1 \{ \dots \}^2$ 1 CONTENT 2 CONTENT
$\backslash\text{splitoffbase}$
$\backslash\text{splitofffull}$
$\backslash\text{splitoffkind}$
$\backslash\text{splitoffname}$
$\backslash\text{splitoffpath}$
$\backslash\text{splitoffroot}$
$\backslash\text{splitofftokens } \dots \text{ }^1 \backslash \text{from } \dots \text{ }^2 \backslash \text{to } \dots \text{ }^3$ 1 TEXT 2 TEXT 3 CSNAME
$\backslash\text{splitofftype}$
$\backslash\text{splitstring } \dots \text{ }^1 \backslash \text{at } \dots \text{ }^2 \backslash \text{to } \dots \text{ }^3 \backslash \text{and } \dots \text{ }^4$ 1 TEXT 2 TEXT 3 CSNAME 4 CSNAME
$\backslash\text{spreadhbox } \dots$ * CSNAME NUMBER

$\backslash\text{sqrt}$ [ <sup>1</sup> ...] { <sup>2</sup> ...} 1 TEXT OPT 2 CONTENT
$\backslash\text{stackrel}$ { <sup>1</sup> ...} { <sup>2</sup> ...} 1 CONTENT 2 CONTENT
$\backslash\text{stanga}$ ... * CHARACTER
$\backslash\text{start}$ [ <sup>*</sup> ...] ... $\backslash\text{stop}$ * NAME OPT
$\backslash\text{startalignment}$ [... <sup>*</sup> ...] ... $\backslash\text{stopalignment}$ * inherits: \seteazaalinierea
$\backslash\text{startaliniatcentru}$ ... $\backslash\text{stopaliniatcentru}$
$\backslash\text{startaliniatdreapta}$ ... $\backslash\text{stopaliniatdreapta}$
$\backslash\text{startaliniatstanga}$ ... $\backslash\text{stopaliniatstanga}$
$\backslash\text{startallmodes}$ [... <sup>*</sup> ...] ... $\backslash\text{stopallmodes}$ * NAME
$\backslash\text{startantettabel}$ [ <sup>*</sup> ...] ... $\backslash\text{stopantettabel}$ * NAME
$\backslash\text{startATTACHMENT}$ [ <sup>1</sup> ...] [... <sup>2</sup> ... <sup>2</sup> ...] ... $\backslash\text{stopATTACHMENT}$ 1 NAME OPT OPT 2 inherits: \setupattachment instances: attachment
$\backslash\text{startattachment}$ [ <sup>1</sup> ...] [... <sup>2</sup> ... <sup>2</sup> ...] ... $\backslash\text{stopattachment}$ 1 NAME OPT OPT 2 inherits: \setupattachment
$\backslash\text{startbar}$ [ <sup>*</sup> ...] ... $\backslash\text{stopbar}$ * NAME
$\backslash\text{startbbordermatrix}$ ... $\backslash\text{stopbbordermatrix}$
$\backslash\text{startbitmapimage}$ [... <sup>*</sup> ...] ... $\backslash\text{stopbitmapimage}$ * culoare = rgb cmyk gri latime = DIMENSION inaltime = DIMENSION x = NUMMER y = NUMMER
$\backslash\text{startblocsectioneambient}$ [ <sup>*</sup> ...] ... $\backslash\text{stopblocsectioneambient}$ * NAME
$\backslash\text{startbordermatrix}$ ... $\backslash\text{stopbordermatrix}$
$\backslash\text{startbtxrenderingdefinitions}$ [ <sup>*</sup> ...] ... $\backslash\text{stopbtxrenderingdefinitions}$ * NAME

<code>\startbuffer [...] ... \stopbuffer</code> *    NAME                    OPT
<code>\startBUFFER ... \stopBUFFER</code> instances: hiding
<code>\starthiding ... \stophiding</code>
<code>\startcatcodetable \* ... \stopcatcodetable</code> *    CSNAME
<code>\startcenteraligned ... \stopcenteraligned</code>
<code>\startcharacteralign [...,.*=...,...] ... \stopcharacteralign</code> *    inherits: \setupcharacteralign
<code>\startcharacteralign [...] ... \stopcharacteralign</code> *    TEXT number->TEXT text->TEXT
<code>\startcheckedfences ... \stopcheckedfences</code>
<code>\startchemical [<sup>1</sup>] [...,.*<sup>2</sup>=...,...] ... \stopchemical</code> 1    NAME                    OPT                    OPT 2    inherits: \setupchemical
<code>\startcollect ... \stopcollect</code>
<code>\startcollecting ... \stopcollecting</code>
<code>\startcoloane [...,.*=...,...] ... \stopcoloane</code> *    inherits: \seteazacol <sup>OPT</sup> ane
<code>\startcolorintent [...] ... \stopcolorintent</code> *    knockout overprint niciunul
<code>\startcoloronly [...] ... \stopcoloronly</code> *    COLOR
<code>\startcolorset [...] ... \stopcolorset</code> *    NAME
<code>\startcolumnset [<sup>1</sup>] [...,.*<sup>2</sup>=...,...] ... \stopcolumnset</code> 1    NAME                    OPT                    OPT 2    inherits: \setupcolumnset
<code>\startcolumnsetspan [<sup>1</sup>] [...,.*<sup>2</sup>=...,...] ... \stopcolumnsetspan</code> 1    NAME                    OPT 2    inherits: \setupcolumnsetspan
<code>\startCOLUMNSET [...,.*=...,...] ... \stopCOLUMNSET</code> *    inherits: \setupcolumnset <sup>OPT</sup>
<code>\startcolumnspan [...,.*=...,...] ... \stopcolumnspan</code> *    inherits: \setupcolumnspan <sup>OPT</sup>

<pre> \startcombination [...]<sup>1</sup> [...]<sup>2</sup>... \stopcombination 1  NAME          OPT          OPT 2  inherits: \setupcombination </pre>
<pre> \startcombination [...]<sup>1</sup> [...]<sup>2</sup>... \stopcombination 1  NAME          OPT          OPT 2  N*M </pre>
<pre> \startcomentariupagina ... \stopcomentariupagina </pre>
<pre> \startCOMMENT [...]<sup>1</sup> [...]<sup>2</sup>... \stopCOMMENT 1  TEXT          OPT          OPT 2  inherits: \seteazacomentariu instances: comment </pre>
<pre> \startcomment [...]<sup>1</sup> [...]<sup>2</sup>... \stopcomment 1  TEXT          OPT          OPT 2  inherits: \seteazacomentariu </pre>
<pre> \startcomponenta [...]<sup>*</sup>... \stopcomponenta *  FILE * </pre>
<pre> \startcomponenta ...<sup>*</sup>... \stopcomponenta *  FILE * </pre>
<pre> \startcontextcode ... \stopcontextcode </pre>
<pre> \startcontextdefinitioncode ... \stopcontextdefinitioncode </pre>
<pre> \startctxfunction ...<sup>*</sup>... \stopctxfunction *  NAME </pre>
<pre> \startctxfunctiondefinition ...<sup>*</sup>... \stopctxfunctiondefinition *  NAME </pre>
<pre> \startculoare [...]<sup>*</sup>... \stopculoare *  COLOR </pre>
<pre> \startcurrentcolor ... \stopcurrentcolor </pre>
<pre> \startcurrentlistentrywrapper ... \stopcurrentlistentrywrapper </pre>
<pre> \startdelimited [...]<sup>1</sup> [...]<sup>2</sup> [...]<sup>3</sup>... \stopdelimited 1  NAME          OPT          OPT 2  SPRACHE 3  inherits: \startingust </pre>
<pre> \startdelimitedtext [...]<sup>1</sup> [...]<sup>2</sup> [...]<sup>3</sup>... \stopdelimitedtext 1  NAME          OPT          OPT 2  SPRACHE 3  inherits: \startingust </pre>
<pre> \startDELIMITEDTEXT [...]<sup>1</sup> [...]<sup>2</sup>... \stopDELIMITEDTEXT 1  SPRACHE          OPT          OPT 2  inherits: \startingust instances: quotation quote blockquote speech aside </pre>



$\backslash\text{startaside}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...,...] ... $\backslash\text{stopaside}$ 1 SPRACHE OPT OPT 2 inherits: $\backslash\text{startingust}$
$\backslash\text{startblockquote}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...,...] ... $\backslash\text{stopblockquote}$ 1 SPRACHE OPT OPT 2 inherits: $\backslash\text{startingust}$
$\backslash\text{startquotation}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...,...] ... $\backslash\text{stopquotation}$ 1 SPRACHE OPT OPT 2 inherits: $\backslash\text{startingust}$
$\backslash\text{startquote}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...,...] ... $\backslash\text{stopquote}$ 1 SPRACHE OPT OPT 2 inherits: $\backslash\text{startingust}$
$\backslash\text{startspeech}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...,...] ... $\backslash\text{stopspeech}$ 1 SPRACHE OPT OPT 2 inherits: $\backslash\text{startingust}$
$\backslash\text{startDESCRIERE}$ [...,.. <sup>*</sup> ...,...] ... $\backslash\text{stopDESCRIERE}$ * titlu = TEXT OPT semncarte = TEXT lista = TEXT referinta = REFERENCE
$\backslash\text{startDESCRIERE}$ [..., <sup>1</sup> ...] { <sup>2</sup> ...} ... $\backslash\text{stopDESCRIERE}$ 1 REFERENCE OPT OPT 2 TEXT
$\backslash\text{startdespachetat}$ ... $\backslash\text{stopdespachetat}$
$\backslash\text{startdisplaymath}$ ... $\backslash\text{stopdisplaymath}$
$\backslash\text{startdmath}$ ... $\backslash\text{stopdmath}$
$\backslash\text{startdocument}$ [...,.. <sup>*</sup> ...,...] ... $\backslash\text{stopdocument}$ * inherits: $\backslash\text{setupdocument}$ OPT
$\backslash\text{startdute}$ [...] ... $\backslash\text{stopdute}$ * REFERENCE
$\backslash\text{starteffect}$ [...] ... $\backslash\text{stopeffect}$ * NAME
$\backslash\text{startEFFECT}$ ... $\backslash\text{stopEFFECT}$
$\backslash\text{startelement}$ [..., <sup>*</sup> ...] ... $\backslash\text{stopelement}$ * REFERENCE OPT
$\backslash\text{startembeddedxtable}$ [...,.. <sup>*</sup> ...,...] ... $\backslash\text{stopembeddedxtable}$ * inherits: $\backslash\text{setupxtable}$ OPT
$\backslash\text{startembeddedxtable}$ [ <sup>*</sup> ...] ... $\backslash\text{stopembeddedxtable}$ * NAME OPT

<pre> \startENUMERARE [...,..<sup>*</sup>...,...] ... \stopENUMERARE *   titlu       = TEXT      OPT     semncarte   = TEXT     lista       = TEXT     referinta    = REFERENCE </pre>
<pre> \startENUMERARE [...,<sup>1</sup>...] {..<sup>2</sup>} ... \stopENUMERARE 1   REFERENCE      OPT      OPT 2   TEXT </pre>
<pre> \startexceptions [...] ... \stopexceptions *   SPRACHE </pre>
<pre> \startexpanded ... \stopexpanded </pre>
<pre> \startexpandedcollect ... \stopexpandedcollect </pre>
<pre> \startextendedcatcodetable \*... ... \stopextendedcatcodetable *   CSNAME </pre>
<pre> \startexternalfigurecollection [...] ... \stopexternalfigurecollection *   NAME </pre>
<pre> \startfacingfloat [...] ... \stopfacingfloat *   NAME </pre>
<pre> \startfigura [<sup>1</sup>.] [<sup>2</sup>.] [...,<sup>3</sup>...,...] ... \stopfigura 1   NAME      OPT 2   FILE 3   inherits: \figuraexterna </pre>
<pre> \startfittingpage [<sup>1</sup>.] [...,<sup>2</sup>...,...] ... \stopfittingpage 1   NAME      OPT 2   inherits: \setupfittingpage </pre>
<pre> \startFITTINGPAGE [...,..<sup>*</sup>...,...] ... \stopFITTINGPAGE *   inherits: \setupfittingpage<sup>OPT</sup> instances: TEXpage MPpage </pre>
<pre> \startMPpage [...,..<sup>*</sup>...,...] ... \stopMPpage *   inherits: \setupfittingpage<sup>OPT</sup> </pre>
<pre> \startTEXpage [...,..<sup>*</sup>...,...] ... \stopTEXpage *   inherits: \setupfittingpage<sup>OPT</sup> </pre>
<pre> \startfixat [<sup>*</sup>.] ... \stopfixat *   jos centru inat<sup>OPT</sup> lohi implicit </pre>
<pre> \startfloatcombination [...,..<sup>*</sup>...,...] ... \stopfloatcombination *   inherits: \setupcombination      OPT </pre>
<pre> \startfloatcombination [<sup>*</sup>.] ... \stopfloatcombination *   N*M NAME      OPT </pre>

```

\startFLOATtext [...1,...] [...2,...] {...3} ... \stopFLOATtext
1 split totdeauna stangaOPTdreapta internOPTextern spatiuspate cutspace instanga indreapta inmargin marginestanga
marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inalttime
adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine
[-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva
effective antet subsol
2 REFERENCE
3 TEXT
instances: chemical figure table intermezzo graphic

```

```

\startchemicaltext [...1,...] [...2,...] {...3} ... \stopchemicaltext
1 split totdeauna stanga dreapta internOPTextern spatiuspate cutspace instanga indreapta inmargin marginestanga
marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inalttime
adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine
[-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva
effective antet subsol
2 REFERENCE
3 TEXT

```

```

\startfiguretext [...1,...] [...2,...] {...3} ... \stopfiguretext
1 split totdeauna stanga dreapta internOPTextern spatiuspate cutspace instanga indreapta inmargin marginestanga
marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inalttime
adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine
[-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva
effective antet subsol
2 REFERENCE
3 TEXT

```

```

\startgraphicstext [...1,...] [...2,...] {...3} ... \stopgraphicstext
1 split totdeauna stanga dreapta internOPTextern spatiuspate cutspace instanga indreapta inmargin marginestanga
marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inalttime
adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine
[-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva
effective antet subsol
2 REFERENCE
3 TEXT

```

```

\startintermezzotext [...1,...] [...2,...] {...3} ... \stopintermezzotext
1 split totdeauna stanga dreapta internOPTextern spatiuspate cutspace instanga indreapta inmargin marginestanga
marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inalttime
adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine
[-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva
effective antet subsol
2 REFERENCE
3 TEXT

```

```

\starttabletext [...1,...] [...2,...] {...3} ... \stoptabletext
1 split totdeauna stanga dreapta internOPTextern spatiuspate cutspace instanga indreapta inmargin marginestanga
marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inalttime
adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine
[-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva
effective antet subsol
2 REFERENCE
3 TEXT

```

```

\startfont [...] ... \stopfont
* FONT OPT

```

```

\startfontclass [...] ... \stopfontclass
* fiecare NAME

```

```

\startfontsolution [...] ... \stopfontsolution
* NAME

```

```

\startformula [...*,...] ... \stopformula
* impachetat tight centru incadrat adancime linie jumatatelinie -linie -jumatatelinie inherits: \seteazafonttext

```

```
\startformula [...*=... ] ... \stopformula
*   optune = impachetatopt tight centru incadrat adancime linie jumatatelinie -linie -jumatatelinie inherits: \seteazafonttext
      margine = da nu standard DIMENSION
      grid    = inherits: \snaptogrid
```

```
\startFORMULAformula [...] ... \stopFORMULAformula
*   impacchetat tight centru incadrat OPT adancime linie jumatatelinie -linie -jumatatelinie inherits: \seteazafonttext
instances: sp sd mp md
```

`\startmdformula [...]*... \stopmdformula`  
`*   impachetat tight centrort incadrat adancime linie jumatatelinie -linie -jumatatelinie inherits: \seteazafonttext`

`\startmpformula [...;...] ... \stopmpformula`  
`* impacehtat tight centRTincadrat adancime linie jumatatelinie -linie -jumatatelinie inherits: \seteazafonttext`

`\startsdformula [...,*...] ... \stopsdformula`  
`* impacetati tight centRT incadrat adancime linie iumatatelinie -linie -iumatatelinie inherits: \seteazafonttext`

`\startspformula [...,*...] ... \stopspformula`  
`* impachetat tight centrtrincadrat adancime linie jumatatelinie -linie -jumatatelinie inherits: \seteazafonttext`

`\startformule [...,*...] ... \stopformule`  
`* + - REFERENCE` `OPT`

```
\startframed [...] [.,.,.2.,.] ... \stopframed
1 NAME OPT OPT
2 inherits: \seteazainconjurat
```

```
\startframedcell [...,*=...,...] ... \stopframedcell
* inherits: \seteazainconjuratOPT
```

```
\startframedcontent [...] ... \stopframedcontent
*   NAME dezactivat           OPT
```

```
\startframedrow [...,*=.,...] ... \stopframedrow
* inherits: \seteazainconjurat
```

```
\startframedtable [.1.] [...,2...,...] ... \stopframedtable
1 NAME OPT
2 inherits: \seteazainconjurat
```

```
\startfundal [...*=...,...] ... \stopfundal
* inherits:\seteazafundal
```

```
\startFUNDAL [.,..*=.,..] ... \stopFUNDAL
* inherits: \seteazafundal
instances: fundal
```

```
\startgridsnapping [...] ... \stopgridsnapping
*   normal standard da strict tolerant sus subzol ambele broad ajustat primul ultim inalt unu jos niciunul linie strut
    box min max centru math:linie math:jumatatelinie math:-line math:-halfline NAME
```

```
\startgridsnapping [...,*...] ... \stopgridsnapping
* inherits: \definegridsnappingOPT
```

`\starthboxestohbox ... \stop hboxestohbox`

$\backslash\mathrm{starthboxregister} \dots \backslash\mathrm{stophboxregister}$ * CSNAME NUMBER
$\backslash\mathrm{startHELP} [\dots] \dots \backslash\mathrm{stopHELP}$ * REFERENCE <small>OPT</small> instances: helptext
$\backslash\mathrm{starthelptext} [\dots] \dots \backslash\mathrm{stophelptext}$ * REFERENCE <small>OPT</small>
$\backslash\mathrm{starthhighlight} [\dots] \dots \backslash\mathrm{stophighlight}$ * NAME
$\backslash\mathrm{starthyphenation} [\dots, \dots] \dots \backslash\mathrm{stophyphenation}$ * original tex implicit hyphenate expanded traditional niciunul
$\backslash\mathrm{startimath} \dots \backslash\mathrm{stopimath}$
$\backslash\mathrm{startimpachetat} [\dots] \dots \backslash\mathrm{stopimpachetat}$ * blank <small>OPT</small>
$\backslash\mathrm{startindentedtext} [\dots] \dots \backslash\mathrm{stopindentedtext}$ * NAME
$\backslash\mathrm{startINDENTEDTEXT} \dots \backslash\mathrm{stopINDENTEDTEXT}$
$\backslash\mathrm{startingust} [\overset{1}{\dots}] [\dots, \dots, \overset{2}{\dots}] \dots \backslash\mathrm{stopingust}$ 1 NAME <small>OPT</small> <small>OPT</small> 2 inherits: \seteazaingust
$\backslash\mathrm{startingust} [\dots, \dots, \overset{1}{\dots}] [\dots, \dots, \overset{2}{\dots}] \dots \backslash\mathrm{stopingust}$ 1 inherits: \seteazaingust <small>OPT</small> <small>OPT</small> 2 [-+]stanga [-+]centru [-+]dreapta NUMBER*stanga NUMBER*centru NUMBER*dreapta reset reverse
$\backslash\mathrm{startingust} [\overset{1}{\dots}] [\dots, \overset{2}{\dots}] \dots \backslash\mathrm{stopingust}$ 1 NAME <small>OPT</small> <small>OPT</small> 2 [-+]stanga [-+]centru [-+]dreapta NUMBER*stanga NUMBER*centru NUMBER*dreapta reset reverse
$\backslash\mathrm{startinteractiune} [\dots] \dots \backslash\mathrm{stopinteractiune}$ * ascuns NAME
$\backslash\mathrm{startinterface} \dots \dots \backslash\mathrm{stopinterface}$ * tot SPRACHE
$\backslash\mathrm{startintertext} \dots \backslash\mathrm{stopintertext}$
$\backslash\mathrm{startitemgroup} [\overset{1}{\dots}] [\dots, \overset{2}{\dots}] [\dots, \dots, \overset{3}{\dots}] \dots \backslash\mathrm{stopitemgroup}$ 1 NAME <small>OPT</small> <small>OPT</small> 2 inherits: \setupitemgroup 3 inherits: \setupitemgroup
$\backslash\mathrm{startITEMGROUP} [\dots, \overset{1}{\dots}] [\dots, \dots, \overset{2}{\dots}] \dots \backslash\mathrm{stopITEMGROUP}$ 1 inherits: \setupitemgroup <small>OPT</small> <small>OPT</small> 2 inherits: \setupitemgroup instances: itemize
$\backslash\mathrm{startitemize} [\dots, \overset{1}{\dots}] [\dots, \dots, \overset{2}{\dots}] \dots \backslash\mathrm{stopitemize}$ 1 inherits: \setupitemgroup <small>OPT</small> <small>OPT</small> 2 inherits: \setupitemgroup

<pre> \startJScode <sup>1</sup>... <sup>2</sup>... <sup>3</sup>... \stopJScode 1  NAME 2  uses 3  NAME </pre>
<pre> \startJSreamble <sup>1</sup>... <sup>2</sup>... <sup>3</sup>... \stopJSreamble 1  NAME 2  folosit 3  now later </pre>
<pre> \startknockout ... \stopknockout </pre>
<pre> \startlayout [...]<sup>*</sup> ... \stoplayout *  NAME </pre>
<pre> \startlimba [...]<sup>*</sup> ... \stoplimba *  SPRACHE </pre>
<pre> \startlinealignment [...]<sup>*</sup> ... \stoplinealignment *  stanga centru dreapta max </pre>
<pre> \startlinecorrection [...]<sup>*</sup>...<sup>OPT</sup> ... \stoplinecorrection *  blank inherits: \blanc </pre>
<pre> \startlinefiller [...]<sup>1</sup> [...]<sup>2</sup>...<sup>OPT</sup>... \stoplinefiller 1  filler NAME 2  inherits: \setuplinefiller </pre>
<pre> \startLINENOTE [...]<sup>1</sup> {...}<sup>2</sup> 1  REFERENCE 2  TEXT instances: linenote </pre>
<pre> \startlinenote [...]<sup>1</sup> {...}<sup>2</sup> 1  REFERENCE 2  TEXT </pre>
<pre> \startlinenumbering [...]<sup>1</sup> [...]<sup>2</sup>...<sup>OPT</sup>...<sup>OPT</sup> \stoplinenumbering 1  NAME 2  continua = da nu    start   = NUMMER    pas     = NUMMER    metoda  = pagina primul urmatorul </pre>
<pre> \startlinenumbering [...]<sup>1</sup> [...]<sup>2</sup>... \stoplinenumbering 1  NAME 2  continuu NUMMER </pre>
<pre> \startlinetable ... \stoplinetable </pre>
<pre> \startlinetablebody ... \stoplinetablebody </pre>
<pre> \startlinetablecell [...]<sup>*</sup>...<sup>OPT</sup>... \stoplinetablecell *  inherits: \setuplinetable </pre>
<pre> \startlinetablehead ... \stoplinetablehead </pre>
<pre> \startlinie [...]<sup>*</sup> *  REFERENCE </pre>



$\backslash\text{startMPenvironment}$ [...] ... $\backslash\text{stopMPenvironment}$ *    reset global +                    OPT
$\backslash\text{startMPextensions}$ {...,*,...} ... $\backslash\text{stopMPextensions}$ *    NAME                                OPT
$\backslash\text{startMPinclusions}$ [ <sup>1</sup> ...] { <sup>2</sup> ...} ... $\backslash\text{stopMPinclusions}$ 1    +                                    OPT        OPT 2    NAME
$\backslash\text{startMPinitializations}$ ... $\backslash\text{stopMPinitializations}$
$\backslash\text{startMPpositiongraphic}$ { <sup>1</sup> ...} { <sup>2</sup> ...,...} ... $\backslash\text{stopMPpositiongraphic}$ 1    NAME    OPT 2    KEY
$\backslash\text{startMPpositionmethod}$ {...} ... $\backslash\text{stopMPpositionmethod}$ *    NAME
$\backslash\text{startMPrun}$ {...} ... $\backslash\text{stopMPrun}$ *    NAME                                OPT
$\backslash\text{startmakeup}$ [ <sup>1</sup> ] [..., <sup>2</sup> ...,...] ... $\backslash\text{stopmakeup}$ 1    NAME    OPT 2    inherits: \seteazamakeup
$\backslash\text{startMAKEUPmakeup}$ [...,*...,...] ... $\backslash\text{stopMAKEUPmakeup}$ *    inherits: \seteazamakeup                                OPT instances: standard page text middle
$\backslash\text{startmiddlemakeup}$ [...,*...,...] ... $\backslash\text{stopmiddlemakeup}$ *    inherits: \seteazamakeup                                OPT
$\backslash\text{startpagemakeup}$ [...,*...,...] ... $\backslash\text{stoppagemakeup}$ *    inherits: \seteazamakeup                                OPT
$\backslash\text{startstandardmakeup}$ [...,*...,...] ... $\backslash\text{stopstandardmakeup}$ *    inherits: \seteazamakeup                                OPT
$\backslash\text{starttextmakeup}$ [...,*...,...] ... $\backslash\text{stoptextmakeup}$ *    inherits: \seteazamakeup                                OPT
$\backslash\text{startmarginblock}$ [...] ... $\backslash\text{stopmarginblock}$ *    NAME    OPT
$\backslash\text{startmarkedcontent}$ [...] ... $\backslash\text{stopmarkedcontent}$ *    reset tot NAME    OPT
$\backslash\text{startmarkpages}$ [...] ... $\backslash\text{stopmarkpages}$ *    NAME
$\backslash\text{startMATHALIGNMENT}$ [...,*...,...] ... $\backslash\text{stopMATHALIGNMENT}$ *    inherits: \setupmathalignment <sup>OPT</sup> instances: align mathalignment
$\backslash\text{startalign}$ [...,*...,...] ... $\backslash\text{stopalign}$ *    inherits: \setupmathalignment <sup>OPT</sup>



$\backslash\mathrm{startmathalignment} [\dots\overset{*}{=}\dots] \dots \backslash\mathrm{stopmathalignment}$ * inherits: $\backslash\mathrm{setupmathalignment}^{\mathrm{OPT}}$
$\backslash\mathrm{startMATHCASES} [\dots\overset{*}{=}\dots] \dots \backslash\mathrm{stopMATHCASES}$ * inherits: $\backslash\mathrm{setupmathcases}^{\mathrm{OPT}}$ <b>instances:</b> <b>cases mathcases</b>
$\backslash\mathrm{startcases} [\dots\overset{*}{=}\dots] \dots \backslash\mathrm{stopcases}$ * inherits: $\backslash\mathrm{setupmathcases}^{\mathrm{OPT}}$
$\backslash\mathrm{startmathcases} [\dots\overset{*}{=}\dots] \dots \backslash\mathrm{stopmathcases}$ * inherits: $\backslash\mathrm{setupmathcases}^{\mathrm{OPT}}$
$\backslash\mathrm{startMATHMATRIX} [\dots\overset{*}{=}\dots] \dots \backslash\mathrm{stopMATHMATRIX}$ * inherits: $\backslash\mathrm{setupmathmatrix}^{\mathrm{OPT}}$ <b>instances:</b> <b>matrix mathmatrix</b>
$\backslash\mathrm{startmathmatrix} [\dots\overset{*}{=}\dots] \dots \backslash\mathrm{stopmathmatrix}$ * inherits: $\backslash\mathrm{setupmathmatrix}^{\mathrm{OPT}}$
$\backslash\mathrm{startmatrix} [\dots\overset{*}{=}\dots] \dots \backslash\mathrm{stopmatrix}$ * inherits: $\backslash\mathrm{setupmathmatrix}^{\mathrm{OPT}}$
$\backslash\mathrm{startmathmode} \dots \backslash\mathrm{stopmathmode}$
$\backslash\mathrm{startmathstyle} [\dots\overset{*}{=}\dots] \dots \backslash\mathrm{stopmathstyle}$ * display text script scriptscript cramped uncramped normal impachetat mic mare NAME
$\backslash\mathrm{startmatrices} [\dots\overset{*}{=}\dots] \dots \backslash\mathrm{stopmatrices}$ * inherits: $\backslash\mathrm{setupmathmatrix}^{\mathrm{OPT}}$
$\backslash\mathrm{startmaxaligned} \dots \backslash\mathrm{stopmaxaligned}$
$\backslash\mathrm{startmediu} [\dots\overset{*}{=}\dots] \dots \backslash\mathrm{stopmediu}$ * FILE *
$\backslash\mathrm{startmediu} \dots \dots \backslash\mathrm{stopmediu}$ * FILE *
$\backslash\mathrm{startmeniuinteractiune} [\dots\overset{*}{=}\dots] \dots \backslash\mathrm{stopmeniuinteractiune}$ * NAME
$\backslash\mathrm{startmiddlealigned} \dots \backslash\mathrm{stopmiddlealigned}$
$\backslash\mathrm{startmixedcolumns} [\overset{1}{\dots}] [\dots\overset{2}{=}\dots] \dots \backslash\mathrm{stopmixedcolumns}$ 1 NAME OPT OPT 2 inherits: $\backslash\mathrm{setupmixedcolumns}$
$\backslash\mathrm{startMIXEDCOLUMNS} [\dots\overset{*}{=}\dots] \dots \backslash\mathrm{stopMIXEDCOLUMNS}$ * inherits: $\backslash\mathrm{setupmixedcolumns}^{\mathrm{OPT}}$ <b>instances:</b> <b>itemgroupcolumns boxedcolumns</b>
$\backslash\mathrm{startboxedcolumns} [\dots\overset{*}{=}\dots] \dots \backslash\mathrm{stopboxedcolumns}$ * inherits: $\backslash\mathrm{setupmixedcolumns}^{\mathrm{OPT}}$
$\backslash\mathrm{startitemgroupcolumns} [\dots\overset{*}{=}\dots] \dots \backslash\mathrm{stopitemgroupcolumns}$ * inherits: $\backslash\mathrm{setupmixedcolumns}^{\mathrm{OPT}}$

<pre> \startmode [...,*...] ... \stopmode *   NAME </pre>
<pre> \startmodeset [...,<sup>1</sup>...] {<sup>2</sup>...} ... \stopmodeset 1   NAME implicit 2   CONTENT </pre>
<pre> \startmodule [...*] ... \stopmodule *   FILE </pre>
<pre> \startmoduletestsection ... \stopmoduletestsection </pre>
<pre> \startmodule ...* ... \stopmodule *   FILE </pre>
<pre> \startnamedsection [...,<sup>1</sup>] [...,<sup>2</sup>...<sub>OPT</sub>] [...,<sup>3</sup>...<sub>OPT</sub>] ... \stopnamedsection 1   ABSCHNITT 2   titlu           = TEXT     semncarte       = TEXT     marcaje         = TEXT     lista           = TEXT     referinta       = REFERENCE     numarpropriu    = TEXT 3   KEY = VALUE </pre>
<pre> \startnamedsubformulas [...,<sup>1</sup>...] {<sup>2</sup>...} ... \stopnamedsubformulas 1   + - REFERENCE <sub>OPT</sub> 2   TEXT </pre>
<pre> \startnarrower [...,*...] ... \stopnarrower *   [-+]stanga [-+]centru<sup>PT</sup>[-+]dreapta NUMMER*stanga NUMMER*centru NUMMER*dreapta reset reverse </pre>
<pre> \startNARROWER [...,*...] ... \stopNARROWER *   [-+]stanga [-+]centru<sup>PT</sup>[-+]dreapta NUMMER*stanga NUMMER*centru NUMMER*dreapta reset reverse </pre>
<pre> \startnegativ ... \stopnegativ </pre>
<pre> \startnicelyfilledbox [...,<sup>*</sup>...<sub>OPT</sub>] ... \stopnicelyfilledbox *   ltime = DIMENSION     inalttime = DIMENSION     offset = DIMENSION     strut = da nu </pre>
<pre> \startnointerference ... \stopnointerference </pre>
<pre> \startnotallmodes [...,*...] ... \stopnotallmodes *   NAME </pre>
<pre> \startNOTE [...,*...] ... \stopNOTE *   REFERENCE <sub>OPT</sub> instances: footnote endnote </pre>
<pre> \startNOTE [...,<sup>*</sup>...<sub>OPT</sub>] ... \stopNOTE *   titlu       = TEXT<sup>OPT</sup>     semncarte   = TEXT     lista       = TEXT     referinta   = REFERENCE instances: footnote endnote </pre>

<pre> \startendnote [...,*...] ... \stopendnote * titlu      = TEXT      OPT   semncarte  = TEXT   lista      = TEXT   referinta  = REFERENCE </pre>
<pre> \startfootnote [...,*...] ... \stopfootnote * titlu      = TEXT      OPT   semncarte  = TEXT   lista      = TEXT   referinta  = REFERENCE </pre>
<pre> \startendnote [...,*...] ... \stopendnote * REFERENCE      OPT </pre>
<pre> \startfootnote [...,*...] ... \stopfootnote * REFERENCE      OPT </pre>
<pre> \startnotext ... \stopnotext </pre>
<pre> \startnotmode [...,*...] ... \stopnotmode * NAME </pre>
<pre> \startopus ... \stopopus </pre>
<pre> \startoutputstream [...*] ... \stopoutputstream * NAME </pre>
<pre> \startoverlay ... \stopoverlay </pre>
<pre> \startoverprint ... \stopoverprint </pre>
<pre> \startpagecolumns [...,*...] ... \stoppagecolumns * inherits: \setuppagecolumns<sup>OPT</sup> </pre>
<pre> \startPAGECOLUMNS ... \stopPAGECOLUMNS </pre>
<pre> \startpagecolumns [...*] ... \stoppagecolumns * NAME      OPT </pre>
<pre> \startpagefigure [...<sup>1</sup>] [...,*<sup>2</sup>...] ... \stoppagefigure 1 FILE      OPT 2 offset = implicit overlay niciunul DIMENSION </pre>
<pre> \startpagelayout [...*] ... \stoppagelayout * pagina paginastanga paginadreaapta </pre>
<pre> \startpar [...<sup>1</sup>] [...,*<sup>2</sup>...] ... \stoppar 1 NAME      OPT      OPT 2 inherits: \setupparagraph </pre>
<pre> \startparagraf [...<sup>1</sup>] [...,*<sup>2</sup>...] ... \stopparagraf 1 NAME      OPT      OPT 2 inherits: \setupparagraph </pre>
<pre> \startparagraphs [...*] ... \stopparagraphs * NAME </pre>

<code>\startparagraphscell ... \stopparagraphscell</code>
<code>\startPARAGRAPHS ... \stopPARAGRAPHS</code>
<code>\startPARALLEL ... \stopPARALLEL</code>
<code>\startparbuilder [...]</code> ... <code>\stopparbuilder</code> * implicit oneline basic NAME
<code>\startplacefloat [...]</code> <sup>1</sup> <code>[...]</code> <sup>2</sup> <code>[...]</code> <sup>3</sup> <code>[...]</code> ... <code>\stopplacefloat</code> 1 SINGULAR OPT OPT 2 titlu = TEXT semncarte = TEXT marcaje = TEXT lista = TEXT locatie = split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva effective antet subsol referinta = REFERENCE 3 KEY = VALUE
<code>\startpuneFLOAT [...]</code> <sup>1</sup> <code>[...]</code> <sup>2</sup> <code>[...]</code> ... <code>\stoppuneFLOAT</code> 1 titlu = TEXT OPT OPT semncarte = TEXT marcaje = TEXT lista = TEXT locatie = split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva effective antet subsol referinta = REFERENCE 2 KEY = VALUE instances: chemical figure table intermezzo graphic
<code>\startpunechemical [...]</code> <sup>1</sup> <code>[...]</code> <sup>2</sup> <code>[...]</code> ... <code>\stoppunechemical</code> 1 titlu = TEXT OPT OPT semncarte = TEXT marcaje = TEXT lista = TEXT locatie = split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva effective antet subsol referinta = REFERENCE 2 KEY = VALUE
<code>\startpunefigure [...]</code> <sup>1</sup> <code>[...]</code> <sup>2</sup> <code>[...]</code> ... <code>\stoppunefigure</code> 1 titlu = TEXT OPT OPT semncarte = TEXT marcaje = TEXT lista = TEXT locatie = split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva effective antet subsol referinta = REFERENCE 2 KEY = VALUE

```

\startpunegraphic [...1...2...] ... \stoppunegraphic
1 titlu      = TEXT          OPT          OPT
  semncarte = TEXT
  marcaje   = TEXT
  lista     = TEXT
  locatie   = split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin
             marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge
             text opus reset inaltime adancime [--]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber
             niciunul local aici fortat margine [--]suspenda suspendat inalt ambele centru offset sus subsol auto
             pagina paginastanga paginadreapta undeva effective antet subsol
  referinta = REFERENCE
2 KEY = VALUE

```

```

\startpuneintermezzo [...1...2...] ... \stoppuneintermezzo
1 titlu      = TEXT          OPT          OPT
  semncarte = TEXT
  marcaje   = TEXT
  lista     = TEXT
  locatie   = split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin
             marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge
             text opus reset inaltime adancime [--]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber
             niciunul local aici fortat margine [--]suspenda suspendat inalt ambele centru offset sus subsol auto
             pagina paginastanga paginadreapta undeva effective antet subsol
  referinta = REFERENCE
2 KEY = VALUE

```

```

\startpunetable [...1...2...] ... \stoppunetable
1 titlu      = TEXT          OPT          OPT
  semncarte = TEXT
  marcaje   = TEXT
  lista     = TEXT
  locatie   = split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin
             marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge
             text opus reset inaltime adancime [--]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber
             niciunul local aici fortat margine [--]suspenda suspendat inalt ambele centru offset sus subsol auto
             pagina paginastanga paginadreapta undeva effective antet subsol
  referinta = REFERENCE
2 KEY = VALUE

```

```

\startplacepairedbox [...1...2...] ... \stopplacepairedbox
1 NAME          OPT
2 inherits: \setuppairedbox

```

```

\startpunePAIREDBOX [...*...] ... \stoppunePAIREDBOX
* inherits: \setuppairedbox OPT
instances: legend

```

```

\startpunelegend [...*...] ... \stoppunelegend
* inherits: \setuppairedbox OPT

```

```

\startpositioning [...1...2...] ... \stoppositioning
1 NAME          OPT          OPT
2 inherits: \setarepozitie

```

```

\startpositionoverlay {...} ... \stoppositionoverlay
* NAME

```

```

\startpositiv ... \stoppositiv

```

```

\startpostponing [...] ... \stoppostponing
* [--]NUMBER OPT

```

```

\startpostponingnotes ... \stoppostponingnotes

```

```

\startprocessassignmentcommand [...*...] ... \stopprocessassignmentcommand
* KEY = VALUE

```



<pre> \startreusableMPgraphic {...} {...<sup>2</sup>...} ... \stopreusableMPgraphic 1  NAME 2  KEY </pre>
<pre> \starttriglatext {...} ... \stoptriglatext *  TEXT </pre>
<pre> \startruby [...] ... \stopruby *  NAME </pre>
<pre> \startscript [...] ... \stopscrip *  hangul hanzi nihongo ethiopic thai test NAME </pre>
<pre> \startsectionblock [...<sup>1</sup>] [...<sup>2</sup>...<sup>2</sup>...] ... \stopsectionblock 1  NAME 2  semncarte = TEXT    inherits: \seteazablocsectionue </pre>
<pre> \startSECTIONBLOCK [...<sup>*</sup>...<sup>*</sup>...] ... \stopSECTIONBLOCK *  semncarte = TEXT    inherits: \seteazablocsectionue instances: frontmatter bodymatter appendices backmatter </pre>
<pre> \startappendices [...<sup>*</sup>...<sup>*</sup>...] ... \stopappendices *  semncarte = TEXT    inherits: \seteazablocsectionue </pre>
<pre> \startbackmatter [...<sup>*</sup>...<sup>*</sup>...] ... \stopbackmatter *  semncarte = TEXT    inherits: \seteazablocsectionue </pre>
<pre> \startbodymatter [...<sup>*</sup>...<sup>*</sup>...] ... \stopbodymatter *  semncarte = TEXT    inherits: \seteazablocsectionue </pre>
<pre> \startfrontmatter [...<sup>*</sup>...<sup>*</sup>...] ... \stopfrontmatter *  semncarte = TEXT    inherits: \seteazablocsectionue </pre>
<pre> \startsectionlevel [...<sup>1</sup>...] [...<sup>2</sup>...<sup>2</sup>...] [...<sup>3</sup>...<sup>3</sup>...] ... \stopsectionlevel 1  NAME 2  titlu      = TEXT    semncarte  = TEXT    marcaje   = TEXT    lista     = TEXT    referinta  = REFERENCE    numarpropriu = TEXT 3  KEY = VALUE </pre>
<pre> \startSECTION [...<sup>1</sup>...<sup>1</sup>...] [...<sup>2</sup>...<sup>2</sup>...] ... \stopSECTION 1  titlu      = TEXT    semncarte  = TEXT    marcaje   = TEXT    lista     = TEXT    referinta  = REFERENCE    numarpropriu = TEXT 2  KEY = VALUE instances: part chapter section subsection subsubsection subsubsubsection subsubsubsubsection title subject subsubject subsubsubject subsubsubsubject subsubsubsubsubject </pre>

```

\startchapter [...1...2...] ... \stopchapter
1 titlu          = TEXTOPT
  semncarte      = TEXT
  marcaje        = TEXT
  lista          = TEXT
  referinta      = REFERENCE
  numarpropriu   = TEXT
2 KEY = VALUE

```

```

\startpart [...1...2...] ... \stoppart
1 titlu          = TEXTOPT
  semncarte      = TEXT
  marcaje        = TEXT
  lista          = TEXT
  referinta      = REFERENCE
  numarpropriu   = TEXT
2 KEY = VALUE

```

```

\startsection [...1...2...] ... \stopsection
1 titlu          = TEXTOPT
  semncarte      = TEXT
  marcaje        = TEXT
  lista          = TEXT
  referinta      = REFERENCE
  numarpropriu   = TEXT
2 KEY = VALUE

```

```

\startsubject [...1...2...] ... \stopsubject
1 titlu          = TEXTOPT
  semncarte      = TEXT
  marcaje        = TEXT
  lista          = TEXT
  referinta      = REFERENCE
  numarpropriu   = TEXT
2 KEY = VALUE

```

```

\startsubsection [...1...2...] ... \stopsubsection
1 titlu          = TEXTOPT
  semncarte      = TEXT
  marcaje        = TEXT
  lista          = TEXT
  referinta      = REFERENCE
  numarpropriu   = TEXT
2 KEY = VALUE

```

```

\startsubsubject [...1...2...] ... \stopsubsubject
1 titlu          = TEXTOPT
  semncarte      = TEXT
  marcaje        = TEXT
  lista          = TEXT
  referinta      = REFERENCE
  numarpropriu   = TEXT
2 KEY = VALUE

```

```

\startsubsubsection [...1...2...] ... \stopsubsubsection
1 titlu          = TEXTOPT
  semncarte      = TEXT
  marcaje        = TEXT
  lista          = TEXT
  referinta      = REFERENCE
  numarpropriu   = TEXT
2 KEY = VALUE

```

```

\startsubsubsubject [...1...2...] ... \stopsubsubsubject
1 titlu          = TEXTOPT
  semncarte      = TEXT
  marcaje        = TEXT
  lista          = TEXT
  referinta      = REFERENCE
  numarpropriu   = TEXT
2 KEY = VALUE

```



<pre> \startsubsubsubsection [...,\subsubsubsec<sup>1</sup>...,...] [...,\subsubsubsec<sup>2</sup>...,...] ... \stopsubsubsubsection 1  titlu           = TEXT     semncarte      = TEXT     marcaje        = TEXT     lista          = TEXT     referinta      = REFERENCE     numarpropriu   = TEXT 2  KEY = VALUE </pre>
<pre> \startsubsubsubsubject [...,\subsubsubsub<sup>1</sup>...,...] [...,\subsubsubsub<sup>2</sup>...,...] ... \stopsubsubsubsubject 1  titlu           = TEXT     semncarte      = TEXT     marcaje        = TEXT     lista          = TEXT     referinta      = REFERENCE     numarpropriu   = TEXT 2  KEY = VALUE </pre>
<pre> \startsubsubsubsubsubsection [...,\subsubsubsubsub<sup>1</sup>...,...] [...,\subsubsubsubsub<sup>2</sup>...,...] ... \stopsubsubsubsubsubsection 1  titlu           = TEXT     semncarte      = TEXT     marcaje        = TEXT     lista          = TEXT     referinta      = REFERENCE     numarpropriu   = TEXT 2  KEY = VALUE </pre>
<pre> \startsubsubsubsubsubsubject [...,\subsubsubsubsubsub<sup>1</sup>...,...] [...,\subsubsubsubsubsub<sup>2</sup>...,...] ... \stopsubsubsubsubsubsubject 1  titlu           = TEXT     semncarte      = TEXT     marcaje        = TEXT     lista          = TEXT     referinta      = REFERENCE     numarpropriu   = TEXT 2  KEY = VALUE </pre>
<pre> \starttitle [...,\subsubsubsubsubsub<sup>1</sup>...,...] [...,\subsubsubsubsubsub<sup>2</sup>...,...] ... \stoptitle 1  titlu           = TEXT     semncarte      = TEXT     marcaje        = TEXT     lista          = TEXT     referinta      = REFERENCE     numarpropriu   = TEXT 2  KEY = VALUE </pre>
<pre> \startsetups [...,\subsubsubsubsubsub<sup>1</sup>...,...] [...,\subsubsubsubsubsub<sup>2</sup>...,...] ... \stopsetups 1  grila           = TEXT 2  NAME </pre>
<pre> \startsetups ... .. \stopsetups *  NAME </pre>
<pre> \startshift [...,\subsubsubsubsubsub<sup>1</sup>...,...] ... \stopshift *  NAME </pre>
<pre> \startsidebar [...,\subsubsubsubsubsub<sup>1</sup>...,...] [...,\subsubsubsubsubsub<sup>2</sup>...,...] ... \stopsidebar 1  NAME           = TEXT 2  inherits: \setupsidebar </pre>
<pre> \startsimplecolumns [...,\subsubsubsubsubsub<sup>1</sup>...,...] ... \stopsimplecolumns *  inherits: \setsimplecolumnhsides </pre>
<pre> \startspecialitem [...,\subsubsubsubsubsub<sup>1</sup>...,...] [...,\subsubsubsubsubsub<sup>2</sup>...,...] ... \stopspecialitem 1  element        = TEXT 2  REFERENCE </pre>

`\startspecialitem [...] ... \stopspecialitem`

`\startspecialitem [...]1 {...}2 ... \stopspecialitem`

$$\backslash\mathrm{startsplitsformula} \dots \backslash\mathrm{stopsplitsformula}$$

`\startspread ... \stopspread`

```
\startstaticMPfigure {...} ... \stopstaticMPfigure
```

$$\backslash\mathrm{startstaticMPgraphic}\{\dots\}\{\dots,\dots\}\dots\backslash\mathrm{stopstaticMPgraphic}$$
$$\backslash STARTSTOP \{.\dots\}$$

```
\startstrictinspectnextcharacter ... \stopstrictinspectnextcharacter
```

$$\text{\texttt{\textbackslash startstyle [...] ... \textbackslash stopstyle}}$$

`\startstyle [...] ... \stopstyle`

`\startSTYLE ... \stopSTYLE`

$$\backslash\text{startsubjectlevel } [\dots] [\dots, \dots^2 \dots, \dots] [\dots, \dots^3 \dots, \dots] \dots \backslash\text{stopsubjectlevel}$$

<code>\startsubsentence ... \stopsubsentence</code>
<code>\startsubsoltabel [...]</code> ... <code>\stopsubsoltabel</code> *    NAME
<code>\startsubstack ... \stopsubstack</code>
<code>\startsuspendat [...<sup>1</sup>...<sup>2</sup>...] {...}</code> ... <code>\stopsuspendat</code> 1 <code>distanta</code> = DIMENSION    OPT <code>n</code> = NUMMER <code>locatie</code> = stanga dreapta 2    CONTENT
<code>\startsuspendat [...<sup>1</sup>] {...<sup>2</sup>}</code> ... <code>\stopsuspendat</code> 1 <code>stanga dreapta</code> OPT 2    CONTENT
<code>\startsymbolset [...<sup>1</sup>] [...<sup>2</sup>...]<sup>2</sup>...</code> ... <code>\stopsymbolset</code> 1    NAME                            OPT 2 <code>font</code> = FONT
<code>\startTABLE [...<sup>*</sup>...]<sup>*</sup>...</code> ... <code>\stopTABLE</code> *    inherits: <code>\setupTABLE</code>
<code>\startTABLEbody [...<sup>*</sup>...]<sup>*</sup>...</code> ... <code>\stopTABLEbody</code> *    inherits: <code>\setupTABLE</code> OPT
<code>\startTABLEfoot [...<sup>*</sup>...]<sup>*</sup>...</code> ... <code>\stopTABLEfoot</code> *    inherits: <code>\setupTABLE</code> OPT
<code>\startTABLEhead [...<sup>*</sup>...]<sup>*</sup>...</code> ... <code>\stopTABLEhead</code> *    inherits: <code>\setupTABLE</code> OPT
<code>\startTABLEnext [...<sup>*</sup>...]<sup>*</sup>...</code> ... <code>\stopTABLEnext</code> *    inherits: <code>\setupTABLE</code> OPT
<code>\starttabelele [ ... ]</code> ... <code>\stoptabelele</code> *    TEMPLATE
<code>\starttabelele [...]</code> ... <code>\stoptabelele</code> *    NAME
<code>\starttabelul [ ... ] [...<sup>2</sup>...]<sup>2</sup>...</code> ... <code>\stoptabelul</code> 1    TEMPLATE                            OPT 2    inherits: <code>\seteazatabele</code>
<code>\starttabelul [...<sup>1</sup>] [...<sup>2</sup>...]<sup>2</sup>...</code> ... <code>\stoptabelul</code> 1    NAME                            OPT 2    inherits: <code>\seteazatabele</code>
<code>\starttabulate [/.<sup>1</sup>/] [...<sup>2</sup>...]<sup>2</sup>...</code> ... <code>\stoptabulate</code> 1    TEMPLATE                            OPT                            OPT 2    inherits: <code>\seteazatabulatori</code>
<code>\starttabulatehead [...<sup>*</sup>]...</code> ... <code>\stoptabulatehead</code> *    NAME                            OPT
<code>\starttabulatetail [...<sup>*</sup>]...</code> ... <code>\stoptabulatetail</code> *    NAME                            OPT

$\backslash\text{startTABULATE} [\text{...}] [\text{...}, \text{...} \overset{2}{=}\text{...}, \text{...}] \dots \backslash\text{stopTABULATE}$ 1    NAME                    OPT                    OPT 2    inherits: \seteazatabulatori instances: legend fact
$\backslash\text{startfact} [\text{...}] [\text{...}, \text{...} \overset{2}{=}\text{...}, \text{...}] \dots \backslash\text{stopfact}$ 1    NAME                    OPT                    OPT 2    inherits: \seteazatabulatori
$\backslash\text{startlegend} [\text{...}] [\text{...}, \text{...} \overset{2}{=}\text{...}, \text{...}] \dots \backslash\text{stoplegend}$ 1    NAME                    OPT                    OPT 2    inherits: \seteazatabulatori
$\backslash\text{startTABULATION} [\text{...}] [\text{...}, \text{...} \overset{2}{=}\text{...}, \text{...}] \dots \backslash\text{stopTABULATION}$ 1    NAME                    OPT                    OPT 2    inherits: \setuptabulation
$\backslash\text{starttexcode} \dots \backslash\text{stoptexcode}$
$\backslash\text{starttexdefinition} \overset{1}{\dots} \overset{2}{\dots} \overset{3}{\dots} \overset{4}{\dots} \overset{5}{\dots} \overset{6}{\dots} \overset{7}{\dots} \dots \backslash\text{stoptexdefinition}$ 1    spaces nospaces                    OPT    OPT    OPT    OPT    OPT    OPT    OPT 2    global 3    unexpanded 4    expanded 5    singleempty doubleempty tripleempty quadrupleempty quintupleempty sextupleempty singleargument doubleargument tripleargument quadrupleargument quintupleargument sextupleargument 6    NAME 7    TEMPLATE
$\backslash\text{starttext} \dots \backslash\text{stoptext}$
$\backslash\text{starttextajutator} [\text{...}] \dots \backslash\text{stoptextajutator}$ *    REFERENCE                    OPT
$\backslash\text{starttextbackground} [\text{...}] [\text{...}, \text{...} \overset{2}{=}\text{...}, \text{...}] \dots \backslash\text{stoptextbackground}$ 1    NAME                    OPT 2    inherits: \setuptextbackground
$\backslash\text{starttextbackgroundmanual} \dots \backslash\text{stoptextbackgroundmanual}$
$\backslash\text{startTEXTBACKGROUND} [\text{...}, \text{...} \overset{*}{=}\text{...}, \text{...}] \dots \backslash\text{stopTEXTBACKGROUND}$ *    inherits: \setuptextbackground OPT
$\backslash\text{starttextcolor} [\text{...}] \dots \backslash\text{stoptextcolor}$ *    COLOR
$\backslash\text{starttextcolorintent} \dots \backslash\text{stoptextcolorintent}$
$\backslash\text{startLABELtext} [\text{...}] [\text{...}] \dots \backslash\text{stopLABELtext}$ 1    SPRACHE                    OPT 2    KEY instances: head label mathlabel taglabel unit operator prefix suffix btxlabel
$\backslash\text{startbtxlabeltext} [\text{...}] [\text{...}] \dots \backslash\text{stopbtxlabeltext}$ 1    SPRACHE                    OPT 2    KEY
$\backslash\text{startheadtext} [\text{...}] [\text{...}] \dots \backslash\text{stopheadtext}$ 1    SPRACHE                    OPT 2    KEY

$\backslash\text{startlabeltext}$ [...] [ <sup>1</sup> ...] [...] ... $\backslash\text{stoplabeltext}$ 1    SPRACHE                    OPT 2    KEY
$\backslash\text{startmathlabeltext}$ [...] [ <sup>1</sup> ...] [...] ... $\backslash\text{stopmathlabeltext}$ 1    SPRACHE                    OPT 2    KEY
$\backslash\text{startoperatortext}$ [...] [ <sup>1</sup> ...] [...] ... $\backslash\text{stopoperatortext}$ 1    SPRACHE                    OPT 2    KEY
$\backslash\text{startprefixtext}$ [...] [ <sup>1</sup> ...] [...] ... $\backslash\text{stopprefixtext}$ 1    SPRACHE                    OPT 2    KEY
$\backslash\text{startsuffixtext}$ [...] [ <sup>1</sup> ...] [...] ... $\backslash\text{stopsuffixtext}$ 1    SPRACHE                    OPT 2    KEY
$\backslash\text{starttaglabeltext}$ [...] [ <sup>1</sup> ...] [...] ... $\backslash\text{stoptaglabeltext}$ 1    SPRACHE                    OPT 2    KEY
$\backslash\text{startunittext}$ [...] [ <sup>1</sup> ...] [...] ... $\backslash\text{stopunittext}$ 1    SPRACHE                    OPT 2    KEY
$\backslash\text{starttextflow}$ [...] ... $\backslash\text{stoptextflow}$ *    NAME
$\backslash\text{startFRAMEDTEXT}$ [...] [...] [ <sup>1</sup> ...] [...] [ <sup>2</sup> ...] [...] ... $\backslash\text{stopFRAMEDTEXT}$ 1    stanga dreapta centr@Pniciunul                    OPT 2    inherits: \setupframedtext <b>instances: framedtext</b>
$\backslash\text{startframedtext}$ [...] [...] [ <sup>1</sup> ...] [...] [ <sup>2</sup> ...] [...] ... $\backslash\text{stopframedtext}$ 1    stanga dreapta centr@Pniciunul                    OPT 2    inherits: \setupframedtext
$\backslash\text{starttitlu}$ [...] [ <sup>1</sup> ...] [...] { <sup>2</sup> ...} ... $\backslash\text{stoptitlu}$ 1    REFERENCE                    OPT 2    TEXT
$\backslash\text{starttokenlist}$ [...] ... $\backslash\text{stoptokenlist}$ *    NAME
$\backslash\text{starttokens}$ [...] ... $\backslash\text{stoptokens}$ *    NAME
$\backslash\text{starttransparent}$ [...] ... $\backslash\text{stoptransparent}$ *    COLOR
$\backslash\text{starttypescript}$ [...] [ <sup>1</sup> ...] [...] [ <sup>2</sup> ...] [...] [ <sup>3</sup> ...] [...] ... $\backslash\text{stoptypescript}$ 1    serif sans mono math handwriting calligraphy                    OPT 2    NAME 3    size nume
$\backslash\text{starttypescriptcollection}$ [...] ... $\backslash\text{stoptypescriptcollection}$ *    NAME

<pre> \startTYPING [...,*=...,...] ... \stopTYPING * inherits: \seteazatyping<sup>OPT</sup> instances: typing LUA MP PARSEDXML TEX XML </pre>
<pre> \startTYPING [...,*=...,...] ... \stopTYPING * continuu<sup>OPT</sup> instances: typing LUA MP PARSEDXML TEX XML </pre>
<pre> \startLUA [...,*=...,...] ... \stopLUA * continuu<sup>OPT</sup> </pre>
<pre> \startMP [...,*=...,...] ... \stopMP * continuu<sup>OPT</sup> </pre>
<pre> \startPARSEDXML [...,*=...,...] ... \stopPARSEDXML * continuu<sup>OPT</sup> </pre>
<pre> \startTEX [...,*=...,...] ... \stopTEX * continuu<sup>OPT</sup> </pre>
<pre> \starttyping [...,*=...,...] ... \stoptyping * continuu<sup>OPT</sup> </pre>
<pre> \startXML [...,*=...,...] ... \stopXML * continuu<sup>OPT</sup> </pre>
<pre> \startLUA [...,*=...,...] ... \stopLUA * inherits: \seteazatyping<sup>OPT</sup> </pre>
<pre> \startMP [...,*=...,...] ... \stopMP * inherits: \seteazatyping<sup>OPT</sup> </pre>
<pre> \startPARSEDXML [...,*=...,...] ... \stopPARSEDXML * inherits: \seteazatyping<sup>OPT</sup> </pre>
<pre> \startTEX [...,*=...,...] ... \stopTEX * inherits: \seteazatyping<sup>OPT</sup> </pre>
<pre> \starttyping [...,*=...,...] ... \stoptyping * inherits: \seteazatyping<sup>OPT</sup> </pre>
<pre> \startXML [...,*=...,...] ... \stopXML * inherits: \seteazatyping<sup>OPT</sup> </pre>
<pre> \startuniqueMPgraphic {...} {...,<sup>2</sup>...} ... \stopuniqueMPgraphic 1 NAME<sup>1</sup> 2 KEY<sup>OPT</sup> </pre>
<pre> \startuniqueMPpagegraphic {...} {...,<sup>2</sup>...} ... \stopuniqueMPpagegraphic 1 NAME<sup>1</sup> 2 KEY<sup>OPT</sup> </pre>
<pre> \startusableMPgraphic {...} {...,<sup>2</sup>...} ... \stopusableMPgraphic 1 NAME<sup>1</sup> 2 KEY<sup>OPT</sup> </pre>

$\backslash\text{startuseMPgraphic}$ <sup>1</sup> {...} <sup>2</sup> {...,...} ... $\backslash\text{stopuseMPgraphic}$ 1 NAME OPT 2 KEY
$\backslash\text{startusemathstyleparameter}$ \.* ... $\backslash\text{stopusemathstyleparameter}$ * CSNAME
$\backslash\text{startuserdata}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...,... <sup>2</sup> ...,...] ... $\backslash\text{stopuserdata}$ 1 NAME OPT OPT 2 KEY = VALUE
$\backslash\text{startusingbtxs specification}$ [ <sup>*</sup> ...] ... $\backslash\text{stopusingbtxs specification}$ * NAME
$\backslash\text{startvboxregister}$ \.* ... $\backslash\text{stopvboxregister}$ * CSNAME NUMMER
$\backslash\text{startvboxto hbox}$ ... $\backslash\text{stopvboxto hbox}$
$\backslash\text{startvboxto hbox separator}$ ... $\backslash\text{stopvboxto hbox separator}$
$\backslash\text{startviewerlayer}$ [ <sup>*</sup> ...] ... $\backslash\text{stopviewerlayer}$ * NAME
$\backslash\text{startVIEWERLAYER}$ ... $\backslash\text{stopVIEWERLAYER}$
$\backslash\text{startvtopregister}$ \.* ... $\backslash\text{stopvtopregister}$ * CSNAME NUMMER
$\backslash\text{startxcell}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...,... <sup>2</sup> ...,...] ... $\backslash\text{stopxcell}$ 1 NAME OPT OPT 2 nx = NUMMER ny = NUMMER nc = NUMMER nr = NUMMER inherits: \setupxtable
$\backslash\text{startxcellgroup}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...,... <sup>2</sup> ...,...] ... $\backslash\text{stopxcellgroup}$ 1 NAME OPT OPT 2 inherits: \setupxtable
$\backslash\text{startxcolumn}$ [ <sup>*</sup> ...,... <sup>*</sup> ...,...] ... $\backslash\text{stopxcolumn}$ * inherits: \setupxtable <sup>PT</sup>
$\backslash\text{startxcolumn}$ [ <sup>*</sup> ...] ... $\backslash\text{stopxcolumn}$ * NAME OPT
$\backslash\text{startxgroup}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...,... <sup>2</sup> ...,...] ... $\backslash\text{stopxgroup}$ 1 NAME OPT OPT 2 inherits: \setupxtable
$\backslash\text{startxmldisplayverbatim}$ [ <sup>*</sup> ...] ... $\backslash\text{stopxmldisplayverbatim}$ * NAME
$\backslash\text{startxmllineverbatim}$ [ <sup>*</sup> ...] ... $\backslash\text{stopxmllineverbatim}$ * NAME
$\backslash\text{startxmlraw}$ ... $\backslash\text{stopxmlraw}$

$\backslash\text{startxmlsetups}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...] ... $\backslash\text{stopxmlsetups}$ 1 grila OPT 2 NAME
$\backslash\text{startxmlsetups}$ ... $\backslash\text{stopxmlsetups}$ * NAME
$\backslash\text{startxrow}$ [ <sup>1</sup> ...] [..., <sup>2</sup> ...,...] ... $\backslash\text{stopxrow}$ 1 NAME OPT OPT 2 inherits: \setupxtable
$\backslash\text{startxrowgroup}$ [ <sup>1</sup> ...] [..., <sup>2</sup> ...,...] ... $\backslash\text{stopxrowgroup}$ 1 NAME OPT OPT 2 inherits: \setupxtable
$\backslash\text{startxtable}$ [..., <sup>*</sup> ...,...] ... $\backslash\text{stopxtable}$ * inherits: \setupxtable
$\backslash\text{startxtablebody}$ [..., <sup>*</sup> ...,...] ... $\backslash\text{stopxtablebody}$ * inherits: \setupxtable OPT
$\backslash\text{startxtablebody}$ [...] ... $\backslash\text{stopxtablebody}$ * NAME OPT
$\backslash\text{startxtablefoot}$ [..., <sup>*</sup> ...,...] ... $\backslash\text{stopxtablefoot}$ * inherits: \setupxtable OPT
$\backslash\text{startxtablefoot}$ [...] ... $\backslash\text{stopxtablefoot}$ * NAME OPT
$\backslash\text{startxtablehead}$ [..., <sup>*</sup> ...,...] ... $\backslash\text{stopxtablehead}$ * inherits: \setupxtable OPT
$\backslash\text{startxtablehead}$ [...] ... $\backslash\text{stopxtablehead}$ * NAME OPT
$\backslash\text{startxtablenext}$ [..., <sup>*</sup> ...,...] ... $\backslash\text{stopxtablenext}$ * inherits: \setupxtable OPT
$\backslash\text{startxtablenext}$ [...] ... $\backslash\text{stopxtablenext}$ * NAME OPT
$\backslash\text{startXTABLE}$ [..., <sup>*</sup> ...,...] ... $\backslash\text{stopXTABLE}$ * inherits: \setupxtable OPT
$\backslash\text{startxtable}$ [...] ... $\backslash\text{stopxtable}$ * NAME OPT
$\backslash\text{stivacampuri}$ [ <sup>1</sup> ] [..., <sup>2</sup> ...] [..., <sup>3</sup> ...,...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupfieldcategory
$\backslash\text{stopLINENOTE}$ [...] * REFERENCE instances: linenote



\stoplinenote [...] *   REFERENCE
\stoplinie [...] *   REFERENCE
\stopregister [...] [...] 1   NAME 2   NAME
\stopstructurepageregister [...] [...] 1   NAME 2   NAME
\strictdoifelsenextoptional {...} {...} 1   TRUE 2   FALSE
\strictdoifnextoptionalelse {...} {...} 1   TRUE 2   FALSE
\stripcharacter ... \from ... \to ... 1   CHARACTER 2   TEXT 3   CSNAME
\strippedcsname \*... *   CSNAME
\strippedcsname ... *   TEXT
\stripspaces \from ... \to ... 1   TEXT 2   CSNAME
\structurelistuservariable {...} *   KEY
\structurenumber
\structuretitle
\structureuservariable {...} *   KEY
\structurevariable {...} *   KEY
\strut
\strutdp
\strutgap
\strutht

<code>\struthtdp</code>
<code>\struttedbox {...}</code> <code>* CONTENT</code>
<code>\strutwd</code>
<code>\style [...<sup>1</sup>...<sup>2</sup>...] {...}</code> <code>1 inherits: \setupstyle</code> <code>2 TEXT</code>
<code>\styleinstance [...]</code> <code>* NAME</code>
<code>\style [...<sup>1</sup>] {...<sup>2</sup>}</code> <code>1 NAME FONT</code> <code>2 TEXT</code>
<code>\STYLE {...}</code> <code>* TEXT</code>
<code>\subpagenumber</code>
<code>\subsentence {...}</code> <code>* CONTENT</code>
<code>\substituteincommalist {...<sup>1</sup>} {...<sup>2</sup>} \...<sup>3</sup></code> <code>1 TEXT</code> <code>2 TEXT</code> <code>3 CSNAME</code>
<code>\subtractfeature [...]</code> <code>* NAME</code>
<code>\subtractfeature {...}</code> <code>* NAME</code>
<code>\swapcounts \...<sup>1</sup> \...<sup>2</sup></code> <code>1 CSNAME</code> <code>2 CSNAME</code>
<code>\swapdimens \...<sup>1</sup> \...<sup>2</sup></code> <code>1 CSNAME</code> <code>2 CSNAME</code>
<code>\swapface</code>
<code>\swapmacros \...<sup>1</sup> \...<sup>2</sup></code> <code>1 CSNAME</code> <code>2 CSNAME</code>
<code>\swaptypeface</code>
<code>\switchstyleonly [...]</code> <code>* rm ss tt hw cg roman serif regular sans sansserif suport type teletype mono scrismanual caligrafic</code>
<code>\switchstyleonly \...<sup>1</sup></code> <code>* CSNAME</code>

\* COLOR

```
1 NAME OPT
2 inherits: \seteazaspatiuinterliniar
```

```
* on dezactivat reset auto mic mediu mare NUMMER DIMENSION
```

\* NAME

## \* REFERENCE

---

---

1	BESCHRIFTUNG	OPT
2	NUMMER	
3	mentine	

\* NAME

```
* da nu auto cap ajustat linie implicit CHARACTER
```

---

\* FILE

---

\* FILE

1	NAME	OPT
2	TEXT	
3	CONTENT	

---

```

1  NAME          OPT
2  TEXT
3  CONTENT

```

```

1  FILE
2  TEXT
3  TEXT

```

<code>\systemlogfirst {...} {...} {...}</code> 1 FILE 2 TEXT 3 TEXT
<code>\systemloglast {...} {...} {...}</code> 1 FILE 2 TEXT 3 TEXT
<code>\systemsetups {...}</code> * NAME
<code>\TABLE</code>
<code>\TaBlE</code>
<code>\TEX</code>
<code>\TeX</code>
<code>\TheNormalizedFontSize</code>
<code>\TransparencyHack</code>
<code>\tabulateautoline</code>
<code>\tabulateautorule</code>
<code>\tabulateline</code>
<code>\tabulaterule</code>
<code>\taggedctxcommand {...}</code> * BEFEHL
<code>\taggedlabeltexts {...} {...} {...}</code> 1 NAME 2 NAME 3 CONTENT
<code>\tbox {...}</code> * CONTENT
<code>\testandsplitstring ... \at ... \to ... \and ...</code> 1 TEXT 2 TEXT 3 CSNAME 4 CSNAME
<code>\testcolumn [...] [...]</code> 1 NUMMER OPT 2 DIMENSION
<code>\testfeature {...} {...}</code> 1 NUMMER 2 CONTENT

<pre> \testfeatureonce {...} {...} 1  NUMBER 2  CONTENT </pre>
<pre> \testpage [...] [...] 1  NUMBER          OPT 2  DIMENSION </pre>
<pre> \testpageonly [...] [...] 1  NUMBER          OPT 2  DIMENSION </pre>
<pre> \testpagesync [...] [...] 1  NUMBER          OPT 2  DIMENSION </pre>
<pre> \testtokens [...] *  NAME </pre>
<pre> \tex {...} *  CONTENT </pre>
<pre> \texdefinition {...} *  NAME </pre>
<pre> \texsetup {...} *  NAME </pre>
<pre> \textajutator [...] {...} {...} 1  REFERENCE      OPT 2  TEXT 3  TEXT </pre>
<pre> \TEXTBACKGROUND {...} *  CONTENT </pre>
<pre> \textcitation [...,...<sup>1</sup>...,...] [...] 1  referinta  = REFERENCE     alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum                 authorityyear     inainte   = BEFEHL     dupa      = BEFEHL     stanga    = BEFEHL     dreapta   = BEFEHL     inherits: \setupbtx 2  REFERENCE </pre>
<pre> \textcitation [...<sup>1</sup>] [...<sup>2</sup>] 1  implicit category<sup>OPT</sup>entry short pagina num textnum an index tag keywords autor authoryears authornum authorityyear 2  REFERENCE </pre>
<pre> \textcitation [...,...<sup>1</sup>...,...] [...,...<sup>2</sup>...,...] 1  referinta  = REFERENCE     alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum                 authorityyear     inainte   = BEFEHL     dupa      = BEFEHL     stanga    = BEFEHL     dreapta   = BEFEHL     inherits: \setupbtx 2  KEY  = VALUE </pre>

```

\textcite [...1...2] [...]
1  referinta    = REFERENCE
   alternativ    = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
                  authoryear
   inainte      = BEFEHL
   dupa         = BEFEHL
   stanga       = BEFEHL
   dreapta      = BEFEHL
   inherits:    \setupbtx
2  REFERENCE

```

```

\textcite [...1] [...2]
1  implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear
2  REFERENCE

```

```

\textcite [...1...2] [...2...1]
1  referinta    = REFERENCE
   alternativ    = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
                  authoryear
   inainte      = BEFEHL
   dupa         = BEFEHL
   stanga       = BEFEHL
   dreapta      = BEFEHL
   inherits:    \setupbtx
2  KEY = VALUE

```

```

\textcontrolsplace

```

```

\LABELtext {...}
*  KEY
instances: head label mathlabel taglabel unit operator prefix suffix btxlabel

```

```

\btxlabeltext {...}
*  KEY

```

```

\headtext {...}
*  KEY

```

```

\labeltext {...}
*  KEY

```

```

\mathlabeltext {...}
*  KEY

```

```

\operatortext {...}
*  KEY

```

```

\prefixtext {...}
*  KEY

```

```

\suffixtext {...}
*  KEY

```

```

\taglabeltext {...}
*  KEY

```

```

\unittext {...}
*  KEY

```

```

\textflowcollector {...}
*  NAME

```

$\backslash$ FRAMEDTEXT [... <sup>1</sup> ... <sup>2</sup> ] {...} 1 inherits: \setupframedtext 2 CONTENT instances: framedtext
$\backslash$ framedtext [... <sup>1</sup> ... <sup>2</sup> ] {...} 1 inherits: \setupframedtext 2 CONTENT
$\backslash$ textmath {...} * CONTENT
$\backslash$ textminus
$\backslash$ textormathchar {...} * NUMMER
$\backslash$ textormathchars {...} * CHARACTER
$\backslash$ textplus
$\backslash$ textumplere [... <sup>1</sup> ... <sup>2</sup> ] <sup>3</sup> {...} {...} 1 inherits: \setezarigtextumplere OPT OPT 2 TEXT 3 TEXT
$\backslash$ textvisiblespace
$\backslash$ thainumerals {...} * NUMMER
$\backslash$ thefirstcharacter {...} * TEXT
$\backslash$ thenormalizedbodyfontsize {...} * DIMENSION
$\backslash$ theremainingcharacters {...} * TEXT
$\backslash$ thickspace
$\backslash$ thinspace
$\backslash$ thirdoffivearguments {... <sup>1</sup> } {... <sup>2</sup> } {... <sup>3</sup> } {... <sup>4</sup> } {... <sup>5</sup> } 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT
$\backslash$ thirdoffourarguments {... <sup>1</sup> } {... <sup>2</sup> } {... <sup>3</sup> } {... <sup>4</sup> } 1 TEXT 2 TEXT 3 TEXT 4 TEXT

<p><code>\thirdofsixarguments {...} {...} {...} {...} {...} {...}</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 TEXT</p> <p>4 TEXT</p> <p>5 TEXT</p> <p>6 TEXT</p>
<p><code>\thirdofthreearguments {...} {...} {...}</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 TEXT</p>
<p><code>\thirdofthreeunexpanded {...} {...} {...}</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 TEXT</p>
<p><code>\threedigitrounding {...}</code></p> <p>* NUMBER</p>
<p><code>\tibetannumerals {...}</code></p> <p>* NUMBER</p>
<p><code>\tightlayer [...]</code></p> <p>* NAME</p>
<p><code>\tilde {...}</code></p> <p>* CHARACTER</p>
<p><code>\tinyfont</code></p>
<p><code>\tlap {...}</code></p> <p>* CONTENT</p>
<p><code>\tochar {...}</code></p> <p>* e:NAME x:NUMBER d:NUMBER s:NUMBER i:NUMBER n:NAME c:NAME u:NAME a:NAME</p>
<p><code>\tolinenote [...]</code></p> <p>* REFERENCE</p>
<p><code>\TOOLTIP [...<sup>1</sup>...<sup>2</sup>...] {...} {...}</code></p> <p>1 inherits: \setup<sup>OPT</sup>tooltip</p> <p>2 TEXT</p> <p>3 TEXT</p> <p>instances: tooltip</p>
<p><code>\TOOLTIP [...<sup>1</sup>] {...<sup>2</sup>} {...<sup>3</sup>}</code></p> <p>1 stanga cent<sup>OPT</sup>ru dreapta</p> <p>2 TEXT</p> <p>3 TEXT</p> <p>instances: tooltip</p>
<p><code>\tooltip [...<sup>1</sup>] {...<sup>2</sup>} {...<sup>3</sup>}</code></p> <p>1 stanga cent<sup>OPT</sup>ru dreapta</p> <p>2 TEXT</p> <p>3 TEXT</p>
<p><code>\tooltip [...<sup>1</sup>...<sup>2</sup>...] {...<sup>2</sup>} {...<sup>3</sup>}</code></p> <p>1 inherits: \setup<sup>OPT</sup>tooltip</p> <p>2 TEXT</p> <p>3 TEXT</p>



<code>\topbox {...}</code> *    CONTENT
<code>\topleftbox {...}</code> *    CONTENT
<code>\toplinebox {...}</code> *    CONTENT
<code>\toprightbox {...}</code> *    CONTENT
<code>\topskippedbox {...}</code> *    CONTENT
<code>\tracecatcodetables</code>
<code>\tracedfontname {...}</code> *    FONT
<code>\traceoutputroutines</code>
<code>\tracepositions</code>
<code>\traduce [...,*,...]</code> *    SPRACHE = TEXT <sup>PT</sup>
<code>\transparencycomponents {...}</code> *    COLOR
<code>\transparent [<sup>1</sup>...] {<sup>2</sup>...}</code> 1    COLOR 2    CONTENT
<code>\trecilafonttext [...,*,...]</code> *    inherits: \seteazafonttext
<code>\triplebond</code>
<code>\truefilename {...}</code> *    FILE
<code>\truefontname {...}</code> *    FONT
<code>\ttraggedright</code>
<code>\twodigitrounding {...}</code> *    NUMMER
<code>\tx</code>
<code>\txx</code>

$\backslash\text{typ} [\dots\overset{1}{=}\dots] \{\overset{2}{\dots}\}$ 1 inherits: $\overset{\text{OPT}}{\backslash\text{seteazatype}}$ 2 CONTENT
$\backslash\text{type} [\dots\overset{1}{=}\dots] \{\overset{2}{\dots}\}$ 1 inherits: $\overset{\text{OPT}}{\backslash\text{seteazatype}}$ 2 CONTENT
$\backslash\text{typedefinedbuffer} [\overset{1}{\dots}] [\dots\overset{2}{=}\dots]$ 1 BUFFER 2 inherits: $\backslash\text{seteazatyping}$
$\backslash\text{typeface}$
$\backslash\text{typefile} [\overset{1}{\dots}] [\dots\overset{2}{=}\dots] \{\overset{3}{\dots}\}$ 1 NAME OPT 2 inherits: $\backslash\text{seteazatyping}$ 3 FILE
$\backslash\text{typeinlinebuffer} [\dots\overset{1}{\dots}] [\dots\overset{2}{=}\dots]$ 1 BUFFER OPT 2 inherits: $\backslash\text{seteazatype}$
$\backslash\text{typescriptone}$
$\backslash\text{typescriptprefix} \{.*\}$ * NAME
$\backslash\text{typescriptthree}$
$\backslash\text{typescripttwo}$
$\backslash\text{typesetbuffer} [\overset{1}{\dots}] [\dots\overset{2}{=}\dots]$ 1 * BUFFER OPT 2 inherits: $\backslash\text{setupexternalfigure}$
$\backslash\text{typesetfile} [\overset{1}{\dots}] [\overset{2}{\dots}] [\dots\overset{3}{=}\dots]$ 1 NAME FILE OPT 2 FILE TEXT 3 inherits: $\backslash\text{setupexternalfigure}$
$\backslash\text{type} [\dots\overset{1}{=}\dots] <<\overset{2}{\dots}>>$ 1 inherits: $\overset{\text{OPT}}{\backslash\text{seteazatype}}$ 2 ANGLES
$\backslash\text{TYPE} [\dots\overset{1}{=}\dots] \{\overset{2}{\dots}\}$ 1 inherits: $\overset{\text{OPT}}{\backslash\text{seteazatype}}$ 2 CONTENT
$\backslash\text{TYPE} [\dots\overset{1}{=}\dots] <<\overset{2}{\dots}>>$ 1 inherits: $\overset{\text{OPT}}{\backslash\text{seteazatype}}$ 2 ANGLES
$\backslash\text{typ} [\dots\overset{1}{=}\dots] <<\overset{2}{\dots}>>$ 1 inherits: $\overset{\text{OPT}}{\backslash\text{seteazatype}}$ 2 ANGLES
$\backslash\text{uconvertnumber} \{\overset{1}{\dots}\} \{\overset{2}{\dots}\}$ 1 inherits: $\backslash\text{converttestenumar}$ 2 NUMMER

<code>\uedcatcodecommand \<sup>1</sup>... <sup>2</sup>... {<sup>3</sup>...}</code> 1 CSNAME 2 CHARACTER NUMBER 3 BEFEHL
<code>\ultimasubpagina</code>
<code>\undefinevalue {*.}</code> * NAME
<code>\undepthed {*.}</code> * CONTENT
<code>\underset {<sup>1</sup>...} {<sup>2</sup>...}</code> 1 TEXT 2 TEXT
<code>\undeva {<sup>1</sup>...} {<sup>2</sup>...} [<sup>3</sup>...]</code> 1 TEXT 2 TEXT 3 REFERENCE
<code>\undoassign [<sup>1</sup>...] [<sup>2</sup>...]</code> 1 TEXT 2 KEY = VALUE
<code>\unexpandeddocumentvariable {*.}</code> * KEY
<code>\unhhbox <sup>1</sup>... \with {<sup>2</sup>...}</code> 1 CSNAME NUMBER 2 BEFEHL
<code>\unihex {*.}</code> * NUMMER
<code>\uniqueMPgraphic {<sup>1</sup>...} {<sup>2</sup>...,...<sup>2</sup>...,...}</code> 1 NAME 2 KEY = VALUE <small>OPT</small>
<code>\uniqueMPpagegraphic {<sup>1</sup>...} {<sup>2</sup>...,...<sup>2</sup>...,...}</code> 1 NAME 2 KEY = VALUE <small>OPT</small>
<code>\UNIT {*.}</code> * CONTENT instances: unit
<code>\unit {*.}</code> * CONTENT
<code>\unprotect ... \protect</code>
<code>\unprotected <sup>*</sup>... \par</code> * CONTENT
<code>\unregisterhyphenationpattern [<sup>1</sup>...] [<sup>2</sup>...]</code> 1 SPRACHE 2 TEXT <small>OPT</small>

<code>\unspaceafter \<sup>1</sup> \<sup>2</sup></code> 1 CSNAME 2 TEXT
<code>\unspaceargument \<sup>1</sup> \to \<sup>2</sup></code> 1 TEXT 2 CSNAME
<code>\unspaced {...}</code> * TEXT
<code>\unspacestring \<sup>1</sup> \to \<sup>2</sup></code> 1 TEXT 2 CSNAME
<code>\untexargument {...} \to \<sup>2</sup></code> 1 TEXT 2 CSNAME
<code>\untexcommand {...} \to \<sup>2</sup></code> 1 CSNAME 2 CSNAME
<code>\uppercased {...}</code> * TEXT
<code>\uppercasestring \<sup>1</sup> \to \<sup>2</sup></code> 1 TEXT 2 CSNAME
<code>\upperlefthdoubleninequote</code>
<code>\upperlefthdoublesixquote</code>
<code>\upperleftsingleninequote</code>
<code>\upperleftsinglesixquote</code>
<code>\upperrighthdoubleninequote</code>
<code>\upperrighthdoublesixquote</code>
<code>\upperrightsingleninequote</code>
<code>\upperrightsinglesixquote</code>
<code>\url [...]</code> * NAME
<code>\urmatoareasubpagina</code>
<code>\usealignparameter \<sup>*</sup></code> * CSNAME
<code>\useblankparameter \<sup>*</sup></code> * CSNAME

<pre> \usebodyfont [...] * inherits: \seteazafonttext </pre>
<pre> \usebodyfontparameter \*.. * CSNAME </pre>
<pre> \usebtxdataset [...] [...] [...] [...] 1 NAME OPT OPT 2 FILE 3 specification = NAME </pre>
<pre> \usebtxdefinitions [...] * FILE </pre>
<pre> \usecitation [...] * REFERENCE </pre>
<pre> \usecitation {*.} * REFERENCE </pre>
<pre> \usecolors [...] * FILE </pre>
<pre> \usecomponent [...] * FILE </pre>
<pre> \usedummycolorparameter {*.} * KEY </pre>
<pre> \usedummystyleandcolor {*.} {*.} 1 KEY 2 KEY </pre>
<pre> \usedummystyleparameter {*.} * KEY </pre>
<pre> \useenvironment [...] * FILE </pre>
<pre> \useexternalrendering [...] [...] [...] [...] 1 NAME 2 NAME 3 FILE 4 auto embed </pre>
<pre> \usefigurebase [...] * reset FILE </pre>
<pre> \usefile [...] [...] [...] 1 NAME OPT 2 FILE 3 TEXT </pre>
<pre> \usegridparameter \*.. * CSNAME </pre>
<pre> \useindentingparameter \*.. * CSNAME </pre>

<code>\useindentnextparameter \*...</code> <code>* CSNAME</code>
<code>\useinterlinespaceparameter \*...</code> <code>* CSNAME</code>
<code>\uselanguageparameter \*...</code> <code>* CSNAME</code>
<code>\uselua module [...]</code> <code>* FILE</code>
<code>\useMPenvironmentbuffer [...]</code> <code>* NAME</code>
<code>\useMPgraphic {...} {...<sup>2</sup>...}</code> <code>1 NAME</code> <code>2 KEY = VALUE</code>
<code>\useMPlibrary [...]</code> <code>* FILE</code>
<code>\useMPrun {...} {...}</code> <code>1 NAME</code> <code>2 NUMMER</code>
<code>\useMPvariables [...]<sup>2</sup>...</code> <code>1 NAME</code> <code>2 KEY</code>
<code>\usemathstyleparameter \*...</code> <code>* CSNAME</code>
<code>\useproduct [...]</code> <code>* FILE</code>
<code>\useprofileparameter \*...</code> <code>* CSNAME</code>
<code>\useproject [...]</code> <code>* FILE</code>
<code>\userreferenceparameter \*...</code> <code>* CSNAME</code>
<code>\userpagenumber</code>
<code>\usesetupparameter \*...</code> <code>* CSNAME</code>
<code>\usestaticMPfigure [...]<sup>1</sup>...<sup>2</sup>...</code> <code>1 inherits: \setupscale</code> <code>2 NAME</code>
<code>\usesubpath [...]*...]</code> <code>* PATH</code>

<code>\usetexmodule [...]<sup>1</sup> [...,<sup>2</sup>...] [...,<sup>3</sup>...,...]</code> 1    m p s x t                    OPT                    OPT 2    FILE 3    KEY = VALUE
<code>\usetypescript [...]<sup>1</sup> [...]<sup>2</sup> [...]<sup>3</sup></code> 1    serif sans mono <sup>OPT</sup> math handwriting <sup>OPT</sup> Calligraphy casual tot 2    NAME fallback implicit dtp simple 3    size nume
<code>\usetypescriptfile [...]</code> *    reset FILE
<code>\usezipfile [...]<sup>1</sup> [...]<sup>2</sup></code> 1    FILE                    OPT 2    FILE
<code>\utfchar {...}</code> *    NUMMER
<code>\utflower {...}</code> *    TEXT
<code>\utfupper {...}</code> *    TEXT
<code>\utilityregisterlength</code>
<code>\VerboseNumber {...}</code> *    NUMMER
<code>\valoareculoare {...}</code> *    COLOR
<code>\vboxreference [...]<sup>1</sup>,... {...}<sup>2</sup></code> 1    REFERENCE 2    CONTENT
<code>\vec {...}</code> *    CHARACTER
<code>\verbatim {...}</code> *    CONTENT
<code>\verbatimstring {...}</code> *    CONTENT
<code>\verbosenumber {...}</code> *    NUMMER
<code>\versiune [...]</code> *    concept fisier temporar final NAME
<code>\verticalgrowingbar [...]<sup>*</sup>...,...]</code> *    inherits: \setuppositionbar
<code>\verticalpositionbar [...]<sup>*</sup>...,...]</code> *    inherits: \setuppositionbar

<code>\veryraggedcenter</code>
<code>\veryraggedleft</code>
<code>\veryraggedright</code>
<code>\vglue ...</code> <code>*    DIMENSION</code>
<code>\viewerlayer [...]{...}</code> <code>1    NAME</code> <code>2    CONTENT</code>
<code>\vl [...]</code> <code>*    NUMBER</code>
<code>\vphantom {...}</code> <code>*    CONTENT</code>
<code>\vpos {...}{...}</code> <code>1    NAME</code> <code>2    CONTENT</code>
<code>\vsmash {...}</code> <code>*    CONTENT</code>
<code>\vsmashbox ...</code> <code>*    CSNAME NUMBER</code>
<code>\vsmashed {...}</code> <code>*    CONTENT</code>
<code>\vspace [...]{...}</code> <code>1    NAME        OPT        OPT</code> <code>2    NAME</code>
<code>\vspacing [...]{...}</code> <code>*    preferinta acea<sup>OPT</sup>si pagina max fortat enable dezactivat faraalb impachetat inapot overlay totdeauna weak strong  implicit inainte intre dupa fixat flexibil niciunul mic mediu mare linie jumatatelinie quarterline formula alb  inaltime adancime standard NUMBER*mic NUMBER*mediu NUMBER*mare NUMBER*linie NUMBER*jumatatelinie NUMBER*quarterline  NUMBER*formula NUMBER*alb NUMBER*inaltime NUMBER*adancime category:NUMBER order:NUMBER penalty:NUMBER DIMENSION  NAME</code>
<code>\WidthSpanningText {...}{...}{...}</code> <code>1    TEXT</code> <code>2    DIMENSION</code> <code>3    FONT</code>
<code>\wdofstring {...}</code> <code>*    TEXT</code>
<code>\widthhofstring {...}</code> <code>*    TEXT</code>
<code>\widthspanningtext {...}{...}{...}</code> <code>1    TEXT</code> <code>2    DIMENSION</code> <code>3    FONT</code>



<code>\withoutpt {...}</code> *    DIMENSION
<code>\words {...}</code> *    TEXT
<code>\wordtonumber {...} {...}</code> 1    unu doi trei patru cinci 2    TEXT
<code>\writadatolist [...] [...,<sup>2</sup>...,<sup>3</sup>...,...]</code> 1    LISTE 2    inherits: \seteazalista 3    KEY = VALUE
<code>\writestatus {...} {...}</code> 1    TEXT 2    TEXT
<code>\XETEX</code>
<code>\XeTeX</code>
<code>\xdefconvertedargument \<sup>1</sup>... {...}</code> 1    CSNAME 2    TEXT
<code>\xmladdindex {...}</code> *    NODE
<code>\xmlafterdocumentsetup {...} {...} {...}</code> 1    NAME 2    SETUP 3    SETUP
<code>\xmlafterssetup {...} {...}</code> 1    SETUP 2    SETUP
<code>\xmlall {...} {...}</code> 1    NODE 2    LPATH
<code>\xmlappenddocumentsetup {...} {...}</code> 1    NAME 2    SETUP
<code>\xmlappendsetup {...}</code> *    SETUP
<code>\xmlapplyselectors {...}</code> *    NODE
<code>\xmlatt {...} {...}</code> 1    NODE 2    NAME

\xmlattdef {...} {...} {...} 1    NODE 2    NAME 3    TEXT
\xmlattribute {...} {...} {...} 1    NODE 2    LPATH 3    NAME
\xmlattributedef {...} {...} {...} {...} 1    NODE 2    LPATH 3    NAME 4    TEXT
\xmlbadinclusions {...} *    NODE
\xmlbeforedocumentsetup {...} {...} {...} 1    NAME 2    SETUP 3    SETUP
\xmlbeforesetup {...} {...} 1    SETUP 2    SETUP
\xmlchainatt {...} {...} 1    NODE 2    NAME
\xmlchainattdef {...} {...} {...} 1    NODE 2    NAME 3    TEXT
\xmlchecknamespace {...} {...} 1    NODE 2    NAME
\xmlcommand {...} {...} {...} 1    NODE 2    LPATH 3    XMLSETUP
\xmlconcat {...} {...} {...} 1    NODE 2    LPATH 3    TEXT
\xmlconcatrange {...} {...} {...} {...} {...} 1    NODE 2    LPATH 3    TEXT 4    FIRST 5    LAST
\xmlcontext {...} {...} 1    NODE 2    LPATH
\xmlcount {...} *    NODE

\xmldefaulttotext {...} *    NODE
\xmldirectives {...} *    NODE
\xmldirectivesafter {...} *    NODE
\xmldirectivesbefore {...} *    NODE
\xmldisplayverbatim {...} *    NODE
\xmldoif {...} {...} {...} 1    NODE 2    LPATH 3    TRUE
\xmldoifatt {...} {...} 1    NODE 2    TRUE
\xmldoifelse {...} {...} {...} {...} 1    NODE 2    LPATH 3    TRUE 4    FALSE
\xmldoifelseatt {...} {...} {...} 1    NODE 2    TRUE 3    FALSE
\xmldoifelseempty {...} {...} {...} {...} 1    NODE 2    LPATH 3    TRUE 4    FALSE
\xmldoifelseselfempty {...} {...} {...} 1    NODE 2    TRUE 3    FALSE
\xmldoifelsetext {...} {...} {...} {...} 1    NODE 2    LPATH 3    TRUE 4    FALSE
\xmldoifelsevalue {...} {...} {...} {...} 1    CATEGORY 2    NAME 3    TRUE 4    FALSE
\xmldoifnot {...} {...} {...} 1    NODE 2    LPATH 3    TRUE

\xmldoifnotatt {...} {...} 1    NODE 2    TRUE
\xmldoifnotselfempty {...} {...} 1    NODE 2    TRUE
\xmldoifnottext {...} {...} {...} 1    NODE 2    LPATH 3    TRUE
\xmldoifselfempty {...} {...} 1    NODE 2    TRUE
\xmldoiftext {...} {...} {...} 1    NODE 2    LPATH 3    TRUE
\xmlelement {...} {...} 1    NODE 2    NUMMER
\xmlfilter {...} {...} 1    NODE 2    LPATH
\xmlfirst {...} {...} 1    NODE 2    LPATH
\xmlflush {...} *    NODE
\xmlflushcontext {...} *    NODE
\xmlflushdocumentsetups {...} {...} 1    NAME 2    SETUP
\xmlflushlinewise {...} *    NODE
\xmlflushpure {...} *    NODE
\xmlflushspacewise {...} *    NODE
\xmlflushtext {...} *    NODE
\xmlinclude {...} {...} {...} 1    NODE 2    LPATH 3    NAME

<code>\xmlinclusion {...}</code> *    NODE
<code>\xmlinclusions {...}</code> *    NODE
<code>\xmlinfo {...}</code> *    NODE
<code>\xmlinjector {...}</code> *    NAME
<code>\xmllineprettyprint {...} {...}</code> 1    NODE 2    mp lua xml parsed-xml nested tex context niciunul NAME
<code>\xmllineprettyprinttext {...} {...}</code> 1    NODE 2    mp lua xml parsed-xml nested tex context niciunul NAME
<code>\xmllineverbatim {...}</code> *    NODE
<code>\xmlinstalldirective {...} {...}</code> 1    NAME 2    CSNAME
<code>\xmllast {...} {...}</code> 1    NODE 2    LPATH
<code>\xmllastatt</code>
<code>\xmllastmatch</code>
<code>\xmllastpar</code>
<code>\xmlloadbuffer {...} {...} {...}</code> 1    BUFFER 2    NAME 3    XMLSETUP
<code>\xmlloaddata {...} {...} {...}</code> 1    NAME 2    TEXT 3    XMLSETUP
<code>\xmlloaddirectives {...}</code> *    FILE
<code>\xmlloadfile {...} {...} {...}</code> 1    NAME 2    FILE 3    XMLSETUP
<code>\xmlloadonly {...} {...} {...}</code> 1    NAME 2    FILE 3    XMLSETUP

<pre> \xmlmain {...} *   NAME </pre>
<pre> \xmlmapvalue {...} {...} {...} 1   CATEGORY 2   NAME 3   TEXT </pre>
<pre> \xmlname {...} *   NODE </pre>
<pre> \xmlnamespace {...} *   NODE </pre>
<pre> \xmlnonspace {...} {...} 1   NODE 2   LPATH </pre>
<pre> \xmlpar {...} {...} 1   NODE 2   NAME </pre>
<pre> \xmlparam {...} {...} {...} 1   NODE 2   LPATH 3   NAME </pre>
<pre> \xmlpath {...} *   NODE </pre>
<pre> \xmlpos {...} *   NODE </pre>
<pre> \xmlposition {...} {...} {...} 1   NODE 2   LPATH 3   NUMMER </pre>
<pre> \xmlprependdocumentsetup {...} {...} 1   NAME 2   SETUP </pre>
<pre> \xmlprependsetup {...} *   SETUP </pre>
<pre> \xmlprettyprint {...} {...} 1   NODE 2   mp lua xml parsed-xml nested tex context niciunul NAME </pre>
<pre> \xmlprettyprinttext {...} {...} 1   NODE 2   mp lua xml parsed-xml nested tex context niciunul NAME </pre>
<pre> \xmlprocessbuffer {...} {...} {...} 1   BUFFER 2   NAME 3   XMLSETUP </pre>

\xmlprocessdata {...} {...} {...} 1 NAME 2 TEXT 3 XMLSETUP
\xmlprocessfile {...} {...} {...} 1 NAME 2 FILE 3 XMLSETUP
\xmlpure {...} {...} 1 NODE 2 LPATH
\xmlraw {...} * NODE
\xmlrefatt {...} {...} 1 NODE 2 NAME
\xmlregistereddokumentsetups {...} {...} 1 NAME 2 SETUP
\xmlregisteredsetups
\xmlregisterns {...} {...} 1 NAME 2 URL
\xmlremapname {...} {...} {...} {...} 1 NODE 2 LPATH 3 NAME 4 NAME
\xmlremapnamespace {...} {...} {...} 1 NODE 2 NAME 3 NAME
\xmlremoveddocumentsetup {...} {...} 1 NAME 2 SETUP
\xmlremovesetup {...} * SETUP
\xmlresetdocumentsetups {...} * NAME
\xmlresetinjectors
\xmlresetsetups {...} * NAME
\xmlsave {...} {...} 1 NODE 2 FILE

<pre> \xmlsetatt {...} {...} {...} 1  NODE 2  NAME 3  TEXT </pre>
<pre> \xmlsetattribute {...} {...} {...} {...} 1  NODE 2  LPATH 3  NAME 4  TEXT </pre>
<pre> \xmlsetentity {...} {...} 1  NAME 2  TEXT </pre>
<pre> \xmlsetfunction {...} {...} {...} 1  NODE 2  LPATH 3  LUAFUNCTION </pre>
<pre> \xmlsetinjectors [...,*...] *  NAME </pre>
<pre> \xmlsetpar {...} {...} {...} 1  NODE 2  NAME 3  TEXT </pre>
<pre> \xmlsetparam {...} {...} {...} {...} 1  NODE 2  LPATH 3  NAME 4  TEXT </pre>
<pre> \xmlsetsetup {...} {...} {...} 1  NAME 2  LPATH 3  SETUP </pre>
<pre> \xmlsetup {...} {...} 1  NODE 2  SETUP </pre>
<pre> \xmlshow {...} *  NODE </pre>
<pre> \xmlsnippet {...} {...} 1  NODE 2  NUMMER </pre>
<pre> \xmlstrip {...} {...} 1  NODE 2  LPATH </pre>
<pre> \xmlstripnolines {...} {...} 1  NODE 2  LPATH </pre>
<pre> \xmlstripped {...} {...} 1  NODE 2  LPATH </pre>



\xmlstrippednolines {...} {...} 1    NODE 2    LPATH
\xmltag {...} *    NODE
\xmltexentity {...} {...} 1    NAME 2    TEXT
\xmltext {...} {...} 1    NODE 2    LPATH
\xmltobuffer {...} {...} {...} 1    NODE 2    LPATH 3    BUFFER
\xmltobufferverbose {...} {...} {...} 1    NODE 2    LPATH 3    BUFFER
\xmltofile {...} {...} {...} 1    NODE 2    LPATH 3    FILE
\xmlvalue {...} {...} {...} 1    CATEGORY 2    NAME 3    TEXT
\xmlverbatim {...} *    NODE
\xsplitstring \... {...} 1    CSNAME 2    TEXT
\xypos {...} *    NAME
\ZIDINSAPTAMANA {...} *    NUMMER
\zidinsaptamana {...} *    NUMMER





**PRAGMA ADE**  
**Ridderstraat 27**  
**8061GH Hasselt NL**  
**[www.pragma-ade.com](http://www.pragma-ade.com)**