



# ConTExT

comenzile

# RO



# ConTeXt

## comenzile

ro / română  
8 aprilie 2018



\AfterPar {...} * BEFEHL
\Alphabeticnumerals {...} * NUMMER
\AMSTEX
\AmSTeX
\And
\abjadnaivenumerals {...} * NUMMER
\abjadnodotnumerals {...} * NUMMER
\abjadnumerals {...} * NUMMER
\activatespacehandler {...} * on dezactivat da fixat
\acute {...} * CHARACTER
\adaptcollector [... <sup>1</sup> ] [..., <sup>2</sup> ...] 1 NAME OPT 2 inherits: \setupcollector
\adapteazaaspect [... <sup>1</sup> ,...] [..., <sup>2</sup> ...] 1 NUMMER OPT 2 inaltime = max DIMENSION linii = NUMMER
\adaptfontfeature [... <sup>1</sup> ] [..., <sup>2</sup> ...] 1 NAME 2 inherits: \definefontfeature
\adaptpapersize [... <sup>1</sup> ,...] [..., <sup>2</sup> ...] 1 inherits: \seteazadimensiunihartie OPT 2 inherits: \seteazadimensiunihartie
\addfeature [...] * NAME
\addfeature {...} * NAME
\addfontpath [...*,...] * PATH
\addtocommalist {... <sup>1</sup> } \... <sup>2</sup> .. 1 TEXT 2 CSNAME

\addtoJSreamble {...} {...} 1 NAME 2 CONTENT
\addvalue {...} {...} 1 NAME 2 TEXT
\adubuffer [...] * BUFFER OPT
\getBUFFER
\adumarcaje [...] [...] [...] 1 BESCHRIFTUNG OPT OPT 2 pagina NAME 3 primul ultim curent precedent urmatorul sus subsol implicit ambele tot first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck
\afiseazaaspect [...,*...] * pt bp cm mm dd cc pc <del>nd</del> <sup>OPT</sup> nc sp in
\afiseazaculoare [...] * COLOR
\afiseazafonttext [...,*...] * inherits: \seteazafonttext
\afiseazagrid [...,*...] * reset subsol sus <del>ni</del> <sup>OPT</sup> funul tot linii incadrat nonumber dreapta stanga extern coloane
\afiseazagrupculoare [...] [...] [...] 1 NAME OPT 2 orizontal vertical numar valoare nume
\afiseazamakeup [...] * marcaj tot boxes <del>li</del> <sup>OPT</sup> fe glyph fontkern hbox vbox vtop kern glue penalty strut whatsit simple simplehbox simplevbox simplevtop user math italic origin reset
\afiseazamediufonttext [...,*...] * inherits: \seteazafonttext
\afiseazapaleta [...] [...] [...] 1 NAME OPT 2 orizontal vertical numar valoare nume
\afiseazarama [...] [...] [...] 1 sus antet text <del>sub</del> <sup>OPT</sup> sol subsol OPT 2 bordurastanga marginestanga text marginedreapta borduradreapta
\afiseazasetari [...,*...] * pt bp cm mm dd cc pc <del>nd</del> <sup>OPT</sup> nc sp in
\afiseazasetsimboluri [...] * NAME
\afiseazastruts

<code>\afiseazatiparire [...<sup>1</sup>,...] [...<sup>2</sup>,...] [...<sup>3</sup>,...]</code> 1 inherits: \seteazadimensiuni <sup>qRT</sup> hartie OPT OPT 2 inherits: \seteazadimensiuni <sup>qRT</sup> hartie 3 inherits: \seteazaaspect
<code>\aftersplitstring ... \at ... \to ...</code> 1 TEXT 2 TEXT 3 CSNAME
<code>\aftertestandsplitstring ... \at ... \to ...</code> 1 TEXT 2 TEXT 3 CSNAME
<code>\aldin</code>
<code>\aldininclinat</code>
<code>\aldinitalic</code>
<code>\alignbottom</code>
<code>\aligned [...<sup>1</sup>,...] {...<sup>2</sup>}</code> 1 stanga centru dreapta sus subsol linie l c r m t b g 2 CONTENT
<code>\alignedbox [...<sup>1</sup>,...] ...<sup>2</sup> {...<sup>3</sup>}</code> 1 stanga centru dreapta sus subsol linie l c r m t b g 2 CSNAME 3 CONTENT
<code>\alignedline {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}</code> 1 stanga dreapta centru flushleft flushright center max intern extern innermargin outermargin inneredge outeredge spatiuspate cutspace marginestanga marginedreapta bordurastanga borduradreapta 2 stanga dreapta centru flushleft flushright center max intern extern innermargin outermargin inneredge outeredge spatiuspate cutspace marginestanga marginedreapta bordurastanga borduradreapta 3 CONTENT
<code>\alignhere</code>
<code>\alignmentcharacter</code>
<code>\aliniatcentru {...}</code> * CONTENT
<code>\aliniatdreapta {...}</code> * CONTENT
<code>\aliniatstanga {...}</code> * CONTENT
<code>\allinputpaths</code>
<code>\alphabeticnumerals {...}</code> * NUMMER

**\alwayscitation** [ $\dots\stackrel{1}{=}\dots$ ] [ $\dots\stackrel{2}{=}\dots$ ]

```
1  referinta = REFERENCEOPT
   alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
               authoryear
   inainte   = BEFEHL
   dupa      = BEFEHL
   stanga    = BEFEHL
   dreapta   = BEFEHL
   inherits: \setupbtx
2  REFERENCE
```

**\alwayscitation** [ $\dots\stackrel{1}{=}\dots$ ] [ $\dots\stackrel{2}{=}\dots$ ]

```
1  implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear
2  REFERENCE
```

**\alwayscitation** [ $\dots\stackrel{1}{=}\dots$ ] [ $\dots\stackrel{2}{=}\dots$ ]

```
1  referinta = REFERENCE
   alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
               authoryear
   inainte   = BEFEHL
   dupa      = BEFEHL
   stanga    = BEFEHL
   dreapta   = BEFEHL
   inherits: \setupbtx
2  KEY = VALUE
```

**\alwayscite** [ $\dots\stackrel{1}{=}\dots$ ] [ $\dots\stackrel{2}{=}\dots$ ]

```
1  referinta = REFERENCEREFN
   alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
               authoryear
   inainte   = BEFEHL
   dupa      = BEFEHL
   stanga    = BEFEHL
   dreapta   = BEFEHL
   inherits: \setupbtx
2  REFERENCE
```

**\alwayscite** [ $\dots\stackrel{1}{=}\dots$ ] [ $\dots\stackrel{2}{=}\dots$ ]

```
1  implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear
2  REFERENCE
```

**\alwayscite** [ $\dots\stackrel{1}{=}\dots$ ] [ $\dots\stackrel{2}{=}\dots$ ]

```
1  referinta = REFERENCE
   alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
               authoryear
   inainte   = BEFEHL
   dupa      = BEFEHL
   stanga    = BEFEHL
   dreapta   = BEFEHL
   inherits: \setupbtx
2  KEY = VALUE
```

**\ampersand**

**\anchor** [ $\dots\stackrel{1}{=}\dots$ ] [ $\dots\stackrel{2}{=}\dots$ ] [ $\dots\stackrel{3}{=}\dots$ ] [ $\dots\stackrel{4}{=}\dots$ ]

```
1  NAMEOPT
2  inherits: \setuplayer
3  inherits: \setuplayerinherits: \seteazainconjurat
4  CONTENT
```

**\appendetoks**  $\dots\stackrel{1}{=}\dots$  \to  $\dots\stackrel{2}{=}\dots$

```
1  BEFEHL
2  CSNAME
```

**\appendgvalue** [ $\dots\stackrel{1}{=}\dots$ ] [ $\dots\stackrel{2}{=}\dots$ ]

```
1  NAME
2  BEFEHL
```



\appendtocommalist {...} \ <sup>2</sup> ... 1 TEXT 2 CSNAME
\appendtoks \ <sup>1</sup> ... \to \ <sup>2</sup> ... 1 BEFEHL 2 CSNAME
\appendtoksonce \ <sup>1</sup> ... \to \ <sup>2</sup> ... 1 BEFEHL 2 CSNAME
\appendvalue {...} {\ <sup>2</sup> ...} 1 NAME 2 BEFEHL
\apply {...} {\ <sup>2</sup> ...} 1 CONTENT 2 CONTENT
\applyalternativestyle {...} * NAME
\applyprocessor {\ <sup>1</sup> ...} {\ <sup>2</sup> ...} 1 NAME 2 CONTENT
\applytocharacters \ <sup>1</sup> ... {\ <sup>2</sup> ...} 1 CSNAME 2 TEXT
\applytofirstcharacter \ <sup>1</sup> ... {\ <sup>2</sup> ...} 1 CSNAME 2 TEXT
\applytosplitstringchar \ <sup>1</sup> ... {\ <sup>2</sup> ...} 1 CSNAME 2 TEXT
\applytosplitstringcharspaced \ <sup>1</sup> ... {\ <sup>2</sup> ...} 1 CSNAME 2 TEXT
\applytosplitstringline \ <sup>1</sup> ... {\ <sup>2</sup> ...} 1 CSNAME 2 TEXT
\applytosplitstringlinespaced \ <sup>1</sup> ... {\ <sup>2</sup> ...} 1 CSNAME 2 TEXT
\applytosplitstringword \ <sup>1</sup> ... {\ <sup>2</sup> ...} 1 CSNAME 2 TEXT
\applytosplitstringwordspaced \ <sup>1</sup> ... {\ <sup>2</sup> ...} 1 CSNAME 2 TEXT

<code>\applytowords \<sup>1</sup>... {<sup>2</sup>...}</code> 1 CSNAME 2 TEXT
<code>\arabicdecimals {<sup>*</sup>...}</code> * NUMBER
<code>\arabicexnumerals {<sup>*</sup>...}</code> * NUMBER
<code>\arabicnumerals {<sup>*</sup>...}</code> * NUMBER
<code>\arg {<sup>*</sup>...}</code> * CONTENT
<code>\asciistr {<sup>*</sup>...}</code> * CONTENT
<code>\ascundeblocuri [...,<sup>1</sup>...] [...,<sup>2</sup>...]</code> 1 NAME 2 NAME OPT
<code>\assignalfadimension {<sup>1</sup>...} \<sup>2</sup>... {<sup>3</sup>...} {<sup>4</sup>...} {<sup>5</sup>...}</code> 1 mic mediu mare niciunul DIMENSION 2 CSNAME 3 DIMENSION 4 DIMENSION 5 DIMENSION
<code>\assigndimen \<sup>1</sup>... {<sup>2</sup>...}</code> 1 CSNAME 2 DIMENSION
<code>\assigndimension {<sup>1</sup>...} \<sup>2</sup>... {<sup>3</sup>...} {<sup>4</sup>...} {<sup>5</sup>...}</code> 1 [-+]mic [-+]mediu [-+]mare niciunul DIMENSION 2 CSNAME 3 DIMENSION 4 DIMENSION 5 DIMENSION
<code>\assignifempty \<sup>1</sup>... {<sup>2</sup>...}</code> 1 CSNAME 2 BEFEHL
<code>\assigntranslation [...,<sup>1</sup>...,...] \to \<sup>2</sup>...</code> 1 SPRACHE = TEXT 2 CSNAME
<code>\assignvalue {<sup>1</sup>...} \<sup>2</sup>... {<sup>3</sup>...} {<sup>4</sup>...} {<sup>5</sup>...}</code> 1 mic mediu mare TEXT 2 CSNAME 3 BEFEHL 4 BEFEHL 5 BEFEHL
<code>\assignwidth {<sup>1</sup>...} \<sup>2</sup>... {<sup>3</sup>...} {<sup>4</sup>...}</code> 1 ajustat broad DIMENSION 2 CSNAME 3 TEXT 4 DIMENSION

$\backslash\text{assumelongusagecs } \overset{1}{\dots} \{ \overset{2}{\dots} \}$ 1 CSNAME 2 CONTENT
$\backslash\text{astype } \{ \dots \}$ * CONTENT
$\backslash\text{ATTACHMENT } [ \overset{1}{\dots} ] [ \dots, \overset{2}{\dots}, \dots ]$ 1 NAME OPT OPT 2 inherits: $\backslash\text{setupattachment}$ instances: attachment
$\backslash\text{attachment } [ \overset{1}{\dots} ] [ \dots, \overset{2}{\dots}, \dots ]$ 1 NAME OPT OPT 2 inherits: $\backslash\text{setupattachment}$
$\backslash\text{autocap } \{ \dots \}$ * TEXT
$\backslash\text{autodirhbox } \overset{1}{\dots} \{ \overset{2}{\dots} \}$ 1 TEXT OPT 2 CONTENT
$\backslash\text{autodirvbox } \overset{1}{\dots} \{ \overset{2}{\dots} \}$ 1 TEXT OPT 2 CONTENT
$\backslash\text{autodirvtop } \overset{1}{\dots} \{ \overset{2}{\dots} \}$ 1 TEXT OPT 2 CONTENT
$\backslash\text{autoinsertnextspace}$
$\backslash\text{autointegral } \{ \overset{1}{\dots} \} \{ \overset{2}{\dots} \} \{ \overset{3}{\dots} \}$ 1 TEXT 2 TEXT 3 TEXT
$\backslash\text{automathematics } \{ \dots \}$ * CONTENT
$\backslash\text{autosetups } \{ \dots, \dots \}$ * NAME
$\backslash\text{autostarttext } \dots \backslash\text{autostoptext}$
$\backslash\text{availablehsize}$
$\backslash\text{averagecharwidth}$
$\backslash\text{BeforePar } \{ \dots \}$ * BEFEHL
$\backslash\text{Big } \dots$ * CHARACTER
$\backslash\text{Bigg } \dots$ * CHARACTER

\Biggl ... * CHARACTER
\Biggm ... * CHARACTER
\Biggr ... * CHARACTER
\Bigl ... * CHARACTER
\Bigm ... * CHARACTER
\Bigr ... * CHARACTER
\backgroundimage {...} {...} {...} {...} 1 NUMBER 2 DIMENSION 3 DIMENSION 4 BEFEHL
\backgroundimagefill {...} {...} {...} {...} 1 NUMBER 2 DIMENSION 3 DIMENSION 4 BEFEHL
\backgroundline [...] {...} 1 COLOR 2 CONTENT
\bar {...} * CHARACTER
\baraculoare [...*,...] * COLOR
\barainteractiune [...] [... <sup>2</sup> ...,...] 1 NAME OPT OPT 2 inherits: \seteazabarainteractiune
\BAR {...} * CONTENT instances: overbar underbar overstrike understrike overbars underbars overstrikes understrikes underrandom underrandoms underdash underdashes underdot underdots nobar hiddenbar
\hiddenbar {...} * CONTENT
\nobar {...} * CONTENT
\overbar {...} * CONTENT

<code>\overbars {...}</code> *    CONTENT
<code>\overstrike {...}</code> *    CONTENT
<code>\overstrikes {...}</code> *    CONTENT
<code>\underbar {...}</code> *    CONTENT
<code>\underbars {...}</code> *    CONTENT
<code>\underdash {...}</code> *    CONTENT
<code>\underdashes {...}</code> *    CONTENT
<code>\underdot {...}</code> *    CONTENT
<code>\underdots {...}</code> *    CONTENT
<code>\underrandom {...}</code> *    CONTENT
<code>\underrandoms {...}</code> *    CONTENT
<code>\understrike {...}</code> *    CONTENT
<code>\understrikes {...}</code> *    CONTENT
<code>\basegrid [...,.*=...,...]</code> *    nx        = NUMMER *    ny        = NUMMER *    dx        = NUMMER *    dy        = NUMMER *    factor    = NUMMER *    scala     = NUMMER *    xstep     = NUMMER *    ystep     = NUMMER *    offset    = DIMENSION *    xoffset   = DIMENSION *    yoffset   = DIMENSION *    aliniere   = centru *    unitate   = cm mm in pc pt bp *    stil      = STYLE BEFEHL *    culoare   = COLOR
<code>\baselinebottom</code>
<code>\baselineleftbox {...}</code> *    CONTENT

<code>\baselinemiddlebox {...}</code> *    CONTENT
<code>\baselinerightbox {...}</code> *    CONTENT
<code>\bbordermatrix {...}</code> *    CONTENT
<code>\bbox {...}</code> *    CONTENT
<code>\beforesplitstring .<sup>1</sup>. \at .<sup>2</sup>. \to \<sup>3</sup>..</code> 1    TEXT 2    TEXT 3    CSNAME
<code>\beforetestandsplitstring .<sup>1</sup>. \at .<sup>2</sup>. \to \<sup>3</sup>..</code> 1    TEXT 2    TEXT 3    CSNAME
<code>\beginBLOCK [...*,...] ... \endBLOCK</code> *    + - NAME                    OPT
<code>\beginhbox ... \endhbox</code>
<code>\beginofshapebox ... \endofshapebox</code>
<code>\beginvbox ... \endvbox</code>
<code>\beginvtop ... \endvtop</code>
<code>\begstrut ... \endstrut</code>
<code>\bigbodyfont</code>
<code>\bigg ...</code> *    CHARACTER
<code>\bigger</code>
<code>\biggl ...</code> *    CHARACTER
<code>\biggm ...</code> *    CHARACTER
<code>\biggr ...</code> *    CHARACTER
<code>\bigl ...</code> *    CHARACTER
<code>\bigm ...</code> *    CHARACTER

<code>\bigr ...</code> <code>* CHARACTER</code>
<code>\bigskip</code>
<code>\bitmapimage [...,\stackrel{1}{...},...] {\stackrel{2}{...}}</code> <code>1 culoare = rgb cmyk gri</code> <code>latime = DIMENSION</code> <code>inaltime = DIMENSION</code> <code>x = NUMMER</code> <code>y = NUMMER</code> <code>2 NUMMER</code>
<code>\blanc [...,\stackrel{OPT}{...},...]</code> <code>* preferinta<sup>OPT</sup>aceasipagina max fortat enable dezactivat faraalb inapot overlay totdeauna weak strong implicit</code> <code>inainte intre dupa fixat flexibil niciunul mic mediu mare linie jumatatelinie quarterline formula alb inaltime</code> <code>adancime standard NUMMER*mic NUMMER*mediu NUMMER*mare NUMMER*linie NUMMER*jumatatelinie NUMMER*quarterline</code> <code>NUMMER*formula NUMMER*alb NUMMER*inaltime NUMMER*adancime category:NUMMER order:NUMMER penalty:NUMMER DIMENSION</code> <code>NAME</code>
<code>\blap {...}</code> <code>* CONTENT</code>
<code>\bleed [...,\stackrel{1}{...},...] {\stackrel{2}{...}}</code> <code>1 inherits: \setupbleeding</code> <code>2 CONTENT</code>
<code>\bleedheight</code>
<code>\bleedwidth</code>
<code>\blockligatures [...,\stackrel{1}{...},...]</code> <code>* TEXT</code>
<code>\blocksynctexfile [...,\stackrel{1}{...},...]</code> <code>* FILE</code>
<code>\bodyfontenvironmentlist</code>
<code>\bodyfontsize</code>
<code>\boldface</code>
<code>\booleanmodevalue {...}</code> <code>* NAME</code>
<code>\bordermatrix {...}</code> <code>* CONTENT</code>
<code>\bottombox {...}</code> <code>* CONTENT</code>
<code>\bottomleftbox {...}</code> <code>* CONTENT</code>
<code>\bottomrightbox {...}</code> <code>* CONTENT</code>
<code>\boxcursor</code>

<code>\boxmarker {<sup>1</sup>...} {<sup>2</sup>...}</code> 1 NAME 2 NUMMER
<code>\boxofsize \<sup>1</sup>... \<sup>2</sup>... {<sup>3</sup>...}</code> 1 CSNAME 2 DIMENSION 3 CONTENT
<code>\boxreference [...,<sup>1</sup>...] \<sup>2</sup>... {<sup>3</sup>...}</code> 1 REFERENCE 2 CSNAME 3 CONTENT
<code>\bpar ... \epar</code>
<code>\bpos {<sup>*</sup>...}</code> * NAME
<code>\breakhere</code>
<code>\breve {<sup>*</sup>...}</code> * CHARACTER
<code>\bTABLE [...,<sup>*</sup>...,...] ... \eTABLE</code> * inherits: <code>\setupTABLE</code>
<code>\bTABLEbody [...,<sup>*</sup>...,...] ... \eTABLEbody</code> * inherits: <code>\setupTABLE</code>
<code>\bTABLEfoot [...,<sup>*</sup>...,...] ... \eTABLEfoot</code> * inherits: <code>\setupTABLE</code>
<code>\bTABLEhead [...,<sup>*</sup>...,...] ... \eTABLEhead</code> * inherits: <code>\setupTABLE</code>
<code>\bTABLEnext [...,<sup>*</sup>...,...] ... \eTABLEnext</code> * inherits: <code>\setupTABLE</code>
<code>\bTC [...,<sup>*</sup>...,...] ... \eTC</code> * inherits: <code>\bTD</code>
<code>\bTD [...,<sup>*</sup>...,...] ... \eTD</code> * nx = <sup>OPT</sup> NUMBER ny = NUMBER nc = NUMBER nr = NUMBER n = NUMBER m = NUMBER actiune = REFERENCE inherits: <code>\setupTABLE</code>
<code>\bTDs [...<sup>*</sup>] ... \eTDs</code> * NAME
<code>\bTH [...,<sup>*</sup>...,...] ... \eTH</code> * inherits: <code>\bTD</code>
<code>\bTN [...,<sup>*</sup>...,...] ... \eTN</code> * inherits: <code>\bTD</code>



<pre> \bTR [...,...<sup>*</sup>...,...] ... \eTR * inherits: <sup>OPT</sup>\setupTABLE </pre>
<pre> \bTRs [...] ... \eTRs * NAME </pre>
<pre> \bTX [...,...<sup>*</sup>...,...] ... \eTX * inherits: <sup>OPT</sup>\bTD </pre>
<pre> \bTY [...,...<sup>*</sup>...,...] ... \eTY * inherits: <sup>OPT</sup>\setupTABLE </pre>
<pre> \btxabbreviatedjournal {...} * NAME </pre>
<pre> \btxaddjournal [...<sup>1</sup>] [...<sup>2</sup>] 1 NAME 2 NAME </pre>
<pre> \btxalwayscitation [...,...<sup>1</sup>...,...] [...<sup>2</sup>] 1 referinta = REFERENCE <sup>OPT</sup>   alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum               authoryear   inainte   = BEFEHL   dupa      = BEFEHL   stanga    = BEFEHL   dreapta   = BEFEHL   inherits: \setupbtx 2 REFERENCE </pre>
<pre> \btxalwayscitation [...<sup>1</sup>] [...<sup>2</sup>] 1 implicit category entry<sup>OPT</sup> short pagina num textnum an index tag keywords autor authoryears authornum authoryear 2 REFERENCE </pre>
<pre> \btxalwayscitation [...,...<sup>1</sup>...,...] [...,...<sup>2</sup>...,...] 1 referinta = REFERENCE   alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum               authoryear   inainte   = BEFEHL   dupa      = BEFEHL   stanga    = BEFEHL   dreapta   = BEFEHL   inherits: \setupbtx 2 KEY = VALUE </pre>
<pre> \btxauthorfield {...} * initials firstnames vons surnames juniors </pre>
<pre> \btxdetail {...} * address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language   luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an   yearfiled NAME </pre>
<pre> \btxdirect {...} * address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language   luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an   yearfiled NAME </pre>
<pre> \btxdoif {...<sup>1</sup>} {...<sup>2</sup>} 1 address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language   luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an   yearfiled NAME 2 TRUE </pre>

\btxdfcombiinlistelse {...} {...} {...} {...}

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

\btxdfotherwise {...} {...} {...}

- 1 address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME
- 2 TRUE
- 3 FALSE

\btxdfotherwisecombiinlist {...} {...} {...} {...}

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

\btxdfelsesameasprevious {...} {...} {...}

- 1 address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME
- 2 TRUE
- 3 FALSE

\btxdfelsesameaspreviouschecked {...} {...} {...} {...}

- 1 totdeauna douafete
- 2 address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME
- 3 TRUE
- 4 FALSE

\btxdfelseuservariable {...} {...} {...}

- 1 KEY
- 2 TRUE
- 3 FALSE

\btxdfifnot {...} {...}

- 1 address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME
- 2 TRUE

\btxdfisameaspreviouscheckedelse {...} {...} {...} {...}

- 1 totdeauna douafete
- 2 address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME
- 3 TRUE
- 4 FALSE

\btxdfisameaspreviouselse {...} {...} {...}

- 1 address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME
- 2 TRUE
- 3 FALSE

\btxdfuservariableelse {...} {...} {...}

- 1 KEY
- 2 TRUE
- 3 FALSE

\btxexpandedjournal {...}

- \* NAME

<p><code>\btxfieldd {...}</code></p> <p>* address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME</p>
<p><code>\btxfielddname {...}</code></p> <p>* address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME</p>
<p><code>\btxfielddtype {...}</code></p> <p>* address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME</p>
<p><code>\btxfirstofrange {...}</code></p> <p>* volume pages</p>
<p><code>\btxflush {...}</code></p> <p>* address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME</p>
<p><code>\btxflushauthor [<sup>1</sup>...] {<sup>2</sup>...}</code></p> <p>1 num normal normalshort inverted invertedshort</p> <p>2 autor editor</p>
<p><code>\btxflushauthorinverted {...}</code></p> <p>* autor editor</p>
<p><code>\btxflushauthorinvertedshort {...}</code></p> <p>* autor editor</p>
<p><code>\btxflushauthorname {...}</code></p> <p>* autor editor</p>
<p><code>\btxflushauthornormal {...}</code></p> <p>* autor editor</p>
<p><code>\btxflushauthornormalshort {...}</code></p> <p>* autor editor</p>
<p><code>\btxflushsuffix</code></p>
<p><code>\btxfoundname {...}</code></p> <p>* address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME</p>
<p><code>\btxfoundtype {...}</code></p> <p>* address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME</p>
<p><code>\btxhiddencitation [...]</code></p> <p>* REFERENCE</p>

```

\btxhybridcite [...1...] [...2]
1  referinta = REFERENCEOPT
   alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
               authoryear
   inainte   = BEFEHL
   dupa      = BEFEHL
   stanga    = BEFEHL
   dreapta   = BEFEHL
   inherits: \setupbtx
2  REFERENCE

```

```

\btxhybridcite [...1] [...2]
1  implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear
2  REFERENCE

```

```

\btxhybridcite {...}
*  REFERENCE

```

```

\btxhybridcite [...1...] [...2...]
1  referinta = REFERENCE
   alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
               authoryear
   inainte   = BEFEHL
   dupa      = BEFEHL
   stanga    = BEFEHL
   dreapta   = BEFEHL
   inherits: \setupbtx
2  KEY = VALUE

```

```

\btxlistcitation [...1...] [...2]
1  referinta = REFERENCEOPT
   alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
               authoryear
   inainte   = BEFEHL
   dupa      = BEFEHL
   stanga    = BEFEHL
   dreapta   = BEFEHL
   inherits: \setupbtx
2  REFERENCE

```

```

\btxlistcitation [...1] [...2]
1  implicit category entryOPT short pagina num textnum an index tag keywords autor authoryears authornum authoryear
2  REFERENCE

```

```

\btxlistcitation [...1...] [...2...]
1  referinta = REFERENCE
   alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
               authoryear
   inainte   = BEFEHL
   dupa      = BEFEHL
   stanga    = BEFEHL
   dreapta   = BEFEHL
   inherits: \setupbtx
2  KEY = VALUE

```

```

\btxloadjournalist [...]
*  FILE

```

```

\btxoneorrange {...} {...} {...}
1  volume pages
2  TRUE
3  FALSE

```

```

\btxremapauthor [...1] [...2]
1  TEXT
2  TEXT

```

<code>\btxsavejournalist [...]</code> *    FILE
<code>\btxsetup {...}</code> *    NAME
<code>\btxsingularorplural {...} {...} {...}</code> 1    editor producer director 2    TRUE 3    FALSE
<code>\btxsingularplural {...} {...} {...}</code> 1    editor producer director 2    TRUE 3    FALSE
<code>\btxttextcitation [...,<sup>1</sup>...,<sup>2</sup>...] [...]</code> 1    referinta    = REFERENCE <sup>OPT</sup> alternativ   = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authorityyear inainte     = BEFEHL dupa        = BEFEHL stanga      = BEFEHL dreapta     = BEFEHL inherits:   \setupbtx 2    REFERENCE
<code>\btxttextcitation [...]<sup>1</sup> [...]<sup>2</sup></code> 1    implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authorityyear 2    REFERENCE
<code>\btxttextcitation [...,<sup>1</sup>...,<sup>2</sup>...] [...,<sup>2</sup>...,<sup>1</sup>...]</code> 1    referinta   = REFERENCE alternativ   = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authorityyear inainte     = BEFEHL dupa        = BEFEHL stanga      = BEFEHL dreapta     = BEFEHL inherits:   \setupbtx 2    KEY   = VALUE
<code>\buildmathaccent {...} {...}</code> 1    CHARACTER 2    CHARACTER
<code>\buildtextaccent {...} {...}</code> 1    CHARACTER 2    CHARACTER
<code>\buildtextbottomcomma {...}</code> *    CHARACTER
<code>\buildtextbottomdot {...}</code> *    CHARACTER
<code>\buildtextcedilla {...}</code> *    CHARACTER
<code>\buildtextgrave {...}</code> *    CHARACTER
<code>\buildtextmacron {...}</code> *    CHARACTER

\buildtextognek {...} * CHARACTER
\butoaneinteractiune [..., <sup>1</sup> ...,...] [..., <sup>2</sup> ,...] 1 inherits: \seteazabarainteractiune 2 pagina subpagina REFERENCE
\buton [..., <sup>1</sup> ...,...] {... <sup>2</sup> } [... <sup>3</sup> ] 1 inherits: \setupbutton 2 TEXT 3 REFERENCE
\butonmeniu [..., <sup>1</sup> ...,...] {... <sup>2</sup> } {... <sup>3</sup> } 1 inherits: \setupbutton 2 TEXT 3 REFERENCE
\butonmeniu [... <sup>1</sup> ] [..., <sup>2</sup> ...,...] {... <sup>3</sup> } {... <sup>4</sup> } 1 NAME OPT 2 inherits: \seteazameniuinteractiune 3 TEXT 4 REFERENCE
\BUTTON [..., <sup>1</sup> ...,...] {... <sup>2</sup> } [... <sup>3</sup> ] 1 inherits: \setupbutton 2 TEXT 3 REFERENCE instances: button
\Caps {...} * TEXT
\CONTEXT
\ConTeXt
\Context
\ConvertConstantAfter \... {... <sup>2</sup> } {... <sup>3</sup> } 1 CSNAME 2 TEXT 3 TEXT
\ConvertToConstant \... {... <sup>2</sup> } {... <sup>3</sup> } 1 CSNAME 2 TEXT 3 TEXT
\CUVANT {...} * TEXT
\CUVINTE {...} * TEXT
\Cuvant {...} * TEXT
\Cuvinte {...} * TEXT

<code>\caligrific</code>
<code>\camel {...}</code> * TEXT
<code>\camp [...]</code> <sup>1</sup> <code>[...]</code> <sup>2</sup> 1 NAME OPT 2 TEXT
<code>\catcodetablename</code>
<code>\cbox ...</code> <sup>1</sup> <code>{...}</code> <sup>2</sup> 1 TEXT OPT 2 CONTENT
<code>\centraligned {...}</code> * CONTENT
<code>\centerbox ...</code> <sup>1</sup> <code>{...}</code> <sup>2</sup> 1 TEXT OPT 2 CONTENT
<code>\centeredbox ...</code> <sup>1</sup> <code>{...}</code> <sup>2</sup> 1 TEXT OPT 2 CONTENT
<code>\centeredlastline</code>
<code>\centerednextbox ...</code> <sup>1</sup> <code>{...}</code> <sup>2</sup> 1 TEXT OPT 2 CONTENT
<code>\centerline {...}</code> * CONTENT
<code>\centru ...</code> * CHARACTER
<code>\cfrac [...]</code> <sup>1</sup> <code>{...}</code> <sup>2</sup> <code>{...}</code> <sup>3</sup> 1 l c r l <sup>P</sup> l <sup>c</sup> l <sup>r</sup> c <sup>l</sup> c <sup>c</sup> c <sup>r</sup> r <sup>l</sup> r <sup>c</sup> r <sup>r</sup> 2 CONTENT 3 CONTENT
<code>\CHARACTERKERNING [...]</code> <sup>1</sup> <code>{...}</code> <sup>2</sup> 1 NUMMER OPT 2 TEXT
<code>\chardescription {...}</code> * NUMMER
<code>\charwidthlanguage</code>
<code>\check {...}</code> * CHARACTER
<code>\checkcharacteralign {...}</code> * CONTENT

<pre> \checkedchar {...} {...} 1  NUMMER 2  CHARACTER </pre>
<pre> \checkedfiller {...} *   sym simbol rigla latime spatiu NAME BEFEHL </pre>
<pre> \checkedstrippedcsname \*.. *   CSNAME </pre>
<pre> \checkedstrippedcsname ... *   TEXT </pre>
<pre> \checkinjector [...] *   NAME </pre>
<pre> \checknextindentation [...] *   da nu auto </pre>
<pre> \checknextinjector [...*] *   NAME </pre>
<pre> \checkpage [...<sup>1</sup>] [...,<sup>2</sup>...<sub>OPT</sub>,...] 1  NAME 2  inherits: \setuppagechecker </pre>
<pre> \checkparameters [...*] *   TEXT </pre>
<pre> \checkpreviousinjector [...*] *   NAME </pre>
<pre> \checksoundtrack {...*} *   NAME </pre>
<pre> \checktwopassdata {...*} *   NAME </pre>
<pre> \checkvariables [...<sup>1</sup>] [...,<sup>2</sup>...<sub>OPT</sub>,...] 1  NAME 2  set      = BEFEHL    reset    = BEFEHL    KEY      = VALUE </pre>
<pre> \chem {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} 1  TEXT 2  TEXT 3  TEXT </pre>
<pre> \chemical [...<sup>1</sup>] [...,<sup>2</sup>...<sub>OPT</sub>] [...,<sup>3</sup>...<sub>OPT</sub>] 1  NAME 2  TEXT 3  TEXT </pre>
<pre> \chemicalbottext {...*} *   TEXT </pre>
<pre> \chemicalmidtext {...*} *   TEXT </pre>



<code>\chemicalsymbol [...]</code> * NAME
<code>\chemicaltext {...}</code> * TEXT
<code>\chemicaltopertext {...}</code> * TEXT
<code>\chineseallnumerals {...}</code> * NUMMER
<code>\chinesecapnumerals {...}</code> * NUMMER
<code>\chinesenumerals {...}</code> * NUMMER
<code>\citation [...<sup>1</sup>...<sup>2</sup>...] [...]</code> 1 referinta = REFERENCE alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear inainte = BEFEHL dupa = BEFEHL stanga = BEFEHL dreapta = BEFEHL inherits: \setupbtx 2 REFERENCE
<code>\citation [...<sup>1</sup>] [...<sup>2</sup>]</code> 1 implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear 2 REFERENCE
<code>\citation {...}</code> * REFERENCE
<code>\citation [...<sup>1</sup>...<sup>2</sup>...] [...<sup>2</sup>...]</code> 1 referinta = REFERENCE alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear inainte = BEFEHL dupa = BEFEHL stanga = BEFEHL dreapta = BEFEHL inherits: \setupbtx 2 KEY = VALUE
<code>\cite [...<sup>1</sup>...<sup>2</sup>...] [...]</code> 1 referinta <sup>REF</sup> REFERENCE alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear inainte = BEFEHL dupa = BEFEHL stanga = BEFEHL dreapta = BEFEHL inherits: \setupbtx 2 REFERENCE
<code>\cite [...<sup>1</sup>] [...<sup>2</sup>]</code> 1 implicit <sup>REF</sup> category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear 2 REFERENCE
<code>\cite {...}</code> * REFERENCE

```

\cite [...1...] [...2...]
1  referinta = REFERENCE
   alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
               authoryear
   inainte   = BEFEHL
   dupa      = BEFEHL
   stanga    = BEFEHL
   dreapta   = BEFEHL
   inherits: \setupbtx
2  KEY = VALUE

```

```

\clap {...}
*  CONTENT

```

```

\classfont {...} {...}
1  NAME
2  FONT

```

```

\cldcommand {...}
*  BEFEHL

```

```

\cldcontext {...}
*  BEFEHL

```

```

\cldloadfile {...}
*  FILE

```

```

\cldprocessfile {...}
*  FILE

```

```

\clip [...1...] {...}
1  inherits: \seteazaclipping
2  CONTENT

```

```

\cloneazacamp [...1] [...2] [...3] [...4,...]
1  NAME
2  NAME
3  NAME
4  NAME

```

```

\collect {...}
*  CONTENT

```

```

\collectedtext [...1...] [...2...] {...3} {...4}
1  inherits: \setupcollectOPT
2  stil      = STYLE BEFEHL
   culoare   = COLOR
   inherits: \seteazainconjurat
3  TEXT
4  CONTENT

```

```

\collectexpanded {...}
*  CONTENT

```

```

\coloana [...*,...]
*  inherits: \columnbreak

```

```

\colorcomponents {...}
*  COLOR

```

```

\colored [...1...] {...2}
1  inherits: \definesteculoare
2  CONTENT

```

\colored [ <sup>1</sup> ...] { <sup>2</sup> ...} 1 COLOR 2 CONTENT
\coloronly [ <sup>1</sup> ...] { <sup>2</sup> ...} 1 COLOR 2 CONTENT
\columnbreak [..., <sup>*</sup> ...] * da nu preferinta local fortat primul ultim NUMBER NAME
\combinepages [ <sup>1</sup> ...] [..., <sup>2</sup> ...] 1 FILE OPT 2 alternativ = a b c orizontal vertical n = NUMBER nx = NUMBER ny = NUMBER start = NUMBER stop = NUMBER distanta = DIMENSION sus = BEFEHL jos = BEFEHL stanga = BEFEHL dreapta = BEFEHL inainte = BEFEHL dupa = BEFEHL intre = BEFEHL frame = on dezactivat fundal = primplan culoare NAME culoarefundal = COLOR
\COMMENT [ <sup>1</sup> ...] [..., <sup>2</sup> ...] { <sup>3</sup> ...} 1 TEXT OPT OPT 2 inherits: \seteazacommentariu 3 TEXT instances: comment
\comment [ <sup>1</sup> ...] [..., <sup>2</sup> ...] { <sup>3</sup> ...} 1 TEXT OPT OPT 2 inherits: \seteazacommentariu 3 TEXT
\commalistelement
\commalistsentence [..., <sup>1</sup> ...] [..., <sup>2</sup> ...] 1 TEXT OPT 2 TEXT
\commalistsize
\comparagrupculoare [...] * NAME
\comparapaleta [...] * NAME
\comparedimension { <sup>1</sup> ...} { <sup>2</sup> ...} 1 DIMENSION 2 DIMENSION
\comparedimensioneps { <sup>1</sup> ...} { <sup>2</sup> ...} 1 DIMENSION 2 DIMENSION

\completeazanumarpagina	
\completebtxrendering [...] <sup>1</sup> [...] <sup>2</sup> ...	
1	NAME OPT OPT
2	inherits: \setupbtxrendering
\completCOMBINEDLIST [...] <sup>*</sup> ...	
*	inherits: \seteazalista OPT
instances: content	
\completcontent [...] <sup>*</sup> ...	
*	inherits: \seteazalista OPT
\completelist [...] <sup>1</sup> [...] <sup>2</sup> ...	
1	LISTE OPT
2	inherits: \seteazalista
\completelistofFLOATS [...] <sup>*</sup> ...	
*	inherits: \seteazalista OPT
instances: chemicals figures tables intermezzi graphics	
\completelistofchemicals [...] <sup>*</sup> ...	
*	inherits: \seteazalista OPT
\completelistoffigures [...] <sup>*</sup> ...	
*	inherits: \seteazalista OPT
\completelistofgraphics [...] <sup>*</sup> ...	
*	inherits: \seteazalista OPT
\completelistofintermezzi [...] <sup>*</sup> ...	
*	inherits: \seteazalista OPT
\completelistoftables [...] <sup>*</sup> ...	
*	inherits: \seteazalista OPT
\completelistofpublications [...] <sup>1</sup> [...] <sup>2</sup> ...	
1	NAME OPT OPT
2	inherits: \setupbtxrendering
\completelistofsorts [...] <sup>1</sup> [...] <sup>2</sup> ...	
1	SINGULAR OPT
2	inherits: \seteazasortare
\completelistofSORTS [...] <sup>*</sup> ...	
*	inherits: \seteazasortare OPT
instances: logos	
\completelistoflogos [...] <sup>*</sup> ...	
*	inherits: \seteazasortare OPT
\completelistofsynonyms [...] <sup>1</sup> [...] <sup>2</sup> ...	
1	SINGULAR OPT
2	inherits: \seteazasinonime
\completelistofSYNONYMS [...] <sup>*</sup> ...	
*	inherits: \seteazasinonime OPT
instances: abbreviations	

<code>\completelistofabbreviations [...,..<sup>*</sup>...,...]</code> <code>* inherits: \seteazasinonime</code> <sup>OPT</sup>
<code>\completeregister [...,..<sup>1</sup>...] [...,..<sup>2</sup>...,...]</code> <code>1 NAME</code> <sup>OPT</sup> <code>2 inherits: \seteazaregistru</code>
<code>\completREGISTER [...,..<sup>*</sup>...,...]</code> <code>* inherits: \seteazaregistru<sup>OPT</sup></code> <code>instances: index</code>
<code>\completindex [...,..<sup>*</sup>...,...]</code> <code>* inherits: \seteazaregistru<sup>OPT</sup></code>
<code>\complexorsimple \*..</code> <code>* CSNAME</code>
<code>\complexorsimpleempty \*..</code> <code>* CSNAME</code>
<code>\complexorsimpleempty {.*..}</code> <code>* TEXT CSNAME</code>
<code>\complexorsimple {.*..}</code> <code>* TEXT CSNAME</code>
<code>\componenta [...]</code> <code>* FILE</code>
<code>\componenta ...</code> <code>* FILE</code>
<code>\composedcollector {.*..}</code> <code>* NAME</code>
<code>\composedlayer {.*..}</code> <code>* NAME</code>
<code>\compresult</code>
<code>\constantdimen \*..</code> <code>* CSNAME</code>
<code>\constantdimenargument \*..</code> <code>* CSNAME</code>
<code>\constantemptyargument \*..</code> <code>* CSNAME</code>
<code>\constantnumber \*..</code> <code>* CSNAME</code>
<code>\constantnumberargument \*..</code> <code>* CSNAME</code>

$\backslash\text{contentreference}$ [... <sup>1</sup> ,...] [... <sup>2</sup> ,... <sup>2</sup> ,...] {... <sup>3</sup> } 1 REFERENCE 2 inherits: \seteazainconjurat 3 CONTENT
$\backslash\text{continuednumber}$ {...} * NUMMER
$\backslash\text{continueifinputfile}$ {...} * FILE
$\backslash\text{convertargument}$ ... \to \^2.. 1 TEXT 2 CSNAME
$\backslash\text{convertcommand}$ \^1... \to \^2.. 1 CSNAME 2 CSNAME
$\backslash\text{convertedcounter}$ [... <sup>1</sup> ] [... <sup>2</sup> ,... <sup>2</sup> ,...] 1 NAME 2 inherits: \setupcounter
$\backslash\text{converteddimen}$ {... <sup>1</sup> } {... <sup>2</sup> } 1 DIMENSION 2 ex em pt in cm mm sp bp pc dd cc nc
$\backslash\text{convertedsubcounter}$ [... <sup>1</sup> ] [... <sup>2</sup> ] [... <sup>3</sup> ,... <sup>3</sup> ,...] 1 NAME 2 NUMBER NUMBER:NUMBER NUMBER:* NUMBER:tot 3 inherits: \setupcounter
$\backslash\text{converttestenunar}$ {... <sup>1</sup> } {... <sup>2</sup> } 1 gol implicit niciunul luna month:mnem caracter Caracater caractere Caractere a A Numere cuvant words Cuvant Cuvinte n N numereromane Numereromane i I r R KR RK grec Grec g G abjadnumerals abjadnodotnumerals abjadnaivenumerals thainumerals devanagarinumerals gurmurkhinumerals gujaratinnumerals tibetannumerals greeknumerals Greeknumerals arabicnumerals persiannumerals arabicexnumerals arabicdecimals persiandecimals koreannumerals koreanparentnumerals koreancirlenumerals kr kr-p kr-c chinesenumerals chinesecapnumerals chineseallnumerals cn cn-c cn-a sloveniannumerals slovenianNumerals spanishnumerals spanishNumerals mathgreek set_0 set_1 set_2 set_3 continued NAME 2 NUMMER
$\backslash\text{convertmonth}$ {...} * NUMMER
$\backslash\text{convertvalue}$ ... \to \^2.. 1 NAME 2 CSNAME
$\backslash\text{convertvboxtohbox}$
$\backslash\text{copiazacamp}$ [... <sup>1</sup> ] [... <sup>2</sup> ] 1 NAME 2 NAME
$\backslash\text{copyboxfromcache}$ {... <sup>1</sup> } {... <sup>2</sup> } ... <sup>3</sup> .. 1 NAME 2 NUMMER TEXT 3 CSNAME NUMMER

$\backslash copyLABELtext$ [ <sup>1</sup> ...] [ <sup>2</sup> ...,...] 1 SPRACHE OPT 2 KEY = KEY instances: head label mathlabel taglabel unit operator prefix suffix btxlabel
$\backslash copybtxlabeltext$ [ <sup>1</sup> ...] [ <sup>2</sup> ...,...] 1 SPRACHE OPT 2 KEY = KEY
$\backslash copyheadtext$ [ <sup>1</sup> ...] [ <sup>2</sup> ...,...] 1 SPRACHE OPT 2 KEY = KEY
$\backslash copylabeltext$ [ <sup>1</sup> ...] [ <sup>2</sup> ...,...] 1 SPRACHE OPT 2 KEY = KEY
$\backslash copymathlabeltext$ [ <sup>1</sup> ...] [ <sup>2</sup> ...,...] 1 SPRACHE OPT 2 KEY = KEY
$\backslash copyoperatortext$ [ <sup>1</sup> ...] [ <sup>2</sup> ...,...] 1 SPRACHE OPT 2 KEY = KEY
$\backslash copyprefixtext$ [ <sup>1</sup> ...] [ <sup>2</sup> ...,...] 1 SPRACHE OPT 2 KEY = KEY
$\backslash copysuffixtext$ [ <sup>1</sup> ...] [ <sup>2</sup> ...,...] 1 SPRACHE OPT 2 KEY = KEY
$\backslash copytaglabeltext$ [ <sup>1</sup> ...] [ <sup>2</sup> ...,...] 1 SPRACHE OPT 2 KEY = KEY
$\backslash copyunittext$ [ <sup>1</sup> ...] [ <sup>2</sup> ...,...] 1 SPRACHE OPT 2 KEY = KEY
$\backslash copypages$ [ <sup>1</sup> ...] [ <sup>2</sup> ...,...] <sup>3</sup> ...,...] 1 FILE OPT OPT 2 marcaje = on dezactivat offset = DIMENSION n = NUMMER 3 inherits: \setupexternalfigure
$\backslash copyparameters$ [ <sup>1</sup> ...] [ <sup>2</sup> ...] [ <sup>3</sup> ...,...] 1 TEXT 2 TEXT 3 KEY
$\backslash copyposition$ { <sup>1</sup> ...} { <sup>2</sup> ...} 1 NAME 2 NAME
$\backslash corectezaspatialb$ {.*} * CONTENT

$\backslash\text{countersubs}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...] 1 NAME OPT 2 NUMMER
$\backslash\text{counttoken}$ ... \in ... \to \^3... 1 TEXT 2 TEXT 3 CSNAME
$\backslash\text{counttokens}$ ... \to \^2... 1 TEXT 2 CSNAME
$\backslash\text{cramped}$ {...} * CONTENT
$\backslash\text{crampedclap}$ {...} * CONTENT
$\backslash\text{crampedllap}$ {...} * CONTENT
$\backslash\text{crampedrlap}$ {...} * CONTENT
$\backslash\text{ctop}$ ... { <sup>1</sup> ...} 1 TEXT OPT 2 CONTENT
$\backslash\text{ctxcommand}$ {...} * BEFEHL
$\backslash\text{ctxdirectcommand}$ {...} * BEFEHL
$\backslash\text{ctxdirectlua}$ {...} * BEFEHL
$\backslash\text{ctxfunction}$ {...} * NAME
$\backslash\text{CTXFUNCTIONDEFINITION}$
$\backslash\text{CTXFUNCTION}$
$\backslash\text{ctxlatecommand}$ {...} * BEFEHL
$\backslash\text{ctxlatelua}$ {...} * BEFEHL
$\backslash\text{ctxloadluafile}$ {...} * FILE
$\backslash\text{ctxlua}$ {...} * BEFEHL



\ctxluabuffer [...] *    BUFFER                    OPT
\ctxluacode {...} *    BEFEHL
\ctxreport {...} *    BEFEHL
\ctxsprint {...} *    BEFEHL
\culoare [...] {...} 1    COLOR 2    CONTENT
\culoaregri [...] {...} 1    COLOR 2    CONTENT
\currentassignmentlistkey
\currentassignmentlistvalue
\currentbtxuservariable {...} *    KEY
\currentcommalistitem
\currentcomponent
\currentenvironment
\currentfeaturetest
\currentinterface
\currentETICHETA [... <sup>1</sup> ...] {... <sup>2</sup> } 1    REFERENCE                    OPT                    OPT 2    TEXT
\currentlanguage
\currentlistentrydestinationattribute
\currentlistentrylimitedtext {...} *    TEXT
\currentlistentrynumber
\currentlistentrypagenumber
\currentlistentryreferenceattribute {...} *    numar text numarpagina tot
\currentlistentrytitle

\currentlistentrytitlerendered
\currentlistsymbol
\currentmainlanguage
\currentmessagetext
\currentmoduleparameter {...} * KEY
\currentoutputstream
\currentproduct
\currentproject
\currentregime
\currentregisterpageuserdata {...} * KEY
\currentresponses
\currenttime [...*,...] * h m TEXT OPT
\currentvalue
\currentxtablecolumn
\currentxtablerow
\cuvant {...} * TEXT
\cuvantdreapta [... <sup>1</sup> ]{... <sup>2</sup> } 1 dreapta DIMENSION OPT 2 CONTENT
\d {...} * CHARACTER
\data [..., <sup>1</sup> ...,... <sup>2</sup> ][...,...] 1 d = NUMBER OPT m = NUMBER y = NUMBER 2 inherits: \datacurenta
\datacurenta [...*,...] * an luna zi zisaptamana y yy Y m mm M d dd D w W spatiu \ month:mnem m:mnem d:ord day:ord dd:ord D:ord TEXT referinta day:+ day:++ d:+ d:++ dd:+ dd:++ D:+ D:++ month:jalali m:jalali jalali:to jalali:from
\datasetvariable {... <sup>1</sup> }{... <sup>2</sup> }{... <sup>3</sup> } 1 NAME 2 NAME NUMBER 3 KEY realpage



`\defineactivecharacter` <sup>1</sup>... {<sup>2</sup>...}

1 CHARACTER  
2 BEFEHL

`\definealternativestyle` [...,<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...]

1 NAME  
2 BEFEHL  
3 BEFEHL

`\defineanchor` [<sup>1</sup>...] [<sup>2</sup>...] [...,<sup>3</sup>...,...] [...,<sup>4</sup>...,...]

1 NAME  
2 NAME  
3 inherits: \setuplayer  
4 inherits: \setuplayerinherits: \seteazainconjurat

`\defineattachment` [<sup>1</sup>...] [<sup>2</sup>...] [...,<sup>3</sup>...,...]

1 NAME  
2 NAME  
3 inherits: \setupattachment

`\defineattribute` [<sup>1</sup>...] [...,<sup>2</sup>...]

1 NAME  
2 local global public private

`\definebackground` [<sup>1</sup>...] [<sup>2</sup>...] [...,<sup>3</sup>...,...]

1 NAME  
2 NAME  
3 inherits: \seteazafundal

`\definebar` [<sup>1</sup>...] [<sup>2</sup>...] [...,<sup>3</sup>...,...]

1 NAME  
2 NAME  
3 inherits: \setupbar

`\definebodyfontswitch` [<sup>1</sup>...] [...,<sup>2</sup>...]

1 NAME  
2 inherits: \seteazafonttext

`\definebreakpoint` [<sup>1</sup>...] [<sup>2</sup>...] [...,<sup>3</sup>...,...]

1 NAME  
2 CHARACTER  
3 type = 1 2 3 4 5  
nstanga = NUMMER  
ndreapta = NUMMER  
stanga = BEFEHL  
mijloc = BEFEHL  
dreapta = BEFEHL  
range = da nu  
language = SPRACHE

`\definebreakpoints` [...]

\* NAME

`\definebtx` [<sup>1</sup>...] [<sup>2</sup>...] [...,<sup>3</sup>...,...]

1 NAME  
2 NAME  
3 inherits: \setupbtx

`\definebtxdataset` [<sup>1</sup>...] [<sup>2</sup>...] [...,<sup>3</sup>...,...]

1 NAME  
2 NAME  
3 inherits: \setupbtxdataset

```
\definebtxregister [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupbtxregister
```

```
\definebtxrendering [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupbtxrendering
```

```
\definebutton [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupbutton
```

```
\definecapitals [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \seteazamazjuscule
```

```
\definecharacterkerning [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupcharacterkerning
```

```
\definecharacterspacing [*]
* NAME
```

```
\definechemical [...] {...}
1 NAME
2 CONTENT
```

```
\definechemicals [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupchemical
```

```
\definechemicalsymbol [...] [...]
1 NAME
2 TEXT
```

```
\definecollector [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupcollector
```

```
\definecolumnbreak [...] [...]
1 NAME
2 da nu preferinta local fortat primul ultim NUMMER
```

```
\definecombination [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupcombination
```

```
\definecomment [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \seteazacomentariu
```

```
\definecomplexorsimple [*]
* CSNAME
```

<pre> \definecomplexorsimpleempty \... * CSNAME </pre>
<pre> \definecomplexorsimpleempty {...} * TEXT CSNAME </pre>
<pre> \definecomplexorsimple {...} * TEXT CSNAME </pre>
<pre> \defineconversionset [...] [...] [...] 1 NAME SECTIONBLOCK:NAME OPT 2 NAME PROCESSOR-&gt;NAME 3 NAME PROCESSOR-&gt;NAME </pre>
<pre> \definecounter [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupcounter </pre>
<pre> \definedataset [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupdataset </pre>
<pre> \definedelimitedtext [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupdelimitedtext </pre>
<pre> \definedfont [...] * FONT OPT </pre>
<pre> \defineeffect [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupeffect </pre>
<pre> \defineexpandable [...] \... {...} 1 NUMMER OPT 2 CSNAME 3 CONTENT </pre>
<pre> \defineexternalfigure [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupexternalfigure </pre>
<pre> \definefallbackfamily [...] [...] [...] [...] 1 NAME OPT 2 rm ss tt mm hw cg roman serif regular sansserif sans suport teletype type mono scrismmanual caligrafic math matematica 3 FONT 4 rscale = NUMMER designsize = implicit auto goodies = FILE range = NUMMER NAME offset = NUMMER NAME check = da nu fortat = da nu features = NAME tf = TEXT bf = TEXT it = TEXT sl = TEXT bi = TEXT bs = TEXT sc = TEXT </pre>

```
\definefallbackfamily [...] [...] [...] [...] [...]
1 NAME
2 rm ss tt mm hw cg roman serif regular sansserif sans suport teletype type mono scrismathematica
3 FONT
4 NAME
```

```
\definefieldbody [...] [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupfieldbody
```

```
\definefieldbodyset [...] [...]
1 NAME
2 NAME
```

```
\definefieldcategory [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupfieldcategory
```

```
\definefileconstant {...} {...}
1 NAME
2 NAME
```

```
\definefilefallback [...] [...]
1 NAME
2 FILE
```

```
\definefilesynonym [...] [...]
1 NAME
2 FILE
```

```
\definefiller [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupfiller
```

```
\definefirstline [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupfirstline
```

```
\definefittingpage [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupfittingpage
```

```
\definefontalternative [...]
* NAME
```

```
\definefontfallback [...] [...] [...] [...]
1 NAME
2 FONT NAME
3 NAME NUMMER
4 rscale = NUMMER
fortat = da nu
check = da nu
offset = NUMMER NAME
features = NAME
factor = NUMMER
```

```

\definefontfamily [...] [...] [...] [...] [...]
1  NAME
2  rm ss tt mm hw cg roman serif regular sansserif sans suport teletype type mono scrismatematica
3  FONT
4  rscale      = NUMBER
   designsizes = implicit auto
   goodies     = FILE
   features    = NAME
   tf          = TEXT
   bf          = TEXT
   it          = TEXT
   sl          = TEXT
   bi          = TEXT
   bs          = TEXT
   sc          = TEXT

```

```

\definefontfamilypreset [...] [...]
1  NAME
2  inherits: \definefontfamily

```

```

\definefontfamilypreset [...] [...]
1  NAME
2  NAME

```

```

\definefontfamily [...] [...] [...] [...] [...]
1  NAME
2  rm ss tt mm hw cg roman serif regular sansserif sans suport teletype type mono scrismatematica
3  FONT
4  NAME

```



**\definefontfeature** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...<sup>3</sup>...,...]

```
1  NAME                                OPT
2  NAME
3  language      = NAME
   script        = NAME auto
   mode          = node base auto niciunul
   liga          = da nu
   kern          = da nu
   extrakerns    = da nu
   tlig          = da nu
   trep          = da nu
   missing       = da nu
   dummies       = da nu
   analyze       = da nu
   unicoding     = da nu
   expansiune    = NAME
   protrusion    = NAME
   nostackmath   = da nu
   realdimensions = da nu
   itlc          = da nu
   textitalics   = da nu
   mathitalics   = da nu
   slant         = NUMMER
   extend        = NUMMER
   dimensions    = NUMMER
   boundingbox    = da nu fundal incadrat gol COLOR
   compose       = da nu
   char-ligatures = da nu
   compat-ligatures = da nu
   goodies       = FILE
   extrafeatures = da nu
   featureset    = NAME
   colorscheme   = NAME
   postprocessor = NAME
   mathdimensions = NAME
   keepligatures = da nu auto
   devanagari    = da nu
   features      = da nu
   tcom          = da nu
   anum          = da nu
   mathsize      = da nu
   decomposehangul = da nu
   mathalternatives = da nu
   mathgaps      = da nu
   checkmarks    = da nu
   NAME          = da nu
   mathnolimitsmode = NUMMER
   blockligatures = da nu
```

**\definefontfile** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...<sup>3</sup>...,...]

```
1  NAME                                OPT
2  FILE
3  features      = NAME
   fallbacks    = NAME
   goodies      = NAME
   designsize    = auto implicit
```

**\definefontsize** [...]

```
*  NAME
```

**\definefontsolution** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...<sup>3</sup>...,...]

```
1  NAME                                OPT      OPT
2  NAME
3  inherits: \setupfontsolution
```

**\defineformula** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...<sup>3</sup>...,...]

```
1  NAME                                OPT      OPT
2  NAME
3  inherits: \setupformula
```

**\defineformulaalternative** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...]

```
1  NAME
2  CSNAME
3  CSNAME
```

```
\defineformulaframed [...1] [...2] [...,...3...,...]  
1 NAME OPT OPT  
2 NAME  
3 inherits: \setupformulaframed
```

```
\defineframedcontent [...1] [...2] [...,...3...,...]  
1 NAME OPT OPT  
2 NAME  
3 inherits: \setupframedcontent
```

```
\defineframedtable [...1] [...2]  
1 NAME OPT  
2 NAME
```

```
\definefrozenfont [...1] [...2]  
1 NAME  
2 FONT
```

```
\defineglobalcolor [...1] [...,...2...,...]  
1 NAME  
2 inherits: \definesteculoare
```

```
\defineglobalcolor [...1] [...2]  
1 NAME  
2 COLOR
```

```
\definegraphicstypesynonym [...1] [...2]  
1 NAME  
2 NAME
```

```
\definegridsnapping [...1] [...,...2...,...]  
1 NAME  
2 local global noheight nodepth box max min niciunul linie jumatatelinie primul ultim inaltime minima maxheight  
mindepth maxdepth sus subsol strut NUMMER minheight:NUMMER maxheight:NUMMER mindepth:NUMMER maxdepth:NUMMER  
box:NUMMER top:NUMMER bottom:NUMMER offset:NUMMER
```

```
\defineheadalternative [...1] [...2] [...,...3...,...]  
1 NAME OPT OPT  
2 NAME  
3 inherits: \setupheadalternative
```

```
\definehelp [...1] [...2] [...,...3...,...]  
1 NAME OPT OPT  
2 NAME  
3 inherits: \setuphelp
```

```
\definehigh [...1] [...2] [...,...3...,...]  
1 NAME OPT OPT  
2 NAME  
3 inherits: \setuphigh
```

```
\definehighlight [...1] [...2] [...,...3...,...]  
1 NAME OPT OPT  
2 NAME  
3 inherits: \setuphighlight
```

```
\definehspace [...1] [...2] [...3]  
1 NAME OPT  
2 NAME  
3 DIMENSION
```

**\definehyphenationfeatures** [<sup>1</sup>...] [<sup>2</sup>...<sup>3</sup>...]

```
1 NAME
2 characters = TEXT
  hyphens   = da tot TEXT
  joiners    = da tot TEXT
  rightwords = NUMMER
  hyphenmin  = NUMMER
  lefthyphenmin = NUMMER
  righthyphenmin = NUMMER
  lefthyphenchar = NUMMER
  righthyphenchar = NUMMER
  alternativ  = original tex hyphenate expanded traditional niciunul
  borduradreapta = tex
  rightchars = cuvant NUMMER
```

**\defineindentedtext** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...<sup>3</sup>...]

```
1 NAME
2 NAME
3 inherits: \setupindentedtext
```

**\defineindenting** [<sup>1</sup>...] [<sup>2</sup>...]

```
1 NAME
2 [-+]mic [-+]mediu [-+]mare niciunul nu nu primul urmatorul da totdeauna niciodata impar par normal reset toggle
  DIMENSION
```

**\defineinitial** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...<sup>3</sup>...]

```
1 NAME
2 NAME
3 inherits: \setupinitial
```

**\defineinsertion** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...<sup>3</sup>...]

```
1 NAME
2 NAME
3 inherits: \setupinsertion
```

**\defineinteraction** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...<sup>3</sup>...]

```
1 NAME
2 NAME
3 inherits: \seteazainteractiunea
```

**\defineinteractionbar** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...<sup>3</sup>...]

```
1 NAME
2 NAME
3 inherits: \seteazabarainteractiune
```

**\defineinterfaceconstant** {<sup>1</sup>...} {<sup>2</sup>...}

```
1 NAME
2 NAME
```

**\defineinterfaceelement** {<sup>1</sup>...} {<sup>2</sup>...}

```
1 NAME
2 NAME
```

**\defineinterfacevariable** {<sup>1</sup>...} {<sup>2</sup>...}

```
1 NAME
2 NAME
```

**\defineinterlinespace** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...<sup>3</sup>...]

```
1 NAME
2 NAME
3 inherits: \seteazaspatiuinterliniar
```

**\defineintermediatecolor** [<sup>1</sup>...] [<sup>2</sup>...<sup>2</sup>...] [<sup>3</sup>...<sup>3</sup>...<sup>3</sup>...]

```
1 NAME
2 COLOR NUMMER
3 a = NUMMER
  t = NUMMER
```

<pre> \defineitemgroup [...] [...] [...] [...] 1  NAME                      OPT      OPT 2  NAME 3  inherits: \setupitemgroup </pre>
<pre> \defineitems [...] [...] [...] [...] 1  NAME                      OPT      OPT 2  NAME 3  inherits: \seteazaelemente </pre>
<pre> \definelabelclass [...] [...] 1  NAME                      OPT 2  NUMMER </pre>
<pre> \definelayer [...] [...] [...] 1  NAME                      OPT      OPT 2  NAME 3  inherits: \setuplayer </pre>
<pre> \definelayerpreset [...] [...] 1  NAME 2  inherits: \setuplayer </pre>
<pre> \definelayerpreset [...] [...] 1  NAME 2  NAME </pre>
<pre> \definelayout [...] [...] [...] 1  NAME                      OPT      OPT 2  NAME 3  inherits: \seteazaaspect </pre>
<pre> \definelinefiller [...] [...] [...] 1  NAME                      OPT      OPT 2  NAME 3  inherits: \setuplinefiller </pre>
<pre> \definelinenote [...] [...] [...] 1  NAME                      OPT      OPT 2  NAME 3  inherits: \setuplinenote </pre>
<pre> \definelinenumbering [...] [...] [...] 1  NAME                      OPT      OPT 2  NAME 3  inherits: \seteazanumerotarelinii </pre>
<pre> \definelines [...] [...] [...] 1  NAME                      OPT      OPT 2  NAME 3  inherits: \seteazalinii </pre>
<pre> \definelistalternative [...] [...] [...] 1  NAME                      OPT      OPT 2  NAME 3  inherits: \setuplistalternative </pre>
<pre> \definelistextra [...] [...] [...] 1  NAME                      OPT      OPT 2  NAME 3  inherits: \setuplistextra </pre>

<pre> \definelow [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...<sub>=</sub>...,...] 1  NAME                OPT          OPT 2  NAME 3  inherits: \setuplow </pre>
<pre> \definelowhigh [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...<sub>=</sub>...,...] 1  NAME                OPT          OPT 2  NAME 3  inherits: \setuplowhigh </pre>
<pre> \definelowmidhigh [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...<sub>=</sub>...,...] 1  NAME                OPT          OPT 2  NAME 3  inherits: \setuplowmidhigh </pre>
<pre> \defineMPinstance [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...<sub>=</sub>...,...] 1  NAME                OPT          OPT 2  NAME 3  inherits: \setupMPinstance </pre>
<pre> \definemarginblock [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...<sub>=</sub>...,...] 1  NAME                OPT          OPT 2  NAME 3  inherits: \setupmarginblock </pre>
<pre> \definemargindata [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...<sub>=</sub>...,...] 1  NAME                OPT          OPT 2  NAME 3  inherits: \setupmargindata </pre>
<pre> \definemarker [...]  *  NAME </pre>
<pre> \definemathaccent <sup>1</sup>... <sup>2</sup>... 1  NAME 2  CHARACTER </pre>
<pre> \definemathalignment [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...<sub>=</sub>...,...] 1  NAME                OPT          OPT 2  NAME 3  inherits: \setupmathalignment </pre>
<pre> \definemathcases [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...<sub>=</sub>...,...] 1  NAME                OPT          OPT 2  NAME 3  inherits: \setupmathcases </pre>
<pre> \definemathcommand [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...] {<sup>4</sup>...} 1  NAME                OPT          OPT          OPT 2  ord op bin rel open close punct alpha intern nothing limop nolog box 3  unu doi 4  BEFEHL \...##1 \...##1##2 </pre>
<pre> \definemathdouble [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...] [<sup>4</sup>...] 1  ambele vfenced NAME 2  NAME 3  NUMMER 4  NUMMER </pre>
<pre> \definemathdoubleextensible [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...] [<sup>4</sup>...] 1  ambele vfenced                OPT 2  NAME 3  NUMMER 4  NUMMER </pre>

<pre> \definemathe<sup>1</sup>matics [...]<sup>2</sup> [...]<sup>3</sup> [...,...,...] 1  NAME                                OPT      OPT 2  NAME 3  inherits: \setupmathematics </pre>
<pre> \definemathextensible [...]<sup>1</sup> [...]<sup>2</sup> [...]<sup>3</sup> 1  reverse matematica text chemistry 2  NAME 3  NUMMER </pre>
<pre> \definemathfence [...]<sup>1</sup> [...]<sup>2</sup> [...,...<sup>3</sup>...,...] 1  NAME                                OPT      OPT 2  NAME 3  inherits: \setupmathfence </pre>
<pre> \definemathfraction [...]<sup>1</sup> [...]<sup>2</sup> [...,...<sup>3</sup>...,...] 1  NAME                                OPT      OPT 2  NAME 3  inherits: \setupmathfraction </pre>
<pre> \definemathframed [...]<sup>1</sup> [...]<sup>2</sup> [...,...<sup>3</sup>...,...] 1  NAME                                OPT      OPT 2  NAME 3  inherits: \setupmathframed </pre>
<pre> \definemathmatrix [...]<sup>1</sup> [...]<sup>2</sup> [...,...<sup>3</sup>...,...] 1  NAME                                OPT      OPT 2  NAME 3  inherits: \setupmathmatrix </pre>
<pre> \definemathornament [...]<sup>1</sup> [...]<sup>2</sup> [...,...<sup>3</sup>...,...] 1  NAME                                OPT      OPT 2  NAME 3  inherits: \setupmathornament </pre>
<pre> \definemathover [...]<sup>1</sup> [...]<sup>2</sup> [...]<sup>3</sup> 1  sus vfenced NAME 2  NAME 3  NUMMER </pre>
<pre> \definemathoverextensible [...]<sup>1</sup> [...]<sup>2</sup> [...]<sup>3</sup> 1  sus vfenced                                OPT 2  NAME 3  NUMMER </pre>
<pre> \definemathovertexttextensible [...]<sup>1</sup> [...]<sup>2</sup> [...]<sup>3</sup> 1  bothtext                                OPT 2  NAME 3  NUMMER </pre>
<pre> \definemathradical [...]<sup>1</sup> [...]<sup>2</sup> [...,...<sup>3</sup>...,...] 1  NAME                                OPT      OPT 2  NAME 3  inherits: \setupmathradical </pre>
<pre> \definemathstackers [...]<sup>1</sup> [...]<sup>2</sup> [...,...<sup>3</sup>...,...] 1  NAME                                OPT      OPT 2  NAME 3  inherits: \setupmathstackers </pre>
<pre> \definemathstyle [...]<sup>1</sup> [...,...<sup>2</sup>...] 1  NAME 2  display text script scriptscript cramped uncramped normal impachetat mic mare </pre>

`\definemathtriplet [1...] [2...] [3...]`

1 NAME OPT OPT  
2 NAME  
3 TEXT

`\definemathunder [1...] [2...] [3...]`

1 subsol vfenced NAME  
2 NAME  
3 NUMMER

`\definemathunderextensible [1...] [2...] [3...]`

1 subsol vfenced OPT  
2 NAME  
3 NUMMER

`\definemathundertexttextensible [1...] [2...] [3...]`

1 bothtext OPT  
2 NAME  
3 NUMMER

`\definemathunstacked [1...] [2...] [3...]`

1 larg OPT  
2 NAME  
3 NUMMER

`\definemeasure [1...] [2...]`

1 NAME  
2 DIMENSION

`\definemessageconstant {...}`

\* NAME

`\definemixedcolumns [1...] [2...] [...,3...,...]`

1 NAME OPT OPT  
2 NAME  
3 inherits: \setupmixedcolumns

`\definemode [...,1...] [2...]`

1 NAME OPT  
2 da nu mentine

`\definemultitonecolor [1...] [...,2...,...][...,3...,...][...,4...,...]`

1 NAME OPT  
2 COLOR = NUMMER  
3 inherits: \definesteculoare  
4 inherits: \definespotcolor

`\definenamecolor [1...] [...,2...,...]`

1 NAME  
2 inherits: \definesteculoare

`\definenamecolor [1...] [2...]`

1 NAME  
2 COLOR

`\definenamespace [1...] [...,2...,...]`

1 NAME  
2 nume = TEXT  
parent = TEXT  
stil = da nu  
comanda = da nu lista  
setup = da nu lista  
set = da nu lista  
frame = da nu

<pre> \definennarrower [...] [...] [...] [...] 1 NAME 2 NAME 3 inherits: \seteazaingust </pre>
<pre> \definennote [...] [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setupnote </pre>
<pre> \defineornament [...] [...] [...] [...] 1 NAME 2 alternativ = a b   inherits: \setupcollector 3 stil = STYLE BEFEHL   culoare = COLOR   inherits: \seteazainconjurat </pre>
<pre> \defineornament [...] [...] [...] [...] 1 NAME 2 alternativ = a b   inherits: \setupplayer 3 inherits: \setuplayeredtext </pre>
<pre> \defineoutputroutine [...] [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setupoutputroutine </pre>
<pre> \defineoutputroutinecommand [...,*...] * KEY </pre>
<pre> \definepage [...] [...] 1 NAME 2 REFERENCE </pre>
<pre> \definepagebreak [...] [...] 1 NAME 2 gol antet subsol dummy incadrat NUMMER +NUMMER implicit reset dezactivat da nu marcaj blank preferinta preferintamare   stanga dreapta par impar cvadрупul ultim ultimpagina start stop </pre>
<pre> \definepagechecker [...] [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setuppagechecker </pre>
<pre> \definepagegrid [...] [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setuppagegrid </pre>
<pre> \definepagegridarea [...] [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setuppagegridarea </pre>
<pre> \definepagegridspan [...] [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setuppagegridspan </pre>
<pre> \definepageinjection [...] [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setuppageinjection </pre>



<pre> \definepageinjectionalternative [...] [...] [...] [...] 1  NAME                                OPT      OPT 2  NAME 3  inherits: \setuppageinjectionalternative </pre>
<pre> \definepageshift [...] [...] [...] 1  NAME 2  orizontal vertical 3  DIMENSION </pre>
<pre> \definepagestate [...] [...] [...] 1  NAME                                OPT      OPT 2  NAME 3  inherits: \setuppagestate </pre>
<pre> \definepairedbox [...] [...] [...] 1  NAME                                OPT      OPT 2  NAME 3  inherits: \setuppairedbox </pre>
<pre> \defineparagraph [...] [...] [...] 1  NAME                                OPT      OPT 2  NAME 3  inherits: \setupparagraph </pre>
<pre> \defineparallel [...] [...] 1  NAME 2  NAME </pre>
<pre> \defineparbuilder [...] *  NAME </pre>
<pre> \defineplacement [...] [...] [...] 1  NAME                                OPT      OPT 2  NAME 3  inherits: \setupplacement </pre>
<pre> \definepositioning [...] [...] [...] 1  NAME                                OPT      OPT 2  NAME 3  inherits: \setarepozitie </pre>
<pre> \defineprefixset [...] [...] [...] 1  NAME SECTIONBLOCK:NAME            OPT 2  ABSCHNITT 3  ABSCHNITT </pre>
<pre> \defineprocesscolor [...] [...] [...] 1  NAME                                OPT 2  COLOR 3  inherits: \definesteculoare </pre>
<pre> \defineprocessor [...] [...] [...] 1  NAME                                OPT      OPT 2  NAME 3  inherits: \setupprocessor </pre>
<pre> \definepushbutton [...] [...] 1  NAME                                OPT 2  inherits: \setupfieldcontentframed </pre>
<pre> \definepushsymbol [...] [...] 1  NAME 2  n r d </pre>

<pre> \definerenderingwindow [...] [...] [...] [...] 1  NAME                                OPT      OPT 2  NAME 3  inherits: \setuprenderingwindow </pre>
<pre> \defineresetset [...] [...] [...] 1  NAME SECTIONBLOCK:NAME              OPT 2  NUMMER 3  NUMMER </pre>
<pre> \definescale [...] [...] [...] 1  NAME                                OPT      OPT 2  NAME 3  inherits: \setupscale </pre>
<pre> \definescript [...] [...] [...] 1  NAME                                OPT      OPT 2  NAME 3  inherits: \setupscrip </pre>
<pre> \definesectionlevels [...] [...] 1  NAME 2  ABSCHNITT </pre>
<pre> \defineselector [...] [...] 1  NAME                                OPT 2  inherits: \setupselector </pre>
<pre> \defineseparatorset [...] [...] [...] 1  NAME SECTIONBLOCK:NAME              OPT 2  BEFEHL PROCESSOR-&gt;BEFEHL 3  BEFEHL PROCESSOR-&gt;BEFEHL </pre>
<pre> \defineshift [...] [...] [...] 1  NAME                                OPT      OPT 2  NAME 3  inherits: \setupshift </pre>
<pre> \definesidebar [...] [...] [...] 1  NAME                                OPT      OPT 2  NAME 3  inherits: \setupsidebar </pre>
<pre> \definesort [...] [...] [...] [...] 1  da nu                                OPT 2  SINGULAR 3  NAME 4  CONTENT </pre>
<pre> \definespotcolor [...] [...] [...] 1  NAME 2  COLOR 3  a = NUMMER niciunul normal multiply ecran overlay softlight hardlight colordodge colorburn darken lighten     difference exclusion hue saturation culoare luminosity     t = NUMMER     e = TEXT     p = NUMMER </pre>
<pre> \defineste [...] [...] [...] 1  NUMMER                                OPT 2  CSNAME 3  CONTENT </pre>

`\definesteaccent 1... 2... 3...`

- 1 CHARACTER
- 2 CHARACTER
- 3 CHARACTER

`\definesteantet [...1] [...2] [...,3...,...]`

- 1 NAME OPT OPT
- 2 ABSCHNITT
- 3 inherits: \seteazatitlu

`\definestebloc [...1] [...2] [...,3...,...]`

- 1 NAME OPT OPT
- 2 NAME
- 3 inherits: \seteazabloc

`\definesteblocsectiune [...1] [...2] [...,3...,...]`

- 1 NAME OPT
- 2 NAME
- 3 inherits: \seteazablocsectiune

`\definestebuffer [...1] [...2] [...,3...,...]`

- 1 NAME OPT OPT
- 2 BUFFER
- 3 inherits: \seteazabuffer

`\definestecamp [...1] [...2] [...3] [...,4...] [...5]`

- 1 NAME
- 2 radio sub text linie push check signature
- 3 NAME
- 4 NAME
- 5 NAME

`\definestecaracter 1... 2...`

- 1 CHARACTER
- 2 NUMMER

`\definestecomanda 1... 2...`

- 1 CHARACTER
- 2 BEFEHL

`\definesteconversie [...1] [...2] [...3]`

- 1 SPRACHE OPT
- 2 NAME
- 3 CSNAME

`\definesteconversie [...1] [...2] [...,3...]`

- 1 SPRACHE OPT
- 2 NAME
- 3 TEXT

`\definesteculoare [...1] [...,2...,...]`

- 1 NAME
- 2 r = NUMMER
- g = NUMMER
- b = NUMMER
- c = NUMMER
- m = NUMMER
- y = NUMMER
- k = NUMMER
- h = NUMMER
- s = NUMMER
- v = NUMMER
- x = NUMMER
- a = NUMMER niciunul normal multiply ecran overlay softlight hardlight colordodge colorburn darken lighten difference exclusion hue saturation culoare luminosity
- t = NUMMER

**\definesteculoare** [<sup>1</sup>...] [<sup>2</sup>...]

- 1 NAME
- 2 COLOR

**\definestedescriere** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...<sup>3</sup>...,...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupdescription

**\definestedimensiunehartie** [<sup>1</sup>...] [<sup>2</sup>...,...<sup>2</sup>...,...]

- 1 NAME
- 2 latime = DIMENSION
- inaltime = DIMENSION
- sus = BEFEHL
- jos = BEFEHL
- stanga = BEFEHL
- dreapta = BEFEHL
- distanta = DIMENSION
- pagina = inherits: \seteazadimensiunihartie
- hartie = inherits: \seteazadimensiunihartie

**\definestedimensiunehartie** [<sup>1</sup>...] [<sup>2</sup>...,...<sup>2</sup>...] [<sup>3</sup>...,...<sup>3</sup>...,...]

- 1 NAME
- 2 inherits: \seteazadimensiunihartie
- 3 inherits: \seteazadimensiunihartie

**\definesteenumerare** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...<sup>3</sup>...,...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupenumeration

**\definesteeticheta** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...<sup>3</sup>...,...]

- 1 NAME
- 2 NAME
- 3 inherits: \setuplabel

**\definestefloat** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...<sup>3</sup>...,...]

- 1 SINGULAR
  - 2 SINGULAR PLURAL
  - 3 inherits: \seteazafloat
- instances: chemical figure table intermezzo graphic

**\definestefloat** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...]

- 1 SINGULAR
  - 2 PLURAL
  - 3 SINGULAR
- instances: chemical figure table intermezzo graphic

**\definestefont** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...<sup>3</sup>...,...]

- 1 NAME
- 2 FONT
- 3 inherits: \seteazaspatiuinterliniar

```

\definestefonttext [...] [...] [...] [...]
1 NAME implicit
2 NAME DIMENSION
3 rm ss tt hw cg
4 tf = FILE
bf = FILE
it = FILE
sl = FILE
bi = FILE
bs = FILE
sc = FILE
mr = FILE
mrlr = FILE
mrrl = FILE
mb = FILE
mblr = FILE
mbrl = FILE

```

```

\definestefonttext [...] [...] [...] [...]
1 NAME implicit
2 NAME DIMENSION
3 rm ss tt hw cg
4 NAME

```

```

\definestefont [...] [...] [...]
1 NAME
2 FONT
3 NAME

```

```

\definesteformatreferinte [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupreferenceformat

```

```

\definestegrupculori [...] [...] [x:y:z,...]
1 NAME
2 gri rgb cmyk spot
3 TRIPLET

```

```

\definestehbox [...] [...]
1 NAME
2 DIMENSION

```

```

\definesteinconjurare [...] [...] [...]
1 NAME
2 NAME
3 inherits: \seteazainconjurat

```

```

\definestelista [...] [...] [...]
1 NAME
2 LISTE
3 inherits: \seteazalista

```

```

\definestelistacombinata [...] [...] [...]
1 NAME
2 LISTE
3 inherits: \seteazalista

```

```

\definestemakeup [...] [...] [...]
1 NAME
2 NAME
3 inherits: \seteazamakeup

```

```

\definestemarcaje [...] [...] [...]
1 NAME
2 BESCHRIFTUNG
3 inherits: \seteazamarcaje

```

```

\definestemediulfonttext [...] [...] [...]
1 NAME OPT OPT
2 implicit DIMENSION
3 mare = DIMENSION NUMBER
mic = DIMENSION NUMBER
a = DIMENSION NUMBER
b = DIMENSION NUMBER
c = DIMENSION NUMBER
d = DIMENSION NUMBER
text = DIMENSION NUMBER
x = DIMENSION NUMBER
xx = DIMENSION NUMBER
script = DIMENSION NUMBER
scriptscript = DIMENSION NUMBER
spatiereinterliniara = DIMENSION
em = inclinat italic STYLE BEFEHL
* = NUMBER

```

```

\definestemeniuiinteractiune [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \seteazameniuiinteractiune

```

```

\definesteoverlay [...] [...] [...]
1 NAME OPT
2 NAME
3 BEFEHL

```

```

\definestepaleta [...] [...]
1 NAME
2 NAME = COLOR

```

```

\definestepaleta [...] [...]
1 NAME
2 NAME

```

```

\definesteparagraf [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \seteazaparagrafe

```

```

\definesteprofil [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupprofile

```

```

\definesteprogram [...] [...] [...]
1 NAME OPT
2 TEXT
3 TEXT

```

```

\definestereferinte [...] [...]
1 NAME
2 REFERENCE

```

```

\definesteregistru [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \seteazaregistru

```

```

\definestesablontabel [...] [...] [...] [...]
1 NAME OPT OPT
2 TEMPLATE
3 NAME
4 NAME

```

<pre> \definestesectione [...] *   NAME </pre>
<pre> \definestesimbol [...] [...] [...] 1   NAME 2   NAME 3   BEFEHL </pre>
<pre> \definestesimbolfigura [...] [...] [...] 1   NAME 2   FILE NAME 3   inherits: \figuraexterna </pre>
<pre> \definestesinonim [...] [...] [...] 1   SINGULAR 2   PLURAL 3   CSNAME 4   CSNAME </pre>
<pre> \definestesinonimfont [...] [...] [...] 1   NAME 2   FONT 3   features    = NAME    fallbacks   = NAME    goodies     = NAME    designsize  = auto implicit </pre>
<pre> \definestesortare [...] [...] [...] 1   SINGULAR 2   PLURAL 3   niciunul CSNAME </pre>
<pre> \definestestartstop [...] [...] [...] 1   NAME 2   NAME 3   inherits: \setupstartstop </pre>
<pre> \definestestil [...] [...] [...] 1   NAME 2   NAME 3   inherits: \setupstyle </pre>
<pre> \definestestilfont [...,^...] [...] 1   NAME 2   NAME </pre>
<pre> \definestestivacampuri [...] [...] [...] 1   NAME 2   NAME 3   inherits: \setupfieldcategory </pre>
<pre> \definestesubcamp [...] [...] [...] 1   NAME 2   NAME 3   NAME </pre>
<pre> \definestetabulatori [...] [...] [...] 1   NAME 2   NAME 3   TEMPLATE </pre>

```
\definestetext [...] [...] [...] [...] [...] [...] [...]
1 NAME
2 sus antet text subsol subsol
3 text margine bordura
4 data numarpagina BESCHRIFTUNG TEXT BEFEHL
5 data numarpagina BESCHRIFTUNG TEXT BEFEHL
6 data numarpagina BESCHRIFTUNG TEXT BEFEHL
7 data numarpagina BESCHRIFTUNG TEXT BEFEHL
```

```
\definestetexteinconjugate [...] [...] [...]
1 NAME
2 inherits: \setupframedtext
```

```
\definestetextinconjurat [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupframedtext
```

```
\definestetyping [...] [...] [...]
1 NAME
2 NAME
3 inherits: \seteazatyping
```

```
\definestyleinstance [...] [...] [...]
1 NAME
2 rm ss tt mm hw cg
3 tf bf it sl bi bs sc
4 BEFEHL
```

```
\definesubformula [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupsubformula
```

```
\definesynonym [...] [...] [...] {...} {...}
1 da nu
2 SINGULAR
3 NAME
4 TEXT
5 CONTENT
```

```
\definesystemattribute [...] [...] [...]
1 NAME
2 local global public private
```

```
\definesystemconstant {...}
* NAME
```

```
\definesystemvariable {...}
* NAME
```

```
\defineTABLEsetup [...] [...] [...]
1 NAME
2 inherits: \setupTABLE
```

```
\definetabulation [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setuptabulation
```

```
\definetextbackground [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setuptextbackground
```



<pre> \definetextflow [...] [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setuptextflow </pre>
<pre> \definetooltip [...] [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setuptooltip </pre>
<pre> \definetransparency [...] [...] 1 NAME 2 NUMMER </pre>
<pre> \definetransparency [...] [...] 1 NAME 2 a = NUMMER niciunul normal multiply ecran overlay softlight hardlight colordodge colorburn darken lighten difference exclusion hue saturation culoare luminosity t = NUMMER </pre>
<pre> \definetransparency [...] [...] 1 NAME 2 NAME </pre>
<pre> \definetwopasslist {...} * NAME </pre>
<pre> \definetype [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \seteazatype </pre>
<pre> \definetypeface [...] [...] [...] [...] [...] [...] 1 NAME OPT OPT 2 rm ss tt mm hw cg 3 serif sans mono math handwriting calligraphy 4 NAME 5 implicit dtp 6 rscale = auto NUMMER features = NAME fallbacks = NAME goodies = NAME designsize = auto implicit directie = ambele </pre>
<pre> \definetypescriptprefix [...] [...] 1 NAME 2 TEXT </pre>
<pre> \definetypescriptsynonym [...] [...] 1 NAME 2 TEXT </pre>
<pre> \definetypesetting [...] [...] [...] 1 NAME OPT OPT 2 TEXT 3 inherits: \setuexternalfigure </pre>
<pre> \defineunit [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupunit </pre>

$\backslash$ <b>defineviewerlayer</b> [ <sup>1</sup> ...] [ <sup>2</sup> ...] [ <sup>3</sup> ... <sub>OPT</sub> ... <sub>OPT</sub> ...] 1 NAME 2 NAME 3 inherits: \setupviewerlayer
$\backslash$ <b>definespace</b> [ <sup>1</sup> ...] [ <sup>2</sup> ...] [ <sup>3</sup> ...] 1 NAME 2 NAME 3 DIMENSION
$\backslash$ <b>definevspacing</b> [ <sup>1</sup> ...] [ <sup>2</sup> ...] 1 NAME 2 inherits: \vspacing
$\backslash$ <b>definevspacingamount</b> [ <sup>1</sup> ...] [ <sup>2</sup> ...] [ <sup>3</sup> ...] 1 NAME 2 DIMENSION 3 DIMENSION
$\backslash$ <b>definetable</b> [ <sup>1</sup> ...] [ <sup>2</sup> ...] [ <sup>3</sup> ... <sub>OPT</sub> ... <sub>OPT</sub> ...] 1 NAME 2 NAME 3 inherits: \setupxtable
$\backslash$ <b>delimited</b> [ <sup>1</sup> ...] [ <sup>2</sup> ...] { <sup>3</sup> ...} 1 NAME 2 SPRACHE 3 CONTENT
$\backslash$ <b>delimitedtext</b> [ <sup>1</sup> ...] [ <sup>2</sup> ...] { <sup>3</sup> ...} 1 NAME 2 SPRACHE 3 CONTENT
$\backslash$ <b>DELIMITEDTEXT</b> [ <sup>1</sup> ...] { <sup>2</sup> ...} 1 SPRACHE 2 CONTENT <b>instances:</b> quotation quote blockquote speech aside
$\backslash$ <b>aside</b> [ <sup>1</sup> ...] { <sup>2</sup> ...} 1 SPRACHE <sub>OPT</sub> 2 CONTENT
$\backslash$ <b>blockquote</b> [ <sup>1</sup> ...] { <sup>2</sup> ...} 1 SPRACHE 2 CONTENT
$\backslash$ <b>quotation</b> [ <sup>1</sup> ...] { <sup>2</sup> ...} 1 SPRACHE 2 CONTENT
$\backslash$ <b>quote</b> [ <sup>1</sup> ...] { <sup>2</sup> ...} 1 SPRACHE <sub>OPT</sub> 2 CONTENT
$\backslash$ <b>speech</b> [ <sup>1</sup> ...] { <sup>2</sup> ...} 1 SPRACHE <sub>OPT</sub> 2 CONTENT
$\backslash$ <b>depthofstring</b> {*.} * TEXT

<p><code>\depthonlybox {...}</code></p> <p>*    CONTENT</p>
<p><code>\depthspanningtext {...} {...} {...}</code></p> <p>1    TEXT</p> <p>2    DIMENSION</p> <p>3    FONT</p>
<p><code>\depthstrut</code></p>
<p><code>\DESCRIERE [...<sup>1</sup>,...] {...<sup>2</sup>} ...<sup>3</sup> \par</code></p> <p>1    REFERENCE            OPT            OPT</p> <p>2    TEXT</p> <p>3    CONTENT</p>
<p><code>\despre [...]</code></p> <p>*    REFERENCE</p>
<p><code>\determinacaracteristicilelistei [...<sup>1</sup>,...] [...<sup>2</sup>...<sup>2</sup>...]</code></p> <p>1    LISTE</p> <p>2    inherits: \seteazalista</p>
<p><code>\determinacaracteristiciregistru [...<sup>1</sup>] [...<sup>2</sup>...<sup>2</sup>...]</code></p> <p>1    NAME</p> <p>2    language        = implicit DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-sc9 SPRACHE</p> <p>     metoda        = implicit inainte dupa primul ultim ch mm zm pm mc zc pc uc</p> <p>     numberorder   = numere</p> <p>     compress       = da nu tot</p> <p>     criteriu       = local text curent precedent tot ABSCHNITT</p>
<p><code>\determinanumartitlu [...]</code></p> <p>*    ABSCHNITT</p>
<p><code>\determinenoflines {...}</code></p> <p>*    CONTENT</p>
<p><code>\devanagarinumeralis {...}</code></p> <p>*    NUMMER</p>
<p><code>\digits {...}</code></p> <p>*    NUMMER</p>
<p><code>\digits ...</code></p> <p>*    NUMMER</p>
<p><code>\dimensiontocount {...} \<sup>2</sup>...</code></p> <p>1    DIMENSION</p> <p>2    CSNAME</p>
<p><code>\din [...]</code></p> <p>*    REFERENCE</p>
<p><code>\directboxfromcache {...} {...<sup>2</sup>}</code></p> <p>1    NAME</p> <p>2    NUMMER TEXT</p>
<p><code>\directcolor [...]</code></p> <p>*    COLOR</p>

<code>\directcolored [...,*...]</code> * inherits: \definesteculoare
<code>\directcolored [...]</code> * COLOR
<code>\directconvertedcounter {...} {...}</code> 1 NAME 2 primul precedent urmatorul ultim numar
<code>\directcopyboxfromcache {...} {...}</code> 1 NAME 2 NUMMER TEXT
<code>\directdummyparameter {...}</code> * KEY
<code>\directgetboxllx ...</code> * CSNAME NUMBER
<code>\directgetboxlly ...</code> * CSNAME NUMBER
<code>\directhighlight {...} {...}</code> 1 NAME 2 TEXT
<code>\directlocalframed [...] {...}</code> 1 NAME 2 CONTENT
<code>\directluacode {...}</code> * BEFEHL
<code>\directselect {...} {...} {...} {...} {...} {...}</code> 1 NAME 2 CONTENT 3 CONTENT 4 CONTENT 5 CONTENT 6 CONTENT
<code>\directsetbar {...}</code> * NAME
<code>\directsetup {...}</code> * NAME
<code>\directsymbol {...} {...}</code> 1 NAME 2 NAME
<code>\directvspacing {...,*...}</code> * inherits: \vspacing
<code>\dis {...}</code> * CONTENT
<code>\disabledirectives [...,*...]</code> * NAME

\disableexperiments [...,*,...] *   NAME
\disablemode [...,*,...] *   NAME
\disableoutputstream
\disableparpositions
\disableregime
\disabletrackers [...,*,...] *   NAME
\displaymath {...} *   CONTENT
\displaymathematics {...} *   CONTENT
\displaymessage {...} *   TEXT
\distributedhsize {...} {...} {...} 1   DIMENSION 2   DIMENSION 3   NUMMER
\dividedsize {...} {...} {...} 1   DIMENSION 2   DIMENSION 3   NUMMER
\doadaptleftskip {...} *   da nu standard DIMENSION
\doadaptrightskip {...} *   da nu standard DIMENSION
\doaddfeature [...,*,...] *   NAME
\doassign [... <sup>1</sup> ] [... <sup>2</sup> ...] 1   TEXT 2   KEY = VALUE
\doassignempty [... <sup>1</sup> ] [... <sup>2</sup> ...] 1   TEXT 2   KEY = VALUE
\doboundtext {... <sup>1</sup> } {... <sup>2</sup> } {... <sup>3</sup> .} 1   TEXT 2   DIMENSION 3   BEFEHL
\docheckassignment {...} *   TEXT

\docheckedpagestate {...} {...} {...} {...} {...} {...} {...} 1 REFERENCE 2 BEFEHL 3 BEFEHL 4 BEFEHL 5 BEFEHL 6 BEFEHL 7 BEFEHL
\docheckedpair {...,*...} * TEXT
\documentvariable {...} * KEY
\dodoubleargument \ <sup>1</sup> ... [ <sup>2</sup> ...] [ <sup>3</sup> ...] 1 CSNAME 2 TEXT 3 TEXT
\dodoubleargumentwithset \ <sup>1</sup> ... [..., <sup>2</sup> ...] [ <sup>3</sup> ...] 1 CSNAME 2 TEXT 3 TEXT
\dodoubleempty \ <sup>1</sup> ... [ <sup>2</sup> ...] [ <sup>3</sup> ...] 1 CSNAME OPT OPT 2 TEXT 3 TEXT
\dodoubleemptywithset \ <sup>1</sup> ... [..., <sup>2</sup> ...] [ <sup>3</sup> ...] 1 CSNAME OPT OPT 2 TEXT 3 TEXT
\dodoublegroupempty \ <sup>1</sup> ... { <sup>2</sup> ...} { <sup>3</sup> ...} 1 CSNAME OPT OPT 2 TEXT 3 TEXT
\doeassign [... <sup>1</sup> ] [... <sup>2</sup> ...] 1 TEXT 2 KEY = VALUE
\doexpandedrecurse {... <sup>1</sup> } {... <sup>2</sup> } 1 NUMMER 2 BEFEHL
\dofastloopcs {... <sup>1</sup> } \ <sup>2</sup> .. 1 NUMMER 2 CSNAME
\dogetattribute {...} * NAME
\dogetattributeid {...} * NAME
\dogetcommacommandelement <sup>1</sup> ... \from <sup>2</sup> ... \to \ <sup>3</sup> .. 1 NUMMER 2 TEXT 3 CSNAME

<pre> \dogobbledoubleempty [...] [...] 1  TEXT          OPT      OPT 2  TEXT </pre>
<pre> \dogobblesingleempty [...] *  TEXT          OPT </pre>
<pre> \doif {.<sup>1</sup>.} {..<sup>2</sup>.} {..<sup>3</sup>.} 1  CONTENT 2  CONTENT 3  TRUE </pre>
<pre> \doifallcommon {...,<sup>1</sup>...} {...,<sup>2</sup>...} {..<sup>3</sup>.} 1  TEXT 2  TEXT 3  TRUE </pre>
<pre> \doifallcommonelse {...,<sup>1</sup>...} {...,<sup>2</sup>...} {..<sup>3</sup>.} {..<sup>4</sup>.} 1  TEXT 2  TEXT 3  TRUE 4  FALSE </pre>
<pre> \doifalldefinedelse {...,<sup>1</sup>...} {..<sup>2</sup>.} {..<sup>3</sup>.} 1  NAME 2  TRUE 3  FALSE </pre>
<pre> \doifallmodes {...,<sup>1</sup>...} {..<sup>2</sup>.} {..<sup>3</sup>.} 1  NAME 2  TRUE 3  FALSE </pre>
<pre> \doifallmodeselse {...,<sup>1</sup>...} {..<sup>2</sup>.} {..<sup>3</sup>.} 1  NAME 2  TRUE 3  FALSE </pre>
<pre> \doifassignmentelse {..<sup>1</sup>.} {..<sup>2</sup>.} {..<sup>3</sup>.} 1  TEXT 2  TRUE 3  FALSE </pre>
<pre> \doifblackelse {..<sup>1</sup>.} {..<sup>2</sup>.} {..<sup>3</sup>.} 1  COLOR 2  TRUE 3  FALSE </pre>
<pre> \doifbothsides {..<sup>1</sup>.} {..<sup>2</sup>.} {..<sup>3</sup>.} 1  BEFEHL 2  BEFEHL 3  BEFEHL </pre>
<pre> \doifbothsidesoverruled {..<sup>1</sup>.} {..<sup>2</sup>.} {..<sup>3</sup>.} 1  BEFEHL 2  BEFEHL 3  BEFEHL </pre>
<pre> \doifboxelse {..<sup>1</sup>.} {..<sup>2</sup>.} {..<sup>3</sup>.} {..<sup>4</sup>.} 1  NAME 2  NAME 3  TRUE 4  FALSE </pre>

`\doifbufferelse {...} {...} {...}`

1 BUFFER  
2 TRUE  
3 FALSE

`\doifcolor {...} {...}`

1 COLOR  
2 TRUE

`\doifcolorelse {...} {...} {...}`

1 COLOR  
2 TRUE  
3 FALSE

`\doifcommandhandler \... {...} {...}`

1 CSNAME  
2 NAME  
3 TRUE

`\doifcommandhandlerelse \... {...} {...} {...}`

1 CSNAME  
2 NAME  
3 TRUE  
4 FALSE

`\doifcommon {...,1...} {...,2...} {...}`

1 TEXT  
2 TEXT  
3 TRUE

`\doifcommonelse {...,1...} {...,2...} {...} {...}`

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

`\doifcontent {...} {...} {...} \...4 {...5}`

1 BEFEHL  
2 BEFEHL  
3 BEFEHL  
4 CSNAME  
5 CONTENT

`\doifconversiondefinedelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifconversionnumberelse {...} {...} {...} {...}`

1 NAME  
2 NUMMER  
3 TRUE  
4 FALSE

`\doifcounter {...} {...}`

1 NAME  
2 TRUE

`\doifcounterelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE



<pre> \doifcurrentfonthasfeatureelse {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifdefined {...} {...} 1 NAME 2 TRUE </pre>
<pre> \doifdefinedcounter {...} {...} 1 NAME 2 TRUE </pre>
<pre> \doifdefinedcounterelse {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifdefinedelse {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifdimensionelse {...} {...} {...} 1 TEXT 2 TRUE 3 FALSE </pre>
<pre> \doifdimenstringelse {...} {...} {...} 1 TEXT 2 TRUE 3 FALSE </pre>
<pre> \doifdocumentargument {...} {...} 1 NAME 2 TRUE </pre>
<pre> \doifdocumentargumentelse {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifdocumentfilename {...} {...} 1 NUMMER 2 TRUE </pre>
<pre> \doifdocumentfilenameelse {...} {...} {...} 1 NUMMER 2 TRUE 3 FALSE </pre>
<pre> \doifdrawingblackelse {...} {...} 1 TRUE 2 FALSE </pre>
<pre> \doifelse {...} {...} {...} {...} 1 CONTENT 2 CONTENT 3 TRUE 4 FALSE </pre>

```
\doifelseallcommon {...,1...} {...,2...} {...} {...}
1 TEXT
2 TEXT
3 TRUE
4 FALSE
```

```
\doifelsealldefined {...,1...} {...} {...}
1 NAME
2 TRUE
3 FALSE
```

```
\doifelseallmodes {...,1...} {...} {...}
1 NAME
2 TRUE
3 FALSE
```

```
\doifelseassignment {...1} {...2} {...3}
1 TEXT
2 TRUE
3 FALSE
```

```
\doifelseblack {...1} {...2} {...3}
1 COLOR
2 TRUE
3 FALSE
```

```
\doifelsebox {...1} {...2} {...3} {...4}
1 NAME
2 NAME
3 TRUE
4 FALSE
```

```
\doifelseboxincache {...1} {...2} {...3} {...4}
1 NAME
2 NUMMER TEXT
3 TRUE
4 FALSE
```

```
\doifelsebuffer {...1} {...2} {...3}
1 BUFFER
2 TRUE
3 FALSE
```

```
\doifelsecolor {...1} {...2} {...3}
1 COLOR
2 TRUE
3 FALSE
```

```
\doifelsecommandhandler \...1 {...2} {...3} {...4}
1 CSNAME
2 NAME
3 TRUE
4 FALSE
```

```
\doifelsecommon {...,1...} {...,2...} {...} {...4}
1 TEXT
2 TEXT
3 TRUE
4 FALSE
```

```
\doifelseconversiondefined {...1} {...2} {...3}
1 NAME
2 TRUE
3 FALSE
```

\doifelseconversionnumber {...} {...} {...} {...}

1 NAME  
2 NUMMER  
3 TRUE  
4 FALSE

\doifelsecounter {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsecurrentfonthasfeature {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsecurrentsortingused {...} {...}

1 TRUE  
2 FALSE

\doifelsecurrentsynonymshown {...} {...}

1 TRUE  
2 FALSE

\doifelsecurrentsynonymused {...} {...}

1 TRUE  
2 FALSE

\doifelsedefined {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsedefinedcounter {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsedimension {...} {...} {...}

1 TEXT  
2 TRUE  
3 FALSE

\doifelsedimenstring {...} {...} {...}

1 TEXT  
2 TRUE  
3 FALSE

\doifelsedocumentargument {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsedocumentfilename {...} {...} {...}

1 NUMMER  
2 TRUE  
3 FALSE

\doifelsedrawingblack {...} {...}

1 TRUE  
2 FALSE

`\doifelseempty {...} {...} {...}`

1 CONTENT  
2 TRUE  
3 FALSE

`\doifelseemptyvalue {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifelseemptyvariable {...} {...} {...} {...}`

1 NAME  
2 KEY  
3 TRUE  
4 FALSE

`\doifelseenv {...} {...} {...}`

1 KEY  
2 TRUE  
3 FALSE

`\doifelsefastoptionalcheck {...} {...}`

1 TRUE  
2 FALSE

`\doifelsefastoptionalcheckcs \^1 \^2`

1 CSNAME  
2 CSNAME

`\doifelsefieldbody {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifelsefieldcategory {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifelsefigure {...} {...} {...}`

1 FILE  
2 TRUE  
3 FALSE

`\doifelsefile {...} {...} {...}`

1 FILE  
2 TRUE  
3 FALSE

`\doifelsefiledefined {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifelsefileexists {...} {...} {...}`

1 FILE  
2 TRUE  
3 FALSE

`\doifelsefirstchar {...} {...} {...} {...}`

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

\doifelseflagged {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsefontchar {...} {...} {...} {...}

1 FONT  
2 NUMBER  
3 TRUE  
4 FALSE

\doifelsefontpresent {...} {...} {...}

1 FONT  
2 TRUE  
3 FALSE

\doifelsefontsynonym {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsehasspace {...} {...} {...}

1 TEXT  
2 TRUE  
3 FALSE

\doifelsehelp {...} {...}

1 TRUE  
2 FALSE

\doifelseincsname {...} {...} {...} {...}

1 TEXT  
2 CSNAME  
3 TRUE  
4 FALSE

\doifelseinelement {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelseinputfile {...} {...} {...}

1 FILE  
2 TRUE  
3 FALSE

\doifelseinsertion {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelseinset {...} {...,<sup>2</sup>...} {...} {...<sup>4</sup>}

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

\doifelseinstring {...} {...} {...} {...<sup>4</sup>}

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

`\doifelseinsymbolset {...} {...} {...} {...}`

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

`\doifelseintoks {...} {...} {...} {...}`

1 BEFEHL  
2 BEFEHL  
3 TRUE  
4 FALSE

`\doifelseintwopassdata {...} {...} {...} {...}`

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

`\doifelseitalic {...} {...}`

1 TRUE  
2 FALSE

`\doifelselanguage {...} {...} {...}`

1 SPRACHE  
2 TRUE  
3 FALSE

`\doifelselayerdata {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifelselayoutdefined {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifelselayoutsomeline {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifelselayouttextline {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifelseleapyear {...} {...} {...}`

1 NUMMER  
2 TRUE  
3 FALSE

`\doifelselist {...} {...} {...}`

1 LISTE  
2 TRUE  
3 FALSE

`\doifelselocation {...} {...}`

1 TRUE  
2 FALSE

`\doifselocfile {...} {...} {...}`

1 FILE  
2 TRUE  
3 FALSE

\doifelseMPgraphic {...} {...} {...} 1 NAME 2 TRUE 3 FALSE
\doifelsemainfloatbody {...} {...} 1 TRUE 2 FALSE
\doifelsemarkedpage {...} {...} {...} 1 NAME 2 TRUE 3 FALSE
\doifelsemarking {...} {...} {...} 1 BESCHRIFTUNG 2 TRUE 3 FALSE
\doifelsemeaning \^1... \^2... {...} {...} 1 CSNAME 2 CSNAME 3 TRUE 4 FALSE
\doifelsemessage {...} {...} {...} {...} 1 NAME 2 NAME NUMBER 3 TRUE 4 FALSE
\doifelsemode {..., <sup>1</sup> ...} {...} {...} 1 NAME 2 TRUE 3 FALSE
\doifelsenextbgroup {...} {...} 1 TRUE 2 FALSE
\doifelsenextbgroupcs \^1... \^2... 1 CSNAME 2 CSNAME
\doifelsenextchar {...} {...} {...} 1 CHARACTER 2 TRUE 3 FALSE
\doifelsenextoptional {...} {...} 1 TRUE 2 FALSE
\doifelsenextoptionalcs \^1... \^2... 1 CSNAME 2 CSNAME
\doifelsenextparenthesis {...} {...} 1 TRUE 2 FALSE

\doifelsenonzeropositive {...} {...} {...}

1 NUMMER  
2 TRUE  
3 FALSE

\doifelsenoteonsamepage {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsenothing {...} {...} {...}

1 TEXT  
2 TRUE  
3 FALSE

\doifelsenumber {...} {...} {...}

1 TEXT  
2 TRUE  
3 FALSE

\doifelseobjectfound {...} {...} {...} {...}

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

\doifelseobjectreferencefound {...} {...} {...} {...}

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

\doifelseoddpage {...} {...}

1 BEFEHL  
2 BEFEHL

\doifelseoddpagefloat {...} {...}

1 TRUE  
2 FALSE

\doifelseoldercontext {...} {...} {...}

1 NUMMER  
2 TRUE  
3 FALSE

\doifelseolderversion {...} {...} {...} {...}

1 NUMMER  
2 NUMMER  
3 TRUE  
4 FALSE

\doifelseoverlapping {...} {...} {...} {...}

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

\doifelseoverlay {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE



```
\doifelseparallel {...} {...,2...} {...} {...}
1 NAME
2 NAME tot
3 TRUE
4 FALSE
```

```
\doifelseparentfile {...} {...} {...}
1 FILE
2 TRUE
3 FALSE
```

```
\doifelsepath {...} {...} {...}
1 PATH
2 TRUE
3 FALSE
```

```
\doifelsepathexists {...} {...} {...}
1 PATH
2 TRUE
3 FALSE
```

```
\doifelsepatterns {...} {...} {...}
1 SPRACHE
2 TRUE
3 FALSE
```

```
\doifelseposition {...} {...} {...}
1 NAME
2 TRUE
3 FALSE
```

```
\doifelsepositionaction {...} {...} {...}
1 NAME
2 TRUE
3 FALSE
```

```
\doifelsepositiononpage {...} {...} {...} {...}
1 NAME
2 NUMMER
3 TRUE
4 FALSE
```

```
\doifelsepositionsonsamepage {...,1...} {...} {...}
1 NAME
2 TRUE
3 FALSE
```

```
\doifelsepositionsonthispage {...,1...} {...} {...}
1 NAME
2 TRUE
3 FALSE
```

```
\doifelsepositionsused {...} {...}
1 TRUE
2 FALSE
```

```
\doifelserreferencefound {...} {...} {...}
1 REFERENCE
2 TRUE
3 FALSE
```

```
\doifelserightpagefloat {...} {...}
1 TRUE
2 FALSE
```

\doifelserighttopleftinbox <sup>1</sup> {...} {...}

1 CSNAME NUMBER  
2 TRUE  
3 FALSE

\doifelsesamelinereference <sup>1</sup> {...} <sup>2</sup> {...} <sup>3</sup> {...}

1 REFERENCE  
2 TRUE  
3 FALSE

\doifelsesamestring <sup>1</sup> {...} <sup>2</sup> {...} <sup>3</sup> {...} <sup>4</sup> {...}

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

\doifelsesetups <sup>1</sup> {...} <sup>2</sup> {...} <sup>3</sup> {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsesomebackground <sup>1</sup> {...} <sup>2</sup> {...} <sup>3</sup> {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsesomespace <sup>1</sup> {...} <sup>2</sup> {...} <sup>3</sup> {...}

1 TEXT  
2 TRUE  
3 FALSE

\doifelsesomething <sup>1</sup> {...} <sup>2</sup> {...} <sup>3</sup> {...}

1 TEXT  
2 TRUE  
3 FALSE

\doifelsesometoks <sup>1</sup> {...} <sup>2</sup> {...} <sup>3</sup> {...}

1 CSNAME  
2 TRUE  
3 FALSE

\doifelsestringinstring <sup>1</sup> {...} <sup>2</sup> {...} <sup>3</sup> {...} <sup>4</sup> {...}

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

\doifelsestructurelisthasnumber <sup>1</sup> {...} <sup>2</sup> {...}

1 TRUE  
2 FALSE

\doifelsestructurelisthaspage <sup>1</sup> {...} <sup>2</sup> {...}

1 TRUE  
2 FALSE

\doifelsesymboldefined <sup>1</sup> {...} <sup>2</sup> {...} <sup>3</sup> {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsesymbolset <sup>1</sup> {...} <sup>2</sup> {...} <sup>3</sup> {...}

1 NAME  
2 TRUE  
3 FALSE

<pre> \doifelsetext {...} {...} {...} 1 TEXT 2 TRUE 3 FALSE </pre>
<pre> \doifelsetextflow {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifelsetextflowcollector {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifelsetopofpage {...} {...} 1 TRUE 2 FALSE </pre>
<pre> \doifelsetypingfile {...} {...} {...} 1 FILE 2 TRUE 3 FALSE </pre>
<pre> \doifelseundefined {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifelseurldefined {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifelsevalue {...} {...} {...} {...} 1 NAME 2 TEXT 3 TRUE 4 FALSE </pre>
<pre> \doifelsevaluenothing {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifelsevariable {...} {...} {...} {...} 1 NAME 2 KEY 3 TRUE 4 FALSE </pre>
<pre> \doifempty {...} {...} 1 CONTENT 2 TRUE </pre>
<pre> \doifemptyelse {...} {...} {...} 1 CONTENT 2 TRUE 3 FALSE </pre>
<pre> \doifemptytoks \... {...} 1 CSNAME 2 TRUE </pre>

<pre> \doifemptyvalue {...} {...} 1  NAME 2  TRUE </pre>
<pre> \doifemptyvalueelse {...} {...} {...} 1  NAME 2  TRUE 3  FALSE </pre>
<pre> \doifemptyvariable {...} {...} {...} 1  NAME 2  KEY 3  TRUE </pre>
<pre> \doifemptyvariableelse {...} {...} {...} {...} 1  NAME 2  KEY 3  TRUE 4  FALSE </pre>
<pre> \doifenv {...} {...} 1  KEY 2  TRUE </pre>
<pre> \doifenvelse {...} {...} {...} 1  KEY 2  TRUE 3  FALSE </pre>
<pre> \doiffastoptionalcheckcselse \.^... \.^... 1  CSNAME 2  CSNAME </pre>
<pre> \doiffastoptionalcheckelse {...} {...} 1  TRUE 2  FALSE </pre>
<pre> \doiffielddbodyelse {...} {...} {...} 1  NAME 2  TRUE 3  FALSE </pre>
<pre> \doiffielddcategoryelse {...} {...} {...} 1  NAME 2  TRUE 3  FALSE </pre>
<pre> \doiffigureelse {...} {...} {...} 1  FILE 2  TRUE 3  FALSE </pre>
<pre> \doiffile {...} {...} 1  FILE 2  TRUE </pre>
<pre> \doiffiledefinedelse {...} {...} {...} 1  NAME 2  TRUE 3  FALSE </pre>

\doiffileelse {...} {...} {...}

1 FILE  
2 TRUE  
3 FALSE

\doiffileexistseelse {...} {...} {...}

1 FILE  
2 TRUE  
3 FALSE

\doiffirstcharelse {...} {...} {...} {...}

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

\doifflaggedelse {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doiffontcharelse {...} {...} {...} {...}

1 FONT  
2 NUMBER  
3 TRUE  
4 FALSE

\doiffontpresentelse {...} {...} {...}

1 FONT  
2 TRUE  
3 FALSE

\doiffontsynonymelse {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifhasspaceelse {...} {...} {...}

1 TEXT  
2 TRUE  
3 FALSE

\doifhelpelse {...} {...}

1 TRUE  
2 FALSE

\doifincsnameelse {...} {...} {...} {...}

1 TEXT  
2 CSNAME  
3 TRUE  
4 FALSE

\doifinelementelse {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifinputfileelse {...} {...} {...}

1 FILE  
2 TRUE  
3 FALSE

**\doifinsertionelse** {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

**\doifinset** {...} {...,<sup>2</sup>...} {...<sup>3</sup>}

1 TEXT  
2 TEXT  
3 TRUE

**\doifinsetelse** {...} {...,<sup>2</sup>...} {...} {...<sup>4</sup>}

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

**\doifinstring** {...} {...<sup>2</sup>} {...<sup>3</sup>}

1 TEXT  
2 TEXT  
3 TRUE

**\doifinstringelse** {...} {...<sup>2</sup>} {...<sup>3</sup>} {...<sup>4</sup>}

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

**\doifinsymbolset** {...} {...} {...} {...<sup>4</sup>}

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

**\doifinsymbolsetelse** {...} {...} {...} {...<sup>4</sup>}

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

**\doifintokselse** {...} {...} {...} {...<sup>4</sup>}

1 BEFEHL  
2 BEFEHL  
3 TRUE  
4 FALSE

**\doifintwopassdataelse** {...} {...} {...} {...<sup>4</sup>}

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

**\doifitalicelse** {...} {...<sup>2</sup>}

1 TRUE  
2 FALSE

**\doiflanguageelse** {...} {...} {...<sup>3</sup>}

1 SPRACHE  
2 TRUE  
3 FALSE

**\doiflayerdataelse** {...} {...} {...<sup>3</sup>}

1 NAME  
2 TRUE  
3 FALSE

`\doiflayoutdefinedelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doiflayoutsomelineelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doiflayouttextlineelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifleapyearelse {...} {...} {...}`

1 NUMMER  
2 TRUE  
3 FALSE

`\doiflistelse {...} {...} {...}`

1 LISTE  
2 TRUE  
3 FALSE

`\doiflocationelse {...} {...}`

1 TRUE  
2 FALSE

`\doiflocfileelse {...} {...} {...}`

1 FILE  
2 TRUE  
3 FALSE

`\doifMPgraphicelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifmainfloatbodyelse {...} {...}`

1 TRUE  
2 FALSE

`\doifmarkingelse {...} {...} {...}`

1 BESCHRIFTUNG  
2 TRUE  
3 FALSE

`\doifmeaningelse \... \... {...} {...}`

1 CSNAME  
2 CSNAME  
3 TRUE  
4 FALSE

`\doifmessageelse {...} {...} {...} {...}`

1 NAME  
2 NAME NUMMER  
3 TRUE  
4 FALSE

`\doifmode {...,1...} {...2}`

1 NAME  
2 TRUE

<pre> \doifmodeelse {...,<sup>1</sup>...} {...<sup>2</sup>} {...<sup>3</sup>} 1  NAME 2  TRUE 3  FALSE </pre>
<pre> \doifnextbgroupcselse \<sup>1</sup>... \<sup>2</sup>... 1  CSNAME 2  CSNAME </pre>
<pre> \doifnextbgroupelse {...<sup>1</sup>} {...<sup>2</sup>} 1  TRUE 2  FALSE </pre>
<pre> \doifnextcharelse {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} 1  CHARACTER 2  TRUE 3  FALSE </pre>
<pre> \doifnextoptionalcselse \<sup>1</sup>... \<sup>2</sup>... 1  CSNAME 2  CSNAME </pre>
<pre> \doifnextoptionalelse {...<sup>1</sup>} {...<sup>2</sup>} 1  TRUE 2  FALSE </pre>
<pre> \doifnextparenthesiselse {...<sup>1</sup>} {...<sup>2</sup>} 1  TRUE 2  FALSE </pre>
<pre> \doifnonzeropositiveelse {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} 1  NUMBER 2  TRUE 3  FALSE </pre>
<pre> \doifnot {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} 1  CONTENT 2  CONTENT 3  TRUE </pre>
<pre> \doifnotallcommon {...,<sup>1</sup>...} {...,<sup>2</sup>...} {...<sup>3</sup>} 1  TEXT 2  TEXT 3  TRUE </pre>
<pre> \doifnotallmodes {...,<sup>1</sup>...} {...<sup>2</sup>} {...<sup>3</sup>} 1  NAME 2  TRUE 3  FALSE </pre>
<pre> \doifnotcommandhandler \<sup>1</sup>... {...<sup>2</sup>} {...<sup>3</sup>} 1  CSNAME 2  NAME 3  TRUE </pre>
<pre> \doifnotcommon {...,<sup>1</sup>...} {...,<sup>2</sup>...} {...<sup>3</sup>} 1  TEXT 2  TEXT 3  TRUE </pre>
<pre> \doifnotcounter {...<sup>1</sup>} {...<sup>2</sup>} 1  NAME 2  TRUE </pre>



<pre> \doifnotdocumentargument {...} {...} 1 NAME 2 TRUE </pre>
<pre> \doifnotdocumentfilename {...} {...} 1 NUMMER 2 TRUE </pre>
<pre> \doifnotempty {...} {...} 1 CONTENT 2 TRUE </pre>
<pre> \doifnotemptyvalue {...} {...} 1 NAME 2 TRUE </pre>
<pre> \doifnotemptyvariable {...} {...} {...} 1 NAME 2 KEY 3 TRUE </pre>
<pre> \doifnotenv {...} {...} 1 KEY 2 TRUE </pre>
<pre> \doifnoteonsamepageelse {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifnotescollected {...} {...} 1 NAME 2 TRUE </pre>
<pre> \doifnotfile {...} {...} 1 FILE 2 TRUE </pre>
<pre> \doifnotflagged {...} {...} 1 NAME 2 TRUE </pre>
<pre> \doifnothing {...} {...} 1 TEXT 2 TRUE </pre>
<pre> \doifnothingelse {...} {...} {...} 1 TEXT 2 TRUE 3 FALSE </pre>
<pre> \doifnotinset {...} {...<sup>2</sup>,...} {...<sup>3</sup>} 1 TEXT 2 TEXT 3 TRUE </pre>
<pre> \doifnotinsidesplitfloat {...} * TRUE </pre>
<pre> \doifnotinstring {...} {...} {...} 1 TEXT 2 TEXT 3 TRUE </pre>

<pre> \doifnotmode {...<sup>1</sup>,...} {...<sup>2</sup>} 1  NAME 2  TRUE </pre>
<pre> \doifnotnumber {...<sup>1</sup>} {...<sup>2</sup>} 1  TEXT 2  TRUE </pre>
<pre> \doifnotsamestring {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} 1  TEXT 2  TEXT 3  TRUE </pre>
<pre> \doifnotsetups {...<sup>1</sup>} {...<sup>2</sup>} 1  NAME 2  TRUE </pre>
<pre> \doifnotvalue {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} 1  NAME 2  TEXT 3  TRUE </pre>
<pre> \doifnotvariable {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} 1  NAME 2  KEY 3  TRUE </pre>
<pre> \doifnumber {...<sup>1</sup>} {...<sup>2</sup>} 1  TEXT 2  TRUE </pre>
<pre> \doifnumberelse {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} 1  TEXT 2  TRUE 3  FALSE </pre>
<pre> \doifobjectfoundelse {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} {...<sup>4</sup>} 1  NAME 2  NAME 3  TRUE 4  FALSE </pre>
<pre> \doifobjectreferencefoundelse {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} {...<sup>4</sup>} 1  NAME 2  NAME 3  TRUE 4  FALSE </pre>
<pre> \doifoddpagelse {...<sup>1</sup>} {...<sup>2</sup>} 1  BEFEHL 2  BEFEHL </pre>
<pre> \doifoddpagefloatelse {...<sup>1</sup>} {...<sup>2</sup>} 1  TRUE 2  FALSE </pre>
<pre> \doifoldercontextelse {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} 1  NUMMER 2  TRUE 3  FALSE </pre>

```
\doifolderversionelse {...} {...} {...} {...}
1  NUMMER
2  NUMMER
3  TRUE
4  FALSE
```

```
\doifoverlappingelse {...} {...} {...} {...}
1  NAME
2  NAME
3  TRUE
4  FALSE
```

```
\doifoverlayelse {...} {...} {...}
1  NAME
2  TRUE
3  FALSE
```

```
\doifparallelelse {...} {...,2...} {...} {...}
1  NAME
2  NAME tot
3  TRUE
4  FALSE
```

```
\doifparentfileelse {...} {...} {...}
1  FILE
2  TRUE
3  FALSE
```

```
\doifpathelse {...} {...} {...}
1  PATH
2  TRUE
3  FALSE
```

```
\doifpathexistselse {...} {...} {...}
1  PATH
2  TRUE
3  FALSE
```

```
\doifpatternselse {...} {...} {...}
1  SPRACHE
2  TRUE
3  FALSE
```

```
\doifposition {...} {...} {...}
1  NAME
2  TRUE
3  FALSE
```

```
\doifpositionaction {...} {...} {...}
1  NAME
2  TRUE
3  FALSE
```

```
\doifpositionactionelse {...} {...} {...}
1  NAME
2  TRUE
3  FALSE
```

```
\doifpositionelse {...} {...} {...}
1  NAME
2  TRUE
3  FALSE
```

\doifpositiononpageelse {...} {...} {...} {...}

1 NAME  
2 NUMMER  
3 TRUE  
4 FALSE

\doifpositionsonsamepageelse {...,<sup>1</sup>...} {...<sup>2</sup>} {...<sup>3</sup>}

1 NAME  
2 TRUE  
3 FALSE

\doifpositionsonthispageelse {...,<sup>1</sup>...} {...<sup>2</sup>} {...<sup>3</sup>}

1 NAME  
2 TRUE  
3 FALSE

\doifpositionsusedelse {...<sup>1</sup>} {...<sup>2</sup>}

1 TRUE  
2 FALSE

\doifreferencefoundelse {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

1 REFERENCE  
2 TRUE  
3 FALSE

\doifrightpagefloatelse {...<sup>1</sup>} {...<sup>2</sup>}

1 TRUE  
2 FALSE

\doifrighttoleftinboxelse ...<sup>1</sup> {...<sup>2</sup>} {...<sup>3</sup>}

1 CSNAME NUMMER  
2 TRUE  
3 FALSE

\doifsamelinereferenceelse {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

1 REFERENCE  
2 TRUE  
3 FALSE

\doifsamestring {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

1 TEXT  
2 TEXT  
3 TRUE

\doifsamestringelse {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} {...<sup>4</sup>}

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

\doifsetups {...<sup>1</sup>} {...<sup>2</sup>}

1 NAME  
2 TRUE

\doifsetupselse {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

1 NAME  
2 TRUE  
3 FALSE

\doifsomebackground {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

1 NAME  
2 TRUE  
3 FALSE

\doifsomebackgroundelse {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifsomespaceelse {...} {...} {...}

1 TEXT  
2 TRUE  
3 FALSE

\doifsomething {...} {...}

1 TEXT  
2 TRUE

\doifsomethingelse {...} {...} {...}

1 TEXT  
2 TRUE  
3 FALSE

\doifsometoks \... {...}

1 CSNAME  
2 TRUE

\doifsometokselse \... {...} {...}

1 CSNAME  
2 TRUE  
3 FALSE

\doifstringinstringelse {...} {...} {...} {...}

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

\doifstructurelisthasnumberelse {...} {...}

1 TRUE  
2 FALSE

\doifstructurelisthaspageelse {...} {...}

1 TRUE  
2 FALSE

\doifsymboldefinedelse {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifsymbolsetelse {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doiftext {...} {...} {...}

1 TEXT  
2 TRUE  
3 FALSE

\doiftextelse {...} {...} {...}

1 TEXT  
2 TRUE  
3 FALSE

`\doiftextflowcollectorelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doiftextflowelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doiftopofpageelse {...} {...}`

1 TRUE  
2 FALSE

`\doiftypingfileelse {...} {...} {...}`

1 FILE  
2 TRUE  
3 FALSE

`\doifundefined {...} {...}`

1 NAME  
2 TRUE

`\doifundefinedcounter {...} {...}`

1 NAME  
2 TRUE

`\doifundefinedelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifurldefinedelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifvalue {...} {...} {...}`

1 NAME  
2 TEXT  
3 TRUE

`\doifvalueelse {...} {...} {...} {...}`

1 NAME  
2 TEXT  
3 TRUE  
4 FALSE

`\doifvaluenothing {...} {...}`

1 NAME  
2 TRUE

`\doifvaluenothingelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifvaluesomething {...} {...}`

1 NAME  
2 TRUE

<code>\doifvariable {<sup>1</sup>..} {<sup>2</sup>..} {<sup>3</sup>..}</code> 1 NAME 2 KEY 3 TRUE
<code>\doifvariableelse {<sup>1</sup>..} {<sup>2</sup>..} {<sup>3</sup>..} {<sup>4</sup>..}</code> 1 NAME 2 KEY 3 TRUE 4 FALSE
<code>\doindentation</code>
<code>\dollar</code>
<code>\doloop {<sup>*</sup>..}</code> * BEFEHL
<code>\doloopoverlist {<sup>1</sup>...,<sup>2</sup>..} {<sup>2</sup>..}</code> 1 TEXT 2 BEFEHL
<code>\donothing</code>
<code>\dontconvertfont</code>
<code>\dontleavehmode</code>
<code>\dontpermitspacesbetweenengroups</code>
<code>\dopositionaction {<sup>*</sup>..}</code> * NAME
<code>\doprocesslocalsetups {<sup>*</sup>...,<sup>*</sup>..}</code> * NAME
<code>\doquadrupleargument \<sup>1</sup>... [<sup>2</sup>..] [<sup>3</sup>..] [<sup>4</sup>..] [<sup>5</sup>..]</code> 1 CSNAME 2 TEXT 3 TEXT 4 TEXT 5 TEXT
<code>\doquadrupleempty \<sup>1</sup>... [<sup>2</sup>..] [<sup>3</sup>..] [<sup>4</sup>..] [<sup>5</sup>..]</code> 1 CSNAME 2 TEXT 3 TEXT 4 TEXT 5 TEXT
<code>\doquadruplegroupempty \<sup>1</sup>... {<sup>2</sup>..} {<sup>3</sup>..} {<sup>4</sup>..} {<sup>5</sup>..}</code> 1 CSNAME 2 TEXT 3 TEXT 4 TEXT 5 TEXT

<p><code>\doquintupleargument \<sup>1</sup>... [<sup>2</sup>...] [<sup>3</sup>...] [<sup>4</sup>...] [<sup>5</sup>...] [<sup>6</sup>...]</code></p> <p>1 CSNAME 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT</p>
<p><code>\doquintupleempty \<sup>1</sup>... [<sup>2</sup>...] [<sup>3</sup>...] [<sup>4</sup>...] [<sup>5</sup>...] [<sup>6</sup>...]</code></p> <p>1 CSNAME 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT</p>
<p><code>\doquintuplegroupempty \<sup>1</sup>... {<sup>2</sup>...} {<sup>3</sup>...} {<sup>4</sup>...} {<sup>5</sup>...} {<sup>6</sup>...}</code></p> <p>1 CSNAME 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT</p>
<p><code>\dorechecknextindentation</code></p>
<p><code>\dorecurse {<sup>1</sup>...} {<sup>2</sup>...}</code></p> <p>1 NUMBER 2 BEFEHL</p>
<p><code>\dorepeatwithcommand [<sup>1</sup>...] \<sup>2</sup>...</code></p> <p>1 TEXT NUMBER*TEXT 2 CSNAME</p>
<p><code>\doreplacefeature {...,*...}</code></p> <p>* NAME</p>
<p><code>\doresetandafffeature {...,*...}</code></p> <p>* NAME</p>
<p><code>\doresetattribute {<sup>*</sup>...}</code></p> <p>* NAME</p>
<p><code>\dorotatebox {<sup>1</sup>...} \<sup>2</sup>... {<sup>3</sup>...}</code></p> <p>1 NUMBER 2 CSNAME 3 CONTENT</p>
<p><code>\dosetattribute {<sup>1</sup>...} {<sup>2</sup>...}</code></p> <p>1 NAME 2 NUMBER</p>
<p><code>\dosetleftskipadaption {<sup>*</sup>...}</code></p> <p>* da nu standard DIMENSION</p>
<p><code>\dosetrighskipadaption {<sup>*</sup>...}</code></p> <p>* da nu standard DIMENSION</p>
<p><code>\dosetupcheckedinterlinespace {...,*=...,...}</code></p> <p>* inherits: \seteazaspatiuinterliniar</p>
<p><code>\dosetupcheckedinterlinespace {...,*...}</code></p> <p>* on dezactivat reset auto mic mediu mare NUMBER DIMENSION</p>



<pre> \dosetupcheckedinterlinespace {...} *   NAME </pre>
<pre> \doseventupleargument \.<sup>1</sup>. [...]<sup>2</sup> [...]<sup>3</sup> [...]<sup>4</sup> [...]<sup>5</sup> [...]<sup>6</sup> [...]<sup>7</sup> [...]<sup>8</sup> 1  CSNAME 2  TEXT 3  TEXT 4  TEXT 5  TEXT 6  TEXT 7  TEXT 8  TEXT </pre>
<pre> \doseventupleempty \.<sup>1</sup>. [...]<sup>2</sup> [...]<sup>3</sup> [...]<sup>4</sup> [...]<sup>5</sup> [...]<sup>6</sup> [...]<sup>7</sup> [...]<sup>8</sup> 1  CSNAME 2  TEXT 3  TEXT 4  TEXT 5  TEXT 6  TEXT 7  TEXT 8  TEXT </pre>
<pre> \dosingleargument \.<sup>1</sup>. [...]<sup>2</sup> 1  CSNAME 2  TEXT </pre>
<pre> \dosingleempty \.<sup>1</sup>. [...]<sup>2</sup> 1  CSNAME 2  TEXT </pre>
<pre> \dosinglegroupempty \.<sup>1</sup>. {...}<sup>2</sup> 1  CSNAME 2  TEXT </pre>
<pre> \dosixtupleargument \.<sup>1</sup>. [...]<sup>2</sup> [...]<sup>3</sup> [...]<sup>4</sup> [...]<sup>5</sup> [...]<sup>6</sup> [...]<sup>7</sup> 1  CSNAME 2  TEXT 3  TEXT 4  TEXT 5  TEXT 6  TEXT 7  TEXT </pre>
<pre> \dosixtupleempty \.<sup>1</sup>. [...]<sup>2</sup> [...]<sup>3</sup> [...]<sup>4</sup> [...]<sup>5</sup> [...]<sup>6</sup> [...]<sup>7</sup> 1  CSNAME 2  TEXT 3  TEXT 4  TEXT 5  TEXT 6  TEXT 7  TEXT </pre>
<pre> \dostarttagged {...}<sup>1</sup> {...}<sup>2</sup> ... \dostoptagged 1  NAME 2  NAME </pre>
<pre> \dostepwiserecurse {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup> {...}<sup>4</sup> 1  NUMBER 2  NUMBER 3  [-+]NUMBER 4  BEFEHL </pre>
<pre> \dosubtractfeature {...,*...} *   NAME </pre>

`\dotfskip {...}`

\* DIMENSION

`\dotoks \...`

\* CSNAME

`\dotripleargument \1... [2...] [3] [4]`

1 CSNAME

2 TEXT

3 TEXT

4 TEXT

`\dotripleargumentwithset \1... [...,2...] [3] [4]`

1 CSNAME

2 TEXT

3 TEXT

4 TEXT

`\dotripleempty \1... [2] [3] [4]`

1 CSNAME

OPT

OPT

OPT

2 TEXT

3 TEXT

4 TEXT

`\dotripleemptywithset \1... [...,2...] [3] [4]`

1 CSNAME

OPT

OPT

OPT

2 TEXT

3 TEXT

4 TEXT

`\dotriplegroupempty \1... {2...} {3...} {4...}`

1 CSNAME

OPT

OPT

OPT

2 TEXT

3 TEXT

4 TEXT

`\doublebond`

`\dowith {...,1...} {2...}`

1 BEFEHL

2 BEFEHL

`\dowithnextbox {1...} \2... {3...}`

1 BEFEHL

2 CSNAME

3 CONTENT

`\dowithnextboxcontent {1...} {2...} \3... {4...}`

1 BEFEHL

2 BEFEHL

3 CSNAME

4 CONTENT

`\dowithnextboxcontentcs \1... \2... \3... {4...}`

1 CSNAME

2 CSNAME

3 CSNAME

4 CONTENT

`\dowithnextboxcs \1... \2... {3...}`

1 CSNAME

2 CSNAME

3 CONTENT

<code>\dowithpargument \...</code> <code>* CSNAME</code>
<code>\dowithrange {...<sup>1</sup>,...} \<sup>2</sup>...</code> <code>1 NUMBER NUMBER:NUMBER</code> <code>2 CSNAME</code>
<code>\dowithwargument \...</code> <code>* CSNAME</code>
<code>\dpofstring {...}</code> <code>* TEXT</code>
<code>\dreapta ...</code> <code>* CHARACTER</code>
<code>\dummydigit</code>
<code>\dummyparameter {...}</code> <code>* KEY</code>
<code>\dute {...<sup>1</sup>} [...<sup>2</sup>]</code> <code>1 CONTENT</code> <code>2 REFERENCE</code>
<code>\dutebox {...<sup>1</sup>} [...<sup>2</sup>]</code> <code>1 CONTENT</code> <code>2 REFERENCE</code>
<code>\dutepagina {...<sup>1</sup>} [...<sup>2</sup>]</code> <code>1 TEXT</code> <code>2 REFERENCE</code>
<code>\ETEX</code>
<code>\EveryLine {...}</code> <code>* BEFEHL</code>
<code>\EveryPar {...}</code> <code>* BEFEHL</code>
<code>\ecran [...<sup>*</sup>,...]</code> <code>* inherits: <sup>QPT</sup>\pagina</code>
<code>\edefconvertedargument \<sup>1</sup>... {<sup>2</sup>...}</code> <code>1 CSNAME</code> <code>2 TEXT</code>
<code>\efcmxheight {...}</code> <code>* NAME</code>
<code>\efcmxwidth {...}</code> <code>* NAME</code>
<code>\efcminheight {...}</code> <code>* NAME</code>

<code>\efcminwidth {...}</code> <code>* NAME</code>
<code>\efcparameter {...} {...}</code> <code>1 NAME</code> <code>2 KEY</code>
<code>\effect [...]{...}</code> <code>1 NAME</code> <code>2 CONTENT</code>
<code>\elapsedseconds</code>
<code>\elapsedtime</code>
<code>\element [...,*...]</code> <code>* REFERENCE OPT</code>
<code>\em</code>
<code>\emphasisboldface</code>
<code>\emphasistypeface</code>
<code>\emptylines [...*...]</code> <code>* NUMMER OPT</code>
<code>\emspace</code>
<code>\enabledirectives [...,*...]</code> <code>* NAME</code>
<code>\enableexperiments [...,*...]</code> <code>* NAME</code>
<code>\enablemode [...,*...]</code> <code>* NAME</code>
<code>\enableoutputstream [...]</code> <code>* NAME</code>
<code>\enableparpositions</code>
<code>\enableregime [...]</code> <code>* cp1250 cp1251 cp1252 cp1253 cp1254 cp1255 cp1256 cp1257 cp1258 8859-1 8859-2 8859-3 8859-4 8859-9 8859-10 8859-13 8859-14 8859-15 8859-16 utf windows-1250 windows-1251 windows-1252 windows-1253 windows-1254 windows-1255 windows-1256 windows-1257 windows-1258 il1 il2 il3 il4 il5 il6 il7 il8 il9 il10 iso-8859-1 iso-8859-2 iso-8859-3 iso-8859-4 iso-8859-9 iso-8859-10 iso-8859-13 iso-8859-14 iso-8859-15 iso-8859-16 latin1 latin2 latin3 latin4 latin5 latin6 latin7 latin8 latin9 latin10 utf-8 utf8 windows</code>
<code>\enabletrackers [...,*...]</code> <code>* NAME</code>
<code>\enskip</code>
<code>\enspace</code>

$\backslash$ ENUMERARE [... <sup>1</sup> ,...] {... <sup>2</sup> } ... <sup>3</sup> \par 1    REFERENCE            OPT            OPT 2    TEXT 3    CONTENT
$\backslash$ env {...} *    KEY
$\backslash$ envvar {... <sup>1</sup> } {... <sup>2</sup> } 1    KEY 2    BEFEHL
$\backslash$ epos {...} *    NAME
$\backslash$ equaldigits {...} *    TEXT
$\backslash$ eTeX
$\backslash$ ETICHETA [... <sup>1</sup> ,...] {... <sup>2</sup> } 1    REFERENCE            OPT            OPT 2    TEXT
$\backslash$ executeifdefined {... <sup>1</sup> } {... <sup>2</sup> } 1    NAME 2    BEFEHL
$\backslash$ exitloop
$\backslash$ exitloopnow
$\backslash$ expandcheckedcsname \... {... <sup>2</sup> } {... <sup>3</sup> } 1    CSNAME 2    KEY 3    TEXT
$\backslash$ expanded {...} *    CONTENT
$\backslash$ expandfontsynonym \... {... <sup>2</sup> } 1    CSNAME 2    NAME
$\backslash$ expdoif {... <sup>1</sup> } {... <sup>2</sup> } {... <sup>3</sup> } 1    CONTENT 2    CONTENT 3    TRUE
$\backslash$ expdoifcommonelse {... <sup>1</sup> ,...} {... <sup>2</sup> ,...} {... <sup>3</sup> } {... <sup>4</sup> } 1    TEXT 2    TEXT 3    TRUE 4    FALSE
$\backslash$ expdoifelse {... <sup>1</sup> } {... <sup>2</sup> } {... <sup>3</sup> } {... <sup>4</sup> } 1    CONTENT 2    CONTENT 3    TRUE 4    FALSE

<code>\expdoifelsecommon {...,<sup>1</sup>...} {...,<sup>2</sup>...} {...} {...}</code> 1 TEXT 2 TEXT 3 TRUE 4 FALSE
<code>\expdoifelseinset {...,<sup>1</sup>...} {...,<sup>2</sup>...} {...} {...}</code> 1 TEXT 2 TEXT 3 TRUE 4 FALSE
<code>\expdoifinsetelse {...,<sup>1</sup>...} {...,<sup>2</sup>...} {...} {...}</code> 1 TEXT 2 TEXT 3 TRUE 4 FALSE
<code>\expdoifnot {...,<sup>1</sup>...} {...,<sup>2</sup>...} {...}</code> 1 CONTENT 2 CONTENT 3 TRUE
<code>\externalfigurecollectionmaxheight {...}</code> * NAME
<code>\externalfigurecollectionmaxwidth {...}</code> * NAME
<code>\externalfigurecollectionminheight {...}</code> * NAME
<code>\externalfigurecollectionminwidth {...}</code> * NAME
<code>\externalfigurecollectionparameter {...,<sup>1</sup>...} {...,<sup>2</sup>...}</code> 1 NAME 2 KEY
<code>\fakebox ...</code> * CSNAME NUMBER
<code>\faraliniiantetsisubsol</code>
<code>\faraliniisussijos</code>
<code>\faraspatiu</code>
<code>\fastdecrement \...</code> * CSNAME
<code>\fastincrement \...</code> * CSNAME
<code>\fastlocalframed [...,<sup>1</sup>...] [...,<sup>2</sup>...,...] {...,<sup>3</sup>...}</code> 1 NAME 2 inherits: \setezainconjurat 3 CONTENT
<code>\fastloopfinal</code>

<code>\fastloopindex</code>
<code>\fastscale {<sup>1</sup>...} {<sup>2</sup>...}</code> 1    NUMMER 2    CONTENT
<code>\fastsetup {<sup>*</sup>...}</code> *    NAME
<code>\fastsetupwithargument {<sup>1</sup>...} {<sup>2</sup>...}</code> 1    NAME 2    CONTENT
<code>\fastsetupwithargumentswapped {<sup>1</sup>...} {<sup>2</sup>...}</code> 1    CONTENT 2    NAME
<code>\fastswitchtobodyfont {<sup>*</sup>...}</code> *    x xx mic mare script scriptscript
<code>\fastsxsy {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...}</code> 1    NUMMER 2    NUMMER 3    CONTENT
<code>\feature [<sup>1</sup>...] [<sup>2</sup>...,...]</code> 1    + - = ! > < more less nou reset implicit old local 2    NAME
<code>\feature {<sup>1</sup>...} {<sup>2</sup>...,...}</code> 1    + - = ! > < more less nou reset implicit old local 2    NAME
<code>\fence</code>
<code>\fenced [<sup>1</sup>...] {<sup>2</sup>...}</code> 1    NAME 2    CONTENT
<code>\FENCE {<sup>*</sup>...}</code> *    CONTENT
<code>\fetchallmarkings [<sup>1</sup>...] [<sup>2</sup>...]</code> 1    BESCHRIFTUNG 2    pagina NAME
<code>\fetchallmarks [<sup>*</sup>...]</code> *    BESCHRIFTUNG
<code>\fetchmark [<sup>1</sup>...] [<sup>2</sup>...]</code> 1    BESCHRIFTUNG            OPT 2    primul ultim curent precedent urmatorul sus subsol implicit ambele tot first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck
<code>\fetchmarking [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...]</code> 1    BESCHRIFTUNG 2    pagina NAME 3    primul ultim curent precedent urmatorul sus subsol implicit ambele tot first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck

`\fetchonemark` [<sup>1</sup>...] [<sup>2</sup>...]

```

1  BESCHRIFTUNG          OPT
2  primul ultim curent precedent urmatorul sus subsol implicit ambele tot first:nochek last:nochek previous:nochek
   next:nochek top:nochek bottom:nochek

```

```
\fetchonemarking [...] [...] [...]
```

```

1  BESCHRIFTUNG
2  pagina NAME
3  primul ultim curent precedent urmatorul sus subsol implicit ambele tot first:unchecked last:unchecked previous:unchecked
   next:unchecked top:unchecked bottom:unchecked

```

```
\fetchruntimecommand \.^... {.^...}
```

```
1 CSNAME
2 FILE
```

```
\fetchtwomarkings [...] [...]
```

```
1  BESCHRIFTUNG
2  pagina NAME
```

```
\fetchtwomarks [...]
```

\* BESCHRIFTUNG

$$\backslash\mathrm{fieldbody} \left[ \dots \right] \left[ \dots, \dots \stackrel{2}{=} \dots, \dots \right]$$

```
1 NAME OPT
2 inherits: \setupfieldbody
```

`\fifthofffivearguments`  $\{...\}^1 \{...\}^2 \{...\}^3 \{...\}^4 \{...\}^5$

1	TEXT
2	TEXT
3	TEXT
4	TEXT
5	TEXT

`\fifthofsixarguments`  $\{\dots\}^1 \{\dots\}^2 \{\dots\}^3 \{\dots\}^4 \{\dots\}^5 \{\dots\}^6$

1	TEXT
2	TEXT
3	TEXT
4	TEXT
5	TEXT
6	TEXT

$$\backslash\text{figuraexterna} \left[ \begin{smallmatrix} \cdot \\ \cdot \\ \cdot \end{smallmatrix} \right] \left[ \begin{smallmatrix} \cdot \\ \cdot \\ \cdot \end{smallmatrix} \right] \left[ \dots, \dots \stackrel{3}{=} \dots, \dots \right]$$

```

1  FILE                                OPT                OPT
2  NAME
3  inherits: \setupexternalfigure

```

\figurefilename

\figurefilepath

\figurefiletype

`\figurefullname`

\figureheight

\figurenaturalheight

\figurenaturalwidth



```
\figuresymbol [...] [...1,...2...,...]
1 FILE NAME OPT
2 inherits: \figuraexterna
```

<code>\figurewidth</code>
---------------------------

```
\filename {...}  
* FILE
```

\filledhboxb <sup>1</sup> ... { <sup>2</sup> ...}	
1	TEXT OPT
2	CONTENT

<pre>\filledhboxc ... {...}</pre>
<pre>1 TEXT OPT</pre>
<pre>2 CONTENT</pre>

```
\filledhboxg ... {...}
1  TEXT          OPT
2  CONTENT
```

```
\filledhboxk ... {...}
1 TEXT OPT
2 CONTENT
```

\filledhboxm ... {...}	
1	TEXT OPT
2	CONTENT

\filledhboxr ... {...}	
1	TEXT OPT
2	CONTENT

\filledhboxy <sup>1</sup> .. { <sup>2</sup> ..}		
1	TEXT	OPT
2	CONTENT	

```
\filler [...]  
*   sym simbol rigla latime spatiu NAME
```

```
\filterfromnext {..1.} {..2.} {..3.} {..4.} {..5.} {..6.} {..7.}
1  NUMBER
2  NUMBER
3  CONTENT
4  CONTENT
5  CONTENT
6  CONTENT
7  CONTENT
```

```
\filterfromvalue {...} {...} {...}
1 NAME
2 NUMBER
3 NUMBER
```

```
\filterpages [.1.] [...,2...] [...,3.,...]  
1 FILE OPT  
2 par impar NUMMER NUMMER:NUMMER  
3 latime = DIMENSION  
n = NUMMER  
category = NAME
```

<pre>\filterreference {...} *   implicit text titlu numar pagina realpage</pre>
---

\findtwopassdata {...} {...} 1 NAME 2 NAME
\finishregisterentry [...] <sup>1</sup> [...,... <sup>2</sup> ...] [...,... <sup>3</sup> ...] <sup>OPT</sup> 1 NAME 2 eticheta = NAME keys = TEXT PROCESSOR->TEXT entries = TEXT PROCESSOR->TEXT alternativ = TEXT 3 KEY = VALUE
\firdepar
\firstcharacter
\firstcounter [...] <sup>1</sup> [...] <sup>2</sup> <sup>OPT</sup> 1 NAME 2 NUMMER
\firstcountervalue [...] <sup>*</sup> * NAME
\firstoffivearguments {...} <sup>1</sup> {...} <sup>2</sup> {...} <sup>3</sup> {...} <sup>4</sup> {...} <sup>5</sup> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT
\firstoffourarguments {...} <sup>1</sup> {...} <sup>2</sup> {...} <sup>3</sup> {...} <sup>4</sup> 1 TEXT 2 TEXT 3 TEXT 4 TEXT
\firstofoneargument {...} <sup>*</sup> * TEXT
\firstofoneunexpanded {...} <sup>*</sup> * TEXT
\firstofsixarguments {...} <sup>1</sup> {...} <sup>2</sup> {...} <sup>3</sup> {...} <sup>4</sup> {...} <sup>5</sup> {...} <sup>6</sup> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT
\firstofthreearguments {...} <sup>1</sup> {...} <sup>2</sup> {...} <sup>3</sup> 1 TEXT 2 TEXT 3 TEXT
\firstofthreeunexpanded {...} <sup>1</sup> {...} <sup>2</sup> {...} <sup>3</sup> 1 TEXT 2 TEXT 3 TEXT
\firstoftwoarguments {...} <sup>1</sup> {...} <sup>2</sup> 1 TEXT 2 TEXT

\firstoftwounexpanded {...} {...} 1 TEXT 2 TEXT
\firstrealpage
\firstrealpagenumber
\firstsubcountervalue [... <sup>1</sup> ] [... <sup>2</sup> ] 1 NAME 2 NUMMER
\firstsubpagenumber
\firstuserpage
\firstuserpagenumber
\fitfieldframed [... <sup>1</sup> ... <sup>2</sup> ...] {...} 1 inherits: \seteazainconjunctat 2 CONTENT
\fittopbaselinegrid {...} * CONTENT
\flag {...} * NAME
\floatuserdataparameter {...} * KEY
\flushbox {...} {...} 1 NAME 2 NAME
\flushboxregister ... * CSNAME NUMMER
\flushcollector [...] * NAME
\flushedrightlastline
\flushlayer [...] * NAME
\flushlocalfloats
\flushnextbox
\flushnotes
\flushoutputstream [...] * NAME
\flushshapebox

\* NAME

\* NAME

\* CSNAME

```

2      NAME
3      criteriu = text ABSCHNITT

```

\* PATH

3 TEXT

```
4 inherits: \setupexternalfigure
```

3 KEY = VALUE

2 FILE

1 FILE  
2 NAME

\* FILE

4 TEXT

#### 4 TEXT

\* NAME

\fontcharbyindex {...} *    NUMMER
\fontclass
\fontclassname {...} {...} 1    NAME 2    FONT
\fontface
\fontfeaturelist [...] [...] 1    NAME 2    TEXT
\fontsize
\fontstyle
\footnotetext [..., <sup>1</sup> ...] {...} 1    REFERENCE            OPT 2    TEXT
\footnotetext [..., <sup>*</sup> ...] [...] *    titlu        = TEXT semncarte = TEXT lista       = TEXT referinta = REFERENCE
\forcecharacterstripping
\forcelocalfloats
\forgeteverypar
\forgetparameters [..., <sup>1</sup> ...] [..., <sup>2</sup> ...] [...] 1    TEXT 2    KEY = VALUE
\forgetragged
\formula [..., <sup>1</sup> ...] {...} 1    impachetat tight centru incadrat adancime linie jumatatelinie -linie -jumatatelinie inherits: \seteazafonttext 2    CONTENT
\foundbox {...} {...} 1    NAME 2    NAME
\fourthoffivearguments {...} {...} {...} {...} {...} 1    TEXT 2    TEXT 3    TEXT 4    TEXT 5    TEXT

$\backslash\text{fourthoffourarguments}$ $\{.^1.\}$ $\{.^2.\}$ $\{.^3.\}$ $\{.^4.\}$ 1 TEXT 2 TEXT 3 TEXT 4 TEXT
$\backslash\text{fourthofsixarguments}$ $\{.^1.\}$ $\{.^2.\}$ $\{.^3.\}$ $\{.^4.\}$ $\{.^5.\}$ $\{.^6.\}$ 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT
$\backslash\text{FRACTION}$ $\{.^1.\}$ $\{.^2.\}$ 1 CONTENT 2 CONTENT instances: xfrac xxfrac frac sfrac dfrac binom dbinom tbinom
$\backslash\text{binom}$ $\{.^1.\}$ $\{.^2.\}$ 1 CONTENT 2 CONTENT
$\backslash\text{dbinom}$ $\{.^1.\}$ $\{.^2.\}$ 1 CONTENT 2 CONTENT
$\backslash\text{dfrac}$ $\{.^1.\}$ $\{.^2.\}$ 1 CONTENT 2 CONTENT
$\backslash\text{frac}$ $\{.^1.\}$ $\{.^2.\}$ 1 CONTENT 2 CONTENT
$\backslash\text{sfrac}$ $\{.^1.\}$ $\{.^2.\}$ 1 CONTENT 2 CONTENT
$\backslash\text{tbinom}$ $\{.^1.\}$ $\{.^2.\}$ 1 CONTENT 2 CONTENT
$\backslash\text{xfrac}$ $\{.^1.\}$ $\{.^2.\}$ 1 CONTENT 2 CONTENT
$\backslash\text{xxfrac}$ $\{.^1.\}$ $\{.^2.\}$ 1 CONTENT 2 CONTENT
$\backslash\text{framed}$ $[...,\overset{1}{=},...,...] \{.^2.\}$ 1 inherits: $\backslash\text{setazainconjurat}$ 2 CONTENT
$\backslash\text{frameddimension}$ $\{.^*\}$ * KEY
$\backslash\text{framedparameter}$ $\{.^*\}$ * KEY

$\backslash FRAMED$ [... <sup>1</sup> ... <sup>2</sup> ] {...} 1 inherits: \seteazainconjurat 2 CONTENT instances: unframed fitfieldframed
$\backslash fitfieldframed$ [... <sup>1</sup> ... <sup>2</sup> ] {...} 1 inherits: \seteazainconjurat 2 CONTENT
$\backslash unframed$ [... <sup>1</sup> ... <sup>2</sup> ] {...} 1 inherits: \seteazainconjurat 2 CONTENT
$\backslash freezedimenmacro$ \... \... 1 CSNAME 2 CSNAME
$\backslash freezemeasure$ [... <sup>1</sup> ] [... <sup>2</sup> ] 1 NAME 2 DIMENSION
$\backslash frenchspacing$
$\backslash fromlinenote$ [... <sup>1</sup> ] [... <sup>2</sup> ] 1 REFERENCE 2 TEXT
$\backslash frozenhbox$ {...} * CONTENT
$\backslash frule$ .. ... .. \relax * width <sub>1</sub> DIMENSION height <sub>1</sub> DIMENSION depth <sub>1</sub> DIMENSION radius <sub>1</sub> DIMENSION line <sub>1</sub> DIMENSION type <sub>1</sub> TEXT data <sub>1</sub> TEXT name <sub>1</sub> TEXT
$\backslash fundal$ {...} * CONTENT
$\backslash FUNDAL$ {...} * CONTENT instances: fundal
$\backslash GetPar$
$\backslash GotoPar$
$\backslash Greeknumerals$ {...} * NUMMER
$\backslash gdefconvertedargument$ \... <sup>1</sup> {... <sup>2</sup> } 1 CSNAME 2 TEXT
$\backslash gdefconvertedcommand$ \... <sup>1</sup> \... <sup>2</sup> .. 1 CSNAME 2 CSNAME
$\backslash getboxfromcache$ {... <sup>1</sup> } {... <sup>2</sup> } ... <sup>3</sup> .. 1 NAME 2 NUMMER TEXT 3 CSNAME NUMMER

\getboxllx ... * CSNAME NUMMER
\getboxlly ... * CSNAME NUMMER
\getbufferdata [...] <small>OPT</small> * BUFFER
\getcommacommandsize [...*...] * BEFEHL
\getcommalistsize [...*...] * BEFEHL
\getdayoftheweek {... <sup>1</sup> } {... <sup>2</sup> } {... <sup>3</sup> } 1 NUMMER 2 NUMMER 3 NUMMER
\getdayspermonth {... <sup>1</sup> } {... <sup>2</sup> } 1 NUMMER 2 NUMMER
\getdefinedbuffer [...] <small>OPT</small> * BUFFER
\getdocumentargument {...} * NAME
\getdocumentargumentdefault {... <sup>1</sup> } {... <sup>2</sup> } 1 NAME 2 TEXT
\getdocumentfilename {...} * NUMMER
\getdummyparameters [... <sup>1</sup> ... <sup>2</sup> ...] * KEY = VALUE
\getemptyparameters [... <sup>1</sup> ] [... <sup>2</sup> ...] 1 TEXT 2 KEY = VALUE
\getparameters [... <sup>1</sup> ] [... <sup>2</sup> ...] 1 TEXT 2 KEY = VALUE
\getexpandedparameters [... <sup>1</sup> ] [... <sup>2</sup> ...] 1 TEXT 2 KEY = VALUE
\getfiguredimensions [... <sup>1</sup> ] [... <sup>2</sup> ...] <small>OPT</small> 1 FILE 2 inherits: \setupexternalfigure
\getfirstcharacter {...} * TEXT



\getfirsttwopassdata {...} *   NAME
\getfromcommacommand [..., <sup>1</sup> ...] [ <sup>2</sup> ...] 1   BEFEHL 2   NUMMER
\getfromcommalist [..., <sup>1</sup> ...] [ <sup>2</sup> ...] 1   BEFEHL 2   NUMMER
\getfromtwopassdata {.. <sup>1</sup> } {.. <sup>2</sup> } 1   NAME 2   NAME
\getglyphdirect {.. <sup>1</sup> } {.. <sup>2</sup> } 1   FONT 2   NUMMER CHARACTER
\getglyphstyled {.. <sup>1</sup> } {.. <sup>2</sup> } 1   FONT 2   NUMMER CHARACTER
\getgparameters [...] <sup>1</sup> [..., <sup>2</sup> ...,...] 1   TEXT 2   KEY = VALUE
\getlasttwopassdata {.. <sup>*</sup> } *   NAME
\getlocalfloat {.. <sup>*</sup> } *   NUMMER
\getlocalfloats
\getMPdrawing
\getMPlayer [...] <sup>1</sup> [..., <sup>2</sup> ...,...] <sup>OPT</sup> {.. <sup>3</sup> } 1   NAME 2   inherits: \seteazainconjurat 3   CONTENT
\getmessage {.. <sup>1</sup> } {.. <sup>2</sup> } 1   NAME 2   NAME NUMMER
\getnamedglyphdirect {.. <sup>1</sup> } {.. <sup>2</sup> } 1   FONT 2   NAME
\getnamedglyphstyled {.. <sup>1</sup> } {.. <sup>2</sup> } 1   FONT 2   NAME
\getnamedtwopassdatalist \.. <sup>1</sup> {.. <sup>2</sup> } 1   CSNAME 2   NAME
\getnaturaldimensions .. <sup>*</sup> *   CSNAME NUMMER

\getnoflines {...} *    DIMENSION
\getobject {...} {...} 1    NAME 2    NAME
\getobjectdimensions {...} {...} 1    NAME 2    NAME
\getpaletsize [...] ... *    NAME
\getparameters [...] [...] ... 1    TEXT 2    KEY = VALUE
\getprivatechar {...} *    NAME
\getprivateslot {...} *    NAME
\getrandomcount \... {...} {...} 1    CSNAME 2    NUMMER 3    NUMMER
\getrandomdimen \... {...} {...} 1    CSNAME 2    DIMENSION 3    DIMENSION
\getrandomfloat \... {...} {...} 1    CSNAME 2    NUMMER 3    NUMMER
\getrandomnumber \... {...} {...} 1    CSNAME 2    NUMMER 3    NUMMER
\getrandomseed \... *    CSNAME
\getraweparameters [...] [...] ... 1    TEXT 2    KEY = VALUE
\getrawgparameters [...] [...] ... 1    TEXT 2    KEY = VALUE
\getrawnoflines {...} *    DIMENSION
\getrawparameters [...] [...] ... 1    TEXT 2    KEY = VALUE

<pre> \getrawxparameters [...] [...,<sup>2</sup>...,...] 1 TEXT 2 KEY = VALUE </pre>
<pre> \getreference [...] [...<sup>2</sup>.] 1 implicit text titlu numar pagina realpage 2 REFERENCE </pre>
<pre> \getreferenceentry {...} * implicit text titlu numar pagina realpage </pre>
<pre> \getroundednoflines {...} * DIMENSION </pre>
<pre> \getsubstring {...} {...<sup>2</sup>.} {...<sup>3</sup>.} 1 NUMMER 2 NUMMER 3 TEXT </pre>
<pre> \gettwopassdata {...} * NAME </pre>
<pre> \gettwopassdatalist {...} * NAME </pre>
<pre> \getuvalue {...} * NAME </pre>
<pre> \getvalue {...} * NAME </pre>
<pre> \getvariable {...} {...<sup>2</sup>.} 1 NAME 2 KEY </pre>
<pre> \getvariabledefault {...} {...<sup>2</sup>.} {...<sup>3</sup>.} 1 NAME 2 KEY 3 BEFEHL </pre>
<pre> \getxparameters [...] [...,<sup>2</sup>...,...] 1 TEXT 2 KEY = VALUE </pre>
<pre> \globaldisablemode [...,<sup>*</sup>...] * NAME </pre>
<pre> \globalenablemode [...,<sup>*</sup>...] * NAME </pre>
<pre> \globalletempty \... * CSNAME </pre>
<pre> \globalpopbox ... * CSNAME NUMMER </pre>
<pre> \globalpopmacro \... * CSNAME </pre>

<code>\globalpreventmode [...,*,...]</code> *    NAME
<code>\globalprocesscommalist [...]<sup>1</sup> \...<sup>2</sup></code> 1    BEFEHL 2    CSNAME
<code>\globalpushbox ...</code> *    CSNAME NUMBER
<code>\globalpushmacro \...</code> *    CSNAME
<code>\globalpushreferenceprefix {...<sup>*</sup>} ... \globalpopreferenceprefix</code> *    + - TEXT
<code>\globalswapcounts \...<sup>1</sup> \...<sup>2</sup></code> 1    CSNAME 2    CSNAME
<code>\globalswapdimens \...<sup>1</sup> \...<sup>2</sup></code> 1    CSNAME 2    CSNAME
<code>\globalswapmacros \...<sup>1</sup> \...<sup>2</sup></code> 1    CSNAME 2    CSNAME
<code>\globalundefine {...}</code> *    NAME
<code>\glyphfontfile {...}</code> *    FONT
<code>\gobbledoubleempty [...<sup>1</sup>] [...<sup>2</sup>]</code> 1    TEXT                    OPT        OPT 2    TEXT
<code>\gobbleeightarguments {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} {...<sup>4</sup>} {...<sup>5</sup>} {...<sup>6</sup>} {...<sup>7</sup>} {...<sup>8</sup>}</code> 1    CONTENT 2    CONTENT 3    CONTENT 4    CONTENT 5    CONTENT 6    CONTENT 7    CONTENT 8    CONTENT
<code>\gobblefivearguments {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} {...<sup>4</sup>} {...<sup>5</sup>}</code> 1    CONTENT 2    CONTENT 3    CONTENT 4    CONTENT 5    CONTENT
<code>\gobblefiveoptionals [...<sup>1</sup>] [...<sup>2</sup>] [...<sup>3</sup>] [...<sup>4</sup>] [...<sup>5</sup>]</code> 1    TEXT 2    TEXT 3    TEXT 4    TEXT 5    TEXT

`\gobblefourarguments {...} {...} {...} {...}`

1 CONTENT  
2 CONTENT  
3 CONTENT  
4 CONTENT

`\gobblefouroptionals [...] [...] [...] [...]`

1 TEXT  
2 TEXT  
3 TEXT  
4 TEXT

`\gobbleninearguments {...} {...} {...} {...} {...} {...} {...} {...} {...}`

1 CONTENT  
2 CONTENT  
3 CONTENT  
4 CONTENT  
5 CONTENT  
6 CONTENT  
7 CONTENT  
8 CONTENT  
9 CONTENT

`\gobbleoneargument {...}`

\* CONTENT

`\gobbleoneoptional [...]`

\* TEXT

`\gobblesevenarguments {...} {...} {...} {...} {...} {...} {...}`

1 CONTENT  
2 CONTENT  
3 CONTENT  
4 CONTENT  
5 CONTENT  
6 CONTENT  
7 CONTENT

`\gobblesingleempty [...]`

\* TEXT

OPT

`\gobblesixarguments {...} {...} {...} {...} {...} {...}`

1 CONTENT  
2 CONTENT  
3 CONTENT  
4 CONTENT  
5 CONTENT  
6 CONTENT

`\gobblespacetokens`

`\gobblenarguments {...} {...} {...} {...} {...} {...} {...} {...} {...} {...}`

1 CONTENT  
2 CONTENT  
3 CONTENT  
4 CONTENT  
5 CONTENT  
6 CONTENT  
7 CONTENT  
8 CONTENT  
9 CONTENT  
10 CONTENT

`\gobblethreearguments {...} {...} {...}`

1 CONTENT  
2 CONTENT  
3 CONTENT

<p><code>\gobblethreoptionals [...] [...] [...]</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 TEXT</p>
<p><code>\gobbletwoarguments {...} {...}</code></p> <p>1 CONTENT</p> <p>2 CONTENT</p>
<p><code>\gobbletwooptionals [...] [...]</code></p> <p>1 TEXT</p> <p>2 TEXT</p>
<p><code>\gobbleuntil \*..</code></p> <p>* CSNAME</p>
<p><code>\gobbleuntilrelax ... \relax</code></p> <p>* CONTENT</p>
<p><code>\grabbufferdata [...] [...] [...] [...]</code></p> <p>1 CATEGORY <small>OPT</small></p> <p>2 NAME</p> <p>3 NAME</p> <p>4 NAME</p>
<p><code>\grabbufferdatadirect {...} {...} {...}</code></p> <p>1 NAME</p> <p>2 NAME</p> <p>3 NAME</p>
<p><code>\grabuntil {...} \*..</code></p> <p>1 NAME</p> <p>2 CSNAME</p>
<p><code>\grave {...}</code></p> <p>* CHARACTER</p>
<p><code>\grayvalue {...}</code></p> <p>* COLOR</p>
<p><code>\greedystring \*... \at ... \to \*... \and \*...</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 CSNAME</p> <p>4 CSNAME</p>
<p><code>\greeknumerals {...}</code></p> <p>* NUMBER</p>
<p><code>\grid [..., ..., ..., ...]</code></p> <p>* inherits: <small>base</small> \basegrid</p>
<p><code>\grosimelinie</code></p>
<p><code>\groupedcommand {...} {...}</code></p> <p>1 BEFEHL</p> <p>2 BEFEHL</p>
<p><code>\gsetboxllx \*... {...}</code></p> <p>1 CSNAME NUMBER</p> <p>2 DIMENSION</p>

<code>\gsetboxlly ...<sup>1</sup> {...}</code> 1 CSNAME NUMBER 2 DIMENSION
<code>\gujaratinumerals {...}</code> * NUMBER
<code>\gurmukhinumerals {...}</code> * NUMBER
<code>\hairspace</code>
<code>\halflinestrut</code>
<code>\halfstrut</code>
<code>\halfwaybox {...}</code> * CONTENT
<code>\handletokens ...<sup>1</sup> \with ...<sup>2</sup></code> 1 TEXT 2 CSNAME
<code>\hash</code>
<code>\hat {...}</code> * CHARACTER
<code>\hboxofvbox ...</code> * CSNAME NUMBER
<code>\hboxreference [...,<sup>1</sup>...] {...<sup>2</sup>}</code> 1 REFERENCE 2 CONTENT
<code>\hboxBOX {...}</code> * CONTENT
<code>\hdofstring {...}</code> * TEXT
<code>\headhbox ...<sup>1</sup> {...<sup>2</sup>}</code> 1 TEXT <small>OPT</small> 2 CONTENT
<code>\headnumbercontent</code>
<code>\headnumberdistance</code>
<code>\headnumberwidth</code>
<code>\headreferenceattributes</code>
<code>\headsetupspacing</code>
<code>\headtextcontent</code>

<code>\headtextdistance</code>
<code>\headtextwidth</code>
<code>\headvbox</code> <sup>1</sup> ... { <sup>2</sup> ...} 1 TEXT <small>OPT</small> 2 CONTENT
<code>\headwidth</code>
<code>\heightanddepthofstring</code> { <sup>*</sup> ...} * TEXT
<code>\heightofstring</code> { <sup>*</sup> ...} * TEXT
<code>\heightspanningtext</code> { <sup>1</sup> ...} { <sup>2</sup> ...} { <sup>3</sup> ...} 1 TEXT 2 DIMENSION 3 FONT
<code>\HELP</code> [ <sup>1</sup> ...] { <sup>2</sup> ...} { <sup>3</sup> ...} 1 REFERENCE 2 TEXT 3 TEXT <b>instances:</b> helptext
<code>\helptext</code> [ <sup>1</sup> ...] { <sup>2</sup> ...} { <sup>3</sup> ...} 1 REFERENCE <small>OPT</small> 2 TEXT 3 TEXT
<code>\hglue</code> ... * DIMENSION
<code>\hiddencitation</code> [...] * REFERENCE
<code>\hiddencite</code> [...] * REFERENCE
<code>\highlight</code> [ <sup>1</sup> ...] { <sup>2</sup> ...} 1 NAME 2 TEXT
<code>\HIGHLIGHT</code> { <sup>*</sup> ...} * TEXT
<code>\highordinalstr</code> { <sup>*</sup> ...} * TEXT
<code>\hilo</code> [ <sup>1</sup> ...] { <sup>2</sup> ...} { <sup>3</sup> ...} 1 stanga <sup>OPT</sup> dreapta 2 CONTENT 3 CONTENT
<code>\himilo</code> { <sup>1</sup> ...} { <sup>2</sup> ...} { <sup>3</sup> ...} 1 CONTENT 2 CONTENT 3 CONTENT



<code>\hl [...]</code> *    NUMBER
<code>\horizontalgrowingbar [...,.*=.,...]</code> *    inherits: \setuppositionbar
<code>\horizontalpositionbar [...,.*=.,...]</code> *    inherits: \setuppositionbar
<code>\hphantom {...}</code> *    CONTENT
<code>\hpos {...} {...}</code> 1    NAME 2    CONTENT
<code>\hsizefraction {...} {...}</code> 1    DIMENSION 2    NUMBER
<code>\hsmash {...}</code> *    CONTENT
<code>\hsmashbox ...</code> *    CSNAME NUMBER
<code>\hsmashed {...}</code> *    CONTENT
<code>\hspace [...] [...]</code> 1    NAME        OPT        OPT 2    mic mediu mare normal implicit niciunul .5 1 2 3 speech minicitat interquotation citat sentence intersentence NAME
<code>\htdpofstring {...}</code> *    TEXT
<code>\htofstring {...}</code> *    TEXT
<code>\hyphen</code>
<code>\hyphenatedcoloredword {...}</code> *    TEXT
<code>\hyphenatedfile {...}</code> *    FILE
<code>\hyphenatedfilename {...}</code> *    TEXT
<code>\hyphenatedhbox {...}</code> *    CONTENT
<code>\hyphenatedpar {...}</code> *    TEXT
<code>\hyphenatedurl {...}</code> *    TEXT

<code>\hyphenatedword {...}</code> * TEXT
<code>\INRSTEX</code>
<code>\ibox {...}</code> * CONTENT
<code>\ifassignment .<sup>1</sup>. \else .<sup>2</sup>. \fi</code> 1 TRUE 2 FALSE
<code>\iff</code>
<code>\ifinobject .<sup>1</sup>. \else .<sup>2</sup>. \fi</code> 1 TRUE 2 FALSE
<code>\ifinoutputstream .<sup>1</sup>. \else .<sup>2</sup>. \fi</code> 1 TRUE 2 FALSE
<code>\ifparameters .<sup>1</sup>. \else .<sup>2</sup>. \fi</code> 1 TRUE 2 FALSE
<code>\iftrialtypesetting .<sup>1</sup>. \else .<sup>2</sup>. \fi</code> 1 TRUE 2 FALSE
<code>\ignoreimplicitspaces</code>
<code>\ignorevalue {...}</code> * NAME
<code>\immediatesavetwopassdata {...} {...} {...}</code> 1 NAME 2 NUMMER 3 CONTENT
<code>\impartefloat [...,<sup>1</sup>...,...] {...} {...}</code> 1 inherits: \seteazaimpartefloat <sup>OPT</sup> 2 BEFEHL 3 CONTENT
<code>\impliedby</code>
<code>\implies</code>
<code>\in {...} {...} [...]</code> 1 TEXT <sup>OPT</sup> OPT 2 TEXT 3 REFERENCE
<code>\inalt {...}</code> * CONTENT

<code>\HIGH {...}</code> *   CONTENT instances: unitshigh
<code>\unitshigh {...}</code> *   CONTENT
<code>\inclinat</code>
<code>\inclinataldin</code>
<code>\includemenu [...]</code> *   NAME
<code>\includeversioninfo {...}</code> *   NAME
<code>\increment \...</code> *   CSNAME
<code>\incrementcounter [...<sup>1</sup>] [...<sup>2</sup>]</code> 1   NAME                           OPT 2   NUMMER
<code>\incrementedcounter [...]</code> *   NAME
<code>\incrementpagenumber</code>
<code>\incrementsubpagenumber</code>
<code>\incrementvalue {...}</code> *   NAME
<code>\increment cd:parenttheses-1</code> *   CSNAME NUMMER
<code>\indentation</code>
<code>\infofont</code>
<code>\infofontbold</code>
<code>\inframed [...<sup>1</sup>...<sup>2</sup>]{...}</code> 1   inherits: \setea2ainconjurat 2   CONTENT
<code>\inheritparameter [...<sup>1</sup>][...<sup>2</sup>][...<sup>3</sup>]</code> 1   TEXT 2   TEXT 3   KEY
<code>\inhibitblank</code>
<code>\initializeboxstack {...}</code> *   NAME

$\backslash$ injos [...] * DIMENSION
$\backslash$ inlinebuffer [..., <sup>OPT</sup> ...] * BUFFER
$\backslash$ inlinedbox {...} * CONTENT
$\backslash$ inlinemath {...} * CONTENT
$\backslash$ inlinemathematics {...} * CONTENT
$\backslash$ inlinemessage {...} * TEXT
$\backslash$ inlineordisplaymath {... <sup>1</sup> } {... <sup>2</sup> } 1 CONTENT 2 CONTENT
$\backslash$ inlineprettyprintbuffer {... <sup>1</sup> } {... <sup>2</sup> } 1 BUFFER 2 mp lua xml parsed-xml nested tex context niciunul NAME
$\backslash$ inlinerange [...] * REFERENCE
$\backslash$ inlinie {... <sup>1</sup> } [... <sup>2</sup> ] 1 TEXT <sup>OPT</sup> 2 REFERENCE
$\backslash$ innerflushshapebox
$\backslash$ input {...} * FILE
$\backslash$ inputfilebarename
$\backslash$ inputfilename
$\backslash$ inputfilerealsuffix
$\backslash$ inputfilesuffix
$\backslash$ inputgivenfile {...} * FILE
$\backslash$ input ... * FILE
$\backslash$ insertpages [... <sup>1</sup> ] [... <sup>2</sup> ,...] <sup>OPT</sup> [... <sup>3</sup> ,... <sup>3</sup> ,...] <sup>OPT</sup> 1 FILE 2 NUMMER 3 latime = DIMENSION n = NUMMER category = NAME

<pre> \instalarelimba [...] [...<sup>2</sup>...,...] 1  NAME 2  inherits: \setarelimba </pre>
<pre> \instalarelimba [...] [...<sup>2</sup>] 1  NAME 2  SPRACHE </pre>
<pre> \installactionhandler {...} *  NAME </pre>
<pre> \installactivecharacter ... *  CHARACTER </pre>
<pre> \installanddefineactivecharacter <sup>1</sup>... {...<sup>2</sup>} 1  CHARACTER 2  BEFEHL </pre>
<pre> \installattributestack \*... *  CSNAME </pre>
<pre> \installautocommandhandler \<sup>1</sup>... {...<sup>2</sup>} \<sup>3</sup>... 1  CSNAME 2  NAME 3  CSNAME </pre>
<pre> \installautosetuphandler \<sup>1</sup>... {...<sup>2</sup>} 1  CSNAME 2  NAME </pre>
<pre> \installbasicautosetuphandler \<sup>1</sup>... {...<sup>2</sup>} \<sup>3</sup>... 1  CSNAME 2  NAME 3  CSNAME </pre>
<pre> \installbasicparameterhandler \<sup>1</sup>... {...<sup>2</sup>} 1  CSNAME 2  NAME </pre>
<pre> \installbottomframerenderer {...<sup>1</sup>} {...<sup>2</sup>} 1  NAME 2  BEFEHL </pre>
<pre> \installcommandhandler \<sup>1</sup>... {...<sup>2</sup>} \<sup>3</sup>... 1  CSNAME 2  NAME 3  CSNAME </pre>
<pre> \installcorenamespace {...} *  NAME </pre>
<pre> \installdefinehandler \<sup>1</sup>... {...<sup>2</sup>} \<sup>3</sup>... 1  CSNAME 2  NAME 3  CSNAME </pre>
<pre> \installdefinitionset \<sup>1</sup>... {...<sup>2</sup>} 1  CSNAME 2  NAME </pre>

\installdefinitionsetmember \... {...} \... {...}

1 CSNAME  
2 NAME  
3 CSNAME  
4 NAME

\installdirectcommandhandler \... {...}

1 CSNAME  
2 NAME

\installdirectparameterhandler \... {...}

1 CSNAME  
2 NAME

\installdirectparametersethandler \... {...}

1 CSNAME  
2 NAME

\installdirectsetuphandler \... {...}

1 CSNAME  
2 NAME

\installdirectstyleandcolorhandler \... {...}

1 CSNAME  
2 NAME

\installframedautocommandhandler \... {...} \...

1 CSNAME  
2 NAME  
3 CSNAME

\installframedcommandhandler \... {...} \...

1 CSNAME  
2 NAME  
3 CSNAME

\installleftframerenderer {...} {...}

1 NAME  
2 BEFEHL

\installnamespace {...}

\* NAME

\installoutputroutine \... {...}

1 CSNAME  
2 BEFEHL

\installpagearrangement ... {...}

1 NAME  
2 BEFEHL

\installparameterhandler \... {...}

1 CSNAME  
2 NAME

\installparameterhashhandler \... {...}

1 CSNAME  
2 NAME

\installparametersethandler \... {...}

1 CSNAME  
2 NAME

\installparentinjector \ <sup>1</sup> ... { <sup>2</sup> ...} 1 CSNAME 2 NAME
\installrightframerenderer { <sup>1</sup> ...} { <sup>2</sup> ...} 1 NAME 2 BEFEHL
\installrootparameterhandler \ <sup>1</sup> ... { <sup>2</sup> ...} 1 CSNAME 2 NAME
\installsetuphandler \ <sup>1</sup> ... { <sup>2</sup> ...} 1 CSNAME 2 NAME
\installsetuponlycommandhandler \ <sup>1</sup> ... { <sup>2</sup> ...} 1 CSNAME 2 NAME
\installshipoutmethod { <sup>1</sup> ...} { <sup>2</sup> ...} 1 NAME 2 BEFEHL
\installsimplecommandhandler \ <sup>1</sup> ... { <sup>2</sup> ...} \ <sup>3</sup> ... 1 CSNAME 2 NAME 3 CSNAME
\installsimpleframedcommandhandler \ <sup>1</sup> ... { <sup>2</sup> ...} \ <sup>3</sup> ... 1 CSNAME 2 NAME 3 CSNAME
\installstyleandcolorhandler \ <sup>1</sup> ... { <sup>2</sup> ...} 1 CSNAME 2 NAME
\installswitchcommandhandler \ <sup>1</sup> ... { <sup>2</sup> ...} \ <sup>3</sup> ... 1 CSNAME 2 NAME 3 CSNAME
\installswitchsetuphandler \ <sup>1</sup> ... { <sup>2</sup> ...} 1 CSNAME 2 NAME
\installtexdirective { <sup>1</sup> ...} { <sup>2</sup> ...} { <sup>3</sup> ...} 1 NAME 2 BEFEHL 3 BEFEHL
\installtextracker { <sup>1</sup> ...} { <sup>2</sup> ...} { <sup>3</sup> ...} 1 NAME 2 BEFEHL 3 BEFEHL
\installtopframerenderer { <sup>1</sup> ...} { <sup>2</sup> ...} 1 NAME 2 BEFEHL

<code>\installunitsseparator {...} {...}</code> 1 NAME 2 BEFEHL
<code>\installunitsspace {...} {...}</code> 1 NAME 2 BEFEHL
<code>\installversioninfo {...} {...}</code> 1 NAME 2 BEFEHL
<code>\integerrounding {...}</code> * NUMMER
<code>\intertext {...}</code> * TEXT
<code>\intins [...,...<sup>1</sup>...,...] {...}</code> 1 inherits: \set <sup>OPT</sup> upstretched 2 TEXT
<code>\invokepagehandler {...} {...}</code> 1 normal niciunul NAME 2 CONTENT
<code>\istltdir ...</code> * TLT TRT
<code>\istrtdir ...</code> * TLT TRT
<code>\italic</code>
<code>\italicaldin</code>
<code>\italiccorrection</code>
<code>\italicface</code>
<code>\itemtag [...,*,...]</code> * REFERENCE <sup>OPT</sup>
<code>\jobfilename</code>
<code>\jobfilesuffix</code>
<code>\jos {...}</code> * CONTENT
<code>\jossus [...<sup>1</sup>] {...} {...<sup>3</sup>}</code> 1 stanga dreapta <sup>OPT</sup> 2 CONTENT 3 CONTENT
<code>\LOW {...}</code> * CONTENT instances: unitslow



<code>\unitslow {...}</code> *   CONTENT
<code>\Kap {...}</code> *   TEXT
<code>\kap {...}</code> *   TEXT
<code>\keeplinestogether {...}</code> *   NUMMER
<code>\keepunwantedspaces</code>
<code>\kerncharacters [...]</code> <small>OPT</small> <code>{...}</code> 1   NUMBER 2   TEXT
<code>\koreancirclenumerals {...}</code> *   NUMBER
<code>\koreannumerals {...}</code> *   NUMBER
<code>\koreannumeralsc {...}</code> *   NUMBER
<code>\koreannumeralsp {...}</code> *   NUMBER
<code>\koreanparentnumerals {...}</code> *   NUMBER
<code>\LAMSTEX</code>
<code>\LATEX</code>
<code>\LamSTeX</code>
<code>\LaTeX</code>
<code>\Litera {...}</code> *   NUMBER
<code>\Litere {...}</code> *   NUMBER
<code>\LUAJITTEX</code>
<code>\LUATEX</code>
<code>\LUNA {...}</code> *   NUMBER
<code>\Lua</code>

<code>\LuajitTeX</code>
<code>\LuaTeX</code>
<code>\la {<sup>1</sup>...} {<sup>2</sup>...} [<sup>3</sup>...]</code> 1 <code>TEXT<sup>PT</sup></code> <code>OPT</code> 2 <code>TEXT</code> 3 <code>REFERENCE</code>
<code>\LABELlimba</code> instances: head label mathlabel taglabel unit operator prefix suffix btxlabel
<code>\btxlabellimba</code>
<code>\headlimba</code>
<code>\labellimba</code>
<code>\mathlabellimba</code>
<code>\operatorlimba</code>
<code>\prefixlimba</code>
<code>\suffixlimba</code>
<code>\taglabellimba</code>
<code>\unitlimba</code>
<code>\LABELtexts {<sup>1</sup>...} {<sup>2</sup>...}</code> 1 <code>KEY</code> 2 <code>TEXT</code> instances: head label mathlabel
<code>\headtexts {<sup>1</sup>...} {<sup>2</sup>...}</code> 1 <code>KEY</code> 2 <code>TEXT</code>
<code>\labeltexts {<sup>1</sup>...} {<sup>2</sup>...}</code> 1 <code>KEY</code> 2 <code>TEXT</code>
<code>\mathlabeltexts {<sup>1</sup>...} {<sup>2</sup>...}</code> 1 <code>KEY</code> 2 <code>TEXT</code>
<code>\languageCharacters {<sup>*</sup>...}</code> * <code>NUMMER</code>
<code>\languagecharacters {<sup>*</sup>...}</code> * <code>NUMMER</code>
<code>\languagecharwidth {<sup>*</sup>...}</code> * <code>SPRACHE</code>

<code>\lapagina [...]</code> * REFERENCE
<code>\lastcounter [<sup>1</sup>...] [<sup>2</sup>...]</code> 1 NAME OPT 2 NUMMER
<code>\lastcountervalue [...]</code> * NAME
<code>\lastdigit {...}</code> * NUMMER
<code>\lastlinewidth</code>
<code>\lastnaturalboxdp</code>
<code>\lastnaturalboxht</code>
<code>\lastnaturalboxwd</code>
<code>\lastpredefinedsymbol</code>
<code>\lastrealpage</code>
<code>\lastrealpagenumber</code>
<code>\lastsubcountervalue [<sup>1</sup>...] [<sup>2</sup>...]</code> 1 NAME 2 NUMMER
<code>\lastsubpagenumber</code>
<code>\lasttwodigits {...}</code> * NUMMER
<code>\lastuserpage</code>
<code>\lastuserpagenumber</code>
<code>\lateluacode {...}</code> * BEFEHL
<code>\layeredtext [...,<sup>1</sup>...,...] [...,<sup>2</sup>...,...] {...} {...<sup>4</sup>}</code> 1 inherits: \setuplayer <sup>P</sup> PT OPT 2 inherits: \setuplayeredtext 3 TEXT 4 CONTENT
<code>\layerheight</code>
<code>\layerwidth</code>

$\backslash\text{lazysavetaggedtwopassdata}$ $\{.^1.\}$ $\{.^2.\}$ $\{.^3.\}$ $\{.^4.\}$ 1 NAME 2 NUMMER 3 NAME 4 CONTENT
$\backslash\text{lazysavetwopassdata}$ $\{.^1.\}$ $\{.^2.\}$ $\{.^3.\}$ 1 NAME 2 NUMMER 3 CONTENT
$\backslash\text{lbox}$ $\{.^1.\}$ $\{.^2.\}$ 1 TEXT <small>OPT</small> 2 CONTENT
$\backslash\text{leftbottombox}$ $\{.^*.\}$ * CONTENT
$\backslash\text{leftbox}$ $\{.^*.\}$ * CONTENT
$\backslash\text{lefthbox}$ $\{.^*.\}$ * CONTENT
$\backslash\text{leftLABELtext}$ $\{.^*.\}$ * KEY instances: head label mathlabel
$\backslash\text{leftheadtext}$ $\{.^*.\}$ * KEY
$\backslash\text{leftlabeltext}$ $\{.^*.\}$ * KEY
$\backslash\text{leftmathlabeltext}$ $\{.^*.\}$ * KEY
$\backslash\text{leftline}$ $\{.^*.\}$ * CONTENT
$\backslash\text{lefttorrighthbox}$ $\{.^1.\}$ $\{.^2.\}$ 1 TEXT <small>OPT</small> 2 CONTENT
$\backslash\text{lefttorrightvbox}$ $\{.^1.\}$ $\{.^2.\}$ 1 TEXT <small>OPT</small> 2 CONTENT
$\backslash\text{lefttorrightvtop}$ $\{.^1.\}$ $\{.^2.\}$ 1 TEXT <small>OPT</small> 2 CONTENT
$\backslash\text{leftskipadaption}$
$\backslash\text{leftsubguillemot}$
$\backslash\text{lefttopbox}$ $\{.^*.\}$ * CONTENT

<code>\lefttoright</code>
<code>\lefttorighthbox</code> <sup>1</sup> ... { <sup>2</sup> ...} 1 TEXT OPT 2 CONTENT
<code>\lefttorightvbox</code> <sup>1</sup> ... { <sup>2</sup> ...} 1 TEXT OPT 2 CONTENT
<code>\lefttorightvtop</code> <sup>1</sup> ... { <sup>2</sup> ...} 1 TEXT OPT 2 CONTENT
<code>\letbeundefined</code> {.*} * NAME
<code>\letcatcodecommand</code> \ <sup>1</sup> ... <sup>2</sup> ... \ <sup>3</sup> ... 1 CSNAME 2 CHARACTER NUMBER 3 CSNAME
<code>\letcscsname</code> \ <sup>1</sup> ... \csname <sup>2</sup> ... \endcsname 1 CSNAME 2 NAME
<code>\letcsnamecs</code> \csname <sup>1</sup> ... \endcsname \ <sup>2</sup> ... 1 NAME 2 CSNAME
<code>\letcsnamecsname</code> \csname <sup>1</sup> ... \endcsname \csname <sup>2</sup> ... \endcsname 1 NAME 2 NAME
<code>\letdummyparameter</code> { <sup>1</sup> ...} \ <sup>2</sup> ... 1 KEY 2 CSNAME
<code>\letempty</code> \*... * CSNAME
<code>\letgvalue</code> { <sup>1</sup> ...} \ <sup>2</sup> ... 1 NAME 2 CSNAME
<code>\letgvalueempty</code> {.*} * NAME
<code>\letgvalurelax</code> {.*} * NAME
<code>\letterampersand</code>
<code>\letterat</code>
<code>\letterbackslash</code>
<code>\letterbar</code>

<code>\letterbgroup</code>
<code>\letterclosebrace</code>
<code>\lettercolon</code>
<code>\letterdollar</code>
<code>\letterdoublequote</code>
<code>\letteregroup</code>
<code>\letterescape</code>
<code>\letterexclamationmark</code>
<code>\letterhash</code>
<code>\letterhat</code>
<code>\letterleftbrace</code>
<code>\letterleftbracket</code>
<code>\letterleftparenthesis</code>
<code>\letterless</code>
<code>\lettermore</code>
<code>\letteropenbrace</code>
<code>\letterpercent</code>
<code>\letterquestionmark</code>
<code>\letterrightbrace</code>
<code>\letterrightbracket</code>
<code>\letterrightparenthesis</code>
<code>\lettersinglequote</code>
<code>\letterslash</code>
<code>\letterspacing</code> [ <sup>1</sup> ...] { <sup>2</sup> ...} 1    NUMBER                    OPT 2    TEXT
<code>\lettertilde</code>
<code>\letterunderscore</code>

<code>\letvalue {...} \^2..</code> 1 NAME 2 CSNAME
<code>\letvalueempty {...}</code> * NAME
<code>\letvaluerelax {...}</code> * NAME
<code>\lfence {...}</code> * CHARACTER
<code>\lhbox {...}</code> * CONTENT
<code>\limba [...]</code> * SPRACHE
<code>\limbaprinzipala [...]</code> * SPRACHE
<code>\LANGUAGE</code>
<code>\limitatefirstline {...} {...} {...}</code> 1 TEXT 2 DIMENSION 3 BEFEHL
<code>\limitatelines {...} {...} {...}</code> 1 NUMMER 2 BEFEHL 3 TEXT
<code>\limitatetext {...} {...} {...}</code> 1 TEXT 2 [-+]DIMENSION 3 BEFEHL
<code>\limitatetext {...} {...^2,...} {...}</code> 1 TEXT 2 [-+]DIMENSION 3 BEFEHL
<code>\LINENOTE {...}</code> * TEXT instances: linenote
<code>\linenote {...}</code> * TEXT
<code>\linespanningtext {...} {...} {...}</code> 1 TEXT 2 DIMENSION 3 FONT
<code>\linie {...}</code> * CONTENT

\linieneagra [...,.*,...] * inherits: \seteazalinifinegre
\liniesubtire
\linieumplere [...,.*,...] * inherits: \seteazaliniiumplere
\liniinegre [...,.*,...] * inherits: \seteazalinifinegre
\liniisubtiri [...,.*,...] * inherits: \seteazalinifsubtire
\listcitation [...,.*,...] [...^2] 1 referinta = REFERENCE alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear inainte = BEFEHL dupa = BEFEHL stanga = BEFEHL dreapta = BEFEHL inherits: \setupbtx 2 REFERENCE
\listcitation [...^1] [...^2] 1 implicit category <sup>OPT</sup> entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear 2 REFERENCE
\listcitation [...,.*,...] [...,.*,...] 1 referinta = REFERENCE alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear inainte = BEFEHL dupa = BEFEHL stanga = BEFEHL dreapta = BEFEHL inherits: \setupbtx 2 KEY = VALUE
\listcite [...,.*,...] [...^2] 1 referinta = REFERENCE alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear inainte = BEFEHL dupa = BEFEHL stanga = BEFEHL dreapta = BEFEHL inherits: \setupbtx 2 REFERENCE
\listcite [...^1] [...^2] 1 implicit category <sup>OPT</sup> entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear 2 REFERENCE
\listcite [...,.*,...] [...,.*,...] 1 referinta = REFERENCE alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear inainte = BEFEHL dupa = BEFEHL stanga = BEFEHL dreapta = BEFEHL inherits: \setupbtx 2 KEY = VALUE
\listnamespaces



<code>\litera {...}</code> *   NUMBER
<code>\litere {...}</code> *   NUMBER
<code>\llap {...}</code> *   CONTENT
<code>\loadanyfile [...]</code> *   FILE
<code>\loadanyfileonce [...]</code> *   FILE
<code>\loadbtxdefinitionfile [...]</code> *   FILE
<code>\loadbtxreplacementfile [...]</code> *   FILE
<code>\loadcldfile [...]</code> *   FILE
<code>\loadcldfileonce [...]</code> *   FILE
<code>\loadfontgoodies [...]</code> *   FILE
<code>\loadluafile [...]</code> *   FILE
<code>\loadluafileonce [...]</code> *   FILE
<code>\loadspellchecklist [...] [...]</code> 1   NAME 2   FILE
<code>\loadtexfile [...]</code> *   FILE
<code>\loadtexfileonce [...]</code> *   FILE
<code>\loadtypescriptfile [...]</code> *   FILE
<code>\localframed [...] [...<sup>2</sup>...<sup>2</sup>...] {...<sup>3</sup>}</code> 1   NAME 2   inherits: \setezainconjurat 3   CONTENT
<code>\localframedwithsettings [...] [...<sup>2</sup>...<sup>2</sup>...] {...<sup>3</sup>}</code> 1   NAME 2   inherits: \setezainconjurat 3   CONTENT

<code>\localhsize</code>
<code>\localpopbox ...</code> <code>* CSNAME NUMBER</code>
<code>\localpopmacro \...</code> <code>* CSNAME</code>
<code>\localpushbox ...</code> <code>* CSNAME NUMBER</code>
<code>\localpushmacro \...</code> <code>* CSNAME</code>
<code>\localundefine {...}</code> <code>* NAME</code>
<code>\locatedfilepath</code>
<code>\locatefilepath {...}</code> <code>* FILE</code>
<code>\locfilename {...}</code> <code>* FILE</code>
<code>\lomihi {...} {...} {...}</code> <code>1 CONTENT</code> <code>2 CONTENT</code> <code>3 CONTENT</code>
<code>\lowerbox {...} \.^ {...}</code> <code>1 DIMENSION</code> <code>2 CSNAME</code> <code>3 CONTENT</code>
<code>\lowercased {...}</code> <code>* TEXT</code>
<code>\lowercasestring ... \to \.^</code> <code>1 TEXT</code> <code>2 CSNAME</code>
<code>\lowerlefthdoubleninequote</code>
<code>\lowerleftsingleninequote</code>
<code>\lowerrighthdoubleninequote</code>
<code>\lowerrightsingleninequote</code>
<code>\LOWHIGH [...]<sup>OPT</sup> {...} {...}</code> <code>1 stanga dreapta</code> <code>2 CONTENT</code> <code>3 CONTENT</code>

$\backslash LOWMIDHIGH$ $\{.^1.\}$ $\{.^2.\}$ $\{.^3.\}$ 1    CONTENT 2    CONTENT 3    CONTENT
$\backslash rttb\!box$ $\{.^1.\}$ $\{.^2.\}$ $\{.^3.\}$ $\{.^4.\}$ $\{.^5.\}$ 1    DIMENSION 2    DIMENSION 3    DIMENSION 4    DIMENSION 5    CONTENT
$\backslash ltop$ $\{.^1.\}$ $\{.^2.\}$ 1    TEXT <sup>OPT</sup> 2    CONTENT
$\backslash lua\!code$ $\{.^*.\}$ *    BEFEHL
$\backslash lua\!conditional$ $\backslash \{.^*.\}$ *    CSNAME
$\backslash lua\!environment$ $\{.^*.\}$ *    FILE
$\backslash lua\!expanded$ $\{.^*.\}$ *    BEFEHL
$\backslash lua\!expr$ $\{.^*.\}$ *    CONTENT
$\backslash lua\!function$ $\{.^*.\}$ *    BEFEHL
$\backslash lua\!jitTeX$
$\backslash lua\!major\!version$
$\backslash lua\!minor\!version$
$\backslash lua\!parameterset$ $\{.^1.\}$ $\{.^2.\}$ 1    NAME 2    CONTENT
$\backslash lua\!setup$ $\{.^*.\}$ *    NAME
$\backslash luaTeX$
$\backslash lua\!version$
$\backslash luna$ $\{.^*.\}$ *    NUMMER
$\backslash lungimelista$
$\backslash META\!FONT$

<code>\METAFUN</code>
<code>\METAPOST</code>
<code>\MetaFont</code>
<code>\MetaFun</code>
<code>\MetaPost</code>
<code>\MKII</code>
<code>\MKIV</code>
<code>\MKIX</code>
<code>\MKVI</code>
<code>\MKXI</code>
<code>\MONTHLONG {...}</code> *    NUMBER
<code>\MONTHSHORT {...}</code> *    NUMBER
<code>\MPanchor {...}</code> *    NAME
<code>\MPbetex {...}</code> *    NAME
<code>\MPc {...}</code> *    NAME
<code>\MPcode {...<sup>1</sup>} {...<sup>2</sup>}</code> 1    NAME        OPT 2    CONTENT
<code>\MPcolor {...}</code> *    COLOR
<code>\MPcoloronly {...}</code> *    COLOR
<code>\MPcolumn {...}</code> *    NAME
<code>\MPd {...}</code> *    NAME
<code>\MPdrawing {...}</code> *    CONTENT

\MPfontsizehskip {...} *    FONT
\MPgetmultipars {...} {...} 1    NAME 2    NAME
\MPgetmultishape {...} {...} 1    NAME 2    NAME
\MPgetposboxes {..., <sup>1</sup> ...} {... <sup>2</sup> } 1    NAME 2    NAME
\MPH {...} *    NAME
\MPII
\MPIV
\MPinclusions [... <sup>1</sup> ] {... <sup>2</sup> } {... <sup>3</sup> } 1    +                    OPT        OPT 2    NAME 3    CONTENT
\MPleftskip {...} *    NAME
\MPll {...} *    NAME
\MPlr {...} *    NAME
\MPls {...} *    NAME
\MPmenubuttons {...} *    NAME
\MPn {...} *    NAME
\MPoptions {...} *    COLOR
\MPoverlayanchor {...} *    NAME
\MPp {...} *    NAME
\MPpage {...} *    NAME

`\MPpardata {...}`

\* NAME

$$\backslash\mathrm{MPplus} \{.^1.\} \{.^2.\} \{.^3.\}$$

1 NAME

2 NUMMER

### 3 CONTENT

$$\backslash \text{MP}_{\text{pos}} \{ \dots \}$$

\* NAME

$$\backslash MPpositiongraphic \{...\} \{...,... \stackrel{2}{=} ...,...\}$$

1 NAME

2    KEY    =    VALUE

$$\backslash \text{MPposset} \{...\}$$

\* NAME

$$\backslash \text{MP}r \{..*\}$$

\* NAME

$$\backslash \text{MPrawvar} \{.^1..\} \{.^2..\}$$

1 NAME

2 KEY

`\MPregion {...}`

\* NAME

`\MPrest {..1.} {..2.}`

1 NAME

2 CONTENT

`\MPrightskip {...}`

\* NAME

`\MPrs {..*..}`

\* NAME

$$\backslash \text{MPstring} \{...\}$$

\* NAME

`\MPtext {...}`

\* NAME

`\MPtransparency {...}`

\* COLOR

$$\backslash\mathrm{MPu1} \{.\!.\!.\}$$

\* NAME

$$\backslash\text{MPur} \{.\dots\}$$

\* NAME

\MPVI

$$\backslash \text{MPv} \quad \{ \dots^1 \} \quad \{ \dots^2 \} \quad \{ \dots^3 \}$$

1 NAME

1	NAME
2	NUMMER

3 CONTENT

\MPvar {...} * KEY
\MPvariable {...} * KEY
\MPvv {... <sup>1</sup> } {... <sup>2</sup> } 1 NAME 2 CONTENT
\MPw {...} * NAME
\MPwhd {...} * NAME
\MPx {...} * NAME
\MPxy {...} * NAME
\MPxywhd {...} * NAME
\MPy {...} * NAME
\m [... <sup>1</sup> ] {... <sup>2</sup> } 1 NAME 2 CONTENT
\makecharacteractive ... * CHARACTER
\makerawcommalist [... <sup>1</sup> ,...] \... <sup>2</sup> ... 1 BEFEHL 2 CSNAME
\makestrutofbox ... * CSNAME NUMBER
\mapfontsize [... <sup>1</sup> ] [... <sup>2</sup> ] 1 DIMENSION 2 DIMENSION
\marcaje (... <sup>1</sup> ,...) (... <sup>2</sup> ,...) [... <sup>3</sup> ] 1 POSITION 2 POSITION 3 REFERENCE
\mare ... * CHARACTER
\margindata [... <sup>1</sup> ] [... <sup>2</sup> ... <sup>2</sup> ...] [... <sup>3</sup> ... <sup>3</sup> ...] {... <sup>4</sup> } 1 NAME 2 referinta = REFERENCE 3 inherits: \setupmargindata 4 inherits: \setupmarginframed 4 CONTENT

`\MARGINDATA [...,\1...,...] [...,\2...,...] {\3...}`

1 referinta = REFERENCE<sup>OPT</sup>  
 inherits: \setupmargindata  
 2 inherits: \setupmarginframed  
 3 CONTENT

instances: inleftmargin inrightmargin inoutermargin ininnermargin inleftedge inrightedge  
 inouteredge ininneredge atleftmargin atrightmargin inleft inright inouter ininner inmargin  
 inother margintext

`\atleftmargin [...,\1...,...] [...,\2...,...] {\3...}`

1 referinta = REFERENCE<sup>T</sup>  
 inherits: \setupmargindata  
 2 inherits: \setupmarginframed  
 3 CONTENT

`\atrightmargin [...,\1...,...] [...,\2...,...] {\3...}`

1 referinta = REFERENCE<sup>OPT</sup>  
 inherits: \setupmargindata  
 2 inherits: \setupmarginframed  
 3 CONTENT

`\ininner [...,\1...,...] [...,\2...,...] {\3...}`

1 referinta = REFERENCE<sup>OPT</sup>  
 inherits: \setupmargindata  
 2 inherits: \setupmarginframed  
 3 CONTENT

`\ininneredge [...,\1...,...] [...,\2...,...] {\3...}`

1 referinta = REFERENCE<sup>OPT</sup>  
 inherits: \setupmargindata  
 2 inherits: \setupmarginframed  
 3 CONTENT

`\ininnermargin [...,\1...,...] [...,\2...,...] {\3...}`

1 referinta = REFERENCE<sup>OPT</sup>  
 inherits: \setupmargindata  
 2 inherits: \setupmarginframed  
 3 CONTENT

`\inleft [...,\1...,...] [...,\2...,...] {\3...}`

1 referinta = REFERENCE<sup>OPT</sup>  
 inherits: \setupmargindata  
 2 inherits: \setupmarginframed  
 3 CONTENT

`\inleftedge [...,\1...,...] [...,\2...,...] {\3...}`

1 referinta = REFERENCE<sup>OPT</sup>  
 inherits: \setupmargindata  
 2 inherits: \setupmarginframed  
 3 CONTENT

`\inleftmargin [...,\1...,...] [...,\2...,...] {\3...}`

1 referinta = REFERENCE<sup>T</sup>  
 inherits: \setupmargindata  
 2 inherits: \setupmarginframed  
 3 CONTENT

`\inmargin [...,\1...,...] [...,\2...,...] {\3...}`

1 referinta = REFERENCE<sup>OPT</sup>  
 inherits: \setupmargindata  
 2 inherits: \setupmarginframed  
 3 CONTENT



<pre> \inother [...<sup>1</sup>...<sup>2</sup>...] {...<sup>3</sup>} 1 referinta = REFERENCE<sup>OPT</sup>   inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT </pre>
<pre> \inouter [...<sup>1</sup>...<sup>2</sup>...] {...<sup>3</sup>} 1 referinta = REFERENCE<sup>OPT</sup>   inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT </pre>
<pre> \inouteredge [...<sup>1</sup>...<sup>2</sup>...] {...<sup>3</sup>} 1 referinta = REFERENCE<sup>OPT</sup>   inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT </pre>
<pre> \inoutermargin [...<sup>1</sup>...<sup>2</sup>...] {...<sup>3</sup>} 1 referinta = REFERENCE<sup>OPT</sup>   inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT </pre>
<pre> \inright [...<sup>1</sup>...<sup>2</sup>...] {...<sup>3</sup>} 1 referinta = REFERENCE<sup>OPT</sup>   inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT </pre>
<pre> \inrightedge [...<sup>1</sup>...<sup>2</sup>...] {...<sup>3</sup>} 1 referinta = REFERENCE<sup>OPT</sup>   inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT </pre>
<pre> \inrightmargin [...<sup>1</sup>...<sup>2</sup>...] {...<sup>3</sup>} 1 referinta = REFERENCE<sup>OPT</sup>   inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT </pre>
<pre> \marginext [...<sup>1</sup>...<sup>2</sup>...] {...<sup>3</sup>} 1 referinta = REFERENCE<sup>OPT</sup>   inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT </pre>
<pre> \markcontent [...<sup>1</sup>] {...<sup>2</sup>} 1 reset tot NAME<sup>OPT</sup> 2 CONTENT </pre>
<pre> \markinjector [...] * NAME </pre>
<pre> \markpage [...<sup>1</sup>] [...<sup>2</sup>] 1 NAME<sup>OPT</sup> 2 [-+]NUMBER </pre>
<pre> \mat {...} * CONTENT </pre>
<pre> \matematica [...<sup>1</sup>] {...<sup>2</sup>} 1 NAME<sup>OPT</sup> 2 CONTENT </pre>

$\backslash\mathrm{math} [\textsuperscript{1}] \{\textsuperscript{2}\}$ 1 NAME OPT 2 CONTENT
$\backslash\mathrm{mathbf}$
$\backslash\mathrm{mathbi}$
$\backslash\mathrm{mathblackboard}$
$\backslash\mathrm{mathbs}$
$\backslash\mathrm{MATHCOMMAND} \{\textsuperscript{1}\} \{\textsuperscript{2}\}$ 1 TEXT OPT OPT 2 TEXT
$\backslash\mathrm{mathdefault}$
$\backslash\mathrm{mathdouble} [\textsuperscript{1}] \{\textsuperscript{2}\} \{\textsuperscript{3}\} \{\textsuperscript{4}\}$ 1 ambele vfenced <sup>PT</sup> 2 NUMBER 3 TEXT 4 TEXT
$\backslash\mathrm{MATHDOUBLEEXTENSIBLE} \{\textsuperscript{1}\} \{\textsuperscript{2}\}$ 1 TEXT 2 TEXT instances: doublebar doublebrace doubleparent doublebracket overbarunderbar overbraceunderbrace overparentunderparent overbracketunderbracket
$\backslash\mathrm{doublebar} \{\textsuperscript{1}\} \{\textsuperscript{2}\}$ 1 TEXT 2 TEXT
$\backslash\mathrm{doublebrace} \{\textsuperscript{1}\} \{\textsuperscript{2}\}$ 1 TEXT 2 TEXT
$\backslash\mathrm{doublebracket} \{\textsuperscript{1}\} \{\textsuperscript{2}\}$ 1 TEXT 2 TEXT
$\backslash\mathrm{doubleparent} \{\textsuperscript{1}\} \{\textsuperscript{2}\}$ 1 TEXT 2 TEXT
$\backslash\mathrm{overbarunderbar} \{\textsuperscript{1}\} \{\textsuperscript{2}\}$ 1 TEXT 2 TEXT
$\backslash\mathrm{overbraceunderbrace} \{\textsuperscript{1}\} \{\textsuperscript{2}\}$ 1 TEXT 2 TEXT
$\backslash\mathrm{overbracketunderbracket} \{\textsuperscript{1}\} \{\textsuperscript{2}\}$ 1 TEXT 2 TEXT

`\overparentunderparent {...} {...}`

1 TEXT  
2 TEXT

`\MATHEXTENSIBLE {...} {...}`

1 TEXT OPT OPT  
2 TEXT

instances: xrel xequal xleftarrow xrightarrow xleftrightharrow xLeftarrow xRightarrow  
xleftrightharrow xtwoheadleftarrow xtwoheadrightarrow xmapsto xhookleftarrow xhookrightarrow  
xleftharpoondown xleftharpoonup xrightarpoondown xrightarpoonup xrightoverleftarrow  
xleftrightharpoons xrightleftharpoons xtriplerel mrel mequal mleftarrow mrightarrow mleftrightharrow  
mLeftarrow mRightarrow mLeftrightharrow mtwoheadleftarrow mtwoheadrightarrow mmapsto mhookleftarrow  
mhookrightarrow mleftharpoondown mleftharpoonup mrightarpoondown mrightarpoonup mrightoverleftarrow  
mleftrightharpoons mrightleftharpoons mtriplerel eleftrightarrowfill erightarrowfill eleftrightharrowfill  
etwoheadrightarrowfill eleftharpoondownfill eleftharpoonupfill erightharpoondownfill  
erightharpoonupfill eoverbarfill eunderbarfill eoverbracefill eunderbracefill eoverparentfill  
eunderparentfill eoverbracketfill eunderbracketfill trel tequal tmapsto tleftarrow trightarrow  
tleftrightharrow tLeftarrow tRightarrow tLeftrightharrow ttwoheadleftarrow ttwoheadrightarrow  
thookleftarrow thookrightarrow tleftharpoondown tleftharpoonup trightharpoondown trightharpoonup  
trightoverleftarrow tleftrightharpoons trightleftharpoons ttriplerel cleftarrow crightarrow  
crightoverleftarrow

`\cleftarrow {...} {...}`

1 TEXT OPT OPT  
2 TEXT

`\crightarrow {...} {...}`

1 TEXT OPT OPT  
2 TEXT

`\crightoverleftarrow {...} {...}`

1 TEXT OPT OPT  
2 TEXT

`\eleftrightarrowfill {...} {...}`

1 TEXT OPT OPT  
2 TEXT

`\eleftharpoondownfill {...} {...}`

1 TEXT OPT OPT  
2 TEXT

`\eleftharpoonupfill {...} {...}`

1 TEXT OPT OPT  
2 TEXT

`\eleftrightharrowfill {...} {...}`

1 TEXT OPT OPT  
2 TEXT

`\eoverbarfill {...} {...}`

1 TEXT OPT OPT  
2 TEXT

`\eoverbracefill {...} {...}`

1 TEXT OPT OPT  
2 TEXT

`\eoverbracketfill {...} {...}`

1 TEXT OPT OPT  
2 TEXT

$\backslash\text{eoverparentfill}$ $\{...\}^1 \{...\}^2$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash\text{erightarrowfill}$ $\{...\}^1 \{...\}^2$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash\text{erightharpoondownfill}$ $\{...\}^1 \{...\}^2$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash\text{erightharpoonupfill}$ $\{...\}^1 \{...\}^2$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash\text{etwoheadrightarrowfill}$ $\{...\}^1 \{...\}^2$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash\text{eunderbarfill}$ $\{...\}^1 \{...\}^2$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash\text{eunderbracefill}$ $\{...\}^1 \{...\}^2$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash\text{eunderbracketfill}$ $\{...\}^1 \{...\}^2$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash\text{eunderparentfill}$ $\{...\}^1 \{...\}^2$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash\text{mequal}$ $\{...\}^1 \{...\}^2$ 1    TEXT            OPT            OPT 2    TEXT
$\backslash\text{mhookleftarrow}$ $\{...\}^1 \{...\}^2$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash\text{mhookrightarrow}$ $\{...\}^1 \{...\}^2$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash\text{mLeftarrow}$ $\{...\}^1 \{...\}^2$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash\text{mLeftrightarrow}$ $\{...\}^1 \{...\}^2$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash\text{mleftarrow}$ $\{...\}^1 \{...\}^2$ 1    TEXT                    OPT            OPT 2    TEXT

$\backslash\mleftharpoonowdown \{...\} \{...\}$ 1    TEXT                      OPT            OPT 2    TEXT
$\backslash\mleftharpoonowup \{...\} \{...\}$ 1    TEXT                      OPT            OPT 2    TEXT
$\backslash\mleftrightharpoonow \{...\} \{...\}$ 1    TEXT                      OPT            OPT 2    TEXT
$\backslash\mleftrightharpoonows \{...\} \{...\}$ 1    TEXT                      OPT            OPT 2    TEXT
$\backslash\mmapsto \{...\} \{...\}$ 1    TEXT                      OPT            OPT 2    TEXT
$\backslash\mRightharpoonow \{...\} \{...\}$ 1    TEXT                      OPT            OPT 2    TEXT
$\backslash\mrel \{...\} \{...\}$ 1    TEXT    OPT            OPT 2    TEXT
$\backslash\mrightharpoonow \{...\} \{...\}$ 1    TEXT                      OPT            OPT 2    TEXT
$\backslash\mrightharpoonowdown \{...\} \{...\}$ 1    TEXT                      OPT            OPT 2    TEXT
$\backslash\mrightharpoonowup \{...\} \{...\}$ 1    TEXT                      OPT            OPT 2    TEXT
$\backslash\mrightharpoonows \{...\} \{...\}$ 1    TEXT                      OPT            OPT 2    TEXT
$\backslash\mrightharpoonowleftarrow \{...\} \{...\}$ 1    TEXT                      OPT            OPT 2    TEXT
$\backslash\mtriplerel \{...\} \{...\}$ 1    TEXT                      OPT            OPT 2    TEXT
$\backslash\mtwoheadleftarrow \{...\} \{...\}$ 1    TEXT                      OPT            OPT 2    TEXT
$\backslash\mtwoheadrightarrow \{...\} \{...\}$ 1    TEXT                      OPT            OPT 2    TEXT

$\backslash tequal \{...\} \{...\}$ 1    TEXT            OPT            OPT 2    TEXT
$\backslash thookleftarrow \{...\} \{...\}$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash thookrightarrow \{...\} \{...\}$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash tLeftarrow \{...\} \{...\}$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash tLeftrightarrow \{...\} \{...\}$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash tleftarrow \{...\} \{...\}$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash tleftharpoondown \{...\} \{...\}$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash tleftharpoonup \{...\} \{...\}$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash tleftrightharpoonup \{...\} \{...\}$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash tleftrightharpoons \{...\} \{...\}$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash tmapsto \{...\} \{...\}$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash tRrightarrow \{...\} \{...\}$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash trel \{...\} \{...\}$ 1    TEXT    OPT            OPT 2    TEXT
$\backslash trightarrow \{...\} \{...\}$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash trightharpoondown \{...\} \{...\}$ 1    TEXT                    OPT            OPT 2    TEXT

$\backslash trightharpoonup \{...\} \{...\}$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash trightleftharpoons \{...\} \{...\}$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash trightoverleftarrow \{...\} \{...\}$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash ttriplerel \{...\} \{...\}$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash twoheadleftarrow \{...\} \{...\}$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash twoheadrightarrow \{...\} \{...\}$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash xequal \{...\} \{...\}$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash xhookleftarrow \{...\} \{...\}$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash xhookrightarrow \{...\} \{...\}$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash xLeftarrow \{...\} \{...\}$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash xLeftrightarrow \{...\} \{...\}$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash xleftarrow \{...\} \{...\}$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash xleftharpoondown \{...\} \{...\}$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash xleftharpoonup \{...\} \{...\}$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash xleftrightharpoonup \{...\} \{...\}$ 1    TEXT                    OPT            OPT 2    TEXT

$$\xleftrightarrow{\dots} \dots$$

1	TEXT	OPT	OPT
---	------	-----	-----

2 TEXT

$$\backslash xmapsto \{...\} \{...\}$$

1	TEXT	OPT	OPT
---	------	-----	-----

```

1  TEXT
2  TEXT

```

 $\xrightarrow{\{...\} \{...\}}$ 

1	TEXT	OPT	OPT
---	------	-----	-----

```

1  TEXT
2  TEXT

```

$$\backslash xrel \{.^1..\} \{.^2..\}$$

1 TEXT OPT OPT

2 TEXT

 $\xrightarrow{\{...\} \{...\}}$ 

1	TEXT	OPT	OPT
---	------	-----	-----

2 TEXT

$$\xrightarrow{\text{right}} \{...\} \{...\}$$

	C	I			OPT	OPT
1	TEXT					

2 TEXT

$$\xrightarrow{\quad} \{...\} \{...\}$$

1	TEXT	OPT	OPT
---	------	-----	-----

```
1  TEXT
2  TEXT
```

 $\xrightarrow{\text{left}} \{...\} \{...\}$ 

	TEXT	OPT	OPT
--	------	-----	-----

1 TEXT  
2 TEXT

 $\xrightarrow{\scriptscriptstyle 1} \scriptscriptstyle 2$ 

1	TEXT	OPT	OPT
---	------	-----	-----

2 TEXT

$$\backslash xtriplerel \{...\} \{...\}$$

1	TEXT	OPT	OPT
---	------	-----	-----

```
1 TEXT
2 TEXT
```

$$\xrightarrow{\text{twoheadleftarrow}} \{...\} \{...\}$$

1	TEXT	OPT	OPT
---	------	-----	-----

```
1 TEXT
2 TEXT
```

$$\xrightarrow{\text{twohead}} \{...\}^1 \{...\}^2$$

1	TEXT	OPT	OPT
---	------	-----	-----

```

1  TEXT
2  TEXT

```

 $\mathfrak{m}$ 
$$\backslash\mathrm{MATHFRAMED}\ [\dots\overset{1}{=}\dots,\dots]\ \{\dots\overset{2}{.}\}$$

```
1 inherits: \setupmathframedOPT
```

2 CONTENT

```
instances: mframed inmframed mcfamed
```

$$\backslash inmframed [\dots\overset{1}{=}\dots] \{\overset{2}{\dots}\}$$

```
1 inherits: \setupmathframedOPT
```

2 CONTENT



$\backslash mcfboxed$ [ $\dots$ .. $\overset{1}{=}\dots$ .. $\dots$ ] $\{\dots\}$ 1 inherits: $\backslash setupmcfboxed$ 2 CONTENT
$\backslash mboxed$ [ $\dots$ .. $\overset{1}{=}\dots$ .. $\dots$ ] $\{\dots\}$ 1 inherits: $\backslash setupmboxed$ 2 CONTENT
$\backslash mathfunction$ $\{\dots\}$ * CONTENT
$\backslash mathit$
$\backslash mathitalic$
$\backslash mathop$ $\{\dots\}$ * CONTENT
$\backslash MATHORNAMENT$ $\{\dots\}$ * CONTENT
$\backslash mathover$ [ $\overset{1}{\dots}$ ] $\{\overset{2}{\dots}\}$ $\{\overset{3}{\dots}\}$ 1 sus vfenced <sup>OPT</sup> 2 NUMMER 3 TEXT
$\backslash MATHOVEREXTENSIBLE$ $\{\dots\}$ * TEXT
$\backslash MATHOVERTEXTTEXTENSIBLE$ $\{\overset{1}{\dots}\}$ $\{\overset{2}{\dots}\}$ 1 TEXT 2 TEXT instances:
$\backslash MATHRADICAL$ [ $\overset{1}{\dots}$ ] $\{\overset{2}{\dots}\}$ 1 TEXT <sup>OPT</sup> 2 CONTENT
$\backslash mathrm$
$\backslash mathscript$
$\backslash mathsl$
$\backslash mathss$
$\backslash mathtext$ .. $\overset{1}{\dots}$ $\{\overset{2}{\dots}\}$ 1 TEXT <sup>OPT</sup> 2 TEXT
$\backslash mathtextbf$ .. $\overset{1}{\dots}$ $\{\overset{2}{\dots}\}$ 1 TEXT <sup>OPT</sup> 2 TEXT
$\backslash mathtextbi$ .. $\overset{1}{\dots}$ $\{\overset{2}{\dots}\}$ 1 TEXT <sup>OPT</sup> 2 TEXT

$\backslash\mathtextbs$ $\dots$ $\{^1\!\dots\}$ 1    TEXT            OPT 2    TEXT
$\backslash\mathtextit$ $\dots$ $\{^1\!\dots\}$ 1    TEXT            OPT 2    TEXT
$\backslash\mathtextsl$ $\dots$ $\{^1\!\dots\}$ 1    TEXT            OPT 2    TEXT
$\backslash\mathtexttf$ $\dots$ $\{^1\!\dots\}$ 1    TEXT            OPT 2    TEXT
$\backslash\mathttf$
$\backslash\mathtripler$ $[^1\!\dots]$ $\{^2\!\dots\}$ $\{^3\!\dots\}$ $\{^4\!\dots\}$ 1    NAME            OPT            OPT            OPT            OPT 2    TEXT 3    TEXT 4    TEXT
$\backslash\mathtripler$ $[^1\!\dots]$ $\{^2\!\dots\}$ $\{^3\!\dots\}$ $\{^4\!\dots\}$ 1    NAME            OPT            OPT            OPT            OPT 2    TEXT 3    TEXT 4    TEXT
$\backslash\mathtt$
$\backslash\mathunder$ $[^1\!\dots]$ $\{^2\!\dots\}$ $\{^3\!\dots\}$ 1    subsol    vfence $\mathbb{F}$ 2    NUMMER 3    TEXT
$\backslash\mathunderextensible$ $\{^*\!\dots\}$ *    TEXT
$\backslash\mathunderextextensible$ $\{^1\!\dots\}$ $\{^2\!\dots\}$ 1    TEXT 2    TEXT instances:
$\backslash\mathunstacked$
$\backslash\mathupright$
$\backslash\mathword$ $\dots$ $\{^1\!\dots\}$ 1    TEXT            OPT 2    TEXT
$\backslash\mathwordbf$ $\dots$ $\{^1\!\dots\}$ 1    TEXT            OPT 2    TEXT
$\backslash\mathwordbi$ $\dots$ $\{^1\!\dots\}$ 1    TEXT            OPT 2    TEXT

$\backslash\mathrm{mathwordbs} \mathrel{\mathop{\cdot}}^1 \dots \{\mathrel{\mathop{\cdot}}^2 \dots\}$ 1    TEXT            OPT 2    TEXT
$\backslash\mathrm{mathwordit} \mathrel{\mathop{\cdot}}^1 \dots \{\mathrel{\mathop{\cdot}}^2 \dots\}$ 1    TEXT            OPT 2    TEXT
$\backslash\mathrm{mathwordsl} \mathrel{\mathop{\cdot}}^1 \dots \{\mathrel{\mathop{\cdot}}^2 \dots\}$ 1    TEXT            OPT 2    TEXT
$\backslash\mathrm{mathwordtf} \mathrel{\mathop{\cdot}}^1 \dots \{\mathrel{\mathop{\cdot}}^2 \dots\}$ 1    TEXT            OPT 2    TEXT
$\backslash\mathrm{maxaligned} \{...\}$ *    CONTENT
$\backslash\mathrm{mbox} \{...\}$ *    CONTENT
$\backslash\mathrm{measure} \{...\}$ *    NAME
$\backslash\mathrm{measured} \{...\}$ *    NAME
$\backslash\mathrm{mediu} [...]$ *    FILE
$\backslash\mathrm{mediu} \mathrel{\mathop{\cdot}}^*$ *    FILE
$\backslash\mathrm{medskip}$
$\backslash\mathrm{medspace}$
$\backslash\mathrm{menuinteractiune} [\mathrel{\mathop{\cdot}}^1] [\dots, \mathrel{\mathop{\cdot}}^2 \dots, \dots]$ 1    NAME            OPT 2    inherits: $\backslash\mathrm{seteazameniuinteractiune}$
$\backslash\mathrm{message} \{...\}$ *    TEXT
$\backslash\mathrm{metaTeX}$
$\backslash\mathrm{mfence} \{...\}$ *    CHARACTER
$\backslash\mathrm{mfunction} \{...\}$ *    CONTENT
$\backslash\mathrm{mfunctionlabeltext} \{...\}$ *    NAME
$\backslash\mathrm{mhbox} \{...\}$ *    CONTENT

<code>\mic</code>
<code>\micaldin</code>
<code>\micaldininclinat</code>
<code>\micinclinat</code>
<code>\micinclinataldin</code>
<code>\micitalicaldin</code>
<code>\micnormal</code>
<code>\mictype</code>
<code>\middlealigned {...}</code> *   CONTENT
<code>\middlebox {...}</code> *   CONTENT
<code>\midhbox {...}</code> *   CONTENT
<code>\midsubsentence</code>
<code>\minimalhbox <sup>1</sup>... <sup>2</sup>{...}</code> 1   TEXT           OPT 2   CONTENT
<code>\mixedcaps {...}</code> *   TEXT
<code>\mkvibuffer [...]</code> *   BUFFER           OPT
<code>\moduleparameter <sup>1</sup>{...} <sup>2</sup>{...}</code> 1   FILE 2   KEY
<code>\molecule {...}</code> *   CONTENT
<code>\mono</code>
<code>\monoaldin</code>
<code>\mononormal</code>
<code>\monthlong {...}</code> *   NUMMER
<code>\monthshort {...}</code> *   NUMMER

<code>\mprandomnumber</code>
<code>\mtext {...}</code> *   CONTENT
<code>\NormalizeFontHeight \<sup>1</sup>... {<sup>2</sup>...} {<sup>3</sup>...} {<sup>4</sup>...}</code> 1   CSNAME 2   TEXT 3   DIMENSION 4   FONT
<code>\NormalizeFontWidth \<sup>1</sup>... {<sup>2</sup>...} {<sup>3</sup>...} {<sup>4</sup>...}</code> 1   CSNAME 2   TEXT 3   DIMENSION 4   FONT
<code>\NormalizeTextHeight {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...}</code> 1   FONT 2   DIMENSION 3   TEXT
<code>\NormalizeTextWidth {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...}</code> 1   FONT 2   DIMENSION 3   TEXT
<code>\Numere {...}</code> *   NUMMER
<code>\Numereromane {...}</code> *   NUMMER
<code>\namedheadnumber {...}</code> *   ABSCHNITT
<code>\namedstructureheadlocation {...}</code> *   ABSCHNITT
<code>\namedstructureuservariable {<sup>1</sup>...} {<sup>2</sup>...}</code> 1   ABSCHNITT 2   KEY
<code>\namedstructurevariable {<sup>1</sup>...} {<sup>2</sup>...}</code> 1   ABSCHNITT 2   KEY
<code>\namedtaggedlabeltexts {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...} {<sup>4</sup>...} {<sup>5</sup>...}</code> 1   NAME 2   NAME 3   NAME 4   NAME 5   CONTENT
<code>\naturalhbox <sup>1</sup>... {<sup>2</sup>...}</code> 1   TEXT           OPT 2   CONTENT
<code>\naturalhpack <sup>1</sup>... {<sup>2</sup>...}</code> 1   TEXT           OPT 2   CONTENT

$\backslash\text{naturalvbox}$ $\overset{1}{\dots}$ $\{\overset{2}{\dots}\}$ 1 TEXT OPT 2 CONTENT
$\backslash\text{naturalvcenter}$ $\overset{1}{\dots}$ $\{\overset{2}{\dots}\}$ 1 TEXT OPT 2 CONTENT
$\backslash\text{naturalvpack}$ $\overset{1}{\dots}$ $\{\overset{2}{\dots}\}$ 1 TEXT OPT 2 CONTENT
$\backslash\text{naturalvtop}$ $\overset{1}{\dots}$ $\{\overset{2}{\dots}\}$ 1 TEXT OPT 2 CONTENT
$\backslash\text{naturalwd}$ $\dots$ * CSNAME NUMBER
$\backslash\text{necunosc}$
$\backslash\text{negatecolorbox}$ $\dots$ * CSNAME NUMBER
$\backslash\text{negated}$ $\{\dots\}$ * TEXT
$\backslash\text{negthinspace}$
$\backslash\text{newattribute}$ $\backslash\dots$ * CSNAME
$\backslash\text{newcatcodetable}$ $\backslash\dots$ * CSNAME
$\backslash\text{newcounter}$ $\backslash\dots$ * CSNAME
$\backslash\text{newevery}$ $\overset{1}{\backslash\dots}$ $\overset{2}{\backslash\dots}$ 1 CSNAME 2 CSNAME
$\backslash\text{newfrenchspacing}$
$\backslash\text{newmode}$ $\{\dots\}$ * NAME
$\backslash\text{newsignal}$ $\backslash\dots$ * CSNAME
$\backslash\text{newsystemmode}$ $\{\dots\}$ * NAME
$\backslash\text{nextbox}$
$\backslash\text{nextboxdp}$

<code>\nextboxht</code>
<code>\nextboxhtdp</code>
<code>\nextboxwd</code>
<code>\nextcounter [...]</code> <sup>1</sup> <code>[...]</code> <sup>2</sup> 1 NAME OPT 2 NUMMER
<code>\nextcountervalue [...]</code> * NAME
<code>\nextdepth</code>
<code>\nextparagraphs</code>
<code>\urmatoru1PARAGRAPHS</code>
<code>\nextrealpage</code>
<code>\nextrealpagenumber</code>
<code>\nextsubcountervalue [...]</code> <sup>1</sup> <code>[...]</code> <sup>2</sup> 1 NAME 2 NUMMER
<code>\nextsubpagenumber</code>
<code>\nextuserpage</code>
<code>\nextuserpagenumber</code>
<code>\nocitation [...]</code> * REFERENCE
<code>\nocitation {...}</code> * REFERENCE
<code>\nocite [...]</code> * REFERENCE
<code>\nocite {...}</code> * REFERENCE
<code>\nodetostring \... {...}</code> 1 CSNAME 2 CONTENT
<code>\nofigurepages</code>
<code>\noflines</code>
<code>\noflocalfloats</code>

<code>\noheightstrut</code>
<code>\noindentation</code>
<code>\noitem</code>
<code>\nokap {...}</code> *    TEXT
<code>\nonfrenchspacing</code>
<code>\nonmathematics {...}</code> *    CONTENT
<code>\normal</code>
<code>\normalboldface</code>
<code>\normalframedwithsettings [...,\overset{1}{...},...] {\overset{2}{...}}</code> 1    inherits: \seteazainconjurat 2    CONTENT
<code>\normalitalicface</code>
<code>\normalizebodyfontsize \overset{1}{...} {\overset{2}{...}}</code> 1    CSNAME 2    DIMENSION
<code>\normalizedfontsize</code>
<code>\normalizefontdepth \overset{1}{...} {\overset{2}{...}} {\overset{3}{...}} {\overset{4}{...}}</code> 1    CSNAME 2    TEXT 3    DIMENSION 4    FONT
<code>\normalizefontheight \overset{1}{...} {\overset{2}{...}} {\overset{3}{...}} {\overset{4}{...}}</code> 1    CSNAME 2    TEXT 3    DIMENSION 4    FONT
<code>\normalizefontline \overset{1}{...} {\overset{2}{...}} {\overset{3}{...}} {\overset{4}{...}}</code> 1    CSNAME 2    TEXT 3    DIMENSION 4    FONT
<code>\normalizefontwidth \overset{1}{...} {\overset{2}{...}} {\overset{3}{...}} {\overset{4}{...}}</code> 1    CSNAME 2    TEXT 3    DIMENSION 4    FONT
<code>\normalizetextdepth {\overset{1}{...}} {\overset{2}{...}} {\overset{3}{...}}</code> 1    FONT 2    DIMENSION 3    TEXT



<code>\normalizetextheight {...} {...} {...}</code> 1 FONT 2 DIMENSION 3 TEXT
<code>\normalizetextline {...} {...} {...}</code> 1 FONT 2 DIMENSION 3 TEXT
<code>\normalizetextwidth {...} {...} {...}</code> 1 FONT 2 DIMENSION 3 TEXT
<code>\normalslantedface</code>
<code>\normaltypeface</code>
<code>\nota [...]<sup>1</sup> [...]<sup>2</sup></code> 1 NAME OPT 2 REFERENCE
<code>\NOTE [...]<sup>1</sup>,...<sup>2</sup></code> 1 REFERENCE <sup>PT</sup> 2 TEXT instances: footnote endnote
<code>\NOTE [...]<sup>*</sup>,...<sup>*</sup></code> * titlu = TEXT semncarte = TEXT lista = TEXT referinta = REFERENCE instances: footnote endnote
<code>\endnote [...]<sup>*</sup>,...<sup>*</sup></code> * titlu = TEXT semncarte = TEXT lista = TEXT referinta = REFERENCE
<code>\footnote [...]<sup>*</sup>,...<sup>*</sup></code> * titlu = TEXT semncarte = TEXT lista = TEXT referinta = REFERENCE
<code>\endnote [...]<sup>1</sup>,...<sup>2</sup></code> 1 REFERENCE OPT 2 TEXT
<code>\footnote [...]<sup>1</sup>,...<sup>2</sup></code> 1 REFERENCE OPT 2 TEXT
<code>\notesymbol [...]<sup>1</sup> [...]<sup>2</sup></code> 1 NAME OPT 2 REFERENCE
<code>\notragged</code>

<code>\ntimes {...} {...}</code> 1 TEXT 2 NUMMER
<code>\numarformula [...,*,...]</code> * REFERENCE OPT
<code>\numarpagina</code>
<code>\numartitlu [...] [...]</code> 1 ABSCHNITT OPT 2 precedent curent urmatorul primul ultim
<code>\numartitlucurent</code>
<code>\numberofpoints {...}</code> * DIMENSION
<code>\numere {...}</code> * NUMMER
<code>\numereromane {...}</code> * NUMMER
<code>\obeydepth</code>
<code>\objectdepth</code>
<code>\objectheight</code>
<code>\objectmargin</code>
<code>\objectwidth</code>
<code>\obox {...}</code> * CONTENT
<code>\offset [...,...<sup>1</sup>...,...] {...}</code> 1 inherits: \setupoffset OPT 2 CONTENT
<code>\offsetbox [...,...<sup>1</sup>...,...] \^2... {...}</code> 1 inherits: \setupoffsetbox OPT 2 CSNAME 3 CONTENT
<code>\olinie [...]</code> * REFERENCE
<code>\onedigitrounding {...}</code> * NUMMER
<code>\ordinaldaynumber {...}</code> * NUMMER
<code>\ordinalstr {...}</code> * TEXT

$\backslash\text{ornamenttext}$ [ $\dots$ , $\dots$ , $\overset{1}{=}\dots$ , $\dots$ ] [ $\dots$ , $\dots$ , $\overset{2}{=}\dots$ , $\dots$ ] $\{\dots\}$ $\{\dots\}$ 1    alternativ = a b inherits: \setupcollector 2    stil       = STYLE BEFEHL culoare = COLOR inherits: \seteazainconjurat 3    TEXT 4    CONTENT
$\backslash\text{ornamenttext}$ [ $\overset{1}{.}\dots$ ] $\{\overset{2}{.}\dots\}$ $\{\overset{3}{.}\dots\}$ 1    NAME 2    TEXT 3    CONTENT
$\backslash\text{ornamenttext}$ [ $\dots$ , $\dots$ , $\overset{1}{=}\dots$ , $\dots$ ] [ $\dots$ , $\dots$ , $\overset{2}{=}\dots$ , $\dots$ ] $\{\dots\}$ $\{\dots\}$ 1    alternativ = a b inherits: \setupplayer 2    inherits: \setuplayeredtext 3    TEXT 4    CONTENT
$\backslash\text{ORNAMENT}$ $\{\overset{1}{.}\dots\}$ $\{\overset{2}{.}\dots\}$ 1    TEXT 2    CONTENT
$\backslash\text{outputfilename}$
$\backslash\text{outputstreambox}$ [ $\dots$ ] *    NAME
$\backslash\text{outputstreamcopy}$ [ $\dots$ ] *    NAME
$\backslash\text{outputstreamunvbox}$ [ $\dots$ ] *    NAME
$\backslash\text{outputstreamunvcopy}$ [ $\dots$ ] *    NAME
$\backslash\text{over}$ [ $\dots$ ] *    REFERENCE
$\backslash\text{overlaybutton}$ [ $\dots$ ] *    REFERENCE
$\backslash\text{overlaybutton}$ $\{\dots\}$ *    REFERENCE
$\backslash\text{overlaycolor}$
$\backslash\text{overlaydepth}$
$\backslash\text{overlayfigure}$ $\{\dots\}$ *    FILE
$\backslash\text{overlayheight}$
$\backslash\text{overlaylinecolor}$
$\backslash\text{overlaylinewidth}$

<code>\overlayoffset</code>
<code>\overlayrollbutton [...]<sup>1</sup> [...]<sup>2</sup></code> 1 REFERENCE 2 REFERENCE
<code>\overlaywidth</code>
<code>\overloaderror</code>
<code>\overset {...}<sup>1</sup> {...}<sup>2</sup></code> 1 TEXT 2 TEXT
<code>\PDFcolor {...}</code> * NAME
<code>\PDFETEX</code>
<code>\PDFTEX</code>
<code>\PICTEX</code>
<code>\PiCTeX</code>
<code>\PointsToBigPoints {...}<sup>1</sup> \...<sup>2</sup></code> 1 DIMENSION 2 CSNAME
<code>\PointsToReal {...}<sup>1</sup> \...<sup>2</sup></code> 1 DIMENSION 2 CSNAME
<code>\PointsToWholeBigPoints {...}<sup>1</sup> \...<sup>2</sup></code> 1 DIMENSION 2 CSNAME
<code>\PPCHTEX</code>
<code>\PPCHTeX</code>
<code>\PRAGMA</code>
<code>\PtToCm {...}</code> * DIMENSION
<code>\pagearea [...]<sup>1</sup> [...]<sup>2</sup> [...]<sup>3</sup></code> 1 sus antet text subso <sup>OPT</sup> I subso <sup>OPT</sup> I 2 text margine bordura 3 stanga dreapta lefttext middletext righttext
<code>\pagebreak [...]<sup>*</sup> [...]</code> * gol antet subso <sup>OPT</sup> I dummy incadrat NUMMER +NUMMER implicit reset dezactivat da nu marcaj blank preferinta preferintamare stanga dreapta par impar cvadрупul ultim ultimapagina start stop NAME
<code>\pagefigure [...]<sup>1</sup> [...]<sup>2</sup> [...]<sup>2</sup> [...]</code> 1 FILE OPT 2 offset = implicit overlay niciunul DIMENSION

<p><code>\pagegridspanwidth {...}</code></p> <p>*   NUMBER</p>
<p><code>\pageinjection [...] [...] [...] [...]</code></p> <p>1   NAME           OPT           OPT</p> <p>2   KEY = VALUE</p>
<p><code>\pageinjection [...] [...] [...] [...] [...]</code></p> <p>1   inherits: \setuppageinjection   OPT</p> <p>2   KEY = VALUE</p>
<p><code>\pagestaterealpage {...} {...}</code></p> <p>1   NAME</p> <p>2   NAME NUMBER</p>
<p><code>\pagina [...]*,...]</code></p> <p>*   inherits: \pagebreak</p>
<p><code>\paletsize</code></p>
<p><code>\PARAGRAPHS</code></p>
<p><code>\pastreazablocuri [...] [...] [...] [...]</code></p> <p>1   NAME                   OPT</p> <p>2   NAME</p>
<p><code>\pdfactualtext {...} {...}</code></p> <p>1   CONTENT</p> <p>2   TEXT</p>
<p><code>\pdfbackendactualtext {...} {...}</code></p> <p>1   CONTENT</p> <p>2   TEXT</p>
<p><code>\pdfbackendcurrentresources</code></p>
<p><code>\pdfbackendsetcatalog {...} {...}</code></p> <p>1   NAME</p> <p>2   TEXT</p>
<p><code>\pdfbackendsetcolorspace {...} {...}</code></p> <p>1   NAME</p> <p>2   TEXT</p>
<p><code>\pdfbackendsettextgstate {...} {...}</code></p> <p>1   NAME</p> <p>2   TEXT</p>
<p><code>\pdfbackendsetinfo {...} {...}</code></p> <p>1   NAME</p> <p>2   TEXT</p>
<p><code>\pdfbackendsetname {...} {...}</code></p> <p>1   NAME</p> <p>2   TEXT</p>
<p><code>\pdfbackendsetpageattribute {...} {...}</code></p> <p>1   NAME</p> <p>2   TEXT</p>

<code>\pdfbackendsetpageresource {...} {...}</code> 1 NAME 2 TEXT
<code>\pdfbackendsetpagesattribute {...} {...}</code> 1 NAME 2 TEXT
<code>\pdfbackendsetpattern {...} {...}</code> 1 NAME 2 TEXT
<code>\pdfbackendsetshade {...} {...}</code> 1 NAME 2 TEXT
<code>\pdfcolor {...}</code> * NAME
<code>\pdfeTeX</code>
<code>\pdfTeX</code>
<code>\pelung {...}</code> * NAME
<code>\percent</code>
<code>\percentdimen {...} {...}</code> 1 DIMENSION CSNAME 2 DIMENSION NUMBER
<code>\permitcaretescape</code>
<code>\permitcircumflexescape</code>
<code>\permitspacesbetweengroups</code>
<code>\persiandecimals {...}</code> * NUMMER
<code>\persiannumerals {...}</code> * NUMMER
<code>\phantom {...}</code> * CONTENT
<code>\phantombox [..., ...<sup>*</sup>..., ...]</code> * latime = DIMENSION inaltme = DIMENSION inaltime = DIMENSION
<code>\pickupgroupedcommand {...} {...} {...}</code> 1 BEFEHL 2 BEFEHL 3 BEFEHL
<code>\placeattachments</code>

<p><b>\placebtxrendering</b> [<sup>1</sup>...] [<sup>2</sup>...<sub>OPT</sub>...]</p> <p>1 NAME OPT OPT</p> <p>2 inherits: \setupbtxrendering</p>
<p><b>\placecitation</b> [...]</p> <p>* REFERENCE</p>
<p><b>\placecomments</b></p>
<p><b>\placecurrentformulanumber</b></p>
<p><b>\placedbox</b> {...}</p> <p>* CONTENT</p>
<p><b>\placefloat</b> [<sup>1</sup>...] [<sup>2</sup>...<sub>OPT</sub>...] [<sup>3</sup>...<sub>OPT</sub>...] {...<sup>4</sup>} {...<sup>5</sup>}</p> <p>1 SINGULAR OPT OPT</p> <p>2 split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva effective antet subsol</p> <p>3 REFERENCE</p> <p>4 TEXT</p> <p>5 CONTENT</p>
<p><b>\placefloatwithsetups</b> [<sup>1</sup>...] [<sup>2</sup>...<sub>OPT</sub>...] [<sup>3</sup>...<sub>OPT</sub>...] {...<sup>4</sup>} {...<sup>5</sup>}</p> <p>1 NAME OPT OPT</p> <p>2 split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva effective antet subsol</p> <p>3 REFERENCE</p> <p>4 TEXT</p> <p>5 CONTENT</p>
<p><b>\puneFLOAT</b> [<sup>1</sup>...<sub>OPT</sub>...] [<sup>2</sup>...<sub>OPT</sub>...] {...<sup>3</sup>} {...<sup>4</sup>}</p> <p>1 split totdeauna <sup>OPT</sup>stanga dreapta <sup>OPT</sup>intern extern spatiuspate cutspace instanga indreapta inmargin marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva effective antet subsol</p> <p>2 REFERENCE</p> <p>3 TEXT</p> <p>4 CONTENT</p> <p>instances: chemical figure table intermezzo graphic</p>
<p><b>\punechemical</b> [<sup>1</sup>...<sub>OPT</sub>...] [<sup>2</sup>...<sub>OPT</sub>...] {...<sup>3</sup>} {...<sup>4</sup>}</p> <p>1 split totdeauna <sup>OPT</sup>stanga dreapta <sup>OPT</sup>intern extern spatiuspate cutspace instanga indreapta inmargin marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva effective antet subsol</p> <p>2 REFERENCE</p> <p>3 TEXT</p> <p>4 CONTENT</p>
<p><b>\punefigure</b> [<sup>1</sup>...<sub>OPT</sub>...] [<sup>2</sup>...<sub>OPT</sub>...] {...<sup>3</sup>} {...<sup>4</sup>}</p> <p>1 split totdeauna <sup>OPT</sup>stanga dreapta <sup>OPT</sup>intern extern spatiuspate cutspace instanga indreapta inmargin marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva effective antet subsol</p> <p>2 REFERENCE</p> <p>3 TEXT</p> <p>4 CONTENT</p>

**\punegraphic** [...<sup>1</sup>,...] [...<sup>2</sup>,...] {...<sup>3</sup>} {...<sup>4</sup>}

- 1 split totdeauna <sup>OPT</sup>stanga dreapta <sup>OPT</sup>intern extern spatiuspate cutspace instanga indreapta inmargin marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva effective antet subsol
- 2 REFERENCE
- 3 TEXT
- 4 CONTENT

**\puneintermezzo** [...<sup>1</sup>,...] [...<sup>2</sup>,...] {...<sup>3</sup>} {...<sup>4</sup>}

- 1 split totdeauna <sup>OPT</sup>stanga dreapta <sup>OPT</sup>intern extern spatiuspate cutspace instanga indreapta inmargin marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva effective antet subsol
- 2 REFERENCE
- 3 TEXT
- 4 CONTENT

**\punetable** [...<sup>1</sup>,...] [...<sup>2</sup>,...] {...<sup>3</sup>} {...<sup>4</sup>}

- 1 split totdeauna <sup>OPT</sup>stanga dreapta <sup>OPT</sup>intern extern spatiuspate cutspace instanga indreapta inmargin marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva effective antet subsol
- 2 REFERENCE
- 3 TEXT
- 4 CONTENT

**\placeframed** [...<sup>1</sup>] [...<sup>2</sup>,...<sup>2</sup>,...] {...<sup>3</sup>}

- 1 NAME <sup>OPT</sup>
- 2 inherits: \seteazainconjurat
- 3 CONTENT

**\placeheadnumber** [...\*]

- \* ABSCHNITT

**\placeheadtext** [...\*]

- \* ABSCHNITT

**\placehelp**

**\placeinitial** [...\*]

- \* NAME <sup>OPT</sup>

**\placelayer** [...\*]

- \* NAME

**\placelayeredtext** [...<sup>1</sup>] [...<sup>2</sup>,...<sup>2</sup>,...] [...<sup>3</sup>,...<sup>3</sup>,...] {...<sup>4</sup>} {...<sup>5</sup>}

- 1 NAME <sup>OPT</sup>
- 2 inherits: \setuplayer
- 3 inherits: \setuplayeredtext
- 4 TEXT
- 5 CONTENT

**\placelistofFLOATS** [...<sup>\*</sup>,...<sup>\*</sup>,...]

- \* inherits: \seteazalista <sup>OPT</sup>
- instances: chemicals figures tables intermezzi graphics

**\placelistofchemicals** [...<sup>\*</sup>,...<sup>\*</sup>,...]

- \* inherits: \seteazalista <sup>OPT</sup>

**\placelistoffigures** [...<sup>\*</sup>,...<sup>\*</sup>,...]

- \* inherits: \seteazalista <sup>OPT</sup>



$\backslash\mathrm{placelistofgraphics}$ [ $\dots^*\dots$ ] * inherits: \seteazalista <small>OPT</small>
$\backslash\mathrm{placelistofintermezzi}$ [ $\dots^*\dots$ ] * inherits: \seteazalista <small>OPT</small>
$\backslash\mathrm{placelistoftables}$ [ $\dots^*\dots$ ] * inherits: \seteazalista <small>OPT</small>
$\backslash\mathrm{placelistofpublications}$ [ $\dots^1$ ] [ $\dots^2\dots$ ] 1 NAME <small>OPT</small> <small>OPT</small> 2 inherits: \setupbt rendering
$\backslash\mathrm{placelistofsorts}$ [ $\dots^1$ ] [ $\dots^2\dots$ ] 1 SINGULAR <small>OPT</small> 2 inherits: \seteazasortare
$\backslash\mathrm{placelistofSORTS}$ [ $\dots^*\dots$ ] * inherits: \seteazasortare <small>OPT</small> instances: logos
$\backslash\mathrm{placelistoflogos}$ [ $\dots^*\dots$ ] * inherits: \seteazasortare <small>OPT</small>
$\backslash\mathrm{placelistofsynonyms}$ [ $\dots^1$ ] [ $\dots^2\dots$ ] 1 SINGULAR <small>OPT</small> 2 inherits: \seteazasinonime
$\backslash\mathrm{placelistofSYNONYMS}$ [ $\dots^*\dots$ ] * inherits: \seteazasinonime <small>OPT</small> instances: abbreviations
$\backslash\mathrm{placelistofabbreviations}$ [ $\dots^*\dots$ ] * inherits: \seteazasinonime <small>OPT</small>
$\backslash\mathrm{placelocalnotes}$ [ $\dots^1$ ] [ $\dots^2\dots$ ] 1 NAME <small>OPT</small> 2 inherits: \setupnote
$\backslash\mathrm{placement}$ [ $\dots^1$ ] [ $\dots^2\dots$ ] $\{\dots^3\}$ 1 NAME <small>OPT</small> 2 inherits: \setupplacement 3 CONTENT
$\backslash\mathrm{PLACEMENT}$ [ $\dots^1\dots$ ] $\{\dots^2\}$ 1 inherits: \setupplacement <small>OPT</small> 2 CONTENT
$\backslash\mathrm{placenamefloat}$ [ $\dots^1$ ] [ $\dots^2$ ] 1 NAME 2 REFERENCE
$\backslash\mathrm{placenameformula}$ [ $\dots^1\dots$ ] $\{\dots^2\}$ 1 + - REFERENCE <small>OPT</small> 2 TEXT
$\backslash\mathrm{placenotes}$ [ $\dots^1\dots$ ] [ $\dots^2\dots$ ] 1 NAME <small>OPT</small> 2 inherits: \setupnote

$\backslash\text{placepairedbox}$ [ <sup>1</sup> ...] [ <sup>2</sup> ... <sup>2</sup> ... <sup>2</sup> ...] {...} {...} 1 NAME 2 inherits: \setuppairedbox 3 CONTENT 4 TEXT
$\backslash\text{punePAIREDBOX}$ [ <sup>1</sup> ... <sup>1</sup> ... <sup>1</sup> ...] {...} {...} 1 inherits: \setuppairedbox 2 CONTENT 3 TEXT instances: legend
$\backslash\text{punelegend}$ [ <sup>1</sup> ... <sup>1</sup> ... <sup>1</sup> ...] {...} {...} 1 inherits: \setuppairedbox 2 CONTENT 3 TEXT
$\backslash\text{placeparallel}$ [ <sup>1</sup> ...] [ <sup>2</sup> ... <sup>2</sup> ...] [ <sup>3</sup> ... <sup>3</sup> ... <sup>3</sup> ...] 1 NAME 2 NAME 3 inherits: \setupparallel
$\backslash\text{placerawlist}$ [ <sup>1</sup> ...] [ <sup>2</sup> ... <sup>2</sup> ... <sup>2</sup> ...] 1 LISTE 2 inherits: \seteazalista
$\backslash\text{placereadingwindow}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...] 1 NAME 2 NAME
$\backslash\text{plaseazapegrid}$ [ <sup>1</sup> ...] {...} 1 normal standard da strict tolerant sus subsol ambele broad ajustat primul ultim inalt unu jos niciunul linie strut box min max centru math math:linie math:jumatatelinie math:-line math:-halfline NAME 2 CONTENT
$\backslash\text{plaseazapegrid}$ [ <sup>1</sup> ... <sup>1</sup> ... <sup>1</sup> ...] {...} 1 inherits: \definegridding 2 CONTENT
$\backslash\text{plaseazasemnecarte}$ [ <sup>1</sup> ... <sup>1</sup> ... <sup>1</sup> ...] [ <sup>2</sup> ... <sup>2</sup> ... <sup>2</sup> ...] [ <sup>3</sup> ... <sup>3</sup> ... <sup>3</sup> ... <sup>3</sup> ...] 1 ABSCHNITT LISTE 2 ABSCHNITT LISTE 3 inherits: \setupbookmark
$\backslash\text{popattribute}$ \*... * CSNAME
$\backslash\text{popmacro}$ \*... * CSNAME
$\backslash\text{popmode}$ [...] * NAME
$\backslash\text{popsystemmode}$ {...} * NAME
$\backslash\text{positionoverlay}$ {...} * NAME
$\backslash\text{positionregionoverlay}$ {...} {...} 1 NAME 2 NAME

<code>\postponenotes</code>
<code>\potrivestecamp [...]<sup>1</sup> [...]<sup>2</sup>...</code> 1 NAME 2 inherits: \setupfieldbody
<code>\pozitie [...]<sup>1</sup> (...)<sup>2</sup> {...}</code> 1 inherits: \setarepozitie 2 POSITION 3 CONTENT
<code>\predefinedfont [...]</code> * FONT
<code>\predefinefont [...]<sup>1</sup> [...]<sup>2</sup></code> 1 NAME 2 FONT
<code>\predefinesymbol [...]</code> * NAME
<code>\prefixedpagenumber</code>
<code>\prependetoks ... \to \^...</code> 1 BEFEHL 2 CSNAME
<code>\prependgvalue {...}<sup>1</sup> {...}<sup>2</sup></code> 1 NAME 2 BEFEHL
<code>\prependtocommalist {...}<sup>1</sup> \^...</code> 1 TEXT 2 CSNAME
<code>\prependtoks ... \to \^...</code> 1 BEFEHL 2 CSNAME
<code>\prependtoksonce ... \to \^...</code> 1 BEFEHL 2 CSNAME
<code>\prependvalue {...}<sup>1</sup> {...}<sup>2</sup></code> 1 NAME 2 BEFEHL
<code>\presetdocument [...]<sup>*</sup>...</code> * inherits: \setupdocument
<code>\presetfieldsymbols [...]<sup>*</sup>...</code> * NAME
<code>\presetLABELtext [...]<sup>1</sup> [...]<sup>2</sup>...</code> 1 SPRACHE 2 KEY = VALUE instances: head label mathlabel taglabel unit operator prefix suffix btxlabel

<pre> \presetbtxlabeltext [...] [...] 1  SPRACHE 2  KEY  =  VALUE </pre>
<pre> \presetheadtext [...] [...] 1  SPRACHE 2  KEY  =  VALUE </pre>
<pre> \presetlabeltext [...] [...] 1  SPRACHE 2  KEY  =  VALUE </pre>
<pre> \presetmathlabeltext [...] [...] 1  SPRACHE 2  KEY  =  VALUE </pre>
<pre> \presetoperatortext [...] [...] 1  SPRACHE 2  KEY  =  VALUE </pre>
<pre> \presetprefixtext [...] [...] 1  SPRACHE 2  KEY  =  VALUE </pre>
<pre> \presetsuffixtext [...] [...] 1  SPRACHE 2  KEY  =  VALUE </pre>
<pre> \presettaglabeltext [...] [...] 1  SPRACHE 2  KEY  =  VALUE </pre>
<pre> \presetunittext [...] [...] 1  SPRACHE 2  KEY  =  VALUE </pre>
<pre> \pretocommalist {...} \^2. 1  TEXT 2  CSNAME </pre>
<pre> \prettyprintbuffer {...} {...} 1  BUFFER 2  mp lua xml parsed-xml nested tex context niciunul NAME </pre>
<pre> \prevcounter [...] [...] 1  NAME 2  NUMMER </pre>
<pre> \prevcountervalue [...] *  NAME </pre>
<pre> \preventmode [...]*[...] *  NAME </pre>
<pre> \prevrealpage </pre>
<pre> \prevrealpagenumber </pre>

<pre> \prevsubcountervalue [...] [...] 1  NAME 2  NUMMER </pre>
<pre> \prevsubpage </pre>
<pre> \prevsubpagenumber </pre>
<pre> \prevuserpage </pre>
<pre> \prevuserpagenumber </pre>
<pre> \primasubpagina </pre>
<pre> \procent </pre>
<pre> \proceseazabloc [...] [...] [...] 1  NAME 2  NAME 3  criteriu = text ABSCHNITT </pre>
<pre> \processaction [...] [...] 1  BEFEHL 2  APPLY </pre>
<pre> \processallactionsinset [...] [...] 1  BEFEHL 2  APPLY </pre>
<pre> \processassignlist [...] \... 1  TEXT 2  CSNAME </pre>
<pre> \processassignmentcommand [...] \... 1  KEY = VALUE 2  CSNAME </pre>
<pre> \processassignmentlist [...] \... 1  KEY = VALUE 2  CSNAME </pre>
<pre> \processbetween {...} \... 1  NAME 2  CSNAME </pre>
<pre> \processbodyfontenvironmentlist \... *  CSNAME </pre>
<pre> \processcolorcomponents {...} *  COLOR </pre>
<pre> \processcommacommand [...] \... 1  BEFEHL 2  CSNAME </pre>
<pre> \processcommalist [...] \... 1  BEFEHL 2  CSNAME </pre>

<pre> \processcommalistwithparameters [...,<sup>1</sup>...] \<sup>2</sup>... 1  BEFEHL 2  CSNAME </pre>
<pre> \processcontent {...} \<sup>2</sup>... 1  NAME 2  CSNAME </pre>
<pre> \processfile {...} *  FILE </pre>
<pre> \processfilemany {...} *  FILE </pre>
<pre> \processfilenone {...} *  FILE </pre>
<pre> \processfileonce {...} *  FILE </pre>
<pre> \processfirstactioninset [...]<sup>1</sup> [...,<sup>2</sup>...=&gt;...,...] 1  BEFEHL 2  APPLY </pre>
<pre> \processisolatedchars {...} \<sup>2</sup>... 1  TEXT 2  CSNAME </pre>
<pre> \processisolatedwords {...} \<sup>2</sup>... 1  TEXT 2  CSNAME </pre>
<pre> \processlinetablebuffer [...]<sup>1</sup> *  BUFFER OPT </pre>
<pre> \processlinetablefile {...} *  FILE </pre>
<pre> \processlist {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} \<sup>4</sup>... 1  CHARACTER 2  CHARACTER 3  TEXT 4  CSNAME </pre>
<pre> \processMPbuffer [...,<sup>1</sup>...] *  NAME OPT </pre>
<pre> \processMPfigurefile {...} *  FILE </pre>
<pre> \processmonth {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} 1  NUMMER 2  NUMMER 3  BEFEHL </pre>
<pre> \processranges [...,<sup>1</sup>...] \<sup>2</sup>... 1  NUMMER NUMMER:NUMMER 2  CSNAME </pre>

<pre> \processseparatedlist [...]<sup>1</sup> [...]<sup>2</sup> {...}<sup>3</sup> 1 TEXT 2 TEXT 3 CSNAME BEFEHL </pre>
<pre> \processTeXbuffer [...]<sup>*</sup> * BUFFER OPT </pre>
<pre> \processtokens {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup> {...}<sup>4</sup> {...}<sup>5</sup> 1 BEFEHL 2 BEFEHL 3 BEFEHL 4 BEFEHL 5 TEXT </pre>
<pre> \processuntil \... * CSNAME </pre>
<pre> \processxtablebuffer [...]<sup>*</sup> * NAME OPT </pre>
<pre> \processyear {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup> {...}<sup>4</sup> 1 NUMMER 2 BEFEHL 3 BEFEHL 4 BEFEHL </pre>
<pre> \produs [...]<sup>*</sup> * FILE </pre>
<pre> \produs ...<sup>*</sup> * FILE </pre>
<pre> \profiledbox [...]<sup>1</sup> [...,...<sup>2</sup>...,...]<sup>2</sup> {...}<sup>3</sup> 1 niciunul fixat strict halfixed quarterfixed eightsfixed NAME 2 inherits: \setupprofile 3 CONTENT </pre>
<pre> \profilegivenbox {...}<sup>1</sup> ...<sup>2</sup> 1 niciunul fixat strict halfixed quarterfixed eightsfixed NAME 2 CSNAME NUMMER </pre>
<pre> \program [...]<sup>*</sup> * NAME </pre>
<pre> \proiect [...]<sup>*</sup> * FILE </pre>
<pre> \proiect ...<sup>*</sup> * FILE </pre>
<pre> \pseudoMixedCapped {...}<sup>*</sup> * TEXT </pre>
<pre> \pseudoSmallCapped {...}<sup>*</sup> * TEXT </pre>
<pre> \pseudoSmallcapped {...}<sup>*</sup> * TEXT </pre>

<p><b>\pseudosmallcapped {...}</b></p> <p>* TEXT</p>
<p><b>\punct {...}</b></p> <p>* CHARACTER</p>
<p><b>\puncte [...]</b></p> <p>* NUMMER <small>OPT</small></p>
<p><b>\puncte [...,...<sup>*</sup>...,...]</b></p> <p>* inherits: \setupperiods <small>OPT</small></p>
<p><b>\punedeasuprafiecareia {...} {...}</b></p> <p>1 CONTENT</p> <p>2 CONTENT</p>
<p><b>\punefatainfata {...} {...}</b></p> <p>1 CONTENT</p> <p>2 CONTENT</p>
<p><b>\puneformula [...,<sup>*</sup>...]</b></p> <p>* + - REFERENCE <small>OPT</small></p>
<p><b>\punelista [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]</b></p> <p>1 LISTE <small>OPT</small></p> <p>2 inherits: \seteazalista</p>
<p><b>\punelistacombinata [...<sup>1</sup>] [...,<sup>2</sup>...,...]</b></p> <p>1 LISTE <small>OPT</small></p> <p>2 inherits: \seteazalista</p>
<p><b>\puneCOMBINEDLIST [...,<sup>*</sup>...,...]</b></p> <p>* inherits: \seteazalista <small>OPT</small></p> <p>instances: content</p>
<p><b>\punecontent [...,<sup>*</sup>...,...]</b></p> <p>* inherits: \seteazalista <small>OPT</small></p>
<p><b>\punenotesubsol [...,<sup>*</sup>...,...]</b></p> <p>* inherits: \setupnote <small>OPT</small></p>
<p><b>\punenotesubsollocale [...,<sup>*</sup>...,...]</b></p> <p>* inherits: \setupnote <small>OPT</small></p>
<p><b>\punenumarpagina</b></p>
<p><b>\puneregistru [...<sup>1</sup>] [...,<sup>2</sup>...,...]</b></p> <p>1 NAME <small>OPT</small></p> <p>2 inherits: \seteazaregistru</p>
<p><b>\puneREGISTER [...,<sup>*</sup>...,...]</b></p> <p>* inherits: \seteazaregistru <small>OPT</small></p> <p>instances: index</p>
<p><b>\puneindex [...,<sup>*</sup>...,...]</b></p> <p>* inherits: \seteazaregistru <small>OPT</small></p>



<p><code>\punesubformula [...,*...]</code></p> <p>*   + - REFERENCE                      OPT</p>
<p><code>\purenumber {...}</code></p> <p>*      NUMMER</p>
<p><code>\pusharrangedpages ... \poparrangedpages</code></p>
<p><code>\pushattribute \*...</code></p> <p>*      CSNAME</p>
<p><code>\pushbar [...] ... \popbar</code></p> <p>*      NAME</p>
<p><code>\pushbutton [<sup>1</sup>...] [<sup>2</sup>...]</code></p> <p>1      NAME</p> <p>2      REFERENCE</p>
<p><code>\pushcatcodetable ... \popcatcodetable</code></p>
<p><code>\pushculoare [...] ... \popculoare</code></p> <p>*      COLOR</p>
<p><code>\pushendofline ... \popendofline</code></p>
<p><code>\pushfundal [...] ... \popfundal</code></p> <p>*      NAME</p>
<p><code>\pushindentation ... \popindentation</code></p>
<p><code>\pushMPdrawing ... \popMPdrawing</code></p>
<p><code>\pushmacro \*...</code></p> <p>*      CSNAME</p>
<p><code>\pushmathstyle ... \popmathstyle</code></p>
<p><code>\pushmode [...]</code></p> <p>*      NAME</p>
<p><code>\pushoutputstream [...]</code></p> <p>*      NAME                              OPT</p>
<p><code>\pushpath [...] ... \poppath</code></p> <p>*      PATH</p>
<p><code>\pushpunctuation ... \poppunctuation</code></p>
<p><code>\pushrandomseed ... \poprandomseed</code></p>
<p><code>\pushreferenceprefix {...} ... \popreferenceprefix</code></p> <p>*      + - TEXT</p>
<p><code>\pushsystemmode {...}</code></p> <p>*      NAME</p>

<p><code>\putboxincache {<sup>1</sup>...} {<sup>2</sup>...} <sup>3</sup>...</code></p> <p>1 NAME 2 NUMMER TEXT 3 CSNAME NUMBER</p>
<p><code>\putnextboxincache {<sup>1</sup>...} {<sup>2</sup>...} \<sup>3</sup>... {<sup>4</sup>...}</code></p> <p>1 NAME 2 NUMMER TEXT 3 CSNAME 4 CONTENT</p>
<p><code>\qqquad</code></p>
<p><code>\quad</code></p>
<p><code>\quads [...]</code></p> <p>* NUMMER <small>OPT</small></p>
<p><code>\quarterstrut</code></p>
<p><code>\quitcommalist</code></p>
<p><code>\quitprevcommalist</code></p>
<p><code>\quittypescriptscanning</code></p>
<p><code>\ReadFile {<sup>1</sup>...}</code></p> <p>* FILE</p>
<p><code>\raggedbottom</code></p>
<p><code>\raggedcenter</code></p>
<p><code>\raggedleft</code></p>
<p><code>\raggedright</code></p>
<p><code>\raggedwidecenter</code></p>
<p><code>\raisebox {<sup>1</sup>...} \<sup>2</sup>... {<sup>3</sup>...}</code></p> <p>1 DIMENSION 2 CSNAME 3 CONTENT</p>
<p><code>\randomizetext {<sup>1</sup>...}</code></p> <p>* TEXT</p>
<p><code>\randomnumber {<sup>1</sup>...} {<sup>2</sup>...}</code></p> <p>1 NUMMER 2 NUMMER</p>
<p><code>\rawcounter [...] [<sup>2</sup>...]</code></p> <p>1 NAME <small>OPT</small> 2 NUMMER</p>
<p><code>\rawcountervalue [...]</code></p> <p>* NAME</p>

<pre> \rawdate [...] * inherits: \datacurenta </pre>
<pre> \rawdoifelseinset {<sup>1</sup>...} {<sup>2</sup>...,...} {<sup>3</sup>...} {<sup>4</sup>...} 1 TEXT 2 TEXT 3 TRUE 4 FALSE </pre>
<pre> \rawdoifinset {<sup>1</sup>...} {<sup>2</sup>...,...} {<sup>3</sup>...} 1 TEXT 2 TEXT 3 TRUE </pre>
<pre> \rawdoifinsetelse {<sup>1</sup>...} {<sup>2</sup>...,...} {<sup>3</sup>...} {<sup>4</sup>...} 1 TEXT 2 TEXT 3 TRUE 4 FALSE </pre>
<pre> \rawgetparameters [<sup>1</sup>...] [<sup>2</sup>...,...<sub>=</sub>...] 1 TEXT 2 KEY = VALUE </pre>
<pre> \rawprocessaction [<sup>1</sup>...] [<sup>2</sup>...,...<sub>&gt;</sub>...] 1 BEFEHL 2 APPLY </pre>
<pre> \rawprocesscommacommand [...,<sup>1</sup>...] \<sup>2</sup>... 1 BEFEHL 2 CSNAME </pre>
<pre> \rawprocesscommalist [...,<sup>1</sup>...] \<sup>2</sup>... 1 BEFEHL 2 CSNAME </pre>
<pre> \rawstructurelistuservariable {*...} * KEY </pre>
<pre> \rawsubcountervalue [<sup>1</sup>...] [<sup>2</sup>...] 1 NAME 2 NUMMER </pre>
<pre> \rbox <sup>1</sup>... {<sup>2</sup>...} 1 TEXT <sup>OPT</sup> 2 CONTENT </pre>
<pre> \readfile {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...} 1 FILE 2 TRUE 3 FALSE </pre>
<pre> \readfixfile {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...} {<sup>4</sup>...} 1 PATH 2 FILE 3 TRUE 4 FALSE </pre>
<pre> \readjobfile {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...} 1 FILE 2 TRUE 3 FALSE </pre>

<code>\readlocfile {...} {...} {...}</code> 1 FILE 2 TRUE 3 FALSE
<code>\readsetfile {...} {...} {...} {...}</code> 1 PATH 2 FILE 3 TRUE 4 FALSE
<code>\readsysfile {...} {...} {...}</code> 1 FILE 2 TRUE 3 FALSE
<code>\readtexfile {...} {...} {...}</code> 1 FILE 2 TRUE 3 FALSE
<code>\readxmlfile {...} {...} {...}</code> 1 FILE 2 TRUE 3 FALSE
<code>\realpagenumber</code>
<code>\realSmallCapped {...}</code> * TEXT
<code>\realSmallcapped {...}</code> * TEXT
<code>\realsmallcapped {...}</code> * TEXT
<code>\recursedepth</code>
<code>\recurselevel</code>
<code>\recursestring</code>
<code>\redoconvertfont</code>
<code>\ref [...]<sup>1</sup> [...]<sup>2</sup></code> 1 implicit text titlu numar pagina realpage 2 REFERENCE
<code>\REFERENCEFORMAT {...}<sup>1</sup> {...}<sup>2</sup> [...]<sup>3</sup></code> 1 TEXT                   OPT       OPT 2 TEXT 3 REFERENCE
<code>\referenceprefix</code>
<code>\referinta [...]<sup>1</sup>, [...] {...}<sup>2</sup></code> 1 REFERENCE 2 TEXT

<pre> \referintapagina [...,*...] *   REFERENCE </pre>
<pre> \referintatext [...<sup>1</sup>,...] {..<sup>2</sup>.} 1   REFERENCE 2   TEXT </pre>
<pre> \referring (...<sup>1</sup>,...) (...<sup>2</sup>,...) [...<sup>3</sup>.] 1   POSITION 2   POSITION 3   REFERENCE </pre>
<pre> \reflexie {...} *   CONTENT </pre>
<pre> \registerattachment [...<sup>1</sup>.] [.....<sup>2</sup>...,...] 1   NAME 2   inherits: \setupattachment </pre>
<pre> \registerctxluafile {...<sup>1</sup>.} {...<sup>2</sup>.} 1   FILE 2   NUMMER </pre>
<pre> \registerexternalfigure [...<sup>1</sup>.] [...<sup>2</sup>.] [.....<sup>3</sup>...,...] 1   FILE          OPT          OPT 2   NAME 3   inherits: \setupexternalfigure </pre>
<pre> \registerfontclass {...} *   NAME </pre>
<pre> \registerhyphenationexception [...<sup>1</sup>.] [...<sup>2</sup>.] 1   SPRACHE          OPT 2   TEXT </pre>
<pre> \registerhyphenationpattern [...<sup>1</sup>.] [...<sup>2</sup>.] 1   SPRACHE          OPT 2   TEXT </pre>
<pre> \registermenubuttons [...<sup>1</sup>.] [...<sup>2</sup>.] 1   NAME 2   TEXT </pre>
<pre> \registersort [...<sup>1</sup>.] [...<sup>2</sup>.] 1   SINGULAR 2   NAME </pre>
<pre> \registersynonym [...<sup>1</sup>.] [...<sup>2</sup>.] 1   SINGULAR 2   NAME </pre>
<pre> \registerunit [...<sup>1</sup>.] [.....<sup>2</sup>...,...] 1   prefix unitate operator suffixe simbol packaged 2   KEY = VALUE </pre>
<pre> \REGISTER [...<sup>1</sup>.] [...+..<sup>2</sup>...+] 1   TEXT PROCESSOR-&gt;TEXT 2   INDEX instances: index </pre>

<code>\index [...]<sup>1</sup> [...+...+...]<sup>2</sup></code> 1 TEXT PROCESSOR->TEXT 2 INDEX
<code>\REGISTER [...]<sup>1</sup> {...}<sup>2</sup> [...+...+...]<sup>3</sup></code> 1 TEXT PROCESSOR->TEXT 2 TEXT 3 INDEX <b>instances:</b> index
<code>\index [...]<sup>1</sup> {...}<sup>2</sup> [...+...+...]<sup>3</sup></code> 1 TEXT PROCESSOR->TEXT 2 TEXT 3 INDEX
<code>\regular</code>
<code>\relatemarking [...]<sup>1</sup> [...]<sup>2</sup></code> 1 BESCHRIFTUNG 2 BESCHRIFTUNG
<code>\relateparameterhandlers {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup> {...}<sup>4</sup></code> 1 NAME 2 NAME 3 NAME 4 NAME
<code>\relaxvalueifundefined {...}</code> * NAME
<code>\remainingcharacters</code>
<code>\remarca (...<sup>1</sup>,...) (...<sup>2</sup>,...) [...<sup>3</sup>,...<sup>3</sup>...]<sup>4</sup> {...}</code> 1 POSITION 2 POSITION 3 inherits: \setezainconjurat 4 TEXT
<code>\removebottomthings</code>
<code>\removedepth</code>
<code>\removefromcommalist {...}<sup>1</sup> \...<sup>2</sup></code> 1 TEXT 2 CSNAME
<code>\removelastskip</code>
<code>\removelastspace</code>
<code>\removemarkedcontent [...]</code> * NAME
<code>\removepunctuation</code>
<code>\removesubstring ...<sup>1</sup> \from ...<sup>2</sup> \to \...<sup>3</sup></code> 1 TEXT 2 TEXT 3 CSNAME

\removetoks <sup>1</sup> ... \from \ <sup>2</sup> ... 1 BEFEHL 2 CSNAME
\removeunwantedspaces
\replacefeature [...] * NAME
\replacefeature {...} * NAME
\replaceincommalist \ <sup>1</sup> ... { <sup>2</sup> ...} 1 CSNAME 2 NUMMER
\replaceword [ <sup>1</sup> ...] [ <sup>2</sup> ...] [ <sup>3</sup> ...] 1 NAME 2 TEXT 3 TEXT
\rescan {...} * CONTENT
\rescanwithsetup { <sup>1</sup> ...} { <sup>2</sup> ...} 1 NAME 2 CONTENT
\resetallattributes
\resetandaddfeature [...] * NAME
\resetandaddfeature {...} * NAME
\resetbar
\resetboxesincache {...} * NAME
\resetbreakpoints
\resetbuffer [...] * BUFFER
\resetcharacteralign
\resetcharacterkerning
\resetcharacterspacing
\resetcharacterstripping
\resetcollector [...] * NAME

\resetcounter [...] [...] 1 NAME OPT 2 NUMMER
\resetdigitsmanipulation
\resetdirection
\reseteazamarcaje [...] * BESCHRIFTUNG
\resetfeature
\resetflag {...} * NAME
\resetfontcolorscheme
\resetfontfallback [...] [...] 1 NAME OPT 2 FONT
\resetfontsolution
\resethyphenationfeatures
\resetinjector [...] * NAME
\resetinteractionmenu [...] * NAME
\resetitaliccorrection
\resetlayer [...] * NAME
\resetlocalfloats
\resetMPdrawing
\resetMPenvironment
\resetMPinstance [...] * NAME
\resetmarker [...] * NAME
\resetmode {...} * NAME
\resetpagenumber





<code>\resolvedglyphdirect {...} {...}</code> 1 FONT 2 e:NAME x:NUMMER d:NUMMER s:NUMMER i:NUMMER n:NAME c:NAME u:NAME a:NAME
<code>\resolvedglyphstyled {...} {...}</code> 1 FONT 2 e:NAME x:NUMMER d:NUMMER s:NUMMER i:NUMMER n:NAME c:NAME u:NAME a:NAME
<code>\restartcounter [...] [...<sup>2</sup>] [...<sup>3</sup>]</code> 1 NAME 2 NUMMER 3 NUMMER
<code>\restorebox {...} {...<sup>2</sup>}</code> 1 NAME 2 NAME
<code>\restorecatcodes</code>
<code>\restorecounter [...]</code> * NAME
<code>\restorecurrentattributes {...}</code> * NAME
<code>\restoreendofline</code>
<code>\restoreglobalbodyfont</code>
<code>\reusableMPgraphic {...} {...<sup>2</sup>...}</code> 1 NAME 2 KEY = VALUE
<code>\reuseMPgraphic {...} {...<sup>2</sup>...}</code> 1 NAME 2 KEY = VALUE
<code>\reuserandomseed</code>
<code>\revivefeature</code>
<code>\rfence {...}</code> * CHARACTER
<code>\rhbox {...}</code> * CONTENT
<code>\rightbottombox {...}</code> * CONTENT
<code>\rightbox {...}</code> * CONTENT
<code>\righthbox {...}</code> * CONTENT

$\backslash rightLABELtext \{...\}$ * KEY instances: head label mathlabel
$\backslash righththeadtext \{...\}$ * KEY
$\backslash rightlabeltext \{...\}$ * KEY
$\backslash rightmathlabeltext \{...\}$ * KEY
$\backslash rightline \{...\}$ * CONTENT
$\backslash rightorleftpageaction \{.^1\} \{.^2\}$ 1 BEFEHL 2 BEFEHL
$\backslash rightskipadaption$
$\backslash rightsubguillemot$
$\backslash righttopleft$
$\backslash righttopleftthbox \{.^1\} \{.^2\}$ 1 TEXT OPT 2 CONTENT
$\backslash righttopleftvbox \{.^1\} \{.^2\}$ 1 TEXT OPT 2 CONTENT
$\backslash righttopleftvtop \{.^1\} \{.^2\}$ 1 TEXT OPT 2 CONTENT
$\backslash righttopbox \{...\}$ * CONTENT
$\backslash riglatext \{.^1\} \{.^2\}$ 1 sus centru sub <sup>OPT</sup> sol OPT 2 TEXT
$\backslash ringleumplere \{...\} \{.^1\} \{.^2\} \{.^3\}$ 1 inherits: \seteazarig <sup>OPT</sup> leumplere OPT OPT 2 TEXT 3 TEXT
$\backslash ring \{...\}$ * CHARACTER
$\backslash rlap \{...\}$ * CONTENT
$\backslash robustaddtocommalist \{.^1\} \backslash.^2$ 1 TEXT 2 CSNAME

<code>\robustdoifelseinset {...} {...,<sup>2</sup>...} {...<sup>3</sup>} {...<sup>4</sup>}</code> 1 TEXT 2 TEXT 3 TRUE 4 FALSE
<code>\robustdoifinsetelse {...} {...,<sup>2</sup>...} {...<sup>3</sup>} {...<sup>4</sup>}</code> 1 TEXT 2 TEXT 3 TRUE 4 FALSE
<code>\robustpretocommalist {...} \<sup>2</sup>...</code> 1 TEXT 2 CSNAME
<code>\rollbutton [...,<sup>1</sup>...<sup>2</sup>,...] ...<sup>3</sup> [...<sup>4</sup>]</code> 1 inherits: \setupbutton 2 TEXT 3 REFERENCE
<code>\rollbutton [...<sup>1</sup>] [...,<sup>2</sup>...<sup>3</sup>,...] ...<sup>4</sup> [...<sup>5</sup>]</code> 1 NAME OPT OPT 2 inherits: \setezameniuinteractiune 3 TEXT 4 REFERENCE
<code>\roman</code>
<code>\roteste [...,<sup>1</sup>...<sup>2</sup>,...] {...}</code> 1 inherits: \setezarotare 2 CONTENT
<code>\rtop ...<sup>1</sup> {...<sup>2</sup>}</code> 1 TEXT OPT 2 CONTENT
<code>\ruledhbox ...<sup>1</sup> {...<sup>2</sup>}</code> 1 TEXT OPT 2 CONTENT
<code>\ruledhpack ...<sup>1</sup> {...<sup>2</sup>}</code> 1 TEXT OPT 2 CONTENT
<code>\ruledmbox {...}</code> * CONTENT
<code>\ruledtopv ...<sup>1</sup> {...<sup>2</sup>}</code> 1 TEXT OPT 2 CONTENT
<code>\ruledtpack ...<sup>1</sup> {...<sup>2</sup>}</code> 1 TEXT OPT 2 CONTENT
<code>\ruledvbox ...<sup>1</sup> {...<sup>2</sup>}</code> 1 TEXT OPT 2 CONTENT
<code>\ruledvpack ...<sup>1</sup> {...<sup>2</sup>}</code> 1 TEXT OPT 2 CONTENT

<pre> \ruledvtop <sup>1</sup>... {<sup>2</sup>...} 1  TEXT          OPT 2  CONTENT </pre>
<pre> \runMPbuffer [...,<sup>*</sup>...] *  NAME          OPT </pre>
<pre> \runninghbox {<sup>*</sup>...} *  CONTENT </pre>
<pre> \ScaledPointsToBigPoints {<sup>1</sup>...} \<sup>2</sup>... 1  DIMENSION 2  CSNAME </pre>
<pre> \ScaledPointsToWholeBigPoints {<sup>1</sup>...} \<sup>2</sup>... 1  DIMENSION 2  CSNAME </pre>
<pre> \Smallcapped {<sup>*</sup>...} *  TEXT </pre>
<pre> \safechar {<sup>*</sup>...} *  NUMMER </pre>
<pre> \samplefile {<sup>*</sup>...} *  FILE </pre>
<pre> \sans </pre>
<pre> \sansaldin </pre>
<pre> \sansnormal </pre>
<pre> \sansserif </pre>
<pre> \savebox {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...} 1  NAME 2  NAME 3  CONTENT </pre>
<pre> \savebtxdataset [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...<sup>3</sup>...,...] 1  NAME          OPT      OPT      OPT 2  FILE 3  dataset      = NAME    type         = bib lua xml    fisier       = FILE    criteriu     = tot text intro referinta curent aici precedent local componenta SECTIONBLOCK:tot SECTIONBLOCK:referinta                   SECTIONBLOCK:curent SECTIONBLOCK:precedent </pre>
<pre> \savebuffer [...,<sup>*</sup>...,...] *  lista      = NAME    fisier     = FILE    prefix     = da nu </pre>
<pre> \savebuffer [...,<sup>1</sup>...] [<sup>2</sup>...] 1  BUFFER 2  FILE </pre>
<pre> \savecounter [...<sup>*</sup>...] *  NAME </pre>

<code>\saveculoare ... \restoreculoare</code>
<code>\savecurrentattributes {...}</code> <code>*    NAME</code>
<code>\savenormalmeaning \...</code> <code>*    CSNAME</code>
<code>\savetaggedtwopassdata {...} {...} {...} {...}</code> <code>1    NAME</code> <code>2    NUMMER</code> <code>3    NAME</code> <code>4    CONTENT</code>
<code>\savetwopassdata {...} {...} {...}</code> <code>1    NAME</code> <code>2    NUMMER</code> <code>3    CONTENT</code>
<code>\sbox {...}</code> <code>*    CONTENT</code>
<code>\scala [...]<sup>1</sup> [...,...<sup>2</sup>...,...]<sup>2</sup> {...}<sup>3</sup></code> <code>1    NAME        OPT                OPT</code> <code>2    inherits: \setupscale</code> <code>3    CONTENT</code>
<code>\scriebuffer [...,...<sup>1</sup>...] [...,...<sup>2</sup>...,...]<sup>2</sup></code> <code>1    BUFFER                OPT                OPT</code> <code>2    inherits: \seteazatyping</code>
<code>\typeBUFFER [...,...<sup>*</sup>...,...]</code> <code>*    inherits: \seteazatyping<sup>OPT</sup></code>
<code>\scrieinlista [...]<sup>1</sup> [...,...<sup>2</sup>...,...]<sup>2</sup> {...}<sup>3</sup> {...}<sup>4</sup></code> <code>1    LISTE                        OPT</code> <code>2    inherits: \seteazalista</code> <code>3    NUMMER</code> <code>4    TEXT</code>
<code>\scrieintreliste [...]<sup>1</sup> [...,...<sup>2</sup>...,...]<sup>2</sup> {...}<sup>3</sup></code> <code>1    LISTE                        OPT</code> <code>2    inherits: \seteazalista</code> <code>3    BEFEHL</code>
<code>\SCRIPT</code> <code>instances: hangul hanzi nihongo ethiopic thai latin test</code>
<code>\ethiopic</code>
<code>\hangul</code>
<code>\hanzi</code>
<code>\latin</code>
<code>\nihongo</code>
<code>\test</code>

<code>\thai</code>
<code>\scrismanual</code>
<code>\secondoffivearguments {.^1.} {.^2.} {.^3.} {.^4.} {.^5.}</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT
<code>\secondoffourarguments {.^1.} {.^2.} {.^3.} {.^4.}</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT
<code>\secondofsixarguments {.^1.} {.^2.} {.^3.} {.^4.} {.^5.} {.^6.}</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT
<code>\secondofthreearguments {.^1.} {.^2.} {.^3.}</code> 1 TEXT 2 TEXT 3 TEXT
<code>\secondofthreeunexpanded {.^1.} {.^2.} {.^3.}</code> 1 TEXT 2 TEXT 3 TEXT
<code>\secondoftwoarguments {.^1.} {.^2.}</code> 1 TEXT 2 TEXT
<code>\secondoftwounexpanded {.^1.} {.^2.}</code> 1 TEXT 2 TEXT
<code>\SECTION [...,<sup>1</sup>...] {.^2.}</code> 1 REFERENCE <small>OPT</small> 2 TEXT instances: part chapter section subsection subsubsection subsubsubsection subsubsubsubsection title subject subsubject subsubsubject subsubsubsubject subsubsubsubsubject
<code>\SECTION [...,<sup>*</sup>...,...]</code> * titlu = TEXT semncarte = TEXT marcaje = TEXT lista = TEXT referinta = REFERENCE numarpropriu = TEXT instances: part chapter section subsection subsubsection subsubsubsection subsubsubsubsection title subject subsubject subsubsubject subsubsubsubject subsubsubsubsubject
<code>\chapter [...,<sup>*</sup>...,...]</code> * titlu = TEXT semncarte = TEXT marcaje = TEXT lista = TEXT referinta = REFERENCE numarpropriu = TEXT

`\part [...,.*,...]`

\* titlu = TEXT  
semncarte = TEXT  
marcaje = TEXT  
lista = TEXT  
referinta = REFERENCE  
numarpropriu = TEXT

`\section [...,.*,...]`

\* titlu = TEXT  
semncarte = TEXT  
marcaje = TEXT  
lista = TEXT  
referinta = REFERENCE  
numarpropriu = TEXT

`\subject [...,.*,...]`

\* titlu = TEXT  
semncarte = TEXT  
marcaje = TEXT  
lista = TEXT  
referinta = REFERENCE  
numarpropriu = TEXT

`\subsection [...,.*,...]`

\* titlu = TEXT  
semncarte = TEXT  
marcaje = TEXT  
lista = TEXT  
referinta = REFERENCE  
numarpropriu = TEXT

`\subsubject [...,.*,...]`

\* titlu = TEXT  
semncarte = TEXT  
marcaje = TEXT  
lista = TEXT  
referinta = REFERENCE  
numarpropriu = TEXT

`\subsubsection [...,.*,...]`

\* titlu = TEXT  
semncarte = TEXT  
marcaje = TEXT  
lista = TEXT  
referinta = REFERENCE  
numarpropriu = TEXT

`\subsubsubject [...,.*,...]`

\* titlu = TEXT  
semncarte = TEXT  
marcaje = TEXT  
lista = TEXT  
referinta = REFERENCE  
numarpropriu = TEXT

`\subsubsubsection [...,.*,...]`

\* titlu = TEXT  
semncarte = TEXT  
marcaje = TEXT  
lista = TEXT  
referinta = REFERENCE  
numarpropriu = TEXT



`\subsubsubsubject [...,.*=...,...]`

\* titlu = TEXT  
semncarte = TEXT  
marcaje = TEXT  
lista = TEXT  
referinta = REFERENCE  
numarpropriu = TEXT

`\subsubsubsubsection [...,.*=...,...]`

\* titlu = TEXT  
semncarte = TEXT  
marcaje = TEXT  
lista = TEXT  
referinta = REFERENCE  
numarpropriu = TEXT

`\subsubsubsubsubject [...,.*=...,...]`

\* titlu = TEXT  
semncarte = TEXT  
marcaje = TEXT  
lista = TEXT  
referinta = REFERENCE  
numarpropriu = TEXT

`\title [...,.*=...,...]`

\* titlu = TEXT  
semncarte = TEXT  
marcaje = TEXT  
lista = TEXT  
referinta = REFERENCE  
numarpropriu = TEXT

`\chapter [...,1...] {..2.}`

1 REFERENCE <sup>OPT</sup>  
2 TEXT

`\SECTION [...,1...] {..2.} {..3.}`

1 REFERENCE <sup>OPT</sup>  
2 NUMMER  
3 TEXT

instances: part chapter section subsection subsubsection subsubsubsection subsubsubsubsection  
title subject subsubject subsubsubject subsubsubsubject subsubsubsubsubject

`\chapter [...,1...] {..2.} {..3.}`

1 REFERENCE <sup>OPT</sup>  
2 NUMMER  
3 TEXT

`\part [...,1...] {..2.} {..3.}`

1 REFERENCE<sup>OPT</sup>  
2 NUMMER  
3 TEXT

`\section [...,1...] {..2.} {..3.}`

1 REFERENCE <sup>OPT</sup>  
2 NUMMER  
3 TEXT

`\subject [...,1...] {..2.} {..3.}`

1 REFERENCE <sup>OPT</sup>  
2 NUMMER  
3 TEXT

`\subsection [...,1...] {..2.} {..3.}`

1 REFERENCE <sup>OPT</sup>  
2 NUMMER  
3 TEXT

$\backslash\text{subsubject} [\dots^1, \dots] \{\dots^2\} \{\dots^3\}$ 1    REFERENCE                    OPT 2    NUMMER 3    TEXT
$\backslash\text{subsubsection} [\dots^1, \dots] \{\dots^2\} \{\dots^3\}$ 1    REFERENCE                    OPT 2    NUMMER 3    TEXT
$\backslash\text{subsubsubject} [\dots^1, \dots] \{\dots^2\} \{\dots^3\}$ 1    REFERENCE                    OPT 2    NUMMER 3    TEXT
$\backslash\text{subsubsubsection} [\dots^1, \dots] \{\dots^2\} \{\dots^3\}$ 1    REFERENCE                    OPT 2    NUMMER 3    TEXT
$\backslash\text{subsubsubsubject} [\dots^1, \dots] \{\dots^2\} \{\dots^3\}$ 1    REFERENCE                    OPT 2    NUMMER 3    TEXT
$\backslash\text{subsubsubsubsection} [\dots^1, \dots] \{\dots^2\} \{\dots^3\}$ 1    REFERENCE                    OPT 2    NUMMER 3    TEXT
$\backslash\text{subsubsubsubsubject} [\dots^1, \dots] \{\dots^2\} \{\dots^3\}$ 1    REFERENCE                    OPT 2    NUMMER 3    TEXT
$\backslash\text{title} [\dots^1, \dots] \{\dots^2\} \{\dots^3\}$ 1    REFERENCE                    OPT 2    NUMMER 3    TEXT
$\backslash\text{part} [\dots^1, \dots] \{\dots^2\}$ 1    REFERENCE <sup>PT</sup> 2    TEXT
$\backslash\text{section} [\dots^1, \dots] \{\dots^2\}$ 1    REFERENCE                    OPT 2    TEXT
$\backslash\text{subject} [\dots^1, \dots] \{\dots^2\}$ 1    REFERENCE                    OPT 2    TEXT
$\backslash\text{subsection} [\dots^1, \dots] \{\dots^2\}$ 1    REFERENCE                    OPT 2    TEXT
$\backslash\text{subsubject} [\dots^1, \dots] \{\dots^2\}$ 1    REFERENCE                    OPT 2    TEXT
$\backslash\text{subsubsection} [\dots^1, \dots] \{\dots^2\}$ 1    REFERENCE                    OPT 2    TEXT

<p><code>\subsubsubject [...<sup>1</sup>,...] {...<sup>2</sup>}</code></p> <p>1 REFERENCE OPT</p> <p>2 TEXT</p>
<p><code>\subsubsubsection [...<sup>1</sup>,...] {...<sup>2</sup>}</code></p> <p>1 REFERENCE OPT</p> <p>2 TEXT</p>
<p><code>\subsubsubsubject [...<sup>1</sup>,...] {...<sup>2</sup>}</code></p> <p>1 REFERENCE OPT</p> <p>2 TEXT</p>
<p><code>\subsubsubsubsection [...<sup>1</sup>,...] {...<sup>2</sup>}</code></p> <p>1 REFERENCE OPT</p> <p>2 TEXT</p>
<p><code>\subsubsubsubsubject [...<sup>1</sup>,...] {...<sup>2</sup>}</code></p> <p>1 REFERENCE OPT</p> <p>2 TEXT</p>
<p><code>\title [...<sup>1</sup>,...] {...<sup>2</sup>}</code></p> <p>1 REFERENCE OPT</p> <p>2 TEXT</p>
<p><code>\veziREGISTER [...<sup>1</sup>] [...+...<sup>2</sup>+...] {...<sup>3</sup>}</code></p> <p>1 TEXT PROCESSOR-&gt;TEXT</p> <p>2 INDEX</p> <p>3 TEXT PROCESSOR-&gt;TEXT</p> <p>instances: index</p>
<p><code>\veziindex [...<sup>1</sup>] [...+...<sup>2</sup>+...] {...<sup>3</sup>}</code></p> <p>1 TEXT PROCESSOR-&gt;TEXT</p> <p>2 INDEX</p> <p>3 TEXT PROCESSOR-&gt;TEXT</p>
<p><code>\select {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} {...<sup>4</sup>} {...<sup>5</sup>} {...<sup>6</sup>}</code></p> <p>1 NAME OPT OPT OPT OPT OPT</p> <p>2 CONTENT</p> <p>3 CONTENT</p> <p>4 CONTENT</p> <p>5 CONTENT</p> <p>6 CONTENT</p>
<p><code>\selecteazablocuri [...<sup>1</sup>,...] [...<sup>2</sup>,...] [...<sup>3</sup>,...<sup>3</sup>,...]</code></p> <p>1 NAME OPT OPT</p> <p>2 NAME</p> <p>3 criteriu = text ABSCHNITT</p>
<p><code>\semncarte [...<sup>1</sup>] {...<sup>2</sup>}</code></p> <p>1 ABSCHNITT LISTE</p> <p>2 TEXT</p>
<p><code>\serializecommalist [...<sup>*</sup>,...]</code></p> <p>* BEFEHL</p>
<p><code>\serializedcommalist</code></p>
<p><code>\serif</code></p>
<p><code>\serifbold</code></p>
<p><code>\serifnormal</code></p>

\setare [...]

\* NAME

\setareitemization [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME NAME:NUMMER

OPT

2 inherits: \setupitemgroup

\setarelimba [...]<sup>1</sup> [...,<sup>2</sup>...,...]

1 SPRACHE implicit<sup>OPT</sup>

2 implicit = SPRACHE  
stare = start stop  
data = inherits: \datacurenta  
patterns = FILE  
lefthyphenmin = NUMMER  
righthyphenmin = NUMMER  
lefthyphenchar = NUMMER  
righthyphenchar = NUMMER  
setups = NAME  
spatiere = broad impachetat  
font = auto  
bidi = stanga dreapta l2r r2l  
text = TEXT  
limittext = TEXT  
hyphen = TEXT  
compoundhyphen = TEXT  
leftcompoundhyphen = TEXT  
rightcompoundhyphen = TEXT  
minicitatstanga = BEFEHL  
minicitatdreapta = BEFEHL  
citastanga = BEFEHL  
citadreapta = BEFEHL  
leftspeech = BEFEHL  
rightspeech = BEFEHL  
propositiestanga = BEFEHL  
middlespeech = BEFEHL  
propositiedreapta = BEFEHL  
midsentence = BEFEHL  
subpropositiestanga = BEFEHL  
subpropositiedreapta = BEFEHL  
factor = da nu

\setarepozitie [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME

OPT

2 offset = da nu  
unitate = ex em pt in cm mm sp bp pc dd cc nc  
stare = start overlay  
xoffset = DIMENSION  
yoffset = DIMENSION  
xstep = absolut relativ  
ystep = absolut relativ  
xscala = NUMMER  
yscala = NUMMER  
xfactor = NUMMER  
yfactor = NUMMER  
factor = NUMMER  
scala = NUMMER

\setare {...}

\* NAME

\setbar [...]

\* NAME

\setbigbodyfont

\setboxllx ... {...}

1 CSNAME NUMMER

2 DIMENSION

<pre> \setboxlly <sup>1</sup>... {<sup>2</sup>...} 1 CSNAME NUMMER 2 DIMENSION </pre>
<pre> \setbreakpoints [...] * reset NAME </pre>
<pre> \setbuffer [...] ... \endbuffer * NAME </pre>
<pre> \setcapstrut </pre>
<pre> \setcatcodetable \*... * CSNAME </pre>
<pre> \setcharacteralign {<sup>1</sup>...} {<sup>2</sup>...} 1 NUMMER 2 TEXT number-&gt;TEXT text-&gt;TEXT </pre>
<pre> \setcharactercasing [...] * reset CUVANT cuvânt Cuvant Cuvinte majuscula Majuscula niciunul aleator mixed camel cap Cap </pre>
<pre> \setcharactercleaning [...] * reset 1 </pre>
<pre> \setcharacterkerning [...] * reset NAME </pre>
<pre> \setcharacterspacing [...] * reset NAME </pre>
<pre> \setcharacterstripping [...] * reset 1 </pre>
<pre> \setcharstrut {*...} * TEXT </pre>
<pre> \setcollector [<sup>1</sup>...] [<sup>2</sup>...<sub>OPT</sub>...<sup>3</sup>] {<sup>3</sup>...} 1 NAME 2 inherits: \setupcollector 3 CONTENT </pre>
<pre> \setcolormodel1 [...] * black bw gri rgb cmyk tot niciunul </pre>
<pre> \setcounter [<sup>1</sup>...] [<sup>2</sup>...<sub>OPT</sub>] [<sup>3</sup>...] 1 NAME 2 NUMMER 3 NUMMER </pre>
<pre> \setcounterown [<sup>1</sup>...] [<sup>2</sup>...<sub>OPT</sub>] [<sup>3</sup>...] 1 NAME 2 NUMMER 3 TEXT </pre>
<pre> \setcurrentfontclass {*...} * NAME </pre>

<pre> \setdataset [...] [...] [...] [...] 1 NAME OPT 2 NAME 3 KEY = VALUE </pre>
<pre> \setdefaultpenalties </pre>
<pre> \setdigitsmanipulation [...] * reset NUMMER </pre>
<pre> \setdirection [...] * NUMMER </pre>
<pre> \setdocumentargument {...} {...} 1 NAME 2 TEXT </pre>
<pre> \setdocumentargumentdefault {...} {...} 1 NAME 2 TEXT </pre>
<pre> \setdocumentfilename {...} {...} 1 NUMMER 2 TEXT </pre>
<pre> \setdummyparameter {...} {...} 1 KEY 2 BEFEHL </pre>
<pre> \seteazaaliniat [...,*...] * [-+]mic [-+]mediu [-+]mare niciunul nu nu primul urmatorul da totdeauna niciodata impar par normal reset toggle DIMENSION NAME </pre>
<pre> \seteazaalinieria [...,*...] * broad larg subsol inaltime linie inalt jos lohi flushright flushleft centru da nu latime normal reset intern extern flushinner flushouter stanga dreapta center dezactivat ultim end paragraf lefttoright righttoleft l2r r2l tabelul lesshyphenation morehyphenation suspendat nothanging hz fullhz nohz despsilabe nedespsilabe tolerant foartetolerant dilatat extremestretch final 1*final 2*final 3*final 4*final more 1*more 2*more </pre>
<pre> \seteazaantet [...] [...] 1 text margine bordura 2 inherits: \setuplayoutelement </pre>
<pre> \seteazaaranjareapag [...,*...] * dezactivat oglindit douafete negativ 90 180 270 reset fundal normal 2*16 2*8 2*4 2*2 2**2 2SIDE 2TOP 2UP 2DOWN 2*4*2 2*2*4 2TOPSIDE 2*8*Z 2*6*Z 1*8 1*4 3SIDE TRYPTICHON ZFLYER-8 ZFLYER-10 ZFLYER-12 MAPFLYER-12 DOUBLEWINDOW 1*2-Conference 1*4-Conference 2*2*2 2*2*3 XY NAME </pre>

\setezaaspect [...]<sup>1</sup> [...,...<sup>2</sup>...,...]

```

1  NAME OPT
2  stare = start stop normal repetat
    margine = DIMENSION
    bordura = DIMENSION
    distantamargine = DIMENSION
    distantabordura = DIMENSION
    distantabordurastanga = DIMENSION
    distantacoltdreapta = DIMENSION
    distantamarginestanga = DIMENSION
    distantamarginedreapta = DIMENSION
    distantasus = DIMENSION
    distantaantet = DIMENSION
    distantasubsol = DIMENSION
    distantajos = DIMENSION
    preset = NAME
    marginestanga = DIMENSION
    marginedreapta = DIMENSION
    bordurastanga = DIMENSION
    borduradreapta = DIMENSION
    antet = DIMENSION
    subsol = DIMENSION
    sus = DIMENSION
    jos = DIMENSION
    spatiuspate = DIMENSION
    spatiusus = DIMENSION
    setups = NAME
    cutspace = DIMENSION
    latime = DIMENSION centru ajustat
    spatiujos = DIMENSION
    linii = NUMMER
    inaltime = DIMENSION centru ajustat
    offsetoriz = DIMENSION
    veroffset = DIMENSION
    coloane = NUMMER
    distantacoloane = DIMENSION
    metoda = implicit normal NAME
    locatie = stanga centru dreapta sus subsol ofata douafete
    latimetext = DIMENSION
    inaltimetext = DIMENSION
    nx = NUMMER
    ny = NUMMER
    dx = DIMENSION
    dy = DIMENSION
    scala = NUMMER
    sx = NUMMER
    sy = NUMMER
    marcaje = on dezactivat pagina gol culoare unu doi patru
    grid = da nu dezactivat
    textdistance = DIMENSION
    alternativ = implicit normal marcaj NAME
    clipoffset = DIMENSION
    cropoffset = DIMENSION
    trimoffset = DIMENSION
    bleedoffset = DIMENSION
    artoffset = DIMENSION

```

\setezaaspect [...]

\* reset NAME

\seteazabarainteractiune [...]<sup>1</sup>,... [...,...<sup>2</sup>...,...]

```

1  NAME OPT
2  alternativ = a b c d e f g
    stare = start stop
    comanda = CSNAME
    latime = DIMENSION
    inaltime = DIMENSION max broad
    inaltime = DIMENSION max
    distanta = DIMENSION
    pas = mic mediu mare
    culoarefundal = COLOR
    stil = STYLE BEFEHL
    culoare = COLOR
    culoarecontrast = COLOR
    simbol = da nu
    inherits: \seteazainconjurat

```

**\seteazablanc** [...,\*,...]

\* inherits: \blanc OPT

**\seteazabloc** [...,<sup>1</sup>,...] [...,..<sup>2</sup>...,...]

1 NAME OPT  
2 inainte = BEFEHL  
dupa = BEFEHL  
intern = BEFEHL  
stil = STYLE BEFEHL  
culoare = COLOR

**\seteazablocsectione** [...,<sup>1</sup>,...] [...,..<sup>2</sup>...,...]

1 NAME OPT  
2 pagina = inherits: \pagina  
inainte = BEFEHL  
dupa = BEFEHL  
numar = da nu

**\seteazabuffer** [...,<sup>1</sup>,...] [...,..<sup>2</sup>...,...]

1 BUFFER OPT  
2 inainte = BEFEHL  
dupa = BEFEHL

**\seteazacamp** [...,<sup>1</sup>...] [...,..<sup>2</sup>...,...] [...,..<sup>3</sup>...,...] [...,..<sup>4</sup>...,...] [...,..<sup>5</sup>...,...]

1 NAME OPT  
2 reset eticheta incadrat orizontal vertical  
3 inherits: \setupfieldtotalframed  
4 inherits: \setupfieldlabelframed  
5 inherits: \setupfieldcontentframed

**\seteazacampuri** [...,<sup>1</sup>,...] [...,..<sup>2</sup>...,...] [...,..<sup>3</sup>...,...] [...,..<sup>4</sup>...,...]

1 reset eticheta incadrat OPT orizontal vertical  
2 inherits: \setupfieldtotalframed  
3 inherits: \setupfieldlabelframed  
4 inherits: \setupfieldcontentframed

**\seteazaclipping** [...,..<sup>\*</sup>...,...]

\* stare = start stop  
latime = DIMENSION  
inaltime = DIMENSION  
hoffset = DIMENSION  
voffset = DIMENSION  
x = NUMMER  
y = NUMMER  
nx = NUMMER  
ny = NUMMER  
sx = NUMMER  
sy = NUMMER  
offsetstanga = DIMENSION  
offsetdreapta = DIMENSION  
offsetsus = DIMENSION  
offsetjos = DIMENSION  
mp = NAME  
n = NUMMER  
offset = DIMENSION

**\seteazacoloane** [...,..<sup>\*</sup>...,...]

\* n = NUMMER  
distanta = DIMENSION  
optiune = fundal  
offset = DIMENSION  
comanda = \...##1  
inaltime = DIMENSION  
directie = stanga dreapta  
balanta = da nu  
alinie = setupalign  
toleranta = settolerance  
blanc = inherits: \blanc  
nsus = NUMMER  
rigla = on dezactivat BEFEHL



\seteazacommentariu [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
2 stare = start stop niciunul  
metoda = normal ascuns  
simbol = Comment Ajutor Insert Cheie Newparagraph Note Paragraf Default  
latime = ajustat DIMENSION  
inaltime = ajustat DIMENSION  
inaltime = ajustat DIMENSION  
titlu = TEXT  
subtitlu = TEXT  
autor = TEXT  
nx = NUMMER  
ny = NUMMER  
culoare = COLOR  
optiune = xml max  
textlayer = NAME  
locatie = bordurastanga borduradreaapta inmarginestanga marginedreaapta text inalt niciunul  
distanta = DIMENSION  
spatiu = da  
buffer = BUFFER

\seteazacommentariupagina [...<sup>\*</sup>,...]

\* locatie = stanga dreapta sus subsol niciunul  
stare = start stop niciunul  
offset = DIMENSION  
distanta = DIMENSION  
latime = DIMENSION  
inaltime = DIMENSION

\seteazaculoare [...]

\* FILE

\seteazaculori [...<sup>\*</sup>,...]

\* stare = start stop  
spot = da nu  
expansiune = da nu  
factor = da nu  
rgb = da nu  
cmyk = da nu  
conversie = da nu totdeauna  
pagecolormodel = auto niciunul NAME  
culoaretext = COLOR  
intent = overprint knockout niciunul

\seteazadimensiunihartie [...<sup>1</sup>] [...<sup>2</sup>,...]

1 NAME OPT  
2 sus = BEFEHL  
jos = BEFEHL  
stanga = BEFEHL  
dreapta = BEFEHL  
metoda = normal niciunul NAME  
scala = NUMMER  
nx = NUMMER  
ny = NUMMER  
dx = DIMENSION  
dy = DIMENSION  
latime = DIMENSION  
inaltime = DIMENSION  
spatiusus = DIMENSION  
spatiuspate = DIMENSION  
offset = DIMENSION  
pagina = reset vedere oglindit negativ rotat 90 180 270 NAME  
hartie = reset vedere oglindit negativ rotat 90 180 270 NAME  
optiune = ajustat max  
distanta = DIMENSION

\seteazadimensiunihartie [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 reset vedere oglindit negativ rotat<sup>OPT</sup> 90 180 270<sup>OP</sup>NAME  
2 reset vedere oglindit negativ rotat 90 180 270 NAME

`\seteazaecraninteractiune [...,..*...]`

\* latime = ajustat max tight DIMENSION  
inaltime = ajustat max tight DIMENSION  
spatiuspate = DIMENSION  
offsetoriz = DIMENSION  
veroffset = DIMENSION  
spatiusus = DIMENSION  
optiune = ajustat max ofata douafete semncarte auto niciunul implicit fixat vedere portrait pagina foaie  
attachment layer  
copies = NUMMER  
print = LISTE  
intarziere = niciunul NUMMER

`\seteazaelemente [...,1...] [...,..2...]`

1 NAME OPT  
2 alternativ = stanga dreapta sus subsol inmarginie  
latimetext = DIMENSION  
latime = DIMENSION  
distanta = DIMENSION  
simbol = niciunul NAME  
aliniere = stanga centru dreapta flushleft flushright intern extern marginie  
textalign = stanga centru dreapta flushleft flushright intern extern  
n = NUMMER  
inainte = BEFEHL  
dupa = BEFEHL  
intre = BEFEHL

`\seteazaenumerare [...,1...] [...,..2...]`

1 NAME OPT  
2 inherits: \setupenumeration

```

\seteazafloat [...1,...] [...2,...]
1 SINGULAR OPT
2 aliniaturmator = da nu auto
   implicit      = inherits: \placefloat
   fallback      = inherits: \placefloat
   intern        = BEFEHL
   criteriu      = DIMENSION
   metoda        = NUMMER
   sidemethod     = NUMMER
   textmethod     = NUMMER
   sidealign     = inaltime adancime linie jumatatelinie grila normal
   grid          = inherits: \snaptogrid
   local         = da nu
   comanda       = \...##1
   availablewidth = DIMENSION
   availableheight = DIMENSION
   latimeminima  = DIMENSION
   latimemaxima  = DIMENSION
   locatie       = stanga dreapta centru flushleft flushright center max intern extern innermargin outermargin
                  inneredge outeredge spatuspate cutspace marginestanga marginedreapta borduradreapta
                  borduradreapta
   distantamarginestanga = DIMENSION
   distantamarginedreapta = DIMENSION
   marginestanga = DIMENSION
   marginedreapta = DIMENSION
   innermargin   = DIMENSION
   outermargin   = DIMENSION
   bottombefore  = BEFEHL
   bottomafter   = BEFEHL
   expansiune    = da nu xml
   referenceprefix = + - TEXT
   xmlsetup      = NAME
   catcodes      = NAME
   freeregion    = da nu
   spatiuinainte = niciunul inherits: \blanc
   spatiudupa    = niciunul inherits: \blanc
   latime        = DIMENSION
   inaltime      = DIMENSION
   offset        = DIMENSION niciunul overlay
   spatiulateralinainte = niciunul inherits: \blanc
   spatiulateraldupa = niciunul inherits: \blanc
   spacebeforeside = niciunul inherits: \blanc
   spaceafterside = niciunul inherits: \blanc
   sidethreshold = old dimension
   margine       = DIMENSION
   nsus          = DIMENSION
   njos          = DIMENSION
   pas           = mic mediu mare linie adancime
   nlinii        = NUMMER
   cache         = da nu

```

```

\seteazaflats [...1,...] [...2,...]
1 SINGULAR OPT
2 inherits: \seteazafloat

```

```

\seteazafonttext [...*,...]
* DIMENSION NAME global reset x xx mic mare script scriptscript rm ss tt hw cg roman serif regular sans sansserif
  suport type teletype mono scrismmanual caligrafic

```

```

\seteazaformulare [...*,...]
* metoda = XML HTML PDF
  export = da nu

```

```

\seteazaformule [...1,...] [...2,...]
1 NAME OPT
2 inherits: \setupformula

```

`\seteazafundal [...,1...] [...,2...,...]`

1 NAME OPT  
2 stare = start stop  
offsetstanga = DIMENSION  
offsetdreapta = DIMENSION  
offsetsus = DIMENSION  
offsetjos = DIMENSION  
inainte = BEFEHL  
dupa = BEFEHL  
inherits: \seteazainconjurat

`\seteazafundaluri [...,1...] [...,2...] [...,3...,...]`

1 sus antet text subsol subsol OPT  
2 bordurastanga marginestanga text marginedreapta borduradreapta  
3 inherits: \seteazainconjurat

`\seteazafundaluri [...,1...] [...,2...,...]`

1 foaie pagina paginastanga<sup>OPT</sup>paginadreapta text ascuns  
2 stare = start stop  
inherits: \seteazainconjurat

`\seteazagrosimelinie [...]`

\* mic mediu mare DIMENSION

`\seteazaimpartireafloat [...,*...,...]`

\* inainte = BEFEHL  
dupa = BEFEHL  
intre = BEFEHL  
linii = auto NUMMER  
conversie = NAME

\seteazainconjurat [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```

1  NAME                      OPT
2  colt                      = rectangular rotund NUMMER
   coltframe                 = rectangular rotund NUMMER
   coltfundal                = rectangular rotund NUMMER
   raza                      = DIMENSION
   razaframe                 = DIMENSION
   razafundal                = DIMENSION
   inaltime                  = DIMENSION
   adancimeframe             = DIMENSION
   adancimefundal           = DIMENSION
   culoareframe              = COLOR
   framesus                  = on dezactivat NAME
   framejos                  = on dezactivat NAME
   framestanga               = on dezactivat NAME
   framedreapta              = on dezactivat NAME
   region                    = da nu
   grosimerigla              = DIMENSION
   offsetframe               = DIMENSION
   frame                     = on dezactivat overlay niciunul
   fundal                    = primplan culoare NAME
   offsetfundal              = incadrat DIMENSION
   component                 = NAME
   extras                    = BEFEHL
   foregroundstyle           = STYLE BEFEHL
   foregroundcolor           = COLOR
   setups                    = NAME
   offset                    = implicit overlay niciunul DIMENSION
   latime                    = local ajustat max broad fixat DIMENSION
   inaltime                  = ajustat max broad DIMENSION
   aliniere                  = inherits: \seteazaalinierea
   strut                     = da nu niciunul local global
   autostrut                 = da nu
   locatie                   = inaltime adancime inalt jos sus centru subsol linie lohi suspendat mentine formula matematica
                               normal
   autolatime                = da nu fortat
   linii                     = NUMMER
   sus                       = BEFEHL
   jos                       = BEFEHL
   blanc                     = da nu
   profile                   = NAME
   gol                       = da nu
   loffset                   = DIMENSION
   roffset                   = DIMENSION
   toffset                   = DIMENSION
   boffset                   = DIMENSION
   orientation               = NUMMER

```

\seteazaingust [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```

1  NAME                      OPT
2  stanga                    = DIMENSION
   mijloc                    = DIMENSION
   dreapta                   = DIMENSION
   implicit                  = [-+]stanga [-+]centru [-+]dreapta NUMMER*stanga NUMMER*centru NUMMER*dreapta reset
   inainte                   = BEFEHL
   dupa                      = BEFEHL

```

```

\seteazainteractiunea [...] [...]
1 NAME OPT
2 stare = start stop
  stil = STYLE BEFEHL
  culoare = COLOR
  culoarecontrast = COLOR
  titlu = TEXT
  subtitlu = COLOR
  autor = TEXT
  data = TEXT
  keyword = TEXT
  focus = standard incadrat latime latimeminima inaltime inaltimeminima ajustat tight
  meniu = on dezactivat
  fieldlayer = auto NAME
  calculeaza = REFERENCE
  click = da nu
  display = normal nou
  pagina = da nu pagina nume auto
  actiunedeschidere = REFERENCE
  actiuneinchidere = REFERENCE
  actiunedeschiderepagina = REFERENCE
  actiuneinchiderepagina = REFERENCE
  setsimbol = NAME
  inaltime = DIMENSION
  inaltime = DIMENSION
  focusoffset = DIMENSION

```

```

\seteazainteractiunea [...]
* NAME OPT

```

```

\seteazajos [...] [...]
1 text margine OPTbdura
2 inherits: \setuplayoutelement

```

```

\seteazalegenda [...] [...]
1 NAME OPT
2 inherits: \setupfloatcaption

```

```

\seteazalegendele [...] [...]
1 NAME OPT
2 inherits: \setupfloatcaption

```

```

\seteazaliniesilabe [...] [...]
* semn = normal larg

```

```

\seteazaliniesubtire [...] [...]
* inaltime = max DIMENSION
  inaltime = max DIMENSION
  fundal = culoare
  frame = on dezactivat
  grosimerigla = DIMENSION
  alternativ = a b c niciunul
  culoarefundal = COLOR
  culoare = COLOR
  spatiereinterliniara = mic mediu mare NUMMER
  inainte = BEFEHL
  dupa = BEFEHL
  intre = BEFEHL
  n = NUMMER

```

`\seteazalinii [...1,...] [...2...,...]`

```
1 NAME OPT
2 optiune = impachetat
  inainte = BEFEHL
  dupa = BEFEHL
  intre = BEFEHL
  aliniat = inherits: \seteazaaliniat
  aliniere = inherits: \seteazaalinierea
  spatiu = da on dezactivat fixat implicit
  comanda = BEFEHL
  stil = STYLE BEFEHL
  culoare = COLOR
  stanga = BEFEHL
  dreapta = BEFEHL
```

`\seteazaliniimargine [...1] [...2...,...]`

```
1 NUMMER OPT
2 inherits: \setupmarginrule
```

`\seteazaliniinegre [...*...,...]`

```
* latime = max DIMENSION
  inaltime = max DIMENSION
  inaltime = max DIMENSION
  distanta = DIMENSION
  n = NUMMER
  alternativ = a b
  stil = STYLE BEFEHL
  culoare = COLOR
  type = mp da nu
  mp = NAME
```

`\seteazaliniiumplere [...*...,...]`

```
* inainte = BEFEHL
  dupa = BEFEHL
  margine = DIMENSION
  latime = DIMENSION
  distanta = DIMENSION
  grosimerigla = DIMENSION
  culoare = COLOR
```

```

\seteazalista [...1,...] [...2,...]
1  LISTE
2  stare = start stop
    locatie = niciunul aici
    type = simple comanda userdata
    criteriu = local intro referinta SECTIONBLOCK:referinta tot SECTIONBLOCK:tot text SECTIONBLOCK:text
              curent SECTIONBLOCK:curent aici precedent SECTIONBLOCK:precedent componenta ABSCHNITT
              SECTIONBLOCK:ABSCHNITT

    lista = NAME
    latime = ajustat broad auto DIMENSION
    inaltime = ajustat broad DIMENSION
    inaltime = ajustat broad DIMENSION
    simbol = unu doi trei niciunul implicit
    eticheta = da nu niciunul NAME
    starter = BEFEHL
    stopper = BEFEHL
    comanda = \...##1##2##3
    comandanumar = \...##1
    comandatext = \...##1
    comandapagina = \...##1
    numarpagina = da nu totdeauna
    numartitlu = da nu totdeauna
    inainte = BEFEHL
    dupa = BEFEHL
    intre = BEFEHL
    margine = niciunul DIMENSION
    distanta = niciunul DIMENSION
    alinieretitlu = da nu
    numberalign = stanga dreapta centru flushleft flushright intern extern
    aliniere = inherits: \seteazaaliniere
    suspenda = da nu
    stanga = BEFEHL
    dreapta = BEFEHL
    interactiune = da nu tot numar text titlu pagina numarsetiune numarpagina
    limittext = da nu TEXT
    stil = STYLE BEFEHL
    culoare = COLOR
    stilnumar = STYLE BEFEHL
    culoarenumar = COLOR
    stiltext = STYLE BEFEHL
    culoarettext = COLOR
    stilpagina = STYLE BEFEHL
    culoarepagina = COLOR
    referinta = NUMBER
    extras = NAME
    order = comanda tot titlu
    alternativ = a b c d e f g stanga dreapta sus subsol comanda niciunul interactive paragraf orizontal
              vertical NAME

    latimemaxima = DIMENSION
    pageprefix = da nu
    pageprefixseparatorset = NAME
    pageprefixconversionset = NAME
    pageprefixset = NAME
    pageprefixsegments = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:tot ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:*
                      ABSCHNITT:tot
    pageprefixconnector = BEFEHL PROCESSOR->BEFEHL
    pageconversionset = NAME
    pagestarter = BEFEHL PROCESSOR->BEFEHL
    pagestopper = BEFEHL PROCESSOR->BEFEHL
    inherits: \setupcounterinherits: \seteazainconjurat

```

```

\seteazalistacombinata [...1] [...2,...]
1  LISTE
2  inherits: \seteazalista

```

```

\setareCOMBINEDLIST [...*,...]
* inherits: \seteazalista
instances: content

```

```

\setarecontent [...*,...]
* inherits: \seteazalista

```



```

\seteazamajuscule [...,1...] [...,2...,...]
1 NAME OPT
2 titlu = da nu
  sc = da nu
  stil = STYLE BEFEHL

```

```

\seteazamakeup [...,1...] [...,2...,...]
1 NAME OPT
2 pagina = inherits: \pagina
  comanda = BEFEHL
  latime = DIMENSION
  inaltime = DIMENSION
  aliniere = inherits: \seteazaalinierea
  setups = NAME
  sus = BEFEHL
  jos = BEFEHL
  inainte = BEFEHL
  dupa = BEFEHL
  locatie = sus
  referinta = REFERENCE
  pagestate = start stop
  stareantet = start stop inalt gol niciunul normal
  staresubsol = start stop inalt gol niciunul normal
  staresus = start stop inalt gol niciunul normal
  starejos = start stop inalt gol niciunul normal
  staretext = start stop inalt gol niciunul normal
  douafete = da nu gol
  stil = STYLE BEFEHL
  culoare = COLOR

```

```

\seteazamarcaje [...,1...] [...,2...,...]
1 BESCHRIFTUNG OPT
2 stare = start stop
  expansiune = da nu
  separator = BEFEHL
  filtercommand = \...##1

```

```

\seteazameniuiinteractiune [...,1...] [...,2...,...]
1 NAME OPT
2 alternativ = vertical orizontal ascuns
  category = NAME
  offsetstanga = overlay incadrat niciunul implicit DIMENSION
  offsetdreapta = overlay incadrat niciunul implicit DIMENSION
  offsetsus = overlay incadrat niciunul implicit DIMENSION
  offsetjos = overlay incadrat niciunul implicit DIMENSION
  latimemaxima = DIMENSION
  inaltimemaxima = DIMENSION
  itemalign = stanga centru dreapta flushleft flushright jos inalt lohi
  stare = start gol local
  stanga = BEFEHL
  dreapta = BEFEHL
  distanta = overlay DIMENSION
  inainte = BEFEHL
  dupa = BEFEHL
  intre = BEFEHL
  pozitie = da nu
  mijloc = BEFEHL
  stil = STYLE BEFEHL
  culoare = COLOR
  aceeasipagina = da nu gol niciunul normal implicit
  culoarecontrast = COLOR
  inherits: \seteazainconjurat

```

```

\seteazaminicitat [...,*...,...]
* inherits: \setupdelimitedtext

```

```

\seteazanumarpagina [...,*...,...]
* inherits: \setuppagenumber

```

```

\seteazanumarsubpagina [...,*...,...]
* inherits: \setupcounter

```

\seteazanumartitlu [...]<sup>1</sup> [...]<sup>2</sup>

1 ABSCHNITT  
2 [-+]NUMMER

\seteazanumerotarelinii [...]<sup>1</sup>,...<sup>2</sup> [...],...<sup>2</sup>,...]

1 NAME OPT  
2 start = NUMMER  
pas = NUMMER  
metoda = pagina primul urmatorul  
conversie = NAME  
continua = da nu  
locatie = text begin end implicit stanga dreapta intern extern instanga indreapta margine inmargine  
distanta = DIMENSION  
aliniere = intern extern flushleft flushright stanga dreapta centru auto  
comanda = \...##1  
stanga = BEFEHL  
dreapta = BEFEHL  
margine = DIMENSION  
latime = margine DIMENSION  
stil = STYLE BEFEHL  
culoare = COLOR

\seteazanumerotarepagina [...],...<sup>\*</sup>,...]

\* alternativ = ofata douafete  
pagina = inherits: \pagina  
strut = da nu  
comanda = \...##1  
stanga = BEFEHL  
dreapta = BEFEHL  
stare = start stop  
latime = DIMENSION  
locatie = antet subsol stanga centru dreapta instanga indreapta margine inmargine lamargine marginebordura  
stil = STYLE BEFEHL  
culoare = COLOR

\seteazanumerotareparagrafe [...],...<sup>\*</sup>,...]

\* stare = start stop linie reset  
distanta = DIMENSION  
stil = STYLE BEFEHL  
culoare = COLOR

\seteazapaleta [...]

\* NAME

\seteazaparagrafe [...]<sup>1</sup> [...],...<sup>2</sup> [...],...<sup>3</sup>,...]

1 NAME OPT OPT  
2 fiecare NUMMER  
3 n = NUMMER  
inainte = BEFEHL  
dupa = BEFEHL  
latime = DIMENSION  
distanta = DIMENSION  
inaltime = DIMENSION ajustat  
sus = BEFEHL  
jos = BEFEHL  
aliniere = inherits: \seteazaalinieria  
intern = BEFEHL  
comanda = BEFEHL  
rigla = on dezactivat  
grosimerigla = DIMENSION  
culoarerigla = COLOR  
stil = STYLE BEFEHL  
culoare = COLOR

**\seteazaparafrage** [<sup>1</sup>...] [<sup>2</sup>...,...]

1 NAME:NUMMER OPT  
2 n = NUMMER  
inainte = BEFEHL  
dupa = BEFEHL  
latime = DIMENSION  
distanta = DIMENSION  
inaltime = DIMENSION ajustat  
sus = BEFEHL  
jos = BEFEHL  
alinieri = inherits: \seteazaalinierea  
intern = BEFEHL  
comanda = BEFEHL  
rigla = on dezactivat  
grosimerigla = DIMENSION  
culoarerigla = COLOR  
stil = STYLE BEFEHL  
culoare = COLOR

**\seteazaplasareaopozita** [...,\*...]

\* stare = start stop  
inainte = BEFEHL  
dupa = BEFEHL  
intre = BEFEHL

**\seteazaprograme** [...,\*...]

\* stil = STYLE BEFEHL  
culoare = COLOR

**\seteazareferinte** [...,\*...]

\* stare = start stop  
expansiune = da nu xml  
autofile = da nu  
export = da nu  
stanga = BEFEHL  
dreapta = BEFEHL  
latime = DIMENSION  
douafete = da nu  
interactiune = eticheta text simbol tot  
separator = BEFEHL  
prefix = + - TEXT

\seteazaregistru [<sup>1</sup>...] [<sup>2</sup>...,...]

```

1  NAME NAME:NUMMER      OPT
2  referencemethod      = avans
   expansiune           = da nu xml
   numarpropriu         = da nu
   xmlsetup             = NAME
   alternativ            = a b A B
   metoda               = implicit inainte dupa primul ultim ch mm zm pm mc zc pc uc
   compress             = da nu tot
   criteriu             = local text curent precedent tot ABSCHNITT
   pageprefixseparatorset = BEFEHL
   pageprefixconversionset = NAME
   pageprefixstarter    = BEFEHL PROCESSOR->BEFEHL
   pageprefixstopper    = BEFEHL PROCESSOR->BEFEHL
   pageprefixset        = NAME
   pageprefixsegments   = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:tot ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:*
                           ABSCHNITT:tot

   pageprefixconnector  = BEFEHL
   pageprefix           = da nu
   pageseparatorset     = NAME
   pageconversionset    = NAME
   pagestarter          = BEFEHL PROCESSOR->BEFEHL
   pagestopper          = BEFEHL PROCESSOR->BEFEHL
   pagesegments         = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:tot
   latimemaxima         = DIMENSION
   indicator            = da nu
   inainte              = BEFEHL
   dupa                 = BEFEHL
   comanda              = \...#1
   comandatext          = \...#1
   deeptextcommand      = \...#1
   comandapagina        = \...#1
   distanta             = DIMENSION
   interactiune         = text numarpagina
   numarpagina          = da nu
   simbol               = a n niciunul 1 2 BEFEHL
   language             = implicit DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scn SPRACHE
   stil                 = STYLE BEFEHL
   culoare              = COLOR
   stiltext             = STYLE BEFEHL
   culoaretext          = COLOR
   stilpagina           = STYLE BEFEHL
   culoarepagina        = COLOR
   n                    = NUMBER
   balanta              = da nu
   aliniere             = inherits: \seteazaalinierea
   numberorder          = numere

```

\seteazaregistru [...,<sup>1</sup>...] [...,<sup>2</sup>...] [...,<sup>3</sup>...,...]

```

1  NAME                      OPT          OPT
2  NUMMER
3  referencemethod           = avans
   expansiune                = da nu xml
   numarpropriu              = da nu
   xmlsetup                  = NAME
   alternativ                 = a b A B
   metoda                    = implicit inainte dupa primul ultim ch mm zm pm mc zc pc uc
   compress                  = da nu tot impachetat
   criteriu                  = local text curent precedent tot ABSCHNITT
   pageprefixseparatorset    = BEFEHL
   pageprefixconversionset   = NAME
   pageprefixstarter         = BEFEHL PROCESSOR->BEFEHL
   pageprefixstopper         = BEFEHL PROCESSOR->BEFEHL
   pageprefixset             = NAME
   pageprefixsegments        = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:tot ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:*
                               ABSCHNITT:tot
   pageprefixconnector       = BEFEHL
   pageprefix                = da nu
   pageseparatorset          = NAME
   pageconversionset         = NAME
   pagestarter               = BEFEHL PROCESSOR->BEFEHL
   pagestopper               = BEFEHL PROCESSOR->BEFEHL
   pagesegments              = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:tot
   latimemaxima              = DIMENSION
   indicator                 = da nu
   inainte                   = BEFEHL
   dupa                      = BEFEHL
   comanda                   = \...##1
   comandatext               = \...##1
   deeptextcommand           = \...##1
   comandapagina             = \...##1
   distanta                  = DIMENSION
   interactiune              = text numarpagina
   numarpagina               = da nu
   simbol                    = a n niciunul 1 2 BEFEHL
   language                  = implicit DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scen SPRACHE
   stil                      = STYLE BEFEHL
   culoare                   = COLOR
   stiltext                  = STYLE BEFEHL
   culoaretext               = COLOR
   stilpagina                = STYLE BEFEHL
   culoarepagina             = COLOR
   n                         = NUMMER
   balanta                   = da nu
   aliniere                  = inherits: \seteazaalinierea
   numberorder               = numere

```

\setareREGISTER [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

```

1  NUMMER                      OPT
2  inherits: \seteazaregistru
instances: index

```

\setareindex [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

```

1  NUMMER                      OPT
2  inherits: \seteazaregistru

```

\seteazarigletext [...,<sup>\*</sup>...,...]

```

*  inainte                   = BEFEHL
   dupa                      = BEFEHL
   intre                     = BEFEHL
   grosimerigla              = DIMENSION
   locatie                   = stanga inmarginie
   stil                      = STYLE BEFEHL
   culoare                   = COLOR
   culoarerigla              = COLOR
   latime                    = DIMENSION
   inaltime                  = DIMENSION
   distanta                  = DIMENSION
   corectieadancime          = on dezactivat
   fonttext                  = inherits: \seteazafonttext

```

**\seteazarigleumplere** [...,..<sup>\*</sup>...,...]

\*    inainte                = BEFEHL  
     dupa                 = BEFEHL  
     n                     = NUMBER  
     spatiereinterliniara = mic mediu mare NUMBER  
     distanta              = DIMENSION  
     latime                = ajustat broad DIMENSION  
     separator            = BEFEHL  
     stil                  = STYLE BEFEHL  
     culoare              = COLOR

**\seteazarotare** [...,..<sup>\*</sup>...,...]

\*    locatie = ajustat broad adancime inalt centru implicit normal  
     rotatie = stanga dreapta intern extern NUMBER  
     inherits: \seteazainconjurat

**\seteazasimbol** [...]

\*    NAME

**\seteazasinonime** [...,<sup>1</sup>...] [...,..<sup>2</sup>...,...]

1    SINGULAR                <sup>OPT</sup>  
2    expansiune              = da nu xml  
     alternativ               = primul ultim normal NAME  
     urmatorul               = BEFEHL  
     comanda                = \...##1##2##3  
     comandatext            = \...##1  
     synonymcommand        = \...##1  
     language               = implicit DIN<sub>5007-1</sub> DIN<sub>5007-2</sub> Duden de-DE de-CH de-AT ru-iso9 ocs-sc<sub>n</sub> SPRACHE  
     metoda                 = implicit inainte dupa primul ultim ch mm zm pm mc zc pc uc  
     criteriu                = curent precedent local text tot ABSCHNITT  
     stil                    = STYLE BEFEHL  
     culoare                = COLOR  
     stiltext                = STYLE BEFEHL  
     culoaretext            = COLOR  
     stilsinonim            = STYLE BEFEHL  
     culoaresinonim        = COLOR

**\seteazasortare** [...,<sup>1</sup>...] [...,..<sup>2</sup>...,...]

1    SINGULAR                <sup>OPT</sup>  
2    expansiune              = da nu xml  
     alternativ               = primul ultim normal NAME  
     urmatorul               = BEFEHL  
     comanda                = \...##1##2##3  
     comandatext            = \...##1  
     synonymcommand        = \...##1  
     language               = implicit DIN<sub>5007-1</sub> DIN<sub>5007-2</sub> Duden de-DE de-CH de-AT ru-iso9 ocs-sc<sub>n</sub> SPRACHE  
     metoda                 = implicit inainte dupa primul ultim ch mm zm pm mc zc pc uc  
     criteriu                = curent precedent local text tot ABSCHNITT  
     stil                    = STYLE BEFEHL  
     culoare                = COLOR  
     stiltext                = STYLE BEFEHL  
     culoaretext            = COLOR  
     stilsinonim            = STYLE BEFEHL  
     culoaresinonim        = COLOR

**\seteazaspatiu** [...]

\*    fixat impachetat <sup>OPT</sup> ~~broad~~

**\seteazaspatialb** [...,<sup>\*</sup>...]

\*    fix fixat flexibil linie <sup>OPT</sup> jumatatelinie quarterline niciunul mic mediu mare implicit DIMENSION

```

\seteazaspatiuiinterliniar [...1,...2,...]
1 NAME OPT
2 linie = DIMENSION
  inalttime = NUMMER
  inalttime = NUMMER
  inaltimeminima = NUMMER
  mindepth = NUMMER
  distanta = DIMENSION
  sus = NUMMER inalttime
  jos = NUMMER
  dilatata = NUMMER
  shrink = NUMMER

```

```

\seteazaspatiuiinterliniar [...*,...]
* on dezactivat reset auto mic mediu mareOPT NUMMER DIMENSION

```

```

\seteazaspatiuiinterliniar [...*]
* NAME

```

```

\seteazasubsol [...1] [...2,...2,...]
1 text margine borduraOPT
2 inherits: \setuplayoutelement

```

```

\seteazasus [...1] [...2,...2,...]
1 text margine borduraOPT
2 inherits: \setuplayoutelement

```

```

\seteazatabele [...*,...2,...]
* text = DIMENSION max
  split = da nu repetat auto
  frame = on dezactivat
  NL = inherits: \blanc
  VL = mic mediu mare niciunul NUMMER
  HL = mic mediu mare niciunul NUMMER
  distanta = mic mediu mare niciunul
  aliniere = stanga centru dreapta
  comenzi = BEFEHL
  fonttext = inherits: \seteazafonttext
  grosimerigla = DIMENSION
  inalttime = strut NUMMER
  inalttime = strut NUMMER
  openup = DIMENSION

```

```

\seteazatabulatori [...1] [...2] [...3,...3,...]
1 NAME OPT OPT
2 NAME
3 inherits: \setuptabulation

```

```

\seteazatext [...1] [...2,...2,...]
1 text margine borduraOPT
2 inherits: \setuplayoutelement

```

```

\seteazatexteantet [...1] [...2] [...3] [...4] [...5]
1 text margine bordura OPT OPT OPT OPT OPT
2 data numarpagina BESCHRIFTUNG TEXT BEFEHL
3 data numarpagina BESCHRIFTUNG TEXT BEFEHL
4 data numarpagina BESCHRIFTUNG TEXT BEFEHL
5 data numarpagina BESCHRIFTUNG TEXT BEFEHL

```

```

\seteazatextejos [...1] [...2] [...3] [...4] [...5]
1 text margine borduraOPT OPT OPT OPT OPT
2 data numarpagina BESCHRIFTUNG TEXT BEFEHL
3 data numarpagina BESCHRIFTUNG TEXT BEFEHL
4 data numarpagina BESCHRIFTUNG TEXT BEFEHL
5 data numarpagina BESCHRIFTUNG TEXT BEFEHL

```

```
\seteazatextesubsol [...1] [...2] [...3] [...4] [...5]
1 text margine bordura OPT OPT OPT OPT OPT
2 data numarpagina BESCHRIFTUNG TEXT BEFEHL
3 data numarpagina BESCHRIFTUNG TEXT BEFEHL
4 data numarpagina BESCHRIFTUNG TEXT BEFEHL
5 data numarpagina BESCHRIFTUNG TEXT BEFEHL
```

```
\seteazatextesus [...1] [...2] [...3] [...4] [...5]
1 text margine bordura OPT OPT OPT OPT OPT
2 data numarpagina BESCHRIFTUNG TEXT BEFEHL
3 data numarpagina BESCHRIFTUNG TEXT BEFEHL
4 data numarpagina BESCHRIFTUNG TEXT BEFEHL
5 data numarpagina BESCHRIFTUNG TEXT BEFEHL
```

```
\seteazatextetext [...1] [...2] [...3] [...4] [...5]
1 text margine bordura OPT OPT OPT OPT OPT
2 data numarpagina BESCHRIFTUNG TEXT BEFEHL
3 data numarpagina BESCHRIFTUNG TEXT BEFEHL
4 data numarpagina BESCHRIFTUNG TEXT BEFEHL
5 data numarpagina BESCHRIFTUNG TEXT BEFEHL
```

```
\setareLABELtext [...1] [...,2...,...]
1 SPRACHE OPT
2 KEY = VALUE
instances: head label mathlabel taglabel unit operator prefix suffix btxlabel
```

```
\setarebtxlabeltext [...1] [...,2...,...]
1 SPRACHE OPT
2 KEY = VALUE
```

```
\setareheadtext [...1] [...,2...,...]
1 SPRACHE OPT
2 KEY = VALUE
```

```
\setarelabeltext [...1] [...,2...,...]
1 SPRACHE OPT
2 KEY = VALUE
```

```
\setaremathlabeltext [...1] [...,2...,...]
1 SPRACHE OPT
2 KEY = VALUE
```

```
\setareoperatortext [...1] [...,2...,...]
1 SPRACHE OPT
2 KEY = VALUE
```

```
\setareprefixtext [...1] [...,2...,...]
1 SPRACHE OPT
2 KEY = VALUE
```

```
\setaresuffixtext [...1] [...,2...,...]
1 SPRACHE OPT
2 KEY = VALUE
```

```
\setaretaglabeltext [...1] [...,2...,...]
1 SPRACHE OPT
2 KEY = VALUE
```

```
\setareunittext [...1] [...,2...,...]
1 SPRACHE OPT
2 KEY = VALUE
```



\seteazatitlu [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```

1  ABSCHNITT          OPT
2  frontpartlabel     = NAME
   bodypartlabel      = NAME
   appendixlabel      = NAME
   backpartlabel      = NAME
   expansiune         = da nu xml
   catcodes           = NAME
   sectionresetset    = NAME
   sectionseparatorset = NAME
   sectionconversionset = NAME
   conversie          = NAME
   sectionstarter      = BEFEHL PROCESSOR->BEFEHL
   sectionstopper      = BEFEHL PROCESSOR->BEFEHL
   sectionset          = NAME
   sectionsegments    = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:tot ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:*
                        ABSCHNITT:tot
   referenceprefix    = + - TEXT
   stil               = STYLE BEFEHL
   culoare            = COLOR
   stiltext           = STYLE BEFEHL
   culoaretext        = COLOR
   stilnumar          = STYLE BEFEHL
   culoarenumar       = COLOR
   cuplare            = ABSCHNITT
   numarpropriu       = da nu
   beforesection      = BEFEHL
   aftersection       = BEFEHL
   insidesection      = BEFEHL
   numarincrement     = da nu lista gol
   punetitlu          = da nu ascuns gol sectiune
   numar             = da nu
   pagina             = inherits: \pagina
   marcaje            = pagina reset
   antet              = start stop inalt niciunul normal gol faramarcare NAME
   text               = start stop inalt niciunul normal gol faramarcare NAME
   subsol             = start stop inalt niciunul normal gol faramarcare NAME
   inainte            = BEFEHL
   dupa               = BEFEHL
   intre              = BEFEHL
   continua           = da nu
   alinieretitlu      = da nu obiectmobil
   spatiereinterliniara = NAME
   interactiune       = lista referinta
   internalgrid       = NAME
   grid               = normal standard da strict tolerant sus subsol ambele broad ajustat primul ultim inalt unu
                        jos niciunul linie strut box min max centru math math:linie math:jumatatelinie math:-line
                        math:-halfline NAME
   aliniere           = inherits: \seteazaalinierea
   toleranta          = inherits: \seteazatoleranta
   strut              = da nu
   suspenda           = linie broad ajustat niciunul NUMMER
   margine            = DIMENSION
   aliniaturmator     = da nu auto
   alternativ          = text paragraf normal margine inmargine sus centru subsol reverse textmarginal NAME
   latime             = DIMENSION
   numberwidth        = DIMENSION
   latimetext         = DIMENSION
   distanta           = DIMENSION
   textdistance       = DIMENSION
   comandainainte     = BEFEHL
   comandadupa        = BEFEHL
   comanda            = \...##1##2
   comandatext        = \...##1
   deepertextcommand  = \...##1
   comandanumar       = \...##1
   deepnumbercommand  = \...##1
   locatie            = NAME
   criteriu           = strict pozitiv tot

```

\seteazatitluri [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```

1  ABSCHNITT          OPT
2  inherits: \seteazatitlu

```

\seteazatoleranta [...\*,...]

\* orizontal vertical foarteststrict strict tolerant foartetolerant spatiu dilatat

**\seteazatranzitiepagina** [<sup>1</sup>...]

\* reset auto start aleator NUMBER

**\seteazatype** [<sup>1</sup>...,...]<sup>2</sup> [<sup>2</sup>...,...]

1 NAME OPT  
2 optiune = mp lua xml parsed-xml nested tex context niciunul NAME  
comanda = CSNAME  
stanga = BEFEHL  
dreapta = BEFEHL  
tab = da nu NUMBER  
compact = absolut ultim tot  
escape = da nu TEXT PROCESSOR->TEXT  
stil = STYLE BEFEHL  
culoare = COLOR  
linii = da nu normal despsilabe  
spatiu = on dezactivat normal fixat dilatat

**\seteazatyping** [<sup>1</sup>...,...]<sup>2</sup> [<sup>2</sup>...,...]

1 NAME OPT  
2 margineimpara = DIMENSION  
marginepara = DIMENSION  
margine = da nu standard DIMENSION  
optiune = mp lua xml parsed-xml nested tex context niciunul NAME  
stil = STYLE BEFEHL  
culoare = COLOR  
alinie = inherits: \seteazaalinie  
linii = da nu normal despsilabe  
spatiu = on dezactivat normal fixat dilatat  
keeptogether = da nu  
inainte = BEFEHL  
dupa = BEFEHL  
strip = da nu NUMBER  
range = NUMBER NAME  
tab = da nu NUMBER  
escape = da nu TEXT PROCESSOR->TEXT  
aliniaturmator = da nu auto  
continua = da nu  
start = NUMBER  
stop = NUMBER  
pas = NUMBER  
numerotare = fisier linie nu  
blanc = inherits: \blanc

**\seteazaurl** [<sup>1</sup>...,...<sup>\*</sup>...,...]

\* stil = STYLE BEFEHL  
culoare = COLOR

**\setelementexporttag** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...]

1 NAME OPT  
2 export nature pdf  
3 inline display mixed

**\setemeasure** {<sup>1</sup>...} {<sup>2</sup>...}

1 NAME  
2 DIMENSION

**\setevalue** {<sup>1</sup>...} {<sup>2</sup>...}

1 NAME  
2 CONTENT

**\setevariable** {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...}

1 NAME  
2 KEY  
3 VALUE

**\setevariables** [<sup>1</sup>...] [<sup>2</sup>...,...<sup>2</sup>...,...]

1 NAME  
2 set = BEFEHL  
reset = BEFEHL  
KEY = VALUE

<code>\setfirstline [...]</code> *    NAME                    OPT
<code>\setflag {...}</code> *    NAME
<code>\setfont ...</code> *    FONT
<code>\setfontcolorsheme [...]</code> *    NAME
<code>\setfontfeature {...}</code> *    NAME
<code>\setfontsolution [...]</code> *    NAME
<code>\setfontstrut</code>
<code>\setgmeasure {...} {...}</code> 1    NAME 2    DIMENSION
<code>\setgvalue {...} {...}</code> 1    NAME 2    CONTENT
<code>\setgvariable {...} {...} {...}</code> 1    NAME 2    KEY 3    VALUE
<code>\setgvariables [...][...<sup>2</sup>...]</code> 1    NAME 2    set     = BEFEHL reset   = BEFEHL KEY     = VALUE
<code>\sethboxregister ...<sup>1</sup> {...}</code> 1    CSNAME NUMBER 2    CONTENT
<code>\sethyphenatedurlafter {...}</code> *    TEXT
<code>\sethyphenatedurlbefore {...}</code> *    TEXT
<code>\sethyphenatedurlnormal {...}</code> *    TEXT
<code>\sethyphenationfeatures [...,<sup>*</sup>...]</code> *    NAME reset                    OPT
<code>\setinitial [...<sup>1</sup>][...<sup>2</sup>...]</code> 1    NAME                    OPT                    OPT 2    inherits: \setupinitial

1	NAME
2	NUMMER
3	BEFEHL

\* ascuns NAME

```

1  NAME
2  NAME

```

```
1  NAME
2  NAME
```

```

1  NAME
2  NAME

```

```

1  NAME
2  titlu NAME NUMMER
3  TEXT

```

1	NAME
2	NAME

```
1  NAME
2  auto embed
3  CONTENT
```

```
* reset 1 2
```

1	NAME
2	CONTENT

```

1  NAME                                OPT
2  stanga dreapta par impar
3  inherits: \setupplayer
4  CONTENT

```

```

1  NAME
2  inherits: \setupplayer
3  inherits: \seteazainconjurat
4  CONTENT

```

```

1  NAME                                OPT
2  inherits: \setupplayerinherits: \seteazainconjurat
3  CONTENT

```

**\setlayertext** [<sup>1</sup>...] [<sup>2</sup>...<sub>OPT</sub>...] [<sup>3</sup>...<sub>OPT</sub>...] {<sup>4</sup>...}

1 NAME  
2 inherits: \setuplayer  
3 aliniere = inherits: \seteazaalinierea  
latime = DIMENSION  
stil = STYLE BEFEHL  
culoare = COLOR  
4 TEXT

**\setlinefiller** [...]

\* filler NAME

**\setlocalhsize** [...]

\* [-+]DIMENSION <sub>OPT</sub>

**\setMPlayer** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...<sub>OPT</sub>...] {<sup>4</sup>...}

1 NAME  
2 NAME  
3 inherits: \setuplayer  
4 CONTENT

**\setMPpositiongraphic** {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...<sub>OPT</sub>...}

1 NAME  
2 NAME  
3 KEY = VALUE

**\setMPpositiongraphicrange** {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...} {<sup>4</sup>...<sub>OPT</sub>...}

1 NAME  
2 NAME  
3 NAME  
4 KEY = VALUE

**\setMPtext** {<sup>1</sup>...} {<sup>2</sup>...}

1 NAME  
2 TEXT

**\setMPvariable** [<sup>1</sup>...] [<sup>2</sup>...]

1 NAME  
2 KEY = VALUE

**\setMPvariables** [<sup>1</sup>...] [<sup>2</sup>...<sub>OPT</sub>...]

1 NAME  
2 KEY = VALUE

**\setmainbodyfont**

**\setmainparbuilder** [...]

\* implicit oneline basic NAME

**\setmarker** [<sup>1</sup>...] [<sup>2</sup>...]

1 NAME  
2 NUMMER

**\setmarking** [<sup>1</sup>...] {<sup>2</sup>...}

1 BESCHRIFTUNG  
2 TEXT

**\setmathstyle** {...,\*...}

\* display text script scriptscript cramped uncramped normal impachetat mic mare NAME

**\setmeasure** {<sup>1</sup>...} {<sup>2</sup>...}

1 NAME  
2 DIMENSION

\setmessagetext {...} {...} 1 NAME 2 NAME NUMMER
\setmode {...} * NAME
\setnostrut
\setnote [...] <sup>1</sup> [..., <sup>2</sup> ...] {...} <sup>3</sup> 1 NAME 2 REFERENCE 3 TEXT
\setnotetext [...] <sup>1</sup> [..., <sup>2</sup> ...] {...} <sup>3</sup> 1 NAME 2 REFERENCE 3 TEXT
\setnotetext [...] <sup>1</sup> [..., <sup>2</sup> ...] 1 NAME 2 titlu = TEXT semncarte = TEXT lista = TEXT referinta = REFERENCE
\setnote [...] <sup>1</sup> [..., <sup>2</sup> ...] 1 NAME 2 titlu = TEXT semncarte = TEXT lista = TEXT referinta = REFERENCE
\setobject {...} <sup>1</sup> {...} <sup>2</sup> \... {...} <sup>4</sup> 1 NAME 2 NAME 3 CSNAME 4 CONTENT
\setoldstyle
\setpagegrid [...] <sup>1</sup> [...] <sup>2</sup> 1 c = NUMBER r = NUMBER optiune = niciunul 2 CONTENT
\setpagereference {...} <sup>1</sup> {..., <sup>2</sup> ...} 1 NAME 2 REFERENCE
\setpagestate [...] <sup>1</sup> [...] <sup>2</sup> 1 NAME 2 NAME NUMMER
\setpagestaterealpageno {...} <sup>1</sup> {...} <sup>2</sup> 1 NAME 2 NAME NUMMER
\setpenalties \... {...} <sup>1</sup> {...} <sup>2</sup> {...} <sup>3</sup> 1 CSNAME 2 NUMMER 3 NUMMER

<pre> \setpercentdimen {...} {...} 1  DIMENSION CSNAME 2  DIMENSION NUMBER </pre>
<pre> \setposition {...} *  NAME </pre>
<pre> \setpositionbox {...} \... {...} 1  NAME 2  CSNAME 3  CONTENT </pre>
<pre> \setpositiondata {...} {...} {...} {...} 1  NAME 2  DIMENSION 3  DIMENSION 4  DIMENSION </pre>
<pre> \setpositiondataplus {...} {...} {...} {...} {...,<sup>5</sup>...} 1  NAME 2  DIMENSION 3  DIMENSION 4  DIMENSION 5  TEXT </pre>
<pre> \setpositiononly {...} *  NAME </pre>
<pre> \setpositionplus {...} {...,<sup>2</sup>...} \... {...<sup>4</sup>} 1  NAME 2  TEXT 3  CSNAME 4  CONTENT </pre>
<pre> \setpositionstrut {...} *  NAME </pre>
<pre> \setprofile [...<sup>*</sup>] *  niciunul fixat strict halfixed quarterfixed eightsfixed NAME </pre>
<pre> \setrandomseed {...} *  NUMMER </pre>
<pre> \setreference [...,<sup>1</sup>...] [...,<sup>2</sup>...,...] 1  REFERENCE 2  KEY = VALUE </pre>
<pre> \setreferencedobject {...} {...} \... {...<sup>4</sup>} 1  NAME 2  NAME 3  CSNAME 4  CONTENT </pre>

<pre> \setregisterentry [...] [...] [...] 1  NAME 2  eticheta    = NAME     keys       = TEXT PROCESSOR-&gt;TEXT     entries    = TEXT PROCESSOR-&gt;TEXT     keys:1     = TEXT     keys:2     = TEXT     keys:3     = TEXT     entries:1  = TEXT     entries:2  = TEXT     entries:3  = TEXT     alternativ  = TEXT 3  KEY  = VALUE </pre>
<pre> \setreplacement [...] *  reset NAME </pre>
<pre> \setrigidcolumnbalance ... *  CSNAME NUMMER </pre>
<pre> \setrigidcolumnhsize {...} {...} {...} 1  DIMENSION 2  DIMENSION 3  NUMMER </pre>
<pre> \setscript [...] *  hangul hanzi nihongo ethiopic thai test NAME </pre>
<pre> \setsectionblock [...] [...] 1  NAME 2  semncarte = TEXT </pre>
<pre> \setsimplecolumnhsize [...]*[...][...] *  n      = NUMMER     latime = DIMENSION     distanta = DIMENSION     linii  = NUMMER </pre>
<pre> \setsmallbodyfont </pre>
<pre> \setsmallcaps </pre>
<pre> \setstackbox {...} {...} {...} 1  NAME 2  NAME 3  CONTENT </pre>
<pre> \setstructurepageregister [...] [...] [...] 1  NAME 2  eticheta    = NAME     keys       = TEXT PROCESSOR-&gt;TEXT     entries    = TEXT PROCESSOR-&gt;TEXT     keys:1     = TEXT     keys:2     = TEXT     keys:3     = TEXT     entries:1  = TEXT     entries:2  = TEXT     entries:3  = TEXT     alternativ  = TEXT 3  KEY  = VALUE </pre>
<pre> \setstrut </pre>
<pre> \setsuperiors </pre>



<pre> \setssystemmode {...} *   NAME </pre>
<pre> \settabular </pre>
<pre> \settaggedmetadata [...,*...,...] *   KEY  =  VALUE </pre>
<pre> \settextcontent [...] [...] [...] [...] [...] 1   sus antet text subsol subsol      OPT      OPT 2   text margine bordura 3   stanga centru dreapta 4   data numarpagina BESCHRIFTUNG TEXT BEFEHL 5   data numarpagina BESCHRIFTUNG TEXT BEFEHL </pre>
<pre> \settightobject {...} {...} \... {...} 1   NAME 2   NAME 3   CSNAME 4   CONTENT </pre>
<pre> \settightreferencedobject {...} {...} \... {...} 1   NAME 2   NAME 3   CSNAME 4   CONTENT </pre>
<pre> \settightunreferencedobject {...} {...} \... {...} 1   NAME 2   NAME 3   CSNAME 4   CONTENT </pre>
<pre> \settrialtypesetting </pre>
<pre> \setuevalue {...} {...} 1   NAME 2   CONTENT </pre>
<pre> \setugvalue {...} {...} 1   NAME 2   CONTENT </pre>
<pre> \setunreferencedobject {...} {...} \... {...} 1   NAME 2   NAME 3   CSNAME 4   CONTENT </pre>
<pre> \setupalternativestyles [...,*...,...] *   metoda =  normal auto </pre>

\setupattachment [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
2 titlu = TEXT  
subtitlu = TEXT  
autor = TEXT  
fisier = FILE  
nume = NAME  
buffer = BUFFER  
stare = start stop  
metoda = normal ascuns  
simbol = Graph Paperclip Pushpin Default  
latime = ajustat DIMENSION  
inaltime = ajustat DIMENSION  
inaltime = ajustat DIMENSION  
culoare = COLOR  
textlayer = NAME  
locatie = bordurastanga borduradreaapta inmarginestanga marginedreaapta text inalt niciunul  
distanta = DIMENSION

\setupattachments [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
2 inherits: \setupattachment

\setupbackend [...<sup>\*</sup>,...]

\* export = da FILE  
xhtml = FILE  
fisier = FILE  
intent = Coated FOGRA39 (ISO 12647-2:2004) GRACoL2006\_Coated1v2.icc ISO Coated v2 300 ISO Coated v2 (ECI)  
ISOnewspaper26v4 ISOnewspaper26v4\_gr ISO Uncoated ISO Uncoated Yellowish ISO Web Coated Japan Color  
2001 Coated Japan Color 2002 Newspaper Japan Web Coated (Ad) SNAP 2007 SWOP2006\_Coated3v2.icc SWOP2006\_Coated5v2.icc  
Uncoated FOGRA29 (ISO 12647-2:2004) Web Coated FOGRA28 (ISO 12647-2:2004) PSR\_LWC\_PLUS\_V2\_PT PSR\_LWC\_STD\_V2\_PT  
PSR\_SC\_PLUS\_V2\_PT PSR\_SC\_STD\_V2\_PT PSRgravureMF  
spatiu = da nu  
xmpfile = FILE  
format = version implicit PDF/X-1a:2001 PDF/X-1a:2003 PDF/X-3:2002 PDF/X-3:2003 PDF/X-4 PDF/X-4p PDF/X-5g  
PDF/X-5pg PDF/X-5n PDF/A-1a:2005 PDF/A-1b:2005 PDF/A-2a PDF/A-3a PDF/UA-1  
nivel = NUMMER  
optiune = totdeauna niciodata  
profile = FILE

\setupbar [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
2 culoare = COLOR  
continua = da nu tot  
gol = da nu  
unitate = ex em pt in cm mm sp bp pc dd cc nc  
order = primplan fundal  
grosimerigla = DIMENSION  
metoda = NUMMER  
offset = NUMMER  
dy = NUMMER  
max = NUMMER  
foregroundstyle = STYLE BEFEHL  
foregroundcolor = COLOR  
mp = NAME  
stanga = TEXT  
dreapta = TEXT

\setupbars [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
2 inherits: \setupbar

\setupbleeding [...<sup>\*</sup>,...]

\* latime = DIMENSION  
inaltime = DIMENSION  
offset = DIMENSION  
hoffset = DIMENSION  
voffset = DIMENSION  
locatie = t b l r bl lb br rb tl lt tr rt  
dilatata = da nu  
pagina = da nu

\setupbookmark [...,..<sup>1</sup>...,...]

\* fortat = da nu  
numar = da nu  
numberseparatorset = NAME  
numberconversionset = NAME  
numberstarter = BEFEHL  
numberstopper = BEFEHL  
numbersegments = NUMBER NUMBER:NUMBER NUMBER:\* NUMBER:tot ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:\* ABSCHNITT:tot  
sectionblock = da nu

\setupbtx [...,..<sup>1</sup>...,..<sup>2</sup>...,...]

1 NAME <sup>OPT</sup>  
2 specification = implicit apa aps NAME  
dataset = implicit NAME  
comanda = \...##1  
stanga = BEFEHL  
dreapta = BEFEHL  
authorconversion = normal normalshort normalinverted invertedshort short  
etallimit = NUMBER  
etaldisplay = NUMBER  
etaloption = ultim  
stopper = initials  
interactiune = start stop numar text pagina tot  
alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears  
authornum authoryear  
sorttype = normal reverse  
compress = da nu  
implicit = implicit NAME  
stil = STYLE BEFEHL  
culoare = COLOR

\setupbtxdataset [...,..<sup>1</sup>...,..<sup>2</sup>...,...]

1 NAME <sup>OPT</sup>  
2 language = SPRACHE

\setupbtxlist [...,..<sup>1</sup>...,..<sup>2</sup>...,...]

1 NAME <sup>OPT</sup>  
2 inherits: \seteazalista

\setupbtxregister [...,..<sup>1</sup>...,..<sup>2</sup>...,...]

1 NAME <sup>OPT</sup>  
2 stare = start stop  
dataset = NAME  
field = keyword range numarpagina autor  
register = NAME  
metoda = once  
alternativ = normalshort invertedshort  
stil = STYLE BEFEHL  
culoare = COLOR

\setupbtxrendering [...,..<sup>1</sup>...,..<sup>2</sup>...,...]

1 NAME <sup>OPT</sup>  
2 staretext = start stop  
pagestate = start stop  
separator = BEFEHL  
criteriu = precedent cite aici tot niciunul  
filter = TEXT  
specification = NAME  
titlu = TEXT  
inainte = BEFEHL  
dupa = BEFEHL  
dataset = NAME  
metoda = dataset fortat local global niciunul  
sorttype = short dataset lista referinta folosit implicit cite index  
repetat = da nu  
group = NAME  
numerotare = da nu num index tag short pagina

\setupbtx [...]

\* NAME

**\setupbutton** [...<sup>1</sup>,...] [...<sup>2</sup>...,...]

1 NAME OPT  
2 stare = start stop  
aceeasipagina = da nu gol niciunul normal implicit  
stil = STYLE BEFEHL  
culoare = COLOR  
culoarecontrast = COLOR  
alternativ = ascuns  
inherits: \seteazainconjurat

**\setupcharacterkerning** [...<sup>1</sup>,...] [...<sup>2</sup>...,...]

1 NAME OPT  
2 factor = max NUMBER  
latime = DIMENSION  
features = NAME  
stil = STYLE BEFEHL  
culoare = COLOR

**\setupcharacterspacing** [...<sup>1</sup>.] [...<sup>2</sup>.] [...<sup>3</sup>...,...]

1 NAME OPT  
2 NUMMER  
3 stanga = NUMMER  
dreapta = NUMMER  
alternativ = 0 1

**\setupchemical** [...<sup>1</sup>,...] [...<sup>2</sup>...,...]

1 NAME OPT  
2 strut = da nu auto cap ajustat linie implicit CHARACTER  
latime = ajustat niciunul NUMMER  
inaltime = ajustat niciunul NUMMER  
stanga = ajustat niciunul NUMMER  
dreapta = ajustat niciunul NUMMER  
sus = ajustat niciunul NUMMER  
jos = ajustat niciunul NUMMER  
scala = mic mediu mare normal NUMMER  
rotatie = NUMMER  
symalinie = auto  
axa = on dezactivat  
culoareframe = COLOR  
grosimerigla = DIMENSION  
offset = DIMENSION  
unitate = DIMENSION  
factor = NUMMER  
frame = on dezactivat  
culoarerigla = COLOR  
fonttext = inherits: \seteazafonttext  
dimensiune = mic mediu mare  
stil = STYLE BEFEHL  
culoare = COLOR

**\setupchemicalframed** [...<sup>1</sup>,...] [...<sup>2</sup>...,...]

1 NAME OPT  
2 inherits: \seteazainconjurat

**\setupcollector** [...<sup>1</sup>,...] [...<sup>2</sup>...,...]

1 NAME OPT  
2 rotatie = stanga dreapta intern extern NUMMER  
colt = stanga centru dreapta sus subsol  
x = DIMENSION  
y = DIMENSION  
hoffset = DIMENSION  
voffset = DIMENSION  
locatie = stanga centru dreapta sus subsol linie l c r m t b g  
stare = start stop

**\setupcolumnspan** [...<sup>\*</sup>...,...]

\* n = NUMMER  
inherits: \seteazainconjurat

\setupcombination [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
2 nx = NUMBER  
ny = NUMBER  
latime = ajustat DIMENSION  
inaltime = ajustat DIMENSION  
locatie = stanga centru dreapta sus subsol  
distanta = DIMENSION  
alternativ = eticheta text  
alinieri = inherits: \seteazaalinierea  
continua = da nu  
inainte = BEFEHL  
dupa = BEFEHL  
intre = BEFEHL  
stil = STYLE BEFEHL  
culoare = COLOR

\setupcounter [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
2 start = NUMBER  
counter = NAME  
metoda = pagina  
stare = start stop  
mod = bypagina byblock bytext byantet byABSCHNITT  
prefix = da nu  
prefixseparatorset = NAME  
prefixconversion = NAME  
prefixconversionset = NAME  
prefixstarter = BEFEHL PROCESSOR->BEFEHL  
prefixstopper = BEFEHL PROCESSOR->BEFEHL  
prefixset = NAME  
prefixsegments = NUMBER NUMBER:NUMBER NUMBER:\* NUMBER:tot ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:\* ABSCHNITT:tot  
numberorder = reverse  
numberseparatorset = NAME  
numberconversion = NAME  
numberconversionset = NAME  
numberstarter = BEFEHL PROCESSOR->BEFEHL  
numberstopper = BEFEHL PROCESSOR->BEFEHL  
numbersegments = NUMBER NUMBER:NUMBER NUMBER:\* NUMBER:tot  
type = primul precedent urmatorul ultim numar  
criteriu = strict pozitiv tot  
prefixconnector = BEFEHL PROCESSOR->BEFEHL

\setupdataset [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
2 intarziere = da nu

\setupdelimitedtext [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
2 inainte = BEFEHL  
dupa = BEFEHL  
language = local global SPRACHE  
metoda = font  
repeta = da nu  
locatie = text paragraf margine  
stanga = BEFEHL  
mijloc = BEFEHL  
dreapta = BEFEHL  
nextleft = BEFEHL  
nextright = BEFEHL  
spatiuinainte = inherits: \blanc  
spatiudupa = inherits: \blanc  
marginestanga = da nu standard DIMENSION  
marginedreapta = da nu standard DIMENSION  
aliniat = inherits: \seteazaaliniat  
aliniaturmator = da nu auto  
stil = STYLE BEFEHL  
culoare = COLOR  
stilsimbol = STYLE BEFEHL  
culoaresimbol = COLOR

\setupdescription [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

```

1  NAME          OPT
2  titlu          = da nu
   nivel          = NUMMER
   text           = TEXT
   headcommand    = \...##1
   inainte        = BEFEHL
   dupa           = BEFEHL
   intre          = BEFEHL
   alternativ      = stanga dreapta inmargin instanga indreapta margine marginestanga marginedreapta innermargin
                   outermargin serried suspendat sus comanda NAME
   aliniere       = inherits: \seteazaalinierea
   headalign      = inherits: \seteazaalinierea
   aliniat        = inherits: \seteazaaliniat
   display        = da nu
   aliniaturmator = da nu auto
   latime         = ajustat broad linie DIMENSION
   distanta       = niciunul DIMENSION
   dilatata       = NUMMER
   shrink         = NUMMER
   suspenda       = ajustat broad niciunul margine NUMMER
   closesymbol    = BEFEHL
   closecommand   = \...##1
   expansiune     = da nu xml
   referenceprefix = + - TEXT
   exemplu        = TEXT
   margine        = da nu standard DIMENSION
   stil           = STYLE BEFEHL
   culoare        = COLOR
   stiltitlu      = STYLE BEFEHL
   culoaretitlu   = COLOR

```

\setupdirections [...,<sup>\*</sup>...,...]

```

*  bidi          = on dezactivat local global
   metoda        = unu doi implicit
   fences        = da nu
   break         = ambele inainte

```

\setupdocument [...,<sup>\*</sup>...,...]

```

*  inainte       = BEFEHL
   dupa          = BEFEHL
   metadata:author = TEXT
   metadata:title  = TEXT
   metadata:subject = TEXT
   metadata:keywords = TEXT
   KEY           = VALUE

```

\setupeffect [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

```

1  NAME          OPT
2  metoda        = niciunul comanda
   dilatata      = NUMMER
   grosimerigla  = NUMMER
   alternativ     = normal intern extern ambele ascuns dilatata

```

`\setupenumeration [...1,...] [...2,...]`

```
1 NAME OPT
2 titlu = da nu
  numar = da nu
  comandanumar = \...##1
  distantatitlu = DIMENSION
  stiltitlu = STYLE BEFEHL
  culoaretitlu = COLOR
  titlecommand = \...##1
  titleleft = BEFEHL
  titleright = BEFEHL
  stanga = BEFEHL
  dreapta = BEFEHL
  simbol = BEFEHL
  starter = BEFEHL
  stopper = BEFEHL
  cuplare = NAME
  counter = NAME
  nivel = NUMMER
  text = TEXT
  headcommand = \...##1
  inainte = BEFEHL
  dupa = BEFEHL
  intre = BEFEHL
  alternativ = stanga dreapta inmargin instanga indreapta margine marginestanga marginedreapta innermargin
              outermargin serried suspendat sus comanda NAME
  aliniere = inherits: \seteazaalinierea
  headalign = inherits: \seteazaalinierea
  aliniat = inherits: \seteazaaliniat
  display = da nu
  aliniaturmator = da nu auto
  latime = ajustat broad linie DIMENSION
  distanta = niciunul DIMENSION
  dilatat = NUMMER
  shrink = NUMMER
  suspenda = ajustat broad niciunul margine NUMMER
  closesymbol = BEFEHL
  closecommand = \...##1
  expansiune = da nu xml
  referenceprefix = + - TEXT
  exemplu = TEXT
  margine = da nu standard DIMENSION
  stil = STYLE BEFEHL
  culoare = COLOR
  stiltitlu = STYLE BEFEHL
  culoaretitlu = COLOR
  inherits: \setupcounter
```

`\setupenv [...*,...]`

```
* set = BEFEHL
  reset = BEFEHL
  KEY = VALUE
```

`\setupexport [...*,...]`

```
* aliniere = flushleft centru flushright normal
  fonttext = DIMENSION
  latime = DIMENSION
  titlu = TEXT
  subtitlu = TEXT
  autor = TEXT
  alternativ = html div
  properties = da nu
  hyphen = da nu
  cssfile = FILE
  primapagina = FILE
  ultimapagina = FILE
```

\setupexternalfigure [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```

1  NAME                                OPT
2  latime                             = DIMENSION
   inaltime                           = DIMENSION
   eticheta                            = NAME
   pagina                             = NUMMER
   obiect                              = da nu
   prefix                             = TEXT
   metoda                             = pdf mps jpg png jp2 jbig svg eps gif tif mov buffer tex cld auto
   controale                           = da nu
   previzualizare                     = da nu
   mask                               = niciunul
   rezolutie                           = NUMMER
   culoare                             = COLOR
   arguments                           = TEXT
   repeta                              = da nu
   factor                             = ajustat broad max auto implicit
   hfactor                             = ajustat broad max auto implicit
   factorw                             = ajustat broad max auto implicit
   latimemaxima                       = DIMENSION
   inaltimemaxima                     = DIMENSION
   equalwidth                          = DIMENSION
   equalheight                         = DIMENSION
   scala                              = NUMMER
   xscala                             = NUMMER
   yscala                             = NUMMER
   s                                  = NUMMER
   sx                                  = NUMMER
   sy                                  = NUMMER
   linii                              = NUMMER
   locatie                             = local global implicit
   director                           = PATH
   optiune                             = test incadrat gol
   foregroundcolor                     = COLOR
   reset                              = da nu
   fundal                             = culoare primplan NAME
   frame                              = on dezactivat
   culoarefundal                       = COLOR
   xmax                               = NUMMER
   ymax                               = NUMMER
   frames                             = on dezactivat
   interactiune                        = da tot niciunul referinta layer semncarte
   fonttext                           = DIMENSION
   comment                             = BEFEHL TEXT
   dimensiune                          = niciunul media crop trim art
   cache                              = PATH
   resources                           = PATH
   display                             = FILE
   conversie                           = TEXT
   order                              = LISTE
   crossreference                      = da nu NUMMER

```

\setupexternalsoundtracks [...<sup>\*</sup>,...]

\* optiune = repetat

\setupfieldbody [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```

1  NAME                                OPT
2  category = NAME
   inherits: \setupfieldcategory

```



**\setupfieldcategory** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```
1 NAME OPT
2 start = NUMMER
  stil = STYLE BEFEHL
  culoare = COLOR
  type = radio sub text linie push check signature
  values = TEXT
  implicit = TEXT
  culoareframecamp = COLOR
  culoarefundalcamp = COLOR
  latime = DIMENSION
  inaltime = DIMENSION
  inaltime = DIMENSION
  aliniere = stanga centru dreapta flushleft center flushright
  n = NUMMER
  simbol = NAME
  fieldlayer = NAME
  optiune = readonly obligatoriu protejat sortat nedisponibil nocheck fixat fisier ascuns tiparibil auto
  clickintru = REFERENCE
  clickies = REFERENCE
  regiuneintrare = REFERENCE
  regiuneiesire = REFERENCE
  dupatasta = REFERENCE
  format = REFERENCE
  verifica = REFERENCE
  calculeaza = REFERENCE
  focusin = REFERENCE
  focusout = REFERENCE
  openpage = REFERENCE
  closepage = REFERENCE
```

**\setupfieldcontentframed** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```
1 NAME OPT
2 inherits: \seteazainconjuratinherits: \setupfieldcategory
```

**\setupfieldlabelframed** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```
1 NAME OPT
2 inherits: \seteazainconjurat
```

**\setupfieldtotalframed** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```
1 NAME OPT
2 inainte = BEFEHL
  dupa = BEFEHL
  intre = BEFEHL
  distanta = DIMENSION
  alternativ = reset eticheta incadrat orizontal vertical
  inherits: \seteazainconjurat
```

**\setupfiller** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```
1 NAME OPT
2 marginestanga = DIMENSION
  marginedreapta = DIMENSION
  stanga = BEFEHL
  dreapta = BEFEHL
  alternativ = simbol dilatat rigla spatiu
  metoda = local global centru broad
  latime = DIMENSION
  inaltime = DIMENSION
  inaltime = DIMENSION
  offset = DIMENSION
  distanta = DIMENSION
  aliniere = stanga dreapta centru flushleft flushright intern extern
  simbol = BEFEHL
  stil = STYLE BEFEHL
  culoare = COLOR
```

**\setupfirstline** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```
1 NAME OPT
2 n = NUMMER
  alternativ = implicit linie cuvant
  stil = STYLE BEFEHL
  culoare = COLOR
```

\setupfittingpage [...<sup>1</sup>,...] [...<sup>2</sup>,...,...]

1 NAME OPT  
2 pagestate = start stop  
comanda = \...##1  
margine = pagina  
scala = NUMMER  
hartie = auto implicit NAME  
inherits: \seteazainconjurat

\setupfloatcaption [...<sup>1</sup>,...] [...<sup>2</sup>,...,...]

1 NAME OPT  
2 suffix = BEFEHL  
suffixseparator = BEFEHL  
suffixstopper = BEFEHL  
locatie = stanga dreapta centru jos inalt grila overlay intern extern innermargin outermargin marginestanga  
margin dreapta lefthanging righthanging suspenda sus subsol dilatat tolerant foartetolerant  
niciunul implicit  
comanda = \...##1  
comandanumar = \...##1  
comandatext = \...##1  
spatiuinainte = inherits: \blanc  
spaceinbetween = inherits: \blanc  
spatiudupa = inherits: \blanc  
distanta = DIMENSION  
headseparator = TEXT  
intre = BEFEHL  
stil = STYLE BEFEHL  
culoare = COLOR  
offsetsus = DIMENSION  
offsetjos = DIMENSION  
numar = da nu niciunul  
group = TEXT  
marginestanga = DIMENSION  
margin dreapta = DIMENSION  
innermargin = DIMENSION  
outermargin = DIMENSION  
alinie = inherits: \seteazaalinierea  
latime = ajustat max DIMENSION  
latimeminima = ajustat DIMENSION  
latimemaxima = DIMENSION  
inherits: \setupcounter

\setupfontexpansion [...<sup>1</sup>,...] [...<sup>2</sup>,...,...]

1 NAME  
2 vector = NAME  
factor = NUMMER  
dilatat = NUMMER  
shrink = NUMMER  
pas = NUMMER

\setupfontprotrusion [...<sup>1</sup>,...] [...<sup>2</sup>,...,...]

1 NAME  
2 vector = NAME  
factor = NUMMER  
stanga = NUMMER  
dreapta = NUMMER

\setupfonts [...<sup>\*</sup>,...,...]

\* language = nu auto

\setupfontsolution [...<sup>1</sup>,...] [...<sup>2</sup>,...,...]

1 NAME OPT  
2 goodies = FILE  
solution = NAME  
less = NAME  
more = NAME  
metoda = preroll split normal reverse aleator  
criteriu = NUMMER

`\setupformula [...1,...] [...2...,...]`

```
1 NAME OPT
2 locatie = stanga dreapta
alinieri = stanga centru dreapta flushleft center flushright normal
split = da nu pagina
strut = da nu
distanta = DIMENSION
stanga = BEFEHL
dreapta = BEFEHL
spatiuinainte = inherits: \blanc
spatiudupa = inherits: \blanc
comandanumar = \...##1
culoare = COLOR
stilnumar = STYLE BEFEHL
culoarenumar = COLOR
optiune = impachetat tight centru incadrat adancime linie jumatatelinie -linie -jumatatelinie inherits: \seteazafonttext
margine = da nu standard DIMENSION
marginestanga = DIMENSION
marginedreapta = DIMENSION
alternativ = NAME
aliniaturmator = da nu auto
grid = inherits: \snaptogrid
frame = numar
suspenda = niciunul auto
expansiune = da nu xml
referenceprefix = + - TEXT
xmlsetup = NAME
catcodes = NAME
inherits: \setupcounter
```

`\setupformulaframed [...1,...] [...2...,...]`

```
1 NAME OPT
2 inherits: \seteazainconjurat
```

`\setupframedcontent [...1,...] [...2...,...]`

```
1 NAME OPT
2 stanga = BEFEHL
dreapta = BEFEHL
leftoffser = DIMENSION
offsetdreapta = DIMENSION
offsetsus = DIMENSION
offsetjos = DIMENSION
corectielinie = da nu
inherits: \seteazainconjurat
```

`\setupframedtable [...1] [...2...,...]`

```
1 NAME OPT
2 inainte = BEFEHL
dupa = BEFEHL
intre = BEFEHL
distanta = DIMENSION
inherits: \seteazainconjurat
```

`\setupframedtablecolumn [...1] [...2] [...3...,...]`

```
1 NAME OPT
2 NUMMER fiecare
3 inherits: \seteazainconjurat
```

`\setupframedtablerow [...1] [...2] [...3...,...]`

```
1 NAME OPT
2 NUMMER fiecare
3 inherits: \seteazainconjurat
```

```

\setupframedtext [...1,...] [...2,...]
1  NAME                      OPT
2  stanga                    = BEFEHL
   dreapta                   = BEFEHL
   intern                     = BEFEHL
   locatie                   = stanga dreapta centru niciunul
   corectieadancime          = on dezactivat
   fonttext                   = inherits: \seteazafonttext
   aliniat                    = inherits: \seteazaaliniat
   stil                       = STYLE BEFEHL
   culoare                    = COLOR
   inherits: \seteazainconjuratinherits: \setupplacement

```

```

\setupglobalreferenceprefix [...]
*  + - TEXT

```

```

\setupheadalternative [...1,...] [...2,...]
1  NAME                      OPT
2  alternativ                  = orizontal vertical undeva
   renderingsetup            = NAME

```

```

\setuphelp [...1,...] [...2,...]
1  NAME                      OPT
2  inherits: \seteazainconjurat

```

```

\setuphigh [...1,...] [...2,...]
1  NAME                      OPT
2  distanta                  = DIMENSION
   up                        = DIMENSION
   stil                       = STYLE BEFEHL
   culoare                    = COLOR

```

```

\setuphighlight [...1,...] [...2,...]
1  NAME                      OPT
2  comanda                   = da nu
   stil                       = STYLE BEFEHL
   culoare                    = COLOR

```

```

\setuphyphenation [...*,...]
*  metoda = original tex implicit hyphenate expanded traditional niciunul

```

```

\setupindentedtext [...1,...] [...2,...]
1  NAME                      OPT
2  inainte                   = BEFEHL
   dupa                      = BEFEHL
   distanta                   = DIMENSION
   exemplu                    = TEXT
   text                       = TEXT
   latime                     = ajustat broad DIMENSION
   separator                  = BEFEHL
   stil                       = STYLE BEFEHL
   culoare                    = COLOR
   stiltitlu                  = STYLE BEFEHL
   culoaretitlu               = COLOR

```

```

\setupinitial [...1,...] [...2,...]
1  NAME                      OPT
2  n                          = NUMMER
   m                          = NUMMER
   inainte                    = BEFEHL
   distanta                   = DIMENSION
   hoffset                    = DIMENSION
   voffset                    = linie DIMENSION
   stil                       = STYLE BEFEHL
   culoare                    = COLOR
   font                       = FONT
   text                       = TEXT
   locatie                    = margine text
   metoda                     = primul ultim auto niciunul

```

\setupinsertion [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
2 locatie = pagina text coloane firstcolumn lastcolumn

\setupitaliccorrection [...,\*...]

\* text totdeauna global niciunul

\setupitemgroup [...<sup>1</sup>] [...<sup>2</sup>,...] [...<sup>3</sup>,...] [...<sup>4</sup>,...]

1 NAME OPT OPT OPT OPT  
2 fiecare NUMMER  
3 intro aleator continuu impachetat autointro broad text inainte dupa faraalb margine inmargin lamargine intext  
larg ajustat nofit paragraf unit serried stopper nostopper despachetat repetat norepeat reverse coloane unu doi  
trei patru cinci six seven eight nine standard NUMMER\*broad NUMMER\*serried orizontal NAME  
4 inainte = BEFEHL  
dupa = BEFEHL  
intre = BEFEHL  
inaintetitlu = BEFEHL  
dupatitlu = BEFEHL  
textstanga = BEFEHL  
textdreapta = BEFEHL  
stanga = BEFEHL  
dreapta = BEFEHL  
factor = NUMMER  
pas = DIMENSION  
latime = DIMENSION  
distanta = DIMENSION  
margine = da nu standard DIMENSION  
marginestanga = da nu standard DIMENSION  
marginedreapta = da nu standard DIMENSION  
aliniere = inherits: \seteazaalinierea  
aliniat = inherits: \seteazaaliniat  
start = NUMMER  
symaliniere = stanga centru dreapta flushleft center flushright  
simbol = NAME  
n = NUMMER  
aliniaturmator = da nu auto  
intern = BEFEHL  
comanda = CSNAME  
elemente = NUMMER  
latimemaxima = DIMENSION  
itemalign = stanga dreapta centru flushleft flushright intern extern  
alignsymbol = da nu  
textdistance = mic mediu mare niciunul spatiu DIMENSION  
punestopper = da nu  
stil = STYLE BEFEHL  
culoare = COLOR  
stiltitlu = STYLE BEFEHL  
culoaretitlu = COLOR  
stilmarcaj = STYLE BEFEHL  
culoaremarcaj = COLOR  
stilsimbol = STYLE BEFEHL  
culoaresimbol = COLOR  
grid = inherits: \definegridsnapping  
inherits: \setupcounter

**\setupitemgroup** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```

1  NAME NAME:NUMBER      OPT
2  inainte                = BEFEHL
   dupa                   = BEFEHL
   intre                  = BEFEHL
   inaintetitlu           = BEFEHL
   dupatitlu              = BEFEHL
   textstanga             = BEFEHL
   textdreapta            = BEFEHL
   stanga                 = BEFEHL
   dreapta                = BEFEHL
   factor                 = NUMBER
   pas                    = DIMENSION
   latime                 = DIMENSION
   distanta               = DIMENSION
   optiune                = intro aleator continuu impachetat autointro broad text inainte dupa faraalb margine inmargin
                           lamargine intext larg ajustat nofit paragraf unit serried stopper despachetat repetat norepeat
                           reverse coloane unu doi trei patru cinci six seven eight nine standard NUMBER*broad NUMBER*serried
                           orizontal NAME
   margine                = da nu standard DIMENSION
   marginestanga          = da nu standard DIMENSION
   marginedreapta         = da nu standard DIMENSION
   aliniere               = inherits: \seteazaalinierea
   aliniat                = inherits: \seteazaaliniat
   start                  = NUMBER
   symaliniere            = stanga centru dreapta flushleft center flushright
   simbol                 = NAME
   n                      = NUMBER
   aliniaturmator         = da nu auto
   intern                 = BEFEHL
   comanda                = CSNAME
   elemente               = NUMBER
   latimemaxima           = DIMENSION
   itemalign              = stanga dreapta centru flushleft flushright intern extern
   alignsymbol            = da nu
   textdistance           = mic mediu mare niciunul spatiu DIMENSION
   punestopper            = da nu
   stil                   = STYLE BEFEHL
   culoare                = COLOR
   stiltitlu              = STYLE BEFEHL
   culoaretitlu           = COLOR
   stilmarcaj             = STYLE BEFEHL
   culoaremarcaj          = COLOR
   stilsimbol             = STYLE BEFEHL
   culoaresimbol          = COLOR
   grid                   = inherits: \definegridsnapping
inherits: \setupcounter

```

**\setareITEMGROUP** [...<sup>1</sup>,...] [...<sup>2</sup>,...] [...<sup>3</sup>,...]

```

1  fiecare NUMBER      OPT      OPT      OPT
2  inherits: \setupitemgroup
3  inherits: \setupitemgroup
instances: itemize

```

**\setareitemize** [...<sup>1</sup>,...] [...<sup>2</sup>,...] [...<sup>3</sup>,...]

```

1  fiecare NUMBER      OPT      OPT      OPT
2  inherits: \setupitemgroup
3  inherits: \setupitemgroup

```

\setuplabel [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```

1  NAME          OPT
2  titlu          = da nu
   numar          = da nu
   comandanumar   = \...##1
   distantatitlu  = DIMENSION
   stiltitlu      = STYLE BEFEHL
   culoaretitlu   = COLOR
   titlecommand   = \...##1
   titleleft      = BEFEHL
   titleright     = BEFEHL
   stanga         = BEFEHL
   dreapta        = BEFEHL
   simbol         = BEFEHL
   starter        = BEFEHL
   stopper        = BEFEHL
   cuplare        = NAME
   counter        = NAME
   nivel          = NUMMER
   text           = TEXT
   headcommand    = \...##1
   inainte        = BEFEHL
   dupa           = BEFEHL
   intre          = BEFEHL
   alternativ      = stanga dreapta inmargin instanga indreapta margine marginestanga marginedreapta innermargin
                   outermargin serried suspendat sus comanda intext NAME
   aliniere       = inherits: \seteazaalinierea
   headalign      = inherits: \seteazaalinierea
   aliniat        = inherits: \seteazaaliniat
   display        = da nu
   aliniaturmator = da nu auto
   latime         = ajustat broad linie DIMENSION
   distanta       = niciunul DIMENSION
   dilatat        = NUMMER
   shrink         = NUMMER
   suspenda       = ajustat broad niciunul margine NUMMER
   closesymbol    = BEFEHL
   closecommand   = \...##1
   expansiune     = da nu xml
   referenceprefix = + - TEXT
   exemplu        = TEXT
   margine        = da nu standard DIMENSION
   stil           = STYLE BEFEHL
   culoare        = COLOR
   stiltitlu      = STYLE BEFEHL
   culoaretitlu   = COLOR
   inherits: \setupcounter

```

\setuplayer [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```

1  NAME          OPT
2  stare         = start stop continuu urmatorul repetat
   optiune       = test
   pagina        = NUMMER
   latime        = DIMENSION
   inaltime      = DIMENSION
   region        = NAME
   rotatie       = stanga dreapta intern extern NUMMER
   pozitie       = da nu overlay
   hoffset       = max DIMENSION
   voffset       = max DIMENSION
   offset        = DIMENSION
   dx            = DIMENSION
   dy            = DIMENSION
   sx            = NUMMER
   sy            = NUMMER
   x             = DIMENSION
   y             = DIMENSION
   colt          = stanga centru dreapta sus subsol
   locatie       = grila stanga centru dreapta sus subsol linie l c r m t b g
   linie         = NUMMER
   coloana       = NUMMER
   directie      = normal reverse
   douafete      = da nu
   metoda        = ajustat overlay
   repeta        = da
   preset        = lefttop righttop leftbottom rightbottom centru middletop middlebottom middleleft middleright lefttopleft
                   lefttopright NAME

```

`\setuplayeredtext [...1,...] [...2,...]`

```
1 NAME OPT
2 stil = STYLE BEFEHL
  culoare = COLOR
  inherits: \seteazainconjurat
```

`\setuplayouttext [...1] [...2] [...3,...]`

```
1 sus antet text subsol subsolOPT
2 text margine bordura
3 stare = start stop gol inalt niciunul normal faramarcare NAME
  stil = STYLE BEFEHL
  culoare = COLOR
  strut = da nu
  n = NUMMER
  inainte = BEFEHL
  dupa = BEFEHL
  stilstanga = STYLE BEFEHL
  stildreapta = STYLE BEFEHL
  culoarestanga = COLOR
  culoaredreapta = COLOR
  latime = DIMENSION
  latimestanga = DIMENSION
  marginedreapta = DIMENSION
```

`\setuplinefiller [...1,...] [...2,...]`

```
1 NAME OPT
2 locatie = stanga dreapta ambele
  scop = stanga dreapta local
  mp = NAME
  inaltime = DIMENSION
  inaltime = DIMENSION
  distanta = DIMENSION
  threshold = DIMENSION
  grosimerigla = DIMENSION
  inainte = BEFEHL
  dupa = BEFEHL
  culoare = COLOR
  stiltext = STYLE BEFEHL
  culoaretext = COLOR
  aliniere = inherits: \seteazaalinierea
```

`\setuplinefillers [...1,...] [...2,...]`

```
1 NAME OPT
2 inherits: \setuplinefiller
```

`\setuplinenote [...1,...] [...2,...]`

```
1 NAME OPT
2 compress = da nu
  compressmethod = separator stopper spatiu
  compressseparator = BEFEHL
  compressdistance = DIMENSION
  inherits: \setupnote
```



**\setuplinetable** [<sup>1</sup>...] [<sup>2</sup>...] [...,<sup>3</sup>...,...]

```
1  r c          OPT      OPT
2  impar par antet NUMBER
3  linii        = ajustat NUMBER
   inainte      = BEFEHL
   dupa         = BEFEHL
   intre       = BEFEHL
   dilatata    = da nu DIMENSION
   latimemaxima = ajustat DIMENSION
   nstanga     = NUMBER
   n           = NUMBER
   repeta      = da nu
   nx          = NUMBER
   latime      = DIMENSION
   inaltime    = ajustat linie DIMENSION
   distanta    = DIMENSION
   offsetstanga = DIMENSION
   offsetdreapta = DIMENSION
   aliniere    = inherits: \seteazaalinierea
   fundal      = culoare
   culoarefundal = COLOR
   xheight     = max DIMENSION
   xdepth      = max DIMENSION
   stil        = STYLE BEFEHL
   culoare     = COLOR
```

**\setuplistalternative** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

```
1  NAME          OPT
2  inainte      = BEFEHL
   dupa         = BEFEHL
   comanda      = \...##1##2##3
   renderingsetup = NAME
   latime       = DIMENSION
   distanta     = DIMENSION
   dilatata    = DIMENSION
   filler       = BEFEHL
```

**\setuplistextra** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

```
1  NAME          OPT
2  inainte = BEFEHL
   dupa    = BEFEHL
```

**\setuplocalfloats** [...,<sup>\*</sup>...,...]

```
*  inainte = BEFEHL
   dupa    = BEFEHL
   intre   = BEFEHL
```

**\setuplocalinterlinespace** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

```
1  NAME          OPT
2  inherits: \seteazaspatiuinterliniar
```

**\setuplocalinterlinespace** [...,<sup>\*</sup>...]

```
*  on dezactivat reset auto mic mediu mare OPT NUMBER DIMENSION
```

**\setuplocalinterlinespace** [...<sup>\*</sup>]

```
*  NAME
```

**\setuplow** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

```
1  NAME          OPT
2  distanta = DIMENSION
   down     = DIMENSION
   stil     = STYLE BEFEHL
   culoare  = COLOR
```

```
\setuplowhigh [...1,...] [...2,...]
```

```
1 NAME OPT
2 distanta = DIMENSION
  up       = DIMENSION
  down     = DIMENSION
  stil     = STYLE BEFEHL
  culoare  = COLOR
```

```
\setuplowmidhigh [...1,...] [...2,...]
```

```
1 NAME OPT
2 up     = DIMENSION
  down   = DIMENSION
  stil   = STYLE BEFEHL
  culoare = COLOR
```

```
\setupMPgraphics [...*,...]
```

```
* culoare = local global
  mpy     = FILE
```

```
\setupMPinstance [...1,...] [...2,...]
```

```
1 NAME OPT
2 format      = metafun mpost
  initializations = da nu
  setups       = NAME
  stiltext     = STYLE BEFEHL
  culoaretext  = COLOR
  extensions   = da nu
  metoda      = binary decimal double scaled implicit
```

```
\setupMPpage [...*,...]
```

```
* inherits: \setupfittingpage
```

```
\setupMPvariables [...1] [...2,...]
```

```
1 NAME OPT
2 KEY = VALUE
```

```
\setupmarginblock [...1,...] [...2,...]
```

```
1 NAME OPT
2 stare = start stop
  latime = DIMENSION
  inainte = BEFEHL
  dupa    = BEFEHL
  intre   = BEFEHL
  aliniere = inherits: \seteazaalinierea
  stil    = STYLE BEFEHL
  culoare = COLOR
  sus     = BEFEHL
  jos     = BEFEHL
  locatie = stanga dreapta centru inmarginie
  stanga  = BEFEHL
  dreapta = BEFEHL
```

```

\setupmargindata [...1,...] [...2,...]
1  NAME                      OPT
2  strut                    = da nu auto cap ajustat linie implicit CHARACTER
    comanda                = \...#1
    latime                  = DIMENSION
    aliniere                = inherits: \seteazaalinierea
    anchor                  = region text
    locatie                 = stanga dreapta intern extern
    metoda                  = sus linie primul adancime inaltime
    category                = implicit bordura
    scop                    = local global
    optiune                 = text paragraf
    margine                 = local normal margine bordura
    distanta                = DIMENSION
    hoffset                 = DIMENSION
    voffset                 = DIMENSION
    dy                      = DIMENSION
    spatiu jos              = DIMENSION
    threshold               = DIMENSION
    linie                   = NUMMER
    stack                   = da continuu
    stil                    = STYLE BEFEHL
    culoare                  = COLOR

```

```

\setupmarginframed [...1,...] [...2,...]
1  NAME                      OPT
2  inherits: \seteazainconjurat

```

```

\setupmarginrule [...1,...] [...2,...]
1  NUMMER                    OPT
2  inherits: \setupsidebar

```

```

\setupmathalignment [...1,...] [...2,...]
1  NAME                      OPT
2  n                        = NUMMER
    m                      = NUMMER
    distanta                = DIMENSION
    numar                   = auto
    separator               = TEXT
    aliniere                = stanga centru dreapta normal
    locatie                 = sus center subsol normal
    grid                    = math nu

```

```

\setupmathcases [...1,...] [...2,...]
1  NAME                      OPT
2  stanga                   = BEFEHL
    dreapta                 = BEFEHL
    strut                   = da nu
    stil                     = STYLE BEFEHL
    distanta                = DIMENSION
    numberdistance          = DIMENSION

```

`\setupmathematics [...1,...] [...2,...]`

```

1  NAME                      OPT
2  openup                    = da nu
   setsymbol                 = NAME
   functionstyle              = STYLE BEFEHL
   compact                    = da nu
   aliniere                   = l2r r2l
   bidi                       = da nu
   sygreek                    = normal italic niciunul
   lcgreek                    = normal italic niciunul
   ucgreek                    = normal italic niciunul
   italics                    = 1 2 3 4 niciunul reset
   autopunctuation            = da nu tot comma yes,semicolon comma,semicolon all,semicolon
   setups                     = NAME
   domain                     = NAME reset
   stiltext                   = STYLE BEFEHL
   culoaretext                = COLOR
   functioncolor              = COLOR
   integral                   = limits nolimits autolimits displaylimits niciunul
   stylealternative           = NAME
   implicit                   = normal italic
   fraction                   = ams ctx
   ampersand                  = normal

```

`\setupmathfence [...1,...] [...2,...]`

```

1  NAME                      OPT
2  comanda                    = da nu
   stanga                     = NUMMER
   mijloc                     = NUMMER
   dreapta                    = NUMMER
   mathstyle                  = display text script scriptscript cramped uncramped normal impachetat mic mare
   culoare                    = COLOR
   stare                      = auto
   metoda                     = auto
   factor                      = niciunul auto NUMMER
   mathclass                  = NUMMER

```

`\setupmathfraction [...1,...] [...2,...]`

```

1  NAME                      OPT
2  distantasus                = DIMENSION
   distantajos                = DIMENSION
   margine                    = DIMENSION
   culoare                    = COLOR
   strut                      = da nu math tight
   alternativ                  = intern extern ambele
   rigla                      = da nu auto
   stanga                     = NUMMER
   dreapta                    = NUMMER
   grosimerigla               = DIMENSION
   mathstyle                  = STYLE BEFEHL
   distanta                   = nu niciunul overlay
   inlinethreshold            = auto NUMMER
   displaythreshold           = auto NUMMER
   fences                     = NAME

```

`\setupmathfractions [...1,...] [...2,...]`

```

1  NAME                      OPT
2  inherits: \setupmathfraction

```

`\setupmathframed [...1,...] [...2,...]`

```

1  NAME                      OPT
2  inherits: \setezainconjurat

```

`\setupmathmatrix [...1,...] [...2,...]`

```

1  NAME                      OPT
2  stanga                     = BEFEHL
   dreapta                    = BEFEHL
   strut                      = da nu NUMMER
   aliniere                   = stanga centru dreapta normal
   stil                       = STYLE BEFEHL
   distanta                   = DIMENSION
   simplecommand              = TEXT
   locatie                    = sus subsol inalt jos lohi normal

```

```

\setupmathornament [...1,...] [...2,...]
1 NAME OPT
2 alternativ = mp
  culoare = COLOR
  mpoffset = DIMENSION
  mp = NAME

```

```

\setupmathradical [...1,...] [...2,...]
1 NAME OPT
2 alternativ = implicit normal mp
  culoare = COLOR
  mpoffset = DIMENSION
  mp = NAME

```

```

\setupmathstackers [...1,...] [...2,...]
1 NAME OPT
2 stanga = BEFEHL
  dreapta = BEFEHL
  topcommand = \...##1
  bottomcommand = \...##1
  middlecommand = \...##1
  mp = NAME
  mpheight = DIMENSION
  mpdepth = DIMENSION
  mpoffset = DIMENSION
  culoare = COLOR
  hoffset = DIMENSION
  voffset = DIMENSION
  inaltimeminima = DIMENSION
  mindepth = DIMENSION
  mathclass = rel ord
  offset = min max normal
  locatie = sus subsol inalt jos centru NUMMER
  strut = da nu
  alternativ = normal implicit mp
  latimeminima = DIMENSION
  distanta = DIMENSION
  moffset = DIMENSION
  order = normal reverse
  mathlimits = da nu

```

```

\setupmathstyle [...,*...]
* display text script scriptscript cramped uncramped normal impachetat mic mare NAME

```

```

\setupmixedcolumns [...1,...] [...2,...]
1 NAME OPT
2 grid = inherits: \definegridsnapping
  grosimerigla = DIMENSION
  metoda = otr box
  inainte = BEFEHL
  dupa = BEFEHL
  distanta = DIMENSION
  n = NUMMER
  inaltimaxima = DIMENSION
  latimaxima = DIMENSION
  pas = DIMENSION
  profile = NAME
  aliniere = inherits: \seteazaalinierea
  setups = NAME
  balanta = da nu
  splitmethod = niciunul fixat
  alternativ = local global
  internalgrid = linie jumatatelinie
  separator = rigla
  strut = da nu
  culoare = COLOR
  culoarerigla = COLOR
  directie = normal reverse
  inherits: \seteazainconjurat

```

```

\setupmodule [...1] [...2,...]
1 FILE OPT
2 test = da nu
  KEY = VALUE

```

`\setupnotation [...1,...] [...2,...]`

```

1  NAME                OPT
2  titlu                = da nu
   numar                = da nu
   type                 = note
   comandanumar         = \...##1
   distantatitlu        = DIMENSION
   stiltitlu            = STYLE BEFEHL
   culoaretitlu         = COLOR
   titlecommand         = \...##1
   titleleft            = BEFEHL
   titleright           = BEFEHL
   stanga               = BEFEHL
   dreapta              = BEFEHL
   simbol               = BEFEHL
   starter              = BEFEHL
   stopper              = BEFEHL
   cuplare              = NAME
   counter              = NAME
   nivel                = NUMMER
   text                 = TEXT
   headcommand          = \...##1
   inainte              = BEFEHL
   dupa                 = BEFEHL
   intre                = BEFEHL
   alternativ            = stanga dreapta inmargine instanga indreapta margine marginestanga marginedreapta innermargin
                        outermargin serried suspendat sus comanda note NAME
   aliniere              = inherits: \seteazaalinierea
   headalign            = inherits: \seteazaalinierea
   aliniat              = inherits: \seteazaaliniat
   display              = da nu
   aliniaturmator       = da nu auto
   latime               = ajustat broad linie DIMENSION
   distanta             = niciunul DIMENSION
   dilatat              = NUMMER
   shrink               = NUMMER
   suspenda             = ajustat broad niciunul margine NUMMER
   closesymbol          = BEFEHL
   closecommand         = \...##1
   expansiune           = da nu xml
   referenceprefix      = + - TEXT
   exemplu              = TEXT
   margine              = da nu standard DIMENSION
   stil                 = STYLE BEFEHL
   culoare              = COLOR
   stiltitlu            = STYLE BEFEHL
   culoaretitlu         = COLOR
   inherits: \setupcounter

```

`\setupnotations [...1,...] [...2,...]`

```

1  NAME                OPT
2  inherits: \setupnotation

```

**\setupnote** [...<sup>1</sup>...] [...<sup>2</sup>...]

```
1 NAME OPT
2 interactiune = da nu numar text tot
  symbolcommand = \...#1
  comandatext = \...#1
  indicator = da nu
  separatortext = BEFEHL
  latime = DIMENSION
  inaltime = DIMENSION
  distanta = DIMENSION
  rulecommand = BEFEHL
  rigla = on dezactivat normal stanga dreapta comanda paragraf
  split = tolerant strict foartestRICT NUMMER
  factor = NUMMER
  locatie = text pagina inalt subsol niciunul coloane firstcolumn lastcolumn
  urmatorul = BEFEHL
  n = NUMMER
  culoarerigla = COLOR
  grosimerigla = DIMENSION
  setups = NAME
  spatiereinterliniara = NAME
  paragraf = da nu
  inainte = BEFEHL
  dupa = BEFEHL
  intre = BEFEHL
  scop = pagina
  distantacoloane = DIMENSION
  continua = da nu
  alternativ = grila fixat coloane note niciunul
  criteriu = pagina
  fonttext = inherits: \seteazafonttext
  aliniere = inherits: \seteazaaliniere
  stiltext = STYLE BEFEHL
  culoaretex = COLOR
  anchor = urmatorul
  spatiuinainte = inherits: \blanc
  spaceinbetween = inherits: \blanc
  inherits: \seteazainconjurat
```

**\setupnotes** [...<sup>1</sup>...] [...<sup>2</sup>...]

```
1 NAME OPT
2 inherits: \setupnote
```

**\setupoffset** [...<sup>\*</sup>...]

```
* inherits: \setupoffsetbox
```

**\setupoffsetbox** [...<sup>\*</sup>...]

```
* x = DIMENSION
  y = DIMENSION
  offsetstanga = DIMENSION
  offsetdreapta = DIMENSION
  offsetsus = DIMENSION
  offsetjos = DIMENSION
  metoda = fixat
  latime = DIMENSION
  inaltime = DIMENSION
  inaltime = DIMENSION
  locatie = stanga centru dreapta sus subsol linie l c r m t b g
```

**\setupoutputroutine** [...<sup>1</sup>...] [...<sup>2</sup>...]

```
1 NAME OPT
2 KEY = CSNAME
```

**\setupoutputroutine** [...]

```
* NAME
```

\setuppagechecker [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
2 linii = NUMBER  
offset = DIMENSION  
metoda = 0 1 2 3  
inainte = BEFEHL  
dupa = BEFEHL  
intre = BEFEHL

\setuppagegrid [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
2 n = NUMBER  
nstanga = NUMBER  
ndreapta = NUMBER  
latime = DIMENSION auto  
distanta = DIMENSION  
linii = NUMBER  
latimemaxima = DIMENSION  
inaltimemaxima = DIMENSION  
directie = normal reverse  
pagina = inherits: \pagina  
inherits: \seteazainconjurat

\setuppagegridarea [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
2 stare = start stop repetat  
x = NUMBER  
y = NUMBER  
nx = NUMBER  
ny = NUMBER  
stil = STYLE BEFEHL  
culoare = COLOR  
clipoffset = DIMENSION  
offsetdreapta = DIMENSION  
inherits: \seteazainconjurat

\setuppagegridareatext [...<sup>1</sup>] [...<sup>2</sup>]

1 NAME  
2 TEXT

\setuppagegridlines [...<sup>1</sup>] [...<sup>2</sup>] [...<sup>3</sup>] [...<sup>4</sup>]

1 NAME  
2 NUMMER  
3 NUMMER  
4 NUMMER

\setuppagegridspan [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
2 n = NUMBER  
stil = STYLE BEFEHL  
culoare = COLOR  
inainte = BEFEHL  
dupa = BEFEHL  
inherits: \seteazainconjurat

\setuppagegridstart [...<sup>1</sup>] [...<sup>2</sup>] [...<sup>3</sup>] [...<sup>4</sup>]

1 NAME  
2 NUMMER  
3 NUMMER  
4 NUMMER

\setuppageinjection [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
2 stare = precedent urmatorul NUMMER  
intarziere = da nu  
alternativ = figura buffer setups niciunul NAME  
pagina = inherits: \pagina  
pagestate = start stop  
n = NUMBER  
inherits: \seteazainconjurat



```
\setuppageinjectionalternative [...,1...] [...,2...]
1 NAME OPT
2 renderingsetup = NAME
```

```
\setuppageshift [...1] [...2] [...3]
1 pagina foaie OPT OPT
2 NAME
3 NAME
```

```
\setuppagestate [...,1...] [...,2...]
1 NAME OPT
2 intarziere = da nu
```

```
\setuppairedbox [...,1...] [...,2...]
1 NAME OPT
2 inainte = BEFEHL
dupa = BEFEHL
intre = BEFEHL
locatie = stanga centru dreapta sus subsol inalt jos
n = NUMMER
distanta = DIMENSION
fonttext = inherits: \seteazafonttext
latime = DIMENSION
inaltime = DIMENSION
latimemaxima = DIMENSION
inaltimemaxima = DIMENSION
alinieri = inherits: \seteazaalinieria
stil = STYLE BEFEHL
culoare = COLOR
```

```
\setarePAIREDBOX [...,*...]
* inherits: \setuppairedbox
instances: legend
```

```
\setarelegend [...,*...]
* inherits: \setuppairedbox
```

```
\setuppaper [...,*...]
* inherits: \seteazadimensiunihartie
```

```
\setupparagraph [...,1...] [...,2...]
1 NAME OPT
2 stil = STYLE BEFEHL
culoare = COLOR
alinieri = inherits: \seteazaalinieria
setups = NAME
```

```
\setupparagraphintro [...,1...] [...2]
1 reset fiecare primul urmatorul
2 BEFEHL
```

```
\setupparallel [...1] [...2,...] [...,3...]
1 NAME
2 NAME
3 setups = NAME
start = NUMMER
n = NUMMER
criteriu = tot
```

```
\setupperiods [...,*...]
* n = NUMMER
latime = DIMENSION ajustat
distanta = DIMENSION
simbol = BEFEHL
```

`\setupplacement [...1,...] [...2,...]`

```
1 NAME OPT
2 inainte = BEFEHL
  dupa    = BEFEHL
  stanga  = BEFEHL
  dreapta = BEFEHL
  grid    = inherits: \snaptogrid
  corectielinie = on dezactivat
  corectieadancime = on dezactivat
  margine = da nu standard
```

`\setuppositionbar [...*,...]`

```
* stil      = STYLE BEFEHL
  culoare   = COLOR
  n         = NUMMER
  min       = NUMMER
  max       = NUMMER
  text      = TEXT
  latime    = DIMENSION
  inaltime  = DIMENSION
  inaltime  = DIMENSION
```

`\setupprocessor [...1,...] [...2,...]`

```
1 NAME OPT
2 stare = start stop
  stanga = BEFEHL
  dreapta = BEFEHL
  comanda = \...##1
  stil    = STYLE BEFEHL
  culoare = COLOR
```

`\setupprofile [...1,...] [...2,...]`

```
1 NAME OPT
2 inaltime = DIMENSION
  inaltime = DIMENSION
  distanta = DIMENSION
  factor    = NUMMER
  linii     = NUMMER
  metoda    = strict fixat niciunul
```

`\setupquotation [...*,...]`

```
* inherits: \setupdelimitedtext
```

`\setuprealpagenumber [...*,...]`

```
* inherits: \setupcounter
```

`\setupreferenceformat [...1,...] [...2,...]`

```
1 NAME OPT
2 eticheta = * NAME
  stanga   = BEFEHL
  dreapta  = BEFEHL
  type     = implicit text titlu numar pagina realpage
  setups   = NAME
  autocase = da nu
  text     = TEXT
  stil     = STYLE BEFEHL
  culoare  = COLOR
```

`\setupreferenceprefix [...]`

```
* + - TEXT
```

\setupreferencestructureprefix [...]<sup>1</sup> [...]<sup>2</sup> [...,...]<sup>3</sup>...,...]

```
1 NAME ABSCHNITT OPT OPT
2 implicit
3 prefix = da nu
  prefixseparatorset = NAME
  prefixconversion = NAME
  prefixconversionset = NAME
  prefixstarter = BEFEHL PROCESSOR->BEFEHL
  prefixstopper = BEFEHL PROCESSOR->BEFEHL
  prefixset = NAME
  prefixsegments = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:tot ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:* ABSCHNITT:tot
  numberconversion = NAME
  numberconversionset = NAME
  numberstarter = BEFEHL PROCESSOR->BEFEHL
  numberstopper = BEFEHL PROCESSOR->BEFEHL
  numbersegments = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:tot
  numberseparatorset = NAME
  prefixconnector = BEFEHL PROCESSOR->BEFEHL
```

\setupregisters [...]<sup>1</sup> [...,...]<sup>2</sup>...,...]

```
1 NAME NAME:NUMBER OPT
2 inherits: \seteazaregistru
```

\setupregisters [...]<sup>1</sup>...,... [...]<sup>2</sup>...,... [...,...]<sup>3</sup>...,...]

```
1 NAME OPT OPT
2 NUMMER
3 inherits: \seteazaregistru
```

\setuprenderingwindow [...]<sup>1</sup>...,... [...,...]<sup>2</sup>...,...]

```
1 NAME OPT
2 actiunedeschiderepagina = REFERENCE
  actiuneinchiderepagina = REFERENCE
  inherits: \seteazainconjurat
```

\setups [...]\*...,...]

```
* NAME
```

\setupscale [...]<sup>1</sup>...,... [...,...]<sup>2</sup>...,...]

```
1 NAME OPT
2 scala = NUMMER
  xscala = NUMMER
  yscala = NUMMER
  latime = DIMENSION
  inaltime = DIMENSION
  inaltime = da nu
  linii = NUMMER
  factor = ajustat broad max auto implicit
  hfactor = ajustat broad max auto implicit
  factorw = ajustat broad max auto implicit
  latimemaxima = DIMENSION
  inaltimemaxima = DIMENSION
  s = NUMMER
  sx = NUMMER
  sy = NUMMER
  equalwidth = DIMENSION
  equalheight = DIMENSION
  grid = da ajustat inaltime adancime jumatatelinie
```

\setupscript [...]<sup>1</sup>...,... [...,...]<sup>2</sup>...,...]

```
1 NAME OPT
2 metoda = hangul hanzi nihongo ethiopic thai test
  preset = NAME
  features = auto
```

\setupscripts [...]<sup>1</sup>...,... [...,...]<sup>2</sup>...,...]

```
1 NAME OPT
2 inherits: \setupscript
```

`\setupselector [...]1 [...]2...`

1 NAME  
2 n = NUMBER  
m = NUMBER

`\setupshift [...]1 [...]2...`

1 NAME OPT  
2 continua = da nu  
unitate = ex em pt in cm mm sp bp pc dd cc nc  
metoda = NUMBER  
dy = NUMBER  
aliniera = inherits: \setezaaliniera  
stil = STYLE BEFEHL  
culoare = COLOR

`\setupsidebar [...]1 [...]2...`

1 NAME OPT  
2 grosimerigla = DIMENSION  
culoarerigla = COLOR  
alternativ = NUMBER  
offsetsus = DIMENSION  
offsetjos = DIMENSION  
distanta = DIMENSION  
distantamarginestanga = DIMENSION  
nivel = NUMBER

`\setupspellchecking [...]*...`

\* stare = start stop  
metoda = 1 2 3  
lista = NAME

`\setupstartstop [...]1 [...]2...`

1 NAME OPT  
2 inainte = BEFEHL  
dupa = BEFEHL  
intre = BEFEHL  
setups = NAME  
stanga = BEFEHL  
dreapta = BEFEHL  
stil = STYLE BEFEHL  
culoare = COLOR

`\setupstretched [...]*...`

\* inherits: \setupcharacterkerning

`\setupstruts [...]`

\* da nu auto cap <sup>OPT</sup>ajustat linie implicit CHARACTER

`\setupstyle [...]1 [...]2...`

1 NAME OPT  
2 metoda = comanda  
stil = STYLE BEFEHL  
culoare = COLOR

`\setupsubformula [...]1 [...]2...`

1 NAME OPT  
2 aliniaturmator = da nu auto

`\setupsubformulas [...]1 [...]2...`

1 NAME OPT  
2 inherits: \setupsubformula

`\setupsynctex [...]*...`

\* stare = start stop  
metoda = min max

```
\setups {...,*,...}
```

```
* NAME
```

```
\setupTABLE [...,1...] [...,2...] [...,3...,...]
```

```
1 r c x y rand colona primul ultim start antet fiecare impar par unu NUMMER -NUMMER
2 primul least fiecare doi impar par NUMMER -NUMMER
3 extras = BEFEHL
  stanga = BEFEHL
  dreapta = BEFEHL
  culoaretitlu = COLOR
  stiltitlu = STYLE BEFEHL
  distantamarginestanga = DIMENSION
  distantamarginedreapta = DIMENSION
  distantacoloane = DIMENSION
  latimemaxima = DIMENSION
  setups = NAME
  latimetext = DIMENSION local
  split = da nu repetat auto
  antet = repetat
  optiune = dilatat tight
  inainte = BEFEHL
  dupa = BEFEHL
  aceeasipagina = inainte dupa ambele
  spaceinbetween = inherits: \blanc
  splitoffset = DIMENSION
  aliniazacaracter = da nu
  alierecaracter = TEXT number->TEXT text->TEXT
  distanta = DIMENSION
  culoare = COLOR
  stil = math STYLE BEFEHL
  inherits: \seteazainconjurat
```

```
\setupTEXpage [...,*...,...]
```

```
* inherits: \setupfittingpage
```

```
\setuptabulation [...,1...] [...,2...,...]
```

```
1 NAME OPT
2 format = TEMPLATE niciunul
  inainte = BEFEHL
  dupa = BEFEHL
  distanta = mic mediu mare niciunul blank adancime grila DIMENSION
  aliniere = stanga centru dreapta dimension
  rigla = linie normal
  culoarerigla = COLOR
  grosimerigla = DIMENSION
  fonttext = inherits: \seteazafonttext
  aliniat = da nu
  split = da nu repetat auto
  unitate = DIMENSION
  margine = DIMENSION
  intern = BEFEHL
  EQ = BEFEHL
  antet = da repetat text
  frame = on dezactivat
  titlu = TEXT
  keptogether = da nu
```

```
\setuptagging [...,*...,...]
```

```
* stare = start stop
  metoda = auto
```

**\setuptextbackground** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME OPT  
2 stare = start stop  
locatie = text paragraf totdeauna niciunul  
criteriu = NUMMER  
alternativ = NUMMER  
mp = NAME  
metoda = NAME  
fundal = culoare  
culoarefundal = COLOR  
colt = rectangular rotund  
nivel = NUMMER  
offsetfundal = DIMENSION  
inainte = BEFEHL  
dupa = BEFEHL  
alinieri = inherits: \seteazaalinieria  
dash = NUMMER  
raza = DIMENSION  
frame = on dezactivat  
culoareframe = COLOR  
grosimerigla = DIMENSION  
voffset = DIMENSION  
offsetframe = DIMENSION  
offsetstanga = da nu standard DIMENSION  
offsetdreapta = da nu standard DIMENSION  
offsetsus = mic mediu mare linie DIMENSION  
offsetjos = mic mediu mare linie DIMENSION  
stil = STYLE BEFEHL  
culoare = COLOR

**\setuptextflow** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME OPT  
2 latime = DIMENSION  
stil = STYLE BEFEHL  
culoare = COLOR

**\setuptooltip** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME OPT  
2 locatie = stanga centru dreapta  
inherits: \seteazainconjurat

**\setupunit** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME OPT  
2 metoda = 1 2 3 4 5 6  
language = SPRACHE  
alternativ = text matematica  
order = reverse normal  
separator = mic mediu mare normal niciunul NAME  
spatiu = mic mediu mare normal niciunul NAME  
stil = STYLE BEFEHL  
culoare = COLOR

**\setupuserpagenumber** [...,<sup>\*</sup>...,...]

\* viewerprefix = TEXT  
stare = start stop niciunul mentine gol  
inherits: \setupcounter

**\setupversion** [...]

\* concept fisier temporar final NAME

**\setupviewerlayer** [...,<sup>\*</sup>...,...]

\* titlu = TEXT  
stare = start stop  
export = da nu  
tiparibil = da nu  
scop = local global  
metoda = niciunul comanda

**\setupvspacing** [...,<sup>\*</sup>...,...]

\* inherits: \vspacing OPT

**\setupwithargument** {...} {...}

- 1 NAME
- 2 CONTENT

**\setupwithargumentswapped** {...} {...}

- 1 CONTENT
- 2 NAME

**\setupxml** [..., ...<sup>\*</sup>..., ...]

- \* implicit = ascuns niciunul text
- compress = da nu

**\setupxtable** [...,<sup>1</sup>...] [...,<sup>2</sup>..., ...]

- 1 NAME OPT
- 2 latimetext = DIMENSION local
- fonttext = inherits: \seteazafonttext
- spaceinbetween = inherits: \blanc
- optiune = tight max dilatat latime inaltime fixat
- inaltimetext = DIMENSION
- latimemaxima = DIMENSION
- distantacoloane = DIMENSION
- distantamarginestanga = DIMENSION
- distantamarginedreapta = DIMENSION
- antet = repetat
- subsol = repetat
- grosimerigla = DIMENSION
- split = da nu repetat auto
- splitoffset = DIMENSION
- aceeasipagina = inainte dupa ambele
- distanta = DIMENSION
- inherits: \seteazainconjurat

**\setuvalue** {...} {...}

- 1 NAME
- 2 CONTENT

**\setuxvalue** {...} {...}

- 1 NAME
- 2 CONTENT

**\setvalue** {...} {...}

- 1 NAME
- 2 CONTENT

**\setvariable** {...} {...} {...}

- 1 NAME
- 2 KEY
- 3 VALUE

**\setvariables** [...]<sup>1</sup> [...,<sup>2</sup>..., ...]

- 1 NAME
- 2 set = BEFEHL
- reset = BEFEHL
- KEY = VALUE

**\setvboxregister** ...<sup>1</sup> {...}

- 1 CSNAME NUMBER
- 2 CONTENT

**\setvisualizerfont** [...]<sup>\*</sup>

- \* FONT OPT

**\setvtopregister** ...<sup>1</sup> {...}

- 1 CSNAME NUMBER
- 2 CONTENT

<pre> \setwidthof <sup>1</sup>... \to \<sup>2</sup>... 1 TEXT 2 CSNAME </pre>
<pre> \setxmeasure {...} {...} 1 NAME 2 DIMENSION </pre>
<pre> \setxvalue {...} {...} 1 NAME 2 CONTENT </pre>
<pre> \setxvariable {...} {...} {...} 1 NAME 2 KEY 3 VALUE </pre>
<pre> \setxvariables [<sup>1</sup>...] [<sup>2</sup>...=...,...] 1 NAME 2 set = BEFEHL reset = BEFEHL KEY = VALUE </pre>
<pre> \shapedhbox {...} * CONTENT </pre>
<pre> \SHIFT {...} * CONTENT instances: shiftup shiftdown </pre>
<pre> \shiftdown {...} * CONTENT </pre>
<pre> \shiftup {...} * CONTENT </pre>
<pre> \showallmakeup </pre>
<pre> \showattributes </pre>
<pre> \showboxes </pre>
<pre> \showbtxdatasetauthors [...,<sup>*</sup>...,...] * specification = NAME OPT dataset = NAME field = address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME </pre>
<pre> \showbtxdatasetauthors [...]<sup>*</sup> * NAME OPT </pre>
<pre> \showbtxdatasetcompleteness [...,<sup>*</sup>...,...] * specification = NAME OPT dataset = NAME field = address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME </pre>
<pre> \showbtxdatasetcompleteness [...]<sup>*</sup> * NAME OPT </pre>



<pre> \showbtxdatasetfields [...,.*=...,...] *  specification = NAME          OPT    dataset       = NAME    field         = address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution                   journal language luna monthfiled nationality note numar unu doi organization pages publisher                   school series titlu type volume an yearfiled NAME </pre>
<pre> \showbtxdatasetfields [...] *  NAME          OPT </pre>
<pre> \showbtxfields [...,.*=...,...] *  rotatie       = NUMMER<sup>OPT</sup>    specification = NAME </pre>
<pre> \showbtxfields [...] *  NAME          OPT </pre>
<pre> \showbtxhashedauthors [...] *  TEXT          OPT </pre>
<pre> \showbtxtables [...] *  TEXT          OPT </pre>
<pre> \showchardata {...} *  TEXT </pre>
<pre> \showcharratio {...} *  TEXT </pre>
<pre> \showcolorbar [...] *  COLOR </pre>
<pre> \showcolorcomponents [...] *  COLOR </pre>
<pre> \showcolorset [...] *  COLOR </pre>
<pre> \showcolorstruts </pre>
<pre> \showcounter [...] *  NAME </pre>
<pre> \showdirectives </pre>
<pre> \showdirlsinmargin </pre>
<pre> \showedebuginfo </pre>
<pre> \showexperiments </pre>
<pre> \showfont [...]<sup>1</sup> [...,]<sup>2</sup> [...]<sup>OPT</sup> 1  FONT 2  NUMMER </pre>
<pre> \showfontdata </pre>

<code>\showfontitalics</code>
<code>\showfontkerns</code>
<code>\showfontparameters</code>
<code>\showfontstrip [...*...]</code> <code>* inherits: \seteazafonttext</code>
<code>\showfontstyle [...<sup>1</sup>...] [...<sup>2</sup>...] [...<sup>3</sup>...] [...<sup>4</sup>...]</code> <code>1 inherits: \seteazafonttext</code> <code>2 rm ss tt mm hw cg</code> <code>3 tf bf it sl bi bs</code> <code>4 tot NUMMER</code>
<code>\showglyphs</code>
<code>\showgridsnapping</code>
<code>\showhelp {...} [...]</code> <code>1 TEXT</code> <code>2 REFERENCE</code>
<code>\showhyphenationtrace [...<sup>1</sup>] [...<sup>2</sup>]</code> <code>1 SPRACHE</code> <code>2 TEXT</code>
<code>\showhyphens {...}</code> <code>* TEXT</code>
<code>\showinjector [...*...]</code> <code>* NAME</code>
<code>\showjustification</code>
<code>\showkerning {...}</code> <code>* TEXT</code>
<code>\showlayoutcomponents</code>
<code>\showligature {...}</code> <code>* TEXT</code>
<code>\showligatures [...]</code> <code>* FONT</code>
<code>\showlogcategories</code>
<code>\showmargins</code>
<code>\showmessage {...} {...<sup>2</sup>} {...<sup>3</sup>,...}</code> <code>1 NAME</code> <code>2 NAME NUMMER</code> <code>3 TEXT</code>
<code>\showminimalbaseline</code>

\shownextbox \ <sup>1</sup> ... { <sup>2</sup> ...} 1 CSNAME 2 CONTENT
\showotfcomposition { <sup>1</sup> ...} { <sup>2</sup> ...} { <sup>3</sup> ...} 1 FONT 2 -1 1 +1 l2r r2l 3 TEXT
\showparentchain \ <sup>1</sup> ... { <sup>2</sup> ...} 1 CSNAME 2 NAME
\showsetupsdefinition [...] * NAME
\showtimer { <sup>*</sup> ...} * TEXT
\showtokens [... <sup>*</sup> ...] * NAME
\showtrackers
\showvalue { <sup>*</sup> ...} * NAME
\showvariable { <sup>1</sup> ...} { <sup>2</sup> ...} 1 NAME 2 KEY
\showwarning { <sup>1</sup> ...} { <sup>2</sup> ...} { <sup>3</sup> ...,...} 1 NAME 2 NAME NUMBER 3 TEXT
\simbol [... <sup>1</sup> ...] [... <sup>2</sup> ...] 1 NAME <small>OPT</small> 2 NAME
\simbol { <sup>*</sup> ...} * NAME
\simplealignedbox { <sup>1</sup> ...} { <sup>2</sup> ...} { <sup>3</sup> ...} 1 DIMENSION 2 stanga dreapta centru flushleft flushright intern extern 3 CONTENT
\simplealignedboxplus { <sup>1</sup> ...} { <sup>2</sup> ...} { <sup>3</sup> ...} { <sup>4</sup> ...} 1 DIMENSION 2 stanga dreapta centru flushleft flushright intern extern 3 TEXT 4 CONTENT
\simplealignedspreadbox { <sup>1</sup> ...} { <sup>2</sup> ...} { <sup>3</sup> ...} 1 DIMENSION 2 stanga dreapta centru flushleft flushright intern extern 3 CONTENT

$\backslash\text{simplegroupedcommand}$ $\{.^1.\}$ $\{.^2.\}$ 1 BEFEHL 2 BEFEHL
$\backslash\text{simplereversealignedbox}$ $\{.^1.\}$ $\{.^2.\}$ $\{.^3.\}$ 1 DIMENSION 2 stanga dreapta centru flushleft flushright intern extern 3 CONTENT
$\backslash\text{simplereversealignedboxplus}$ $\{.^1.\}$ $\{.^2.\}$ $\{.^3.\}$ $\{.^4.\}$ 1 DIMENSION 2 stanga dreapta centru flushleft flushright intern extern 3 TEXT 4 CONTENT
$\backslash\text{singalcharacteralign}$ $\{.^1.\}$ $\{.^2.\}$ 1 NUMMER 2 NUMMER
$\backslash\text{singlebond}$
$\backslash\text{sixthofsixarguments}$ $\{.^1.\}$ $\{.^2.\}$ $\{.^3.\}$ $\{.^4.\}$ $\{.^5.\}$ $\{.^6.\}$ 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT
$\backslash\text{slantedface}$
$\backslash\text{slicepages}$ $[\text{...}]$ $[\text{...}\overset{2}{=}\text{...}\text{...}]$ $[\text{...}\overset{3}{=}\text{...}\text{...}]$ 1 FILE OPT OPT 2 offset = DIMENSION hoffset = DIMENSION voffset = DIMENSION latime = DIMENSION inaltime = DIMENSION n = NUMMER 3 offset = DIMENSION hoffset = DIMENSION voffset = DIMENSION latime = DIMENSION inaltime = DIMENSION n = NUMMER
$\backslash\text{slovenianNumerals}$ $\{.^*.\}$ * NUMMER
$\backslash\text{sloveniannumerals}$ $\{.^*.\}$ * NUMMER
$\backslash\text{smallbodyfont}$
$\backslash\text{smallcappedcharacters}$ $\{.^*.\}$ * NUMMER
$\backslash\text{smallcappedromannumerals}$ $\{.^*.\}$ * NUMMER
$\backslash\text{smaller}$
$\backslash\text{smallskip}$

$\backslash\text{smash} [\text{...}] \{\text{...}\}$ 1 $\text{w h d t}^{\text{OPT}}$ 2    CONTENT
$\backslash\text{smashbox} \text{...}$ *    CSNAME NUMBER
$\backslash\text{smashboxed} \text{...}$ *    CSNAME NUMBER
$\backslash\text{smashedhbox} \text{...} \text{...} \{\text{...}\}$ 1    TEXT $\text{OPT}$ 2    CONTENT
$\backslash\text{smashedvbox} \text{...} \text{...} \{\text{...}\}$ 1    TEXT $\text{OPT}$ 2    CONTENT
$\backslash\text{snaptogrid} [\text{...}] \text{...} \{\text{...}\}$ 1    normal standard $\text{OPT}$ da strict tolerant sus subsol ambele broad ajustat primul ultim inalt unu jos niciunul linie strut box min max centru math math:linie math:jumatatelinie math:-line math:-halfline NAME 2    CSNAME 3    CONTENT
$\backslash\text{snaptogrid} [\text{...}, \text{...}] \text{...} \{\text{...}\}$ 1    inherits: $\backslash\text{define}^{\text{OPT}}\text{gridsnapping}$ 2    CSNAME 3    CONTENT
$\backslash\text{someheadnumber} [\text{...}] [\text{...}]$ 1    ABSCHNITT 2    precedent curent urmatorul primul ultim
$\backslash\text{somekindoftab} [\text{...}, \text{...}^*, \text{...}]$ *    alternativ    =    orizonta $\text{PT}$ vertical latime            =    DIMENSION inaltime          =    DIMENSION n                  =    NUMMER m                  =    NUMMER
$\backslash\text{somelocalfloat}$
$\backslash\text{somenamedheadnumber} \{\text{...}\} \{\text{...}\}$ 1    ABSCHNITT 2    precedent curent urmatorul primul ultim
$\backslash\text{someplace} \{\text{...}\} \{\text{...}\} \{\text{...}\} \{\text{...}\} \{\text{...}\} [\text{...}]$ 1    TEXT 2    TEXT 3    TEXT 4    TEXT 5    TEXT 6    REFERENCE
$\backslash\text{SORTING} [\text{...}] \{\text{...}\}$ 1    NAME $\text{OPT}$ 2    CONTENT instances: logo
$\backslash\text{logo} [\text{...}] \{\text{...}\}$ 1    NAME $\text{OPT}$ 2    CONTENT

$\backslash\text{spanishNumerals } \{...\}$ *    NUMBER
$\backslash\text{spanishnumerals } \{...\}$ *    NUMBER
$\backslash\text{spatiifixate}$
$\backslash\text{spatiu}$
$\backslash\text{spatiufixat}$
$\backslash\text{splitatasterisk } ^1... \ ^2... \ ^3...$ 1    TEXT 2    CSNAME 3    CSNAME
$\backslash\text{splitatcolon } ^1... \ ^2... \ ^3...$ 1    TEXT 2    CSNAME 3    CSNAME
$\backslash\text{splitatcolons } ^1... \ ^2... \ ^3...$ 1    TEXT 2    CSNAME 3    CSNAME
$\backslash\text{splitatcomma } ^1... \ ^2... \ ^3...$ 1    TEXT 2    CSNAME 3    CSNAME
$\backslash\text{splitatperiod } ^1... \ ^2... \ ^3...$ 1    TEXT 2    CSNAME 3    CSNAME
$\backslash\text{splitdfrac } \{.^1...\} \{.^2...\}$ 1    CONTENT 2    CONTENT
$\backslash\text{splitfilename } \{...\}$ *    FILE
$\backslash\text{splitfrac } \{.^1...\} \{.^2...\}$ 1    CONTENT 2    CONTENT
$\backslash\text{splitoffbase}$
$\backslash\text{splitofffull}$
$\backslash\text{splitoffkind}$
$\backslash\text{splitoffname}$
$\backslash\text{splitoffpath}$
$\backslash\text{splitoffroot}$

<code>\splitofftokens</code> <sup>1</sup> ... \from <sup>2</sup> ... \to \ <sup>3</sup> ... 1 TEXT 2 TEXT 3 CSNAME
<code>\splitofftype</code>
<code>\splitstring</code> <sup>1</sup> ... \at <sup>2</sup> ... \to \ <sup>3</sup> ... \and \ <sup>4</sup> ... 1 TEXT 2 TEXT 3 CSNAME 4 CSNAME
<code>\spreadhbox</code> ... * CSNAME NUMBER
<code>\sqrt</code> [ <sup>1</sup> ...] { <sup>2</sup> ...} 1 TEXT <small>OPT</small> 2 CONTENT
<code>\stackrel</code> { <sup>1</sup> ...} { <sup>2</sup> ...} 1 CONTENT 2 CONTENT
<code>\stanga</code> ... * CHARACTER
<code>\startalignment</code> [...,*...] ... \stopalignment * inherits: \seteazaalinierea
<code>\startaliniatcentru</code> ... \stopaliniatcentru
<code>\startaliniatdreapta</code> ... \stopaliniatdreapta
<code>\startaliniatstanga</code> ... \stopaliniatstanga
<code>\startallmodes</code> [...,*...] ... \stopallmodes * NAME
<code>\startantettabel</code> [...] ... \stopantettabel * NAME
<code>\startATTACHMENT</code> [ <sup>1</sup> ] [..., <sup>2</sup> ..., <sup>2</sup> ...,...] ... \stopATTACHMENT 1 NAME <small>OPT</small> <small>OPT</small> 2 inherits: \setupattachment instances: attachment
<code>\startattachment</code> [ <sup>1</sup> ] [..., <sup>2</sup> ..., <sup>2</sup> ...,...] ... \stopattachment 1 NAME <small>OPT</small> <small>OPT</small> 2 inherits: \setupattachment
<code>\startbar</code> [...] ... \stopbar * NAME
<code>\startbbordermatrix</code> ... \stopbbordermatrix

<pre> \startbitmapimage [...,*=...,...] ... \stopbitmapimage *   culoare   = rgb cmyk gri       latime   = DIMENSION       inaltime = DIMENSION       x        = NUMMER       y        = NUMMER </pre>
<pre> \startblocsectiuneambient [...] ... \stopblocsectiuneambient *   NAME </pre>
<pre> \startbordermatrix ... \stopbordermatrix </pre>
<pre> \startbtxrenderingdefinitions [...] ... \stopbtxrenderingdefinitions *   NAME </pre>
<pre> \startbuffer [...] ... \stopbuffer *   NAME          OPT </pre>
<pre> \startBUFFER ... \stopBUFFER instances: hiding </pre>
<pre> \starthiding ... \stophiding </pre>
<pre> \startcatcodetable \* ... \stopcatcodetable *   CSNAME </pre>
<pre> \startcenteraligned ... \stopcenteraligned </pre>
<pre> \startcharacteralign [...] ... \stopcharacteralign *   TEXT number-&gt;TEXT text-&gt;TEXT<sup>OPT</sup> </pre>
<pre> \startcheckedfences ... \stopcheckedfences </pre>
<pre> \startchemical [<sup>1</sup>...] [...,<sup>2</sup>=...,...] ... \stopchemical 1   NAME          OPT          OPT 2   inherits: \setupchemical </pre>
<pre> \startcollect ... \stopcollect </pre>
<pre> \startcollecting ... \stopcollecting </pre>
<pre> \startcoloane [...,*=...,...] ... \stopcoloane *   inherits: \seteazacoloane<sup>OPT</sup> </pre>
<pre> \startcolorintent [...] ... \stopcolorintent *   knockout overprint niciunul </pre>
<pre> \startcoloronly [...] ... \stopcoloronly *   COLOR </pre>
<pre> \startcolorset [...] ... \stopcolorset *   NAME </pre>
<pre> \startcolumnspan [...,*=...,...] ... \stopcolumnspan *   inherits: \setupcolumnspan<sup>OPT</sup> </pre>



\startcombination [...] <sup>1</sup> [...] <sup>2</sup> ... \stopcombination 1 NAME OPT OPT 2 inherits: \setupcombination
\startcombination [...] <sup>1</sup> [...] <sup>2</sup> ... \stopcombination 1 NAME OPT OPT 2 N*M
\startcomentariupagina ... \stopcomentariupagina
\startCOMMENT [...] <sup>1</sup> [...] <sup>2</sup> ... \stopCOMMENT 1 TEXT OPT OPT 2 inherits: \seteazacomentariu instances: comment
\startcomment [...] <sup>1</sup> [...] <sup>2</sup> ... \stopcomment 1 TEXT OPT OPT 2 inherits: \seteazacomentariu
\startcomponenta [...] <sup>*</sup> ... \stopcomponenta * FILE *
\startcomponenta ... <sup>*</sup> ... \stopcomponenta * FILE *
\startcontextcode ... \stopcontextcode
\startcontextdefinitioncode ... \stopcontextdefinitioncode
\startctxfunction ... <sup>*</sup> ... \stopctxfunction * NAME
\startctxfunctiondefinition ... <sup>*</sup> ... \stopctxfunctiondefinition * NAME
\startculoare [...] <sup>*</sup> ... \stopculoare * COLOR
\startcurrentcolor ... \stopcurrentcolor
\startcurrentlistentrywrapper ... \stopcurrentlistentrywrapper
\startdelimited [...] <sup>1</sup> [...] <sup>2</sup> [...] <sup>3</sup> ... \stopdelimited 1 NAME OPT OPT 2 SPRACHE 3 inherits: \startingust
\startdelimitedtext [...] <sup>1</sup> [...] <sup>2</sup> [...] <sup>3</sup> ... \stopdelimitedtext 1 NAME OPT OPT 2 SPRACHE 3 inherits: \startingust
\startDELIMITEDTEXT [...] <sup>1</sup> [...] <sup>2</sup> ... \stopDELIMITEDTEXT 1 SPRACHE OPT OPT 2 inherits: \startingust instances: quotation quote blockquote speech aside

$\backslash\text{startaside}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...,...] ... $\backslash\text{stopaside}$ 1 SPRACHE OPT OPT 2 inherits: $\backslash\text{startingust}$
$\backslash\text{startblockquote}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...,...] ... $\backslash\text{stopblockquote}$ 1 SPRACHE OPT OPT 2 inherits: $\backslash\text{startingust}$
$\backslash\text{startquotation}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...,...] ... $\backslash\text{stopquotation}$ 1 SPRACHE OPT OPT 2 inherits: $\backslash\text{startingust}$
$\backslash\text{startquote}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...,...] ... $\backslash\text{stopquote}$ 1 SPRACHE OPT OPT 2 inherits: $\backslash\text{startingust}$
$\backslash\text{startspeech}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...,...] ... $\backslash\text{stopspeech}$ 1 SPRACHE OPT OPT 2 inherits: $\backslash\text{startingust}$
$\backslash\text{startDESCRIERE}$ [..., ... <sup>*</sup> ..., ...] ... $\backslash\text{stopDESCRIERE}$ * titlu = TEXT OPT semncarte = TEXT lista = TEXT referinta = REFERENCE
$\backslash\text{startDESCRIERE}$ [..., <sup>1</sup> ...] { <sup>2</sup> ...} ... $\backslash\text{stopDESCRIERE}$ 1 REFERENCE OPT OPT 2 TEXT
$\backslash\text{startdespachetat}$ ... $\backslash\text{stopdespachetat}$
$\backslash\text{startdisplaymath}$ ... $\backslash\text{stopdisplaymath}$
$\backslash\text{startdmath}$ ... $\backslash\text{stopdmath}$
$\backslash\text{startdocument}$ [..., ... <sup>*</sup> ..., ...] ... $\backslash\text{stopdocument}$ * inherits: $\backslash\text{setupdocument}$ <sup>OPT</sup>
$\backslash\text{startdute}$ [...] ... $\backslash\text{stopdute}$ * REFERENCE
$\backslash\text{starteffect}$ [...] ... $\backslash\text{stopeffect}$ * NAME
$\backslash\text{startEFFECT}$ ... $\backslash\text{stopEFFECT}$
$\backslash\text{startelement}$ [..., <sup>*</sup> ...] ... $\backslash\text{stopelement}$ * REFERENCE OPT
$\backslash\text{startembeddedxtable}$ [..., ... <sup>*</sup> ..., ...] ... $\backslash\text{stopembeddedxtable}$ * inherits: $\backslash\text{setupxtable}$ OPT
$\backslash\text{startembeddedxtable}$ [... <sup>*</sup> ] ... $\backslash\text{stopembeddedxtable}$ * NAME OPT

<pre> \startENUMERARE [...,*=...,...] ... \stopENUMERARE *   titlu       = TEXT      OPT     semncarte   = TEXT     lista       = TEXT     referinta    = REFERENCE </pre>
<pre> \startENUMERARE [...,<sup>1</sup>...] {<sup>2</sup>...} ... \stopENUMERARE 1   REFERENCE      OPT      OPT 2   TEXT </pre>
<pre> \startexceptions [...] ... \stopexceptions *   SPRACHE </pre>
<pre> \startexpanded ... \stopexpanded </pre>
<pre> \startexpandedcollect ... \stopexpandedcollect </pre>
<pre> \startextendedcatcodetable \*... ... \stopextendedcatcodetable *   CSNAME </pre>
<pre> \startexternalfigurecollection [...] ... \stopexternalfigurecollection *   NAME </pre>
<pre> \startfigura [<sup>1</sup>...] [<sup>2</sup>...] [...,<sup>3</sup>=...,...] ... \stopfigura 1   NAME      OPT 2   FILE 3   inherits: \figuraexterna </pre>
<pre> \startfittingpage [<sup>1</sup>...] [...,<sup>2</sup>=...,...] ... \stopfittingpage 1   NAME      OPT 2   inherits: \setupfittingpage </pre>
<pre> \startFITTINGPAGE [...,*=...,...] ... \stopFITTINGPAGE *   inherits: \setupfittingpage<sup>OPT</sup> instances: TEXpage MPpage </pre>
<pre> \startMPpage [...,*=...,...] ... \stopMPpage *   inherits: \setupfittingpage<sup>OPT</sup> </pre>
<pre> \startTEXpage [...,*=...,...] ... \stopTEXpage *   inherits: \setupfittingpage<sup>OPT</sup> </pre>
<pre> \startfixat [...] ... \stopfixat *   jos centru inalt lohi implicit </pre>
<pre> \startfloatcombination [...,*=...,...] ... \stopfloatcombination *   inherits: \setupcombination OPT </pre>
<pre> \startfloatcombination [...] ... \stopfloatcombination *   N*M NAME      OPT </pre>
<pre> \startFLOATtext [...,<sup>1</sup>...] [...,<sup>2</sup>...] {<sup>3</sup>...} ... \stopFLOATtext 1   split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmarginie marginestanga     marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime     adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine     [-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva     effective antet subsol 2   REFERENCE 3   TEXT instances: chemical figure table intermezzo graphic </pre>

```

\startchemicaltext [...,1...] [...,2...] {...3} ... \stopchemicaltext
1 split totdeauna stanga dreapta internOPT extern spatiuspate cutspace instanga indreapta inmargin marginestanga
marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime
adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine
[-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva
effective antet subsol
2 REFERENCE
3 TEXT

```

```

\startfiguretext [...,1...] [...,2...] {...3} ... \stopfiguretext
1 split totdeauna stanga dreapta internOPT extern spatiuspate cutspace instanga indreapta inmargin marginestanga
marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime
adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine
[-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva
effective antet subsol
2 REFERENCE
3 TEXT

```

```

\startgraphicstext [...,1...] [...,2...] {...3} ... \stopgraphicstext
1 split totdeauna stanga dreapta internOPT extern spatiuspate cutspace instanga indreapta inmargin marginestanga
marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime
adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine
[-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva
effective antet subsol
2 REFERENCE
3 TEXT

```

```

\startintermezzotext [...,1...] [...,2...] {...3} ... \stopintermezzotext
1 split totdeauna stanga dreapta internOPT extern spatiuspate cutspace instanga indreapta inmargin marginestanga
marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime
adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine
[-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva
effective antet subsol
2 REFERENCE
3 TEXT

```

```

\starttabletext [...,1...] [...,2...] {...3} ... \stoptabletext
1 split totdeauna stanga dreapta internOPT extern spatiuspate cutspace instanga indreapta inmargin marginestanga
marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime
adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine
[-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva
effective antet subsol
2 REFERENCE
3 TEXT

```

```

\startfont [...] ... \stopfont
* FONT OPT

```

```

\startfontclass [...] ... \stopfontclass
* fiecare NAME

```

```

\startfontsolution [...] ... \stopfontsolution
* NAME

```

```

\startformula [...,*...] ... \stopformula
* impachetat tight centru incadrat adancime linie jumatatelinie -linie -jumatatelinie inherits: \seteazafonttext

```

```

\startformula [...,*...] ... \stopformula
* optiune = impachetatOPT tight centru incadrat adancime linie jumatatelinie -linie -jumatatelinie inherits: \seteazafonttext
margine = da nu standard DIMENSION
grid = inherits: \snaptogrid

```

```

\startFORMULAformula [...,*...] ... \stopFORMULAformula
* impachetat tight centru incadrat adancime linie jumatatelinie -linie -jumatatelinie inherits: \seteazafonttext
instances: sp sd mp md

```

$\backslash\mathrm{startmdformula} [\dots,*,\dots] \dots \backslash\mathrm{stopmdformula}$ $\ast$ $\mathrm{impachetat}$ $\mathrm{tight}$ $\mathrm{centru}$ <sup>OPT</sup> $\mathrm{incadrat}$ $\mathrm{adancime}$ $\mathrm{linie}$ $\mathrm{jumatatelinie}$ $\mathrm{-linie}$ $\mathrm{-jumatatelinie}$ $\mathrm{inherits:}$ $\backslash\mathrm{seteazafonttext}$
$\backslash\mathrm{startmpformula} [\dots,*,\dots] \dots \backslash\mathrm{stopmpformula}$ $\ast$ $\mathrm{impachetat}$ $\mathrm{tight}$ $\mathrm{centru}$ <sup>OPT</sup> $\mathrm{incadrat}$ $\mathrm{adancime}$ $\mathrm{linie}$ $\mathrm{jumatatelinie}$ $\mathrm{-linie}$ $\mathrm{-jumatatelinie}$ $\mathrm{inherits:}$ $\backslash\mathrm{seteazafonttext}$
$\backslash\mathrm{startsdfformula} [\dots,*,\dots] \dots \backslash\mathrm{stopsdfformula}$ $\ast$ $\mathrm{impachetat}$ $\mathrm{tight}$ $\mathrm{centru}$ <sup>OPT</sup> $\mathrm{incadrat}$ $\mathrm{adancime}$ $\mathrm{linie}$ $\mathrm{jumatatelinie}$ $\mathrm{-linie}$ $\mathrm{-jumatatelinie}$ $\mathrm{inherits:}$ $\backslash\mathrm{seteazafonttext}$
$\backslash\mathrm{startspformula} [\dots,*,\dots] \dots \backslash\mathrm{stopspformula}$ $\ast$ $\mathrm{impachetat}$ $\mathrm{tight}$ $\mathrm{centru}$ <sup>OPT</sup> $\mathrm{incadrat}$ $\mathrm{adancime}$ $\mathrm{linie}$ $\mathrm{jumatatelinie}$ $\mathrm{-linie}$ $\mathrm{-jumatatelinie}$ $\mathrm{inherits:}$ $\backslash\mathrm{seteazafonttext}$
$\backslash\mathrm{startformule} [\dots,*,\dots] \dots \backslash\mathrm{stopformule}$ $\ast$ $\ast$ $\mathrm{-}$ $\mathrm{REFERENCE}$ $\mathrm{OPT}$
$\backslash\mathrm{startframed} [\overset{1}{\dots},\dots,\overset{2}{\dots},\dots] \dots \backslash\mathrm{stopframed}$ 1 $\mathrm{NAME}$ $\mathrm{OPT}$ $\mathrm{OPT}$ 2 $\mathrm{inherits:}$ $\backslash\mathrm{seteazainconjurat}$
$\backslash\mathrm{startframedcell} [\dots,\dots,\overset{*}{\dots},\dots] \dots \backslash\mathrm{stopframedcell}$ $\ast$ $\mathrm{inherits:}$ $\backslash\mathrm{seteazainconjurat}$ <sup>OPT</sup>
$\backslash\mathrm{startframedcontent} [\dots] \dots \backslash\mathrm{stopframedcontent}$ $\ast$ $\mathrm{NAME}$ $\mathrm{dezactivat}$ $\mathrm{OPT}$
$\backslash\mathrm{startframedrow} [\dots,\dots,\overset{*}{\dots},\dots] \dots \backslash\mathrm{stopframedrow}$ $\ast$ $\mathrm{inherits:}$ $\backslash\mathrm{seteazainconjurat}$ <sup>OPT</sup>
$\backslash\mathrm{startframedtable} [\overset{1}{\dots}] [\dots,\dots,\overset{2}{\dots},\dots] \dots \backslash\mathrm{stopframedtable}$ 1 $\mathrm{NAME}$ $\mathrm{OPT}$ $\mathrm{OPT}$ 2 $\mathrm{inherits:}$ $\backslash\mathrm{seteazainconjurat}$
$\backslash\mathrm{startfundal} [\dots,\dots,\overset{*}{\dots},\dots] \dots \backslash\mathrm{stopfundal}$ $\ast$ $\mathrm{inherits:}$ $\backslash\mathrm{seteazafundal}$ <sup>OPT</sup>
$\backslash\mathrm{startFUNDAL} [\dots,\dots,\overset{*}{\dots},\dots] \dots \backslash\mathrm{stopFUNDAL}$ $\ast$ $\mathrm{inherits:}$ $\backslash\mathrm{seteazafundal}$ <sup>OPT</sup> <b>instances:</b> <b>fundal</b>
$\backslash\mathrm{startgridsnapping} [\dots] \dots \backslash\mathrm{stopgridsnapping}$ $\ast$ $\mathrm{normal}$ $\mathrm{standard}$ $\mathrm{da}$ $\mathrm{strict}$ <sup>OPT</sup> $\mathrm{tolerant}$ $\mathrm{sus}$ $\mathrm{subsol}$ $\mathrm{ambele}$ $\mathrm{broad}$ $\mathrm{ajustat}$ $\mathrm{primul}$ $\mathrm{ultim}$ $\mathrm{inalt}$ $\mathrm{unu}$ $\mathrm{jos}$ $\mathrm{niciunul}$ $\mathrm{linie}$ $\mathrm{strut}$ $\mathrm{box}$ $\mathrm{min}$ $\mathrm{max}$ $\mathrm{centru}$ $\mathrm{math}$ $\mathrm{math:linie}$ $\mathrm{math:jumatatelinie}$ $\mathrm{math:-line}$ $\mathrm{math:-halfline}$ $\mathrm{NAME}$
$\backslash\mathrm{startgridsnapping} [\dots,*,\dots] \dots \backslash\mathrm{stopgridsnapping}$ $\ast$ $\mathrm{inherits:}$ $\backslash\mathrm{definegridsnapping}$ <sup>OPT</sup>
$\backslash\mathrm{starthboxestohbox} \dots \backslash\mathrm{stophboxestohbox}$
$\backslash\mathrm{starthboxregister} \dots \dots \backslash\mathrm{stophboxregister}$ $\ast$ $\mathrm{CSNAME}$ $\mathrm{NUMBER}$
$\backslash\mathrm{starthelp} [\dots] \dots \backslash\mathrm{stophelp}$ $\ast$ $\mathrm{REFERENCE}$ $\mathrm{OPT}$ <b>instances:</b> <b>helptext</b>
$\backslash\mathrm{starthelptext} [\dots] \dots \backslash\mathrm{stophelptext}$ $\ast$ $\mathrm{REFERENCE}$ $\mathrm{OPT}$

$\backslash$ starthighlight [...] ... $\backslash$ stophighlight * NAME
$\backslash$ starthyphenation [...,*...] ... $\backslash$ stophyphenation * original tex implicit hyphenate expanded traditional niciunul
$\backslash$ startimath ... $\backslash$ stopimath
$\backslash$ startimpachetat [...] ... $\backslash$ stopimpachetat * blank OPT
$\backslash$ startindentedtext [...] ... $\backslash$ stopindentedtext * NAME
$\backslash$ startINDENTEDTEXT ... $\backslash$ stopINDENTEDTEXT
$\backslash$ startingust [...] [...] [...] ... $\backslash$ stopingust 1 NAME OPT OPT 2 inherits: \seteazaingust
$\backslash$ startingust [...,*...] [...] [...] ... $\backslash$ stopingust 1 inherits: \seteazaingust OPT 2 [-+]stanga [-+]centru [-+]dreapta NUMMER*stanga NUMMER*centru NUMMER*dreapta reset reverse
$\backslash$ startingust [...] [...] [...] ... $\backslash$ stopingust 1 NAME OPT OPT 2 [-+]stanga [-+]centru [-+]dreapta NUMMER*stanga NUMMER*centru NUMMER*dreapta reset reverse
$\backslash$ startinteractiune [...] ... $\backslash$ stopinteractiune * ascuns NAME
$\backslash$ startinterface *... ... $\backslash$ stopinterface * tot SPRACHE
$\backslash$ startintertext ... $\backslash$ stopintertext
$\backslash$ startitemgroup [...] [...] [...] [...] ... $\backslash$ stopitemgroup 1 NAME OPT OPT 2 inherits: \setupitemgroup 3 inherits: \setupitemgroup
$\backslash$ startITEMGROUP [...,*...] [...] [...] ... $\backslash$ stopITEMGROUP 1 inherits: \setupitemgroup OPT 2 inherits: \setupitemgroup instances: itemize
$\backslash$ startitemize [...,*...] [...] [...] ... $\backslash$ stopitemize 1 inherits: \setupitemgroup OPT 2 inherits: \setupitemgroup
$\backslash$ startJSCode ... .. $\backslash$ stopJSCode 1 NAME 2 uses 3 NAME
$\backslash$ startJSreamble ... .. $\backslash$ stopJSreamble 1 NAME 2 folositi 3 now later

<code>\startknockout ... \stopknockout</code>
<code>\startlayout [...] ... \stoplayout</code> <code>* NAME</code>
<code>\startlinealignment [...] ... \stoplinealignment</code> <code>* stanga centru dreapta max</code>
<code>\startlinecorrection [...,*...] ... \stoplinecorrection</code> <code>* blank inherits: \blanc</code> <small>OPT</small>
<code>\startlinefiller [...<sup>1</sup>] [...,<sup>2</sup>...,...] ... \stoplinefiller</code> <code>1 filler NAME</code> <small>OPT</small> <code>2 inherits: \setuplinefiller</code>
<code>\startLINENOTE [...<sup>1</sup>] {...<sup>2</sup>}</code> <code>1 REFERENCE</code> <code>2 TEXT</code> <code>instances: linenote</code>
<code>\startlinenote [...<sup>1</sup>] {...<sup>2</sup>}</code> <code>1 REFERENCE</code> <code>2 TEXT</code>
<code>\startlinenumbering [...<sup>1</sup>] [...,<sup>2</sup>...,...] ... \stoplinenumbering</code> <code>1 NAME</code> <small>OPT</small> <small>OPT</small> <code>2 continua = da nu</code> <code>start = NUMMER</code> <code>pas = NUMMER</code> <code>metoda = pagina primul urmatorul</code>
<code>\startlinenumbering [...<sup>1</sup>] [...<sup>2</sup>] ... \stoplinenumbering</code> <code>1 NAME</code> <small>OPT</small> <small>OPT</small> <code>2 continuu NUMMER</code>
<code>\startlinetable ... \stoplinetable</code>
<code>\startlinetablebody ... \stoplinetablebody</code>
<code>\startlinetablecell [...,<sup>*</sup>...,...] ... \stoplinetablecell</code> <code>* inherits: \setuplinetable</code> <small>OPT</small>
<code>\startlinetablehead ... \stoplinetablehead</code>
<code>\startlinie [...<sup>*</sup>]</code> <code>* REFERENCE</code>
<code>\startliniemargine [...<sup>*</sup>] ... \stopliniemargine</code> <code>* NUMMER</code> <small>OPT</small>
<code>\startliniemargine [...,<sup>*</sup>...,...] ... \stopliniemargine</code> <code>* inherits: \setupmarginrule</code> <small>OPT</small>
<code>\startLINES [...,<sup>*</sup>...,...] ... \stopLINES</code> <code>* inherits: \seteazal<sup>OPT</sup>iii</code> <code>instances: lines</code>
<code>\startlines [...,<sup>*</sup>...,...] ... \stoplines</code> <code>* inherits: \seteazal<sup>OPT</sup>iii</code>

<code>\startlocalfootnotes ... \stoplocalfootnotes</code>
<code>\startlocalheadsetup ... \stoplocalheadsetup</code>
<code>\startlocallinecorrection [...,*...] ... \stoplocallinecorrection</code> <code>* blank inherits: \blanc</code> <small>OPT</small>
<code>\startlocalnotes [...,*...] ... \stoplocalnotes</code> <code>* NAME</code>
<code>\startlocalsetups [.<sup>1</sup>.] [.<sup>2</sup>.] ... \stoplocalsetups</code> <code>1 grila</code> <small>OPT</small> <code>2 NAME</code>
<code>\startlocalsetups .* ... \stoplocalsetups</code> <code>* NAME</code>
<code>\startlua ... \stoplua</code>
<code>\startluacode ... \stopluacode</code>
<code>\startluaparameterset [.*] ... \stopluaparameterset</code> <code>* NAME</code>
<code>\startluasetups [.<sup>1</sup>.] [.<sup>2</sup>.] ... \stopluasetups</code> <code>1 grila</code> <small>OPT</small> <code>2 NAME</code>
<code>\startluasetups .* ... \stopluasetups</code> <code>* NAME</code>
<code>\startMPclip {...} ... \stopMPclip</code> <code>* NAME</code>
<code>\startMPcode {...} ... \stopMPcode</code> <code>* NAME</code> <small>OPT</small>
<code>\startMPdefinitions {...} ... \stopMPdefinitions</code> <code>* NAME</code> <small>OPT</small>
<code>\startMPdrawing [.*] ... \stopMPdrawing</code> <code>* -</code> <small>OPT</small>
<code>\startMPenvironment [.*] ... \stopMPenvironment</code> <code>* reset global +</code> <small>OPT</small>
<code>\startMPextensions {...,*...} ... \stopMPextensions</code> <code>* NAME</code> <small>OPT</small>
<code>\startMPinclusions [.<sup>1</sup>.] {.<sup>2</sup>.} ... \stopMPinclusions</code> <code>1 +</code> <small>OPT</small> <small>OPT</small> <code>2 NAME</code>
<code>\startMPinitializations ... \stopMPinitializations</code>



$\backslash\text{startMPpositiongraphic}$ <sup>1</sup> {...} <sup>2</sup> {...,...} ... $\backslash\text{stopMPpositiongraphic}$ 1 NAME 2 KEY
$\backslash\text{startMPpositionmethod}$ {...} ... $\backslash\text{stopMPpositionmethod}$ * NAME
$\backslash\text{startMPrun}$ {...} ... $\backslash\text{stopMPrun}$ * NAME
$\backslash\text{startmakeup}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...,... <sub>OPT</sub> ,...] ... $\backslash\text{stopmakeup}$ 1 NAME 2 inherits: $\backslash\text{seteazamakeup}$
$\backslash\text{startMAKEUPmakeup}$ [ <sup>*</sup> ...,... <sub>OPT</sub> ,...] ... $\backslash\text{stopMAKEUPmakeup}$ * inherits: $\backslash\text{seteazamakeup}$ instances: standard page text middle
$\backslash\text{startmiddlemakeup}$ [ <sup>*</sup> ...,... <sub>OPT</sub> ,...] ... $\backslash\text{stopmiddlemakeup}$ * inherits: $\backslash\text{seteazamakeup}$
$\backslash\text{startpagemakeup}$ [ <sup>*</sup> ...,... <sub>OPT</sub> ,...] ... $\backslash\text{stoppagemakeup}$ * inherits: $\backslash\text{seteazamakeup}$
$\backslash\text{startstandardmakeup}$ [ <sup>*</sup> ...,... <sub>OPT</sub> ,...] ... $\backslash\text{stopstandardmakeup}$ * inherits: $\backslash\text{seteazamakeup}$
$\backslash\text{starttextmakeup}$ [ <sup>*</sup> ...,... <sub>OPT</sub> ,...] ... $\backslash\text{stoptextmakeup}$ * inherits: $\backslash\text{seteazamakeup}$
$\backslash\text{startmarginblock}$ [ <sup>*</sup> ...] ... $\backslash\text{stopmarginblock}$ * NAME
$\backslash\text{startmarkedcontent}$ [ <sup>*</sup> ...] ... $\backslash\text{stopmarkedcontent}$ * reset tot NAME
$\backslash\text{startMATHALIGNMENT}$ [ <sup>*</sup> ...,... <sub>OPT</sub> ,...] ... $\backslash\text{stopMATHALIGNMENT}$ * inherits: $\backslash\text{setupmathalignment}$ <sub>OPT</sub> instances: align mathalignment
$\backslash\text{startalign}$ [ <sup>*</sup> ...,... <sub>OPT</sub> ,...] ... $\backslash\text{stopalign}$ * inherits: $\backslash\text{setupmathalignment}$ <sub>OPT</sub>
$\backslash\text{startmathalignment}$ [ <sup>*</sup> ...,... <sub>OPT</sub> ,...] ... $\backslash\text{stopmathalignment}$ * inherits: $\backslash\text{setupmathalignment}$ <sub>OPT</sub>
$\backslash\text{startMATHCASES}$ [ <sup>*</sup> ...,... <sub>OPT</sub> ,...] ... $\backslash\text{stopMATHCASES}$ * inherits: $\backslash\text{setupmathcases}$ <sub>OPT</sub> instances: cases mathcases
$\backslash\text{startcases}$ [ <sup>*</sup> ...,... <sub>OPT</sub> ,...] ... $\backslash\text{stopcases}$ * inherits: $\backslash\text{setupmathcases}$ <sub>OPT</sub>
$\backslash\text{startmathcases}$ [ <sup>*</sup> ...,... <sub>OPT</sub> ,...] ... $\backslash\text{stopmathcases}$ * inherits: $\backslash\text{setupmathcases}$ <sub>OPT</sub>

$\backslash\text{startMATHMATRIX} [\dots,*\dots] \dots \backslash\text{stopMATHMATRIX}$ * inherits: $\backslash\text{setupmathmatrix}^{\text{OPT}}$ instances: matrix mathmatrix
$\backslash\text{startmathmatrix} [\dots,*\dots] \dots \backslash\text{stopmathmatrix}$ * inherits: $\backslash\text{setupmathmatrix}^{\text{OPT}}$
$\backslash\text{startmatrix} [\dots,*\dots] \dots \backslash\text{stopmatrix}$ * inherits: $\backslash\text{setupmathmatrix}^{\text{OPT}}$
$\backslash\text{startmathmode} \dots \backslash\text{stopmathmode}$
$\backslash\text{startmathstyle} [\dots,*\dots] \dots \backslash\text{stopmathstyle}$ * display text script scriptscript cramped uncramped normal impachetat mic mare NAME
$\backslash\text{startmatrices} [\dots,*\dots] \dots \backslash\text{stopmatrices}$ * inherits: $\backslash\text{setupmathmatrix}^{\text{OPT}}$
$\backslash\text{startmaxaligned} \dots \backslash\text{stopmaxaligned}$
$\backslash\text{startmediu} [\dots] \dots \backslash\text{stopmediu}$ * FILE *
$\backslash\text{startmediu} \dots \dots \backslash\text{stopmediu}$ * FILE *
$\backslash\text{startmeniuinteractiune} [\dots] \dots \backslash\text{stopmeniuinteractiune}$ * NAME
$\backslash\text{startmiddlealigned} \dots \backslash\text{stopmiddlealigned}$
$\backslash\text{startmixedcolumns} [\dots] [\dots] [\dots] \dots \backslash\text{stopmixedcolumns}$ 1 NAME OPT OPT 2 inherits: $\backslash\text{setupmixedcolumns}$
$\backslash\text{startMIXEDCOLUMNS} [\dots,*\dots] \dots \backslash\text{stopMIXEDCOLUMNS}$ * inherits: $\backslash\text{setupmixedcolumns}^{\text{OPT}}$ instances: itemgroupcolumns boxedcolumns
$\backslash\text{startboxedcolumns} [\dots,*\dots] \dots \backslash\text{stopboxedcolumns}$ * inherits: $\backslash\text{setupmixedcolumns}^{\text{OPT}}$
$\backslash\text{startitemgroupcolumns} [\dots,*\dots] \dots \backslash\text{stopitemgroupcolumns}$ * inherits: $\backslash\text{setupmixedcolumns}^{\text{OPT}}$
$\backslash\text{startmode} [\dots,*\dots] \dots \backslash\text{stopmode}$ * NAME
$\backslash\text{startmodeset} [\dots] \{\dots\} \dots \backslash\text{stopmodeset}$ 1 NAME implicit 2 CONTENT
$\backslash\text{startmodule} [\dots] \dots \backslash\text{stopmodule}$ * FILE
$\backslash\text{startmoduletestsection} \dots \backslash\text{stopmoduletestsection}$

<pre> \startmodule ... \stopmodule * FILE </pre>
<pre> \startnamedsection [...<sup>1</sup>] [...<sup>2</sup>...] [...<sup>3</sup>...] ... \stopnamedsection 1  ABSCHNITT          OPT          OPT 2  titlu              = TEXT    semncarte          = TEXT    marcaje            = TEXT    lista              = TEXT    referinta          = REFERENCE    numarpropriu       = TEXT 3  KEY = VALUE </pre>
<pre> \startnamedsubformulas [...<sup>1</sup>...] {...<sup>2</sup>} ... \stopnamedsubformulas 1  + - REFERENCE      OPT 2  TEXT </pre>
<pre> \startnarrower [...*,...] ... \stopnarrower *  [-+]stanga [-+]centru<sup>OPT</sup>[-+]dreapta NUMMER*stanga NUMMER*centru NUMMER*dreapta reset reverse </pre>
<pre> \startNARROWER [...*,...] ... \stopNARROWER *  [-+]stanga [-+]centru<sup>OPT</sup>[-+]dreapta NUMMER*stanga NUMMER*centru NUMMER*dreapta reset reverse </pre>
<pre> \startnegativ ... \stopnegativ </pre>
<pre> \startnicelyfilledbox [...,*=...,...] ... \stopnicelyfilledbox *  latime      = DIMENSION      OPT    inaltime    = DIMENSION    offset      = DIMENSION    strut       = da nu </pre>
<pre> \startnointerference ... \stopnointerference </pre>
<pre> \startnotallmodes [...*,...] ... \stopnotallmodes *  NAME </pre>
<pre> \startNOTE [...*,...] ... \stopNOTE *  REFERENCE      OPT instances: footnote endnote </pre>
<pre> \startNOTE [...,*=...,...] ... \stopNOTE *  titlu      = TEXT<sup>OPT</sup>    semncarte  = TEXT    lista      = TEXT    referinta  = REFERENCE instances: footnote endnote </pre>
<pre> \startendnote [...,*=...,...] ... \stopendnote *  titlu      = TEXT      OPT    semncarte  = TEXT    lista      = TEXT    referinta  = REFERENCE </pre>
<pre> \startfootnote [...,*=...,...] ... \stopfootnote *  titlu      = TEXT      OPT    semncarte  = TEXT    lista      = TEXT    referinta  = REFERENCE </pre>
<pre> \startendnote [...*,...] ... \stopendnote *  REFERENCE      OPT </pre>

<code>\startfootnote [...*...] ... \stopfootnote</code> *    REFERENCE                      OPT
<code>\startnotext ... \stopnotext</code>
<code>\startnotmode [...*...] ... \stopnotmode</code> *    NAME
<code>\startopus ... \stopopus</code>
<code>\startoutputstream [...*] ... \stopoutputstream</code> *    NAME
<code>\startoverlay ... \stopoverlay</code>
<code>\startoverprint ... \stopoverprint</code>
<code>\startpagefigure [...<sup>1</sup>...] [......<sup>2</sup>...] ... \stoppagefigure</code> 1    FILE                              OPT 2    offset = implicit overlay niciunul DIMENSION
<code>\startpagegrid [...<sup>1</sup>...] [......<sup>2</sup>...] ... \stoppagegrid</code> 1    NAME                      OPT                      OPT 2    inherits: \setuppagegrid
<code>\startpagegridspan [...<sup>1</sup>...] [......<sup>2</sup>...] ... \stoppagegridspan</code> 1    NAME                              OPT 2    inherits: \setuppagegridspan
<code>\startPAGEGRID [......*...] ... \stopPAGEGRID</code> *    inherits: \setuppagegrid <sup>OPT</sup>
<code>\startpagelayout [...*] ... \stoppagelayout</code> *    pagina paginastanga paginadreapta
<code>\startpar [...<sup>1</sup>...] [......<sup>2</sup>...] ... \stoppar</code> 1    NAME                      OPT                      OPT 2    inherits: \setupparagraph
<code>\startparagraf [...<sup>1</sup>...] [......<sup>2</sup>...] ... \stopparagraf</code> 1    NAME                      OPT                      OPT 2    inherits: \setupparagraph
<code>\startparagraphs [...*] ... \stopparagraphs</code> *    NAME
<code>\startparagraphscell ... \stopparagraphscell</code>
<code>\startPARAGRAPHS ... \stopPARAGRAPHS</code>
<code>\startPARALLEL ... \stopPARALLEL</code>
<code>\startparbuilder [...*] ... \stopparbuilder</code> *    implicit oneline basic NAME

```

\startplacefloat [...1...] [...2...] [...3...] ... \stopplacefloat
1 SINGULAR
2 titlu = TEXT
   semncarte = TEXT
   marcaje = TEXT
   lista = TEXT
   locatie = split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin
             marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge
             text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber
             niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto
             pagina paginastanga paginadreapta undeva effective antet subsol
   referinta = REFERENCE
3 KEY = VALUE

```

```

\startpuneFLOAT [...1...] [...2...] ... \stoppuneFLOAT
1 titlu = TEXT
   semncarte = TEXT
   marcaje = TEXT
   lista = TEXT
   locatie = split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin
             marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge
             text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber
             niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto
             pagina paginastanga paginadreapta undeva effective antet subsol
   referinta = REFERENCE
2 KEY = VALUE
instances: chemical figure table intermezzo graphic

```

```

\startpunechemical [...1...] [...2...] ... \stoppunechemical
1 titlu = TEXT
   semncarte = TEXT
   marcaje = TEXT
   lista = TEXT
   locatie = split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin
             marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge
             text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber
             niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto
             pagina paginastanga paginadreapta undeva effective antet subsol
   referinta = REFERENCE
2 KEY = VALUE

```

```

\startpunefigure [...1...] [...2...] ... \stoppunefigure
1 titlu = TEXT
   semncarte = TEXT
   marcaje = TEXT
   lista = TEXT
   locatie = split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin
             marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge
             text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber
             niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto
             pagina paginastanga paginadreapta undeva effective antet subsol
   referinta = REFERENCE
2 KEY = VALUE

```

```

\startpunegraphic [...1...] [...2...] ... \stoppunegraphic
1 titlu = TEXT
   semncarte = TEXT
   marcaje = TEXT
   lista = TEXT
   locatie = split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin
             marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge
             text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber
             niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto
             pagina paginastanga paginadreapta undeva effective antet subsol
   referinta = REFERENCE
2 KEY = VALUE

```

<pre> \startpuneintermezzo [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] ... \stoppuneintermezzo 1  titlu      = TEXT          OPT          OPT    semncarte = TEXT    marcaje   = TEXT    lista      = TEXT    locatie    = split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin                 marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge                 text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber                 niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto                 pagina paginastanga paginadreapta undeva effective antet subsol    referinta = REFERENCE 2  KEY = VALUE </pre>
<pre> \startpunetable [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] ... \stoppunetable 1  titlu      = TEXT          OPT          OPT    semncarte = TEXT    marcaje   = TEXT    lista      = TEXT    locatie    = split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin                 marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge                 text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber                 niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto                 pagina paginastanga paginadreapta undeva effective antet subsol    referinta = REFERENCE 2  KEY = VALUE </pre>
<pre> \startplacepairedbox [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] ... \stopplacepairedbox 1  NAME          OPT 2  inherits: \setuppairedbox </pre>
<pre> \startpunePAIREDBOX [...,\stackrel{*}{=},...] ... \stoppunePAIREDBOX *  inherits: \setuppairedbox OPT instances: legend </pre>
<pre> \startpunelegend [...,\stackrel{*}{=},...] ... \stoppunelegend *  inherits: \setuppairedbox OPT </pre>
<pre> \startpositioning [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] ... \stoppositioning 1  NAME          OPT          OPT 2  inherits: \setarepozitie </pre>
<pre> \startpositionoverlay {...} ... \stoppositionoverlay *  NAME </pre>
<pre> \startpositiv ... \stoppositiv </pre>
<pre> \startpostponing [...] ... \stoppostponing *  [-+]NUMBER OPT </pre>
<pre> \startprocessassignmentcommand [...,\stackrel{*}{=},...] ... \stopprocessassignmentcommand *  KEY = VALUE </pre>
<pre> \startprocessassignmentlist [...,\stackrel{*}{=},...] ... \stopprocessassignmentlist *  KEY = VALUE </pre>
<pre> \startprocesscommacommand [...,*,...] ... \stopprocesscommacommand *  BEFEHL </pre>
<pre> \startprocesscommalist [...,*,...] ... \stopprocesscommalist *  BEFEHL </pre>
<pre> \startprodus [...] ... \stopprodus *  FILE * </pre>

\startprodus ... \stopprodus * FILE *
\startproiect [...] ... \stopproiect * FILE *
\startproiect ... \stopproiect * FILE *
\startprotectedcolors ... \stopprotectedcolors
\startpublicatie [...] [...] ... \stoppublicatie 1 NAME OPT OPT 2 tag = REFERENCE category = TEXT k = REFERENCE t = TEXT
\startpuneformula [...] [...] ... \stoppuneformula * titlu = TEXT OPT suffix = TEXT referinta = + - REFERENCE
\startpuneformula [...] [...] ... \stoppuneformula * + - REFERENCE OPT
\starandomized ... \stoprandomized
\starawsetups [...] [...] ... \stoprawsetups 1 grila OPT 2 NAME
\starawsetups ... \stoprawsetups * NAME
\startreadingfile ... \stopreadingfile
\startregime [...] ... \stopregime * inherits: \enableregime
\startregister [...] [...] [...] [...] [...] [...] ... 1 NAME OPT OPT 2 NAME 3 TEXT 4 TEXT PROCESSOR->TEXT 5 INDEX
\startreusableMPgraphic [...] [...] ... \stopreusableMPgraphic 1 NAME OPT 2 KEY
\stariglatext [...] ... \stopriglatext * TEXT
\startscript [...] ... \stopscript * hangul hanzi nihongo ethiopic thai test NAME
\startsectionblock [...] [...] ... \stopsectionblock 1 NAME OPT 2 semncarte = TEXT inherits: \seteazablocsectiune

```

\startSECTIONBLOCK [...,..1...,...] ... \stopSECTIONBLOCK
*   semncarte = TEXT OPT
    inherits: \seteazablocsectione
instances: frontmatter bodymatter appendices backmatter

```

```

\startappendices [...,..1...,...] ... \stopappendices
*   semncarte = TEXT OPT
    inherits: \seteazablocsectione

```

```

\startbackmatter [...,..1...,...] ... \stopbackmatter
*   semncarte = TEXT OPT
    inherits: \seteazablocsectione

```

```

\startbodymatter [...,..1...,...] ... \stopbodymatter
*   semncarte = TEXT OPT
    inherits: \seteazablocsectione

```

```

\startfrontmatter [...,..1...,...] ... \stopfrontmatter
*   semncarte = TEXT OPT
    inherits: \seteazablocsectione

```

```

\startsectionlevel [...,..1...,...] [...,..2...,...] [...,..3...,...] ... \stopsectionlevel
1   NAME OPT OPT OPT
2   titlu      = TEXT
    semncarte  = TEXT
    marcaje    = TEXT
    lista      = TEXT
    referinta  = REFERENCE
    numarpropriu = TEXT
3   KEY = VALUE

```

```

\startSECTION [...,..1...,...] [...,..2...,...] ... \stopSECTION
1   titlu      = TEXT OPT OPT
    semncarte  = TEXT
    marcaje    = TEXT
    lista      = TEXT
    referinta  = REFERENCE
    numarpropriu = TEXT
2   KEY = VALUE
instances: part chapter section subsection subsubsection subsubsubsection subsubsubsubsection
title subject subsubject subsubsubject subsubsubsubject subsubsubsubsubject

```

```

\startchapter [...,..1...,...] [...,..2...,...] ... \stopchapter
1   titlu      = TEXT OPT OPT
    semncarte  = TEXT
    marcaje    = TEXT
    lista      = TEXT
    referinta  = REFERENCE
    numarpropriu = TEXT
2   KEY = VALUE

```

```

\startpart [...,..1...,...] [...,..2...,...] ... \stoppart
1   titlu      = TEXT OPT OPT
    semncarte  = TEXT
    marcaje    = TEXT
    lista      = TEXT
    referinta  = REFERENCE
    numarpropriu = TEXT
2   KEY = VALUE

```

```

\startsection [...,..1...,...] [...,..2...,...] ... \stopsection
1   titlu      = TEXT OPT OPT
    semncarte  = TEXT
    marcaje    = TEXT
    lista      = TEXT
    referinta  = REFERENCE
    numarpropriu = TEXT
2   KEY = VALUE

```



`\startsubject [...,\u{1}...,...]\ [...,\u{2}...,...]\ ... \stopsubject`

1 titlu = TEXT OPT OPT  
semncarte = TEXT  
marcaje = TEXT  
lista = TEXT  
referinta = REFERENCE  
numarpropriu = TEXT  
2 KEY = VALUE

`\startsubsection [...,\u{1}...,...]\ [...,\u{2}...,...]\ ... \stopsubsection`

1 titlu = TEXT OPT OPT  
semncarte = TEXT  
marcaje = TEXT  
lista = TEXT  
referinta = REFERENCE  
numarpropriu = TEXT  
2 KEY = VALUE

`\startsubsubject [...,\u{1}...,...]\ [...,\u{2}...,...]\ ... \stopsubsubject`

1 titlu = TEXT OPT OPT  
semncarte = TEXT  
marcaje = TEXT  
lista = TEXT  
referinta = REFERENCE  
numarpropriu = TEXT  
2 KEY = VALUE

`\startsubsubsection [...,\u{1}...,...]\ [...,\u{2}...,...]\ ... \stopsubsubsection`

1 titlu = TEXT OPT OPT  
semncarte = TEXT  
marcaje = TEXT  
lista = TEXT  
referinta = REFERENCE  
numarpropriu = TEXT  
2 KEY = VALUE

`\startsubsubsubject [...,\u{1}...,...]\ [...,\u{2}...,...]\ ... \stopsubsubsubject`

1 titlu = TEXT OPT OPT  
semncarte = TEXT  
marcaje = TEXT  
lista = TEXT  
referinta = REFERENCE  
numarpropriu = TEXT  
2 KEY = VALUE

`\startsubsubsubsection [...,\u{1}...,...]\ [...,\u{2}...,...]\ ... \stopsubsubsubsection`

1 titlu = TEXT OPT OPT  
semncarte = TEXT  
marcaje = TEXT  
lista = TEXT  
referinta = REFERENCE  
numarpropriu = TEXT  
2 KEY = VALUE

`\startsubsubsubsubject [...,\u{1}...,...]\ [...,\u{2}...,...]\ ... \stopsubsubsubsubject`

1 titlu = TEXT OPT OPT  
semncarte = TEXT  
marcaje = TEXT  
lista = TEXT  
referinta = REFERENCE  
numarpropriu = TEXT  
2 KEY = VALUE

`\startsubsubsubsubsection [...,\u{1}...,...]\ [...,\u{2}...,...]\ ... \stopsubsubsubsubsection`

1 titlu = TEXT OPT OPT  
semncarte = TEXT  
marcaje = TEXT  
lista = TEXT  
referinta = REFERENCE  
numarpropriu = TEXT  
2 KEY = VALUE

<pre> \startsubsubsubsubsubject [...,\subscript{1}...,...]\stopsubsubsubsubsubject 1  titlu           = TEXT    semncarte      = TEXT    marcaje        = TEXT    lista          = TEXT    referinta      = REFERENCE    numarpropriu   = TEXT 2  KEY = VALUE </pre>
<pre> \starttitle [...,\subscript{1}...,...]\stoptitle 1  titlu           = TEXT    semncarte      = TEXT    marcaje        = TEXT    lista          = TEXT    referinta      = REFERENCE    numarpropriu   = TEXT 2  KEY = VALUE </pre>
<pre> \startsetups [\subscript{1}...] [\subscript{2}...] ... \stopsetups 1  grila          = TEXT 2  NAME </pre>
<pre> \startsetups ... .. \stopsetups *  NAME </pre>
<pre> \startshift [...]\stopshift *  NAME </pre>
<pre> \startsidebar [\subscript{1}...] [\subscript{2}...,...]\stopsidebar 1  NAME 2  inherits: \setupsidebar </pre>
<pre> \startsimplecolumns [...,\subscript{1}...,...]\stopsimplecolumns *  inherits: \setsimplecolumnsize </pre>
<pre> \startspecialitem [\subscript{1}...] [\subscript{2}...,...]\stopspecialitem 1  element 2  REFERENCE </pre>
<pre> \startspecialitem [...]\stopspecialitem *  sub propriu </pre>
<pre> \startspecialitem [...] {\subscript{1}...} \stopspecialitem 1  sym rulat mar 2  TEXT </pre>
<pre> \startsplitformula ... \stopsplitformula </pre>
<pre> \startspread ... \stopspread </pre>
<pre> \start [...] ... \stop *  NAME </pre>
<pre> \startSTARTSTOP ... \stopSTARTSTOP </pre>
<pre> \startstaticMPfigure {...} ... \stopstaticMPfigure *  NAME </pre>
<pre> \startstaticMPgraphic {\subscript{1}...} {\subscript{2}...,...} ... \stopstaticMPgraphic 1  NAME 2  KEY </pre>

\STARTSTOP {...} *   CONTENT
\startstrictinspectnextcharacter ... \stopstrictinspectnextcharacter
\startstructurepageregister [...] <sup>1</sup> [...] <sup>2</sup> [...,... <sup>3</sup> ...,...] <sup>4</sup> [...,... <sup>4</sup> ...,...] <sup>OPT</sup> 1   NAME 2   NAME 3   eticheta     =   NAME keys       =   TEXT   PROCESSOR->TEXT entries    =   TEXT   PROCESSOR->TEXT keys:1     =   TEXT keys:2     =   TEXT keys:3     =   TEXT entries:1  =   TEXT entries:2  =   TEXT entries:3  =   TEXT alternativ =   TEXT 4   KEY =   VALUE
\startstyle [...,... <sup>*</sup> ...,...] *   inherits: \setupstyle
\startstyle [...] <sup>*</sup> ... \stopstyle *   NAME FONT
\startSTYLE ... \stopSTYLE
\startsubformulas [...,...] <sup>*</sup> ... \stopsubformulas *   + - REFERENCE <sup>OPT</sup>
\startsubjectlevel [...] <sup>1</sup> [...,... <sup>2</sup> ...,...] <sup>OPT</sup> [...,... <sup>3</sup> ...,...] <sup>OPT</sup> ... \stopsubjectlevel <sup>OPT</sup> 1   NAME 2   titlu        =   TEXT semncarte   =   TEXT marcaje     =   TEXT lista       =   TEXT referinta   =   REFERENCE numarpropriu =   TEXT 3   KEY =   VALUE
\startsubsentence ... \stopsubsentence
\startsubsolabel [...] <sup>*</sup> ... \stopsubsolabel *   NAME
\startsubstack ... \stopsubstack
\startsuspendat [...,... <sup>1</sup> ...,...] <sup>OPT</sup> {...} <sup>2</sup> ... \stopsuspendat 1   distanta   =   DIMENSION <sup>OPT</sup> n         =   NUMMER locatie   =   stanga dreapta 2   CONTENT
\startsuspendat [...] <sup>1</sup> {...} <sup>2</sup> ... \stopsuspendat <sup>OPT</sup> 1   stanga dreapta 2   CONTENT
\startsymbolset [...] <sup>*</sup> ... \stopsymbolset *   NAME
\startTABLE [...,... <sup>*</sup> ...,...] *   inherits: \setupTABLE <sup>OFF</sup>

$\backslash\text{startTABLEbody}$ [ $\dots$ $\overset{*}{=}\dots$ ] ... $\backslash\text{stopTABLEbody}$ $*$ inherits: $\backslash\text{setupTABLE}$ <small>OPT</small>
$\backslash\text{startTABLEfoot}$ [ $\dots$ $\overset{*}{=}\dots$ ] ... $\backslash\text{stopTABLEfoot}$ $*$ inherits: $\backslash\text{setupTABLE}$ <small>OPT</small>
$\backslash\text{startTABLEhead}$ [ $\dots$ $\overset{*}{=}\dots$ ] ... $\backslash\text{stopTABLEhead}$ $*$ inherits: $\backslash\text{setupTABLE}$ <small>OPT</small>
$\backslash\text{startTABLEnext}$ [ $\dots$ $\overset{*}{=}\dots$ ] ... $\backslash\text{stopTABLEnext}$ $*$ inherits: $\backslash\text{setupTABLE}$ <small>OPT</small>
$\backslash\text{starttabellele}$ [ $ \dots $ ] ... $\backslash\text{stoptabellele}$ $*$ TEMPLATE
$\backslash\text{starttabellele}$ [ $\dots$ ] ... $\backslash\text{stoptabellele}$ $*$ NAME
$\backslash\text{starttabelul}$ [ $ \overset{1}{\dots} $ ] [ $\dots$ $\overset{2}{=}\dots$ ] ... $\backslash\text{stoptabelul}$ 1 TEMPLATE <small>OPT</small> 2 inherits: $\backslash\text{seteazatabele}$
$\backslash\text{starttabelul}$ [ $\overset{1}{\dots}$ ] [ $\dots$ $\overset{2}{=}\dots$ ] ... $\backslash\text{stoptabelul}$ 1 NAME <small>OPT</small> 2 inherits: $\backslash\text{seteazatabele}$
$\backslash\text{starttabulate}$ [ $ \overset{1}{\dots} $ ] [ $\dots$ $\overset{2}{=}\dots$ ] ... $\backslash\text{stoptabulate}$ 1 TEMPLATE <small>OPT</small> <small>OPT</small> 2 inherits: $\backslash\text{seteazatabulatori}$
$\backslash\text{starttabulatehead}$ [ $\dots$ ] ... $\backslash\text{stoptabulatehead}$ $*$ NAME <small>OPT</small>
$\backslash\text{starttabulatetail}$ [ $\dots$ ] ... $\backslash\text{stoptabulatetail}$ $*$ NAME <small>OPT</small>
$\backslash\text{startTABULATE}$ [ $\overset{1}{\dots}$ ] [ $\dots$ $\overset{2}{=}\dots$ ] ... $\backslash\text{stopTABULATE}$ 1 NAME <small>OPT</small> <small>OPT</small> 2 inherits: $\backslash\text{seteazatabulatori}$ instances: legend fact
$\backslash\text{startfact}$ [ $\overset{1}{\dots}$ ] [ $\dots$ $\overset{2}{=}\dots$ ] ... $\backslash\text{stopfact}$ 1 NAME <small>OPT</small> <small>OPT</small> 2 inherits: $\backslash\text{seteazatabulatori}$
$\backslash\text{startlegend}$ [ $\overset{1}{\dots}$ ] [ $\dots$ $\overset{2}{=}\dots$ ] ... $\backslash\text{stoplegend}$ 1 NAME <small>OPT</small> <small>OPT</small> 2 inherits: $\backslash\text{seteazatabulatori}$
$\backslash\text{startTABULATION}$ [ $\overset{1}{\dots}$ ] [ $\dots$ $\overset{2}{=}\dots$ ] ... $\backslash\text{stopTABULATION}$ 1 NAME <small>OPT</small> <small>OPT</small> 2 inherits: $\backslash\text{setuptabulation}$
$\backslash\text{starttexcode}$ ... $\backslash\text{stoptexcode}$

```

\starttexdefinition ...1 ...2 ...3 ...4 ...5 ...6 ...7 ... \stoptexdefinition
1  spaces nospaces      OPT  OPT  OPT  OPT  OPT  OPT
2  global
3  unexpanded
4  expanded
5  singleempty doubleempty tripleempty quadrupleempty quintupleempty sextupleempty singleargument doubleargument
   tripleargument quadrupleargument quintupleargument sextupleargument
6  NAME
7  TEMPLATE

```

```

\starttext ... \stoptext

```

```

\starttextajutator [...]* ... \stoptextajutator
*  REFERENCE      OPT

```

```

\starttextbackground [...]1 [...]2 ... \stoptextbackground
1  NAME      OPT
2  inherits: \setuptextbackground

```

```

\starttextbackgroundmanual ... \stoptextbackgroundmanual

```

```

\startTEXTBACKGROUND [...]* ... \stopTEXTBACKGROUND
*  inherits: \setuptextbackground OPT

```

```

\starttextcolor [...]* ... \stoptextcolor
*  COLOR

```

```

\starttextcolorintent ... \stoptextcolorintent

```

```

\startLABELtext [...]1 [...]2 ... \stopLABELtext
1  SPRACHE      OPT
2  KEY
instances: head label mathlabel taglabel unit operator prefix suffix btxlabel

```

```

\startbtxlabeltext [...]1 [...]2 ... \stopbtxlabeltext
1  SPRACHE      OPT
2  KEY

```

```

\startheadtext [...]1 [...]2 ... \stoptheadtext
1  SPRACHE      OPT
2  KEY

```

```

\startlabeltext [...]1 [...]2 ... \stoplabeltext
1  SPRACHE      OPT
2  KEY

```

```

\startmathlabeltext [...]1 [...]2 ... \stopmathlabeltext
1  SPRACHE      OPT
2  KEY

```

```

\startoperatortext [...]1 [...]2 ... \stopoperatortext
1  SPRACHE      OPT
2  KEY

```

```

\startprefixtext [...]1 [...]2 ... \stopprefixtext
1  SPRACHE      OPT
2  KEY

```

```

\startsuffixtext [...]1 [...]2 ... \stopsuffixtext
1  SPRACHE      OPT
2  KEY

```

$\backslash\text{starttaglabeltext}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...] ... $\backslash\text{stoptaglabeltext}$ 1 SPRACHE OPT 2 KEY
$\backslash\text{startunittext}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...] ... $\backslash\text{stopunittext}$ 1 SPRACHE OPT 2 KEY
$\backslash\text{starttextflow}$ [...] ... $\backslash\text{stoptextflow}$ * NAME
$\backslash\text{startFRAMEDTEXT}$ [ <sup>1</sup> ...] [..., <sup>2</sup> ...,...] ... $\backslash\text{stopFRAMEDTEXT}$ 1 stanga dreapta centr <sup>P</sup> iniunul OPT 2 inherits: $\backslash\text{setupframedtext}$ <b>instances: framedtext</b>
$\backslash\text{startframedtext}$ [ <sup>1</sup> ...] [..., <sup>2</sup> ...,...] ... $\backslash\text{stopframedtext}$ 1 stanga dreapta centr <sup>P</sup> iniunul OPT 2 inherits: $\backslash\text{setupframedtext}$
$\backslash\text{starttitlu}$ [..., <sup>1</sup> ...] { <sup>2</sup> ...} ... $\backslash\text{stoptitlu}$ 1 REFERENCE OPT 2 TEXT
$\backslash\text{starttokens}$ [...] ... $\backslash\text{stoptokens}$ * NAME
$\backslash\text{starttransparent}$ [...] ... $\backslash\text{stoptransparent}$ * COLOR
$\backslash\text{starttypescript}$ [..., <sup>1</sup> ...] [..., <sup>2</sup> ...] [..., <sup>3</sup> ...] ... $\backslash\text{stoptypescript}$ 1 serif sans mono math hand <sup>w</sup> riting calligraphy OPT 2 NAME 3 size nume
$\backslash\text{starttypescriptcollection}$ [...] ... $\backslash\text{stoptypescriptcollection}$ * NAME
$\backslash\text{startTYPING}$ [..., <sup>*</sup> ...,...] ... $\backslash\text{stopTYPING}$ * inherits: $\backslash\text{seteazatyPing}$ <b>instances: typing</b> LUA MP PARSEDXML TEX XML
$\backslash\text{startTYPING}$ [..., <sup>*</sup> ...] ... $\backslash\text{stopTYPING}$ * continuu OPT <b>instances: typing</b> LUA MP PARSEDXML TEX XML
$\backslash\text{startLUA}$ [..., <sup>*</sup> ...] ... $\backslash\text{stopLUA}$ * continuu OPT
$\backslash\text{startMP}$ [..., <sup>*</sup> ...] ... $\backslash\text{stopMP}$ * continuu OPT
$\backslash\text{startPARSEDXML}$ [..., <sup>*</sup> ...] ... $\backslash\text{stopPARSEDXML}$ * continuu OPT
$\backslash\text{startTEX}$ [..., <sup>*</sup> ...] ... $\backslash\text{stopTEX}$ * continuu OPT

```
*      continuu                                OPT
```

```
*      continuu      OPT
```

```
* inherits: \seteazatypingOPT
```

```
* inherits: \seteazatypingOPT
```

```
* inherits: \seteazatypingOPT
```

```
* inherits: \seteazOPTtyping
```

```
* inherits: \seteazatypingOPT
```

```
* inherits: \seteazOPTtyping
```

```

1  NAME                                     OPT
2  KEY

```

```

1  NAME                                OPT
2  KEY

```

```

1  NAME                                OPT
2  KEY

```

```

1  NAME                                OPT
2  KEY

```

\* CSNAME

\* NAME

\* CSNAME NUMMER

`\startvboxtohbox ... \stopvboxtohbox`

`\startvboxtohboxseparator ... \stopvboxtohboxseparator`

\* NAME

```
\startVIEWERLAYER ... \stopVIEWERLAYER
```

<pre> \startvtopregister ... \stopvtopregister * CSNAME NUMBER </pre>
<pre> \startxcell [...] [...] ... \stopxcell 1 NAME OPT OPT 2 nx = NUMBER ny = NUMBER nc = NUMBER nr = NUMBER inherits: \setupxtable </pre>
<pre> \startxcellgroup [...] [...] ... \stopxcellgroup 1 NAME OPT OPT 2 inherits: \setupxtable </pre>
<pre> \startxgroup [...] [...] ... \stopxgroup 1 NAME OPT OPT 2 inherits: \setupxtable </pre>
<pre> \startxmldisplayverbatim [...] ... \stopxmldisplayverbatim * NAME </pre>
<pre> \startxmllineverbatim [...] ... \stopxmllineverbatim * NAME </pre>
<pre> \startxmlraw ... \stopxmlraw </pre>
<pre> \startxmlsetups [...] [...] ... \stopxmlsetups 1 grila OPT 2 NAME </pre>
<pre> \startxmlsetups ... \stopxmlsetups * NAME </pre>
<pre> \startxrow [...] [...] ... \stopxrow 1 NAME OPT OPT 2 inherits: \setupxtable </pre>
<pre> \startxrowgroup [...] [...] ... \stopxrowgroup 1 NAME OPT OPT 2 inherits: \setupxtable </pre>
<pre> \startxtable [...] [...] ... \stopxtable * inherits: \setupxtable </pre>
<pre> \startxtablebody [...] [...] ... \stopxtablebody * inherits: \setupxtable OPT </pre>
<pre> \startxtablebody [...] ... \stopxtablebody * NAME OPT </pre>
<pre> \startxtablefoot [...] [...] ... \stopxtablefoot * inherits: \setupxtable OPT </pre>
<pre> \startxtablefoot [...] ... \stopxtablefoot * NAME OPT </pre>
<pre> \startxtablehead [...] [...] ... \stopxtablehead * inherits: \setupxtable OPT </pre>





<code>\structurelistuservariable {...}</code> * KEY
<code>\structurenumber</code>
<code>\structuretitle</code>
<code>\structureuservariable {...}</code> * KEY
<code>\structurevariable {...}</code> * KEY
<code>\strut</code>
<code>\strutdp</code>
<code>\strutgap</code>
<code>\strutht</code>
<code>\struthtdp</code>
<code>\struttedbox {...}</code> * CONTENT
<code>\strutwd</code>
<code>\style [...<sup>1</sup>...<sup>2</sup>...] {...}</code> 1 inherits: \setupstyle 2 TEXT
<code>\styleinstance [...]</code> * NAME
<code>\style [...<sup>1</sup>] {...<sup>2</sup>}</code> 1 NAME FONT 2 TEXT
<code>\STYLE {...}</code> * TEXT
<code>\subpagenumber</code>
<code>\subsentence {...}</code> * CONTENT
<code>\substituteincommalist {...<sup>1</sup>} {...<sup>2</sup>} \<sup>3</sup>...</code> 1 TEXT 2 TEXT 3 CSNAME
<code>\subtractfeature [...]</code> * NAME

<code>\subtractfeature {...}</code> *    NAME
<code>\swapcounts \<sup>1</sup>... \<sup>2</sup>...</code> 1    CSNAME 2    CSNAME
<code>\swapdimens \<sup>1</sup>... \<sup>2</sup>...</code> 1    CSNAME 2    CSNAME
<code>\swapface</code>
<code>\swapmacros \<sup>1</sup>... \<sup>2</sup>...</code> 1    CSNAME 2    CSNAME
<code>\swaptypesface</code>
<code>\switchstyleonly [...]</code> *    rm ss tt hw cg roman serif regular sans sansserif suport type teletype mono scrismmanual caligrafic
<code>\switchstyleonly \<sup>*</sup>...</code> *    CSNAME
<code>\switchtocolour [...]</code> *    COLOR
<code>\switchtointerlinespace [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]</code> 1    NAME <span style="float:right">OPT</span> 2    inherits: \seteazaspatiuinterliniar
<code>\switchtointerlinespace [...,<sup>*</sup>...]</code> *    on dezactivat reset auto mic med <sup>OPT</sup> mare NUMMER DIMENSION
<code>\switchtointerlinespace [...]</code> *    NAME
<code>\symbolreference [...]</code> *    REFERENCE
<code>\synchronizeblank</code>
<code>\synchronizeindenting</code>
<code>\synchronizemarking [...]<sup>1</sup> [...]<sup>2</sup> [...]<sup>3</sup></code> 1    BESCHRIFTUNG <span style="float:right">OPT</span> 2    NUMMER 3    mentine
<code>\synchronizeoutputstreams [...,<sup>*</sup>...]</code> *    NAME
<code>\synchronizestrut {...}</code> *    da nu auto cap ajustat linie implicit CHARACTER
<code>\synchronizewhitespace</code>

<code>\synctexblockfilename {...}</code> <code>* FILE</code>
<code>\synctexresetfilename</code>
<code>\synctexsetfilename {...}</code> <code>* FILE</code>
<code>\SYNONYM [...]<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup></code> <code>1 NAME OPT</code> <code>2 TEXT</code> <code>3 CONTENT</code> <b>instances:</b> abbreviation
<code>\abbreviation [...]<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup></code> <code>1 NAME OPT</code> <code>2 TEXT</code> <code>3 CONTENT</code>
<code>\systemlog {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup></code> <code>1 FILE</code> <code>2 TEXT</code> <code>3 TEXT</code>
<code>\systemlogfirst {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup></code> <code>1 FILE</code> <code>2 TEXT</code> <code>3 TEXT</code>
<code>\systemloglast {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup></code> <code>1 FILE</code> <code>2 TEXT</code> <code>3 TEXT</code>
<code>\systemsetups {...}</code> <code>* NAME</code>
<code>\TABLE</code>
<code>\TaBlE</code>
<code>\TEX</code>
<code>\TeX</code>
<code>\TheNormalizedFontSize</code>
<code>\TransparencyHack</code>
<code>\tabulateautoline</code>
<code>\tabulateautorule</code>
<code>\tabulateline</code>
<code>\tabulaterule</code>

<code>\taggedctxcommand {...}</code> *    BEFEHL
<code>\taggedlabeltexts {.<sup>1</sup>.} {.<sup>2</sup>.} {.<sup>3</sup>.}</code> 1    NAME 2    NAME 3    CONTENT
<code>\tbox {...}</code> *    CONTENT
<code>\testandsplitstring .<sup>1</sup>. \at .<sup>2</sup>. \to \.<sup>3</sup>. \and \.<sup>4</sup>.</code> 1    TEXT 2    TEXT 3    CSNAME 4    CSNAME
<code>\testcolumn [.<sup>1</sup>.] [.<sup>2</sup>.]</code> 1    NUMMER                    OPT 2    DIMENSION
<code>\testfeature {.<sup>1</sup>.} {.<sup>2</sup>.}</code> 1    NUMMER 2    CONTENT
<code>\testfeatureonce {.<sup>1</sup>.} {.<sup>2</sup>.}</code> 1    NUMMER 2    CONTENT
<code>\testpage [.<sup>1</sup>.] [.<sup>2</sup>.]</code> 1    NUMMER                    OPT 2    DIMENSION
<code>\testpageonly [.<sup>1</sup>.] [.<sup>2</sup>.]</code> 1    NUMMER                    OPT 2    DIMENSION
<code>\testpagesync [.<sup>1</sup>.] [.<sup>2</sup>.]</code> 1    NUMMER                    OPT 2    DIMENSION
<code>\testtokens [.<sup>*</sup>.]</code> *    NAME
<code>\tex {...}</code> *    CONTENT
<code>\texdefinition {...}</code> *    NAME
<code>\texsetup {...}</code> *    NAME
<code>\textajutator [.<sup>1</sup>.] {.<sup>2</sup>.} {.<sup>3</sup>.}</code> 1    REFERENCE                OPT 2    TEXT 3    TEXT
<code>\TEXTBACKGROUND {...}</code> *    CONTENT

```

\textcitation [...1...][...2...]
1  referinta = REFERENCE
   alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
               authorityyear
   inainte   = BEFEHL
   dupa      = BEFEHL
   stanga    = BEFEHL
   dreapta   = BEFEHL
   inherits: \setupbtx
2  REFERENCE

```

```

\textcitation [...1...][...2...]
1  implicit categoryOP entry short pagina num textnum an index tag keywords autor authoryears authornum authorityyear
2  REFERENCE

```

```

\textcitation [...1...][...2...]
1  referinta = REFERENCE
   alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
               authorityyear
   inainte   = BEFEHL
   dupa      = BEFEHL
   stanga    = BEFEHL
   dreapta   = BEFEHL
   inherits: \setupbtx
2  KEY = VALUE

```

```

\textcite [...1...][...2...]
1  referinta = REFERENCE
   alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
               authorityyear
   inainte   = BEFEHL
   dupa      = BEFEHL
   stanga    = BEFEHL
   dreapta   = BEFEHL
   inherits: \setupbtx
2  REFERENCE

```

```

\textcite [...1...][...2...]
1  implicit categoryOP entry short pagina num textnum an index tag keywords autor authoryears authornum authorityyear
2  REFERENCE

```

```

\textcite [...1...][...2...]
1  referinta = REFERENCE
   alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
               authorityyear
   inainte   = BEFEHL
   dupa      = BEFEHL
   stanga    = BEFEHL
   dreapta   = BEFEHL
   inherits: \setupbtx
2  KEY = VALUE

```

```

\textcontrolspace

```

```

\LABELtext {...}
* KEY
instances: head label mathlabel taglabel unit operator prefix suffix btxlabel

```

```

\btxlabeltext {...}
* KEY

```

```

\headtext {...}
* KEY

```

```

\labeltext {...}
* KEY

```

$\backslash\mathrm{mathlabeltext}\{...\}$ * KEY
$\backslash\mathrm{operatortext}\{...\}$ * KEY
$\backslash\mathrm{prefixtext}\{...\}$ * KEY
$\backslash\mathrm{suffixtext}\{...\}$ * KEY
$\backslash\mathrm{taglabeltext}\{...\}$ * KEY
$\backslash\mathrm{unittext}\{...\}$ * KEY
$\backslash\mathrm{textflowcollector}\{...\}$ * NAME
$\backslash\mathrm{FRAMEDTEXT}[\dots\overset{1}{=}\dots]\{\overset{2}{.}\}$ 1 inherits: $\backslash\mathrm{setupframedtext}$ 2 CONTENT instances: framedtext
$\backslash\mathrm{framedtext}[\dots\overset{1}{=}\dots]\{\overset{2}{.}\}$ 1 inherits: $\backslash\mathrm{setupframedtext}$ 2 CONTENT
$\backslash\mathrm{textmath}\{...\}$ * CONTENT
$\backslash\mathrm{textminus}$
$\backslash\mathrm{textormathchar}\{...\}$ * NUMBER
$\backslash\mathrm{textplus}$
$\backslash\mathrm{textumplere}[\dots\overset{1}{=}\dots]\{\overset{2}{.}\}\{\overset{3}{.}\}$ 1 inherits: $\backslash\mathrm{seteazarigtextumplere}$ OPT OPT 2 TEXT 3 TEXT
$\backslash\mathrm{textvisiblespace}$
$\backslash\mathrm{thainumerals}\{...\}$ * NUMBER
$\backslash\mathrm{thefirstcharacter}\{...\}$ * TEXT
$\backslash\mathrm{thenormalizedbodyfontsize}\{...\}$ * DIMENSION
$\backslash\mathrm{theremainingcharacters}\{...\}$ * TEXT

<code>\thickspace</code>
<code>\thinspace</code>
<code>\thirtoffivearguments {<sup>1</sup>.} {<sup>2</sup>.} {<sup>3</sup>.} {<sup>4</sup>.} {<sup>5</sup>.}</code> 1    TEXT 2    TEXT 3    TEXT 4    TEXT 5    TEXT
<code>\thirtoffourarguments {<sup>1</sup>.} {<sup>2</sup>.} {<sup>3</sup>.} {<sup>4</sup>.}</code> 1    TEXT 2    TEXT 3    TEXT 4    TEXT
<code>\thirdotsixarguments {<sup>1</sup>.} {<sup>2</sup>.} {<sup>3</sup>.} {<sup>4</sup>.} {<sup>5</sup>.} {<sup>6</sup>.}</code> 1    TEXT 2    TEXT 3    TEXT 4    TEXT 5    TEXT 6    TEXT
<code>\thir dofthreearguments {<sup>1</sup>.} {<sup>2</sup>.} {<sup>3</sup>.}</code> 1    TEXT 2    TEXT 3    TEXT
<code>\thir dofthreeunexpanded {<sup>1</sup>.} {<sup>2</sup>.} {<sup>3</sup>.}</code> 1    TEXT 2    TEXT 3    TEXT
<code>\threedigitrounding {<sup>*</sup>.}</code> *    NUMBER
<code>\tibetan numerals {<sup>*</sup>.}</code> *    NUMBER
<code>\tightlayer [<sup>*</sup>.]</code> *    NAME
<code>\tilde {<sup>*</sup>.}</code> *    CHARACTER
<code>\tinyfont</code>
<code>\tlap {<sup>*</sup>.}</code> *    CONTENT
<code>\tochar {<sup>*</sup>.}</code> *    e:NAME x:NUMBER d:NUMBER s:NUMBER i:NUMBER n:NAME c:NAME u:NAME a:NAME
<code>\tolinenote [<sup>*</sup>.]</code> *    REFERENCE



<code>\TOOLTIP [...<sup>1</sup>...<sup>2</sup>...<sup>3</sup>]</code> <code>1 inherits: \setup<sup>OPT</sup>tooltip</code> <code>2 TEXT</code> <code>3 TEXT</code> <code>instances: tooltip</code>
<code>\TOOLTIP [...<sup>1</sup>...] {...<sup>2</sup>} {...<sup>3</sup>}</code> <code>1 stanga centru dreapta</code> <code>2 TEXT</code> <code>3 TEXT</code> <code>instances: tooltip</code>
<code>\tooltip [...<sup>1</sup>...] {...<sup>2</sup>} {...<sup>3</sup>}</code> <code>1 stanga centru dreapta</code> <code>2 TEXT</code> <code>3 TEXT</code>
<code>\tooltip [...<sup>1</sup>...<sup>2</sup>...<sup>3</sup>...] {...<sup>2</sup>} {...<sup>3</sup>}</code> <code>1 inherits: \setup<sup>OPT</sup>tooltip</code> <code>2 TEXT</code> <code>3 TEXT</code>
<code>\topbox {...}</code> <code>* CONTENT</code>
<code>\topleftbox {...}</code> <code>* CONTENT</code>
<code>\toplinebox {...}</code> <code>* CONTENT</code>
<code>\toprightbox {...}</code> <code>* CONTENT</code>
<code>\topskippedbox {...}</code> <code>* CONTENT</code>
<code>\tracecatcodetables</code>
<code>\tracedfontname {...}</code> <code>* FONT</code>
<code>\traceoutputroutines</code>
<code>\tracepositions</code>
<code>\traduce [...<sup>*</sup>...]</code> <code>* SPRACHE = TEXT<sup>OPT</sup></code>
<code>\transparencycomponents {...}</code> <code>* COLOR</code>
<code>\transparent [...<sup>1</sup>...] {...<sup>2</sup>}</code> <code>1 COLOR</code> <code>2 CONTENT</code>
<code>\trecilafonttext [...<sup>*</sup>...]</code> <code>* inherits: \seteazafonttext</code>

<code>\triplebond</code>
<code>\truefilename {...}</code> *    FILE
<code>\truefontname {...}</code> *    FONT
<code>\ttraggedright</code>
<code>\twodigitrounding {...}</code> *    NUMMER
<code>\tx</code>
<code>\txx</code>
<code>\typ [...,<sup>1</sup>...,<sup>2</sup>...] {...}</code> 1    inherits: \seteazatype 2    CONTENT
<code>\type [...,<sup>1</sup>...,<sup>2</sup>...] {...}</code> 1    inherits: \seteazatype 2    CONTENT
<code>\typedefinedbuffer [...,<sup>1</sup>...] [...,<sup>2</sup>...,<sup>OPT</sup>...]</code> 1    BUFFER 2    inherits: \seteazatyping
<code>\typeface</code>
<code>\typefile [...,<sup>1</sup>...] [...,<sup>2</sup>...,<sup>3</sup>...] {...}</code> 1    NAME            OPT 2    inherits: \seteazatyping 3    FILE
<code>\typeinlinebuffer [...,<sup>1</sup>...] [...,<sup>2</sup>...,<sup>3</sup>...,<sup>OPT</sup>...]</code> 1    BUFFER            OPT 2    inherits: \seteazatype
<code>\typescriptone</code>
<code>\typescriptprefix {...}</code> *    NAME
<code>\typescriptthree</code>
<code>\typescripttwo</code>
<code>\typesetbuffer [...,<sup>1</sup>...] [...,<sup>2</sup>...,<sup>3</sup>...,<sup>OPT</sup>...]</code> 1    * BUFFER            OPT 2    inherits: \setuexternalfigure
<code>\typesetfile [...,<sup>1</sup>...] [...,<sup>2</sup>...] [...,<sup>3</sup>...,<sup>4</sup>...,<sup>OPT</sup>...]</code> 1    NAME FILE            OPT 2    FILE TEXT 3    inherits: \setuexternalfigure

$\backslash\text{type} [\dots, \dots, \dots] \ll \dots \gg$ 1 inherits: $\backslash\text{seteazatype}^{\text{OPT}}$ 2 ANGLES
$\backslash\text{TYPE} [\dots, \dots, \dots] \{ \dots \}$ 1 inherits: $\backslash\text{seteazatype}^{\text{OPT}}$ 2 CONTENT
$\backslash\text{TYPE} [\dots, \dots, \dots] \ll \dots \gg$ 1 inherits: $\backslash\text{seteazatype}^{\text{OPT}}$ 2 ANGLES
$\backslash\text{typ} [\dots, \dots, \dots] \ll \dots \gg$ 1 inherits: $\backslash\text{seteazatype}^{\text{OPT}}$ 2 ANGLES
$\backslash\text{uconvertnumber} \{ \dots \} \{ \dots \}$ 1 inherits: $\backslash\text{converttestenumar}$ 2 NUMMER
$\backslash\text{uedcatcodecommand} \backslash \dots \dots \{ \dots \}$ 1 CSNAME 2 CHARACTER NUMBER 3 BEFEHL
$\backslash\text{ultimasubpagina}$
$\backslash\text{undefinevalue} \{ \dots \}$ * NAME
$\backslash\text{undepthed} \{ \dots \}$ * CONTENT
$\backslash\text{underset} \{ \dots \} \{ \dots \}$ 1 TEXT 2 TEXT
$\backslash\text{undeva} \{ \dots \} \{ \dots \} [ \dots ]$ 1 TEXT 2 TEXT 3 REFERENCE
$\backslash\text{undoassign} [ \dots ] [ \dots ]$ 1 TEXT 2 KEY = VALUE
$\backslash\text{unexpandeddocumentvariable} \{ \dots \}$ * KEY
$\backslash\text{unhhbox} \dots \backslash\text{with} \{ \dots \}$ 1 CSNAME NUMBER 2 BEFEHL
$\backslash\text{unihex} \{ \dots \}$ * NUMMER
$\backslash\text{uniqueMPgraphic} \{ \dots \} \{ \dots, \dots, \dots \}$ 1 NAME 2 KEY = VALUE <span style="float: right;">OPT</span>

$\backslash\text{uniqueMPpagegraphic}$ $\{...\}^1 \{...\}^2_{\text{OPT}}$ 1 NAME 2 KEY = VALUE
$\backslash\text{UNIT}$ $\{...\}$ * CONTENT instances: unit
$\backslash\text{unit}$ $\{...\}$ * CONTENT
$\backslash\text{unprotect}$ ... $\backslash\text{protect}$
$\backslash\text{unprotected}$ $\{...\}^*$ $\backslash\text{par}$ * CONTENT
$\backslash\text{unregisterhyphenationpattern}$ $[...]^1 [...]^2_{\text{OPT}}$ 1 SPRACHE 2 TEXT
$\backslash\text{unspaceafter}$ $\{...\}^1 \{...\}^2$ 1 CSNAME 2 TEXT
$\backslash\text{unspaceargument}$ $\{...\}^1 \backslash\text{to } \{...\}^2$ 1 TEXT 2 CSNAME
$\backslash\text{unspaced}$ $\{...\}^*$ * TEXT
$\backslash\text{unspacestring}$ $\{...\}^1 \backslash\text{to } \{...\}^2$ 1 TEXT 2 CSNAME
$\backslash\text{untexargument}$ $\{...\} \backslash\text{to } \{...\}^2$ 1 TEXT 2 CSNAME
$\backslash\text{untexcommand}$ $\{...\} \backslash\text{to } \{...\}^2$ 1 CSNAME 2 CSNAME
$\backslash\text{uppercased}$ $\{...\}^*$ * TEXT
$\backslash\text{uppercasestring}$ $\{...\}^1 \backslash\text{to } \{...\}^2$ 1 TEXT 2 CSNAME
$\backslash\text{upperlefthdoubleninequote}$
$\backslash\text{upperlefthdoublesixquote}$
$\backslash\text{upperleftsingleninequote}$
$\backslash\text{upperleftsinglesixquote}$

<code>\upperrightdoubleninequote</code>
<code>\upperrightdoublesixquote</code>
<code>\upperrightsingleninequote</code>
<code>\upperrightsinglesixquote</code>
<code>\url [...]</code> *    NAME
<code>\urmatoareasubpagina</code>
<code>\usealignparameter \...</code> *    CSNAME
<code>\useblankparameter \...</code> *    CSNAME
<code>\usebodyfont [...,*,...]</code> *    inherits: \seteazafonttext
<code>\usebodyfontparameter \...</code> *    CSNAME
<code>\usebtxdataset [...<sup>1</sup>] [...<sup>2</sup>] [...,...<sup>3</sup>...,...]</code> 1    NAME                      OPT                      OPT 2    FILE 3    specification = NAME
<code>\usebtxdefinitions [...]</code> *    FILE
<code>\usecitation [...]</code> *    REFERENCE
<code>\usecitation {...}</code> *    REFERENCE
<code>\usecolors [...]</code> *    FILE
<code>\usecomponent [...]</code> *    FILE
<code>\usedummycolorparameter {...}</code> *    KEY
<code>\usedummystyleandcolor {...<sup>1</sup>} {...<sup>2</sup>}</code> 1    KEY 2    KEY
<code>\usedummystyleparameter {...}</code> *    KEY
<code>\useenvironment [...]</code> *    FILE

$\backslash\text{useexternalrendering}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...] [ <sup>3</sup> ...] [ <sup>4</sup> ...] 1 NAME 2 NAME 3 FILE 4 auto embed
$\backslash\text{usefigurebase}$ [...] * reset FILE
$\backslash\text{usefile}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...] [ <sup>3</sup> ...] 1 NAME <small>OPT</small> 2 FILE 3 TEXT
$\backslash\text{usegridparameter}$ \*... * CSNAME
$\backslash\text{useindentingparameter}$ \*... * CSNAME
$\backslash\text{useindentnextparameter}$ \*... * CSNAME
$\backslash\text{useinterlinespaceparameter}$ \*... * CSNAME
$\backslash\text{uselanguageparameter}$ \*... * CSNAME
$\backslash\text{uselua module}$ [...] * FILE
$\backslash\text{useMPenvironmentbuffer}$ [...] * NAME
$\backslash\text{useMPgraphic}$ { <sup>1</sup> ...} { <sup>2</sup> ...,... <small>OPT</small> ,...} 1 NAME 2 KEY = VALUE
$\backslash\text{useMPlibrary}$ [...] * FILE
$\backslash\text{useMPrun}$ { <sup>1</sup> ...} { <sup>2</sup> ...} 1 NAME 2 NUMMER
$\backslash\text{useMPvariables}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...,...] 1 NAME 2 KEY
$\backslash\text{usemathstyleparameter}$ \*... * CSNAME
$\backslash\text{useproduct}$ [...] * FILE
$\backslash\text{useprofileparameter}$ \*... * CSNAME

<code>\useproject [...]</code> <code>* FILE</code>
<code>\userreferenceparameter \*..</code> <code>* CSNAME</code>
<code>\userpagenumber</code>
<code>\usesetupparameter \*..</code> <code>* CSNAME</code>
<code>\usestaticMPfigure [...,<sup>1</sup>...,<sup>2</sup>...] [...]</code> <code>1 inherits: \setupscale OPT</code> <code>2 NAME</code>
<code>\usesubpath [...,*,...]</code> <code>* PATH</code>
<code>\usetextmodule [...<sup>1</sup>] [...<sup>2</sup>,...] [...<sup>3</sup>...,...]</code> <code>1 m p s x t OPT</code> <code>2 FILE</code> <code>3 KEY = VALUE</code>
<code>\usetypescript [...<sup>1</sup>] [...<sup>2</sup>] [...<sup>3</sup>]</code> <code>1 serif sans mono<sup>OPT</sup> math handwriting<sup>OPT</sup> calligraphy casual tot</code> <code>2 NAME fallback implicit dtp simple</code> <code>3 size nume</code>
<code>\usetypescriptfile [...]</code> <code>* reset FILE</code>
<code>\usezipfile [...<sup>1</sup>] [...<sup>2</sup>]</code> <code>1 FILE OPT</code> <code>2 FILE</code>
<code>\utfchar {...}</code> <code>* NUMMER</code>
<code>\utflower {...}</code> <code>* TEXT</code>
<code>\utfupper {...}</code> <code>* TEXT</code>
<code>\utilityregisterlength</code>
<code>\VerboseNumber {...}</code> <code>* NUMMER</code>
<code>\valoareculoare {...}</code> <code>* COLOR</code>
<code>\vboxreference [...,<sup>1</sup>...] {...<sup>2</sup>}</code> <code>1 REFERENCE</code> <code>2 CONTENT</code>
<code>\vec {...}</code> <code>* CHARACTER</code>

<code>\verbatim {...}</code> *    CONTENT
<code>\verbatimstring {...}</code> *    CONTENT
<code>\verbosenummer {...}</code> *    NUMMER
<code>\versiune [...]</code> *    concept fisier temporar final NAME
<code>\verticalgrowingbar [...,*...]</code> *    inherits: \setuppositionbar
<code>\verticalpositionbar [...,*...]</code> *    inherits: \setuppositionbar
<code>\veryraggedcenter</code>
<code>\veryraggedleft</code>
<code>\veryraggedright</code>
<code>\vglue ...</code> *    DIMENSION
<code>\viewerlayer [...<sup>1</sup>] {...<sup>2</sup>}</code> 1    NAME 2    CONTENT
<code>\vl [...]</code> *    NUMMER
<code>\vphantom {...}</code> *    CONTENT
<code>\vpos {...<sup>1</sup>} {...<sup>2</sup>}</code> 1    NAME 2    CONTENT
<code>\vsmash {...}</code> *    CONTENT
<code>\vsmashbox ...</code> *    CSNAME NUMMER
<code>\vsmashed {...}</code> *    CONTENT
<code>\vspace [...<sup>1</sup>] [...<sup>2</sup>]</code> 1    NAME        OPT        OPT 2    NAME



<p><code>\vspacing [...*...]</code></p> <p>* preferinta accesasipagina max fortat enable dezactivat faraalb impachetat inapot overlay totdeauna weak strong implicit inainte intre dupa fixat flexibil niciunul mic mediu mare linie jumatatelinie quarterline formula alb inaltime adancime standard NUMMER*mic NUMMER*mediu NUMMER*mare NUMMER*linie NUMMER*jumatatelinie NUMMER*quarterline NUMMER*formula NUMMER*alb NUMMER*inaltime NUMMER*adancime category:NUMMER order:NUMMER penalty:NUMMER DIMENSION NAME</p>
<p><code>\WidthSpanningText {...} {...} {...}</code></p> <p>1 TEXT</p> <p>2 DIMENSION</p> <p>3 FONT</p>
<p><code>\wdofstring {...}</code></p> <p>* TEXT</p>
<p><code>\widthhofstring {...}</code></p> <p>* TEXT</p>
<p><code>\widthspanningtext {...} {...} {...}</code></p> <p>1 TEXT</p> <p>2 DIMENSION</p> <p>3 FONT</p>
<p><code>\withoutpt {...}</code></p> <p>* DIMENSION</p>
<p><code>\words {...}</code></p> <p>* TEXT</p>
<p><code>\wordtonumber {...} {...}</code></p> <p>1 unu doi trei patru cinci</p> <p>2 TEXT</p>
<p><code>\writadatolist [...] [...<sup>2</sup>...<sup>2</sup>...] [...<sup>3</sup>...<sup>3</sup>...]</code></p> <p>1 LISTE</p> <p>2 inherits: \seteazalista</p> <p>3 KEY = VALUE</p>
<p><code>\writestatus {...} {...}</code></p> <p>1 TEXT</p> <p>2 TEXT</p>
<p><code>\XETEX</code></p>
<p><code>\XeTeX</code></p>
<p><code>\xdefconvertedargument \<sup>1</sup>... {...}</code></p> <p>1 CSNAME</p> <p>2 TEXT</p>
<p><code>\xmladdindex {...}</code></p> <p>* NODE</p>
<p><code>\xmلاfterdocumentsetup {...} {...} {...}</code></p> <p>1 NAME</p> <p>2 SETUP</p> <p>3 SETUP</p>
<p><code>\xmلاftersetup {...} {...}</code></p> <p>1 SETUP</p> <p>2 SETUP</p>

\xmlall { <sup>1</sup> ..} { <sup>2</sup> ..} 1    NODE 2    LPATH
\xmlappenddocumentsetup { <sup>1</sup> ..} { <sup>2</sup> ..} 1    NAME 2    SETUP
\xmlappendsetup { <sup>*</sup> ..} *    SETUP
\xmlapplyselectors { <sup>*</sup> ..} *    NODE
\xmlatt { <sup>1</sup> ..} { <sup>2</sup> ..} 1    NODE 2    NAME
\xmlattdef { <sup>1</sup> ..} { <sup>2</sup> ..} { <sup>3</sup> ..} 1    NODE 2    NAME 3    TEXT
\xmlattribute { <sup>1</sup> ..} { <sup>2</sup> ..} { <sup>3</sup> ..} 1    NODE 2    LPATH 3    NAME
\xmlattributedef { <sup>1</sup> ..} { <sup>2</sup> ..} { <sup>3</sup> ..} { <sup>4</sup> ..} 1    NODE 2    LPATH 3    NAME 4    TEXT
\xmlbadinclusions { <sup>*</sup> ..} *    NODE
\xmlbeforedocumentsetup { <sup>1</sup> ..} { <sup>2</sup> ..} { <sup>3</sup> ..} 1    NAME 2    SETUP 3    SETUP
\xmlbeforesetup { <sup>1</sup> ..} { <sup>2</sup> ..} 1    SETUP 2    SETUP
\xmlchainatt { <sup>1</sup> ..} { <sup>2</sup> ..} 1    NODE 2    NAME
\xmlchainattdef { <sup>1</sup> ..} { <sup>2</sup> ..} { <sup>3</sup> ..} 1    NODE 2    NAME 3    TEXT
\xmlchecknamespace { <sup>1</sup> ..} { <sup>2</sup> ..} 1    NODE 2    NAME
\xmlcommand { <sup>1</sup> ..} { <sup>2</sup> ..} { <sup>3</sup> ..} 1    NODE 2    LPATH 3    XMLSETUP

<code>\xmlconcat {...} {...} {...}</code> 1    NODE 2    LPATH 3    TEXT
<code>\xmlconcatrange {...} {...} {...} {...} {...}</code> 1    NODE 2    LPATH 3    TEXT 4    FIRST 5    LAST
<code>\xmlcontext {...} {...}</code> 1    NODE 2    LPATH
<code>\xmlcount {...}</code> *    NODE
<code>\xmldefaulttotext {...}</code> *    NODE
<code>\xmldirectives {...}</code> *    NODE
<code>\xmldirectivesafter {...}</code> *    NODE
<code>\xmldirectivesbefore {...}</code> *    NODE
<code>\xmldisplayverbatim {...}</code> *    NODE
<code>\xmldoif {...} {...} {...}</code> 1    NODE 2    LPATH 3    TRUE
<code>\xmldoifatt {...} {...}</code> 1    NODE 2    TRUE
<code>\xmldoifelse {...} {...} {...} {...}</code> 1    NODE 2    LPATH 3    TRUE 4    FALSE
<code>\xmldoifelseatt {...} {...} {...}</code> 1    NODE 2    TRUE 3    FALSE
<code>\xmldoifelseempty {...} {...} {...} {...}</code> 1    NODE 2    LPATH 3    TRUE 4    FALSE

\xmldoifselfempty { <sup>1</sup> ..} { <sup>2</sup> ..} { <sup>3</sup> ..} 1    NODE 2    TRUE 3    FALSE
\xmldoifelsetext { <sup>1</sup> ..} { <sup>2</sup> ..} { <sup>3</sup> ..} { <sup>4</sup> ..} 1    NODE 2    LPATH 3    TRUE 4    FALSE
\xmldoifelsevalue { <sup>1</sup> ..} { <sup>2</sup> ..} { <sup>3</sup> ..} { <sup>4</sup> ..} 1    CATEGORY 2    NAME 3    TRUE 4    FALSE
\xmldoifnot { <sup>1</sup> ..} { <sup>2</sup> ..} { <sup>3</sup> ..} 1    NODE 2    LPATH 3    TRUE
\xmldoifnotatt { <sup>1</sup> ..} { <sup>2</sup> ..} 1    NODE 2    TRUE
\xmldoifnotselfempty { <sup>1</sup> ..} { <sup>2</sup> ..} 1    NODE 2    TRUE
\xmldoifnottext { <sup>1</sup> ..} { <sup>2</sup> ..} { <sup>3</sup> ..} 1    NODE 2    LPATH 3    TRUE
\xmldoifselfempty { <sup>1</sup> ..} { <sup>2</sup> ..} 1    NODE 2    TRUE
\xmldoiftext { <sup>1</sup> ..} { <sup>2</sup> ..} { <sup>3</sup> ..} 1    NODE 2    LPATH 3    TRUE
\xmlelement { <sup>1</sup> ..} { <sup>2</sup> ..} 1    NODE 2    NUMMER
\xmlfilter { <sup>1</sup> ..} { <sup>2</sup> ..} 1    NODE 2    LPATH
\xmlfirst { <sup>1</sup> ..} { <sup>2</sup> ..} 1    NODE 2    LPATH
\xmlflush { <sup>*</sup> ..} *    NODE
\xmlflushcontext { <sup>*</sup> ..} *    NODE

<code>\xmlflushdocumentsetups {...} {...}</code> 1 NAME 2 SETUP
<code>\xmlflushlinewise {...}</code> * NODE
<code>\xmlflushpure {...}</code> * NODE
<code>\xmlflushspacewise {...}</code> * NODE
<code>\xmlflushtext {...}</code> * NODE
<code>\xmlinclude {...} {...} {...}</code> 1 NODE 2 LPATH 3 NAME
<code>\xmlinclusion {...}</code> * NODE
<code>\xmlinclusions {...}</code> * NODE
<code>\xmlinfo {...}</code> * NODE
<code>\xmlinjector {...}</code> * NAME
<code>\xmlinlineprettyprint {...} {...}</code> 1 NODE 2 mp lua xml parsed-xml nested tex context niciunul NAME
<code>\xmlinlineprettyprinttext {...} {...}</code> 1 NODE 2 mp lua xml parsed-xml nested tex context niciunul NAME
<code>\xmlinlineverbatim {...}</code> * NODE
<code>\xmlinstalldirective {...} {...}</code> 1 NAME 2 CSNAME
<code>\xmllast {...} {...}</code> 1 NODE 2 LPATH
<code>\xmllastatt</code>
<code>\xmllastmatch</code>
<code>\xmllastpar</code>

\xmlloadbuffer {...} {...} {...} 1 BUFFER 2 NAME 3 XMLSETUP
\xmlloaddata {...} {...} {...} 1 NAME 2 TEXT 3 XMLSETUP
\xmlloaddirectives {...} * FILE
\xmlloadfile {...} {...} {...} 1 NAME 2 FILE 3 XMLSETUP
\xmlloadonly {...} {...} {...} 1 NAME 2 FILE 3 XMLSETUP
\xmlmain {...} * NAME
\xmlmapvalue {...} {...} {...} 1 CATEGORY 2 NAME 3 TEXT
\xmlname {...} * NODE
\xmlnamespace {...} * NODE
\xmlnonspace {...} {...} 1 NODE 2 LPATH
\xmlpar {...} {...} 1 NODE 2 NAME
\xmlparam {...} {...} {...} 1 NODE 2 LPATH 3 NAME
\xmlpath {...} * NODE
\xmlpos {...} * NODE
\xmlposition {...} {...} {...} 1 NODE 2 LPATH 3 NUMMER

<code>\xmlprependdocumentsetup {...} {...}</code> 1 NAME 2 SETUP
<code>\xmlprependsetup {...}</code> * SETUP
<code>\xmlprettyprint {...} {...}</code> 1 NODE 2 mp lua xml parsed-xml nested tex context niciunul NAME
<code>\xmlprettyprinttext {...} {...}</code> 1 NODE 2 mp lua xml parsed-xml nested tex context niciunul NAME
<code>\xmlprocessbuffer {...} {...} {...}</code> 1 BUFFER 2 NAME 3 XMLSETUP
<code>\xmlprocessdata {...} {...} {...}</code> 1 NAME 2 TEXT 3 XMLSETUP
<code>\xmlprocessfile {...} {...} {...}</code> 1 NAME 2 FILE 3 XMLSETUP
<code>\xmlpure {...} {...}</code> 1 NODE 2 LPATH
<code>\xmlraw {...}</code> * NODE
<code>\xmlrefatt {...} {...}</code> 1 NODE 2 NAME
<code>\xmlregistereddokumentsetups {...} {...}</code> 1 NAME 2 SETUP
<code>\xmlregisteredsetups</code>
<code>\xmlregisterns {...} {...}</code> 1 NAME 2 URL
<code>\xmlremapname {...} {...} {...} {...}</code> 1 NODE 2 LPATH 3 NAME 4 NAME
<code>\xmlremapnamespace {...} {...} {...}</code> 1 NODE 2 NAME 3 NAME

\xmlremovedocumentsetup {...} {...} 1 NAME 2 SETUP
\xmlremovesetup {...} * SETUP
\xmlresetdocumentsetups {...} * NAME
\xmlresetinjectors
\xmlresetsetups {...} * NAME
\xmlsave {...} {...} 1 NODE 2 FILE
\xmlsetatt {...} {...} {...} 1 NODE 2 NAME 3 TEXT
\xmlsetattribute {...} {...} {...} {...} 1 NODE 2 LPATH 3 NAME 4 TEXT
\xmlsetentity {...} {...} 1 NAME 2 TEXT
\xmlsetfunction {...} {...} {...} 1 NODE 2 LPATH 3 LUAFUNCTION
\xmlsetinjectors [...,*...] * NAME
\xmlsetpar {...} {...} {...} 1 NODE 2 NAME 3 TEXT
\xmlsetparam {...} {...} {...} {...} 1 NODE 2 LPATH 3 NAME 4 TEXT
\xmlsetsetup {...} {...} {...} 1 NAME 2 LPATH 3 SETUP
\xmlsetup {...} {...} 1 NODE 2 SETUP



<code>\xmlshow {...}</code> *    NODE
<code>\xmlsnippet {...} {...}</code> 1    NODE 2    NUMMER
<code>\xmlstrip {...} {...}</code> 1    NODE 2    LPATH
<code>\xmlstripnolines {...} {...}</code> 1    NODE 2    LPATH
<code>\xmlstripped {...} {...}</code> 1    NODE 2    LPATH
<code>\xmlstrippednolines {...} {...}</code> 1    NODE 2    LPATH
<code>\xmltag {...}</code> *    NODE
<code>\xmltexentity {...} {...}</code> 1    NAME 2    TEXT
<code>\xmltext {...} {...}</code> 1    NODE 2    LPATH
<code>\xmlobuffer {...} {...} {...}</code> 1    NODE 2    LPATH 3    BUFFER
<code>\xmlobufferverbose {...} {...} {...}</code> 1    NODE 2    LPATH 3    BUFFER
<code>\xmltofile {...} {...} {...}</code> 1    NODE 2    LPATH 3    FILE
<code>\xmlvalue {...} {...} {...}</code> 1    CATEGORY 2    NAME 3    TEXT
<code>\xmlverbatim {...}</code> *    NODE
<code>\xsplitstring \... {...}</code> 1    CSNAME 2    TEXT

\xypos {...}

\* NAME

\ZIDINSAPTAMANA {...}

\* NUMMER

\zidinsaptamana {...}

\* NUMMER





**PRAGMA ADE**  
**Ridderstraat 27**  
**8061GH Hasselt NL**  
**[www.pragma-ade.com](http://www.pragma-ade.com)**