



# ConTeXt

commands

# EN



# ConTeXt

## commands

en / english  
May 24, 2017



<code>\AfterPar {...}</code> *    COMMAND
<code>\Alphabeticnumerals {...}</code> *    NUMBER
<code>\AMSTEX</code>
<code>\AmSTeX</code>
<code>\And</code>
<code>\abjadnaivenumerals {...}</code> *    NUMBER
<code>\abjadnodotnumerals {...}</code> *    NUMBER
<code>\abjadnumerals {...}</code> *    NUMBER
<code>\about [...]</code> *    REFERENCE
<code>\activatespacehandler {...}</code> *    on <u>off</u> yes fixed
<code>\acute {...}</code> *    CHARACTER
<code>\adaptcollector [...]<sup>1</sup> [...,...<sup>2</sup>...,...]</code> <div style="text-align: center;"><small>OPT</small></div> 1    NAME 2    inherits: \setupcollector
<code>\adaptfontfeature [...]<sup>1</sup> [...,...<sup>2</sup>...,...]</code> 1    NAME 2    inherits: \definefontfeature
<code>\adaptlayout [...]<sup>1</sup>,...]</code> <div style="text-align: center;"><small>OPT</small></div> 1    NUMBER 2    height = max DIMENSION lines = NUMBER
<code>\adaptpapersize [...]<sup>1</sup>,...]</code> <div style="text-align: center;"><small>OPT</small></div> 1    inherits: \setuppapersize 2    inherits: \setuppapersize

<p><code>\addfeature [...]</code></p> <p>* NAME</p>
<p><code>\addfeature {...}</code></p> <p>* NAME</p>
<p><code>\addtocommalist {...} \.^{2..}</code></p> <p>1 TEXT</p> <p>2 CSNAME</p>
<p><code>\addtoJSreamble {...} {...}^{2..}</code></p> <p>1 NAME</p> <p>2 CONTENT</p>
<p><code>\addvalue {...} {...}^{2..}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\aftersplitstring .^{1..} \at .^{2..} \to \.^{3..}</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 CSNAME</p>
<p><code>\aftertestandsplitstring .^{1..} \at .^{2..} \to \.^{3..}</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 CSNAME</p>
<p><code>\alignbottom</code></p>
<p><code>\aligned [...,^{1..},...] {...}^{2..}</code></p> <p>1 left middle right top bottom line l c r m t b g</p> <p>2 CONTENT</p>
<p><code>\alignedbox [...,^{1..},...] \.^{2..} {...}^{3..}</code></p> <p>1 left middle right top bottom line l c r m t b g</p> <p>2 CSNAME</p> <p>3 CONTENT</p>
<p><code>\alignedline {...}^{1..} {...}^{2..} {...}^{3..}</code></p> <p>1 left right middle flushleft flushright center max inner outer innermargin outermargin inneredge outeredge backspace cutspace leftmargin rightmargin leftedge rightedge</p> <p>2 left right middle flushleft flushright center max inner outer innermargin outermargin inneredge outeredge backspace cutspace leftmargin rightmargin leftedge rightedge</p> <p>3 CONTENT</p>
<p><code>\alignmentcharacter</code></p>
<p><code>\allinputpaths</code></p>

`\alphabeticnumerals {...}`

\* NUMBER

`\alwayscitation [...1...2...] [...]`  
OPT

1 reference = REFERENCE  
alternative = default category entry short page num textnum year index tag keywords author authoryears authornum  
authoryear  
before = COMMAND  
after = COMMAND  
left = COMMAND  
right = COMMAND  
inherits: \setupbtx

2 REFERENCE

`\alwayscitation [...1...] [...2...]`  
OPT

1 default category entry short page num textnum year index tag keywords author authoryears authornum authoryear

2 REFERENCE

`\alwayscitation [...1...2...] [...2...]`

1 reference = REFERENCE  
alternative = default category entry short page num textnum year index tag keywords author authoryears authornum  
authoryear  
before = COMMAND  
after = COMMAND  
left = COMMAND  
right = COMMAND  
inherits: \setupbtx

2 KEY = VALUE

`\alwayscite [...1...2...] [...]`  
OPT

1 reference = REFERENCE  
alternative = default category entry short page num textnum year index tag keywords author authoryears authornum  
authoryear  
before = COMMAND  
after = COMMAND  
left = COMMAND  
right = COMMAND  
inherits: \setupbtx

2 REFERENCE

`\alwayscite [...1...] [...2...]`  
OPT

1 default category entry short page num textnum year index tag keywords author authoryears authornum authoryear

2 REFERENCE

`\alwayscite [...1...2...] [...2...]`

1 reference = REFERENCE  
alternative = default category entry short page num textnum year index tag keywords author authoryears authornum  
authoryear  
before = COMMAND  
after = COMMAND  
left = COMMAND  
right = COMMAND  
inherits: \setupbtx

2 KEY = VALUE

`\ampersand`

**\anchor** [<sup>1</sup>...] [<sub>OPT</sub>...<sup>2</sup>...]<sub>OPT</sub> [<sub>OPT</sub>...<sup>3</sup>...]<sub>OPT</sub> {...}<sup>4</sup>}

- 1 NAME
- 2 inherits: \setupplayer
- 3 inherits: \setupplayerinherits: \setupframed
- 4 CONTENT

**\appendetoks** <sup>1</sup>... \to \<sup>2</sup>...

- 1 COMMAND
- 2 CSNAME

**\appendgvalue** {...} {...}<sup>1</sup> <sup>2</sup>}

- 1 NAME
- 2 COMMAND

**\appendtocommalist** {...} \<sup>1</sup>...<sup>2</sup>...

- 1 TEXT
- 2 CSNAME

**\appendtoks** <sup>1</sup>... \to \<sup>2</sup>...

- 1 COMMAND
- 2 CSNAME

**\appendtoksonce** <sup>1</sup>... \to \<sup>2</sup>...

- 1 COMMAND
- 2 CSNAME

**\appendvalue** {...} {...}<sup>1</sup> <sup>2</sup>}

- 1 NAME
- 2 COMMAND

**\apply** {...} {...}<sup>1</sup> <sup>2</sup>}

- 1 CONTENT
- 2 CONTENT

**\applyalternativestyle** {...}<sup>\*</sup>

- \* NAME

**\applyprocessor** {...} {...}<sup>1</sup> <sup>2</sup>}

- 1 NAME
- 2 CONTENT

**\applytocharacters** \<sup>1</sup>... {...}<sup>2</sup>}

- 1 CSNAME
- 2 TEXT



`\applytofirstcharacter \1... {2...}`

1 CSNAME

2 TEXT

`\applytosplitstringchar \1... {2...}`

1 CSNAME

2 TEXT

`\applytosplitstringcharspaced \1... {2...}`

1 CSNAME

2 TEXT

`\applytosplitstringline \1... {2...}`

1 CSNAME

2 TEXT

`\applytosplitstringlinespaced \1... {2...}`

1 CSNAME

2 TEXT

`\applytosplitstringword \1... {2...}`

1 CSNAME

2 TEXT

`\applytosplitstringwordspaced \1... {2...}`

1 CSNAME

2 TEXT

`\applytowords \1... {2...}`

1 CSNAME

2 TEXT

`\arabicdecimals {*...}`

\* NUMBER

`\arabicexnumerals {*...}`

\* NUMBER

`\arabicnumerals {*...}`

\* NUMBER

`\arg {*...}`

\* CONTENT

`\asciistr {*...}`

\* CONTENT

`\assignalfadimension {...} \^2... {...} {...} {...}`

1    small medium big none DIMENSION  
2    CSNAME  
3    DIMENSION  
4    DIMENSION  
5    DIMENSION

`\assigndimen \^1... {...}`

1    CSNAME  
2    DIMENSION

`\assigndimension {...} \^2... {...} {...} {...}`

1    [-+]small [-+]medium [-+]big none DIMENSION  
2    CSNAME  
3    DIMENSION  
4    DIMENSION  
5    DIMENSION

`\assignifempty \^1... {...}`

1    CSNAME  
2    COMMAND

`\assigntranslation [...,\^1...,\^2...]`

1    LANGUAGE = TEXT  
2    CSNAME

`\assignvalue {...} \^2... {...} {...} {...}`

1    small medium big TEXT  
2    CSNAME  
3    COMMAND  
4    COMMAND  
5    COMMAND

`\assignwidth {...} \^2... {...} {...}`

1    fit broad DIMENSION  
2    CSNAME  
3    TEXT  
4    DIMENSION

`\assumelongusagecs \^1... {...}`

1    CSNAME  
2    CONTENT

`\astype {...}`

\*    CONTENT

$\backslash\text{at}$ $\overset{1}{\{...\}}$ $\overset{2}{\{...\}}$ $[\overset{3}{...}]$ $\text{OPT}$ $\text{OPT}$ 1    TEXT 2    TEXT 3    REFERENCE
$\backslash\text{atpage}$ [...] *    REFERENCE
$\backslash\text{ATTACHMENT}$ $[\overset{1}{...}]$ $[\dots,\overset{2}{...},\dots]$ $\text{OPT}$ $\text{OPT}$ 1    NAME 2    inherits: $\backslash\text{setupattachment}$  instances: attachment
$\backslash\text{autocap}$ {...} *    TEXT
$\backslash\text{autodirhbox}$ $\overset{1}{...}$ $\{\overset{2}{...}\}$ $\text{OPT}$ 1    TEXT 2    CONTENT
$\backslash\text{autodirvbox}$ $\overset{1}{...}$ $\{\overset{2}{...}\}$ $\text{OPT}$ 1    TEXT 2    CONTENT
$\backslash\text{autodirvtop}$ $\overset{1}{...}$ $\{\overset{2}{...}\}$ $\text{OPT}$ 1    TEXT 2    CONTENT
$\backslash\text{autoinsertnextspace}$
$\backslash\text{autointegral}$ $\{\overset{1}{...}\}$ $\{\overset{2}{...}\}$ $\{\overset{3}{...}\}$ 1    TEXT 2    TEXT 3    TEXT
$\backslash\text{automathematics}$ {...} *    CONTENT
$\backslash\text{autosetups}$ {...,*,...} *    NAME
$\backslash\text{autostarttext}$ ... $\backslash\text{autostoptext}$
$\backslash\text{availablehsize}$
$\backslash\text{averagecharwidth}$

$\backslash\text{BeforePar} \{...\}$ *    COMMAND
$\backslash\text{Big} ...$ *    CHARACTER
$\backslash\text{Bigg} ...$ *    CHARACTER
$\backslash\text{Biggl} ...$ *    CHARACTER
$\backslash\text{Biggm} ...$ *    CHARACTER
$\backslash\text{Biggr} ...$ *    CHARACTER
$\backslash\text{Bigl} ...$ *    CHARACTER
$\backslash\text{Bigm} ...$ *    CHARACTER
$\backslash\text{Bigr} ...$ *    CHARACTER
$\backslash\text{background} \{...\}$ *    CONTENT
$\backslash\text{backgroundimage} \{...\} \{...\} \{...\} \{...\}$ 1    NUMBER 2    DIMENSION 3    DIMENSION 4    COMMAND
$\backslash\text{backgroundimagefill} \{...\} \{...\} \{...\} \{...\}$ 1    NUMBER 2    DIMENSION 3    DIMENSION 4    COMMAND
$\backslash\text{backgroundline} [..] \{...\}$ 1    COLOR 2    CONTENT

`\BACKGROUND {...}`

\* CONTENT

instances: background

`\bar {...}`

\* CHARACTER

`\BAR {...}`

\* CONTENT

instances: overbar underbar overstrike understrike overbars underbars overstrikes understrikes  
underrandom underrandoms underdash underdashes underdot underdots nobar hiddenbar

`\basegrid [...,...*...,...]`  
OPT

\* nx = NUMBER  
ny = NUMBER  
dx = NUMBER  
dy = NUMBER  
factor = NUMBER  
scale = NUMBER  
xstep = NUMBER  
ystep = NUMBER  
offset = DIMENSION  
xoffset = DIMENSION  
yoffset = DIMENSION  
align = middle  
unit = cm mm in pc pt bp  
style = STYLE COMMAND  
color = COLOR

`\baselinebottom`

`\baselineleftbox {...}`

\* CONTENT

`\baselinemiddlebox {...}`

\* CONTENT

`\baselinerightbox {...}`

\* CONTENT

`\bbox {...}`

\* CONTENT

`\beforesplitstring 1... \at 2... \to 3...`

1 TEXT  
2 TEXT  
3 CSNAME

`\beforetestandsplitstring 1... \at 2... \to 3...`

1 TEXT  
2 TEXT  
3 CSNAME

$\backslash beginBLOCK [...,*...] \dots \backslash endBLOCK$ <small>OPT</small> *    + - NAME
$\backslash beginhbox \dots \backslash endhbox$
$\backslash beginofshapebox \dots \backslash endofshapebox$
$\backslash beginvbox \dots \backslash endvbox$
$\backslash beginvtop \dots \backslash endvtop$
$\backslash begstrut \dots \backslash endstrut$
$\backslash big \dots$ *    CHARACTER
$\backslash bigbodyfont$
$\backslash bigg \dots$ *    CHARACTER
$\backslash bigger$
$\backslash biggl \dots$ *    CHARACTER
$\backslash biggm \dots$ *    CHARACTER
$\backslash biggr \dots$ *    CHARACTER
$\backslash bigl \dots$ *    CHARACTER
$\backslash bigm \dots$ *    CHARACTER
$\backslash bigr \dots$ *    CHARACTER
$\backslash bigskip$
$\backslash bitmapimage [...,\dots^1\dots] \{ \dots^2 \}$  1    color    =    rgb cmyk gray width    =    DIMENSION height   =    DIMENSION x        =    NUMBER y        =    NUMBER  2    NUMBER

<code>\blackrule [...,*=...,...]</code> <small>OPT</small> <code>* inherits: \setupblackrules</code>
<code>\blackrules [...,*=...,...]</code> <small>OPT</small> <code>* inherits: \setupblackrules</code>
<code>\blank [...,*=...,...]</code> <small>OPT</small> <code>* inherits: \vspacing</code>
<code>\blap {...}</code> <code>* CONTENT</code>
<code>\bleed [...,*=...,...]{...}</code> <small>OPT</small> <code>1 inherits: \setupbleeding</code> <code>2 CONTENT</code>
<code>\bleedheight</code>
<code>\bleedwidth</code>
<code>\blockligatures [...,*=...,...]</code> <code>* TEXT</code>
<code>\bodyfontenvironmentlist</code>
<code>\bodyfontsize</code>
<code>\bold</code>
<code>\boldface</code>
<code>\bolditalic</code>
<code>\boldslanted</code>
<code>\bookmark [...,*=...,...]{...}</code> <small>OPT</small> <code>1 SECTION LIST</code> <code>2 TEXT</code>
<code>\booleanmodevalue {...}</code> <code>* NAME</code>
<code>\bottombox {...}</code> <code>* CONTENT</code>
<code>\bottomleftbox {...}</code> <code>* CONTENT</code>

<code>\bottomrightbox {...}</code>  *    CONTENT
<code>\boxcursor</code>
<code>\boxmarker {...} {...}</code>  1    NAME 2    NUMBER
<code>\boxofsize \... .. <sup>2</sup>... .. {...}</code> <div style="text-align: center; margin-left: 100px;"><small>OPT</small></div> 1    CSNAME 2    DIMENSION 3    CONTENT
<code>\boxreference [...,<sup>1</sup>...] \... <sup>2</sup>{...}</code> <div style="text-align: center; margin-left: 100px;"><small>1</small></div> 1    REFERENCE 2    CSNAME 3    CONTENT
<code>\bpar ... \epar</code>
<code>\bpos {...}</code>  *    NAME
<code>\breve {...}</code>  *    CHARACTER
<code>\bTABLE [...,<sup>*</sup>...,...] ... \eTABLE</code> <div style="text-align: center; margin-left: 100px;"><small>OPT</small></div> *    inherits: \setupTABLE
<code>\bTABLEbody [...,<sup>*</sup>...,...] ... \eTABLEbody</code> <div style="text-align: center; margin-left: 100px;"><small>OPT</small></div> *    inherits: \setupTABLE
<code>\bTABLEfoot [...,<sup>*</sup>...,...] ... \eTABLEfoot</code> <div style="text-align: center; margin-left: 100px;"><small>OPT</small></div> *    inherits: \setupTABLE
<code>\bTABLEhead [...,<sup>*</sup>...,...] ... \eTABLEhead</code> <div style="text-align: center; margin-left: 100px;"><small>OPT</small></div> *    inherits: \setupTABLE
<code>\bTABLEnext [...,<sup>*</sup>...,...] ... \eTABLEnext</code> <div style="text-align: center; margin-left: 100px;"><small>OPT</small></div> *    inherits: \setupTABLE
<code>\bTC [...,<sup>*</sup>...,...] ... \eTC</code> <div style="text-align: center; margin-left: 100px;"><small>OPT</small></div> *    inherits: \bTD



<p><code>\bTD [...<sup>*</sup>...] ... \eTD</code></p> <p>OPT</p> <p>*    nx        = NUMBER</p> <p>     ny        = NUMBER</p> <p>     nc        = NUMBER</p> <p>     nr        = NUMBER</p> <p>     n         = NUMBER</p> <p>     m         = NUMBER</p> <p>     action    = REFERENCE</p> <p>     inherits: \setupTABLE</p>
<p><code>\bTDs [...] ... \eTDs</code></p> <p>*    NAME</p>
<p><code>\bTH [...<sup>*</sup>...] ... \eTH</code></p> <p>OPT</p> <p>*    inherits: \bTD</p>
<p><code>\bTN [...<sup>*</sup>...] ... \eTN</code></p> <p>OPT</p> <p>*    inherits: \bTD</p>
<p><code>\bTR [...<sup>*</sup>...] ... \eTR</code></p> <p>OPT</p> <p>*    inherits: \setupTABLE</p>
<p><code>\bTRs [...] ... \eTRs</code></p> <p>*    NAME</p>
<p><code>\bTX [...<sup>*</sup>...] ... \eTX</code></p> <p>OPT</p> <p>*    inherits: \bTD</p>
<p><code>\bTY [...<sup>*</sup>...] ... \eTY</code></p> <p>OPT</p> <p>*    inherits: \setupTABLE</p>
<p><code>\bthiddencitation [...]</code></p> <p>*    REFERENCE</p>
<p><code>\btxabbreviatedjournal {...}</code></p> <p>*    NAME</p>
<p><code>\btxaddjournal [...<sup>1</sup>] [...<sup>2</sup>]</code></p> <p>1    NAME</p> <p>2    NAME</p>
<p><code>\btxalwayscitation [...<sup>1</sup>...] [...<sup>2</sup>]</code></p> <p>OPT</p> <p>1    reference    = REFERENCE</p> <p>     alternative = default category entry short page num textnum year index tag keywords author authoryears authornum                   authoryear</p> <p>     before      = COMMAND</p> <p>     after       = COMMAND</p> <p>     left        = COMMAND</p> <p>     right       = COMMAND</p> <p>     inherits: \setupbtx</p> <p>2    REFERENCE</p>

\btخالwayscitation [...]<sup>1</sup> [...]<sup>2</sup>

OPT

1 default category entry short page num textnum year index tag keywords author authoryears authornum authoryear  
2 REFERENCE

\btخالwayscitation [...]<sup>1</sup> [...]<sup>2</sup> [...]

1 reference = REFERENCE  
alternative = default category entry short page num textnum year index tag keywords author authoryears authornum  
authoryear  
before = COMMAND  
after = COMMAND  
left = COMMAND  
right = COMMAND  
inherits: \setupbtx  
2 KEY = VALUE

\btخالauthorfield {...}

\* initials firstnames vons surnames juniors

\btخالdetail {...}

\* address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language  
month monthfiled nationality note number one two organization pages publisher school series title type volume year  
yearfiled NAME

\btخالdirect {...}

\* address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language  
month monthfiled nationality note number one two organization pages publisher school series title type volume year  
yearfiled NAME

\btخالdoif {...}<sup>1</sup> {...}<sup>2</sup>

1 address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language  
month monthfiled nationality note number one two organization pages publisher school series title type volume year  
yearfiled NAME  
2 TRUE

\btخالdoifcombiinlistelse {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup> {...}<sup>4</sup>

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

\btخالdoifelse {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup>

1 address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language  
month monthfiled nationality note number one two organization pages publisher school series title type volume year  
yearfiled NAME  
2 TRUE  
3 FALSE

\btخالdoifelsecombiinlist {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup> {...}<sup>4</sup>

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

\btxdoifelsesameasprevious {...} {...} {...}

- 1 address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language month monthfiled nationality note number one two organization pages publisher school series title type volume year yearfiled NAME
- 2 TRUE
- 3 FALSE

\btxdoifelsesameaspreviouschecked {...} {...} {...} {...}

- 1 always doublesided
- 2 address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language month monthfiled nationality note number one two organization pages publisher school series title type volume year yearfiled NAME
- 3 TRUE
- 4 FALSE

\btxdoifelseuservariable {...} {...} {...}

- 1 KEY
- 2 TRUE
- 3 FALSE

\btxdoifnot {...} {...}

- 1 address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language month monthfiled nationality note number one two organization pages publisher school series title type volume year yearfiled NAME
- 2 TRUE

\btxdoifsameaspreviouscheckedelse {...} {...} {...} {...}

- 1 always doublesided
- 2 address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language month monthfiled nationality note number one two organization pages publisher school series title type volume year yearfiled NAME
- 3 TRUE
- 4 FALSE

\btxdoifsameaspreviouselse {...} {...} {...}

- 1 address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language month monthfiled nationality note number one two organization pages publisher school series title type volume year yearfiled NAME
- 2 TRUE
- 3 FALSE

\btxdoifuservariableelse {...} {...} {...}

- 1 KEY
- 2 TRUE
- 3 FALSE

\btxexpandedjournal {...}

- \* NAME

\btxfield {...}

- \* address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language month monthfiled nationality note number one two organization pages publisher school series title type volume year yearfiled NAME

\btxfielddname {...}

\* address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language  
month monthfiled nationality note number one two organization pages publisher school series title type volume year  
yearfiled NAME

\btxfielddtype {...}

\* address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language  
month monthfiled nationality note number one two organization pages publisher school series title type volume year  
yearfiled NAME

\btxfirstofrange {...}

\* volume pages

\btxflush {...}

\* address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language  
month monthfiled nationality note number one two organization pages publisher school series title type volume year  
yearfiled NAME

\btxflushauthor [...<sup>1</sup>...] {...<sup>2</sup>...}

OPT

1 num normal normalshort inverted invertedshort

2 author editor

\btxflushauthorinverted {...}

\* author editor

\btxflushauthorinvertedshort {...}

\* author editor

\btxflushauthorname {...}

\* author editor

\btxflushauthornormal {...}

\* author editor

\btxflushauthornormalshort {...}

\* author editor

\btxflushsuffix

\btxfoundname {...}

\* address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language  
month monthfiled nationality note number one two organization pages publisher school series title type volume year  
yearfiled NAME

\btxfoundtype {...}

\* address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language  
month monthfiled nationality note number one two organization pages publisher school series title type volume year  
yearfiled NAME

`\btxhybridcite [...1...2...] [...]`  
OPT

- 1 reference = REFERENCE  
alternative = default category entry short page num textnum year index tag keywords author authoryears authornum authoryear  
before = COMMAND  
after = COMMAND  
left = COMMAND  
right = COMMAND  
inherits: \setupbtx
- 2 REFERENCE

`\btxhybridcite [...1...] [...2...]`  
OPT

- 1 default category entry short page num textnum year index tag keywords author authoryears authornum authoryear
- 2 REFERENCE

`\btxhybridcite {...}`

- \* REFERENCE

`\btxhybridcite [...1...2...] [...2...1...]`

- 1 reference = REFERENCE  
alternative = default category entry short page num textnum year index tag keywords author authoryears authornum authoryear  
before = COMMAND  
after = COMMAND  
left = COMMAND  
right = COMMAND  
inherits: \setupbtx
- 2 KEY = VALUE

`\btxlistcitation [...1...2...] [...]`  
OPT

- 1 reference = REFERENCE  
alternative = default category entry short page num textnum year index tag keywords author authoryears authornum authoryear  
before = COMMAND  
after = COMMAND  
left = COMMAND  
right = COMMAND  
inherits: \setupbtx
- 2 REFERENCE

`\btxlistcitation [...1...] [...2...]`  
OPT

- 1 default category entry short page num textnum year index tag keywords author authoryears authornum authoryear
- 2 REFERENCE

`\btxlistcitation [...1...2...] [...2...1...]`

- 1 reference = REFERENCE  
alternative = default category entry short page num textnum year index tag keywords author authoryears authornum authoryear  
before = COMMAND  
after = COMMAND  
left = COMMAND  
right = COMMAND  
inherits: \setupbtx
- 2 KEY = VALUE

`\btxloadjournalist [...]`

- \* FILE

`\btandoneorrangle {...} {...} {...}`

- 1 volume pages
- 2 TRUE
- 3 FALSE

`\btxremapauthor [...] [...]`

- 1 TEXT
- 2 TEXT

`\btxsavejournalist [...]`

- \* FILE

`\btxsetup {...}`

- \* NAME

`\btxsingularorplural {...} {...} {...}`

- 1 editor producer director
- 2 TRUE
- 3 FALSE

`\btxsingularplural {...} {...} {...}`

- 1 editor producer director
- 2 TRUE
- 3 FALSE

`\btxttextcitation [...,...1...,...] [...]`  
OPT

- 1 reference = REFERENCE  
alternative = default category entry short page num textnum year index tag keywords author authoryears authornum  
authoryear  
before = COMMAND  
after = COMMAND  
left = COMMAND  
right = COMMAND  
inherits: \setupbtx
- 2 REFERENCE

`\btxttextcitation [...] [...]`  
OPT

- 1 default category entry short page num textnum year index tag keywords author authoryears authornum authoryear
- 2 REFERENCE

`\btxttextcitation [...,...1...,...] [...,...2...,...]`

- 1 reference = REFERENCE  
alternative = default category entry short page num textnum year index tag keywords author authoryears authornum  
authoryear  
before = COMMAND  
after = COMMAND  
left = COMMAND  
right = COMMAND  
inherits: \setupbtx
- 2 KEY = VALUE

$\backslash\text{buildmathaccent} \{.^1.\} \{.^2.\}$  1 CHARACTER 2 CHARACTER
$\backslash\text{buildtextaccent} \{.^1.\} \{.^2.\}$  1 CHARACTER 2 CHARACTER
$\backslash\text{buildtextbottomcomma} \{.^*.\}$  * CHARACTER
$\backslash\text{buildtextbottomdot} \{.^*.\}$  * CHARACTER
$\backslash\text{buildtextcedilla} \{.^*.\}$  * CHARACTER
$\backslash\text{buildtextgrave} \{.^*.\}$  * CHARACTER
$\backslash\text{buildtextmacron} \{.^*.\}$  * CHARACTER
$\backslash\text{buildtextognek} \{.^*.\}$  * CHARACTER
$\backslash\text{button} [.,.,.\overset{.1}{.}.,.,.] \{.^2.\} [.^3.]$ 1 inherits: $\backslash\text{setupbutton}$ 2 TEXT 3 REFERENCE
$\backslash\text{BUTTON} [.,.,.\overset{.1}{.}.,.,.] \{.^2.\} [.^3.]$ 1 inherits: $\backslash\text{setupbutton}$ 2 TEXT 3 REFERENCE  instances: button
$\backslash\text{Caps} \{.^*.\}$  * TEXT
$\backslash\text{Character} \{.^*.\}$  * NUMBER
$\backslash\text{Characters} \{.^*.\}$  * NUMBER
$\backslash\text{CONTEXT}$

<code>\ConTeXt</code>
<code>\Context</code>
<code>\ConvertConstantAfter \.<sup>1</sup> {.<sup>2</sup>} {.<sup>3</sup>}</code>  1 CSNAME 2 TEXT 3 TEXT
<code>\ConvertToConstant \.<sup>1</sup> {.<sup>2</sup>} {.<sup>3</sup>}</code>  1 CSNAME 2 TEXT 3 TEXT
<code>\calligraphic</code>
<code>\camel {.*}</code>  * TEXT
<code>\catcodetablename</code>
<code>\cbox <sup>1</sup> {.<sup>2</sup>}</code> <small>OPT</small> 1 TEXT 2 CONTENT
<code>\centeraligned {.*}</code>  * CONTENT
<code>\centerbox <sup>1</sup> {.<sup>2</sup>}</code> <small>OPT</small> 1 TEXT 2 CONTENT
<code>\centeredbox <sup>1</sup> {.<sup>2</sup>}</code> <small>OPT</small> 1 TEXT 2 CONTENT
<code>\centeredlastline</code>
<code>\centerednextbox <sup>1</sup> {.<sup>2</sup>}</code> <small>OPT</small> 1 TEXT 2 CONTENT
<code>\centerline {.*}</code>  * CONTENT



$\backslash\mathrm{cfrac}$ [ <sup>1</sup> ...] { <sup>2</sup> ...} { <sup>3</sup> ...} <small>OPT</small> 1 l c r ll lc lr cl cc cr rl rc rr 2 CONTENT 3 CONTENT
$\backslash\mathrm{character}$ {...} * NUMBER
$\backslash\mathrm{CHARACTERKERNING}$ [ <sup>1</sup> ...] { <sup>2</sup> ...} <small>OPT</small> 1 NUMBER 2 TEXT
$\backslash\mathrm{characters}$ {...} * NUMBER
$\backslash\mathrm{chardescription}$ {...} * NUMBER
$\backslash\mathrm{charwidthlanguage}$
$\backslash\mathrm{check}$ {...} * CHARACTER
$\backslash\mathrm{checkcharacteralign}$ {...} * CONTENT
$\backslash\mathrm{checkedchar}$ { <sup>1</sup> ...} { <sup>2</sup> ...} 1 NUMBER 2 CHARACTER
$\backslash\mathrm{checkedfiller}$ {...} * sym symbol rule width space NAME COMMAND
$\backslash\mathrm{checkedstrippedcsname}$ \*.. * CSNAME
$\backslash\mathrm{checkedstrippedcsname}$ *.. * TEXT
$\backslash\mathrm{checkinjector}$ [.. * NAME
$\backslash\mathrm{checknextindentation}$ [.. * yes no auto
$\backslash\mathrm{checknextinjector}$ [.. * NAME

\checkpage [<sup>1</sup>...] [<sup>2</sup>...<sub>OPT</sub>...]

1 NAME

2 inherits: \setuppagechecker

\checkparameters [...]

\* TEXT

\checkpreviousinjector [...]

\* NAME

\checksoundtrack {...}

\* NAME

\checktwopassdata {...}

\* NAME

\checkvariables [<sup>1</sup>...] [<sup>2</sup>...<sub>OPT</sub>...]

1 NAME

2 set = COMMAND

reset = COMMAND

KEY = VALUE

\chem {...} {...<sup>2</sup>} {...<sup>3</sup>}

1 TEXT

2 TEXT

3 TEXT

\chemical [<sup>1</sup>...] [<sup>2</sup>...<sub>OPT</sub>...] [<sup>3</sup>...<sub>OPT</sub>...]

1 NAME

2 TEXT

3 TEXT

\chemicalbottext {...}

\* TEXT

\chemicalmidtext {...}

\* TEXT

\chemicalsymbol [...]

\* NAME

\chemicaltext {...}

\* TEXT

\chemicaltoptext {...}

\* TEXT

`\chineseallnumerals {...}`

\* NUMBER

`\chinesecapnumerals {...}`

\* NUMBER

`\chinesenumerals {...}`

\* NUMBER

`\citation [...1...2...] [...]`  
OPT

1 reference = REFERENCE  
alternative = default category entry short page num textnum year index tag keywords author authoryears authornum  
authoryear  
before = COMMAND  
after = COMMAND  
left = COMMAND  
right = COMMAND  
inherits: \setupbtx

2 REFERENCE

`\citation [...1...] [...2...]`  
OPT

1 default category entry short page num textnum year index tag keywords author authoryears authornum authoryear

2 REFERENCE

`\citation {...}`

\* REFERENCE

`\citation [...1...2...] [...2...]`

1 reference = REFERENCE  
alternative = default category entry short page num textnum year index tag keywords author authoryears authornum  
authoryear  
before = COMMAND  
after = COMMAND  
left = COMMAND  
right = COMMAND  
inherits: \setupbtx

2 KEY = VALUE

`\cite [...1...2...] [...]`  
OPT

1 reference = REFERENCE  
alternative = default category entry short page num textnum year index tag keywords author authoryears authornum  
authoryear  
before = COMMAND  
after = COMMAND  
left = COMMAND  
right = COMMAND  
inherits: \setupbtx

2 REFERENCE

`\cite [...1...] [...2...]`  
OPT

1 default category entry short page num textnum year index tag keywords author authoryears authornum authoryear

2 REFERENCE

`\cite {...}`

\* REFERENCE

`\cite [...1...] [...2...]`

```
1  reference      = REFERENCE
   alternative    = default category entry short page num textnum year index tag keywords author authoryears authornum
                        authoryear
   before        = COMMAND
   after         = COMMAND
   left          = COMMAND
   right         = COMMAND
   inherits: \setupbtx
2  KEY = VALUE
```

`\clap {...}`

\* CONTENT

`\classfont {...1} {...2}`

1 NAME

2 FONT

`\cldcommand {...}`

\* COMMAND

`\cldcontext {...}`

\* COMMAND

`\cldloadfile {...}`

\* FILE

`\cldprocessfile {...}`

\* FILE

`\cleftarrow {...1} {...2}`  
                  OPT      OPT

1 TEXT

2 TEXT

`\clip [...1...] {...2}`  
                  OPT

1 inherits: \setupclipping

2 CONTENT

`\clonefield [...1] [...2] [...3] [...4,...]`

1 NAME

2 NAME

3 NAME

4 NAME

`\collect {...}`

\* CONTENT

$\backslash\text{collectedtext}$ [ $\dots,\dots,\overset{1}{=}\dots,\dots$ ] [ $\dots,\dots,\overset{2}{=}\dots,\dots$ ] $\{\dots\}$ $\{\dots\}$ <small>OPT</small> <small>OPT</small>
1 inherits: $\backslash\text{setupcollector}$ 2 style = STYLE COMMAND color = COLOR inherits: $\backslash\text{setupframed}$ 3 TEXT 4 CONTENT
$\backslash\text{collectexpanded}$ $\{\dots\}$ * CONTENT
$\backslash\text{color}$ [ $\overset{1}{.}\dots$ ] $\{\overset{2}{.}\dots\}$ 1 COLOR 2 CONTENT
$\backslash\text{colorbar}$ [ $\dots,\dots,\dots$ ] * COLOR
$\backslash\text{colorcomponents}$ $\{\dots\}$ * COLOR
$\backslash\text{colored}$ [ $\dots,\dots,\overset{1}{=}\dots,\dots$ ] $\{\overset{2}{.}\dots\}$ 1 inherits: $\backslash\text{definecolor}$ 2 CONTENT
$\backslash\text{colored}$ [ $\overset{1}{.}\dots$ ] $\{\overset{2}{.}\dots\}$ 1 COLOR 2 CONTENT
$\backslash\text{coloronly}$ [ $\overset{1}{.}\dots$ ] $\{\overset{2}{.}\dots\}$ 1 COLOR 2 CONTENT
$\backslash\text{colorvalue}$ $\{\dots\}$ * COLOR
$\backslash\text{column}$ [ $\dots,\dots,\dots$ ] <small>OPT</small>
* inherits: $\backslash\text{columnbreak}$
$\backslash\text{columnbreak}$ [ $\dots,\dots,\dots$ ] <small>OPT</small>
* yes no preference local force first last NUMBER NAME

**\combinepages** [<sup>1</sup>...] [<sup>2</sup>...<sub>OPT</sub>...]

1 FILE

2 alternative = a b c horizontal vertical  
n = NUMBER  
nx = NUMBER  
ny = NUMBER  
start = NUMBER  
stop = NUMBER  
distance = DIMENSION  
top = COMMAND  
bottom = COMMAND  
left = COMMAND  
right = COMMAND  
before = COMMAND  
after = COMMAND  
inbetween = COMMAND  
frame = on off  
background = foreground color NAME  
backgroundcolor = COLOR

**\commalistelement**

**\commalistsentence** [...<sup>1</sup>,...] [...<sup>2</sup>,...]<sub>OPT</sub>

1 TEXT  
2 TEXT

**\commalistsize**

**\COMMENT** [<sup>1</sup>...] [...<sup>2</sup>,...]<sub>OPT</sub> {...}<sup>3</sup>

1 TEXT  
2 inherits: \setupcomment  
3 TEXT

instances: comment

**\comparecolorgroup** [...]

\* NAME

**\comparedimension** {...<sup>1</sup>} {...<sup>2</sup>}

1 DIMENSION  
2 DIMENSION

**\comparedimensioneps** {...<sup>1</sup>} {...<sup>2</sup>}

1 DIMENSION  
2 DIMENSION

**\comparepalet** [...]

\* NAME

**\completebt rendering** [<sup>1</sup>...] [...<sup>2</sup>,...]<sub>OPT</sub>

1 NAME  
2 inherits: \setupbt rendering

$\backslash completeCOMBINEDLIST [\dots, \dots, \dots]$ <small>OPT</small> * inherits: \setuplist  instances: content
$\backslash completelist [\dots] [\dots, \dots, \dots]$ <small>OPT</small> 1 LIST 2 inherits: \setuplist
$\backslash completelistofFLOATS [\dots, \dots, \dots]$ <small>OPT</small> * inherits: \setuplist  instances: chemicals figures tables intermezzi graphics
$\backslash completelistofpublications [\dots] [\dots, \dots, \dots]$ <small>OPT</small> <small>OPT</small> 1 NAME 2 inherits: \setupbtxrendering
$\backslash completelistofsorts [\dots] [\dots, \dots, \dots]$ <small>OPT</small> 1 SINGULAR 2 inherits: \setupsorting
$\backslash completelistofSORTS [\dots, \dots, \dots]$ <small>OPT</small> * inherits: \setupsorting  instances: logos
$\backslash completelistofsynonyms [\dots] [\dots, \dots, \dots]$ <small>OPT</small> 1 SINGULAR 2 inherits: \setupsynonyms
$\backslash completelistofSYNONYMS [\dots, \dots, \dots]$ <small>OPT</small> * inherits: \setupsynonyms  instances: abbreviations
$\backslash completepagenumber$
$\backslash completeregister [\dots] [\dots, \dots, \dots]$ <small>OPT</small> 1 NAME 2 inherits: \setupregister
$\backslash completeREGISTER [\dots, \dots, \dots]$ <small>OPT</small> * inherits: \setupregister  instances: index
$\backslash setupindex [\dots, \dots] [\dots, \dots, \dots]$ <small>OPT</small> 1 NUMBER 2 inherits: \setupregister

\complexorsimple \*.. * CSNAME
\complexorsimpleempty \*.. * CSNAME
\complexorsimpleempty {...} * TEXT CSNAME
\complexorsimple {...} * TEXT CSNAME
\component [...]
\component *.. * FILE
\composedcollector {...} * NAME
\composedlayer {...} * NAME
\compresult
\constantdimen \*.. * CSNAME
\constantdimenargument \*.. * CSNAME
\constantemptyargument \*.. * CSNAME
\constantnumber \*.. * CSNAME
\constantnumberargument \*.. * CSNAME
\contentreference [..., <sup>1</sup> ...] [..., <sup>2</sup> ...,...] <sup>3</sup> {...} 1 REFERENCE 2 inherits: \setupframed 3 CONTENT
\continuednumber {...} * NUMBER



$\backslash\text{continueifinputfile}$ {...} *    FILE
$\backslash\text{convertargument}$ $\overset{1}{...}$ $\backslash\text{to}$ $\overset{2}{...}$ 1    TEXT 2    CSNAME
$\backslash\text{convertcommand}$ $\backslash\overset{1}{...}$ $\backslash\text{to}$ $\overset{2}{...}$ 1    CSNAME 2    CSNAME
$\backslash\text{convertedcounter}$ [ $\overset{1}{...}$ ] [ $\overset{2}{...}$ $\overset{2}{\equiv}$ $\overset{2}{...}$ ,...] <div style="text-align: center;"><small>OPT</small></div> 1    NAME 2    inherits: $\backslash\text{setupcounter}$
$\backslash\text{convertedddimen}$ $\{\overset{1}{...}\}$ $\{\overset{2}{...}\}$ 1    DIMENSION 2    ex em pt in cm mm sp bp pc dd cc nc
$\backslash\text{convertedsubcounter}$ [ $\overset{1}{...}$ ] [ $\overset{2}{...}$ ] [ $\overset{3}{...}$ $\overset{3}{\equiv}$ $\overset{3}{...}$ ,...] <div style="display: flex; justify-content: space-around; width: 100%;"><div><small>OPT</small></div><div><small>OPT</small></div></div> 1    NAME 2    NUMBER NUMBER:NUMBER NUMBER:* NUMBER:all 3    inherits: $\backslash\text{setupcounter}$
$\backslash\text{convertmonth}$ {...} *    NUMBER
$\backslash\text{convertnumber}$ $\{\overset{1}{...}\}$ $\{\overset{2}{...}\}$ 1    empty default none month month:mnem character Character characters Characters a A Numbers word words Word Words n N romannumerals Romannumerals i I r R KR RK greek Greek g G abjadnumerals abjadnodotnumerals abjadnaivenumerals thainumerals devanagarinumerals gurmukhinumerals gujaratinnumerals tibetannumerals greeknumerals Greeknumerals arabicnumerals persiannumerals arabicexnumerals arabicdecimals persiandecimals koreannumerals koreanparentnumerals koreancirlenumerals kr kr-p kr-c chinesenumerals chinesecapnumerals chineseallnumerals cn cn-c cn-a sloveniannumerals slovenianNumerals spanishnumerals spanishNumerals mathgreek set_0 set_1 set_2 set_3 continued NAME 2    NUMBER
$\backslash\text{convertvalue}$ $\overset{1}{...}$ $\backslash\text{to}$ $\overset{2}{...}$ 1    NAME 2    CSNAME
$\backslash\text{convertvboxtohbox}$
$\backslash\text{copyboxfromcache}$ $\{\overset{1}{...}\}$ $\{\overset{2}{...}\}$ $\overset{3}{...}$ 1    NAME 2    NUMBER TEXT 3    CSNAME NUMBER
$\backslash\text{copyfield}$ [ $\overset{1}{...}$ ] [ $\overset{2}{...}$ ] 1    NAME 2    NAME

`\copyLABELtext` [<sup>1</sup>...] [<sup>2</sup>...<sub>OPT</sub>...]

1 LANGUAGE

2 KEY = KEY

instances: head label mathlabel taglabel unit operator prefix suffix btxlabel

`\coppages` [<sup>1</sup>...] [<sub>OPT</sub>...<sup>2</sup>...]<sub>OPT</sub> [<sub>OPT</sub>...<sup>3</sup>...]

1 FILE

2 marking = on off  
offset = DIMENSION  
n = NUMBER

3 inherits: \setupexternalfigure

`\copyparameters` [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...]

1 TEXT

2 TEXT

3 KEY

`\copyposition` {<sup>1</sup>...} {<sup>2</sup>...}

1 NAME

2 NAME

`\correctwhitespace` {<sup>\*</sup>...}

\* CONTENT

`\countersubs` [<sup>1</sup>...] [<sub>OPT</sub>...<sup>2</sup>...]

1 NAME

2 NUMBER

`\counttoken` <sup>1</sup>... \in <sup>2</sup>... \to \<sup>3</sup>...

1 TEXT

2 TEXT

3 CSNAME

`\counttokens` <sup>1</sup>... \to \<sup>2</sup>...

1 TEXT

2 CSNAME

`\cramped` {<sup>\*</sup>...}

\* CONTENT

`\crampedclap` {<sup>\*</sup>...}

\* CONTENT

`\crampedllap` {<sup>\*</sup>...}

\* CONTENT

`\crampedrlap` {<sup>\*</sup>...}

\* CONTENT

$\backslash\mathrm{crightarrow} \overset{1}{\{...\}} \overset{2}{\{...\}}$ 1    TEXT 2    TEXT
$\backslash\mathrm{crightoverleftarrow} \overset{1}{\{...\}} \overset{2}{\{...\}}$ 1    TEXT 2    TEXT
$\backslash\mathrm{ctop} \overset{1}{...} \overset{2}{\{...\}}$ 1    TEXT 2    CONTENT
$\backslash\mathrm{ctxcommand} \{...\}$ *    COMMAND
$\backslash\mathrm{ctxdirectcommand} \{...\}$ *    COMMAND
$\backslash\mathrm{ctxdirectlua} \{...\}$ *    COMMAND
$\backslash\mathrm{ctxfunction} \{...\}$ *    NAME
$\backslash\mathrm{CTXFUNCTIONDEFINITION}$
$\backslash\mathrm{CTXFUNCTION}$
$\backslash\mathrm{ctxlatecommand} \{...\}$ *    COMMAND
$\backslash\mathrm{ctxlatelua} \{...\}$ *    COMMAND
$\backslash\mathrm{ctxloadluafile} \{...\}$ *    FILE
$\backslash\mathrm{ctxlua} \{...\}$ *    COMMAND
$\backslash\mathrm{ctxluabuffer} [\overset{1}{...}]$ *    BUFFER
$\backslash\mathrm{ctxluacode} \{...\}$ *    COMMAND
$\backslash\mathrm{ctxreport} \{...\}$ *    COMMAND

\ctxsprint {...} *   COMMAND
\currentassignmentlistkey
\currentassignmentlistvalue
\currentbtxuservariable {...} *   KEY
\currentcommalistitem
\currentcomponent
\currentdate [...,*,...] OPT *   year month day weekday y yy Y m mm M d dd D w W space \_ month:mnem m:mnem d:ord day:ord dd:ord D:ord TEXT referral day:+ day:++ d:+ d:++ dd:+ dd:++ D:+ D:++ month:jalali m:jalali jalali:to jalali:from
\currentenvironment
\currentfeaturetest
\currentheadnumber
\currentinterface
\currentLABEL [..., <sup>1</sup> ...] {.. <sup>2</sup> .} OPT                                  OPT 1   REFERENCE 2   TEXT
\currentlanguage
\currentlistentrydestinationattribute
\currentlistentrylimitedtext {...} *   TEXT
\currentlistentrynumber
\currentlistentrypagenumber
\currentlistentryreferenceattribute {...} *   number text pagenumber all
\currentlistentrytitle
\currentlistentrytitlerendered
\currentlistsymbol

<code>\currentmainlanguage</code>
<code>\currentmessagetext</code>
<code>\currentmoduleparameter {...}</code> *    KEY
<code>\currentoutputstream</code>
<code>\currentproduct</code>
<code>\currentproject</code>
<code>\currentregime</code>
<code>\currentregisterpageuserdata {...}</code> *    KEY
<code>\currentresponses</code>
<code>\currenttime [...,*,...]</code> <div style="text-align: center; margin-left: 100px;"><small>OPT</small></div> *    h m TEXT
<code>\currentvalue</code>
<code>\currentxtablecolumn</code>
<code>\currentxtablerow</code>
<code>\d {...}</code> *    CHARACTER
<code>\datasetvariable {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}</code> 1    NAME 2    NAME NUMBER 3    KEY realpage
<code>\date [...,*<sup>1</sup>*,...]</code> <code>[...,*<sup>2</sup>*,...]</code> <div style="display: flex; justify-content: space-around; width: 100%;"> <div style="text-align: center;"><small>OPT</small></div> <div style="text-align: center;"><small>OPT</small></div> </div> 1    d   =   NUMBER m   =   NUMBER y   =   NUMBER 2    inherits: \currentdate
<code>\dayoftheweek {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}</code> 1    NUMBER 2    NUMBER 3    NUMBER

<code>\dayspermonth {...} {...}</code>  1    NUMBER 2    NUMBER
<code>\ddot {...}</code>  *    CHARACTER
<code>\decrement \...</code>  *    CSNAME
<code>\decrementcounter [...]<sup>1</sup> [...]<sup>2</sup></code> <div style="text-align: right; margin-right: 100px;"><small>OPT</small></div> 1    NAME 2    NUMBER
<code>\decrementedcounter [...]</code>  *    NAME
<code>\decrementpagenumber</code>
<code>\decrementsubpagenumber</code>
<code>\decrementvalue {...}</code>  *    NAME
<code>\decrement cd:parentheses-1</code>  *    CSNAME NUMBER
<code>\defaultinterface</code>
<code>\defaultobjectpage</code>
<code>\defaultobjectreference</code>
<code>\defcatcodecommand \...<sup>1</sup> ...<sup>2</sup> {...}<sup>3</sup></code>  1    CSNAME 2    CHARACTER NUMBER 3    COMMAND
<code>\defconvertedargument \...<sup>1</sup> {...}<sup>2</sup></code>  1    CSNAME 2    TEXT
<code>\defconvertedcommand \...<sup>1</sup> \...<sup>2</sup></code>  1    CSNAME 2    CSNAME

`\defconvertedvalue \1... {\2...}`

1 CSNAME

2 NAME

`\define [1...] \2... {\3...}`  
OPT

1 NUMBER

2 CSNAME

3 CONTENT

`\defineaccent \1... \2... \3...`

1 CHARACTER

2 CHARACTER

3 CHARACTER

`\defineactivecharacter \1... {\2...}`

1 CHARACTER

2 COMMAND

`\definealternativestyle [...,\1...] [\2...] [\3...]`

1 NAME

2 COMMAND

3 COMMAND

`\defineanchor [1...] [2...] [...,\3...,...] [...,\4...,...]`  
OPT OPT

1 NAME

2 NAME

3 inherits: \setupplayer

4 inherits: \setupplayerinherits: \setupframed

`\defineattachment [1...] [2...] [...,\3...,...]`  
OPT OPT

1 NAME

2 NAME

3 inherits: \setupattachment

`\defineattribute [1...] [...,\2...,...]`  
OPT

1 NAME

2 local global public private

`\definebackground [1...] [2...] [...,\3...,...]`  
OPT OPT

1 NAME

2 NAME

3 inherits: \setupbackground

`\definebar [1...] [2...] [...,\3...,...]`  
OPT OPT

1 NAME

2 NAME

3 inherits: \setupbar

```
\defineblock [...]1 [...]2 [...]3 [...]
                        OPT      OPT
```

- 1 NAME
- 2 NAME
- 3 inherits: \setupblock

```
\definebodyfont [...]1 [...]2 [...]3 [...]4 [...]
                        OPT      OPT
```

- 1 NAME default
- 2 NAME DIMENSION
- 3 rm ss tt hw cg
- 4
 

tf	=	FILE
bf	=	FILE
it	=	FILE
sl	=	FILE
bi	=	FILE
bs	=	FILE
sc	=	FILE
mr	=	FILE
mrlr	=	FILE
mrrl	=	FILE
mb	=	FILE
mblr	=	FILE
mbrl	=	FILE

```
\definebodyfontenvironment [...]1 [...]2 [...]3 [...]
                        OPT      OPT
```

- 1 NAME
- 2 default DIMENSION
- 3
 

big	=	DIMENSION NUMBER
small	=	DIMENSION NUMBER
a	=	DIMENSION NUMBER
b	=	DIMENSION NUMBER
c	=	DIMENSION NUMBER
d	=	DIMENSION NUMBER
text	=	DIMENSION NUMBER
x	=	DIMENSION NUMBER
xx	=	DIMENSION NUMBER
script	=	DIMENSION NUMBER
scriptscript	=	DIMENSION NUMBER
interlinespace	=	DIMENSION
em	=	slanted italic STYLE COMMAND
*	=	NUMBER

```
\definebodyfontswitch [...]1 [...]2 [...]
```

- 1 NAME
- 2 inherits: \setupbodyfont

```
\definebodyfont [...]1 [...]2 [...]3 [...]4 [...]
                        OPT      OPT
```

- 1 NAME default
- 2 NAME DIMENSION
- 3 rm ss tt hw cg
- 4 NAME



```

\definebreakpoint [1...] [2...] [3...OPT...]

1  NAME

2  CHARACTER

3  type      = 1 2 3 4 5
   nleft     = NUMBER
   nright     = NUMBER
   left      = COMMAND
   middle     = COMMAND
   right     = COMMAND
   range     = yes no
   language  = LANGUAGE

```

```

\definebreakpoints [...*]

*  NAME

```

```

\definebtx [1...] [2...] [3...OPT...]

1  NAME

2  NAME

3  inherits: \setupbtx

```

```

\definebtxdataset [1...] [2...] [3...OPT...]

1  NAME

2  NAME

3  inherits: \setupbtxdataset

```

```

\definebtxregister [1...] [2...] [3...OPT...]

1  NAME

2  NAME

3  inherits: \setupbtxregister

```

```

\definebtxrendering [1...] [2...] [3...OPT...]

1  NAME

2  NAME

3  inherits: \setupbtxrendering

```

```

\definebuffer [1...] [2...] [3...OPT...]

1  NAME

2  BUFFER

3  inherits: \setupbuffer

```

```

\definebutton [1...] [2...] [3...OPT...]

1  NAME

2  NAME

3  inherits: \setupbutton

```

```

\definecapitals [1...] [2...] [3...OPT...]

1  NAME

2  NAME

3  inherits: \setupcapitals

```

`\definecharacter 1... 2...`

1 CHARACTER

2 NUMBER

`\definecharacterkerning [1...] [2...] [3...3...]`  
OPT OPT

1 NAME

2 NAME

3 inherits: \setupcharacterkerning

`\definecharacterspacing [...]`

\* NAME

`\definechemical [1] {2...}`

1 NAME

2 CONTENT

`\definechemicals [1] [2...] [3...3...]`  
OPT OPT

1 NAME

2 NAME

3 inherits: \setupchemical

`\definechemicalsymbol [1] [2...]`

1 NAME

2 TEXT

`\definecollector [1] [2...] [3...3...]`  
OPT OPT

1 NAME

2 NAME

3 inherits: \setupcollector

`\definecolor [1] [2...2...]`

1 NAME

2 r = NUMBER

g = NUMBER

b = NUMBER

c = NUMBER

m = NUMBER

y = NUMBER

k = NUMBER

h = NUMBER

s = NUMBER

v = NUMBER

x = NUMBER

a = NUMBER none normal multiply screen overlay softlight hardlight colordodge colorburn darken lighten difference  
exclusion hue saturation color luminosity

t = NUMBER

`\definecolorgroup [1] [2...] [x:y:3z,...]`  
OPT

1 NAME

2 gray rgb cmyk spot

3 TRIPLET

`\definecolor [...]1 [...]2`

- 1 NAME
- 2 COLOR

`\definecolumnbreak [...]1 [...]2,...]`

- 1 NAME
- 2 yes no preference local force first last NUMBER

`\definecombination [...]1 [...]2 [...]3,...]`  
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupcombination

`\definecombinedlist [...]1 [...]2,... [...]3,...]`  
OPT

- 1 NAME
- 2 LIST
- 3 inherits: \setuplist

`\definecommand ...1 ...2`

- 1 CHARACTER
- 2 COMMAND

`\definecomment [...]1 [...]2 [...]3,...]`  
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupcomment

`\definecomplexorsimple \*...`

- \* CSNAME

`\definecomplexorsimpleempty \*...`

- \* CSNAME

`\definecomplexorsimpleempty {*...}`

- \* TEXT CSNAME

`\definecomplexorsimple {*...}`

- \* TEXT CSNAME

`\defineconversion [...]1 [...]2 [...]3`  
OPT

- 1 LANGUAGE
- 2 NAME
- 3 CSNAME

```
\defineconversionset [...] [...] [...]
                                OPT
1  NAME SECTIONBLOCK:NAME
2  NAME PROCESSOR->NAME
3  NAME PROCESSOR->NAME
```

```
\defineconversion [...] [...] [...]
                   OPT
1  LANGUAGE
2  NAME
3  TEXT
```

```
\definecounter [...] [...] [...]
                OPT      OPT
1  NAME
2  NAME
3  inherits: \setupcounter
```

```
\definedataset [...] [...] [...]
                OPT      OPT
1  NAME
2  NAME
3  inherits: \setupdataset
```

```
\definedelimitedtext [...] [...] [...]
                      OPT      OPT
1  NAME
2  NAME
3  inherits: \setupdelimitedtext
```

```
\definedescription [...] [...] [...]
                   OPT      OPT
1  NAME
2  NAME
3  inherits: \setupdescription
```

```
\definedfont [...]
              OPT
*  FONT
```

```
\defineeffect [...] [...] [...]
                OPT      OPT
1  NAME
2  NAME
3  inherits: \setupeffect
```

```
\defineenumeration [...] [...] [...]
                    OPT      OPT
1  NAME
2  NAME
3  inherits: \setupenumeration
```

```
\defineexpandable [...] \... {...}
                   OPT
1  NUMBER
2  CSNAME
3  CONTENT
```

```
\defineexternalfigure [1...] [2...] [3...,...OPT...,...]OPT
```

- 1 NAME
- 2 NAME
- 3 inherits: \setupexternalfigure

```
\definefallbackfamily [1...] [2...] [3...] [4...,...OPT...,...]OPT
```

- 1 NAME
- 2 rm ss tt mm hw cg roman serif regular sansserif sans support teletype type mono handwritten calligraphic math mathematics
- 3 FONT
- 4
 

rscale	=	NUMBER
designsize	=	default auto
goodies	=	FILE
range	=	NUMBER NAME
offset	=	NUMBER NAME
check	=	yes <u>no</u>
force	=	yes <u>no</u>
features	=	NAME
tf	=	TEXT
bf	=	TEXT
it	=	TEXT
sl	=	TEXT
bi	=	TEXT
bs	=	TEXT
sc	=	TEXT

```
\definefallbackfamily [1...] [2...] [3...] [4...,...OPT...,...]OPT
```

- 1 NAME
- 2 rm ss tt mm hw cg roman serif regular sansserif sans support teletype type mono handwritten calligraphic math mathematics
- 3 FONT
- 4 NAME

```
\definefield [1...] [2...] [3...] [4...,...]OPT [5...]
```

- 1 NAME
- 2 radio sub text line push check signature
- 3 NAME
- 4 NAME
- 5 NAME

```
\definefieldbody [1...] [2...] [3...,...OPT...,...]OPT
```

- 1 NAME
- 2 NAME
- 3 inherits: \setupfieldbody

```
\definefieldbodyset [1...] [2...,...]
```

- 1 NAME
- 2 NAME

```
\definefieldcategory [1...] [2...] [3...,...OPT...,...]OPT
```

- 1 NAME
- 2 NAME
- 3 inherits: \setupfieldcategory

`\definefieldstack [...]1 [...]2 [...]3...`  
OPT

1 NAME

2 NAME

3 inherits: \setupfieldcategory

`\definefiguresymbol [...]1 [...]2 [...]3...`  
OPT

1 NAME

2 FILE NAME

3 inherits: \externalfigure

`\definefileconstant {...}1 {...}2`

1 NAME

2 NAME

`\definefilefallback [...]1 [...]2...`

1 NAME

2 FILE

`\definefilesynonym [...]1 [...]2`

1 NAME

2 FILE

`\definefiller [...]1 [...]2 [...]3...`  
OPT OPT

1 NAME

2 NAME

3 inherits: \setupfiller

`\definefirstline [...]1 [...]2 [...]3...`  
OPT OPT

1 NAME

2 NAME

3 inherits: \setupfirstline

`\definefittingpage [...]1 [...]2 [...]3...`  
OPT OPT

1 NAME

2 NAME

3 inherits: \setupfittingpage

`\definefloat [...]1 [...]2 [...]3...`  
OPT OPT

1 SINGULAR

2 SINGULAR PLURAL

3 inherits: \setupfloat

instances: chemical figure table intermezzo graphic

```
\definefloat [1...] [2...] [3...]  
                OPT      OPT
```

```
1  SINGULAR  
2  PLURAL  
3  SINGULAR
```

instances: chemical figure table intermezzo graphic

```
\definefont [1...] [2...] [3...,...]  
                OPT
```

```
1  NAME  
2  FONT  
3  inherits: \setupinterlinespace
```

```
\definefontalternative [...]
```

```
*  NAME
```

```
\definefontfallback [1...] [2...] [3...,...]  
                OPT
```

```
1  NAME  
2  FONT NAME  
3  NAME NUMBER  
4  rscale    = NUMBER  
    force    = yes no  
    check    = yes no  
    offset   = NUMBER NAME  
    features  = NAME
```

```
\definefontfamily [1...] [2...] [3...] [4...,...]  
                OPT
```

```
1  NAME  
2  rm ss tt mm hw cg roman serif regular sansserif sans support teletype type mono handwritten calligraphic math  
   mathematics  
3  FONT  
4  rscale    = NUMBER  
    designsize = default auto  
    goodies   = FILE  
    features  = NAME  
    tf       = TEXT  
    bf       = TEXT  
    it       = TEXT  
    sl       = TEXT  
    bi       = TEXT  
    bs       = TEXT  
    sc       = TEXT
```

```
\definefontfamilypreset [1...] [2...,...]
```

```
1  NAME  
2  inherits: \definefontfamily
```

```
\definefontfamilypreset [1...] [2...]
```

```
1  NAME  
2  NAME
```

`\definefontfamily` [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...] [<sup>4</sup>...,...]  
OPT

- 1 NAME
- 2 `rm ss tt mm hw cg roman serif regular sansserif sans support teletype type mono handwritten calligraphic math mathematics`
- 3 FONT
- 4 NAME

`\definefontfeature` [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...]  
OPT

- 1 NAME
- 2 NAME
- 3
 

language	=	NAME
script	=	NAME auto
mode	=	node base auto none
liga	=	yes no
kern	=	yes no
extrakerns	=	yes no
tlig	=	yes no
trep	=	yes no
missing	=	yes no
dummies	=	yes no
analyze	=	yes no
unicoding	=	yes no
expansion	=	NAME
protrusion	=	NAME
nostackmath	=	yes no
realdimensions	=	yes no
itlc	=	yes no
textitalics	=	yes no
mathitalics	=	yes no
slant	=	NUMBER
extend	=	NUMBER
dimensions	=	NUMBER
boundingbox	=	yes no
compose	=	yes no
char-ligatures	=	yes no
compat-ligatures	=	yes no
goodies	=	FILE
extrafeatures	=	yes no
featureset	=	NAME
colorscheme	=	NAME
postprocessor	=	NAME
mathdimensions	=	NAME
keepligatures	=	yes no auto
devanagari	=	yes no
features	=	yes no
tcom	=	yes no
anum	=	yes no
mathsize	=	yes no
decomposehangul	=	yes no
mathalternatives	=	yes no
mathgaps	=	yes no
checkmarks	=	<u>yes</u> no
NAME	=	yes <u>no</u>
mathnolimitsmode	=	NUMBER
blockligatures	=	yes <u>no</u>

`\definefontfile` [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...]  
OPT

- 1 NAME
- 2 FILE
- 3
 

features	=	NAME
fallbacks	=	NAME
goodies	=	NAME
designsize	=	auto default

`\definefontsize` [.\*]

- \* NAME



```

\definefontsolution [1...] [2...] [3...OPT...OPT]

1  NAME
2  NAME
3  inherits: \setupfontsolution

```

```

\definefontstyle [1...] [2...]

1  NAME
2  NAME

```

```

\definefontsynonym [1...] [2...] [3...OPT...OPT]

1  NAME
2  FONT
3  features    = NAME
    fallbacks  = NAME
    goodies    = NAME
    designsize = auto default

```

```

\definefont [1...] [2...] [3...OPT]

1  NAME
2  FONT
3  NAME

```

```

\defineformula [1...] [2...] [3...OPT...OPT]

1  NAME
2  NAME
3  inherits: \setupformula

```

```

\defineformulaalternative [1...] [2...] [3...]

1  NAME
2  CSNAME
3  CSNAME

```

```

\defineformulaframed [1...] [2...] [3...OPT...OPT]

1  NAME
2  NAME
3  inherits: \setupformulaframed

```

```

\defineframed [1...] [2...] [3...OPT...OPT]

1  NAME
2  NAME
3  inherits: \setupframed

```

```

\defineframedcontent [1...] [2...] [3...OPT...OPT]

1  NAME
2  NAME
3  inherits: \setupframedcontent

```

**\defineframedtext** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...<sub>OPT</sub>...<sub>OPT</sub>]

- 1 NAME
- 2 NAME
- 3 inherits: \setupframedtext

**\definefrozenfont** [<sup>1</sup>...] [<sup>2</sup>...]

- 1 NAME
- 2 FONT

**\defineglobalcolor** [<sup>1</sup>...] [<sup>2</sup>...<sub>OPT</sub>...]

- 1 NAME
- 2 inherits: \definecolor

**\defineglobalcolor** [<sup>1</sup>...] [<sup>2</sup>...]

- 1 NAME
- 2 COLOR

**\definegraphictypesynonym** [<sup>1</sup>...] [<sup>2</sup>...]

- 1 NAME
- 2 NAME

**\definegridsnapping** [<sup>1</sup>...] [<sup>2</sup>...<sub>OPT</sub>...]

- 1 NAME
- 2 local global noheight nodepth box max min none line halflines first last minheight maxheight mindepth maxdepth top bottom strut NUMBER minheight:NUMBER maxheight:NUMBER mindepth:NUMBER maxdepth:NUMBER box:NUMBER top:NUMBER bottom:NUMBER offset:NUMBER

**\definehbox** [<sup>1</sup>...] [<sup>2</sup>...]

- 1 NAME
- 2 DIMENSION

**\definehead** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...<sub>OPT</sub>...<sub>OPT</sub>]

- 1 NAME
- 2 SECTION
- 3 inherits: \setuphead

**\defineheadalternative** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...<sub>OPT</sub>...<sub>OPT</sub>]

- 1 NAME
- 2 NAME
- 3 inherits: \setupheadalternative

**\definehelp** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...<sub>OPT</sub>...<sub>OPT</sub>]

- 1 NAME
- 2 NAME
- 3 inherits: \setuphelp

```
\definehigh [...]1 [...]2 [...,...3...,...]3
```

OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setuphigh

```
\definehighlight [...]1 [...]2 [...,...3...,...]3
```

OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setuphighlight

```
\definehspace [...]1 [...]2 [...]3
```

OPT

- 1 NAME
- 2 NAME
- 3 DIMENSION

```
\definehyphenationfeatures [...]1 [...,...2...,...]2
```

- 1 NAME
- 2
 

characters	=	TEXT
hyphens	=	yes all TEXT
joiners	=	yes all TEXT
rightwords	=	NUMBER
hyphenmin	=	NUMBER
lefthyphenmin	=	NUMBER
rightthyphenmin	=	NUMBER
lefthyphenchar	=	NUMBER
rightthyphenchar	=	NUMBER
alternative	=	original tex <u>hyphenate</u> expanded traditional none
rightedge	=	tex
rightchars	=	word NUMBER

```
\defineindentedtext [...]1 [...]2 [...,...3...,...]3
```

OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupindentedtext

```
\defineindenting [...]1 [...,...2...,...]2
```

- 1 NAME
- 2 [-+]small [-+]medium [-+]big none no not first next yes always never odd even normal reset toggle DIMENSION

```
\defineinitial [...]1 [...]2 [...,...3...,...]3
```

OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupinitial

```
\defineinsertion [...]1 [...]2 [...,...3...,...]3
```

OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupinsertion

```
\defineinteraction [1...] [2...] [3...,...OPT...,...]OPT
```

- 1 NAME
- 2 NAME
- 3 inherits: \setupinteraction

```
\defineinteractionbar [1...] [2...] [3...,...OPT...,...]OPT
```

- 1 NAME
- 2 NAME
- 3 inherits: \setupinteractionbar

```
\defineinteractionmenu [1...] [2...] [3...,...OPT...,...]OPT
```

- 1 NAME
- 2 NAME
- 3 inherits: \setupinteractionmenu

```
\defineinterfaceconstant {1...} {2...}
```

- 1 NAME
- 2 NAME

```
\defineinterfaceelement {1...} {2...}
```

- 1 NAME
- 2 NAME

```
\defineinterfacevariable {1...} {2...}
```

- 1 NAME
- 2 NAME

```
\defineinterlinespace [1...] [2...] [3...,...OPT...,...]OPT
```

- 1 NAME
- 2 NAME
- 3 inherits: \setupinterlinespace

```
\defineintermediatecolor [1...] [2...,...]OPT [3...,...OPT...,...]
```

- 1 NAME
- 2 COLOR NUMBER
- 3 a = NUMBER  
t = NUMBER

```
\defineitemgroup [1...] [2...] [3...,...OPT...,...]OPT
```

- 1 NAME
- 2 NAME
- 3 inherits: \setupitemgroup

```
\defineitems [1...] [2...] [3...,...OPT...,...]OPT
```

- 1 NAME
- 2 NAME
- 3 inherits: \setupitems

```
\definelabel [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setuplabel
```

```
\definelabelclass [...] [...]
1 NAME
2 NUMBER
```

```
\setupbtxlabeltext [...] [...]
1 LANGUAGE
2 KEY = VALUE
```

```
\setupheadtext [...] [...]
1 LANGUAGE
2 KEY = VALUE
```

```
\setuplabeltext [...] [...]
1 LANGUAGE
2 KEY = VALUE
```

```
\setupmathlabeltext [...] [...]
1 LANGUAGE
2 KEY = VALUE
```

```
\setupoperatorotext [...] [...]
1 LANGUAGE
2 KEY = VALUE
```

```
\setupprefixtext [...] [...]
1 LANGUAGE
2 KEY = VALUE
```

```
\setupsuffixtext [...] [...]
1 LANGUAGE
2 KEY = VALUE
```

```
\setuptaglabeltext [...] [...]
1 LANGUAGE
2 KEY = VALUE
```

```
\setupunittext [...] [...]
1 LANGUAGE
2 KEY = VALUE
```

`\definelaye1r [...]2 [...]3 [...,...,...]`  
                                  OPT                                  OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setuplayer

`\definelayerpreset [...]1 [...,...2...,...]`

- 1 NAME
- 2 inherits: \setuplayer

`\definelayerpreset [...]1 [...]2`

- 1 NAME
- 2 NAME

`\definelayout [...]1 [...]2 [...,...3...,...]`  
                                  OPT                                  OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setuplayout

`\definelinefiller [...]1 [...]2 [...,...3...,...]`  
                                  OPT                                  OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setuplinefiller

`\definelinenote [...]1 [...]2 [...,...3...,...]`  
                                  OPT                                  OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setuplinenote

`\definelinenumbering [...]1 [...]2 [...,...3...,...]`  
                                  OPT                                  OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setuplinenumbering

`\definelines [...]1 [...]2 [...,...3...,...]`  
                                  OPT                                  OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setuplines

`\definelist [...]1 [...]2 [...,...3...,...]`  
                                  OPT                                  OPT

- 1 NAME
- 2 LIST
- 3 inherits: \setuplist

`\definelistalternative [...]1 [...]2 [...,...3...,...]`  
                                  OPT                                  OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setuplistalternative

```
\definelistextra [...]1 [...]2 [...,...]3...]
```

1 NAME

2 NAME

3 inherits: \setuplistextra

```
\definelow [...]1 [...]2 [...,...]3...]
```

1 NAME

2 NAME

3 inherits: \setuplow

```
\definelowhigh [...]1 [...]2 [...,...]3...]
```

1 NAME

2 NAME

3 inherits: \setuplowhigh

```
\definelowmidhigh [...]1 [...]2 [...,...]3...]
```

1 NAME

2 NAME

3 inherits: \setuplowmidhigh

```
\defineMPinstance [...]1 [...]2 [...,...]3...]
```

1 NAME

2 NAME

3 inherits: \setupMPinstance

```
\definemakeup [...]1 [...]2 [...,...]3...]
```

1 NAME

2 NAME

3 inherits: \setupmakeup

```
\definemarginblock [...]1 [...]2 [...,...]3...]
```

1 NAME

2 NAME

3 inherits: \setupmarginblock

```
\definemargindata [...]1 [...]2 [...,...]3...]
```

1 NAME

2 NAME

3 inherits: \setupmargindata

```
\definemarker [...]
```

\* NAME

```
\definemarking [...]1 [...]2 [...,...]3...]
```

1 NAME

2 MARK

3 inherits: \setupmarking

`\definemathaccent 1... 2...`

1 NAME

2 CHARACTER

`\definemathalignment [1...] [2...] [...,3...,...]`  
OPT OPT

1 NAME

2 NAME

3 inherits: \setupmathalignment

`\definemathcases [1...] [2...] [...,3...,...]`  
OPT OPT

1 NAME

2 NAME

3 inherits: \setupmathcases

`\definemathcommand [1...] [2...] [3...] {4...}`  
OPT OPT OPT

1 NAME

2 ord op bin rel open close punct alpha inner nothing limop nolong box

3 one two

4 COMMAND \...#1 \...#1#2

`\definemathdoubleextensible [1...] [2...] [3...] [4...]`  
OPT

1 both vfenced

2 NAME

3 NUMBER

4 NUMBER

`\definemathematics [1...] [2...] [...,3...,...]`  
OPT OPT

1 NAME

2 NAME

3 inherits: \setupmathematics

`\definemathextensible [1...] [2...] [3...]`  
OPT

1 reverse mathematics text chemistry

2 NAME

3 NUMBER

`\definemathfence [1...] [2...] [...,3...,...]`  
OPT OPT

1 NAME

2 NAME

3 inherits: \setupmathfence

`\definemathfraction [1...] [2...] [...,3...,...]`  
OPT OPT

1 NAME

2 NAME

3 inherits: \setupmathfraction



```
\definemathframed [...]1 [...]2 [...,...]3...]
```

- 1 NAME
- 2 NAME
- 3 inherits: \setupmathframed

```
\definemathmatrix [...]1 [...]2 [...,...]3...]
```

- 1 NAME
- 2 NAME
- 3 inherits: \setupmathmatrix

```
\definemathornament [...]1 [...]2 [...,...]3...]
```

- 1 NAME
- 2 NAME
- 3 inherits: \setupmathornament

```
\definemathoverextensible [...]1 [...]2 [...]3
```

- 1 top vfenced
- 2 NAME
- 3 NUMBER

```
\definemathovertextextensible [...]1 [...]2 [...]3
```

- 1 bothtext
- 2 NAME
- 3 NUMBER

```
\definemathradical [...]1 [...]2 [...,...]3...]
```

- 1 NAME
- 2 NAME
- 3 inherits: \setupmathradical

```
\definemathstackers [...]1 [...]2 [...,...]3...]
```

- 1 NAME
- 2 NAME
- 3 inherits: \setupmathstackers

```
\definemathstyle [...]1 [...]2...
```

- 1 NAME
- 2 display text script scriptscript cramped uncramped normal packed small big

```
\definemathtriplet [...]1 [...]2 [...]3
```

- 1 NAME
- 2 NAME
- 3 TEXT

```
\definemathunderextensible [1...] [2...] [3...]
                        OPT
1  bottom vfenced
2  NAME
3  NUMBER
```

```
\definemathundertextextensible [1...] [2...] [3...]
                        OPT
1  bothtext
2  NAME
3  NUMBER
```

```
\definemathunstacked [1...] [2...] [3...]
                        OPT
1  wide
2  NAME
3  NUMBER
```

```
\definemeasure [1...] [2...]
1  NAME
2  DIMENSION
```

```
\definemessageconstant {.*}
*  NAME
```

```
\definemixedcolumns [1...] [2...] [3...,...3...,...]
                        OPT      OPT
1  NAME
2  NAME
3  inherits: \setupmixedcolumns
```

```
\definemode [...,1...] [2...]
                        OPT
1  NAME
2  yes no keep
```

```
\definemultitonecolor [1...] [...,2...,...2...] [...,3...,...3...] [...,4...,...4...,...]
                        OPT
1  NAME
2  COLOR = NUMBER
3  inherits: \definecolor
4  inherits: \definespotcolor
```

```
\definenamecolor [1...] [...,2...,...2...]
1  NAME
2  inherits: \definecolor
```

```
\definenamecolor [1...] [2...]
1  NAME
2  COLOR
```

`\definenamespace` [<sup>1</sup>...] [<sup>2</sup>...]

```
1  NAME
2  name      = TEXT
   parent    = TEXT
   style     = yes no
   command   = yes no list
   setup     = yes no list
   set       = yes no list
   frame     = yes no
```

`\definennarrower` [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...]

```
1  NAME
2  NAME
3  inherits: \setupnarrower
```

`\definernote` [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...]

```
1  NAME
2  NAME
3  inherits: \setupnote
```

`\defineornament` [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...]

```
1  NAME
2  alternative = a b
   inherits: \setupcollector
3  style      = STYLE COMMAND
   color      = COLOR
   inherits: \setupframed
```

`\defineornament` [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...]

```
1  NAME
2  alternative = a b
   inherits: \setupplayer
3  inherits: \setuplayeredtext
```

`\defineoutputroutine` [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...]

```
1  NAME
2  NAME
3  inherits: \setupoutputroutine
```

`\defineoutputroutinecommand` [...,\*...]

```
*  KEY
```

`\defineoverlay` [...,<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...]

```
1  NAME
2  NAME
3  COMMAND
```

`\definepage` [<sup>1</sup>...] [<sup>2</sup>...]

```
1  NAME
2  REFERENCE
```

`\definepagebreak [...]1 [...]2,...]`

- 1 NAME
- 2 empty header footer dummy frame NUMBER +NUMBER default reset disable yes no makeup blank preference bigpreference  
left right even odd quadruple last lastpage start stop

`\definepagechecker [...]1 [...]2 [...]3,...]`  
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setuppagechecker

`\definepagegrid [...]1 [...]2 [...]3,...]`  
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setuppagegrid

`\definepagegridarea [...]1 [...]2 [...]3,...]`  
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setuppagegridarea

`\definepagegridspan [...]1 [...]2 [...]3,...]`  
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setuppagegridspan

`\definepageinjection [...]1 [...]2 [...]3,...]`  
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setuppageinjection

`\definepageinjectionalternative [...]1 [...]2 [...]3,...]`  
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setuppageinjectionalternative

`\definepageshift [...]1 [...]2 [...]3,...]`

- 1 NAME
- 2 horizontal vertical
- 3 DIMENSION

`\definepagestate [...]1 [...]2 [...]3,...]`  
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setuppagestate

```
\definepairedbox [1...] [2...] [3...OPT...OPT]
```

- 1 NAME
- 2 NAME
- 3 inherits: \setuppairedbox

```
\definepalet [1...] [2...OPT...]
```

- 1 NAME
- 2 NAME = COLOR

```
\definepalet [1...] [2...]
```

- 1 NAME
- 2 NAME

```
\definepapersize [1...] [2...OPT...]
```

- 1 NAME
- 2 width = DIMENSION  
height = DIMENSION  
top = COMMAND  
bottom = COMMAND  
left = COMMAND  
right = COMMAND  
distance = DIMENSION  
page = inherits: \setuppapersize  
paper = inherits: \setuppapersize

```
\definepapersize [1...] [2...OPT...] [3...OPT...]
```

- 1 NAME
- 2 inherits: \setuppapersize
- 3 inherits: \setuppapersize

```
\defineparagraph [1...] [2...OPT] [3...OPT...]
```

- 1 NAME
- 2 NAME
- 3 inherits: \setupparagraph

```
\defineparagraphs [1...] [2...OPT] [3...OPT...]
```

- 1 NAME
- 2 NAME
- 3 inherits: \setupparagraphs

```
\defineparallel [1...] [2...OPT...]
```

- 1 NAME
- 2 NAME

```
\defineparbuilder [...*]
```

- \* NAME

```
\defineplacement [1...] [2...OPT] [3...OPT...]
```

- 1 NAME
- 2 NAME
- 3 inherits: \setupplacement

```
\definepositioning [1...] [2...] [3...OPT...OPT]

1  NAME
2  NAME
3  inherits: \setuppositioning
```

```
\defineprefixset [1...] [2...,...]OPT [3...]

1  NAME SECTIONBLOCK:NAME
2  SECTION
3  SECTION
```

```
\defineprocesscolor [1...] [2...] [3...OPT...OPT]

1  NAME
2  COLOR
3  inherits: \definecolor
```

```
\defineprocessor [1...] [2...] [3...OPT...OPT]

1  NAME
2  NAME
3  inherits: \setupprocessor
```

```
\defineprofile [1...] [2...] [3...OPT...OPT]

1  NAME
2  NAME
3  inherits: \setupprofile
```

```
\defineprogram [1...] [2...] [3...OPT]

1  NAME
2  TEXT
3  TEXT
```

```
\definepushbutton [1...] [2...OPT...OPT]

1  NAME
2  inherits: \setupfieldcontentframed
```

```
\definepushsymbol [1...] [2...]

1  NAME
2  n r d
```

```
\definereference [1...] [2...,...]OPT

1  NAME
2  REFERENCE
```

```
\definereferenceformat [1...] [2...] [3...OPT...OPT]

1  NAME
2  NAME
3  inherits: \setupreferenceformat
```

`\defineregister [...]1 [...]2 [...,...3...,...]`  
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupregister

`\definerenderingwindow [...]1 [...]2 [...,...3...,...]`  
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setuprenderingwindow

`\defineresetset [...]1 [...,2...] [...]3`  
OPT

- 1 NAME SECTIONBLOCK:NAME
- 2 NUMBER
- 3 NUMBER

`\definescale [...]1 [...]2 [...,...3...,...]`  
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupscale

`\definescript [...]1 [...]2 [...,...3...,...]`  
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupscript

`\definesection [...]`

- \* NAME

`\definesectionblock [...]1 [...]2 [...,...3...,...]`  
OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupsectionblock

`\definesectionlevels [...]1 [...,2...]`

- 1 NAME
- 2 SECTION

`\defineselector [...]1 [...,...2...,...]`  
OPT

- 1 NAME
- 2 inherits: \setupselector

`\defineseparatorset [...]1 [...,2...] [...]3`  
OPT

- 1 NAME SECTIONBLOCK:NAME
- 2 COMMAND PROCESSOR->COMMAND
- 3 COMMAND PROCESSOR->COMMAND

```
\defineshift [...] [...] [...] [...]
                        OPT      OPT
```

- 1 NAME
- 2 NAME
- 3 inherits: \setupshift

```
\definesidebar [...] [...] [...] [...]
                        OPT      OPT
```

- 1 NAME
- 2 NAME
- 3 inherits: \setupsidebar

```
\definesort [...] [...] [...] [...]
                        OPT
```

- 1 yes no
- 2 SINGULAR
- 3 NAME
- 4 CONTENT

```
\definesorting [...] [...] [...]
                        OPT
```

- 1 SINGULAR
- 2 PLURAL
- 3 none CSNAME

```
\placelistoflogos [...] [...]
                        OPT
```

- \* inherits: \setupsorting

```
\definespotcolor [...] [...] [...] [...]
                        OPT      OPT
```

- 1 NAME
- 2 COLOR
- 3 a = NUMBER none normal multiply screen overlay softlight hardlight colordodge colorburn darken lighten difference  
exclusion hue saturation color luminosity  
t = NUMBER  
e = TEXT  
p = NUMBER

```
\definestartstop [...] [...] [...] [...]
                        OPT      OPT
```

- 1 NAME
- 2 NAME
- 3 inherits: \setupstartstop

```
\definestyle [...] [...] [...] [...]
                        OPT      OPT
```

- 1 NAME
- 2 NAME
- 3 inherits: \setupstyle

```
\definestyleinstance [...] [...] [...] [...]
                        OPT      OPT
```

- 1 NAME
- 2 rm ss tt mm hw cg
- 3 tf bf it sl bi bs sc
- 4 COMMAND



`\definesubfield [...]1 [...]2 [...]3,...]`

- 1 NAME
- 2 NAME
- 3 NAME

`\definesubformula [...]1 [...]2 [...]3,...]`  
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupsubformula

`\definesymbol [...]1 [...]2 [...]3`  
OPT

- 1 NAME
- 2 NAME
- 3 COMMAND

`\definesynonym [...]1 [...]2 [...]3 {...}4 {...}5`  
OPT

- 1 yes no
- 2 SINGULAR
- 3 NAME
- 4 TEXT
- 5 CONTENT

`\definesynonyms [...]1 [...]2 [...]3 [...]4`  
OPT OPT

- 1 SINGULAR
- 2 PLURAL
- 3 CSNAME
- 4 CSNAME

`\placelistofabbreviations [...]*,...]`  
OPT

- \* inherits: \setupsynonyms

`\definesystemattribute [...]1 [...]2,...]`  
OPT

- 1 NAME
- 2 local global public private

`\definesystemconstant {...}*`

- \* NAME

`\definesystemvariable {...}*`

- \* NAME

`\defineTABLEsetup [...]1 [...]2,...]`

- 1 NAME
- 2 inherits: \setupTABLE

`\definetabletemplate` [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...] [<sup>4</sup>...]  
OPT OPT

- 1 NAME
- 2 TEMPLATE
- 3 NAME
- 4 NAME

`\definetabulate` [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>.../]  
OPT OPT

- 1 NAME
- 2 NAME
- 3 TEMPLATE

`\definetabulation` [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...<sup>3</sup>...]  
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setuptabulation

`\definetext` [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...] [<sup>4</sup>...] [<sup>5</sup>...] [<sup>6</sup>...] [<sup>7</sup>...]  
OPT OPT OPT OPT

- 1 NAME
- 2 top header text footer bottom
- 3 text margin edge
- 4 date pagenumber MARK TEXT COMMAND
- 5 date pagenumber MARK TEXT COMMAND
- 6 date pagenumber MARK TEXT COMMAND
- 7 date pagenumber MARK TEXT COMMAND

`\definetextbackground` [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...<sup>3</sup>...]  
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setuptextbackground

`\definetextflow` [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...<sup>3</sup>...]  
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setuptextflow

`\definetooltip` [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...<sup>3</sup>...]  
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setuptooltip

`\definetransparency` [<sup>1</sup>...] [<sup>2</sup>...]

- 1 NAME
- 2 NUMBER

`\definetransparency [1...] [2...]`

1 NAME  
2 a = NUMBER none normal multiply screen overlay softlight hardlight colordodge colorburn darken lighten difference  
exclusion hue saturation color luminosity  
t = NUMBER

`\definetransparency [1...] [2...]`

1 NAME  
2 NAME

`\definewopasslist {...}`

\* NAME

`\definetypetype [1...] [2...] [3...]`  
OPT OPT

1 NAME  
2 NAME  
3 inherits: \setuptype

`\definetypesface [1...] [2...] [3...] [4...] [5...] [6...]`  
OPT OPT

1 NAME  
2 rm ss tt mm hw cg  
3 serif sans mono math handwriting calligraphy  
4 NAME  
5 default dtp  
6 rscale = auto NUMBER  
features = NAME  
fallbacks = NAME  
goodies = NAME  
designsize = auto default  
direction = both

`\definetypescriptprefix [1...] [2...]`

1 NAME  
2 TEXT

`\definetypescriptsynonym [1...] [2...]`

1 NAME  
2 TEXT

`\definetypesetting [1...] [2...] [3...]`  
OPT OPT

1 NAME  
2 TEXT  
3 inherits: \setupexternalfigure

`\definetyping [1...] [2...] [3...]`  
OPT OPT

1 NAME  
2 NAME  
3 inherits: \setuptyping

`\defineunit [...]1 [...]2 [...]3...`  
                                  OPT                                  OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupunit

`\defineviewerlayer [...]1 [...]2 [...]3...`  
                                  OPT                                  OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupviewerlayer

`\definespace [...]1 [...]2 [...]3`  
                                  OPT

- 1 NAME
- 2 NAME
- 3 DIMENSION

`\definevspacing [...]1 [...]2`

- 1 NAME
- 2 inherits: \vspacing

`\definevspacingamount [...]1 [...]2 [...]3`  
                                  OPT                                  OPT

- 1 NAME
- 2 DIMENSION
- 3 DIMENSION

`\definetable [...]1 [...]2 [...]3...`  
                                  OPT                                  OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupxtable

`\delimited [...]1 [...]2 {...}3`  
                                  OPT

- 1 NAME
- 2 LANGUAGE
- 3 CONTENT

`\delimitedtext [...]1 [...]2 {...}3`  
                                  OPT

- 1 NAME
- 2 LANGUAGE
- 3 CONTENT

`\DELIMITEDTEXT [...]1 {...}2`  
                                  OPT

- 1 LANGUAGE
- 2 CONTENT

instances: quotation quote blockquote speech aside

`\depthofstring {...}`

- \* TEXT

<p><code>\depthonlybox {...}</code></p> <p>*    CONTENT</p>
<p><code>\depthspanningtext {...} {...} {...}</code></p> <p>1    TEXT</p> <p>2    DIMENSION</p> <p>3    FONT</p>
<p><code>\DESCRIPTION [...<sup>1</sup>,...] {..<sup>2</sup>.} <sup>3</sup>. \par</code>  <small>          OPT                  OPT</small></p> <p>1    REFERENCE</p> <p>2    TEXT</p> <p>3    CONTENT</p>
<p><code>\determineheadnumber [...]</code></p> <p>*    SECTION</p>
<p><code>\determinelistcharacteristics [...<sup>1</sup>,...] [...<sup>2</sup>...,...]</code>  <small>  OPT</small></p> <p>1    LIST</p> <p>2    inherits: \setuplist</p>
<p><code>\determinenoflines {...}</code></p> <p>*    CONTENT</p>
<p><code>\determineregistercharacteristics [<sup>1</sup>.] [...<sup>2</sup>...,...]</code>  <small>  OPT</small></p> <p>1    NAME</p> <p>2    language    = default DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-sc<sub>n</sub> LANGUAGE</p> <p>     method     = default before after first last ch mm zn pm mc zc pc uc</p> <p>     numberorder = <u>numbers</u></p> <p>     compress    = yes <u>no</u> all</p> <p>     criterium   = local text current previous <u>all</u> SECTION</p>
<p><code>\devanagarinumerals {...}</code></p> <p>*    NUMBER</p>
<p><code>\digits {...}</code></p> <p>*    NUMBER</p>
<p><code>\digits ...</code></p> <p>*    NUMBER</p>
<p><code>\dimensiontocount {..<sup>1</sup>.} \<sup>2</sup>..</code></p> <p>1    DIMENSION</p> <p>2    CSNAME</p>
<p><code>\directboxfromcache {..<sup>1</sup>.} {..<sup>2</sup>.}</code></p> <p>1    NAME</p> <p>2    NUMBER TEXT</p>

<code>\directcolor [...]</code> *    COLOR
<code>\directcolored [...,\stackrel{*}{=},...]</code> *    inherits: \definecolor
<code>\directcolored [...]</code> *    COLOR
<code>\directconvertedcounter {...} {...}</code> 1    NAME 2    first previous next last number
<code>\directcopyboxfromcache {...} {...}</code> 1    NAME 2    NUMBER TEXT
<code>\directdummyparameter {...}</code> *    KEY
<code>\directgetboxllx ...</code> *    CSNAME NUMBER
<code>\directgetboxlly ...</code> *    CSNAME NUMBER
<code>\directhighlight {...} {...}</code> 1    NAME 2    TEXT
<code>\directlocalframed [...] {...}</code> 1    NAME 2    CONTENT
<code>\directluacode {...}</code> *    COMMAND
<code>\directselect {...} {...} {...} {...} {...} {...}</code> <div> <div></div> <div>OPT</div> <div>OPT</div> <div>OPT</div> <div>OPT</div> <div>OPT</div> </div> 1    NAME 2    CONTENT 3    CONTENT 4    CONTENT 5    CONTENT 6    CONTENT
<code>\directsetbar {...}</code> *    NAME

$\backslash\text{directsetup}$ {...} *    NAME
$\backslash\text{directsymbol}$ {... <sup>1</sup> } {... <sup>2</sup> } 1    NAME 2    NAME
$\backslash\text{directvspacing}$ {...,*...} *    inherits: \vspacing
$\backslash\text{dis}$ {...} *    CONTENT
$\backslash\text{disabledirectives}$ [...,*...]
*    NAME
$\backslash\text{disableexperiments}$ [...,*...]
*    NAME
$\backslash\text{disablemode}$ [...,*...]
*    NAME
$\backslash\text{disableoutputstream}$
$\backslash\text{disableparpositions}$
$\backslash\text{disableregime}$
$\backslash\text{disabletrackers}$ [...,*...]
*    NAME
$\backslash\text{displaymath}$ {...} *    CONTENT
$\backslash\text{displaymathematics}$ {...} *    CONTENT
$\backslash\text{displaymessage}$ {...} *    TEXT
$\backslash\text{distributedhsize}$ {... <sup>1</sup> } {... <sup>2</sup> } {... <sup>3</sup> } 1    DIMENSION 2    DIMENSION 3    NUMBER

`\dividedsize {...} {...} {...}`

- 1 DIMENSION
- 2 DIMENSION
- 3 NUMBER

`\doadaptleftskip {...}`

- \* yes no standard DIMENSION

`\doadaptrightskip {...}`

- \* yes no standard DIMENSION

`\doaddfeature {...}`

- \* NAME

`\doassign [...]1 [...]2...`

- 1 TEXT
- 2 KEY = VALUE

`\doassignempty [...]1 [...]2...`

- 1 TEXT
- 2 KEY = VALUE

`\doboundtext {...}1 {...}2 {...}3`

- 1 TEXT
- 2 DIMENSION
- 3 COMMAND

`\docheckassignment {...}`

- \* TEXT

`\docheckedpagestate {...}1 {...}2 {...}3 {...}4 {...}5 {...}6 {...}7`

- 1 REFERENCE
- 2 COMMAND
- 3 COMMAND
- 4 COMMAND
- 5 COMMAND
- 6 COMMAND
- 7 COMMAND

`\docheckedpair {...}*...`

- \* TEXT

`\documentvariable {...}`

- \* KEY



`\dodoubleargument \1... [2...] [3]`

- 1 CSNAME
- 2 TEXT
- 3 TEXT

`\dodoubleargumentwithset \1... [2...,3...] [3]`

- 1 CSNAME
- 2 TEXT
- 3 TEXT

`\dodoubleempty \1... [2...] [3]`  
OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT

`\dodoubleemptywithset \1... [2...,3...] [3]`  
OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT

`\dodoublegroupempty \1... {2...} {3...}`  
OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT

`\doeassign [1...] [2...]`

- 1 TEXT
- 2 KEY = VALUE

`\doexpandedrecurse {1...} {2...}`

- 1 NUMBER
- 2 COMMAND

`\dofastloopcs {1...} \2...`

- 1 NUMBER
- 2 CSNAME

`\dogetattribute {.*}`

- \* NAME

`\dogetattributeid {.*}`

- \* NAME

`\dogetcommacommandelement 1... \from 2... \to \3...`

- 1 NUMBER
- 2 TEXT
- 3 CSNAME

`\dogobbledoubleempty [...]1 [...]2`  
OPT OPT

1 TEXT

2 TEXT

`\dogobblesingleempty [...]*`  
OPT

\* TEXT

`\doif {...}1 {...}2 {...}3`

1 CONTENT

2 CONTENT

3 TRUE

`\doifallcommon {...,1...} {...,2...} {...}3`

1 TEXT

2 TEXT

3 TRUE

`\doifallcommonelse {...,1...} {...,2...} {...}3 {...}4`

1 TEXT

2 TEXT

3 TRUE

4 FALSE

`\doifalldefinedelse {...,1...} {...}2 {...}3`

1 NAME

2 TRUE

3 FALSE

`\doifallmodes {...,1...} {...}2 {...}3`

1 NAME

2 TRUE

3 FALSE

`\doifallmodeselse {...,1...} {...}2 {...}3`

1 NAME

2 TRUE

3 FALSE

`\doifassignmentelse {...}1 {...}2 {...}3`

1 TEXT

2 TRUE

3 FALSE

`\doifblackelse {...}1 {...}2 {...}3`

1 COLOR

2 TRUE

3 FALSE

`\doifbothsides {...} {...} {...}`

- 1    COMMAND
- 2    COMMAND
- 3    COMMAND

`\doifbothsidesoverruled {...} {...} {...}`

- 1    COMMAND
- 2    COMMAND
- 3    COMMAND

`\doifboxelse {...} {...} {...} {...}`

- 1    NAME
- 2    NAME
- 3    TRUE
- 4    FALSE

`\doifbufferelse {...} {...} {...}`

- 1    BUFFER
- 2    TRUE
- 3    FALSE

`\doifcolor {...} {...}`

- 1    COLOR
- 2    TRUE

`\doifcolorelse {...} {...} {...}`

- 1    COLOR
- 2    TRUE
- 3    FALSE

`\doifcommandhandler \... {...} {...}`

- 1    CSNAME
- 2    NAME
- 3    TRUE

`\doifcommandhandlerelse \... {...} {...} {...}`

- 1    CSNAME
- 2    NAME
- 3    TRUE
- 4    FALSE

`\doifcommon {...,1...} {...,2...} {...}`

- 1    TEXT
- 2    TEXT
- 3    TRUE

`\doifcommonelse {...,1...} {...,2...} {...3} {...4}`

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

`\doifcontent {...1} {...2} {...3} \...4 {...5}`

- 1 COMMAND
- 2 COMMAND
- 3 COMMAND
- 4 CSNAME
- 5 CONTENT

`\doifconversiondefinedelse {...1} {...2} {...3}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifconversionnumberelse {...1} {...2} {...3} {...4}`

- 1 NAME
- 2 NUMBER
- 3 TRUE
- 4 FALSE

`\doifcounter {...1} {...2}`

- 1 NAME
- 2 TRUE

`\doifcounterelse {...1} {...2} {...3}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifcurrentfonthasfeatureelse {...1} {...2} {...3}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifdefined {...1} {...2}`

- 1 NAME
- 2 TRUE

`\doifdefinedcounter {...1} {...2}`

- 1 NAME
- 2 TRUE

`\doifdefinedcounterelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifdefinedelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifdimensionelse {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifdimenstringelse {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifdocumentargument {...} {...}`

- 1 NAME
- 2 TRUE

`\doifdocumentargumentelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifdocumentfilename {...} {...}`

- 1 NUMBER
- 2 TRUE

`\doifdocumentfilenameelse {...} {...} {...}`

- 1 NUMBER
- 2 TRUE
- 3 FALSE

`\doifdrawingblackelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifelse {...} {...} {...} {...}`

- 1 CONTENT
- 2 CONTENT
- 3 TRUE
- 4 FALSE

`\doifelseallcommon {...,1...} {...,2...} {...3} {...4}`

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

`\doifelsealldefined {...,1...} {...2} {...3}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelseallmodes {...,1...} {...2} {...3}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelseassignment {...1} {...2} {...3}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifelseblack {...1} {...2} {...3}`

- 1 COLOR
- 2 TRUE
- 3 FALSE

`\doifelsebox {...1} {...2} {...3} {...4}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifelseboxincache {...1} {...2} {...3} {...4}`

- 1 NAME
- 2 NUMBER TEXT
- 3 TRUE
- 4 FALSE

`\doifelsebuffer {...1} {...2} {...3}`

- 1 BUFFER
- 2 TRUE
- 3 FALSE

`\doifelsecolor {...1} {...2} {...3}`

- 1 COLOR
- 2 TRUE
- 3 FALSE

`\doifelsecommandhandler \...1 {...}2 {...}3 {...}4`

- 1 CSNAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifelsecommon {...,1...} {...,2...} {...}3 {...}4`

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

`\doifelseconversiondefined {...}1 {...}2 {...}3`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelseconversionnumber {...}1 {...}2 {...}3 {...}4`

- 1 NAME
- 2 NUMBER
- 3 TRUE
- 4 FALSE

`\doifelsecounter {...}1 {...}2 {...}3`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsecurrentfonthasfeature {...}1 {...}2 {...}3`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsecurrentsortingtongused {...}1 {...}2`

- 1 TRUE
- 2 FALSE

`\doifelsecurrentsynonymshown {...}1 {...}2`

- 1 TRUE
- 2 FALSE

`\doifelsecurrentsynonymused {...}1 {...}2`

- 1 TRUE
- 2 FALSE

`\doifelsedefined {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsedefinedcounter {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsedimension {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifelsedimenstring {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifelsedocumentargument {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsedocumentfilename {...} {...} {...}`

- 1 NUMBER
- 2 TRUE
- 3 FALSE

`\doifelsedrawingblack {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifelseempty {...} {...} {...}`

- 1 CONTENT
- 2 TRUE
- 3 FALSE

`\doifelseemptyvalue {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE



`\doifelseemptyvariable {...} {...} {...} {...}`

- 1 NAME
- 2 KEY
- 3 TRUE
- 4 FALSE

`\doifelseenv {...} {...} {...}`

- 1 KEY
- 2 TRUE
- 3 FALSE

`\doifelsefastoptionalcheck {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifelsefastoptionalcheckcs \^1 \^2`

- 1 CSNAME
- 2 CSNAME

`\doifelsefieldbody {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsefieldcategory {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsefigure {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifelsefile {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifelsefiledefined {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsefileexists {...} {...} {...}`

1 FILE  
2 TRUE  
3 FALSE

`\doifelsefirstchar {...} {...} {...} {...}`

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

`\doifelseflagged {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifelsefontchar {...} {...} {...} {...}`

1 FONT  
2 NUMBER  
3 TRUE  
4 FALSE

`\doifelsefontpresent {...} {...} {...}`

1 FONT  
2 TRUE  
3 FALSE

`\doifelsefontsynonym {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifelsehasspace {...} {...} {...}`

1 TEXT  
2 TRUE  
3 FALSE

`\doifelsehelp {...} {...}`

1 TRUE  
2 FALSE

`\doifelseinciname {...} {...} {...} {...}`

1 TEXT  
2 CSNAME  
3 TRUE  
4 FALSE

`\doifelseinelement {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelseinputfile {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifelseinsertion {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelseinset {...} {...,2...} {...} {...4}`

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

`\doifelseinstring {...} {...} {...} {...4}`

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

`\doifelseinsymbolset {...} {...} {...} {...}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifelseintoks {...} {...} {...} {...4}`

- 1 COMMAND
- 2 COMMAND
- 3 TRUE
- 4 FALSE

`\doifelseintwopassdata {...} {...} {...} {...4}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifelseitalic {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifelselanguage {...} {...} {...}`

- 1 LANGUAGE
- 2 TRUE
- 3 FALSE

`\doifelselayerdata {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelselayoutdefined {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelselayoutsomeline {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelselayouttextline {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelseleapyear {...} {...} {...}`

- 1 NUMBER
- 2 TRUE
- 3 FALSE

`\doifelselist {...} {...} {...}`

- 1 LIST
- 2 TRUE
- 3 FALSE

`\doifelselocation {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifelselocfile {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifelseMPgraphic {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsemainfloatbody {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifelsemarking {...} {...} {...}`

- 1 MARK
- 2 TRUE
- 3 FALSE

`\doifelsemeaning \1... \2... {...} {...}`

- 1 CSNAME
- 2 CSNAME
- 3 TRUE
- 4 FALSE

`\doifelsemessage {...} {...} {...} {...}`

- 1 NAME
- 2 NAME NUMBER
- 3 TRUE
- 4 FALSE

`\doifelsemode {...,1...} {...2} {...3}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsenextbgroup {...1} {...2}`

- 1 TRUE
- 2 FALSE

`\doifelsenextbgroupcs \1... \2...`

- 1 CSNAME
- 2 CSNAME

`\doifelsenextchar {...1} {...2} {...3}`

- 1 CHARACTER
- 2 TRUE
- 3 FALSE

`\doifelsenextoptional {...1} {...2}`

- 1 TRUE
- 2 FALSE

`\doifelsenextoptionalcs \1... \2...`

1 CSNAME

2 CSNAME

`\doifelsenextparenthesis {\1...} {\2...}`

1 TRUE

2 FALSE

`\doifelsenonzeropositive {\1...} {\2...} {\3...}`

1 NUMBER

2 TRUE

3 FALSE

`\doifelsenoteonsamepage {\1...} {\2...} {\3...}`

1 NAME

2 TRUE

3 FALSE

`\doifelsenothing {\1...} {\2...} {\3...}`

1 TEXT

2 TRUE

3 FALSE

`\doifelsenumber {\1...} {\2...} {\3...}`

1 TEXT

2 TRUE

3 FALSE

`\doifelseobjectfound {\1...} {\2...} {\3...} {\4...}`

1 NAME

2 NAME

3 TRUE

4 FALSE

`\doifelseobjectreferencefound {\1...} {\2...} {\3...} {\4...}`

1 NAME

2 NAME

3 TRUE

4 FALSE

`\doifelseoddpage {\1...} {\2...}`

1 COMMAND

2 COMMAND

`\doifelseoddpagefloat {\1...} {\2...}`

1 TRUE

2 FALSE

\doifelseoldercontext {...} {...} {...}

- 1 NUMBER
- 2 TRUE
- 3 FALSE

\doifelseolderversion {...} {...} {...} {...}

- 1 NUMBER
- 2 NUMBER
- 3 TRUE
- 4 FALSE

\doifelseoverlapping {...} {...} {...} {...}

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

\doifelseoverlay {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelseparallel {...} {...,<sup>2</sup>...} {...} {...}

- 1 NAME
- 2 NAME all
- 3 TRUE
- 4 FALSE

\doifelseparentfile {...} {...} {...}

- 1 FILE
- 2 TRUE
- 3 FALSE

\doifelsepath {...} {...} {...}

- 1 PATH
- 2 TRUE
- 3 FALSE

\doifelsepathexists {...} {...} {...}

- 1 PATH
- 2 TRUE
- 3 FALSE

\doifelsepatterns {...} {...} {...}

- 1 LANGUAGE
- 2 TRUE
- 3 FALSE

`\doifelseposition {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsepositionaction {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsepositiononpage {...} {...} {...} {...}`

- 1 NAME
- 2 NUMBER
- 3 TRUE
- 4 FALSE

`\doifelsepositionsonsamepage {...,1...} {...2} {...3}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsepositionsonthispage {...,1...} {...2} {...3}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsepositionsused {...1} {...2}`

- 1 TRUE
- 2 FALSE

`\doifelserreferencefound {...} {...} {...}`

- 1 REFERENCE
- 2 TRUE
- 3 FALSE

`\doifelserightpagefloat {...1} {...2}`

- 1 TRUE
- 2 FALSE

`\doifelserighttoleftinbox ...1 {...2} {...3}`

- 1 CSNAME NUMBER
- 2 TRUE
- 3 FALSE



`\doifelsesamelinereference {...} {...} {...}`

- 1   REFERENCE
- 2   TRUE
- 3   FALSE

`\doifelsesamestring {...} {...} {...} {...}`

- 1   TEXT
- 2   TEXT
- 3   TRUE
- 4   FALSE

`\doifelsesetups {...} {...} {...}`

- 1   NAME
- 2   TRUE
- 3   FALSE

`\doifelsesomebackground {...} {...} {...}`

- 1   NAME
- 2   TRUE
- 3   FALSE

`\doifelsesomespace {...} {...} {...}`

- 1   TEXT
- 2   TRUE
- 3   FALSE

`\doifelsesomething {...} {...} {...}`

- 1   TEXT
- 2   TRUE
- 3   FALSE

`\doifelsesometoks \... {...} {...}`

- 1   CSNAME
- 2   TRUE
- 3   FALSE

`\doifelsestringinstr {...} {...} {...} {...}`

- 1   TEXT
- 2   TEXT
- 3   TRUE
- 4   FALSE

`\doifelsestructurelisthasnumber {...} {...}`

- 1   TRUE
- 2   FALSE

`\doifelsestructurelisthaspage {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifelsesymboldefined {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsesymbolset {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsetext {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifelsetextflow {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsetextflowcollector {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsetypingfile {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifelseundefined {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelseurldefined {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsevalue {...} {...} {...} {...}`

- 1 NAME
- 2 TEXT
- 3 TRUE
- 4 FALSE

`\doifelsevaluenothing {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsevariable {...} {...} {...} {...}`

- 1 NAME
- 2 KEY
- 3 TRUE
- 4 FALSE

`\doifempty {...} {...}`

- 1 CONTENT
- 2 TRUE

`\doifemptyelse {...} {...} {...}`

- 1 CONTENT
- 2 TRUE
- 3 FALSE

`\doifemptytoks \^1... {...}`

- 1 CSNAME
- 2 TRUE

`\doifemptyvalue {...} {...}`

- 1 NAME
- 2 TRUE

`\doifemptyvalueelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifemptyvariable {...} {...} {...}`

- 1 NAME
- 2 KEY
- 3 TRUE

`\doifemptyvariableelse {...} {...} {...} {...}`

1 NAME  
2 KEY  
3 TRUE  
4 FALSE

`\doifenv {...} {...}`

1 KEY  
2 TRUE

`\doifenvelse {...} {...} {...}`

1 KEY  
2 TRUE  
3 FALSE

`\doiffastoptionalcheckcselse \1 \2`

1 CSNAME  
2 CSNAME

`\doiffastoptionalcheckelse {...} {...}`

1 TRUE  
2 FALSE

`\doiffielddbbodyelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doiffielddcategoryelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doiffigureelse {...} {...} {...}`

1 FILE  
2 TRUE  
3 FALSE

`\doiffile {...} {...}`

1 FILE  
2 TRUE

`\doiffiledefinedelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doiffileelse {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doiffileexistselse {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doiffirstcharelse {...} {...} {...} {...}`

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

`\doifflaggedelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doiffontcharelse {...} {...} {...} {...}`

- 1 FONT
- 2 NUMBER
- 3 TRUE
- 4 FALSE

`\doiffontpresentelse {...} {...} {...}`

- 1 FONT
- 2 TRUE
- 3 FALSE

`\doiffontsynonymelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifhasspaceelse {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifhelpelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifincsnameelse {1..} {2..} {3..} {4..}`

- 1 TEXT
- 2 CSNAME
- 3 TRUE
- 4 FALSE

`\doifinelementelse {1..} {2..} {3..}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifinputfileelse {1..} {2..} {3..}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifinsertionelse {1..} {2..} {3..}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifinset {1..} {2..2..3..} {3..}`

- 1 TEXT
- 2 TEXT
- 3 TRUE

`\doifinsetelse {1..} {2..2..3..} {3..} {4..}`

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

`\doifinstring {1..} {2..} {3..}`

- 1 TEXT
- 2 TEXT
- 3 TRUE

`\doifinstringelse {1..} {2..} {3..} {4..}`

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

`\doifinsymbolset {...} {...} {...} {...}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifinsymbolsetelse {...} {...} {...} {...}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifintokselse {...} {...} {...} {...}`

- 1 COMMAND
- 2 COMMAND
- 3 TRUE
- 4 FALSE

`\doifintwopassdataelse {...} {...} {...} {...}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifitalicelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\doiflanguageelse {...} {...} {...}`

- 1 LANGUAGE
- 2 TRUE
- 3 FALSE

`\doiflayerdataelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doiflayoutdefinedelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doiflayoutsomelineelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

```
\doiflayouttextlineelse {.1.} {.2.} {.3.}
```

- 1 NAME
- 2 TRUE
- 3 FALSE

```
\doifleapyearelse {.1.} {.2.} {.3.}
```

- 1 NUMBER
- 2 TRUE
- 3 FALSE

```
\doiflistelse {.1.} {.2.} {.3.}
```

- 1 LIST
- 2 TRUE
- 3 FALSE

```
\doiflocationelse {.1.} {.2.}
```

- 1 TRUE
- 2 FALSE

```
\doiflocfileelse {.1.} {.2.} {.3.}
```

- 1 FILE
- 2 TRUE
- 3 FALSE

```
\doifMPgraphicelse {.1.} {.2.} {.3.}
```

- 1 NAME
- 2 TRUE
- 3 FALSE

```
\doifmainfloatbodyelse {.1.} {.2.}
```

- 1 TRUE
- 2 FALSE

```
\doifmarkingelse {.1.} {.2.} {.3.}
```

- 1 MARK
- 2 TRUE
- 3 FALSE

```
\doifmeaningelse \.1. \.2. {.3.} {.4.}
```

- 1 CSNAME
- 2 CSNAME
- 3 TRUE
- 4 FALSE



`\doifmessageelse {...} {...} {...} {...}`

- 1 NAME
- 2 NAME NUMBER
- 3 TRUE
- 4 FALSE

`\doifmode {...1,...} {...2}`

- 1 NAME
- 2 TRUE

`\doifmodeelse {...,1,...} {...2} {...3}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifnextbgroupcselse \... \...1 \...2..`

- 1 CSNAME
- 2 CSNAME

`\doifnextbgroupelse {...1} {...2}`

- 1 TRUE
- 2 FALSE

`\doifnextcharelse {...1} {...2} {...3}`

- 1 CHARACTER
- 2 TRUE
- 3 FALSE

`\doifnextoptionalcselse \... \...1 \...2..`

- 1 CSNAME
- 2 CSNAME

`\doifnextoptionalelse {...1} {...2}`

- 1 TRUE
- 2 FALSE

`\doifnextparenthesiselse {...1} {...2}`

- 1 TRUE
- 2 FALSE

`\doifnonzeropositiveelse {...1} {...2} {...3}`

- 1 NUMBER
- 2 TRUE
- 3 FALSE

`\doifnot {...} {...} {...}`

- 1 CONTENT
- 2 CONTENT
- 3 TRUE

`\doifnotallcommon {...,1...} {...,2...} {...3}`

- 1 TEXT
- 2 TEXT
- 3 TRUE

`\doifnotallmodes {...,1...} {...2} {...3}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifnotcommandhandler \...1 {...} {...3}`

- 1 CSNAME
- 2 NAME
- 3 TRUE

`\doifnotcommon {...,1...} {...,2...} {...3}`

- 1 TEXT
- 2 TEXT
- 3 TRUE

`\doifnotcounter {...} {...2}`

- 1 NAME
- 2 TRUE

`\doifnotdocumentargument {...1} {...2}`

- 1 NAME
- 2 TRUE

`\doifnotdocumentfilename {...1} {...2}`

- 1 NUMBER
- 2 TRUE

`\doifnotempty {...} {...2}`

- 1 CONTENT
- 2 TRUE

`\doifnotemptyvalue {...} {...2}`

- 1 NAME
- 2 TRUE

`\doifnotemptyvariable {...} {...} {...}`

- 1 NAME
- 2 KEY
- 3 TRUE

`\doifnotenv {...} {...}`

- 1 KEY
- 2 TRUE

`\doifnoteonsamepageelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifnotescollected {...} {...}`

- 1 NAME
- 2 TRUE

`\doifnotfile {...} {...}`

- 1 FILE
- 2 TRUE

`\doifnotflagged {...} {...}`

- 1 NAME
- 2 TRUE

`\doifnothing {...} {...}`

- 1 TEXT
- 2 TRUE

`\doifnothingelse {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifnotinset {...} {...,2...} {...3}`

- 1 TEXT
- 2 TEXT
- 3 TRUE

`\doifnotinsidesplitfloat {...}`

- \* TRUE

`\doifnotinstring {...} {...} {...}`

- 1 TEXT
- 2 TEXT
- 3 TRUE

`\doifnotmode {...1,...} {...2}`

- 1 NAME
- 2 TRUE

`\doifnotnumber {...1.} {...2.}`

- 1 TEXT
- 2 TRUE

`\doifnotsamestring {...1.} {...2.} {...3.}`

- 1 TEXT
- 2 TEXT
- 3 TRUE

`\doifnotsetups {...1.} {...2.}`

- 1 NAME
- 2 TRUE

`\doifnotvalue {...1.} {...2.} {...3.}`

- 1 NAME
- 2 TEXT
- 3 TRUE

`\doifnotvariable {...1.} {...2.} {...3.}`

- 1 NAME
- 2 KEY
- 3 TRUE

`\doifnumber {...1.} {...2.}`

- 1 TEXT
- 2 TRUE

`\doifnumberelse {...1.} {...2.} {...3.}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifobjectfoundelse {...1.} {...2.} {...3.} {...4.}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifobjectreferencefoundelse {...1.} {...2.} {...3.} {...4.}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

\doifoddpagelse {<sup>1</sup>.} {<sup>2</sup>.}

- 1    COMMAND
- 2    COMMAND

\doifoddpagefloatelse {<sup>1</sup>.} {<sup>2</sup>.}

- 1    TRUE
- 2    FALSE

\doifoldercontextelse {<sup>1</sup>.} {<sup>2</sup>.} {<sup>3</sup>.}

- 1    NUMBER
- 2    TRUE
- 3    FALSE

\doifolderversionelse {<sup>1</sup>.} {<sup>2</sup>.} {<sup>3</sup>.} {<sup>4</sup>.}

- 1    NUMBER
- 2    NUMBER
- 3    TRUE
- 4    FALSE

\doifoverlappingelse {<sup>1</sup>.} {<sup>2</sup>.} {<sup>3</sup>.} {<sup>4</sup>.}

- 1    NAME
- 2    NAME
- 3    TRUE
- 4    FALSE

\doifoverlayelse {<sup>1</sup>.} {<sup>2</sup>.} {<sup>3</sup>.}

- 1    NAME
- 2    TRUE
- 3    FALSE

\doifparallelelse {<sup>1</sup>.} {<sup>2</sup>...,<sup>3</sup>...} {<sup>3</sup>.} {<sup>4</sup>.}

- 1    NAME
- 2    NAME all
- 3    TRUE
- 4    FALSE

\doifparentfileelse {<sup>1</sup>.} {<sup>2</sup>.} {<sup>3</sup>.}

- 1    FILE
- 2    TRUE
- 3    FALSE

\doifpathelse {<sup>1</sup>.} {<sup>2</sup>.} {<sup>3</sup>.}

- 1    PATH
- 2    TRUE
- 3    FALSE

`\doifpathexistselse {...} {...} {...}`

- 1    PATH
- 2    TRUE
- 3    FALSE

`\doifpatternselect {...} {...} {...}`

- 1    LANGUAGE
- 2    TRUE
- 3    FALSE

`\doifposition {...} {...} {...}`

- 1    NAME
- 2    TRUE
- 3    FALSE

`\doifpositionaction {...} {...} {...}`

- 1    NAME
- 2    TRUE
- 3    FALSE

`\doifpositionactionelse {...} {...} {...}`

- 1    NAME
- 2    TRUE
- 3    FALSE

`\doifpositionelse {...} {...} {...}`

- 1    NAME
- 2    TRUE
- 3    FALSE

`\doifpositiononpageelse {...} {...} {...} {...}`

- 1    NAME
- 2    NUMBER
- 3    TRUE
- 4    FALSE

`\doifpositionsonsamepageelse {...,1...} {...} {...}`

- 1    NAME
- 2    TRUE
- 3    FALSE

`\doifpositionsonthispageelse {...,1...} {...} {...}`

- 1    NAME
- 2    TRUE
- 3    FALSE

`\doifpositionsusedelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifreferencefoundelse {...} {...} {...}`

- 1 REFERENCE
- 2 TRUE
- 3 FALSE

`\doifrightpagefloatelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifrighttoleftinboxedelse ... {...} {...}`

- 1 CSNAME NUMBER
- 2 TRUE
- 3 FALSE

`\doifsamelinereferenceelse {...} {...} {...}`

- 1 REFERENCE
- 2 TRUE
- 3 FALSE

`\doifsamestring {...} {...} {...}`

- 1 TEXT
- 2 TEXT
- 3 TRUE

`\doifsamestringelse {...} {...} {...} {...}`

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

`\doifsetups {...} {...}`

- 1 NAME
- 2 TRUE

`\doifsetupself {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifsomebackground {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifsomebackgroundelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifsomespaceelse {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifsomething {...} {...}`

- 1 TEXT
- 2 TRUE

`\doifsomethingelse {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifsometoks \... {...}`

- 1 CSNAME
- 2 TRUE

`\doifsometokselse \... {...} {...}`

- 1 CSNAME
- 2 TRUE
- 3 FALSE

`\doifstringinstringelse {...} {...} {...} {...}`

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

`\doifstructurelisthasnumberelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifstructurelisthaspageelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifsymboldefinedelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE



```
\doifsymbolsetelse {...} {...} {...}
```

- 1 NAME
- 2 TRUE
- 3 FALSE

```
\doiftext {...} {...} {...}
```

- 1 TEXT
- 2 TRUE
- 3 FALSE

```
\doiftextelse {...} {...} {...}
```

- 1 TEXT
- 2 TRUE
- 3 FALSE

```
\doiftextflowcollectorelse {...} {...} {...}
```

- 1 NAME
- 2 TRUE
- 3 FALSE

```
\doiftextflowelse {...} {...} {...}
```

- 1 NAME
- 2 TRUE
- 3 FALSE

```
\doiftypingfileelse {...} {...} {...}
```

- 1 FILE
- 2 TRUE
- 3 FALSE

```
\doifundefined {...} {...}
```

- 1 NAME
- 2 TRUE

```
\doifundefinedcounter {...} {...}
```

- 1 NAME
- 2 TRUE

```
\doifundefinedelse {...} {...} {...}
```

- 1 NAME
- 2 TRUE
- 3 FALSE

```
\doifurldefinedelse {...} {...} {...}
```

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifvalue {...} {...} {...}`

- 1 NAME
- 2 TEXT
- 3 TRUE

`\doifvalueelse {...} {...} {...} {...}`

- 1 NAME
- 2 TEXT
- 3 TRUE
- 4 FALSE

`\doifvaluenothing {...} {...}`

- 1 NAME
- 2 TRUE

`\doifvaluenothingelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifvaluesomething {...} {...}`

- 1 NAME
- 2 TRUE

`\doifvariable {...} {...} {...}`

- 1 NAME
- 2 KEY
- 3 TRUE

`\doifvariableelse {...} {...} {...} {...}`

- 1 NAME
- 2 KEY
- 3 TRUE
- 4 FALSE

`\doindentation`

`\dollar`

`\doloop {...}`

- \* COMMAND

`\doloopoverlist {...,1...} {...2}`

- 1 TEXT
- 2 COMMAND

`\donothing`

<code>\dontconvertfont</code>
<code>\dontleavehmode</code>
<code>\dontpermitspacesbetweengroups</code>
<code>\dopositionaction {.*}</code> *    NAME
<code>\doprocesslocalsetups {...,*,...}</code> *    NAME
<code>\doquadrupleargument \<sup>1</sup>... [<sup>2</sup>...] [<sup>3</sup>...] [<sup>4</sup>...] [<sup>5</sup>...]</code> 1    CSNAME 2    TEXT 3    TEXT 4    TEXT 5    TEXT
<code>\doquadrupleempty \<sup>1</sup>... [<sup>2</sup>...] [<sup>3</sup>...] [<sup>4</sup>...] [<sup>5</sup>...]</code> <div style="display: flex; justify-content: space-around; margin: 0 100px;"> <span>OPT</span> <span>OPT</span> <span>OPT</span> <span>OPT</span> </div> 1    CSNAME 2    TEXT 3    TEXT 4    TEXT 5    TEXT
<code>\doquadruplegroupempty \<sup>1</sup>... {<sup>2</sup>...} {<sup>3</sup>...} {<sup>4</sup>...} {<sup>5</sup>...}</code> <div style="display: flex; justify-content: space-around; margin: 0 100px;"> <span>OPT</span> <span>OPT</span> <span>OPT</span> <span>OPT</span> </div> 1    CSNAME 2    TEXT 3    TEXT 4    TEXT 5    TEXT
<code>\doquintupleargument \<sup>1</sup>... [<sup>2</sup>...] [<sup>3</sup>...] [<sup>4</sup>...] [<sup>5</sup>...] [<sup>6</sup>...]</code> 1    CSNAME 2    TEXT 3    TEXT 4    TEXT 5    TEXT 6    TEXT

`\doquintupleempty \1... [2...]OPT [3...]OPT [4...]OPT [5...]OPT [6...]OPT`

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT
- 6 TEXT

`\doquintuplegroupempty \1... {2...}OPT {3...}OPT {4...}OPT {5...}OPT {6...}OPT`

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT
- 6 TEXT

`\dorechecknextindentation`

`\dorecurse {1...} {2...}`

- 1 NUMBER
- 2 COMMAND

`\dorepeatwithcommand [1...] \2...`

- 1 TEXT NUMBER\*TEXT
- 2 CSNAME

`\doreplacefeature {.*}`

\* NAME

`\doresetandafffeature {.*}`

\* NAME

`\doresetattribute {.*}`

\* NAME

`\dorotatebox {1...} \2... {3...}`

- 1 NUMBER
- 2 CSNAME
- 3 CONTENT

`\dosetattribute {1...} {2...}`

- 1 NAME
- 2 NUMBER

`\dosetleftskipadaption {.*}`

\* yes no standard DIMENSION

<p><code>\dosetrightrightskipadaption {...}</code></p> <p>*    yes no standard DIMENSION</p>
<p><code>\dosetupcheckedinterlinespace {...,*=...,...}</code></p> <p>*    inherits: \setupinterlinespace</p>
<p><code>\dosetupcheckedinterlinespace {...,*...}</code></p> <p>*    on off reset auto small medium big NUMBER DIMENSION</p>
<p><code>\dosetupcheckedinterlinespace {...}</code></p> <p>*    NAME</p>
<p><code>\doseventupleargument \... [<sup>1</sup>... [<sup>2</sup>... [<sup>3</sup>... [<sup>4</sup>... [<sup>5</sup>... [<sup>6</sup>... [<sup>7</sup>... [<sup>8</sup>...</code></p> <p>1    CSNAME</p> <p>2    TEXT</p> <p>3    TEXT</p> <p>4    TEXT</p> <p>5    TEXT</p> <p>6    TEXT</p> <p>7    TEXT</p> <p>8    TEXT</p>
<p><code>\doseventupleempty \... [<sup>2</sup>... [<sup>3</sup>... [<sup>4</sup>... [<sup>5</sup>... [<sup>6</sup>... [<sup>7</sup>... [<sup>8</sup>...</code>  <div>OPT</div> <div>OPT</div> <div>OPT</div> <div>OPT</div> <div>OPT</div> <div>OPT</div> <div>OPT</div> <div>OPT</div> </p> <p>1    CSNAME</p> <p>2    TEXT</p> <p>3    TEXT</p> <p>4    TEXT</p> <p>5    TEXT</p> <p>6    TEXT</p> <p>7    TEXT</p> <p>8    TEXT</p>
<p><code>\dosingleargument \... [<sup>2</sup>...</code></p> <p>1    CSNAME</p> <p>2    TEXT</p>
<p><code>\dosingleempty \... [<sup>2</sup>...</code>  <div>OPT</div> </p> <p>1    CSNAME</p> <p>2    TEXT</p>
<p><code>\dosinglegroupempty \... {<sup>2</sup>...}</code>  <div>OPT</div> </p> <p>1    CSNAME</p> <p>2    TEXT</p>

`\dosixtupleargument \1... [2...] [3...] [4...] [5...] [6...] [7...]`

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT
- 6 TEXT
- 7 TEXT

`\dosixtupleempty \1... [2...] [3...] [4...] [5...] [6...] [7...]`  
OPT OPT OPT OPT OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT
- 6 TEXT
- 7 TEXT

`\dostarttagged {1...} {2...} ... \dostoptagged`

- 1 NAME
- 2 NAME

`\dostepwiserecurse {1...} {2...} {3...} {4...}`

- 1 NUMBER
- 2 NUMBER
- 3 [-+]NUMBER
- 4 COMMAND

`\dosubtractfeature {*...}`

- \* NAME

`\dot {*...}`

- \* CHARACTER

`\dotfskip {*...}`

- \* DIMENSION

`\dotoks \*...`

- \* CSNAME

`\dotripleargument \1... [2...] [3...] [4...]`

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT

`\dotripleargumentwithset \1... [2...2,...] [3...] [4...]`

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT

`\dotripleempty \1... [2...] [3...] [4...]`  
OPT OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT

`\dotripleemptywithset \1... [2...2,...] [3...] [4...]`  
OPT OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT

`\dotriplegroupempty \1... {2...} {3...} {4...}`  
OPT OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT

`\doublebar {...}`

- \* TEXT

`\doublebond`

`\doublebrace {...}`

- \* TEXT

`\doublebracket {...}`

- \* TEXT

`\doubleparent {...}`

- \* TEXT

`\dowith {...1,...} {...2}`

- 1 COMMAND
- 2 COMMAND

`\dowithnextbox {...1} \2... {...3}`

- 1 COMMAND
- 2 CSNAME
- 3 CONTENT

`\dowithnextboxcontent {...} {...} \dots {...}`

- 1    COMMAND
- 2    COMMAND
- 3    CSNAME
- 4    CONTENT

`\dowithnextboxcontentcs \dots \dots \dots {...}`

- 1    CSNAME
- 2    CSNAME
- 3    CSNAME
- 4    CONTENT

`\dowithnextboxcs \dots \dots {...}`

- 1    CSNAME
- 2    CSNAME
- 3    CONTENT

`\dowithpargument \dots`

- \*    CSNAME

`\dowithrange {...,1...} \dots`

- 1    NUMBER NUMBER:NUMBER
- 2    CSNAME

`\dowithwargument \dots`

- \*    CSNAME

`\dpofstring {...}`

- \*    TEXT

`\dummydigit`

`\dummyparameter {...}`

- \*    KEY

`\ETEX`

`\EveryLine {...}`

- \*    COMMAND

`\EveryPar {...}`

- \*    COMMAND

`\edefconvertedargument \dots {...}`

- 1    CSNAME
- 2    TEXT



<code>\efcmaxheight {...}</code>  *    NAME
<code>\efcmaxwidth {...}</code>  *    NAME
<code>\efcminheight {...}</code>  *    NAME
<code>\efcminwidth {...}</code>  *    NAME
<code>\efcparameter {...} {...}</code>  1    NAME 2    KEY
<code>\effect [...] {...}</code>  1    NAME 2    CONTENT
<code>\elapsedseconds</code>
<code>\elapsedtime</code>
<code>\leftarrowfill {...} {...}</code> <div style="display: flex; justify-content: space-around; width: 100%;"> <span>OPT</span> <span>OPT</span> </div> 1    TEXT 2    TEXT
<code>\leftharpoondownfill {...} {...}</code> <div style="display: flex; justify-content: space-around; width: 100%;"> <span>OPT</span> <span>OPT</span> </div> 1    TEXT 2    TEXT
<code>\leftharpoonupfill {...} {...}</code> <div style="display: flex; justify-content: space-around; width: 100%;"> <span>OPT</span> <span>OPT</span> </div> 1    TEXT 2    TEXT
<code>\leftrightarrowfill {...} {...}</code> <div style="display: flex; justify-content: space-around; width: 100%;"> <span>OPT</span> <span>OPT</span> </div> 1    TEXT 2    TEXT
<code>\emphasisboldface</code>
<code>\emphasistypeface</code>
<code>\emptylines [...]</code> <div style="display: flex; justify-content: space-around; width: 100%;"> <span>OPT</span> </div> *    NUMBER
<code>\emspace</code>

<code>\enabledirectives [...,*,...]</code>  <code>* NAME</code>
<code>\enableexperiments [...,*,...]</code>  <code>* NAME</code>
<code>\enablemode [...,*,...]</code>  <code>* NAME</code>
<code>\enableoutputstream [...]</code>  <code>* NAME</code>
<code>\enableparpositions</code>
<code>\enableregime [...]</code>  <code>* cp1250 cp1251 cp1252 cp1253 cp1254 cp1255 cp1256 cp1257 cp1258 8859-1 8859-2 8859-3 8859-4 8859-9 8859-10 8859-13 8859-14 8859-15 8859-16 utf windows-1250 windows-1251 windows-1252 windows-1253 windows-1254 windows-1255 windows-1256 windows-1257 windows-1258 il1 il2 il3 il4 il5 il6 il7 il8 il9 il10 iso-8859-1 iso-8859-2 iso-8859-3 iso-8859-4 iso-8859-9 iso-8859-10 iso-8859-13 iso-8859-14 iso-8859-15 iso-8859-16 latin1 latin2 latin3 latin4 latin5 latin6 latin7 latin8 latin9 latin10 utf-8 utf8 windows</code>
<code>\enabletrackers [...,*,...]</code>  <code>* NAME</code>
<code>\enskip</code>
<code>\enspace</code>
<code>\ENUMERATION [...,<sup>1</sup>...]{...<sup>2</sup>} ...<sup>3</sup> \par</code> <code>                                  OPT                                  OPT</code> <code>1 REFERENCE</code> <code>2 TEXT</code> <code>3 CONTENT</code>
<code>\env {...}</code>  <code>* KEY</code>
<code>\environment [...]</code>  <code>* FILE</code>
<code>\environment ...</code>  <code>* FILE</code>
<code>\envvar {...<sup>1</sup>} {...<sup>2</sup>}</code>  <code>1 KEY</code> <code>2 COMMAND</code>
<code>\eoverbarfill {...<sup>1</sup>} {...<sup>2</sup>}</code> <code>                                  OPT                                  OPT</code> <code>1 TEXT</code> <code>2 TEXT</code>

`\eoverbracefill {1...} {2...}`  
                    OPT      OPT

1 TEXT

2 TEXT

`\eoverbracketfill {1...} {2...}`  
                    OPT      OPT

1 TEXT

2 TEXT

`\eoverparentfill {1...} {2...}`  
                    OPT      OPT

1 TEXT

2 TEXT

`\epos {...}`

\* NAME

`\equaldigits {...}`

\* TEXT

`\erightarrowfill {1...} {2...}`  
                    OPT      OPT

1 TEXT

2 TEXT

`\erightharpoondownfill {1...} {2...}`  
                    OPT      OPT

1 TEXT

2 TEXT

`\erightharpoonupfill {1...} {2...}`  
                    OPT      OPT

1 TEXT

2 TEXT

`\eTeX`

`\etwoheadrightarrowfill {1...} {2...}`  
                    OPT      OPT

1 TEXT

2 TEXT

`\eunderbarfill {1...} {2...}`  
                    OPT      OPT

1 TEXT

2 TEXT

`\eunderbracefill {1...} {2...}`  
                    OPT      OPT

1 TEXT

2 TEXT

`\eunderbracketfill {1...} {2...}`  
                    OPT      OPT

1 TEXT

2 TEXT

`\eunderparentfill`  $\overset{1}{\{...\}}$   $\overset{2}{\{...\}}$   
                                  OPT          OPT

1 TEXT

2 TEXT

`\executeifdefined`  $\{...\}$   $\{...\}$

1 NAME

2 COMMAND

`\exitloop`

`\exitloopnow`

`\expandcheckedcsname`  $\backslash\overset{1}{...}$   $\overset{2}{\{...\}}$   $\overset{3}{\{...\}}$

1 CSNAME

2 KEY

3 TEXT

`\expanded`  $\{...\}$

\* CONTENT

`\expandfontsynonym`  $\backslash\overset{1}{...}$   $\overset{2}{\{...\}}$

1 CSNAME

2 NAME

`\expdoif`  $\{...\overset{1}{\}}$   $\{...\overset{2}{\}}$   $\{...\overset{3}{\}}$

1 CONTENT

2 CONTENT

3 TRUE

`\expdoifcommonelse`  $\{...\overset{1}{},...\}$   $\{...\overset{2}{},...\}$   $\{...\overset{3}{\}}$   $\{...\overset{4}{\}}$

1 TEXT

2 TEXT

3 TRUE

4 FALSE

`\expdoifelse`  $\{...\overset{1}{\}}$   $\{...\overset{2}{\}}$   $\{...\overset{3}{\}}$   $\{...\overset{4}{\}}$

1 CONTENT

2 CONTENT

3 TRUE

4 FALSE

`\expdoifelsecommon`  $\{...\overset{1}{},...\}$   $\{...\overset{2}{},...\}$   $\{...\overset{3}{\}}$   $\{...\overset{4}{\}}$

1 TEXT

2 TEXT

3 TRUE

4 FALSE

`\expdoifelseinset {...} {...,2...} {...3} {...4}`

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

`\expdoifinsetelse {...} {...,2...} {...3} {...4}`

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

`\expdoifnot {...} {...2} {...3}`

- 1 CONTENT
- 2 CONTENT
- 3 TRUE

`\externalfigure [...]OPT [...]OPT [...,3...]`

- 1 FILE
- 2 NAME
- 3 inherits: \setupexternalfigure

`\externalfigurecollectionmaxheight {...}`

- \* NAME

`\externalfigurecollectionmaxwidth {...}`

- \* NAME

`\externalfigurecollectionminheight {...}`

- \* NAME

`\externalfigurecollectionminwidth {...}`

- \* NAME

`\externalfigurecollectionparameter {...} {...2}`

- 1 NAME
- 2 KEY

`\fakebox ...`

- \* CSNAME NUMBER

`\fastdecrement \...`

- \* CSNAME

`\fastincrement \...`

- \* CSNAME

<p><b>\fastlocalframed</b> [<sup>1</sup>...] [<sup>2</sup>...<sub>...</sub>] {<sup>3</sup>...}</p> <p>1 NAME</p> <p>2 inherits: \setupframed</p> <p>3 CONTENT</p>
<p><b>\fastloopfinal</b></p>
<p><b>\fastloopindex</b></p>
<p><b>\fastscale</b> {<sup>1</sup>...} {<sup>2</sup>...}</p> <p>1 NUMBER</p> <p>2 CONTENT</p>
<p><b>\fastsetup</b> {.*...}</p> <p>* NAME</p>
<p><b>\fastsetupwithargument</b> {<sup>1</sup>...} {<sup>2</sup>...}</p> <p>1 NAME</p> <p>2 CONTENT</p>
<p><b>\fastsetupwithargumentswapped</b> {<sup>1</sup>...} {<sup>2</sup>...}</p> <p>1 CONTENT</p> <p>2 NAME</p>
<p><b>\fastswitchtobodyfont</b> {.*...}</p> <p>* x xx small big script scriptscript</p>
<p><b>\fastsxsy</b> {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...}</p> <p>1 NUMBER</p> <p>2 NUMBER</p> <p>3 CONTENT</p>
<p><b>\feature</b> [<sup>1</sup>...] [<sup>2</sup>...]</p> <p>1 + - = ! &gt; &lt; more less new reset default old local</p> <p>2 NAME</p>
<p><b>\feature</b> {<sup>1</sup>...} {<sup>2</sup>...}</p> <p>1 + - = ! &gt; &lt; more less new reset default old local</p> <p>2 NAME</p>
<p><b>\fence</b></p>
<p><b>\fenced</b> [<sup>1</sup>...] {<sup>2</sup>...}</p> <p>1 NAME</p> <p>2 CONTENT</p>
<p><b>\FENCE</b> {.*...}</p> <p>* CONTENT</p>

<pre> \fetchallmarkings [...] [...]  1  MARK  2  page NAME </pre>
<pre> \fetchallmarks [...]  *  MARK </pre>
<pre> \fetchmark [...] [...]                 OPT 1  MARK  2  first last current previous next top bottom default both all first:unchecked last:unchecked previous:unchecked next:unchecked    top:unchecked bottom:unchecked </pre>
<pre> \fetchmarking [...] [...] [...]  1  MARK  2  page NAME  3  first last current previous next top bottom default both all first:unchecked last:unchecked previous:unchecked next:unchecked    top:unchecked bottom:unchecked </pre>
<pre> \fetchonemark [...] [...]                 OPT 1  MARK  2  first last current previous next top bottom default both all first:unchecked last:unchecked previous:unchecked next:unchecked    top:unchecked bottom:unchecked </pre>
<pre> \fetchonemarking [...] [...] [...]  1  MARK  2  page NAME  3  first last current previous next top bottom default both all first:unchecked last:unchecked previous:unchecked next:unchecked    top:unchecked bottom:unchecked </pre>
<pre> \fetchruntimecommand \... {...}  1  CSNAME  2  FILE </pre>
<pre> \fetchtwomarkings [...] [...]  1  MARK  2  page NAME </pre>
<pre> \fetchtwomarks [...]  *  MARK </pre>
<pre> \field [...] [...]                 OPT 1  NAME  2  TEXT </pre>
<pre> \fieldbody [...] [...] [...]                 OPT 1  NAME  2  inherits: \setupfieldbody </pre>

$\backslash\text{fieldstack}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...,...] <sub>OPT</sub> [ <sup>3</sup> ...,...] <sub>OPT</sub>
1 NAME 2 NAME 3 inherits: \setupfieldcategory
$\backslash\text{fifthoffivearguments}$ {...} {...} {...} {...} {...}
1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT
$\backslash\text{fifthofsixarguments}$ {...} {...} {...} {...} {...} {...}
1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT
$\backslash\text{figurefilename}$
$\backslash\text{figurefilepath}$
$\backslash\text{figurefiletype}$
$\backslash\text{figurefullname}$
$\backslash\text{figureheight}$
$\backslash\text{figurenaturalheight}$
$\backslash\text{figurenaturalwidth}$
$\backslash\text{figuresymbol}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...,...] <sub>OPT</sub>
1 FILE NAME 2 inherits: \externalfigure
$\backslash\text{figurewidth}$
$\backslash\text{filename}$ {...}
* FILE
$\backslash\text{filledhboxb}$ <sup>1</sup> ... {...} <sub>OPT</sub>
1 TEXT 2 CONTENT



`\filledhboxc`  $\overset{1}{\dots} \{\overset{2}{\dots}\}$   
OPT

1 TEXT

2 CONTENT

`\filledhboxg`  $\overset{1}{\dots} \{\overset{2}{\dots}\}$   
OPT

1 TEXT

2 CONTENT

`\filledhboxk`  $\overset{1}{\dots} \{\overset{2}{\dots}\}$   
OPT

1 TEXT

2 CONTENT

`\filledhboxm`  $\overset{1}{\dots} \{\overset{2}{\dots}\}$   
OPT

1 TEXT

2 CONTENT

`\filledhboxr`  $\overset{1}{\dots} \{\overset{2}{\dots}\}$   
OPT

1 TEXT

2 CONTENT

`\filledhboxy`  $\overset{1}{\dots} \{\overset{2}{\dots}\}$   
OPT

1 TEXT

2 CONTENT

`\filler` [ $\dots$ ]

\* sym symbol rule width space NAME

`\fillinline` [ $\dots\overset{*}{=}\dots$ ]

\* inherits: \setupfillinlines

`\fillinrules` [ $\dots\overset{1}{=}\dots$ ]  $\{\overset{2}{\dots}\} \{\overset{3}{\dots}\}$   
OPT OPT OPT

1 inherits: \setupfillinrules

2 TEXT

3 TEXT

`\fillintext` [ $\dots\overset{1}{=}\dots$ ]  $\{\overset{2}{\dots}\} \{\overset{3}{\dots}\}$   
OPT OPT OPT

1 inherits: \setupfillinrules

2 TEXT

3 TEXT

\filterfromnext {...} {...} {...} {...} {...} {...} {...}  
OPT OPT OPT OPT OPT

- 1 NUMBER
- 2 NUMBER
- 3 CONTENT
- 4 CONTENT
- 5 CONTENT
- 6 CONTENT
- 7 CONTENT

\filterfromvalue {...} {...} {...}

- 1 NAME
- 2 NUMBER
- 3 NUMBER

\filterpages [...]<sup>1</sup> [...,<sup>2</sup>...] [...,<sup>3</sup>...]  
OPT

- 1 FILE
- 2 even odd NUMBER NUMBER:NUMBER
- 3 width = DIMENSION  
n = NUMBER  
category = NAME

\filterreference {...}

\* default text title number page realpage

\findtwopassdata {...} {...}

- 1 NAME
- 2 NAME

\finishregisterentry [...]<sup>1</sup> [...,<sup>2</sup>...] [...,<sup>3</sup>...]  
OPT

- 1 NAME
- 2 label = NAME  
keys = TEXT PROCESSOR->TEXT  
entries = TEXT PROCESSOR->TEXT  
alternative = TEXT
- 3 KEY = VALUE

\firstcharacter

\firstcounter [...]<sup>1</sup> [...]<sup>2</sup>  
OPT

- 1 NAME
- 2 NUMBER

\firstcountervalue [...]

\* NAME

\firstoffivearguments {...} {...} {...} {...} {...}

1 TEXT  
2 TEXT  
3 TEXT  
4 TEXT  
5 TEXT

\firstoffourarguments {...} {...} {...} {...}

1 TEXT  
2 TEXT  
3 TEXT  
4 TEXT

\firstofoneargument {...}

\* TEXT

\firstofoneunexpanded {...}

\* TEXT

\firstofsixarguments {...} {...} {...} {...} {...} {...}

1 TEXT  
2 TEXT  
3 TEXT  
4 TEXT  
5 TEXT  
6 TEXT

\firstofthreearguments {...} {...} {...}

1 TEXT  
2 TEXT  
3 TEXT

\firstofthreeunexpanded {...} {...} {...}

1 TEXT  
2 TEXT  
3 TEXT

\firstoftwoarguments {...} {...}

1 TEXT  
2 TEXT

\firstoftwounexpanded {...} {...}

1 TEXT  
2 TEXT

\firstrealpage

<code>\firstrealpagenumber</code>
<code>\firstsubcountervalue</code> [ <sup>1</sup> ...] [ <sup>2</sup> ...] 1 NAME 2 NUMBER
<code>\firstsubpage</code>
<code>\firstsubpagenumber</code>
<code>\firstuserpage</code>
<code>\firstuserpagenumber</code>
<code>\fitfield</code> [ <sup>1</sup> ...] [..., <sup>2</sup> ...] <small>OPT</small> 1 NAME 2 inherits: \setupfieldbody
<code>\fitfieldframed</code> [..., <sup>1</sup> ...]{ <sup>2</sup> ...} <small>OPT</small> 1 inherits: \setupframed 2 CONTENT
<code>\fittopbaselinegrid</code> {...} * CONTENT
<code>\fixedspace</code>
<code>\fixedspaces</code>
<code>\flag</code> {...} * NAME
<code>\placelistofchemicals</code> [..., <sup>*</sup> ...] <small>OPT</small> * inherits: \setuplist
<code>\placelistoffigures</code> [..., <sup>*</sup> ...] <small>OPT</small> * inherits: \setuplist
<code>\placelistofgraphics</code> [..., <sup>*</sup> ...] <small>OPT</small> * inherits: \setuplist
<code>\placelistofintermezzi</code> [..., <sup>*</sup> ...] <small>OPT</small> * inherits: \setuplist
<code>\placelistoftables</code> [..., <sup>*</sup> ...] <small>OPT</small> * inherits: \setuplist
<code>\floatuserdataparameter</code> {...} * KEY

\flushboxregister ... * CSNAME NUMBER
\flushcollector [...] * NAME
\flushedrightlastline
\flushlayer [...] * NAME
\flushlocalfloats
\flushnextbox
\flushnotes
\flushoutputstream [...] * NAME
\flushshapebox
\flushtextflow {...} * NAME
\flushtokens [...] * NAME
\flushtoks \... * CSNAME
\fontalternative
\fontbody
\fontchar {...} * NAME
\fontcharbyindex {...} * NUMBER
\fontclass
\fontclassname {... <sup>1</sup> } {... <sup>2</sup> } 1 NAME 2 FONT
\fontface

<code>\fontfeaturelist [...]<sup>1</sup> [...]<sup>2</sup></code>  1 NAME 2 TEXT
<code>\fontsize</code>
<code>\fontstyle</code>
<code>\footnotetext [...]<sup>1</sup>,...<sub>OPT</sub> {...}<sup>2</sup></code>  1 REFERENCE 2 TEXT
<code>\footnotetext [...]<sup>*</sup>,...]</code>  * title = TEXT bookmark = TEXT list = TEXT reference = REFERENCE
<code>\forcecharacterstripping</code>
<code>\forcelocalfloats</code>
<code>\forgeteverypar</code>
<code>\forgetparameters [...]<sup>1</sup> [...]<sup>2</sup>,...]</code>  1 TEXT 2 KEY = VALUE
<code>\forgetragged</code>
<code>\formula [...]<sup>1</sup>,...<sub>OPT</sub> {...}<sup>2</sup></code>  1 packed tight middle frame inherits: \setupbodyfont 2 CONTENT
<code>\formulanumber [...]<sup>*</sup>,...<sub>OPT</sub></code>  * REFERENCE
<code>\foundbox {...}<sup>1</sup> {...}<sup>2</sup></code>  1 NAME 2 NAME
<code>\fourthoffivearguments {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup> {...}<sup>4</sup> {...}<sup>5</sup></code>  1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT

`\fourthoffourarguments {1...} {2...} {3...} {4...}`

1 TEXT  
2 TEXT  
3 TEXT  
4 TEXT

`\fourthofsixarguments {1...} {2...} {3...} {4...} {5...} {6...}`

1 TEXT  
2 TEXT  
3 TEXT  
4 TEXT  
5 TEXT  
6 TEXT

`\FRACTION {1...} {2...}`

1 CONTENT  
2 CONTENT

instances: xfrac xxfrac frac sfrac dfrac binom dbinom tbinom

`\framed [...1...2...] {2...}`  
OPT

1 inherits: \setupframed  
2 CONTENT

`\frameddimension {*...}`

\* KEY

`\framedparameter {*...}`

\* KEY

`\FRAMEDTEXT [...1...2...] {2...}`  
OPT

1 inherits: \setupframedtext  
2 CONTENT

instances: framedtext

`\FRAMED [...1...2...] {2...}`  
OPT

1 inherits: \setupframed  
2 CONTENT

instances: unframed fitfieldframed

`\fitfieldframed [...1...2...] {2...}`  
OPT

1 inherits: \setupframed  
2 CONTENT

`\unframed [...1...2...] {2...}`  
OPT

1 inherits: \setupframed  
2 CONTENT

<code>\freezedimenmacro \<sup>1</sup> \<sup>2</sup></code>  1 CSNAME 2 CSNAME
<code>\freezemeasure [<sup>1</sup>] [<sup>2</sup>]</code>  1 NAME 2 DIMENSION
<code>\frenchspacing</code>
<code>\from [...]</code>  * REFERENCE
<code>\fromlinenote [<sup>1</sup>] {<sup>2</sup>}</code>  1 REFERENCE 2 TEXT
<code>\frozenhbox {<sup>*</sup>}</code>  * CONTENT
<code>\GetPar</code>
<code>\GotoPar</code>
<code>\Greeknumpers {<sup>*</sup>}</code>  * NUMBER
<code>\gdefconvertedargument \<sup>1</sup> {<sup>2</sup>}</code>  1 CSNAME 2 TEXT
<code>\gdefconvertedcommand \<sup>1</sup> \<sup>2</sup></code>  1 CSNAME 2 CSNAME
<code>\getboxfromcache {<sup>1</sup>} {<sup>2</sup>} <sup>3</sup></code>  1 NAME 2 NUMBER TEXT 3 CSNAME NUMBER
<code>\getboxllx ...</code>  * CSNAME NUMBER
<code>\getboxlly ...</code>  * CSNAME NUMBER
<code>\getbuffer [...]</code> <small>OPT</small> * BUFFER



<code>\getbufferdata [...]</code> <div> <div>OPT</div> <div></div> </div>
<div> <div></div> <div>* BUFFER</div> </div>
<code>\getBUFFER</code>
<code>\getcommacommandsize [...,*,...]</code>
<div> <div></div> <div>* COMMAND</div> </div>
<code>\getcommalistsize [...,*,...]</code>
<div> <div></div> <div>* COMMAND</div> </div>
<code>\getdayoftheweek {...} {...} {...}</code>
<div> <div>1</div> <div>NUMBER</div> </div> <div> <div>2</div> <div>NUMBER</div> </div> <div> <div>3</div> <div>NUMBER</div> </div>
<code>\getdayspermonth {...} {...}</code>
<div> <div>1</div> <div>NUMBER</div> </div> <div> <div>2</div> <div>NUMBER</div> </div>
<code>\getdefinedbuffer [...]</code>
<div> <div></div> <div>* BUFFER</div> </div>
<code>\getdocumentargument {...}</code>
<div> <div></div> <div>* NAME</div> </div>
<code>\getdocumentargumentdefault {...} {...}</code>
<div> <div>1</div> <div>NAME</div> </div> <div> <div>2</div> <div>TEXT</div> </div>
<code>\getdocumentfilename {...}</code>
<div> <div></div> <div>* NUMBER</div> </div>
<code>\getdummyparameters [...,*,...]</code>
<div> <div></div> <div>* KEY = VALUE</div> </div>
<code>\getemptyparameters [...] [...,*,...]</code>
<div> <div>1</div> <div>TEXT</div> </div> <div> <div>2</div> <div>KEY = VALUE</div> </div>
<code>\getparameters [...] [...,*,...]</code>
<div> <div>1</div> <div>TEXT</div> </div> <div> <div>2</div> <div>KEY = VALUE</div> </div>
<code>\getexpandedparameters [...] [...,*,...]</code>
<div> <div>1</div> <div>TEXT</div> </div> <div> <div>2</div> <div>KEY = VALUE</div> </div>

$\backslash\text{getfiguredimensions}$ [ <sup>1</sup> ...] [ <sup>2</sup> ... <sub>OPT</sub> ...] 1 FILE 2 inherits: $\backslash\text{setupeexternalfigure}$
$\backslash\text{getfirstcharacter}$ {...} * TEXT
$\backslash\text{getfirsttwopassdata}$ {...} * NAME
$\backslash\text{getfromcommacommand}$ [..., <sup>1</sup> ...] [ <sup>2</sup> ...] 1 COMMAND 2 NUMBER
$\backslash\text{getfromcommalist}$ [..., <sup>1</sup> ...] [ <sup>2</sup> ...] 1 COMMAND 2 NUMBER
$\backslash\text{getfromtwopassdata}$ { <sup>1</sup> ...} { <sup>2</sup> ...} 1 NAME 2 NAME
$\backslash\text{getglyphdirect}$ { <sup>1</sup> ...} { <sup>2</sup> ...} 1 FONT 2 NUMBER CHARACTER
$\backslash\text{getglyphstyled}$ { <sup>1</sup> ...} { <sup>2</sup> ...} 1 FONT 2 NUMBER CHARACTER
$\backslash\text{getgparameters}$ [ <sup>1</sup> ...] [ <sup>2</sup> ... <sub>OPT</sub> ...] 1 TEXT 2 KEY = VALUE
$\backslash\text{getlasttwopassdata}$ {...} * NAME
$\backslash\text{getlocalfloat}$ {...} * NUMBER
$\backslash\text{getlocalfloats}$
$\backslash\text{getMPdrawing}$
$\backslash\text{getMPlayer}$ [ <sup>1</sup> ...] [ <sup>2</sup> ... <sub>OPT</sub> ...] { <sup>3</sup> ...} 1 NAME 2 inherits: $\backslash\text{setupframed}$ 3 CONTENT

<pre> \getmarking [...] [...] [...]                 OPT      OPT 1  MARK 2  page NAME 3  first last current previous next top bottom default both all first:nocheck last:nocheck previous:nocheck next:nocheck    top:nocheck bottom:nocheck </pre>
<pre> \getmessage {...} {...} 1  NAME 2  NAME NUMBER </pre>
<pre> \getnamedglyphdirect {...} {...} 1  FONT 2  NAME </pre>
<pre> \getnamedglyphstyled {...} {...} 1  FONT 2  NAME </pre>
<pre> \getnamedtwopassdatalist \... {...} 1  CSNAME 2  NAME </pre>
<pre> \getnaturaldimensions ... *  CSNAME NUMBER </pre>
<pre> \getnoflines {...} *  DIMENSION </pre>
<pre> \getobject {...} {...} 1  NAME 2  NAME </pre>
<pre> \getobjectdimensions {...} {...} 1  NAME 2  NAME </pre>
<pre> \getpaletsize [...] *  NAME </pre>
<pre> \getparameters [...] [...] [...] 1  TEXT 2  KEY = VALUE </pre>
<pre> \getprivatechar {...} *  NAME </pre>
<pre> \getprivateslot {...} *  NAME </pre>

`\getrandomcount \1... {2...} {3...}`

- 1 CSNAME
- 2 NUMBER
- 3 NUMBER

`\getrandomdimen \1... {2...} {3...}`

- 1 CSNAME
- 2 DIMENSION
- 3 DIMENSION

`\getrandomfloat \1... {2...} {3...}`

- 1 CSNAME
- 2 NUMBER
- 3 NUMBER

`\getrandomnumber \1... {2...} {3...}`

- 1 CSNAME
- 2 NUMBER
- 3 NUMBER

`\getrandomseed \*...`

- \* CSNAME

`\getraweparameters [1...] [...,2...,...]`

- 1 TEXT
- 2 KEY = VALUE

`\getrawgparameters [1...] [...,2...,...]`

- 1 TEXT
- 2 KEY = VALUE

`\getrawnoflines {*...}`

- \* DIMENSION

`\getrawparameters [1...] [...,2...,...]`

- 1 TEXT
- 2 KEY = VALUE

`\getrawxparameters [1...] [...,2...,...]`

- 1 TEXT
- 2 KEY = VALUE

`\getreference [1...] [2...]`

- 1 default text title number page realpage
- 2 REFERENCE

```
\getreferenceentry {...}
```

```
*  default text title number page realpage
```

```
\getroundednoflines {...}
```

\* DIMENSION

```
\getsubstring {...} {...} {...}
```

1 NUMBER

2 NUMBER

3 TEXT

```
\gettwopassdata {...}
```

\* NAME

```
\gettwopassdatalist {...}
```

\* NAME

```
\getuvalue {...}
```

\* NAME

$$\backslash\mathrm{getvalue}\ \{...\}$$

\* NAME

```
\getvariable {...} {...}
```

1 NAME

2 KEY

```
\getvariabledefault {...} {...} {...}
```

1 NAME

2 KEY

### 3 COMMAND

$$\backslash\mathrm{getxparameters} \left[ \overset{1}{\dots} \right] \left[ \dots, \dots \overset{2}{=} \dots, \dots \right]$$

1 TEXT

2 KEY = VALUE

`\globalisablemode [...,*,...]`

\* NAME

`\globalenablemode [...,*,...]`

\* NAME

\globalletempty \.\*...

\* CSNAME

\globalpopbox ...

\* CSNAME NUMBER

<code>\globalpopmacro \*..</code> <code>* CSNAME</code>
<code>\globalpreventmode [...*,...]</code> <code>* NAME</code>
<code>\globalprocesscommalist [...<sup>1</sup>] \*<sup>2</sup>..</code> <code>1 COMMAND</code> <code>2 CSNAME</code>
<code>\globalpushbox ...</code> <code>* CSNAME NUMBER</code>
<code>\globalpushmacro \*..</code> <code>* CSNAME</code>
<code>\globalpushreferenceprefix {...<sup>*</sup>} ... \globalpopreferenceprefix</code> <code>* + - TEXT</code>
<code>\globalswapcounts \*<sup>1</sup>... \*<sup>2</sup>..</code> <code>1 CSNAME</code> <code>2 CSNAME</code>
<code>\globalswapdimens \*<sup>1</sup>... \*<sup>2</sup>..</code> <code>1 CSNAME</code> <code>2 CSNAME</code>
<code>\globalswapmacros \*<sup>1</sup>... \*<sup>2</sup>..</code> <code>1 CSNAME</code> <code>2 CSNAME</code>
<code>\globalundefine {...<sup>*</sup>}</code> <code>* NAME</code>
<code>\glyphfontfile {...<sup>*</sup>}</code> <code>* FONT</code>
<code>\gobbledoubleempty [...<sup>1</sup>] [...<sup>2</sup>]</code> <code>1 TEXT</code> <code>2 TEXT</code>

`\gobbleeightarguments {...} {...} {...} {...} {...} {...} {...} {...}`

- 1 CONTENT
- 2 CONTENT
- 3 CONTENT
- 4 CONTENT
- 5 CONTENT
- 6 CONTENT
- 7 CONTENT
- 8 CONTENT

`\gobblefivearguments {...} {...} {...} {...} {...}`

- 1 CONTENT
- 2 CONTENT
- 3 CONTENT
- 4 CONTENT
- 5 CONTENT

`\gobblefiveoptionals [...] [...] [...] [...] [...]`

- 1 TEXT
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT

`\gobblefourarguments {...} {...} {...} {...}`

- 1 CONTENT
- 2 CONTENT
- 3 CONTENT
- 4 CONTENT

`\gobblefouroptionals [...] [...] [...] [...]`

- 1 TEXT
- 2 TEXT
- 3 TEXT
- 4 TEXT

`\gobbleninearguments {...} {...} {...} {...} {...} {...} {...} {...} {...}`

- 1 CONTENT
- 2 CONTENT
- 3 CONTENT
- 4 CONTENT
- 5 CONTENT
- 6 CONTENT
- 7 CONTENT
- 8 CONTENT
- 9 CONTENT

\gobbleoneargument {...}

\* CONTENT

\gobbleoneoptional [...]

\* TEXT

\gobblesevenarguments {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} {...<sup>4</sup>} {...<sup>5</sup>} {...<sup>6</sup>} {...<sup>7</sup>}

1 CONTENT

2 CONTENT

3 CONTENT

4 CONTENT

5 CONTENT

6 CONTENT

7 CONTENT

\gobblesingleempty [...]  
OPT

\* TEXT

\gobblesixarguments {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} {...<sup>4</sup>} {...<sup>5</sup>} {...<sup>6</sup>}

1 CONTENT

2 CONTENT

3 CONTENT

4 CONTENT

5 CONTENT

6 CONTENT

\gobblespacetokens

\gobbletenarguments {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} {...<sup>4</sup>} {...<sup>5</sup>} {...<sup>6</sup>} {...<sup>7</sup>} {...<sup>8</sup>} {...<sup>9</sup>} {...<sup>10</sup>}

1 CONTENT

2 CONTENT

3 CONTENT

4 CONTENT

5 CONTENT

6 CONTENT

7 CONTENT

8 CONTENT

9 CONTENT

10 CONTENT

\gobblethreearguments {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

1 CONTENT

2 CONTENT

3 CONTENT



`\gobblethreeoptionals [...] [...] [...]`

- 1 TEXT
- 2 TEXT
- 3 TEXT

`\gobbletwoarguments {...} {...}`

- 1 CONTENT
- 2 CONTENT

`\gobbletwooptionals [...] [...]`

- 1 TEXT
- 2 TEXT

`\gobbleuntil \*..`

- \* CSNAME

`\gobbleuntilrelax ... \relax`

- \* CONTENT

`\godown [...]`

- \* DIMENSION

`\goto {...} [...]`

- 1 CONTENT
- 2 REFERENCE

`\gotobox {...} [...]`

- 1 CONTENT
- 2 REFERENCE

`\gotopage {...} [...]`

- 1 TEXT
- 2 REFERENCE

`\grabbufferdata [...] [...] [...] [...] OPT`

- 1 CATEGORY
- 2 NAME
- 3 NAME
- 4 NAME

`\grabbufferdatadirect {...} {...} {...}`

- 1 NAME
- 2 NAME
- 3 NAME

$\backslash$ grabuntil <sup>1</sup> {...} \ <sup>2</sup> ... 1 NAME 2 CSNAME
$\backslash$ grave {...} * CHARACTER
$\backslash$ graycolor [ <sup>1</sup> ...] { <sup>2</sup> ...} 1 COLOR 2 CONTENT
$\backslash$ grayvalue {...} * COLOR
$\backslash$ greedysplitstring <sup>1</sup> ... \at <sup>2</sup> ... \to \ <sup>3</sup> ... \and \ <sup>4</sup> ... 1 TEXT 2 TEXT 3 CSNAME 4 CSNAME
$\backslash$ greeknumerals {...} * NUMBER
$\backslash$ grid [... <sup>*</sup> ...] <small>OPT</small> * inherits: \basegrid
$\backslash$ groupedcommand <sup>1</sup> {...} { <sup>2</sup> ...} 1 COMMAND 2 COMMAND
$\backslash$ gsetboxllx <sup>1</sup> ... { <sup>2</sup> ...} 1 CSNAME NUMBER 2 DIMENSION
$\backslash$ gsetboxlly <sup>1</sup> ... { <sup>2</sup> ...} 1 CSNAME NUMBER 2 DIMENSION
$\backslash$ gujaratinumerals {...} * NUMBER
$\backslash$ gurmukhinumerals {...} * NUMBER
$\backslash$ hairline
$\backslash$ hairspace

<code>\halfwaybox {...}</code> *    CONTENT
<code>\handletokens ... \with ...<sup>1</sup></code> 1    TEXT 2    CSNAME
<code>\handwritten</code>
<code>\hash</code>
<code>\hat {...}</code> *    CHARACTER
<code>\hboxofvbox ...</code> *    CSNAME NUMBER
<code>\hboxreference [...,<sup>1</sup>...] {...<sup>2</sup>}</code> 1    REFERENCE 2    CONTENT
<code>\hboxBOX {...}</code> *    CONTENT
<code>\hdofstring {...}</code> *    TEXT
<code>\headhbox ...<sup>1</sup> {...<sup>2</sup>}</code> OPT 1    TEXT 2    CONTENT
<code>\headnumber [...<sup>1</sup>] [...<sup>2</sup>]</code> OPT 1    SECTION 2    previous <u>current</u> next first last
<code>\headnumbercontent</code>
<code>\headnumberdistance</code>
<code>\headnumberwidth</code>
<code>\headreferenceattributes</code>
<code>\headsetupspacing</code>
<code>\headtextcontent</code>
<code>\headtextdistance</code>

<code>\headtextwidth</code>
<code>\headvbox</code> <sup>1</sup> <code>...</code> <sup>2</sup> <code>{...}</code> <small>OPT</small> 1    TEXT 2    CONTENT
<code>\headwidth</code>
<code>\heightanddepthofstring</code> <sup>*</sup> <code>{...}</code> *    TEXT
<code>\heightofstring</code> <sup>*</sup> <code>{...}</code> *    TEXT
<code>\heightspanningtext</code> <sup>1</sup> <code>{...}</code> <sup>2</sup> <code>{...}</code> <sup>3</sup> <code>{...}</code> 1    TEXT 2    DIMENSION 3    FONT
<code>\helptext</code> [ <sup>1</sup> <code>...</code> ] <sup>2</sup> <code>{...}</code> <sup>3</sup> <code>{...}</code> <small>OPT</small> 1    REFERENCE 2    TEXT 3    TEXT
<code>\HELP</code> [ <sup>1</sup> <code>...</code> ] <sup>2</sup> <code>{...}</code> <sup>3</sup> <code>{...}</code> <small>OPT</small> 1    REFERENCE 2    TEXT 3    TEXT  <b>instances:</b> <code>helptext</code>
<code>\hglue</code> <sup>*</sup> <code>...</code> *    DIMENSION
<code>\hiddencitation</code> [ <sup>*</sup> <code>...</code> ] *    REFERENCE
<code>\hiddencite</code> [ <sup>*</sup> <code>...</code> ] *    REFERENCE
<code>\hideblocks</code> [ <sup>1</sup> <code>...</code> , <sup>1</sup> <code>...</code> ] [ <sup>2</sup> <code>...</code> , <sup>2</sup> <code>...</code> ] <small>OPT</small> 1    NAME 2    NAME
<code>\high</code> <sup>*</sup> <code>{...}</code> *    CONTENT

$\backslash\text{highlight} [\text{...}] \{\text{...}\}$  1 NAME 2 TEXT
$\backslash\text{HIGHLIGHT} \{\text{...}\}$  * TEXT
$\backslash\text{highordinalstr} \{\text{...}\}$  * TEXT
$\backslash\text{HIGH} \{\text{...}\}$  * CONTENT  instances: unitshigh
$\backslash\text{hilo} [\text{...}] \{\text{...}\} \{\text{...}\}$ $\text{OPT}$ 1 left <u>right</u> 2 CONTENT 3 CONTENT
$\backslash\text{himilo} \{\text{...}\} \{\text{...}\} \{\text{...}\}$  1 CONTENT 2 CONTENT 3 CONTENT
$\backslash\text{hl} [\text{...}]$ $\text{OPT}$ * NUMBER
$\backslash\text{horizontalgrowingbar} [\text{...},\text{...}^*\text{...},\text{...}]$  * inherits: \setuppositionbar
$\backslash\text{horizontalpositionbar} [\text{...},\text{...}^*\text{...},\text{...}]$  * inherits: \setuppositionbar
$\backslash\text{hphantom} \{\text{...}\}$  * CONTENT
$\backslash\text{hpos} \{\text{...}\} \{\text{...}\}$  1 NAME 2 CONTENT
$\backslash\text{hsizedfraction} \{\text{...}\} \{\text{...}\}$  1 DIMENSION 2 NUMBER
$\backslash\text{hsmash} \{\text{...}\}$  * CONTENT

<p><code>\hsmashbox ...</code></p> <p>* CSNAME NUMBER</p>
<p><code>\hsmashed {...}</code></p> <p>* CONTENT</p>
<p><code>\hspace [...]<sup>1</sup> [...]<sup>2</sup></code></p> <p>OPT OPT</p> <p>1 NAME</p> <p>2 small medium big normal <u>default</u> none .5 1 2 3 speech quote interquotation quotation sentence intersentence NAME</p>
<p><code>\htdpofstring {...}</code></p> <p>* TEXT</p>
<p><code>\htofstring {...}</code></p> <p>* TEXT</p>
<p><code>\hyphen</code></p>
<p><code>\hyphenatedcoloredword {...}</code></p> <p>* TEXT</p>
<p><code>\hyphenatedfile {...}</code></p> <p>* FILE</p>
<p><code>\hyphenatedfilename {...}</code></p> <p>* TEXT</p>
<p><code>\hyphenatedhbox {...}</code></p> <p>* CONTENT</p>
<p><code>\hyphenatedpar {...}</code></p> <p>* TEXT</p>
<p><code>\hyphenatedurl {...}</code></p> <p>* TEXT</p>
<p><code>\hyphenatedword {...}</code></p> <p>* TEXT</p>
<p><code>\INRSTEX</code></p>
<p><code>\ibox {...}</code></p> <p>* CONTENT</p>
<p><code>\ifassignment ...<sup>1</sup> \else ...<sup>2</sup> \fi</code></p> <p>1 TRUE</p> <p>2 FALSE</p>

<code>\iff</code>
<code>\ifinobject <sup>1</sup>... \else <sup>2</sup>... \fi</code> 1    TRUE 2    FALSE
<code>\ifinoutputstream <sup>1</sup>... \else <sup>2</sup>... \fi</code> 1    TRUE 2    FALSE
<code>\ifparameters <sup>1</sup>... \else <sup>2</sup>... \fi</code> 1    TRUE 2    FALSE
<code>\iftrialeasetting <sup>1</sup>... \else <sup>2</sup>... \fi</code> 1    TRUE 2    FALSE
<code>\ignoreimplicitspaces</code>
<code>\ignorevalue {...}</code> *    NAME
<code>\immediatesavetwopassdata {...} {...} {...}</code> 1    NAME 2    NUMBER 3    CONTENT
<code>\impliedby</code>
<code>\implies</code>
<code>\in <sup>1</sup>... <sup>2</sup>... [...]</code> <small>OPT            OPT</small> 1    TEXT 2    TEXT 3    REFERENCE
<code>\includemenu [...]</code> *    NAME
<code>\includeversioninfo {...}</code> *    NAME
<code>\increment \...</code> *    CSNAME

<code>\incrementcounter [...]<sup>1</sup> [...]<sup>2</sup></code> <div> <div>OPT</div> <div> 1 NAME  2 NUMBER </div> </div>
<code>\incrementedcounter [...]</code> <div> <div>*</div> <div>NAME</div> </div>
<code>\incrementpagenumber</code>
<code>\incrementsubpagenumber</code>
<code>\incrementvalue {...}</code> <div> <div>*</div> <div>NAME</div> </div>
<code>\increment cd:parentheses-1</code> <div> <div>*</div> <div>CSNAME NUMBER</div> </div>
<code>\indentation</code>
<code>\infofont</code>
<code>\infofontbold</code>
<code>\inframed [...]<sup>1</sup> [...]<sup>2</sup></code> <div> <div>OPT</div> <div> 1 inherits: \setupframed  2 CONTENT </div> </div>
<code>\infull {...}</code> <div> <div>*</div> <div>NAME</div> </div>
<code>\inheritparameter [...]<sup>1</sup> [...]<sup>2</sup> [...]<sup>3</sup></code> <div> <div> 1 TEXT  2 TEXT  3 KEY </div> </div>
<code>\inhibitblank</code>
<code>\initializeboxstack {...}</code> <div> <div>*</div> <div>NAME</div> </div>
<code>\inline {...}<sup>1</sup> [...]<sup>2</sup></code> <div> <div>OPT</div> <div> 1 TEXT  2 REFERENCE </div> </div>
<code>\inlinebuffer [...]<sup>*</sup> [...]</code> <div> <div>OPT</div> <div> <div>*</div> <div>BUFFER</div> </div> </div>



<code>\inlinedbox {...}</code> *    CONTENT
<code>\inlinemath {...}</code> *    CONTENT
<code>\inlinemathematics {...}</code> *    CONTENT
<code>\inlinemessage {...}</code> *    TEXT
<code>\inlineordisplaymath {...} {...}</code> 1    CONTENT 2    CONTENT
<code>\inlinerange [...]</code> *    REFERENCE
<code>\innerflushshapebox</code>
<code>\input {...}</code> *    FILE
<code>\inputfilebarename</code>
<code>\inputfilename</code>
<code>\inputfilerealsuffix</code>
<code>\inputfilesuffix</code>
<code>\inputgivenfile {...}</code> *    FILE
<code>\input ...</code> *    FILE
<code>\insertpages [...]<sup>1</sup> [...,<sup>2</sup>...] [...,<sup>3</sup>...<sub>OPT</sub>...]<sub>OPT</sub></code> 1    FILE 2    NUMBER 3    width    = DIMENSION n        = NUMBER category = NAME
<code>\installactionhandler {...}</code> *    NAME

```
\installactivecharacter ...
```

\* CHARACTER

```
\installanddefineactivecharacter ... {1... {2...}}
```

1 CHARACTER

2 COMMAND

```
\installattributestack \*
```

\* CSNAME

```
\installautocommandhandler \... {1... {2...}} \...3...
```

1 CSNAME

2 NAME

3 CSNAME

```
\installautosetuphandler \... {1... {2...}}
```

1 CSNAME

2 NAME

```
\installbasicautosetuphandler \... {1... {2...}} \...3...
```

1 CSNAME

2 NAME

3 CSNAME

```
\installbasicparameterhandler \... {1... {2...}}
```

1 CSNAME

2 NAME

```
\installbottomframerenderer {1...} {2...}
```

1 NAME

2 COMMAND

```
\installcommandhandler \... {1... {2...}} \...3...
```

1 CSNAME

2 NAME

3 CSNAME

```
\installcorenamespace {*...}
```

\* NAME

```
\installdefinehandler \... {1... {2...}} \...3...
```

1 CSNAME

2 NAME

3 CSNAME

\installdefinitionset \...<sup>1</sup> {...}<sup>2</sup>}

- 1 CSNAME
- 2 NAME

\installdefinitionsetmember \...<sup>1</sup> {...}<sup>2</sup> \...<sup>3</sup> {...}<sup>4</sup>}

- 1 CSNAME
- 2 NAME
- 3 CSNAME
- 4 NAME

\installdirectcommandhandler \...<sup>1</sup> {...}<sup>2</sup>}

- 1 CSNAME
- 2 NAME

\installdirectparameterhandler \...<sup>1</sup> {...}<sup>2</sup>}

- 1 CSNAME
- 2 NAME

\installdirectparametersethandler \...<sup>1</sup> {...}<sup>2</sup>}

- 1 CSNAME
- 2 NAME

\installdirectsetuphandler \...<sup>1</sup> {...}<sup>2</sup>}

- 1 CSNAME
- 2 NAME

\installdirectstyleandcolorhandler \...<sup>1</sup> {...}<sup>2</sup>}

- 1 CSNAME
- 2 NAME

\installframedautocommandhandler \...<sup>1</sup> {...}<sup>2</sup> \...<sup>3</sup>

- 1 CSNAME
- 2 NAME
- 3 CSNAME

\installframedcommandhandler \...<sup>1</sup> {...}<sup>2</sup> \...<sup>3</sup>

- 1 CSNAME
- 2 NAME
- 3 CSNAME

\installlanguage [...]<sup>1</sup> [...]<sup>2</sup>...

- 1 NAME
- 2 inherits: \setuplanguage

\installlanguage [...]<sup>1</sup> [...]<sup>2</sup>

- 1 NAME
- 2 LANGUAGE

\installleftframerenderer {...} {...}

- 1 NAME
- 2 COMMAND

\installnamespace {...}

- \* NAME

\installoutputroutine \... {...}

- 1 CSNAME
- 2 COMMAND

\installpagearrangement ... {...}

- 1 NAME
- 2 COMMAND

\installparameterhandler \... {...}

- 1 CSNAME
- 2 NAME

\installparameterhashhandler \... {...}

- 1 CSNAME
- 2 NAME

\installparametersethandler \... {...}

- 1 CSNAME
- 2 NAME

\installparentinjector \... {...}

- 1 CSNAME
- 2 NAME

\installrightframerenderer {...} {...}

- 1 NAME
- 2 COMMAND

\installrootparameterhandler \... {...}

- 1 CSNAME
- 2 NAME

\installsetuphandler \... {...}

- 1 CSNAME
- 2 NAME

\installsetuponlycommandhandler \... {...}

- 1 CSNAME
- 2 NAME

`\installshipoutmethod {...} {...}`

- 1 NAME
- 2 COMMAND

`\installsimplecommandhandler ^{1}... {...} ^{3}...`

- 1 CSNAME
- 2 NAME
- 3 CSNAME

`\installsimpleframedcommandhandler ^{1}... {...} ^{3}...`

- 1 CSNAME
- 2 NAME
- 3 CSNAME

`\installstyleandcolorhandler ^{1}... {...}`

- 1 CSNAME
- 2 NAME

`\installswitchcommandhandler ^{1}... {...} ^{3}...`

- 1 CSNAME
- 2 NAME
- 3 CSNAME

`\installswitchsetuphandler ^{1}... {...}`

- 1 CSNAME
- 2 NAME

`\installtexdirective {...} {...} {...}`

- 1 NAME
- 2 COMMAND
- 3 COMMAND

`\installtexttracker {...} {...} {...}`

- 1 NAME
- 2 COMMAND
- 3 COMMAND

`\installtopframerenderer {...} {...}`

- 1 NAME
- 2 COMMAND

`\installunitsseparator {...} {...}`

- 1 NAME
- 2 COMMAND

<code>\installunitsspace {...} {...}</code>  1    NAME 2    COMMAND
<code>\installversioninfo {...} {...}</code>  1    NAME 2    COMMAND
<code>\integerrounding {...}</code>  *    NUMBER
<code>\interactionbar [...]<sup>1</sup> [...,...]<sup>2</sup> [...,...]</code> <div style="text-align: center;"> <small>OPT</small> <small>OPT</small> </div> 1    NAME 2    inherits: \setupinteractionbar
<code>\interactionbuttons [...,...]<sup>1</sup> [...,...]</code> <div style="text-align: center;"> <small>OPT</small> </div> 1    inherits: \setupinteractionbar 2    page subpage REFERENCE
<code>\interactionmenu [...]<sup>1</sup> [...,...]<sup>2</sup> [...,...]</code> <div style="text-align: center;"> <small>OPT</small> </div> 1    NAME 2    inherits: \setupinteractionmenu
<code>\intertext {...}</code>  *    TEXT
<code>\invokepagehandler {...} {...}</code>  1    normal none NAME 2    CONTENT
<code>\istltdir ...</code>  *    TLT TRT
<code>\istrtdir ...</code>  *    TLT TRT
<code>\italic</code>
<code>\italicbold</code>
<code>\italiccorrection</code>
<code>\item [...]<sup>*</sup> [...]</code> <div style="text-align: center;"> <small>OPT</small> </div> *    REFERENCE
<code>\items [...,...]<sup>1</sup> [...,...]</code> <div style="text-align: center;"> <small>OPT</small> </div> 1    inherits: \setupitems 2    TEXT

$\backslash$ itemtag [...] <sup>OPT</sup> *    REFERENCE
$\backslash$ jobfilename
$\backslash$ jobfilesuffix
$\backslash$ kap {...} *    TEXT
$\backslash$ keepblocks [...] <sup>1</sup> [...] <sup>2</sup> [...] <sup>OPT</sup> 1    NAME 2    NAME
$\backslash$ keeplinestogether {...} *    NUMBER
$\backslash$ keepunwantedspaces
$\backslash$ kerncharacters [...] <sup>1</sup> {...} <sup>2</sup> <sup>OPT</sup> 1    NUMBER 2    TEXT
$\backslash$ koreancirclednumerals {...} *    NUMBER
$\backslash$ koreannumerals {...} *    NUMBER
$\backslash$ koreannumeralsc {...} *    NUMBER
$\backslash$ koreannumeralsp {...} *    NUMBER
$\backslash$ koreanparentnumerals {...} *    NUMBER
$\backslash$ LAMSTEX
$\backslash$ LATEX
$\backslash$ LamSTeX
$\backslash$ LaTeX
$\backslash$ LUAJITEX
$\backslash$ LUATEX

<code>\Lua</code>
<code>\LuajitTeX</code>
<code>\LuaTeX</code>
<code>\LABELlanguage</code> instances: head label mathlabel taglabel unit operator prefix suffix btxlabel
<code>\btxlabeltext {...}</code> * KEY
<code>\headtext {...}</code> * KEY
<code>\labeltext {...}</code> * KEY
<code>\mathlabeltext {...}</code> * KEY
<code>\operatorortext {...}</code> * KEY
<code>\prefixtext {...}</code> * KEY
<code>\suffixtext {...}</code> * KEY
<code>\taglabeltext {...}</code> * KEY
<code>\unittext {...}</code> * KEY
<code>\LABELtexts {...} {...}</code> 1 KEY 2 TEXT instances: head label mathlabel
<code>\leftheadtext {...}</code> * KEY
<code>\leftlabeltext {...}</code> * KEY



$\backslash\mathrm{leftmathlabeltext}\{...\}$ * KEY
$\backslash\mathrm{LABELtext}\{...\}$ * KEY instances: head label mathlabel taglabel unit operator prefix suffix btxlabel
$\backslash\mathrm{btxlabellanguage}$
$\backslash\mathrm{headlanguage}$
$\backslash\mathrm{labellanguage}$
$\backslash\mathrm{mathlabellanguage}$
$\backslash\mathrm{operatorlanguage}$
$\backslash\mathrm{prefixlanguage}$
$\backslash\mathrm{suffixlanguage}$
$\backslash\mathrm{taglabellanguage}$
$\backslash\mathrm{unitlanguage}$
$\backslash\mathrm{LABEL}\left[\overset{1}{...},\overset{2}{...}\right]\{\overset{*}{...}\}$ 1 REFERENCE 2 TEXT
$\backslash\mathrm{language}\left[...\right]$ * LANGUAGE
$\backslash\mathrm{languageCharacters}\{...\}$ * NUMBER
$\backslash\mathrm{languagecharacters}\{...\}$ * NUMBER
$\backslash\mathrm{languagecharwidth}\{...\}$ * LANGUAGE
$\backslash\mathrm{LANGUAGE}$
$\backslash\mathrm{lastcounter}\left[\overset{1}{...}\right]\left[\overset{2}{...}\right]$ 1 NAME 2 NUMBER

<code>\lastcountervalue [...]</code> *    NAME
<code>\lastdigit {...}</code> *    NUMBER
<code>\lastlinewidth</code>
<code>\lastnaturalboxdp</code>
<code>\lastnaturalboxht</code>
<code>\lastnaturalboxwd</code>
<code>\lastpredefinedsymbol</code>
<code>\lastrealpage</code>
<code>\lastrealpagenumber</code>
<code>\lastsubcountervalue [...]<sup>1</sup> [...]<sup>2</sup></code> 1    NAME 2    NUMBER
<code>\lastsubpage</code>
<code>\lastsubpagenumber</code>
<code>\lasttwodigits {...}</code> *    NUMBER
<code>\lastuserpage</code>
<code>\lastuserpagenumber</code>
<code>\lateluacode {...}</code> *    COMMAND
<code>\layeredtext [...]<sub>OPT</sub><sup>1</sup> [...]<sub>OPT</sub><sup>2</sup> {...}<sup>3</sup> {...}<sup>4</sup></code> 1    inherits: \setuplayer 2    inherits: \setuplayeredtext 3    TEXT 4    CONTENT
<code>\layerheight</code>
<code>\layerwidth</code>

`\lazysavetaggedtwopassdata {...} {...} {...} {...}`

- 1 NAME
- 2 NUMBER
- 3 NAME
- 4 CONTENT

`\lazysavetwopassdata {...} {...} {...}`

- 1 NAME
- 2 NUMBER
- 3 CONTENT

`\lbox 1... {...}`  
OPT

- 1 TEXT
- 2 CONTENT

`\left ...`

- \* CHARACTER

`\leftaligned {...}`

- \* CONTENT

`\leftbottombox {...}`

- \* CONTENT

`\leftbox {...}`

- \* CONTENT

`\lefthbox {...}`

- \* CONTENT

`\leftLABELtext {...}`

- \* KEY

instances: head label mathlabel

`\rightheadtext {...}`

- \* KEY

`\rightlabeltext {...}`

- \* KEY

`\rightmathlabeltext {...}`

- \* KEY

`\leftline {...}`

- \* CONTENT

$\backslash\text{lefttorrighthbox} \overset{1}{\dots} \{\overset{2}{\dots}\}$ <p>1 TEXT</p> <p>2 CONTENT</p>
$\backslash\text{lefttorrightvbox} \overset{1}{\dots} \{\overset{2}{\dots}\}$ <p>1 TEXT</p> <p>2 CONTENT</p>
$\backslash\text{lefttorrightvtop} \overset{1}{\dots} \{\overset{2}{\dots}\}$ <p>1 TEXT</p> <p>2 CONTENT</p>
$\backslash\text{leftskipadaption}$
$\backslash\text{leftsubguillemot}$
$\backslash\text{lefttopbox} \{.*\}$ <p>* CONTENT</p>
$\backslash\text{lefttoright}$
$\backslash\text{lefttorrighthbox} \overset{1}{\dots} \{\overset{2}{\dots}\}$ <p>1 TEXT</p> <p>2 CONTENT</p>
$\backslash\text{lefttorrightvbox} \overset{1}{\dots} \{\overset{2}{\dots}\}$ <p>1 TEXT</p> <p>2 CONTENT</p>
$\backslash\text{lefttorrightvtop} \overset{1}{\dots} \{\overset{2}{\dots}\}$ <p>1 TEXT</p> <p>2 CONTENT</p>
$\backslash\text{letbeundefined} \{.*\}$ <p>* NAME</p>
$\backslash\text{letcatcodecommand} \overset{1}{\dots} \overset{2}{\dots} \overset{3}{\dots}$ <p>1 CSNAME</p> <p>2 CHARACTER NUMBER</p> <p>3 CSNAME</p>
$\backslash\text{letcsname} \overset{1}{\dots} \backslash\text{csname} \overset{2}{\dots} \backslash\text{endcsname}$ <p>1 CSNAME</p> <p>2 NAME</p>
$\backslash\text{letcsnamecs} \backslash\text{csname} \overset{1}{\dots} \backslash\text{endcsname} \overset{2}{\dots}$ <p>1 NAME</p> <p>2 CSNAME</p>

$$\backslash\mathrm{letcsname}\mathrm{csname}\ \backslash\mathrm{csname}\ \dots\ \backslash\mathrm{endcsname}\ \backslash\mathrm{csname}\ \dots\ \backslash\mathrm{endcsname}$$

1 NAME

2 NAME

$$\backslash \text{letdummysparameter} \{...\} \backslash ...$$

1 KEY

2 CSNAME

```
\letempty \.*...
```

\* CSNAME

$$\backslash letgvalue \{...\} \backslash ...$$

1 NAME

2 CSNAME

```
\letgvalueempty {..}
```

\* NAME

`\letgvalurelax {...}`

\* NAME

\letterampersand

\letterat

\letterbackslash

\letterbar

`\letterbgroup`

\letterclosebrace

\lettercolon

`\letterdollar`

\letterdoublequote

\letteregroup

\letterscape

\letterexclamationmark

\letterhash

`\letterhat`

\letterleftbrace

<code>\letterless</code>
<code>\lettermore</code>
<code>\letteropenbrace</code>
<code>\letterpercent</code>
<code>\letterquestionmark</code>
<code>\letterrightbrace</code>
<code>\lettersinglequote</code>
<code>\letterslash</code>
<code>\letterspacing</code> [ <sup>1</sup> ...] { <sup>2</sup> ...} <small>OPT</small> 1    NUMBER 2    TEXT
<code>\lettertilde</code>
<code>\letterunderscore</code>
<code>\letvalue</code> { <sup>1</sup> ...} \ <sup>2</sup> ... 1    NAME 2    CSNAME
<code>\letvalueempty</code> {.*} *    NAME
<code>\letvaluerelax</code> {.*} *    NAME
<code>\lfence</code> {.*} *    CHARACTER
<code>\lhbox</code> {.*} *    CONTENT
<code>\limitatelines</code> { <sup>1</sup> ...} { <sup>2</sup> ...} { <sup>3</sup> ...} 1    NUMBER 2    COMMAND 3    TEXT
<code>\limitatetext</code> { <sup>1</sup> ...} { <sup>2</sup> ...} { <sup>3</sup> ...} 1    TEXT 2    [-+]DIMENSION 3    COMMAND

`\limitatetext {...} {...,2...} {...3}`

- 1 TEXT
- 2 [-+]DIMENSION
- 3 COMMAND

`\limtatefirstline {...} {...2} {...3}`

- 1 TEXT
- 2 DIMENSION
- 3 COMMAND

`\line {...}`

- \* CONTENT

`\LINENOTE {...}`

- \* TEXT

instances: linenote

`\startlinenote [...1] {...2}`

- 1 REFERENCE
- 2 TEXT

`\linespanningtext {...1} {...2} {...3}`

- 1 TEXT
- 2 DIMENSION
- 3 FONT

`\linewidth`

`\listcitation [...1...2...] [...2]`

- 1 reference = REFERENCE  
alternative = default category entry short page num textnum year index tag keywords author authoryears authornum  
authoryear  
before = COMMAND  
after = COMMAND  
left = COMMAND  
right = COMMAND  
inherits: \setupbtx
- 2 REFERENCE

`\listcitation [...1] [...2]`

- 1 default category entry short page num textnum year index tag keywords author authoryears authornum authoryear
- 2 REFERENCE

`\listcitation [...1...2...] [...2...2...]`

- 1 reference = REFERENCE  
alternative = default category entry short page num textnum year index tag keywords author authoryears authornum  
authoryear  
before = COMMAND  
after = COMMAND  
left = COMMAND  
right = COMMAND  
inherits: \setupbtx
- 2 KEY = VALUE

```

\listcite [...,\1...,...]\2...
OPT
1  reference      = REFERENCE
   alternative    = default category entry short page num textnum year index tag keywords author authoryears authornum
                        authoryear
   before        = COMMAND
   after         = COMMAND
   left          = COMMAND
   right         = COMMAND
   inherits: \setupbtx
2  REFERENCE

```

```

\listcite [...]\1...]\2...
OPT
1  default category entry short page num textnum year index tag keywords author authoryears authornum authoryear
2  REFERENCE

```

```

\listcite [...,\1...,...]\2...,...]\3...,...
1  reference      = REFERENCE
   alternative    = default category entry short page num textnum year index tag keywords author authoryears authornum
                        authoryear
   before        = COMMAND
   after         = COMMAND
   left          = COMMAND
   right         = COMMAND
   inherits: \setupbtx
2  KEY = VALUE

```

```

\listlength

```

```

\listnamespaces

```

```

\llap {...}

```

```

* CONTENT

```

```

\loadanyfile [...]

```

```

* FILE

```

```

\loadanyfileonce [...]

```

```

* FILE

```

```

\loadbtxdefinitionfile [...]

```

```

* FILE

```

```

\loadbtxreplacementfile [...]

```

```

* FILE

```

```

\loadcldfile [...]

```

```

* FILE

```

```

\loadcldfileonce [...]

```

```

* FILE

```

```

\loadfontgoodies [...]

```

```

* FILE

```



<code>\loadluafile [...]</code> *    FILE
<code>\loadluafileonce [...]</code> *    FILE
<code>\loadspellchecklist [<sup>1</sup>...] [<sup>2</sup>...]</code> 1    NAME 2    FILE
<code>\loadtexfile [...]</code> *    FILE
<code>\loadtexfileonce [...]</code> *    FILE
<code>\loadtypescriptfile [...]</code> *    FILE
<code>\localframed [<sup>1</sup>] [...,<sup>2</sup>...,<sup>OPT</sup>...] {<sup>3</sup>...}</code> 1    NAME 2    inherits: \setupframed 3    CONTENT
<code>\localframedwithsettings [<sup>1</sup>] [...,<sup>2</sup>...,<sup>3</sup>...] {<sup>3</sup>...}</code> 1    NAME 2    inherits: \setupframed 3    CONTENT
<code>\localhsize</code>
<code>\localpopbox ...</code> *    CSNAME NUMBER
<code>\localpopmacro \...</code> *    CSNAME
<code>\localpushbox ...</code> *    CSNAME NUMBER
<code>\localpushmacro \...</code> *    CSNAME
<code>\localundefine {...}</code> *    NAME
<code>\locatedfilepath</code>

$\backslash\text{locatefilepath} \{...\}$  *    FILE
$\backslash\text{locfilename} \{...\}$  *    FILE
$\backslash\text{lohi} \overset{\text{OPT}}{[.{}^1.]} \{...\} \{...\}$ 1    left <u>right</u> 2    CONTENT 3    CONTENT
$\backslash\text{lomihi} \{.{}^1.\} \{.{}^2.\} \{.{}^3.\}$  1    CONTENT 2    CONTENT 3    CONTENT
$\backslash\text{low} \{...\}$  *    CONTENT
$\backslash\text{lowerbox} \{...\} \backslash.{}^2. \{...\}$  1    DIMENSION 2    CSNAME 3    CONTENT
$\backslash\text{lowercased} \{...\}$  *    TEXT
$\backslash\text{lowercasestring} .{}^1. \backslash\text{to} \backslash.{}^2.$  1    TEXT 2    CSNAME
$\backslash\text{lowerlefthdoubleninequote}$
$\backslash\text{lowerleftsingleninequote}$
$\backslash\text{lowerrightdoubleninequote}$
$\backslash\text{lowerrightsingleninequote}$
$\backslash\text{LOWHIGH} \overset{\text{OPT}}{[.{}^1.]} \{...\} \{...\}$ 1    left <u>right</u> 2    CONTENT 3    CONTENT
$\backslash\text{LOWMIDHIGH} \{.{}^1.\} \{.{}^2.\} \{.{}^3.\}$  1    CONTENT 2    CONTENT 3    CONTENT

$\backslash LOW \{...\}$  *    CONTENT  instances: unitslow
$\backslash lrtb\!box \{.^1.\} \{.^2.\} \{.^3.\} \{.^4.\} \{.^5.\}$  1    DIMENSION 2    DIMENSION 3    DIMENSION 4    DIMENSION 5    CONTENT
$\backslash ltop \overset{1}{...} \{.^2.\}$ <small>OPT</small> 1    TEXT 2    CONTENT
$\backslash luacode \{...\}$  *    COMMAND
$\backslash luaconditional \backslash^*...$  *    CSNAME
$\backslash luaenvironment ...$  *    FILE
$\backslash luaexpanded \{...\}$  *    COMMAND
$\backslash luaexpr \{...\}$  *    CONTENT
$\backslash luafunction \{...\}$  *    COMMAND
$\backslash luajit\!TeX$
$\backslash luamajorversion$
$\backslash luaminorversion$
$\backslash luaparameterset \{.^1.\} \{.^2.\}$  1    NAME 2    CONTENT
$\backslash luasetup \{...\}$  *    NAME
$\backslash luaTeX$

<code>\luaversion</code>
<code>\METAFONT</code>
<code>\METAFUN</code>
<code>\METAPOST</code>
<code>\MetaFont</code>
<code>\MetaFun</code>
<code>\MetaPost</code>
<code>\MKII</code>
<code>\MKIV</code>
<code>\MKIX</code>
<code>\MKVI</code>
<code>\MKXI</code>
<code>\MONTH {.*.}</code> *    NUMBER
<code>\MONTHLONG {.*.}</code> *    NUMBER
<code>\MONTHSHORT {.*.}</code> *    NUMBER
<code>\MPanchor {...}</code> *    NAME
<code>\MPbetex {...}</code> *    NAME
<code>\MPc {.*.}</code> *    NAME
<code>\MPcode {<sup>1</sup>.*.} {<sup>2</sup>.*.}</code> <div style="text-align: center; margin-left: 100px;"><small>OPT</small></div> 1    NAME 2    CONTENT
<code>\MPcolor {...}</code> *    COLOR

\MPcoloronly {...}  *    COLOR
\MPcolumn {...}  *    NAME
\MPd {...}  *    NAME
\MPdrawing {...}  *    CONTENT
\MPfontsizehskip {...}  *    FONT
\MPgetmultipars {... <sup>1</sup> } {... <sup>2</sup> }  1    NAME 2    NAME
\MPgetmultishape {... <sup>1</sup> } {... <sup>2</sup> }  1    NAME 2    NAME
\MPgetposboxes {..., <sup>1</sup> ...} {... <sup>2</sup> }  1    NAME 2    NAME
\MPh {...}  *    NAME
\MPII
\MPIV
\MPinclusions [... <sup>1</sup> ] {... <sup>2</sup> } {... <sup>3</sup> } OPT            OPT 1    + 2    NAME 3    CONTENT
\MPlleftskip {...}  *    NAME
\MPll {...}  *    NAME
\MPlr {...}  *    NAME

\MPIs {...}  *    NAME
\MPmenubuttons {...}  *    NAME
\MPn {...}  *    NAME
\MPoptions {...}  *    COLOR
\MPoverlayanchor {...}  *    NAME
\MPp {...}  *    NAME
\MPpage {...}  *    NAME
\MPpardata {...}  *    NAME
\MPplus {... <sup>1</sup> } {... <sup>2</sup> } {... <sup>3</sup> }  1    NAME 2    NUMBER 3    CONTENT
\MPpos {...}  *    NAME
\MPpositiongraphic {... <sup>1</sup> } {..., <sup>2</sup> ... <sub>OPT</sub> ,...}  1    NAME 2    KEY = VALUE
\MPposset {...}  *    NAME
\MPr {...}  *    NAME
\MPrawvar {... <sup>1</sup> } {... <sup>2</sup> }  1    NAME 2    KEY
\MPregion {...}  *    NAME

\MPrest {...} {...}  1    NAME 2    CONTENT
\MPrightskip {...}  *    NAME
\MPrs {...}  *    NAME
\MPstring {...}  *    NAME
\MPtext {...}  *    NAME
\MPtransparency {...}  *    COLOR
\MPul {...}  *    NAME
\MPur {...}  *    NAME
\MPVI
\MPv {...} {...} {...}  1    NAME 2    NUMBER 3    CONTENT
\MPvar {...}  *    KEY
\MPvariable {...}  *    KEY
\MPvv {...} {...}  1    NAME 2    CONTENT
\MPw {...}  *    NAME
\MPwhd {...}  *    NAME

<code>\MPx {...}</code>  *    NAME
<code>\MPxy {...}</code>  *    NAME
<code>\MPxywhd {...}</code>  *    NAME
<code>\MPy {...}</code>  *    NAME
<code>\m [<sup>1</sup>...] {<sup>2</sup>...}</code> <div>OPT</div> 1    NAME 2    CONTENT
<code>\mainlanguage [...]</code>  *    LANGUAGE
<code>\makecharacteractive ...</code>  *    CHARACTER
<code>\makerawcommalist [...,<sup>1</sup>...] \<sup>2</sup>...</code>  1    COMMAND 2    CSNAME
<code>\makestrutofbox ...</code>  *    CSNAME NUMBER
<code>\mapfontsize [<sup>1</sup>] [<sup>2</sup>...]</code>  1    DIMENSION 2    DIMENSION
<code>\margindata [<sup>1</sup>] [...,<sup>2</sup>...,...] [...,<sup>3</sup>...,...] {<sup>4</sup>...}</code> <div>OPT                      OPT</div> 1    NAME 2    reference = REFERENCE inherits: \setupmargindata 3    inherits: \setupmarginframed 4    CONTENT
<code>\MARGINDATA [...,<sup>1</sup>...,...] [...,<sup>2</sup>...,...] {<sup>3</sup>...}</code> <div>OPT                      OPT</div> 1    reference = REFERENCE inherits: \setupmargindata 2    inherits: \setupmarginframed 3    CONTENT  instances: inleftmargin inrightmargin inoutermargin ininnermargin inleftedge inrightedge inouteredge ininneredge atleftmargin atrightmargin inleft inright inouter ininner inmargin inother margintext



$\backslash\text{markcontent}$ [ <sup>1</sup> ...] { <sup>2</sup> ...} <small>OPT</small> 1    reset <u>all</u> NAME 2    CONTENT
$\backslash\text{marking}$ (..., <sup>1</sup> ...) (..., <sup>2</sup> ...) [...] <sup>3</sup>
$\backslash\text{markinjector}$ [...] *    NAME
$\backslash\text{mat}$ {...} *    CONTENT
$\backslash\text{math}$ [ <sup>1</sup> ...] { <sup>2</sup> ...} <small>OPT</small> 1    NAME 2    CONTENT
$\backslash\text{mathbf}$
$\backslash\text{mathbi}$
$\backslash\text{mathblackboard}$
$\backslash\text{mathbs}$
$\backslash\text{mathcommand}$ {...} *    NAME
$\backslash\text{MATHCOMMAND}$ { <sup>1</sup> ...} { <sup>2</sup> ...} <small>OPT</small> <small>OPT</small> 1    TEXT 2    TEXT
$\backslash\text{mathdefault}$
$\backslash\text{MATHDOUBLEEXTENSIBLE}$ {...} *    TEXT
$\backslash\text{mathematics}$ [ <sup>1</sup> ...] { <sup>2</sup> ...} <small>OPT</small> 1    NAME 2    CONTENT
$\backslash\text{MATHEXTENSIBLE}$ [...] <sup>1</sup> { <sup>2</sup> ...} <sup>3</sup> { <sup>3</sup> ...} <small>OPT</small> <small>OPT</small> <small>OPT</small> 1    reverse mathematics text chemistry 2    TEXT 3    TEXT

<code>\mathfraktur</code>
$\backslash MATHFRAMED [\dots,\overset{1}{=}\dots,\dots] \{\overset{2}{\dots}\}$ $\text{OPT}$ <p>1 inherits: \setupmathframed</p> <p>2 CONTENT</p> <p>instances: mframed inmframed mcframed</p>
<code>\mathfunction {.*.}</code> <p>* CONTENT</p>
<code>\mathit</code>
<code>\mathitalic</code>
<code>\mathop {.*.}</code> <p>* CONTENT</p>
<code>\MATHORNAMENT {.*.}</code> <p>* CONTENT</p>
<code>\MATHOVEREXTENSIBLE {.*.}</code> <p>* TEXT</p>
<code>\MATHOVERTEXTEXTENSIBLE {\overset{1}{.}} \{\overset{2}{.}\}</code> <p>1 TEXT</p> <p>2 TEXT</p>
$\backslash MATHRADICAL [\overset{1}{.}] \{\overset{2}{.}\}$ $\text{OPT}$ <p>1 TEXT</p> <p>2 CONTENT</p>
<code>\mathrm</code>
<code>\mathscript</code>
<code>\mathsl</code>
<code>\mathss</code>
<code>\mathtext \overset{1}{.} \{\overset{2}{.}\}</code> $\text{OPT}$ <p>1 TEXT</p> <p>2 TEXT</p>
<code>\mathtextbf \overset{1}{.} \{\overset{2}{.}\}</code> $\text{OPT}$ <p>1 TEXT</p> <p>2 TEXT</p>

$\backslash\mathtextbi \overset{1}{...} \{\overset{2}{...}\}$ $\text{OPT}$ 1    TEXT 2    TEXT
$\backslash\mathtextbs \overset{1}{...} \{\overset{2}{...}\}$ $\text{OPT}$ 1    TEXT 2    TEXT
$\backslash\mathtextit \overset{1}{...} \{\overset{2}{...}\}$ $\text{OPT}$ 1    TEXT 2    TEXT
$\backslash\mathtextsl \overset{1}{...} \{\overset{2}{...}\}$ $\text{OPT}$ 1    TEXT 2    TEXT
$\backslash\mathtexttf \overset{1}{...} \{\overset{2}{...}\}$ $\text{OPT}$ 1    TEXT 2    TEXT
$\backslash\mathtf$
$\backslash\mathtripler [\overset{1}{...}] \{\overset{2}{...}\} \{\overset{3}{...}\} \{\overset{4}{...}\}$ $\text{OPT} \quad \text{OPT} \quad \text{OPT} \quad \text{OPT}$ 1    NAME 2    TEXT 3    TEXT 4    TEXT
$\backslash\mathtripleT [\overset{1}{...}] \{\overset{2}{...}\} \{\overset{3}{...}\} \{\overset{4}{...}\}$ $\text{OPT} \quad \text{OPT} \quad \text{OPT} \quad \text{OPT}$ 1    NAME 2    TEXT 3    TEXT 4    TEXT
$\backslash\mathtt$
$\backslash\mathunderextensible \{\overset{*}{...}\}$ *    TEXT
$\backslash\mathunderextextensible \{\overset{1}{...}\} \{\overset{2}{...}\}$ 1    TEXT 2    TEXT
$\backslash\mathunstacked$
$\backslash\mathupright$

$\backslash\mathrm{mathword} \mathop{\mathrm{...}}^1 \{\mathop{\mathrm{...}}^2\}$ $\mathrm{OPT}$ 1    TEXT 2    TEXT
$\backslash\mathrm{mathwordbf} \mathop{\mathrm{...}}^1 \{\mathop{\mathrm{...}}^2\}$ $\mathrm{OPT}$ 1    TEXT 2    TEXT
$\backslash\mathrm{mathwordbi} \mathop{\mathrm{...}}^1 \{\mathop{\mathrm{...}}^2\}$ $\mathrm{OPT}$ 1    TEXT 2    TEXT
$\backslash\mathrm{mathwordbs} \mathop{\mathrm{...}}^1 \{\mathop{\mathrm{...}}^2\}$ $\mathrm{OPT}$ 1    TEXT 2    TEXT
$\backslash\mathrm{mathwordit} \mathop{\mathrm{...}}^1 \{\mathop{\mathrm{...}}^2\}$ $\mathrm{OPT}$ 1    TEXT 2    TEXT
$\backslash\mathrm{mathwordsl} \mathop{\mathrm{...}}^1 \{\mathop{\mathrm{...}}^2\}$ $\mathrm{OPT}$ 1    TEXT 2    TEXT
$\backslash\mathrm{mathwordtf} \mathop{\mathrm{...}}^1 \{\mathop{\mathrm{...}}^2\}$ $\mathrm{OPT}$ 1    TEXT 2    TEXT
$\backslash\mathrm{maxaligned} \{\mathop{\mathrm{...}}^*\}$ *    CONTENT
$\backslash\mathrm{mbox} \{\mathop{\mathrm{...}}^*\}$ *    CONTENT
$\backslash\mathrm{measure} \{\mathop{\mathrm{...}}^*\}$ *    NAME
$\backslash\mathrm{measured} \{\mathop{\mathrm{...}}^*\}$ *    NAME
$\backslash\mathrm{medskip}$
$\backslash\mathrm{medspace}$
$\backslash\mathrm{menubutton} [\mathop{\mathrm{...}}^1\mathop{\mathrm{...}}^2\mathop{\mathrm{...}}^3] \{\mathop{\mathrm{...}}^2\} \{\mathop{\mathrm{...}}^3\}$ 1    inherits: $\backslash\mathrm{setupbutton}$ 2    TEXT 3    REFERENCE

$\backslash\text{menubutton} [\overset{1}{...}] [\dots,\dots,\overset{2}{...},\dots] \{\overset{3}{...}\} \{\overset{4}{...}\}$ <p>1 NAME</p> <p>2 inherits: \setupinteractionmenu</p> <p>3 TEXT</p> <p>4 REFERENCE</p>
$\backslash\text{mequal} \{\overset{1}{...}\} \{\overset{2}{...}\}$ <p>1 TEXT</p> <p>2 TEXT</p>
$\backslash\text{message} \{...\}$ <p>* TEXT</p>
$\backslash\text{metaTeX}$
$\backslash\text{mfence} \{...\}$ <p>* CHARACTER</p>
$\backslash\text{mfunction} \{...\}$ <p>* CONTENT</p>
$\backslash\text{mfunctionlabeltext} \{...\}$ <p>* NAME</p>
$\backslash\text{mhbox} \{...\}$ <p>* CONTENT</p>
$\backslash\text{mhookleftarrow} \{\overset{1}{...}\} \{\overset{2}{...}\}$ <p>1 TEXT</p> <p>2 TEXT</p>
$\backslash\text{mhookrightarrow} \{\overset{1}{...}\} \{\overset{2}{...}\}$ <p>1 TEXT</p> <p>2 TEXT</p>
$\backslash\text{midaligned} \{...\}$ <p>* CONTENT</p>
$\backslash\text{middle} ...$ <p>* CHARACTER</p>
$\backslash\text{middlealigned} \{...\}$ <p>* CONTENT</p>
$\backslash\text{middlebox} \{...\}$ <p>* CONTENT</p>

$\backslash\mathrm{midhbox}\{\dots\}$ *    CONTENT
$\backslash\mathrm{minimalhbox}\overset{1}{\dots}\overset{2}{\{\dots\}}$ 1    TEXT 2    CONTENT
$\backslash\mathrm{mirror}\{\dots\}$ *    CONTENT
$\backslash\mathrm{mixedcaps}\{\dots\}$ *    TEXT
$\backslash\mathrm{mkvibuffer}[\overset{*}{\dots}]$ *    BUFFER
$\backslash\mathrm{mLeftarrow}\overset{1}{\{\dots\}}\overset{2}{\{\dots\}}$ 1    TEXT 2    TEXT
$\backslash\mathrm{mLeftrightarrow}\overset{1}{\{\dots\}}\overset{2}{\{\dots\}}$ 1    TEXT 2    TEXT
$\backslash\mathrm{mleftarrow}\overset{1}{\{\dots\}}\overset{2}{\{\dots\}}$ 1    TEXT 2    TEXT
$\backslash\mathrm{mleftharpoondown}\overset{1}{\{\dots\}}\overset{2}{\{\dots\}}$ 1    TEXT 2    TEXT
$\backslash\mathrm{mleftharpoonup}\overset{1}{\{\dots\}}\overset{2}{\{\dots\}}$ 1    TEXT 2    TEXT
$\backslash\mathrm{mleftrightarrow}\overset{1}{\{\dots\}}\overset{2}{\{\dots\}}$ 1    TEXT 2    TEXT
$\backslash\mathrm{mleftrightharpoons}\overset{1}{\{\dots\}}\overset{2}{\{\dots\}}$ 1    TEXT 2    TEXT
$\backslash\mathrm{mmapsto}\overset{1}{\{\dots\}}\overset{2}{\{\dots\}}$ 1    TEXT 2    TEXT

$$\backslash\mathrm{moduleparameter}\ \{.^1..\}\ \{.^2..\}$$

1 FILE

2 KEY

`\molecule {...}`

\* CONTENT

\mono

\monobold

\mononormal

```
\month {...}
```

\* NUMBER

`\monthlong {...}`

\* NUMBER

`\monthshort {.*}`

\* NUMBER

\mprandomnumber

$$\backslash\mathrm{mRightarrow} \mathop{\{\ldots\}}_{\mathrm{OPT}}^1 \mathop{\{\ldots\}}_{\mathrm{OPT}}^2$$

1 TEXT

2 TEXT

$$\backslash\mathrm{mrel} \quad \underbrace{\{...\}}_{\mathrm{OPT}} \quad \underbrace{\{...\}}_{\mathrm{OPT}}$$

1 TEXT

2 TEXT

$$\xrightarrow[\text{OPT}]{\text{OPT}} \dots$$

1 TEXT

2 TEXT

$$\mathrm{\mrightharpoonopdown} \underset{\mathrm{OPT}}{\{...\}^1} \underset{\mathrm{OPT}}{\{...\}^2}$$

1 TEXT

2 TEXT

$$\backslash\mathrm{mrightharpoonup} \quad \overset{1}{\{...\}} \quad \overset{2}{\{...\}}$$

1 TEXT

2 TEXT

$$\mrightarrowlefttharpoons^{\scriptscriptstyle 1}_{\scriptscriptstyle \text{OPT}}^{\scriptscriptstyle 2}_{\scriptscriptstyle \text{OPT}} \{...\} \{...\}$$

1 TEXT

2 TEXT

$\backslash\mathrm{mrightrightarrowleftarrow} \overset{1}{\{...\}} \overset{2}{\{...\}}$ 1 TEXT 2 TEXT
$\backslash\mathrm{mtext} \{...\}$ * CONTENT
$\backslash\mathrm{mtriplerel} \overset{1}{\{...\}} \overset{2}{\{...\}}$ 1 TEXT 2 TEXT
$\backslash\mathrm{mtwoheadleftarrow} \overset{1}{\{...\}} \overset{2}{\{...\}}$ 1 TEXT 2 TEXT
$\backslash\mathrm{mtwoheadrightarrow} \overset{1}{\{...\}} \overset{2}{\{...\}}$ 1 TEXT 2 TEXT
$\backslash\mathrm{NormalizeFontHeight} \backslash^1 \{...\} \{...\} \{...\} \{...\}$ 1 CSNAME 2 TEXT 3 DIMENSION 4 FONT
$\backslash\mathrm{NormalizeFontWidth} \backslash^1 \{...\} \{...\} \{...\} \{...\}$ 1 CSNAME 2 TEXT 3 DIMENSION 4 FONT
$\backslash\mathrm{NormalizeTextHeight} \overset{1}{\{...\}} \overset{2}{\{...\}} \overset{3}{\{...\}}$ 1 FONT 2 DIMENSION 3 TEXT
$\backslash\mathrm{NormalizeTextWidth} \overset{1}{\{...\}} \overset{2}{\{...\}} \overset{3}{\{...\}}$ 1 FONT 2 DIMENSION 3 TEXT
$\backslash\mathrm{Numbers} \{...\}$ * NUMBER
$\backslash\mathrm{namedheadnumber} \{...\}$ * SECTION



<p><code>\namedstructureheadlocation {...}</code></p> <p>*    SECTION</p>
<p><code>\namedstructureuservariable {...} {...}</code></p> <p>1    SECTION</p> <p>2    KEY</p>
<p><code>\namedstructurevariable {...} {...}</code></p> <p>1    SECTION</p> <p>2    KEY</p>
<p><code>\namedtaggedlabeltexts {...} {...} {...} {...} {...}</code></p> <p>1    NAME</p> <p>2    NAME</p> <p>3    NAME</p> <p>4    NAME</p> <p>5    CONTENT</p>
<p><code>\naturalhbox ...<sup>1</sup> {...}</code>  <small>OPT</small></p> <p>1    TEXT</p> <p>2    CONTENT</p>
<p><code>\naturalhpack ...<sup>1</sup> {...}</code>  <small>OPT</small></p> <p>1    TEXT</p> <p>2    CONTENT</p>
<p><code>\naturalvbox ...<sup>1</sup> {...}</code>  <small>OPT</small></p> <p>1    TEXT</p> <p>2    CONTENT</p>
<p><code>\naturalvcenter ...<sup>1</sup> {...}</code>  <small>OPT</small></p> <p>1    TEXT</p> <p>2    CONTENT</p>
<p><code>\naturalvpack ...<sup>1</sup> {...}</code>  <small>OPT</small></p> <p>1    TEXT</p> <p>2    CONTENT</p>
<p><code>\naturalvtop ...<sup>1</sup> {...}</code>  <small>OPT</small></p> <p>1    TEXT</p> <p>2    CONTENT</p>
<p><code>\naturalwd ...</code></p> <p>*    CSNAME NUMBER</p>
<p><code>\negatecolorbox ...</code></p> <p>*    CSNAME NUMBER</p>

<code>\negated {...}</code> * TEXT
<code>\negthinspace</code>
<code>\newattribute \*..</code> * CSNAME
<code>\newcatcodetable \*..</code> * CSNAME
<code>\newcounter \*..</code> * CSNAME
<code>\newevery \<sup>1</sup>... \<sup>2</sup>..</code> 1 CSNAME 2 CSNAME
<code>\newfrenchspacing</code>
<code>\newmode {...}</code> * NAME
<code>\newsignal \*..</code> * CSNAME
<code>\newsystemmode {...}</code> * NAME
<code>\nextbox</code>
<code>\nextboxdp</code>
<code>\nextboxht</code>
<code>\nextboxhtdp</code>
<code>\nextboxwd</code>
<code>\nextcounter [...] [<sup>2</sup>...]</code> 1 NAME 2 NUMBER <small>OPT</small>
<code>\nextcountervalue [...]</code> * NAME
<code>\nextdepth</code>
<code>\nextparagraphs</code>

<code>\nextPARAGRAPHS</code>
<code>\nextrealpage</code>
<code>\nextrealpagenumber</code>
<code>\nextsubcountervalue</code> [ <sup>1</sup> .] [ <sup>2</sup> .] 1    NAME 2    NUMBER
<code>\nextsubpage</code>
<code>\nextsubpagenumber</code>
<code>\nextuserpage</code>
<code>\nextuserpagenumber</code>
<code>\nocitation</code> [...] *    REFERENCE
<code>\nocitation</code> {...} *    REFERENCE
<code>\nocite</code> [...] *    REFERENCE
<code>\nocite</code> {...} *    REFERENCE
<code>\nodetostring</code> \ <sup>1</sup> . { <sup>2</sup> .} 1    CSNAME 2    CONTENT
<code>\nofigurepages</code>
<code>\noflines</code>
<code>\noflocalfloats</code>
<code>\noheaderandfooterlines</code>
<code>\noindentation</code>
<code>\noitem</code>
<code>\nonfrenchspacing</code>

<code>\nonmathematics {...}</code>  *    CONTENT
<code>\normal</code>
<code>\normalboldface</code>
<code>\normalframedwithsettings [...,\u00b1...,...] {...}</code>  1    inherits: \setupframed 2    CONTENT
<code>\normalizebodyfontsize \^1... {...}</code>  1    CSNAME 2    DIMENSION
<code>\normalizedfontsize</code>
<code>\normalizefontdepth \^1... {...} {...} {...}</code>  1    CSNAME 2    TEXT 3    DIMENSION 4    FONT
<code>\normalizefontheight \^1... {...} {...} {...}</code>  1    CSNAME 2    TEXT 3    DIMENSION 4    FONT
<code>\normalizefontline \^1... {...} {...} {...}</code>  1    CSNAME 2    TEXT 3    DIMENSION 4    FONT
<code>\normalizefontwidth \^1... {...} {...} {...}</code>  1    CSNAME 2    TEXT 3    DIMENSION 4    FONT
<code>\normalizetextdepth {...} {...} {...}</code>  1    FONT 2    DIMENSION 3    TEXT

`\normalizetextheight {...} {...} {...}`

- 1 FONT
- 2 DIMENSION
- 3 TEXT

`\normalizetextline {...} {...} {...}`

- 1 FONT
- 2 DIMENSION
- 3 TEXT

`\normalizetextwidth {...} {...} {...}`

- 1 FONT
- 2 DIMENSION
- 3 TEXT

`\normaltypeface`

`\nospace`

`\note [...]1 [...]2`  
OPT

- 1 NAME
- 2 REFERENCE

`\notesymbol [...]1 [...]2`  
OPT

- 1 NAME
- 2 REFERENCE

`\NOTE [...]1, [...]2`  
OPT

- 1 REFERENCE
- 2 TEXT

`instances: footnote endnote`

`\NOTE [...]*, [...]`

- \* title = TEXT
- bookmark = TEXT
- list = TEXT
- reference = REFERENCE

`instances: footnote endnote`

`\endnote [...]1, [...]2`  
OPT

- 1 REFERENCE
- 2 TEXT

`\footnote [...]1, [...]2`  
OPT

- 1 REFERENCE
- 2 TEXT

`\notopandbottomlines`

<code>\notragged</code>
<code>\notsmallcapped {...}</code> *    TEXT
<code>\ntimes {...} {...}</code> 1    TEXT 2    NUMBER
<code>\numberofpoints {...}</code> *    DIMENSION
<code>\numbers {...}</code> *    NUMBER
<code>\obeydepth</code>
<code>\objectdepth</code>
<code>\objectheight</code>
<code>\objectmargin</code>
<code>\objectwidth</code>
<code>\obox {...}</code> *    CONTENT
<code>\offset [...,\overset{1}{\text{...}},...] {...}</code> <small>OPT</small> 1    inherits: \setupoffset 2    CONTENT
<code>\offsetbox [...,\overset{1}{\text{...}},...] \overset{2}{\text{...}} {...}</code> <small>OPT</small> 1    inherits: \setupoffsetbox 2    CSNAME 3    CONTENT
<code>\onedigitrounding {...}</code> *    NUMBER
<code>\ordinaldaynumber {...}</code> *    NUMBER
<code>\ordinalstr {...}</code> *    TEXT

$\backslash\text{ornamenttext}$ [ $\dots$ <sup>1</sup> $\dots$ ] [ $\dots$ <sup>2</sup> $\dots$ ] { $\dots$ } { $\dots$ } <small>OPT</small> 1 <code>alternative = <u>a</u> b</code> <code>inherits: \setupcollector</code> 2 <code>style = STYLE COMMAND</code> <code>color = COLOR</code> <code>inherits: \setupframed</code> 3    TEXT 4    CONTENT
$\backslash\text{ornamenttext}$ [ $\dots$ ] { $\dots$ } { $\dots$ } 1    NAME 2    TEXT 3    CONTENT
$\backslash\text{ornamenttext}$ [ $\dots$ <sup>1</sup> $\dots$ ] [ $\dots$ <sup>2</sup> $\dots$ ] { $\dots$ } { $\dots$ } <small>OPT</small> 1 <code>alternative = a <u>b</u></code> <code>inherits: \setupplayer</code> 2 <code>inherits: \setuplayeredtext</code> 3    TEXT 4    CONTENT
$\backslash\text{ORNAMENT}$ { $\dots$ } { $\dots$ } 1    TEXT 2    CONTENT
$\backslash\text{outputfilename}$
$\backslash\text{outputstreambox}$ [ $\dots$ ] *    NAME
$\backslash\text{outputstreamcopy}$ [ $\dots$ ] *    NAME
$\backslash\text{outputstreamunvbox}$ [ $\dots$ ] *    NAME
$\backslash\text{outputstreamunvcopy}$ [ $\dots$ ] *    NAME
$\backslash\text{over}$ [ $\dots$ ] *    REFERENCE
$\backslash\text{overbar}$ { $\dots$ } *    TEXT
$\backslash\text{overbartext}$ { $\dots$ } { $\dots$ } 1    TEXT 2    TEXT

<code>\overbarunderbar {...}</code> * TEXT
<code>\overbrace {...}</code> * TEXT
<code>\overbracetext {...} {...}</code> 1 TEXT 2 TEXT
<code>\overbraceunderbrace {...}</code> * TEXT
<code>\overbracket {...}</code> * TEXT
<code>\overbrackettext {...} {...}</code> 1 TEXT 2 TEXT
<code>\overbracketunderbracket {...}</code> * TEXT
<code>\overlaybutton [...]</code> * REFERENCE
<code>\overlaybutton {...}</code> * REFERENCE
<code>\overlaycolor</code>
<code>\overlaydepth</code>
<code>\overlayfigure {...}</code> * FILE
<code>\overlayheight</code>
<code>\overlaylinecolor</code>
<code>\overlaylinewidth</code>
<code>\overlayoffset</code>
<code>\overlayrollbutton [...] [...]</code> 1 REFERENCE 2 REFERENCE
<code>\overlaywidth</code>



$\overleftarrow{\{...\}}$ 

\* TEXT

 $\overleftarrow{\hspace{1.5cm}} \{...\}$ 

\* TEXT

 $\overleftarrow{\hspace{1.5cm}}$ 

\* TEXT

 $\overleftrightarrow{\dots}$ 

\* TEXT

\overloaderror

$$\overparent{\dots}$$

\* TEXT

$$\overparenttext \{...\} \{...\}$$

1 TEXT

2 TEXT

$$\overparentunderparent \{...\}$$

\* TEXT

 $\overrightarrow{\{...\}}$ 

\* TEXT

`\overrightharpoonowdown {...}`

\* TEXT

 $\overset{\cdot}{\rightarrow}$  `\overrightarrow{\cdot}`

\* TEXT

$$\overset{1}{\dots} \overset{2}{\dots}$$

1 TEXT

2 TEXT

 $\overrightarrow{\hspace{1.5cm}}$ 

\* TEXT

`\overtwoheadrightarrow {...}`

\* TEXT

\PDFcolor {...}

\* NAME

\PDFETEX

<code>\PDFTEX</code>
<code>\PICTEX</code>
<code>\PiCTeX</code>
<code>\PointsToBigPoints {<sup>1</sup>..<sup>2</sup>..}</code> 1    DIMENSION 2    CSNAME
<code>\PointsToReal {<sup>1</sup>..<sup>2</sup>..}</code> 1    DIMENSION 2    CSNAME
<code>\PointsToWholeBigPoints {<sup>1</sup>..<sup>2</sup>..}</code> 1    DIMENSION 2    CSNAME
<code>\PPCHTEX</code>
<code>\PPCHTeX</code>
<code>\PRAGMA</code>
<code>\PtToCm {<sup>*</sup>..<sup>*</sup>}</code> *    DIMENSION
<code>\page [...<sup>*</sup>..<sup>*</sup>]</code> <small>OPT</small> *    inherits: \pagebreak
<code>\pagearea [...<sup>1</sup>..<sup>2</sup>..<sup>3</sup>]</code> <small>OPT</small> <small>OPT</small> 1    top header text footer bottom 2    text margin edge 3    left right lefttext <u>middletext</u> righttext
<code>\pagebreak [...<sup>*</sup>..<sup>*</sup>]</code> <small>OPT</small> *    empty header footer dummy frame NUMBER +NUMBER default reset disable yes no makeup blank preference bigpreference left right even odd quadruple last lastpage start stop NAME
<code>\pagefigure [...<sup>1</sup>..<sup>2</sup>..<sup>2</sup>..<sup>2</sup>..<sup>2</sup>..<sup>2</sup>]</code> <small>OPT</small> 1    FILE 2    inherits: \setupexternalfigure
<code>\pagegridspanwidth {<sup>*</sup>..<sup>*</sup>}</code> *    NUMBER
<code>\pageinjection [...<sup>1</sup>..<sup>2</sup>..<sup>2</sup>..<sup>2</sup>..<sup>2</sup>..<sup>2</sup>]</code> <small>OPT</small> <small>OPT</small> 1    NAME 2    KEY = VALUE

<p><code>\pageinjection [...,\overset{1}{=},...]\ [...,\overset{2}{=},...]</code></p> <p>1 inherits: \setuppageinjection</p> <p>2 KEY = VALUE</p>
<p><code>\pagenumber</code></p>
<p><code>\pagereference [...,*,...]</code></p> <p>* REFERENCE</p>
<p><code>\pagestaterealpage {...} {...}</code></p> <p>1 NAME</p> <p>2 NAME NUMBER</p>
<p><code>\paletsize</code></p>
<p><code>\PARAGRAPHS</code></p>
<p><code>\pdfactualtext {...} {...}</code></p> <p>1 CONTENT</p> <p>2 TEXT</p>
<p><code>\pdfbackendactualtext {...} {...}</code></p> <p>1 CONTENT</p> <p>2 TEXT</p>
<p><code>\pdfbackendcurrentresources</code></p>
<p><code>\pdfbackendsetcatalog {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetcolorspace {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsettextgstate {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetinfo {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetname {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>

<code>\pdfbackendsetpageattribute {...} {...}</code>  1    NAME 2    TEXT
<code>\pdfbackendsetpageresource {...} {...}</code>  1    NAME 2    TEXT
<code>\pdfbackendsetpagesattribute {...} {...}</code>  1    NAME 2    TEXT
<code>\pdfbackendsetpattern {...} {...}</code>  1    NAME 2    TEXT
<code>\pdfbackendsetshade {...} {...}</code>  1    NAME 2    TEXT
<code>\pdfcolor {...}</code>  *    NAME
<code>\pdfeTeX</code>
<code>\pdfTeX</code>
<code>\percent</code>
<code>\percentdimen {...} {...}</code>  1    DIMENSION CSNAME 2    DIMENSION NUMBER
<code>\periods [...]</code> <small>OPT</small> *    NUMBER
<code>\periods [..., ...<sup>*</sup>..., ...]</code> <small>OPT</small> *    inherits: \setupperiods
<code>\permitcaretescape</code>
<code>\permitcircumflexescape</code>
<code>\permitspacesbetweengroups</code>
<code>\persiandecimals {...}</code>  *    NUMBER

<p><code>\persiannumerals {...}</code></p> <p>*    NUMBER</p>
<p><code>\phantom {...}</code></p> <p>*    CONTENT</p>
<p><code>\phantombox [...,*...,...]</code></p> <p>*    width    = DIMENSION             height   = DIMENSION             depth    = DIMENSION</p>
<p><code>\pickupgroupedcommand {...} {...} {...}</code></p> <p>1    COMMAND          2    COMMAND          3    COMMAND</p>
<p><code>\placeattachments</code></p>
<p><code>\placebookmarks [...,<sup>1</sup>...] [...,<sup>2</sup>...] [...,<sup>3</sup>*,...]</code>                                  OPT                   OPT                   OPT</p> <p>1    SECTION LIST          2    SECTION LIST          3    inherits: \setupbookmark</p>
<p><code>\placebtxrendering [...,<sup>1</sup>...] [...,<sup>2</sup>*,...]</code>                                  OPT                   OPT</p> <p>1    NAME          2    inherits: \setupbtxrendering</p>
<p><code>\placecitation [...]</code></p> <p>*    REFERENCE</p>
<p><code>\placecombinedlist [...,<sup>1</sup>...] [...,<sup>2</sup>*,...]</code>          OPT</p> <p>1    LIST          2    inherits: \setuplist</p>
<p><code>\placeCOMBINEDLIST [...,*...,...]</code>                                  OPT</p> <p>*    inherits: \setuplist</p> <p>instances: content</p>
<p><code>\setupcontent [...,*...,...]</code></p> <p>*    inherits: \setuplist</p>
<p><code>\placecomments</code></p>
<p><code>\placecurrentformulanumber</code></p>
<p><code>\placedbox {...}</code></p> <p>*    CONTENT</p>

`\placefloat` [<sup>1</sup>...] [<sup>2</sup>...,...] [<sup>3</sup>...,...] {<sup>4</sup>...} {<sup>5</sup>...}  
OPT OPT

- 1 SINGULAR
- 2 split always left right inner outer backspace cutspace inleft inright inmargin leftmargin rightmargin leftedge rightedge innermargin outermargin inneredge outeredge text opposite reset height depth [-+]line halfline grid high low fit 90 180 270 nonumber none local here force margin [-+]hang hanging tall both middle offset top bottom auto page leftpage rightpage somewhere effective header footer
- 3 REFERENCE
- 4 TEXT
- 5 CONTENT

`\placefloatwithsetups` [<sup>1</sup>...] [<sup>2</sup>...,...] [<sup>3</sup>...,...] {<sup>4</sup>...} {<sup>5</sup>...}  
OPT OPT

- 1 NAME
- 2 split always left right inner outer backspace cutspace inleft inright inmargin leftmargin rightmargin leftedge rightedge innermargin outermargin inneredge outeredge text opposite reset height depth [-+]line halfline grid high low fit 90 180 270 nonumber none local here force margin [-+]hang hanging tall both middle offset top bottom auto page leftpage rightpage somewhere effective header footer
- 3 REFERENCE
- 4 TEXT
- 5 CONTENT

`\placeFLOAT` [<sup>1</sup>...,...] [<sup>2</sup>...,...] {<sup>3</sup>...} {<sup>4</sup>...}  
OPT OPT

- 1 split always left right inner outer backspace cutspace inleft inright inmargin leftmargin rightmargin leftedge rightedge innermargin outermargin inneredge outeredge text opposite reset height depth [-+]line halfline grid high low fit 90 180 270 nonumber none local here force margin [-+]hang hanging tall both middle offset top bottom auto page leftpage rightpage somewhere effective header footer
- 2 REFERENCE
- 3 TEXT
- 4 CONTENT

instances: chemical figure table intermezzo graphic

`\placefootnotes` [...,..<sup>\*</sup>...,...]  
OPT

\* inherits: \setupnote

`\placeformula` [...,..<sup>\*</sup>...]  
OPT

\* + - REFERENCE

`\placeframed` [<sup>1</sup>...] [<sup>2</sup>...,..<sup>2</sup>...,...] {<sup>3</sup>...}  
OPT

- 1 NAME
- 2 inherits: \setupframed
- 3 CONTENT

`\placeheadnumber` [...<sup>\*</sup>...]

\* SECTION

`\placeheadtext` [...<sup>\*</sup>...]

\* SECTION

`\placehelp`

`\placeinitial` [...<sup>\*</sup>...]  
OPT

\* NAME

<p><code>\placelayer [...]</code></p> <p>* NAME</p>
<p><code>\placelayeredtext [...]<sup>1</sup> [...,...<sup>2</sup>...,...]<sub>OPT</sub> [...,...<sup>3</sup>...,...]<sub>OPT</sub> {...<sup>4</sup>} {...<sup>5</sup>}</code></p> <p>1 NAME</p> <p>2 inherits: \setuplayer</p> <p>3 inherits: \setuplayeredtext</p> <p>4 TEXT</p> <p>5 CONTENT</p>
<p><code>\placelist [...,<sup>1</sup>...] [...,...<sup>2</sup>...,...]<sub>OPT</sub></code></p> <p>1 LIST</p> <p>2 inherits: \setuplist</p>
<p><code>\placelistofFLOATS [...,...<sup>*</sup>...,...]<sub>OPT</sub></code></p> <p>* inherits: \setuplist</p> <p>instances: chemicals figures tables intermezzi graphics</p>
<p><code>\completelistofchemicals [...,...<sup>*</sup>...,...]<sub>OPT</sub></code></p> <p>* inherits: \setuplist</p>
<p><code>\completelistoffigures [...,...<sup>*</sup>...,...]<sub>OPT</sub></code></p> <p>* inherits: \setuplist</p>
<p><code>\completelistofgraphics [...,...<sup>*</sup>...,...]<sub>OPT</sub></code></p> <p>* inherits: \setuplist</p>
<p><code>\completelistofintermezzi [...,...<sup>*</sup>...,...]<sub>OPT</sub></code></p> <p>* inherits: \setuplist</p>
<p><code>\completelistoftables [...,...<sup>*</sup>...,...]<sub>OPT</sub></code></p> <p>* inherits: \setuplist</p>
<p><code>\placelistofpublications [...,<sup>1</sup>...] [...,...<sup>2</sup>...,...]<sub>OPT</sub><sub>OPT</sub></code></p> <p>1 NAME</p> <p>2 inherits: \setupbtxrendering</p>
<p><code>\placelistofsorts [...]<sup>1</sup> [...,...<sup>2</sup>...,...]<sub>OPT</sub></code></p> <p>1 SINGULAR</p> <p>2 inherits: \setupsorting</p>
<p><code>\placelistofSORTS [...,...<sup>*</sup>...,...]<sub>OPT</sub></code></p> <p>* inherits: \setupsorting</p> <p>instances: logos</p>

$\backslash\text{completelistoflogos}$ [ $\dots$ ] <sup>*</sup> <sub>OPT</sub> [ $\dots$ ] * inherits: \setupsorting
$\backslash\text{placelistofsynonyms}$ [ $\dots$ ] <sup>1</sup> [ $\dots$ ] <sup>2</sup> <sub>OPT</sub> [ $\dots$ ] 1 SINGULAR 2 inherits: \setupsynonyms
$\backslash\text{placelistofSYNONYMS}$ [ $\dots$ ] <sup>*</sup> <sub>OPT</sub> [ $\dots$ ] * inherits: \setupsynonyms  instances: abbreviations
$\backslash\text{completelistofabbreviations}$ [ $\dots$ ] <sup>*</sup> <sub>OPT</sub> [ $\dots$ ] * inherits: \setupsynonyms
$\backslash\text{placelocalfootnotes}$ [ $\dots$ ] <sup>*</sup> <sub>OPT</sub> [ $\dots$ ] * inherits: \setupnote
$\backslash\text{placelocalnotes}$ [ $\dots$ ] <sup>1</sup> [ $\dots$ ] <sup>2</sup> <sub>OPT</sub> [ $\dots$ ] 1 NAME 2 inherits: \setupnote
$\backslash\text{placement}$ [ $\dots$ ] <sup>1</sup> [ $\dots$ ] <sup>2</sup> <sub>OPT</sub> [ $\dots$ ] { $\dots$ } <sup>3</sup> 1 NAME 2 inherits: \setupplacement 3 CONTENT
$\backslash\text{PLACEMENT}$ [ $\dots$ ] <sup>1</sup> <sub>OPT</sub> [ $\dots$ ] { $\dots$ } <sup>2</sup> 1 inherits: \setupplacement 2 CONTENT
$\backslash\text{placenamefloat}$ [ $\dots$ ] <sup>1</sup> [ $\dots$ ] <sup>2</sup> 1 NAME 2 REFERENCE
$\backslash\text{placenameformula}$ [ $\dots$ ] <sup>1</sup> <sub>OPT</sub> [ $\dots$ ] { $\dots$ } <sup>2</sup> 1 + - REFERENCE 2 TEXT
$\backslash\text{placenotes}$ [ $\dots$ ] <sup>1</sup> [ $\dots$ ] <sup>2</sup> <sub>OPT</sub> [ $\dots$ ] 1 NAME 2 inherits: \setupnote
$\backslash\text{placeongrid}$ [ $\dots$ ] <sup>1</sup> <sub>OPT</sub> { $\dots$ } <sup>2</sup> 1 normal standard yes strict tolerant top bottom both broad fit first last high one low none line strut box min max middle NAME 2 CONTENT



$\backslash\text{placeongrid}$ [ $\dots$ , $\dots$ ] <sup>1</sup> { $\dots$ } <sup>2</sup> <small>OPT</small> 1 inherits: $\backslash\text{definegridsnapping}$ 2 CONTENT
$\backslash\text{placeontopofeachother}$ { $\dots$ } <sup>1</sup> { $\dots$ } <sup>2</sup> 1 CONTENT 2 CONTENT
$\backslash\text{placepagenumber}$
$\backslash\text{placepairedbox}$ [ $\dots$ ] <sup>1</sup> [ $\dots$ , $\dots$ ] <sup>2</sup> $\dots$ , $\dots$ ] { $\dots$ } <sup>3</sup> { $\dots$ } <sup>4</sup> <small>OPT</small> 1 NAME 2 inherits: $\backslash\text{setuppairedbox}$ 3 CONTENT 4 TEXT
$\backslash\text{placePAIREDBOX}$ [ $\dots$ , $\dots$ ] <sup>1</sup> $\dots$ , $\dots$ ] { $\dots$ } <sup>2</sup> { $\dots$ } <sup>3</sup> <small>OPT</small> 1 inherits: $\backslash\text{setuppairedbox}$ 2 CONTENT 3 TEXT  instances: legend
$\backslash\text{setuplegend}$ [ $\dots$ , $\dots$ ] <sup>*</sup> $\dots$ , $\dots$ ] * inherits: $\backslash\text{setuppairedbox}$
$\backslash\text{placeparallel}$ [ $\dots$ ] <sup>1</sup> [ $\dots$ , $\dots$ ] <sup>2</sup> [ $\dots$ , $\dots$ ] <sup>3</sup> $\dots$ , $\dots$ ] <small>OPT</small> 1 NAME 2 NAME 3 inherits: $\backslash\text{setupparallel}$
$\backslash\text{placeraawlist}$ [ $\dots$ ] <sup>1</sup> [ $\dots$ , $\dots$ ] <sup>2</sup> $\dots$ , $\dots$ ] <small>OPT</small> 1 LIST 2 inherits: $\backslash\text{setuplist}$
$\backslash\text{placeregister}$ [ $\dots$ ] <sup>1</sup> [ $\dots$ , $\dots$ ] <sup>2</sup> $\dots$ , $\dots$ ] <small>OPT</small> 1 NAME 2 inherits: $\backslash\text{setupregister}$
$\backslash\text{placeREGISTER}$ [ $\dots$ , $\dots$ ] <sup>*</sup> $\dots$ , $\dots$ ] <small>OPT</small> * inherits: $\backslash\text{setupregister}$  instances: index
$\backslash\text{completeindex}$ [ $\dots$ , $\dots$ ] <sup>*</sup> $\dots$ , $\dots$ ] <small>OPT</small> * inherits: $\backslash\text{setupregister}$

$\backslash\text{placereadingwindow}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...] <small>OPT</small> 1 NAME 2 NAME
$\backslash\text{placesidebyside}$ {...} {...} 1 CONTENT 2 CONTENT
$\backslash\text{placesubformula}$ [... <sup>*</sup> ...] <small>OPT</small> * + - REFERENCE
$\backslash\text{popattribute}$ \*... * CSNAME
$\backslash\text{popmacro}$ \*... * CSNAME
$\backslash\text{popmode}$ [...] * NAME
$\backslash\text{popsystemmode}$ {...} * NAME
$\backslash\text{position}$ [... <sup>1</sup> ... <sup>1</sup> ... <sup>1</sup> ...] (... <sup>2</sup> ,... <sup>2</sup> ) {... <sup>3</sup> } <small>OPT</small> 1 inherits: \setuppositioning 2 POSITION 3 CONTENT
$\backslash\text{positionoverlay}$ {...} * NAME
$\backslash\text{positionregionoverlay}$ {... <sup>1</sup> } {... <sup>2</sup> } 1 NAME 2 NAME
$\backslash\text{postponenotes}$
$\backslash\text{predefinedfont}$ [...] * FONT
$\backslash\text{predefinefont}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...] 1 NAME 2 FONT
$\backslash\text{predefinesymbol}$ [...] * NAME
$\backslash\text{prefixedpagenumber}$

`\prependetoks ... \to ...`

- 1 COMMAND
- 2 CSNAME

`\prependgvalue {...} {...}`

- 1 NAME
- 2 COMMAND

`\prependtocommalist {...} ...`

- 1 TEXT
- 2 CSNAME

`\prependtoks ... \to ...`

- 1 COMMAND
- 2 CSNAME

`\prependtoksonce ... \to ...`

- 1 COMMAND
- 2 CSNAME

`\prependvalue {...} {...}`

- 1 NAME
- 2 COMMAND

`\presetdocument [...,*...,...]`

\* inherits: \setupdocument

`\presetfieldsymbols [...,*...,...]`

\* NAME

`\presetLABELtext [...]OPT [...,*...,...]`

- 1 LANGUAGE
- 2 KEY = VALUE

instances: head label mathlabel taglabel unit operator prefix suffix btxlabel

`\copybtxlabeltext [...]OPT [...,*...,...]`

- 1 LANGUAGE
- 2 KEY = KEY

`\copyheadtext [...]OPT [...,*...,...]`

- 1 LANGUAGE
- 2 KEY = KEY

`\copylabeltext [...]OPT [...,*...,...]`

- 1 LANGUAGE
- 2 KEY = KEY

$\backslash\text{copymathlabeltext}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...,...] <small>OPT</small> 1 LANGUAGE 2 KEY = KEY
$\backslash\text{copyoperatorortext}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...,...] <small>OPT</small> 1 LANGUAGE 2 KEY = KEY
$\backslash\text{copyprefixtext}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...,...] <small>OPT</small> 1 LANGUAGE 2 KEY = KEY
$\backslash\text{copiesuffixtext}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...,...] <small>OPT</small> 1 LANGUAGE 2 KEY = KEY
$\backslash\text{copytaglabeltext}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...,...] <small>OPT</small> 1 LANGUAGE 2 KEY = KEY
$\backslash\text{copyunittext}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...,...] <small>OPT</small> 1 LANGUAGE 2 KEY = KEY
$\backslash\text{pretocommalist}$ {...} \ <sup>2</sup> ... 1 TEXT 2 CSNAME
$\backslash\text{prevcounter}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...] <small>OPT</small> 1 NAME 2 NUMBER
$\backslash\text{prevcountervalue}$ [...] * NAME
$\backslash\text{preventmode}$ [...*,...] * NAME
$\backslash\text{prevrealpage}$
$\backslash\text{prevrealpagenumber}$
$\backslash\text{prevsubcountervalue}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...] 1 NAME 2 NUMBER
$\backslash\text{prevsubpage}$

<code>\prevsubpagenumber</code>
<code>\prevuserpage</code>
<code>\prevuserpagenumber</code>
<code>\procent</code>
<code>\processaction [...]<sup>1</sup> [...,...<sup>2</sup>&gt;...,...]</code> 1    COMMAND 2    APPLY
<code>\processallactionsinset [...]<sup>1</sup> [...,...<sup>2</sup>&gt;...,...]</code> 1    COMMAND 2    APPLY
<code>\processassignlist [...,...]<sup>1</sup> \...<sup>2</sup></code> 1    TEXT 2    CSNAME
<code>\processassignmentcommand [...,...<sup>1</sup>...,...] \...<sup>2</sup></code> 1    KEY = VALUE 2    CSNAME
<code>\processassignmentlist [...,...<sup>1</sup>...,...] \...<sup>2</sup></code> 1    KEY = VALUE 2    CSNAME
<code>\processbetween {...}<sup>1</sup> \...<sup>2</sup></code> 1    NAME 2    CSNAME
<code>\processblocks [...,...]<sup>1</sup> [...,...]<sup>2</sup><sub>OPT</sub> [...,...<sup>3</sup>...,...]<sup>3</sup><sub>OPT</sub></code> 1    NAME 2    NAME 3    criterium = <u>text</u> SECTION
<code>\processbodyfontenvironmentlist \...</code> *    CSNAME
<code>\processcolorcomponents {...}</code> *    COLOR
<code>\processcommacommand [...,...]<sup>1</sup> \...<sup>2</sup></code> 1    COMMAND 2    CSNAME

<pre>\processcommalist [...<sup>1</sup>,...] \<sup>2</sup>..</pre> <pre>1  COMMAND</pre> <pre>2  CSNAME</pre>
<pre>\processcommalistwithparameters [...<sup>1</sup>,...] \<sup>2</sup>..</pre> <pre>1  COMMAND</pre> <pre>2  CSNAME</pre>
<pre>\processcontent {...<sup>1</sup>} \<sup>2</sup>..</pre> <pre>1  NAME</pre> <pre>2  CSNAME</pre>
<pre>\processfile {...}</pre> <pre>*  FILE</pre>
<pre>\processfilemany {...}</pre> <pre>*  FILE</pre>
<pre>\processfilenone {...}</pre> <pre>*  FILE</pre>
<pre>\processfileonce {...}</pre> <pre>*  FILE</pre>
<pre>\processfirstactioninset [...<sup>1</sup>] [...<sup>2</sup>⇒...]</pre> <pre>1  COMMAND</pre> <pre>2  APPLY</pre>
<pre>\processisolatedchars {...<sup>1</sup>} \<sup>2</sup>..</pre> <pre>1  TEXT</pre> <pre>2  CSNAME</pre>
<pre>\processisolatedwords {...<sup>1</sup>} \<sup>2</sup>..</pre> <pre>1  TEXT</pre> <pre>2  CSNAME</pre>
<pre>\processlinetablebuffer [...<sup>*</sup>] OPT</pre> <pre>*  BUFFER</pre>
<pre>\processlinetablefile {...}</pre> <pre>*  FILE</pre>
<pre>\processlist {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} \<sup>4</sup>..</pre> <pre>1  CHARACTER</pre> <pre>2  CHARACTER</pre> <pre>3  TEXT</pre> <pre>4  CSNAME</pre>

<p><code>\processMPbuffer [...<sup>*</sup>...]</code></p> <p><small>OPT</small></p> <p>* NAME</p>
<p><code>\processMPfigurefile {...}</code></p> <p>* FILE</p>
<p><code>\processmonth {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}</code></p> <p>1 NUMBER</p> <p>2 NUMBER</p> <p>3 COMMAND</p>
<p><code>\processranges [...<sup>1</sup>...]<sup>2</sup> \...</code></p> <p>1 NUMBER NUMBER:NUMBER</p> <p>2 CSNAME</p>
<p><code>\processseparatedlist [...<sup>1</sup>] [...<sup>2</sup>] {...<sup>3</sup>}</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 CSNAME COMMAND</p>
<p><code>\processTEXbuffer [...<sup>*</sup>]</code></p> <p><small>OPT</small></p> <p>* BUFFER</p>
<p><code>\processtokens {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} {...<sup>4</sup>} {...<sup>5</sup>}</code></p> <p>1 COMMAND</p> <p>2 COMMAND</p> <p>3 COMMAND</p> <p>4 COMMAND</p> <p>5 TEXT</p>
<p><code>\processuntil \...<sup>*</sup></code></p> <p>* CSNAME</p>
<p><code>\processxtablebuffer [...<sup>*</sup>]</code></p> <p><small>OPT</small></p> <p>* NAME</p>
<p><code>\processyear {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} {...<sup>4</sup>}</code></p> <p>1 NUMBER</p> <p>2 COMMAND</p> <p>3 COMMAND</p> <p>4 COMMAND</p>
<p><code>\product [...<sup>*</sup>]</code></p> <p>* FILE</p>
<p><code>\product ...<sup>*</sup></code></p> <p>* FILE</p>

<p><code>\profiledbox</code> [<sup>1</sup>...] [<sup>2</sup>...<sub>OPT</sub>...] {<sup>3</sup>...}</p> <p>1 none fixed strict halffixed quarterfixed eightsfixed NAME</p> <p>2 inherits: \setupprofile</p> <p>3 CONTENT</p>
<p><code>\profilegivenbox</code> {<sup>1</sup>...} <sup>2</sup>...</p> <p>1 none fixed strict halffixed quarterfixed eightsfixed NAME</p> <p>2 CSNAME NUMBER</p>
<p><code>\program</code> [...]</p> <p>* NAME</p>
<p><code>\project</code> [...]</p> <p>* FILE</p>
<p><code>\project</code> ...</p> <p>* FILE</p>
<p><code>\pseudoMixedCapped</code> {...}</p> <p>* TEXT</p>
<p><code>\pseudoSmallCapped</code> {...}</p> <p>* TEXT</p>
<p><code>\pseudoSmallcapped</code> {...}</p> <p>* TEXT</p>
<p><code>\pseudosmallcapped</code> {...}</p> <p>* TEXT</p>
<p><code>\purenumber</code> {...}</p> <p>* NUMBER</p>
<p><code>\pusharrangedpages</code> ... <code>\poparrangedpages</code></p>
<p><code>\pushattribute</code> \...</p> <p>* CSNAME</p>
<p><code>\pushbackground</code> [...] ... <code>\popbackground</code></p> <p>* NAME</p>
<p><code>\pushbar</code> [...] ... <code>\popbar</code></p> <p>* NAME</p>
<p><code>\pushbutton</code> [<sup>1</sup>...] [<sup>2</sup>...]</p> <p>1 NAME</p> <p>2 REFERENCE</p>



<code>\pushcatcodetable ... \popcatcodetable</code>
<code>\pushcolor [...] ... \popcolor</code> *    COLOR
<code>\pushendofline ... \popendofline</code>
<code>\pushindentation ... \popindentation</code>
<code>\pushMPdrawing ... \popMPdrawing</code>
<code>\pushmacro \*...</code> *    CSNAME
<code>\pushmathstyle ... \popmathstyle</code>
<code>\pushmode [...]</code> *    NAME
<code>\pushoutputstream [...]</code> <small>OPT</small> *    NAME
<code>\pushpath [...] ... \poppath</code> *    PATH
<code>\pushpunctuation ... \poppunctuation</code>
<code>\pushrandomseed ... \poprandomseed</code>
<code>\pushreferenceprefix {...} ... \popreferenceprefix</code> *    + - TEXT
<code>\pushsystemmode {...}</code> *    NAME
<code>\putboxincache {...} {...} ...</code> 1    NAME 2    NUMBER TEXT 3    CSNAME NUMBER
<code>\putnextboxincache {...} {...} \^3 {...} {...}</code> 1    NAME 2    NUMBER TEXT 3    CSNAME 4    CONTENT
<code>\qqquad</code>
<code>\quad</code>

<code>\quads [...]</code> <small>OPT</small> *    NUMBER
<code>\quitcommalist</code>
<code>\quitprevcommalist</code>
<code>\quittypescriptscanning</code>
<code>\ReadFile {...}</code> *    FILE
<code>\Romannumerals {...}</code> *    NUMBER
<code>\raggedbottom</code>
<code>\raggedcenter</code>
<code>\raggedleft</code>
<code>\raggedright</code>
<code>\raggedwidecenter</code>
<code>\raisebox {...} \^2... {...}</code> 1    DIMENSION 2    CSNAME 3    CONTENT
<code>\randomizetext {...}</code> *    TEXT
<code>\randomnumber {...} {...}</code> 1    NUMBER 2    NUMBER
<code>\rawcounter [...]<sup>1</sup> [...]<sup>2</sup></code> <small>OPT</small> 1    NAME 2    NUMBER
<code>\rawcountervalue [...]</code> *    NAME
<code>\rawdate [...,*,...]</code> *    inherits: \currentdate

`\rawdoifelseinset {...1} {...,2...} {...3} {...4}`

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

`\rawdoifinset {...1} {...,2...} {...3}`

- 1 TEXT
- 2 TEXT
- 3 TRUE

`\rawdoifinsetelse {...1} {...,2...} {...3} {...4}`

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

`\rawgetparameters [...1] [...,2...]`

- 1 TEXT
- 2 KEY = VALUE

`\rawprocessaction [...1] [...,2=>...]`

- 1 COMMAND
- 2 APPLY

`\rawprocesscommacommand [...,1...] \...2..`

- 1 COMMAND
- 2 CSNAME

`\rawprocesscommalist [...,1...] \...2..`

- 1 COMMAND
- 2 CSNAME

`\rawstructurelistuservariable {...*}`

- \* KEY

`\rawsubcountervalue [...1] [...2]`

- 1 NAME
- 2 NUMBER

`\rbox ...1 {...2}`  
OPT

- 1 TEXT
- 2 CONTENT

`\readfile {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\readfixfile {...} {...} {...} {...}`

- 1 PATH
- 2 FILE
- 3 TRUE
- 4 FALSE

`\readjobfile {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\readlocfile {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\readsetfile {...} {...} {...} {...}`

- 1 PATH
- 2 FILE
- 3 TRUE
- 4 FALSE

`\readsysfile {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\readtexfile {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\readxmlfile {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\realpagenumber`

`\realSmallCapped {...}`

- \* TEXT

<code>\realSmallcapped {...}</code> * TEXT
<code>\realSmallcapped {...}</code> * TEXT
<code>\recursedepth</code>
<code>\recurselevel</code>
<code>\recursestring</code>
<code>\redoconvertfont</code>
<code>\ref [...<sup>1</sup>] [...<sup>2</sup>]</code> 1 default text title number page realpage 2 REFERENCE
<code>\reference [...<sup>1</sup>,...] {...<sup>2</sup>}</code> 1 REFERENCE 2 TEXT
<code>\REFERENCEFORMAT {...<sup>1</sup>} {...<sup>2</sup>} [...<sup>3</sup>]</code> <small>OPT OPT</small> 1 TEXT 2 TEXT 3 REFERENCE
<code>\referenceprefix</code>
<code>\referring (...<sup>1</sup>,...) (...<sup>2</sup>,...) [...<sup>3</sup>]</code> 1 POSITION 2 POSITION 3 REFERENCE
<code>\registerattachment [...<sup>1</sup>] [...,...<sup>2</sup>...,...]</code> 1 NAME 2 inherits: \setupattachment
<code>\attachment [...<sup>1</sup>] [...,...<sup>2</sup>...,...]</code> <small>OPT OPT</small> 1 NAME 2 inherits: \setupattachment
<code>\registercxtluafile {...<sup>1</sup>} {...<sup>2</sup>}</code> 1 FILE 2 NUMBER

`\registerexternalfigure [...]1 [...]2 [...,...3...,...]`  
OPT OPT

1 FILE

2 NAME

3 inherits: \setupeexternalfigure

`\registerfontclass {...}`

\* NAME

`\registerhyphenationexception [...]1 [...]2`  
OPT

1 LANGUAGE

2 TEXT

`\registerhyphenationpattern [...]1 [...]2`  
OPT

1 LANGUAGE

2 TEXT

`\registermenubuttons [...]1 [...]2`

1 NAME

2 TEXT

`\registersort [...]1 [...]2`

1 SINGULAR

2 NAME

`\registersynonym [...]1 [...]2`

1 SINGULAR

2 NAME

`\registerunit [...]1 [...,...2...,...]`  
OPT

1 prefix unit operator suffixe symbol packaged

2 KEY = VALUE

`\REGISTER [...]1 [...+...2+...]`  
OPT

1 TEXT PROCESSOR->TEXT

2 INDEX

instances: index

`\seeindex [...]1 [...+...2+...] {...3}`  
OPT

1 TEXT PROCESSOR->TEXT

2 INDEX

3 TEXT PROCESSOR->TEXT

<code>\REGISTER [...]<sup>1</sup> {...}<sup>2</sup> [...+...+...]<sup>3</sup></code> <code>                  <sup>OPT</sup></code> 1    TEXT   PROCESSOR->TEXT 2    TEXT 3    INDEX  instances: index
<code>\regular</code>
<code>\relatemarking [...]<sup>1</sup> [...]<sup>2</sup></code>  1    MARK 2    MARK
<code>\relateparameterhandlers {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup> {...}<sup>4</sup></code>  1    NAME 2    NAME 3    NAME 4    NAME
<code>\relaxvalueifundefined {...}<sup>*</sup></code>  <sup>*</sup> NAME
<code>\remainingcharacters</code>
<code>\remark (...<sup>1</sup>,...<sup>1</sup>) (...<sup>2</sup>,...<sup>2</sup>) [...<sup>3</sup>,...<sup>3</sup>,...<sup>3</sup>]<sup>OPT</sup> {...}<sup>4</sup></code>  1    POSITION 2    POSITION 3    inherits: \setupframed 4    TEXT
<code>\removebottomthings</code>
<code>\removedepth</code>
<code>\removefromcommalist {...}<sup>1</sup> \...<sup>2</sup></code>  1    TEXT 2    CSNAME
<code>\removelastskip</code>
<code>\removelastspace</code>
<code>\removemarkedcontent [...]<sup>*</sup></code>  <sup>*</sup> NAME
<code>\removepunctuation</code>

<p><code>\removesubstring</code> <sup>1</sup>... \from <sup>2</sup>... \to <sup>3</sup>...</p> <p>1    TEXT</p> <p>2    TEXT</p> <p>3    CSNAME</p>
<p><code>\removetoks</code> <sup>1</sup>... \from <sup>2</sup>...</p> <p>1    COMMAND</p> <p>2    CSNAME</p>
<p><code>\removeunwantedspaces</code></p>
<p><code>\replacefeature</code> [...]</p> <p>*    NAME</p>
<p><code>\replacefeature</code> {...}</p> <p>*    NAME</p>
<p><code>\replaceincommalist</code> <sup>1</sup>... {<sup>2</sup>...}</p> <p>1    CSNAME</p> <p>2    NUMBER</p>
<p><code>\replaceword</code> [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...]</p> <p>1    NAME</p> <p>2    TEXT</p> <p>3    TEXT</p>
<p><code>\rescan</code> {...}</p> <p>*    CONTENT</p>
<p><code>\rescanwithsetup</code> {...} {...}</p> <p>1    NAME</p> <p>2    CONTENT</p>
<p><code>\resetallattributes</code></p>
<p><code>\resetandaddfeature</code> [<sup>*</sup>...]</p> <p>*    NAME</p>
<p><code>\resetandaddfeature</code> {...}</p> <p>*    NAME</p>
<p><code>\resetbar</code></p>
<p><code>\resetboxesincache</code> {...}</p> <p>*    NAME</p>
<p><code>\resetbreakpoints</code></p>



\resetbuffer [...] *    BUFFER
\resetcharacteralign
\resetcharacterkerning
\resetcharacterspacing
\resetcharacterstripping
\resetcollector [...] *    NAME
\resetcounter [...] <sup>1</sup> [...] <sup>2</sup> <small>OPT</small> 1    NAME 2    NUMBER
\resetdigitsmanipulation
\resetdirection
\resetfeature
\resetflag {...} *    NAME
\resetfontcolorsheme
\resetfontfallback [...] <sup>1</sup> [...] <sup>2</sup> <small>OPT</small> 1    NAME 2    FONT
\resetfontsolution
\resethyphenationfeatures
\resetinjector [...] *    NAME
\resetinteractionmenu [...] *    NAME
\resetitaliccorrection
\resetlayer [...] *    NAME
\resetlocalfloats

<code>\resetMPdrawing</code>
<code>\resetMPenvironment</code>
<code>\resetMPinstance [...]</code> *    NAME
<code>\resetmarker [...]</code> *    NAME
<code>\resetmarking [...]</code> *    MARK
<code>\resetmode {...}</code> *    NAME
<code>\resetpagenumber</code>
<code>\resetparallel [...]<sup>1</sup> [...]<sup>2</sup>,...]</code> <small>OPT</small> 1    NAME 2    NAME <u>all</u>
<code>\resetpath</code>
<code>\resetpenalties \...</code> *    CSNAME
<code>\resetprofile</code>
<code>\resetrecurselevel</code>
<code>\resetreference [...]</code> *    NAME
<code>\resetreplacement</code>
<code>\resetscript</code>
<code>\resetsetups [...]</code> *    NAME
<code>\resetshownsynonyms [...]</code> *    SINGULAR
<code>\resetsubpagenumber</code>
<code>\resetsymbolset</code>

\resetsystemmode {...} *    NAME
\resettimer
\resettrackers
\resettrialtypesetting
\resetusedsortings [...] *    SINGULAR
\resetusedsynonyms [...] *    SINGULAR
\resetuserpagenumber
\resetvalue {...} *    NAME
\resetvisualizers
\reshapebox {...} *    COMMAND
\resolvedglyphdirect {...} {...} 1    FONT 2    e:NAME x:NUMBER d:NUMBER s:NUMBER i:NUMBER n:NAME c:NAME u:NAME a:NAME
\resolvedglyphstyled {...} {...} 1    FONT 2    e:NAME x:NUMBER d:NUMBER s:NUMBER i:NUMBER n:NAME c:NAME u:NAME a:NAME
\restartcounter [...] [...] [...] <div> <div>OPT</div> <div> 1    NAME  2    NUMBER  3    NUMBER </div> </div>
\restorebox {...} {...} 1    NAME 2    NAME
\restorecatcodes
\restorecounter [...] *    NAME

$\backslash$ restorecurrentattributes {...} * NAME
$\backslash$ restoreendofline
$\backslash$ restoreglobalbodyfont
$\backslash$ reusableMPgraphic {...} {... <sup>1</sup> ... <sup>2</sup> ...} <small>OPT</small> 1 NAME 2 KEY = VALUE
$\backslash$ reuseMPgraphic {...} {... <sup>1</sup> ... <sup>2</sup> ...} <small>OPT</small> 1 NAME 2 KEY = VALUE
$\backslash$ reuserandomseed
$\backslash$ revivefeature
$\backslash$ rfence {...} * CHARACTER
$\backslash$ rhbox {...} * CONTENT
$\backslash$ right ... * CHARACTER
$\backslash$ rightaligned {...} * CONTENT
$\backslash$ rightbottombox {...} * CONTENT
$\backslash$ rightbox {...} * CONTENT
$\backslash$ right hbox {...} * CONTENT
$\backslash$ right LABEL text {...} * KEY instances: head label mathlabel
$\backslash$ rightline {...} * CONTENT

$\backslash\mathrm{righttorleftpageaction}\ \{.^1.\}\ \{.^2.\}$  1    COMMAND 2    COMMAND
$\backslash\mathrm{rightskipadaption}$
$\backslash\mathrm{rightsubguillemot}$
$\backslash\mathrm{righttopleft}$
$\backslash\mathrm{righttopleftthbox}\ \overset{1}{.}\dots\ \{.^2.\}$ <div style="text-align: center; margin-left: 100px;"><small>OPT</small></div> 1    TEXT 2    CONTENT
$\backslash\mathrm{righttopleftvbox}\ \overset{1}{.}\dots\ \{.^2.\}$ <div style="text-align: center; margin-left: 100px;"><small>OPT</small></div> 1    TEXT 2    CONTENT
$\backslash\mathrm{righttopleftvtop}\ \overset{1}{.}\dots\ \{.^2.\}$ <div style="text-align: center; margin-left: 100px;"><small>OPT</small></div> 1    TEXT 2    CONTENT
$\backslash\mathrm{righttopbox}\ \{.^*.\}$  *    CONTENT
$\backslash\mathrm{rlap}\ \{.^*.\}$  *    CONTENT
$\backslash\mathrm{robustaddtocommalist}\ \{.^1.\}\ \backslash.^2.$  1    TEXT 2    CSNAME
$\backslash\mathrm{robustdoifelseinset}\ \{.^1.\}\ \{\dots,^2,\dots\}\ \{.^3.\}\ \{.^4.\}$  1    TEXT 2    TEXT 3    TRUE 4    FALSE
$\backslash\mathrm{robustdoifinsetelse}\ \{.^1.\}\ \{\dots,^2,\dots\}\ \{.^3.\}\ \{.^4.\}$  1    TEXT 2    TEXT 3    TRUE 4    FALSE
$\backslash\mathrm{robustpretocommalist}\ \{.^1.\}\ \backslash.^2.$  1    TEXT 2    CSNAME

`\rollbutton [...,\stackrel{1}{=}{...}] \stackrel{2}{...} [...]`

- 1 inherits: \setupbutton
- 2 TEXT
- 3 REFERENCE

`\rollbutton [...]\stackrel{1}{...} [...,\stackrel{2}{=}{...}] \stackrel{3}{...} [...]`

- 1 NAME
- 2 inherits: \setupinteractionmenu
- 3 TEXT
- 4 REFERENCE

`\roman`

`\romannumerals {...}`

- \* NUMBER

`\rotate [...,\stackrel{1}{=}{...}] \stackrel{2}{...}`

- 1 inherits: \setuprotate
- 2 CONTENT

`\rtop \stackrel{1}{...} \stackrel{2}{...}`

- 1 TEXT
- 2 CONTENT

`\ruledhbox \stackrel{1}{...} \stackrel{2}{...}`

- 1 TEXT
- 2 CONTENT

`\ruledhpack \stackrel{1}{...} \stackrel{2}{...}`

- 1 TEXT
- 2 CONTENT

`\ruledmbox {...}`

- \* CONTENT

`\ruledtopv \stackrel{1}{...} \stackrel{2}{...}`

- 1 TEXT
- 2 CONTENT

`\ruledtpack \stackrel{1}{...} \stackrel{2}{...}`

- 1 TEXT
- 2 CONTENT

`\ruledvbox \stackrel{1}{...} \stackrel{2}{...}`

- 1 TEXT
- 2 CONTENT

$\backslash\text{ruledvpack} \overset{1}{...} \{\overset{2}{...}\}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{ruledvtop} \overset{1}{...} \{\overset{2}{...}\}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{runMPbuffer} [...,\dots]$ <small>OPT</small> * NAME
$\backslash\text{runninghbox} \{...\}$ * CONTENT
$\backslash\text{ScaledPointsToBigPoints} \{\overset{1}{...}\} \backslash\overset{2}{...}$ 1 DIMENSION 2 CSNAME
$\backslash\text{ScaledPointsToWholeBigPoints} \{\overset{1}{...}\} \backslash\overset{2}{...}$ 1 DIMENSION 2 CSNAME
$\backslash\text{SmallCapped} \{...\}$ * TEXT
$\backslash\text{Smallcapped} \{...\}$ * TEXT
$\backslash\text{safechar} \{...\}$ * NUMBER
$\backslash\text{sans}$
$\backslash\text{sansbold}$
$\backslash\text{sansnormal}$
$\backslash\text{sansserif}$
$\backslash\text{savebox} \{\overset{1}{...}\} \{\overset{2}{...}\} \{\overset{3}{...}\}$ 1 NAME 2 NAME 3 CONTENT

\savebtxdataset [...]<sup>1</sup> [...]<sup>2</sup> [...,...]<sup>3</sup> [...,...]

OPT OPT OPT

1 NAME

2 FILE

3 dataset = NAME

type = bib lua xml

file = FILE

criterium = all text intro reference current here previous local component SECTIONBLOCK:all SECTIONBLOCK:reference  
SECTIONBLOCK:current SECTIONBLOCK:previous

\savebuffer [...,...]<sup>\*</sup> [...,...]

\* list = NAME

file = FILE

prefix = yes no

\savebuffer [...]<sup>1</sup> [...]<sup>2</sup>

1 BUFFER

2 FILE

\savecolor ... \restorecolor

\savecounter [...]

\* NAME

\savecurrentattributes {...}

\* NAME

\savenormalmeaning \...

\* CSNAME

\savetaggedtwopassdata {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup> {...}<sup>4</sup>

1 NAME

2 NUMBER

3 NAME

4 CONTENT

\savetwopassdata {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup>

1 NAME

2 NUMBER

3 CONTENT

\sbox {...}

\* CONTENT

\scale [...]<sup>1</sup> [...,...]<sup>2</sup> {...}<sup>3</sup>

OPT OPT

1 NAME

2 inherits: \setupscale

3 CONTENT

\screen [...]<sup>\*</sup>

OPT

\* inherits: \page



<code>\SCRIPT</code> instances: hangul hanzi nihongo ethiopic thai latin test
<code>\ethiopic</code>
<code>\hangul</code>
<code>\hanzi</code>
<code>\latin</code>
<code>\nihongo</code>
<code>\test</code>
<code>\thai</code>
<code>\secondoffivearguments {<sup>1</sup>.} {<sup>2</sup>.} {<sup>3</sup>.} {<sup>4</sup>.} {<sup>5</sup>.}</code>  1    TEXT 2    TEXT 3    TEXT 4    TEXT 5    TEXT
<code>\secondoffourarguments {<sup>1</sup>.} {<sup>2</sup>.} {<sup>3</sup>.} {<sup>4</sup>.}</code>  1    TEXT 2    TEXT 3    TEXT 4    TEXT
<code>\secondofsixarguments {<sup>1</sup>.} {<sup>2</sup>.} {<sup>3</sup>.} {<sup>4</sup>.} {<sup>5</sup>.} {<sup>6</sup>.}</code>  1    TEXT 2    TEXT 3    TEXT 4    TEXT 5    TEXT 6    TEXT
<code>\secondofthreearguments {<sup>1</sup>.} {<sup>2</sup>.} {<sup>3</sup>.}</code>  1    TEXT 2    TEXT 3    TEXT
<code>\secondofthreeunexpanded {<sup>1</sup>.} {<sup>2</sup>.} {<sup>3</sup>.}</code>  1    TEXT 2    TEXT 3    TEXT

<pre> \secondoftwoarguments {...} {...}  1  TEXT 2  TEXT </pre>
<pre> \secondoftwounexpanded {...} {...}  1  TEXT 2  TEXT </pre>
<pre> \SECTION [...,<sup>1</sup>...] {...}                 OPT 1  REFERENCE 2  TEXT  instances: part chapter section subsection subsubsection subsubsubsection subsubsubsubsection title subject subsubject subsubsubject subsubsubsubject subsubsubsubsubject </pre>
<pre> \SECTION [...,<sup>*</sup>...]  *  title      = TEXT    bookmark   = TEXT    marking    = TEXT    list       = TEXT    reference  = REFERENCE    ownnumber  = TEXT  instances: part chapter section subsection subsubsection subsubsubsection subsubsubsubsection title subject subsubject subsubsubject subsubsubsubject subsubsubsubsubject </pre>
<pre> \SECTION [...,<sup>1</sup>...] {...} {...}                 OPT 1  REFERENCE 2  NUMBER 3  TEXT  instances: part chapter section subsection subsubsection subsubsubsection subsubsubsubsection title subject subsubject subsubsubject subsubsubsubject subsubsubsubsubject </pre>
<pre> \seeREGISTER [...,<sup>1</sup>][...<sup>2</sup>+...]{...}                 OPT 1  TEXT PROCESSOR-&gt;TEXT 2  INDEX 3  TEXT PROCESSOR-&gt;TEXT  instances: index </pre>
<pre> \placeindex [...,<sup>*</sup>...]                 OPT *  inherits: \setupregister </pre>
<pre> \select {...} {...} {...} {...} {...} {...}                 OPT     OPT     OPT     OPT     OPT 1  NAME 2  CONTENT 3  CONTENT 4  CONTENT 5  CONTENT 6  CONTENT </pre>

`\selectblocks [...,1...] [...,2...] [...,3...OPT...]`

1 NAME

2 NAME

3 criterium = text SECTION

`\serializecommalist [...,*,...]`

\* COMMAND

`\serializedcommalist`

`\serif`

`\serifbold`

`\serifnormal`

`\setbar [...]`

\* NAME

`\setbigbodyfont`

`\setboxllx 1... {2...}`

1 CSNAME NUMBER

2 DIMENSION

`\setboxlly 1... {2...}`

1 CSNAME NUMBER

2 DIMENSION

`\setbreakpoints [...]`

\* reset NAME

`\setbuffer [...] ... \endbuffer`

\* NAME

`\setcapstrut`

`\setcatcodetable \*`

\* CSNAME

`\setcharacteralign {1...} {2...}`

1 NUMBER

2 TEXT number->TEXT text->TEXT

`\setcharactercasing [...]`

\* reset WORD word Word Words capital Capital none random mixed camel cap Cap

\setcharactercleaning [...] *    reset 1
\setcharacterkerning [...] *    reset NAME
\setcharacterspacing [...] *    reset NAME
\setcharacterstripping [...] *    reset 1
\setcharstrut {...} *    TEXT
\setcollector [ <sup>1</sup> ...] [ <sup>2</sup> ... <sub>OPT</sub> ...] { <sup>3</sup> ...} 1    NAME 2    inherits: \setupcollector 3    CONTENT
\setcolormodel1 [...] *    black bw gray rgb cmyk <u>all</u> none
\setcounter [ <sup>1</sup> ...] [ <sup>2</sup> ... <sub>OPT</sub> ] [ <sup>3</sup> ...] 1    NAME 2    NUMBER 3    NUMBER
\setcounterown [ <sup>1</sup> ...] [ <sup>2</sup> ... <sub>OPT</sub> ] [ <sup>3</sup> ...] 1    NAME 2    NUMBER 3    TEXT
\setcurrentfontclass {...} *    NAME
\setdataset [ <sup>1</sup> ...] [ <sup>2</sup> ... <sub>OPT</sub> ] [ <sup>3</sup> ... <sub>3</sub> ...] 1    NAME 2    NAME 3    KEY = VALUE
\setdefaultpenalties
\setdigitsmanipulation [...] *    reset NUMBER
\setdirection [...] *    NUMBER

`\setdocumentargument {...} {...}`

- 1 NAME
- 2 TEXT

`\setdocumentargumentdefault {...} {...}`

- 1 NAME
- 2 TEXT

`\setdocumentfilename {...} {...}`

- 1 NUMBER
- 2 TEXT

`\setdummyparameter {...} {...}`

- 1 KEY
- 2 COMMAND

`\setelementexporttag [...] [...]2 [...]`  
OPT

- 1 NAME
- 2 `export` nature pdf
- 3 inline display mixed

`\setemeasure {...} {...}`

- 1 NAME
- 2 DIMENSION

`\setevalue {...} {...}`

- 1 NAME
- 2 CONTENT

`\setevariable {...} {...} {...}`

- 1 NAME
- 2 KEY
- 3 VALUE

`\setevariables [...] [...,...2...,...]`

- 1 NAME
- 2 `set` = COMMAND  
`reset` = COMMAND  
`KEY` = VALUE

`\setfirstline [...]*`  
OPT

- \* NAME

`\setflag {...}`

- \* NAME

`\setfont ...`

- \* FONT

<code>\setfontcolorsheme [...]</code>  *    NAME
<code>\setfontfeature {...}</code>  *    NAME
<code>\setfontsolution [...]</code>  *    NAME
<code>\setfontstrut</code>
<code>\setgmeasure {...} {...}</code>  1    NAME 2    DIMENSION
<code>\setgvalue {...} {...}</code>  1    NAME 2    CONTENT
<code>\setgvariable {...} {...} {...}</code>  1    NAME 2    KEY 3    VALUE
<code>\setgvariables [...]<sup>1</sup> [...,...<sup>2</sup>...,...]</code>  1    NAME 2    set    =    COMMAND reset =    COMMAND KEY    =    VALUE
<code>\sethboxregister ... {...}</code>  1    CSNAME NUMBER 2    CONTENT
<code>\sethyphenatedurlafter {...}</code>  *    TEXT
<code>\sethyphenatedurlbefore {...}</code>  *    TEXT
<code>\sethyphenatedurlnormal {...}</code>  *    TEXT
<code>\sethyphenationfeatures [...,...<sup>*</sup>...]</code> <div style="text-align: center;"><small>OPT</small></div> *    NAME reset

```
\setinitial [...] [...2...]  
                OPT      OPT
```

1 NAME

2 inherits: \setupinitial

```
\setinjector [...] [...2,...] [...3]
```

1 NAME

2 NUMBER

3 COMMAND

```
\setinteraction [...]
```

\* hidden NAME

```
\setinterfacecommand {...} {...}
```

1 NAME

2 NAME

```
\setinterfaceconstant {...} {...}
```

1 NAME

2 NAME

```
\setinterfaceelement {...} {...}
```

1 NAME

2 NAME

```
\setinterfacemessage {...} {...} {...}
```

1 NAME

2 title NAME NUMBER

3 TEXT

```
\setinterfacevariable {...} {...}
```

1 NAME

2 NAME

```
\setinternalrendering [...] [...2] [...3]
```

1 NAME

2 auto embed

3 CONTENT

```
\setitaliccorrection [...]
```

\* reset 1 2

```
\setJSpreamble {...} {...}
```

1 NAME

2 CONTENT

```
1  NAME
2  left right even odd
3  inherits: \setupplayer
4  CONTENT
```

```
1  NAME
2  inherits: \setupplayer
3  inherits: \setupframed
4  CONTENT
```

```
1  NAME
2  inherits: \setupplayerinherits: \setupframed
3  CONTENT
```

```

1  NAME
2  inherits: \setupplayer
3  align = inherits: \setupalign
   width = DIMENSION
   style = STYLE COMMAND
   color = COLOR
4  TEXT

```

```
*  filler NAME
```

\* [-+] DIMENSION

```
1  NAME
2  NAME
3  inherits: \setupplayer
4  CONTENT
```

```
1  NAME
2  NAME
3  KEY  =  VALUE
```

```

1  NAME
2  NAME
3  NAME
4  KEY  =  VALUE

```



`\setMPtext {...} {...}`

- 1 NAME
- 2 TEXT

`\setMPvariable [...] [...2...]`

- 1 NAME
- 2 KEY = VALUE

`\setMPvariables [...] [...2...,...]`  
OPT

- 1 NAME
- 2 KEY = VALUE

`\setmainbodyfont`

`\setmainparbuilder [...]`

- \* default oneline basic NAME

`\setmarker [...] [...2...]`

- 1 NAME
- 2 NUMBER

`\setmarking [...] {...2...}`

- 1 MARK
- 2 TEXT

`\setmathstyle {...,*...}`

- \* display text script scriptscript cramped uncramped normal packed small big NAME

`\setmeasure {...1...} {...2...}`

- 1 NAME
- 2 DIMENSION

`\setmessagetext {...1...} {...2...}`

- 1 NAME
- 2 NAME NUMBER

`\setmode {...}`

- \* NAME

`\setnostrut`

`\setnote [...1] [...2,...] {...3...}`  
OPT

- 1 NAME
- 2 REFERENCE
- 3 TEXT

\setnotetext [<sup>1</sup>...] [<sup>2</sup>...,...<sup>2</sup>] {<sup>3</sup>...}  
OPT

- 1 NAME
- 2 REFERENCE
- 3 TEXT

\setnotetext [<sup>1</sup>...] [<sup>2</sup>...,...<sup>2</sup>...,...]

- 1 NAME
- 2 title = TEXT  
bookmark = TEXT  
list = TEXT  
reference = REFERENCE

\setnote [<sup>1</sup>...] [<sup>2</sup>...,...<sup>2</sup>...,...]

- 1 NAME
- 2 title = TEXT  
bookmark = TEXT  
list = TEXT  
reference = REFERENCE

\setobject {<sup>1</sup>...} {<sup>2</sup>...} \<sup>3</sup>... {<sup>4</sup>...}

- 1 NAME
- 2 NAME
- 3 CSNAME
- 4 CONTENT

\setoldstyle

\setpagegrid [...<sup>1</sup>...,...<sup>1</sup>...,...<sup>1</sup>...] {<sup>2</sup>...}  
OPT

- 1 c = NUMBER  
r = NUMBER  
option = none
- 2 CONTENT

\setpagereference {<sup>1</sup>...} {<sup>2</sup>...,...}

- 1 NAME
- 2 REFERENCE

\setpagestate [<sup>1</sup>...] [<sup>2</sup>...]  
OPT

- 1 NAME
- 2 NAME NUMBER

\setpagestaterealpageno {<sup>1</sup>...} {<sup>2</sup>...}

- 1 NAME
- 2 NAME NUMBER

\setpenalties \<sup>1</sup>... {<sup>2</sup>...} {<sup>3</sup>...}

- 1 CSNAME
- 2 NUMBER
- 3 NUMBER

`\setpercentdimen {...} {...}`

- 1 DIMENSION CSNAME
- 2 DIMENSION NUMBER

`\setposition {...}`

- \* NAME

`\setpositionbox {...} \^ {...} {...}`

- 1 NAME
- 2 CSNAME
- 3 CONTENT

`\setpositiondata {...} {...} {...} {...}`

- 1 NAME
- 2 DIMENSION
- 3 DIMENSION
- 4 DIMENSION

`\setpositiondataplus {...} {...} {...} {...} {...,5...}`

- 1 NAME
- 2 DIMENSION
- 3 DIMENSION
- 4 DIMENSION
- 5 TEXT

`\setpositiononly {...}`

- \* NAME

`\setpositionplus {...} {...,2...} \^ {...} {...}`

- 1 NAME
- 2 TEXT
- 3 CSNAME
- 4 CONTENT

`\setpositionstrut {...}`

- \* NAME

`\setprofile [...]`

- \* none fixed strict halffixed quarterfixed eightsfixed NAME

`\setrandomseed {...}`

- \* NUMBER

`\setreference [...,1...] [...,2...,...]`

- 1 REFERENCE
- 2 KEY = VALUE

`\setreferencedobject {...} {...} \... {...}`

- 1 NAME
- 2 NAME
- 3 CSNAME
- 4 CONTENT

`\setregisterentry [...]1 [...,...2...,...]2 [...,...3...,...]3`  
OPT

- 1 NAME
- 2 label = NAME  
keys = TEXT PROCESSOR->TEXT  
entries = TEXT PROCESSOR->TEXT  
keys:1 = TEXT  
keys:2 = TEXT  
keys:3 = TEXT  
entries:1 = TEXT  
entries:2 = TEXT  
entries:3 = TEXT  
alternative = TEXT
- 3 KEY = VALUE

`\setreplacement [...]`

- \* reset NAME

`\setrigidcolumnbalance ...`

- \* CSNAME NUMBER

`\setrigidcolumnhsize {...}1 {...}2 {...}3`

- 1 DIMENSION
- 2 DIMENSION
- 3 NUMBER

`\setscript [...]`

- \* hangul hanzi nihongo ethiopic thai test NAME

`\setsectionblock [...]1 [...,...2...,...]2`  
OPT

- 1 NAME
- 2 bookmark = TEXT

`\setsimplecolumnhsize [...,...*...,...]`

- \* n = NUMBER  
width = DIMENSION  
distance = DIMENSION  
lines = NUMBER

`\setsmallbodyfont`

`\setsmallcaps`

`\setstackbox {...}1 {...}2 {...}3`

- 1 NAME
- 2 NAME
- 3 CONTENT

```

\setstructurepageregister [...] [...] [...]
                                     OPT
1  NAME
2  label      = NAME
   keys       = TEXT PROCESSOR->TEXT
   entries    = TEXT PROCESSOR->TEXT
   keys:1     = TEXT
   keys:2     = TEXT
   keys:3     = TEXT
   entries:1  = TEXT
   entries:2  = TEXT
   entries:3  = TEXT
   alternative = TEXT
3  KEY = VALUE

```

```

\setstrut

```

```

\setsuperiors

```

```

\setsystemmode {...}

```

```

*  NAME

```

```

\settabular

```

```

\settaggedmetadata [...] [...]

```

```

*  KEY = VALUE

```

```

\settextcontent [...] [...] [...] [...] [...]
                                     OPT      OPT

```

```

1  top header text footer bottom
2  text margin edge
3  left middle right
4  date pagenumber MARK TEXT COMMAND
5  date pagenumber MARK TEXT COMMAND

```

```

\settightobject {...} {...} \... {...}

```

```

1  NAME
2  NAME
3  CSNAME
4  CONTENT

```

```

\settightreferencedobject {...} {...} \... {...}

```

```

1  NAME
2  NAME
3  CSNAME
4  CONTENT

```

```

\settightunreferencedobject {...} {...} \... {...}

```

```

1  NAME
2  NAME
3  CSNAME
4  CONTENT

```

```

\settrialtypesetting

```

`\setuevalue {...} {...}`

- 1 NAME
- 2 CONTENT

`\setugvalue {...} {...}`

- 1 NAME
- 2 CONTENT

`\setunreferencedobject {...} {...} \... {...}`

- 1 NAME
- 2 NAME
- 3 CSNAME
- 4 CONTENT

`\setup [...]`

- \* NAME

`\setupalign [...,*,...]`

- \* broad wide bottom height line high low lohi flushright flushleft middle yes no width normal reset inner outer  
flushinner flushouter left right center disable last end paragraph lefttoright righttoleft l2r r2l table lessshyphenation  
morehyphenation hanging nothanging hz fullhz nohz hyphenated nothyphenated tolerant verytolerant stretch extremestretch  
final 2\*final 3\*final 4\*final

`\setuparranging [...,*,...]`

- \* disable mirrored doublesided negative 90 180 270 reset background normal 2\*16 2\*8 2\*4 2\*2 2\*\*2 2SIDE 2TOP 2UP  
2DOWN 2\*4\*2 2\*2\*4 2TOPSIDE 2\*8\*Z 2\*6\*Z 1\*8 1\*4 3SIDE TRYPTICHON ZFLYER-8 ZFLYER-10 ZFLYER-12 MAPFLYER-12 DOUBLEWINDOW  
1\*2-Conference 1\*4-Conference 2\*2\*2 2\*2\*3 XY NAME

`\setupattachment [...,1...] [...,2...,...]`  
OPT

- 1 NAME
- 2 title = TEXT  
subtitle = TEXT  
author = TEXT  
file = FILE  
name = NAME  
buffer = BUFFER  
state = start stop  
method = normal hidden  
symbol = Graph Paperclip Pushpin Default  
width = fit DIMENSION  
height = fit DIMENSION  
depth = fit DIMENSION  
color = COLOR  
textlayer = NAME  
location = leftedge rightedge inmargin leftmargin rightmargin text high none  
distance = DIMENSION

`\setupattachments [...,1...] [...,2...,...]`  
OPT

- 1 NAME
- 2 inherits: \setupattachment

`\setupbackend [...,..1...,...]`

\* export = yes FILE  
xhtml = FILE  
file = FILE  
intent = NAME  
space = yes no  
xmpfile = FILE  
format = version default NAME  
level = NUMBER  
option = always never  
profile = FILE

`\setupbackground [...,..1...] [...,..2...,...]`  
OPT

1 NAME  
2 state = start stop  
leftoffset = DIMENSION  
rightoffset = DIMENSION  
topoffset = DIMENSION  
bottomoffset = DIMENSION  
before = COMMAND  
after = COMMAND  
inherits: \setupframed

`\setupbackgrounds [...,..1...] [...,..2...] [...,..3...,...]`  
OPT

1 top header text footer bottom  
2 leftedge leftmargin text rightmargin rightedge  
3 inherits: \setupframed

`\setupbackgrounds [...,..1...] [...,..2...,...]`  
OPT

1 paper page leftpage rightpage text hidden  
2 state = start stop  
inherits: \setupframed

`\setupbar [...,..1...] [...,..2...,...]`  
OPT

1 NAME  
2 color = COLOR  
continue = yes no all  
empty = yes no  
unit = ex em pt in cm mm sp bp pc dd cc nc  
order = foreground background  
rulethickness = DIMENSION  
method = NUMBER  
offset = NUMBER  
dy = NUMBER  
max = NUMBER  
foregroundstyle = STYLE COMMAND  
foregroundcolor = COLOR  
mp = NAME  
left = TEXT  
right = TEXT

`\setupbars [...,..1...] [...,..2...,...]`  
OPT

1 NAME  
2 inherits: \setupbar

`\hiddenbar {...}`

\* CONTENT

`\nobar {...}`

\* CONTENT

$$\overline{\{...\}^*}$$

\* CONTENT

$$\overline{\{...\}}$$

\* CONTENT

$$\overline{\{...\}}$$

\* CONTENT

$$\overstruck{\dots}$$

\* CONTENT

$$\underline{\{...\}^*}$$

\* CONTENT

$$\backslash\underbars \{...\}$$

\* CONTENT

 $\underdash \{...\}$ 

\* CONTENT

`\underdashes {...}`

\* CONTENT

 $\underset{\cdot}{\cdot}\{...\}$ 

\* CONTENT

 $\underset{\cdot}{\cdot} \{.\dots\}$ 

\* CONTENT

 $\text{\textit{\textbackslash underrandom}} \{...\}$ 

\* CONTENT

 $\underset{\text{randoms}}{\{...\}}$ 

\* CONTENT

`\underline {...}`

\* CONTENT

`\understrikes {...}`

\* CONTENT



`\setupblackrules [...,.*=.,...]`

\* width = max DIMENSION  
height = max DIMENSION  
depth = max DIMENSION  
distance = DIMENSION  
n = NUMBER  
alternative = a b  
style = STYLE COMMAND  
color = COLOR  
type = mp yes no  
mp = NAME

`\setupblank [...,*,...]`

OPT

\* inherits: \vspacing

`\setupbleeding [...,.*=.,...]`

\* width = DIMENSION  
height = DIMENSION  
offset = DIMENSION  
hoffset = DIMENSION  
voffset = DIMENSION  
location = t b l r bl lb br rb tl lt tr rt  
stretch = yes no  
page = yes no

`\setupblock [...,1...] [...,.*2=.,...]`

OPT

1 NAME  
2 before = COMMAND  
after = COMMAND  
inner = COMMAND  
style = STYLE COMMAND  
color = COLOR

`\setupbodyfont [...,*,...]`

OPT

\* DIMENSION NAME global reset x xx small big script scriptscript rm ss tt hw cg roman serif regular sans sansserif support type teletype mono handwritten calligraphic

`\setupbookmark [...,.*=.,...]`

\* force = yes no  
number = yes no  
numberseparatorset = NAME  
numberconversionset = NAME  
numberstarter = COMMAND  
numberstopper = COMMAND  
numbersegments = NUMBER NUMBER:NUMBER NUMBER:\* NUMBER:all SECTION SECTION:SECTION SECTION:\* SECTION:all  
sectionblock = yes no

`\setupbottom [...,1...] [...,.*2=.,...]`

OPT

1 text margin edge  
2 inherits: \setuplayoutelement

`\setupbottomtexts [...,1...] [...,2...] [...,3...] [...,4...] [...,5...]`

OPT

OPT

OPT

OPT

OPT

1 text margin edge  
2 date pagenumber MARK TEXT COMMAND  
3 date pagenumber MARK TEXT COMMAND  
4 date pagenumber MARK TEXT COMMAND  
5 date pagenumber MARK TEXT COMMAND

`\setupbtx` [<sup>1</sup>...] [<sup>2</sup>...<sub>OPT</sub>...]

```

1  NAME

2  specification = default apa aps NAME
   dataset      = default NAME
   command      = \...##1
   left         = COMMAND
   right        = COMMAND
   authorconversion = normal normalshort normalinverted invertedshort short
   etallimit     = NUMBER
   etaldisplay   = NUMBER
   etaloption    = last
   stopper       = initials
   interaction    = start stop all
   alternative    = default category entry short page num textnum year index tag keywords author authoryears
                   authornum authoryear
   sorttype      = normal reverse
   compress      = yes no
   default       = default NAME
   style         = STYLE COMMAND
   color         = COLOR

```

`\setupbtxdataset` [<sup>1</sup>...] [<sup>2</sup>...<sub>OPT</sub>...]

```

1  NAME

2  language = LANGUAGE

```

`\setupbtxlist` [<sup>1</sup>...] [<sup>2</sup>...<sub>OPT</sub>...]

```

1  NAME

2  inherits: \setuplist

```

`\setupbtxregister` [<sup>1</sup>...] [<sup>2</sup>...<sub>OPT</sub>...]

```

1  NAME

2  state      = start stop
   dataset    = NAME
   field      = keyword range pagenumber author
   register    = NAME
   method     = once
   alternative = normalshort invertedshort
   style      = STYLE COMMAND
   color      = COLOR

```

`\setupbtxrendering` [<sup>1</sup>...] [<sup>2</sup>...<sub>OPT</sub>...]

```

1  NAME

2  textstate    = start stop
   pagestate    = start stop
   separator    = COMMAND
   criterium     = previous cite here all none
   specification = NAME
   title        = TEXT
   before       = COMMAND
   after        = COMMAND
   dataset      = NAME
   method       = dataset force local global none
   sorttype     = short dataset list reference used default cite index
   repeat       = yes no
   group        = NAME
   numbering    = yes no num index tag short page

```

`\setupbtx` [...]

```

*  NAME

```

`\setupbuffer [...1,...] [...2,...]`  
OPT

- 1 BUFFER
- 2 before = COMMAND  
after = COMMAND

`\setupbutton [...1,...] [...2,...]`  
OPT

- 1 NAME
- 2 state = start stop  
samepage = yes no empty none normal default  
style = STYLE COMMAND  
color = COLOR  
contrastcolor = COLOR  
alternative = hidden  
inherits: \setupframed

`\setupcapitals [...1,...] [...2,...]`  
OPT

- 1 NAME
- 2 title = yes no  
sc = yes no  
style = STYLE COMMAND

`\setupcaption [...1,...] [...2,...]`  
OPT

- 1 NAME
- 2 inherits: \setupfloatcaption

`\setupcaptions [...1,...] [...2,...]`  
OPT

- 1 NAME
- 2 inherits: \setupfloatcaption

`\placechemical [...1,...] [...2,...] {...3} {...4}`  
OPT OPT

- 1 split always left right inner outer backspace cutspace inleft inright inmargin leftmargin rightmargin leftedge rightedge innermargin outermargin inneredge outeredge text opposite reset height depth [-+]line halfline grid high low fit 90 180 270 nonumber none local here force margin [-+]hang hanging tall both middle offset top bottom auto page leftpage rightpage somewhere effective header footer
- 2 REFERENCE
- 3 TEXT
- 4 CONTENT

`\placefigure [...1,...] [...2,...] {...3} {...4}`  
OPT OPT

- 1 split always left right inner outer backspace cutspace inleft inright inmargin leftmargin rightmargin leftedge rightedge innermargin outermargin inneredge outeredge text opposite reset height depth [-+]line halfline grid high low fit 90 180 270 nonumber none local here force margin [-+]hang hanging tall both middle offset top bottom auto page leftpage rightpage somewhere effective header footer
- 2 REFERENCE
- 3 TEXT
- 4 CONTENT

`\placegraphic [...1,...] [...2,...] {...3} {...4}`  
OPT OPT

- 1 split always left right inner outer backspace cutspace inleft inright inmargin leftmargin rightmargin leftedge rightedge innermargin outermargin inneredge outeredge text opposite reset height depth [-+]line halfline grid high low fit 90 180 270 nonumber none local here force margin [-+]hang hanging tall both middle offset top bottom auto page leftpage rightpage somewhere effective header footer
- 2 REFERENCE
- 3 TEXT
- 4 CONTENT

`\placeintermezzo [...1,...] [...2,...] {...3} {...4}`  
OPT OPT

1 split always left right inner outer backspace cutspace inleft inright inmargin leftmargin rightmargin leftedge  
 rightedge innermargin outermargin inneredge outeredge text opposite reset height depth [-+]line halfline grid high  
 low fit 90 180 270 nonumber none local here force margin [-+]hang hanging tall both middle offset top bottom auto  
 page leftpage rightpage somewhere effective header footer

2 REFERENCE

3 TEXT

4 CONTENT

`\placetable [...1,...] [...2,...] {...3} {...4}`  
OPT OPT

1 split always left right inner outer backspace cutspace inleft inright inmargin leftmargin rightmargin leftedge  
 rightedge innermargin outermargin inneredge outeredge text opposite reset height depth [-+]line halfline grid high  
 low fit 90 180 270 nonumber none local here force margin [-+]hang hanging tall both middle offset top bottom auto  
 page leftpage rightpage somewhere effective header footer

2 REFERENCE

3 TEXT

4 CONTENT

`\setupcharacterkerning [...1,...] [...2,...]`  
OPT

1 NAME

2 factor = max NUMBER  
 width = DIMENSION  
 features = NAME  
 style = STYLE COMMAND  
 color = COLOR

`\setupcharacterspacing [...1.] [...2.] [...3,...]`  
OPT

1 NAME

2 NUMBER

3 left = NUMBER  
 right = NUMBER  
 alternative = 0 1

`\setupchemical [...1,...] [...2,...]`  
OPT

1 NAME

2 strut = yes no auto cap fit line default CHARACTER  
 width = fit none NUMBER  
 height = fit none NUMBER  
 left = fit none NUMBER  
 right = fit none NUMBER  
 top = fit none NUMBER  
 bottom = fit none NUMBER  
 scale = small medium big normal NUMBER  
 rotation = NUMBER  
 symalign = auto  
 axis = on off  
 framecolor = COLOR  
 rulethickness = DIMENSION  
 offset = DIMENSION  
 unit = DIMENSION  
 factor = NUMBER  
 frame = on off  
 rulecolor = COLOR  
 bodyfont = inherits: \setupbodyfont  
 size = small medium big  
 style = STYLE COMMAND  
 color = COLOR

`\setupchemicalframed [...1,...] [...2,...]`  
OPT

1 NAME

2 inherits: \setupframed

\setupclipping [...,\*...]

```
* state      = start stop
width        = DIMENSION
height       = DIMENSION
hoffset      = DIMENSION
voffset      = DIMENSION
x            = NUMBER
y            = NUMBER
nx           = NUMBER
ny           = NUMBER
sx           = NUMBER
sy           = NUMBER
leftoffset   = DIMENSION
rightoffset  = DIMENSION
topoffset    = DIMENSION
bottomoffset = DIMENSION
mp           = NAME
n            = NUMBER
offset       = DIMENSION
```

\setupcollector [...,<sup>1</sup>...] [...,<sup>2</sup>...]
OPT

```
1 NAME

2 rotation = left right inner outer NUMBER
corner     = left middle right top bottom
x          = DIMENSION
y          = DIMENSION
hoffset    = DIMENSION
voffset    = DIMENSION
location   = left middle right top bottom line l c r m t b g
state      = start stop
```

\setupcolor [...]

```
* FILE
```

\setupcolors [...,\*...]

```
* state      = start stop
spot         = yes no
expansion    = yes no
factor       = yes no
rgb          = yes no
cmym         = yes no
conversion   = yes no always
pagecolormodel = auto none NAME
textcolor    = COLOR
intent       = overprint knockout none
```

\setupcolumns [...,\*...]

```
* n          = NUMBER
distance     = DIMENSION
option       = background
offset       = DIMENSION
command      = \...##1
height       = DIMENSION
direction    = left right
balance      = yes no
align        = setupalign
tolerance    = setuptolerance
blank        = inherits: \blank
ntop         = NUMBER
rule         = on off COMMAND
```

\setupcolumnspan [...,\*...]

```
* n = NUMBER
inherits: \setupframed
```

`\setupcombination` [<sup>1</sup>...]<sub>OPT</sub> [<sup>2</sup>...<sub>...</sub>]

```

1  NAME

2  nx      = NUMBER
   ny      = NUMBER
   width   = fit DIMENSION
   height  = fit DIMENSION
   location = left middle right top bottom
   distance = DIMENSION
   alternative = label text
   align    = inherits: \setupalign
   continue = yes no
   before   = COMMAND
   after    = COMMAND
   inbetween = COMMAND
   style    = STYLE COMMAND
   color    = COLOR

```

`\setupcombinedlist` [<sup>1</sup>...]<sub>OPT</sub> [<sup>2</sup>...<sub>...</sub>]

```

1  LIST

2  inherits: \setuplist

```

`\setupCOMBINEDLIST` [<sup>\*</sup>...<sub>...</sub>]

\* inherits: \setuplist

instances: content

`\placecontent` [<sup>\*</sup>...<sub>OPT</sub>...]

\* inherits: \setuplist

`\setupcomment` [<sup>1</sup>...]<sub>OPT</sub> [<sup>2</sup>...<sub>...</sub>]

```

1  NAME

2  state      = start stop none
   method     = normal hidden
   symbol      = Comment Help Insert Key Newparagraph Note Paragraph Default
   width       = fit DIMENSION
   height      = fit DIMENSION
   depth       = fit DIMENSION
   title       = TEXT
   subtitle    = TEXT
   author      = TEXT
   nx          = NUMBER
   ny          = NUMBER
   color       = COLOR
   option      = xml max
   textlayer   = NAME
   location    = leftedge rightedge inmargin leftmargin rightmargin text high none
   distance    = DIMENSION
   space       = yes
   buffer      = BUFFER

```

`\comment` [<sup>1</sup>...]<sub>OPT</sub> [<sup>2</sup>...<sub>OPT</sub>...]<sub>OPT</sub> {...<sup>3</sup>}

```

1  TEXT

2  inherits: \setupcomment

3  TEXT

```

`\setupcounter [...1,...] [...2,...]`  
OPT

1 NAME

2 start = NUMBER  
counter = NAME  
method = page  
state = start stop  
way = bypage byblock bytext byhead bySECTION  
prefix = yes no  
prefixseparatorset = NAME  
prefixconversion = NAME  
prefixconversionset = NAME  
prefixstarter = COMMAND PROCESSOR->COMMAND  
prefixstopper = COMMAND PROCESSOR->COMMAND  
prefixset = NAME  
prefixsegments = NUMBER NUMBER:NUMBER NUMBER:\* NUMBER:all SECTION SECTION:SECTION SECTION:\* SECTION:all  
numberorder = reverse  
numberseparatorset = NAME  
numberconversion = NAME  
numberconversionset = NAME  
numberstarter = COMMAND PROCESSOR->COMMAND  
numberstopper = COMMAND PROCESSOR->COMMAND  
numbersegments = NUMBER NUMBER:NUMBER NUMBER:\* NUMBER:all  
type = first previous next last number  
criterium = strict positive all  
prefixconnector = COMMAND PROCESSOR->COMMAND

`\setupdataset [...1,...] [...2,...]`  
OPT

1 NAME

2 delay = yes no

`\setupdelimitedtext [...1,...] [...2,...]`  
OPT

1 NAME

2 before = COMMAND  
after = COMMAND  
language = local global LANGUAGE  
method = font  
repeat = yes no  
location = text paragraph margin  
left = COMMAND  
middle = COMMAND  
right = COMMAND  
nextleft = COMMAND  
nextright = COMMAND  
spacebefore = inherits: \blank  
spaceafter = inherits: \blank  
leftmargin = yes no standard DIMENSION  
rightmargin = yes no standard DIMENSION  
indenting = inherits: \setupindenting  
indentnext = yes no auto  
style = STYLE COMMAND  
color = COLOR  
symstyle = STYLE COMMAND  
symcolor = COLOR

`\aside [...1] {...2}`  
OPT

1 LANGUAGE

2 CONTENT

`\blockquote [...1] {...2}`  
OPT

1 LANGUAGE

2 CONTENT

`\quotation [...1] {...2}`  
OPT

1 LANGUAGE

2 CONTENT

`\quote [...]1 {...}2`

1 LANGUAGE

2 CONTENT

`\speech [...]1 {...}2`

1 LANGUAGE

2 CONTENT

`\setupdescription [...]1,...2 [...],...2,...]`

1 NAME

2 title = yes no  
level = NUMBER  
text = TEXT  
headcommand = \...##1  
before = COMMAND  
after = COMMAND  
inbetween = COMMAND  
alternative = left right inmargin inleft inright margin leftmargin rightmargin innermargin outermargin  
serried hanging top command NAME  
align = inherits: \setupalign  
headalign = inherits: \setupalign  
indenting = inherits: \setupindenting  
display = yes no  
indentnext = yes no auto  
width = fit broad line DIMENSION  
distance = none DIMENSION  
hang = fit broad none margin NUMBER  
closesymbol = COMMAND  
closecommand = \...##1  
expansion = yes no xml  
referenceprefix = + - TEXT  
sample = TEXT  
margin = yes no standard DIMENSION  
style = STYLE COMMAND  
color = COLOR  
headstyle = STYLE COMMAND  
headcolor = COLOR

`\setupdirections [...],...*,...]`

\* bidi = on off local global  
method = one two default  
fences = yes no

`\setupdocument [...],...*,...]`

\* before = COMMAND  
after = COMMAND  
metadata:author = TEXT  
metadata:title = TEXT  
metadata:subject = TEXT  
metadata:keywords = TEXT  
KEY = VALUE

`\setupeffect [...]1,...2 [...],...2,...]`

1 NAME

2 method = none command  
stretch = NUMBER  
rulethickness = NUMBER  
alternative = normal inner outer both hidden stretch



`\setupenumeration` [ $\dots^1, \dots$ ] [ $\dots^2, \dots$ ]  
OPT

```

1  NAME

2  title           = yes no
   number          = yes no
   numbercommand   = \...##1
   titledistance   = DIMENSION
   titlestyle      = STYLE COMMAND
   titlecolor      = COLOR
   titlecommand    = \...##1
   titleleft       = COMMAND
   titleright      = COMMAND
   left            = COMMAND
   right           = COMMAND
   symbol          = COMMAND
   starter         = COMMAND
   stopper         = COMMAND
   coupling        = NAME
   counter         = NAME
   level           = NUMBER
   text            = TEXT
   headcommand     = \...##1
   before          = COMMAND
   after           = COMMAND
   inbetween       = COMMAND
   alternative      = left right inmargin inleft inright margin leftmargin rightmargin innermargin outermargin
                     serried hanging top command NAME

   align           = inherits: \setupalign
   headalign       = inherits: \setupalign
   indenting       = inherits: \setupindenting
   display         = yes no
   indentnext      = yes no auto
   width           = fit broad line DIMENSION
   distance        = none DIMENSION
   hang            = fit broad none margin NUMBER
   closesymbol     = COMMAND
   closecommand    = \...##1
   expansion       = yes no xml
   referenceprefix = + - TEXT
   sample          = TEXT
   margin          = yes no standard DIMENSION
   style           = STYLE COMMAND
   color           = COLOR
   headstyle       = STYLE COMMAND
   headcolor       = COLOR
   inherits: \setupcounter

```

`\setupenumerations` [ $\dots^1, \dots$ ] [ $\dots^2, \dots$ ]  
OPT

```

1  NAME

2  inherits: \setupenumeration

```

`\setupenv` [ $\dots^* \dots$ ]

```

*  set    = COMMAND
   reset  = COMMAND
   KEY    = VALUE

```

`\setupexport` [ $\dots^* \dots$ ]

```

*  align      = flushleft middle flushright normal
   bodyfont   = DIMENSION
   width      = DIMENSION
   title      = TEXT
   subtitle   = TEXT
   author     = TEXT
   alternative = html div
   properties = yes no
   hyphen     = yes no
   cssfile    = FILE
   firstpage  = FILE
   lastpage   = FILE

```

`\setupexternalfigure [...,1...] [...,2...,...]`  
OPT

```

1  NAME
2  width          = DIMENSION
   height         = DIMENSION
   label          = NAME
   page           = NUMBER
   object         = yes no
   prefix         = TEXT
   method         = pdf mps jpg png jp2 jbig svg eps gif tif mov buffer tex cld auto
   controls       = yes no
   preview        = yes no
   mask           = none
   resolution     = NUMBER
   color          = COLOR
   arguments      = TEXT
   repeat         = yes no
   factor         = fit broad max auto default
   hfactor        = fit broad max auto default
   wfactor        = fit broad max auto default
   maxwidth       = DIMENSION
   maxheight      = DIMENSION
   equalwidth     = DIMENSION
   equalheight    = DIMENSION
   scale          = NUMBER
   xscale         = NUMBER
   yscale         = NUMBER
   s              = NUMBER
   sx             = NUMBER
   sy             = NUMBER
   lines          = NUMBER
   location       = local global default
   directory      = PATH
   option         = test frame empty
   foregroundcolor = COLOR
   reset          = yes no
   background     = color foreground NAME
   frame          = on off
   backgroundcolor = COLOR
   align          = inherits: \setupalign
   xmax           = NUMBER
   ymax           = NUMBER
   frames         = on off
   interaction     = yes all none reference layer bookmark
   bodyfont       = DIMENSION
   comment        = COMMAND TEXT
   size           = none media crop trim art
   cache          = PATH
   resources      = PATH
   display        = FILE
   conversion     = TEXT
   order          = LIST
   crossreference = yes no NUMBER

```

`\setupexternalsoundtracks [...,*...,...]`

\* option = repeat

`\setupfield [...,1...] [...,2...,...]`  
OPT      OPT      OPT

```

1  NAME
2  reset label frame horizontal vertical
3  inherits: \setupfieldtotalframed
4  inherits: \setupfieldlabelframed
5  inherits: \setupfieldcontentframed

```

`\setupfieldbody [...,1...] [...,2...,...]`  
OPT

```

1  NAME
2  category = NAME
   inherits: \setupfieldcategory

```

`\setupfieldcategory [...,1...] [...,2...]`  
OPT

```

1  NAME

2  start          = NUMBER
   style          = STYLE COMMAND
   color          = COLOR
   type           = radio sub text line push check signature
   values         = TEXT
   default        = TEXT
   fieldframecolor = COLOR
   fieldbackgroundcolor = COLOR
   width          = DIMENSION
   height         = DIMENSION
   depth         = DIMENSION
   align          = left middle right flushleft center flushright
   n              = NUMBER
   symbol         = NAME
   fieldlayer     = NAME
   option         = readonly required protected sorted unavailable nocheck fixed file hidden printable auto
   clickin        = REFERENCE
   clickout       = REFERENCE
   regionin       = REFERENCE
   regionout      = REFERENCE
   afterkey       = REFERENCE
   format         = REFERENCE
   validate       = REFERENCE
   calculate      = REFERENCE
   focusin        = REFERENCE
   focusout       = REFERENCE
   openpage       = REFERENCE
   closepage      = REFERENCE

```

`\setupfieldcontentframed [...,1...] [...,2...]`  
OPT

```

1  NAME

2  inherits: \setupframedinherits: \setupfieldcategory

```

`\setupfieldlabelframed [...,1...] [...,2...]`  
OPT

```

1  NAME

2  inherits: \setupframed

```

`\setupfields [...,1...] [...,2...] [...,3...] [...,4...]`  
OPT OPT OPT OPT

```

1  reset label frame horizontal vertical

2  inherits: \setupfieldtotalframed

3  inherits: \setupfieldlabelframed

4  inherits: \setupfieldcontentframed

```

`\setupfieldtotalframed [...,1...] [...,2...]`  
OPT

```

1  NAME

2  before      = COMMAND
   after       = COMMAND
   inbetween   = COMMAND
   distance    = DIMENSION
   alternative = reset label frame horizontal vertical
   inherits: \setupframed

```

`\setupfiller [...1,...] [...2,...]`  
OPT

```
1  NAME

2  leftmargin   = DIMENSION
   rightmargin  = DIMENSION
   left         = COMMAND
   right        = COMMAND
   alternative  = symbol stretch rule space
   method       = local global middle broad
   width        = DIMENSION
   height       = DIMENSION
   depth        = DIMENSION
   offset       = DIMENSION
   distance     = DIMENSION
   align        = left right middle flushleft flushright inner outer
   symbol       = COMMAND
   style        = STYLE COMMAND
   color        = COLOR
```

`\setupfillinlines [...*,...]`

```
*  before       = COMMAND
   after        = COMMAND
   margin       = DIMENSION
   width        = DIMENSION
   distance     = DIMENSION
   rulethickness = DIMENSION
   color        = COLOR
```

`\setupfillinrules [...*,...]`

```
*  before       = COMMAND
   after        = COMMAND
   n            = NUMBER
   interlinespace = small medium big NUMBER
   distance     = DIMENSION
   width        = fit broad DIMENSION
   separator    = COMMAND
   style        = STYLE COMMAND
   color        = COLOR
```

`\setupfirstline [...1,...] [...2,...]`  
OPT

```
1  NAME

2  n            = NUMBER
   alternative  = default line word
   style       = STYLE COMMAND
   color       = COLOR
```

`\setupfittingpage [...1,...] [...2,...]`  
OPT

```
1  NAME

2  pagestate   = start stop
   command     = \...##1
   margin      = page
   scale       = NUMBER
   paper       = auto default NAME
   inherits:   \setupframed
```

`\setupfloat` [<sup>1</sup>...,<sup>2</sup>...] [<sup>1</sup>...,<sup>2</sup>...,...]  
OPT

```

1  SINGULAR

2  indentnext      = yes no auto
   default         = inherits: \placefloat
   fallback        = inherits: \placefloat
   inner           = COMMAND
   criterium       = DIMENSION
   method          = NUMBER
   sidemethod      = NUMBER
   textmethod      = NUMBER
   sidealign       = height depth line halfline grid normal
   grid            = CD:STRING
   local           = yes no
   command         = \...##1
   availablewidth  = DIMENSION
   availableheight = DIMENSION
   minwidth        = DIMENSION
   maxwidth        = DIMENSION
   location        = left right middle flushleft flushright center max inner outer innermargin outermargin
                   inneredge outeredge backspace cutspace leftmargin rightmargin leftedge rightedge

   leftmargindistance = DIMENSION
   rightmargindistance = DIMENSION
   leftmargin         = DIMENSION
   rightmargin        = DIMENSION
   innermargin        = DIMENSION
   outermargin        = DIMENSION
   bottombefore       = COMMAND
   bottomafter        = COMMAND
   expansion          = yes no xml
   referenceprefix    = + - TEXT
   xmlsetup           = NAME
   catcodes           = NAME
   freeregion         = yes no
   spacebefore        = none inherits: \blank
   spaceafter         = none inherits: \blank
   width              = DIMENSION
   height             = DIMENSION
   offset             = DIMENSION none overlay
   sidespacebefore    = none inherits: \blank
   sidespaceafter     = none inherits: \blank
   margin             = DIMENSION
   ntop               = DIMENSION
   nbottom            = DIMENSION
   step              = small medium big line depth
   nlines             = NUMBER
   cache              = yes no

```

`\setupfloatcaption` [<sup>1</sup>...,<sup>2</sup>...] [<sup>1</sup>...,<sup>2</sup>...,...]  
OPT

```

1  NAME

2  suffix          = COMMAND
   suffixseparator = COMMAND
   suffixstopper   = COMMAND
   location        = left right middle low high grid overlay inner outer innermargin outermargin leftmargin rightmargin
                   lefthanging righthanging hang top bottom stretch none default

   command         = \...##1
   numbercommand    = \...##1
   textcommand      = \...##1
   spacebefore      = inherits: \blank
   spaceinbetween   = inherits: \blank
   spaceafter       = inherits: \blank
   distance         = DIMENSION
   inbetween        = COMMAND
   style            = STYLE COMMAND
   color            = COLOR
   topoffset        = DIMENSION
   bottomoffset     = DIMENSION
   number           = yes no none
   group            = TEXT
   leftmargin       = DIMENSION
   rightmargin      = DIMENSION
   innermargin      = DIMENSION
   outermargin      = DIMENSION
   align            = inherits: \setupalign
   width            = fit max DIMENSION
   minwidth         = fit DIMENSION
   maxwidth         = DIMENSION
   inherits: \setupcounter

```

```
\setupfloats [...1,...] [...2...,...]
                        OPT
```

```
1 SINGULAR
```

```
2 inherits: \setupfloat
```

```
\setupfloatsplitting [...*...,...]
```

```
* before      = COMMAND
  after       = COMMAND
  inbetween   = COMMAND
  lines       = auto NUMBER
  conversion  = NAME
```

```
\setupfontexpansion [...1.] [...2...,...]
```

```
1 NAME
```

```
2 vector      = NAME
  factor      = NUMBER
  stretch    = NUMBER
  shrink      = NUMBER
  step        = NUMBER
```

```
\setupfontprotrusion [...1.] [...2...,...]
```

```
1 NAME
```

```
2 vector      = NAME
  factor      = NUMBER
  left        = NUMBER
  right       = NUMBER
```

```
\setupfonts [...*...,...]
```

```
* language    = no auto
```

```
\setupfontsolution [...1,...] [...2...,...]
                        OPT
```

```
1 NAME
```

```
2 goodies      = FILE
  solution     = NAME
  less         = NAME
  more         = NAME
  method       = preroll split normal reverse random
  criterium    = NUMBER
```

```
\setupfooter [...1.] [...2...,...]
                        OPT
```

```
1 text margin edge
```

```
2 inherits: \setuplayoutelement
```

```
\setupfootertexts [...1.] [...2.] [...3.] [...4.] [...5.]
                        OPT      OPT      OPT      OPT      OPT
```

```
1 text margin edge
```

```
2 date pagenumber MARK TEXT COMMAND
```

```
3 date pagenumber MARK TEXT COMMAND
```

```
4 date pagenumber MARK TEXT COMMAND
```

```
5 date pagenumber MARK TEXT COMMAND
```

```
\setupforms [...*...,...]
```

```
* method      = XML HTML PDF
  export       = yes no
```

`\setupformula [...1,...] [...2...,...]`  
OPT

```

1  NAME

2  location      = left right
   align         = left middle right flushleft center flushright normal
   strut         = yes no
   distance      = DIMENSION
   left          = COMMAND
   right         = COMMAND
   spacebefore   = inherits: \blank
   spaceafter    = inherits: \blank
   numbercommand = \...##1
   color         = COLOR
   numberstyle   = STYLE COMMAND
   numbercolor   = COLOR
   option        = packed tight middle frame inherits: \setupbodyfont
   margin        = yes no standard DIMENSION
   leftmargin    = DIMENSION
   rightmargin   = DIMENSION
   alternative   = NAME
   indentnext    = yes no auto
   grid          = inherits: \suptogrid
   frame         = number
   expansion     = yes no xml
   referenceprefix = + - TEXT
   xmlsetup      = NAME
   catcodes      = NAME
   inherits: \setupcounter

```

`\setupformulaframed [...1,...] [...2...,...]`  
OPT

```

1  NAME

2  inherits: \setupframed

```

`\setupformulas [...1,...] [...2...,...]`  
OPT

```

1  NAME

2  inherits: \setupformula

```

`\setupframed [...1,...] [...2...,...]`  
OPT

```

1  NAME

2  corner          = rectangular round NUMBER
   framecorner     = rectangular round NUMBER
   backgroundcorner = rectangular round NUMBER
   radius          = DIMENSION
   frameradius     = DIMENSION
   backgroundradius = DIMENSION
   depth          = DIMENSION
   frameddepth     = DIMENSION
   backgrounddepth = DIMENSION
   framecolor      = COLOR
   topframe        = on off NAME
   bottomframe     = on off NAME
   leftframe       = on off NAME
   rightframe      = on off NAME
   region          = yes no
   rulethickness   = DIMENSION
   frameoffset     = DIMENSION
   frame           = on off overlay none
   background      = foreground color NAME
   backgroundoffset = frame DIMENSION
   component       = NAME
   extras          = COMMAND
   foregroundstyle  = STYLE COMMAND
   foregroundcolor  = COLOR
   setups          = NAME
   offset          = default overlay none DIMENSION
   width           = local fit max broad fixed DIMENSION
   height          = fit max broad DIMENSION
   align           = inherits: \setupalign
   strut           = yes no none local global
   autostrut       = yes no
   location        = height depth high low top middle bottom line lohi hanging keep formula mathematics normal
   autowidth       = yes no force
   lines           = NUMBER
   top             = COMMAND
   bottom          = COMMAND
   blank           = yes no
   profile         = NAME
   empty           = yes no
   loffset         = DIMENSION
   roffset         = DIMENSION
   toffset         = DIMENSION
   boffset         = DIMENSION
   orientation     = NUMBER

```

`\setupframedcontent [...1,...] [...2...,...]`  
OPT

```

1  NAME

2  left            = COMMAND
   right           = COMMAND
   leftoffset      = DIMENSION
   rightoffset     = DIMENSION
   topoffset       = DIMENSION
   bottomoffset    = DIMENSION
   linecorrection  = yes no
   inherits: \setupframed

```

`\setupframedtext [...1,...] [...2...,...]`  
OPT

```

1  NAME

2  left            = COMMAND
   right           = COMMAND
   inner           = COMMAND
   location        = left right middle none
   depthcorrection = on off
   bodyfont        = inherits: \setupbodyfont
   indenting       = inherits: \setupindenting
   style           = STYLE COMMAND
   color           = COLOR
   inherits: \setupframed inherits: \setupplacement

```



`\setupframedtexts [...,1...] [...,2...]`  
OPT

1 NAME

2 inherits: \setupframedtext

`\framedtext [...,1...] {...}`  
OPT

1 inherits: \setupframedtext

2 CONTENT

`\setupglobalreferenceprefix [...]`

\* + - TEXT

\setuphead [...<sup>1</sup>,...] [...<sup>2</sup>,...]  
OPT

```

1 SECTION
2 frontpartlabel      = NAME
  bodypartlabel       = NAME
  appendixlabel       = NAME
  backpartlabel       = NAME
  expansion           = yes no xml
  catcodes            = NAME
  sectionresetset     = NAME
  sectionseparatorset = NAME
  sectionconversionset = NAME
  conversion          = NAME
  sectionstarter      = COMMAND PROCESSOR->COMMAND
  sectionstopper      = COMMAND PROCESSOR->COMMAND
  sectionset          = NAME
  sectionsegments     = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:all SECTION SECTION:SECTION SECTION:* SECTION:all
  referenceprefix     = + - TEXT
  style               = STYLE COMMAND
  color               = COLOR
  textstyle           = STYLE COMMAND
  textcolor           = COLOR
  numberstyle         = STYLE COMMAND
  numbercolor         = COLOR
  coupling            = SECTION
  ownnumber           = yes no
  beforesection       = COMMAND
  aftersection        = COMMAND
  insidesection       = COMMAND
  incrementnumber     = yes no list empty
  placehead           = yes no hidden empty
  number              = yes no
  page                = inherits: \page
  marking             = page reset
  header              = start stop high none normal empty nomarking NAME
  text                = start stop high none normal empty nomarking NAME
  footer              = start stop high none normal empty nomarking NAME
  before              = COMMAND
  after               = COMMAND
  inbetween           = COMMAND
  continue            = yes no
  aligntitle          = yes no float
  interlinespace      = NAME
  interaction         = list reference
  internalgrid        = NAME
  grid                = normal standard yes strict tolerant top bottom both broad fit first last high one low
                        none line strut box min max middle NAME
  align               = inherits: \setupalign
  tolerance           = inherits: \setuptolerance
  strut               = yes no
  hang                = line broad fit none NUMBER
  margin              = DIMENSION
  indentnext          = yes no auto
  alternative         = text paragraph normal margin inmargin top middle bottom reverse margintext NAME
  width               = DIMENSION
  numberwidth         = DIMENSION
  textwidth           = DIMENSION
  distance            = DIMENSION
  textdistance        = DIMENSION
  commandbefore       = COMMAND
  commandafter        = COMMAND
  command             = \...##1##2
  textcommand         = \...##1
  deeptextcommand     = \...##1
  numbercommand       = \...##1
  deepnumbercommand   = \...##1
  location            = NAME

```

\setupheadalternative [...<sup>1</sup>,...] [...<sup>2</sup>,...]  
OPT

```

1 NAME
2 alternative = horizontal vertical somewhere
  renderingsetup = NAME

```

`\setupheader [...]1 [...,...2...,...]`  
OPT

1 text margin edge

2 inherits: \setuplayoutelement

`\setupheadertexts [...]1 [...]2 [...]3 [...]4 [...]5`  
OPT OPT OPT OPT OPT

1 text margin edge

2 date pagenumber MARK TEXT COMMAND

3 date pagenumber MARK TEXT COMMAND

4 date pagenumber MARK TEXT COMMAND

5 date pagenumber MARK TEXT COMMAND

`\setupheadnumber [...]1 [...]2`

1 SECTION

2 [-+]NUMBER

`\setupheads [...]1,... [...,...2...,...]`  
OPT

1 SECTION

2 inherits: \setuphead

`\chapter [...]1,... {...}2`  
OPT

1 REFERENCE

2 TEXT

`\part [...]1,... {...}2`  
OPT

1 REFERENCE

2 TEXT

`\section [...]1,... {...}2`  
OPT

1 REFERENCE

2 TEXT

`\subject [...]1,... {...}2`  
OPT

1 REFERENCE

2 TEXT

`\subsection [...]1,... {...}2`  
OPT

1 REFERENCE

2 TEXT

`\subsubject [...]1,... {...}2`  
OPT

1 REFERENCE

2 TEXT

`\subsubsection [...]1,... {...}2`  
OPT

1 REFERENCE

2 TEXT

$\backslash\text{subsubsubject} [\dots,\overset{1}{\dots}] \{\overset{2}{\dots}\}$ $\text{OPT}$ <p>1    REFERENCE</p> <p>2    TEXT</p>
$\backslash\text{subsubsubsection} [\dots,\overset{1}{\dots}] \{\overset{2}{\dots}\}$ $\text{OPT}$ <p>1    REFERENCE</p> <p>2    TEXT</p>
$\backslash\text{subsubsubsubject} [\dots,\overset{1}{\dots}] \{\overset{2}{\dots}\}$ $\text{OPT}$ <p>1    REFERENCE</p> <p>2    TEXT</p>
$\backslash\text{subsubsubsubsection} [\dots,\overset{1}{\dots}] \{\overset{2}{\dots}\}$ $\text{OPT}$ <p>1    REFERENCE</p> <p>2    TEXT</p>
$\backslash\text{subsubsubsubsubject} [\dots,\overset{1}{\dots}] \{\overset{2}{\dots}\}$ $\text{OPT}$ <p>1    REFERENCE</p> <p>2    TEXT</p>
$\backslash\text{title} [\dots,\overset{1}{\dots}] \{\overset{2}{\dots}\}$ $\text{OPT}$ <p>1    REFERENCE</p> <p>2    TEXT</p>
$\backslash\text{setuphelp} [\dots,\overset{1}{\dots}] [\dots,\overset{2}{\dots},\dots]$ $\text{OPT}$ <p>1    NAME</p> <p>2    inherits: \setupframed</p>
$\backslash\text{helptext} [\overset{1}{\dots}] \{\overset{2}{\dots}\} \{\overset{3}{\dots}\}$ $\text{OPT}$ <p>1    REFERENCE</p> <p>2    TEXT</p> <p>3    TEXT</p>
$\backslash\text{setuphigh} [\dots,\overset{1}{\dots}] [\dots,\overset{2}{\dots},\dots]$ $\text{OPT}$ <p>1    NAME</p> <p>2    distance = DIMENSION</p> <p>      up     = DIMENSION</p> <p>      style  = STYLE COMMAND</p> <p>      color  = COLOR</p>
$\backslash\text{setuphighlight} [\dots,\overset{1}{\dots}] [\dots,\overset{2}{\dots},\dots]$ $\text{OPT}$ <p>1    NAME</p> <p>2    command = yes no</p> <p>      style  = STYLE COMMAND</p> <p>      color  = COLOR</p>
$\backslash\text{unitshigh} \{\overset{*}{\dots}\}$ <p>*    CONTENT</p>

`\setuphyphenation [...,.*,...]`

\* method = original tex default hyphenate expanded traditional none

`\setuphyphenmark [...,.*,...]`

\* sign = normal wide

`\setupindentedtext [...,1...] [...,..2...,...]`  
OPT

1 NAME

2 before = COMMAND  
after = COMMAND  
distance = DIMENSION  
sample = TEXT  
text = TEXT  
width = fit broad DIMENSION  
separator = COMMAND  
style = STYLE COMMAND  
color = COLOR  
headstyle = STYLE COMMAND  
headcolor = COLOR

`\setupindenting [...,*...]`  
OPT

\* [-+]small [-+]medium [-+]big none no not first next yes always never odd even normal reset toggle DIMENSION NAME

`\setupinitial [...,1...] [...,..2...,...]`  
OPT

1 NAME

2 n = NUMBER  
m = NUMBER  
before = COMMAND  
distance = DIMENSION  
hoffset = DIMENSION  
voffset = line DIMENSION  
style = STYLE COMMAND  
color = COLOR  
font = FONT  
text = TEXT  
location = margin text  
method = first last auto none

`\setupinsertion [...,1...] [...,..2...,...]`  
OPT

1 NAME

2 location = page text columns firstcolumn lastcolumn

`\setupinteraction` [ $\dots$ , $\dots$ ]<sup>1</sup> [ $\dots$ , $\dots$ ]<sup>2</sup> $\dots$ , $\dots$ ]  
OPT

```

1  NAME

2  state      = start stop
   style      = STYLE COMMAND
   color      = COLOR
   contrastcolor = COLOR
   title      = TEXT
   subtitle   = COLOR
   author     = TEXT
   date       = TEXT
   keyword    = TEXT
   focus      = standard frame width minwidth height minheight fit tight
   menu       = on off
   fieldlayer = auto NAME
   calculate  = REFERENCE
   click      = yes no
   display    = normal new
   page       = yes no page name auto
   openaction = REFERENCE
   closeaction = REFERENCE
   openpageaction = REFERENCE
   closepageaction = REFERENCE
   symbolset  = NAME
   height     = DIMENSION
   depth      = DIMENSION
   focusoffset = DIMENSION

```

`\setupinteractionbar` [ $\dots$ , $\dots$ ]<sup>1</sup> [ $\dots$ , $\dots$ ]<sup>2</sup> $\dots$ , $\dots$ ]  
OPT

```

1  NAME

2  alternative = a b c d e f g
   state      = start stop
   command    = CSNAME
   width      = DIMENSION
   height     = DIMENSION max broad
   depth      = DIMENSION max
   distance   = DIMENSION
   step       = small medium big
   backgroundcolor = COLOR
   style      = STYLE COMMAND
   color      = COLOR
   contrastcolor = COLOR
   symbol     = yes no
   inherits: \setupframed

```

`\setupinteractionmenu` [ $\dots$ , $\dots$ ]<sup>1</sup> [ $\dots$ , $\dots$ ]<sup>2</sup> $\dots$ , $\dots$ ]  
OPT

```

1  NAME

2  alternative = vertical horizontal hidden
   category   = NAME
   leftoffset = overlay frame none default DIMENSION
   rightoffset = overlay frame none default DIMENSION
   topoffset  = overlay frame none default DIMENSION
   bottomoffset = overlay frame none default DIMENSION
   maxwidth   = DIMENSION
   maxheight  = DIMENSION
   itemalign  = left middle right flushleft flushright low high lohi
   state      = start empty local
   left       = COMMAND
   right      = COMMAND
   distance   = overlay DIMENSION
   before     = COMMAND
   after      = COMMAND
   inbetween  = COMMAND
   position   = yes no
   middle     = COMMAND
   style      = STYLE COMMAND
   color      = COLOR
   samepage   = yes no empty none normal default
   contrastcolor = COLOR
   inherits: \setupframed

```

`\setupinteractionscreen [...,*...]`

\* width = fit max tight DIMENSION  
height = fit max tight DIMENSION  
backspace = DIMENSION  
horoffset = DIMENSION  
veroffset = DIMENSION  
topspace = DIMENSION  
option = fit max singlesided doublesided bookmark auto none default fixed landscape portrait page paper  
copies = NUMBER  
delay = none NUMBER

`\setupinteraction [...]`

OPT

\* NAME

`\setupinterlinespace [...,1...] [...,2...]`

OPT

1 NAME

2 line = DIMENSION  
height = NUMBER  
depth = NUMBER  
minheight = NUMBER  
mindepth = NUMBER  
distance = DIMENSION  
top = NUMBER height  
bottom = NUMBER  
stretch = NUMBER  
shrink = NUMBER

`\setupinterlinespace [...,*...]`

OPT

\* on off reset auto small medium big NUMBER DIMENSION

`\setupinterlinespace [...]`

\* NAME

`\setupitaliccorrection [...,*...]`

\* text always global none

`\setupitemgroup` [<sup>1</sup>...] [<sup>2</sup>...,...] [<sup>3</sup>...,...] [<sup>4</sup>...,...]  
OPT OPT OPT OPT

```

1  NAME
2  each NUMBER
3  intro random continue packed autointro broad text before after nowwhite margin inmargin atmargin intext loose fit
   nofit paragraph joinedup serried stopper unpacked repeat norepeat reverse columns one two three four five six
   seven eight nine standard NUMBER*broad NUMBER*serried horizontal NAME
4  before      = COMMAND
   after       = COMMAND
   inbetween   = COMMAND
   beforehead  = COMMAND
   afterhead   = COMMAND
   lefttext    = COMMAND
   righttext   = COMMAND
   left        = COMMAND
   right       = COMMAND
   factor      = NUMBER
   step        = DIMENSION
   width       = DIMENSION
   distance    = DIMENSION
   margin      = yes no standard DIMENSION
   leftmargin  = yes no standard DIMENSION
   rightmargin = yes no standard DIMENSION
   align       = inherits: \setupalign
   indenting   = inherits: \setupindenting
   start       = NUMBER
   symalign    = left middle right flushleft center flushright
   symbol      = NAME
   n           = NUMBER
   indentnext  = yes no auto
   inner       = COMMAND
   command     = CSNAME
   items       = NUMBER
   maxwidth    = DIMENSION
   itemalign   = left right middle flushleft flushright inner outer
   alignsymbol = yes no
   textdistance = small medium big none space DIMENSION
   placestopper = yes no
   style       = STYLE COMMAND
   color       = COLOR
   headstyle   = STYLE COMMAND
   headcolor   = COLOR
   marstyle    = STYLE COMMAND
   marcolor    = COLOR
   symstyle    = STYLE COMMAND
   symcolor    = COLOR
   grid        = inherits: \definegridsnapping
   inherits: \setupcounter

```

`\setupitemgroups` [<sup>1</sup>...,...] [<sup>2</sup>...,...]  
OPT OPT

```

1  NAME NAME:NUMBER
2  inherits: \setupitemgroup

```

`\setupitemize` [<sup>1</sup>...,...] [<sup>2</sup>...,...] [<sup>3</sup>...,...]  
OPT OPT OPT

```

1  each NUMBER
2  inherits: \setupitemgroup
3  inherits: \setupitemgroup

```



`\setupitemgroup [...1,...] [...2,...]`  
OPT

```

1  NAME NAME:NUMBER

2  before      = COMMAND
   after       = COMMAND
   inbetween   = COMMAND
   beforehead  = COMMAND
   afterhead   = COMMAND
   lefttext    = COMMAND
   righttext   = COMMAND
   left        = COMMAND
   right       = COMMAND
   factor      = NUMBER
   step        = DIMENSION
   width       = DIMENSION
   distance    = DIMENSION
   option      = intro random continue packed autointro broad text before after nowwhite margin inmargin atmargin
                intext loose fit nofit paragraph joinedup serried stopper unpacked repeat norepeat reverse
                columns one two three four five six seven eight nine standard NUMBER*broad NUMBER*serried horizontal
                NAME
   margin      = yes no standard DIMENSION
   leftmargin  = yes no standard DIMENSION
   rightmargin = yes no standard DIMENSION
   align       = inherits: \setupalign
   indenting   = inherits: \setupindenting
   start       = NUMBER
   symalign    = left middle right flushleft center flushright
   symbol      = NAME
   n           = NUMBER
   indentnext  = yes no auto
   inner       = COMMAND
   command     = CSNAME
   items       = NUMBER
   maxwidth    = DIMENSION
   itemalign   = left right middle flushleft flushright inner outer
   alignsymbol = yes no
   textdistance = small medium big none space DIMENSION
   placestopper = yes no
   style       = STYLE COMMAND
   color       = COLOR
   headstyle   = STYLE COMMAND
   headcolor   = COLOR
   marstyle    = STYLE COMMAND
   marcolor    = COLOR
   symstyle    = STYLE COMMAND
   symcolor    = COLOR
   grid        = inherits: \definegridsnapping
   inherits: \setupcounter

```

`\setupITEMGROUP [...1,...] [...2,...] [...3,...]`  
OPT OPT OPT

```

1  each NUMBER

2  inherits: \setupitemgroup

3  inherits: \setupitemgroup

```

`instances: itemize`

`\setupitems [...1,...] [...2,...]`  
OPT

```

1  NAME

2  alternative = left right top bottom inmargin
   textwidth  = DIMENSION
   width      = DIMENSION
   distance   = DIMENSION
   symbol     = none NAME
   align      = left middle right flushleft flushright inner outer margin
   textalign  = left middle right flushleft flushright inner outer
   n         = NUMBER
   before     = COMMAND
   after      = COMMAND
   inbetween  = COMMAND

```

`\setuplabel [...1,...] [...2,...]`  
OPT

```

1  NAME

2  title           = yes no
   number          = yes no
   numbercommand   = \...##1
   titledistance   = DIMENSION
   titlestyle      = STYLE COMMAND
   titlecolor      = COLOR
   titlecommand    = \...##1
   titleleft       = COMMAND
   titleright      = COMMAND
   left            = COMMAND
   right           = COMMAND
   symbol          = COMMAND
   starter         = COMMAND
   stopper         = COMMAND
   coupling        = NAME
   counter         = NAME
   level           = NUMBER
   text            = TEXT
   headcommand     = \...##1
   before          = COMMAND
   after           = COMMAND
   inbetween       = COMMAND
   alternative      = left right inmargin inleft inright margin leftmargin rightmargin innermargin outermargin
                     serried hanging top command intext NAME

   align           = inherits: \setupalign
   headalign        = inherits: \setupalign
   indenting        = inherits: \setupindenting
   display          = yes no
   indentnext       = yes no auto
   width            = fit broad line DIMENSION
   distance         = none DIMENSION
   hang            = fit broad none margin NUMBER
   closesymbol      = COMMAND
   closecommand     = \...##1
   expansion        = yes no xml
   referenceprefix  = + - TEXT
   sample          = TEXT
   margin           = yes no standard DIMENSION
   style            = STYLE COMMAND
   color            = COLOR
   headstyle        = STYLE COMMAND
   headcolor        = COLOR
   inherits: \setupcounter

```

`\setupLABELtext [...1] [...2,...]`  
OPT

```

1  LANGUAGE

2  KEY = VALUE

```

instances: head label mathlabel taglabel unit operator prefix suffix btxlabel

`\presetbtxlabeltext [...1] [...2,...]`  
OPT

```

1  LANGUAGE

2  KEY = VALUE

```

`\presetheadtext [...1] [...2,...]`  
OPT

```

1  LANGUAGE

2  KEY = VALUE

```

`\presetlabeltext [...1] [...2,...]`  
OPT

```

1  LANGUAGE

2  KEY = VALUE

```

```
\presetmathlabeltext [...]1 [...,...2...,...]OPT

1 LANGUAGE
2 KEY = VALUE
```

```
\presetoperatortext [...]1 [...,...2...,...]OPT

1 LANGUAGE
2 KEY = VALUE
```

```
\presetprefixtext [...]1 [...,...2...,...]OPT

1 LANGUAGE
2 KEY = VALUE
```

```
\presetsuffixtext [...]1 [...,...2...,...]OPT

1 LANGUAGE
2 KEY = VALUE
```

```
\presettaglabeltext [...]1 [...,...2...,...]OPT

1 LANGUAGE
2 KEY = VALUE
```

```
\presetunittext [...]1 [...,...2...,...]OPT

1 LANGUAGE
2 KEY = VALUE
```

```
\setuplanguage [...]1 [...,...2...,...]OPT

1 LANGUAGE default
2 default = LANGUAGE
state = start stop
date = inherits: \currentdate
patterns = FILE
lefthyphenmin = NUMBER
righthyphenmin = NUMBER
lefthyphenchar = NUMBER
righthyphenchar = NUMBER
setups = NAME
spacing = broad packed
font = auto
text = TEXT
limittext = TEXT
hyphen = TEXT
compoundhyphen = TEXT
leftcompoundhyphen = TEXT
rightcompoundhyphen = TEXT
leftquote = COMMAND
rightquote = COMMAND
leftquotation = COMMAND
rightquotation = COMMAND
leftspeech = COMMAND
rightspeech = COMMAND
leftsentence = COMMAND
middlespeech = COMMAND
rightsentence = COMMAND
midsentence = COMMAND
leftsubsentence = COMMAND
rightsubsentence = COMMAND
factor = yes no
```

`\setuplayer [...1,...] [...2,...]`  
OPT

```

1  NAME

2  state      = start stop continue next repeat
   option     = test
   page       = NUMBER
   width      = DIMENSION
   height     = DIMENSION
   region     = NAME
   rotation   = left right inner outer NUMBER
   position   = yes no overlay
   hoffset    = max DIMENSION
   voffset    = max DIMENSION
   offset     = DIMENSION
   dx         = DIMENSION
   dy         = DIMENSION
   sx         = NUMBER
   sy         = NUMBER
   x          = DIMENSION
   y          = DIMENSION
   corner     = left middle right top bottom
   location   = grid left middle right top bottom line l c r m t b g
   line       = NUMBER
   column     = NUMBER
   direction  = normal reverse
   doublesided = yes no
   method     = fit overlay
   repeat     = yes
   preset     = lefttop righttop leftbottom rightbottom middle middletop middlebottom middleleft middleright
               lefttopleft lefttopright NAME

```

`\setuplayeredtext [...1,...] [...2,...]`  
OPT

```

1  NAME

2  style = STYLE COMMAND
   color = COLOR
   inherits: \setupframed

```

\setuplayout [...]<sup>1</sup> [...]<sup>2</sup> [...]<sup>3</sup>

OPT

```

1  NAME

2  state      = start stop normal repeat
   margin     = DIMENSION
   edge       = DIMENSION
   margindistance = DIMENSION
   edgedistance = DIMENSION
   leftedgedistance = DIMENSION
   rightedgedistance = DIMENSION
   leftmargindistance = DIMENSION
   rightmargindistance = DIMENSION
   topdistance = DIMENSION
   headerdistance = DIMENSION
   footerdistance = DIMENSION
   bottomdistance = DIMENSION
   preset     = NAME
   leftmargin = DIMENSION
   rightmargin = DIMENSION
   leftedge   = DIMENSION
   rightedge  = DIMENSION
   header     = DIMENSION
   footer     = DIMENSION
   top        = DIMENSION
   bottom     = DIMENSION
   backspace  = DIMENSION
   topspace   = DIMENSION
   setups     = NAME
   cutspace   = DIMENSION
   width      = DIMENSION middle fit
   bottomspace = DIMENSION
   lines      = NUMBER
   height     = DIMENSION middle fit
   horoffset  = DIMENSION
   veroffset  = DIMENSION
   columns    = NUMBER
   columndistance = DIMENSION
   method     = default normal NAME
   location   = left middle right top bottom singlesided doublesided
   textwidth  = DIMENSION
   textheight = DIMENSION
   nx         = NUMBER
   ny         = NUMBER
   dx         = DIMENSION
   dy         = DIMENSION
   scale      = NUMBER
   sx         = NUMBER
   sy         = NUMBER
   marking    = on off page empty color one two four
   grid       = yes no off
   textdistance = DIMENSION
   alternative = default normal makeup NAME
   clipoffset = DIMENSION
   cropoffset = DIMENSION
   trimoffset = DIMENSION
   bleedoffset = DIMENSION
   artoffset  = DIMENSION

```

\setuplayouttext [...]<sup>1</sup> [...]<sup>2</sup> [...]<sup>3</sup>

OPT

```

1  top header text footer bottom

2  text margin edge

3  state      = start stop empty high none normal nomarking NAME
   style      = STYLE COMMAND
   color      = COLOR
   strut      = yes no
   n          = NUMBER
   before     = COMMAND
   after      = COMMAND
   leftstyle  = STYLE COMMAND
   rightstyle = STYLE COMMAND
   leftcolor  = COLOR
   rightcolor = COLOR
   width      = DIMENSION
   leftwidth  = DIMENSION
   rightwidth = DIMENSION

```

`\setuplayout [...]`

\* reset NAME

`\setuplinefiller [...,1...] [...,2...,...]`  
OPT

1 NAME

2 location = left right both  
scope = left right local  
mp = NAME  
height = DIMENSION  
depth = DIMENSION  
distance = DIMENSION  
threshold = DIMENSION  
rulethickness = DIMENSION  
before = COMMAND  
after = COMMAND  
color = COLOR  
textstyle = STYLE COMMAND  
textcolor = COLOR  
align = inherits: \setupalign

`\setuplinefillers [...,1...] [...,2...,...]`  
OPT

1 NAME

2 inherits: \setuplinefiller

`\setuplinenote [...,1...] [...,2...,...]`  
OPT

1 NAME

2 compress = yes no  
compressmethod = separator stopper space  
compressseparator = COMMAND  
compressdistance = DIMENSION  
inherits: \setupnote

`\linenote {...}`

\* TEXT

`\setuplinenumbering [...,1...] [...,2...,...]`  
OPT

1 NAME

2 start = NUMBER  
step = NUMBER  
method = page first next  
conversion = NAME  
continue = yes no  
location = text begin end default left right inner outer inleft inright margin inmargin  
distance = DIMENSION  
align = inner outer flushleft flushright left right middle auto  
command = \...##1  
left = COMMAND  
right = COMMAND  
margin = DIMENSION  
width = margin DIMENSION  
style = STYLE COMMAND  
color = COLOR

`\setuplines` [<sup>1</sup>...<sup>1</sup>,...]<sub>OPT</sub> [<sup>2</sup>...<sup>2</sup>,...<sup>2</sup>,...]

```

1  NAME
2  option      = packed
   before      = COMMAND
   after       = COMMAND
   inbetween   = COMMAND
   indenting   = inherits: \setupindenting
   align       = inherits: \setupalign
   space       = yes on off fixed default
   command     = COMMAND
   style       = STYLE COMMAND
   color       = COLOR
   left        = COMMAND
   right       = COMMAND

```

`\setuplinetable` [<sup>1</sup>...]<sub>OPT</sub> [<sup>2</sup>...]<sub>OPT</sub> [<sup>3</sup>...<sup>3</sup>,...<sup>3</sup>,...]

```

1  r c
2  odd even header NUMBER
3  lines        = fit NUMBER
   before       = COMMAND
   after        = COMMAND
   inbetween    = COMMAND
   stretch     = yes no DIMENSION
   maxwidth     = fit DIMENSION
   nleft        = NUMBER
   n            = NUMBER
   repeat       = yes no
   nx           = NUMBER
   width        = DIMENSION
   height       = fit line DIMENSION
   distance     = DIMENSION
   leftoffset   = DIMENSION
   rightoffset  = DIMENSION
   align        = inherits: \setupalign
   background   = color
   backgroundcolor = COLOR
   xheight      = max DIMENSION
   xdepth       = max DIMENSION
   style        = STYLE COMMAND
   color        = COLOR

```

`\setuplinewidth` [<sup>\*</sup>...]

\* small medium big DIMENSION

```

\setuplist [...1,...] [...2,...]
                OPT
1  LIST
2  state          = start stop
    location      = none here
    type          = simple command userdata
    criterium     = local intro reference SECTIONBLOCK:reference all SECTIONBLOCK:all text SECTIONBLOCK:text
                  current SECTIONBLOCK:current here previous SECTIONBLOCK:previous component SECTION
                  SECTIONBLOCK:SECTION
    list          = NAME
    width         = fit broad auto DIMENSION
    height        = fit broad DIMENSION
    depth         = fit broad DIMENSION
    symbol         = one two three none default
    label         = yes no none NAME
    starter       = COMMAND
    stopper       = COMMAND
    command       = \...##1##2##3
    numbercommand = \...##1
    textcommand   = \...##1
    pagecommand   = \...##1
    pagenumber    = yes no always
    headnumber    = yes no always
    before        = COMMAND
    after         = COMMAND
    inbetween     = COMMAND
    margin        = none DIMENSION
    distance      = none DIMENSION
    aligntitle    = yes no
    numberalign   = left right middle flushleft flushright inner outer
    align         = inherits: \setupalign
    hang          = yes no
    left          = COMMAND
    right         = COMMAND
    interaction   = yes no all number text title page sectionnumber pagenumber
    limittext     = yes no TEXT
    style         = STYLE COMMAND
    color         = COLOR
    numberstyle   = STYLE COMMAND
    numbercolor   = COLOR
    textstyle     = STYLE COMMAND
    textcolor     = COLOR
    pagestyle     = STYLE COMMAND
    pagecolor     = COLOR
    reference     = NUMBER
    extras        = NAME
    order         = command all title
    alternative   = a b c d e f g left right top bottom command none interactive paragraph horizontal
                  vertical NAME
    maxwidth      = DIMENSION
    pageprefix    = yes no
    pageprefixseparatorset = NAME
    pageprefixconversionset = NAME
    pageprefixset = NAME
    pageprefixsegments = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:all SECTION SECTION:SECTION SECTION:* SECTION:all
    pageprefixconnector = COMMAND PROCESSOR->COMMAND
    pageconversionset = NAME
    pagestarter   = COMMAND PROCESSOR->COMMAND
    pagestopper   = COMMAND PROCESSOR->COMMAND
    inherits: \setupcounterinherits: \setupframed

```

```

\setuplistalternative [...1,...] [...2,...]
                OPT

```

```

1  NAME
2  before        = COMMAND
    after         = COMMAND
    command       = \...##1##2##3
    renderingsetup = NAME
    width         = DIMENSION
    distance      = DIMENSION
    stretch      = DIMENSION
    filler        = COMMAND

```



`\setuplistextra [...,1...] [...,2...,...]`  
OPT

1 NAME  
2 before = COMMAND  
after = COMMAND

`\setuplocalfloats [...,*...,...]`

\* before = COMMAND  
after = COMMAND  
inbetween = COMMAND

`\setuplocalinterlinespace [...,1...] [...,2...,...]`  
OPT

1 NAME  
2 inherits: \setupinterlinespace

`\setuplocalinterlinespace [...,*...]`  
OPT

\* on off reset auto small medium big NUMBER DIMENSION

`\setuplocalinterlinespace [...*...]`

\* NAME

`\setuplow [...,1...] [...,2...,...]`  
OPT

1 NAME  
2 distance = DIMENSION  
down = DIMENSION  
style = STYLE COMMAND  
color = COLOR

`\setuplowhigh [...,1...] [...,2...,...]`  
OPT

1 NAME  
2 distance = DIMENSION  
up = DIMENSION  
down = DIMENSION  
style = STYLE COMMAND  
color = COLOR

`\setuplowmidhigh [...,1...] [...,2...,...]`  
OPT

1 NAME  
2 up = DIMENSION  
down = DIMENSION  
style = STYLE COMMAND  
color = COLOR

`\unitslow {...}`

\* CONTENT

`\setupMPgraphics [...,*...,...]`

\* color = local global  
mpy = FILE

`\setupMPinstance [...1,...] [...2,...]`  
OPT

```
1 NAME

2 format      = metafun mpost
  initializations = yes no
  setups       = NAME
  textstyle    = STYLE COMMAND
  textcolor    = COLOR
  extensions   = yes no
  method       = binary decimal double scaled default
```

`\setupMPpage [...*,...]`

```
* inherits: \setupfittingpage
```

`\setupMPvariables [...1,...] [...2,...]`  
OPT

```
1 NAME

2 KEY = VALUE
```

`\setupmakeup [...1,...] [...2,...]`  
OPT

```
1 NAME

2 page      = inherits: \page
  command   = COMMAND
  width     = DIMENSION
  height    = DIMENSION
  align     = inherits: \setupalign
  setups    = NAME
  top       = COMMAND
  bottom    = COMMAND
  before    = COMMAND
  after     = COMMAND
  location  = top
  reference = REFERENCE
  pagestate = start stop
  headerstate = start stop high empty none normal
  footerstate = start stop high empty none normal
  topstate   = start stop high empty none normal
  bottomstate = start stop high empty none normal
  textstate  = start stop high empty none normal
  doublesided = yes no empty
  style     = inherits: \value-style
  color     = COLOR
```

`\setupmarginblock [...1,...] [...2,...]`  
OPT

```
1 NAME

2 state      = start stop
  width     = DIMENSION
  before    = COMMAND
  after     = COMMAND
  inbetween = COMMAND
  align     = inherits: \setupalign
  style     = STYLE COMMAND
  color     = COLOR
  top       = COMMAND
  bottom    = COMMAND
  location  = left right middle inmargin
  left     = COMMAND
  right    = COMMAND
```

`\setupmargindata` [ $\dots^1\dots$ ] [ $\dots^2\dots$ ]

OPT

```
1 NAME
2 strut      = yes no auto cap fit line default CHARACTER
  command    = \...##1
  width      = DIMENSION
  align      = inherits: \setupalign
  anchor     = region text
  location   = left right inner outer
  method     = top line first depth height
  category   = default edge
  scope      = local global
  option     = text paragraph
  margin     = local normal margin edge
  distance   = DIMENSION
  hoffset    = DIMENSION
  voffset    = DIMENSION
  dy         = DIMENSION
  bottomspace = DIMENSION
  threshold  = DIMENSION
  line       = NUMBER
  stack      = yes continue
  style      = STYLE COMMAND
  color      = COLOR
```

`\setupmarginframed` [ $\dots^1\dots$ ] [ $\dots^2\dots$ ]

OPT

```
1 NAME
2 inherits: \setupframed
```

`\atleftmargin` [ $\dots^1\dots$ ] [ $\dots^2\dots$ ] {... $^3$ ...}

OPT

OPT

```
1 reference = REFERENCE
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT
```

`\atrighmargin` [ $\dots^1\dots$ ] [ $\dots^2\dots$ ] {... $^3$ ...}

OPT

OPT

```
1 reference = REFERENCE
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT
```

`\ininner` [ $\dots^1\dots$ ] [ $\dots^2\dots$ ] {... $^3$ ...}

OPT

OPT

```
1 reference = REFERENCE
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT
```

`\ininneredge` [ $\dots^1\dots$ ] [ $\dots^2\dots$ ] {... $^3$ ...}

OPT

OPT

```
1 reference = REFERENCE
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT
```

`\ininnermargin` [ $\dots^1\dots$ ] [ $\dots^2\dots$ ] {... $^3$ ...}

OPT

OPT

```
1 reference = REFERENCE
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT
```

```

\inleft [...,\overset{1}{=},...] [...,\overset{2}{=},...] {\overset{3}{...}}
1 reference = REFERENCE
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inleftedge [...,\overset{1}{=},...] [...,\overset{2}{=},...] {\overset{3}{...}}
1 reference = REFERENCE
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inleftmargin [...,\overset{1}{=},...] [...,\overset{2}{=},...] {\overset{3}{...}}
1 reference = REFERENCE
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inmargin [...,\overset{1}{=},...] [...,\overset{2}{=},...] {\overset{3}{...}}
1 reference = REFERENCE
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inothet [...,\overset{1}{=},...] [...,\overset{2}{=},...] {\overset{3}{...}}
1 reference = REFERENCE
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inouter [...,\overset{1}{=},...] [...,\overset{2}{=},...] {\overset{3}{...}}
1 reference = REFERENCE
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inouteredge [...,\overset{1}{=},...] [...,\overset{2}{=},...] {\overset{3}{...}}
1 reference = REFERENCE
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inoutermargin [...,\overset{1}{=},...] [...,\overset{2}{=},...] {\overset{3}{...}}
1 reference = REFERENCE
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

`\inright [...,\overset{1}{=},...] [...,\overset{2}{=},...] {\overset{3}{...}}`

1 reference = REFERENCE  
 inherits: \setupmargindata  
 2 inherits: \setupmarginframed  
 3 CONTENT

`\inrightedge [...,\overset{1}{=},...] [...,\overset{2}{=},...] {\overset{3}{...}}`

1 reference = REFERENCE  
 inherits: \setupmargindata  
 2 inherits: \setupmarginframed  
 3 CONTENT

`\inrightmargin [...,\overset{1}{=},...] [...,\overset{2}{=},...] {\overset{3}{...}}`

1 reference = REFERENCE  
 inherits: \setupmargindata  
 2 inherits: \setupmarginframed  
 3 CONTENT

`\margintext [...,\overset{1}{=},...] [...,\overset{2}{=},...] {\overset{3}{...}}`

1 reference = REFERENCE  
 inherits: \setupmargindata  
 2 inherits: \setupmarginframed  
 3 CONTENT

`\setupmarginrule [\overset{1}{...}] [...,\overset{2}{=},...]`

1 NUMBER  
 2 inherits: \setupsidebar

`\setupmarginrules [\overset{1}{...}] [...,\overset{2}{=},...]`

1 NUMBER  
 2 inherits: \setupmarginrule

`\setupmarking [...,\overset{1}{...}] [...,\overset{2}{=},...]`

1 MARK  
 2 state = start stop  
 expansion = yes no  
 separator = COMMAND  
 filtercommand = \...##1

`\setupmathalignment [...,\overset{1}{...}] [...,\overset{2}{=},...]`

1 NAME  
 2 n = NUMBER  
 m = NUMBER  
 distance = DIMENSION  
 align = left middle right normal

`\setupmathcases [...,\overset{1}{...}] [...,\overset{2}{=},...]`

1 NAME  
 2 left = COMMAND  
 right = COMMAND  
 strut = yes no  
 style = STYLE COMMAND  
 distance = DIMENSION  
 numberdistance = DIMENSION

`\setupmathematics [...1,...] [...2...,...]`  
OPT

```

1  NAME

2  openup           = yes no
   symbolset       = NAME
   functionstyle    = STYLE COMMAND
   compact          = yes no
   align            = l2r r2l
   bidi             = yes no
   sygreek          = normal italic none
   lcgreek          = normal italic none
   ucgreek          = normal italic none
   italics          = 1 2 3 4 none reset
   autopunctuation = yes no all
   setups           = NAME
   domain           = NAME reset
   textstyle        = STYLE COMMAND
   textcolor        = COLOR
   functioncolor    = COLOR
   integral         = limits nolimits autolimits displaylimits none
   stylealternative = NAME
   default          = normal italic
   fraction         = ams ctx

```

`\setupmathfence [...1,...] [...2...,...]`  
OPT

```

1  NAME

2  command = yes no
   left    = NUMBER
   middle  = NUMBER
   right   = NUMBER
   mathstyle = display text script scriptscript cramped uncramped normal packed small big
   color    = COLOR
   state    = auto
   factor   = none auto NUMBER

```

`\setupmathfraction [...1,...] [...2...,...]`  
OPT

```

1  NAME

2  topdistance    = DIMENSION
   bottomdistance = DIMENSION
   margin         = DIMENSION
   color          = COLOR
   strut          = yes no math tight
   alternative    = inner outer both
   rule           = yes no auto
   left           = NUMBER
   right          = NUMBER
   rulethickness  = DIMENSION
   mathstyle      = STYLE COMMAND
   distance       = no none overlay

```

`\setupmathfractions [...1,...] [...2...,...]`  
OPT

```

1  NAME

2  inherits: \setupmathfraction

```

`\binom {...1} {...2}`

```

1  CONTENT
2  CONTENT

```

`\dbinom {...1} {...2}`

```

1  CONTENT
2  CONTENT

```

1    CONTENT

2    CONTENT

1    CONTENT

2    CONTENT

1    CONTENT

2    CONTENT

1     CONTENT

2     CONTENT

1     CONTENT

2     CONTENT

1    CONTENT

2    CONTENT

```
1  NAME
2  inherits: \setupframed
```

```
1 inherits: \setupmathframed
2 CONTENT
```

```
1 inherits: \setupmathframed
2 CONTENT
```

```
1 inherits: \setupmathframed
2 CONTENT
```

```

1  NAME
2  left      =  COMMAND
   right     =  COMMAND
   strut     =  yes no NUMBER
   align     =  left middle right normal
   style     =  STYLE COMMAND
   distance  =  DIMENSION
   location  =  top bottom high low lohi normal

```

`\setupmathornament [...1,...] [...2...,...]`  
OPT

1 NAME  
 2 alternative = mp  
 color = COLOR  
 mppoffset = DIMENSION  
 mp = NAME

`\setupmathradical [...1,...] [...2...,...]`  
OPT

1 NAME  
 2 alternative = default normal mp  
 color = COLOR  
 mppoffset = DIMENSION  
 mp = NAME

`\setupmathstackers [...1,...] [...2...,...]`  
OPT

1 NAME  
 2 left = COMMAND  
 right = COMMAND  
 topcommand = \...##1  
 bottomcommand = \...##1  
 middlecommand = \...##1  
 mp = NAME  
 mpheight = DIMENSION  
 mpdepth = DIMENSION  
 mppoffset = DIMENSION  
 color = COLOR  
 hoffset = DIMENSION  
 voffset = DIMENSION  
 minheight = DIMENSION  
 mindepth = DIMENSION  
 mathclass = rel ord  
 offset = min max normal  
 location = top bottom high low middle NUMBER  
 strut = yes no  
 alternative = normal default mp  
 minwidth = DIMENSION  
 distance = DIMENSION  
 moffset = DIMENSION  
 order = normal reverse  
 mathlimits = yes no

`\setupmathstyle [...*,...]`

\* display text script scriptscript cramped uncramped normal packed small big NAME

`\setupmixedcolumns [...1,...] [...2...,...]`  
OPT

1 NAME  
 2 grid = inherits: \definegridsnapping  
 rulethickness = DIMENSION  
 method = otr box  
 before = COMMAND  
 after = COMMAND  
 distance = DIMENSION  
 n = NUMBER  
 maxheight = DIMENSION  
 maxwidth = DIMENSION  
 step = DIMENSION  
 profile = NAME  
 align = inherits: \setupalign  
 setups = NAME  
 balance = yes no  
 splitmethod = none fixed  
 alternative = local global  
 internalgrid = line halflines  
 separator = rule  
 strut = yes no  
 color = COLOR  
 rulecolor = COLOR  
 direction = normal reverse  
 inherits: \setupframed



`\setupmodule [...]1 [...]2...`

OPT

- 1 FILE
- 2 test = yes no  
KEY = VALUE

`\setupnarrower [...]1 [...]2...`

OPT

- 1 NAME
- 2 left = DIMENSION  
middle = DIMENSION  
right = DIMENSION  
default = [-+]left [-+]middle [-+]right NUMBER\*left NUMBER\*middle NUMBER\*right reset  
before = COMMAND  
after = COMMAND

`\setupnotation [...]1 [...]2...`

OPT

- 1 NAME
- 2 title = yes no  
number = yes no  
type = note  
numbercommand = \...##1  
titledistance = DIMENSION  
titlestyle = STYLE COMMAND  
titlecolor = COLOR  
titlecommand = \...##1  
titleleft = COMMAND  
titleright = COMMAND  
left = COMMAND  
right = COMMAND  
symbol = COMMAND  
starter = COMMAND  
stopper = COMMAND  
coupling = NAME  
counter = NAME  
level = NUMBER  
text = TEXT  
headcommand = \...##1  
before = COMMAND  
after = COMMAND  
inbetween = COMMAND  
alternative = left right inmargin inleft inright margin leftmargin rightmargin innermargin outermargin  
serried hanging top command note NAME  
align = inherits: \setupalign  
headalign = inherits: \setupalign  
indenting = inherits: \setupindenting  
display = yes no  
indentnext = yes no auto  
width = fit broad line DIMENSION  
distance = none DIMENSION  
hang = fit broad none margin NUMBER  
closesymbol = COMMAND  
closecommand = \...##1  
expansion = yes no xml  
referenceprefix = + - TEXT  
sample = TEXT  
margin = yes no standard DIMENSION  
style = STYLE COMMAND  
color = COLOR  
headstyle = STYLE COMMAND  
headcolor = COLOR  
inherits: \setupcounter

`\setupnotations [...]1 [...]2...`

OPT

- 1 NAME
- 2 inherits: \setupnotation

`\setupnote [...,1...] [...,2...,...]`  
OPT

```

1  NAME

2  interaction      = yes no number text all
   symbolcommand   = \...##1
   textcommand     = \...##1
   indicator       = yes no
   textseparator   = COMMAND
   width           = DIMENSION
   height          = DIMENSION
   distance        = DIMENSION
   rulecommand     = COMMAND
   rule            = on off normal left right command paragraph
   split           = tolerant strict verystrict NUMBER
   factor          = NUMBER
   location        = text page high bottom none columns firstcolumn lastcolumn
   next            = COMMAND
   n               = NUMBER
   rulecolor       = COLOR
   rulethickness   = DIMENSION
   setups          = NAME
   interlinespace  = NAME
   paragraph       = yes no
   before          = COMMAND
   after           = COMMAND
   inbetween       = COMMAND
   scope           = page
   columndistance  = DIMENSION
   continue        = yes no
   alternative     = grid fixed columns note none
   criterium       = page
   bodyfont        = inherits: \setupbodyfont
   align           = inherits: \setupalign
   textstyle       = STYLE COMMAND
   textcolor       = COLOR
   anchor          = next
   spacebefore     = inherits: \blank
   spaceinbetween  = inherits: \blank
   inherits: \setupframed

```

`\setupnotes [...,1...] [...,2...,...]`  
OPT

```

1  NAME

2  inherits: \setupnote

```

`\setupoffset [...,*...,...]`

```

*  inherits: \setupoffsetbox

```

`\setupoffsetbox [...,*...,...]`

```

*  x               = DIMENSION
   y               = DIMENSION
   leftoffset      = DIMENSION
   rightoffset     = DIMENSION
   topoffset       = DIMENSION
   bottomoffset    = DIMENSION
   method          = fixed
   width           = DIMENSION
   height          = DIMENSION
   depth           = DIMENSION
   location        = left middle right top bottom line l c r m t b g

```

`\setupoppositeplacing [...,*...,...]`

```

*  state          = start stop
   before         = COMMAND
   after          = COMMAND
   inbetween      = COMMAND

```

\setupoutputroutine [...]<sup>1</sup> [...]<sup>2</sup>...

OPT

1 NAME

2 KEY = CSNAME

\setupoutputroutine [...]

\* NAME

\setuppagechecker [...]<sup>1</sup> [...]<sup>2</sup>...

OPT

1 NAME

2 lines = NUMBER  
offset = DIMENSION  
method = 0 1 2 3  
before = COMMAND  
after = COMMAND  
inbetween = COMMAND

\setuppagecomment [...]<sup>\*</sup>...

\* location = left right top bottom none  
state = start stop none  
offset = DIMENSION  
distance = DIMENSION  
width = DIMENSION  
height = DIMENSION

\setuppagegrid [...]<sup>1</sup> [...]<sup>2</sup>...

OPT

1 NAME

2 n = NUMBER  
nleft = NUMBER  
nright = NUMBER  
width = DIMENSION auto  
distance = DIMENSION  
lines = NUMBER  
maxwidth = DIMENSION  
maxheight = DIMENSION  
direction = normal reverse  
page = inherits: \page  
inherits: \setupframed

\setuppagegridarea [...]<sup>1</sup> [...]<sup>2</sup>...

OPT

1 NAME

2 state = start stop repeat  
x = NUMBER  
y = NUMBER  
nx = NUMBER  
ny = NUMBER  
style = STYLE COMMAND  
color = COLOR  
clipoffset = DIMENSION  
rightoffset = DIMENSION  
inherits: \setupframed

\setuppagegridareatext [...]<sup>1</sup> [...]<sup>2</sup>

1 NAME

2 TEXT

\setuppagegridlines [...]<sup>1</sup> [...]<sup>2</sup> [...]<sup>3</sup> [...]<sup>4</sup>

1 NAME

2 NUMBER

3 NUMBER

4 NUMBER

`\setuppagegridspan [...1,...] [...2,...] OPT`

1 NAME  
2 n = NUMBER  
style = STYLE COMMAND  
color = COLOR  
before = COMMAND  
after = COMMAND  
inherits: \setupframed

`\setuppagegridstart [...1] [...2] [...3] [...4]`

1 NAME  
2 NUMBER  
3 NUMBER  
4 NUMBER

`\setuppageinjection [...1,...] [...2,...] OPT`

1 NAME  
2 state = previous next NUMBER  
delay = yes no  
alternative = figure buffer setups none NAME  
page = inherits: \page  
pagestate = start stop  
n = NUMBER  
inherits: \setupframed

`\setuppageinjectionalternative [...1,...] [...2,...] OPT`

1 NAME  
2 renderingsetup = NAME

`\setuppagenumber [...*,...] OPT`

\* inherits: \setupuserpagenumber

`\setuppagenumbering [...*,...] OPT`

\* alternative = singlesided doublesided  
page = inherits: \page  
strut = yes no  
command = \...##1  
left = COMMAND  
right = COMMAND  
state = start stop  
width = DIMENSION  
location = header footer left middle right inleft inright margin inmargin atmargin marginedge  
style = STYLE COMMAND  
color = COLOR

`\setuppageshift [...1] [...2] [...3] OPT OPT`

1 page paper  
2 NAME  
3 NAME

`\setuppagestate [...1,...] [...2,...] OPT`

1 NAME  
2 delay = yes no

`\setuppagetransitions [...*] OPT`

\* reset auto start random NUMBER

`\setuppairedbox [...1,...] [...2,...]`  
OPT

```
1  NAME
2  before    = COMMAND
   after     = COMMAND
   inbetween = COMMAND
   location  = left middle right top bottom high low
   n         = NUMBER
   distance  = DIMENSION
   bodyfont  = inherits: \setupbodyfont
   width     = DIMENSION
   height    = DIMENSION
   maxwidth  = DIMENSION
   maxheight = DIMENSION
   align     = inherits: \setupalign
   style     = STYLE COMMAND
   color     = COLOR
```

`\setupPAIREDBOX [...*,...]`

`* inherits: \setuppairedbox`

`instances: legend`

`\placelegend [...1,...] {...2} {...3}`  
OPT

```
1  inherits: \setuppairedbox
2  CONTENT
3  TEXT
```

`\setuppalet [...*]`

`* NAME`

`\setuppaper [...*,...]`

`* inherits: \setuppapersize`

`\setuppapersize [...1] [...2,...]`  
OPT

```
1  NAME
2  top      = COMMAND
   bottom   = COMMAND
   left     = COMMAND
   right    = COMMAND
   method   = normal none NAME
   scale    = NUMBER
   nx       = NUMBER
   ny       = NUMBER
   dx       = DIMENSION
   dy       = DIMENSION
   width    = DIMENSION
   height   = DIMENSION
   topspace = DIMENSION
   backspace = DIMENSION
   offset   = DIMENSION
   page     = reset landscape mirrored negative rotated 90 180 270 NAME
   paper    = reset landscape mirrored negative rotated 90 180 270 NAME
   option   = fit max
   distance = DIMENSION
```

`\setuppapersize [...1,...] [...2,...]`  
OPT OPT

```
1  reset landscape mirrored negative rotated 90 180 270 NAME
2  reset landscape mirrored negative rotated 90 180 270 NAME
```

`\setupparagraph [...,1...] [...,2...,...]`  
OPT

1 NAME  
 2 style = STYLE COMMAND  
 color = COLOR  
 align = inherits: \setupalign  
 setups = NAME

`\setupparagraphintro [...,1...] [...2.]`

1 reset each first next  
 2 COMMAND

`\setupparagraphnumbering [...,*...,...]`

\* state = start stop line reset  
 distance = DIMENSION  
 style = STYLE COMMAND  
 color = COLOR

`\setupparagraphs [...1.] [...,2...] [...,3...,...]`  
OPT OPT

1 NAME  
 2 each NUMBER  
 3 n = NUMBER  
 before = COMMAND  
 after = COMMAND  
 width = DIMENSION  
 distance = DIMENSION  
 height = DIMENSION fit  
 top = COMMAND  
 bottom = COMMAND  
 align = inherits: \setupalign  
 inner = COMMAND  
 command = COMMAND  
 rule = on off  
 rulethickness = DIMENSION  
 rulecolor = COLOR  
 style = STYLE COMMAND  
 color = COLOR

`\setupparagraphs [...1.] [...,2...,...]`  
OPT

1 NAME:NUMBER  
 2 n = NUMBER  
 before = COMMAND  
 after = COMMAND  
 width = DIMENSION  
 distance = DIMENSION  
 height = DIMENSION fit  
 top = COMMAND  
 bottom = COMMAND  
 align = inherits: \setupalign  
 inner = COMMAND  
 command = COMMAND  
 rule = on off  
 rulethickness = DIMENSION  
 rulecolor = COLOR  
 style = STYLE COMMAND  
 color = COLOR

`\setupparallel [...1.] [...,2...] [...,3...,...]`

1 NAME  
 2 NAME  
 3 setups = NAME  
 start = NUMBER  
 n = NUMBER  
 criterium = all

\setupperiods [...,..<sup>\*</sup>...,...]

\* n = NUMBER  
width = DIMENSION fit  
distance = DIMENSION  
symbol = COMMAND

\setupplacement [...,..<sup>1</sup>...] [...,..<sup>2</sup>...,...]  
OPT

1 NAME  
2 before = COMMAND  
after = COMMAND  
left = COMMAND  
right = COMMAND  
grid = inherits: \snaptogrid  
linecorrection = on off  
depthcorrection = on off  
margin = yes no standard

\setuppositionbar [...,..<sup>\*</sup>...,...]

\* style = STYLE COMMAND  
color = COLOR  
n = NUMBER  
min = NUMBER  
max = NUMBER  
text = TEXT  
width = DIMENSION  
height = DIMENSION  
depth = DIMENSION

\setuppositioning [...,..<sup>1</sup>...] [...,..<sup>2</sup>...,...]  
OPT

1 NAME  
2 offset = yes no  
unit = ex em pt in cm mm sp bp pc dd cc nc  
state = start overlay  
xoffset = DIMENSION  
yoffset = DIMENSION  
xstep = absolute relative  
ystep = absolute relative  
xscale = NUMBER  
yscale = NUMBER  
xfactor = NUMBER  
yfactor = NUMBER  
factor = NUMBER  
scale = NUMBER

\setupprocessor [...,..<sup>1</sup>...] [...,..<sup>2</sup>...,...]  
OPT

1 NAME  
2 state = start stop  
left = COMMAND  
right = COMMAND  
command = \...##1  
style = STYLE COMMAND  
color = COLOR

\setupprofile [...,..<sup>1</sup>...] [...,..<sup>2</sup>...,...]  
OPT

1 NAME  
2 height = DIMENSION  
depth = DIMENSION  
distance = DIMENSION  
factor = NUMBER  
lines = NUMBER  
method = strict fixed none

\setupprograms [...,..<sup>\*</sup>...,...]

\* style = STYLE COMMAND  
color = COLOR

\setupquotation [...,\*...,...]

\* inherits: \setupdelimitedtext

\setupquote [...,\*...,...]

\* inherits: \setupdelimitedtext

\setuprealpagenumber [...,\*...,...]

\* inherits: \setupcounter

\setupreferenceformat [...,<sup>1</sup>...] [...,<sup>2</sup>...] [...,<sup>3</sup>...,...]  
OPT

1 NAME

2 label = \* NAME  
left = COMMAND  
right = COMMAND  
type = default text title number page realpage  
setups = NAME  
autocase = yes no  
text = TEXT  
style = STYLE COMMAND  
color = COLOR

\setupreferenceprefix [...]

\* + - TEXT

\setupreferencestructureprefix [...,<sup>1</sup>...] [...,<sup>2</sup>...] [...,<sup>3</sup>...,...]  
OPT OPT

1 NAME SECTION

2 default

3 prefix = yes no  
prefixseparatorset = NAME  
prefixconversion = NAME  
prefixconversionset = NAME  
prefixstarter = COMMAND PROCESSOR->COMMAND  
prefixstopper = COMMAND PROCESSOR->COMMAND  
prefixset = NAME  
prefixsegments = NUMBER NUMBER:NUMBER NUMBER:\* NUMBER:all SECTION SECTION:SECTION SECTION:\* SECTION:all  
numberconversion = NAME  
numberconversionset = NAME  
numberstarter = COMMAND PROCESSOR->COMMAND  
numberstopper = COMMAND PROCESSOR->COMMAND  
numbersegments = NUMBER NUMBER:NUMBER NUMBER:\* NUMBER:all  
numberseparatorset = NAME  
prefixconnector = COMMAND PROCESSOR->COMMAND

\setuppreferencing [...,\*...,...]

\* state = start stop  
expansion = yes no xml  
autofile = yes no  
export = yes no  
left = COMMAND  
right = COMMAND  
width = DIMENSION  
doublesided = yes no  
interaction = label text symbol all  
separator = COMMAND  
prefix = + - TEXT



\setupregister [...]<sup>1</sup> [...,...]<sup>2</sup>...]

OPT

```

1  NAME NAME:NUMBER

2  referencemethod      = forward
   expansion            = yes no xml
   ownnumber            = yes no
   xmlsetup             = NAME
   alternative          = a b A B
   method               = default before after first last ch mm zm pm mc zc pc uc
   compress             = yes no all
   criterium            = local text current previous all SECTION
   pageprefixseparatorset = COMMAND
   pageprefixconversionset = NAME
   pageprefixstarter    = COMMAND PROCESSOR->COMMAND
   pageprefixstopper    = COMMAND PROCESSOR->COMMAND
   pageprefixset        = NAME
   pageprefixsegments   = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:all SECTION SECTION:SECTION SECTION:* SECTION:all
   pageprefixconnector  = COMMAND
   pageprefix           = yes no
   pageseparatorset     = NAME
   pageconversionset    = NAME
   pagestarter          = COMMAND PROCESSOR->COMMAND
   pagestopper          = COMMAND PROCESSOR->COMMAND
   pagesegments         = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:all
   maxwidth             = DIMENSION
   indicator            = yes no
   before               = COMMAND
   after                = COMMAND
   command              = \...##1
   textcommand          = \...##1
   deeptextcommand      = \...##1
   pagecommand          = \...##1
   distance             = DIMENSION
   interaction          = text pagenumber
   pagenumber           = yes no
   symbol               = a n none 1 2 COMMAND
   language             = default DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scN LANGUAGE
   style                = STYLE COMMAND
   color                = COLOR
   textstyle            = STYLE COMMAND
   textcolor            = COLOR
   pagestyle            = STYLE COMMAND
   pagecolor            = COLOR
   n                    = NUMBER
   balance              = yes no
   align                = inherits: \setupalign
   numberorder          = numbers

```

\setupregisters [...]<sup>1</sup> [...,...]<sup>2</sup>...]

OPT

```

1  NAME NAME:NUMBER

2  inherits: \setupregister

```

\setupregisters [...]<sup>1</sup> [...,...]<sup>2</sup> [...,...]<sup>3</sup>...]

OPT

OPT

```

1  NAME

2  NUMBER

3  inherits: \setupregister

```

\index [...]<sup>1</sup> [...+...+...]<sup>2</sup>

OPT

```

1  TEXT PROCESSOR->TEXT

2  INDEX

```

`\setupregister [...,1...] [...,2...] [...,3...]`  
OPT OPT

```

1  NAME
2  NUMBER
3  referencemethod      = forward
   expansion           = yes no xml
   ownnumber           = yes no
   xmlsetup            = NAME
   alternative         = a b A B
   method              = default before after first last ch mm zm pm mc zc pc uc
   compress            = yes no all packed
   criterium           = local text current previous all SECTION
   pageprefixseparatorset = COMMAND
   pageprefixconversionset = NAME
   pageprefixstarter   = COMMAND PROCESSOR->COMMAND
   pageprefixstopper   = COMMAND PROCESSOR->COMMAND
   pageprefixset       = NAME
   pageprefixsegments  = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:all SECTION SECTION:SECTION SECTION:* SECTION:all
   pageprefixconnector = COMMAND
   pageprefix          = yes no
   pageseparatorset    = NAME
   pageconversionset   = NAME
   pagestarter         = COMMAND PROCESSOR->COMMAND
   pagestopper        = COMMAND PROCESSOR->COMMAND
   pagesegments        = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:all
   maxwidth            = DIMENSION
   indicator           = yes no
   before              = COMMAND
   after               = COMMAND
   command             = \...##1
   textcommand         = \...##1
   deeptextcommand     = \...##1
   pagecommand         = \...##1
   distance            = DIMENSION
   interaction         = text pagenumber
   pagenumber          = yes no
   symbol              = a n none 1 2 COMMAND
   language            = default DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scn LANGUAGE
   style               = STYLE COMMAND
   color               = COLOR
   textstyle           = STYLE COMMAND
   textcolor           = COLOR
   pagestyle           = STYLE COMMAND
   pagecolor           = COLOR
   n                   = NUMBER
   balance             = yes no
   align               = inherits: \setupalign
   numberorder         = numbers

```

`\setupREGISTER [...,1...] [...,2...]`  
OPT

```

1  NUMBER
2  inherits: \setupregister

```

instances: index

`\setuprenderingwindow [...,1...] [...,2...]`  
OPT

```

1  NAME
2  openpageaction = REFERENCE
   closepageaction = REFERENCE
   inherits: \setupframed

```

`\setuprotate [...,*...]`

```

*  location = fit broad depth high middle default normal
   rotation = left right inner outer NUMBER
   inherits: \setupframed

```

`\setups [...,*...]`

```

*  NAME

```

```

\setupscale [...,1...] [...,2...]
               OPT
1  NAME
2  scale      = NUMBER
   xscale     = NUMBER
   yscale     = NUMBER
   width      = DIMENSION
   height     = DIMENSION
   depth      = yes no
   lines      = NUMBER
   factor     = fit broad max auto default
   hfactor    = fit broad max auto default
   wfactor    = fit broad max auto default
   maxwidth   = DIMENSION
   maxheight  = DIMENSION
   s          = NUMBER
   sx         = NUMBER
   sy         = NUMBER
   equalwidth = DIMENSION
   equalheight = DIMENSION
   grid       = yes fit height depth halflne

```

```

\setupscript [...,1...] [...,2...]
               OPT
1  NAME
2  method     = hangul hanzi nihongo ethiopic thai test
   preset     = NAME
   features    = auto

```

```

\setupscripts [...,1...] [...,2...]
               OPT
1  NAME
2  inherits: \setupscript

```

```

\setupsectionblock [...,1...] [...,2...]
                   OPT
1  NAME
2  page      = inherits: \page
   before    = COMMAND
   after     = COMMAND
   number    = yes no

```

```

\setupselector [...,1...] [...,2...]
1  NAME
2  n = NUMBER
   m = NUMBER

```

```

\setupshift [...,1...] [...,2...]
              OPT
1  NAME
2  continue = yes no
   unit     = ex em pt in cm mm sp bp pc dd cc nc
   method   = NUMBER
   dy       = NUMBER
   align    = inherits: \setupalign
   style    = STYLE COMMAND
   color    = COLOR

```

```

\shiftdown {...}
*  CONTENT

```

```

\shiftup {...}
*  CONTENT

```

`\setupsidebar [...1,...] [...2,...]`  
OPT

1 NAME

2 rulethickness = DIMENSION  
rulecolor = COLOR  
alternative = NUMBER  
topoffset = DIMENSION  
bottomoffset = DIMENSION  
distance = DIMENSION  
leftmargindistance = DIMENSION  
level = NUMBER

`\setupsorting [...1,...] [...2,...]`  
OPT

1 SINGULAR

2 expansion = yes no xml  
alternative = first last normal NAME  
next = COMMAND  
command = \...##1##2##3  
textcommand = \...##1  
synonymcommand = \...##1  
language = default DIN\_5007-1 DIN\_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scn LANGUAGE  
method = default before after first last ch mm zm pm mc zc pc uc  
criterion = current previous local text all SECTION  
style = STYLE COMMAND  
color = COLOR  
textstyle = STYLE COMMAND  
textcolor = COLOR  
synonymstyle = STYLE COMMAND  
synonymcolor = COLOR

`\logo [...1] {...2}`  
OPT

1 NAME

2 CONTENT

`\setupspacing [...*]`  
OPT

\* fixed packed broad

`\setupsPELLchecking [...*,...]`

\* state = start stop  
method = 1 2 3  
list = NAME

`\setupstartstop [...1,...] [...2,...]`  
OPT

1 NAME

2 before = COMMAND  
after = COMMAND  
inbetween = COMMAND  
setups = NAME  
left = COMMAND  
right = COMMAND  
style = STYLE COMMAND  
color = COLOR

`\setupstretched [...*,...]`

\* inherits: \setupcharacterkerning

`\setupstruts [...*]`  
OPT

\* yes no auto cap fit line default CHARACTER

`\setupstyle [...,1...] [...,2...,...]`  
OPT

1 NAME  
2 method = command  
style = STYLE COMMAND  
color = COLOR

`\setupsubformula [...,1...] [...,2...,...]`  
OPT

1 NAME  
2 indentnext = yes no auto

`\setupsubformulas [...,1...] [...,2...,...]`  
OPT

1 NAME  
2 inherits: \setupsubformula

`\setupsubpagenumber [...,*...,...]`

\* inherits: \setupcounter

`\setupsymbolset [...]`

\* NAME

`\setupsynonyms [...,1...] [...,2...,...]`  
OPT

1 SINGULAR  
2 expansion = yes no xml  
alternative = first last normal NAME  
next = COMMAND  
command = \...##1##2##3  
textcommand = \...##1  
synonymcommand = \...##1  
language = default DIN\_5007-1 DIN\_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scn LANGUAGE  
method = default before after first last ch mm zm pm mc zc pc uc  
criterium = current previous local text all SECTION  
style = STYLE COMMAND  
color = COLOR  
textstyle = STYLE COMMAND  
textcolor = COLOR  
synonymstyle = STYLE COMMAND  
synonymcolor = COLOR

`\abbreviation [...]1 {...}2 {...}3`  
OPT

1 NAME  
2 TEXT  
3 CONTENT

`\setups {...,*...}`

\* NAME

```

\setupTABLE [...1,...] [...2,...] [...3,...]
               OPT      OPT
1  r c x y row column first last start header each odd even one NUMBER -NUMBER
2  first least each two odd even NUMBER -NUMBER
3  extras          = COMMAND
   left            = COMMAND
   right           = COMMAND
   headcolor       = COLOR
   headstyle       = STYLE COMMAND
   leftmargindistance = DIMENSION
   rightmargindistance = DIMENSION
   columndistance  = DIMENSION
   maxwidth        = DIMENSION
   setups          = NAME
   textwidth       = DIMENSION local
   split           = yes no repeat auto
   header          = repeat
   option          = stretch tight
   before          = COMMAND
   after           = COMMAND
   samepage        = before after both
   spaceinbetween  = inherits: \blank
   splitoffset     = DIMENSION
   aligncharacter  = yes no
   alignmentcharacter = TEXT number->TEXT text->TEXT
   distance        = DIMENSION
   color           = COLOR
   style           = math STYLE COMMAND
   inherits: \setupframed

```

```

\setupTEXpage [...*,...]
*  inherits: \setupfittingpage

```

```

\setuptables [...*,...]
*  text          = DIMENSION max
   split         = yes no repeat auto
   frame         = on off
   NL            = inherits: \blank
   VL            = small medium big none NUMBER
   HL            = small medium big none NUMBER
   distance      = small medium big none
   align         = left middle right
   commands      = COMMAND
   bodyfont      = inherits: \setupbodyfont
   rulethickness = DIMENSION
   height        = strut NUMBER
   depth         = strut NUMBER
   openup        = DIMENSION

```

```

\setuptabulate [...1] [...2] [...3,...]
                OPT      OPT
1  NAME
2  NAME
3  inherits: \setuptabulation

```

`\setuptabulation [...1,...] [...2,...]`  
OPT

```
1 NAME

2 format      = TEMPLATE none
  before      = COMMAND
  after       = COMMAND
  distance    = small medium big none blank depth grid DIMENSION
  align       = left middle right dimension
  rule        = line normal
  rulecolor   = COLOR
  rulethickness = DIMENSION
  bodyfont    = inherits: \setupbodyfont
  indenting   = yes no
  split       = yes no repeat auto
  unit        = DIMENSION
  margin      = DIMENSION
  inner       = COMMAND
  EQ          = COMMAND
  header      = yes repeat text
  frame       = on off
  title       = TEXT
  keeptogether = yes no
```

`\setuptagging [...*,...]`

```
* state = start stop
  method = auto
```

`\setuptext [...1,...] [...2,...]`  
OPT

```
1 text margin edge

2 inherits: \setuplayoutelement
```

`\setuptextbackground [...1,...] [...2,...]`  
OPT

```
1 NAME

2 state      = start stop
  location   = text paragraph none
  alternative = NUMBER
  mp         = NAME
  method     = NAME
  background = color
  backgroundcolor = COLOR
  corner     = rectangular round
  level      = NUMBER
  backgroundoffset = DIMENSION
  before     = COMMAND
  after      = COMMAND
  align      = inherits: \setupalign
  dash       = NUMBER
  radius     = DIMENSION
  frame      = on off
  framecolor = COLOR
  rulethickness = DIMENSION
  voffset    = DIMENSION
  frameoffset = DIMENSION
  leftoffset = yes no standard DIMENSION
  rightoffset = yes no standard DIMENSION
  topoffset  = small medium big line DIMENSION
  bottomoffset = small medium big line DIMENSION
  style      = STYLE COMMAND
  color      = COLOR
```

`\setuptextflow [...1,...] [...2,...]`  
OPT

```
1 NAME

2 width = DIMENSION
  style = STYLE COMMAND
  color = COLOR
```

`\setuptextrules [...,*=...,...]`

\* before = COMMAND  
after = COMMAND  
inbetween = COMMAND  
rulethickness = DIMENSION  
location = left inmargin  
style = STYLE COMMAND  
color = COLOR  
rulecolor = COLOR  
width = DIMENSION  
height = DIMENSION  
distance = DIMENSION  
depthcorrection = on off  
bodyfont = inherits: \setupbodyfont

`\setuptexttexts [...1.] [...2.] [...3.] [...4.] [...5.]`  
OPT OPT OPT OPT OPT

1 text margin edge  
2 date pagenumber MARK TEXT COMMAND  
3 date pagenumber MARK TEXT COMMAND  
4 date pagenumber MARK TEXT COMMAND  
5 date pagenumber MARK TEXT COMMAND

`\setupthinrules [...,*=...,...]`

\* height = max DIMENSION  
depth = max DIMENSION  
background = color  
frame = on off  
rulethickness = DIMENSION  
alternative = a b c none  
backgroundcolor = COLOR  
color = COLOR  
interlinespace = small medium big NUMBER  
before = COMMAND  
after = COMMAND  
inbetween = COMMAND  
n = NUMBER

`\setuptolerance [...,*=...,...]`

\* horizontal vertical veryststrict strict tolerant verytolerant space stretch

`\setuptooltip [...,1.] [...,2.=...,...]`  
OPT

1 NAME  
2 location = left middle right  
inherits: \setupframed

`\tooltip [...,1.=...,...] {...2.} {...3.}`  
OPT

1 inherits: \setuptooltip  
2 TEXT  
3 TEXT

`\setuptop [...1.] [...,2.=...,...]`  
OPT

1 text margin edge  
2 inherits: \setuplayoutelement



`\setuptoptexts` [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...] [<sup>4</sup>...] [<sup>5</sup>...]  
OPT OPT OPT OPT OPT

- 1 `text` margin edge
- 2 `date` pagenumber MARK TEXT COMMAND
- 3 `date` pagenumber MARK TEXT COMMAND
- 4 `date` pagenumber MARK TEXT COMMAND
- 5 `date` pagenumber MARK TEXT COMMAND

`\setuptype` [<sup>1</sup>...,...] [<sup>2</sup>...,...]  
OPT

- 1 NAME
- 2 `option` = mp lua xml parsed-xml nested tex context none NAME  
`command` = CSNAME  
`left` = COMMAND  
`right` = COMMAND  
`tab` = yes no NUMBER  
`compact` = absolute last all  
`escape` = yes no TEXT PROCESSOR->TEXT  
`style` = STYLE COMMAND  
`color` = COLOR  
`lines` = yes no normal hyphenated  
`space` = on off normal fixed stretch

`\setuptyping` [<sup>1</sup>...,...] [<sup>2</sup>...,...]  
OPT

- 1 NAME
- 2 `oddmargin` = DIMENSION  
`evenmargin` = DIMENSION  
`margin` = yes no standard DIMENSION  
`option` = mp lua xml parsed-xml nested tex context none NAME  
`style` = STYLE COMMAND  
`color` = COLOR  
`align` = inherits: \setupalign  
`lines` = yes no normal hyphenated  
`space` = on off normal fixed stretch  
`keeptogether` = yes no  
`before` = COMMAND  
`after` = COMMAND  
`strip` = yes no NUMBER  
`range` = NUMBER NAME  
`tab` = yes no NUMBER  
`escape` = yes no TEXT PROCESSOR->TEXT  
`indentnext` = yes no auto  
`continue` = yes no  
`start` = NUMBER  
`stop` = NUMBER  
`step` = NUMBER  
`numbering` = file line no  
`blank` = inherits: \blank

`\setupunit` [<sup>1</sup>...,...] [<sup>2</sup>...,...]  
OPT

- 1 NAME
- 2 `method` = 1 2 3 4 5 6  
`language` = LANGUAGE  
`alternative` = text mathematics  
`order` = reverse normal  
`separator` = small medium big normal none NAME  
`space` = small medium big normal none NAME  
`style` = STYLE COMMAND  
`color` = COLOR

`\unit {...}`

- \* CONTENT

`\setupurl` [...,...\*=...]

- \* `style` = STYLE COMMAND  
`color` = COLOR

`\setupuserpagenumber [...,*=...,...]`

\* viewerprefix = TEXT  
state = start stop none keep empty  
inherits: \setupcounter

`\setupversion [...]`

\* concept file temporary final NAME

`\setupviewerlayer [...,*=...,...]`

\* title = TEXT  
state = start stop  
export = yes no  
printable = yes no  
scope = local global  
method = none command

`\setupvspacing [...,*=...,...]`  
OPT

\* inherits: \vspacing

`\setupwhitespace [...,*=...,...]`  
OPT

\* fix fixed flexible line halfline quarterline none small medium big default DIMENSION

`\setupwithargument {...} {...}`

1 NAME  
2 CONTENT

`\setupwithargumentswapped {...} {...}`

1 CONTENT  
2 NAME

`\setupxml [...,*=...,...]`

\* default = hidden none text  
compress = yes no

`\setupxtable [...,1...,...]` `[...,*=2...,...]`  
OPT

1 NAME  
2 textwidth = DIMENSION local  
bodyfont = inherits: \setupbodyfont  
spaceinbetween = inherits: \blank  
option = tight max stretch width height fixed  
textheight = DIMENSION  
maxwidth = DIMENSION  
columnndistance = DIMENSION  
leftmargindistance = DIMENSION  
rightmargindistance = DIMENSION  
header = repeat  
footer = repeat  
rulethickness = DIMENSION  
split = yes no repeat auto  
splitoffset = DIMENSION  
samepage = before after both  
distance = DIMENSION  
inherits: \setupframed

`\setup {...}`

\* NAME

**\setuvalue** <sup>1</sup>{...} <sup>2</sup>{...}

- 1 NAME
- 2 CONTENT

**\setuxvalue** <sup>1</sup>{...} <sup>2</sup>{...}

- 1 NAME
- 2 CONTENT

**\setvalue** <sup>1</sup>{...} <sup>2</sup>{...}

- 1 NAME
- 2 CONTENT

**\setvariable** <sup>1</sup>{...} <sup>2</sup>{...} <sup>3</sup>{...}

- 1 NAME
- 2 KEY
- 3 VALUE

**\setvariables** [<sup>1</sup>...] [<sup>2</sup>...=...]

- 1 NAME
- 2 **set** = COMMAND  
**reset** = COMMAND  
**KEY** = VALUE

**\setvboxregister** <sup>1</sup>... <sup>2</sup>{...}

- 1 CSNAME NUMBER
- 2 CONTENT

**\setvisualizerfont** [<sup>\*</sup>...]  
OPT

- \* FONT

**\setvtopregister** <sup>1</sup>... <sup>2</sup>{...}

- 1 CSNAME NUMBER
- 2 CONTENT

**\setwidthof** <sup>1</sup>... \to \<sup>2</sup>...

- 1 TEXT
- 2 CSNAME

**\setxmeasure** <sup>1</sup>{...} <sup>2</sup>{...}

- 1 NAME
- 2 DIMENSION

**\setxvalue** <sup>1</sup>{...} <sup>2</sup>{...}

- 1 NAME
- 2 CONTENT

```
\setxvariable {...} {...} {...}
```

```
1  NAME
2  KEY
3  VALUE
```

```
\setxvariables [...] [...,..2...,...]
```

```
1  NAME
2  set    = COMMAND
   reset  = COMMAND
   KEY    = VALUE
```

```
\shapedhbox {...}
```

```
*  CONTENT
```

```
\SHIFT {...}
```

```
*  CONTENT
```

```
instances: shiftup shiftdown
```

```
\showallmakeup
```

```
\showattributes
```

```
\showbodyfont [...,*,...]
```

```
*  inherits: \setupbodyfont
```

```
\showbodyfontenvironment [...,*,...]
```

```
*  inherits: \setupbodyfont
```

```
\showboxes
```

```
\showbtxdatasetauthors [...,..*...,...]  
                        OPT
```

```
*  specification = NAME
   dataset       = NAME
   field         = address assignee author booktitle chapter day dayfiled edition editor howpublished institution
                  journal language month monthfiled nationality note number one two organization pages publisher
                  school series title type volume year yearfiled NAME
```

```
\showbtxdatasetauthors [...]  
                        OPT
```

```
*  NAME
```

```
\showbtxdatasetcompleteness [...,..*...,...]  
                        OPT
```

```
*  specification = NAME
   dataset       = NAME
   field         = address assignee author booktitle chapter day dayfiled edition editor howpublished institution
                  journal language month monthfiled nationality note number one two organization pages publisher
                  school series title type volume year yearfiled NAME
```

```
\showbtxdatasetcompleteness [...]  
                        OPT
```

```
*  NAME
```

<pre> \showbtxdatasetfields [...,..<sup>*</sup>...,...]                                 OPT *  specification = NAME    dataset      = NAME    field        = address assignee author booktitle chapter day dayfiled edition editor howpublished institution                   journal language month monthfiled nationality note number one two organization pages publisher                   school series title type volume year yearfiled NAME </pre>
<pre> \showbtxdatasetfields [...]                                 OPT *  NAME </pre>
<pre> \showbtxfields [...,..<sup>*</sup>...,...]                                 OPT *  rotation      = NUMBER    specification = NAME </pre>
<pre> \showbtxfields [...]                                 OPT *  NAME </pre>
<pre> \showbtxhashedauthors [...]                                 OPT *  TEXT </pre>
<pre> \showbtxtables [...]                                 OPT *  TEXT </pre>
<pre> \showchardata {...} *  TEXT </pre>
<pre> \showcharratio {...} *  TEXT </pre>
<pre> \showcolor [...] *  COLOR </pre>
<pre> \showcolorbar [...] *  COLOR </pre>
<pre> \showcolorcomponents [...] *  COLOR </pre>
<pre> \showcolorgroup [...]<sup>1</sup> [...,<sup>2</sup>...]                                 OPT 1  NAME 2  <u>horizontal</u> vertical number value name </pre>
<pre> \showcolorset [...] *  COLOR </pre>
<pre> \showcolorstruts </pre>
<pre> \showcounter [...] *  NAME </pre>

<code>\showdirectives</code>
<code>\showdirstsinmargin</code>
<code>\showedebuginfo</code>
<code>\showexperiments</code>
<code>\showfont [...]<sup>1</sup> [...]<sup>2</sup>...</code> <div> <div>OPT</div> <div>1 FONT</div> <div>2 NUMBER</div> </div>
<code>\showfontdata</code>
<code>\showfontkerns</code>
<code>\showfontparameters</code>
<code>\showfontstrip [...]*...</code> <div> <div>* inherits: \setupbodyfont</div> </div>
<code>\showfontstyle [...]<sup>1</sup> [...]<sup>2</sup> [...]<sup>3</sup> [...]<sup>4</sup>...</code> <div> <div>OPT</div> <div>OPT</div> <div>OPT</div> <div>OPT</div> <div>1 inherits: \setupbodyfont</div> <div>2 rm ss tt mm hw cg</div> <div>3 tf bf it sl bi bs</div> <div>4 all NUMBER</div> </div>
<code>\showframe [...]<sup>1</sup> [...]<sup>2</sup>...</code> <div> <div>OPT</div> <div>OPT</div> <div>1 top header text footer bottom</div> <div>2 leftedge leftmargin text rightmargin rightedge</div> </div>
<code>\showglyphs</code>
<code>\showgrid [...]*...</code> <div> <div>OPT</div> <div>* reset <u>bottom</u> top none <u>all</u> lines frame nonumber <u>right</u> left outer <u>columns</u></div> </div>
<code>\showgridsnapping</code>
<code>\showhelp {...}<sup>1</sup> [...]<sup>2</sup></code> <div> <div>1 TEXT</div> <div>2 REFERENCE</div> </div>
<code>\showhyphenationtrace [...]<sup>1</sup> [...]<sup>2</sup></code> <div> <div>OPT</div> <div>1 LANGUAGE</div> <div>2 TEXT</div> </div>
<code>\showhyphens {...}</code> <div> <div>* TEXT</div> </div>

<code>\showinjector [...,*...]</code> <div>OPT</div> *    NAME
<code>\showjustification</code>
<code>\showkerning {...}</code> *    TEXT
<code>\showlayout [...,*...]</code> <div>OPT</div> * <u>pt</u> <u>bp</u> <u>cm</u> mm dd cc pc nd nc sp in
<code>\showlayoutcomponents</code>
<code>\showligature {...}</code> *    TEXT
<code>\showligatures [...]</code> *    FONT
<code>\showlogcategories</code>
<code>\showmakeup [...]</code> <div>OPT</div> * <u>makeup</u> all boxes glyph fontkern hbox vbox vtop kern glue penalty strut whatsit simple simplehbox simplevbox simplevtop user math italic origin reset
<code>\showmargins</code>
<code>\showmessage {...} {...} {...,<u>^</u>...}</code> 1    NAME 2    NAME NUMBER 3    TEXT
<code>\showminimalbaseline</code>
<code>\shownextbox \<u>^</u>... {...}</code> 1    CSNAME 2    CONTENT
<code>\showotfcomposition {...} {...} {...}</code> 1    FONT 2    -1 1 +1 l2r r2l 3    TEXT
<code>\showpalet [...] [...,<u>^</u>...]</code> <div>OPT</div> 1    NAME 2 <u>horizontal</u> vertical number value name

<pre> \showparentchain \<sup>1</sup>... {<sup>2</sup>...}  1 CSNAME 2 NAME </pre>
<pre> \showprint [...,<sup>1</sup>...] [...,<sup>2</sup>...] [...,<sup>3</sup>...,...]                OPT      OPT      OPT 1 inherits: \setuppapersize 2 inherits: \setuppapersize 3 inherits: \setuplayout </pre>
<pre> \showsetups [...,<sup>*</sup>...]                OPT * pt bp <u>cm</u> mm dd cc pc nd nc sp in </pre>
<pre> \showsetupsdefinition [...]  * NAME </pre>
<pre> \showstruts </pre>
<pre> \showsymbolset [...]  * NAME </pre>
<pre> \showtimer {<sup>*</sup>...}  * TEXT </pre>
<pre> \showtokens [...]  * NAME </pre>
<pre> \showtrackers </pre>
<pre> \showvalue {<sup>*</sup>...}  * NAME </pre>
<pre> \showvariable {<sup>1</sup>...} {<sup>2</sup>...}  1 NAME 2 KEY </pre>
<pre> \showwarning {<sup>1</sup>...} {<sup>2</sup>...} {...,<sup>3</sup>...}  1 NAME 2 NAME NUMBER 3 TEXT </pre>
<pre> \simplealignedbox {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...}  1 DIMENSION 2 left right middle flushleft flushright inner outer 3 CONTENT </pre>



`\simplealignedboxplus {...} {...} {...} {...}`

- 1 DIMENSION
- 2 left right middle flushleft flushright inner outer
- 3 TEXT
- 4 CONTENT

`\simplealignedspreadbox {...} {...} {...}`

- 1 DIMENSION
- 2 left right middle flushleft flushright inner outer
- 3 CONTENT

`\simplegroupedcommand {...} {...}`

- 1 COMMAND
- 2 COMMAND

`\simplereversealignedbox {...} {...} {...}`

- 1 DIMENSION
- 2 left right middle flushleft flushright inner outer
- 3 CONTENT

`\simplereversealignedboxplus {...} {...} {...} {...}`

- 1 DIMENSION
- 2 left right middle flushleft flushright inner outer
- 3 TEXT
- 4 CONTENT

`\singalcharacteralign {...} {...}`

- 1 NUMBER
- 2 NUMBER

`\singlebond`

`\sixthofsixarguments {...} {...} {...} {...} {...} {...}`

- 1 TEXT
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT
- 6 TEXT

`\slanted`

`\slantedbold`

`\slicepages [...]`  $[...,\dots,\overset{2}{=}\dots]$   $[...,\dots,\overset{3}{=}\dots]$   
OPT OPT

1 FILE

2 offset = DIMENSION  
hoffset = DIMENSION  
voffset = DIMENSION  
width = DIMENSION  
height = DIMENSION  
n = NUMBER

3 offset = DIMENSION  
hoffset = DIMENSION  
voffset = DIMENSION  
width = DIMENSION  
height = DIMENSION  
n = NUMBER

`\slovenianNumerals {...}`

\* NUMBER

`\sloveniannumerals {...}`

\* NUMBER

`\small`

`\smallbodyfont`

`\smallbold`

`\smallbolditalic`

`\smallboldslanted`

`\smallcapped {...}`

\* TEXT

`\smallcappedcharacters {...}`

\* NUMBER

`\smallcappedromannumerals {...}`

\* NUMBER

`\smaller`

`\smallitalicbold`

`\smallnormal`

`\smallskip`

`\smallslanted`

`\smallslantedbold`

`\smalltype`

$\backslash\text{smash} [\text{...}]^{\text{...}}$ $\text{w h d t b}$ CONTENT
$\backslash\text{smashbox} \dots$ * CSNAME NUMBER
$\backslash\text{smashboxed} \dots$ * CSNAME NUMBER
$\backslash\text{smashedhbox} \dots^{\text{...}}$ TEXT CONTENT
$\backslash\text{smashedvbox} \dots^{\text{...}}$ TEXT CONTENT
$\backslash\text{snaptogrid} [\text{...}]^{\text{...}} \backslash^{\text{...}} \{\text{...}\}$ normal standard yes strict tolerant top bottom both broad fit first last high one low none line strut box min max middle NAME CSNAME CONTENT
$\backslash\text{snaptogrid} [\text{...}]^{\text{...}} \backslash^{\text{...}} \{\text{...}\}$ inherits: $\backslash\text{definegridsnapping}$ CSNAME CONTENT
$\backslash\text{someheadnumber} [\text{...}] [\text{...}]$ SECTION previous current next first last
$\backslash\text{somekindoftab} [\text{...}]^{\text{...}}$ * alternative = horizontal <u>vertical</u> width = DIMENSION height = DIMENSION n = NUMBER m = NUMBER
$\backslash\text{someline} [\text{...}]$ * REFERENCE
$\backslash\text{somelocalfloat}$
$\backslash\text{somenamedheadnumber} \{\text{...}\}^{\text{...}}$ SECTION previous current next first last

<p><code>\someplace {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...} {<sup>4</sup>...} {<sup>5</sup>...} [<sup>6</sup>...]</code></p> <p>1    TEXT</p> <p>2    TEXT</p> <p>3    TEXT</p> <p>4    TEXT</p> <p>5    TEXT</p> <p>6    REFERENCE</p>
<p><code>\somewhere {<sup>1</sup>...} {<sup>2</sup>...} [<sup>3</sup>...]</code></p> <p>1    TEXT</p> <p>2    TEXT</p> <p>3    REFERENCE</p>
<p><code>\SORTING [<sup>1</sup>...] {<sup>2</sup>...}</code>  <small>OPT</small></p> <p>1    NAME</p> <p>2    CONTENT</p> <p>instances: logo</p>
<p><code>\space</code></p>
<p><code>\spanishNumerals {...}</code></p> <p>*    NUMBER</p>
<p><code>\spanishnumerals {...}</code></p> <p>*    NUMBER</p>
<p><code>\splitatasterisk <sup>1</sup>... \<sup>2</sup>... \<sup>3</sup>...</code></p> <p>1    TEXT</p> <p>2    CSNAME</p> <p>3    CSNAME</p>
<p><code>\splitatcolon <sup>1</sup>... \<sup>2</sup>... \<sup>3</sup>...</code></p> <p>1    TEXT</p> <p>2    CSNAME</p> <p>3    CSNAME</p>
<p><code>\splitatcolons <sup>1</sup>... \<sup>2</sup>... \<sup>3</sup>...</code></p> <p>1    TEXT</p> <p>2    CSNAME</p> <p>3    CSNAME</p>
<p><code>\splitatcomma <sup>1</sup>... \<sup>2</sup>... \<sup>3</sup>...</code></p> <p>1    TEXT</p> <p>2    CSNAME</p> <p>3    CSNAME</p>

$\backslash\mathrm{splitatperiod} \dots \overset{1}{\backslash}\dots \overset{2}{\backslash}\dots \overset{3}{\backslash}\dots$  1 TEXT 2 CSNAME 3 CSNAME
$\backslash\mathrm{splitdfrac} \{\overset{1}{\dots}\} \{\overset{2}{\dots}\}$  1 CONTENT 2 CONTENT
$\backslash\mathrm{splitfilename} \{.*\}$  * FILE
$\backslash\mathrm{splitfloat} [\dots,\overset{1}{\dots}\overset{OPT}{=}\dots,\dots] \{\overset{2}{\dots}\} \{\overset{3}{\dots}\}$ 1 inherits: $\backslash\mathrm{setupfloats}$ splitting 2 COMMAND 3 CONTENT
$\backslash\mathrm{splitfrac} \{\overset{1}{\dots}\} \{\overset{2}{\dots}\}$  1 CONTENT 2 CONTENT
$\backslash\mathrm{splitoffbase}$
$\backslash\mathrm{splitofffull}$
$\backslash\mathrm{splitoffkind}$
$\backslash\mathrm{splitoffname}$
$\backslash\mathrm{splitoffpath}$
$\backslash\mathrm{splitoffroot}$
$\backslash\mathrm{splitofftokens} \overset{1}{\dots} \backslash\mathrm{from} \overset{2}{\dots} \backslash\mathrm{to} \overset{3}{\dots}$  1 TEXT 2 TEXT 3 CSNAME
$\backslash\mathrm{splitofftype}$
$\backslash\mathrm{splitstring} \overset{1}{\dots} \backslash\mathrm{at} \overset{2}{\dots} \backslash\mathrm{to} \overset{3}{\dots} \backslash\mathrm{and} \overset{4}{\dots}$  1 TEXT 2 TEXT 3 CSNAME 4 CSNAME
$\backslash\mathrm{spreadhbox} \dots$  * CSNAME NUMBER

$\backslash\text{sqrt}$ $[\dots] \{\overset{1}{\dots}\} \{\overset{2}{\dots}\}$ <small>OPT</small> 1    TEXT 2    CONTENT
$\backslash\text{stackrel}$ $\{\overset{1}{\dots}\} \{\overset{2}{\dots}\}$ 1    CONTENT 2    CONTENT
$\backslash\text{startalignment}$ $[\dots, \dots]^* \dots \backslash\text{stopalignment}$ *    inherits: $\backslash\text{setupalign}$
$\backslash\text{startallmodes}$ $[\dots, \dots]^* \dots \backslash\text{stopallmodes}$ *    NAME
$\backslash\text{startATTACHMENT}$ $[\overset{1}{\dots}] [\dots, \dots, \overset{2}{\dots}, \dots] \dots \backslash\text{stopATTACHMENT}$ <small>OPT</small> <small>OPT</small> 1    NAME 2    inherits: $\backslash\text{setupattachment}$  instances: attachment
$\backslash\text{startattachment}$ $[\overset{1}{\dots}] [\dots, \dots, \overset{2}{\dots}, \dots] \dots \backslash\text{stopattachment}$ <small>OPT</small> <small>OPT</small> 1    NAME 2    inherits: $\backslash\text{setupattachment}$
$\backslash\text{startbackground}$ $[\dots, \dots, \dots]^* \dots \backslash\text{stopbackground}$ <small>OPT</small> *    inherits: $\backslash\text{setupbackground}$
$\backslash\text{startBACKGROUND}$ $[\dots, \dots, \dots]^* \dots \backslash\text{stopBACKGROUND}$ <small>OPT</small> *    inherits: $\backslash\text{setupbackground}$  instances: background
$\backslash\text{startbar}$ $[\dots]^* \dots \backslash\text{stopbar}$ *    NAME
$\backslash\text{startbitmapimage}$ $[\dots, \dots, \dots]^* \dots \backslash\text{stopbitmapimage}$  *    color    = rgb cmyk gray width    = DIMENSION height   = DIMENSION x        = NUMBER y        = NUMBER
$\backslash\text{startbtxrenderingdefinitions}$ $[\dots]^* \dots \backslash\text{stopbtxrenderingdefinitions}$ *    NAME
$\backslash\text{startbuffer}$ $[\dots]^* \dots \backslash\text{stopbuffer}$ <small>OPT</small> *    NAME
$\backslash\text{startBUFFER}$ $\dots \backslash\text{stopBUFFER}$ instances: hiding

<p><code>\startcatcodetable \<sup>*</sup>... \stopcatcodetable</code></p> <p><code>* CSNAME</code></p>
<p><code>\startcenteraligned ... \stopcenteraligned</code></p>
<p><code>\startcharacteralign [<sup>*</sup>...] ... \stopcharacteralign</code></p> <p><small>OPT</small></p> <p><code>* TEXT number-&gt;TEXT text-&gt;TEXT</code></p>
<p><code>\startcheckedfences ... \stopcheckedfences</code></p>
<p><code>\startchemical [<sup>1</sup>...] [<sup>2</sup>...] ... \stopchemical</code></p> <p><small>OPT OPT</small></p> <p>1 NAME</p> <p>2 inherits: \setupchemical</p>
<p><code>\startcollect ... \stopcollect</code></p>
<p><code>\startcollecting ... \stopcollecting</code></p>
<p><code>\startcolor [...]\stopcolor</code></p> <p><code>* COLOR</code></p>
<p><code>\startcolorintent [...]\stopcolorintent</code></p> <p><code>* knockout overprint none</code></p>
<p><code>\startcoloronly [...]\stopcoloronly</code></p> <p><code>* COLOR</code></p>
<p><code>\startcolorset [...]\stopcolorset</code></p> <p><code>* NAME</code></p>
<p><code>\startcolumns [...]\stopcolumns</code></p> <p><small>OPT</small></p> <p><code>* inherits: \setupcolumns</code></p>
<p><code>\startcolumnspan [...]\stopcolumnspan</code></p> <p><small>OPT</small></p> <p><code>* inherits: \setupcolumnspan</code></p>
<p><code>\startcombination [<sup>1</sup>...] [<sup>2</sup>...] ... \stopcombination</code></p> <p><small>OPT OPT</small></p> <p>1 NAME</p> <p>2 inherits: \setupcombination</p>
<p><code>\startcombination [<sup>1</sup>...] [<sup>2</sup>...] ... \stopcombination</code></p> <p><small>OPT OPT</small></p> <p>1 NAME</p> <p>2 N*M</p>
<p><code>\startCOMMENT [<sup>1</sup>...] [<sup>2</sup>...] ... \stopCOMMENT</code></p> <p><small>OPT OPT</small></p> <p>1 TEXT</p> <p>2 inherits: \setupcomment</p> <p><code>instances: comment</code></p>

$\backslash startcomment [\overset{1}{...}] [\overset{2}{...},...,\dots] \dots \backslash stopcomment$ <p>1    TEXT</p> <p>2    inherits: \setupcomment</p>
$\backslash startcomponent [...] \dots \backslash stopcomponent$ <p>*    FILE *</p>
$\backslash startcomponent * \dots \backslash stopcomponent$ <p>*    FILE *</p>
$\backslash startcontextcode \dots \backslash stopcontextcode$
$\backslash startcontextdefinitioncode \dots \backslash stopcontextdefinitioncode$
$\backslash startbtxlabeltext [\overset{1}{...}] [\overset{2}{...}] \dots \backslash stopbtxlabeltext$ <p>1    LANGUAGE</p> <p>2    KEY</p>
$\backslash startheadtext [\overset{1}{...}] [\overset{2}{...}] \dots \backslash stopheadtext$ <p>1    LANGUAGE</p> <p>2    KEY</p>
$\backslash startlabeltext [\overset{1}{...}] [\overset{2}{...}] \dots \backslash stoplabeltext$ <p>1    LANGUAGE</p> <p>2    KEY</p>
$\backslash startmathlabeltext [\overset{1}{...}] [\overset{2}{...}] \dots \backslash stopmathlabeltext$ <p>1    LANGUAGE</p> <p>2    KEY</p>
$\backslash startoperatortext [\overset{1}{...}] [\overset{2}{...}] \dots \backslash stopoperatortext$ <p>1    LANGUAGE</p> <p>2    KEY</p>
$\backslash startprefixtext [\overset{1}{...}] [\overset{2}{...}] \dots \backslash stopprefixtext$ <p>1    LANGUAGE</p> <p>2    KEY</p>
$\backslash startsuffixtext [\overset{1}{...}] [\overset{2}{...}] \dots \backslash stopsuffixtext$ <p>1    LANGUAGE</p> <p>2    KEY</p>
$\backslash starttaglabeltext [\overset{1}{...}] [\overset{2}{...}] \dots \backslash stoptaglabeltext$ <p>1    LANGUAGE</p> <p>2    KEY</p>



$\backslash\text{startunittext} [\overset{1}{\dots}] [\overset{2}{\dots}] \dots \backslash\text{stopunittext}$ $\text{OPT}$ 1 LANGUAGE 2 KEY
$\backslash\text{startctxfunction} \dots \dots \backslash\text{stopctxfunction}$ * NAME
$\backslash\text{startctxfunctiondefinition} \dots \dots \backslash\text{stopctxfunctiondefinition}$ * NAME
$\backslash\text{startcurrentcolor} \dots \backslash\text{stopcurrentcolor}$
$\backslash\text{startcurrentlistentrywrapper} \dots \backslash\text{stopcurrentlistentrywrapper}$
$\backslash\text{startdelimited} [\overset{1}{\dots}] [\overset{2}{\dots}] [\overset{3}{\dots}, \dots] \dots \backslash\text{stopdelimited}$ $\text{OPT} \qquad \text{OPT}$ 1 NAME 2 LANGUAGE 3 inherits: \startnarrower
$\backslash\text{startdelimitedtext} [\overset{1}{\dots}] [\overset{2}{\dots}] [\overset{3}{\dots}, \dots] \dots \backslash\text{stopdelimitedtext}$ $\text{OPT} \qquad \text{OPT}$ 1 NAME 2 LANGUAGE 3 inherits: \startnarrower
$\backslash\text{startDELIMITEDTEXT} [\overset{1}{\dots}] [\overset{2}{\dots}, \dots] \dots \backslash\text{stopDELIMITEDTEXT}$ $\text{OPT} \qquad \text{OPT}$ 1 LANGUAGE 2 inherits: \startnarrower  instances: quotation quote blockquote speech aside
$\backslash\text{startaside} [\overset{1}{\dots}] [\overset{2}{\dots}, \dots] \dots \backslash\text{stopaside}$ $\text{OPT} \qquad \text{OPT}$ 1 LANGUAGE 2 inherits: \startnarrower
$\backslash\text{startblockquote} [\overset{1}{\dots}] [\overset{2}{\dots}, \dots] \dots \backslash\text{stopblockquote}$ $\text{OPT} \qquad \text{OPT}$ 1 LANGUAGE 2 inherits: \startnarrower
$\backslash\text{startquotation} [\overset{1}{\dots}] [\overset{2}{\dots}, \dots] \dots \backslash\text{stopquotation}$ $\text{OPT} \qquad \text{OPT}$ 1 LANGUAGE 2 inherits: \startnarrower
$\backslash\text{startquote} [\overset{1}{\dots}] [\overset{2}{\dots}, \dots] \dots \backslash\text{stopquote}$ $\text{OPT} \qquad \text{OPT}$ 1 LANGUAGE 2 inherits: \startnarrower

$\backslash\textit{startspeech} [\overset{1}{\dots}] [\overset{2}{\dots},\dots] \dots \backslash\textit{stopspeech}$ $\text{OPT} \qquad \text{OPT}$ 1 LANGUAGE 2 inherits: \startnarrower
$\backslash\textit{startDESCRIPTION} [\dots,\overset{*}{\dots},\dots] \dots \backslash\textit{stopDESCRIPTION}$ $\text{OPT}$ * title = TEXT bookmark = TEXT list = TEXT reference = REFERENCE
$\backslash\textit{startDESCRIPTION} [\overset{1}{\dots},\dots] \{\overset{2}{\dots}\} \dots \backslash\textit{stopDESCRIPTION}$ $\text{OPT} \qquad \text{OPT}$ 1 REFERENCE 2 TEXT
$\backslash\textit{startdisplaymath} \dots \backslash\textit{stopdisplaymath}$
$\backslash\textit{startdmath} \dots \backslash\textit{stopdmath}$
$\backslash\textit{startdocument} [\dots,\overset{*}{\dots},\dots] \dots \backslash\textit{stopdocument}$ $\text{OPT}$ * inherits: \setupdocument
$\backslash\textit{starteffect} [\overset{*}{\dots}] \dots \backslash\textit{stopeffect}$ * NAME
$\backslash\textit{startEFFECT} \dots \backslash\textit{stopEFFECT}$
$\backslash\textit{startelement} \{\overset{1}{\dots}\} [\dots,\overset{2}{\dots},\dots] \dots \backslash\textit{stopelement}$ $\text{OPT}$ 1 NAME 2 KEY = VALUE
$\backslash\textit{startembeddedxtable} [\dots,\overset{*}{\dots},\dots] \dots \backslash\textit{stopembeddedxtable}$ $\text{OPT}$ * inherits: \setupxtable
$\backslash\textit{startembeddedxtable} [\overset{*}{\dots}] \dots \backslash\textit{stopembeddedxtable}$ $\text{OPT}$ * NAME
$\backslash\textit{startENUMERATION} [\dots,\overset{*}{\dots},\dots] \dots \backslash\textit{stopENUMERATION}$ $\text{OPT}$ * title = TEXT bookmark = TEXT list = TEXT reference = REFERENCE
$\backslash\textit{startENUMERATION} [\overset{1}{\dots},\dots] \{\overset{2}{\dots}\} \dots \backslash\textit{stopENUMERATION}$ $\text{OPT} \qquad \text{OPT}$ 1 REFERENCE 2 TEXT
$\backslash\textit{startenvironment} [\overset{*}{\dots}] \dots \backslash\textit{stopenvironment}$ * FILE *

<code>\startenvironment ... \stopenvironment</code>  <code>* FILE *</code>
<code>\startexceptions [...] \stopexceptions</code>  <code>* LANGUAGE</code>
<code>\startexpanded ... \stopexpanded</code>
<code>\startexpandedcollect ... \stopexpandedcollect</code>
<code>\startextendedcatcodetable \... \stopextendedcatcodetable</code>  <code>* CSNAME</code>
<code>\startexternalfigurecollection [...] \stopexternalfigurecollection</code>  <code>* NAME</code>
<code>\startfigure [<sup>1</sup>] [<sup>2</sup>] [...<sup>3</sup>...] \stopfigure</code> <div style="text-align: center;"><small>OPT</small></div> <code>1 NAME</code> <code>2 FILE</code> <code>3 inherits: \externalfigure</code>
<code>\startfittingpage [<sup>1</sup>] [...<sup>2</sup>...] \stopfittingpage</code> <div style="text-align: center;"><small>OPT</small></div> <code>1 NAME</code> <code>2 inherits: \setupfittingpage</code>
<code>\startFITTINGPAGE [...<sup>*</sup>...] \stopFITTINGPAGE</code> <div style="text-align: center;"><small>OPT</small></div> <code>* inherits: \setupfittingpage</code>  <b>instances: TEXpage MPpage</b>
<code>\startMPpage [...<sup>*</sup>...] \stopMPpage</code> <div style="text-align: center;"><small>OPT</small></div> <code>* inherits: \setupfittingpage</code>
<code>\startTEXpage [...<sup>*</sup>...] \stopTEXpage</code> <div style="text-align: center;"><small>OPT</small></div> <code>* inherits: \setupfittingpage</code>
<code>\startfixed [...] \stopfixed</code> <div style="text-align: center;"><small>OPT</small></div> <code>* low middle high lohi <u>default</u></code>
<code>\startfloatcombination [...<sup>*</sup>...] \stopfloatcombination</code> <div style="text-align: center;"><small>OPT</small></div> <code>* inherits: \setupcombination</code>
<code>\startfloatcombination [...] \stopfloatcombination</code> <div style="text-align: center;"><small>OPT</small></div> <code>* N*M NAME</code>

`\startFLOATtext [...1,...] [...2,...] {...3} ... \stopFLOATtext`

1 split always left right inner outer backspace cutspace inleft inright inmargin leftmargin rightmargin leftedge rightedge innermargin outermargin inneredge outeredge text opposite reset height depth [-+]line halfline grid high low fit 90 180 270 nonumber none local here force margin [-+]hang hanging tall both middle offset top bottom auto page leftpage rightpage somewhere effective header footer

2 REFERENCE

3 TEXT

instances: chemical figure table intermezzo graphic

`\startfont [...OPT] ... \stopfont`

\* FONT

`\startfontclass [...OPT] ... \stopfontclass`

\* each NAME

`\startfontsolution [...OPT] ... \stopfontsolution`

\* NAME

`\startformula [...OPT,...] ... \stopformula`

\* packed tight middle frame inherits: \setupbodyfont

`\startformulas [...OPT,...] ... \stopformulas`

\* + - REFERENCE

`\startFORMULAformula [...OPT,...] ... \stopFORMULAformula`

\* packed tight middle frame inherits: \setupbodyfont

instances: sp sd mp md

`\startframed [...1,...2,...] ... \stopframed`

1 NAME

2 inherits: \setupframed

`\startframedcontent [...OPT] ... \stopframedcontent`

\* NAME off

`\startFRAMEDTEXT [...1,...2,...] ... \stopFRAMEDTEXT`

1 left right middle none

2 inherits: \setupframedtext

instances: framedtext

`\startframedtext [...1,...2,...] ... \stopframedtext`

1 left right middle none

2 inherits: \setupframedtext

`\startgoto [...OPT] ... \stopgoto`

\* REFERENCE

$\backslash\text{startgridsnapping}$ [ $\dots$ ] ... $\backslash\text{stopgridsnapping}$ <small>OPT</small> * normal standard yes strict tolerant top bottom both broad fit first last high one low none line strut box min max middle NAME
$\backslash\text{startgridsnapping}$ [ $\dots^*,\dots$ ] ... $\backslash\text{stopgridsnapping}$ <small>OPT</small> * inherits: $\backslash\text{definegridsnapping}$
$\backslash\text{starthanging}$ [ $\dots,\dots^{\frac{1}{2}},\dots$ ] $\{\dots^2\}$ ... $\backslash\text{stophanging}$ <small>OPT</small> 1 distance = DIMENSION n = NUMBER location = <u>left</u> right 2 CONTENT
$\backslash\text{starthanging}$ [ $\dots^1$ ] $\{\dots^2\}$ ... $\backslash\text{stophanging}$ <small>OPT</small> 1 <u>left</u> right 2 CONTENT
$\backslash\text{starthboxestohbox}$ ... $\backslash\text{stophboxestohbox}$
$\backslash\text{starthboxregister}$ $\dots^*$ ... $\backslash\text{stophboxregister}$ * CSNAME NUMBER
$\backslash\text{starthead}$ [ $\dots,\dots^1$ ] $\{\dots^2\}$ ... $\backslash\text{stophead}$ <small>OPT</small> 1 REFERENCE 2 TEXT
$\backslash\text{starthelptext}$ [ $\dots^*$ ] ... $\backslash\text{stophelptext}$ <small>OPT</small> * REFERENCE
$\backslash\text{starthelp}$ [ $\dots^*$ ] ... $\backslash\text{stopHELP}$ <small>OPT</small> * REFERENCE  instances: helptext
$\backslash\text{starthelptext}$ [ $\dots^*$ ] ... $\backslash\text{stophelptext}$ <small>OPT</small> * REFERENCE
$\backslash\text{starthighlight}$ [ $\dots^*$ ] ... $\backslash\text{stophighlight}$ * NAME
$\backslash\text{starthyphenation}$ [ $\dots^*,\dots$ ] ... $\backslash\text{stophyphenation}$ * original tex <u>default</u> hyphenate expanded traditional none
$\backslash\text{startimath}$ ... $\backslash\text{stopimath}$
$\backslash\text{startindentedtext}$ [ $\dots^*$ ] ... $\backslash\text{stopindentedtext}$ * NAME
$\backslash\text{startINDENTEDTEXT}$ ... $\backslash\text{stopINDENTEDTEXT}$

<code>\starthiding ... \stophiding</code>
<code>\startinteraction [...] ... \stopinteraction</code> <code>* hidden NAME</code>
<code>\startinteractionmenu [...] ... \stopinteractionmenu</code> <code>* NAME</code>
<code>\startinterface ... \stopinterface</code> <code>* all LANGUAGE</code>
<code>\startintertext ... \stopintertext</code>
<code>\startitem [...<sup>*</sup>...] ... \stopitem</code> <small>OPT</small> <code>* REFERENCE</code>
<code>\startitemgroup [...<sup>1</sup>] [...<sup>2</sup>,...] [...<sup>3</sup>,...,...] ... \stopitemgroup</code> <small>OPT OPT</small> <code>1 NAME</code> <code>2 inherits: \setupitemgroup</code> <code>3 inherits: \setupitemgroup</code>
<code>\startITEMGROUP [...<sup>1</sup>,...] [...<sup>2</sup>,...,...] ... \stopITEMGROUP</code> <small>OPT OPT</small> <code>1 inherits: \setupitemgroup</code> <code>2 inherits: \setupitemgroup</code> <code>instances: itemize</code>
<code>\startJScode ...<sup>1</sup> ...<sup>2</sup> ...<sup>3</sup> ... \stopJScode</code> <code>1 NAME</code> <code>2 uses</code> <code>3 NAME</code>
<code>\startJSreamble ...<sup>1</sup> ...<sup>2</sup> ...<sup>3</sup> ... \stopJSreamble</code> <code>1 NAME</code> <code>2 used</code> <code>3 now later</code>
<code>\startknockout ... \stopknockout</code>
<code>\startLABELtext [...<sup>1</sup>] [...<sup>2</sup>] ... \stopLABELtext</code> <small>OPT</small> <code>1 LANGUAGE</code> <code>2 KEY</code> <code>instances: head label mathlabel taglabel unit operator prefix suffix btxlabel</code>
<code>\startlayout [...] ... \stoplayout</code> <code>* NAME</code>
<code>\startleftaligned ... \stopleftaligned</code>

<code>\startline [...]</code>  *   REFERENCE
<code>\startlinealignment [...] ... \stoplinealignment</code>  *   left middle right max
<code>\startlinecorrection [...,<sup>1</sup>...] ... \stoplinecorrection</code> <div style="text-align: center;"><small>OPT</small></div> *   blank inherits: \blank
<code>\startlinefiller [...<sup>1</sup>] [...,<sup>2</sup>...] ... \stoplinefiller</code> <div style="text-align: center;"><small>OPT</small></div> 1   filler NAME 2   inherits: \setuplinefiller
<code>\startLINENOTE [...<sup>1</sup>] {...<sup>2</sup>...}</code>  1   REFERENCE 2   TEXT  instances: linenote
<code>\stoplinenote [...]</code>  *   REFERENCE
<code>\startlinenumbering [...<sup>1</sup>] [...,<sup>2</sup>...] ... \stoplinenumbering</code> <div style="text-align: center;"><small>OPT                      OPT</small></div> 1   NAME  2   continue   =   yes no start       =   NUMBER step        =   NUMBER method      =   page <u>first</u> next
<code>\startlinenumbering [...<sup>1</sup>] [...<sup>2</sup>] ... \stoplinenumbering</code> <div style="text-align: center;"><small>OPT                      OPT</small></div> 1   NAME 2   continue NUMBER
<code>\startLINES [...,<sup>*</sup>...] ... \stopLINES</code> <div style="text-align: center;"><small>OPT</small></div> *   inherits: \setuplines  instances: lines
<code>\startlinetable ... \stoplinetable</code>
<code>\startlinetablebody ... \stoplinetablebody</code>
<code>\startlinetablecell [...,<sup>*</sup>...] ... \stoplinetablecell</code> <div style="text-align: center;"><small>OPT</small></div> *   inherits: \setuplinetable
<code>\startlinetablehead ... \stoplinetablehead</code>
<code>\startlocalfootnotes ... \stoplocalfootnotes</code>
<code>\startlocalheadsetup ... \stoplocalheadsetup</code>

<pre> \startlocallinecorrection [...,*...] ... \stoplocallinecorrection                                 OPT *   blank inherits: \blank </pre>
<pre> \startlocalnotes [...,*...] ... \stoplocalnotes *   NAME </pre>
<pre> \startlocalsetups [...<sup>1</sup>...] [...<sup>2</sup>...] ... \stoplocalsetups                                 OPT 1   grid 2   NAME </pre>
<pre> \startlocalsetups .* ... \stoplocalsetups *   NAME </pre>
<pre> \startlua ... \stoplua </pre>
<pre> \startluacode ... \stopluacode </pre>
<pre> \startluaparameterset [...] ... \stopluaparameterset *   NAME </pre>
<pre> \startluasetups [...<sup>1</sup>...] [...<sup>2</sup>...] ... \stopluasetups                                 OPT 1   grid 2   NAME </pre>
<pre> \startluasetups .* ... \stopluasetups *   NAME </pre>
<pre> \startMPclip {...} ... \stopMPclip *   NAME </pre>
<pre> \startMPcode {...} ... \stopMPcode                 OPT *   NAME </pre>
<pre> \startMPdefinitions {...} ... \stopMPdefinitions                     OPT *   NAME </pre>
<pre> \startMPdrawing [...<sup>1</sup>...] ... \stopMPdrawing                     OPT *   - </pre>
<pre> \startMPenvironment [...<sup>1</sup>...] ... \stopMPenvironment                     OPT *   reset global + </pre>
<pre> \startMPextensions {...,*...} ... \stopMPextensions                     OPT *   NAME </pre>
<pre> \startMPinclusions [...<sup>1</sup>...] {...<sup>2</sup>...} ... \stopMPinclusions                     OPT      OPT 1   + 2   NAME </pre>



<code>\startMPinitializations ... \stopMPinitializations</code>
<code>\startMPpositiongraphic {...} {...,<sup>2</sup>...} ... \stopMPpositiongraphic</code> <small>OPT</small> 1 NAME 2 KEY
<code>\startMPpositionmethod {...} ... \stopMPpositionmethod</code> * NAME
<code>\startMPrun {...} ... \stopMPrun</code> <small>OPT</small> * NAME
<code>\startmakeup [...]<sup>1</sup> [...,<sup>2</sup>...]<sub>OPT</sub> ... \stopmakeup</code> 1 NAME 2 inherits: \setupmakeup
<code>\startMAKEUPmakeup [...]<sup>*</sup>...]<sub>OPT</sub> ... \stopMAKEUPmakeup</code> * inherits: \setupmakeup  instances: standard page text middle
<code>\startmiddlemakeup [...]<sup>*</sup>...]<sub>OPT</sub> ... \stopmiddlemakeup</code> * inherits: \setupmakeup
<code>\startpagemakeup [...]<sup>*</sup>...]<sub>OPT</sub> ... \stoppagemakeup</code> * inherits: \setupmakeup
<code>\startstandardmakeup [...]<sup>*</sup>...]<sub>OPT</sub> ... \stopstandardmakeup</code> * inherits: \setupmakeup
<code>\starttextmakeup [...]<sup>*</sup>...]<sub>OPT</sub> ... \stoptextmakeup</code> * inherits: \setupmakeup
<code>\startmarginblock [...]<sub>OPT</sub> ... \stopmarginblock</code> * NAME
<code>\startmarginrule [...]<sub>OPT</sub> ... \stopmarginrule</code> * NUMBER
<code>\startmarginrule [...]<sup>*</sup>...]<sub>OPT</sub> ... \stopmarginrule</code> * inherits: \setupmarginrule
<code>\startmarkedcontent [...]<sub>OPT</sub> ... \stopmarkedcontent</code> * reset <u>all</u> NAME
<code>\startMATHALIGNMENT [...]<sup>*</sup>...]<sub>OPT</sub> ... \stopMATHALIGNMENT</code> * inherits: \setupmathalignment  instances: align mathalignment

$\backslash startMATHCASES [\dots,\overset{*}{=}\dots] \dots \backslash stopMATHCASES$ <p><small>OPT</small></p> <p>* inherits: \setupmathcases</p> <p>instances: cases mathcases</p>
$\backslash startMATHMATRIX [\dots,\overset{*}{=}\dots] \dots \backslash stopMATHMATRIX$ <p><small>OPT</small></p> <p>* inherits: \setupmathmatrix</p> <p>instances: matrix mathmatrix</p>
$\backslash startmathmode \dots \backslash stopmathmode$
$\backslash startmathstyle [\dots,\dots] \dots \backslash stopmathstyle$ <p>* display text script scriptscript cramped uncramped normal packed small big NAME</p>
$\backslash startmatrices [\dots,\overset{*}{=}\dots] \dots \backslash stopmatrices$ <p><small>OPT</small></p> <p>* inherits: \setupmathmatrix</p>
$\backslash startmaxaligned \dots \backslash stopmaxaligned$
$\backslash startmidaligned \dots \backslash stopmidaligned$
$\backslash startmiddlealigned \dots \backslash stopmiddlealigned$
$\backslash startmixedcolumns [\overset{1}{\dots}] [\dots,\overset{2}{=}\dots] \dots \backslash stopmixedcolumns$ <p><small>OPT</small>      <small>OPT</small></p> <p>1 NAME</p> <p>2 inherits: \setupmixedcolumns</p>
$\backslash startMIXEDCOLUMNS [\dots,\overset{*}{=}\dots] \dots \backslash stopMIXEDCOLUMNS$ <p><small>OPT</small></p> <p>* inherits: \setupmixedcolumns</p> <p>instances: itemgroupcolumns boxedcolumns</p>
$\backslash startboxedcolumns [\dots,\overset{*}{=}\dots] \dots \backslash stopboxedcolumns$ <p><small>OPT</small></p> <p>* inherits: \setupmixedcolumns</p>
$\backslash startitemgroupcolumns [\dots,\overset{*}{=}\dots] \dots \backslash stopitemgroupcolumns$ <p><small>OPT</small></p> <p>* inherits: \setupmixedcolumns</p>
$\backslash startmode [\dots,\dots] \dots \backslash stopmode$ <p>* NAME</p>
$\backslash startmodeset [\dots,\overset{1}{\dots}] \{\overset{2}{\dots}\} \dots \backslash stopmodeset$ <p>1 NAME default</p> <p>2 CONTENT</p>
$\backslash startmodule [\overset{*}{\dots}] \dots \backslash stopmodule$ <p>* FILE</p>
$\backslash startmoduletestsection \dots \backslash stopmoduletestsection$

<pre> \startmodule ... \stopmodule  * FILE </pre>
<pre> \startnamedsection [...]<sup>1</sup> [...]<sup>2</sup> [...] [...] [...] [...] \stopnamedsection                         OPT      OPT 1  SECTION 2  title      = TEXT    bookmark   = TEXT    marking    = TEXT    list       = TEXT    reference  = REFERENCE    ownnumber  = TEXT 3  KEY = VALUE </pre>
<pre> \startnamedsubformulas [...]<sup>1</sup> {...}<sup>2</sup> [...] \stopnamedsubformulas                         OPT 1  + - REFERENCE 2  TEXT </pre>
<pre> \startnarrow [...]<sup>1</sup> [...]<sup>2</sup> [...] \stopnarrow               OPT      OPT 1  NAME 2  inherits: \setupnarrower </pre>
<pre> \startnarrower [...]<sup>*</sup> [...] \stopnarrower                 OPT *  [-+]left [-+]middle [-+]right NUMBER*left NUMBER*middle NUMBER*right reset </pre>
<pre> \startNARROWER [...]<sup>*</sup> [...] \stopNARROWER                 OPT *  [-+]left [-+]middle [-+]right NUMBER*left NUMBER*middle NUMBER*right reset </pre>
<pre> \startnarrow [...]<sup>1</sup> [...]<sup>2</sup> [...] \stopnarrow               OPT      OPT 1  inherits: \setupnarrower 2  [-+]left [-+]middle [-+]right NUMBER*left NUMBER*middle NUMBER*right reset </pre>
<pre> \startnarrow [...]<sup>1</sup> [...]<sup>2</sup> [...] \stopnarrow               OPT      OPT 1  NAME 2  [-+]left [-+]middle [-+]right NUMBER*left NUMBER*middle NUMBER*right reset </pre>
<pre> \startnegative ... \stopnegative </pre>
<pre> \startnicelyfilledbox [...]<sup>*</sup> [...] \stopnicelyfilledbox                       OPT *  width  = DIMENSION    height = DIMENSION    offset = DIMENSION    strut  = <u>yes</u> no </pre>
<pre> \startnointerference ... \stopnointerference </pre>
<pre> \startnotallmodes [...]<sup>*</sup> [...] \stopnotallmodes *  NAME </pre>
<pre> \startnotext ... \stopnotext </pre>

<pre> \startNOTE [...,*...] ... \stopNOTE               OPT *   REFERENCE  instances: footnote endnote </pre>
<pre> \startNOTE [...,*=...,...] ... \stopNOTE               OPT *   title      = TEXT     bookmark   = TEXT     list       = TEXT     reference  = REFERENCE  instances: footnote endnote </pre>
<pre> \startendnote [...,*...] ... \stopendnote               OPT *   REFERENCE </pre>
<pre> \startfootnote [...,*...] ... \stopfootnote               OPT *   REFERENCE </pre>
<pre> \startnotmode [...,*...] ... \stopnotmode *   NAME </pre>
<pre> \startopposite ... \stopopposite </pre>
<pre> \startoutputstream [...*] ... \stopoutputstream *   NAME </pre>
<pre> \startoverlay ... \stopoverlay </pre>
<pre> \startoverprint ... \stopoverprint </pre>
<pre> \startpacked [...*] ... \stoppacked               OPT *   blank </pre>
<pre> \startpagecomment ... \stoppagecomment </pre>
<pre> \startpagefigure [<sup>1</sup>...] [...,*=<sup>2</sup>...,...] ... \stoppagefigure                   OPT 1   FILE 2   inherits: \setupexternalfigure </pre>
<pre> \startpagegrid [<sup>1</sup>...] [...,*=<sup>2</sup>...,...] ... \stoppagegrid                OPT      OPT 1   NAME 2   inherits: \setuppagegrid </pre>
<pre> \startpagegridspan [<sup>1</sup>...] [...,*=<sup>2</sup>...,...] ... \stoppagegridspan                    OPT      OPT 1   NAME 2   inherits: \setuppagegridspan </pre>
<pre> \startPAGEGRID [...,*=...,...] ... \stopPAGEGRID               OPT *   inherits: \setuppagegrid </pre>

`\startpagelayout [...] ... \stoppagelayout`

`* page leftpage rightpage`

`\startpar [1...] [OPT...,...2...,...]OPT ... \stoppar`

1 NAME

2 inherits: \setupparagraph

`\startparagraph [1...] [OPT...,...2...,...]OPT ... \stopparagraph`

1 NAME

2 inherits: \setupparagraph

`\startparagraphs [...] ... \stopparagraphs`

`* NAME`

`\startparagraphscell ... \stopparagraphscell`

`\startPARAGRAPHS ... \stopPARAGRAPHS`

`\startPARALLEL ... \stopPARALLEL`

`\startparbuilder [...] ... \stopparbuilder`

`* default oneline basic NAME`

`\startplacefloat [1...] [OPT...,...2...,...]OPT [OPT...,...3...,...]OPT ... \stopplacefloat`

1 SINGULAR

2 title = TEXT

bookmark = TEXT

marking = TEXT

list = TEXT

location = split always left right inner outer backspace cutspace inleft inright inmargin leftmargin rightmargin  
leftedge rightedge innermargin outermargin inneredge outeredge text opposite reset height depth  
[-+]line halfline grid high low fit 90 180 270 nonumber none local here force margin [-+]hang  
hanging tall both middle offset top bottom auto page leftpage rightpage somewhere effective header  
footer

reference = REFERENCE

3 KEY = VALUE

`\startplaceFLOAT [OPT...,...1...,...]OPT [OPT...,...2...,...]OPT ... \stopplaceFLOAT`

1 title = TEXT

bookmark = TEXT

marking = TEXT

list = TEXT

location = split always left right inner outer backspace cutspace inleft inright inmargin leftmargin rightmargin  
leftedge rightedge innermargin outermargin inneredge outeredge text opposite reset height depth  
[-+]line halfline grid high low fit 90 180 270 nonumber none local here force margin [-+]hang  
hanging tall both middle offset top bottom auto page leftpage rightpage somewhere effective header  
footer

reference = REFERENCE

2 KEY = VALUE

`instances: chemical figure table intermezzo graphic`

```
\startplacechemical [...,\substack{1}{...},...] [...,\substack{2}{...},...] ... \stopplacechemical
```

```
1 title = TEXT
bookmark = TEXT
marking = TEXT
list = TEXT
location = split always left right inner outer backspace cutspace inleft inright inmargin leftmargin rightmargin
leftedge rightedge innermargin outermargin inneredge outeredge text opposite reset height depth
[-+]line halfline grid high low fit 90 180 270 nonumber none local here force margin [-+]hang
hanging tall both middle offset top bottom auto page leftpage rightpage somewhere effective header
footer
reference = REFERENCE

2 KEY = VALUE
```

```
\startplacefigure [...,\substack{1}{...},...] [...,\substack{2}{...},...] ... \stopplacefigure
```

```
1 title = TEXT
bookmark = TEXT
marking = TEXT
list = TEXT
location = split always left right inner outer backspace cutspace inleft inright inmargin leftmargin rightmargin
leftedge rightedge innermargin outermargin inneredge outeredge text opposite reset height depth
[-+]line halfline grid high low fit 90 180 270 nonumber none local here force margin [-+]hang
hanging tall both middle offset top bottom auto page leftpage rightpage somewhere effective header
footer
reference = REFERENCE

2 KEY = VALUE
```

```
\startplacegraphic [...,\substack{1}{...},...] [...,\substack{2}{...},...] ... \stopplacegraphic
```

```
1 title = TEXT
bookmark = TEXT
marking = TEXT
list = TEXT
location = split always left right inner outer backspace cutspace inleft inright inmargin leftmargin rightmargin
leftedge rightedge innermargin outermargin inneredge outeredge text opposite reset height depth
[-+]line halfline grid high low fit 90 180 270 nonumber none local here force margin [-+]hang
hanging tall both middle offset top bottom auto page leftpage rightpage somewhere effective header
footer
reference = REFERENCE

2 KEY = VALUE
```

```
\startplaceintermezzo [...,\substack{1}{...},...] [...,\substack{2}{...},...] ... \stopplaceintermezzo
```

```
1 title = TEXT
bookmark = TEXT
marking = TEXT
list = TEXT
location = split always left right inner outer backspace cutspace inleft inright inmargin leftmargin rightmargin
leftedge rightedge innermargin outermargin inneredge outeredge text opposite reset height depth
[-+]line halfline grid high low fit 90 180 270 nonumber none local here force margin [-+]hang
hanging tall both middle offset top bottom auto page leftpage rightpage somewhere effective header
footer
reference = REFERENCE

2 KEY = VALUE
```

```
\startplacetable [...,\substack{1}{...},...] [...,\substack{2}{...},...] ... \stopplacetable
```

```
1 title = TEXT
bookmark = TEXT
marking = TEXT
list = TEXT
location = split always left right inner outer backspace cutspace inleft inright inmargin leftmargin rightmargin
leftedge rightedge innermargin outermargin inneredge outeredge text opposite reset height depth
[-+]line halfline grid high low fit 90 180 270 nonumber none local here force margin [-+]hang
hanging tall both middle offset top bottom auto page leftpage rightpage somewhere effective header
footer
reference = REFERENCE

2 KEY = VALUE
```

<pre> \startplaceformula [...,\stackrel{*}{...}] ... \stopplaceformula                                 OPT *   title      = TEXT     suffix     = TEXT     reference  = + - REFERENCE </pre>
<pre> \startplaceformula [...,\stackrel{*}{...}] ... \stopplaceformula                                 OPT *   + - REFERENCE </pre>
<pre> \startplacepairedbox [...,\stackrel{2}{...}] ... \stopplacepairedbox                                 OPT 1   NAME 2   inherits: \setuppairedbox </pre>
<pre> \startplacePAIREDBOX [...,\stackrel{*}{...}] ... \stopplacePAIREDBOX                                 OPT *   inherits: \setuppairedbox  instances: legend </pre>
<pre> \startplacelegend [...,\stackrel{*}{...}] ... \stopplacelegend                                 OPT *   inherits: \setuppairedbox </pre>
<pre> \startpositioning [...,\stackrel{2}{...}] ... \stoppositioning                                 OPT   OPT 1   NAME 2   inherits: \setuppositioning </pre>
<pre> \startpositionoverlay {...} ... \stoppositionoverlay *   NAME </pre>
<pre> \startpositive ... \stoppositive </pre>
<pre> \startpostponing [...,\stackrel{*}{...}] ... \stoppostponing                                 OPT *   [-+]NUMBER </pre>
<pre> \startprocessassignmentcommand [...,\stackrel{*}{...}] ... \stopprocessassignmentcommand *   KEY  = VALUE </pre>
<pre> \startprocessassignmentlist [...,\stackrel{*}{...}] ... \stopprocessassignmentlist *   KEY  = VALUE </pre>
<pre> \startprocesscommacommand [...,\stackrel{*}{...}] ... \stopprocesscommacommand *   COMMAND </pre>
<pre> \startprocesscommalist [...,\stackrel{*}{...}] ... \stopprocesscommalist *   COMMAND </pre>
<pre> \startproduct [...] ... \stopproduct *   FILE * </pre>
<pre> \startproduct ... ... \stopproduct *   FILE * </pre>

<pre> \startproject [...] ... \stopproject  *   FILE   * </pre>
<pre> \startproject ... ... \stopproject  *   FILE   * </pre>
<pre> \startprotectedcolors ... \stopprotectedcolors </pre>
<pre> \startpublication [<sup>1</sup>...] [<sup>2</sup>...,...<sub>OPT</sub>] ... \stoppublication 1  NAME 2  tag      = REFERENCE    category = TEXT    k        = REFERENCE    t        = TEXT </pre>
<pre> \starandomized ... \stoprandomized </pre>
<pre> \starawsetups [<sup>1</sup>...] [<sup>2</sup>...] ... \stoprawsetups 1  grid 2  NAME </pre>
<pre> \starawsetups ... ... \stoprawsetups  *   NAME </pre>
<pre> \startreadingfile ... \stopreadingfile </pre>
<pre> \startregime [...] ... \stopregime  *   inherits: \enableregime </pre>
<pre> \startregister [<sup>1</sup>...] [<sup>2</sup>...] [<sub>OPT</sub>...<sub>OPT</sub>] [<sup>4</sup>...] [...<sup>5</sup>+...+...] 1  NAME 2  NAME 3  TEXT 4  TEXT PROCESSOR-&gt;TEXT 5  INDEX </pre>
<pre> \startreusableMPgraphic {<sup>1</sup>...} {<sup>2</sup>...,...<sub>OPT</sub>} ... \stopreusableMPgraphic 1  NAME 2  KEY </pre>
<pre> \startrightaligned ... \stoprightaligned </pre>
<pre> \startscript [...] ... \stopscript  *   hangul hanzi nihongo ethiopic thai test NAME </pre>
<pre> \startsectionblock [<sup>1</sup>...] [<sub>OPT</sub>...,...<sup>2</sup>...,...<sub>OPT</sub>] ... \stopsectionblock 1  NAME 2  bookmark = TEXT    inherits: \setupsectionblock </pre>



<pre> \startsectionblockenvironment [...] ... \stopsectionblockenvironment  *   NAME </pre>
<pre> \startSECTIONBLOCK [...,..<sup>*</sup>...,...] ... \stopSECTIONBLOCK                                 OPT *   bookmark = TEXT     inherits: \setupsectionblock  instances: frontmatter bodymatter appendices backmatter </pre>
<pre> \startappendices [...,..<sup>*</sup>...,...] ... \stopappendices                                 OPT *   bookmark = TEXT     inherits: \setupsectionblock </pre>
<pre> \startbackmatter [...,..<sup>*</sup>...,...] ... \stopbackmatter                                 OPT *   bookmark = TEXT     inherits: \setupsectionblock </pre>
<pre> \startbodymatter [...,..<sup>*</sup>...,...] ... \stopbodymatter                                 OPT *   bookmark = TEXT     inherits: \setupsectionblock </pre>
<pre> \startfrontmatter [...,..<sup>*</sup>...,...] ... \stopfrontmatter                                 OPT *   bookmark = TEXT     inherits: \setupsectionblock </pre>
<pre> \startsectionlevel [<sup>1</sup>...] [<sup>2</sup>...,...] [<sup>3</sup>...,...] ... \stopsectionlevel                    OPT      OPT      OPT 1   NAME  2   title      = TEXT     bookmark    = TEXT     marking     = TEXT     list        = TEXT     reference   = REFERENCE     ownnumber   = TEXT  3   KEY = VALUE </pre>
<pre> \startSECTION [...,..<sup>1</sup>...,...] [...,..<sup>2</sup>...,...] ... \stopSECTION                OPT      OPT 1   title      = TEXT     bookmark    = TEXT     marking     = TEXT     list        = TEXT     reference   = REFERENCE     ownnumber   = TEXT  2   KEY = VALUE  instances: part chapter section subsection subsubsection subsubsubsection subsubsubsubsection title subject subsubject subsubsubject subsubsubsubject subsubsubsubsubject </pre>
<pre> \startchapter [...,..<sup>1</sup>...,...] [...,..<sup>2</sup>...,...] ... \stopchapter                OPT      OPT 1   title      = TEXT     bookmark    = TEXT     marking     = TEXT     list        = TEXT     reference   = REFERENCE     ownnumber   = TEXT  2   KEY = VALUE </pre>

`\startpart [...,\u{1}...,...]\u{2}...,...]\dots\stoppart`  
OPT OPT

1 title = TEXT  
bookmark = TEXT  
marking = TEXT  
list = TEXT  
reference = REFERENCE  
ownnumber = TEXT

2 KEY = VALUE

`\startsection [...,\u{1}...,...]\u{2}...,...]\dots\stopsection`  
OPT OPT

1 title = TEXT  
bookmark = TEXT  
marking = TEXT  
list = TEXT  
reference = REFERENCE  
ownnumber = TEXT

2 KEY = VALUE

`\startsubject [...,\u{1}...,...]\u{2}...,...]\dots\stopsubject`  
OPT OPT

1 title = TEXT  
bookmark = TEXT  
marking = TEXT  
list = TEXT  
reference = REFERENCE  
ownnumber = TEXT

2 KEY = VALUE

`\startsubsection [...,\u{1}...,...]\u{2}...,...]\dots\stopsubsection`  
OPT OPT

1 title = TEXT  
bookmark = TEXT  
marking = TEXT  
list = TEXT  
reference = REFERENCE  
ownnumber = TEXT

2 KEY = VALUE

`\startsubsubject [...,\u{1}...,...]\u{2}...,...]\dots\stopsubsubject`  
OPT OPT

1 title = TEXT  
bookmark = TEXT  
marking = TEXT  
list = TEXT  
reference = REFERENCE  
ownnumber = TEXT

2 KEY = VALUE

`\startsubsubsection [...,\u{1}...,...]\u{2}...,...]\dots\stopsubsubsection`  
OPT OPT

1 title = TEXT  
bookmark = TEXT  
marking = TEXT  
list = TEXT  
reference = REFERENCE  
ownnumber = TEXT

2 KEY = VALUE

`\startsubsubsubject [...,\u{1}...,...]\u{2}...,...]\dots\stopsubsubsubject`  
OPT OPT

1 title = TEXT  
bookmark = TEXT  
marking = TEXT  
list = TEXT  
reference = REFERENCE  
ownnumber = TEXT

2 KEY = VALUE

```

\startsubsubsection [...,\subscript{1}...,\subscript{2}...] ... \stopsubsubsection
                                OPT          OPT

1  title      = TEXT
   bookmark  = TEXT
   marking   = TEXT
   list      = TEXT
   reference = REFERENCE
   ownnumber = TEXT

2  KEY = VALUE

```

```

\startsubsubsubject [...,\subscript{1}...,\subscript{2}...] ... \stopsubsubsubject
                                OPT          OPT

1  title      = TEXT
   bookmark  = TEXT
   marking   = TEXT
   list      = TEXT
   reference = REFERENCE
   ownnumber = TEXT

2  KEY = VALUE

```

```

\startsubsubsubsubsection [...,\subscript{1}...,\subscript{2}...] ... \stopsubsubsubsubsection
                                OPT          OPT

1  title      = TEXT
   bookmark  = TEXT
   marking   = TEXT
   list      = TEXT
   reference = REFERENCE
   ownnumber = TEXT

2  KEY = VALUE

```

```

\startsubsubsubsubsubject [...,\subscript{1}...,\subscript{2}...] ... \stopsubsubsubsubsubject
                                OPT          OPT

1  title      = TEXT
   bookmark  = TEXT
   marking   = TEXT
   list      = TEXT
   reference = REFERENCE
   ownnumber = TEXT

2  KEY = VALUE

```

```

\starttitle [...,\subscript{1}...,\subscript{2}...] ... \stoptitle
                                OPT          OPT

1  title      = TEXT
   bookmark  = TEXT
   marking   = TEXT
   list      = TEXT
   reference = REFERENCE
   ownnumber = TEXT

2  KEY = VALUE

```

```

\startitemize [...,\subscript{1}...,\subscript{2}...] ... \stopitemize
                                OPT          OPT

1  inherits: \setupitemgroup
2  inherits: \setupitemgroup

```

```

\startlines [...,\subscript{*}...] ... \stoplines
                                OPT

*  inherits: \setuptolines

```

```

\startalign [...,\subscript{*}...] ... \stopalign
                                OPT

*  inherits: \setupmathalignment

```

```

\startmathalignment [...,\subscript{*}...] ... \stopmathalignment
                                OPT

*  inherits: \setupmathalignment

```

$\backslash startcases [\dots,*\dots] \dots \backslash stopcases$ <small>OPT</small> * inherits: $\backslash setupmathcases$
$\backslash startmathcases [\dots,*\dots] \dots \backslash stopmathcases$ <small>OPT</small> * inherits: $\backslash setupmathcases$
$\backslash startmathmatrix [\dots,*\dots] \dots \backslash stopmathmatrix$ <small>OPT</small> * inherits: $\backslash setupmathmatrix$
$\backslash startmatrix [\dots,*\dots] \dots \backslash stopmatrix$ <small>OPT</small> * inherits: $\backslash setupmathmatrix$
$\backslash startsetups [\dots^1] [\dots^2] \dots \backslash stopsetups$ <small>OPT</small> 1 grid 2 NAME
$\backslash startmdformula [\dots,*\dots] \dots \backslash stopmdformula$ <small>OPT</small> * packed tight middle frame inherits: $\backslash setupbodyfont$
$\backslash startmpformula [\dots,*\dots] \dots \backslash stopmpformula$ <small>OPT</small> * packed tight middle frame inherits: $\backslash setupbodyfont$
$\backslash startsdformula [\dots,*\dots] \dots \backslash stopsdformula$ <small>OPT</small> * packed tight middle frame inherits: $\backslash setupbodyfont$
$\backslash startspformula [\dots,*\dots] \dots \backslash stopspformula$ <small>OPT</small> * packed tight middle frame inherits: $\backslash setupbodyfont$
$\backslash startsetups \dots \dots \backslash stopsetups$ * NAME
$\backslash startLUA [\dots,*\dots] \dots \backslash stopLUA$ <small>OPT</small> * inherits: $\backslash setuptyping$
$\backslash startMP [\dots,*\dots] \dots \backslash stopMP$ <small>OPT</small> * inherits: $\backslash setuptyping$
$\backslash startPARSEDXML [\dots,*\dots] \dots \backslash stopPARSEDXML$ <small>OPT</small> * inherits: $\backslash setuptyping$
$\backslash startTEX [\dots,*\dots] \dots \backslash stopTEX$ <small>OPT</small> * inherits: $\backslash setuptyping$
$\backslash startttyping [\dots,*\dots] \dots \backslash stoptyping$ <small>OPT</small> * inherits: $\backslash setuptyping$
$\backslash startXML [\dots,*\dots] \dots \backslash stopXML$ <small>OPT</small> * inherits: $\backslash setuptyping$

$\backslash\text{startshift}$ [...] ... $\backslash\text{stopshift}$ *    NAME
$\backslash\text{startsidebar}$ [ <sup>1</sup> ...] [ <small>OPT</small> ..., <sup>2</sup> ..., <small>OPT</small> ...] ... $\backslash\text{stopsidebar}$ 1    NAME 2    inherits: $\backslash\text{setupsidebar}$
$\backslash\text{startsimplecolumns}$ [ <small>OPT</small> ..., <sup>*</sup> ..., <small>OPT</small> ...] ... $\backslash\text{stopsimplecolumns}$ *    inherits: $\backslash\text{setsimplecolumnhsize}$
$\backslash\text{startspecialitem}$ [ <sup>1</sup> ...] [ <small>OPT</small> ..., <sup>2</sup> ..., <small>OPT</small> ...] ... $\backslash\text{stopspecialitem}$ 1 <u>item</u> 2    REFERENCE
$\backslash\text{startspecialitem}$ [...] ... $\backslash\text{stopspecialitem}$ *    sub its
$\backslash\text{startspecialitem}$ [ <sup>1</sup> ...] { <sup>2</sup> ...} ... $\backslash\text{stopspecialitem}$ 1    sym ran mar 2    TEXT
$\backslash\text{startspread}$ ... $\backslash\text{stopspread}$
$\backslash\text{start}$ [ <small>OPT</small> ...] ... $\backslash\text{stop}$ *    NAME
$\backslash\text{startSTARTSTOP}$ ... $\backslash\text{stopSTARTSTOP}$
$\backslash\text{startstaticMPfigure}$ {...} ... $\backslash\text{stopstaticMPfigure}$ *    NAME
$\backslash\text{startstaticMPgraphic}$ { <sup>1</sup> ...} { <small>OPT</small> ..., <sup>2</sup> ..., <small>OPT</small> ...} ... $\backslash\text{stopstaticMPgraphic}$ 1    NAME 2    KEY
$\backslash\text{STARTSTOP}$ {...} *    CONTENT
$\backslash\text{startstrictinspectnextcharacter}$ ... $\backslash\text{stopstrictinspectnextcharacter}$

`\startstructurepageregister [...]1 [...]2 [...,...3...,...]4 [...,...4...,...]OPT`

```
1  NAME
2  NAME
3  label      = NAME
    keys      = TEXT PROCESSOR->TEXT
    entries   = TEXT PROCESSOR->TEXT
    keys:1    = TEXT
    keys:2    = TEXT
    keys:3    = TEXT
    entries:1 = TEXT
    entries:2 = TEXT
    entries:3 = TEXT
    alternative = TEXT
4  KEY = VALUE
```

`\startstyle [...,...*...,...]OPT ... \stopstyle`

`* inherits: \setupstyle`

`\startstyle [...]* ... \stopstyle`

`* NAME FONT`

`\startSTYLE ... \stopSTYLE`

`\startsubformulas [...,...*...,...]OPT ... \stopsubformulas`

`* + - REFERENCE`

`\startsubjectlevel [...]1 [...,...2...,...]OPT [...,...3...,...]OPT ... \stopsubjectlevel`

```
1  NAME
2  title      = TEXT
    bookmark  = TEXT
    marking   = TEXT
    list      = TEXT
    reference = REFERENCE
    ownnumber = TEXT
3  KEY = VALUE
```

`\startsubsentence ... \stopsubsentence`

`\startsubstack ... \stopsubstack`

`\startsymbolset [...]* ... \stopsymbolset`

`* NAME`

`\startTABLE [...,...*...,...]OPT ... \stopTABLE`

`* inherits: \setupTABLE`

`\startTABLEbody [...,...*...,...]OPT ... \stopTABLEbody`

`* inherits: \setupTABLE`

`\startTABLEfoot [...,...*...,...]OPT ... \stopTABLEfoot`

`* inherits: \setupTABLE`

`\startTABLEhead [...,...*...,...]OPT ... \stopTABLEhead`

`* inherits: \setupTABLE`

$\backslash\text{startTABLEnext}$ [ $\dots,\dots^{\text{1}}\dots$ ] ... $\backslash\text{stopTABLEnext}$ <small>OPT</small> * inherits: $\backslash\text{setupTABLE}$
$\backslash\text{starttable}$ [ $\dots^{\text{1}}\dots$ ] [ $\dots,\dots^{\text{2}}\dots$ ] ... $\backslash\text{stoptable}$ <small>OPT</small> 1 TEMPLATE 2 inherits: $\backslash\text{setuptables}$
$\backslash\text{starttablehead}$ [ $\dots$ ] ... $\backslash\text{stoptablehead}$ * NAME
$\backslash\text{starttables}$ [ $\dots^{\text{1}}\dots$ ] ... $\backslash\text{stoptables}$ * TEMPLATE
$\backslash\text{starttables}$ [ $\dots$ ] ... $\backslash\text{stoptables}$ * NAME
$\backslash\text{starttabletail}$ [ $\dots$ ] ... $\backslash\text{stoptabletail}$ * NAME
$\backslash\text{starttable}$ [ $\dots^{\text{1}}\dots$ ] [ $\dots,\dots^{\text{2}}\dots$ ] ... $\backslash\text{stoptable}$ <small>OPT</small> 1 NAME 2 inherits: $\backslash\text{setuptables}$
$\backslash\text{starttabulate}$ [ $\dots^{\text{1}}\dots$ ] [ $\dots,\dots^{\text{2}}\dots$ ] ... $\backslash\text{stoptabulate}$ <small>OPT</small> <small>OPT</small> 1 TEMPLATE 2 inherits: $\backslash\text{setuptabulate}$
$\backslash\text{starttabulatehead}$ [ $\dots^{\text{1}}\dots$ ] ... $\backslash\text{stoptabulatehead}$ <small>OPT</small> * NAME
$\backslash\text{starttabulatetail}$ [ $\dots^{\text{1}}\dots$ ] ... $\backslash\text{stoptabulatetail}$ <small>OPT</small> * NAME
$\backslash\text{startTABULATE}$ [ $\dots^{\text{1}}\dots$ ] [ $\dots,\dots^{\text{2}}\dots$ ] ... $\backslash\text{stopTABULATE}$ <small>OPT</small> <small>OPT</small> 1 NAME 2 inherits: $\backslash\text{setuptabulate}$ instances: legend fact
$\backslash\text{startfact}$ [ $\dots^{\text{1}}\dots$ ] [ $\dots,\dots^{\text{2}}\dots$ ] ... $\backslash\text{stopfact}$ <small>OPT</small> <small>OPT</small> 1 NAME 2 inherits: $\backslash\text{setuptabulate}$
$\backslash\text{startlegend}$ [ $\dots^{\text{1}}\dots$ ] [ $\dots,\dots^{\text{2}}\dots$ ] ... $\backslash\text{stoplegend}$ <small>OPT</small> <small>OPT</small> 1 NAME 2 inherits: $\backslash\text{setuptabulate}$

$\backslash startTABULATION [\overset{1}{...}] [\dots, \dots, \overset{2}{...}, \dots] \dots \backslash stopTABULATION$ $\begin{array}{ccccc} & \text{OPT} & & \text{OPT} & \end{array}$ <div> 1 NAME 2 inherits: \setuptabulation </div>
$\backslash starttexcode \dots \backslash stoptexcode$
$\backslash starttexdefinition \overset{1}{...} \overset{2}{...} \overset{3}{...} \overset{4}{...} \overset{5}{...} \overset{6}{...} \overset{7}{...} \dots \backslash stoptexdefinition$ $\begin{array}{ccccccc} & \text{OPT} & \text{OPT} & \text{OPT} & \text{OPT} & \text{OPT} & \text{OPT} & \end{array}$ <div> 1 spaces nospaces 2 global 3 unexpanded 4 expanded 5 singleempty doubleempty tripleempty quadrupleempty quintupleempty sextupleempty singleargument doubleargument tripleargument quadrupleargument quintupleargument sextupleargument 6 NAME 7 TEMPLATE </div>
$\backslash starttext \dots \backslash stoptext$
$\backslash starttextbackground [\overset{1}{...}] [\dots, \dots, \overset{2}{...}, \dots] \dots \backslash stoptextbackground$ $\begin{array}{ccc} & & \text{OPT} & \end{array}$ <div> 1 NAME 2 inherits: \setuptextbackground </div>
$\backslash starttextbackgroundmanual \dots \backslash stoptextbackgroundmanual$
$\backslash startTEXTBACKGROUND [\dots, \dots, \overset{*}{...}, \dots] \dots \backslash stopTEXTBACKGROUND$ $\begin{array}{ccc} & & \text{OPT} & \end{array}$ <div> * inherits: \setuptextbackground </div>
$\backslash starttextcolor [\overset{*}{...}] \dots \backslash stoptextcolor$ <div> * COLOR </div>
$\backslash starttextcolorintent \dots \backslash stoptextcolorintent$
$\backslash starttextflow [\overset{*}{...}] \dots \backslash stoptextflow$ <div> * NAME </div>
$\backslash starttextrule \{\overset{*}{...}\} \dots \backslash stoptextrule$ <div> * TEXT </div>
$\backslash starttokens [\overset{*}{...}] \dots \backslash stoptokens$ <div> * NAME </div>
$\backslash starttransparent [\overset{*}{...}] \dots \backslash stoptransparent$ <div> * COLOR </div>
$\backslash starttypescript [\overset{1}{...}, \dots] [\dots, \overset{2}{...}] [\dots, \overset{3}{...}] \dots \backslash stoptypescript$ $\begin{array}{ccc} & \text{OPT} & \text{OPT} & \text{OPT} & \end{array}$ <div> 1 serif sans mono math handwriting calligraphy 2 NAME 3 size name </div>



$\backslash\text{starttypescriptcollection} [\dots] \dots \backslash\text{stoptypescriptcollection}$ $\ast$ NAME
$\backslash\text{startTYPING} [\dots, \overset{\text{OPT}}{\ast} \dots, \dots] \dots \backslash\text{stopTYPING}$ $\ast$ inherits: $\backslash\text{setuptyping}$ instances: typing LUA MP PARSEDXML TEX XML
$\backslash\text{startTYPING} [\dots, \overset{\text{OPT}}{\ast} \dots] \dots \backslash\text{stopTYPING}$ $\ast$ continue instances: typing LUA MP PARSEDXML TEX XML
$\backslash\text{startuniqueMPgraphic} \{\overset{1}{\dots}\} \{\dots, \overset{2}{\ast} \dots\} \dots \backslash\text{stopuniqueMPgraphic}$ 1 NAME 2 KEY
$\backslash\text{startuniqueMPpagegraphic} \{\overset{1}{\dots}\} \{\dots, \overset{2}{\ast} \dots\} \dots \backslash\text{stopuniqueMPpagegraphic}$ 1 NAME 2 KEY
$\backslash\text{startunpacked} \dots \backslash\text{stopunpacked}$
$\backslash\text{startusableMPgraphic} \{\overset{1}{\dots}\} \{\dots, \overset{2}{\ast} \dots\} \dots \backslash\text{stopusableMPgraphic}$ 1 NAME 2 KEY
$\backslash\text{startuseMPgraphic} \{\overset{1}{\dots}\} \{\dots, \overset{2}{\ast} \dots\} \dots \backslash\text{stopuseMPgraphic}$ 1 NAME 2 KEY
$\backslash\text{startusemathstyleparameter} \backslash \dots \dots \backslash\text{stopusemathstyleparameter}$ $\ast$ CSNAME
$\backslash\text{startusingbtxs specification} [\dots] \dots \backslash\text{stopusingbtxs specification}$ $\ast$ NAME
$\backslash\text{startvboxregister} \dots \dots \backslash\text{stopvboxregister}$ $\ast$ CSNAME NUMBER
$\backslash\text{startvboxtohbox} \dots \backslash\text{stopvboxtohbox}$
$\backslash\text{startvboxtohboxseparator} \dots \backslash\text{stopvboxtohboxseparator}$
$\backslash\text{startviewerlayer} [\dots] \dots \backslash\text{stopviewerlayer}$ $\ast$ NAME
$\backslash\text{startVIEWERLAYER} \dots \backslash\text{stopVIEWERLAYER}$

`\startvtopregister ... .. \stopvtopregister`

`* CSNAME NUMBER`

`\startxcell [...]1 [...,...2...,...]2 ... \stopxcell`  
OPT OPT

1 NAME

2 nx = NUMBER  
ny = NUMBER  
nc = NUMBER  
nr = NUMBER  
inherits: \setupxtable

`\startxcellgroup [...]1 [...,...2...,...]2 ... \stopxcellgroup`  
OPT OPT

1 NAME

2 inherits: \setupxtable

`\startxgroup [...]1 [...,...2...,...]2 ... \stopxgroup`  
OPT OPT

1 NAME

2 inherits: \setupxtable

`\startxmldisplayverbatim [...]* ... \stopxmldisplayverbatim`

`* NAME`

`\startxmllineverbatim [...]* ... \stopxmllineverbatim`

`* NAME`

`\startxmlraw ... \stopxmlraw`

`\startxmlsetups [...]1 [...]2 ... \stopxmlsetups`  
OPT

1 grid

2 NAME

`\startxmlsetups ... .. \stopxmlsetups`

`* NAME`

`\startxrow [...]1 [...,...2...,...]2 ... \stopxrow`  
OPT OPT

1 NAME

2 inherits: \setupxtable

`\startxrowgroup [...]1 [...,...2...,...]2 ... \stopxrowgroup`  
OPT OPT

1 NAME

2 inherits: \setupxtable

`\startxtable [...,...*...,...]* ... \stopxtable`  
OPT

`* inherits: \setupxtable`

`\startxtablebody [...,...*...,...]* ... \stopxtablebody`  
OPT

`* inherits: \setupxtable`

$\backslash\text{startxtablebody}$ [ $\dots$ ] $\dots$ $\backslash\text{stopxtablebody}$ <small>OPT</small> *    NAME
$\backslash\text{startxtablefoot}$ [ $\dots,\dots,\overset{*}{=}\dots,\dots$ ] $\dots$ $\backslash\text{stopxtablefoot}$ <small>OPT</small> *    inherits: $\backslash\text{setupxtable}$
$\backslash\text{startxtablefoot}$ [ $\dots$ ] $\dots$ $\backslash\text{stopxtablefoot}$ <small>OPT</small> *    NAME
$\backslash\text{startxtablehead}$ [ $\dots,\dots,\overset{*}{=}\dots,\dots$ ] $\dots$ $\backslash\text{stopxtablehead}$ <small>OPT</small> *    inherits: $\backslash\text{setupxtable}$
$\backslash\text{startxtablehead}$ [ $\dots$ ] $\dots$ $\backslash\text{stopxtablehead}$ <small>OPT</small> *    NAME
$\backslash\text{startxtablenext}$ [ $\dots,\dots,\overset{*}{=}\dots,\dots$ ] $\dots$ $\backslash\text{stopxtablenext}$ <small>OPT</small> *    inherits: $\backslash\text{setupxtable}$
$\backslash\text{startxtablenext}$ [ $\dots$ ] $\dots$ $\backslash\text{stopxtablenext}$ <small>OPT</small> *    NAME
$\backslash\text{startXTABLE}$ [ $\dots,\dots,\overset{*}{=}\dots,\dots$ ] $\dots$ $\backslash\text{stopXTABLE}$ <small>OPT</small> *    inherits: $\backslash\text{setupxtable}$
$\backslash\text{startxtable}$ [ $\overset{*}{=}\dots$ ] $\dots$ $\backslash\text{stopxtable}$ <small>OPT</small> *    NAME
$\backslash\text{stopline}$ [ $\dots$ ] *    REFERENCE
$\backslash\text{stopLINENOTE}$ [ $\dots$ ] *    REFERENCE  instances: linenote
$\backslash\text{stopregister}$ [ $\overset{1}{=}\dots$ ] [ $\overset{2}{=}\dots$ ]  1    NAME 2    NAME
$\backslash\text{stopstructurepageregister}$ [ $\overset{1}{=}\dots$ ] [ $\overset{2}{=}\dots$ ]  1    NAME 2    NAME
$\backslash\text{stretched}$ [ $\dots,\dots,\overset{1}{=}\dots,\dots$ ] { $\overset{2}{=}\dots$ } <small>OPT</small> 1    inherits: $\backslash\text{setupstretched}$ 2    TEXT

<code>\strictdoifelsenextoptional {...} {...}</code>  1    TRUE 2    FALSE
<code>\strictdoifnextoptionalelse {...} {...}</code>  1    TRUE 2    FALSE
<code>\stripcharacter ... \from ... \to ...</code>  1    CHARACTER 2    TEXT 3    CSNAME
<code>\strippedcsname \*..</code>  *    CSNAME
<code>\strippedcsname ...</code>  *    TEXT
<code>\stripspaces \from ... \to ...</code>  1    TEXT 2    CSNAME
<code>\structurelistuservariable {...}</code>  *    KEY
<code>\structurenumber</code>
<code>\structuretitle</code>
<code>\structureuservariable {...}</code>  *    KEY
<code>\structurevariable {...}</code>  *    KEY
<code>\strut</code>
<code>\strutdp</code>
<code>\strutht</code>
<code>\struthtdp</code>
<code>\struttedbox {...}</code>  *    CONTENT
<code>\strutwd</code>

<code>\style [...<sup>1</sup>...<sup>2</sup>] {...}</code> 1 inherits: \setupstyle 2 TEXT
<code>\styleinstance [...]</code> * NAME
<code>\style [...<sup>1</sup>] {...<sup>2</sup>}</code> 1 NAME FONT 2 TEXT
<code>\STYLE {...}</code> * TEXT
<code>\subpagenumber</code>
<code>\subsentence {...}</code> * CONTENT
<code>\substituteincommalist {...<sup>1</sup>} {...<sup>2</sup>} \...<sup>3</sup></code> 1 TEXT 2 TEXT 3 CSNAME
<code>\subtractfeature [...]</code> * NAME
<code>\subtractfeature {...}</code> * NAME
<code>\swapcounts \...<sup>1</sup> \...<sup>2</sup></code> 1 CSNAME 2 CSNAME
<code>\swapdimens \...<sup>1</sup> \...<sup>2</sup></code> 1 CSNAME 2 CSNAME
<code>\swapface</code>
<code>\swapmacros \...<sup>1</sup> \...<sup>2</sup></code> 1 CSNAME 2 CSNAME
<code>\swaptypeface</code>
<code>\switchstyleonly [...]</code> * rm ss tt hw cg roman serif regular sans sansserif support type teletype mono handwritten calligraphic

<code>\switchstyleonly \*</code> <code>* CSNAME</code>
<code>\switchtobodyfont [...*,...]</code> <code>* inherits: \setupbodyfont</code>
<code>\switchtocolour [...]</code> <code>* COLOR</code>
<code>\switchtointerlinespace [...,<sup>1</sup>...] [...,<sup>2</sup>...]</code> <small>OPT</small> <code>1 NAME</code> <code>2 inherits: \setupinterlinespace</code>
<code>\switchtointerlinespace [...*,...]</code> <small>OPT</small> <code>* on off reset auto small medium big NUMBER DIMENSION</code>
<code>\switchtointerlinespace [...]</code> <code>* NAME</code>
<code>\symbol [...<sup>1</sup>] [...<sup>2</sup>]</code> <small>OPT</small> <code>1 NAME</code> <code>2 NAME</code>
<code>\symbolreference [...]</code> <code>* REFERENCE</code>
<code>\symbol {...}</code> <code>* NAME</code>
<code>\synchronizeblank</code>
<code>\synchronizeindenting</code>
<code>\synchronizemarking [...<sup>1</sup>] [...<sup>2</sup>] [...<sup>3</sup>]</code> <small>OPT</small> <code>1 MARK</code> <code>2 NUMBER</code> <code>3 keep</code>
<code>\synchronizeoutputstreams [...*,...]</code> <code>* NAME</code>
<code>\synchronizestrut {...}</code> <code>* yes no auto cap fit line default CHARACTER</code>
<code>\synchronizewhitespace</code>

$\backslash$ SYNONYM [ <sup>1</sup> ...] { <sup>2</sup> ...} { <sup>3</sup> ...} <small>OPT</small> 1 NAME 2 TEXT 3 CONTENT instances: abbreviation
$\backslash$ systemlog { <sup>1</sup> ...} { <sup>2</sup> ...} { <sup>3</sup> ...} 1 FILE 2 TEXT 3 TEXT
$\backslash$ systemlogfirst { <sup>1</sup> ...} { <sup>2</sup> ...} { <sup>3</sup> ...} 1 FILE 2 TEXT 3 TEXT
$\backslash$ systemloglast { <sup>1</sup> ...} { <sup>2</sup> ...} { <sup>3</sup> ...} 1 FILE 2 TEXT 3 TEXT
$\backslash$ systemsetups { <sup>1</sup> ...} * NAME
$\backslash$ TABLE
$\backslash$ TaBlE
$\backslash$ TEX
$\backslash$ TeX
$\backslash$ TheNormalizedFontSize
$\backslash$ TransparencyHack
$\backslash$ tabulateautoline
$\backslash$ tabulateautorule
$\backslash$ tabulateline
$\backslash$ tabulaterule
$\backslash$ taggedctxcommand { <sup>1</sup> ...} * COMMAND

`\taggedlabeltexts {...} {...} {...}`

- 1 NAME
- 2 NAME
- 3 CONTENT

`\tbox {...}`

- \* CONTENT

`\tequal {...} {...}`  
OPT OPT

- 1 TEXT
- 2 TEXT

`\testandsplitstring ... \at ... \to ... \and ...`

- 1 TEXT
- 2 TEXT
- 3 CSNAME
- 4 CSNAME

`\testcolumn [...] [...]`  
OPT

- 1 NUMBER
- 2 DIMENSION

`\testfeature {...} {...}`

- 1 NUMBER
- 2 CONTENT

`\testfeatureonce {...} {...}`

- 1 NUMBER
- 2 CONTENT

`\testpage [...] [...]`  
OPT

- 1 NUMBER
- 2 DIMENSION

`\testpageonly [...] [...]`  
OPT

- 1 NUMBER
- 2 DIMENSION

`\testpagesync [...] [...]`  
OPT

- 1 NUMBER
- 2 DIMENSION

`\testtokens [...]`

- \* NAME

`\tex {...}`

- \* CONTENT



`\texdefinition {...}`

\* NAME

`\texsetup {...}`

\* NAME

`\TEXTBACKGROUND {...}`

\* CONTENT

`\textcitation [...1...] [...2]`  
OPT

1 reference = REFERENCE  
alternative = default category entry short page num textnum year index tag keywords author authoryears authornum  
authoryear  
before = COMMAND  
after = COMMAND  
left = COMMAND  
right = COMMAND  
inherits: \setupbtx

2 REFERENCE

`\textcitation [...1...] [...2]`  
OPT

1 default category entry short page num textnum year index tag keywords author authoryears authornum authoryear

2 REFERENCE

`\textcitation [...1...] [...2...]`

1 reference = REFERENCE  
alternative = default category entry short page num textnum year index tag keywords author authoryears authornum  
authoryear  
before = COMMAND  
after = COMMAND  
left = COMMAND  
right = COMMAND  
inherits: \setupbtx

2 KEY = VALUE

`\textcite [...1...] [...2]`  
OPT

1 reference = REFERENCE  
alternative = default category entry short page num textnum year index tag keywords author authoryears authornum  
authoryear  
before = COMMAND  
after = COMMAND  
left = COMMAND  
right = COMMAND  
inherits: \setupbtx

2 REFERENCE

`\textcite [...1...] [...2]`  
OPT

1 default category entry short page num textnum year index tag keywords author authoryears authornum authoryear

2 REFERENCE

`\textcite [...,\sup{1}...,...]` `[...,\sup{2}...,...]`

```
1  reference      = REFERENCE
   alternative    = default category entry short page num textnum year index tag keywords author authoryears authornum
                        authoryear
   before         = COMMAND
   after          = COMMAND
   left           = COMMAND
   right          = COMMAND
   inherits: \setupbtx
2  KEY = VALUE
```

`\textcontrolspace`

`\textflowcollector {...}`

\* NAME

`\textmath {...}`

\* CONTENT

`\textminus`

`\textormathchar {...}`

\* NUMBER

`\textplus`

`\textreference [...,\sup{1}...,...]` `{...\sup{2}...}`

1 REFERENCE

2 TEXT

`\textrule [...,\sup{1}...] {...,\sup{2}...}`  
                  OPT          OPT

1 top middle bottom

2 TEXT

`\textvisiblespace`

`\thainumerals {...}`

\* NUMBER

`\thefirstcharacter {...}`

\* TEXT

`\thenormalizedbodyfontsize {...}`

\* DIMENSION

`\theremainingcharacters {...}`

\* TEXT

`\thickspace`

`\thinrule`

$\backslash\text{thinrules}$ $[...,\overset{\text{OPT}}{...}=...,...]$ $\ast$ inherits: $\backslash\text{setupthinrules}$
$\backslash\text{thinspace}$
$\backslash\text{thirddoffivearguments}$ $\{.^1.\}\{.^2.\}\{.^3.\}\{.^4.\}\{.^5.\}$ 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT
$\backslash\text{thirddoffourarguments}$ $\{.^1.\}\{.^2.\}\{.^3.\}\{.^4.\}$ 1 TEXT 2 TEXT 3 TEXT 4 TEXT
$\backslash\text{thirddofsixarguments}$ $\{.^1.\}\{.^2.\}\{.^3.\}\{.^4.\}\{.^5.\}\{.^6.\}$ 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT
$\backslash\text{thirddofthreearguments}$ $\{.^1.\}\{.^2.\}\{.^3.\}$ 1 TEXT 2 TEXT 3 TEXT
$\backslash\text{thirddofthreeunexpanded}$ $\{.^1.\}\{.^2.\}\{.^3.\}$ 1 TEXT 2 TEXT 3 TEXT
$\backslash\text{thookleftarrow}$ $\{.^1.\}\overset{\text{OPT}}{\{.^2.\}}$ 1 TEXT 2 TEXT
$\backslash\text{thookrightarrow}$ $\{.^1.\}\overset{\text{OPT}}{\{.^2.\}}$ 1 TEXT 2 TEXT
$\backslash\text{threedigitrounding}$ $\{.^{\ast}.\}$ $\ast$ NUMBER

$\backslash\text{tibetan numerals}$ $\{...\}$ *    NUMBER
$\backslash\text{tight layer}$ $[...]$ *    NAME
$\backslash\text{tilde}$ $\{...\}$ *    CHARACTER
$\backslash\text{tiny font}$
$\backslash\text{tLeftarrow}$ $\overset{1}{\{...\}} \overset{2}{\{...\}}$ 1    TEXT 2    TEXT
$\backslash\text{tLeftrightarrow}$ $\overset{1}{\{...\}} \overset{2}{\{...\}}$ 1    TEXT 2    TEXT
$\backslash\text{tlap}$ $\{...\}$ *    CONTENT
$\backslash\text{tleftarrow}$ $\overset{1}{\{...\}} \overset{2}{\{...\}}$ 1    TEXT 2    TEXT
$\backslash\text{tlefttharpoondown}$ $\overset{1}{\{...\}} \overset{2}{\{...\}}$ 1    TEXT 2    TEXT
$\backslash\text{tlefttharpoonup}$ $\overset{1}{\{...\}} \overset{2}{\{...\}}$ 1    TEXT 2    TEXT
$\backslash\text{tleftrightarrow}$ $\overset{1}{\{...\}} \overset{2}{\{...\}}$ 1    TEXT 2    TEXT
$\backslash\text{tleftrightharpoons}$ $\overset{1}{\{...\}} \overset{2}{\{...\}}$ 1    TEXT 2    TEXT
$\backslash\text{tmapsto}$ $\overset{1}{\{...\}} \overset{2}{\{...\}}$ 1    TEXT 2    TEXT
$\backslash\text{tochar}$ $\{...\}$ *    e:NAME x:NUMBER d:NUMBER s:NUMBER i:NUMBER n:NAME c:NAME u:NAME a:NAME

<p><code>\tolinenote [...]</code></p> <p>*   REFERENCE</p>
<p><code>\TOOLTIP [...,<sup>1</sup>...,<sup>2</sup>...,<sup>3</sup>...] {...} {...}</code>  <small>OPT</small></p> <p>1   inherits: \setuptooltip</p> <p>2   TEXT</p> <p>3   TEXT</p> <p>instances: tooltip</p>
<p><code>\TOOLTIP [<sup>1</sup>...] {<sup>2</sup>...} {<sup>3</sup>...}</code>  <small>OPT</small></p> <p>1   left middle right</p> <p>2   TEXT</p> <p>3   TEXT</p> <p>instances: tooltip</p>
<p><code>\topbox {...}</code></p> <p>*   CONTENT</p>
<p><code>\topleftbox {...}</code></p> <p>*   CONTENT</p>
<p><code>\toplinebox {...}</code></p> <p>*   CONTENT</p>
<p><code>\toprightbox {...}</code></p> <p>*   CONTENT</p>
<p><code>\topskippedbox {...}</code></p> <p>*   CONTENT</p>
<p><code>\tRightarrow {<sup>1</sup>...} {<sup>2</sup>...}</code>  <small>OPT           OPT</small></p> <p>1   TEXT</p> <p>2   TEXT</p>
<p><code>\tracecatcodetables</code></p>
<p><code>\tracedfontname {...}</code></p> <p>*   FONT</p>
<p><code>\traceoutputroutines</code></p>
<p><code>\tracepositions</code></p>
<p><code>\translate [...,<sup>*</sup>...,...] <small>OPT</small></code></p> <p>*   LANGUAGE = TEXT</p>

$\backslash$ transparencypart {...} *    COLOR
$\backslash$ transparent [ <sup>1</sup> ] { <sup>2</sup> .} 1    COLOR 2    CONTENT
$\backslash$ trrel { <sup>1</sup> .} { <sup>2</sup> .} OPT        OPT 1    TEXT 2    TEXT
$\backslash$ trightharpoon [ <sup>1</sup> .] { <sup>2</sup> .} OPT        OPT 1    TEXT 2    TEXT
$\backslash$ trightharpoonup [ <sup>1</sup> .] { <sup>2</sup> .} OPT        OPT 1    TEXT 2    TEXT
$\backslash$ trightharpoondown [ <sup>1</sup> .] { <sup>2</sup> .} OPT        OPT 1    TEXT 2    TEXT
$\backslash$ trightharpoonup [ <sup>1</sup> .] { <sup>2</sup> .} OPT        OPT 1    TEXT 2    TEXT
$\backslash$ triggleftharpoons [ <sup>1</sup> .] { <sup>2</sup> .} OPT        OPT 1    TEXT 2    TEXT
$\backslash$ trightoverleftarrow [ <sup>1</sup> .] { <sup>2</sup> .} OPT        OPT 1    TEXT 2    TEXT
$\backslash$ triplebond
$\backslash$ truefilename {...} *    FILE
$\backslash$ truefontname {...} *    FONT
$\backslash$ tttraggedright
$\backslash$ tttriplerel { <sup>1</sup> .} { <sup>2</sup> .} OPT        OPT 1    TEXT 2    TEXT
$\backslash$ ttwoheadleftarrow [ <sup>1</sup> .] { <sup>2</sup> .} OPT        OPT 1    TEXT 2    TEXT

$\backslash\text{twoheadrightarrow}$ $\overset{1}{\{...\}}$ $\overset{2}{\{...\}}$ <small>OPT OPT</small> 1 TEXT 2 TEXT
$\backslash\text{twodigitrounding}$ $\{...\}$ * NUMBER
$\backslash\text{tx}$
$\backslash\text{txx}$
$\backslash\text{typ}$ $[\dots,\overset{1}{\equiv}\dots]$ $\overset{2}{\{...\}}$ <small>OPT</small> 1 inherits: $\backslash\text{setuptype}$ 2 CONTENT
$\backslash\text{type}$ $[\dots,\overset{1}{\equiv}\dots]$ $\overset{2}{\{...\}}$ <small>OPT</small> 1 inherits: $\backslash\text{setuptype}$ 2 CONTENT
$\backslash\text{typebuffer}$ $[\dots,\overset{1}{\equiv}\dots]$ $[\dots,\overset{2}{\equiv}\dots]$ <small>OPT OPT</small> 1 BUFFER 2 inherits: $\backslash\text{setuptyping}$
$\backslash\text{typeBUFFER}$ $[\dots,\overset{*}{\equiv}\dots]$ <small>OPT</small> * inherits: $\backslash\text{setuptyping}$
$\backslash\text{typedefinedbuffer}$ $[\dots]$ $[\dots,\overset{2}{\equiv}\dots]$ <small>OPT</small> 1 BUFFER 2 inherits: $\backslash\text{setuptyping}$
$\backslash\text{typeface}$
$\backslash\text{typefile}$ $[\overset{1}{\dots}]$ $[\dots,\overset{2}{\equiv}\dots]$ $\overset{3}{\{...\}}$ <small>OPT OPT</small> 1 NAME 2 inherits: $\backslash\text{setuptyping}$ 3 FILE
$\backslash\text{typescriptone}$
$\backslash\text{typescriptprefix}$ $\{...\}$ * NAME
$\backslash\text{typescriptthree}$
$\backslash\text{typescripttwo}$

$\backslash\text{typesetbuffer}$ $\overset{1}{[...]} \overset{2}{[...,...]}$ <small>OPT OPT</small> 1   *   BUFFER 2   inherits: \setupeexternalfigure
$\backslash\text{typesetfile}$ $\overset{1}{[...]} \overset{2}{[...]} \overset{3}{[...,...]}$ <small>OPT OPT</small> 1   NAME FILE 2   FILE TEXT 3   inherits: \setupeexternalfigure
$\backslash\text{type}$ $\overset{1}{[...,...]} <<\overset{2}{...}>$ <small>OPT</small> 1   inherits: \setuptype 2   ANGLES
$\backslash\text{TYPE}$ $\overset{1}{[...,...]} \{\overset{2}{...}\}$ <small>OPT</small> 1   inherits: \setuptype 2   CONTENT
$\backslash\text{TYPE}$ $\overset{1}{[...,...]} <<\overset{2}{...}>$ <small>OPT</small> 1   inherits: \setuptype 2   ANGLES
$\backslash\text{typ}$ $\overset{1}{[...,...]} <<\overset{2}{...}>$ <small>OPT</small> 1   inherits: \setuptype 2   ANGLES
$\backslash\text{uconvertnumber}$ $\{\overset{1}{...}\} \{\overset{2}{...}\}$ 1   inherits: \convertnumber 2   NUMBER
$\backslash\text{uedcatcodecommand}$ $\overset{1}{...} \overset{2}{...} \{\overset{3}{...}\}$ 1   CSNAME 2   CHARACTER NUMBER 3   COMMAND
$\backslash\text{undefinevalue}$ $\{\overset{*}{...}\}$ *   NAME
$\backslash\text{undepthed}$ $\{\overset{*}{...}\}$ *   CONTENT
$\backslash\text{underbar}$ $\{\overset{*}{...}\}$ *   TEXT
$\backslash\text{underbartext}$ $\{\overset{1}{...}\} \{\overset{2}{...}\}$ 1   TEXT 2   TEXT



$\underbrace{\dots}$ * TEXT
$\underbracetext{\dots}{\dots}$ 1 TEXT 2 TEXT
$\underbracket{\dots}$ * TEXT
$\underbrackettext{\dots}{\dots}$ 1 TEXT 2 TEXT
$\underleftarrow{\dots}$ * TEXT
$\underleftharpoonowdown{\dots}$ * TEXT
$\underleftharpoonowup{\dots}$ * TEXT
$\underleftrightharrow{\dots}$ * TEXT
$\underparent{\dots}$ * TEXT
$\underparenttext{\dots}{\dots}$ 1 TEXT 2 TEXT
$\underrightharrow{\dots}$ * TEXT
$\underrightharpoonowdown{\dots}$ * TEXT
$\underrightharpoonowup{\dots}$ * TEXT
$\underset{\dots}{\dots}$ 1 TEXT 2 TEXT
$\undertwoheadleftarrow{\dots}$ * TEXT

$\backslash$ undertwoheadrightarrow {...} * TEXT
$\backslash$ undoassign [...] <sup>1</sup> [...] <sup>2</sup> .. 1 TEXT 2 KEY = VALUE
$\backslash$ unhhbox ... <sup>1</sup> \with {...} <sup>2</sup> .. 1 CSNAME NUMBER 2 COMMAND
$\backslash$ unihex {...} * NUMBER
$\backslash$ uniqueMPgraphic {...} <sup>1</sup> {..., <sup>2</sup> .. <sup>OPT</sup> .. 1 NAME 2 KEY = VALUE
$\backslash$ uniqueMPpagegraphic {...} <sup>1</sup> {..., <sup>2</sup> .. <sup>OPT</sup> .. 1 NAME 2 KEY = VALUE
$\backslash$ UNIT {...} * CONTENT  instances: unit
$\backslash$ unknown
$\backslash$ unprotect ... \protect
$\backslash$ unprotected ... <sup>*</sup> \par * CONTENT
$\backslash$ unregisterhyphenationpattern [...] <sup>1</sup> [...] <sup>2</sup> .. 1 LANGUAGE 2 TEXT
$\backslash$ unspaceafter \... <sup>1</sup> {...} <sup>2</sup> .. 1 CSNAME 2 TEXT
$\backslash$ unspaceargument ... <sup>1</sup> \to \... <sup>2</sup> .. 1 TEXT 2 CSNAME
$\backslash$ unspaced {...} * TEXT

<code>\unspacestring <sup>1</sup> \to <sup>2</sup>...</code> 1    TEXT 2    CSNAME
<code>\untexargument {...} \to <sup>2</sup>...</code> 1    TEXT 2    CSNAME
<code>\untexcommand {...} \to <sup>2</sup>...</code> 1    CSNAME 2    CSNAME
<code>\uppercased {...}</code> *    TEXT
<code>\uppercasestring <sup>1</sup> \to <sup>2</sup>...</code> 1    TEXT 2    CSNAME
<code>\upperlefthdoubleninequote</code>
<code>\upperlefthdoublesixquote</code>
<code>\upperleftsingleninequote</code>
<code>\upperleftsinglesixquote</code>
<code>\upperrighthdoubleninequote</code>
<code>\upperrighthdoublesixquote</code>
<code>\upperrightsingleninequote</code>
<code>\upperrightsinglesixquote</code>
<code>\url [...]</code> *    NAME
<code>\usealignparameter \^...</code> *    CSNAME
<code>\useblankparameter \^...</code> *    CSNAME
<code>\useblocks [...<sup>1</sup>,...] [...<sup>2</sup><sub>OPT</sub>,...] [...<sup>3</sup><sub>OPT</sub>,...]</code> 1    NAME 2    NAME 3    criterium = <u>text</u> SECTION

<p><code>\usebodyfont [...,*,...]</code></p> <p>* inherits: \setupbodyfont</p>
<p><code>\usebodyfontparameter \.*..</code></p> <p>* CSNAME</p>
<p><code>\usebtxdataset [...<sup>1</sup>.] [...<sup>2</sup>.] [...,...<sup>3</sup>.,...]</code></p> <p>1 NAME</p> <p>2 FILE</p> <p>3 specification = NAME</p>
<p><code>\usebtxdefinitions [...*]</code></p> <p>* FILE</p>
<p><code>\usecolors [...*]</code></p> <p>* FILE</p>
<p><code>\usecomponent [...*]</code></p> <p>* FILE</p>
<p><code>\usedummycolorparameter {...*}</code></p> <p>* KEY</p>
<p><code>\usedummystyleandcolor {...<sup>1</sup>.} {...<sup>2</sup>.}</code></p> <p>1 KEY</p> <p>2 KEY</p>
<p><code>\usedummystyleparameter {...*}</code></p> <p>* KEY</p>
<p><code>\useenvironment [...*]</code></p> <p>* FILE</p>
<p><code>\useexternaldocument [...<sup>1</sup>.] [...<sup>2</sup>.] [...<sup>3</sup>.]</code></p> <p>1 NAME</p> <p>2 FILE</p> <p>3 TEXT</p>
<p><code>\useexternalfigure [...<sup>1</sup>.] [...<sup>2</sup>.] [...<sup>3</sup>.] [...,...<sup>4</sup>.,...]</code></p> <p>1 NAME</p> <p>2 FILE</p> <p>3 NAME</p> <p>4 inherits: \setuexternalfigure</p>

`\useexternalrendering [...]1 [...]2 [...]3 [...]4`

- 1 NAME
- 2 NAME
- 3 FILE
- 4 auto embed

`\useexternalsoundtrack [...]1 [...]2`

- 1 NAME
- 2 FILE

`\usefigurebase [...]`

- \* reset FILE

`\usefile [...]1 [...]2 [...]3`  
OPT

- 1 NAME
- 2 FILE
- 3 TEXT

`\usegridparameter \*...`

- \* CSNAME

`\useindentingparameter \*...`

- \* CSNAME

`\useindentnextparameter \*...`

- \* CSNAME

`\useinterlinespaceparameter \*...`

- \* CSNAME

`\useJSscripts [...]1 [...]2,...]`  
OPT

- 1 FILE
- 2 NAME

`\uselanguageparameter \*...`

- \* CSNAME

`\uselua module [...]`

- \* FILE

`\useMPenvironmentbuffer [...]`

- \* NAME

`\useMPgraphic {...}1 {...,2...,...}`  
OPT

- 1 NAME
- 2 KEY = VALUE

$\backslash$ useMPlibrary [...] *    FILE
$\backslash$ useMPrun {...} {...} 1    NAME 2    NUMBER
$\backslash$ useMPvariables [...] [... <sup>2</sup> ,...] 1    NAME 2    KEY
$\backslash$ usemathstyleparameter \*... *    CSNAME
$\backslash$ usemodule [... <sup>1</sup> ] [... <sup>2</sup> ,...] [... <sup>3</sup> ,...] OPT                                  OPT 1    m p s x t 2    FILE 3    KEY = VALUE
$\backslash$ usepath [...*,...] *    PATH
$\backslash$ useproduct [...] *    FILE
$\backslash$ useprofileparameter \*... *    CSNAME
$\backslash$ useproject [...] *    FILE
$\backslash$ userreferenceparameter \*... *    CSNAME
$\backslash$ userpagenumber
$\backslash$ usesetupparameter \*... *    CSNAME
$\backslash$ usestaticMPfigure [... <sup>1</sup> ,...] <sup>2</sup> [...] [...] OPT 1    inherits: \setupscale 2    NAME
$\backslash$ usesubpath [...*,...] *    PATH
$\backslash$ usesymbols [...] *    FILE

```
\usetexmodule [...]1 [...]2,... [...]3,...OPT
1 m p s x t
2 FILE
3 KEY = VALUE
```

```
\usetypescript [...]OPT [...]OPT [...]OPT
1 serif sans mono math handwriting calligraphy casual all
2 NAME fallback default dtp simple
3 size name
```

```
\usetypescriptfile [...]OPT
* reset FILE
```

```
\useURL [...]OPT [...]OPT [...]OPT [...]OPT
1 NAME
2 URL
3 FILE
4 TEXT
```

```
\useurl [...]OPT [...]OPT [...]OPT [...]OPT
1 NAME
2 URL
3 FILE
4 TEXT
```

```
\usezipfile [...]OPT [...]OPT
1 FILE
2 FILE
```

```
\utfchar {...}
* NUMBER
```

```
\utflower {...}
* TEXT
```

```
\utfupper {...}
* TEXT
```

```
\utilityregisterlength
```

```
\VerboseNumber {...}
* NUMBER
```

```
\vboxreference [...]1,... {...}2
1 REFERENCE
2 CONTENT
```

$\backslash\text{vec}$ {...} * CHARACTER
$\backslash\text{verbatim}$ {...} * CONTENT
$\backslash\text{verbatimstring}$ {...} * CONTENT
$\backslash\text{verbosenum}$ {...} * NUMBER
$\backslash\text{version}$ [...] * concept file temporary final NAME
$\backslash\text{verticalgrowingbar}$ [..., ..., * ..., ...] * inherits: \setuppositionbar
$\backslash\text{verticalpositionbar}$ [..., ..., * ..., ...] * inherits: \setuppositionbar
$\backslash\text{veryraggedcenter}$
$\backslash\text{veryraggedleft}$
$\backslash\text{veryraggedright}$
$\backslash\text{vglue}$ ... * DIMENSION
$\backslash\text{viewerlayer}$ [...] {...} 1 NAME 2 CONTENT
$\backslash\text{vl}$ [...] <small>OPT</small> * NUMBER
$\backslash\text{vphantom}$ {...} * CONTENT
$\backslash\text{vpos}$ {... <sup>1</sup> } {... <sup>2</sup> } 1 NAME 2 CONTENT
$\backslash\text{vsmash}$ {...} * CONTENT



<p><code>\vsmashbox ...</code></p> <p>* CSNAME NUMBER</p>
<p><code>\vsmashed {...}</code></p> <p>* CONTENT</p>
<p><code>\vspace [...]<sup>1</sup> [...]<sup>2</sup></code></p> <p>1 NAME</p> <p>2 NAME</p>
<p><code>\vspacing [...]<sup>*</sup>...</code></p> <p>           * preference samepage max force enable disable nowhite back overlay always weak strong default before inbetween            after fixed flexible none small medium big line halfline quarterline formula white height depth standard NUMBER*small            NUMBER*medium NUMBER*big NUMBER*line NUMBER*halfline NUMBER*quarterline NUMBER*formula NUMBER*white NUMBER*height            NUMBER*depth category:NUMBER order:NUMBER penalty:NUMBER DIMENSION NAME         </p>
<p><code>\WEEKDAY {...}</code></p> <p>* NUMBER</p>
<p><code>\WidthSpanningText {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup></code></p> <p>1 TEXT</p> <p>2 DIMENSION</p> <p>3 FONT</p>
<p><code>\WORD {...}</code></p> <p>* TEXT</p>
<p><code>\WORDS {...}</code></p> <p>* TEXT</p>
<p><code>\Word {...}</code></p> <p>* TEXT</p>
<p><code>\Words {...}</code></p> <p>* TEXT</p>
<p><code>\wdofstring {...}</code></p> <p>* TEXT</p>
<p><code>\weekday {...}</code></p> <p>* NUMBER</p>
<p><code>\widthofstring {...}</code></p> <p>* TEXT</p>
<p><code>\widthspanningtext {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup></code></p> <p>1 TEXT</p> <p>2 DIMENSION</p> <p>3 FONT</p>

<code>\withoutpt {...}</code>  *    DIMENSION
<code>\word {...}</code>  *    TEXT
<code>\wordright [...]<sup>1</sup> {...}<sup>2</sup></code> <small>OPT</small> 1    right DIMENSION 2    CONTENT
<code>\words {...}</code>  *    TEXT
<code>\wordtonumber {...}<sup>1</sup> {...}<sup>2</sup></code>  1    one two three four five 2    TEXT
<code>\writebetweenlist [...]<sup>1</sup> [...,...<sup>2</sup>...,...]<sup>2</sup> {...}<sup>3</sup></code> <small>OPT</small> 1    LIST 2    inherits: \setuplist 3    COMMAND
<code>\writedatatolist [...]<sup>1</sup> [...,...<sup>2</sup>...,...]<sup>2</sup> [...,...<sup>3</sup>...,...]<sup>3</sup></code> <small>OPT</small> 1    LIST 2    inherits: \setuplist 3    KEY = VALUE
<code>\writestatus {...}<sup>1</sup> {...}<sup>2</sup></code>  1    TEXT 2    TEXT
<code>\writetolist [...]<sup>1</sup> [...,...<sup>2</sup>...,...]<sup>2</sup> {...}<sup>3</sup> {...}<sup>4</sup></code> <small>OPT</small> 1    LIST 2    inherits: \setuplist 3    NUMBER 4    TEXT
<code>\XETEX</code>
<code>\XeTeX</code>
<code>\xdefconvertedargument \...<sup>1</sup> {...}<sup>2</sup></code>  1    CSNAME 2    TEXT
<code>\xequal {...}<sup>1</sup> {...}<sup>2</sup></code> <small>OPT                  OPT</small> 1    TEXT 2    TEXT

`\xhookleftarrow {...} {...}`  
                    <sub>OPT</sub>          <sub>OPT</sub>

1    TEXT

2    TEXT

`\xhookrightarrow {...} {...}`  
                    <sub>OPT</sub>          <sub>OPT</sub>

1    TEXT

2    TEXT

`\xLeftarrow {...} {...}`  
                    <sub>OPT</sub>          <sub>OPT</sub>

1    TEXT

2    TEXT

`\xLeftrightarrow {...} {...}`  
                    <sub>OPT</sub>          <sub>OPT</sub>

1    TEXT

2    TEXT

`\xleftarrow {...} {...}`  
                    <sub>OPT</sub>          <sub>OPT</sub>

1    TEXT

2    TEXT

`\xleftharpoondown {...} {...}`  
                    <sub>OPT</sub>          <sub>OPT</sub>

1    TEXT

2    TEXT

`\xleftharpoonup {...} {...}`  
                    <sub>OPT</sub>          <sub>OPT</sub>

1    TEXT

2    TEXT

`\xleftrightarrow {...} {...}`  
                    <sub>OPT</sub>          <sub>OPT</sub>

1    TEXT

2    TEXT

`\xleftrightharpoons {...} {...}`  
                    <sub>OPT</sub>          <sub>OPT</sub>

1    TEXT

2    TEXT

`\xmapsto {...} {...}`  
                    <sub>OPT</sub>          <sub>OPT</sub>

1    TEXT

2    TEXT

`\xmladdindex {...}`

\*    NODE

`\xmllafterdocumentsetup {...} {...} {...}`

1    NAME

2    SETUP

3    SETUP

`\xmلاftersetup {...} {...}`

1    SETUP

2    SETUP

`\xmلاll {...} {...}`

1    NODE

2    LPATH

`\xmلاppenddocumentsetup {...} {...}`

1    NAME

2    SETUP

`\xmلاppendsetup {...}`

\*    SETUP

`\xmلاpplyselectors {...}`

\*    NODE

`\xmلاtt {...} {...}`

1    NODE

2    NAME

`\xmلاttdef {...} {...} {...}`

1    NODE

2    NAME

3    TEXT

`\xmلاttribute {...} {...} {...}`

1    NODE

2    LPATH

3    NAME

`\xmلاtributedef {...} {...} {...} {...}`

1    NODE

2    LPATH

3    NAME

4    TEXT

`\xmلاbadinclusions {...}`

\*    NODE

`\xmلاbeforedocumentsetup {...} {...} {...}`

1    NAME

2    SETUP

3    SETUP

`\xmlbeforesetup {...} {...}`

- 1 SETUP
- 2 SETUP

`\xmlchainatt {...} {...}`

- 1 NODE
- 2 NAME

`\xmlchainattdef {...} {...} {...}`

- 1 NODE
- 2 NAME
- 3 TEXT

`\xmlchecknamespace {...} {...}`

- 1 NODE
- 2 NAME

`\xmlcommand {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 XMLSETUP

`\xmlconcat {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 TEXT

`\xmlconcatrange {...} {...} {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 TEXT
- 4 FIRST
- 5 LAST

`\xmlcontext {...} {...}`

- 1 NODE
- 2 LPATH

`\xmlcount {...}`

- \* NODE

`\xmldefaulttotext {...}`

- \* NODE

`\xmldirectives {...}`

- \* NODE

\xmldirectivesafter {...}

\* NODE

\xmldirectivesbefore {...}

\* NODE

\xmldisplayverbatim {...}

\* NODE

\xmldoif {...} {...} {...}

1 NODE

2 LPATH

3 TRUE

\xmldoifelse {...} {...} {...} {...}

1 NODE

2 LPATH

3 TRUE

4 FALSE

\xmldoifelseempty {...} {...} {...} {...}

1 NODE

2 LPATH

3 TRUE

4 FALSE

\xmldoifelseselfempty {...} {...} {...}

1 NODE

2 TRUE

3 FALSE

\xmldoifelsetext {...} {...} {...} {...}

1 NODE

2 LPATH

3 TRUE

4 FALSE

\xmldoifelsevalue {...} {...} {...} {...}

1 CATEGORY

2 NAME

3 TRUE

4 FALSE

\xmldoifnot {...} {...} {...}

1 NODE

2 LPATH

3 TRUE

\xmldoifnotselfempty {...} {...}

- 1 NODE
- 2 TRUE

\xmldoifnottext {...} {...} {...}

- 1 NODE
- 2 LPATH
- 3 TRUE

\xmldoifselfempty {...} {...}

- 1 NODE
- 2 TRUE

\xmldoiftext {...} {...} {...}

- 1 NODE
- 2 LPATH
- 3 TRUE

\xmlelement {...} {...}

- 1 NODE
- 2 NUMBER

\xmlfilter {...} {...}

- 1 NODE
- 2 LPATH

\xmlfirst {...} {...}

- 1 NODE
- 2 LPATH

\xmlflush {...}

- \* NODE

\xmlflushcontext {...}

- \* NODE

\xmlflushdocumentsetups {...} {...}

- 1 NAME
- 2 SETUP

\xmlflushlinewise {...}

- \* NODE

\xmlflushpure {...}

- \* NODE

\xmlflushspacewise {...}  *    NODE
\xmlflushtext {...}  *    NODE
\xmlinclude {...} {...} {...}  1    NODE 2    LPATH 3    NAME
\xmlinclusion {...}  *    NODE
\xmlinclusions {...}  *    NODE
\xmlinfo {...}  *    NODE
\xmlinjector {...}  *    NAME
\xmlinlineverbatim {...}  *    NODE
\xmlinstalldirective {...} {...}  1    NAME 2    CSNAME
\xmllast {...} {...}  1    NODE 2    LPATH
\xmllastatt
\xmllastmatch
\xmlloadbuffer {...} {...} {...}  1    BUFFER 2    NAME 3    XMLSETUP
\xmlloaddata {...} {...} {...}  1    NAME 2    TEXT 3    XMLSETUP



<pre>\xmlloadaddirectives {...}</pre> <p>*    FILE</p>
<pre>\xmlloadfile {...} {...} {...}</pre> <p>1    NAME</p> <p>2    FILE</p> <p>3    XMLSETUP</p>
<pre>\xmlloadonly {...} {...} {...}</pre> <p>1    NAME</p> <p>2    FILE</p> <p>3    XMLSETUP</p>
<pre>\xmlmain {...}</pre> <p>*    NAME</p>
<pre>\xmlmapvalue {...} {...} {...}</pre> <p>1    CATEGORY</p> <p>2    NAME</p> <p>3    TEXT</p>
<pre>\xmlname {...}</pre> <p>*    NODE</p>
<pre>\xmlnamespace {...}</pre> <p>*    NODE</p>
<pre>\xmlnonspace {...} {...}</pre> <p>1    NODE</p> <p>2    LPATH</p>
<pre>\xmlpath {...}</pre> <p>*    NODE</p>
<pre>\xmlpos {...}</pre> <p>*    NODE</p>
<pre>\xmlposition {...} {...} {...}</pre> <p>1    NODE</p> <p>2    LPATH</p> <p>3    NUMBER</p>
<pre>\xmlprependdocumentsetup {...} {...}</pre> <p>1    NAME</p> <p>2    SETUP</p>

\xmlprependsetup {...}

\* SETUP

\xmlprettyprint {...} {...}

1 NODE

2 NAME

\xmlprocessbuffer {...} {...} {...}

1 BUFFER

2 NAME

3 XMLSETUP

\xmlprocessdata {...} {...} {...}

1 NAME

2 TEXT

3 XMLSETUP

\xmlprocessfile {...} {...} {...}

1 NAME

2 FILE

3 XMLSETUP

\xmlpure {...} {...}

1 NODE

2 LPATH

\xmlraw {...}

\* NODE

\xmlrefatt {...} {...}

1 NODE

2 NAME

\xmlregistereddokumentsetups {...} {...}

1 NAME

2 SETUP

\xmlregisteredsetups

\xmlregisterns {...} {...}

1 NAME

2 URL

`\xmlremapname {...} {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 NAME
- 4 NAME

`\xmlremapnamespace {...} {...} {...}`

- 1 NODE
- 2 NAME
- 3 NAME

`\xmlremovedocumentsetup {...} {...}`

- 1 NAME
- 2 SETUP

`\xmlremovesetup {...}`

- \* SETUP

`\xmlresetdocumentsetups {...}`

- \* NAME

`\xmlresetinjectors`

`\xmlresetsetups {...}`

- \* NAME

`\xmlsave {...} {...}`

- 1 NODE
- 2 FILE

`\xmlsetentity {...} {...}`

- 1 NAME
- 2 TEXT

`\xmlsetfunction {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 LUAFUNCTION

`\xmlsetinjectors [...;...]`

- \* NAME

`\xmlsetsetup {...} {...} {...}`

- 1 NAME
- 2 LPATH
- 3 SETUP

\xmlsetup {...} {...}

- 1 NODE
- 2 SETUP

\xmlshow {...}

- \* NODE

\xmlsnippet {...} {...}

- 1 NODE
- 2 NUMBER

\xmlstrip {...} {...}

- 1 NODE
- 2 LPATH

\xmlstripnolines {...} {...}

- 1 NODE
- 2 LPATH

\xmlstripped {...} {...}

- 1 NODE
- 2 LPATH

\xmlstrippednolines {...} {...}

- 1 NODE
- 2 LPATH

\xmltag {...}

- \* NODE

\xmltexentity {...} {...}

- 1 NAME
- 2 TEXT

\xmltext {...} {...}

- 1 NODE
- 2 LPATH

\xmltobuffer {...} {...} {...}

- 1 NODE
- 2 LPATH
- 3 BUFFER

\xmltobufferverbose {...} {...} {...}

- 1 NODE
- 2 LPATH
- 3 BUFFER

`\xmltofile {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 FILE

`\xmlvalue {...} {...} {...}`

- 1 CATEGORY
- 2 NAME
- 3 TEXT

`\xmlverbatim {...}`

- \* NODE

`\xrightarrow {...} {...}`

- 1 TEXT
- 2 TEXT

`\xrel {...} {...}`

- 1 TEXT
- 2 TEXT

`\xrightarrow {...} {...}`

- 1 TEXT
- 2 TEXT

`\xrightarrowdown {...} {...}`

- 1 TEXT
- 2 TEXT

`\xrightarrowup {...} {...}`

- 1 TEXT
- 2 TEXT

`\xrightarrowleft {...} {...}`

- 1 TEXT
- 2 TEXT

`\xrightarrowleftarrow {...} {...}`

- 1 TEXT
- 2 TEXT

`\xsplitstring \... {...}`

- 1 CSNAME
- 2 TEXT

`\xtriplerel {...} {...}`  
                  <sup>1</sup>          <sup>2</sup>  
                  OPT          OPT

1   TEXT

2   TEXT

`\xtwoheadleftarrow {...} {...}`  
                  <sup>1</sup>          <sup>2</sup>  
                  OPT          OPT

1   TEXT

2   TEXT

`\xtwoheadrightarrow {...} {...}`  
                  <sup>1</sup>          <sup>2</sup>  
                  OPT          OPT

1   TEXT

2   TEXT

`\xypos {...}`

\*   NAME



The background is an abstract composition of various geometric shapes, primarily rectangles and squares, in shades of green and grey. The shapes are layered and overlapping, creating a sense of depth and movement. Some shapes have thick green outlines, while others are solid grey or light green. The overall effect is a modern, minimalist design.

**PRAGMA ADE**  
**Ridderstraat 27**  
**8061GH Hasselt NL**  
**[www.pragma-ade.com](http://www.pragma-ade.com)**