attributes backends bit bit32 blobs boolean buffers builders caches callbacks catcodes characters chemistry commands containers context converters coroutine ctxrunner debug dir directives document documentdata environment epdf experiments figures file floats font fontloader fonts functions global graphics gzip img interactions interfaces io jit job languages layouts lfs libraries lmx logs lpdf lpeg ltn12 lua luatex lxml math mathematics mbox md5 metapost mime moduledata modules mplib noads node nodes number os package pagebuilders parametersets pdfscanner physics profiler publications regimes resolvers scripts set socket sorters statistics storage streams **string** structures xconfig texio thirddata tok tokens tracers trackers typesetters unicode url userdata utilities vf visualizers xml zip zlib

ConT_EXt MkIV

global (alias: _G)

| LUAVERSTON | | 16 | |
|-------------------------------------|----------|-----------------|----------|
| _LUAVERSION | number | epdf | table |
| _MAJORVERSION | number | error | function |
| _MINORVERSION | number | experiments | table |
| _cldo_ | function | figures | table |
| arg | table | file | table |
| assert | function | floats | table |
| attributes | table | font | table |
| backends | table | fontloader | table |
| beginpage | function | fonts | table |
| bit | table | format_n | function |
| bit32 | table | frozen | boolean |
| blobs | table | functions | table |
| boolean | table | gcinfo | function |
| border_set | boolean | getfenv | function |
| buffers | table | getmetatable | function |
| builders | table | getreadfilename | function |
| caches | table | global | table |
| callback | table | graphics | table |
| callbacks | table | gzip | table |
| catcodes | table | img | table |
| characters | table | inspect | function |
| chemistry | table | interactions | table |
| collectgarbage | function | interfaces | table |
| commands | table | io | table |
| containers | table | ipairs | function |
| context | function | jit | table |
| context_applyprocessor | function | job | table |
| ${\tt context_firstofoneargument}$ | function | lang | table |
| converters | table | languages | table |
| coroutine | table | layouts | table |
| ctxrunner | table | lfs | table |
| debug | table | libraries | table |
| delta | number | lmx | table |
| dimen | function | lmxconvert | function |
| dir | table | lmxnew | function |
| directives | table | load | function |
| document | table | loadfile | function |
| documentdata | table | loadstring | function |
| dofile | function | logs | table |
| endpage | function | lp_fastpos_n | userdata |
| environment | table | lp_fastpos_p | userdata |

| Indf | +-610 | naniman | table |
|-----------------|----------------|-------------------|----------|
| lpdf | table table | regimes | |
| lpeg | | report_characters | function |
| ltn12 | table | require | function |
| lua | table | resolve_fences | function |
| luatex | table | resolvers | table |
| lxml | table | scripts | table |
| math | table | select | function |
| mathematics | table | set | table |
| mbox | table | setcharacteralign | function |
| md5 | table | setfenv | function |
| metapost | table | setinspector | function |
| mime | table | setmetatable | function |
| module | function | socket | table |
| moduledata | table | sorters | table |
| modules | table | statistics | table |
| mplib | table | status | table |
| newline | function | storage | table |
| newproxy | function | streams | table |
| next | function | string | table |
| noads | table | stripmath | function |
| node | table | structures | table |
| nodes | table | swiglib | function |
| number | table | table | table |
| optionalrequire | function | tex | table |
| os | table | texconfig | table |
| outputpagestree | function | texio | table |
| package | table | thirddata | table |
| pagebuilders | table | toboolean | function |
| pairs | function | token | table |
| parametersets | table | tokens | table |
| pattern | userdata | tonumber | function |
| pcall | function | tostring | function |
| pdf | table | trace_characters | boolean |
| pdfborder | function | tracers | table |
| pdfscanner | table | trackers | table |
| physics | table | type | function |
| print | function | typesetters | table |
| profiler | table | unicode | table |
| protect | function | unpack | function |
| publications | table | url | table |
| rawequal | function | userdata | table |
| rawget | function | utf | table |
| rawlen | function | utilities | table |
| rawset | function | vf | table |
| | | | |

visualizers
xml table
xmlconvert function
xpcall function
zip table
zlib table

attributes (context)

| colorintents | table | F mpoptions | |
|-----------------|-------------|-----------------|------------|
| N attribute | | U none | |
| D data | | F popset | |
| F enable | | F processcolorc | omponents |
| F handler | | F pushset | |
| F register | | F register | |
| D registered | | D registered | |
| colors | table | F registerspotc | olor |
| N attribute | | F rgb | |
| F cmyk | | F rgbtocmyk | |
| F cmyktogray | | F rgbtogray | |
| F cmyktorgb | | F rgbtohsv | |
| F colorcomponer | nts | N selector | |
| B couple | | F setlist | |
| D data | | F setmodel | |
| N default | | D sets | |
| F defineinterme | ediatecolor | F spec | |
| F definemixcolo | or | F spot | |
| F definemultito | onecolor | F spotcolorname | |
| F defineprocess | scolor | F spotcolorpare | nt |
| F definesimple | gray | F spotcolorvalu | е |
| F definespotcol | lor | B supported | |
| F definetranspa | arency | F transparencyc | omponents |
| F enable | | B triggering | |
| F filter | | F usecolors | |
| F forcedmodel | | F value | |
| F forcesupport | | D values | |
| F formatcolor | | B weightgray | |
| F formatgray | | define | function |
| F gray | | effects | table |
| F graytohsv | | N attribute | |
| F handler | | D data | |
| F hsvtogray | | F enable | |
| F hsvtorgb | | F handler | |
| F iccprofile | | F register | |
| F isblack | | D registered | |
| N main | | D values | |
| S model | | handlers | table |
| D models | | list | data table |
| F mpcolor | | names | data table |
| F mpnamedcolor | | negatives | table |

N attribute
D data
F enable
F handler
F register
D registered
nbers

states table

F disabletriggering

F enabletriggering
F finalize

F initialize

F process

F selective

F stacked

F stacker

transparencies table

N attribute

D data

F enable

F forcesupport

F handler

U none

F register

D registered

B supported

B triggering

F value

D values

unsetvalue number
viewerlayers table

N attribute

D data

F define

F enable

F forcesupport

F handler

B hasorder

D listwise

F register

D registered

F resolve_begin

F resolve_end

F resolve_step

D scopes

F setfeatures

F start

F stop

B supported

D values

backends (context)

F hasmatrix

codeinjections table F insertrenderingwindow F synchronizecolormodel F mergereferences current strina F mergeviewerlavers defaults table F prerollreference T codeinjections F presetsymbol F aethpos F presetsymbollist F getmatrix F processrendering F getpos F registerdocumentcloseaction F registerdocumentopenaction F getypos F hasmatrix F registeredsymbol T nodeiniections F registerpagecloseaction T registrations F registerpageopenaction D tables F registersymbol install function F setfieldcalculationset nodeinjections table F setfigurealternative F restore F setfigurecolorspace F save F setfiguremask F transform F setformat nothina function F setformsmethod pdf table F setpagetransition T codeiniections F setupcanvas F addbookmarks F setupidentity F attachmentid F setxmpfile F clonefield F startlayer F definefield F stoplayer F definefieldset F supportedformats F defineviewerlayer F useviewerlayer F embedfile F validfield F enabletags F validfieldcategory F exportformdata F validfieldset F getdefaultfieldvalue S comment F getfieldcategory T nodeiniections F getfieldset F addtags F annotation F getformatoption F gethpos F attachfile F getmatrix F changestackedlayer F getoutputfilename F cmykcolor F comment F getpos F destination F getpreviewfigure F getypos F effect

F graycolor

- F injectbitmap
- F insertmovie
- F insertsound
- F insertswf
- F insertu3d
- F knockout
- F negative
- F overprint
- F positive
- F reference
- F rgbcolor
- F spotcolor
- F startlayer
- F startstackedlayer
- F stoplayer
- F stopstackedlayer
- F transparency
- F typesetfield
- T registrations
 - F cmykindexcolor
 - F cmykspotcolor
 - F getspotcolorreference
 - F grayindexcolor
 - F grayspotcolor
 - F rgbindexcolor
 - F rgbspotcolor
 - F spotcolorname
 - F transparency
- T tables
 - D vfspecials

registrations table tables table

bit (context)

```
arshift function
band
        function
        function
bnot
        function
bor
        function
bswap
        function
bxor
        function
lshift
rol
        function
ror
        function
rshift
        function
tobit
        function
tohex
        function
```

bit32 (basic lua)

```
arshift function
band
       function
       function
bnot
bor
       function
       function
btest
bxor function
extract function
lrotate function
lshift function
replace function
rrotate function
rshift function
```

blobs (context)

| append | function |
|-------------|----------|
| dimensions | function |
| dispose | function |
| new | function |
| pack | function |
| strdp | function |
| strhd | function |
| strht | function |
| strwd | function |
| tohpack | function |
| tohpackfast | function |
| tonodes | function |
| tovpack | function |
| tovpackfast | function |
| write | function |

boolean (context)

tocontext function
tonumber function

buffers (context)

append function assign function collectcontent function erase function function exists function getcontent function getlines loadcontent function parallel table

F define

F hassomecontent

F next
F place
F reset
F save

prepend function
raw function

builders (context)

kernel table F hyphenation F kernina F ligaturing F mlist_to_hlist paragraphs table T constructors N attribute F define F disable F enable F handler T methods F basic F default F oneline D names D numbers F set F start F stop T expansion F trace F keeptogether F registertogether T solutions T splitters F define F optimize T registered F reset F set F split F start F stop F tag vspacing table F analyze D categories F collapsevbox

T data

D map D skip D snapmethods F definesnapmethod B fixed F pagehandler F resetprevdepth F setmap F setskip F snapbox F tocategories F tocategory F vboxhandler

caches (context)

ask boolean base string collapsecontent function configfiles function function contentstate defaults table define function direct boolean force boolean **getfirstreadablefile** function getfirstreadablefile_TEST_ME_FIRST function getreadablepaths function getwritablepath function hashed function is writable function loadcontent function loaddata function strina more relocate boolean savecontent function function savedata setfirstwritablefile function setluanames function tree string treehash function function usedpaths

callback (basic tex)

find function
list function

register overloaded function

callbacks (context)

freeze
known function
list data table
pop function
push function
register function
report function

catcodes (context)

characters (context)

| activeoffset | number |
|--------------|------------|
| adobename | function |
| bidi | data table |
| blockrange | function |
| blocks | data table |
| casemap | table |
| categories | data table |
| category | function |
| categorytags | data table |
| combined | data table |
| contextname | function |
| data | data table |
| decomposed | data table |
| define | function |
| description | function |
| descriptions | data table |
| directions | table |
| enccodes | data table |
| entities | data table |
| fallbacks | data table |
| filters | data table |
| fromnumber | function |
| fschars | data table |
| fscodes | data table |
| getrange | function |
| graphemes | data table |
| hangul | data table |
| initialize | function |
| is_character | data table |
| is_command | data table |
| is_letter | data table |
| is_mark | data table |
| is_spacing | data table |
| lcchars | data table |
| lccode | function |
| lccodes | data table |
| lettered | function |
| lower | function |
| math | table |
| mathpairs | data table |
| mirrors | table |
| | |

| otfscripts | data table |
|----------------------|------------|
| ranges | data table |
| registerentities | function |
| remap_hangul_syllabe | function |
| safechar | function |
| setcodes | function |
| shape | function |
| shaped | function |
| shchars | data table |
| shcodes | data table |
| showstring | function |
| specialchars | data table |
| specials | data table |
| subscripts | table |
| superscripts | table |
| synonyms | data table |
| tex | table |
| | |

D accentmapping F defineaccents

F toutf

textclasses
tonumber
ucchars
uccode
uccodes
unicodechar
upper

table
function
data table
function
data table
function
function

chemistry (context)

component function define function definitions data table format string instance string molecule function moleculeparser userdata start function stop function number structures undefine function

commands (context)

| Alphabetic | function | assignbuffer | function |
|-------------------------|----------|----------------------------|----------|
| Character | function | attachproperty | function |
| Characters | function | autofinishstructurelevels | function |
| MPc | function | autonextspace | function |
| MPd | function | autonextstructurelevel | function |
| MPh | function | autosetups | function |
| MPll | function | autostarttext | function |
| MPlr | function | autostoptext | function |
| MPls | function | averagecharwidth | function |
| MPn | function | bcolumn | function |
| MPp | function | boolcase | function |
| MPpardata | function | boxtostring | function |
| MPplus | function | btxauthor | function |
| MPpos | function | btxcitevariant | function |
| MPposset | function | btxcollectlistentries | function |
| MPr | function | btxdestination | function |
| MPrest | function | btxdetail | function |
| MPrs | function | btxdoif | function |
| MPul | function | btxdoifelse | function |
| MPur | function | btxdoifelselistentryplaced | function |
| MPw | function | btxdoifnot | function |
| MPx | function | btxfetchlistentries | function |
| MPxy | function | btxfield | function |
| MPxywhd | function | btxflush | function |
| MPy | function | btxflushlistentries | function |
| Romannumerals | function | btxhandlecite | function |
| abjadnodotnumerals | function | btxhandlenocite | function |
| abjadnumerals | function | btxlistvariant | function |
| addbtxentry | function | btxreference | function |
| addcounter | function | btxregisterlistentry | function |
| addlinklistelement | function | btxresolvelistreference | function |
| addreplacements | function | btxsetlistmethod | function |
| addtojavascriptpreamble | function | btxsingularorplural | function |
| addtolist | function | buildtextaccent | function |
| allinputpaths | function | character | function |
| alphabetic | function | characters | function |
| analysefloatmethod | function | chardescription | function |
| analyzelist | function | checkcharactersinfont | function |
| applytochars | function | checkcountersetup | function |
| applytofirstcharacter | function | checkedconversion | function |
| applytowords | function | checkedpagefloat | function |

| checktwopassdata | function | definefieldset | function |
|-------------------------|----------|-------------------------|----------|
| chemicalcomponent | function | definefilefallback | function |
| chineseallnumerals | function | definefilesynonym | function |
| chinesecapnumerals | function | definefont one | function |
| chinesenumerals | function | definefont two | function |
| cleanfontname | function | definefontfamily | function |
| cleanupbox | function | definefontfeature | function |
| cleanuplayers | function | definefontsolution | function |
| clonefield | function | defineinsertion | function |
| collectfloat | function | defineintermediatecolor | function |
| collecthelp | function | definelabels | function |
| colorcomponents | function | definelanguage | function |
| concatcommalist | function | definelinkedlist | function |
| consultfloat | function | definemarking | function |
| convertbtxdatasettoxml | function | definemetafont | function |
| copyposition | function | definemultitonecolor | function |
| cos | function | definenote | function |
| cosd | function | defineparallel | function |
| countervalue | function | defineparbuilder | function |
| counttwopassdata | function | defineprocesscolor | function |
| ctxfunction | function | defineprogram | function |
| currentcomponent | function | definereference | function |
| currentdate | function | defineregister | function |
| currentenvironment | function | definesectionlevels | function |
| currentproduct | function | defineselectfont | function |
| currentproject | function | definesnapmethod | function |
| currentreferencedefault | function | definespotcolor | function |
| currentreferenceorder | function | definestructureblock | function |
| currentregime | function | definestructureset | function |
| currentsectiontolist | function | definetransparency | function |
| datasetvariable | function | definetwopasslist | function |
| dayname | function | defineviewerlayer | function |
| deferredproperty | function | defrostrandomseed | function |
| defineattribute | function | depthnumber | function |
| definebreakpoint | function | digits | function |
| definebreakpoints | function | disableautofontscript | function |
| definecatcodetable | function | disableparbuilder | function |
| definecharacterspacing | function | disableregime | function |
| definechemical | function | disablespellchecking | function |
| defineconversion | function | discardfromlist | function |
| definecounter | function | doanalyzeframedbox | function |
| definedviewerlayer | function | doif | function |
| definefallbackfamily | function | doifblackelse | function |
| definefield | function | doifcommonelse | function |

| doifcounter | function | doifposition | function |
|---|----------|-----------------------------|----------|
| doifdimenstringelse | function | doifpositionelse | function |
| doifdrawingblackelse | function | doifpositiononpage | function |
| doifelse | function | doifpositionsonsamepageelse | function |
| doifelsebuffer | function | doifpositionsonthispageelse | function |
| doifelsecontinuewithfile | function | doifurldefinedelse | function |
| doifelsecounter | function | doprocesstypescriptfile | function |
| ${\tt doifelsecurrent fonthas feature}$ | function | doreshapeframedbox | function |
| doifelseintwopassdata | function | dostarttextfile | function |
| doifelsemarking | function | dostoptextfile | function |
| doifelsemessage | function | ecolumn | function |
| doifelsemultipar | function | elapsedtime | function |
| doifelseparallel | function | enableautofontscript | function |
| doifelsepositionsused | function | enablecolor | function |
| doifelserangeonpage | function | enablecolorintents | function |
| doifelsereference | function | enablefontcolorschemes | function |
| doifelsesavedfloat | function | enableparbuilder | function |
| doifelsespaces | function | enableregime | function |
| doifelseutfmathabove | function | enablespellchecking | function |
| doifelseutfmathaccent | function | enabletransparency | function |
| doifelseutfmathbelow | function | enhancelinkedlist | function |
| doifelsevisualizer | function | enhancelist | function |
| doiffieldcategoryelse | function | enhancereference | function |
| doiffieldelse | function | enhanceregister | function |
| doiffieldsetelse | function | erasebuffer | function |
| doiffiledefinedelse | function | expandcurrentreference | function |
| doiffileexistelse | function | exportformdata | function |
| doiffirstcharelse | function | exportreferences | function |
| doifinputfileelse | function | extendregister | function |
| doifinsetelse | function | extensiblecode | function |
| doifleapyearelse | function | feature | function |
| doiflisthasentry | function | featureattribute | function |
| doiflisthasnumberelse | function | featurelist | function |
| doiflisthaspageelse | function | feedback | function |
| doiflisthastitleelse | function | fetchallmarks | function |
| doiflocfileelse | function | fetchmultipar | function |
| doifnot | function | fetchmultishape | function |
| doifnotcounter | function | fetchonemark | function |
| doifnotecontent | function | fetchposboxes | function |
| doifnoteonsamepageasprevious | function | fetchtwomarks | function |
| doifobjectreferencefoundelse | function | figurefilename | function |
| doifolderversionelse | function | figurefilepath | function |
| doifoverlappingelse | function | figurefiletype | function |
| doifparentfileelse | function | figurerequest | function |

| figurestatus | function | getfloatvariable | function |
|-----------------------------|----------|--------------------------|----------|
| figureused | function | getfullsectionnumber | function |
| figurevariable | function | getinternallistreference | function |
| filterdefaultreference | function | getinternalreference | function |
| filterreference | function | getlasttwopassdata | function |
| finalizebox | function | getmarking | function |
| findtwopassdata | function | getmessage | function |
| firstcountervalue | function | getmpextensions | function |
| firstinset | function | getnotestate | function |
| flushfloat | function | getplaceholderchar | function |
| flushnotes | function | getprivateattribute | function |
| flushpostponedblocks | function | getprivatechar | function |
| flushpostponednotes | function | getprogram | function |
| fontchar | function | getrandomcounta | function |
| fontcollectionclone | function | getrandomcountb | function |
| fontcollectiondefine | function | getrandomseed | function |
| fontcollectionprepare | function | getreadfilename | function |
| fontcollectionregister | function | getsectionnumber | function |
| fontcollectionreport | function | getstructuredata | function |
| fontcollectionreset | function | getsubstring | function |
| fontlookupgetkey | function | gettexbuffer | function |
| fontlookupgetkeyofindex | function | gettwopassdata | function |
| fontlookupinitialize | function | gettwopassdatalist | function |
| fontlookupnoffound | function | geturl | function |
| forceendjob | function | grabbuffer | function |
| forcequitjob | function | hboxtovbox | function |
| format | function | helpaction | function |
| formatcolor | function | helpreference | function |
| formatgray | function | hexstringtonumber | function |
| freezerandomseed | function | horizontalcode | function |
| from | function | hour | function |
| getbidimode | function | hyphenatedlist | function |
| getbuffer | function | hyphenatedurl | function |
| getbufferctxlua | function | D characters | |
| getbuffermkvi | function | N lefthyphenmin | |
| getcommandline | function | D mapping | |
| getctxfile | function | N righthyphenmin | |
| getcurrentprefixspec | function | F setcharacters | |
| getcurrentreferencemetadata | function | immediateproperty | function |
| getcurrentsectionlevel | function | incrementedcounter | function |
| getdefaultfieldvalue | function | initializetexdirectives | function |
| getfieldcategory | function | initializetextrackers | function |
| getfirstcharacter | function | injectcurrentreference | function |
| getfirsttwopassdata | function | injectreference | function |

| inlinechemical | function | minute | function |
|-----------------------|----------|----------------------------|----------|
| insertattachment | function | mixcleanup | function |
| insertcomment | function | mixfinalize | function |
| insertfield | function | mixflushlist | function |
| insertionnumber | function | mixflushrest | function |
| insertrenderingwindow | function | mixgetsplit | function |
| insertsoundclip | function | mixsetsplit | function |
| installedlanguages | function | mixstate | function |
| installtexdirective | function | molecule | function |
| installtextracker | function | month | function |
| languagenumber | function | monthmnem | function |
| lastcountervalue | function | monthname | function |
| lchexnumber | function | mpcolor | function |
| lchexnumbers | function | mpoptions | function |
| leapyear | function | mprunvar | function |
| linenumbersstageone | function | namedstructureuservariable | function |
| linenumbersstagetwo | function | namedstructurevariable | function |
| listgroupindex | function | nbfs | function |
| listlabel | function | nextcountervalue | function |
| listlocation | function | nextparallel | function |
| listprefixednumber | function | nofdays | function |
| listprefixedpage | function | nofitems | function |
| listrealpage | function | nofstackedfloats | function |
| listsize | function | notedeltapage | function |
| listtitle | function | notelistindex | function |
| listuserdata | function | notenumberpage | function |
| loadbtxdefinitionfile | function | noteprefixednumber | function |
| loadexamodes | function | notesymbolpage | function |
| loadfontgoodies | function | notetitle | function |
| loadspellchecklist | function | ntimes | function |
| loadtypescriptfile | function | number | function |
| loadvisualizer | function | F LuaSnippet | |
| locatefilepath | function | F LuaSnippetBoundary | |
| locfilename | function | F LuaSnippetComment | |
| lower | function | F LuaSnippetName | |
| makeactive | function | F LuaSnippetNameBase | |
| manipulated | function | F LuaSnippetNameCore | |
| markfonts | function | F LuaSnippetNameLibraries | |
| markingnumber | function | F LuaSnippetQuote | |
| markingtitle | function | F LuaSnippetSpecial | |
| markregionbox | function | F LuaSnippetString | |
| math_frac | function | F MPcolor | |
| mathrenderset | function | F MetapostSnippet | |
| maxitemwidth | function | F MetapostSnippetBoundary | |

F MetapostSnippetComment F hold F MetapostSnippetConstructor F btxchecklistentry F MetapostSnippetName F btxcitevariantparameter F MetapostSnippetNameMetafun F btxdirectlink F MetapostSnippetNamePlain F btxdomarkcitation F MetapostSnippetNamePrimitive F btxhandlelistentry F MetapostSnippetQuote F btxlistparameter F htxlistvariantnarameter F MetapostSnippetSpecial F MetapostSnippetString F callfunctiononce F char F NC F NR F chardef F ParsedXmlSnippetCdata F color F ParsedXmlSnippetComment F colordefage F ParsedXmlSnippetDoctype F colordefagt F ParsedXmlSnippetElement F colordefalc F ParsedXmlSnippetInstruction F colordefalt F ParsedXmlSnippetKey F colordeffac F ParsedXmlSnippetValue F colordeffgt F colordefflc F TexSnippet F TexSnippetBoundary F colordefflt F TexSnippetComment F colordefrac F TexSnippetGroup F colordefrat F colordefrlc F TexSnippetName F colordefrlt F TexSnippetSpecial F XmlSnippet F concat F XmlSnippetBoundary F constructcs F XmlSnippetCdata F constructcsonly F XmlSnippetComment F convertnumber F XmlSnippetEntity F ctxreport F XmlSnippetEqual F darkblue F XmlSnippetKey F darkgreen F XmlSnippetName F darkred F XmlSnippetString F definefontsynonym F flush T delayed F __flushdirect F digitsdigit F __flushlines F digitsfinalcomma F addaskedblankskip F digitsfinalperiod F addpredefinedblankskip F digitshighspace F digitsintermediatecomma F applyprocessor F beginhbox F digitsintermediateperiod F beginvbox F digitsminus F bf F digitsnegative F bgroup F digitsplus F blank F digitspositive

F digitspower F flexibleblankskip F digitspowerminus F flushblankhandling F digitspowerplus F flushboxregister F digitsseparatorspace F flushnode F digitssignspace F fntsetdefname F digitsspace F fntsetnopsize F digitszeropadding F fntsetsomename F direct F fntsetsomesize F directsetup T formatted F dodirectfullreference F fprint F dodisplayverbatimbeginline T generics F dodisplayverbatimemptyline S starttabulate F dodisplayverbatiminitialize S stoptabulate F dodisplayverbatimnewline F getlogger F dodisplayverbatimstart F getreferencestructureprefix F dodisplayverbatimstop F getvalue F dofastdefinetypeface F glyph F dofinishsomereference F gobbleoneargument F dofromfiledescription F goto F dofromfileliteral F hrule F dofromurldescription F input F dofromurlliteral T knownfunctions F doinlineverbatimbeginline F lateluafunction F doinlineverbatimemptyline F letvaluerelax F doinlineverbatimnewline F loadfile F doinlineverbatimstart F loadfoundtypescriptfile F doinlineverbatimstop F luasetup F m F donestedtypingstart T metafun F donestedtypingstop F dostarttext F color F doverbatimspace T delayed F egroup F start F emptyreference F stop F enablemode T nested F endhbox F markingcommand F endvbox F markingseparator F environment F newbox F expandreferencearguments F newcount F expandreferenceoperation F newdimen F finalizeautostructurelevel F newindexer F finishjob F newmuskip F firstofoneargument F newskip F firstoftwoarguments F newtexthandler F fixedblankskip F newtoks

F newverbosehandler F startMetapostSnippet F nointerlineskip F startParsedXmlSnippet F normalatop F startTexSnippet F normalover F startXmlSnippet F overstrike F startblankhandling F par F startcolumns F pdfliteral F startcomponentindeed F startenvironmentindeed F popcatcodes F poplogger F startfontclass F printlines F starthboxregister F processfilemany F startproductindeed F processfilenone F startprojectindeed F processfileonce F startreadingfile F protect F startregisterentries T puretext F startregisterentry F pushcatcodes F startregisteroutput F pushlogger F startregisterpages F registerentry F startregistersection F registerfunction F startregisterseewords F registeronepage F starttabulate F registerpagerange F starttext F registerseeword F starttitle F reservefunction F startvboxregister F startxtitle F rlap F runfile F stopLuaSnippet F secondoftwoarguments F stopMetapostSnippet F stopParsedXmlSnippet F setblankcategory F setblankorder F stopTexSnippet F setblankpenalty F stopXmlSnippet F setconditional F stopblankhandling F setfalsevalue F stopcolumns F sethboxregister F stopcomponentindeed F setsomevalue F stopenvironmentindeed F settabulateentry F stopfontclass F settabulatelastentry F stophboxregister F settracing F stopproductindeed F setupsystem F stopprojectindeed F setupwithargument F stopreadingfile F setvalue F stopregisterentries F setyboxregister F stopregisterentry F setxvalue F stopregisteroutput F space F stopregisterpages F sprint F stopregistersection F startLuaSnippet F stopregisterseewords

F stoptabulate F LuaSnippetString F stoptext F MetapostSnippetBoundary F MetapostSnippetComment F stoptitle F MetapostSnippetConstructor F stopvboxregister F stopxtitle F MetapostSnippetName F storenode F MetapostSnippetNameMetafun F synonymentry F MetapostSnippetNamePlain F tabulaterow F MetapostSnippetNamePrimitive F tabulaterowbold F MetapostSnippetQuote F MetapostSnippetSpecial F tabulaterowtyp F tabulaterowtype F MetapostSnippetString F template F ParsedXmlSnippetCdata T templates F ParsedXmlSnippetComment F texsetup F ParsedXmlSnippetDoctype F tobuffer F ParsedXmlSnippetElement F tocontext F ParsedXmlSnippetInstruction F tolines F TexSnippetBoundary F units(F TexSnippetComment F TexSnippetGroup F unitsN F unitsNspace F TexSnippetName F unitsNstart F TexSnippetSpecial F unitsNstop F XmlSnippetBoundary F XmlSnippetCdata F units0 F unitsP F XmlSnippetComment F unitsPS F XmlSnippetEntity F unitsPII F XmlSnippetEqual F unitsPUS F XmlSnippetKey F units0 F XmlSnippetName F unitsS F XmlSnippetString F unitsU F ctxreport F unitsUS F viafile F unprotect F vrule F unregisterfunction F xmlcdataafter F xmlcdatabefore F usemodule F utfchar F xmlcdataobeyedline T verbatim F xmlcdataobeyedspace F LuaSnippetBoundary F xmlprocessbuffer F xmlsetup F LuaSnippetComment function F LuaSnippetName numbers F LuaSnippetNameBase F LuaSnippet F LuaSnippetNameCore F LuaSnippetBoundary F LuaSnippetNameLibraries F LuaSnippetComment

F LuaSnippetName

F LuaSnippetNameBase

F LuaSnippetQuote

F LuaSnippetSpecial

F LuaSnippetNameCore F addaskedblankskip F LuaSnippetNameLibraries F addpredefinedblankskip F LuaSnippetQuote F applyprocessor F LuaSnippetSpecial F beginhbox F LuaSnippetString F beginvbox F MPcolor F bf F MetapostSnippet F baroup F blank F MetapostSnippetBoundary F MetapostSnippetComment F hold F MetapostSnippetConstructor F btxchecklistentry F MetapostSnippetName F btxcitevariantparameter F MetapostSnippetNameMetafun F btxdirectlink F MetapostSnippetNamePlain F btxdomarkcitation F MetapostSnippetNamePrimitive F btxhandlelistentrv F MetapostSnippetQuote F btxlistparameter F MetapostSnippetSpecial F btxlistvariantparameter F MetapostSnippetString F callfunctiononce F NC F char F chardef F NR F ParsedXmlSnippetCdata F color F ParsedXmlSnippetComment F colordefagc F ParsedXmlSnippetDoctype F colordefagt F ParsedXmlSnippetElement F colordefalc F ParsedXmlSnippetInstruction F colordefalt F ParsedXmlSnippetKev F colordeffac F ParsedXmlSnippetValue F colordeffat F colordefflc F TexSnippet F TexSnippetBoundary F colordefflt F TexSnippetComment F colordefrgc F TexSnippetGroup F colordefrqt F TexSnippetName F colordefrlc F TexSnippetSpecial F colordefrlt F XmlSnippet F concat F XmlSnippetBoundary F constructcs F XmlSnippetCdata F constructcsonly F XmlSnippetComment F convertnumber F XmlSnippetEntity F ctxreport F XmlSnippetEqual F darkblue F darkgreen F XmlSnippetKey F XmlSnippetName F darkred F XmlSnippetString F definefontsynonym T delayed F __flush F flushdirect F digitsdigit F flushlines F digitsfinalcomma

F digitsfinalperiod F environment F digitshighspace F expandreferencearguments F digitsintermediatecomma F expandreferenceoperation F digitsintermediateperiod F finalizeautostructurelevel F digitsminus F finishjob F digitsnegative F firstofoneargument F firstoftwoarguments F digitsplus F digitspositive F fixedblankskin F digitspower F flexibleblankskip F flushblankhandling F digitspowerminus F digitspowerplus F flushboxregister F digitsseparatorspace F flushnode F digitssignspace F fntsetdefname F digitsspace F fntsetnopsize F digitszeropadding F fntsetsomename F direct F fntsetsomesize F directsetup T formatted F dodirectfullreference F fprint F dodisplayverbatimbeginline T generics F dodisplayverbatimemptyline S starttabulate F dodisplavverbatiminitialize S stoptabulate F dodisplayverbatimnewline F getlogger F dodisplayverbatimstart F getreferencestructureprefix F dodisplayverbatimstop F getvalue F dofastdefinetypeface F glyph F dofinishsomereference F gobbleoneargument F dofromfiledescription F goto F dofromfileliteral F hrule F dofromurldescription F input F dofromurlliteral T knownfunctions F doinlineverbatimbeginline F lateluafunction F doinlineverbatimemptyline F letvaluerelax F doinlineverbatimnewline F loadfile F doinlineverbatimstart F loadfoundtypescriptfile F doinlineverbatimstop F luasetup F donestedtypingstart F m F donestedtypingstop T metafun F dostarttext F color F doverbatimspace T delayed F egroup F start F emptyreference F stop F enablemode T nested F endhbox F markingcommand F endvbox F markingseparator

F newbox F setupsystem F newcount F setupwithargument F newdimen F setvalue F newindexer F setyboxregister F newmuskip F setxvalue F newskip F space F newtexthandler F sprint F newtoks F startLuaSnippet F newverbosehandler F startMetapostSnippet F nointerlineskip F startParsedXmlSnippet F normalatop F startTexSnippet F normalover F startXmlSnippet F overstrike F startblankhandling F startcolumns F par F pdfliteral F startcomponentindeed F popcatcodes F startenvironmentindeed F poplogger F startfontclass F printlines F starthboxregister F processfilemany F startproductindeed F processfilenone F startprojectindeed F processfileonce F startreadingfile F protect F startregisterentries F startregisterentry T puretext F pushcatcodes F startregisteroutput F pushlogger F startregisterpages F registerentry F startregistersection F startregisterseewords F registerfunction F registeronepage F starttabulate F starttext F registerpagerange F registerseeword F starttitle F reservefunction F startvboxregister F rlap F startxtitle F runfile F stopLuaSnippet F secondoftwoarguments F stopMetapostSnippet F setblankcategory F stopParsedXmlSnippet F setblankorder F stopTexSnippet F setblankpenalty F stopXmlSnippet F setconditional F stopblankhandling F setfalsevalue F stopcolumns F sethboxregister F stopcomponentindeed F setsomevalue F stopenvironmentindeed F settabulateentry F stopfontclass

F stophboxregister

F stopproductindeed

F settabulatelastentry

F settracing

F stopprojectindeed F LuaSnippetBoundary F stopreadingfile F LuaSnippetComment F stopregisterentries F LuaSnippetName F LuaSnippetNameBase F stopregisterentry F stopregisteroutput F LuaSnippetNameCore F stopregisterpages F LuaSnippetNameLibraries F stopregistersection F LuaSnippetOuote F LuaSnippetSpecial F stopregisterseewords F stoptabulate F LuaSnippetString F MetapostSnippetBoundary F stoptext F stoptitle F MetapostSnippetComment F stopyboxregister F MetapostSnippetConstructor F stopxtitle F MetapostSnippetName F storenode F MetapostSnippetNameMetafun F synonymentry F MetapostSnippetNamePlain F tabulaterow F MetapostSnippetNamePrimitive F tabulaterowbold F MetapostSnippetQuote F MetapostSnippetSpecial F tabulaterowtyp F tabulaterowtype F MetapostSnippetString F template F ParsedXmlSnippetCdata T templates F ParsedXmlSnippetComment F texsetup F ParsedXmlSnippetDoctype F tobuffer F ParsedXmlSnippetElement F tocontext F ParsedXmlSnippetInstruction F tolines F TexSnippetBoundary F unitsC F TexSnippetComment F unitsN F TexSnippetGroup F unitsNspace F TexSnippetName F unitsNstart F TexSnippetSpecial F unitsNstop F XmlSnippetBoundary F units0 F XmlSnippetCdata FunitsP F XmlSnippetComment F unitsPS F XmlSnippetEntity F unitsPU F XmlSnippetEqual F unitsPUS F XmlSnippetKey F units0 F XmlSnippetName F unitsS F XmlSnippetString F unitsU F ctxreport F unitsUS F viafile F unprotect F vrule F unregisterfunction F xmlcdataafter F usemodule F xmlcdatabefore F utfchar F xmlcdataobeyedline T verbatim F xmlcdataobeyedspace

| F xmlprocessbuffer | | processcolorcomponents | function |
|---|----------|----------------------------|----------|
| F xmlsetup | | processedfile | function |
| objectnumber | function | processedfiles | function |
| objectpage | function | processfile | function |
| octnumber | function | processfilemany | function |
| octstringtonumber | function | processfilenone | function |
| ordinal | function | processfileonce | function |
| overloadbookmark | function | processlist | function |
| <pre>page_injections_flush_after</pre> | function | processregister | function |
| <pre>page_injections_flush_before</pre> | function | processsplit | function |
| page_injections_save | function | processsynonyms | function |
| pagestaterealpage | function | purefontname | function |
| parpos | function | pushfloat | function |
| pdfrotation | function | pushitaliccorrection | function |
| pdfstartmatrix | function | pushlist | function |
| pdfstartmirroring | function | pushreferenceprefix | function |
| pdfstartrotation | function | pushregime | function |
| pdfstartscaling | function | pushsectionblock | function |
| pdfstopmatrix | function | rawcharacter | function |
| pdfstopmirroring | function | rawcountervalue | function |
| pdfstoprotation | function | rawdate | function |
| pdfstopscaling | function | referencepagestate | function |
| percentageof | function | referencerealpage | function |
| pgfxcolorspec | function | registerattachment | function |
| placeparallel | function | registerbookmark | function |
| popfloat | function | registerbuttons | function |
| popitaliccorrection | function | registercatcodetable | function |
| poplist | function | registercolor | function |
| popreferenceprefix | function | registercolorintent | function |
| popregime | function | registeredviewerlayer | function |
| popsectionblock | function | registerhelp | function |
| pos | function | registeritemgroup | function |
| posplus | function | registerlanguagefeatures | function |
| posstrut | function | registerlinenumbering | function |
| postponenotes | function | registermaintextcolor | function |
| poswhd | function | registernamespace | function |
| posxy | function | registerpostponedblock | function |
| prefixedconverted | function | registerrendering | function |
| prepareMPvariable | function | registersection | function |
| preparedfile | function | registersoundclip | function |
| presetsymbollist | function | registerstructureprocessor | function |
| presettabulate | function | registersynonym | function |
| prevcountervalue | function | registertransparency | function |
| processbuffer | function | registerunit | function |

| registerusedsynonym | function | savetwopassdata | function |
|--------------------------|----------|-------------------------|----------|
| registeruserdata | function | savevariable | function |
| relatemarking | function | second | function |
| remapentity | function | selectstructureblock | function |
| removemissingcharacters | function | setbreakpoints | function |
| renderingvar | function | setbtxdataset | function |
| replacemissingcharacters | function | setbtxentry | function |
| replacepospxywhd | function | setcharacteralign | function |
| reportstructure | function | setcharactercasing | function |
| resavefloat | function | setcharactercleaning | function |
| resetcharacteralign | function | setcharactercodes | function |
| resetcounter | function | setcharacterkerning | function |
| resetfontfeature | function | setcharacterspacing | function |
| resetfontsolution | function | setcharacterstripping | function |
| resetmarking | function | setclosedocumentaction | function |
| resetmathattributes | function | setclosepageaction | function |
| resetmathitalics | function | setcolormodel | function |
| resetnullfont | function | setcounter | function |
| resetparallel | function | setdataset | function |
| resetprevdepth | function | setdigitsmanipulation | function |
| resetreference | function | setdirection | function |
| resetstructureprocessor | function | setdocumentenvironments | function |
| resettimer | function | setdocumentfilenames | function |
| restartcounter | function | setdocumentmodes | function |
| restorecounter | function | setdocumentmodules | function |
| restorecurrentattributes | function | setfigurelookuporder | function |
| restorenote | function | setfirstline | function |
| romannumerals | function | setfontfeature | function |
| runbuffer | function | setfontofid | function |
| safechar | function | setfontsolution | function |
| savebuffer | function | setformat | function |
| savecounter | function | setformsmethod | function |
| savecurrentattributes | function | setinitial | function |
| savedlistnumber | function | setinsertionlocation | function |
| savedlistprefixednumber | function | setinterfaceconstant | function |
| savedlisttitle | function | setinterfaceelement | function |
| savefloat | function | setinterfacemessage | function |
| savemargindata | function | setinterfacemessages | function |
| savenote | function | setinterfacevariable | function |
| saveobject | function | setinternalreference | function |
| savepagedata | function | setjobcomment | function |
| saveparallel | function | setlanguageexceptions | function |
| savestructureblock | function | setlanguagesynonym | function |
| savetaggedtwopassdata | function | setlayer | function |

| setmarking | function | setupcanvas | function |
|--------------------------|----------|----------------------------|----------|
| setmathalphabet | function | setupcharacterspacing | function |
| setmathalternate | function | setupexport | function |
| setmathattribute | function | setupfontexpansion | function |
| setmathdirection | function | setupfontprotrusion | function |
| setmathitalics | function | setupidentity | function |
| setmathstyle | function | setupinsertion | function |
| setnextinternalreference | function | setupitaliccorrection | function |
| setnextreferenceorder | function | setuplinenumbering | function |
| setnotestate | function | setvisual | function |
| setnotesymbolpage | function | setxmpfile | function |
| setobject | function | showassignerror | function |
| setopendocumentaction | function | showattributes | function |
| setopenpageaction | function | showbtxdatasetcompleteness | function |
| setowncounter | function | showbtxdatasetfields | function |
| setpagestate | function | showcallbacks | function |
| setpagestaterealpageno | function | showchardata | function |
| setpagetransition | function | showcounter | function |
| setparbuilder | function | showfontparameters | function |
| setpos | function | showhyphenatedinlist | function |
| setrandomseed | function | showjustification | function |
| setrealign | function | showmessage | function |
| setreferencearguments | function | sin | function |
| setreferenceattribute | function | sind | function |
| setreferenceoperation | function | splitfilename | function |
| setregistermethod | function | spotcolorname | function |
| setreplacements | function | spotcolorparent | function |
| setsectionblock | function | spotcolorvalue | function |
| setsectionentry | function | startchemical | function |
| setsectionlevel | function | startcolorset | function |
| setsectionnumber | function | startcomponent | function |
| setstructureblockstate | function | startenvironment | function |
| settagcombination | function | startfontsolution | function |
| settagdescription | function | startparbuilder | function |
| settagdescriptionsymbol | function | startproduct | function |
| settagfigure | function | startproject | function |
| settaghighlight | function | startregime | function |
| settagitemgroup | function | startsectionlevel | function |
| settagproperty | function | starttag | function |
| settagsorting | function | starttext | function |
| settagsynonym | function | startviewerlayer | function |
| settagtablecell | function | stopchemical | function |
| settagtabulatecell | function | stopcolorset | function |
| setupbookmarks | function | stopcomponent | function |

| stopenvironment | function | typefile | function |
|---------------------------|----------|-----------------------|----------|
| stopfontsolution | function | typestring | function |
| stopparbuilder | function | uchexnumber | function |
| stopproduct | function | uchexnumbers | function |
| stopproject | function | undefinechemical | function |
| stopregime | function | unicodechar | function |
| stopsectionlevel | function | unit | function |
| stoptag | function | unloadlanguage | function |
| stoptext | function | upper | function |
| stopviewerlayer | function | useMPlibrary | function |
| storejavascriptcode | function | useanyfile | function |
| storejavascriptpreamble | function | usebtxdataset | function |
| storenote | function | usecldfile | function |
| storeregister | function | usecolors | function |
| strdp | function | usecomponent | function |
| strhd | function | useenvironment | function |
| strht | function | usefile | function |
| strip | function | usejavascriptpreamble | function |
| structureautocatcodedget | function | usejavascriptscripts | function |
| structurecatcodedget | function | uselibrary | function |
| structuregivencatcodedget | function | useluafile | function |
| structurenumber | function | useluamodule | function |
| structuretitle | function | usemodules | function |
| structureuservariable | function | usepath | function |
| structurevariable | function | useproduct | function |
| strwd | function | useproject | function |
| subcountervalues | function | usesubpath | function |
| synchronizecolormodel | function | usesymbols | function |
| synchronizemarking | function | usetexfile | function |
| synonymmeaning | function | useurl | function |
| synonymname | function | usexmlfile | function |
| taggedmathfunction | function | usezipfile | function |
| tan | function | utfchar | function |
| tand | function | utfmathclass | function |
| testcase | function | utfmathcommand | function |
| textime | function | utfmathcommandabove | function |
| thefirstcharacter | function | utfmathcommandbelow | function |
| theremainingcharacters | function | utfmathfiller | function |
| thetexdefinition | function | utfmathstretch | function |
| transparencycomponents | function | vboxlisttohbox | function |
| triggereffect | function | verbose | function |
| triggernegative | function | visual | function |
| truefilename | function | vspacing | function |
| typebuffer | function | vspacingcollapse | function |
| | | | |

| vspacingdefine | function |
|----------------------------|----------|
| vspacingsetamount | function |
| vspacingsnap | function |
| way | function |
| weekday | function |
| weekdayname | function |
| writestatus | function |
| x_table_c | function |
| x_table_cleanup | function |
| x_table_construct | function |
| x_table_create | function |
| x_table_flush | function |
| x_table_init_construct | function |
| x_table_init_reflow_height | function |
| x_table_init_reflow_width | function |
| x_table_next_row | function |
| x_table_r | function |
| x_table_reflow_height | function |
| x_table_reflow_width | function |
| x_table_set_construct | function |
| x_table_set_reflow_height | function |
| x_table_set_reflow_width | function |
| year | function |
| - | |

containers (context)

```
cleanname function
content function
define function
is_usable function
read function
usecache boolean
write function
```

converters (context)

| Alphabetic | function |
|--------------------|------------|
| Character | function |
| Characters | function |
| Romannumerals | function |
| abjadnodotnumerals | function |
| abjadnumerals | function |
| alphabetic | function |
| character | function |
| characters | function |
| chineseallnumerals | function |
| chinesecapnumerals | function |
| chinesenumerals | function |
| chr | function |
| chrs | function |
| convert | function |
| define | function |
| hexstringtonumber | function |
| hour | function |
| isleapyear | function |
| leapyear | function |
| maxchrs | function |
| minute | function |
| month | function |
| nofdays | function |
| number | function |
| numbers | function |
| octstringtonumber | function |
| ordinal | function |
| rawcharacter | function |
| romannumerals | function |
| second | function |
| sequences | data table |
| textime | function |
| toabjad | function |
| tochinese | function |
| toroman | function |
| verbose | table |
| D data | |

weekday function year function

F translate

coroutine (basic lua)

```
create function
resume function
running function
status function
wrap function
yield function
```

ctxrunner (context)

load function
prepfiles data table
resolve function

debug (basic lua)

| debug | function |
|--------------|----------|
| getfenv | function |
| gethook | function |
| getinfo | function |
| getlocal | function |
| getmetatable | function |
| getregistry | function |
| getupvalue | function |
| getuservalue | function |
| setfenv | function |
| sethook | function |
| setlocal | function |
| setmetatable | function |
| setupvalue | function |
| setuservalue | function |
| traceback | function |
| upvalueid | function |
| upvaluejoin | function |

dir (context)

| collectpattern | function |
|----------------|----------|
| current | function |
| expandname | function |
| found | function |
| glob | function |
| globfiles | function |
| globpattern | function |
| ls | function |
| makedirs | function |
| mkdirs | function |
| рор | function |
| push | function |

directives (context)

data data table default function disable function enable function list function name string register function report function show function value function

document (context)

arguments data table
files table
getargument function
getfilename function
options table

T commandline

D environments

D modes

D modules

T ctxfile

D environments

D modes

D modules

setargument function
setdefaultargument function
setfilename function
variables data table

environment (context)

function argument arguments data table basicengines data table currentrun number default texmfcnf strina engineflags data table filename strina files table data table filesynonyms number forcedruns getargument function homedir string initex boolean **initializearguments** function initializefilenames function inputfilebarename string inputfilename strina **inputfilesuffix** string **jobfilename** string **jobfilesuffix** string kindofrun number loadluafile function luafile function luafilechunk function maxnofruns number originalarguments data table outputfilename string ownbin string ownmain string ownname string ownpath strina boolean prerollrun data table rawarguments reconstructcommandline function relativepath function setargument function **splitarguments** function suffix string texfile function texmfos string texos string

texroot truefilename validengines string function data table

epdf (extra tex)

Array function
Dict function
Object function
PDFRectangle function
open function
type function

experiments (context)

data data table default function disable function enable function list function name string register function report function show function value function

figures (context)

applyratio function bases data table function bitmapimage boxnumber number cachepaths data table check function checkers data table data table converters function current defaultdepth number defaultheight number defaultsearch boolean defaultwidth number function done dummy function existers data table exists function formats data table found data table function get auess function hash function identifiers data table function identify include function includers data table initialize function loaded data table localpaths data table magics data table mergegoodies function nofprocessed number order data table paths data table patterns data table function pop preferquality boolean programs data table push function registerpattern function registerresource function

registersuffix resources scale setlookups setorder setpaths suffixes

used

function data table function function function function data table data table

file (basic lua)

| addsuffix | function |
|-------------------|----------|
| basename | function |
| checksum | function |
| collapsepath | function |
| сору | function |
| dirname | function |
| expandname | function |
| extname | function |
| is_qualified_path | function |
| is_readable | function |
| is_rootbased_path | function |
| is_writable | function |
| isreadable | function |
| iswritable | function |
| join | function |
| joinpath | function |
| loadchecksum | function |
| nameonly | function |
| nametotable | function |
| needs_updating | function |
| needsupdating | function |
| pathpart | function |
| readdata | function |
| removesuffix | function |
| replacesuffix | function |
| reslash | function |
| robustname | function |
| savechecksum | function |
| savedata | function |
| size | function |
| splitbase | function |
| splitname | function |
| splitpath | function |
| strip | function |
| suffix | function |
| suffixes | function |
| suffixesonly | function |
| suffixonly | function |
| syncmtimes | function |
| | |

floats (context)

| analysemethod | function |
|------------------|----------|
| checkedpagefloat | function |
| collect | function |
| consult | function |
| flush | function |
| getvariable | function |
| nofstacked | function |
| рор | function |
| push | function |
| resave | function |
| save | function |
| stacked | function |

font (basic tex)

current function define function each function fonts table frozen function id function

getfont overloaded function

max function nextid function read_tfm function read_vf function setfont function

fontloader (extra tex)

| apply_afmfile | function |
|-------------------|----------|
| apply_featurefile | function |
| close | function |
| fields | function |
| fullinfo | function |
| info | function |
| open | function |
| to_table | function |
| totable | function |

fonts (context)

| analyzers | table | F report |
|-----------------|-------|---------------------------|
| T features | | F reset |
| N blwf | | T vectors |
| N fina | | constructors table |
| N half | | F aftercopyingcharacters |
| N init | | F applymanipulators |
| N isol | | F assignmathparameters |
| N medi | | B autocleanup |
| N pref | | F beforecopyingcharacters |
| N pstf | | D cache |
| N rphf | | F calculatescale |
| D initializers | | F checkedfeatures |
| D methods | | F checkedfilename |
| F setstate | | F checkvirtualids |
| T states | | F cleanuptable |
| N blwf | | F collectprocessors |
| N fina | | D designsizes |
| N half | | D dontembed |
| N init | | F enhanceparameters |
| N isol | | N factor |
| N mark | | F finalize |
| N medi | | F getfeatureaction |
| N pref | | F hashfeatures |
| N pstf | | F hashinstance |
| N rest | | T hashmethods |
| N rphf | | F normal |
| B useunicodemar | ks | F virtual |
| checkers | table | F initializefeatures |
| F getmissing | | T keys |
| F missing | | T character |
| cid | table | S depth |
| F getmap | | S height |
| F loadfile | | S italic |
| collections | table | S width |
| F checkenabled | | T description |
| F clonevector | | T boundingbox |
| F define | | S depth |
| T definitions | | S height |
| F prepare | | S width |
| F process | | T parameters |
| F registermain | | S ascender |

| S descender | S encodingbyt | es |
|--------------------------|------------------|----------|
| S designsize | S filename | |
| T expansion | S finalized | |
| S auto | S fontname | |
| S shrink | S format | |
| S step | S fullname | |
| S stretch | S hasitalics | |
| S extendfactor | S hasmath | |
| S factor | S mathitalics | |
| S hfactor | S mode | |
| S mathsize | S name | |
| T protrusion | S noglyphname | S |
| S auto | S nostackmath | |
| S quad | S psname | |
| S scaledpoints | S textitalics | |
| S scriptpercentage | S virtualized | |
| S scriptscriptpercentage | D loadedfonts | |
| S size | S namemode | |
| S slantfactor | F newfeatures | |
| S slantperpoint | F newhandler | |
| T spacing | N noffontsloaded | |
| S extra | N nofsharedfonts | |
| S shrink | N nofsharedhashe | s |
| S stretch | N nofsharedvecto | rs |
| S width | N privateoffset | |
| T synonyms | F readanddefine | |
| S em | F registerfeatur | e |
| S ex | B resolvevirtual | too |
| S extra_space | F scale | |
| S extraspace | F scaled | |
| S slant | F setfactor | |
| S space | F setname | |
| S space_shrink | B sharefonts | |
| S space_stretch | F trytosharefont | |
| S spaceshrink | N version | |
| S spacestretch | current | function |
| S x_height | currentid | function |
| S units | definers | table |
| S vfactor | F addlookup | |
| S xheight | F analyze | |
| T properties | F applypostproce | ssors |
| S autoitalicamount | F checkedmode | |
| T cidinfo | F checkedscript | |
| S embedding | F current | |
| | | |

| C d-f1+1l | | C mathamatica |
|-------------------|------------|-------------------------|
| S defaultlookup | | F mathematics |
| F define | | F protrusions |
| F getspecificat | ion | F solutions |
| F internal | | F treatments |
| F loadfont | | F typefaces |
| F makespecifica | tion | F load |
| T methods | | F prepare_features |
| F install | | F register |
| D variants | | F registerpostprocessor |
| F read | | F report |
| F register | | handlers table |
| F registered | | T afm |
| F registersplit | | B addkerns |
| F resetnullfont | | B addligatures |
| F resolve | | B addtexligatures |
| T resolvers | | B autoprefixed |
| F file | | D cache |
| F name | | D features |
| F spec | | T helpdata |
| definetypeface | function | D bothkerned |
| encodings | table | D leftkerned |
| T agl | | D ligatures |
| D cache | | D rightkerned |
| F is_known | | D texligatures |
| D known | | F load |
| F load | | F setfeatures |
| F make_unicode_ | vector | B syncspace |
| D math | | N version |
| N version | | T otf |
| expansions | data table | F addfeature |
| formats | data table | D cache |
| goodies | table | T chainhandlers |
| D colorschemes | | F normal |
| D data | | F verbose |
| D designsizes | | F collectlookups |
| D filenames | | F dataset |
| F getcompositions | | S defaultbasealternate |
| T list | | S defaultnodealternate |
| F compositions | | D enhancers |
| F designsizes | | D features |
| F expansions | | F fileformat |
| F featureset | | F getalternate |
| F filenames | | T glists |
| F files | | T handlers |
| | | |

| F contextchain | D math | |
|---|-----------------|-------|
| F devanagari_remove_joiners | D predefined | |
| F devanagari_reorder_matras | D whatever | |
| F devanagari_reorder_pre_base_reordering_consonants | hashes | table |
| F devanagari_reorder_reph | D characters | |
| F gpos_context | D csnames | |
| F gpos_contextchain | D descriptions | |
| F gpos_cursive | D dynamics | |
| F gpos_mark2base | D emwidths | |
| F gpos_mark2ligature | D exheights | |
| F gpos_mark2mark | D extensibles | |
| F gpos_pair | D features | |
| F gpos_single | D identifiers | |
| F gsub_alternate | D italics | |
| F gsub_context | D lastmathids | |
| F gsub_contextchain | D marks | |
| F gsub_ligature | D parameters | |
| F gsub_multiple | T processes | |
| F gsub_reversecontextchain | D properties | |
| F gsub_single | D quads | |
| F load | D resources | |
| F scriptandlanguage | T setdynamics | |
| F setcontextchain | D spaces | |
| F setdynamics | D spacings | |
| F setfeatures | D unicodes | |
| T statistics | D xheights | |
| D usedfeatures | helpers | table |
| T tables | F addprivate | |
| D baselines | F dimenfactor | |
| D features | F expandglyph | |
| D languages | F fontpatternha | ssize |
| D scripts | F getdigitwidth | |
| N version | F getparameters | |
| T pfb | F getprivatenod | е |
| T tfm | F hasprivate | |
| D features | F name | |
| F setfeatures | F nametoslot | |
| T vf | F setdigitwidth | |
| T combinations | F splitfontpatt | ern |
| F combine | iterators | table |
| T combiner | F characters | |
| D commands | F descriptions | |
| F find | F glyphs | |
| D helpers | loggers | table |
| | | |

| F add_placeholde T category_to_pl S ll S lm S lo S lt S lu | | nulldata protrusions readers F afm F check_lua F check_tfm F dfont | data table data table table |
|---|------------|--|-----------------------------------|
| S mc S me S mn S nd S nl S no S pc | | F lua F opentype F otf F pfb D sequence F tfm F ttc | |
| S pd S pe S pf S pi S po S ps S sc S sk S sm S so F format F onetimemessage F register F reportdefinedf | | F ttf select T data F definetypeface T fallbacks F filterinput T methods F default F features F file F goodies F name F selectfont F simplefonts | table |
| F reportusedfeat mappings F addtounicode F fromunicode16 F loadfile F loadline F loadlumtable F makenameparser F reset F tounicode16 F tounicode16sec mp D cache B inline | table | F spec F style F registerfalls: F searchfiles Specifiers D contextmerged F contextnumber: D contextsetups F contexttostrin F definecontext F mergecontext F presetcontext | table s |
| N version names | data table | F showcontext F splitcontext | |

D synonyms

D variants

symbols table

F uselibrary

tables table
tracers table
treatments table

F applyfixes

D data

S filename

F ignoredfile

F report

F trace

typefaces data table

functions (context)

dummy function

graphics (context)

backgrounds table

F calculatemultipar

F fetchmultipar

F pair

F path

F point

gzip (extra lua)

```
close function
lines function
load function
open function
save function
suffix function
```

img (basic tex)

| boxes | function |
|----------------|----------|
| check | function |
| checksize | function |
| clone | function |
| сору | function |
| immediatewrite | function |
| keys | function |
| new | function |
| node | function |
| ofindex | function |
| package | function |
| print | function |
| scan | function |
| serialize | function |
| totable | function |
| types | function |
| write | function |

interactions (context)

```
attachments data table
fields
               table
   F clone
   F define
   F defineset
   F insert
general
               table
   F getidentity
   F setupidentity
help
               table
   F collect
   F reference
   F register
javascripts table
   F addtopreamble
   F code
   D codes
   F flushpreambles
   D functions
   D preambles
   F setpreamble
   F storecode
   F storepreamble
   F usepreamblenow
   F usescripts
linkedlists data table
               table
pages
   F setpagetransition
   F setupcanvas
references table
   F setclosedocument
   F setclosepage
   F setopendocument
   F setopenpage
              data table
renderings
soundclips data table
```

interfaces (context)

addvalidkeys function cachedsetups data table cachesetup function checkedspecification function complete data table constants data table corenamespaces data table definecommand function doifelsemessage function elements data table formats data table getcheckedparameters function function getmessage data table hashedsetups interfacedcommand function interfaces table invalidkev function function is command table namespaces

F define F list

registernamespace function setconstant function setelement function setformat function setmessage function function setmessages settranslation function function setuserinterface setvalidkeys function setvariable function function showmessage data table syntax tolist function translations data table variables data table

io (basic lua)

ask function bytes function characters function close function exists function fileseparator string flush function i limiter function i limiters table

T paranoid

input function limiter function lines function loadchunk function loaddata function loadlines function noflines function function o limiter o limiters table

T paranoid

open overloaded function

output function
pathseparator string

function read readall function readnumber function readstring function savedata function size function stderr userdata stdin userdata stdout userdata **tmpfile** function function type write function

jit (context)

arch string
attach function
flush function
off function
on function
opt table

F start

os string
status function
util table

F funcbc

F funcinfo

F funck

F funcuvname

F ircalladdr

F traceexitstub

F traceinfo

F traceir

F tracek

F tracemc

F tracesnap

version string
version_num number

job (context)

| _ | | |
|-----------------|----------|------------------------|
| comment | function | F getcollected |
| datasets | table | F getdata |
| D collected | | F getfield |
| F extend | | F gettobesaved |
| F getdata | | F inlist |
| F setdata | | F last |
| D tobesaved | | F list |
| | function | F save |
| files | table | F savetagged |
| D collected | | D tobesaved |
| F context | | positions table |
| B forcerun | | F b_col |
| F run | | F b_region |
| D tobesaved | | F c |
| initialize - | function | D collected |
| load | function | F column |
| loadother | function | F copy |
| objects | table | F depth |
| D collected | | F e_col |
| F get | | F e_region |
| F number | | F enhance |
| F page | | F extra |
| F save | | F get |
| F set | | F getreserved |
| D tobesaved | | F hangafter |
| pack | boolean | F hangindent |
| packversion | | F height |
| pagestates | table | F hsize |
| D collected | | F leftskip |
| F extend | | F lowerleft |
| F realpage | | F lowerright |
| F setstate | | F markregionbox |
| D tobesaved | | Fn |
| passes | table | F onsamepage |
| F check | | F overlapping |
| D collected | | Fp |
| F count | | F page |
| F define | | F paragraph |
| F find | | F parindent |
| F first | | F position |
| F get | | Fr |

- F region
- F replace
- F rightskip
- F set
- F setall
- F setdim
- D tobesaved
- F upperleft
- F upperright
- F width
- Fx
- F xy
- Fу

structure

register function save function table

- D collected
- T components
- T tobesaved
 - T branches
 - S name
 - S type

variables table

- D checksums
- D collected
- F getchecksum
- F makechecksum
- F restore
- F save
- F setchecksum
- D tobesaved

version number

lang (basic tex)

| clean | function |
|-------------------|----------|
| clear_hyphenation | function |
| clear_patterns | function |
| exceptions | function |
| hyphenate | function |
| hyphenation | function |
| id | function |
| new | function |
| patterns | function |
| postexhyphenchar | function |
| posthyphenchar | function |
| preexhyphenchar | function |
| prehyphenchar | function |

languages (context)

associate function associated data table association function counters data table function current data data table define function table frequencies F averagecharwidth F getdata getnumber function hyphenate function installed function labels table F define F split lefthyphenmin function loadable function loadwords function table logger F report numbers data table posthyphenchar function function prehyphenchar data table registered replacements table F add F handler F set righthyphenmin function setexceptions function function setsynonym unload function version number table words

F check
T data
F disable
F enable
T enablers
B enables

F load T methods N threshold

F found

layouts (context)

status table

F isleftpage

F leftorrightpagection

lfs (extra lua)

attributes function chdir function currentdir function dir function

isfile function lock function lock dir function mkdir function mkdirs function readlink function rmdir function function setmode function shortname symlinkattributes function touch function unlock function

libraries (context)

```
basiclua data table
basictex data table
builtin data table
extralua data table
extratex data table
functions data table
globals data table
```

lmx (context)

color function convert function convertfile function function convertstring einject function eprint function escape function finalized function finject function fprint function get function getvariables function htmfile function html table

Fa

F td F th

include function
inherited table

S color-background-four

S color-background-one

S color-background-three

S color-background-two

S title

initialize function inject function **lmxfile** function loadedfile function function new overloaderror function popupfile function print function pν function report function reset function result function function set show function showdebuginfo function showerror function stripcss function tv function
type function
urlescape function
variable function
variables table

S color-background-blue

S color-background-body

S color-background-green

S color-background-main

S color-background-purple

S color-background-yellow

S title-default

logs (context)

application function categories function direct function disable function function enable exporters table extendbanner function flush function function help function messenger new function newline function function poptarget function pushtarget report function reportbanner function function reporter table reporters

> F banner F export

F help

F info

F lines

F version

function reportline reportlines function setformats function setformatters function setlogfile function setmessenger function setprocessor function function setprogram settarget function settimedlog function settranslations function show function show close function show load function function show open simple function simpleline function

simplelines function function start page number status function function stop_page_number subdirect function subreport function system function function texerrormessage writer function

lpdf (context)

| action | function | gethpos | function |
|--------------------------|------------|---------------------------|------------|
| adddocumentcolorspace | function | getmatrix | function |
| adddocumentextgstate | function | getpos | function |
| adddocumentpattern | function | getvpos | function |
| adddocumentshade | function | graycode | function |
| addtocatalog | function | hasmatrix | function |
| addtoinfo | function | id | function |
| addtonames | function | injectxmpinfo | function |
| addtopageattributes | function | insertxmpinfo | function |
| addtopageresources | function | layerreference | function |
| addtopagesattributes | function | limited | function |
| addxmpinfo | function | linearshade | function |
| annotationspecification | function | nametree | function |
| array . | function | null | function |
| boolean | function | number | function |
| border | function | pagedestinations | data table |
| checkedkey | function | pagereference | function |
| checkedvalue | function | pagereferences | data table |
| circularshade | function | pdfcolor | function |
| cmykcode | function | pdftimestamp | function |
| collectedresources | function | protectresources | boolean |
| color | function | rectangle | function |
| colorspace | function | reference | function |
| colorspaceconstants | data table | registerannotation | function |
| colorspec | function | registerdestination | function |
| colorvalue | function | registerdocumentfinalizer | function |
| colorvalues | function | registerpagefinalizer | function |
| constant | function | reserveobject | function |
| delayedobject | function | rgbcode | function |
| destinationspecification | function | rotationcm | function |
| dictionary | function | shareobject | function |
| epdf | table | shareobjectreference | function |
| F expand | | spotcode | function |
| Fload | | stream | function |
| finalizedocument | function | string | function |
| finalizepage | function | timestamp | function |
| finishtransparencycode | function | toeight | function |
| flushobject | function | tosixteen | function |
| flushstreamfileobject | function | transform | function |
| flushstreamobject | function | transparency | function |
| formats | data table | transparencycode | function |

transparencygroups table

B none

transparencyvalue function
unicode function
verbose function

lpeg (basic lua)

| В | function |
|-----------------|------------|
| C | function |
| Carg | function |
| Cb | function |
| Cc | function |
| Cf | function |
| Cg | function |
| Cmt | function |
| Ср | function |
| Cs | function |
| Ct | function |
| P | function |
| R | function |
| S | function |
| UP | function |
| UR | function |
| US | function |
| V | function |
| afterprefix | function |
| anywhere | function |
| append | function |
| balancer | function |
| beforesuffix | function |
| checkedsplit | function |
| counter | function |
| endstripper | function |
| finder | function |
| firstofsplit | function |
| frontstripper | function |
| instringchecker | function |
| is_lpeg | function |
| keeper | function |
| locale | function |
| match | function |
| oneof | function |
| patterns | data table |
| pcode | function |
| print | function |
| ptree | function |
| replacer | function |
| secondofsplit | function |

| setmaxstack | function |
|-------------------------------|----------|
| split | function |
| splitat | function |
| splitter | function |
| stripper | function |
| times | function |
| tsplitat | function |
| tsplitter | function |
| type | function |
| ${\tt utfchartabletopattern}$ | function |
| version | function |

ltn12 (extra lua)

BLOCKSIZE number filter table F chain F cycle pump table F all F step sink table F chain F error F file F null F simplify F table source table F cat F chain F empty F error F file F rewind F simplify

F string

lua (basic tex)

bytecode table bytedata data table bytedone table collectgarbage function function delay finalize function firstbytecode number flush function flushdelayed function get_functions_table function getbytecode function function getluaname lastbytecode number string mask messages data table name table numbers data table registercode function registeredcodes function registerfinalizer function registername function setbytecode function setluaname function startupfile string version string

luatex (context)

cleanuptempfiles function
registerstartactions function
registerstopactions
registertempfile function
starttime number

lxml (context)

| addindex | function | getid | function |
|-------------------|-------------------|------------------|----------|
| all | function | getindex | function |
| applyfunction | function | id | function |
| att | function | idsplitter | userdata |
| attribute | function | include | function |
| chainattribute | function | index | function |
| checkindex | function | info | function |
| collected | function | inlineverbatim | function |
| command | function | installsetup | function |
| concat | function | last | function |
| concatrange | function | load | function |
| content | function | loadbuffer | function |
| context | function | loaddata | function |
| convert | function | loaded | table |
| count | function | loadregistered | function |
| delete | function | main | function |
| direct | function | match | function |
| directives | table | name | function |
| F after | | namespace | function |
| F before | | nonspace | function |
| F handle | | pos | function |
| F load | | position | function |
| F setup | | raw | function |
| displayverbatim | function | rawroot | function |
| doif | function | register | function |
| doifelse | function | registerentity | function |
| doifelsetext | function | removesetup | function |
| doifnot | function | resetcdata | function |
| doifnottext | function | resetsetups | function |
| doiftext | function | resolvedentity | function |
| element | function | root | function |
| elements | function | serialize | function |
| entities | data table | setaction | function |
| filter | function | setcdata | function |
| filterlist | function | setcommandtonone | function |
| first | function | setcommandtotext | function |
| flush | function | setsetup | function |
| flushlinewise | function | snippet | function |
| flushsetups | function | sorters | table |
| flushspacewise | function function | F add | |
| get_id | + unction | F compare | |

F flush
F reset
F show

F sort

splitid function startraw function stopraw function store function strip function stripped function tag function text function tofile function toparameters function toverbatim function verbatim function withindex function data table xmltexhandler

math (basic lua)

| abs | function |
|----------------|----------|
| acos | function |
| asin | function |
| atan | function |
| atan2 | function |
| ceil | function |
| cos | function |
| cosd | function |
| cosh | function |
| deg | function |
| div | function |
| even | function |
| ехр | function |
| floor | function |
| fmod | function |
| frexp | function |
| huge | number |
| initialseed | number |
| ldexp | function |
| log | function |
| log10 | function |
| max | function |
| min | function |
| mod | function |
| modf | function |
| odd | function |
| pi | number |
| pow | function |
| rad | function |
| random | function |
| randomseed | function |
| round | function |
| setrandomseedi | function |
| sin | function |
| sind | function |
| sinh | function |
| sqrt | function |
| tan | function |
| tand | function |
| tanh | function |

mathematics (context)

| addfallbacks | function |
|------------------------|------------|
| alphabets | data table |
| big | function |
| boldmap | table |
| categories | table |
| D functions | |
| checkaccentbaseheight | function |
| checkprivateparameters | function |
| classes | data table |
| codes | data table |
| define | function |
| dimensions | function |
| extensiblecode | function |
| extensibles | data table |
| extrabase | number |
| extras | table |
| E add | |

setalternate function setitalics function svncboth function function syncname function syncstyle toname function tostyle function function tweakaftercopyingfont tweakbeforecopyingfont function table tweaks utfmathaccent function utfmathclass function utfmathcommand function utfmathfiller function utfmathstretch function

F add F copy

fallbacks table

F apply
F install

fallbackstyleattr function **families** data table table gaps getboth function getstyle function initializeparameters function injectfallbacks function makefont function mapremap data table **overloaddimensions** function overloadparameters | function privatebase number remapalphabets function renderings table

 ${\bf D}\ {\bf mappings}$

D numbers

D sets

renderset function
resetitalics function
scaleparameters function

mbox (context)

```
parse function
parse_from function
parse_header function
parse_message function
split_headers function
split_mbox function
split_message function
```

md5 (extra lua)

```
HEX function
crypt function
dec function
exor function
hex function
sum function
sumhexa function
```

metapost (context)

| | function | anttoyt | function |
|----------------------------------|------------|--------------------|----------------------|
| analyzeplugins checkformat | function | gettext graphic | function function |
| checktexts | function | graphic_base_pass | function |
| collapse | boolean | instance | function |
| colorinitializer | function | intermediate | table |
| convert | | | table |
| | function | T actions | |
| defaultformat | string | F makempy | |
| defaultinstance defaultmethod | string | lastlog | string |
| | string | llx | number |
| directrun | function | lly | number |
| edefsxsy | function | load | function |
| escaped | function | makempy | table |
| exectime | table | N nofconverted | |
| extensiondata | data table | F processgraphics | |
| filterclippath | function | F registerfile | |
| finder | function | metafun | table |
| flush | function | F interpolate | |
| flushers | table | F topath | |
| T pdf | | method | number |
| F comment | | mptopdf | table |
| F flushfigure | | F convertmpstopdf | |
| F startfigure | | N nofconverted | |
| F stopfigure | | multipass | boolean |
| F textfigure | | n | number |
| flushliteral | function | nvformat | function |
| flushnormalpath | function | optimize | boolean |
| flushreset | function | parse | function |
| fonts | table | pdfliterals | function |
| F define | | pluginactions | function |
| T flusher | | process | function |
| F flushfigure | | processplugins | function |
| F startfigure | | processspecial | function |
| F stopfigure | | quickanddirty | function |
| N instances | | reducetogray | boolean |
| F process | | reporterror | function |
| format | function | reset | function |
| format_number | function | resetlastlog | function |
| format_string | function | resetplugins | function |
| formatnumber | function | resettextexts | function |
| getclippath | function | setextensions | function |
| getextensions | function | setoutercolor | function |

settext function
settextexts function
showlog boolean
svformat function
tex table

F get
F reset
F set

boolean texerrors function textextsdata theclippath function function totable unload function untagvariable function urx number number ury variables table

mime (extra lua)

```
b64
           function
           function
decode
decodet
           table
   F base64
   F quoted-printable
dot
           function
encode
           function
encodet
           table
   F base64
   F quoted-printable
eol
           function
normalize function
           function
qp
           function
qpwrp
stuff
           function
unb64
           function
           function
unqp
           function
wrap
           table
wrapt
   F base64
   F default
   F quoted-printable
   F text
           function
wrp
```

mplib (extra tex)

fields function
finders table

F file

new function
pen_info function
preprocessed function
version function

noads (context)

handlers table F check F classes F collapse F families F italics F relocate F render F resize F showtree F tags F unscript F variants function process processors table T collapse F mlist_to_hlist T relocate T render T resize

T unscript

node (basic tex)

| сору | function | F protect_glyphs | |
|--------------------------|----------|-------------------------|----------|
| copy_list | function | F protrusion_skippable | |
| count | function | F remove | |
| current attr | function | F set_attribute | |
| dimensions | function | F set_properties_mode | |
| direct | table | F setbox | |
| F copy | cabic | F setfield | |
| F copy_list | | F setproperty | |
| F count | | F slide | |
| F current_attr | | F tail | |
| F dimensions | | F todirect | |
| F do_ligature_n | | F tonode | |
| F end_of_math | | F tostring | |
| F first_glyph | | F traverse | |
| F flush_list | | F traverse_id | |
| - F flush_node | | - F unprotect_glyphs | |
| F flush_properties_table | | F unset_attribute | |
| F free | | - F usedlist | |
| F get_properties_table | | F vpack | |
| F getbox | | F write | |
| F getchar | | do_ligature_n | function |
| F getfield | | end_of_math | function |
| F getfont | | family_font | function |
| F getid | | fields | function |
| F getleader | | first_character | function |
| F getlist | | first_glyph | function |
| F getnext | | flush_list | function |
| F getprev | | flush_node | function |
| F getproperty | | flush_properties_table | function |
| F getsubtype | | free | function |
| F has_attribute | | get_properties_table | function |
| F has_field | | getchar | function |
| F has_glyph | | getfield | function |
| F hpack | | getfont | function |
| F insert_after | | getid | function |
| F insert_before | | getleader | function |
| F is_direct | | getlist | function |
| F is_node | | getnext | function |
| F last_node | | getprev | function |
| F length | | getproperty | function |
| F new | | getsubtype | function |

| has_attribute | function |
|---------------------------------|----------|
| has_field | function |
| has_glyph | function |
| hpack | function |
| id | function |
| insert_after | function |
| insert_before | function |
| is_node | function |
| kerning | function |
| last_node | function |
| length | function |
| ligaturing | function |
| mlist_to_hlist | function |
| new | function |
| next | function |
| prev | function |
| protect_glyphs | function |
| <pre>protrusion_skippable</pre> | function |
| remove | function |
| set_attribute | function |
| set_properties_mode | function |
| setfield | function |
| setproperty | function |
| slide | function |
| subtype | function |
| tail | function |
| tostring | function |
| traverse | function |
| traverse_id | function |
| type | function |
| types | function |
| unprotect_glyphs | function |
| unset_attribute | function |
| usedlist | function |
| vpack | function |
| whatsits | function |
| write | function |

nodes (context)

| | | • | |
|--|--|--|----------------------------------|
| accentcodes | data table | free_spec | function |
| aligned | function | getattr | function |
| append | function | getattribute | function |
| astable | function | getbox | function |
| basepoints | function | getchar | function |
| builders | table | getfield | function |
| F buildpage_filter | | getfont | function |
| F vpack_filter | | getid | function |
| codes | data table | getleader - · | function |
| concat | function | getlist | function |
| сору | function | getnext | function |
| copy_list | function | getprev | function |
| copy_spec | function | getskip | function |
| count | function | getsubtype | function |
| current_attr | function | gluecodes | data table |
| delete | function | glyphcodes | data table |
| destinations | table | glyphdir_is_equal | data table |
| N attribute | | glyphdir_is_opposite | data table |
| T done | | glyphdir_is_orthogonal | data table |
| F handler | | gonuts | boolean |
| T stack | | handlers | table |
| dimensionfields | data table | F accessibility | |
| dimensions | function | F alignbackgrounds | |
| dir_is_pop | data table | F backgrounds | |
| dir_negation | data table | F characters | |
| disccodes | data table | F checkforleaks | |
| discretionarycodes | data table | F checkglyphs | |
| do_ligature_n | function | F cleanupbox | |
| end_of_math | function | F cleanuppage | |
| fasthpack | function | F export | |
| fencecodes | data table | F finalize | |
| fields | function | F migrate | |
| fillcodes | data table | F protectglyphs | |
| first_character | function | F stripping | |
| | | | |
| first_glyph | function | F unprotectglyphs | |
| first_glyph firstcharacter | function function | F unprotectglyphs has_attribute | function |
| | | | function function |
| firstcharacter | function | has_attribute | |
| firstcharacter firstcharinbox | function function | has_attribute has_field | function |
| firstcharacter firstcharinbox firstglyph | function function function | has_attribute has_field has_glyph | function function |
| firstcharacter firstcharinbox firstglyph flush_list | function function function function | has_attribute has_field has_glyph hpack | function function function |

| injections | table | markers |
|-------------------------|------------|------------------|
| F handler | | F get |
| F installnewkern | | mathcodes |
| F setcursive | | mlist_to_hlist |
| F setkern | | new |
| F setmark | | noadcodes |
| F setpair | | nodecodes |
| insert_after | function | nopts |
| insert_before | function | nuts |
| insert_list_after | function | F append |
| installattributehandler | function | F concat |
| is_direct | function | F copy |
| is_display_math | function | F copy_list |
| is_mirrored | data table | F count |
| is_node | function | F current_attr |
| is_nut | function | F delete |
| is_rotated | data table | F dimensions |
| kerncodes | data table | F do_ligature_n |
| kerning | function | F end_of_math |
| keys | table | F fasthpack |
| T whatsit | | F first_glyph |
| last_node | function | F firstcharacter |
| leftmarginwidth | function | F firstcharinbox |
| ligaturing | function | F firstglyph |
| lines | table | F flush_list |
| T boxed | | F flush_node |
| F register | | F free |
| F setup | | F getattr |
| F stage_one | | F getattribute |
| F stage_two | | F getbox |
| F stage_zero | | F getchar |
| D data | | F getfield |
| F finalize | | F getfont |
| F number | | F getid |
| N scratchbox | | F getleader |
| link | function | F getlist |
| linked | function | F getnext |
| list | function | F getprev |
| listablefields | data table | F getprop |
| listcodes | data table | F getskip |
| listtoutf | function | F getsubtype |
| load | function | F has_attribute |
| locate | function | F has_field |
| margincodes | data table | F has_glyph |

data table function function data table data table

function table

table

F hpack F rightskip F insert_after F rule F insert_before F shrink F special F insert list after F is direct F stretch F is display math F temp F is_node F textdir F is nut F usage T userids F kerning F last node N margins.inline F leftmarginwidth N property F ligaturing N splitters.one F link N splitters.two F userlist F linked F usernumber F locate F mlist_to_hlist F userstring F nestedtracedslide F usertokens F new F vlist T pool F zeroglue F baselineskip F prepend F cleanup F protect_glyphs F disc F protrusion_skippable F fontkern F reference F glue F remove F gluespec F repackhlist F glyph F replace F hlist F rightmarginwidth F set_attribute F kern F latelua F setattr F lateluafunction F setattribute F leftmarginkern F setattributes F leftskip F setbox F lineskip F setfield F noad F setprop F pdfannotation F setunsetattributes F pdfdestination F slide F pdfdirect F somepenalty F pdfliteral F somespace F pdfrestore F tail F pdfsave F takebox F pdfsetmatrix F tonode F penalty F tonodes F register F tonut F rightmarginkern F tostring

| F tracedslide | | F baselineskip | |
|--|-------------------|--|----------------------------------|
| F traverse | | F cleanup | |
| F traverse_id | | F glyph | |
| T typesetters | | F kern | |
| F fast_hpack | | F latelua | |
| F hpack | | F lateluafunction | |
| F tohpack | | F lineskip | |
| F tohpackfast | | F pdfliteral | |
| F tonodes | | F pdfsetmatrix | |
| F tovpack | | F register | |
| F tovpackfast | | F rule | |
| F vpack | | F special | |
| F unprotect_glyphs | | F usage | |
| F unset_attribute | | T userids | |
| F unsetattribute | | N margins.inline | |
| F unsetattributes | | N property | |
| F untracedslide | | N splitters.one | |
| F usedlist | | N splitters.two | |
| F vianodes | | F usernumber | |
| F vianuts | | prepend | function |
| F vpack | | print | function |
| F writable_spec | | processors | table |
| F write | | B enabled | |
| packlist | function | F hpack_filter | |
| pardir_is_equal | data table | F post_linebreak_filter | |
| <pre>pardir_is_opposite</pre> | data table | F pre_linebreak_filter | |
| pardir_is_parallel | data table | F tracer | |
| partextdir_is_equal | data table | processwords | function |
| penaltycodes | data table | properties | table |
| plugindata | table | T actions | |
| F finalizer | | F delayed | |
| F initializer | | F fdelayed | |
| S name | | F immediate | |
| T namespace | | F attach | |
| N attribute | | T data | |
| D data | | F delayed | |
| F enable | | | |
| | | protect_glyphs | function |
| F handler | | protect_glyphs protrusion_skippable | function |
| F handler F register | | protrusion_skippable pts | function function |
| F register D registered | | protrusion_skippable pts reference | function function function |
| F register D registered D values | | protrusion_skippable pts reference references | function function |
| F register D registered D values F processor | | <pre>protrusion_skippable pts reference references N attribute</pre> | function function function |
| F register D registered D values | function table | protrusion_skippable pts reference references | function function function |

| T stack | | tail | function |
|--------------------|------------|---------------------|------------|
| remove | function | takebox | function |
| repackhlist | function | tasks | table |
| replace | function | F actions | |
| report | function | F appendaction | |
| rightmarginwidth | function | F disableaction | |
| rules | table | F disablegroup | |
| D data | | F enableaction | |
| F define | | F enablegroup | |
| F enable | | F freeze | |
| F handler | | F freezegroup | |
| save | function | F new | |
| serialize | function | F prependaction | |
| serializebox | function | F removeaction | |
| set_attribute | function | F restart | |
| setattr | function | F setaction | |
| setattribute | function | F showactions | |
| setattributes | function | F table | |
| setbox | function | textdir_is_equal | data table |
| setfield | function | textdir_is_is | data table |
| setunsetattributes | function | textdir_is_opposite | data table |
| shifts | table | textdir_is_parallel | data table |
| D data | | tobasepoints | function |
| F define | | tocentimeters | function |
| F enable | | tociceros | function |
| F handler | | todidots | function |
| show | function | todimen | function |
| showboxes | function | toinches | function |
| showcodes | function | tomillimeters | function |
| showlist | function | tonewciceros | function |
| showsimplelist | function | tonewdidots | function |
| skipcodes | data table | tonode | function |
| slide | function | tonodes | function |
| snapshots | table | tonut | function |
| F getparameters | | topicas | function |
| F getsamples | | topoints | function |
| F resetsamples | | toscaledpoints | function |
| F takesample | | tosequence | function |
| somepenalty | function | tostring | function |
| somespace | function | totable | function |
| stripping | table | totree | function |
| T glyphs | | toutf | function |
| F set | | tracers | table |
| striprange | function | T characters | |

F collect F hpack F equal F tohpack F indices F tohpackfast F start F tonodes F string F tovpack F unicodes F tovpackfast T colors F vpack function F reset unprotect glyphs F set unset attribute function F setlist unsetattribute function unsetattributes function F fontchar usedlist function T frequencies vianodes function F register T pool vianuts function visualizebox function T nodes visualizers F rule table T nuts F box F rule F handler F resetproperties F markfonts F setfont F rule F setlist F setlaver F setproperties F setvisual function F start vpack data table T steppers whatcodes whatsitcodes data table F check writable spec function F codes write function F features F font F glyphs F message F messages F nofsteps F register F reset F start F stop F stop T transparencies F reset F set F setlist function traverse function traverse id typesetters table

number (context)

function basepoints function bit function bits function clearbit function dimenfactors data table formatted function hasbit function maxdimen number function nopts percent function points function pts function function setbit signed function sparseexponent function **splitdimen** function tobasepoints function tobitstring function tocentimeters function tociceros function todidots function todimen function toevenhex function toinches function **tomillimeters** function tonewciceros function tonewdidots function tonumberf function tonumberg function topicas function topoints function toscaled function toscaledpoints function function toset valid function

os (basic lua)

| getenv | function | |
|--------------|------------|----------|
| setenv | function | |
| binsuffix | string | |
| binsuffixes | table | |
| clock | function | |
| converttime | function | |
| date | function | |
| difftime | function | |
| env | data table | |
| exec | overloaded | function |
| execute | overloaded | function |
| exit | function | |
| fulltime | function | |
| getenv | overloaded | function |
| gettimeofday | function | |
| isleapyear | function | |
| launch | function | |
| libsuffix | string | |
| localtime | function | |
| name | string | |
| nofdays | function | |
| now | function | |
| platform | string | |
| remove | function | |
| rename | function | |
| resolvers | table | |
| F bits | | |
| resultof | function | |
| runtime | function | |
| selfdir | string | |
| setenv | overloaded | |
| setlocale | overloaded | function |
| sleep | function | |
| spawn | overloaded | tunction |
| time | function | |
| times | function | |
| timezone | function | |
| tmpdir | function | |
| tmpname | function | |
| today | function | |

string

type

uname function
uuid function
validdate function
weekday function
where function
which function

package (basic lua)

| config | string |
|---------------|----------|
| cpath | string |
| extralibpath | function |
| extralibpaths | function |
| extraluapath | function |
| extraluapaths | function |
| helpers | table |
| libpaths | function |
| loaded | table |
| loaders | table |
| loadlib | function |
| luapaths | function |
| path | string |
| preload | table |
| searchpath | function |
| seeall | function |

pagebuilders (context)

injections table

- F flushafter
- F flushbefore
- F save

mixedcolumns table

- F cleanup
- F finalize
- F getlist
- F getrest
- F getsplit
- F setsplit

pdf (basic tex)

| gethpos | function |
|-----------------|----------|
| getmatrix | function |
| getpos | function |
| getvpos | function |
| hasmatrix | function |
| immediateobj | function |
| mapfile | function |
| mapline | function |
| maxobjnum | function |
| obj | function |
| objtype | function |
| pageattributes | string |
| pageref | function |
| pageresources | string |
| pagesattributes | string |
| pdfmapfile | function |
| pdfmapline | function |
| print | function |
| refobj | function |
| registerannot | function |
| reserveobj | function |
| | |

pdfscanner (context)

scan function

physics (context)

units table
 D tables

profiler (extra lua)

```
pause function
resume function
start function
stop function
```

publications (context)

| addtexentry | function | F setmethod | |
|---------------------|------------|------------------|----------|
| analyze | function | T sorters | |
| authors | table | F author | |
| F concat | | F dataset | |
| F inverted | | F reference | |
| F invertedshort | | F short | |
| F normal | | listvariants | table |
| F normalshort | | F default | |
| F preparedsort | | F num | |
| F setsettings | | F short | |
| F short | | load | function |
| F sorted | | loadbibdata | function |
| F splitstring | | loaders | table |
| citeconcat | function | F bib | |
| citevariants | table | F endnote | |
| F author | | F lua | |
| F authornum | | F refman | |
| F authoryear | | F xml | |
| F authoryears | | markasupdated | function |
| F default | | new | function |
| F num | | refman_to_btx | function |
| F page | | singularorplural | function |
| F serial | | statistics | table |
| F short | | N nofbytes | |
| collected | data table | N nofdatasets | |
| converttoxml | function | N nofdefinitions | |
| datasets | table | N nofshortcuts | |
| endnotes_to_btx | function | tracers | table |
| enhance | function | T categories | |
| getindex | function | T article | |
| listconcat | function | T optional | |
| lists | table | T required | |
| F collectentries | | T book | |
| F doifalreadyplaced | i | T optional | |
| F fetchentries | | T required | |
| F filterall | | T booklet | |
| F flushentries | | T optional | |
| F nofregistered | | T required | |
| F register | | T inbook | |
| F registerplaced | | T optional | |
| F resolve | | T required | |
| | | | |

T incollection T optional

T required

T inproceedings

T optional

T required

T manual

T optional

T required

T mastersthesis

T optional

T required

T misc

T optional

T required

T phdthesis

T optional

T required

T proceedings

T optional

T required

T techreport

T optional

T required

T unpublished

T optional

T required

T citevariants

T fields

T listvariants

F showdatasetcompleteness

F showdatasetfields

regimes (context)

```
cleanup function
disable function
enable function
pop function
process function
push function
toregime function
translate function
```

resolvers (context)

finders

| allprefixes | function | findfile |
|--|--|---|
| appendhash | function | findfiles |
| automount | function | findgivenfile |
| automounted | table | findgivenfiles |
| booleanvariable | function | findpath |
| cacheversion | string | findtexfile |
| checkedvariable | function | findwildcardfile |
| cleanpath | function | findwildcardfiles |
| cleanpathlist | function | formatofsuffix |
| concatinators | data table | formatofvariable |
| configbanner | string | formats |
| criticalvars | data table | generators |
| dangerous | data table | getenv |
| datastate | function | getownpath |
| defaultsuffixes | table | getreadfilename |
| dowithfilesandreport | function | hashers |
| dowithfilesintree | function | homedir |
| dowithpath | function | inputstack |
| dowithvariable | function | installinputfilehandler |
| env | function | installinputlinehandler |
| | | |
| executers | table | instance |
| executers F check | table | · |
| | table | instance |
| F check | table | <pre>instance D data</pre> |
| F check F exec | table | <pre>instance D data B diskcache</pre> |
| F check F exec F execute | table | <pre>instance D data B diskcache D environment</pre> |
| F check F exec F execute F finalize | table | instance D data B diskcache D environment D expansions |
| F check F exec F execute F finalize F popen | table | instance D data B diskcache D environment D expansions D fakepaths |
| F check F exec F execute F finalize F popen F register | function | instance D data B diskcache D environment D expansions D fakepaths D files |
| F check F exec F execute F finalize F popen F register F spawn | | instance D data B diskcache D environment D expansions D fakepaths D files B force_suffixes |
| F check F exec F execute F finalize F popen F register F spawn expandbraces expandedpathfromlist expandedpathlist | function function function | instance D data B diskcache D environment D expansions D fakepaths D files B force_suffixes D found |
| F check F exec F execute F finalize F popen F register F spawn expandbraces expandedpathfromlist | function function function | instance D data B diskcache D environment D expansions D fakepaths D files B force_suffixes D found D foundintrees |
| F check F exec F execute F finalize F popen F register F spawn expandbraces expandedpathfromlist expandedpathlist expandedpathlistfromvariable expandpath | function function function function function | instance D data B diskcache D environment D expansions D fakepaths D files B force_suffixes D found D foundintrees D hashed |
| F check F exec F execute F finalize F popen F register F spawn expandbraces expandedpathfromlist expandedpathlist expandedpathlistfromvariable | function function function function | instance D data B diskcache D environment D expansions D fakepaths D files B force_suffixes D found D foundintrees D hashed D hashes |
| F check F exec F execute F finalize F popen F register F spawn expandbraces expandedpathfromlist expandedpathlist expandedpathlist expandpath expandpath expandpathfromvariable expandpathfromvariable expansion | function function function function function | instance D data B diskcache D environment D expansions D fakepaths D files B force_suffixes D found D foundintrees D hashed D hashes D lists |
| F check F exec F execute F finalize F popen F register F spawn expandbraces expandedpathfromlist expandedpathlist expandedpathlist expandpath | function function function function function function function function | instance D data B diskcache D environment D expansions D fakepaths D files B force_suffixes D found D foundintrees D hashed D hashes D lists B loaderror |
| F check F exec F execute F finalize F popen F register F spawn expandbraces expandedpathfromlist expandedpathlist expandedpathlistfromvariable expandpath expandpath expandpath expandpathfromvariable expansion extendtexmfvariable find_file | function function function function function function function function function | instance D data B diskcache D environment D expansions D fakepaths D files B force_suffixes D found D foundintrees D hashed D hashes D lists B loaderror D order |
| F check F exec F execute F finalize F popen F register F spawn expandbraces expandedpathfromlist expandedpathlist expandedpathlistfromvariable expandpath expandpath expandpathfromvariable expansion extendtexmfvariable find_file find_files | function function function function function function function function function function | instance D data B diskcache D environment D expansions D fakepaths D files B force_suffixes D found D foundintrees D hashed D hashes D lists B loaderror D order B remember |
| F check F exec F execute F finalize F popen F register F spawn expandbraces expandedpathfromlist expandedpathlist expandedpathlistfromvariable expandpath expandpath expandpath expandpathfromvariable expansion extendtexmfvariable find_file | function function function function function function function function function | Instance D data B diskcache D environment D expansions D fakepaths D files B force_suffixes D found D foundintrees D hashed D hashes D lists B loaderror D order B remember B renewcache |

D specification

data table

| D variables | | registerintrees | function |
|----------------------|------------|------------------------|------------|
| jobs | table | registermethod | function |
| F currentcomponent | | registerzipfile | function |
| F currentenvironment | | relations | data table |
| F currentproduct | | renew | function |
| F currentproject | | repath | function |
| F justacomponent | | reset | function |
| D processors | | resetextrapath | function |
| F productcomponent | | resetresolve | function |
| F usefile | | resolve | function |
| joinpath | function | savers | data table |
| load | function | scandata | function |
| loadbinfile | function | scanfiles | function |
| loaders | data table | schemes | table |
| loadlualib | function | T cleaners | |
| loadtexfile | function | F md5 | |
| loadtime | function | F none | |
| locateformat | function | F strip | |
| locators | data table | F cleanname | |
| luacnfname | string | F fetchstring | |
| luacnfspec | string | F fetchtable | |
| luacnfstate | string | F install | |
| macros | table | setenv | function |
| F convertfile | | setinstance | function |
| F decodecomment | | showpath | function |
| F enablecomment | | simplescanfiles | function |
| F encodecomment | | splitconfigurationpath | function |
| F preprocessed | | splitexpansions | function |
| F processmk | | splitmethod | function |
| F processmkvi | | splitpath | function |
| F version | | suffixes | data table |
| maxreadlevel | number | suffixmap | data table |
| methodhandler | function | suffixofformat | function |
| newinstance | function | texdatablob | function |
| openbinfile | function | toppath | function |
| openers | data table | unexpandedpath | function |
| openfile | function | unexpandedpathlist | function |
| opentexfile | function | unresolve | function |
| ownpath | string | updaterelations | function |
| prefixes | data table | updatescript | function |
| prependhash | function | usezipfile | function |
| registerextrapath | function | validatedpath | function |
| registerfile | function | variable | function |
| registerfilehash | function | variableofformat | function |

variableofformatorsuffix function wildcardpattern

function

scripts (context)

table

autofontfeature

```
F disable
   F enable
   F handler
categorytonumber data table
colors
                    data table
decomposehangul
                    function
defaults
                    table
   N inter_char_half_shrink_factor
   N inter_char_half_stretch_factor
   N inter_char_hangul_penalty
   N inter_char_quarter_shrink_factor
   N inter char quarter stretch factor
   N inter char shrink factor
   N inter_char_stretch_factor
   N inter_word_stretch_factor
handlers
                    data table
hash
                    table
injectors
                    data table
installdataset
                    function
installmethod
                    function
numbertocategory data table
numbertodataset
                    data table
numbertohandler
                    data table
reset
                    function
set
                    function
splitters
                    data table
```

set (context)

contains function
create function
tolist function
tonumber function
totable function

socket (extra lua)

BLOCKSIZE number S connection DEBUG boolean S content-description SETSIZE number S content-disposition bind function S content-encoding choose function S content-id function connect S content-language connect4 function S content-length connect6 function S content-location dns table S content-md5 F getaddrinfo S content-range F gethostname S content-transfer-encoding F getnameinfo S content-type F tohostname S date F toip S diagnostic-code ftp table S dsn-gateway S PASSWORD S etag N PORT S expect N TIMEOUT S expires S USER S final-log-id F command S final-recipient F get S from S host F open S if-match F put gettime function S if-modified-since headers table S if-none-match S if-range T canonic S accept S if-unmodified-since S accept-charset S in-reply-to S accept-encoding S keywords S accept-language S last-attempt-date S last-modified S accept-ranges S action S location S age S max-forwards S allow S message-id S alternate-recipient S mime-version S original-envelope-id S arrival-date S authorization S original-recipient S bcc S pragma S cache-control S proxy-authenticate S cc S proxy-authorization S comments S range

| S recei | ived | sinkt | table | |
|-------------|-----------------------------|----------------|----------------------|--|
| S recei | ived-from-mta | F close-v | vhen-done | |
| S refe | rences | F default | F default | |
| S refe | rer | F http-ch | nunked | |
| S remot | te-mta | F keep-op | oen | |
| S reply | y-to | skip | function | |
| S repor | rting-mta | sleep | function | |
| S reser | nt-bcc | smtp | table | |
| S reser | nt-cc | S DOMAIN | | |
| S reser | nt-date | N PORT | | |
| S reser | nt-from | S SERVER | | |
| S reser | nt-message-id | N TIMEOUT | Г | |
| S reser | nt-reply-to | S ZONE | | |
| S reser | nt-sender | F message | 2 | |
| S reser | nt-to | F open | | |
| S retry | y-after | F send | | |
| S retu | | source | function | |
| S sende | | sourcet | table | |
| S serve | | F by-leng | | |
| | -remote-recipient | F default | | |
| S status | | F http-chunked | | |
| S subj€ | ect | F until-closed | | |
| S te | | tcp | function | |
| S to | | tcp6 | function | |
| S trail | | tp | table | |
| | sfer-encoding | N TIMEOUT | | |
| S upgra | | F connect | | |
| S user- | -agent | try | function | |
| S vary | | udp udp6 | function function | |
| S via | · | url | table | |
| S warni | | F absolut | | |
| | retry-until authenticate | F build | .e | |
| S x-mai | | F build p | nath | |
| http | table | F escape | , a cii | |
| N PORT | cab to | F parse | | |
| N TIMEOU | Т | F parse_p | nath | |
| S USERAGENT | | F unescap | | |
| F open | | | | |
| F reques | t | | | |
| newtry | function | | | |
| protect | function | | | |
| select | function | | | |
| sink | function | | | |
| | | | | |

sorters (context)

basicsorter function
comparers table

F basic

constants table

S defaultdigits

S defaultlanguage

S defaultmethod

N digitsmaximum

N digitsoffset

N ignoredoffset

N replacementoffset

definitions
firstofsplit
setlanguage
sort
splitters
function
function
splitters
table

Futf

strip function
tracers data table
update function

statistics (context)

| checkfmtstatus | function |
|----------------|----------|
| elapsed | function |
| elapsedindeed | function |
| elapsedseconds | function |
| elapsedtime | function |
| enable | boolean |
| formatruntime | function |
| hastiming | function |
| memused | function |
| register | function |
| resettiming | function |
| runtime | function |
| savefmtstatus | function |
| show | function |
| starttiming | function |
| stoptiming | function |
| threshold | number |
| timed | function |
| tracefunction | function |
| | |

status (basic tex)

list function

storage (context)

allocate function data table mark function marked function number max min number **nofmodules** number noftables number register function shared data table strip boolean tofmodules number toftables number

streams (context)

| collect | function |
|-------------|----------|
| disable | function |
| enable | function |
| flush | function |
| initialize | function |
| push | function |
| start | function |
| stop | function |
| synchronize | function |

string (basic lua)

| autodouble | $ \hbox{function} $ |
|----------------|---------------------|
| autosingle | function |
| booleanstring | $ \hbox{function} $ |
| byte | function |
| bytepairs | $ \hbox{function} $ |
| bytes | $ \hbox{function} $ |
| char | $ \hbox{function} $ |
| characterpairs | $ \hbox{function} $ |
| characters | function |
| checkedsplit | $ \hbox{function} $ |
| collapsespaces | $ \hbox{function} $ |
| count | $ \hbox{function} $ |
| dump | $ \hbox{function} $ |
| escapedpattern | $ \hbox{function} $ |
| explode | $ \hbox{function} $ |
| find | $ \hbox{function} $ |
| format | $ \hbox{function} $ |
| formatter | $ \hbox{function} $ |
| formatters | $ \hbox{function} $ |
| fullstrip | $ \hbox{function} $ |
| gmatch | $ \hbox{function} $ |
| gsub | $ \hbox{function} $ |
| is_boolean | $ \hbox{function} $ |
| is_empty | $ \hbox{function} $ |
| itself | function |
| len | $ \hbox{function} $ |
| limit | function |
| longtostring | function |
| lower | function |
| match | function |
| nspaces | table |
| quote | function |
| quoted | function |
| rep | function |
| reverse | function |
| split | function |
| splitlines | function |
| splitup | function |
| strip | function |
| sub | function |
| tformat | $ \hbox{function} $ |

| toboolean | function |
|---------------|----------|
| tocontext | function |
| todimen | function |
| tonodes | function |
| topattern | function |
| totable | function |
| toutf | function |
| tracedchar | function |
| tracedchars | table |
| unquote | function |
| unquoted | function |
| upper | function |
| utfcharacters | function |
| utfvalues | function |
| valid | function |

structures (context)

| atlocation | function | F setlevel | |
|----------------|----------|----------------------|----------|
| blocks | table | F setoffset | |
| D collected | | F setown | |
| F define | | F setstate | |
| F print | | F setvalue | |
| F save | | T specials | |
| F select | | F userpage | |
| F setstate | | F subs | |
| D states | | D tobesaved | |
| D tobesaved | | F value | |
| bookmarks | table | currentsectionnumber | function |
| F finalize | | descriptions | table |
| F flatten | | documents | table |
| S method | | D data | |
| F overload | | F initialize | |
| F place | | F preset | |
| F register | | F reset | |
| F setup | | floats | table |
| counters | table | formulas | table |
| F add | | F current | |
| F analyze | | F simplify | |
| F check | | F store | |
| D collected | | helpers | table |
| F compact | | F analyze | |
| F converted | | F formulanumber | |
| F currentvalue | | F merged | |
| D data | | F page | |
| F define | | F prefix | |
| F first | | F prefixlastpage | |
| F get | | F prefixpage | |
| F last | | F simplify | |
| F next | | F title | |
| F prev | | F touserdata | |
| F previous | | inserts | table |
| F raw | | D data | |
| F record | | F define | |
| F reset | | F getdata | |
| F restart | | F getlocation | |
| F restore | | F getname | |
| F save | | F getnumber | |
| F set | | F setlocation | |

| F setup | | F uservalue | |
|-------------------|-------|-------------------------|-------|
| D stored | | marks | table |
| itemgroups | table | D data | |
| F maxwidth | | F define | |
| F nofitems | | F exists | |
| F register | | F fetch | |
| lists | table | F fetchallmarks | |
| F addto | | F fetched | |
| F analyze | | F fetchonemark | |
| B autoreorder | | F fetchtwomarks | |
| D cached | | F get | |
| D collected | | F number | |
| F discard | | F relate | |
| F enhance | | F reset | |
| T enhancers | | F set | |
| F filter | | F show | |
| F filtercollected | | F synchronize | |
| F formulanumber | | F title | |
| F groupindex | | T tracers | |
| F hasnumberdata | | F showtable | |
| F haspagedata | | notes | table |
| F hastitledata | | F checkpagechange | |
| F iscached | | F define | |
| F label | | F doifonsamepageasprevi | ous |
| F location | | F get | |
| F number | | F getdeltapage | |
| D ordered | | F getn | |
| F page | | F getnumberpage | |
| F popnesting | | F getstate | |
| F prefix | | F getsymbolpage | |
| F prefixednumber | | F hascontent | |
| F prefixedpage | | F internal | |
| F process | | F internalid | |
| D pushed | | F listindex | |
| F pushnesting | | F ordered | |
| F realpage | | F postpone | |
| F reordered | | F resetpostponed | |
| T result | | F restore | |
| D sectionblocks | | F save | |
| F sectionnumber | | F setstate | |
| F size | | F setsymbolpage | |
| F title | | D states | |
| D tobesaved | | F store | |
| F userdata | | pages | table |

F analyze F import D collected F inject F is odd F injectcurrentset N nofpages S innermethod F number D internals F save F load D tobesaved F loadpresets references table F mark F analyze D pages F checkedfile U prefixsplitter F checkedfileorurl D productdata F checkedprogram T programs F checkedrealpage T data F define F checkedurl D collected F get U componentsplitter F realpageofpage F currentmetadata U referencesplitter F currentorder D referred D currentset F referredpage F define F registerfinalizer D defined F registerinitializer D derived F registerpage F enableinteraction F reportproblems F enhance F reset D executers D runners F set F expandcurrent F setandgetattribute F export T files F setcomponent T data F setinnermethod F define F setinternalreference F get F setnextinternal F filter F setnextorder F filterdefault D specials D filters F splitcomponent F splitprefix D flaginternals F splitreference F from T testrunners F get Finner F getcurrentmetadata F getcurrentprefixspec F special F getinnermethod F special operation F getinternallistreference F special operation with arguments F getinternalreference T testspecials D handlers F deltapage F identify Fί

| F internal | | F findnumber |
|-------------------|----------|---------------------|
| F page | | F fullnumber |
| F realpage | | F getcurrentlevel |
| F section | | F getlevel |
| F userpage | | F getnumber |
| D tobereferred | | F internalreference |
| D tobesaved | | D levelmap |
| T urls | | D levels |
| T data | | F load |
| F define | | F matchingtilldepth |
| F get | | F numberatdepth |
| D usedinternals | | F numbers |
| D usedviews | | F popblock |
| F valid | | F prefixedconverted |
| F whatfrom | | F pushblock |
| registers | table | F register |
| F analyze | | D registered |
| D collected | | F reportstructure |
| F compare | | F save |
| F define | | T sectionblockdata |
| F enhance | | T bodypart |
| F extend | | S bookmark |
| F filter | | F set |
| F filtercollected | | F setblock |
| F finalize | | F setchecker |
| F flush | | F setentry |
| F prepare | | F setlevel |
| F process | | F setnumber |
| F setmethod | | F structuredata |
| F sort | | F title |
| F store | | D tobesaved |
| D tobesaved | | F typesetnumber |
| F unique | | F userdata |
| F userdata | | B verbose |
| sections | table se | ts table |
| F autodepth | | F define |
| F cct | | F get |
| D collected | | F getall |
| F current | | D setlist |
| F currentblock | sp | ecials table |
| F currentid | | D collected |
| F currentlevel | | F retrieve |
| F depthnumber | | F store |
| | | |

D tobesaved

F finddata

table synonyms D taglist F analyzed T userdata D collected F compare F define F filter F finalize F flush F meaning F prepare F process F register F registerused F sort F synonym D tobesaved table tags T data F detailedtag F getid F handler D labels F last F lastinchain T metadata D properties F registerdata F registermetadata F restart F setattributehash F setcombination F setdescription F setdescriptionsymbol F setfigure F sethighlight F setitemgroup F setproperty F setsorting F setsynonym F settablecell F settabulatecell F start

F stop

table (basic lua)

| allkeys | function |
|-----------------|---------------------|
| append | function |
| are_equal | $ \hbox{function} $ |
| autokey | function |
| compact | $ \hbox{function} $ |
| concat | $ \hbox{function} $ |
| contains | function |
| сору | function |
| count | function |
| derive | function |
| deserialize | function |
| drop | function |
| fastcopy | $ \hbox{function} $ |
| fastserialize | function |
| flattened | $ \hbox{function} $ |
| foreach | function |
| foreachi | $ \hbox{function} $ |
| fromhash | function |
| getmetatablekey | $ \hbox{function} $ |
| getn | function |
| has_one_entry | function |
| identical | $ \hbox{function} $ |
| imerge | function |
| imerged | function |
| insert | function |
| is_empty | function |
| keys | function |
| load | function |
| loweredkeys | function |
| maxn | function |
| merge | function |
| merged | function |
| mirrored | function |
| pack | function |
| prepend | function |
| print | function |
| remove | function |
| reverse | function |
| reversed | function |
| save | function |
| sequenced | function |

| serialize | function |
|----------------------|----------|
| setmetatablecall | function |
| setmetatableindex | function |
| setmetatablekey | function |
| setmetatablenewindex | function |
| sort | function |
| sorted | function |
| sortedhash | function |
| sortedhashkeys | function |
| sortedhashonly | function |
| sortedindexonly | function |
| sortedkeys | function |
| sortedpairs | function |
| strip | function |
| sub | function |
| swapped | function |
| tocontext | function |
| tocsv | function |
| tofile | function |
| tohandle | function |
| tohash | function |
| toxml | function |
| twowaymapper | function |
| unique | function |
| unnest | function |
| unpack | function |
| values | function |

tex (basic tex)

| attribute | table | isdefined | data table |
|------------------|------------|---------------------|------------|
| badness | function | isdimen | function |
| box | table | isskip | function |
| catcode | table | istoken | function |
| conditionals | data table | lccode | table |
| constants | data table | linebreak | function |
| count | table | lists | table |
| ctdcatcodes | number | lua math random | function |
| ctxcatcodes | number | lua_math_randomseed | function |
| definefont | function | luacatcodes | number |
| delcode | table | mathcode | table |
| dimen | table | modes | data table |
| directives | data table | nest | table |
| enableprimitives | function | nilcatcodes | number |
| error | function | normal_rand | function |
| extraprimitives | function | notcatcodes | number |
| finish | function | number | function |
| fontidentifier | function | pdffontname | function |
| fontname | function | pdffontobjnum | function |
| fprint | function | pdffontsize | function |
| get | function | pdfpageref | function |
| getattribute | function | pdfxformname | function |
| getbox | function | primitives | function |
| getcatcode | function | print | function |
| getcount | function | printlist | function |
| getdelcode | function | prtcatcodes | number |
| getdimen | function | romannumeral | function |
| getlccode | function | round | function |
| getlist | function | run | function |
| getmath | function | scale | function |
| getmathcode | function | set | function |
| getnest | function | setattribute | function |
| getsfcode | function | setbox | function |
| getskip | function | setcatcode | function |
| gettoks | function | setcount | function |
| getuccode | function | setdelcode | function |
| hashtokens | function | setdimen | function |
| ifs | data table | setlccode | function |
| inicatcodes | number | setlist | function |
| init_rand | function | setmath | function |
| iscount | function | setmathcode | function |

setnest function setsfcode function setskip function settoks function setuccode function sfcode table shipout function function show context skip table function sp sprint function systemmodes data table takebox function texcatcodes number toks table tpacatcodes number tpbcatcodes number function tprint trackers data table txtcatcodes number function type uccode table uniform rand function uniformdeviate function uprint function vrbcatcodes number write function

texconfig (basic tex)

error_line number expand depth number formatname string half_error_line number number hash extra init overloaded function kpse_init boolean max in open number max_print_line number max_strings number nest_size number param_size number save size number shell escape string stack size number

texio (basic tex)

write function
write_nl function

token (basic tex)

| command_id | function |
|---------------|----------|
| command_name | function |
| create | function |
| csname_id | function |
| csname_name | function |
| expand | function |
| get_next | function |
| is_activechar | function |
| is_expandable | function |
| is_protected | function |
| lookup | function |

tokens (context)

```
bgroup
              table
collectors table
   T data
   F defaultwords
   F dowithwords
   F flush
   F handle
   F install
   F register
   T registered
   T remapper
     F convert
    T data
     F store
   F show
   T show_methods
    Fa
    F b
    F c
   F showtoken
   F test
   F trace
egroup
              table
              table
hbox
letter
              function
              function
letters
other
              function
vbox
              table
```

table

vtop

tracers (context)

```
count function
cs function
dimen function
knownlist function
lists table
```

T context
T internals
T scratch

name function
primitive function
printerror function
showlines function
strings table

S undefined

toks function
type function

trackers (context)

data data table default function disable function dumphashtofile function function enable list function string name register function report function savehash function show function value function

typesetters (context)

| alignments | table | F installhandler | |
|----------------------------|-------|------------------|-------|
| F handler | | F processmath | |
| F set | | F set | |
| breakpoints | table | F setcolor | |
| F define | | F setmath | |
| F handler | | F tomode | |
| D mapping | | firstlines | table |
| T methods | | T actions | |
| T numbers | | F default | |
| F set | | F line | |
| F setreplacement | | F word | |
| cases | table | F handler | |
| T actions | | F set | |
| F handler | | initials | table |
| F register | | T actions | |
| F set | | F default | |
| characteralign | table | F handler | |
| F handler | | F set | |
| F resetcharacter | align | italics | table |
| F setcharacteral | ign | F forcevariant | |
| characters | table | F handler | |
| F handler | | F reset | |
| F replacenbsp | | F set | |
| F replacenbspace | S | kerns | table |
| checkers | table | D factors | |
| F handler | | F handler | |
| F reset | | F keepligature | |
| F set | | B keeptogether | |
| cleaners | table | D mapping | |
| F handler | | F set | |
| F set | | margins | table |
| digits | table | F finalhandler | |
| T actions | | F globalhandler | |
| F handler | | F ha | |
| F set | | F localhandler | |
| directions | table | F save | |
| | | processors | table |
| F getfences | | | |
| F getfences F getglobal | | F apply | |
| | | - | |
| F getglobal | | F apply | |

```
F startapply
F stopapply
F stripped
```

F tostring spacings

table

F define

F handler

D mapping

T numbers

T frenchpunctuation

T characters

S name

N number

F reset

F set

F setup

xtables

table

F cleanup

F construct

F create

F flush

F initialize_construct

F initialize_reflow_height

F initialize_reflow_width

F next_row

F reflow_height

F reflow_width

F set_construct

F set_reflow_height

F set_reflow_width

unicode (extra lua)

| ascii | table | F | len |
|--------------------------|-------|------|-------------------|
| F byte | | | lower |
| F char | | | match |
| F dump | | | rep |
| F find | | | reverse |
| F forma | t | F | sub |
| F gfind | | F | upper |
| F gmato | h | utf8 | table |
| F gsub | | F | byte |
| F len | | F | char |
| F lower | | F | characters |
| F match | | F | chrlen |
| F rep | | F | count |
| F rever | se | F | dump |
| F sub | | F | filetype |
| F upper | | F | find |
| grapheme | table | F | format |
| F byte | | F | gfind |
| F char | | F | gmatch |
| F dump | | F | gsub |
| F find | | F | is_valid |
| F forma | t | F | len |
| F gfind | | F | length |
| F gmatc | h | | lower |
| F gsub | | | magic |
| F len | | | match |
| F lower | | | remapper |
| F match | | | rep |
| F rep | | | replacer |
| F rever | se | | reverse |
| F sub | | | split |
| F upper latin1 | table | | splitlines sub |
| F byte | table | | subtituter |
| F char | | | tocodes |
| F dump | | | toeight |
| F find | | | toentities |
| F forma | + | | tostring |
| F gfind | | | totable |
| F gmato | | | upper |
| F gsub | | | ustring |
| 3, | | · | 3 |

- F utf16_to_utf8
- F utf16_to_utf8_be
- F utf16_to_utf8_le
- F utf32_to_utf8
- F utf32_to_utf8_be
- F utf32_to_utf8_le
- F utf8_to_utf16
- F utf8_to_utf16_be
- F utf8_to_utf16_le
- F utf8_to_utf8
- F values
- F xstring

url (context)

| addscheme | function |
|-------------|----------|
| barepath | function |
| construct | function |
| escape | function |
| filename | function |
| hashed | function |
| hasscheme | function |
| query | function |
| split | function |
| toquery | function |
| unescapeget | function |

utilities (context)

| debugger | table | N version | |
|--------------------|-------|-----------------|------------------|
| F disable | | parsers | table |
| F enable | | F add_settings_ | to_array |
| F savestats | | F arguments_to_ | table |
| F showstats | | F array_to_stri | ng |
| F showtraceback | | F csvsplitter | |
| formatters | table | F getparameters | |
| F formatcolumns | | F hash_to_strin | g |
| F list | | F iterator | |
| F stripzeros | | F keq_to_hash | |
| garbagecollector | table | F listitem | |
| F check | | F make_settings | _to_hash_pattern |
| N criterium | | F manipulated | |
| B enabled | | U manipulation | |
| lua | table | T manipulators | |
| B alwaysstripcode | | F lowercase | |
| F compile | | F stripperiod | |
| F loadedluacode | | F uppercase | |
| F loadstripped | | F mergehashes | |
| N nofstrippedbytes | ; | F options_to_ha | sh |
| N nofstrippedchunk | KS. | T patterns | |
| B stripcode | | U settings_to_ | _array |
| T strippedchunks | | U settings_to_ | _hash_a |
| F strippedloadstri | .ng | U settings_to_ | _hash_b |
| T suffixes | | U settings_to_ | _hash_c |
| S lua | | U unittotex | |
| S luc | | F process_strip | ped_settings |
| S lui | | F rfc4180splitt | er |
| S luj | | F runtime | |
| S luv | | F settings_to_a | rray |
| S tma | | F settings_to_a | rray_with_repeat |
| S tmc | | F settings_to_h | ash |
| S tua | | F settings_to_h | ash_strict |
| S tuc | | F settings_to_h | ash_tolerant |
| packers | table | F settings_to_s | et |
| F hashed | | F simple_hash_t | _ |
| F new | | F splitthousand | S |
| F pack | | F stepper | |
| F simplehashed | | F stripped_sett | ings_to_array |
| F strip | | F unittotex | |
| F unpack | | F unittoxml | |

| report | function | Т | striplinepatterns | |
|------------------------|----------|------|-------------------|-------|
| sequencers | table | | U prune | |
| F appendaction | | | U prune and colla | pse |
| F appendgroup | | | U prune and no em | pty |
| F compile | | | U retain | |
| F disableaction | | | U retain and coll | apse |
| F disablegroup | | | U retain and no e | mpty |
| F enableaction | | F | striplines | |
| F enablegroup | | F | striplong | |
| D functions | | F | tabtospace | |
| F localize | | | tracers | |
| F new | | tabl | es | table |
| F nodeprocessor | | | accesstable | |
| F prependaction | | | definedtable | |
| F prependgroup | | | definetable | |
| F removeaction | | | encapsulate | |
| F setkind | | | insertaftervalue | |
| F tostring | 4-11- | | insertbeforevalue | |
| setters | table | | migratetable | |
| F disable | | | removevalue | 4-bl- |
| F enable | | | lates | table |
| F initialize | | | load | |
| F list | | | replace | |
| F new | | | replacer | |
| F register F report | | г | resorve | |
| F reset | | | | |
| F show | | | | |
| stacker | table | | | |
| F new | | | | |
| storage | table | | | |
| F allocate | | | | |
| F checked | | | | |
| F mark | | | | |
| F marked | | | | |
| F setinitializer | | | | |
| F sparse | | | | |
| strings | table | | | |
| F collapsecrlf | | | | |
| T formatters | | | | |
| F add | | | | |
| F new | | | | |
| F newrepeater | | | | |
| F nice | | | | |
| | | | | |

vf (context)

```
char
        function
down
        function
fontid
        function
        function
image
        function
node
        function
nop
        function
pop
push
        function
right
        function
rule
        function
special function
```

visualizers (context)

| escapepatterns | data | table | |
|-----------------------|------------|-------|--|
| getvisualizer | funct | tion | |
| load | funct | tion | |
| makenested | funct | tion | |
| makepattern | funct | tion | |
| newgrammar | funct | tion | |
| newhandler | funct | tion | |
| parsedxml | funct | tion | |
| pattern | funct | tion | |
| register | function | | |
| registerescapecommand | funct | tion | |
| registerescapeline | function | | |
| registerescapepattern | function | | |
| signal | string | | |
| signalpattern | user | data | |
| specifications | data table | | |
| visualize | funct | tion | |
| visualizebuffer | funct | tion | |
| visualizefile | funct | tion | |
| visualizestring | funct | tion | |
| write | funct | tion | |
| writeargument | funct | tion | |
| writedefault | funct | tion | |
| writeemptyline | funct | tion | |
| writenewline | funct | tion | |
| writespace | funct | tion | |

xml (context)

| addentitiesdoctype | function | D tex | |
|----------------------|----------|---------------------------|------------|
| after | function | D texline | |
| all | function | | |
| applylpath | function | D texspace D verbose | |
| assign | function | defaultprotocol | string |
| assign attribute | function | delete | function |
| before | function | delete element | function |
| body | function | each | function |
| builtinentities | table | each_element | function |
| B amp | cable | elements | function |
| B apos | | elementtocdata | function |
| B gt | | empty | function |
| B lt | | empty | data table |
| B quot | | erase | function |
| cdata | function | errorhandler | function |
| cdatatotext | function | escaped | function |
| checkbom | function | expressions | table |
| checkerror | function | F boolean | tabte |
| checknamespace | function | F child | |
| checkns | function | F contains | |
| cleansed | function | F count | |
| collect | function | F error | |
| collect_elements | function | F find | |
| collect_tags | function | F lower | |
| collect texts | function | F name | |
| collected | function | F number | |
| collecttexts | function | F oneof | |
| content | function | F print | |
| convert | function | F quit | |
| сору | function | F tag | |
| count | function | F text | |
| cprint | function | F undefined | |
| css | table | F upper | |
| F colorspecification | | fillin | function |
| F dimension | | filter | function |
| F fontspecification | | finalizers | table |
| F padding | | F paragraphs | |
| defaulthandlers | table | T tex | |
| D file | | F all | |
| D parsedxml | | F attribute | |
| D string | | F chainattribute | |
| | | | |

| F | command | F table | |
|-----|----------------|----------------------------------|---------------------|
| F | concat | F tag | |
| F | concatrange | F tags | |
| F | context | F text | |
| F | count | F texts | |
| F | ctxtext | F upperall | |
| F | default | first | function |
| F | first | found | function |
| F | function | functions | table |
| F | index | getbuffer | function |
| F | last | gethandlers | function |
| F | lettered | gethandlersfunction | function |
| F | lower | helpers | table |
| F | lowerall | F recursetext | |
| F | match | include | function |
| F | name | index | function |
| F | position | inheritedconvert | function |
| F | reverse | inject | function |
| F | stripped | <pre>inject_element</pre> | function |
| F | tag | <pre>inject_element_after</pre> | function |
| F | tags | <pre>inject_element_before</pre> | function |
| F | text | injectafter | function |
| F | upper | injectbefore | function |
| F | upperall | insert | function |
| T > | kml | insert_element | function |
| F | all | <pre>insert_element_after</pre> | function |
| F | att | <pre>insert_element_before</pre> | function |
| F | attribute | insertafter | function |
| F | attributes | insertbefore | function |
| F | cdata | insertcomment | function |
| F | chainattribute | inspect | function |
| F | count | is_valid | function |
| F | default | kind | function |
| F | elements | last | function |
| F | empty | load | function |
| F | first | lpath | function |
| F | function | lpathcached | function |
| F | index | lpathcalls | function |
| F | last | lshow | function |
| F | lowerall | makestandalone | function |
| F | match | match | function |
| F | name | name | function |
| F | position | newhandlers | function |
| F | reverse | nodesettostring | function |
| | | | |

Т

originalload function
package function
parent function
parsedentitylpeg userdata
pihandlers table
placeholders table

F unknown_any_entity
F unknown_dec_entity
F unknown_hex_entity
position function

position function privatecodes table privatetoken function function process process attributes function. process elements function processattributes function profiled table raw function registerentity function registerns function remap name **function function** remap_namespace function remap tag remapname function function remapnamespace function remaptag function renamespace replace function replace element function resolvens function function root function save selection function separate function serialize function

function

function function

function

function

function

function

function

table

setcdata

sprint

string

strip

setproperty settings

specialhandler

strip whitespace

sethandlersfunction

stripelement function stripleadingspaces function table function function text textonly function texttocdata function tocdata function toelement function tostrina function toxml function function tprint function traverse function unescaped unprivatized function withelement function withelements function function wrap

table

xmlns

zip (extra lua)

archives table
close function
closearchive function
open function
openarchive function
openfile function
registeredfiles table
type function

zlib (extra lua)

adler32 function
compress function
crc32 function
decompress function
decompressobj function
version function