



# ConTeXt

přikazy

# CS



# ConTeXt

## příkazy

cs / český  
14. října 2017



\AfterPar {...} *   BEFEHL
\Alphabeticnumerals {...} *   NUMMER
\AMSTEX
\AmSTeX
\And
\abjadnaivenumerals {...} *   NUMMER
\abjadnodotnumerals {...} *   NUMMER
\abjadnumerals {...} *   NUMMER
\activatespacehandler {...} *   zap vyp ano fixne
\acute {...} *   CHARACTER
\adaptcollector [... <sup>1</sup> .] [... <sup>2</sup> ... <sub>OPT</sub> ...] 1   NAME 2   inherits: \setupcollector
\adaptfontfeature [... <sup>1</sup> .] [... <sup>2</sup> ... <sub>OPT</sub> ...] 1   NAME 2   inherits: \definefontfeature
\adaptpapersize [... <sup>1</sup> ,...] [... <sup>2</sup> ,... <sub>OPT</sub> ...] 1   inherits: \nastavvelikostpapiru 2   inherits: \nastavvelikostpapiru
\addfeature [...*] *   NAME
\addfeature {...} *   NAME
\addtocommalist {... <sup>1</sup> .} \... <sup>2</sup> .. 1   TEXT 2   CSNAME
\addtoJSreamble {... <sup>1</sup> .} {... <sup>2</sup> .} 1   NAME 2   CONTENT
\addvalue {... <sup>1</sup> .} {... <sup>2</sup> .} 1   NAME 2   TEXT

<p><code>\aftersplitstring ... \at ... \to ...</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 CSNAME</p>
<p><code>\aftertestandsplitstring ... \at ... \to ...</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 CSNAME</p>
<p><code>\aktualnicislonaadpisu</code></p>
<p><code>\aktualnidatum [...*,...]</code></p> <p>* rok mesic den vsednica y yy Y m mm M d dd D w W mezera \ month:mnem m:mnem d:ord day:ord dd:ord D:ord TEXT znacka day:+ day:++ d:+ d:++ dd:+ dd:++ D:+ D:++ month:jalali m:jalali jalali:to jalali:from</p>
<p><code>\alignbottom</code></p>
<p><code>\aligned [...<sup>1</sup>,...] {...<sup>2</sup>}</code></p> <p>1 vlevo nastred vpravo vrsek spodek radek l c r m t b g</p> <p>2 CONTENT</p>
<p><code>\alignedbox [...<sup>1</sup>,...] \...<sup>2</sup> {...<sup>3</sup>}</code></p> <p>1 vlevo nastred vpravo vrsek spodek radek l c r m t b g</p> <p>2 CSNAME</p> <p>3 CONTENT</p>
<p><code>\alignedline {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}</code></p> <p>1 vlevo vpravo nastred flushleft flushright center max uvnitr vnejsi innermargin outermargin inneredge outeredge zpetnamezera cutspace levyokraj prav yokraj levahrana pravahrana</p> <p>2 vlevo vpravo nastred flushleft flushright center max uvnitr vnejsi innermargin outermargin inneredge outeredge zpetnamezera cutspace levyokraj prav yokraj levahrana pravahrana</p> <p>3 CONTENT</p>
<p><code>\alignmentcharacter</code></p>
<p><code>\allinputpaths</code></p>
<p><code>\alphabeticnumerals {...<sup>*</sup>}</code></p> <p>* NUMMER</p>
<p><code>\alwayscitation [...<sup>1</sup>,...<sup>2</sup>,...] [...<sup>2</sup>]</code></p> <p>1 odkaz = REFERENCE<sup>PT</sup> alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear pred = BEFEHL po = BEFEHL vlevo = BEFEHL vpravo = BEFEHL inherits: \setupbtx</p> <p>2 REFERENCE</p>
<p><code>\alwayscitation [...<sup>1</sup>] [...<sup>2</sup>]</code></p> <p>1 implicitni category<sup>PT</sup> entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear</p> <p>2 REFERENCE</p>

`\alwayscitation [...1...2...]`

```
1 odkaz      = REFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
               authornum authoryear
  pred       = BEFEHL
  po         = BEFEHL
  vlevo      = BEFEHL
  vpravo     = BEFEHL
  inherits: \setupbtx
2 KEY = VALUE
```

`\alwayscite [...1...2...]`

```
1 odkaz      = REFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
               authornum authoryear
  pred       = BEFEHL
  po         = BEFEHL
  vlevo      = BEFEHL
  vpravo     = BEFEHL
  inherits: \setupbtx
2 REFERENCE
```

`\alwayscite [...1...]`

```
1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear
2 REFERENCE
```

`\alwayscite [...1...2...]`

```
1 odkaz      = REFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
               authornum authoryear
  pred       = BEFEHL
  po         = BEFEHL
  vlevo      = BEFEHL
  vpravo     = BEFEHL
  inherits: \setupbtx
2 KEY = VALUE
```

`\ampersand`

`\anchor [...1] [...2...3...]{...4}`

```
1 NAME      OPT
2 inherits: \setupplayer
3 inherits: \setupplayerinherits: \nastavoramovani
4 CONTENT
```

`\antikva`

`\appendetoks ...1 \to ...2`

```
1 BEFEHL
2 CSNAME
```

`\appendgvalue {...1}{...2}`

```
1 NAME
2 BEFEHL
```

`\appendtocommalist {...1}\...2`

```
1 TEXT
2 CSNAME
```

`\appendtoks ...1 \to ...2`

```
1 BEFEHL
2 CSNAME
```

`\appendtoksonce ...1 \to ...2`

```
1 BEFEHL
2 CSNAME
```

\appendvalue {...} {...} 1 NAME 2 BEFEHL
\apply {...} {...} 1 CONTENT 2 CONTENT
\applyalternativestyle {...} * NAME
\applyprocessor {...} {...} 1 NAME 2 CONTENT
\applytofirstcharacter \... {...} 1 CSNAME 2 TEXT
\applytocharacters \... {...} 1 CSNAME 2 TEXT
\applytosplitstringchar \... {...} 1 CSNAME 2 TEXT
\applytosplitstringcharspaced \... {...} 1 CSNAME 2 TEXT
\applytosplitstringline \... {...} 1 CSNAME 2 TEXT
\applytosplitstringlinespaced \... {...} 1 CSNAME 2 TEXT
\applytosplitstringword \... {...} 1 CSNAME 2 TEXT
\applytosplitstringwordspaced \... {...} 1 CSNAME 2 TEXT
\applytowords \... {...} 1 CSNAME 2 TEXT
\arabicdecimals {...} * NUMMER
\arabicexnumerals {...} * NUMMER
\arabicnumerals {...} * NUMMER



<code>\arg {...}</code> *    CONTENT
<code>\asciistr {...}</code> *    CONTENT
<code>\assignalfadimension {...} \^2... {...} {...} {...}</code> 1    male stredni velke zadny DIMENSION 2    CSNAME 3    DIMENSION 4    DIMENSION 5    DIMENSION
<code>\assigndimen \^1... {...}</code> 1    CSNAME 2    DIMENSION
<code>\assigndimension {...} \^2... {...} {...} {...}</code> 1    [-+]male [-+]stredni [-+]velke zadny DIMENSION 2    CSNAME 3    DIMENSION 4    DIMENSION 5    DIMENSION
<code>\assignifempty \^1... {...}</code> 1    CSNAME 2    BEFEHL
<code>\assigntranslation [...,\^1...,\^2...]</code> 1    SPRACHE = TEXT 2    CSNAME
<code>\assignvalue {...} \^2... {...} {...} {...}</code> 1    male stredni velke TEXT 2    CSNAME 3    BEFEHL 4    BEFEHL 5    BEFEHL
<code>\assignwidth {...} \^2... {...} {...}</code> 1    prizpusobive siroky DIMENSION 2    CSNAME 3    TEXT 4    DIMENSION
<code>\assumelongusagecs \^1... {...}</code> 1    CSNAME 2    CONTENT
<code>\astype {...}</code> *    CONTENT
<code>\ATTACHMENT [\^1...][\^2...]</code> 1    NAME            OPT            OPT 2    inherits: \setupattachment instances: attachment
<code>\autocap {...}</code> *    TEXT
<code>\autodirhbox \^1... {...}</code> 1    TEXT            OPT 2    CONTENT

$\backslash\text{autodirvbox}$ $\overset{1}{\dots}$ $\{\overset{2}{\dots}\}$ 1 TEXT OPT 2 CONTENT
$\backslash\text{autodirvtop}$ $\overset{1}{\dots}$ $\{\overset{2}{\dots}\}$ 1 TEXT OPT 2 CONTENT
$\backslash\text{autoinsertnextspace}$
$\backslash\text{autointegral}$ $\{\overset{1}{\dots}\}$ $\{\overset{2}{\dots}\}$ $\{\overset{3}{\dots}\}$ 1 TEXT 2 TEXT 3 TEXT
$\backslash\text{automathematics}$ $\{.*\}$ * CONTENT
$\backslash\text{autosetups}$ $\{\dots,*\dots\}$ * NAME
$\backslash\text{autostarttext}$ $\dots$ $\backslash\text{autostoptext}$
$\backslash\text{availablehsize}$
$\backslash\text{averagecharwidth}$
$\backslash\text{BeforePar}$ $\{.*\}$ * BEFEHL
$\backslash\text{Big}$ $.*$ * CHARACTER
$\backslash\text{Bigg}$ $.*$ * CHARACTER
$\backslash\text{Biggl}$ $.*$ * CHARACTER
$\backslash\text{Biggm}$ $.*$ * CHARACTER
$\backslash\text{Biggr}$ $.*$ * CHARACTER
$\backslash\text{Bigl}$ $.*$ * CHARACTER
$\backslash\text{Bigm}$ $.*$ * CHARACTER
$\backslash\text{Bigr}$ $.*$ * CHARACTER

`\backgroundimage {...} {...} {...} {...}`

1 NUMMER  
2 DIMENSION  
3 DIMENSION  
4 BEFEHL

`\backgroundimagefill {...} {...} {...} {...}`

1 NUMMER  
2 DIMENSION  
3 DIMENSION  
4 BEFEHL

`\backgroundline [...] {...}`

1 COLOR  
2 CONTENT

`\bar {...}`

\* CHARACTER

`\barevnaLista [...,*,...]`

\* COLOR

`\barva [...] {...}`

1 COLOR  
2 CONTENT

`\BAR {...}`

\* CONTENT

instances: overbar underbar overstrike understrike overbars underbars overstrikes understrikes  
underrandom underrandoms underdash underdashes underdot underdots nobar hiddenbar

`\basegrid [...,*=,...]`

\* nx = NUMMER  
ny = NUMMER  
dx = NUMMER  
dy = NUMMER  
faktor = NUMMER  
meritko = NUMMER  
xkrok = NUMMER  
ykrok = NUMMER  
offset = DIMENSION  
xoffset = DIMENSION  
yoffset = DIMENSION  
zarovnani = nastred  
jednotka = cm mm in pc pt bp  
pismo = STYLE BEFEHL  
barva = COLOR

`\baselinebottom`

`\baselineleftbox {...}`

\* CONTENT

`\baselinemiddlebox {...}`

\* CONTENT

`\baselinerightbox {...}`

\* CONTENT

`\bbox {...}`

\* CONTENT

<code>\beforesplitstring <sup>1</sup>... \at <sup>2</sup>... \to <sup>3</sup>...</code> 1 TEXT 2 TEXT 3 CSNAME
<code>\beforetestandsplitstring <sup>1</sup>... \at <sup>2</sup>... \to <sup>3</sup>...</code> 1 TEXT 2 TEXT 3 CSNAME
<code>\beginBLOCK [...<sup>*</sup>,...] ... \endBLOCK</code> * + - NAME <sup>OPT</sup>
<code>\beginhbox ... \endhbox</code>
<code>\beginofshapebox ... \endofshapebox</code>
<code>\beginvbox ... \endvbox</code>
<code>\beginvtop ... \endvtop</code>
<code>\begstrut ... \endstrut</code>
<code>\bezserifu</code>
<code>\bigbodyfont</code>
<code>\bigg <sup>*</sup>...</code> * CHARACTER
<code>\bigger</code>
<code>\biggl <sup>*</sup>...</code> * CHARACTER
<code>\biggm <sup>*</sup>...</code> * CHARACTER
<code>\biggr <sup>*</sup>...</code> * CHARACTER
<code>\bigl <sup>*</sup>...</code> * CHARACTER
<code>\bigm <sup>*</sup>...</code> * CHARACTER
<code>\bigr <sup>*</sup>...</code> * CHARACTER
<code>\bigskip</code>

```
\bitmapimage [..,..1..,..] {..2..}
```

```
1  barva = rgb cmyk seda
   sirka = DIMENSION
   vyska = DIMENSION
   x      = NUMBER
   y      = NUMBER
2  NUMBER
```

`\blap {...}`

\* CONTENT

`\blead [...,\u=...,...] {\u.}`

```
1 inherits: \setupbleeding
2 CONTENT
```

\bleedheight

\bleedwidth

`\blockligatures [...,*,...]`

\* TEXT

\bodyfontenvironmentlist

`\bodyfontsize`

**\boldface**

```
\booleanmodevalue {...}
```

\* NAME

`\bottombox {.*}`

\* CONTENT

`\bottomleftbox {.*.}`

\* CONTENT

`\bottomrightbox {...}`

\* CONTENT

\boxcursor

$$\backslash\mathrm{boxmarker}\ \{.^1..\}\ \{.^2..\}$$

```

1  NAME
2  NUMMER

```

`\boxofsize` <sup>1</sup>... <sup>2</sup>... {<sup>3</sup>...}

```

1  CSNAME                                OPT
2  DIMENSION
3  CONTENT

```

$$\backslash\mathrm{boxreference}\ [\ldots,\ldots]^1\ \backslash\ldots^2\ \{\ldots\}^3$$

1	REFERENCE
2	CSNAME
3	CONTENT

`\bpar ... \epar`

<code>\bpos {...}</code> *    NAME
<code>\breve {...}</code> *    CHARACTER
<code>\bTABLE [...,...<sup>*</sup>...,...] ... \eTABLE</code> *    inherits: \setupTABLE
<code>\bTABLEbody [...,...<sup>*</sup>...,...] ... \eTABLEbody</code> *    inherits: \setupTABLE
<code>\bTABLEfoot [...,...<sup>*</sup>...,...] ... \eTABLEfoot</code> *    inherits: \setupTABLE
<code>\bTABLEhead [...,...<sup>*</sup>...,...] ... \eTABLEhead</code> *    inherits: \setupTABLE
<code>\bTABLEnext [...,...<sup>*</sup>...,...] ... \eTABLEnext</code> *    inherits: \setupTABLE
<code>\bTC [...,...<sup>*</sup>...,...] ... \eTC</code> *    inherits: \bTD
<code>\bTD [...,...<sup>*</sup>...,...] ... \eTD</code> *    nx    = NUMBER *    ny    = NUMBER *    nc    = NUMBER *    nr    = NUMBER *    n     = NUMBER *    m     = NUMBER *    akce = REFERENCE *    inherits: \setupTABLE
<code>\bTDs [...] ... \eTDs</code> *    NAME
<code>\bTH [...,...<sup>*</sup>...,...] ... \eTH</code> *    inherits: \bTD
<code>\bTN [...,...<sup>*</sup>...,...] ... \eTN</code> *    inherits: \bTD
<code>\bTR [...,...<sup>*</sup>...,...] ... \eTR</code> *    inherits: \setupTABLE
<code>\bTRs [...] ... \eTRs</code> *    NAME
<code>\bTX [...,...<sup>*</sup>...,...] ... \eTX</code> *    inherits: \bTD
<code>\bTY [...,...<sup>*</sup>...,...] ... \eTY</code> *    inherits: \setupTABLE
<code>\bthiddencitation [...]</code> *    REFERENCE

<pre> \btxabbreviatedjournal {...} *   NAME </pre>
<pre> \btxaddjournal [...<sup>1</sup>] [...<sup>2</sup>] 1   NAME 2   NAME </pre>
<pre> \btxalwayscitation [...<sup>1</sup>...<sup>2</sup>...] [...<sup>2</sup>] 1   odkaz          = REFERENCE<sup>OPT</sup>     alternativa    = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears                     authornum authoryear     pred            = BEFEHL     po              = BEFEHL     vlevo           = BEFEHL     vpravo          = BEFEHL     inherits: \setupbtx 2   REFERENCE </pre>
<pre> \btxalwayscitation [...<sup>1</sup>...] [...<sup>2</sup>] 1   implicitni category entry<sup>OPT</sup> short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear 2   REFERENCE </pre>
<pre> \btxalwayscitation [...<sup>1</sup>...<sup>2</sup>...] [...<sup>2</sup>...<sup>2</sup>...] 1   odkaz          = REFERENCE     alternativa    = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears                     authornum authoryear     pred            = BEFEHL     po              = BEFEHL     vlevo           = BEFEHL     vpravo          = BEFEHL     inherits: \setupbtx 2   KEY = VALUE </pre>
<pre> \btxauthorfield {...} *   initials firstnames vons surnames juniors </pre>
<pre> \btxdetail {...} *   address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language     mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok     yearfiled NAME </pre>
<pre> \btxdirect {...} *   address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language     mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok     yearfiled NAME </pre>
<pre> \btxdoif {...<sup>1</sup>} {...<sup>2</sup>} 1   address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language     mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok     yearfiled NAME 2   TRUE </pre>
<pre> \btxdoifcombiinlistelse {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} {...<sup>4</sup>} 1   NAME 2   NAME 3   TRUE 4   FALSE </pre>
<pre> \btxdoifelse {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} 1   address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language     mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok     yearfiled NAME 2   TRUE 3   FALSE </pre>

\btxdfelsecombiinlist {...} {...} {...} {...}

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

\btxdfelsesameasprevious {...} {...} {...}

- 1 address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME
- 2 TRUE
- 3 FALSE

\btxdfelsesameaspreviouschecked {...} {...} {...} {...}

- 1 vzdy dvoustranny
- 2 address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME
- 3 TRUE
- 4 FALSE

\btxdfelseuservariable {...} {...} {...}

- 1 KEY
- 2 TRUE
- 3 FALSE

\btxdfifnot {...} {...}

- 1 address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME
- 2 TRUE

\btxdfisameaspreviouselse {...} {...} {...}

- 1 address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME
- 2 TRUE
- 3 FALSE

\btxdfisameaspreviouscheckedelse {...} {...} {...} {...}

- 1 vzdy dvoustranny
- 2 address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME
- 3 TRUE
- 4 FALSE

\btxdfuservariableelse {...} {...} {...}

- 1 KEY
- 2 TRUE
- 3 FALSE

\btfxexpandedjournal {...}

- \* NAME

\btxfieldd {...}

- \* address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME

\btxfielddname {...}

- \* address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME



<p><code>\btxfielddtype {...}</code></p> <p>* address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME</p>
<p><code>\btxfirstofrange {...}</code></p> <p>* volume pages</p>
<p><code>\btxflush {...}</code></p> <p>* address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME</p>
<p><code>\btxflushauthor [...<sup>1</sup>] {...<sup>2</sup>}</code></p> <p>1 num normalni normalshort inverted invertedshort</p> <p>2 autor editor</p>
<p><code>\btxflushauthorinverted {...}</code></p> <p>* autor editor</p>
<p><code>\btxflushauthorinvertedshort {...}</code></p> <p>* autor editor</p>
<p><code>\btxflushauthorname {...}</code></p> <p>* autor editor</p>
<p><code>\btxflushauthornormal {...}</code></p> <p>* autor editor</p>
<p><code>\btxflushauthornormalshort {...}</code></p> <p>* autor editor</p>
<p><code>\btxflushsuffix</code></p>
<p><code>\btxfoundname {...}</code></p> <p>* address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME</p>
<p><code>\btxfoundtype {...}</code></p> <p>* address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME</p>
<p><code>\btxhybridcite [...<sup>1</sup>...<sup>2</sup>] [...]</code></p> <p>1 odkaz = REFERENCE</p> <p>alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear</p> <p>pred = BEFEHL</p> <p>po = BEFEHL</p> <p>vlevo = BEFEHL</p> <p>vpravo = BEFEHL</p> <p>inherits: \setupbtx</p> <p>2 REFERENCE</p>
<p><code>\btxhybridcite [...<sup>1</sup>] [...<sup>2</sup>]</code></p> <p>1 implicitni category<sup>OPT</sup> entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear</p> <p>2 REFERENCE</p>
<p><code>\btxhybridcite {...}</code></p> <p>* REFERENCE</p>

\btxhybridcite [...<sup>1</sup>...] [...<sup>2</sup>...]

```
1 odkaz      = REFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
               authornum authoryear
  pred        = BEFEHL
  po          = BEFEHL
  vlevo       = BEFEHL
  vpravo      = BEFEHL
  inherits: \setupbtx
2 KEY = VALUE
```

\btxlistcitation [...<sup>1</sup>...] [...<sup>2</sup>...]

```
1 odkaz      = REFERENCEOPT
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
               authornum authoryear
  pred        = BEFEHL
  po          = BEFEHL
  vlevo       = BEFEHL
  vpravo      = BEFEHL
  inherits: \setupbtx
2 REFERENCE
```

\btxlistcitation [...<sup>1</sup>...] [...<sup>2</sup>...]

```
1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear
2 REFERENCE
```

\btxlistcitation [...<sup>1</sup>...] [...<sup>2</sup>...]

```
1 odkaz      = REFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
               authornum authoryear
  pred        = BEFEHL
  po          = BEFEHL
  vlevo       = BEFEHL
  vpravo      = BEFEHL
  inherits: \setupbtx
2 KEY = VALUE
```

\btxloadjournalist [...]

\* FILE

\btxoneorrange {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

```
1 volume pages
2 TRUE
3 FALSE
```

\btxremapauthor [...<sup>1</sup>] [...<sup>2</sup>...]

```
1 TEXT
2 TEXT
```

\btxsavejournalist [...]

\* FILE

\btxsetup {...}

\* NAME

\btxsingularorplural {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

```
1 editor producer director
2 TRUE
3 FALSE
```

\btxsingularplural {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

```
1 editor producer director
2 TRUE
3 FALSE
```

**\btxttextcitation** [...<sup>1</sup>...][...<sup>2</sup>]

1 odkaz = REFERENCE<sup>OPT</sup>  
alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears  
authornum authoryear  
pred = BEFEHL  
po = BEFEHL  
vlevo = BEFEHL  
vpravo = BEFEHL  
inherits: \setupbtx  
2 REFERENCE

**\btxttextcitation** [...<sup>1</sup>][...<sup>2</sup>]

1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear  
2 REFERENCE

**\btxttextcitation** [...<sup>1</sup>...][...<sup>2</sup>...]

1 odkaz = REFERENCE  
alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears  
authornum authoryear  
pred = BEFEHL  
po = BEFEHL  
vlevo = BEFEHL  
vpravo = BEFEHL  
inherits: \setupbtx  
2 KEY = VALUE

**\TOOLTIP** [...<sup>1</sup>...]{...<sup>2</sup>} {...<sup>3</sup>}

1 inherits: \setup<sup>OPT</sup>tooltip  
2 TEXT  
3 TEXT  
instances: tooltip

**\TOOLTIP** [...<sup>1</sup>]{...<sup>2</sup>} {...<sup>3</sup>}

1 vlevo nast<sup>OPT</sup>red vpravo  
2 TEXT  
3 TEXT  
instances: tooltip

**\buildmathaccent** {...<sup>1</sup>} {...<sup>2</sup>}

1 CHARACTER  
2 CHARACTER

**\buildtextaccent** {...<sup>1</sup>} {...<sup>2</sup>}

1 CHARACTER  
2 CHARACTER

**\buildtextbottomcomma** {...<sup>\*</sup>}

\* CHARACTER

**\buildtextbottomdot** {...<sup>\*</sup>}

\* CHARACTER

**\buildtextcedilla** {...<sup>\*</sup>}

\* CHARACTER

**\buildtextgrave** {...<sup>\*</sup>}

\* CHARACTER

**\buildtextmacron** {...<sup>\*</sup>}

\* CHARACTER

**\buildtextognek** {...<sup>\*</sup>}

\* CHARACTER

\Caps {...} * TEXT
\Cisla {...} * NUMMER
\CONTEXT
\ConTeXt
\Context
\ConvertConstantAfter \ <sup>1</sup> ... { <sup>2</sup> ...} { <sup>3</sup> ...} 1 CSNAME 2 TEXT 3 TEXT
\ConvertToConstant \ <sup>1</sup> ... { <sup>2</sup> ...} { <sup>3</sup> ...} 1 CSNAME 2 TEXT 3 TEXT
\camel {...} * TEXT
\catcodetablename
\cbox <sup>1</sup> ... { <sup>2</sup> ...} 1 TEXT <sup>OPT</sup> 2 CONTENT
\centeraligned {...} * CONTENT
\centerbox <sup>1</sup> ... { <sup>2</sup> ...} 1 TEXT <sup>OPT</sup> 2 CONTENT
\centeredbox <sup>1</sup> ... { <sup>2</sup> ...} 1 TEXT <sup>OPT</sup> 2 CONTENT
\centeredlastline
\centerednextbox <sup>1</sup> ... { <sup>2</sup> ...} 1 TEXT <sup>OPT</sup> 2 CONTENT
\centerline {...} * CONTENT
\cernalinka [... <sup>*</sup> ...] * inherits: \nastavce <sup>OPT</sup> linky
\cernelinky [... <sup>*</sup> ...] * inherits: \nastavce <sup>OPT</sup> linky

```
\cfrac [...]{...}{...}
1 l c r l1l2c l r c l c c c r l r c r r
2 CONTENT
3 CONTENT
```

```
\csla {...}
* NUMMER
```

```
\cslonadpisu [...][...]OPT
1 ABSCHNITT
2 predchozi aktualni dalsi prvni posledni
```

```
\cslorovnice [...]*[...]OPT
* REFERENCE
```

```
\cslostrany
```

```
\citation [...][...]1[...]2
1 odkaz = REFERENCE
alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
authornum authoryear
pred = BEFEHL
po = BEFEHL
vlevo = BEFEHL
vpravo = BEFEHL
inherits: \setupbtx
2 REFERENCE
```

```
\citation [...][...]OPT
1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear
2 REFERENCE
```

```
\citation {...}
* REFERENCE
```

```
\citation [...][...]1[...][...]2
1 odkaz = REFERENCE
alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
authornum authoryear
pred = BEFEHL
po = BEFEHL
vlevo = BEFEHL
vpravo = BEFEHL
inherits: \setupbtx
2 KEY = VALUE
```

```
\cite [...][...]1[...]2
1 odkazOPT = REFERENCE
alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
authornum authoryear
pred = BEFEHL
po = BEFEHL
vlevo = BEFEHL
vpravo = BEFEHL
inherits: \setupbtx
2 REFERENCE
```

```
\cite [...][...]OPT
1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear
2 REFERENCE
```

```
\cite {...}
* REFERENCE
```

<pre> \cite [...,\sup{1}...,...] [...,\sup{2}...,...] 1   odkaz      = REFERENCE     alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears                     authornum authoryear     pred        = BEFEHL     po          = BEFEHL     vlevo       = BEFEHL     vpravo      = BEFEHL     inherits: \setupbtx 2   KEY = VALUE </pre>
<pre> \clap {...} *   CONTENT </pre>
<pre> \classfont {...} {...} 1   NAME 2   FONT </pre>
<pre> \cldcommand {...} *   BEFEHL </pre>
<pre> \cldcontext {...} *   BEFEHL </pre>
<pre> \cldloadfile {...} *   FILE </pre>
<pre> \cldprocessfile {...} *   FILE </pre>
<pre> \cleftarrow {...} {...} 1   TEXT      OPT      OPT 2   TEXT </pre>
<pre> \collect {...} *   CONTENT </pre>
<pre> \collectedtext [...,\sup{1}...,...] [...,\sup{2}...,...] {...} {...} 1   inherits: \setupcollect<sup>OPT</sup> 2   pismo     = STYLE BEFEHL     barva     = COLOR     inherits: \nastavoramovani 3   TEXT 4   CONTENT </pre>
<pre> \collectexpanded {...} *   CONTENT </pre>
<pre> \colorcomponents {...} *   COLOR </pre>
<pre> \colored [...,\sup{1}...,...] {...} 1   inherits: \definujbarvu 2   CONTENT </pre>
<pre> \colored [...] {...} 1   COLOR 2   CONTENT </pre>
<pre> \coloronly [...] {...} 1   COLOR 2   CONTENT </pre>

<code>\columnbreak [...,*,...]</code> * ano ne nastaveni <sup>OPT</sup> lokalne sila prvni posledni NUMBER NAME
<code>\combinepages [...]<sup>1</sup> [...,...<sup>2</sup>...,...]</code> 1 FILE <sup>OPT</sup> 2 alternativa = a b c horizontalne vertikalne n = NUMBER nx = NUMBER ny = NUMBER start = NUMBER stop = NUMBER vzdalenost = DIMENSION vrsek = BEFEHL spodek = BEFEHL vlevo = BEFEHL vpravo = BEFEHL pred = BEFEHL po = BEFEHL mezi = BEFEHL ramecek = zap vyp pozadi = popredi barevne NAME barvapozadi = COLOR
<code>\commalistelement</code>
<code>\commalistsentence [...]<sup>1</sup>,... [...]<sup>2</sup>,...]</code> 1 TEXT <sup>OPT</sup> 2 TEXT
<code>\commalistsize</code>
<code>\comparedimension {...}<sup>1</sup> {...}<sup>2</sup></code> 1 DIMENSION 2 DIMENSION
<code>\comparedimensioneps {...}<sup>1</sup> {...}<sup>2</sup></code> 1 DIMENSION 2 DIMENSION
<code>\completebtxrendering [...]<sup>1</sup> [...,...<sup>2</sup>...,...]</code> 1 NAME <sup>OPT</sup> <sup>OPT</sup> 2 inherits: \setupbtxrendering
<code>\uplpyCOMBINEDLIST [...,...<sup>*</sup>...,...]</code> * inherits: \nastavseznam <sup>OPT</sup> instances: content
<code>\completelist [...]<sup>1</sup> [...,...<sup>2</sup>...,...]</code> 1 LISTE <sup>OPT</sup> 2 inherits: \nastavseznam
<code>\completelistofFLOATS [...,...<sup>*</sup>...,...]</code> * inherits: \nastavseznam <sup>OPT</sup> instances: chemicals figures tables intermezzi graphics
<code>\completelistofpublications [...]<sup>1</sup> [...,...<sup>2</sup>...,...]</code> 1 NAME <sup>OPT</sup> <sup>OPT</sup> 2 inherits: \setupbtxrendering
<code>\completelistofsorts [...]<sup>1</sup> [...,...<sup>2</sup>...,...]</code> 1 SINGULAR <sup>OPT</sup> 2 inherits: \nastavtrideni

\completelistofSORTS [... <sup>*</sup> ...] * inherits: \nastavtrideni <small>OPT</small> instances: logos
\completelistofsynonyms [... <sup>1</sup> ...] [... <sup>2</sup> ...] 1 SINGULAR <small>OPT</small> 2 inherits: \nastavsynonyma
\completelistofSYNONYMS [... <sup>*</sup> ...] * inherits: \nastavsynonyma <small>OPT</small> instances: abbreviations
\completepagenumber
\completeregister [... <sup>1</sup> ...] [... <sup>2</sup> ...] 1 NAME <small>OPT</small> 2 inherits: \nastavrejstrik
\uplNyREGISTER [... <sup>*</sup> ...] * inherits: \nastavrejstrik <small>OPT</small> instances: index
\nastaveniindex [... <sup>1</sup> ...] [... <sup>2</sup> ...] 1 NUMMER <small>OPT</small> 2 inherits: \nastavrejstrik
\complexorsimple \*... * CSNAME
\complexorsimpleempty \*... * CSNAME
\complexorsimpleempty {...} * TEXT CSNAME
\complexorsimple {...} * TEXT CSNAME
\composedcollector {...} * NAME
\composedlayer {...} * NAME
\compresult
\constantdimen \*... * CSNAME
\constantdimenargument \*... * CSNAME
\constantemptyargument \*... * CSNAME
\constantnumber \*... * CSNAME



<code>\constantnumberargument \*..</code> <code>* CSNAME</code>
<code>\contentreference [...<sup>1</sup>...] [...<sup>2</sup>...] {...<sup>3</sup>}</code> <code>1 REFERENCE</code> <code>2 inherits: \nastavoramovani</code> <code>3 CONTENT</code>
<code>\continuednumber {...}</code> <code>* NUMMER</code>
<code>\continueifinputfile {...}</code> <code>* FILE</code>
<code>\convertargument <sup>1</sup>... \to \<sup>2</sup>...</code> <code>1 TEXT</code> <code>2 CSNAME</code>
<code>\convertcommand \<sup>1</sup>... \to \<sup>2</sup>...</code> <code>1 CSNAME</code> <code>2 CSNAME</code>
<code>\convertedcounter [...<sup>1</sup>] [...<sup>2</sup>...] [...<sup>3</sup>...]</code> <code>1 NAME</code> <code>2 inherits: \setupcounter</code>
<code>\converteddimen {...<sup>1</sup>} {...<sup>2</sup>}</code> <code>1 DIMENSION</code> <code>2 ex em pt in cm mm sp bp pc dd cc nc</code>
<code>\convertedsubcounter [...<sup>1</sup>] [...<sup>2</sup>] [...<sup>3</sup>...]</code> <code>1 NAME</code> <code>2 NUMBER NUMBER:NUMBER NUMBER:* NUMBER:vse</code> <code>3 inherits: \setupcounter</code>
<code>\convertmonth {...}</code> <code>* NUMMER</code>
<code>\convertvalue <sup>1</sup>... \to \<sup>2</sup>...</code> <code>1 NAME</code> <code>2 CSNAME</code>
<code>\convertvboxtohbox</code>
<code>\copyboxfromcache {...<sup>1</sup>} {...<sup>2</sup>} <sup>3</sup>...</code> <code>1 NAME</code> <code>2 NUMBER TEXT</code> <code>3 CSNAME NUMBER</code>
<code>\copyLABELtext [...<sup>1</sup>] [...<sup>2</sup>...] [...<sup>3</sup>...]</code> <code>1 SPRACHE</code> <code>2 KEY = KEY</code> <code>instances: head label mathlabel taglabel unit operator prefix suffix btxlabel</code>
<code>\copypages [...<sup>1</sup>] [...<sup>2</sup>...] [...<sup>3</sup>...]</code> <code>1 FILE</code> <code>2 znaceni = zap vyp</code> <code>offset = DIMENSION</code> <code>n = NUMBER</code> <code>3 inherits: \setupexternalfigure</code>

$\backslash\text{copyparameters}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...] [..., <sup>3</sup> ...] <ul style="list-style-type: none"> <li>1 TEXT</li> <li>2 TEXT</li> <li>3 KEY</li> </ul>
$\backslash\text{copyposition}$ { <sup>1</sup> ...} { <sup>2</sup> ...} <ul style="list-style-type: none"> <li>1 NAME</li> <li>2 NAME</li> </ul>
$\backslash\text{countersubs}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...] <ul style="list-style-type: none"> <li>1 NAME <small>OPT</small></li> <li>2 NUMMER</li> </ul>
$\backslash\text{counttoken}$ <sup>1</sup> ... \in <sup>2</sup> ... \to \sup{3}... <ul style="list-style-type: none"> <li>1 TEXT</li> <li>2 TEXT</li> <li>3 CSNAME</li> </ul>
$\backslash\text{counttokens}$ <sup>1</sup> ... \to \sup{2}... <ul style="list-style-type: none"> <li>1 TEXT</li> <li>2 CSNAME</li> </ul>
$\backslash\text{cramped}$ {.*} <ul style="list-style-type: none"> <li>* CONTENT</li> </ul>
$\backslash\text{crampedclap}$ {.*} <ul style="list-style-type: none"> <li>* CONTENT</li> </ul>
$\backslash\text{crampedllap}$ {.*} <ul style="list-style-type: none"> <li>* CONTENT</li> </ul>
$\backslash\text{crampedrlap}$ {.*} <ul style="list-style-type: none"> <li>* CONTENT</li> </ul>
$\backslash\text{crightarrow}$ { <sup>1</sup> ...} { <sup>2</sup> ...} <ul style="list-style-type: none"> <li>1 TEXT <small>OPT</small> <small>OPT</small></li> <li>2 TEXT</li> </ul>
$\backslash\text{crightoverleftarrow}$ { <sup>1</sup> ...} { <sup>2</sup> ...} <ul style="list-style-type: none"> <li>1 TEXT <small>OPT</small> <small>OPT</small></li> <li>2 TEXT</li> </ul>
$\backslash\text{ctop}$ <sup>1</sup> ... { <sup>2</sup> ...} <ul style="list-style-type: none"> <li>1 TEXT <small>OPT</small></li> <li>2 CONTENT</li> </ul>
$\backslash\text{ctxcommand}$ {.*} <ul style="list-style-type: none"> <li>* BEFEHL</li> </ul>
$\backslash\text{ctxdirectcommand}$ {.*} <ul style="list-style-type: none"> <li>* BEFEHL</li> </ul>
$\backslash\text{ctxdirectlua}$ {.*} <ul style="list-style-type: none"> <li>* BEFEHL</li> </ul>
$\backslash\text{ctxfunction}$ {.*} <ul style="list-style-type: none"> <li>* NAME</li> </ul>
$\backslash\text{CTXFUNCTIONDEFINITION}$

<code>\CTXFUNCTION</code>
<code>\ctxlatecommand {...}</code> * BEFEHL
<code>\ctxlatelua {...}</code> * BEFEHL
<code>\ctxloadluafile {...}</code> * FILE
<code>\ctxlua {...}</code> * BEFEHL
<code>\ctxluabuffer [...]</code> * BUFFER OPT
<code>\ctxluacode {...}</code> * BEFEHL
<code>\ctxreport {...}</code> * BEFEHL
<code>\ctxsprint {...}</code> * BEFEHL
<code>\currentassignmentlistkey</code>
<code>\currentassignmentlistvalue</code>
<code>\currentbtxuservariable {...}</code> * KEY
<code>\currentcommalistitem</code>
<code>\currentcomponent</code>
<code>\currentenvironment</code>
<code>\currentfeaturetest</code>
<code>\currentinterface</code>
<code>\currentPOPISEK [...<sup>1</sup>,...] {...<sup>2</sup>}</code> 1 REFERENCE OPT OPT 2 TEXT
<code>\currentlanguage</code>
<code>\currentlistentrydestinationattribute</code>
<code>\currentlistentrylimitedtext {...}</code> * TEXT

<code>\currentlistentrynumber</code>
<code>\currentlistentrypagenumber</code>
<code>\currentlistentryreferenceattribute {...}</code> <code>*    cislo text cislostranky vse</code>
<code>\currentlistentrytitle</code>
<code>\currentlistentrytitlerendered</code>
<code>\currentlistsymbol</code>
<code>\currentmainlanguage</code>
<code>\currentmessagetext</code>
<code>\currentmoduleparameter {...}</code> <code>*    KEY</code>
<code>\currentoutputstream</code>
<code>\currentproduct</code>
<code>\currentproject</code>
<code>\currentregime</code>
<code>\currentregisterpageuserdata {...}</code> <code>*    KEY</code>
<code>\currentresponses</code>
<code>\currenttime [...,*,...]</code> <code>*    h m TEXT                    OPT</code>
<code>\currentvalue</code>
<code>\currentxtablecolumn</code>
<code>\currentxtablerow</code>
<code>\d {...}</code> <code>*    CHARACTER</code>
<code>\dalsipodstranka</code>
<code>\datasetvariable {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}</code> <code>1    NAME</code> <code>2    NAME NUMBER</code> <code>3    KEY realpage</code>

<code>\datum [...,..<sup>1</sup>...,...] [...,..<sup>2</sup>...]</code> 1 d = NUMBER <sup>OPT</sup> m = NUMBER y = NUMBER 2 inherits: \aktualnidatum
<code>\dayoftheweek {...} {...} {...}</code> 1 NUMMER 2 NUMMER 3 NUMMER
<code>\dayspermonth {...} {...}</code> 1 NUMMER 2 NUMMER
<code>\ddot {...}</code> * CHARACTER
<code>\decrement \...</code> * CSNAME
<code>\decrementcounter [...] [...<sup>2</sup>]</code> 1 NAME 2 NUMMER <sup>OPT</sup>
<code>\decrementedcounter [...]</code> * NAME
<code>\decrementpagenumber</code>
<code>\decrementsubpagenumber</code>
<code>\decrementvalue {...}</code> * NAME
<code>\decrement cd:parentheses-1</code> * CSNAME NUMMER
<code>\defaultinterface</code>
<code>\defaultobjectpage</code>
<code>\defaultobjectreference</code>
<code>\defcatcodecommand \<sup>1</sup>... <sup>2</sup>... {...<sup>3</sup>}</code> 1 CSNAME 2 CHARACTER NUMMER 3 BEFEHL
<code>\defconvertedargument \<sup>1</sup>... {...<sup>2</sup>}</code> 1 CSNAME 2 TEXT
<code>\defconvertedcommand \<sup>1</sup>... \<sup>2</sup>...</code> 1 CSNAME 2 CSNAME

`\defconvertedvalue \... {1... {2...}}`

1 CSNAME  
2 NAME

`\defineactivecharacter ... {1... {2...}}`

1 CHARACTER  
2 BEFEHL

`\definealternativestyle [...1...] [...2...] [...3...]`

1 NAME  
2 BEFEHL  
3 BEFEHL

`\defineanchor [...1...] [...2...] [...3...OPT...] [...4...OPT...]`

1 NAME  
2 NAME  
3 inherits: \setupplayer  
4 inherits: \setupplayerinherits: \nastavoramovani

`\defineattachment [...1...] [...2...] [...3...OPT...OPT...]`

1 NAME  
2 NAME  
3 inherits: \setupattachment

`\defineattribute [...1...] [...2...OPT...]`

1 NAME  
2 lokalne globalne public private

`\definebackground [...1...] [...2...] [...3...OPT...OPT...]`

1 NAME  
2 NAME  
3 inherits: \nastavpozadi

`\definebar [...1...] [...2...] [...3...OPT...OPT...]`

1 NAME  
2 NAME  
3 inherits: \setupbar

`\definebodyfontswitch [...1...] [...2...]`

1 NAME  
2 inherits: \nastavzakladnifont

`\definebreakpoint [...1...] [...2...] [...3...OPT...]`

1 NAME  
2 CHARACTER  
3 typ = 1 2 3 4 5  
nvlevo = NUMMER  
nvpravo = NUMMER  
vlevo = BEFEHL  
stredni = BEFEHL  
vpravo = BEFEHL  
range = ano ne  
language = SPRACHE

`\definebreakpoints [...*...]`

\* NAME

`\definebtx [...1...] [...2...] [...3...OPT...OPT...]`

1 NAME  
2 NAME  
3 inherits: \setupbtx

```
\definebtxdataset [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupbtxdataset
```

```
\definebtxregister [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupbtxregister
```

```
\definebtxrendering [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupbtxrendering
```

```
\definebutton [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupbutton
```

```
\definecapitals [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \nastavkapitalky
```

```
\definecollector [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupcollector
```

```
\definecolumnbreak [...] [...] [...]
1 NAME
2 ano ne nastaveni lokalne sila prvni posledni NUMMER
```

```
\definecombination [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupcombination
```

```
\definecomment [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \nastavkomentar
```

```
\definecomplexorsimple \*..
* CSNAME
```

```
\definecomplexorsimpleempty \*..
* CSNAME
```

```
\definecomplexorsimpleempty {...}
* TEXT CSNAME
```

```
\definecomplexorsimple {...}
* TEXT CSNAME
```

```
\defineconversionset [...] [...] [...] [...]
1 NAME SECTIONBLOCK:NAME OPT
2 NAME PROCESSOR->NAME
3 NAME PROCESSOR->NAME
```

```
\definecounter [...] [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupcounter
```

```
\definedataset [...] [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupdataset
```

```
\definedelimitedtext [...] [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupdelimitedtext
```

```
\definedfont [...]
* FONT
```

```
\defineeffect [...] [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupeffect
```

```
\defineexpandable [...] [...] [...]
1 NUMBER
2 CSNAME
3 CONTENT
```

```
\defineexternalfigure [...] [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupexternalfigure
```

```
\definefallbackfamily [...] [...] [...] [...]
1 NAME
2 rm ss tt mm hw cg antikva serif pravidelne bezserifu sans podpora strojopis opis mono rukopisne kaligraficke math
matematika
3 FONT
4 rscale = NUMBER
designsize = implicitni auto
goodies = FILE
range = NUMBER NAME
offset = NUMBER NAME
check = ano ne
sila = ano ne
features = NAME
tf = TEXT
bf = TEXT
it = TEXT
sl = TEXT
bi = TEXT
bs = TEXT
sc = TEXT
```

```
\definefallbackfamily [...] [...] [...] [...]
1 NAME
2 rm ss tt mm hw cg antikva serif pravidelne bezserifu sans podpora strojopis opis mono rukopisne kaligraficke math
matematika
3 FONT
4 NAME
```

```
\definefieldbody [...] [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupfieldbody
```



`\definefieldbodyset [...]1 [...]2,...]`

1 NAME  
2 NAME

`\definefieldcategory [...]1 [...]2 [...]3,...]`

1 NAME  
2 NAME  
3 inherits: \setupfieldcategory

`\definefileconstant {...}1 {...}2`

1 NAME  
2 NAME

`\definefilefallback [...]1 [...]2,...]`

1 NAME  
2 FILE

`\definefilesynonym [...]1 [...]2`

1 NAME  
2 FILE

`\definefiller [...]1 [...]2 [...]3,...]`

1 NAME  
2 NAME  
3 inherits: \setupfiller

`\definefirstline [...]1 [...]2 [...]3,...]`

1 NAME  
2 NAME  
3 inherits: \setupfirstline

`\definefittingpage [...]1 [...]2 [...]3,...]`

1 NAME  
2 NAME  
3 inherits: \setupfittingpage

`\definefontalternative [...]*`

\* NAME

`\definefontfallback [...]1 [...]2 [...]3,...]4 [...]5,...]`

1 NAME  
2 FONT NAME  
3 NAME NUMMER  
4 rscale = NUMMER  
silas = ano ne  
check = ano ne  
offset = NUMMER NAME  
features = NAME

`\definefontfamily [...]1 [...]2 [...]3 [...]4,...]`

1 NAME  
2 rm ss tt mm hw cg antikva serif pravidelne bezserifu sans podpora strojopis opis mono rukopisne kaligraficke math  
mathematika  
3 FONT  
4 rscale = NUMMER  
designsize = implicitni auto  
goodies = FILE  
features = NAME  
tf = TEXT  
bf = TEXT  
it = TEXT  
sl = TEXT  
bi = TEXT  
bs = TEXT  
sc = TEXT

```
\definefontfamilypreset [...]1 [...,...2...,...]
```

```
1 NAME
2 inherits: \definefontfamily
```

```
\definefontfamilypreset [...]1 [...]2
```

```
1 NAME
2 NAME
```

```
\definefontfamily [...]1 [...]2 [...]3 [...,...4...,...]
```

```
1 NAME
2 rm ss tt mm hw cg antikva serif pravidelne bezserifu sans podpora strojopis opis mono rukopisne kaligraficke math
  matematika
3 FONT
4 NAME
```

```
\definefontfeature [...]1 [...]2 [...,...3...,...]
```

```
1 NAME
2 NAME
3 language = NAME
  script = NAME auto
  mode = node base auto zadny
  liga = ano ne
  kern = ano ne
  extrakerns = ano ne
  tlig = ano ne
  trep = ano ne
  missing = ano ne
  dummies = ano ne
  analyze = ano ne
  unicoding = ano ne
  expanzen = NAME
  protrusion = NAME
  nostackmath = ano ne
  realdimensions = ano ne
  itlc = ano ne
  textitalics = ano ne
  mathitalics = ano ne
  slant = NUMMER
  extend = NUMMER
  dimensions = NUMMER
  boundingbox = ano ne
  compose = ano ne
  char-ligatures = ano ne
  compat-ligatures = ano ne
  goodies = FILE
  extrafeatures = ano ne
  featureset = NAME
  colorscheme = NAME
  postprocessor = NAME
  mathdimensions = NAME
  keepligatures = ano ne auto
  devanagari = ano ne
  features = ano ne
  tcom = ano ne
  anum = ano ne
  mathsize = ano ne
  decomposehangul = ano ne
  mathalternatives = ano ne
  mathgaps = ano ne
  checkmarks = ano ne
  NAME = ano ne
  mathnolimitsmode = NUMMER
  blockligatures = ano ne
```

```
\definefontfile [...]1 [...]2 [...,...3...,...]
```

```
1 NAME
2 FILE
3 features = NAME
  fallbacks = NAME
  goodies = NAME
  designsize = auto implicitni
```

```
\definefontsize [...]*
```

```
* NAME
```

```
\definefontsolution [...]1 [...]2 [...]3...]
```

```
1 NAME OPT OPT
```

```
2 NAME
```

```
3 inherits: \setupfontsolution
```

```
\defineformula [...]1 [...]2 [...]3...]
```

```
1 NAME OPT OPT
```

```
2 NAME
```

```
3 inherits: \setupformula
```

```
\defineformulaalternative [...]1 [...]2 [...]3
```

```
1 NAME
```

```
2 CSNAME
```

```
3 CSNAME
```

```
\defineformulaframed [...]1 [...]2 [...]3...]
```

```
1 NAME OPT OPT
```

```
2 NAME
```

```
3 inherits: \setupformulaframed
```

```
\defineframedcontent [...]1 [...]2 [...]3...]
```

```
1 NAME OPT OPT
```

```
2 NAME
```

```
3 inherits: \setupframedcontent
```

```
\definefrozenfont [...]1 [...]2
```

```
1 NAME
```

```
2 FONT
```

```
\defineglobalcolor [...]1 [...]2...]
```

```
1 NAME
```

```
2 inherits: \definujbarvu
```

```
\defineglobalcolor [...]1 [...]2
```

```
1 NAME
```

```
2 COLOR
```

```
\definegraphictypesynonym [...]1 [...]2
```

```
1 NAME
```

```
2 NAME
```

```
\definegridsnapping [...]1 [...]2...]
```

```
1 NAME
```

```
2 lokalne globalne noheight nodepth box max min zadny radek pulradku prvni posledni minvyska maxheight mindepth
maxdepth vrsek spodek strut NUMMER minheight:NUMMER maxheight:NUMMER mindepth:NUMMER maxdepth:NUMMER box:NUMMER
top:NUMMER bottom:NUMMER offset:NUMMER
```

```
\defineheadalternative [...]1 [...]2 [...]3...]
```

```
1 NAME OPT OPT
```

```
2 NAME
```

```
3 inherits: \setupheadalternative
```

```
\definehelp [...]1 [...]2 [...]3...]
```

```
1 NAME OPT OPT
```

```
2 NAME
```

```
3 inherits: \setuphelp
```

```
\definehigh [...]1 [...]2 [...]3...]
```

```
1 NAME OPT OPT
```

```
2 NAME
```

```
3 inherits: \setuphigh
```

```
\definehighlight [...1] [...2] [...3...]
1 NAME OPT OPT
2 NAME
3 inherits: \setuphighlight
```

```
\definehspace [...1] [...2] [...3]
1 NAME OPT
2 NAME
3 DIMENSION
```

```
\definehyphenationfeatures [...1] [...2...]
1 NAME
2 characters = TEXT
   hyphens = ano vse TEXT
   joiners = ano vse TEXT
   rightwords = NUMMER
   hyphenmin = NUMMER
   lefthyphenmin = NUMMER
   righthyphenmin = NUMMER
   lefthyphenchar = NUMMER
   righthyphenchar = NUMMER
   alternativa = original tex hyphenate expanded traditional zadny
   pravahrana = tex
   rightchars = slovo NUMMER
```

```
\definecharacterkerning [...1] [...2] [...3...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupcharacterkerning
```

```
\definecharacterspacing [...1]
* NAME
```

```
\definechemical [...1] {...2}
1 NAME
2 CONTENT
```

```
\definechemicals [...1] [...2] [...3...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupchemical
```

```
\definechemicalsymbol [...1] [...2]
1 NAME
2 TEXT
```

```
\defineindentedtext [...1] [...2] [...3...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupindentedtext
```

```
\defineindenting [...1] [...2...]
1 NAME
2 [-+]male [-+]stredni [-+]velke zadny ne ne prvni dalsi ano vzdy nikdy liche sude normalni reset toggle DIMENSION
```

```
\defineinitial [...1] [...2] [...3...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupinitial
```

```
\defineinsertion [...1] [...2] [...3...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupinsertion
```

<pre> \defineinteraction [...] [...] [...] [...] 1 NAME 2 NAME 3 inherits: \nastavinterakci </pre>
<pre> \defineinteractionbar [...] [...] [...] [...] 1 NAME 2 NAME 3 inherits: \nastavinterakcnilistu </pre>
<pre> \defineinterfaceconstant {...} {...} 1 NAME 2 NAME </pre>
<pre> \defineinterfaceelement {...} {...} 1 NAME 2 NAME </pre>
<pre> \defineinterfacevariable {...} {...} 1 NAME 2 NAME </pre>
<pre> \defineinterlinespace [...] [...] [...] [...] 1 NAME 2 NAME 3 inherits: \nastavmeziradkovoumezeru </pre>
<pre> \defineintermediatecolor [...] [...] [...] [...] 1 NAME 2 COLOR NUMMER 3 a = NUMMER t = NUMMER </pre>
<pre> \defineitemgroup [...] [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setupitemgroup </pre>
<pre> \defineitems [...] [...] [...] [...] 1 NAME 2 NAME 3 inherits: \nastavpolozky </pre>
<pre> \definelabelclass [...] [...] 1 NAME 2 NUMMER </pre>
<pre> \nastavenibtxlabeltext [...] [...] [...] 1 SPRACHE 2 KEY = VALUE </pre>
<pre> \nastaveniheadtext [...] [...] [...] 1 SPRACHE 2 KEY = VALUE </pre>
<pre> \nastavenilabeltext [...] [...] [...] 1 SPRACHE 2 KEY = VALUE </pre>
<pre> \nastavenimathlabeltext [...] [...] [...] 1 SPRACHE 2 KEY = VALUE </pre>

<pre> \nastavenioperatortext [...] [...] 1  SPRACHE 2  KEY = VALUE </pre>
<pre> \nastaveniprefixtext [...] [...] 1  SPRACHE 2  KEY = VALUE </pre>
<pre> \nastavenisuffixtext [...] [...] 1  SPRACHE 2  KEY = VALUE </pre>
<pre> \nastavenitaglabeltext [...] [...] 1  SPRACHE 2  KEY = VALUE </pre>
<pre> \nastaveniunittext [...] [...] 1  SPRACHE 2  KEY = VALUE </pre>
<pre> \definelaye [...] [...] [...] 1  NAME 2  NAME 3  inherits: \setuplayer </pre>
<pre> \definelaye [...] [...] 1  NAME 2  inherits: \setuplayer </pre>
<pre> \definelaye [...] [...] 1  NAME 2  NAME </pre>
<pre> \definelayout [...] [...] [...] 1  NAME 2  NAME 3  inherits: \nastavvzhled </pre>
<pre> \definelinefiller [...] [...] [...] 1  NAME 2  NAME 3  inherits: \setuplinefiller </pre>
<pre> \definelinenote [...] [...] [...] 1  NAME 2  NAME 3  inherits: \setuplinenote </pre>
<pre> \definelinenumbering [...] [...] [...] 1  NAME 2  NAME 3  inherits: \nastavcislovaniradku </pre>
<pre> \definelines [...] [...] [...] 1  NAME 2  NAME 3  inherits: \nastavradky </pre>
<pre> \definelistalternative [...] [...] [...] 1  NAME 2  NAME 3  inherits: \setuplistalternative </pre>

```
\definelistextra [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setuplistextra
```

```
\definelow [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setuplow
```

```
\definelowhigh [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setuplowhigh
```

```
\definelowmidhigh [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setuplowmidhigh
```

```
\defineMPinstance [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupMPinstance
```

```
\definemarginblock [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupmarginblock
```

```
\definemargindata [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupmargindata
```

```
\definemarker [...]
* NAME
```

```
\definemathaccent ... ..
1 NAME
2 CHARACTER
```

```
\definemathalignment [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupmathalignment
```

```
\definemathcases [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupmathcases
```

```
\definemathcommand [...] [...] [...] [...]
1 NAME OPT OPT OPT
2 ord op bin rel open close punct alpha uvnitr nothing limop nolog box
3 jedna dve
4 BEFEHL \...##1 \...##1##2
```

```
\definemathdoubleextensible [...] [...] [...] [...]
1 obe vfenced OPT
2 NAME
3 NUMMER
4 NUMMER
```

```

\definematheconomics [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupmatheconomics

```

```

\definemathtextensile [...] [...] [...]
1 reverse matematika text chemistry
2 NAME
3 NUMMER

```

```

\definemathtence [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupmathtence

```

```

\definemathtfraction [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupmathtfraction

```

```

\definemathtframed [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupmathtframed

```

```

\definemathtmatrix [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupmathtmatrix

```

```

\definemathtornament [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupmathtornament

```

```

\definemathtoverextensile [...] [...] [...]
1 vrsek vfenced OPT
2 NAME
3 NUMMER

```

```

\definemathttextensile [...] [...] [...]
1 bothtext OPT
2 NAME
3 NUMMER

```

```

\definematht radical [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupmatht radical

```

```

\definemathtstackers [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupmathtstackers

```

```

\definemathtstyle [...] [...]
1 NAME
2 obrazovka text script scriptscript cramped uncramped normalni zhustene male velke

```

```

\definemathtriplet [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 TEXT

```



```
\definemathunderextensible [1...] [2...] [3...]
1   spodek vfenced          OPT
2   NAME
3   NUMMER
```

```
\definemathundertextextensible [1...] [2...] [3...]
1   bothtext                OPT
2   NAME
3   NUMMER
```

```
\definemathunstacked [1...] [2...] [3...]
1   siroce                  OPT
2   NAME
3   NUMMER
```

```
\definemeasure [1...] [2...]
1   NAME
2   DIMENSION
```

```
\definemessageconstant {.*}
*   NAME
```

```
\definemixedcolumns [1...] [2...] [...,3...,...]
1   NAME                    OPT      OPT
2   NAME
3   inherits: \setupmixedcolumns
```

```
\definemode [...,1...] [2...]
1   NAME                    OPT
2   ano ne drzet
```

```
\definemultitonecolor [1...] [...,2...,...] [...,3...,...] [...,4...,...]
1   NAME                    OPT
2   COLOR = NUMMER
3   inherits: \definujbarvu
4   inherits: \definespotcolor
```

```
\definenamecolor [1...] [...,2...,...]
1   NAME
2   inherits: \definujbarvu
```

```
\definenamecolor [1...] [2...]
1   NAME
2   COLOR
```

```
\definenamespace [1...] [...,2...,...]
1   NAME
2   jmeno    = TEXT
   parent   = TEXT
   pismeno   = ano ne
   prikaz    = ano ne seznam
   setup     = ano ne seznam
   set       = ano ne seznam
   ramecek   = ano ne
```

```
\definenarrower [1...] [2...] [...,3...,...]
1   NAME                    OPT      OPT
2   NAME
3   inherits: \nastavzuzeni
```

```
\definernote [1...] [2...] [...,3...,...]
1   NAME                    OPT      OPT
2   NAME
3   inherits: \setupnote
```

<pre> \defineornament [...] [...] [...] 1 NAME 2 alternativa = a b    inherits: \setupcollector 3 pismo = STYLE BEFEHL    barva = COLOR    inherits: \nastavoramovani </pre>
<pre> \defineornament [...] [...] [...] 1 NAME 2 alternativa = a b    inherits: \setupplayer 3 inherits: \setupplayeredtext </pre>
<pre> \defineoutputroutine [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setupoutputroutine </pre>
<pre> \defineoutputroutinecommand [...]*[...] * KEY </pre>
<pre> \definepage [...] [...] 1 NAME 2 REFERENCE </pre>
<pre> \definepagebreak [...] [...] 1 NAME 2 prazdne zhlavi upati dummy ramecek NUMBER +NUMBER implicitni reset zablokovat ano ne zlom prazdny nastaveni    vysokapriorita vlevo vpravo sude liche ctyrnasobny posledni poslednistrana start stop </pre>
<pre> \definepagegrid [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setuppagegrid </pre>
<pre> \definepagegridarea [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setuppagegridarea </pre>
<pre> \definepagegridspan [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setuppagegridspan </pre>
<pre> \definepagechecker [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setuppagechecker </pre>
<pre> \definepageinjection [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setuppageinjection </pre>
<pre> \definepageinjectionalternative [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setuppageinjectionalternative </pre>
<pre> \definepageshift [...] [...] [...] 1 NAME 2 horizontalne vertikalne 3 DIMENSION </pre>

```
\definepagestate [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setuppagestate
```

```
\definepairedbox [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setuppairedbox
```

```
\defineparagraph [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupparagraph
```

```
\defineparallel [...] [...]
1 NAME
2 NAME
```

```
\defineparbuilder [...]
* NAME
```

```
\defineplacement [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupplacement
```

```
\definepositioning [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \nastavumistovani
```

```
\defineprefixset [...] [...] [...]
1 NAME SECTIONBLOCK:NAME OPT
2 ABSCHNITT
3 ABSCHNITT
```

```
\defineprocesscolor [...] [...] [...] [...]
1 NAME OPT
2 COLOR
3 inherits: \definujbarvu
```

```
\defineprocessor [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupprocessor
```

```
\definepushbutton [...] [...] [...]
1 NAME OPT
2 inherits: \setupfieldcontentframed
```

```
\definepushsymbol [...] [...]
1 NAME
2 n r d
```

```
\definerenderingwindow [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setuprenderingwindow
```

<pre> \defineresetset [...] [...] [...] 1  NAME SECTIONBLOCK:NAME 2  NUMMER 3  NUMMER </pre>
<pre> \definescale [...] [...] [...] 1  NAME 2  NAME 3  inherits: \setupscale </pre>
<pre> \definescript [...] [...] [...] 1  NAME 2  NAME 3  inherits: \setupscrip </pre>
<pre> \definesectionlevels [...] [...] 1  NAME 2  ABSCHNITT </pre>
<pre> \defineselector [...] [...] 1  NAME 2  inherits: \setupselector </pre>
<pre> \defineseparatorset [...] [...] 1  NAME SECTIONBLOCK:NAME 2  BEFEHL PROCESSOR-&gt;BEFEHL 3  BEFEHL PROCESSOR-&gt;BEFEHL </pre>
<pre> \defineshift [...] [...] 1  NAME 2  NAME 3  inherits: \setupshift </pre>
<pre> \definesidebar [...] [...] 1  NAME 2  NAME 3  inherits: \setupsidebar </pre>
<pre> \definesort [...] [...] [...] {...} 1  ano ne 2  SINGULAR 3  NAME 4  CONTENT </pre>
<pre> \placelistoflogos [...] [...] *  inherits: \nastavtrideni </pre>
<pre> \definespotcolor [...] [...] [...] 1  NAME 2  COLOR 3  a = NUMMER zadny normalni multiply rastr prekryv softlight hardlight colordodge colorburn darken lighten difference     exclusion hue saturation barevne luminosity     t = NUMMER     e = TEXT     p = NUMMER </pre>
<pre> \definestyleinstance [...] [...] [...] 1  NAME 2  rm ss tt mm hw cg 3  tf bf it sl bi bs sc 4  BEFEHL </pre>

<pre> \definesubformula [...] [...] [...] [...] 1  NAME 2  NAME 3  inherits: \setupsbformula </pre>
<pre> \definesynonym [...] [...] [...] [...] 1  ano ne 2  SINGULAR 3  NAME 4  TEXT 5  CONTENT </pre>
<pre> \placelistofabbreviations [...] [...] *  inherits: \nastavsynonyma </pre>
<pre> \definesystemattribute [...] [...] 1  NAME 2  lokalne globalne public private </pre>
<pre> \definesystemconstant [...] *  NAME </pre>
<pre> \definesystemvariable [...] *  NAME </pre>
<pre> \defineTABLEsetup [...] [...] 1  NAME 2  inherits: \setupTABLE </pre>
<pre> \definetabulation [...] [...] [...] 1  NAME 2  NAME 3  inherits: \setuptabulation </pre>
<pre> \definetextbackground [...] [...] [...] 1  NAME 2  NAME 3  inherits: \setuptextbackground </pre>
<pre> \definetextflow [...] [...] [...] 1  NAME 2  NAME 3  inherits: \setuptextflow </pre>
<pre> \definetooltip [...] [...] [...] 1  NAME 2  NAME 3  inherits: \setuptooltip </pre>
<pre> \definetransparency [...] [...] 1  NAME 2  NUMMER </pre>
<pre> \definetransparency [...] [...] 1  NAME 2  a = NUMMER zadny normalni multiply rastr prekryv softlight hardlight colordodge colorburn darken lighten difference     exclusion hue saturation barevne luminosity     t = NUMMER </pre>
<pre> \definetransparency [...] [...] 1  NAME 2  NAME </pre>

`\definetwopasslist {...}`

\* NAME

`\definetype [...1] [...2] [...3...]`

1 NAME

OPT

OPT

2 NAME

3 inherits: \nastavtype

`\definetypeface [...1] [...2] [...3] [...4] [...5] [...6...]`

1 NAME

OPT

OPT

2 rm ss tt mm hw cg

3 serif sans mono math handwriting calligraphy

4 NAME

5 implicitni dtp

6 rscale = auto NUMBER

features = NAME

fallbacks = NAME

goodies = NAME

designsize = auto implicitni

smer = obe

`\definetypescriptprefix [...1] [...2]`

1 NAME

2 TEXT

`\definetypescriptsynonym [...1] [...2]`

1 NAME

2 TEXT

`\definetypesetting [...1] [...2] [...3...]`

1 NAME

OPT

OPT

2 TEXT

3 inherits: \setupexternalfigure

`\defineunit [...1] [...2] [...3...]`

1 NAME

OPT

OPT

2 NAME

3 inherits: \setupunit

`\defineviewerlayer [...1] [...2] [...3...]`

1 NAME

OPT

OPT

2 NAME

3 inherits: \setupviewerlayer

`\definevspace [...1] [...2] [...3]`

1 NAME

OPT

2 NAME

3 DIMENSION

`\definevspacing [...1] [...2]`

1 NAME

2 inherits: \vspacing

`\definevspacingamount [...1] [...2] [...3]`

1 NAME

OPT

OPT

2 DIMENSION

3 DIMENSION

`\definetable [...1] [...2] [...3...]`

1 NAME

OPT

OPT

2 NAME

3 inherits: \setupxtable

`\definuj [.1.] \.2. {.3.}`

1    NUMBER    OPT  
2    CSNAME  
3    CONTENT

`\definujakcent .1. .2. .3.`

1    CHARACTER  
2    CHARACTER  
3    CHARACTER

`\definujbarvu [.1.] [.,.,.2.,.,.]`

1    NAME  
2    r = NUMBER  
     g = NUMBER  
     b = NUMBER  
     c = NUMBER  
     m = NUMBER  
     y = NUMBER  
     k = NUMBER  
     h = NUMBER  
     s = NUMBER  
     v = NUMBER  
     x = NUMBER  
     a = NUMBER zadny normalni multiply rastr prekryv softlight hardlight colordodge colorburn darken lighten difference  
         exclusion hue saturation barevne luminosity  
     t = NUMBER

`\definujbarvu [.1.] [.2.]`

1    NAME  
2    COLOR

`\definujblok [.1.] [.2.] [.,.,.3.,.,.]`

1    NAME    OPT    OPT  
2    NAME  
3    inherits: \nastavblok

`\definujbloksekce [.1.] [.2.] [.,.,.3.,.,.]`

1    NAME    OPT  
2    NAME  
3    inherits: \nastavbloksekce

`\definujbuffer [.1.] [.2.] [.,.,.3.,.,.]`

1    NAME    OPT    OPT  
2    BUFFER  
3    inherits: \nastavbuffer

`\definujfont [.1.] [.2.] [.,.,.3.,.,.]`

1    NAME    OPT  
2    FONT  
3    inherits: \nastavmeziradkovoumezeru

`\definujfont [.1.] [.2.] [.3.]`

1    NAME    OPT  
2    FONT  
3    NAME

`\definujformatodkazu [.1.] [.2.] [.,.,.3.,.,.]`

1    NAME    OPT    OPT  
2    NAME  
3    inherits: \setupreferenceformat

`\definujhbox [.1.] [.2.]`

1    NAME  
2    DIMENSION

\definujinterakcnimenu [...]<sup>1</sup> [...]<sup>2</sup> [...,...]<sup>3</sup>...

- 1 NAME OPT OPT
- 2 NAME
- 3 inherits: \nastavinterakcnimenu

\definujkombinovanyseznam [...]<sup>1</sup> [...,...]<sup>2</sup> [...,...]<sup>3</sup>...

- 1 NAME OPT
- 2 LISTE
- 3 inherits: \nastavseznam

\definujkonverzi [...]<sup>1</sup> [...]<sup>2</sup> [...]<sup>3</sup>

- 1 SPRACHE OPT
- 2 NAME
- 3 CSNAME

\definujkonverzi [...]<sup>1</sup> [...]<sup>2</sup> [...,...]<sup>3</sup>

- 1 SPRACHE OPT
- 2 NAME
- 3 TEXT

\definujnadpis [...]<sup>1</sup> [...]<sup>2</sup> [...,...]<sup>3</sup>...

- 1 NAME OPT OPT
- 2 ABSCHNITT
- 3 inherits: \nastavnadpis

\definujobrazeksymbol [...]<sup>1</sup> [...]<sup>2</sup> [...,...]<sup>3</sup>...

- 1 NAME OPT
- 2 FILE NAME
- 3 inherits: \externiobraz

\definujodkaz [...]<sup>1</sup> [...,...]<sup>2</sup>

- 1 NAME
- 2 REFERENCE

\definujodstavce [...]<sup>1</sup> [...]<sup>2</sup> [...,...]<sup>3</sup>...

- 1 NAME OPT OPT
- 2 NAME
- 3 inherits: \nastavodstavce

\definujopis [...]<sup>1</sup> [...]<sup>2</sup> [...,...]<sup>3</sup>...

- 1 NAME OPT OPT
- 2 NAME
- 3 inherits: \nastavopis

\definujoramovani [...]<sup>1</sup> [...]<sup>2</sup> [...,...]<sup>3</sup>...

- 1 NAME OPT OPT
- 2 NAME
- 3 inherits: \nastavoramovani

\definujoramovanytext [...]<sup>1</sup> [...]<sup>2</sup> [...,...]<sup>3</sup>...

- 1 NAME OPT OPT
- 2 NAME
- 3 inherits: \setupframedtext

\definujpaletu [...]<sup>1</sup> [...,...]<sup>2</sup>...

- 1 NAME
- 2 NAME = COLOR

\definujpaletu [...]<sup>1</sup> [...]<sup>2</sup>

- 1 NAME
- 2 NAME



```

\definujplvouciobjekt [...] [...] [...]
1 SINGULAR
2 SINGULAR PLURAL
3 inherits: \nastavplvouciobjekt
instances: chemical figure table intermezzo graphic

```

```

\definujplvouciobjekt [...] [...] [...]
1 SINGULAR
2 PLURAL
3 SINGULAR
instances: chemical figure table intermezzo graphic

```

```

\definujpodpole [...] [...] [...]
1 NAME
2 NAME
3 NAME

```

```

\definujpole [...] [...] [...] [...] [...]
1 NAME
2 radio pod text radek push check signature
3 NAME
4 NAME
5 NAME

```

```

\definujpopis [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupdescription

```

```

\definujpopisek [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setuplabel

```

```

\definujprekryv [...] [...] [...]
1 NAME
2 NAME
3 BEFEHL

```

```

\definujprikaz ... ..
1 CHARACTER
2 BEFEHL

```

```

\definujprofil [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupprofile

```

```

\definujprogram [...] [...] [...]
1 NAME
2 TEXT
3 TEXT

```

```

\definujprostredizakladnihofontu [...] [...] [...] [...]
1 NAME OPT OPT
2 implicitni DIMENSION
3 velky = DIMENSION NUMMER
male = DIMENSION NUMMER
a = DIMENSION NUMMER
b = DIMENSION NUMMER
c = DIMENSION NUMMER
d = DIMENSION NUMMER
text = DIMENSION NUMMER
x = DIMENSION NUMMER
xx = DIMENSION NUMMER
script = DIMENSION NUMMER
scriptscript = DIMENSION NUMMER
meziradkovamezera = DIMENSION
em = sklonene kurziva STYLE BEFEHL
* = NUMMER

```

```

\definujrejstrik [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \nastavrejstrik

```

```

\definujsablonutabulky [...] [|...] [...] [...]
1 NAME OPT OPT
2 TEMPLATE
3 NAME
4 NAME

```

```

\definujsekci [...]
* NAME

```

```

\definujseznam [...] [...] [...]
1 NAME OPT OPT
2 LISTE
3 inherits: \nastavseznam

```

```

\definujskupinubarev [...] [...] [x:y:z,...]
1 NAME OPT
2 seda rgb cmyk spot
3 TRIPLET

```

```

\definujstartstop [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupstartstop

```

```

\definujstyl [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupstyle

```

```

\definujstylfontu [...] [...]
1 NAME
2 NAME

```

```

\definujsymbol [...] [...] [...]
1 NAME OPT
2 NAME
3 BEFEHL

```

```

\definujsynonumfontu [...] [...] [...] [...]
1 NAME
2 FONT
3 features = NAME
  fallbacks = NAME
  goodies = NAME
  designsize = auto implicitni

```

```

\definujsynonyma [...] [...] [...] [...]
1 SINGULAR
2 PLURAL
3 CSNAME
4 CSNAME

```

```

\definujtabelaci [...] [...] [...]
1 NAME
2 NAME
3 TEMPLATE

```

```

\definujtext [...] [...] [...] [...] [...] [...] [...]
1 NAME
2 vrsek zahlavi text upati spodek
3 text marginalie hrana
4 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
5 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
6 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
7 datum cislostranky BESCHRIFTUNG TEXT BEFEHL

```

```

\definujtrideni [...] [...] [...]
1 SINGULAR
2 PLURAL
3 zadny CSNAME

```

```

\definujupravu [...] [...] [...]
1 NAME
2 NAME
3 inherits: \nastavupravu

```

```

\definujvelikostpapiru [...] [...] [...]
1 NAME
2 sirka = DIMENSION
  vyska = DIMENSION
  vrsek = BEFEHL
  spodek = BEFEHL
  vlevo = BEFEHL
  vpravo = BEFEHL
  vzdalenost = DIMENSION
  stranka = inherits: \nastavvelikostpapiru
  papir = inherits: \nastavvelikostpapiru

```

```

\definujvelikostpapiru [...] [...] [...]
1 NAME
2 inherits: \nastavvelikostpapiru
3 inherits: \nastavvelikostpapiru

```

```

\definujvycet [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupenumeration

```

```

\definujzakladnifont [...] [...] [...] [...]
1 NAME implicitni OPT
2 NAME DIMENSION
3 rm ss tt hw cg
4 tf = FILE
bf = FILE
it = FILE
sl = FILE
bi = FILE
bs = FILE
sc = FILE
mr = FILE
mrlr = FILE
mrrl = FILE
mb = FILE
mblr = FILE
mbrl = FILE

```

```

\definujzakladnifont [...] [...] [...] [...]
1 NAME implicitni OPT
2 NAME DIMENSION
3 rm ss tt hw cg
4 NAME

```

```

\definujzasobnikpoli [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupfieldcategory

```

```

\definujznaceni [...] [...] [...]
1 NAME OPT OPT
2 BESCHRIFTUNG
3 inherits: \nastavznaceni

```

```

\definujznak ... ..
1 CHARACTER
2 NUMMER

```

```

\delimited [...] [...] {...}
1 NAME OPT
2 SPRACHE
3 CONTENT

```

```

\delimitedtext [...] [...] {...}
1 NAME OPT
2 SPRACHE
3 CONTENT

```

```

\DELIMITEDTEXT [...] {...}
1 SPRACHE OPT
2 CONTENT
instances: quotation quote blockquote speech aside

```

```

\delkaseznamu

```

```

\depthofstring {...}
* TEXT

```

```

\depthonlybox {...}
* CONTENT

```

```

\depthspanningtext {...} {...} {...}
1 TEXT
2 DIMENSION
3 FONT

```

<code>\depthstrut</code>
<code>\determinenoflines {...}</code> *   CONTENT
<code>\devanagarinumerals {...}</code> *   NUMMER
<code>\digits {...}</code> *   NUMMER
<code>\digits ...</code> *   NUMMER
<code>\dimensiontocount {...} \^{1}...</code> 1   DIMENSION 2   CSNAME
<code>\directboxfromcache {...} \^{2}...</code> 1   NAME 2   NUMMER TEXT
<code>\directcolor [...]</code> *   COLOR
<code>\directcolored [...,\^{1}...]</code> *   inherits: \definujbarvu
<code>\directcolored [...]</code> *   COLOR
<code>\directconvertedcounter {...} \^{2}...</code> 1   NAME 2   prvni predchozi dalsi posledni cislo
<code>\directcopyboxfromcache {...} \^{2}...</code> 1   NAME 2   NUMMER TEXT
<code>\directdummyparameter {...}</code> *   KEY
<code>\directgetboxllx ...</code> *   CSNAME NUMMER
<code>\directgetboxlly ...</code> *   CSNAME NUMMER
<code>\directhighlight {...} \^{2}...</code> 1   NAME 2   TEXT
<code>\directlocalframed [...]\^{1}...</code> 1   NAME 2   CONTENT
<code>\directluacode {...}</code> *   BEFEHL

$\backslash\text{directselect}$ $\{^1..\}$ $\{^2..\}$ $\{^3..\}$ $\{^4..\}$ $\{^5..\}$ $\{^6..\}$ 1 NAME OPT OPT OPT OPT OPT 2 CONTENT 3 CONTENT 4 CONTENT 5 CONTENT 6 CONTENT
$\backslash\text{directsetbar}$ $\{^*..\}$ * NAME
$\backslash\text{directsetup}$ $\{^*..\}$ * NAME
$\backslash\text{directsymbol}$ $\{^1..\}$ $\{^2..\}$ 1 NAME 2 NAME
$\backslash\text{directvspacing}$ $\{^*..\}$ * inherits: $\backslash\text{vspacing}$
$\backslash\text{dis}$ $\{^*..\}$ * CONTENT
$\backslash\text{disabledirectives}$ $[^*..\]$ * NAME
$\backslash\text{disableexperiments}$ $[^*..\]$ * NAME
$\backslash\text{disablemode}$ $[^*..\]$ * NAME
$\backslash\text{disableoutputstream}$
$\backslash\text{disableparpositions}$
$\backslash\text{disableregime}$
$\backslash\text{disabletrackers}$ $[^*..\]$ * NAME
$\backslash\text{displaymath}$ $\{^*..\}$ * CONTENT
$\backslash\text{displaymathematics}$ $\{^*..\}$ * CONTENT
$\backslash\text{displaymessage}$ $\{^*..\}$ * TEXT
$\backslash\text{distributedhsize}$ $\{^1..\}$ $\{^2..\}$ $\{^3..\}$ 1 DIMENSION 2 DIMENSION 3 NUMMER

<code>\dividedsize {...} {...} {...}</code> 1    DIMENSION 2    DIMENSION 3    NUMMER
<code>\doadaptleftskip {...}</code> *    ano ne standardni DIMENSION
<code>\doadaptrightskip {...}</code> *    ano ne standardni DIMENSION
<code>\doaddfeature {...}</code> *    NAME
<code>\doassign [...<sup>1</sup>] [...<sup>2</sup>...]</code> 1    TEXT 2    KEY = VALUE
<code>\doassignempty [...<sup>1</sup>] [...<sup>2</sup>...]</code> 1    TEXT 2    KEY = VALUE
<code>\doboundtext {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}</code> 1    TEXT 2    DIMENSION 3    BEFEHL
<code>\documentvariable {...}</code> *    KEY
<code>\dodoubleargument \... [...<sup>2</sup>] [...<sup>3</sup>]</code> 1    CSNAME 2    TEXT 3    TEXT
<code>\dodoubleargumentwithset \... [...<sup>2</sup>,...] [...<sup>3</sup>]</code> 1    CSNAME 2    TEXT 3    TEXT
<code>\dodoubleempty \... [...<sup>2</sup>] [...<sup>3</sup>]</code> 1    CSNAME                    OPT            OPT 2    TEXT 3    TEXT
<code>\dodoubleemptywithset \... [...<sup>2</sup>,...] [...<sup>3</sup>]</code> 1    CSNAME                    OPT            OPT 2    TEXT 3    TEXT
<code>\dodoublegroupempty \... {...<sup>2</sup>} {...<sup>3</sup>}</code> 1    CSNAME                    OPT            OPT 2    TEXT 3    TEXT
<code>\doeassign [...<sup>1</sup>] [...<sup>2</sup>...]</code> 1    TEXT 2    KEY = VALUE
<code>\doexpandedrecurse {...<sup>1</sup>} {...<sup>2</sup>}</code> 1    NUMMER 2    BEFEHL

\dofastloopcs {...} \.. 1    NUMBER 2    CSNAME
\dogetattribute {...} *    NAME
\dogetattributeid {...} *    NAME
\dogetcommacommandelement ... \from ... \to ... 1    NUMBER 2    TEXT 3    CSNAME
\dogobbledoubleempty [...] [...] 1    TEXT                    OPT    OPT 2    TEXT
\dogobblesingleempty [...] *    TEXT                    OPT
\docheckassignment {...} *    TEXT
\docheckedpagestate {...} {...} {...} {...} {...} {...} {...} 1    REFERENCE 2    BEFEHL 3    BEFEHL 4    BEFEHL 5    BEFEHL 6    BEFEHL 7    BEFEHL
\docheckedpair {...,*...} *    TEXT
\doif {...} {...} {...} 1    CONTENT 2    CONTENT 3    TRUE
\doifallcommon {..., <sup>1</sup> ...} {..., <sup>2</sup> ...} {... <sup>3</sup> } 1    TEXT 2    TEXT 3    TRUE
\doifallcommonelse {..., <sup>1</sup> ...} {..., <sup>2</sup> ...} {... <sup>3</sup> } {... <sup>4</sup> } 1    TEXT 2    TEXT 3    TRUE 4    FALSE
\doifalldefinedelse {..., <sup>1</sup> ...} {... <sup>2</sup> } {... <sup>3</sup> } 1    NAME 2    TRUE 3    FALSE
\doifallmodes {..., <sup>1</sup> ...} {... <sup>2</sup> } {... <sup>3</sup> } 1    NAME 2    TRUE 3    FALSE



```
\doifallmodeselse {...,1...} {...2} {...3}
```

```
1 NAME  
2 TRUE  
3 FALSE
```

```
\doifassignmentelse {...1} {...2} {...3}
```

```
1 TEXT  
2 TRUE  
3 FALSE
```

```
\doifblackelse {...1} {...2} {...3}
```

```
1 COLOR  
2 TRUE  
3 FALSE
```

```
\doifbothsides {...1} {...2} {...3}
```

```
1 BEFEHL  
2 BEFEHL  
3 BEFEHL
```

```
\doifbothsidesoverruled {...1} {...2} {...3}
```

```
1 BEFEHL  
2 BEFEHL  
3 BEFEHL
```

```
\doifboxelse {...1} {...2} {...3} {...4}
```

```
1 NAME  
2 NAME  
3 TRUE  
4 FALSE
```

```
\doifbufferelse {...1} {...2} {...3}
```

```
1 BUFFER  
2 TRUE  
3 FALSE
```

```
\doifcolor {...1} {...2}
```

```
1 COLOR  
2 TRUE
```

```
\doifcolorelse {...1} {...2} {...3}
```

```
1 COLOR  
2 TRUE  
3 FALSE
```

```
\doifcommandhandler \... {...2} {...3}
```

```
1 CSNAME  
2 NAME  
3 TRUE
```

```
\doifcommandhandlerelse \... {...2} {...3} {...4}
```

```
1 CSNAME  
2 NAME  
3 TRUE  
4 FALSE
```

```
\doifcommon {...,1...} {...,2...} {...3}
```

```
1 TEXT  
2 TEXT  
3 TRUE
```

```
\doifcommonelse {...1,...} {...2,...} {...3} {...4}
1 TEXT
2 TEXT
3 TRUE
4 FALSE
```

```
\doifcontent {...1} {...2} {...3} \... {...5}
1 BEFEHL
2 BEFEHL
3 BEFEHL
4 CSNAME
5 CONTENT
```

```
\doifconversiondefinedelse {...1} {...2} {...3}
1 NAME
2 TRUE
3 FALSE
```

```
\doifconversionnumberelse {...1} {...2} {...3} {...4}
1 NAME
2 NUMMER
3 TRUE
4 FALSE
```

```
\doifcounter {...1} {...2}
1 NAME
2 TRUE
```

```
\doifcounterelse {...1} {...2} {...3}
1 NAME
2 TRUE
3 FALSE
```

```
\doifcurrentfonthasfeatureelse {...1} {...2} {...3}
1 NAME
2 TRUE
3 FALSE
```

```
\doifdefined {...1} {...2}
1 NAME
2 TRUE
```

```
\doifdefinedcounter {...1} {...2}
1 NAME
2 TRUE
```

```
\doifdefinedcounterelse {...1} {...2} {...3}
1 NAME
2 TRUE
3 FALSE
```

```
\doifdefinedelse {...1} {...2} {...3}
1 NAME
2 TRUE
3 FALSE
```

```
\doifdimensionelse {...1} {...2} {...3}
1 TEXT
2 TRUE
3 FALSE
```

```
\doifdimenstringelse {...1} {...2} {...3}
1 TEXT
2 TRUE
3 FALSE
```

\doifdocumentargument {...} {...}

1 NAME  
2 TRUE

\doifdocumentargumentelse {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifdocumentfilename {...} {...}

1 NUMMER  
2 TRUE

\doifdocumentfilenameelse {...} {...} {...}

1 NUMMER  
2 TRUE  
3 FALSE

\doifdrawingblackelse {...} {...}

1 TRUE  
2 FALSE

\doifelse {...} {...} {...} {...}

1 CONTENT  
2 CONTENT  
3 TRUE  
4 FALSE

\doifelseallcommon {...,<sup>1</sup>...} {...,<sup>2</sup>...} {...<sup>3</sup>} {...<sup>4</sup>}

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

\doifelsealldefined {...,<sup>1</sup>...} {...<sup>2</sup>} {...<sup>3</sup>}

1 NAME  
2 TRUE  
3 FALSE

\doifelseallmodes {...,<sup>1</sup>...} {...<sup>2</sup>} {...<sup>3</sup>}

1 NAME  
2 TRUE  
3 FALSE

\doifelseassignment {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

1 TEXT  
2 TRUE  
3 FALSE

\doifelseblack {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

1 COLOR  
2 TRUE  
3 FALSE

\doifelsebox {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} {...<sup>4</sup>}

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

\doifelseboxincache {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} {...<sup>4</sup>}

1 NAME  
2 NUMMER TEXT  
3 TRUE  
4 FALSE

\doifelsebuffer {...} {...} {...}

1 BUFFER  
2 TRUE  
3 FALSE

\doifelsecolor {...} {...} {...}

1 COLOR  
2 TRUE  
3 FALSE

\doifelsecommandhandler {...} {...} {...} {...}

1 CSNAME  
2 NAME  
3 TRUE  
4 FALSE

\doifelsecommon {...,<sup>1</sup>...} {...,<sup>2</sup>...} {...} {...<sup>4</sup>}

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

\doifelseconversiondefined {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelseconversionnumber {...} {...} {...} {...<sup>4</sup>}

1 NAME  
2 NUMMER  
3 TRUE  
4 FALSE

\doifelsecounter {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsecurrentfonthasfeature {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsecurrentsortingused {...} {...}

1 TRUE  
2 FALSE

\doifelsecurrentsynonymshown {...} {...}

1 TRUE  
2 FALSE

\doifelsecurrentsynonymused {...} {...}

1 TRUE  
2 FALSE

\doifelsedefined {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsedefinedcounter {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsedimension {...} {...} {...}

1 TEXT  
2 TRUE  
3 FALSE

\doifelsedimenstring {...} {...} {...}

1 TEXT  
2 TRUE  
3 FALSE

\doifelsedocumentargument {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsedocumentfilename {...} {...} {...}

1 NUMMER  
2 TRUE  
3 FALSE

\doifelsedrawingblack {...} {...}

1 TRUE  
2 FALSE

\doifelseempty {...} {...} {...}

1 CONTENT  
2 TRUE  
3 FALSE

\doifelseemptyvalue {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelseemptyvariable {...} {...} {...} {...}

1 NAME  
2 KEY  
3 TRUE  
4 FALSE

\doifelseenv {...} {...} {...}

1 KEY  
2 TRUE  
3 FALSE

\doifelsefastoptionalcheck {...} {...}

1 TRUE  
2 FALSE

\doifelsefastoptionalcheckcs \^1 \^2

1 CSNAME  
2 CSNAME

\doifelsefieldbody {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsefieldcategory {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsefigure {...} {...} {...}

1 FILE  
2 TRUE  
3 FALSE

\doifelsefile {...} {...} {...}

1 FILE  
2 TRUE  
3 FALSE

\doifelsefiledefined {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsefileexists {...} {...} {...}

1 FILE  
2 TRUE  
3 FALSE

\doifelsefirstchar {...} {...} {...} {...}

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

\doifelseflagged {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsefontchar {...} {...} {...} {...}

1 FONT  
2 NUMMER  
3 TRUE  
4 FALSE

\doifelsefontpresent {...} {...} {...}

1 FONT  
2 TRUE  
3 FALSE

\doifelsefontsynonym {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsehasspace {...} {...} {...}

1 TEXT  
2 TRUE  
3 FALSE

\doifelsehelp {...} {...}

1 TRUE  
2 FALSE

\doifelseincname {...} {...} {...} {...}

1 TEXT  
2 CSNAME  
3 TRUE  
4 FALSE

\doifelseinelement {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelseinputfile {...} {...} {...}

1 FILE  
2 TRUE  
3 FALSE

\doifelseinsertion {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelseinset {...} {...<sup>2</sup>,...} {...} {...<sup>4</sup>}

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

\doifelseinstring {...} {...<sup>2</sup>} {...} {...<sup>4</sup>}

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

\doifelseinsymbolset {...} {...} {...} {...}

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

\doifelseintoks {...} {...} {...} {...}

1 BEFEHL  
2 BEFEHL  
3 TRUE  
4 FALSE

\doifelseintwopassdata {...} {...} {...} {...}

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

\doifelseitalic {...} {...}

1 TRUE  
2 FALSE

\doifelselanguage {...} {...} {...}

1 SPRACHE  
2 TRUE  
3 FALSE

\doifelselayerdata {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelselayoutdefined {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelselayoutsomeline {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelselayouttextline {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelseleapyear {...} {...} {...}

1 NUMBER  
2 TRUE  
3 FALSE

\doifelselist {...} {...} {...}

1 LISTE  
2 TRUE  
3 FALSE

\doifelselocation {...} {...}

1 TRUE  
2 FALSE

\doifelselocfile {...} {...} {...}

1 FILE  
2 TRUE  
3 FALSE

\doifelseMPgraphic {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsemainfloatbody {...} {...}

1 TRUE  
2 FALSE

\doifelsemarking {...} {...} {...}

1 BESCHRIFTUNG  
2 TRUE  
3 FALSE

\doifelsemeaning \<sup>1</sup>... \<sup>2</sup>... {...} {...}

1 CSNAME  
2 CSNAME  
3 TRUE  
4 FALSE

\doifelsemessage {...} {...} {...} {...}

1 NAME  
2 NAME NUMBER  
3 TRUE  
4 FALSE

\doifelsemode {...,<sup>1</sup>...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsenextbgroup {...} {...}

1 TRUE  
2 FALSE



\doifelsenextbgroupcs \<sup>1</sup> \<sup>2</sup>

1 CSNAME  
2 CSNAME

\doifelsenextchar {<sup>1</sup>} {<sup>2</sup>} {<sup>3</sup>}

1 CHARACTER  
2 TRUE  
3 FALSE

\doifelsenextoptional {<sup>1</sup>} {<sup>2</sup>}

1 TRUE  
2 FALSE

\doifelsenextoptionalcs \<sup>1</sup> \<sup>2</sup>

1 CSNAME  
2 CSNAME

\doifelsenextparenthesis {<sup>1</sup>} {<sup>2</sup>}

1 TRUE  
2 FALSE

\doifelsenonzeropositive {<sup>1</sup>} {<sup>2</sup>} {<sup>3</sup>}

1 NUMMER  
2 TRUE  
3 FALSE

\doifelsenoteonsamepage {<sup>1</sup>} {<sup>2</sup>} {<sup>3</sup>}

1 NAME  
2 TRUE  
3 FALSE

\doifelsenothing {<sup>1</sup>} {<sup>2</sup>} {<sup>3</sup>}

1 TEXT  
2 TRUE  
3 FALSE

\doifelsenumber {<sup>1</sup>} {<sup>2</sup>} {<sup>3</sup>}

1 TEXT  
2 TRUE  
3 FALSE

\doifelseobjectfound {<sup>1</sup>} {<sup>2</sup>} {<sup>3</sup>} {<sup>4</sup>}

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

\doifelseobjectreferencefound {<sup>1</sup>} {<sup>2</sup>} {<sup>3</sup>} {<sup>4</sup>}

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

\doifelseoddpag {<sup>1</sup>} {<sup>2</sup>}

1 BEFEHL  
2 BEFEHL

\doifelseoddpagfloat {<sup>1</sup>} {<sup>2</sup>}

1 TRUE  
2 FALSE

\doifelseoldercontext {...} {...} {...}

1 NUMMER  
2 TRUE  
3 FALSE

\doifelseolderversion {...} {...} {...} {...}

1 NUMMER  
2 NUMMER  
3 TRUE  
4 FALSE

\doifelseoverlapping {...} {...} {...} {...}

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

\doifelseoverlay {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelseparallel {...} {...,<sup>2</sup>...} {...} {...}

1 NAME  
2 NAME vse  
3 TRUE  
4 FALSE

\doifelseparentfile {...} {...} {...}

1 FILE  
2 TRUE  
3 FALSE

\doifelsepath {...} {...} {...}

1 PATH  
2 TRUE  
3 FALSE

\doifelsepathexists {...} {...} {...}

1 PATH  
2 TRUE  
3 FALSE

\doifelsepatterns {...} {...} {...}

1 SPRACHE  
2 TRUE  
3 FALSE

\doifelseposition {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsepositionaction {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsepositiononpage {...} {...} {...} {...}

1 NAME  
2 NUMMER  
3 TRUE  
4 FALSE

\doifelsepositionsonsamepage {...<sup>1</sup>,...} {...<sup>2</sup>} {...<sup>3</sup>}

1 NAME  
2 TRUE  
3 FALSE

\doifelsepositionsonthispage {...<sup>1</sup>,...} {...<sup>2</sup>} {...<sup>3</sup>}

1 NAME  
2 TRUE  
3 FALSE

\doifelsepositionsused {...<sup>1</sup>} {...<sup>2</sup>}

1 TRUE  
2 FALSE

\doifelserreferencefound {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

1 REFERENCE  
2 TRUE  
3 FALSE

\doifelserightpagefloat {...<sup>1</sup>} {...<sup>2</sup>}

1 TRUE  
2 FALSE

\doifelserighttopleftinbox ...<sup>1</sup> {...<sup>2</sup>} {...<sup>3</sup>}

1 CSNAME NUMBER  
2 TRUE  
3 FALSE

\doifelsesamelinereference {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

1 REFERENCE  
2 TRUE  
3 FALSE

\doifelsesamestring {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} {...<sup>4</sup>}

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

\doifelsesetups {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

1 NAME  
2 TRUE  
3 FALSE

\doifelsesomebackground {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

1 NAME  
2 TRUE  
3 FALSE

\doifelsesomespace {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

1 TEXT  
2 TRUE  
3 FALSE

\doifelsesomething {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

1 TEXT  
2 TRUE  
3 FALSE

\doifelsesometoks \... {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

1 CSNAME  
2 TRUE  
3 FALSE

\doifelsestringinstring {...} {...} {...} {...}

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

\doifelsestructurelisthasnumber {...} {...}

1 TRUE  
2 FALSE

\doifelsestructurelisthaspage {...} {...}

1 TRUE  
2 FALSE

\doifelsesymboldefined {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsesymbolset {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsetext {...} {...} {...}

1 TEXT  
2 TRUE  
3 FALSE

\doifelsetextflow {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsetextflowcollector {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsetypingfile {...} {...} {...}

1 FILE  
2 TRUE  
3 FALSE

\doifelseundefined {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelseurldefined {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsevalue {...} {...} {...} {...}

1 NAME  
2 TEXT  
3 TRUE  
4 FALSE

\doifelsevaluenothing {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

```
\doifelsevariable {...} {...} {...} {...}
```

```
1 NAME  
2 KEY  
3 TRUE  
4 FALSE
```

```
\doifempty {...} {...}
```

```
1 CONTENT  
2 TRUE
```

```
\doifemptyelse {...} {...} {...}
```

```
1 CONTENT  
2 TRUE  
3 FALSE
```

```
\doifemptytoks \^1. \^2.
```

```
1 CSNAME  
2 TRUE
```

```
\doifemptyvalue {...} {...}
```

```
1 NAME  
2 TRUE
```

```
\doifemptyvalueelse {...} {...} {...}
```

```
1 NAME  
2 TRUE  
3 FALSE
```

```
\doifemptyvariable {...} {...} {...}
```

```
1 NAME  
2 KEY  
3 TRUE
```

```
\doifemptyvariableelse {...} {...} {...} {...}
```

```
1 NAME  
2 KEY  
3 TRUE  
4 FALSE
```

```
\doifenv {...} {...}
```

```
1 KEY  
2 TRUE
```

```
\doifenvelse {...} {...} {...}
```

```
1 KEY  
2 TRUE  
3 FALSE
```

```
\doiffastoptionalcheckcseelse \^1. \^2.
```

```
1 CSNAME  
2 CSNAME
```

```
\doiffastoptionalcheckelse {...} {...}
```

```
1 TRUE  
2 FALSE
```

```
\doiffieldbodyelse {...} {...} {...}
```

```
1 NAME  
2 TRUE  
3 FALSE
```

\doiffielddcategoryelse {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doiffigureelse {...} {...} {...}

1 FILE  
2 TRUE  
3 FALSE

\doiffile {...} {...}

1 FILE  
2 TRUE

\doiffiledefinedelse {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doiffileelse {...} {...} {...}

1 FILE  
2 TRUE  
3 FALSE

\doiffileexistselse {...} {...} {...}

1 FILE  
2 TRUE  
3 FALSE

\doiffirstcharelse {...} {...} {...} {...}

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

\doifflaggedelse {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doiffontcharelse {...} {...} {...} {...}

1 FONT  
2 NUMMER  
3 TRUE  
4 FALSE

\doiffontpresentelse {...} {...} {...}

1 FONT  
2 TRUE  
3 FALSE

\doiffontsynonymelse {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifhasspaceelse {...} {...} {...}

1 TEXT  
2 TRUE  
3 FALSE

\doifhelpelse {...} {...}

1 TRUE  
2 FALSE

```
\doifincsnameelse {...} {...} {...} {...}
1 TEXT
2 CSNAME
3 TRUE
4 FALSE
```

```
\doifinelementelse {...} {...} {...}
1 NAME
2 TRUE
3 FALSE
```

```
\doifinputfileelse {...} {...} {...}
1 FILE
2 TRUE
3 FALSE
```

```
\doifinsetionelse {...} {...} {...}
1 NAME
2 TRUE
3 FALSE
```

```
\doifinset {...} {...,2...} {...}
1 TEXT
2 TEXT
3 TRUE
```

```
\doifinsetelse {...} {...,2...} {...} {...}
1 TEXT
2 TEXT
3 TRUE
4 FALSE
```

```
\doifinstring {...} {...} {...}
1 TEXT
2 TEXT
3 TRUE
```

```
\doifinstringelse {...} {...} {...} {...}
1 TEXT
2 TEXT
3 TRUE
4 FALSE
```

```
\doifinsymbolset {...} {...} {...} {...}
1 NAME
2 NAME
3 TRUE
4 FALSE
```

```
\doifinsymbolsetelse {...} {...} {...} {...}
1 NAME
2 NAME
3 TRUE
4 FALSE
```

```
\doifintokselse {...} {...} {...} {...}
1 BEFEHL
2 BEFEHL
3 TRUE
4 FALSE
```

```
\doifintwopassdataelse {...} {...} {...} {...}
1 NAME
2 NAME
3 TRUE
4 FALSE
```

`\doifitalicelse {...} {...}`

1 TRUE  
2 FALSE

`\doiflanguageelse {...} {...} {...}`

1 SPRACHE  
2 TRUE  
3 FALSE

`\doiflayerdataelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doiflayoutdefinedelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doiflayoutsomelineelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doiflayouttextlineelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifleapyearelse {...} {...} {...}`

1 NUMMER  
2 TRUE  
3 FALSE

`\doiflistelse {...} {...} {...}`

1 LISTE  
2 TRUE  
3 FALSE

`\doiflocationelse {...} {...}`

1 TRUE  
2 FALSE

`\doiflocfileelse {...} {...} {...}`

1 FILE  
2 TRUE  
3 FALSE

`\doifMPgraphicelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifmainfloatbodyelse {...} {...}`

1 TRUE  
2 FALSE

`\doifmarkingelse {...} {...} {...}`

1 BESCHRIFTUNG  
2 TRUE  
3 FALSE



\doifmeaningelse \<sup>1</sup>... \<sup>2</sup>... {\<sup>3</sup>...} {\<sup>4</sup>...}

1 CSNAME  
2 CSNAME  
3 TRUE  
4 FALSE

\doifmessageelse {\<sup>1</sup>...} {\<sup>2</sup>...} {\<sup>3</sup>...} {\<sup>4</sup>...}

1 NAME  
2 NAME NUMBER  
3 TRUE  
4 FALSE

\doifmode {\<sup>1</sup>...,\<sup>2</sup>...} {\<sup>3</sup>...}

1 NAME  
2 TRUE

\doifmodeelse {\<sup>1</sup>...,\<sup>2</sup>...} {\<sup>3</sup>...} {\<sup>4</sup>...}

1 NAME  
2 TRUE  
3 FALSE

\doifnextbgroupcelse \<sup>1</sup>... \<sup>2</sup>...

1 CSNAME  
2 CSNAME

\doifnextbgroupelse {\<sup>1</sup>...} {\<sup>2</sup>...}

1 TRUE  
2 FALSE

\doifnextcharelse {\<sup>1</sup>...} {\<sup>2</sup>...} {\<sup>3</sup>...}

1 CHARACTER  
2 TRUE  
3 FALSE

\doifnextoptionalcelse \<sup>1</sup>... \<sup>2</sup>...

1 CSNAME  
2 CSNAME

\doifnextoptionalelse {\<sup>1</sup>...} {\<sup>2</sup>...}

1 TRUE  
2 FALSE

\doifnextparenthesiselse {\<sup>1</sup>...} {\<sup>2</sup>...}

1 TRUE  
2 FALSE

\doifnonzeropositiveelse {\<sup>1</sup>...} {\<sup>2</sup>...} {\<sup>3</sup>...}

1 NUMMER  
2 TRUE  
3 FALSE

\doifnot {\<sup>1</sup>...} {\<sup>2</sup>...} {\<sup>3</sup>...}

1 CONTENT  
2 CONTENT  
3 TRUE

\doifnotallcommon {\<sup>1</sup>...,\<sup>2</sup>...} {\<sup>3</sup>...} {\<sup>4</sup>...}

1 TEXT  
2 TEXT  
3 TRUE

\doifnotallmodes {...<sup>1</sup>,...} {...<sup>2</sup>} {...<sup>3</sup>}

1 NAME  
2 TRUE  
3 FALSE

\doifnotcommandhandler \... {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

1 CSNAME  
2 NAME  
3 TRUE

\doifnotcommon {...<sup>1</sup>,...} {...<sup>2</sup>,...} {...<sup>3</sup>}

1 TEXT  
2 TEXT  
3 TRUE

\doifnotcounter {...<sup>1</sup>} {...<sup>2</sup>}

1 NAME  
2 TRUE

\doifnotdocumentargument {...<sup>1</sup>} {...<sup>2</sup>}

1 NAME  
2 TRUE

\doifnotdocumentfilename {...<sup>1</sup>} {...<sup>2</sup>}

1 NUMMER  
2 TRUE

\doifnotempty {...<sup>1</sup>} {...<sup>2</sup>}

1 CONTENT  
2 TRUE

\doifnotemptyvalue {...<sup>1</sup>} {...<sup>2</sup>}

1 NAME  
2 TRUE

\doifnotemptyvariable {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

1 NAME  
2 KEY  
3 TRUE

\doifnotenv {...<sup>1</sup>} {...<sup>2</sup>}

1 KEY  
2 TRUE

\doifnoteonsamepageelse {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

1 NAME  
2 TRUE  
3 FALSE

\doifnotescollected {...<sup>1</sup>} {...<sup>2</sup>}

1 NAME  
2 TRUE

\doifnotfile {...<sup>1</sup>} {...<sup>2</sup>}

1 FILE  
2 TRUE

\doifnotflagged {...<sup>1</sup>} {...<sup>2</sup>}

1 NAME  
2 TRUE

<pre> \doifnothing {...} {...} 1 TEXT 2 TRUE </pre>
<pre> \doifnothingelse {...} {...} {...} 1 TEXT 2 TRUE 3 FALSE </pre>
<pre> \doifnotinset {...} {...,<sup>2</sup>...} {...} 1 TEXT 2 TEXT 3 TRUE </pre>
<pre> \doifnotinfloat {...} * TRUE </pre>
<pre> \doifnotinstring {...} {...} {...} 1 TEXT 2 TEXT 3 TRUE </pre>
<pre> \doifnotmode {...,<sup>1</sup>...} {...} 1 NAME 2 TRUE </pre>
<pre> \doifnotnumber {...} {...} 1 TEXT 2 TRUE </pre>
<pre> \doifnotsamestring {...} {...} {...} 1 TEXT 2 TEXT 3 TRUE </pre>
<pre> \doifnotsetups {...} {...} 1 NAME 2 TRUE </pre>
<pre> \doifnotvalue {...} {...} {...} 1 NAME 2 TEXT 3 TRUE </pre>
<pre> \doifnotvariable {...} {...} {...} 1 NAME 2 KEY 3 TRUE </pre>
<pre> \doifnumber {...} {...} 1 TEXT 2 TRUE </pre>
<pre> \doifnumberelse {...} {...} {...} 1 TEXT 2 TRUE 3 FALSE </pre>
<pre> \doifobjectfoundelse {...} {...} {...} {...} 1 NAME 2 NAME 3 TRUE 4 FALSE </pre>

```
\doifobjectreferencefoundelse {...} {...} {...} {...}
```

```
1 NAME  
2 NAME  
3 TRUE  
4 FALSE
```

```
\doifoddpagelse {...} {...}
```

```
1 BEFEHL  
2 BEFEHL
```

```
\doifoddpagefloatelse {...} {...}
```

```
1 TRUE  
2 FALSE
```

```
\doifoldercontextelse {...} {...} {...}
```

```
1 NUMMER  
2 TRUE  
3 FALSE
```

```
\doifolderversionelse {...} {...} {...} {...}
```

```
1 NUMMER  
2 NUMMER  
3 TRUE  
4 FALSE
```

```
\doifoverlappingelse {...} {...} {...} {...}
```

```
1 NAME  
2 NAME  
3 TRUE  
4 FALSE
```

```
\doifoverlayelse {...} {...} {...}
```

```
1 NAME  
2 TRUE  
3 FALSE
```

```
\doifparallelelse {...} {...,  
2,...} {...} {...}
```

```
1 NAME  
2 NAME vse  
3 TRUE  
4 FALSE
```

```
\doifparentfileelse {...} {...} {...}
```

```
1 FILE  
2 TRUE  
3 FALSE
```

```
\doifpathelse {...} {...} {...}
```

```
1 PATH  
2 TRUE  
3 FALSE
```

```
\doifpathexistseelse {...} {...} {...}
```

```
1 PATH  
2 TRUE  
3 FALSE
```

```
\doifpatternselse {...} {...} {...}
```

```
1 SPRACHE  
2 TRUE  
3 FALSE
```

\doifposition {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifpositionaction {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifpositionactionelse {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifpositionelse {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifpositiononpageelse {...} {...} {...} {...}

1 NAME  
2 NUMMER  
3 TRUE  
4 FALSE

\doifpositionsonsamepageelse {...,<sup>1</sup>...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifpositionsonthispageelse {...,<sup>1</sup>...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifpositionsusedelse {...} {...}

1 TRUE  
2 FALSE

\doifreferencefoundelse {...} {...} {...}

1 REFERENCE  
2 TRUE  
3 FALSE

\doifrightpagefloatelse {...} {...}

1 TRUE  
2 FALSE

\doifrighttopleftinboxelse <sup>1</sup>... {...} {...}

1 CSNAME NUMMER  
2 TRUE  
3 FALSE

\doifsamelinereferenceelse {...} {...} {...}

1 REFERENCE  
2 TRUE  
3 FALSE

\doifsamestring {...} {...} {...}

1 TEXT  
2 TEXT  
3 TRUE

```
\doifsamestringelse {...} {...} {...} {...}
1 TEXT
2 TEXT
3 TRUE
4 FALSE
```

```
\doifsetups {...} {...}
1 NAME
2 TRUE
```

```
\doifsetupself {...} {...} {...}
1 NAME
2 TRUE
3 FALSE
```

```
\doifsomebackground {...} {...} {...}
1 NAME
2 TRUE
3 FALSE
```

```
\doifsomebackgroundelse {...} {...} {...}
1 NAME
2 TRUE
3 FALSE
```

```
\doifsomespaceelse {...} {...} {...}
1 TEXT
2 TRUE
3 FALSE
```

```
\doifsomething {...} {...}
1 TEXT
2 TRUE
```

```
\doifsomethingelse {...} {...} {...}
1 TEXT
2 TRUE
3 FALSE
```

```
\doifsometoks \... {...}
1 CSNAME
2 TRUE
```

```
\doifsometokselse \... {...} {...}
1 CSNAME
2 TRUE
3 FALSE
```

```
\doifstringinstringelse {...} {...} {...} {...}
1 TEXT
2 TEXT
3 TRUE
4 FALSE
```

```
\doifstructurelisthasnumberelse {...} {...}
1 TRUE
2 FALSE
```

```
\doifstructurelisthaspageelse {...} {...}
1 TRUE
2 FALSE
```

`\doifsymboldefinedelse {1.} {2.} {3.}`

1 NAME  
2 TRUE  
3 FALSE

`\doifsymbolsetelse {1.} {2.} {3.}`

1 NAME  
2 TRUE  
3 FALSE

`\doiftext {1.} {2.} {3.}`

1 TEXT  
2 TRUE  
3 FALSE

`\doiftextelse {1.} {2.} {3.}`

1 TEXT  
2 TRUE  
3 FALSE

`\doiftextflowcollectorelse {1.} {2.} {3.}`

1 NAME  
2 TRUE  
3 FALSE

`\doiftextflowelse {1.} {2.} {3.}`

1 NAME  
2 TRUE  
3 FALSE

`\doiftypingfileelse {1.} {2.} {3.}`

1 FILE  
2 TRUE  
3 FALSE

`\doifundefined {1.} {2.}`

1 NAME  
2 TRUE

`\doifundefinedcounter {1.} {2.}`

1 NAME  
2 TRUE

`\doifundefinedelse {1.} {2.} {3.}`

1 NAME  
2 TRUE  
3 FALSE

`\doifurldefinedelse {1.} {2.} {3.}`

1 NAME  
2 TRUE  
3 FALSE

`\doifvalue {1.} {2.} {3.}`

1 NAME  
2 TEXT  
3 TRUE

`\doifvalueelse {1.} {2.} {3.} {4.}`

1 NAME  
2 TEXT  
3 TRUE  
4 FALSE

<code>\doifvaluenothing {...} {...}</code> 1 NAME 2 TRUE
<code>\doifvaluenothingelse {...} {...} {...}</code> 1 NAME 2 TRUE 3 FALSE
<code>\doifvaluesomething {...} {...}</code> 1 NAME 2 TRUE
<code>\doifvariable {...} {...} {...}</code> 1 NAME 2 KEY 3 TRUE
<code>\doifvariableelse {...} {...} {...} {...}</code> 1 NAME 2 KEY 3 TRUE 4 FALSE
<code>\doindentation</code>
<code>\dollar</code>
<code>\doloop {...}</code> * BEFEHL
<code>\doloopoverlist {...,<sup>1</sup>...} {...}</code> 1 TEXT 2 BEFEHL
<code>\donothing</code>
<code>\dontconvertfont</code>
<code>\dontleavehmode</code>
<code>\dontpermitspacesbetweenegroups</code>
<code>\dopositionaction {...}</code> * NAME
<code>\doprocesslocalsetups {...,*...}</code> * NAME
<code>\doquadrupleargument \... [<sup>2</sup>...] [<sup>3</sup>...] [<sup>4</sup>...] [<sup>5</sup>...]</code> 1 CSNAME 2 TEXT 3 TEXT 4 TEXT 5 TEXT



`\doquadrupleempty \1... [2...] [3...] [4...] [5...]`

1 CSNAME  
2 TEXT  
3 TEXT  
4 TEXT  
5 TEXT

OPT OPT OPT OPT

`\doquadruplegroupempty \1... {2...} {3...} {4...} {5...}`

1 CSNAME  
2 TEXT  
3 TEXT  
4 TEXT  
5 TEXT

OPT OPT OPT OPT

`\doquintupleargument \1... [2...] [3...] [4...] [5...] [6...]`

1 CSNAME  
2 TEXT  
3 TEXT  
4 TEXT  
5 TEXT  
6 TEXT

`\doquintupleempty \1... [2...] [3...] [4...] [5...] [6...]`

1 CSNAME  
2 TEXT  
3 TEXT  
4 TEXT  
5 TEXT  
6 TEXT

OPT OPT OPT OPT OPT

`\doquintuplegroupempty \1... {2...} {3...} {4...} {5...} {6...}`

1 CSNAME  
2 TEXT  
3 TEXT  
4 TEXT  
5 TEXT  
6 TEXT

OPT OPT OPT OPT OPT

`\dorecurse {1...} {2...}`

1 NUMMER  
2 BEFEHL

`\dorechecknextindentation`

`\dorepeatwithcommand [1...] \2...`

1 TEXT NUMMER\*TEXT  
2 CSNAME

`\doreplacefeature {.*...}`

\* NAME

`\doresetandafffeature {.*...}`

\* NAME

`\doresetattribute {.*...}`

\* NAME

`\dorotatebox {1...} \2... {3...}`

1 NUMMER  
2 CSNAME  
3 CONTENT

`\dosetattribute {1...} {2...}`

1 NAME  
2 NUMMER

`\dosetleftskipadaption {...}`

\* ano ne standardni DIMENSION

`\dosetrighskipadaption {...}`

\* ano ne standardni DIMENSION

`\dosetupcheckedinterlinespace {...,*=...}`

\* inherits: \nastavmeziradkovoumezeru

`\dosetupcheckedinterlinespace {...,*...}`

\* zap vyp reset auto male stredni velke NUMMER DIMENSION

`\dosetupcheckedinterlinespace {...}`

\* NAME

`\doseventupleargument \1... [2...] [3...] [4...] [5...] [6...] [7...] [8...]`

1 CSNAME  
2 TEXT  
3 TEXT  
4 TEXT  
5 TEXT  
6 TEXT  
7 TEXT  
8 TEXT

`\doseventupleempty \1... [2...] [3...] [4...] [5...] [6...] [7...] [8...]`

1 CSNAME  
2 TEXT  
3 TEXT  
4 TEXT  
5 TEXT  
6 TEXT  
7 TEXT  
8 TEXT

`\dosingleargument \1... [2...]`

1 CSNAME  
2 TEXT

`\dosingleempty \1... [2...]`

1 CSNAME  
2 TEXT

`\dosinglegroupempty \1... {2...}`

1 CSNAME  
2 TEXT

`\dosixtupleargument \1... [2...] [3...] [4...] [5...] [6...] [7...]`

1 CSNAME  
2 TEXT  
3 TEXT  
4 TEXT  
5 TEXT  
6 TEXT  
7 TEXT

`\dosixtupleempty \1... [2...] [3...] [4...] [5...] [6...] [7...]`

1 CSNAME  
2 TEXT  
3 TEXT  
4 TEXT  
5 TEXT  
6 TEXT  
7 TEXT

$\backslash\text{dostarttagged } \{.^1.\} \{.^2.\} \dots \backslash\text{dostoptagged}$ 1 NAME 2 NAME
$\backslash\text{dostepwiserecurse } \{.^1.\} \{.^2.\} \{.^3.\} \{.^4.\}$ 1 NUMBER 2 NUMBER 3 [-+]NUMBER 4 BEFEHL
$\backslash\text{dosubtractfeature } \{.^*.\}$ * NAME
$\backslash\text{dotfskip } \{.^*.\}$ * DIMENSION
$\backslash\text{dotoks } \backslash.^*.$ * CSNAME
$\backslash\text{dotripleargument } \backslash.^1. [.^2.] [.^3.] [.^4.]$ 1 CSNAME 2 TEXT 3 TEXT 4 TEXT
$\backslash\text{dotripleargumentwithset } \backslash.^1. [...,^2...] [.^3.] [.^4.]$ 1 CSNAME 2 TEXT 3 TEXT 4 TEXT
$\backslash\text{dotripleempty } \backslash.^1. [.^2.] [.^3.] [.^4.]$ 1 CSNAME 2 TEXT 3 TEXT 4 TEXT
$\backslash\text{dotripleemptywithset } \backslash.^1. [...,^2...] [.^3.] [.^4.]$ 1 CSNAME 2 TEXT 3 TEXT 4 TEXT
$\backslash\text{dotriplegroupempty } \backslash.^1. \{.^2.\} \{.^3.\} \{.^4.\}$ 1 CSNAME 2 TEXT 3 TEXT 4 TEXT
$\backslash\text{doublebar } \{.^*.\}$ * TEXT
$\backslash\text{doublebond}$
$\backslash\text{doublebrace } \{.^*.\}$ * TEXT
$\backslash\text{doublebracket } \{.^*.\}$ * TEXT
$\backslash\text{doubleparent } \{.^*.\}$ * TEXT

<code>\dowith {...,<sup>1</sup>...} {<sup>2</sup>...}</code> 1 BEFEHL 2 BEFEHL
<code>\dowithnextbox {<sup>1</sup>...} \<sup>2</sup>... {<sup>3</sup>...}</code> 1 BEFEHL 2 CSNAME 3 CONTENT
<code>\dowithnextboxcontent {<sup>1</sup>...} {<sup>2</sup>...} \<sup>3</sup>... {<sup>4</sup>...}</code> 1 BEFEHL 2 BEFEHL 3 CSNAME 4 CONTENT
<code>\dowithnextboxcontentcs \<sup>1</sup>... \<sup>2</sup>... \<sup>3</sup>... {<sup>4</sup>...}</code> 1 CSNAME 2 CSNAME 3 CSNAME 4 CONTENT
<code>\dowithnextboxcs \<sup>1</sup>... \<sup>2</sup>... {<sup>3</sup>...}</code> 1 CSNAME 2 CSNAME 3 CONTENT
<code>\dowithpargument \<sup>*</sup>...</code> * CSNAME
<code>\dowithrange {...,<sup>1</sup>...} \<sup>2</sup>...</code> 1 NUMMER NUMMER:NUMMER 2 CSNAME
<code>\dowithwargument \<sup>*</sup>...</code> * CSNAME
<code>\dpofstring {<sup>*</sup>...}</code> * TEXT
<code>\dummydigit</code>
<code>\dummysparameter {<sup>*</sup>...}</code> * KEY
<code>\ETEX</code>
<code>\EveryLine {<sup>*</sup>...}</code> * BEFEHL
<code>\EveryPar {<sup>*</sup>...}</code> * BEFEHL
<code>\edefconvertedargument \<sup>1</sup>... {<sup>2</sup>...}</code> 1 CSNAME 2 TEXT
<code>\efcmxheight {<sup>*</sup>...}</code> * NAME

<code>\efcmaxwidth {...}</code> *    NAME
<code>\efcminheight {...}</code> *    NAME
<code>\efcminwidth {...}</code> *    NAME
<code>\efcparameter {...} {...}</code> 1    NAME 2    KEY
<code>\effect [...] {...}</code> 1    NAME 2    CONTENT
<code>\elapsedseconds</code>
<code>\elapsedtime</code>
<code>\leftarrowfill {...} {...}</code> 1    TEXT                    OPT        OPT 2    TEXT
<code>\leftharpoondownfill {...} {...}</code> 1    TEXT                    OPT        OPT 2    TEXT
<code>\leftharpoonupfill {...} {...}</code> 1    TEXT                    OPT        OPT 2    TEXT
<code>\leftrightarrowfill {...} {...}</code> 1    TEXT                    OPT        OPT 2    TEXT
<code>\emphasisboldface</code>
<code>\emphasistypeface</code>
<code>\emptylines [...]</code> *    NUMMER                OPT
<code>\emspace</code>
<code>\enabledirectives [...,*,...]</code> *    NAME
<code>\enableexperiments [...,*,...]</code> *    NAME
<code>\enablemode [...,*,...]</code> *    NAME
<code>\enableoutputstream [...]</code> *    NAME

<code>\enableparpositions</code>
<code>\enableregime [...]</code> * cp1250 cp1251 cp1252 cp1253 cp1254 cp1255 cp1256 cp1257 cp1258 8859-1 8859-2 8859-3 8859-4 8859-9 8859-10 8859-13 8859-14 8859-15 8859-16 utf windows-1250 windows-1251 windows-1252 windows-1253 windows-1254 windows-1255 windows-1256 windows-1257 windows-1258 il1 il2 il3 il4 il5 il6 il7 il8 il9 il10 iso-8859-1 iso-8859-2 iso-8859-3 iso-8859-4 iso-8859-9 iso-8859-10 iso-8859-13 iso-8859-14 iso-8859-15 iso-8859-16 latin1 latin2 latin3 latin4 latin5 latin6 latin7 latin8 latin9 latin10 utf-8 utf8 windows
<code>\enabletrackers [...,*,...]</code> * NAME
<code>\enskip</code>
<code>\enspace</code>
<code>\env {...}</code> * KEY
<code>\envvar {...} {...}</code> 1 KEY 2 BEFEHL
<code>\eoverbarfill {...} {...}</code> 1 TEXT OPT OPT 2 TEXT
<code>\eoverbracefill {...} {...}</code> 1 TEXT OPT OPT 2 TEXT
<code>\eoverbracketfill {...} {...}</code> 1 TEXT OPT OPT 2 TEXT
<code>\eoverparentfill {...} {...}</code> 1 TEXT OPT OPT 2 TEXT
<code>\epos {...}</code> * NAME
<code>\equaldigits {...}</code> * TEXT
<code>\erightarrowfill {...} {...}</code> 1 TEXT OPT OPT 2 TEXT
<code>\erightharpoondownfill {...} {...}</code> 1 TEXT OPT OPT 2 TEXT
<code>\erightharpoonupfill {...} {...}</code> 1 TEXT OPT OPT 2 TEXT
<code>\eTeX</code>

`\etwoheadrightarrowfill {...} {...}`

1 TEXT OPT OPT  
2 TEXT

`\eunderbarfill {...} {...}`

1 TEXT OPT OPT  
2 TEXT

`\eunderbracefill {...} {...}`

1 TEXT OPT OPT  
2 TEXT

`\eunderbracketfill {...} {...}`

1 TEXT OPT OPT  
2 TEXT

`\eunderparentfill {...} {...}`

1 TEXT OPT OPT  
2 TEXT

`\executeifdefined {...} {...}`

1 NAME  
2 BEFEHL

`\exitloop`

`\exitloopnow`

`\expanded {...}`

\* CONTENT

`\expandfontsynonym \1... {2...}`

1 CSNAME  
2 NAME

`\expandcheckedcsname \1... {2...} {3...}`

1 CSNAME  
2 KEY  
3 TEXT

`\expdoif {1...} {2...} {3...}`

1 CONTENT  
2 CONTENT  
3 TRUE

`\expdoifcommonelse {...,1...} {...,2...} {3...} {4...}`

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

`\expdoifelse {1...} {2...} {3...} {4...}`

1 CONTENT  
2 CONTENT  
3 TRUE  
4 FALSE

`\expdoifelsecommon {...,1...} {...,2...} {3...} {4...}`

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

```
\expdoifelseinset {...1.} {...2,...} {...3.} {...4.}
1 TEXT
2 TEXT
3 TRUE
4 FALSE
```

```
\expdoifinsetelse {...1} {...2,...} {...3} {...4}
```

```
1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE
```

```
\expdoifnot {.1.} {.2.} {.3.}
1  CONTENT
2  CONTENT
3  TRUE
```

```
\externalfigurecollectionmaxheight {...}
* NAME
```

```
\externalfigurecollectionmaxwidth {...}
* NAME
```

```
\externalfigurecollectionminheight {...}
* NAME
```

```
\externalfigurecollectionminwidth {...}
* NAME
```

```
\externalfigurecollectionparameter {...} {...}
```

- 1 NAME
- 2 KEY

```
\externiobraz [1...] [2...] [...,3...,...]
```

```
1 FILE OPT OPT  
2 NAME  
3 inherits: \setupexternalfigure
```

```
\fakebox ...
* CSNAME NUMBER
```

```
\fastdecrement \*..
* CSNAME
```

```
\fastincrement \*...
* CSNAME
```

```
\fastlocalframed [.1.] [..2..3.] {..3.}
1 NAME
2 inherits: \nastavoramovani
3 CONTENT
```

\fastloopfinal
----------------

\fastloopindex
----------------

```
\fastscale {.^..} {.^..}
```

1    NUMBER

2    CONTENT



\fastsetup {...} *   NAME
\fastsetupwithargument {...} {...} 1   NAME 2   CONTENT
\fastsetupwithargumentswapped {...} {...} 1   CONTENT 2   NAME
\fastswitchtobodyfont {...} *   x xx male velke script scriptscript
\fastsxsy {...} {...} {...} 1   NUMMER 2   NUMMER 3   CONTENT
\feature [...] [...] 1   + - = ! > < more less novy reset implicitni old lokalne 2   NAME
\feature {...} {...} 1   + - = ! > < more less novy reset implicitni old lokalne 2   NAME
\fence
\fenced [...] [...] 1   NAME 2   CONTENT
\FENCE {...} *   CONTENT
\fetchallmarkings [...] [...] 1   BESCHRIFTUNG 2   stranka NAME
\fetchallmarks [...] *   BESCHRIFTUNG
\fetchmark [...] [...] 1   BESCHRIFTUNG       OPT 2   prvni posledni aktualni predchozi dalsi vrsek spodek implicitni obe vse first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck
\fetchmarking [...] [...] [...] 1   BESCHRIFTUNG 2   stranka NAME 3   prvni posledni aktualni predchozi dalsi vrsek spodek implicitni obe vse first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck
\fetchonemark [...] [...] 1   BESCHRIFTUNG       OPT 2   prvni posledni aktualni predchozi dalsi vrsek spodek implicitni obe vse first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck

<code>\fetchonemarking [...] [...] [...]</code> 1 BESCHRIFTUNG 2 stranka NAME 3 prvni posledni aktualni predchozi dalsi vrsek spodek implicitni obe vse first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck
<code>\fetchruntimecommand \.^ {^}</code> 1 CSNAME 2 FILE
<code>\fetchtwomarkings [...] [...]</code> 1 BESCHRIFTUNG 2 stranka NAME
<code>\fetchtwomarks [...]</code> * BESCHRIFTUNG
<code>\fieldbody [...] [...,..<sup>2</sup>...,...]</code> 1 NAME <small>OPT</small> 2 inherits: \setupfieldbody
<code>\fifthoffivearguments {^} {^} {^} {^} {^}</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT
<code>\fifthofsixarguments {^} {^} {^} {^} {^} {^}</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT
<code>\figurefilename</code>
<code>\figurefilepath</code>
<code>\figurefiletype</code>
<code>\figurefullname</code>
<code>\figureheight</code>
<code>\figurenaturalheight</code>
<code>\figurenaturalwidth</code>
<code>\figuresymbol [...] [...,..<sup>2</sup>...,...]</code> 1 FILE NAME <small>OPT</small> 2 inherits: \externiobraz
<code>\figurewidth</code>
<code>\filename {^}</code> * FILE

<pre> \filledhboxb <sup>1</sup>... {<sup>2</sup>...} 1 TEXT OPT 2 CONTENT </pre>
<pre> \filledhboxc <sup>1</sup>... {<sup>2</sup>...} 1 TEXT OPT 2 CONTENT </pre>
<pre> \filledhboxg <sup>1</sup>... {<sup>2</sup>...} 1 TEXT OPT 2 CONTENT </pre>
<pre> \filledhboxk <sup>1</sup>... {<sup>2</sup>...} 1 TEXT OPT 2 CONTENT </pre>
<pre> \filledhboxm <sup>1</sup>... {<sup>2</sup>...} 1 TEXT OPT 2 CONTENT </pre>
<pre> \filledhboxr <sup>1</sup>... {<sup>2</sup>...} 1 TEXT OPT 2 CONTENT </pre>
<pre> \filledhboxy <sup>1</sup>... {<sup>2</sup>...} 1 TEXT OPT 2 CONTENT </pre>
<pre> \filler [...] * sym symbol linka sirka mezera NAME </pre>
<pre> \filterfromnext {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...} {<sup>4</sup>...} {<sup>5</sup>...} {<sup>6</sup>...} {<sup>7</sup>...} 1 NUMMER OPT OPT OPT OPT OPT 2 NUMMER 3 CONTENT 4 CONTENT 5 CONTENT 6 CONTENT 7 CONTENT </pre>
<pre> \filterfromvalue {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...} 1 NAME 2 NUMMER 3 NUMMER </pre>
<pre> \filterpages [...]<sup>1</sup> [...,<sup>2</sup>...] [...,<sup>3</sup>...,...]<sup>OPT</sup> 1 FILE 2 sude liche NUMMER NUMMER:NUMMER 3 sirka = DIMENSION n = NUMMER category = NAME </pre>
<pre> \filterreference {.*} * implicitni text titul cislo stranka realpage </pre>
<pre> \findtwopassdata {<sup>1</sup>...} {<sup>2</sup>...} 1 NAME 2 NAME </pre>

```
\finishregisterentry [...]1 [...,...2...,...]2 [...,...3...,...]3
1 NAME OPT
2 popisek = NAME
keys = TEXT PROCESSOR->TEXT
entries = TEXT PROCESSOR->TEXT
alternativa = TEXT
3 KEY = VALUE
```

```
\firstcounter [...]1 [...]2
1 NAME OPT
2 NUMMER
```

```
\firstcountervalue [...]*
* NAME
```

```
\firstcharacter
```

```
\firstoffivearguments {...}1 {...}2 {...}3 {...}4 {...}5
1 TEXT
2 TEXT
3 TEXT
4 TEXT
5 TEXT
```

```
\firstoffourarguments {...}1 {...}2 {...}3 {...}4
1 TEXT
2 TEXT
3 TEXT
4 TEXT
```

```
\firstofoneargument {...}*
* TEXT
```

```
\firstofoneunexpanded {...}*
* TEXT
```

```
\firstofsixarguments {...}1 {...}2 {...}3 {...}4 {...}5 {...}6
1 TEXT
2 TEXT
3 TEXT
4 TEXT
5 TEXT
6 TEXT
```

```
\firstofthreearguments {...}1 {...}2 {...}3
1 TEXT
2 TEXT
3 TEXT
```

```
\firstofthreeunexpanded {...}1 {...}2 {...}3
1 TEXT
2 TEXT
3 TEXT
```

```
\firstoftwoarguments {...}1 {...}2
1 TEXT
2 TEXT
```

```
\firstoftwounexpanded {...}1 {...}2
1 TEXT
2 TEXT
```

```
\firstrealpage
```

<code>\firstrealpagenumber</code>
<code>\firstsubcountervalue [...]<sup>1</sup> [...]<sup>2</sup></code> 1 NAME 2 NUMMER
<code>\firstsubpagenumber</code>
<code>\firstuserpage</code>
<code>\firstuserpagenumber</code>
<code>\fitfieldframed [...]<sup>1</sup> [...]<sup>2</sup></code> 1 inherits: \nastavoramovan <sup>OPT</sup> 2 CONTENT
<code>\fittopbaselinegrid {...}</code> * CONTENT
<code>\flag {...}</code> * NAME
<code>\placelistoffigures [...]<sup>*</sup> [...]</code> * inherits: \nastavseznam <sup>OPT</sup>
<code>\placelistofgraphics [...]<sup>*</sup> [...]</code> * inherits: \nastavseznam <sup>OPT</sup>
<code>\placelistofchemicals [...]<sup>*</sup> [...]</code> * inherits: \nastavseznam <sup>OPT</sup>
<code>\placelistofintermezzi [...]<sup>*</sup> [...]</code> * inherits: \nastavseznam <sup>OPT</sup>
<code>\placelistoftables [...]<sup>*</sup> [...]</code> * inherits: \nastavseznam <sup>OPT</sup>
<code>\floatuserdataparameter {...}</code> * KEY
<code>\flushboxregister ...</code> * CSNAME NUMMER
<code>\flushcollector [...]</code> * NAME
<code>\flushedrightlastline</code>
<code>\flushlayer [...]</code> * NAME
<code>\flushlocalfloats</code>
<code>\flushnextbox</code>

<code>\flushnotes</code>
<code>\flushoutputstream [...]</code> <code>* NAME</code>
<code>\flushshapebox</code>
<code>\flushtextflow {...}</code> <code>* NAME</code>
<code>\flushtokens [...]</code> <code>* NAME</code>
<code>\flushtoks \...</code> <code>* CSNAME</code>
<code>\fontalternative</code>
<code>\fontbody</code>
<code>\fontclass</code>
<code>\fontclassname {...} {...}</code> <code>1 NAME</code> <code>2 FONT</code>
<code>\fontface</code>
<code>\fontfeaturelist [...] [...]</code> <code>1 NAME</code> <code>2 TEXT</code>
<code>\fontchar {...}</code> <code>* NAME</code>
<code>\fontcharbyindex {...}</code> <code>* NUMMER</code>
<code>\fontsize</code>
<code>\fontstyle</code>
<code>\footnotetext [...,<sup>1</sup>...] {<sup>2</sup>...}</code> <code>1 REFERENCE</code> <small>OPT</small> <code>2 TEXT</code>
<code>\footnotetext [...,<sup>*</sup>...]</code> <code>* titul = TEXT</code> <code>zalozka = TEXT</code> <code>seznam = TEXT</code> <code>odkaz = REFERENCE</code>
<code>\forcecharacterstripping</code>
<code>\forcelocalfloats</code>

<code>\forgeteverypar</code>
<code>\forgetparameters [...]{...}</code> 1 TEXT 2 KEY = VALUE
<code>\forgetragged</code>
<code>\foundbox {...}{...}</code> 1 NAME 2 NAME
<code>\fourthoffivearguments {...}{...}{...}{...}{...}</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT
<code>\fourthoffourarguments {...}{...}{...}{...}</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT
<code>\fourthofsixarguments {...}{...}{...}{...}{...}{...}</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT
<code>\frameddimension {...}</code> * KEY
<code>\framedparameter {...}</code> * KEY
<code>\freezedimenmacro \^1 \^2</code> 1 CSNAME 2 CSNAME
<code>\freezeasure [...]{...}</code> 1 NAME 2 DIMENSION
<code>\frenchspacing</code>
<code>\fromlinenote [...]{...}</code> 1 REFERENCE 2 TEXT
<code>\frozenhbox {...}</code> * CONTENT
<code>\GetPar</code>
<code>\GotoPar</code>

\Greeknumpals {.*} *    NUMBER
\gdefconvertedargument \ <sup>1</sup> ... { <sup>2</sup> ...} 1    CSNAME 2    TEXT
\gdefconvertedcommand \ <sup>1</sup> ... \ <sup>2</sup> ... 1    CSNAME 2    CSNAME
\getboxfromcache { <sup>1</sup> ...} { <sup>2</sup> ...} <sup>3</sup> ... 1    NAME 2    NUMBER TEXT 3    CSNAME NUMBER
\getboxllx <sup>*</sup> ... *    CSNAME NUMBER
\getboxlly <sup>*</sup> ... *    CSNAME NUMBER
\getbufferdata [ <sup>*</sup> ...] <sup>OPT</sup> *    BUFFER
\getcommacommandsize [..., <sup>*</sup> ...] *    BEFEHL
\getcommalistsize [..., <sup>*</sup> ...] *    BEFEHL
\getdayoftheweek { <sup>1</sup> ...} { <sup>2</sup> ...} { <sup>3</sup> ...} 1    NUMBER 2    NUMBER 3    NUMBER
\getdayspermonth { <sup>1</sup> ...} { <sup>2</sup> ...} 1    NUMBER 2    NUMBER
\getdefinedbuffer [ <sup>*</sup> ...] *    BUFFER
\getdocumentargument { <sup>*</sup> ...} *    NAME
\getdocumentargumentdefault { <sup>1</sup> ...} { <sup>2</sup> ...} 1    NAME 2    TEXT
\getdocumentfilename { <sup>*</sup> ...} *    NUMBER
\getdummyparameters [..., <sup>*</sup> ... <sub>=</sub> ...] *    KEY    =    VALUE
\getemptyparameters [ <sup>1</sup> ...] [..., <sup>2</sup> ... <sub>=</sub> ...] 1    TEXT 2    KEY    =    VALUE



<code>\getparameters [...]<sup>1</sup> [...,...<sup>2</sup>...,...]</code> 1 TEXT 2 KEY = VALUE
<code>\getexpandedparameters [...]<sup>1</sup> [...,...<sup>2</sup>...,...]</code> 1 TEXT 2 KEY = VALUE
<code>\getfiguredimensions [...]<sup>1</sup> [...,...<sup>2</sup>...,...]<sup>OPT</sup></code> 1 FILE 2 inherits: \setupexternalfigure
<code>\getfirstcharacter {...}</code> * TEXT
<code>\getfirsttwopassdata {...}</code> * NAME
<code>\getfromcommacommand [...]<sup>1</sup>,... [...]<sup>2</sup></code> 1 BEFEHL 2 NUMMER
<code>\getfromcommalist [...]<sup>1</sup>,... [...]<sup>2</sup></code> 1 BEFEHL 2 NUMMER
<code>\getfromtwopassdata {...}<sup>1</sup> {...}<sup>2</sup></code> 1 NAME 2 NAME
<code>\getglyphdirect {...}<sup>1</sup> {...}<sup>2</sup></code> 1 FONT 2 NUMMER CHARACTER
<code>\getglyphstyled {...}<sup>1</sup> {...}<sup>2</sup></code> 1 FONT 2 NUMMER CHARACTER
<code>\getgparameters [...]<sup>1</sup> [...,...<sup>2</sup>...,...]</code> 1 TEXT 2 KEY = VALUE
<code>\getlasttwopassdata {...}</code> * NAME
<code>\getlocalfloat {...}</code> * NUMMER
<code>\getlocalfloats</code>
<code>\getMPdrawing</code>
<code>\getMPlayer [...]<sup>1</sup> [...,...<sup>2</sup>...,...]<sup>OPT</sup> {...}<sup>3</sup></code> 1 NAME 2 inherits: \nastavoramovani 3 CONTENT

<pre> \getmessage {...} {...} 1  NAME 2  NAME NUMBER </pre>
<pre> \getnamedglyphdirect {...} {...} 1  FONT 2  NAME </pre>
<pre> \getnamedglyphstyled {...} {...} 1  FONT 2  NAME </pre>
<pre> \getnamedtwopassdatalist \... {...} 1  CSNAME 2  NAME </pre>
<pre> \getnaturaldimensions ... *  CSNAME NUMBER </pre>
<pre> \getnoflines {...} *  DIMENSION </pre>
<pre> \getobject {...} {...} 1  NAME 2  NAME </pre>
<pre> \getobjectdimensions {...} {...} 1  NAME 2  NAME </pre>
<pre> \getpaletsize [...] *  NAME </pre>
<pre> \getparameters [...] [..., ...<sup>2</sup>..., ...] 1  TEXT 2  KEY = VALUE </pre>
<pre> \getprivatechar {...} *  NAME </pre>
<pre> \getprivateslot {...} *  NAME </pre>
<pre> \getrandomcount \... {...} {...} 1  CSNAME 2  NUMMER 3  NUMMER </pre>
<pre> \getrandomdimen \... {...} {...} 1  CSNAME 2  DIMENSION 3  DIMENSION </pre>
<pre> \getrandomfloat \... {...} {...} 1  CSNAME 2  NUMMER 3  NUMMER </pre>

\getrandomnumber \ <sup>1</sup> ... { <sup>2</sup> ...} { <sup>3</sup> ...} 1 CSNAME 2 NUMMER 3 NUMMER
\getrandomseed \*.. * CSNAME
\getraweparameters [ <sup>1</sup> ...] [..., <sup>2</sup> ...,...] 1 TEXT 2 KEY = VALUE
\getrawgparameters [ <sup>1</sup> ...] [..., <sup>2</sup> ...,...] 1 TEXT 2 KEY = VALUE
\getrawnoflines {*.. * DIMENSION
\getrawparameters [ <sup>1</sup> ...] [..., <sup>2</sup> ...,...] 1 TEXT 2 KEY = VALUE
\getrawxparameters [ <sup>1</sup> ...] [..., <sup>2</sup> ...,...] 1 TEXT 2 KEY = VALUE
\getreference [ <sup>1</sup> ...] [ <sup>2</sup> .. 1 implicitni text titul cislo stranka realpage 2 REFERENCE
\getreferenceentry {*.. * implicitni text titul cislo stranka realpage
\getroundednoflines {*.. * DIMENSION
\getsubstring { <sup>1</sup> ...} { <sup>2</sup> ...} { <sup>3</sup> ...} 1 NUMMER 2 NUMMER 3 TEXT
\gettwopassdata {*.. * NAME
\gettwopassdatalist {*.. * NAME
\getuvalue {*.. * NAME
\getvalue {*.. * NAME
\getvariable { <sup>1</sup> ...} { <sup>2</sup> ...} 1 NAME 2 KEY

<pre> \getvariabledefault {...} {...} {...} 1 NAME 2 KEY 3 BEFEHL </pre>
<pre> \getxparameters [...]<sup>1</sup> [...,<sup>2</sup>...,...] 1 TEXT 2 KEY = VALUE </pre>
<pre> \globaldisablemode [...,<sup>*</sup>...] * NAME </pre>
<pre> \globalenablemode [...,<sup>*</sup>...] * NAME </pre>
<pre> \globalletempty \<sup>*</sup>... * CSNAME </pre>
<pre> \globalpopbox \<sup>*</sup>... * CSNAME NUMBER </pre>
<pre> \globalpopmacro \<sup>*</sup>... * CSNAME </pre>
<pre> \globalpreventmode [...,<sup>*</sup>...] * NAME </pre>
<pre> \globalprocesscommalist [...]<sup>1</sup> \<sup>2</sup>... 1 BEFEHL 2 CSNAME </pre>
<pre> \globalpushbox \<sup>*</sup>... * CSNAME NUMBER </pre>
<pre> \globalpushmacro \<sup>*</sup>... * CSNAME </pre>
<pre> \globalpushreferenceprefix {...} ... \globalpopreferenceprefix * + - TEXT </pre>
<pre> \globalswapcounts \<sup>1</sup>... \<sup>2</sup>... 1 CSNAME 2 CSNAME </pre>
<pre> \globalswapdimens \<sup>1</sup>... \<sup>2</sup>... 1 CSNAME 2 CSNAME </pre>
<pre> \globalswapmacros \<sup>1</sup>... \<sup>2</sup>... 1 CSNAME 2 CSNAME </pre>
<pre> \globalundefine {...} * NAME </pre>
<pre> \glyphfontfile {...} * FONT </pre>

\gobbledoubleempty [...<sup>1</sup>] [...<sup>2</sup>]

1 TEXT OPT OPT  
2 TEXT

\gobbleeightarguments {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} {...<sup>4</sup>} {...<sup>5</sup>} {...<sup>6</sup>} {...<sup>7</sup>} {...<sup>8</sup>}

1 CONTENT  
2 CONTENT  
3 CONTENT  
4 CONTENT  
5 CONTENT  
6 CONTENT  
7 CONTENT  
8 CONTENT

\gobblefivearguments {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} {...<sup>4</sup>} {...<sup>5</sup>}

1 CONTENT  
2 CONTENT  
3 CONTENT  
4 CONTENT  
5 CONTENT

\gobblefiveoptionals [...<sup>1</sup>] [...<sup>2</sup>] [...<sup>3</sup>] [...<sup>4</sup>] [...<sup>5</sup>]

1 TEXT  
2 TEXT  
3 TEXT  
4 TEXT  
5 TEXT

\gobblefourarguments {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} {...<sup>4</sup>}

1 CONTENT  
2 CONTENT  
3 CONTENT  
4 CONTENT

\gobblefouroptionals [...<sup>1</sup>] [...<sup>2</sup>] [...<sup>3</sup>] [...<sup>4</sup>]

1 TEXT  
2 TEXT  
3 TEXT  
4 TEXT

\gobbleninearguments {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} {...<sup>4</sup>} {...<sup>5</sup>} {...<sup>6</sup>} {...<sup>7</sup>} {...<sup>8</sup>} {...<sup>9</sup>}

1 CONTENT  
2 CONTENT  
3 CONTENT  
4 CONTENT  
5 CONTENT  
6 CONTENT  
7 CONTENT  
8 CONTENT  
9 CONTENT

\gobbleoneargument {...<sup>\*</sup>}

\* CONTENT

\gobbleoneoptional [...<sup>\*</sup>]

\* TEXT

\gobblesevenarguments {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} {...<sup>4</sup>} {...<sup>5</sup>} {...<sup>6</sup>} {...<sup>7</sup>}

1 CONTENT  
2 CONTENT  
3 CONTENT  
4 CONTENT  
5 CONTENT  
6 CONTENT  
7 CONTENT

* TEXT	OPT
1. The first part of the report is a summary of the findings.	
2. The second part of the report is a detailed description of the methodology.	
3. The third part of the report is a discussion of the results.	
4. The fourth part of the report is a conclusion.	
5. The fifth part of the report is a list of references.	
6. The sixth part of the report is an appendix.	
7. The seventh part of the report is a glossary.	
8. The eighth part of the report is a bibliography.	
9. The ninth part of the report is a list of figures.	
10. The tenth part of the report is a list of tables.	

1	CONTENT
2	CONTENT
3	CONTENT
4	CONTENT
5	CONTENT
6	CONTENT

1	CONTENT
2	CONTENT
3	CONTENT
4	CONTENT
5	CONTENT
6	CONTENT
7	CONTENT
8	CONTENT
9	CONTENT
10	CONTENT

1 CONTENT  
2 CONTENT  
3 CONTENT

1	TEXT
2	TEXT
3	TEXT

1 CONTENT

2 CONTENT

1	TEXT
2	TEXT

\* CSNAME

\* CONTENT

1	CATEGORY	OPT
2	NAME	
3	NAME	
4	NAME	

1	NAME
2	NAME
3	NAME

1	NAME
2	CSNAME

<code>\grave {...}</code> * CHARACTER
<code>\grayvalue {...}</code> * COLOR
<code>\greedystring \at ... \to ... \and ...</code> 1 TEXT 2 TEXT 3 CSNAME 4 CSNAME
<code>\greeknumerals {...}</code> * NUMBER
<code>\groupedcommand {...} {...}</code> 1 BEFEHL 2 BEFEHL
<code>\gsetboxllx ... {...}</code> 1 CSNAME NUMBER 2 DIMENSION
<code>\gsetboxlly ... {...}</code> 1 CSNAME NUMBER 2 DIMENSION
<code>\gujaratinumerals {...}</code> * NUMBER
<code>\gurmukhinumerals {...}</code> * NUMBER
<code>\hairspace</code>
<code>\halflinestrut</code>
<code>\halfstrut</code>
<code>\halfwaybox {...}</code> * CONTENT
<code>\handletokens ... \with ...</code> 1 TEXT 2 CSNAME
<code>\hash</code>
<code>\hat {...}</code> * CHARACTER
<code>\hboxofvbox ...</code> * CSNAME NUMBER
<code>\hboxreference [...<sup>1</sup>,...] {...<sup>2</sup>}</code> 1 REFERENCE 2 CONTENT

<code>\hboxBOX {...}</code> *   CONTENT
<code>\hdofstring {...}</code> *   TEXT
<code>\headhbox <sup>1</sup>... {<sup>2</sup>...}</code> 1   TEXT       OPT 2   CONTENT
<code>\headnumbercontent</code>
<code>\headnumberdistance</code>
<code>\headnumberwidth</code>
<code>\headreferenceattributes</code>
<code>\headsetupspacing</code>
<code>\headtextcontent</code>
<code>\headtextdistance</code>
<code>\headtextwidth</code>
<code>\headvbox <sup>1</sup>... {<sup>2</sup>...}</code> 1   TEXT       OPT 2   CONTENT
<code>\headwidth</code>
<code>\heightanddepthofstring {...}</code> *   TEXT
<code>\heightofstring {...}</code> *   TEXT
<code>\heightspanningtext {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...}</code> 1   TEXT 2   DIMENSION 3   FONT
<code>\HELP [<sup>1</sup>...] {<sup>2</sup>...} {<sup>3</sup>...}</code> 1   REFERENCE 2   TEXT 3   TEXT instances: helptext
<code>\hglue ...</code> *   DIMENSION
<code>\hiddencitation [...]</code> *   REFERENCE



<code>\hiddencite [...]</code> *   REFERENCE
<code>\highlight [...]{...}</code> 1   NAME 2   TEXT
<code>\HIGHLIGHT {...}</code> *   TEXT
<code>\highordinalstr {...}</code> *   TEXT
<code>\hilo [...]{...}{...}</code> 1   vlevo <sup>OPT</sup> vpravo 2   CONTENT 3   CONTENT
<code>\himilo {...}{...}{...}</code> 1   CONTENT 2   CONTENT 3   CONTENT
<code>\hl [...]</code> *   NUMBER
<code>\hlavnijazyk [...]</code> *   SPRACHE
<code>\hodnotabarvy {...}</code> *   COLOR
<code>\horizontalgrowingbar [...,.*,...]</code> *   inherits: \setuppositionbar
<code>\horizontalpositionbar [...,.*,...]</code> *   inherits: \setuppositionbar
<code>\hphantom {...}</code> *   CONTENT
<code>\hpos {...}{...}</code> 1   NAME 2   CONTENT
<code>\hsizefraction {...}{...}</code> 1   DIMENSION 2   NUMBER
<code>\hsmash {...}</code> *   CONTENT
<code>\hsmashbox ...</code> *   CSNAME NUMBER
<code>\hsmashed {...}</code> *   CONTENT

<p><code>\hspace [...]</code> <sup>1</sup> <code>[...]</code> <sup>2</sup></p> <p>1 NAME OPT OPT</p> <p>2 male stredni velke normalni implicitni zadny .5 1 2 3 speech citovat interquotation citace sentence intersentence NAME</p>
<p><code>\htdpofstring {...}</code></p> <p>* TEXT</p>
<p><code>\htofstring {...}</code></p> <p>* TEXT</p>
<p><code>\hyphen</code></p>
<p><code>\hyphenatedcoloredword {...}</code></p> <p>* TEXT</p>
<p><code>\hyphenatedfile {...}</code></p> <p>* FILE</p>
<p><code>\hyphenatedfilename {...}</code></p> <p>* TEXT</p>
<p><code>\hyphenatedhbox {...}</code></p> <p>* CONTENT</p>
<p><code>\hyphenatedpar {...}</code></p> <p>* TEXT</p>
<p><code>\hyphenatedurl {...}</code></p> <p>* TEXT</p>
<p><code>\hyphenatedword {...}</code></p> <p>* TEXT</p>
<p><code>\CHARACTERKERNING [...]</code> <sup>1</sup> <code>{...}</code> <sup>2</sup></p> <p>1 NUMMER OPT</p> <p>2 TEXT</p>
<p><code>\chardescription {...}</code></p> <p>* NUMMER</p>
<p><code>\charwidthlanguage</code></p>
<p><code>\check {...}</code></p> <p>* CHARACTER</p>
<p><code>\checkedfiller {...}</code></p> <p>* sym symbol linka sirka mezera NAME BEFEHL</p>
<p><code>\checkedchar {...}</code> <sup>1</sup> <code>{...}</code> <sup>2</sup></p> <p>1 NUMMER</p> <p>2 CHARACTER</p>
<p><code>\checkedstrippedcsname \...</code></p> <p>* CSNAME</p>

\checkedstrippedcsname ... * TEXT
\checkcharacteralign {...} * CONTENT
\checkinjector [...] * NAME
\checknextindentation [...] * ano ne auto
\checknextinjector [...] * NAME
\checkpage [...] <sup>1</sup> [...,... <sup>2</sup> ...] 1 NAME OPT 2 inherits: \setuppagechecker
\checkparameters [...] * TEXT
\checkpreviousinjector [...] * NAME
\checksoundtrack {...} * NAME
\checktwopassdata {...} * NAME
\checkvariables [...] <sup>1</sup> [...,... <sup>2</sup> ...] 1 NAME 2 set = BEFEHL reset = BEFEHL KEY = VALUE
\chem {...} <sup>1</sup> {...} <sup>2</sup> {...} <sup>3</sup> 1 TEXT 2 TEXT 3 TEXT
\chemical [...] <sup>1</sup> [...,... <sup>2</sup> ...] [...,... <sup>3</sup> ...] 1 NAME OPT OPT 2 TEXT 3 TEXT
\chemicalbottext {...} * TEXT
\chemicalmidtext {...} * TEXT
\chemicalsymbol [...] * NAME
\chemicaltext {...} * TEXT

<code>\chemicaltopertext {...}</code> * TEXT
<code>\chineseallnumerals {...}</code> * NUMMER
<code>\chinesecapnumerals {...}</code> * NUMMER
<code>\chinesenumerals {...}</code> * NUMMER
<code>\INRSTEX</code>
<code>\ibox {...}</code> * CONTENT
<code>\ifassignment .<sup>1</sup>. \else .<sup>2</sup>. \fi</code> 1 TRUE 2 FALSE
<code>\iff</code>
<code>\ifinobject .<sup>1</sup>. \else .<sup>2</sup>. \fi</code> 1 TRUE 2 FALSE
<code>\ifinoutputstream .<sup>1</sup>. \else .<sup>2</sup>. \fi</code> 1 TRUE 2 FALSE
<code>\ifparameters .<sup>1</sup>. \else .<sup>2</sup>. \fi</code> 1 TRUE 2 FALSE
<code>\iftrialtypesetting .<sup>1</sup>. \else .<sup>2</sup>. \fi</code> 1 TRUE 2 FALSE
<code>\ignoreimplicitspaces</code>
<code>\ignorevalue {...}</code> * NAME
<code>\immediatesavetwopassdata {...} {...} {...}</code> 1 NAME 2 NUMMER 3 CONTENT
<code>\impliedby</code>
<code>\implies</code>
<code>\includemenu [...]</code> * NAME

$\backslash\text{includeversioninfo}\{...\}$ * NAME
$\backslash\text{incrementcounter}[...][...]$ 1 NAME OPT 2 NUMBER
$\backslash\text{incrementedcounter}[...]$ * NAME
$\backslash\text{incrementpagenumber}$
$\backslash\text{incrementsubpagenumber}$
$\backslash\text{incrementvalue}\{...\}$ * NAME
$\backslash\text{indentation}$
$\backslash\text{infofont}$
$\backslash\text{infofontbold}$
$\backslash\text{inheritparameter}[...][...][...]$ 1 TEXT 2 TEXT 3 KEY
$\backslash\text{inhibitblank}$
$\backslash\text{initializeboxstack}\{...\}$ * NAME
$\backslash\text{inlinebuffer}[...*,...]$ * BUFFER OPT
$\backslash\text{inlinedbox}\{...\}$ * CONTENT
$\backslash\text{inlinemath}\{...\}$ * CONTENT
$\backslash\text{inlinemathematics}\{...\}$ * CONTENT
$\backslash\text{inlinemessage}\{...\}$ * TEXT
$\backslash\text{inlineordisplaymath}\{...\}\{...\}$ 1 CONTENT 2 CONTENT
$\backslash\text{inlinerange}[...]$ * REFERENCE
$\backslash\text{innerflushshapebox}$

<pre>\input {...} * FILE</pre>
<pre>\inputfilebarename</pre>
<pre>\inputfilename</pre>
<pre>\inputfilerealsuffix</pre>
<pre>\inputfilesuffix</pre>
<pre>\inputgivenfile {...} * FILE</pre>
<pre>\input ... * FILE</pre>
<pre>\insertpages [...] [...,<sup>2</sup>...] [...,<sup>3</sup>...,...] 1 FILE          OPT          OPT 2 NUMMER 3 sirka      = DIMENSION   n          = NUMMER   category   = NAME</pre>
<pre>\instalacejazyka [...<sup>1</sup>] [...,<sup>2</sup>...,...] 1 NAME 2 inherits: \nastavjazyk</pre>
<pre>\instalacejazyka [...<sup>1</sup>] [...<sup>2</sup>] 1 NAME 2 SPRACHE</pre>
<pre>\installactionhandler {...} * NAME</pre>
<pre>\installactivecharacter ... * CHARACTER</pre>
<pre>\installanddefineactivecharacter <sup>1</sup>... {<sup>2</sup>...} 1 CHARACTER 2 BEFEHL</pre>
<pre>\installattributestack \*... * CSNAME</pre>
<pre>\installautocommandhandler \... {<sup>2</sup>...} \<sup>3</sup>... 1 CSNAME 2 NAME 3 CSNAME</pre>
<pre>\installautosetuphandler \... {<sup>2</sup>...} 1 CSNAME 2 NAME</pre>
<pre>\installbasicautosetuphandler \... {<sup>2</sup>...} \<sup>3</sup>... 1 CSNAME 2 NAME 3 CSNAME</pre>

\installbasicparameterhandler \... {...}

1 CSNAME  
2 NAME

\installbottomframerenderer {...} {...}

1 NAME  
2 BEFEHL

\installcommandhandler \... {...} \...

1 CSNAME  
2 NAME  
3 CSNAME

\installcorenamespace {...}

\* NAME

\installdefinehandler \... {...} \...

1 CSNAME  
2 NAME  
3 CSNAME

\installdefinitionset \... {...}

1 CSNAME  
2 NAME

\installdefinitionsetmember \... {...} \... {...}

1 CSNAME  
2 NAME  
3 CSNAME  
4 NAME

\installdirectcommandhandler \... {...}

1 CSNAME  
2 NAME

\installdirectparameterhandler \... {...}

1 CSNAME  
2 NAME

\installdirectparametersethandler \... {...}

1 CSNAME  
2 NAME

\installdirectsetuphandler \... {...}

1 CSNAME  
2 NAME

\installdirectstyleandcolorhandler \... {...}

1 CSNAME  
2 NAME

\installframedautocommandhandler \... {...} \...

1 CSNAME  
2 NAME  
3 CSNAME

\installframedcommandhandler \... {...} \...

1 CSNAME  
2 NAME  
3 CSNAME

<pre> \installleftframerenderer {...} {...} 1  NAME 2  BEFEHL </pre>
<pre> \installnamespace {...} *  NAME </pre>
<pre> \installoutputroutine \... {...} 1  CSNAME 2  BEFEHL </pre>
<pre> \installpagearrangement ... {...} 1  NAME 2  BEFEHL </pre>
<pre> \installparameterhandler \... {...} 1  CSNAME 2  NAME </pre>
<pre> \installparameterhashhandler \... {...} 1  CSNAME 2  NAME </pre>
<pre> \installparametersethandler \... {...} 1  CSNAME 2  NAME </pre>
<pre> \installparentinjector \... {...} 1  CSNAME 2  NAME </pre>
<pre> \installrightframerenderer {...} {...} 1  NAME 2  BEFEHL </pre>
<pre> \installrootparameterhandler \... {...} 1  CSNAME 2  NAME </pre>
<pre> \installsetuphandler \... {...} 1  CSNAME 2  NAME </pre>
<pre> \installsetupononlycommandhandler \... {...} 1  CSNAME 2  NAME </pre>
<pre> \installshipoutmethod {...} {...} 1  NAME 2  BEFEHL </pre>
<pre> \installsimplecommandhandler \... {...} \... 1  CSNAME 2  NAME 3  CSNAME </pre>
<pre> \installsimpleframedcommandhandler \... {...} \... 1  CSNAME 2  NAME 3  CSNAME </pre>



$\backslash\text{installstyleandcolorhandler } \overset{1}{\dots} \overset{2}{\{\dots\}}$ 1 CSNAME 2 NAME
$\backslash\text{installswitchcommandhandler } \overset{1}{\dots} \overset{2}{\{\dots\}} \overset{3}{\dots}$ 1 CSNAME 2 NAME 3 CSNAME
$\backslash\text{installswitchsetuphandler } \overset{1}{\dots} \overset{2}{\{\dots\}}$ 1 CSNAME 2 NAME
$\backslash\text{installtexdirective } \overset{1}{\{\dots\}} \overset{2}{\{\dots\}} \overset{3}{\{\dots\}}$ 1 NAME 2 BEFEHL 3 BEFEHL
$\backslash\text{installtextracker } \overset{1}{\{\dots\}} \overset{2}{\{\dots\}} \overset{3}{\{\dots\}}$ 1 NAME 2 BEFEHL 3 BEFEHL
$\backslash\text{installtopframerenderer } \overset{1}{\{\dots\}} \overset{2}{\{\dots\}}$ 1 NAME 2 BEFEHL
$\backslash\text{installunitsseparator } \overset{1}{\{\dots\}} \overset{2}{\{\dots\}}$ 1 NAME 2 BEFEHL
$\backslash\text{installunitsspace } \overset{1}{\{\dots\}} \overset{2}{\{\dots\}}$ 1 NAME 2 BEFEHL
$\backslash\text{installversioninfo } \overset{1}{\{\dots\}} \overset{2}{\{\dots\}}$ 1 NAME 2 BEFEHL
$\backslash\text{integerrounding } \{\dots\}$ * NUMMER
$\backslash\text{interakcnilista } [\overset{1}{\dots}] [\dots, \overset{2}{\dots}, \dots]$ 1 NAME OPT OPT 2 inherits: \nastavinterakcnilistu
$\backslash\text{interakcnitlacitka } [\dots, \overset{1}{\dots}, \dots] [\dots, \overset{2}{\dots}, \dots]$ 1 inherits: \nastavinterakcnilistu 2 stranka podstranka REFERENCE
$\backslash\text{interaktivnimenu } [\overset{1}{\dots}] [\dots, \overset{2}{\dots}, \dots]$ 1 NAME OPT 2 inherits: \nastavinterakcnimenu
$\backslash\text{intertext } \{\dots\}$ * TEXT
$\backslash\text{invokepagehandler } \overset{1}{\{\dots\}} \overset{2}{\{\dots\}}$ 1 normalni zadny NAME 2 CONTENT

\istltdir ... * TLT TRT
\istrtdir ... * TLT TRT
\italiccorrection
\italicface
\itemtag [...*,...] * REFERENCE OPT
\jazyk [...] * SPRACHE
\LANGUAGE
\jdidolu [...] * DIMENSION
\jdina {...} [...] 1 CONTENT 2 REFERENCE
\jdinabox {...} [...] 1 CONTENT 2 REFERENCE
\jdinastranu {...} [...] 1 TEXT 2 REFERENCE
\UNIT {...} * CONTENT instances: unit
\jobfilename
\jobfilesuffix
\Kap {...} * TEXT
\kaligraficke
\kap {...} * TEXT
\keeplinestogether {...} * NUMMER
\keepunwantedspaces

<code>\kerncharacters [...]{...}</code> 1    NUMMER                    OPT 2    TEXT
<code>\klonujpole [...][...][...][...,...]</code> 1    NAME 2    NAME 3    NAME 4    NAME
<code>\COMMENT [...][...,...<sup>2</sup>,...]{...}</code> 1    TEXT                    OPT                    OPT 2    inherits: \nastavkomentar 3    TEXT instances: comment
<code>\komponenta [...]</code> *    FILE
<code>\komponenta ...</code> *    FILE
<code>\konvertujcislo {...}{...}</code> 1    prazdne implicitni zadny mesic month:mnem pismo Pismo pisma Pisma a A Cila slovo words Slovo Slova n N rimskecislice Rimskecislice i I r R KR RK recky Recky g G abjadnumerals abjadnodotnumerals abjadnaivenumerals thainumerals devanagarinumerals gurmurkhinumerals gujaratinnumerals tibetannumerals greeknumerals Greeknumerals arabicnumerals persiannumerals arabicexnumerals arabicdecimals persiandecimals koreannumerals koreanparentnumerals koreancirclenumerals kr kr-p kr-c chinesenumerals chinesecapnumerals chineseallnumerals cn cn-c cn-a sloveniannumerals slovenianNumerals spanishnumerals spanishNumerals mathgreek set_0 set_1 set_2 set_3 continued NAME 2    NUMMER
<code>\kopirujpole [...][...]</code> 1    NAME 2    NAME
<code>\koreancirclenumerals {...}</code> *    NUMMER
<code>\koreannumerals {...}</code> *    NUMMER
<code>\koreannumeralsc {...}</code> *    NUMMER
<code>\koreannumeralsp {...}</code> *    NUMMER
<code>\koreanparentnumerals {...}</code> *    NUMMER
<code>\korekcebilehomista {...}</code> *    CONTENT
<code>\kurziva</code>
<code>\kurzivnitucne</code>
<code>\LAMSTEX</code>
<code>\LATEX</code>

<code>\LamSTeX</code>
<code>\LaTeX</code>
<code>\LUAJITTEX</code>
<code>\LUATEX</code>
<code>\Lua</code>
<code>\LuajitTeX</code>
<code>\LuaTeX</code>
<code>\LABELjazyk</code> instances: head label mathlabel taglabel unit operator prefix suffix btxlabel
<code>\btxlabeltext {...}</code> * KEY
<code>\headtext {...}</code> * KEY
<code>\labeltext {...}</code> * KEY
<code>\mathlabeltext {...}</code> * KEY
<code>\operatorortext {...}</code> * KEY
<code>\prefixtext {...}</code> * KEY
<code>\suffixtext {...}</code> * KEY
<code>\taglabeltext {...}</code> * KEY
<code>\unittext {...}</code> * KEY
<code>\LABELtexts {...} {...}</code> 1 KEY 2 TEXT instances: head label mathlabel
<code>\leftheadtext {...}</code> * KEY
<code>\leftlabeltext {...}</code> * KEY

<code>\leftmathlabeltext {...}</code> * KEY
<code>\languageCharacters {...}</code> * NUMMER
<code>\languagecharacters {...}</code> * NUMMER
<code>\languagecharwidth {...}</code> * SPRACHE
<code>\lastcounter [...]</code> <sup>1</sup> <sup>2</sup> <code>[...]</code> 1 NAME OPT 2 NUMMER
<code>\lastcountervalue [...]</code> * NAME
<code>\lastdigit {...}</code> * NUMMER
<code>\lastlinewidth</code>
<code>\lastnaturalboxdp</code>
<code>\lastnaturalboxht</code>
<code>\lastnaturalboxwd</code>
<code>\lastpredefinedsymbol</code>
<code>\lastrealpage</code>
<code>\lastrealpagenumber</code>
<code>\lastsubcountervalue [...]</code> <sup>1</sup> <sup>2</sup> <code>[...]</code> 1 NAME 2 NUMMER
<code>\lastsubpagenumber</code>
<code>\lasttwodigits {...}</code> * NUMMER
<code>\lastuserpage</code>
<code>\lastuserpagenumber</code>
<code>\lateluacode {...}</code> * BEFEHL

$\backslash\text{layeredtext}$ [... <sup>1</sup> ... <sup>2</sup> ...] {... <sup>3</sup> } {... <sup>4</sup> } 1 inherits: \setuplayer <sup>PT</sup> 2 inherits: \setuplayeredtext 3 TEXT 4 CONTENT
$\backslash\text{layerheight}$
$\backslash\text{layerwidth}$
$\backslash\text{lazysavetaggedtwopassdata}$ {... <sup>1</sup> } {... <sup>2</sup> } {... <sup>3</sup> } {... <sup>4</sup> } 1 NAME 2 NUMMER 3 NAME 4 CONTENT
$\backslash\text{lazysavetwopassdata}$ {... <sup>1</sup> } {... <sup>2</sup> } {... <sup>3</sup> } 1 NAME 2 NUMMER 3 CONTENT
$\backslash\text{lbox}$ ... {... <sup>2</sup> } 1 TEXT <sup>OPT</sup> 2 CONTENT
$\backslash\text{leftbottombox}$ {...} * CONTENT
$\backslash\text{leftbox}$ {...} * CONTENT
$\backslash\text{lefthbox}$ {...} * CONTENT
$\backslash\text{leftLABELtext}$ {...} * KEY instances: head label mathlabel
$\backslash\text{rightheadtext}$ {...} * KEY
$\backslash\text{rightlabeltext}$ {...} * KEY
$\backslash\text{rightmathlabeltext}$ {...} * KEY
$\backslash\text{leftline}$ {...} * CONTENT
$\backslash\text{lefttorrighthbox}$ ... <sup>1</sup> {... <sup>2</sup> } 1 TEXT <sup>OPT</sup> 2 CONTENT
$\backslash\text{lefttorrightvbox}$ ... <sup>1</sup> {... <sup>2</sup> } 1 TEXT <sup>OPT</sup> 2 CONTENT

<code>\leftorrightvtop ...<sup>1</sup> {...}</code> 1 TEXT OPT 2 CONTENT
<code>\leftskipadaption</code>
<code>\leftsubguillemot</code>
<code>\lefttopbox {...}</code> * CONTENT
<code>\lefttoright</code>
<code>\lefttorighthbox ...<sup>1</sup> {...}</code> 1 TEXT OPT 2 CONTENT
<code>\lefttorightvbox ...<sup>1</sup> {...}</code> 1 TEXT OPT 2 CONTENT
<code>\lefttorightvtop ...<sup>1</sup> {...}</code> 1 TEXT OPT 2 CONTENT
<code>\letbeundefined {...}</code> * NAME
<code>\letcatcodecommand \...<sup>1</sup> ...<sup>2</sup> \...<sup>3</sup></code> 1 CSNAME 2 CHARACTER NUMBER 3 CSNAME
<code>\letcscsname \...<sup>1</sup> \csname ...<sup>2</sup> \endcsname</code> 1 CSNAME 2 NAME
<code>\letcsnamecs \csname ...<sup>1</sup> \endcsname \...<sup>2</sup></code> 1 NAME 2 CSNAME
<code>\letcsnamecsname \csname ...<sup>1</sup> \endcsname \csname ...<sup>2</sup> \endcsname</code> 1 NAME 2 NAME
<code>\letdummyparameter {...}<sup>1</sup> \...<sup>2</sup></code> 1 KEY 2 CSNAME
<code>\letempty \...*</code> * CSNAME
<code>\letgvalue {...}<sup>1</sup> \...<sup>2</sup></code> 1 NAME 2 CSNAME
<code>\letgvalueempty {...}</code> * NAME

<code>\letgvalurelax {...}</code> <code>* NAME</code>
<code>\letterampersand</code>
<code>\letterat</code>
<code>\letterbackslash</code>
<code>\letterbar</code>
<code>\letterbgroup</code>
<code>\letterclosebrace</code>
<code>\lettercolon</code>
<code>\letterdollar</code>
<code>\letterdoublequote</code>
<code>\letteregroup</code>
<code>\letterescape</code>
<code>\letterexclamationmark</code>
<code>\letterhash</code>
<code>\letterhat</code>
<code>\letterleftbrace</code>
<code>\letterless</code>
<code>\lettermore</code>
<code>\letteropenbrace</code>
<code>\letterpercent</code>
<code>\letterquestionmark</code>
<code>\letterrightbrace</code>
<code>\lettersinglequote</code>
<code>\letterslash</code>
<code>\letterspacing [...]</code> <code>{...}</code> <code>1    NUMMER</code> <code>OPT</code> <code>2    TEXT</code>



<code>\lettertilde</code>
<code>\letterunderscore</code>
<code>\letvalue {...} \^{2..}</code> 1 NAME 2 CSNAME
<code>\letvalueempty {...}</code> * NAME
<code>\letvaluerelax {...}</code> * NAME
<code>\lfence {...}</code> * CHARACTER
<code>\lhbox {...}</code> * CONTENT
<code>\limitatefirstline {\^{1..}} {\^{2..}} {\^{3..}}</code> 1 TEXT 2 DIMENSION 3 BEFEHL
<code>\limitatelines {\^{1..}} {\^{2..}} {\^{3..}}</code> 1 NUMMER 2 BEFEHL 3 TEXT
<code>\limitatetext {\^{1..}} {\^{2..}} {\^{3..}}</code> 1 TEXT 2 [-+]DIMENSION 3 BEFEHL
<code>\limitatetext {\^{1..}} {\^{2..,3..}} {\^{3..}}</code> 1 TEXT 2 [-+]DIMENSION 3 BEFEHL
<code>\LINENOTE {...}</code> * TEXT instances: linenote
<code>\startlinenote [^{1..}] {\^{2..}}</code> 1 REFERENCE 2 TEXT
<code>\linespanningtext {\^{1..}} {\^{2..}} {\^{3..}}</code> 1 TEXT 2 DIMENSION 3 FONT

```
\listcitation [...1...] [...2]
1 odkaz = REFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
                authornum authoryear
  pred = BEFEHL
  po = BEFEHL
  vlevo = BEFEHL
  vpravo = BEFEHL
  inherits: \setupbtx
2 REFERENCE
```

```
\listcitation [...1] [...2]
1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear
2 REFERENCE
```

```
\listcitation [...1...] [...2...]
1 odkaz = REFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
                authornum authoryear
  pred = BEFEHL
  po = BEFEHL
  vlevo = BEFEHL
  vpravo = BEFEHL
  inherits: \setupbtx
2 KEY = VALUE
```

```
\listcite [...1...] [...2]
1 odkaz = REFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
                authornum authoryear
  pred = BEFEHL
  po = BEFEHL
  vlevo = BEFEHL
  vpravo = BEFEHL
  inherits: \setupbtx
2 REFERENCE
```

```
\listcite [...1] [...2]
1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear
2 REFERENCE
```

```
\listcite [...1...] [...2...]
1 odkaz = REFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
                authornum authoryear
  pred = BEFEHL
  po = BEFEHL
  vlevo = BEFEHL
  vpravo = BEFEHL
  inherits: \setupbtx
2 KEY = VALUE
```

```
\listnamespaces
```

```
\llap {...}
* CONTENT
```

```
\loadanyfile [...]
* FILE
```

```
\loadanyfileonce [...]
* FILE
```

```
\loadbtxdefinitionfile [...]
* FILE
```

\loadbtxreplacementfile [...] * FILE
\loadcldfile [...] * FILE
\loadcldfileonce [...] * FILE
\loadfontgoodies [...] * FILE
\loadluafile [...] * FILE
\loadluafileonce [...] * FILE
\loadspellchecklist [ <sup>1</sup> ...] [ <sup>2</sup> ...] 1 NAME 2 FILE
\loadtexfile [...] * FILE
\loadtexfileonce [...] * FILE
\loadtypescriptfile [...] * FILE
\localframed [ <sup>1</sup> ...] [..., <sup>2</sup> ...,...] { <sup>3</sup> ...} 1 NAME 2 inherits: \nastavoramovani 3 CONTENT
\localframedwithsettings [ <sup>1</sup> ...] [..., <sup>2</sup> ...,...] { <sup>3</sup> ...} 1 NAME 2 inherits: \nastavoramovani 3 CONTENT
\localhsize
\localpopbox ... * CSNAME NUMBER
\localpopmacro \*... * CSNAME
\localpushbox ... * CSNAME NUMBER
\localpushmacro \*... * CSNAME
\localundefine {...} * NAME

<code>\locatedfilepath</code>
<code>\locatefilepath {...}</code> *    FILE
<code>\locfilename {...}</code> *    FILE
<code>\lomihi {...} {...} {...}</code> 1    CONTENT 2    CONTENT 3    CONTENT
<code>\lowerbox {...} \^2... {...}</code> 1    DIMENSION 2    CSNAME 3    CONTENT
<code>\lowercased {...}</code> *    TEXT
<code>\lowercasestring ... \to \^2...</code> 1    TEXT 2    CSNAME
<code>\lowerlefthdoubleninequote</code>
<code>\lowerleftsingleninequote</code>
<code>\lowerrighthdoubleninequote</code>
<code>\lowerrightsingleninequote</code>
<code>\LOWHIGH [...] {...} {...}</code> 1    vlevo vpra <sup>975</sup> 2    CONTENT 3    CONTENT
<code>\LOWMIDHIGH {...} {...} {...}</code> 1    CONTENT 2    CONTENT 3    CONTENT
<code>\lrbbox {...} {...} {...} {...} {...}</code> 1    DIMENSION 2    DIMENSION 3    DIMENSION 4    DIMENSION 5    CONTENT
<code>\ltop ... {...}</code> 1    TEXT <sup>OPT</sup> 2    CONTENT
<code>\luacode {...}</code> *    BEFEHL
<code>\luaconditional \^*...</code> *    CSNAME

\luaenvironment {...} * FILE
\luaexpanded {...} * BEFEHL
\luaexpr {...} * CONTENT
\luafunction {...} * BEFEHL
\luajitTeX
\luamajorversion
\luaminorversion
\luaparameterset {...} {...} 1 NAME 2 CONTENT
\luasetup {...} * NAME
\luaTeX
\luaversion
\MESIC {...} * NUMMER
\METAFONT
\METAFUN
\METAPOST
\MetaFont
\MetaFun
\MetaPost
\MKII
\MKIV
\MKIX
\MKVI
\MKXI

\MONTHLONG {...} *   NUMBER
\MONTHSHORT {...} *   NUMBER
\MPanchor {...} *   NAME
\MPbetex {...} *   NAME
\MPc {...} *   NAME
\MPcode {... <sup>1</sup> } {... <sup>2</sup> } 1   NAME       OPT 2   CONTENT
\MPcolor {...} *   COLOR
\MPcoloronly {...} *   COLOR
\MPcolumn {...} *   NAME
\MPd {...} *   NAME
\MPdrawing {...} *   CONTENT
\MPfontsizehskip {...} *   FONT
\MPgetmultipars {... <sup>1</sup> } {... <sup>2</sup> } 1   NAME 2   NAME
\MPgetmultishape {... <sup>1</sup> } {... <sup>2</sup> } 1   NAME 2   NAME
\MPgetposboxes {... <sup>1</sup> ,... <sup>2</sup> } {... <sup>2</sup> } 1   NAME 2   NAME
\MPh {...} *   NAME
\MPII
\MPIV

\MPinclusions [ <sup>1</sup> ...] { <sup>2</sup> ...} { <sup>3</sup> ...} 1 +                    OPT            OPT 2 NAME 3 CONTENT
\MPlleftskip {...} * NAME
\MPl1 {...} * NAME
\MPlr {...} * NAME
\MPls {...} * NAME
\MPmenubuttons {...} * NAME
\MPn {...} * NAME
\MPOptions {...} * COLOR
\MPOverlayanchor {...} * NAME
\MPp {...} * NAME
\MPpage {...} * NAME
\MPpardata {...} * NAME
\MPplus { <sup>1</sup> ...} { <sup>2</sup> ...} { <sup>3</sup> ...} 1 NAME 2 NUMMER 3 CONTENT
\MPpos {...} * NAME
\MPpositiongraphic { <sup>1</sup> ...} { <sup>2</sup> ...,... <sub>OPT</sub> ...} 1 NAME 2 KEY = VALUE
\MPposset {...} * NAME
\MPr {...} * NAME

\MPrawvar {...} {...} 1 NAME 2 KEY
\MPregion {...} * NAME
\MPrest {...} {...} 1 NAME 2 CONTENT
\MPrightskip {...} * NAME
\MPrs {...} * NAME
\MPstring {...} * NAME
\MPtext {...} * NAME
\MPtransparency {...} * COLOR
\MPul {...} * NAME
\MPur {...} * NAME
\MPVI
\MPv {... <sup>1</sup> ...} {... <sup>2</sup> ...} {... <sup>3</sup> ...} 1 NAME 2 NUMBER 3 CONTENT
\MPvar {...} * KEY
\MPvariable {...} * KEY
\MPvv {... <sup>1</sup> ...} {... <sup>2</sup> ...} 1 NAME 2 CONTENT
\MPw {...} * NAME
\MPwhd {...} * NAME
\MPx {...} * NAME



\* NAME

\* NAME

\* NAME

1	NAME <sup>OPT</sup>
2	CONTENT

\* CHARACTER.

```

1  BEFEHL
2  CSNAME

```

\* CSNAME NUMMER

\male

\malekurzivnitucne

\malenormalni

\malesklonene

\malesklonenetucne

\maletucne

\maletucnekurzivni

\maletucnesklonene

\maletype

1	DIMENSION
2	DIMENSION

```

1  NAME
2  odkaz = REFERENCE
3  inherits: \setupmargindata
4  inherits: \setupmarginframed
5  CONTENT

```

$\backslash$ MARGINDATA [... <sup>1</sup> ... <sup>2</sup> ...] {... <sup>3</sup> } 1 odkaz = REFERENCE <sup>OPT</sup> inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT instances: inleftmargin inrightmargin inoutermargin ininnermargin inleftedge inrightedge inouteredge ininneredge atleftmargin atrightmargin inleft inright inouter ininner inmargin inother margintext
$\backslash$ markcontent [... <sup>1</sup> ] {... <sup>2</sup> } 1 reset vse NAME <sup>OPT</sup> 2 CONTENT
$\backslash$ markinjector [...] * NAME
$\backslash$ mat {...} * CONTENT
$\backslash$ matematika [... <sup>1</sup> ] {... <sup>2</sup> } 1 NAME <sup>OPT</sup> 2 CONTENT
$\backslash$ math [... <sup>1</sup> ] {... <sup>2</sup> } 1 NAME <sup>OPT</sup> 2 CONTENT
$\backslash$ mathbf
$\backslash$ mathbi
$\backslash$ mathblackboard
$\backslash$ mathbs
$\backslash$ mathcommand {...} * NAME
$\backslash$ MATHCOMMAND {... <sup>1</sup> } {... <sup>2</sup> } 1 TEXT <sup>OPT</sup> 2 TEXT <sup>OPT</sup>
$\backslash$ mathdefault
$\backslash$ MATHDOUBLEEXTENSIBLE {...} * TEXT
$\backslash$ MATHEXTENSIBLE [... <sup>1</sup> ] {... <sup>2</sup> } {... <sup>3</sup> } 1 reverse matematika <sup>OPT</sup> text chemistry <sup>OPT</sup> 2 TEXT 3 TEXT
$\backslash$ mathfraktur
$\backslash$ MATHFRAMED [... <sup>1</sup> ...] {... <sup>2</sup> } 1 inherits: \setupmathframed <sup>OPT</sup> 2 CONTENT instances: mframed inmframed mcframed

$\backslash\mathrm{mathfunction}\{...\}$ *    CONTENT
$\backslash\mathrm{mathit}$
$\backslash\mathrm{mathitalic}$
$\backslash\mathrm{mathop}\{...\}$ *    CONTENT
$\backslash\mathrm{MATHORNAMENT}\{...\}$ *    CONTENT
$\backslash\mathrm{MATHOVEREXTENSIBLE}\{...\}$ *    TEXT
$\backslash\mathrm{MATHOVERTEXTEXTENSIBLE}\{...\}^1\{...\}^2$ 1    TEXT 2    TEXT
$\backslash\mathrm{MATHRADICAL}\left[...\right]^{1}\{...\}^{2}$ 1    TEXT                    OPT 2    CONTENT
$\backslash\mathrm{mathrm}$
$\backslash\mathrm{mathscript}$
$\backslash\mathrm{mathsl}$
$\backslash\mathrm{mathss}$
$\backslash\mathrm{mathtext}\{...\}^{1}\{...\}^{2}$ 1    TEXT                    OPT 2    TEXT
$\backslash\mathrm{mathtextbf}\{...\}^{1}\{...\}^{2}$ 1    TEXT                    OPT 2    TEXT
$\backslash\mathrm{mathtextbi}\{...\}^{1}\{...\}^{2}$ 1    TEXT                    OPT 2    TEXT
$\backslash\mathrm{mathtextbs}\{...\}^{1}\{...\}^{2}$ 1    TEXT                    OPT 2    TEXT
$\backslash\mathrm{mathtextit}\{...\}^{1}\{...\}^{2}$ 1    TEXT                    OPT 2    TEXT
$\backslash\mathrm{mathtextsl}\{...\}^{1}\{...\}^{2}$ 1    TEXT                    OPT 2    TEXT

`\mathtexttf` <sup>1</sup>... {<sup>2</sup>...}

1 TEXT OPT  
2 TEXT

`\maththtf`

`\mathtripler` [<sup>1</sup>...] {<sup>2</sup>...} {<sup>3</sup>...} {<sup>4</sup>...}

1 NAME OPT OPT OPT OPT  
2 TEXT  
3 TEXT  
4 TEXT

`\MATHTRIPLER` [<sup>1</sup>...] {<sup>2</sup>...} {<sup>3</sup>...} {<sup>4</sup>...}

1 NAME OPT OPT OPT OPT  
2 TEXT  
3 TEXT  
4 TEXT

`\maththt`

`\MATHUNDEREXTENSIBLE` {<sup>\*</sup>...}

\* TEXT

`\MATHUNDERTEXTTEXTENSIBLE` {<sup>1</sup>...} {<sup>2</sup>...}

1 TEXT  
2 TEXT

`\MATHUNSTACKED`

`\mathupright`

`\mathword` <sup>1</sup>... {<sup>2</sup>...}

1 TEXT OPT  
2 TEXT

`\mathwordbf` <sup>1</sup>... {<sup>2</sup>...}

1 TEXT OPT  
2 TEXT

`\mathwordbi` <sup>1</sup>... {<sup>2</sup>...}

1 TEXT OPT  
2 TEXT

`\mathwordbs` <sup>1</sup>... {<sup>2</sup>...}

1 TEXT OPT  
2 TEXT

`\mathwordit` <sup>1</sup>... {<sup>2</sup>...}

1 TEXT OPT  
2 TEXT

`\mathwordsl` <sup>1</sup>... {<sup>2</sup>...}

1 TEXT OPT  
2 TEXT

`\mathwordtf` <sup>1</sup>... {<sup>2</sup>...}

1 TEXT OPT  
2 TEXT

$\backslash\maxaligned \{...\}$ *    CONTENT
$\backslash\mbox \{...\}$ *    CONTENT
$\backslash\measure \{...\}$ *    NAME
$\backslash\measured \{...\}$ *    NAME
$\backslash\medskip$
$\backslash\medspace$
$\backslash\mequal \{...\} \{...\}$ 1    TEXT        OPT        OPT 2    TEXT
$\backslash\meritko \left[ \overset{1}{...} \right] \left[ ..., ... \overset{2}{=} ..., ... \right] \overset{3}{\{...\}}$ 1    NAME        OPT        OPT 2    inherits: \setupscale 3    CONTENT
$\backslash\mesic \{...\}$ *    NUMMER
$\backslash\message \{...\}$ *    TEXT
$\backslash\metaTeX$
$\backslash\mezera$
$\backslash\mfence \{...\}$ *    CHARACTER
$\backslash\mfunction \{...\}$ *    CONTENT
$\backslash\mfunctionlabeltext \{...\}$ *    NAME
$\backslash\mhbox \{...\}$ *    CONTENT
$\backslash\mhookleftarrow \{...\} \{...\}$ 1    TEXT        OPT        OPT 2    TEXT
$\backslash\mhookrightarrow \{...\} \{...\}$ 1    TEXT        OPT        OPT 2    TEXT
$\backslash\middlealigned \{...\}$ *    CONTENT

$\backslash\text{middlebox } \{...\}$ *    CONTENT
$\backslash\text{midhbox } \{...\}$ *    CONTENT
$\backslash\text{minimalhbox } \overset{1}{...} \overset{2}{\{...\}}$ 1    TEXT            OPT 2    CONTENT
$\backslash\text{mixedcaps } \{...\}$ *    TEXT
$\backslash\text{mkvibuffer } [...\overset{*}{...}]$ *    BUFFER            OPT
$\backslash\text{mLeftarrow } \overset{1}{\{...\}} \overset{2}{\{...\}}$ 1    TEXT            OPT        OPT 2    TEXT
$\backslash\text{mLeftrightarrow } \overset{1}{\{...\}} \overset{2}{\{...\}}$ 1    TEXT            OPT        OPT 2    TEXT
$\backslash\text{mleftarrow } \overset{1}{\{...\}} \overset{2}{\{...\}}$ 1    TEXT            OPT        OPT 2    TEXT
$\backslash\text{mleftharpoondown } \overset{1}{\{...\}} \overset{2}{\{...\}}$ 1    TEXT            OPT        OPT 2    TEXT
$\backslash\text{mleftharpoonup } \overset{1}{\{...\}} \overset{2}{\{...\}}$ 1    TEXT            OPT        OPT 2    TEXT
$\backslash\text{mleftrightarrow } \overset{1}{\{...\}} \overset{2}{\{...\}}$ 1    TEXT            OPT        OPT 2    TEXT
$\backslash\text{mleftrightharpoons } \overset{1}{\{...\}} \overset{2}{\{...\}}$ 1    TEXT            OPT        OPT 2    TEXT
$\backslash\text{mmapsto } \overset{1}{\{...\}} \overset{2}{\{...\}}$ 1    TEXT            OPT        OPT 2    TEXT
$\backslash\text{moduleparameter } \overset{1}{\{...\}} \overset{2}{\{...\}}$ 1    FILE 2    KEY
$\backslash\text{molecule } \{...\}$ *    CONTENT
$\backslash\text{mono}$
$\backslash\text{mononormal}$



\NormalizeFontHeight \ <sup>1</sup> ... { <sup>2</sup> ...} { <sup>3</sup> ...} { <sup>4</sup> ...} 1 CSNAME 2 TEXT 3 DIMENSION 4 FONT
\NormalizeFontWidth \ <sup>1</sup> ... { <sup>2</sup> ...} { <sup>3</sup> ...} { <sup>4</sup> ...} 1 CSNAME 2 TEXT 3 DIMENSION 4 FONT
\NormalizeTextHeight { <sup>1</sup> ...} { <sup>2</sup> ...} { <sup>3</sup> ...} 1 FONT 2 DIMENSION 3 TEXT
\NormalizeTextWidth { <sup>1</sup> ...} { <sup>2</sup> ...} { <sup>3</sup> ...} 1 FONT 2 DIMENSION 3 TEXT
\nadtrzeno { <sup>*</sup> ...} * TEXT
\namedheadnumber { <sup>*</sup> ...} * ABSCHNITT
\namedstructureheadlocation { <sup>*</sup> ...} * ABSCHNITT
\namedstructureuservariable { <sup>1</sup> ...} { <sup>2</sup> ...} 1 ABSCHNITT 2 KEY
\namedstructurevariable { <sup>1</sup> ...} { <sup>2</sup> ...} 1 ABSCHNITT 2 KEY
\namedtaggedlabeltexts { <sup>1</sup> ...} { <sup>2</sup> ...} { <sup>3</sup> ...} { <sup>4</sup> ...} { <sup>5</sup> ...} 1 NAME 2 NAME 3 NAME 4 NAME 5 CONTENT
\nastavbarvu [ <sup>*</sup> ...] * FILE
\nastavbarvy [..., <sup>*</sup> ...,...] * status = start stop spot = ano ne expanzen = ano ne faktor = ano ne rgb = ano ne cmyk = ano ne konverze = ano ne vzdy pagecolormodel = auto zadny NAME barvatextu = COLOR intent = overprint knockout zadny
\nastavbilamista [..., <sup>*</sup> ...,...] * fixuj fixne prizpusobivostTradek pulradku quarterline zadny male stredni velke implicitni DIMENSION



\nastavblok [...,<sup>1</sup>...] [...,<sup>2</sup>...]

1 NAME OPT  
2 pred = BEFEHL  
po = BEFEHL  
vnitrni = BEFEHL  
pismo = STYLE BEFEHL  
barva = COLOR

\nastavbloksekce [...,<sup>1</sup>...] [...,<sup>2</sup>...]

1 NAME OPT  
2 stranka = inherits: \strana  
pred = BEFEHL  
po = BEFEHL  
cislo = ano ne

\nastavbuffer [...,<sup>1</sup>...] [...,<sup>2</sup>...]

1 BUFFER OPT  
2 pred = BEFEHL  
po = BEFEHL

\nastavcernelinky [...,<sup>\*</sup>...]

\* sirka = max DIMENSION  
vyska = max DIMENSION  
hloubka = max DIMENSION  
vzdalenost = DIMENSION  
n = NUMMER  
alternativa = a b  
pismo = STYLE BEFEHL  
barva = COLOR  
typ = mp ano ne  
mp = NAME

\nastavcislonadpisu [...<sup>1</sup>...] [...<sup>2</sup>...]

1 ABSCHNITT  
2 [-+]NUMMER

\nastavcislostrany [...,<sup>\*</sup>...]

\* inherits: \setupuserpagenumber

\nastavcislovaniodstavcu [...,<sup>\*</sup>...]

\* status = start stop radek reset  
vzdalenost = DIMENSION  
pismo = STYLE BEFEHL  
barva = COLOR

\nastavcislovaniradku [...,<sup>1</sup>...] [...,<sup>2</sup>...]

1 NAME OPT  
2 start = NUMMER  
krok = NUMMER  
metoda = stranka prvni dalsi  
konverze = NAME  
pokracovat = ano ne  
misto = text begin end implicitni vlevo vpravo uvnitr vnejsi ivlevo ivpravo marginalie naokraj  
vzdalenost = DIMENSION  
zarovnani = uvnitr vnejsi flushleft flushright vlevo vpravo nastred auto  
prikaz = \...##1  
vlevo = BEFEHL  
vpravo = BEFEHL  
marginalie = DIMENSION  
sirka = marginalie DIMENSION  
pismo = STYLE BEFEHL  
barva = COLOR

`\nastavcislovanistran [...,.*=...]`

```
* alternativa = jednostranne dvoustranny
stranka      = inherits: \strana
strut        = ano ne
prikaz       = \...##1
vlevo        = BEFEHL
vpravo       = BEFEHL
status       = start stop
sirka        = DIMENSION
misto        = zahlavi upati vlevo nastred vpravo ivlevo ivpravo marginalie naokraji naokraji textovahrana
pismeno      = STYLE BEFEHL
barva        = COLOR
```

`\nastavcitaci [...,.*=...]`

```
* inherits: \setupdelimitedtext
```

`\nastavdeleniplvoucichobjektu [...,.*=...]`

```
* pred      = BEFEHL
po          = BEFEHL
mezi        = BEFEHL
radky       = auto NUMMER
konverze    = NAME
```

`\nastavdelitko [...,.*=...]`

```
* znak = normalni siroce
```

`\nastavdolnitexty [...1.] [...2.] [...3.] [...4.] [...5.]`

```
1 text marginalie hranaOPT OPT OPT OPT OPT
2 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
3 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
4 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
5 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
```

`\nastaveni [...]`

```
* NAME
```

`\nastaveni {...}`

```
* NAME
```

`\nastavhorejsek [...1.] [...,.*2=...]`

```
1 text marginalie hranaOPT
2 inherits: \setuplayoutelement
```

`\nastavhornitexty [...1.] [...2.] [...3.] [...4.] [...5.]`

```
1 text marginalie hranaOPT OPT OPT OPT OPT
2 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
3 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
4 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
5 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
```

\nastavinterakci [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```

1  NAME                      OPT
2  status                    = start stop
   pismeno                   = STYLE BEFEHL
   barva                     = COLOR
   kontrastnibarva          = COLOR
   titul                    = TEXT
   podtitulek               = COLOR
   autor                    = TEXT
   datum                    = TEXT
   keyword                  = TEXT
   zaostreni                 = standardni ramecek sirka minsirka vyska minvyska prizpusobive tight
   menu                     = zap vyp
   fieldlayer               = auto NAME
   pocitat                  = REFERENCE
   klik                     = ano ne
   obrazovka                = normalni novy
   stranka                  = ano ne stranka jmeno auto
   oteviakci                = REFERENCE
   zavriakci                = REFERENCE
   akceotevrenistranky      = REFERENCE
   akcezavrenistranky       = REFERENCE
   sadasymbolu              = NAME
   vyska                    = DIMENSION
   hloubka                  = DIMENSION
   focusoffset              = DIMENSION

```

\nastavinterakci [...]

```

*  NAME                      OPT

```

\nastavinterakcnilistu [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```

1  NAME                      OPT
2  alternativa              = a b c d e f g
   status                   = start stop
   prikaz                   = CSNAME
   sirka                    = DIMENSION
   vyska                    = DIMENSION max siroky
   hloubka                  = DIMENSION max
   vzdalenost               = DIMENSION
   krok                     = male stredni velke
   barvapoziadi             = COLOR
   pismeno                   = STYLE BEFEHL
   barva                     = COLOR
   kontrastnibarva          = COLOR
   symbol                   = ano ne
   inherits: \nastavoramovani

```

\nastavinterakcnimenu [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```

1  NAME                      OPT
2  alternativa              = vertikalne horizontalne skryte
   category                 = NAME
   levyoffset               = prekryv ramecek zadny implicitni DIMENSION
   pravyoffset              = prekryv ramecek zadny implicitni DIMENSION
   offsetvrsku              = prekryv ramecek zadny implicitni DIMENSION
   offsetspodku             = prekryv ramecek zadny implicitni DIMENSION
   maxsirka                 = DIMENSION
   maxvyska                 = DIMENSION
   itemalign                = vlevo nastred vpravo flushleft flushright nizko vysoko nivy
   status                   = start prazdne lokalne
   vlevo                    = BEFEHL
   vpravo                   = BEFEHL
   vzdalenost               = prekryv DIMENSION
   pred                     = BEFEHL
   po                       = BEFEHL
   mezi                     = BEFEHL
   position                 = ano ne
   stredni                  = BEFEHL
   pismeno                   = STYLE BEFEHL
   barva                     = COLOR
   stejnastranka            = ano ne prazdne zadny normalni implicitni
   kontrastnibarva          = COLOR
   inherits: \nastavoramovani

```

\nastavinterakcniobrazovku [...,..<sup>\*</sup>...,...]

\* sirka = prizpusobive max tight DIMENSION  
vyska = prizpusobive max tight DIMENSION  
zpetnamezera = DIMENSION  
horoffset = DIMENSION  
offsethlavicky = DIMENSION  
svrchnamezera = DIMENSION  
volba = prizpusobive max jednostranne dvoustranny zalozka auto zadny implicitni fixne nasirku portrait  
stranka papir  
copies = NUMMER  
prodleva = zadny NUMMER

\nastavjazyk [...]<sup>1</sup> [...,..<sup>2</sup>...,...]

1 SPRACHE implicit<sup>OPT</sup>  
2 implicitni = SPRACHE  
status = start stop  
datum = inherits: \aktualnidatum  
patterns = FILE  
lefthyphenmin = NUMMER  
righthyphenmin = NUMMER  
lefthyphenchar = NUMMER  
righthyphenchar = NUMMER  
setups = NAME  
mezerovani = široky zhustene  
font = auto  
text = TEXT  
limittext = TEXT  
hyphen = TEXT  
compoundhyphen = TEXT  
leftcompoundhyphen = TEXT  
rightcompoundhyphen = TEXT  
citovatvlevo = BEFEHL  
citovatvpravo = BEFEHL  
citacevlevo = BEFEHL  
citacevpravo = BEFEHL  
leftspeech = BEFEHL  
rightspeech = BEFEHL  
vetavlevo = BEFEHL  
middlespeech = BEFEHL  
vetavpravo = BEFEHL  
midsentence = BEFEHL  
podvetavlevo = BEFEHL  
podvetavpravo = BEFEHL  
faktor = ano ne

\nastavkapitalky [...]<sup>1</sup> [...,..<sup>2</sup>...,...]

1 NAME <sup>OPT</sup>  
2 titul = ano ne  
sc = ano ne  
pismo = STYLE BEFEHL

\nastavkombinovanyseznam [...]<sup>1</sup> [...,..<sup>2</sup>...,...]

1 LISTE  
2 inherits: \nastavseznam

\nastaveniCOMBINEDLIST [...,..<sup>\*</sup>...,...]

\* inherits: \nastavseznam  
instances: content

\umisticontent [...,..<sup>\*</sup>...,...]

\* inherits: \nastavseznam<sup>OPT</sup>

`\nastavkomentar [...1,...] [...2,...]`

```
1 NAME OPT
2 status = start stop zadny
metoda = normalni skryte
symbol = Comment Napoveda Insert Klavesa Newparagraph Note Odstavec Default
sirka = prizpusobive DIMENSION
vyska = prizpusobive DIMENSION
hloubka = prizpusobive DIMENSION
titul = TEXT
podtitulek = TEXT
autor = TEXT
nx = NUMMER
ny = NUMMER
barva = COLOR
volba = xml max
textlayer = NAME
misto = levahrana pravahrana naokraji lev yokraj prav yokraj text vysoko zadny
vzdalenost = DIMENSION
mezera = ano
buffer = BUFFER
```

`\nastavkomentarstrany [...1,...]`

```
* misto = vlevo vpravo vrsek spodek zadny
status = start stop zadny
offset = DIMENSION
vzdalenost = DIMENSION
sirka = DIMENSION
vyska = DIMENSION
```

`\comment [...1] [...2,...] {...3}`

```
1 TEXT OPT OPT
2 inherits: \nastavkomentar
3 TEXT
```

`\nastavmarginalnilinky [...1] [...2,...]`

```
1 NUMMER OPT
2 inherits: \setupmarginrule
```

`\nastavmeziradkovoumezeru [...1,...] [...2,...]`

```
1 NAME OPT
2 radek = DIMENSION
vyska = NUMMER
hloubka = NUMMER
minvyska = NUMMER
mindepth = NUMMER
vzdalenost = DIMENSION
vrsek = NUMMER vyska
spodek = NUMMER
natahnout = NUMMER
shrink = NUMMER
```

`\nastavmeziradkovoumezeru [...1,...]`

```
* zap vyp reset auto male stredni velke NUMMER DIMENSION
```

`\nastavmeziradkovoumezeru [...1,...]`

```
* NAME
```

\nastavnadpis [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```

1  ABSCHNITT          OPT
2  frontpartlabel     = NAME
   bodypartlabel      = NAME
   appendixlabel       = NAME
   backpartlabel       = NAME
   expanzen            = ano ne xml
   catcodes            = NAME
   sectionresetset     = NAME
   sectionseparatorset = NAME
   sectionconversionset = NAME
   konverze            = NAME
   sectionstarter      = BEFEHL PROCESSOR->BEFEHL
   sectionstopper      = BEFEHL PROCESSOR->BEFEHL
   sectionset          = NAME
   sectionsegments     = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:*
                        ABSCHNITT:vse
   referenceprefix     = + - TEXT
   pismeno             = STYLE BEFEHL
   barva               = COLOR
   styltextu           = STYLE BEFEHL
   barvatextu          = COLOR
   stylcisla           = STYLE BEFEHL
   barvacisla          = COLOR
   propojeni           = ABSCHNITT
   vlastnicislo        = ano ne
   beforesection       = BEFEHL
   aftersection        = BEFEHL
   insidesection       = BEFEHL
   zvysujicicislo     = ano ne seznam prazdne
   umistihlavicku      = ano ne skryte prazdne
   cislo               = ano ne
   stranka             = inherits: \strana
   znaceni             = stranka reset
   zahlavi             = start stop vysoko zadny normalni prazdne zadneznaceni NAME
   text                = start stop vysoko zadny normalni prazdne zadneznaceni NAME
   upati               = start stop vysoko zadny normalni prazdne zadneznaceni NAME
   pred               = BEFEHL
   po                  = BEFEHL
   mezi                = BEFEHL
   pokracovat          = ano ne
   zarovnejtitul       = ano ne plvouciobjekt
   meziradkovamezera   = NAME
   interakce           = seznam odkaz
   internalgrid        = NAME
   mrizka              = normalni standardni ano striktni tolerantni vrsek spodek obe široky prizpusobive prvni
                        posledni vysoko jedna nizko zadny radek strut box min max nastred NAME
   zarovnnani          = inherits: \nastavzarovnnani
   tolerance           = inherits: \nastavtoleranci
   strut              = ano ne
   zaveseni            = radek široky prizpusobive zadny NUMBER
   marginalie          = DIMENSION
   odsadpristi         = ano ne auto
   alternativa         = text odstavec normalni marginalie naokraji vrsek nastred spodek reverse marginalnitext
                        NAME
   sirka               = DIMENSION
   numberwidth         = DIMENSION
   sirkatextu          = DIMENSION
   vzdalenost          = DIMENSION
   textdistance        = DIMENSION
   predchoziprikaz     = BEFEHL
   prikazpo            = BEFEHL
   prikaz              = \...##1##2
   textovyprikaz       = \...##1
   deeptextcommand     = \...##1
   ciselnyprikaz       = \...##1
   deepnumbercommand   = \...##1
   misto               = NAME

```

\nastavnadpisy [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```

1  ABSCHNITT          OPT
2  inherits: \nastavnadpis

```

\chapter [...<sup>1</sup>,...] {...<sup>2</sup>}

```

1  REFERENCE          OPT
2  TEXT

```

`\part [...,1...] {...}`

- 1 REFERENCE<sup>PT</sup>
- 2 TEXT

`\section [...,1...] {...}`

- 1 REFERENCE OPT
- 2 TEXT

`\subject [...,1...] {...}`

- 1 REFERENCE OPT
- 2 TEXT

`\subsection [...,1...] {...}`

- 1 REFERENCE OPT
- 2 TEXT

`\subsubject [...,1...] {...}`

- 1 REFERENCE OPT
- 2 TEXT

`\subsubsection [...,1...] {...}`

- 1 REFERENCE OPT
- 2 TEXT

`\subsubsubject [...,1...] {...}`

- 1 REFERENCE OPT
- 2 TEXT

`\subsubsubsection [...,1...] {...}`

- 1 REFERENCE OPT
- 2 TEXT

`\subsubsubsubject [...,1...] {...}`

- 1 REFERENCE OPT
- 2 TEXT

`\subsubsubsubsection [...,1...] {...}`

- 1 REFERENCE OPT
- 2 TEXT

`\subsubsubsubsubject [...,1...] {...}`

- 1 REFERENCE OPT
- 2 TEXT

`\title [...,1...] {...}`

- 1 REFERENCE OPT
- 2 TEXT

`\nastavodkazovani [...,*...] {...}`

- \* status = start stop
- expanzen = ano ne xml
- autofile = ano ne
- export = ano ne
- vlevo = BEFEHL
- vpravo = BEFEHL
- sirka = DIMENSION
- oboustranne = ano ne
- interakce = popisek text symbol vse
- oddelovac = BEFEHL
- prefix = + - TEXT

`\nastavodsazovani [...,*...]`

\* [-+]male [-+]stredni [-+]velke zadny ne ne prvni dalsi ano vzdy nikdy liche sude normalni reset toggle DIMENSION NAME

`\nastavodstavce [...]1 [...]2 [...]3 [...]`

```
1 NAME OPT OPT
2 kazdy NUMMER
3 n = NUMBER
  pred = BEFEHL
  po = BEFEHL
  sirka = DIMENSION
  vzdalenost = DIMENSION
  vyska = DIMENSION prizpusobive
  vrsek = BEFEHL
  spodek = BEFEHL
  zarovnani = inherits: \nastavzarovnani
  vnitorni = BEFEHL
  prikaz = BEFEHL
  linka = zap vyp
  tloustkalinky = DIMENSION
  barvalinky = COLOR
  pismeno = STYLE BEFEHL
  barva = COLOR
```

`\nastavodstavce [...]1 [...]2 [...]`

```
1 NAME:NUMBER OPT
2 n = NUMBER
  pred = BEFEHL
  po = BEFEHL
  sirka = DIMENSION
  vzdalenost = DIMENSION
  vyska = DIMENSION prizpusobive
  vrsek = BEFEHL
  spodek = BEFEHL
  zarovnani = inherits: \nastavzarovnani
  vnitorni = BEFEHL
  prikaz = BEFEHL
  linka = zap vyp
  tloustkalinky = DIMENSION
  barvalinky = COLOR
  pismeno = STYLE BEFEHL
  barva = COLOR
```

`\nastavopis [...]1 [...]2 [...]`

```
1 NAME OPT
2 lichyokraj = DIMENSION
  sudamarginalie = DIMENSION
  marginalie = ano ne standardni DIMENSION
  volba = mp lua xml parsed-xml nested tex context zadny NAME
  pismeno = STYLE BEFEHL
  barva = COLOR
  zarovnani = inherits: \nastavzarovnani
  radky = ano ne normalni hyphenated
  mezera = zap vyp normalni fixne natahnout
  keptogether = ano ne
  pred = BEFEHL
  po = BEFEHL
  strip = ano ne NUMBER
  range = NUMBER NAME
  tab = ano ne NUMBER
  escape = ano ne TEXT PROCESSOR->TEXT
  odsadpristi = ano ne auto
  pokracovat = ano ne
  start = NUMBER
  stop = NUMBER
  krok = NUMBER
  cislovani = soubor radek ne
  prazdny = inherits: \preskoc
```

`\nastavoramovanetexty [...]1 [...]2 [...]`

```
1 NAME OPT
2 inherits: \setupframedtext
```



`\framedtext [...,..1...,..] {...}`

1 inherits: \setupframedtext<sup>OPT</sup>  
2 CONTENT

`\nastavoramovani [.....1...] [.....2...,..]`

1 NAME<sup>OPT</sup>  
2 roh = pravouhly zaobleny NUMMER  
rohramecku = pravouhly zaobleny NUMMER  
rohpozadi = pravouhly zaobleny NUMMER  
polomer = DIMENSION  
polomerramecku = DIMENSION  
polomerpozadi = DIMENSION  
hloubka = DIMENSION  
hloubkramecku = DIMENSION  
hloubkapozadi = DIMENSION  
barvaramecku = COLOR  
rameceknahore = zap vyp NAME  
ramecekdole = zap vyp NAME  
ramecekvlevo = zap vyp NAME  
ramecekvpravo = zap vyp NAME  
region = ano ne  
tloustkalinky = DIMENSION  
offsetramecku = DIMENSION  
ramecek = zap vyp prekryv zadny  
pozadi = popredi barevne NAME  
offsetpozadi = ramecek DIMENSION  
component = NAME  
extras = BEFEHL  
foregroundstyle = STYLE BEFEHL  
foregroundcolor = COLOR  
setups = NAME  
offset = implicitni prekryv zadny DIMENSION  
sirka = lokalne prizpusobive max siroky fixne DIMENSION  
vyska = prizpusobive max siroky DIMENSION  
zarovnani = inherits: \nastavzarovnani  
strut = ano ne zadny lokalne globalne  
autostrut = ano ne  
misto = vyska podlehloubky vysoko nizko vrsek nastred spodek radek nivy visici drzet rovnice matematika normalni  
autosirka = ano ne sila  
radky = NUMMER  
vrsek = BEFEHL  
spodek = BEFEHL  
prazdny = ano ne  
profile = NAME  
prazdne = ano ne  
loffset = DIMENSION  
roffset = DIMENSION  
toffset = DIMENSION  
boffset = DIMENSION  
orientation = NUMMER

`\nastavorez [...,..*...,..]`

\* status = start stop  
sirka = DIMENSION  
vyska = DIMENSION  
hoffset = DIMENSION  
voffset = DIMENSION  
x = NUMMER  
y = NUMMER  
nx = NUMMER  
ny = NUMMER  
sx = NUMMER  
sy = NUMMER  
levyoffset = DIMENSION  
pravyoffset = DIMENSION  
offsetvrsku = DIMENSION  
offsetspodku = DIMENSION  
mp = NAME  
n = NUMMER  
offset = DIMENSION

`\nastavotoceni [...,..*...,..]`

\* misto = prizpusobive siroky podlehloubky vysoko nastred implicitni normalni  
rotace = vlevo vpravo uvnitr vnejsi NUMMER  
inherits: \nastavoramovani

\nastavpaletu [...]

\* NAME

\nastavplvouciobjekt [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1	SINGULAR	OPT	
2	odsadpristi	=	ano ne auto
	implicitni	=	inherits: \placefloat
	fallback	=	inherits: \placefloat
	vnitrni	=	BEFEHL
	kriterium	=	DIMENSION
	metoda	=	NUMMER
	sidemethod	=	NUMMER
	textmethod	=	NUMMER
	sidealign	=	vyska podlehloubky radek pulradku mrizka normalni
	mrizka	=	CD:STRING
	lokalne	=	ano ne
	prikaz	=	\...##1
	availablewidth	=	DIMENSION
	availableheight	=	DIMENSION
	minsirka	=	DIMENSION
	maxsirka	=	DIMENSION
	misto	=	vlevo vpravo nastred flushleft flushright center max uvnitr vnejsi innermargin outermargin inneredge outeredge zpetnamezera cutspace levyokraj pravyokraj levahrana pravahrana
	vzdalenostlevehookraje	=	DIMENSION
	vzdalenostpravehookraje	=	DIMENSION
	levyokraj	=	DIMENSION
	pravyokraj	=	DIMENSION
	innermargin	=	DIMENSION
	outermargin	=	DIMENSION
	bottombefore	=	BEFEHL
	bottomafter	=	BEFEHL
	expanzen	=	ano ne xml
	referenceprefix	=	+ - TEXT
	xmlsetup	=	NAME
	catcodes	=	NAME
	freeregion	=	ano ne
	mezerapred	=	zadny inherits: \preskoc
	mezeraza	=	zadny inherits: \preskoc
	sirka	=	DIMENSION
	vyska	=	DIMENSION
	offset	=	DIMENSION zadny prekryv
	bocnimezerapred	=	zadny inherits: \preskoc
	bocnimezeraza	=	zadny inherits: \preskoc
	marginalie	=	DIMENSION
	nvrsek	=	DIMENSION
	nspodek	=	DIMENSION
	krok	=	male stredni velke radek podlehloubky
	nradky	=	NUMMER
	cache	=	ano ne

\nastavplvouciobjekty [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1	SINGULAR	OPT	
2	inherits: \nastavplvouciobjekt		

\nastavpodcislostrany [...<sup>\*</sup>,...]

\* inherits: \setupcounter

\nastavpole [...<sup>1</sup>] [...<sup>2</sup>,...] [...<sup>3</sup>,...] [...<sup>4</sup>,...] [...<sup>5</sup>,...]

1	NAME	OPT	OPT	OPT	OPT
2	reset	popisek	ramecek	horizontalne	vertikalne
3	inherits: \setupfieldtotalframed				
4	inherits: \setupfieldlabelframed				
5	inherits: \setupfieldcontentframed				

`\nastavpolozky [...1,...] [...2,...]`

```
1 NAME OPT
2 alternativa = vlevo vpravo vrsek spodek naokraji
  sirkatextu = DIMENSION
  sirka = DIMENSION
  vzdalenost = DIMENSION
  symbol = zadny NAME
  zarovnani = vlevo nastred vpravo flushleft flushright uvnitr vnejsi marginalie
  textalign = vlevo nastred vpravo flushleft flushright uvnitr vnejsi
  n = NUMMER
  pred = BEFEHL
  po = BEFEHL
  mezi = BEFEHL
```

`\nastavpopisek [...1,...] [...2,...]`

```
1 NAME OPT
2 inherits: \setupfloatcaption
```

`\nastavpopisky [...1,...] [...2,...]`

```
1 NAME OPT
2 inherits: \setupfloatcaption
```

`\umistifigure [...1,...] [...2,...] {...3} {...4}`

```
1 split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji levyokraj prav yokraj levahrana
  pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku
  mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko
  obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective zahlavi upati
2 REFERENCE
3 TEXT
4 CONTENT
```

`\umistigraphic [...1,...] [...2,...] {...3} {...4}`

```
1 split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji levyokraj prav yokraj levahrana
  pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku
  mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko
  obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective zahlavi upati
2 REFERENCE
3 TEXT
4 CONTENT
```

`\umistichemical [...1,...] [...2,...] {...3} {...4}`

```
1 split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji levyokraj prav yokraj levahrana
  pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku
  mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko
  obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective zahlavi upati
2 REFERENCE
3 TEXT
4 CONTENT
```

`\umistiintermezzo [...1,...] [...2,...] {...3} {...4}`

```
1 split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji levyokraj prav yokraj levahrana
  pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku
  mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko
  obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective zahlavi upati
2 REFERENCE
3 TEXT
4 CONTENT
```

`\umistitable [...1,...] [...2,...] {...3} {...4}`

```
1 split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji levyokraj prav yokraj levahrana
  pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku
  mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko
  obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective zahlavi upati
2 REFERENCE
3 TEXT
4 CONTENT
```

\nastavpozadi [...,<sup>1</sup>...] [...,<sup>2</sup>...]

1 NAME OPT  
2 status = start stop  
levyoffset = DIMENSION  
pravyoffset = DIMENSION  
offsetvrsku = DIMENSION  
offsetspodku = DIMENSION  
pred = BEFEHL  
po = BEFEHL  
inherits: \nastavoramovani

\nastavpozadi [...,<sup>1</sup>...] [...,<sup>2</sup>...]

1 papir stranka levas<sup>PT</sup>tranka pravastranka text skryte  
2 status = start stop  
inherits: \nastavoramovani

\nastavprechodstrany [...]

\* reset auto start nahodny NUMMER

\nastavpreskok [...,<sup>\*</sup>...]

\* inherits: \vspacing OPT

\nastavprogramy [...,<sup>\*</sup>...]

\* pismeno = STYLE BEFEHL  
barva = COLOR

\nastavradkovani [...]

\* fixne zhustene sirok<sup>PT</sup>y

\nastavradky [...,<sup>1</sup>...] [...,<sup>2</sup>...]

1 NAME OPT  
2 volba = zhustene  
pred = BEFEHL  
po = BEFEHL  
mezi = BEFEHL  
odsazovani = inherits: \nastavodsazovani  
zarovnani = inherits: \nastavzarovnani  
mezera = ano zap vyp fixne implicitni  
prikaz = BEFEHL  
pismeno = STYLE BEFEHL  
barva = COLOR  
vlevo = BEFEHL  
vpravo = BEFEHL

\nastavrejstrik [...]<sup>1</sup> [...,...<sup>2</sup>...,...]

```

1  NAME NAME:NUMMER OPT
2  referencemethod      = vpred
   expanzen             = ano ne xml
   vlastnicislo         = ano ne
   xmlsetup             = NAME
   alternativa          = a b A B
   metoda               = implicitni pred po prvni posledni ch mm zm pm mc zc pc uc
   compress              = ano ne vse
   kriterium            = lokalne text aktualni predchozi vse ABSCHNITT
   pageprefixseparatorset = BEFEHL
   pageprefixconversionset = NAME
   pageprefixstarter     = BEFEHL PROCESSOR->BEFEHL
   pageprefixstopper     = BEFEHL PROCESSOR->BEFEHL
   pageprefixset         = NAME
   pageprefixsegments   = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:*
                        ABSCHNITT:vse

   pageprefixconnector   = BEFEHL
   pageprefix           = ano ne
   pageseparatorset      = NAME
   pageconversionset     = NAME
   pagestarter           = BEFEHL PROCESSOR->BEFEHL
   pagestopper           = BEFEHL PROCESSOR->BEFEHL
   pagesegments          = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:vse
   maxsirka              = DIMENSION
   indikator             = ano ne
   pred                  = BEFEHL
   po                    = BEFEHL
   prikaz                = \...##1
   textovyprikaz         = \...##1
   deeptextcommand       = \...##1
   strankovyprikaz       = \...##1
   vzdalenost            = DIMENSION
   interakce             = text cislostranky
   cislostranky          = ano ne
   symbol                = a n zadny 1 2 BEFEHL
   language              = implicitni DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scn SPRACHE
   pismeno               = STYLE BEFEHL
   barva                 = COLOR
   styltextu             = STYLE BEFEHL
   barvatextu            = COLOR
   stylstranky           = STYLE BEFEHL
   barvastranky          = COLOR
   n                     = NUMBER
   rovnovaha             = ano ne
   zarovnnani            = inherits: \nastavzarovnnani
   numberorder           = cisla

```

\nastavrejstrik [...,<sup>1</sup>...] [...,<sup>2</sup>...] [...,<sup>3</sup>...,...]

```
1  NAME                      OPT          OPT
2  NUMMER
3  referencemethod           = vpred
   expanzen                  = ano ne xml
   vlastnicislo              = ano ne
   xmlsetup                  = NAME
   alternativa               = a b A B
   metoda                   = implicitni pred po prvni posledni ch mm zm pm mc zc pc uc
   compress                  = ano ne vse zhustene
   kriterium                 = lokalne text aktualni predchozi vse ABSCHNITT
   pageprefixseparatorset    = BEFEHL
   pageprefixconversionset   = NAME
   pageprefixstarter         = BEFEHL PROCESSOR->BEFEHL
   pageprefixstopper         = BEFEHL PROCESSOR->BEFEHL
   pageprefixset             = NAME
   pageprefixsegments        = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:*
                               ABSCHNITT:vse
   pageprefixconnector       = BEFEHL
   pageprefix                = ano ne
   pageseparatorset          = NAME
   pageconversionset         = NAME
   pagestarter               = BEFEHL PROCESSOR->BEFEHL
   pagestopper               = BEFEHL PROCESSOR->BEFEHL
   pagesegments              = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse
   maxsirka                  = DIMENSION
   indikator                 = ano ne
   pred                      = BEFEHL
   po                        = BEFEHL
   prikaz                    = \...##1
   textovyprikaz             = \...##1
   deeptextcommand           = \...##1
   strankovyprikaz           = \...##1
   vzdalenost                = DIMENSION
   interakce                 = text cislostranky
   cislostranky              = ano ne
   symbol                    = a n zadny 1 2 BEFEHL
   language                  = implicitni DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scn SPRACHE
   pismo                     = STYLE BEFEHL
   barva                     = COLOR
   styltextu                 = STYLE BEFEHL
   barvatextu                = COLOR
   stylstranky               = STYLE BEFEHL
   barvastranky              = COLOR
   n                         = NUMMER
   rovnovaha                 = ano ne
   zarovnani                 = inherits: \nastavzarovnani
   numberorder               = cisla
```

\nastaveniREGISTER [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

```
1  NUMMER                      OPT
2  inherits: \nastavrejstrik
instances: index
```

\nastavrovnice [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

```
1  NAME                      OPT
2  inherits: \setupformula
```

\nastavsadusymbolu [...]

```
*  NAME
```

\nastavseznam [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

```

1 LISTE OPT
2 status = start stop
misto = zadny zde
typ = simple prikaz userdata
kriterium = lokalne uvod odkaz SECTIONBLOCK:odkaz vse SECTIONBLOCK:vse text SECTIONBLOCK:text
aktualni SECTIONBLOCK:aktualni zde predchozi SECTIONBLOCK:predchozi komponenta ABSCHNITT
SECTIONBLOCK:ABSCHNITT

seznam = NAME
sirka = prizpusobive siroky auto DIMENSION
vyska = prizpusobive siroky DIMENSION
hloubka = prizpusobive siroky DIMENSION
symbol = jedna dve tri zadny implicitni
popisek = ano ne zadny NAME
starter = BEFEHL
predel = BEFEHL
prikaz = \...##1##2##3
ciselnyprikaz = \...##1
textovyprikaz = \...##1
strankovyprikaz = \...##1
cislostranky = ano ne vzdy
cislonadpisu = ano ne vzdy
pred = BEFEHL
po = BEFEHL
mezi = BEFEHL
marginalie = zadny DIMENSION
vzdalenost = zadny DIMENSION
zarovnejtitul = ano ne
numberalign = vlevo vpravo nastred flushleft flushright uvnitr vnejsi
zarovnani = inherits: \nastavzarovnani
zaveseni = ano ne
vlevo = BEFEHL
vpravo = BEFEHL
interakce = ano ne vse cislo text titul stranka cislooddilu cislostranky
limittext = ano ne TEXT
pismeno = STYLE BEFEHL
barva = COLOR
stylcisla = STYLE BEFEHL
barvacisla = COLOR
styltextu = STYLE BEFEHL
barvatextu = COLOR
stylstranky = STYLE BEFEHL
barvastranky = COLOR
odkaz = NUMMER
extras = NAME
order = prikaz vse titul
alternativa = a b c d e f g vlevo vpravo vrsek spodek prikaz zadny interactive odstavec horizontalne
vertikalne NAME

maxsirka = DIMENSION
pageprefix = ano ne
pageprefixseparatorset = NAME
pageprefixconversionset = NAME
pageprefixset = NAME
pageprefixsegments = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:*
ABSCHNITT:vse
pageprefixconnector = BEFEHL PROCESSOR->BEFEHL
pageconversionset = NAME
pagestarter = BEFEHL PROCESSOR->BEFEHL
pagestopper = BEFEHL PROCESSOR->BEFEHL
inherits: \setupcounterinherits: \nastavoramovani

```

\nastavsirkucary [...]

\* male stredni velke DIMENSION

\nastavsloupce [...,<sup>\*</sup>...,...]

```

* n = NUMMER
vzdalenost = DIMENSION
volba = pozadi
offset = DIMENSION
prikaz = \...##1
vyska = DIMENSION
smer = vlevo vpravo
rovnovaha = ano ne
zarovnani = setupalign
tolerance = setuptolerance
prazdny = inherits: \preskoc
nvrsek = NUMMER
linka = zap vyp BEFEHL

```

`\nastavspodek [...]1 [...,...2...,...]`

- 1 text marginalie<sup>OPT</sup> hrana
- 2 inherits: \setuplayoutelement

`\nastavsynonyma [...]1,... [...,...2...,...]`

- 1 SINGULAR<sup>OPT</sup>
- 2 expanden = ano ne xml
- alternativa = prvni posledni normalni NAME
- dalsi = BEFEHL
- prikaz = \...##1##2##3
- textovyprikaz = \...##1
- synonymcommand = \...##1
- language = implicitni DIN<sub>5007-1</sub> DIN<sub>5007-2</sub> Duden de-DE de-CH de-AT ru-iso9 ocs-scn SPRACHE
- metoda = implicitni pred po prvni posledni ch mm zm pm mc zc pc uc
- kriterium = aktualni predchozi lokalne text vse ABSCHNITT
- pismeno = STYLE BEFEHL
- barva = COLOR
- styltextu = STYLE BEFEHL
- barvatextu = COLOR
- stilsynonyma = STYLE BEFEHL
- barvasynonyma = COLOR

`\abbreviation [...]1 {...}2 {...}3`

- 1 NAME<sup>OPT</sup>
- 2 TEXT
- 3 CONTENT

`\nastavtabelaci [...]1 [...]2 [...,...3...,...]`

- 1 NAME<sup>OPT</sup>
- 2 NAME<sup>OPT</sup>
- 3 inherits: \setuptabulation

`\nastavtabulky [...,...*...,...]`

- \* text = DIMENSION max
- split = ano ne opakovat auto
- ramecek = zap vyp
- NL = inherits: \preskoc
- VL = male stredni velke zadny NUMMER
- HL = male stredni velke zadny NUMMER
- vzdalenost = male stredni velke zadny
- zarovnani = vlevo nastred vpravo
- prikazy = BEFEHL
- zakladnifont = inherits: \nastavzakladnifont
- tloustkalinky = DIMENSION
- vyska = strut NUMMER
- hloubka = strut NUMMER
- openup = DIMENSION

`\nastavtenkelinky [...,...*...,...]`

- \* vyska = max DIMENSION
- hloubka = max DIMENSION
- pozadi = barevne
- ramecek = zap vyp
- tloustkalinky = DIMENSION
- alternativa = a b c zadny
- barvapoziadi = COLOR
- barva = COLOR
- meziradkovamezera = male stredni velke NUMMER
- pred = BEFEHL
- po = BEFEHL
- mezi = BEFEHL
- n = NUMMER

`\nastavtext [...]1 [...,...2...,...]`

- 1 text marginalie<sup>OPT</sup> hrana
- 2 inherits: \setuplayoutelement



```

\nastavtextovetlinky [...,\stackrel{*}{...}]
*   pred          = BEFEHL
    po            = BEFEHL
    mezi          = BEFEHL
    tloustkalinky = DIMENSION
    misto         = vlevo naokraji
    pismeno       = STYLE BEFEHL
    barva         = COLOR
    barvalinky    = COLOR
    sirka         = DIMENSION
    vyska        = DIMENSION
    vzdalenost    = DIMENSION
    korekcehloubky = zap vyp
    zakladnifont  = inherits: \nastavzakladnifont

```

```

\nastaveniLABELtext [...,\stackrel{1}{...}\stackrel{2}{...}]
1   SPRACHE      OPT
2   KEY = VALUE
instances: head label mathlabel taglabel unit operator prefix suffix btxlabel

```

```

\presetbtxlabeltext [...,\stackrel{1}{...}\stackrel{2}{...}]
1   SPRACHE      OPT
2   KEY = VALUE

```

```

\presetheadtext [...,\stackrel{1}{...}\stackrel{2}{...}]
1   SPRACHE      OPT
2   KEY = VALUE

```

```

\presetlabeltext [...,\stackrel{1}{...}\stackrel{2}{...}]
1   SPRACHE      OPT
2   KEY = VALUE

```

```

\presetmathlabeltext [...,\stackrel{1}{...}\stackrel{2}{...}]
1   SPRACHE      OPT
2   KEY = VALUE

```

```

\presetoperatortext [...,\stackrel{1}{...}\stackrel{2}{...}]
1   SPRACHE      OPT
2   KEY = VALUE

```

```

\presetprefixtext [...,\stackrel{1}{...}\stackrel{2}{...}]
1   SPRACHE      OPT
2   KEY = VALUE

```

```

\presetsuffixtext [...,\stackrel{1}{...}\stackrel{2}{...}]
1   SPRACHE      OPT
2   KEY = VALUE

```

```

\presettaglabeltext [...,\stackrel{1}{...}\stackrel{2}{...}]
1   SPRACHE      OPT
2   KEY = VALUE

```

```

\presetunittext [...,\stackrel{1}{...}\stackrel{2}{...}]
1   SPRACHE      OPT
2   KEY = VALUE

```

```

\nastavtexttety [...]\stackrel{1}{...}\stackrel{2}{...}\stackrel{3}{...}\stackrel{4}{...}\stackrel{5}{...}
1   text marginalie hran OPT OPT OPT OPT OPT
2   datum cislostranky BESCHRIFTUNG TEXT BEFEHL
3   datum cislostranky BESCHRIFTUNG TEXT BEFEHL
4   datum cislostranky BESCHRIFTUNG TEXT BEFEHL
5   datum cislostranky BESCHRIFTUNG TEXT BEFEHL

```

\nastavtextyupati [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...] [<sup>4</sup>...] [<sup>5</sup>...]

1 text marginalie hrana OPT OPT OPT OPT OPT  
2 datum cislostranky BESCHRIFTUNG TEXT BEFEHL  
3 datum cislostranky BESCHRIFTUNG TEXT BEFEHL  
4 datum cislostranky BESCHRIFTUNG TEXT BEFEHL  
5 datum cislostranky BESCHRIFTUNG TEXT BEFEHL

\nastavtextyzahlavi [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...] [<sup>4</sup>...] [<sup>5</sup>...]

1 text marginalie hrana OPT OPT OPT OPT OPT  
2 datum cislostranky BESCHRIFTUNG TEXT BEFEHL  
3 datum cislostranky BESCHRIFTUNG TEXT BEFEHL  
4 datum cislostranky BESCHRIFTUNG TEXT BEFEHL  
5 datum cislostranky BESCHRIFTUNG TEXT BEFEHL

\nastavtoleranci [...\*...]

\* horizontalne vertikalne velmistriktni striktni tolerantni velmitolerantni mezera natahnout

\nastavtrideni [...<sup>1</sup>...] [...<sup>2</sup>...]

1 SINGULAR OPT  
2 expanzen = ano ne xml  
alternativa = prvni posledni normalni NAME  
dalsi = BEFEHL  
prikaz = \...#1#2#3  
textovyprikaz = \...#1  
synonymcommand = \...#1  
language = implicitni DIN\_5007-1 DIN\_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scn SPRACHE  
metoda = implicitni pred po prvni posledni ch mm zm pm mc zc pc uc  
kriterium = aktualni predchozi lokalne text vse ABSCHNITT  
pismo = STYLE BEFEHL  
barva = COLOR  
styltextu = STYLE BEFEHL  
barvatextu = COLOR  
stylsynonyma = STYLE BEFEHL  
barvasynonyma = COLOR

\logo [<sup>1</sup>...] {<sup>2</sup>...}

1 NAME OPT  
2 CONTENT

\nastavtype [...<sup>1</sup>...] [...<sup>2</sup>...]

1 NAME OPT  
2 volba = mp lua xml parsed-xml nested tex context zadny NAME  
prikaz = CSNAME  
vlevo = BEFEHL  
vpravo = BEFEHL  
tab = ano ne NUMMER  
compact = absolutni posledni vse  
escape = ano ne TEXT PROCESSOR->TEXT  
pismo = STYLE BEFEHL  
barva = COLOR  
radky = ano ne normalni hyphenated  
mezera = zap vyp normalni fixne natahnout

\nastavumisteniprotejsku [...\*...]

\* status = start stop  
pred = BEFEHL  
po = BEFEHL  
mezi = BEFEHL

\nastavumistovani [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```
1 NAME OPT
2 offset = ano ne
jednotka = ex em pt in cm mm sp bp pc dd cc nc
status = start prekryv
xoffset = DIMENSION
yoffset = DIMENSION
xkrok = absolutni relativni
ykrok = absolutni relativni
xmeritko = NUMMER
ymeritko = NUMMER
xfaktor = NUMMER
yfaktor = NUMMER
faktor = NUMMER
meritko = NUMMER
```

\nastavupati [...<sup>1</sup>] [...<sup>2</sup>,...]

```
1 text marginalieOPTstrana
2 inherits: \setuplayoutelement
```

\nastavupravu [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```
1 NAME OPT
2 stranka = inherits: \strana
prikaz = BEFEHL
sirka = DIMENSION
vyska = DIMENSION
zarovnani = inherits: \nastavzarovnani
setups = NAME
vrsek = BEFEHL
spodek = BEFEHL
pred = BEFEHL
po = BEFEHL
misto = vrsek
odkaz = REFERENCE
pagestate = start stop
statuszahlavi = start stop vysoko prazdne zadny normalni
statusupati = start stop vysoko prazdne zadny normalni
statusvrsku = start stop vysoko prazdne zadny normalni
statusspodku = start stop vysoko prazdne zadny normalni
statustextu = start stop vysoko prazdne zadny normalni
oboustranne = ano ne prazdne
pismeno = inherits: \value-style
barva = COLOR
```

\nastavurl [...<sup>\*</sup>,...]

```
* pismeno = STYLE BEFEHL
barva = COLOR
```

\nastavusporadani [...<sup>\*</sup>,...]

```
* zablokovat zrcadleno dvoustranny negativ 90 180 270 reset pozadi normalni 2*16 2*8 2*4 2*2 2**2 2SIDE 2TOP
2UP 2DOWN 2*4*2 2*2*4 2TOPSIDE 2*8*Z 2*6*Z 1*8 1*4 3SIDE TRYPTICHON ZFLYER-8 ZFLYER-10 ZFLYER-12 MAPFLYER-12
DOUBLEWINDOW 1*2-Conference 1*4-Conference 2*2*2 2*2*3 XY NAME
```

\nastavvelikostpapiru [...<sup>1</sup>] [...<sup>2</sup>,...]

```
1 NAME OPT
2 vrsek = BEFEHL
spodek = BEFEHL
vlevo = BEFEHL
vpravo = BEFEHL
metoda = normalni zadny NAME
meritko = NUMMER
nx = NUMMER
ny = NUMMER
dx = DIMENSION
dy = DIMENSION
sirka = DIMENSION
vyska = DIMENSION
svrchnimezera = DIMENSION
zpetnamezera = DIMENSION
offset = DIMENSION
stranka = reset nasirku zrcadleno negativ otoceno 90 180 270 NAME
papier = reset nasirku zrcadleno negativ otoceno 90 180 270 NAME
volba = prizpusobive max
vzdalenost = DIMENSION
```

`\nastavvelikostpapiru [...,1...] [...,2...]`

- 1 reset nasirku zrcadleno negativ<sup>8PT</sup> otoceno 90<sup>OPT</sup> 180 270 NAME
- 2 reset nasirku zrcadleno negativ otoceno 90 180 270 NAME

`\nastavvsechnapole [...,1...] [...,2...,...]OPT [...,3...,...]OPT [...,4...,...]OPT`

- 1 reset popiscek ramecek horizontalne vertik<sup>OPT</sup>alne
- 2 inherits: \setupfieldtotalframed
- 3 inherits: \setupfieldlabelframed
- 4 inherits: \setupfieldcontentframed

`\nastavvycty [...,1...] [...,2...,...]OPT`

- 1 NAME<sup>OPT</sup>
- 2 inherits: \setupenumeration

`\nastaveniitemize [...,1...] [...,2...,...]OPT [...,3...,...]OPT`

- 1 kazdy NUMMER<sup>OPT</sup>
- 2 inherits: \setupitemgroup
- 3 inherits: \setupitemgroup

`\nastavvyplnovelinky [...,*...,...]`

- \* pred = BEFEHL
- po = BEFEHL
- n = NUMMER
- meziradkovamezera = male stredni velke NUMMER
- vzdalenost = DIMENSION
- sirka = prizpusobive siroky DIMENSION
- oddelovac = BEFEHL
- pismeno = STYLE BEFEHL
- barva = COLOR

`\nastavvyplnoveradky [...,*...,...]`

- \* pred = BEFEHL
- po = BEFEHL
- marginalie = DIMENSION
- sirka = DIMENSION
- vzdalenost = DIMENSION
- tloustkalinky = DIMENSION
- barva = COLOR

\nastavvzhled [<sup>1</sup>...] [<sup>2</sup>...,...]

```
1 NAME OPT
2 status = start stop normalni opakovat
  marginalie = DIMENSION
  hrana = DIMENSION
  vzdalenostokraje = DIMENSION
  vzdalenosthrany = DIMENSION
  vzdalenostlevehrany = DIMENSION
  vzdalenostpravehrany = DIMENSION
  vzdalenostlevehookraje = DIMENSION
  vzdalenostpravehookraje = DIMENSION
  vzdalenostvrsku = DIMENSION
  vzdalenostzahlavi = DIMENSION
  vzdalenostupati = DIMENSION
  vzdalenostspodku = DIMENSION
  prednastaveni = NAME
  levyokraj = DIMENSION
  pravyokraj = DIMENSION
  levahrana = DIMENSION
  pravahrana = DIMENSION
  zahlavi = DIMENSION
  upati = DIMENSION
  vrsek = DIMENSION
  spodek = DIMENSION
  zpetnamezera = DIMENSION
  svrchnamezera = DIMENSION
  setups = NAME
  cutspace = DIMENSION
  sirka = DIMENSION nastred prizpusobive
  bottomspace = DIMENSION
  radky = NUMMER
  vyska = DIMENSION nastred prizpusobive
  horoffset = DIMENSION
  offsethlavicky = DIMENSION
  sloupce = NUMMER
  vzdalenostsloupcu = DIMENSION
  metoda = implicitni normalni NAME
  misto = vlevo nastred vpravo vrsek spodek jednostranne dvoustranny
  sirkatextu = DIMENSION
  vyskatextu = DIMENSION
  nx = NUMMER
  ny = NUMMER
  dx = DIMENSION
  dy = DIMENSION
  meritko = NUMMER
  sx = NUMMER
  sy = NUMMER
  znaceni = zap vyp stranka prazdne barevne jedna dve ctyni
  mrizka = ano ne vyp
  textdistance = DIMENSION
  alternativa = implicitni normalni zlom NAME
  clipoffset = DIMENSION
  cropoffset = DIMENSION
  trimoffset = DIMENSION
  bleedoffset = DIMENSION
  artoffset = DIMENSION
```

\nastavvzhled [...]

\* reset NAME

\nastavzahlavi [<sup>1</sup>...] [<sup>2</sup>...,...]

```
1 text marginalie hrana OPT
2 inherits: \setuplayoutelement
```

\nastavzakladnifont [...\*,...]

\* DIMENSION NAME globalne reset x xx male velke script scriptscript rm ss tt hw cg antikva serif pravidelne sans bezserifu podpora opis strojopis mono rukopisne kaligraficke

\nastavzarovnani [...\*,...]

\* široky siroce spodek vyska radek vysoko nizko nivy flushright flushleft nastred ano ne sirka normalni reset uvnitr vnejsi flushinner flushouter vlevo vpravo center zablockovat posledni end odstavec lefttoright righttoleft l2r r2l tabulka lesshyphenation morehyphenation visici nothanging hz fullhz nohz hyphenated nothyphenated tolerantni velmitolerantni natahnout extremestretch finalni 2\*final 3\*final 4\*final

**\nastavznaceni** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 BESCHRIFTUNG OPT  
2 status = start stop  
expanden = ano ne  
oddelovac = BEFEHL  
filtercommand = \...#1

**\nastavzuzeni** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
2 vlevo = DIMENSION  
stredni = DIMENSION  
vpravo = DIMENSION  
implicitni = [-+]vlevo [-+]nastred [-+]vpravo NUMMER\*vlevo NUMMER\*nastred NUMMER\*vpravo reset  
pred = BEFEHL  
po = BEFEHL

**\nastrane** [...]

\* REFERENCE

**\nastred** ...

\* CHARACTER

**\naturalhbox** ...<sup>1</sup> {...<sup>2</sup>}

1 TEXT OPT  
2 CONTENT

**\naturalhpack** ...<sup>1</sup> {...<sup>2</sup>}

1 TEXT OPT  
2 CONTENT

**\naturalvbox** ...<sup>1</sup> {...<sup>2</sup>}

1 TEXT OPT  
2 CONTENT

**\naturalvcenter** ...<sup>1</sup> {...<sup>2</sup>}

1 TEXT OPT  
2 CONTENT

**\naturalvpack** ...<sup>1</sup> {...<sup>2</sup>}

1 TEXT OPT  
2 CONTENT

**\naturalvtop** ...<sup>1</sup> {...<sup>2</sup>}

1 TEXT OPT  
2 CONTENT

**\naturalwd** ...

\* CSNAME NUMMER

**\negatecolorbox** ...

\* CSNAME NUMMER

**\negated** {...}

\* TEXT

**\negthinspace**

**\nejakyradek** [...]

\* REFERENCE

<code>\nekde {<sup>1</sup>...} {<sup>2</sup>...} [<sup>3</sup>...]</code> 1    TEXT 2    TEXT 3    REFERENCE
<code>\newattribute \*..</code> *    CSNAME
<code>\newcatcodetable \*..</code> *    CSNAME
<code>\newcounter \*..</code> *    CSNAME
<code>\newevery \<sup>1</sup>... \<sup>2</sup>..</code> 1    CSNAME 2    CSNAME
<code>\newfrenchspacing</code>
<code>\newmode {...}</code> *    NAME
<code>\newsignal \*..</code> *    CSNAME
<code>\newsystemmode {...}</code> *    NAME
<code>\nextbox</code>
<code>\nextboxdp</code>
<code>\nextboxht</code>
<code>\nextboxhtdp</code>
<code>\nextboxwd</code>
<code>\nextcounter [<sup>1</sup>...] [<sup>2</sup>...]</code> 1    NAME                    OPT 2    NUMMER
<code>\nextcountervalue [...]</code> *    NAME
<code>\nextdepth</code>
<code>\nextparagraphs</code>
<code>\dalsiPARAGRAPHS</code>
<code>\nextrealpage</code>
<code>\nextrealpagenumber</code>

<code>\nextsubcountervalue [...] [...]</code> 1 NAME 2 NUMMER
<code>\nextsubpagenumber</code>
<code>\nextuserpage</code>
<code>\nextuserpagenumber</code>
<code>\neznamo</code>
<code>\nivy [...] {...} {...}</code> 1 vlevo <sup>OPT</sup> pravo 2 CONTENT 3 CONTENT
<code>\nizky {...}</code> * CONTENT
<code>\LOW {...}</code> * CONTENT instances: unitslow
<code>\nocitation [...]</code> * REFERENCE
<code>\nocitation {...}</code> * REFERENCE
<code>\nocite [...]</code> * REFERENCE
<code>\nocite {...}</code> * REFERENCE
<code>\nodetostring \^1... {...}</code> 1 CSNAME 2 CONTENT
<code>\nofigurepages</code>
<code>\noflines</code>
<code>\noflocalfloats</code>
<code>\noheightstrut</code>
<code>\noindentation</code>
<code>\noitem</code>
<code>\nokap {...}</code> * TEXT



<code>\nonfrenchspacing</code>
<code>\nonmathematics {...}</code> *    CONTENT
<code>\normalboldface</code>
<code>\normalframedwithsettings [...<sup>1</sup>...<sup>2</sup>...] {...}</code> 1    inherits: \nastavoramovani 2    CONTENT
<code>\normalitalicface</code>
<code>\normalizebodyfontsize \...<sup>1</sup> {...<sup>2</sup>}</code> 1    CSNAME 2    DIMENSION
<code>\normalizedfontsize</code>
<code>\normalizefontdepth \...<sup>1</sup> {...<sup>2</sup>} {...<sup>3</sup>} {...<sup>4</sup>}</code> 1    CSNAME 2    TEXT 3    DIMENSION 4    FONT
<code>\normalizefontheight \...<sup>1</sup> {...<sup>2</sup>} {...<sup>3</sup>} {...<sup>4</sup>}</code> 1    CSNAME 2    TEXT 3    DIMENSION 4    FONT
<code>\normalizefontline \...<sup>1</sup> {...<sup>2</sup>} {...<sup>3</sup>} {...<sup>4</sup>}</code> 1    CSNAME 2    TEXT 3    DIMENSION 4    FONT
<code>\normalizefontwidth \...<sup>1</sup> {...<sup>2</sup>} {...<sup>3</sup>} {...<sup>4</sup>}</code> 1    CSNAME 2    TEXT 3    DIMENSION 4    FONT
<code>\normalizetextdepth {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}</code> 1    FONT 2    DIMENSION 3    TEXT
<code>\normalizetextheight {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}</code> 1    FONT 2    DIMENSION 3    TEXT
<code>\normalizetextline {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}</code> 1    FONT 2    DIMENSION 3    TEXT
<code>\normalizetextwidth {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}</code> 1    FONT 2    DIMENSION 3    TEXT

<code>\normalni</code>
<code>\normalslantedface</code>
<code>\normaltypeface</code>
<code>\notesymbol [...]<sup>1</sup> [...]<sup>2</sup></code> 1 NAME OPT 2 REFERENCE
<code>\notragged</code>
<code>\ntimes {...}<sup>1</sup> {...}<sup>2</sup></code> 1 TEXT 2 NUMMER
<code>\numberofpoints {...}</code> * DIMENSION
<code>\obeydepth</code>
<code>\objectdepth</code>
<code>\objectheight</code>
<code>\objectmargin</code>
<code>\objectwidth</code>
<code>\obox {...}</code> * CONTENT
<code>\obrazovka [...]<sup>*</sup> [...]</code> * inherits: \strana <sup>OPT</sup>
<code>\odkaz [...]<sup>1</sup> [...]<sup>2</sup></code> 1 REFERENCE 2 TEXT
<code>\odkaznastranu [...]<sup>*</sup> [...]</code> * REFERENCE
<code>\odkaznatext [...]<sup>1</sup> [...]<sup>2</sup></code> 1 REFERENCE 2 TEXT
<code>\odkazujici (...)<sup>1</sup> (...)<sup>2</sup> [...]<sup>3</sup></code> 1 POSITION 2 POSITION 3 REFERENCE
<code>\offset [...]<sup>1</sup> [...]<sup>2</sup></code> 1 inherits: \setupoffset <sup>OPT</sup> 2 CONTENT

<p><b>\offsetbox</b> [...<sup>1</sup>...<sup>2</sup>...] {<sup>3</sup>...}</p> <p>1 inherits: \setupoffsetbox</p> <p>2 CSNAME</p> <p>3 CONTENT</p>
<p><b>\onedigitrounding</b> {...}</p> <p>* NUMMER</p>
<p><b>\opis</b> [...<sup>1</sup>...<sup>2</sup>...] {<sup>3</sup>...}</p> <p>1 inherits: \nastavtype</p> <p>2 CONTENT</p>
<p><b>\opissoubor</b> [...<sup>1</sup>...] [...<sup>2</sup>...<sup>3</sup>...] {<sup>4</sup>...}</p> <p>1 NAME</p> <p>2 inherits: \nastavopis</p> <p>3 FILE</p>
<p><b>\opis</b> [...<sup>1</sup>...<sup>2</sup>...] &lt;&lt;...&gt;&gt;</p> <p>1 inherits: \nastavtype</p> <p>2 ANGLES</p>
<p><b>\OPIS</b> [...<sup>1</sup>...<sup>2</sup>...] {<sup>3</sup>...}</p> <p>1 inherits: \nastavtype</p> <p>2 CONTENT</p>
<p><b>\OPIS</b> [...<sup>1</sup>...<sup>2</sup>...] &lt;&lt;...&gt;&gt;</p> <p>1 inherits: \nastavtype</p> <p>2 ANGLES</p>
<p><b>\oramovani</b> [...<sup>1</sup>...<sup>2</sup>...] {<sup>3</sup>...}</p> <p>1 inherits: \nastavoramovani</p> <p>2 CONTENT</p>
<p><b>\FRAMED</b> [...<sup>1</sup>...<sup>2</sup>...] {<sup>3</sup>...}</p> <p>1 inherits: \nastavoramovani</p> <p>2 CONTENT</p> <p>instances: unframed fitfieldframed</p>
<p><b>\fitfieldframed</b> [...<sup>1</sup>...<sup>2</sup>...] {<sup>3</sup>...}</p> <p>1 inherits: \nastavoramovani</p> <p>2 CONTENT</p>
<p><b>\unframed</b> [...<sup>1</sup>...<sup>2</sup>...] {<sup>3</sup>...}</p> <p>1 inherits: \nastavoramovani</p> <p>2 CONTENT</p>
<p><b>\FRAMEDTEXT</b> [...<sup>1</sup>...<sup>2</sup>...] {<sup>3</sup>...}</p> <p>1 inherits: \setupframedtext</p> <p>2 CONTENT</p> <p>instances: framedtext</p>
<p><b>\ordinaldaynumber</b> {...}</p> <p>* NUMMER</p>
<p><b>\ordinalstr</b> {...}</p> <p>* TEXT</p>
<p><b>\oref</b> [...]</p> <p>* REFERENCE</p>

$\backslash\text{orez}$ [ $\dots$ <sup>1</sup> $\dots$ ] { $\dots$ } 1 inherits: $\backslash\text{astavorez}$ 2 CONTENT
$\backslash\text{ornamenttext}$ [ $\dots$ <sup>1</sup> $\dots$ ] [ $\dots$ <sup>2</sup> $\dots$ ] { $\dots$ } { $\dots$ } 1 alternativa = a b inherits: $\backslash\text{setupcollector}$ 2 pismo = STYLE BEFEHL barva = COLOR inherits: $\backslash\text{nastavoramovani}$ 3 TEXT 4 CONTENT
$\backslash\text{ornamenttext}$ [ $\dots$ ] { $\dots$ } { $\dots$ } 1 NAME 2 TEXT 3 CONTENT
$\backslash\text{ornamenttext}$ [ $\dots$ <sup>1</sup> $\dots$ ] [ $\dots$ <sup>2</sup> $\dots$ ] { $\dots$ } { $\dots$ } 1 alternativa = a b inherits: $\backslash\text{setupplayer}$ 2 inherits: $\backslash\text{setuplayeredtext}$ 3 TEXT 4 CONTENT
$\backslash\text{ORNAMENT}$ { $\dots$ } { $\dots$ } 1 TEXT 2 CONTENT
$\backslash\text{otocit}$ [ $\dots$ <sup>1</sup> $\dots$ ] { $\dots$ } 1 inherits: $\backslash\text{nastavotoceni}$ 2 CONTENT
$\backslash\text{outputfilename}$
$\backslash\text{outputstreambox}$ [ $\dots$ ] * NAME
$\backslash\text{outputstreamcopy}$ [ $\dots$ ] * NAME
$\backslash\text{outputstreamunvbox}$ [ $\dots$ ] * NAME
$\backslash\text{outputstreamunvcopy}$ [ $\dots$ ] * NAME
$\backslash\text{over}$ [ $\dots$ ] * REFERENCE
$\backslash\text{overbartext}$ { $\dots$ } { $\dots$ } 1 TEXT 2 TEXT
$\backslash\text{overbarunderbar}$ { $\dots$ } * TEXT
$\backslash\text{overbrace}$ { $\dots$ } * TEXT



<code>\overloaderror</code>
<code>\overparent {...}</code> * TEXT
<code>\overparenttext {...} {...}</code> 1 TEXT 2 TEXT
<code>\overparentunderparent {...}</code> * TEXT
<code>\overrightarrow {...}</code> * TEXT
<code>\overrightarrowharpoon\downarrow {...}</code> * TEXT
<code>\overrightarrowharpoon\uparrow {...}</code> * TEXT
<code>\overset {...} {...}</code> 1 TEXT 2 TEXT
<code>\overtwoheadleftarrow {...}</code> * TEXT
<code>\overtwoheadrightarrow {...}</code> * TEXT
<code>\oznaceni (...<sup>1</sup>,...) (...<sup>2</sup>,...) [...<sup>3</sup>=...,...] {...<sup>4</sup>}</code> 1 POSITION 2 POSITION 3 inherits: \nastavoramovani 4 TEXT
<code>\PDFcolor {...}</code> * NAME
<code>\PDFETEX</code>
<code>\PDFTEX</code>
<code>\PICTEX</code>
<code>\PiCTeX</code>
<code>\PointsToBigPoints {...} \^ {...}</code> 1 DIMENSION 2 CSNAME
<code>\PointsToReal {...} \^ {...}</code> 1 DIMENSION 2 CSNAME

<code>\PointsToWholeBigPoints {...} \^2.</code> 1 DIMENSION 2 CSNAME
<code>\PPCHTEX</code>
<code>\PPCHTeX</code>
<code>\PRAGMA</code>
<code>\PtToCm {...}</code> * DIMENSION
<code>\pagearea [...^1.] [...^2.] [...^3.]</code> 1 vrsek zahlavi text <sup>OPT</sup> upati spodek 2 text marginalie hrana 3 vlevo vpravo lefttext middletext righttext
<code>\pagebreak [...,*...]</code> * prazdne zahlavi <sup>OPT</sup> upati dummy ramecek NUMMER +NUMMER implicitni reset zablokovat ano ne zlom prazdny nastaveni vysokapriorita vlevo vpravo sude liche ctyrnasobny posledni poslednistrana start stop NAME
<code>\pagefigure [...^1.] [...^2...^2...]</code> 1 FILE <sup>OPT</sup> 2 inherits: \setupexternalfigure
<code>\pagegridspanwidth {...}</code> * NUMMER
<code>\pageinjection [...^1.] [...^2...^2...]</code> 1 NAME <sup>OPT</sup> <sup>OPT</sup> 2 KEY = VALUE
<code>\pageinjection [...^1...^1...^1...] [...^2...^2...]</code> 1 inherits: \setuppageinjection <sup>OPT</sup> 2 KEY = VALUE
<code>\pagestaterealpage {...^1} {...^2}</code> 1 NAME 2 NAME NUMMER
<code>\paletsize</code>
<code>\PARAGRAPHS</code>
<code>\pdfactualtext {...^1} {...^2}</code> 1 CONTENT 2 TEXT
<code>\pdfbackendactualtext {...^1} {...^2}</code> 1 CONTENT 2 TEXT
<code>\pdfbackendcurrentresources</code>
<code>\pdfbackendsetcatalog {...^1} {...^2}</code> 1 NAME 2 TEXT

<p><code>\pdfbackendsetcolorspace {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsettextgstate {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetinfo {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetname {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetpageattribute {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetpageresource {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetpagesattribute {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetpattern {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetshade {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfcolor {...}</code></p> <p>* NAME</p>
<p><code>\pdfeTeX</code></p>
<p><code>\pdfTeX</code></p>
<p><code>\percent</code></p>
<p><code>\percentdimen {...} {...}</code></p> <p>1 DIMENSION CSNAME</p> <p>2 DIMENSION NUMBER</p>
<p><code>\permitcaretescape</code></p>
<p><code>\permitcircumflexescape</code></p>
<p><code>\permitspacesbetweengroups</code></p>
<p><code>\persiandecimals {...}</code></p> <p>* NUMBER</p>



\* NUMMER

\* CONTENT

```
*   sirka      = DIMENSION
    vyska      = DIMENSION
    hloubka    = DIMENSION
```

1	BEFEHL
2	BEFEHL
3	BEFEHL

```
1 inherits: OPTnastavtype
2 CONTENT
```

```
1 inherits: \nastavtype
2 ANGLES
```

```
1 NAME OPT
2 inherits: \setupbtxrendering
```

## \* REFERENCE

\placecurrentformulanumber

\* CONTENT

```

1 SINGULAR                                OPT1      OPT
2 split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraj levyokraj pravyyokraj levahrana
  pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku
  mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko
  obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective zahhlavi upati
3 REFERENCE
4 TEXT
5 CONTENT

```

```

1  NAME                                OPT                                OPT
2  split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraj levyokraj pravyyokraj levahrana
   pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku
   mizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko
   obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective zahlavi upati
3  REFERENCE
4  TEXT
5  CONTENT

```

`\umistiFLOAT [...1,...] [...2,...] {...3} {...4}`

1 split vzdy vlevo vpravo uvnitr<sup>OPT</sup> vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji levyokraj pravyyokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective zahlavi upati

2 REFERENCE

3 TEXT

4 CONTENT

instances: chemical figure table intermezzo graphic

`\placeframed [...1] [...2,...] {...3}`

1 NAME <sup>OPT</sup>

2 inherits: \nastavoramovani

3 CONTENT

`\placeheadnumber [...]`

\* ABSCHNITT

`\placeheadtext [...]`

\* ABSCHNITT

`\placehelp`

`\placeinitial [...]`

\* NAME <sup>OPT</sup>

`\placelayer [...]`

\* NAME

`\placelayeredtext [...1] [...2,...] [...3,...] {...4} {...5}`

1 NAME

2 inherits: \setuplayer <sup>OPT</sup>

3 inherits: \setuplayeredtext <sup>OPT</sup>

4 TEXT

5 CONTENT

`\placelistofFLOATS [...*,...]`

\* inherits: \nastavseznam <sup>OPT</sup>

instances: chemicals figures tables intermezzi graphics

`\completelistoffigures [...*,...]`

\* inherits: \nastavseznam <sup>OPT</sup>

`\completelistofgraphics [...*,...]`

\* inherits: \nastavseznam <sup>OPT</sup>

`\completelistofchemicals [...*,...]`

\* inherits: \nastavseznam <sup>OPT</sup>

`\completelistofintermezzi [...*,...]`

\* inherits: \nastavseznam <sup>OPT</sup>

`\completelistoftables [...*,...]`

\* inherits: \nastavseznam <sup>OPT</sup>

`\placelistofpublications [...1] [...2,...]`

1 NAME <sup>OPT</sup>

2 inherits: \setupbtxrendering <sup>OPT</sup>

<p><b>\placelistofsorts</b> [<sup>1</sup>...] [<sup>2</sup>...<sup>2</sup>...]</p> <p>1 SINGULAR OPT</p> <p>2 inherits: \nastavtrideni</p>
<p><b>\placelistofSORTS</b> [<sup>*</sup>...<sup>*</sup>...]</p> <p>* inherits: \nastavtrideni OPT</p> <p>instances: logos</p>
<p><b>\completelistoflogos</b> [<sup>*</sup>...<sup>*</sup>...]</p> <p>* inherits: \nastavtrideni OPT</p>
<p><b>\placelistofsynonyms</b> [<sup>1</sup>...] [<sup>2</sup>...<sup>2</sup>...]</p> <p>1 SINGULAR OPT</p> <p>2 inherits: \nastavsynonyma</p>
<p><b>\placelistofSYNONYMS</b> [<sup>*</sup>...<sup>*</sup>...]</p> <p>* inherits: \nastavsynonyma OPT</p> <p>instances: abbreviations</p>
<p><b>\completelistofabbreviations</b> [<sup>*</sup>...<sup>*</sup>...]</p> <p>* inherits: \nastavsynonyma OPT</p>
<p><b>\placelocalnotes</b> [<sup>1</sup>...] [<sup>2</sup>...<sup>2</sup>...]</p> <p>1 NAME OPT</p> <p>2 inherits: \setupnote</p>
<p><b>\placement</b> [<sup>1</sup>...] [<sup>2</sup>...<sup>2</sup>...] {<sup>3</sup>...}</p> <p>1 NAME OPT</p> <p>2 inherits: \setupplacement</p> <p>3 CONTENT</p>
<p><b>\PLACEMENT</b> [<sup>1</sup>...<sup>1</sup>...] {<sup>2</sup>...}</p> <p>1 inherits: \setupplacement OPT</p> <p>2 CONTENT</p>
<p><b>\placenamefloat</b> [<sup>1</sup>...] [<sup>2</sup>...]</p> <p>1 NAME</p> <p>2 REFERENCE</p>
<p><b>\placenameformula</b> [<sup>1</sup>...<sup>1</sup>...] {<sup>2</sup>...}</p> <p>1 + - REFERENCE OPT</p> <p>2 TEXT</p>
<p><b>\placenotes</b> [<sup>1</sup>...<sup>1</sup>...] [<sup>2</sup>...<sup>2</sup>...]</p> <p>1 NAME OPT</p> <p>2 inherits: \setupnote</p>
<p><b>\placepagenumber</b></p>
<p><b>\placepairedbox</b> [<sup>1</sup>...] [<sup>2</sup>...<sup>2</sup>...] {<sup>3</sup>...} {<sup>4</sup>...}</p> <p>1 NAME OPT</p> <p>2 inherits: \setuppairedbox</p> <p>3 CONTENT</p> <p>4 TEXT</p>
<p><b>\umistiPAIREDBOX</b> [<sup>1</sup>...<sup>1</sup>...] {<sup>2</sup>...} {<sup>3</sup>...}</p> <p>1 inherits: \setuppairedbox OPT</p> <p>2 CONTENT</p> <p>3 TEXT</p> <p>instances: legend</p>

<code>\nastavenilegend [...,..<sup>1</sup>...,...]</code> <code>* inherits: \setuppairedbox</code>
<code>\placeparallel [...,..<sup>1</sup>] [...,..<sup>2</sup>,...] [...,..<sup>3</sup>...,...]</code> <code>1 NAME</code> <code>2 NAME</code> <code>3 inherits: \setupparallel</code>
<code>\placeraawlist [...,..<sup>1</sup>] [...,..<sup>2</sup>...,...]</code> <code>1 LISTE</code> <code>2 inherits: \nastavseznam</code>
<code>\placereadingwindow [...,..<sup>1</sup>] [...,..<sup>2</sup>]</code> <code>1 NAME</code> <code>2 NAME</code>
<code>\plnezneni {...}</code> <code>* NAME</code>
<code>\podtrzeno {...}</code> <code>* TEXT</code>
<code>\pole [...,..<sup>1</sup>] [...,..<sup>2</sup>]</code> <code>1 NAME</code> <code>2 TEXT</code>
<code>\polozka [...,..<sup>1</sup>,...]</code> <code>* REFERENCE</code>
<code>\polozky [...,..<sup>1</sup>...,...]{...}</code> <code>1 inherits: \nastavpolozky</code> <code>2 TEXT</code>
<code>\popattribute \...</code> <code>* CSNAME</code>
<code>\POPIS [...,..<sup>1</sup>,...]{...} ... \par</code> <code>1 REFERENCE</code> <code>2 TEXT</code> <code>3 CONTENT</code>
<code>\popmacro \...</code> <code>* CSNAME</code>
<code>\popmode [...]</code> <code>* NAME</code>
<code>\POPISEK [...,..<sup>1</sup>,...]{...}</code> <code>1 REFERENCE</code> <code>2 TEXT</code>
<code>\popsystemmode {...}</code> <code>* NAME</code>
<code>\porovnejpaletu [...]</code> <code>* NAME</code>
<code>\porovnejskupinubarev [...]</code> <code>* NAME</code>

\positionoverlay {...} *   NAME
\positionregionoverlay {...} {...} 1   NAME 2   NAME
\poslaednipodstranka
\postponenotes
\pozadi {...} *   CONTENT
\POZADI {...} *   CONTENT instances: pozadi
\pozice [..., <sup>1</sup> ..., <sup>2</sup> ..., <sup>3</sup> ...] (..., <sup>2</sup> ..., <sup>3</sup> ...) {...} 1   inherits: \nastavumistovani 2   POSITION 3   CONTENT
\poznamka [..., <sup>1</sup> ..., <sup>2</sup> ...] [...] 1   NAME           OPT 2   REFERENCE
\NOTE [..., <sup>1</sup> ..., <sup>2</sup> ...] {...} 1   REFERENCE <sup>PT</sup> 2   TEXT instances: footnote endnote
\NOTE [..., <sup>*</sup> ..., <sup>*</sup> ...] [...] *   titul       = TEXT *   zalozka    = TEXT *   seznam     = TEXT *   odkaz      = REFERENCE instances: footnote endnote
\endnote [..., <sup>1</sup> ..., <sup>2</sup> ...] {...} 1   REFERENCE    OPT 2   TEXT
\footnote [..., <sup>1</sup> ..., <sup>2</sup> ...] {...} 1   REFERENCE    OPT 2   TEXT
\pravidelne
\predefinedfont [...] *   FONT
\predefinefont [...] <sup>1</sup> [...] <sup>2</sup> 1   NAME 2   FONT
\predefinesymbol [...] *   NAME

<p><b>\pref</b> <sup>1</sup>{...} <sup>2</sup>{...} [<sup>3</sup>...]</p> <p>1 TEXT OPT OPT</p> <p>2 TEXT</p> <p>3 REFERENCE</p>
<p><b>\prefixedpagenumber</b></p>
<p><b>\prelozit</b> [...<sup>*</sup>...]</p> <p>* SPRACHE = TEXT OPT</p>
<p><b>\prependetoks</b> <sup>1</sup>... \to \<sup>2</sup>...</p> <p>1 BEFEHL</p> <p>2 CSNAME</p>
<p><b>\prependgvalue</b> <sup>1</sup>{...} <sup>2</sup>{...}</p> <p>1 NAME</p> <p>2 BEFEHL</p>
<p><b>\prependtocommalist</b> <sup>1</sup>{...} \<sup>2</sup>...</p> <p>1 TEXT</p> <p>2 CSNAME</p>
<p><b>\prependtoks</b> <sup>1</sup>... \to \<sup>2</sup>...</p> <p>1 BEFEHL</p> <p>2 CSNAME</p>
<p><b>\prependtoksonce</b> <sup>1</sup>... \to \<sup>2</sup>...</p> <p>1 BEFEHL</p> <p>2 CSNAME</p>
<p><b>\prependvalue</b> <sup>1</sup>{...} <sup>2</sup>{...}</p> <p>1 NAME</p> <p>2 BEFEHL</p>
<p><b>\prepninazakladnifont</b> [...<sup>*</sup>...]</p> <p>* inherits: \nastavzakladnifont</p>
<p><b>\presetdocument</b> [...<sup>*</sup>...]</p> <p>* inherits: \setupdocument</p>
<p><b>\presetfieldsymbols</b> [...<sup>*</sup>...]</p> <p>* NAME</p>
<p><b>\presetLABELtext</b> [<sup>1</sup>...] [...<sup>2</sup>...]</p> <p>1 SPRACHE OPT</p> <p>2 KEY = VALUE</p> <p>instances: head label mathlabel taglabel unit operator prefix suffix btxlabel</p>
<p><b>\copybtxlabeltext</b> [<sup>1</sup>...] [...<sup>2</sup>...]</p> <p>1 SPRACHE OPT</p> <p>2 KEY = KEY</p>
<p><b>\copyheadtext</b> [<sup>1</sup>...] [...<sup>2</sup>...]</p> <p>1 SPRACHE OPT</p> <p>2 KEY = KEY</p>
<p><b>\copylabeltext</b> [<sup>1</sup>...] [...<sup>2</sup>...]</p> <p>1 SPRACHE OPT</p> <p>2 KEY = KEY</p>

$\backslash\text{copymathlabeltext}$ [ <sup>1</sup> ...] [ <sup>2</sup> ... <sub>2</sub> ...] 1 SPRACHE OPT 2 KEY = KEY
$\backslash\text{copyoperatortext}$ [ <sup>1</sup> ...] [ <sup>2</sup> ... <sub>2</sub> ...] 1 SPRACHE OPT 2 KEY = KEY
$\backslash\text{copyprefixtext}$ [ <sup>1</sup> ...] [ <sup>2</sup> ... <sub>2</sub> ...] 1 SPRACHE OPT 2 KEY = KEY
$\backslash\text{copysuffixtext}$ [ <sup>1</sup> ...] [ <sup>2</sup> ... <sub>2</sub> ...] 1 SPRACHE OPT 2 KEY = KEY
$\backslash\text{copytaglabeltext}$ [ <sup>1</sup> ...] [ <sup>2</sup> ... <sub>2</sub> ...] 1 SPRACHE OPT 2 KEY = KEY
$\backslash\text{copyunittext}$ [ <sup>1</sup> ...] [ <sup>2</sup> ... <sub>2</sub> ...] 1 SPRACHE OPT 2 KEY = KEY
$\backslash\text{preskoc}$ [...*...] * inherits: $\backslash\text{vs}^{\text{KTC}}\text{acing}$
$\backslash\text{pretocommalist}$ {...} \ <sup>2</sup> .. 1 TEXT 2 CSNAME
$\backslash\text{prevcounter}$ [...] [ <sup>2</sup> ...] 1 NAME OPT 2 NUMMER
$\backslash\text{prevcountervalue}$ [...] * NAME
$\backslash\text{preventmode}$ [...*...] * NAME
$\backslash\text{prevrealpage}$
$\backslash\text{prevrealpagenumber}$
$\backslash\text{prevsubcountervalue}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...] 1 NAME 2 NUMMER
$\backslash\text{prevsubpage}$
$\backslash\text{prevsubpagenumber}$
$\backslash\text{prevuserpage}$
$\backslash\text{prevuserpagenumber}$

<pre> \prizpusobivepole [...] [...] 1 NAME 2 inherits: \setupfieldbody </pre>
<pre> \prizpusobvzhled [...] [...] 1 NUMBER 2 vyska = max DIMENSION    radky = NUMBER </pre>
<pre> \procent </pre>
<pre> \processaction [...] [...] 1 BEFEHL 2 APPLY </pre>
<pre> \processallactionsinset [...] [...] 1 BEFEHL 2 APPLY </pre>
<pre> \processassignlist [...] \^2.. 1 TEXT 2 CSNAME </pre>
<pre> \processassignmentcommand [...] \^2.. 1 KEY = VALUE 2 CSNAME </pre>
<pre> \processassignmentlist [...] \^2.. 1 KEY = VALUE 2 CSNAME </pre>
<pre> \processbetween {...} \^2.. 1 NAME 2 CSNAME </pre>
<pre> \processbodyfontenvironmentlist \^*.. * CSNAME </pre>
<pre> \processcolorcomponents {...} * COLOR </pre>
<pre> \processcommacommand [...] \^2.. 1 BEFEHL 2 CSNAME </pre>
<pre> \processcommalist [...] \^2.. 1 BEFEHL 2 CSNAME </pre>
<pre> \processcommalistwithparameters [...] \^2.. 1 BEFEHL 2 CSNAME </pre>
<pre> \processcontent {...} \^2.. 1 NAME 2 CSNAME </pre>
<pre> \processfile {...} * FILE </pre>



<pre>\processfilemany {...} *   FILE</pre>
<pre>\processfilenone {...} *   FILE</pre>
<pre>\processfileonce {...} *   FILE</pre>
<pre>\processfirstactioninset [...] [...] ...<sup>2</sup>...] 1   BEFEHL 2   APPLY</pre>
<pre>\processisolatedchars {...} \... 1   TEXT 2   CSNAME</pre>
<pre>\processisolatedwords {...} \... 1   TEXT 2   CSNAME</pre>
<pre>\processlinetablebuffer [...] *   BUFFER                      OPT</pre>
<pre>\processlinetablefile {...} *   FILE</pre>
<pre>\processlist {...} {...} {...} \... 1   CHARACTER 2   CHARACTER 3   TEXT 4   CSNAME</pre>
<pre>\processMPbuffer [...]...<sup>*</sup>... *   NAME                      OPT</pre>
<pre>\processMPfigurefile {...} *   FILE</pre>
<pre>\processmonth {...} {...} {...} 1   NUMMER 2   NUMMER 3   BEFEHL</pre>
<pre>\processranges [...]...<sup>1</sup>... \...<sup>2</sup>... 1   NUMMER NUMMER:NUMMER 2   CSNAME</pre>
<pre>\processseparatedlist [...] [...] {...} 1   TEXT 2   TEXT 3   CSNAME BEFEHL</pre>
<pre>\processTEXbuffer [...]...<sup>*</sup>... *   BUFFER                      OPT</pre>

<pre> \processtokens {...} {...} {...} {...} {...} 1  BEFEHL 2  BEFEHL 3  BEFEHL 4  BEFEHL 5  TEXT </pre>
<pre> \processuntil \*. *  CSNAME </pre>
<pre> \processxtablebuffer [...] *  NAME OPT </pre>
<pre> \processyear {...} {...} {...} {...} 1  NUMMER 2  BEFEHL 3  BEFEHL 4  BEFEHL </pre>
<pre> \produkt [...] *  FILE </pre>
<pre> \produkt ... *  FILE </pre>
<pre> \profiledbox [...] [...] {...} 1  zadny fixne striktni halfixed quarterfixed eightsfixed NAME 2  inherits: \setupprofile 3  CONTENT </pre>
<pre> \profilegivenbox {...} ... 1  zadny fixne striktni halfixed quarterfixed eightsfixed NAME 2  CSNAME NUMMER </pre>
<pre> \program [...] *  NAME </pre>
<pre> \projekt [...] *  FILE </pre>
<pre> \projekt ... *  FILE </pre>
<pre> \prostredi [...] *  FILE </pre>
<pre> \prostredi ... *  FILE </pre>
<pre> \prvnipodstranka </pre>
<pre> \pseudoMixedCapped {...} *  TEXT </pre>
<pre> \pseudoSmallCapped {...} *  TEXT </pre>
<pre> \pseudoSmallcapped {...} *  TEXT </pre>

<p><code>\pseudosmallcapped {...}</code></p> <p>* TEXT</p>
<p><code>\purenumber {...}</code></p> <p>* NUMMER</p>
<p><code>\pusharrangedpages ... \poparrangedpages</code></p>
<p><code>\pushattribute \*</code></p> <p>* CSNAME</p>
<p><code>\pushbar [...] ... \popbar</code></p> <p>* NAME</p>
<p><code>\pushbarva [...] ... \popbarva</code></p> <p>* COLOR</p>
<p><code>\pushbutton [<sup>1</sup>...] [<sup>2</sup>...]</code></p> <p>1 NAME</p> <p>2 REFERENCE</p>
<p><code>\pushcatcodetable ... \popcatcodetable</code></p>
<p><code>\pushendofline ... \popendofline</code></p>
<p><code>\pushindentation ... \popindentation</code></p>
<p><code>\pushMPdrawing ... \popMPdrawing</code></p>
<p><code>\pushmacro \*</code></p> <p>* CSNAME</p>
<p><code>\pushmathstyle ... \popmathstyle</code></p>
<p><code>\pushmode [...]</code></p> <p>* NAME</p>
<p><code>\pushoutputstream [...]</code></p> <p>* NAME OPT</p>
<p><code>\pushpath [...] ... \poppath</code></p> <p>* PATH</p>
<p><code>\pushpozadi [...] ... \poppozadi</code></p> <p>* NAME</p>
<p><code>\pushpunctuation ... \poppunctuation</code></p>
<p><code>\pushrandomseed ... \poprandomseed</code></p>
<p><code>\pushreferenceprefix {...} ... \popreferenceprefix</code></p> <p>* + - TEXT</p>
<p><code>\pushsystemmode {...}</code></p> <p>* NAME</p>

<code>\putboxincache {<sup>1</sup>.} {<sup>2</sup>.} <sup>3</sup>.</code> 1 NAME 2 NUMMER TEXT 3 CSNAME NUMMER
<code>\putnextboxincache {<sup>1</sup>.} {<sup>2</sup>.} \<sup>3</sup>. {<sup>4</sup>.}</code> 1 NAME 2 NUMMER TEXT 3 CSNAME 4 CONTENT
<code>\qqquad</code>
<code>\quad</code>
<code>\quads [<sup>*</sup>.]</code> * NUMMER <small>OPT</small>
<code>\quarterstrut</code>
<code>\quitcommalist</code>
<code>\quitprevcommalist</code>
<code>\quittypescriptscanning</code>
<code>\ReadFile {<sup>*</sup>.}</code> * FILE
<code>\Rimskecislice {<sup>*</sup>.}</code> * NUMMER
<code>\radek {<sup>*</sup>.}</code> * CONTENT
<code>\raggedbottom</code>
<code>\raggedcenter</code>
<code>\raggedleft</code>
<code>\raggedright</code>
<code>\raggedwidecenter</code>
<code>\raisebox {<sup>1</sup>.} \<sup>2</sup>. {<sup>3</sup>.}</code> 1 DIMENSION 2 CSNAME 3 CONTENT
<code>\randomizetext {<sup>*</sup>.}</code> * TEXT
<code>\randomnumber {<sup>1</sup>.} {<sup>2</sup>.}</code> 1 NUMMER 2 NUMMER

<pre> \rawcounter [...]<sup>1</sup> [...]<sup>2</sup> 1  NAME                                OPT 2  NUMMER </pre>
<pre> \rawcountervalue [...]  *  NAME </pre>
<pre> \rawdate [...,*...] *  inherits: \aktualnidatum </pre>
<pre> \rawdoifelseinset {...}<sup>1</sup> {...,<sup>2</sup>...} {...}<sup>3</sup> {...}<sup>4</sup> 1  TEXT 2  TEXT 3  TRUE 4  FALSE </pre>
<pre> \rawdoifinset {...}<sup>1</sup> {...,<sup>2</sup>...} {...}<sup>3</sup> 1  TEXT 2  TEXT 3  TRUE </pre>
<pre> \rawdoifinsetelse {...}<sup>1</sup> {...,<sup>2</sup>...} {...}<sup>3</sup> {...}<sup>4</sup> 1  TEXT 2  TEXT 3  TRUE 4  FALSE </pre>
<pre> \rawgetparameters [...]<sup>1</sup> [...,<sup>2</sup>...,...] 1  TEXT 2  KEY = VALUE </pre>
<pre> \rawprocessaction [...]<sup>1</sup> [...,<sup>2</sup>...=&gt;...,...] 1  BEFEHL 2  APPLY </pre>
<pre> \rawprocesscommacommand [...,<sup>1</sup>...]<sup>2</sup> \... 1  BEFEHL 2  CSNAME </pre>
<pre> \rawprocesscommalist [...,<sup>1</sup>...]<sup>2</sup> \... 1  BEFEHL 2  CSNAME </pre>
<pre> \rawstructurelistuservariable {...} *  KEY </pre>
<pre> \rawsubcountervalue [...]<sup>1</sup> [...]<sup>2</sup> 1  NAME 2  NUMMER </pre>
<pre> \rbox ...<sup>1</sup> {...}<sup>2</sup> 1  TEXT<sup>OPT</sup> 2  CONTENT </pre>
<pre> \readfile {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup> 1  FILE 2  TRUE 3  FALSE </pre>

<pre> \readfixfile {...} {...} {...} {...} 1  PATH 2  FILE 3  TRUE 4  FALSE </pre>
<pre> \readjobfile {...} {...} {...} 1  FILE 2  TRUE 3  FALSE </pre>
<pre> \readlocfile {...} {...} {...} 1  FILE 2  TRUE 3  FALSE </pre>
<pre> \readsetfile {...} {...} {...} {...} 1  PATH 2  FILE 3  TRUE 4  FALSE </pre>
<pre> \readsysfile {...} {...} {...} 1  FILE 2  TRUE 3  FALSE </pre>
<pre> \readtexfile {...} {...} {...} 1  FILE 2  TRUE 3  FALSE </pre>
<pre> \readxmlfile {...} {...} {...} 1  FILE 2  TRUE 3  FALSE </pre>
<pre> \realpagenumber </pre>
<pre> \realSmallCapped {...} *  TEXT </pre>
<pre> \realSmallcapped {...} *  TEXT </pre>
<pre> \realsmallcapped {...} *  TEXT </pre>
<pre> \recursedepth </pre>
<pre> \recurselevel </pre>
<pre> \recursestring </pre>
<pre> \redoconvertfont </pre>
<pre> \ref [...] [...] 1  implicitni text titul cislo stranka realpage 2  REFERENCE </pre>

<code>\REFERENCEFORMAT {...} {...} [...]</code> 1    TEXT                    OPT            OPT 2    TEXT 3    REFERENCE
<code>\referenceprefix</code>
<code>\registerattachment [...]<sup>1</sup> [...,...<sup>2</sup>...,...]</code> 1    NAME 2    inherits: \setupattachment
<code>\attachment [...]<sup>1</sup> [...,...<sup>2</sup>...,...]</code> 1    NAME                    OPT            OPT 2    inherits: \setupattachment
<code>\registerctxluafile {...}<sup>1</sup> {...}<sup>2</sup></code> 1    FILE 2    NUMMER
<code>\registerexternalfigure [...]<sup>1</sup> [...]<sup>2</sup> [...,...<sup>3</sup>...,...]</code> 1    FILE                                    OPT            OPT 2    NAME 3    inherits: \setupexternalfigure
<code>\registerfontclass {...}<sup>*</sup></code> *    NAME
<code>\registerhyphenationexception [...]<sup>1</sup> [...]<sup>2</sup></code> 1    SPRACHE                                    OPT 2    TEXT
<code>\registerhyphenationpattern [...]<sup>1</sup> [...]<sup>2</sup></code> 1    SPRACHE                                    OPT 2    TEXT
<code>\registermenubuttons [...]<sup>1</sup> [...]<sup>2</sup></code> 1    NAME 2    TEXT
<code>\registersort [...]<sup>1</sup> [...]<sup>2</sup></code> 1    SINGULAR 2    NAME
<code>\registersynonym [...]<sup>1</sup> [...]<sup>2</sup></code> 1    SINGULAR 2    NAME
<code>\registerunit [...]<sup>1</sup> [...,...<sup>2</sup>...,...]</code> 1    prefix   jednotka <del>OPT</del> operator   suffixe   symbol   packaged 2    KEY   =   VALUE
<code>\REGISTER [...]<sup>1</sup> [...+...<sup>2</sup>+...]</code> 1    TEXT   PROCESSOR->TEXT 2    INDEX <b>instances: index</b>
<code>\vizindex [...]<sup>1</sup> [...+...<sup>2</sup>+...] {...}<sup>3</sup></code> 1    TEXT   PROCESSOR->TEXT 2    INDEX 3    TEXT   PROCESSOR->TEXT

\REGISTER [...] {...} [... <sup>3</sup> +...+...] 1 TEXT PROCESSOR->TEXT 2 TEXT 3 INDEX instances: index
\relatemarking [...] [...]
1 BESCHRIFTUNG 2 BESCHRIFTUNG
\relateparameterhandlers {...} {...} {...} {...} 1 NAME 2 NAME 3 NAME 4 NAME
\relaxvalueifundefined {...} * NAME
\remainingcharacters
\removebottomthings
\removedepth
\removefromcommalist {...} \^2.. 1 TEXT 2 CSNAME
\removelastskip
\removelastspace
\removemarkedcontent [...]
* NAME
\removepunctuation
\removesubstring <sup>1</sup> ... \from <sup>2</sup> ... \to \^3.. 1 TEXT 2 TEXT 3 CSNAME
\removetoks <sup>1</sup> ... \from \^2.. 1 BEFEHL 2 CSNAME
\removeunwantedspaces
\replacefeature [...]
* NAME
\replacefeature {...}
* NAME
\replaceincommalist \^1... {...} 1 CSNAME 2 NUMMER



<pre> \replaceword [...] [...] [...] 1  NAME 2  TEXT 3  TEXT </pre>
<pre> \rescan {...} *  CONTENT </pre>
<pre> \rescanwithsetup {...} {...} 1  NAME 2  CONTENT </pre>
<pre> \resetallattributes </pre>
<pre> \resetandaddfeature [...] *  NAME </pre>
<pre> \resetandaddfeature {...} *  NAME </pre>
<pre> \resetbar </pre>
<pre> \resetboxesincache {...} *  NAME </pre>
<pre> \resetbreakpoints </pre>
<pre> \resetbuffer [...] *  BUFFER </pre>
<pre> \resetcollector [...] *  NAME </pre>
<pre> \resetcounter [...] [...] 1  NAME          OPT 2  NUMMER </pre>
<pre> \resetdigitsmanipulation </pre>
<pre> \resetdirection </pre>
<pre> \resetfeature </pre>
<pre> \resetflag {...} *  NAME </pre>
<pre> \resetfontcolorscheme </pre>
<pre> \resetfontfallback [...] [...] 1  NAME          OPT 2  FONT </pre>
<pre> \resetfontsolution </pre>
<pre> \resethyphenationfeatures </pre>



<code>\resetscript</code>
<code>\resetsetups [...]</code> *    NAME
<code>\resetshownsynonyms [...]</code> *    SINGULAR
<code>\resetsubpagenumber</code>
<code>\resetsymbolset</code>
<code>\resetssystemmode {...}</code> *    NAME
<code>\resettimer</code>
<code>\resettrackers</code>
<code>\resettrialtypesetting</code>
<code>\resetusedsortings [...]</code> *    SINGULAR
<code>\resetusedsynonyms [...]</code> *    SINGULAR
<code>\resetuserpagenumber</code>
<code>\resetvalue {...}</code> *    NAME
<code>\resetvisualizers</code>
<code>\resetznaceni [...]</code> *    BESCHRIFTUNG
<code>\reshapebox {...}</code> *    BEFEHL
<code>\resolvedglyphdirect {...} {...}</code> 1    FONT 2    e:NAME x:NUMMER d:NUMMER s:NUMMER i:NUMMER n:NAME c:NAME u:NAME a:NAME
<code>\resolvedglyphstyled {...} {...}</code> 1    FONT 2    e:NAME x:NUMMER d:NUMMER s:NUMMER i:NUMMER n:NAME c:NAME u:NAME a:NAME
<code>\restartcounter [...] [...<sup>2</sup>] [...<sup>3</sup>]</code> 1    NAME 2    NUMMER 3    NUMMER
<code>\restorebox {...} {...}</code> 1    NAME 2    NAME

<code>\restorecatcodes</code>
<code>\restorecounter [...]</code> <code>* NAME</code>
<code>\restorecurrentattributes {...}</code> <code>* NAME</code>
<code>\restoreendofline</code>
<code>\restoreglobalbodyfont</code>
<code>\reusableMPgraphic {...} {...<sup>1</sup>...<sup>2</sup>...}</code> <code>1 NAME OPT</code> <code>2 KEY = VALUE</code>
<code>\reuseMPgraphic {...} {...<sup>1</sup>...<sup>2</sup>...}</code> <code>1 NAME OPT</code> <code>2 KEY = VALUE</code>
<code>\reuserandomseed</code>
<code>\revivefeature</code>
<code>\rfence {...}</code> <code>* CHARACTER</code>
<code>\rhbox {...}</code> <code>* CONTENT</code>
<code>\rightbottombox {...}</code> <code>* CONTENT</code>
<code>\rightbox {...}</code> <code>* CONTENT</code>
<code>\righthbox {...}</code> <code>* CONTENT</code>
<code>\rightLABELtext {...}</code> <code>* KEY</code> <code>instances: head label mathlabel</code>
<code>\rightline {...}</code> <code>* CONTENT</code>
<code>\rightorleftpageaction {...} {...}</code> <code>1 BEFEHL</code> <code>2 BEFEHL</code>
<code>\rightskipadaption</code>
<code>\rightsubguillemot</code>
<code>\righttopleft</code>

$\backslash\text{righttopleftthbox}$ <sup>1</sup> ... { <sup>2</sup> ...} 1 TEXT OPT 2 CONTENT
$\backslash\text{righttopleftvbox}$ <sup>1</sup> ... { <sup>2</sup> ...} 1 TEXT OPT 2 CONTENT
$\backslash\text{righttopleftvtop}$ <sup>1</sup> ... { <sup>2</sup> ...} 1 TEXT OPT 2 CONTENT
$\backslash\text{righttopbox}$ {...} * CONTENT
$\backslash\text{rimskecislice}$ {...} * NUMBER
$\backslash\text{rlap}$ {...} * CONTENT
$\backslash\text{robustaddtocommalist}$ { <sup>1</sup> ...} \ <sup>2</sup> ... 1 TEXT 2 CSNAME
$\backslash\text{robustdoifelseinset}$ { <sup>1</sup> ...} { <sup>2</sup> ...,...} { <sup>3</sup> ...} { <sup>4</sup> ...} 1 TEXT 2 TEXT 3 TRUE 4 FALSE
$\backslash\text{robustdoifinsetelse}$ { <sup>1</sup> ...} { <sup>2</sup> ...,...} { <sup>3</sup> ...} { <sup>4</sup> ...} 1 TEXT 2 TEXT 3 TRUE 4 FALSE
$\backslash\text{robustpretocommalist}$ { <sup>1</sup> ...} \ <sup>2</sup> ... 1 TEXT 2 CSNAME
$\backslash\text{rollbutton}$ [..., <sup>1</sup> ... <sub>=</sub> ...,...] <sup>2</sup> ... [ <sup>3</sup> ...] 1 inherits: \setupbutton 2 TEXT 3 REFERENCE
$\backslash\text{rollbutton}$ [ <sup>1</sup> ...] [..., <sup>2</sup> ... <sub>=</sub> ...,...] <sup>3</sup> ... [ <sup>4</sup> ...] 1 NAME OPT OPT 2 inherits: \nastavinterakcnimenu 3 TEXT 4 REFERENCE
$\backslash\text{rovnice}$ [..., <sup>1</sup> ...,...] { <sup>2</sup> ...} 1 zhustene tight <sup>OPT</sup> nastred ramecek inherits: \nastavzakladnifont 2 CONTENT
$\backslash\text{rozdelplvouciobjekt}$ [..., <sup>1</sup> ... <sub>=</sub> ...,...] { <sup>2</sup> ...} { <sup>3</sup> ...} 1 inherits: \nastavdeleniplvouciobjekt <sup>OPT</sup> 2 BEFEHL 3 CONTENT

<code>\roztazene [...,<sup>1</sup>...,...] {...}</code> 1 inherits: \setupstretched <sup>OPT</sup> 2 TEXT
<code>\rtop ... {...}</code> 1 TEXT <sup>OPT</sup> 2 CONTENT
<code>\rukopisne</code>
<code>\ruledhbox ... {...}</code> 1 TEXT <sup>OPT</sup> 2 CONTENT
<code>\ruledhpack ... {...}</code> 1 TEXT <sup>OPT</sup> 2 CONTENT
<code>\ruledmbox {...}</code> * CONTENT
<code>\ruledtopv ... {...}</code> 1 TEXT <sup>OPT</sup> 2 CONTENT
<code>\ruledtpack ... {...}</code> 1 TEXT <sup>OPT</sup> 2 CONTENT
<code>\ruledvbox ... {...}</code> 1 TEXT <sup>OPT</sup> 2 CONTENT
<code>\ruledvpack ... {...}</code> 1 TEXT <sup>OPT</sup> 2 CONTENT
<code>\ruledvtop ... {...}</code> 1 TEXT <sup>OPT</sup> 2 CONTENT
<code>\runMPbuffer [...,*...] ...</code> * NAME <sup>OPT</sup>
<code>\runninghbox {...}</code> * CONTENT
<code>\ScaledPointsToBigPoints {...} \^2...</code> 1 DIMENSION 2 CSNAME
<code>\ScaledPointsToWholeBigPoints {...} \^2...</code> 1 DIMENSION 2 CSNAME
<code>\SLOVA {...}</code> * TEXT

\SLOVO {...} * TEXT
\Slova {...} * TEXT
\Slovo {...} * TEXT
\Smallcapped {...} * TEXT
\safechar {...} * NUMMER
\sans
\sansnormal
\sanstucne
\savebarva ... \restorebarva
\savebox {...} {...} {...} 1 NAME 2 NAME 3 CONTENT
\savebtxdataset [... <sup>1</sup> ] [... <sup>2</sup> ] [... <sup>3</sup> ...,...] 1 NAME OPT OPT OPT 2 FILE 3 dataset = NAME typ = bib lua xml soubor = FILE kriterium = vse text uvod odkaz aktualni zde predchozi lokalne komponenta SECTIONBLOCK:vse SECTIONBLOCK:odkaz SECTIONBLOCK:aktualni SECTIONBLOCK:predchozi
\savebuffer [... <sup>1</sup> ... <sup>2</sup> ...] * seznam = NAME soubor = FILE prefix = ano ne
\savebuffer [... <sup>1</sup> ,...] [... <sup>2</sup> .] 1 BUFFER 2 FILE
\savecounter [...] * NAME
\savecurrentattributes {...} * NAME
\savenormalmeaning \*... * CSNAME
\savetaggedtwopassdata {... <sup>1</sup> } {... <sup>2</sup> } {... <sup>3</sup> } {... <sup>4</sup> } 1 NAME 2 NUMMER 3 NAME 4 CONTENT

\save twopassdata {...} {...} {...} 1 NAME 2 NUMMER 3 CONTENT
\sbox {...} * CONTENT
\SCRIPT instances: hangul hanzi nihongo ethiopic thai latin test
\ethiopic
\hangul
\hanzi
\latin
\nihongo
\test
\thai
\secondoffivearguments {...} {...} {...} {...} {...} 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT
\secondoffourarguments {...} {...} {...} {...} 1 TEXT 2 TEXT 3 TEXT 4 TEXT
\secondofsixarguments {...} {...} {...} {...} {...} {...} 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT
\secondofthreearguments {...} {...} {...} 1 TEXT 2 TEXT 3 TEXT
\secondofthreeunexpanded {...} {...} {...} 1 TEXT 2 TEXT 3 TEXT
\secondoftwoarguments {...} {...} 1 TEXT 2 TEXT



<code>\secondoftwounexpanded {...} {...}</code> 1 TEXT 2 TEXT
<code>\sedabarva [...] {...}</code> 1 COLOR 2 CONTENT
<code>\vizREGISTER [...] [...+...+...] {...}</code> 1 TEXT PROCESSOR- <del>9</del> TEXT 2 INDEX 3 TEXT PROCESSOR->TEXT instances: index
<code>\umistiindex [...,*=...,...]</code> * inherits: \nastavrejstrik
<code>\SECTION [...,<sup>1</sup>...] {...<sup>2</sup>}</code> 1 REFERENCE OPT 2 TEXT instances: part chapter section subsection subsubsection subsubsubsection subsubsubsubsection title subject subsubject subsubsubject subsubsubsubject subsubsubsubsubject
<code>\SECTION [...,*=...,...]</code> * titul = TEXT zalozka = TEXT znaceni = TEXT seznam = TEXT odkaz = REFERENCE vlastnicislo = TEXT instances: part chapter section subsection subsubsection subsubsubsection subsubsubsubsection title subject subsubject subsubsubject subsubsubsubject subsubsubsubsubject
<code>\SECTION [...,<sup>1</sup>...] {...<sup>2</sup>} {...<sup>3</sup>}</code> 1 REFERENCE OPT 2 NUMMER 3 TEXT instances: part chapter section subsection subsubsection subsubsubsection subsubsubsubsection title subject subsubject subsubsubject subsubsubsubject subsubsubsubsubject
<code>\select {...} {...<sup>2</sup>} {...<sup>3</sup>} {...<sup>4</sup>} {...<sup>5</sup>} {...<sup>6</sup>}</code> 1 NAME OPT OPT OPT OPT OPT 2 CONTENT 3 CONTENT 4 CONTENT 5 CONTENT 6 CONTENT
<code>\serializecommalist [...,*=...,...]</code> * BEFEHL
<code>\serializedcommalist</code>
<code>\serif</code>
<code>\serifbold</code>
<code>\serifnormal</code>
<code>\setbar [...*]</code> * NAME

<code>\setbigbodyfont</code>
<code>\setboxllx <sup>1</sup>... {<sup>2</sup>...}</code> 1 CSNAME NUMBER 2 DIMENSION
<code>\setboxlly <sup>1</sup>... {<sup>2</sup>...}</code> 1 CSNAME NUMBER 2 DIMENSION
<code>\setbreakpoints [...]</code> * reset NAME
<code>\setbuffer [...] ... \endbuffer</code> * NAME
<code>\setcapstrut</code>
<code>\setcatcodetable \*</code> * CSNAME
<code>\setcollector [<sup>1</sup>...] [...,<sup>2</sup>...<sub>OPT</sub>,...] {<sup>3</sup>...}</code> 1 NAME 2 inherits: \setupcollector 3 CONTENT
<code>\setcolormodel1 [...]</code> * black bw seda rgb cmyk vse zadny
<code>\setcounter [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...]</code> 1 NAME 2 NUMBER 3 NUMBER
<code>\setcounterown [...] [<sup>2</sup>...] [<sup>3</sup>...]</code> 1 NAME 2 NUMBER 3 TEXT
<code>\setcurrentfontclass {<sup>*</sup>...}</code> * NAME
<code>\setdataset [<sup>1</sup>...] [<sup>2</sup>...] [...,<sup>3</sup>...<sub>OPT</sub>,...]</code> 1 NAME 2 NAME 3 KEY = VALUE
<code>\setdefaultpenalties</code>
<code>\setdigitsmanipulation [...]</code> * reset NUMBER
<code>\setdirection [...]</code> * NUMBER
<code>\setdocumentargument {<sup>1</sup>...} {<sup>2</sup>...}</code> 1 NAME 2 TEXT

<pre> \setdocumentargumentdefault {...} {...} 1  NAME 2  TEXT </pre>
<pre> \setdocumentfilename {...} {...} 1  NUMMER 2  TEXT </pre>
<pre> \setdummyparameter {...} {...} 1  KEY 2  BEFEHL </pre>
<pre> \setelementexporttag [...] [...] [...] 1  NAME                                OPT 2  export nature pdf 3  inline obrazovka mixed </pre>
<pre> \setemeasure {...} {...} 1  NAME 2  DIMENSION </pre>
<pre> \setevalue {...} {...} 1  NAME 2  CONTENT </pre>
<pre> \setevariable {...} {...} {...} 1  NAME 2  KEY 3  VALUE </pre>
<pre> \setevariables [...] [...] [...] 1  NAME 2  set    = BEFEHL    reset = BEFEHL    KEY   = VALUE </pre>
<pre> \setfirstline [...] *  NAME                                OPT </pre>
<pre> \setflag {...} *  NAME </pre>
<pre> \setfont ... *  FONT </pre>
<pre> \setfontcolorsheme [...] *  NAME </pre>
<pre> \setfontfeature {...} *  NAME </pre>
<pre> \setfontsolution [...] *  NAME </pre>
<pre> \setfontstrut </pre>
<pre> \setgmeasure {...} {...} 1  NAME 2  DIMENSION </pre>

<pre> \setgvalue {...} {...} 1  NAME 2  CONTENT </pre>
<pre> \setgvariable {...} {...} {...} 1  NAME 2  KEY 3  VALUE </pre>
<pre> \setgvariables [...]<sup>1</sup> [...]<sup>2</sup> [...]<sup>2</sup> [...]<sup>2</sup> 1  NAME 2  set    = BEFEHL    reset  = BEFEHL    KEY    = VALUE </pre>
<pre> \sethboxregister ... {...} 1  CSNAME NUMBER 2  CONTENT </pre>
<pre> \sethyphenatedurlafter {...} *  TEXT </pre>
<pre> \sethyphenatedurlbefore {...} *  TEXT </pre>
<pre> \sethyphenatedurlnormal {...} *  TEXT </pre>
<pre> \sethyphenationfeatures [...]<sup>*</sup> [...]<sup>OPT</sup> *  NAME reset </pre>
<pre> \setcharacteralign {...} {...} 1  NUMBER 2  TEXT number-&gt;TEXT text-&gt;TEXT </pre>
<pre> \setcharactercasing [...]<sup>*</sup> *  reset SLOVO slovo Slovo Slova kapitalky Kapitalky zadny nahodny mixed camel kap Kap </pre>
<pre> \setcharactercleaning [...]<sup>*</sup> *  reset 1 </pre>
<pre> \setcharacterkerning [...]<sup>*</sup> *  reset NAME </pre>
<pre> \setcharacterspacing [...]<sup>*</sup> *  reset NAME </pre>
<pre> \setcharacterstripping [...]<sup>*</sup> *  reset 1 </pre>
<pre> \setcharstrut {...} *  TEXT </pre>
<pre> \setinitial [...]<sup>1</sup> [...]<sup>2</sup> [...]<sup>2</sup> [...]<sup>2</sup> 1  NAME          OPT          OPT 2  inherits: \setupinitial </pre>

\setinjector [...]<sup>1</sup> [...,<sup>2</sup>...] [...]<sup>3</sup>

1 NAME  
2 NUMMER  
3 BEFEHL

\setinteraction [...]

\* skryte NAME

\setinterfacecommand {...}<sup>1</sup> {...}<sup>2</sup>

1 NAME  
2 NAME

\setinterfaceconstant {...}<sup>1</sup> {...}<sup>2</sup>

1 NAME  
2 NAME

\setinterfaceelement {...}<sup>1</sup> {...}<sup>2</sup>

1 NAME  
2 NAME

\setinterfacemessage {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup>

1 NAME  
2 titul NAME NUMMER  
3 TEXT

\setinterfacevariable {...}<sup>1</sup> {...}<sup>2</sup>

1 NAME  
2 NAME

\setinternalrendering [...]<sup>1</sup> [...]<sup>2</sup> {...}<sup>3</sup>

1 NAME  
2 auto embed  
3 CONTENT

\setitaliccorrection [...]

\* reset 1 2

\setJSreamble {...}<sup>1</sup> {...}<sup>2</sup>

1 NAME  
2 CONTENT

\setlayer [...]<sup>1</sup> [...]<sup>2</sup> [...,<sup>3</sup>...,...] {...}<sup>4</sup>

1 NAME  
2 vlevo vpravo sude liche  
3 inherits: \setuplayer  
4 CONTENT

\setlayerframed [...]<sup>1</sup> [...,<sup>2</sup>...,...] [...,<sup>3</sup>...,...] {...}<sup>4</sup>

1 NAME  
2 inherits: \setuplayer  
3 inherits: \nastavoramovani  
4 CONTENT

\setlayerframed [...]<sup>1</sup> [...,<sup>2</sup>...,...] {...}<sup>3</sup>

1 NAME  
2 inherits: \setuplayerinherits: \nastavoramovani  
3 CONTENT

**\setlayertext** [<sup>1</sup>...] [<sup>2</sup>...<sub>OPT</sub>...] [<sup>3</sup>...<sub>OPT</sub>...] {<sup>4</sup>...}

1 NAME  
2 inherits: \setuplayer  
3 zarovnnani = inherits: \nastavzarovnnani  
sirka = DIMENSION  
pismo = STYLE BEFEHL  
barva = COLOR  
4 TEXT

**\setlinefiller** [...]

\* filler NAME

**\setlocalhsize** [...]

\* [-+]DIMENSION <sub>OPT</sub>

**\setMPlayer** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...<sub>OPT</sub>...] {<sup>4</sup>...}

1 NAME  
2 NAME  
3 inherits: \setuplayer  
4 CONTENT

**\setMPpositiongraphic** {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...<sub>OPT</sub>...}

1 NAME  
2 NAME  
3 KEY = VALUE

**\setMPpositiongraphicrange** {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...} {<sup>4</sup>...<sub>OPT</sub>...}

1 NAME  
2 NAME  
3 NAME  
4 KEY = VALUE

**\setMPtext** {<sup>1</sup>...} {<sup>2</sup>...}

1 NAME  
2 TEXT

**\setMPvariable** [<sup>1</sup>...] [<sup>2</sup>...]

1 NAME  
2 KEY = VALUE

**\setMPvariables** [<sup>1</sup>...] [<sup>2</sup>...<sub>OPT</sub>...]

1 NAME  
2 KEY = VALUE

**\setmainbodyfont**

**\setmainparbuilder** [...]

\* implicitni oneline basic NAME

**\setmarker** [<sup>1</sup>...] [<sup>2</sup>...]

1 NAME  
2 NUMMER

**\setmarking** [<sup>1</sup>...] {<sup>2</sup>...}

1 BESCHRIFTUNG  
2 TEXT

**\setmathstyle** {...,\*...}

\* obrazovka text script scriptscript cramped uncramped normalni zhustene male velke NAME

<pre> \setmeasure {...} {...} 1  NAME 2  DIMENSION </pre>
<pre> \setmessagetext {...} {...} 1  NAME 2  NAME NUMBER </pre>
<pre> \setmode {...} *  NAME </pre>
<pre> \setnostrut </pre>
<pre> \setnote [...<sup>1</sup>] [...,<sup>2</sup>...] {...<sup>3</sup>} 1  NAME 2  REFERENCE 3  TEXT </pre>
<pre> \setnotetext [...<sup>1</sup>] [...,<sup>2</sup>...] {...<sup>3</sup>} 1  NAME 2  REFERENCE 3  TEXT </pre>
<pre> \setnotetext [...<sup>1</sup>] [...,<sup>2</sup>...] 1  NAME 2  titul    = TEXT    zalozka = TEXT    seznam  = TEXT    odkaz   = REFERENCE </pre>
<pre> \setnote [...<sup>1</sup>] [...,<sup>2</sup>...] 1  NAME 2  titul    = TEXT    zalozka = TEXT    seznam  = TEXT    odkaz   = REFERENCE </pre>
<pre> \setobject {...<sup>1</sup>} {...<sup>2</sup>} \...<sup>3</sup> {...<sup>4</sup>} 1  NAME 2  NAME 3  CSNAME 4  CONTENT </pre>
<pre> \setoldstyle </pre>
<pre> \setpagegrid [...,<sup>1</sup>...] {...<sup>2</sup>} 1  c      = NUMBER    r      = NUMBER    volba  = zadny 2  CONTENT </pre>
<pre> \setpagereference {...<sup>1</sup>} {...,<sup>2</sup>...} 1  NAME 2  REFERENCE </pre>
<pre> \setpagestate [...<sup>1</sup>] [...<sup>2</sup>] 1  NAME 2  NAME NUMBER </pre>
<pre> \setpagestaterealpageno {...<sup>1</sup>} {...<sup>2</sup>} 1  NAME 2  NAME NUMBER </pre>

\setpenalties \...<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup>

1 CSNAME  
2 NUMMER  
3 NUMMER

\setpercentdimen {...}<sup>1</sup> {...}<sup>2</sup>

1 DIMENSION CSNAME  
2 DIMENSION NUMMER

\setposition {...}

\* NAME

\setpositionbox {...}<sup>1</sup> \...<sup>2</sup> {...}<sup>3</sup>

1 NAME  
2 CSNAME  
3 CONTENT

\setpositiondata {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup> {...}<sup>4</sup>

1 NAME  
2 DIMENSION  
3 DIMENSION  
4 DIMENSION

\setpositiondataplus {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup> {...}<sup>4</sup> {...,<sup>5</sup>...}

1 NAME  
2 DIMENSION  
3 DIMENSION  
4 DIMENSION  
5 TEXT

\setpositiononly {...}

\* NAME

\setpositionplus {...}<sup>1</sup> {...,<sup>2</sup>...} \...<sup>3</sup> {...}<sup>4</sup>

1 NAME  
2 TEXT  
3 CSNAME  
4 CONTENT

\setpositionstrut {...}

\* NAME

\setprofile [...]

\* zadny fixne striktni halffixed quarterfixed eightsfixed NAME

\setrandomseed {...}

\* NUMMER

\setreference [...]<sup>1</sup>,... [...]<sup>2</sup>,...]

1 REFERENCE  
2 KEY = VALUE

\setreferencedobject {...}<sup>1</sup> {...}<sup>2</sup> \...<sup>3</sup> {...}<sup>4</sup>

1 NAME  
2 NAME  
3 CSNAME  
4 CONTENT



`\setregisterentry [...]1 [...,...2...,...]2 [...,...3...,...]3`

1 NAME OPT  
2 popisek = NAME  
keys = TEXT PROCESSOR->TEXT  
entries = TEXT PROCESSOR->TEXT  
keys:1 = TEXT  
keys:2 = TEXT  
keys:3 = TEXT  
entries:1 = TEXT  
entries:2 = TEXT  
entries:3 = TEXT  
alternativa = TEXT  
3 KEY = VALUE

`\setreplacement [...]`

\* reset NAME

`\setrigidcolumnbalance ...`

\* CSNAME NUMMER

`\setrigidcolumnhsize {...}1 {...}2 {...}3`

1 DIMENSION  
2 DIMENSION  
3 NUMMER

`\setscript [...]`

\* hangul hanzi nihongo ethiopic thai test NAME

`\setsectionblock [...]1 [...,...2...,...]2`

1 NAME OPT  
2 zalozka = TEXT

`\setsimplecolumnhsize [...,...1...,...]1`

\* n = NUMMER  
sirka = DIMENSION  
vzdalenost = DIMENSION  
radky = NUMMER

`\setsmallbodyfont`

`\setsmallcaps`

`\setstackbox {...}1 {...}2 {...}3`

1 NAME  
2 NAME  
3 CONTENT

`\setstructurepageregister [...]1 [...,...2...,...]2 [...,...3...,...]3`

1 NAME OPT  
2 popisek = NAME  
keys = TEXT PROCESSOR->TEXT  
entries = TEXT PROCESSOR->TEXT  
keys:1 = TEXT  
keys:2 = TEXT  
keys:3 = TEXT  
entries:1 = TEXT  
entries:2 = TEXT  
entries:3 = TEXT  
alternativa = TEXT  
3 KEY = VALUE

`\setstrut`

`\setsuperiors`

<pre> \setssystemmode {...} *   NAME </pre>
<pre> \settabular </pre>
<pre> \settaggedmetadata [...,*...,...] *   KEY = VALUE </pre>
<pre> \settextcontent [...] [...] [...] [...] [...] 1  vrsek zahlavi text upati spodek      OPT      OPT 2  text marginalie hrana 3  vlevo nastred vpravo 4  datum cislostranky BESCHRIFTUNG TEXT BEFEHL 5  datum cislostranky BESCHRIFTUNG TEXT BEFEHL </pre>
<pre> \settightobject {...} {...} \... {...} 1  NAME 2  NAME 3  CSNAME 4  CONTENT </pre>
<pre> \settightreferencedobject {...} {...} \... {...} 1  NAME 2  NAME 3  CSNAME 4  CONTENT </pre>
<pre> \settightunreferencedobject {...} {...} \... {...} 1  NAME 2  NAME 3  CSNAME 4  CONTENT </pre>
<pre> \settrialtypesetting </pre>
<pre> \setuevalue {...} {...} 1  NAME 2  CONTENT </pre>
<pre> \setugvalue {...} {...} 1  NAME 2  CONTENT </pre>
<pre> \setunreferencedobject {...} {...} \... {...} 1  NAME 2  NAME 3  CSNAME 4  CONTENT </pre>

**\setupattachment** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```
1 NAME OPT
2 titul = TEXT
  podtitulek = TEXT
  autor = TEXT
  soubor = FILE
  jmeno = NAME
  buffer = BUFFER
  status = start stop
  metoda = normalni skryte
  symbol = Graph Paperclip Pushpin Default
  sirka = prizpusobive DIMENSION
  vyska = prizpusobive DIMENSION
  hloubka = prizpusobive DIMENSION
  barva = COLOR
  textlayer = NAME
  misto = levahrana pravahrana naokraj levyokraj pravyokraj text vysoko zadny
  vzdalenost = DIMENSION
```

**\setupattachments** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```
1 NAME OPT
2 inherits: \setupattachment
```

**\setupbackend** [...<sup>\*</sup>,...]

```
* export = ano FILE
  xhtml = FILE
  soubor = FILE
  intent = NAME
  mezera = ano ne
  xmpfile = FILE
  formatovat = version implicitni NAME
  uroven = NUMMER
  volba = vzdy nikdy
  profile = FILE
```

**\setupbar** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```
1 NAME OPT
2 barva = COLOR
  pokracovat = ano ne vse
  prazdne = ano ne
  jednotka = ex em pt in cm mm sp bp pc dd cc nc
  order = popredi pozadi
  tloustkalinky = DIMENSION
  metoda = NUMMER
  offset = NUMMER
  dy = NUMMER
  max = NUMMER
  foregroundstyle = STYLE BEFEHL
  foregroundcolor = COLOR
  mp = NAME
  vlevo = TEXT
  vpravo = TEXT
```

**\setupbars** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```
1 NAME OPT
2 inherits: \setupbar
```

**\hiddenbar** {...}

```
* CONTENT
```

**\nobar** {...}

```
* CONTENT
```

**\overbar** {...}

```
* CONTENT
```

**\overbars** {...}

```
* CONTENT
```

<code>\overstrike {...}</code> *    CONTENT
<code>\overstrikes {...}</code> *    CONTENT
<code>\underbar {...}</code> *    CONTENT
<code>\underbars {...}</code> *    CONTENT
<code>\underdash {...}</code> *    CONTENT
<code>\underdashes {...}</code> *    CONTENT
<code>\underdot {...}</code> *    CONTENT
<code>\underdots {...}</code> *    CONTENT
<code>\underrandom {...}</code> *    CONTENT
<code>\underrandoms {...}</code> *    CONTENT
<code>\understrike {...}</code> *    CONTENT
<code>\understrikes {...}</code> *    CONTENT
<code>\setupbleeding [...,...<sup>*</sup>...,...]</code> *    sirka        = DIMENSION *    vyska       = DIMENSION *    offset      = DIMENSION *    hoffset     = DIMENSION *    voffset     = DIMENSION *    misto       = t b l r bl lb br rb tl lt tr rt *    natahnout   = ano ne *    stranka     = ano ne
<code>\setupbookmark [...,...<sup>*</sup>...,...]</code> *    sila                = ano ne *    cislo               = ano ne *    numberseparatorset = NAME *    numberconversionset = NAME *    numberstarter      = BEFEHL *    numberstopper       = BEFEHL *    numbersegments     = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:* ABSCHNITT:vse *    sectionblock       = ano ne

\setupbtx [<sup>1</sup>...] [<sup>2</sup>...,...]

```
1 NAME OPT
2 specification = implicitni apa aps NAME
  dataset      = implicitni NAME
  prikaz       = \...##1
  vlevo        = BEFEHL
  vpravo       = BEFEHL
  authorconversion = normalni normalshort normalinverted invertedshort short
  etallimit    = NUMMER
  etaldisplay  = NUMMER
  etaloption   = posledni
  predel       = initials
  interakce    = start stop cislo text stranka vse
  alternativa  = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
                authornum authoryear
  sorttype     = normalni reverse
  compress     = ano ne
  implicitni   = implicitni NAME
  pismeno     = STYLE BEFEHL
  barva        = COLOR
```

\setupbtxdataset [<sup>1</sup>...,...] [<sup>2</sup>...,...]

```
1 NAME OPT
2 language = SPRACHE
```

\setupbtxlist [<sup>1</sup>...] [<sup>2</sup>...,...]

```
1 NAME OPT
2 inherits: \nastavseznam
```

\setupbtxregister [<sup>1</sup>...,...] [<sup>2</sup>...,...]

```
1 NAME OPT
2 status      = start stop
  dataset     = NAME
  field       = keyword range cislostranky autor
  register    = NAME
  metoda     = once
  alternativa = normalshort invertedshort
  pismeno     = STYLE BEFEHL
  barva       = COLOR
```

\setupbtxrendering [<sup>1</sup>...,...] [<sup>2</sup>...,...]

```
1 NAME OPT
2 statustextu = start stop
  pagestate   = start stop
  oddelovac   = BEFEHL
  kriterium   = predchozi cite zde vse zadny
  specification = NAME
  titul       = TEXT
  pred        = BEFEHL
  po          = BEFEHL
  dataset     = NAME
  metoda     = dataset sila lokalne globalne zadny
  sorttype    = short dataset seznam odkaz uzito implicitni cite rejstrik
  opakovat    = ano ne
  group       = NAME
  cislovani   = ano ne num rejstrik tag short stranka
```

\setupbtx [...]

```
* NAME
```

\setupbutton [<sup>1</sup>...,...] [<sup>2</sup>...,...]

```
1 NAME OPT
2 status      = start stop
  stejnastranka = ano ne prazdne zadny normalni implicitni
  pismeno      = STYLE BEFEHL
  barva        = COLOR
  kontrastnibarva = COLOR
  alternativa  = skryte
  inherits: \nastavoramovani
```

\setupcollector [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
2 rotace = vlevo vpravo uvnitr vnejsi NUMMER  
roh = vlevo nastred vpravo vrsek spodek  
x = DIMENSION  
y = DIMENSION  
hoffset = DIMENSION  
voffset = DIMENSION  
misto = vlevo nastred vpravo vrsek spodek radek l c r m t b g  
status = start stop

\setupcolumnspan [...<sup>\*</sup>,...]

\* n = NUMMER  
inherits: \nastavoramovani

\setupcombination [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
2 nx = NUMMER  
ny = NUMMER  
sirka = prizpusobive DIMENSION  
vyska = prizpusobive DIMENSION  
misto = vlevo nastred vpravo vrsek spodek  
vzdalenost = DIMENSION  
alternativa = popisek text  
zarovnnani = inherits: \nastavzarovnnani  
pokracovat = ano ne  
pred = BEFEHL  
po = BEFEHL  
mezi = BEFEHL  
pismeno = STYLE BEFEHL  
barva = COLOR

\setupcounter [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
2 start = NUMMER  
counter = NAME  
metoda = stranka  
status = start stop  
zpusob = bystranka byblock bytext byhlavicka byABSCHNITT  
prefix = ano ne  
prefixseparatorset = NAME  
prefixconversion = NAME  
prefixconversionset = NAME  
prefixstarter = BEFEHL PROCESSOR->BEFEHL  
prefixstopper = BEFEHL PROCESSOR->BEFEHL  
prefixset = NAME  
prefixsegments = NUMMER NUMMER:NUMMER NUMMER:\* NUMMER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:\* ABSCHNITT:vse  
numberorder = reverse  
numberseparatorset = NAME  
numberconversion = NAME  
numberconversionset = NAME  
numberstarter = BEFEHL PROCESSOR->BEFEHL  
numberstopper = BEFEHL PROCESSOR->BEFEHL  
numbersegments = NUMMER NUMMER:NUMMER NUMMER:\* NUMMER:vse  
typ = prvni predchozi dalsi posledni cislo  
kriterium = striktni positiv vse  
prefixconnector = BEFEHL PROCESSOR->BEFEHL

\setupdataset [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
2 prodleva = ano ne

`\setupdelimitedtext [...1,...] [...2...,...]`

1	NAME		OPT
2	pred	=	BEFEHL
	po	=	BEFEHL
	language	=	lokalne globalne SPRACHE
	metoda	=	font
	opakovat	=	ano ne
	misto	=	text odstavec marginalie
	vlevo	=	BEFEHL
	stredni	=	BEFEHL
	vpravo	=	BEFEHL
	nextleft	=	BEFEHL
	nextright	=	BEFEHL
	mezerapred	=	inherits: \preskoc
	mezeraza	=	inherits: \preskoc
	levyokraj	=	ano ne standardni DIMENSION
	pravyokraj	=	ano ne standardni DIMENSION
	odsazovani	=	inherits: \nastavodsazovani
	odsadpristi	=	ano ne auto
	pismeno	=	STYLE BEFEHL
	barva	=	COLOR
	stylsymboly	=	STYLE BEFEHL
	barvasymbolu	=	COLOR

`\aside [...1] {...2}`

1	SPRACHE	OPT
2	CONTENT	

`\blockquote [...1] {...2}`

1	SPRACHE	OPT
2	CONTENT	

`\quotation [...1] {...2}`

1	SPRACHE	OPT
2	CONTENT	

`\quote [...1] {...2}`

1	SPRACHE	OPT
2	CONTENT	

`\speech [...1] {...2}`

1	SPRACHE	OPT
2	CONTENT	

**\setupdescription** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1	NAME	OPT
2	titul	= ano ne
	uroven	= NUMMER
	text	= TEXT
	headcommand	= \...##1
	pred	= BEFEHL
	po	= BEFEHL
	mezi	= BEFEHL
	alternativa	= vlevo vpravo naokraj i vlevo ivpravo marginalie levyyokraj pravyyokraj innermargin outermargin semknuto visici vrsek prikaz NAME
	zarovnnani	= inherits: \nastavzarovnnani
	headalign	= inherits: \nastavzarovnnani
	odsazovani	= inherits: \nastavodsazovani
	obrazovka	= ano ne
	odsadpristi	= ano ne auto
	sirka	= prizpusobive široky radek DIMENSION
	vzdalenost	= zadny DIMENSION
	natahnout	= NUMMER
	shrink	= NUMMER
	zaveseni	= prizpusobive široky zadny marginalie NUMMER
	closesymbol	= BEFEHL
	closecommand	= \...##1
	expanzen	= ano ne xml
	referenceprefix	= + - TEXT
	vzor	= TEXT
	marginalie	= ano ne standardni DIMENSION
	pismeno	= STYLE BEFEHL
	barva	= COLOR
	stylhlavicky	= STYLE BEFEHL
	barvahlavicky	= COLOR

**\setupdirections** [...<sup>\*</sup>,...]

*	bidi	= zap vyp lokalne globalne
	metoda	= jedna dve implicitni
	fences	= ano ne
	break	= obe pred

**\setupdocument** [...<sup>\*</sup>,...]

*	pred	= BEFEHL
	po	= BEFEHL
	metadata:author	= TEXT
	metadata:title	= TEXT
	metadata:subject	= TEXT
	metadata:keywords	= TEXT
	KEY	= VALUE

**\setupeffect** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1	NAME	OPT
2	metoda	= zadny prikaz
	natahnout	= NUMMER
	tloustkalinky	= NUMMER
	alternativa	= normalni uvnitr vnejsi obe skryte natahnout



**\setupenumeration** [ $\dots^1\dots$ ] [ $\dots^2\dots$ ]

```

1  NAME                OPT
2  titul               = ano ne
   cislo               = ano ne
   ciselnyprikaz       = \...##1
   vzdalenosttitulek   = DIMENSION
   styltitulek         = STYLE BEFEHL
   barvatitulek        = COLOR
   titlecommand        = \...##1
   titleleft           = BEFEHL
   titleright          = BEFEHL
   vlevo               = BEFEHL
   vpravo              = BEFEHL
   symbol              = BEFEHL
   starter             = BEFEHL
   predel              = BEFEHL
   propojeni           = NAME
   counter             = NAME
   uroven              = NUMMER
   text                = TEXT
   headcommand         = \...##1
   pred               = BEFEHL
   po                  = BEFEHL
   mezi               = BEFEHL
   alternativa         = vlevo vpravo naokraj i vlevo i vpravo marginalie levyokraj pravyokraj innermargin outermargin
                        semknuto visici vrsek prikaz NAME
   zarovnani           = inherits: \nastavzarovnani
   headalign           = inherits: \nastavzarovnani
   odsazovani          = inherits: \nastavodsazovani
   obrazovka           = ano ne
   odsadpristi         = ano ne auto
   sirka               = prizpusobive siroky radek DIMENSION
   vzdalenost          = zadny DIMENSION
   natahnout           = NUMMER
   shrink              = NUMMER
   zaveseni            = prizpusobive siroky zadny marginalie NUMMER
   closesymbol         = BEFEHL
   closecommand        = \...##1
   expanzen            = ano ne xml
   referenceprefix     = + - TEXT
   vzor                = TEXT
   marginalie          = ano ne standardni DIMENSION
   pismo               = STYLE BEFEHL
   barva               = COLOR
   stylhlavicky        = STYLE BEFEHL
   barvahlavicky       = COLOR
   inherits: \setupcounter

```

**\setupenv** [ $\dots^*\dots$ ]

```

*  set      = BEFEHL
   reset    = BEFEHL
   KEY      = VALUE

```

**\setupexport** [ $\dots^*\dots$ ]

```

*  zarovnani      = flushleft nastred flushright normalni
   zakladnifont    = DIMENSION
   sirka          = DIMENSION
   titul          = TEXT
   podtitulek     = TEXT
   autor          = TEXT
   alternativa    = html div
   properties     = ano ne
   hyphen         = ano ne
   cssfile        = FILE
   prvnistranka   = FILE
   poslednistrana = FILE

```

`\setupexternalfigure [...1,...] [...2,...]`

```

1  NAME                      OPT
2  sirka                     = DIMENSION
   vyska                     = DIMENSION
   popisek                   = NAME
   stranka                   = NUMMER
   objekt                     = ano ne
   prefix                     = TEXT
   metoda                    = pdf mps jpg png jp2 jbig svg eps gif tif mov buffer tex cld auto
   controls                   = ano ne
   nahled                     = ano ne
   mask                       = zadny
   rozliseni                  = NUMMER
   barva                      = COLOR
   arguments                  = TEXT
   opakovat                   = ano ne
   faktor                     = prizpusobive siroky max auto implicitni
   vfaktor                    = prizpusobive siroky max auto implicitni
   sfaktor                    = prizpusobive siroky max auto implicitni
   maxsirka                   = DIMENSION
   maxvyska                   = DIMENSION
   equalwidth                 = DIMENSION
   equalheight                = DIMENSION
   meritko                    = NUMMER
   xmeritko                   = NUMMER
   ymeritko                   = NUMMER
   s                           = NUMMER
   sx                         = NUMMER
   sy                         = NUMMER
   radky                      = NUMMER
   misto                      = lokalne globalne implicitni
   adresar                    = PATH
   volba                      = test ramecek prazdne
   foregroundcolor            = COLOR
   reset                      = ano ne
   pozadi                     = barevne popredi NAME
   ramecek                    = zap vyp
   barvapozadi                = COLOR
   zarovnnani                 = inherits: \nastavzarovnnani
   xmax                       = NUMMER
   ymax                       = NUMMER
   ramecky                    = zap vyp
   interakce                  = ano vse zadny odkaz layer zalozka
   zakladnifont                = DIMENSION
   comment                    = BEFEHL TEXT
   velikost                   = zadny media crop trim art
   cache                      = PATH
   resources                  = PATH
   obrazovka                  = FILE
   konverze                   = TEXT
   order                      = LISTE
   crossreference              = ano ne NUMMER

```

`\setupexternalsoundtracks [...*,...]`

\* volba = opakovat

`\setupfieldbody [...1,...] [...2,...]`

```

1  NAME                      OPT
2  category = NAME
   inherits: \setupfieldcategory

```

**\setupfieldcategory** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```

1 NAME OPT
2 start = NUMMER
  pismo = STYLE BEFEHL
  barva = COLOR
  typ = radio pod text radek push check signature
  values = TEXT
  implicitni = TEXT
  barvarameckupole = COLOR
  barvapozadipole = COLOR
  sirka = DIMENSION
  vyska = DIMENSION
  hloubka = DIMENSION
  zarovnani = vlevo nastred vpravo flushleft center flushright
  n = NUMMER
  symbol = NAME
  fieldlayer = NAME
  volba = pouze procteni pozadovane chranene tridene nedostupne nocheck fixne soubor skryte tisknutelne
        auto
  klikuvnitr = REFERENCE
  klikvne = REFERENCE
  oblastuvnitr = REFERENCE
  oblastvne = REFERENCE
  klavesapo = REFERENCE
  formatovat = REFERENCE
  validovat = REFERENCE
  pocitat = REFERENCE
  focusin = REFERENCE
  focusout = REFERENCE
  openpage = REFERENCE
  closepage = REFERENCE

```

**\setupfieldcontentframed** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```

1 NAME OPT
2 inherits: \nastavoramovani inherits: \setupfieldcategory

```

**\setupfieldlabelframed** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```

1 NAME OPT
2 inherits: \nastavoramovani

```

**\setupfieldtotalframed** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```

1 NAME OPT
2 pred = BEFEHL
  po = BEFEHL
  mezi = BEFEHL
  vzdalenost = DIMENSION
  alternativa = reset popisek ramecek horizontalne vertikalne
  inherits: \nastavoramovani

```

**\setupfiller** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```

1 NAME OPT
2 levyokraj = DIMENSION
  pravyokraj = DIMENSION
  vlevo = BEFEHL
  vpravo = BEFEHL
  alternativa = symbol natahnout linka mezera
  metoda = lokalne globalne nastred siroky
  sirka = DIMENSION
  vyska = DIMENSION
  hloubka = DIMENSION
  offset = DIMENSION
  vzdalenost = DIMENSION
  zarovnani = vlevo vpravo nastred flushleft flushright uvnitr vnejsi
  symbol = BEFEHL
  pismo = STYLE BEFEHL
  barva = COLOR

```

**\setupfirstline** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```

1 NAME OPT
2 n = NUMMER
  alternativa = implicitni radek slovo
  pismo = STYLE BEFEHL
  barva = COLOR

```

`\setupfittingpage [...1,...] [...2,...,...]`

```
1 NAME OPT
2 pagestate = start stop
  prikaz = \...##1
  marginalie = stranka
  meritko = NUMMER
  papir = auto default NAME
  inherits: \nastavoramovani
```

`\setupfloatcaption [...1,...] [...2,...,...]`

```
1 NAME OPT
2 suffix = BEFEHL
  suffixseparator = BEFEHL
  suffixstopper = BEFEHL
  misto = vlevo vpravo nastred nizko vysoko mrizka prekryv uvnitr vnejsi innermargin outermargin levyokraj
    pravyokraj lefthanging righthanging zaveseni vrsek spodek natahnout zadny implicitni
  prikaz = \...##1
  ciselnyprikaz = \...##1
  textovyprikaz = \...##1
  mezerapred = inherits: \preskoc
  spaceinbetween = inherits: \preskoc
  mezeraza = inherits: \preskoc
  vzdalenost = DIMENSION
  mezi = BEFEHL
  pismeno = STYLE BEFEHL
  barva = COLOR
  offsetvrsku = DIMENSION
  offsetspodku = DIMENSION
  cislo = ano ne zadny
  group = TEXT
  levyokraj = DIMENSION
  pravyokraj = DIMENSION
  innermargin = DIMENSION
  outermargin = DIMENSION
  zarovnani = inherits: \nastavzarovnani
  sirka = prizpusobive max DIMENSION
  minsirka = prizpusobive DIMENSION
  maxsirka = DIMENSION
  inherits: \setupcounter
```

`\setupfontexpansion [...1,...] [...2,...,...]`

```
1 NAME
2 vector = NAME
  faktor = NUMMER
  natahnout = NUMMER
  shrink = NUMMER
  krok = NUMMER
```

`\setupfontprotrusion [...1,...] [...2,...,...]`

```
1 NAME
2 vector = NAME
  faktor = NUMMER
  vlevo = NUMMER
  vpravo = NUMMER
```

`\setupfonts [...*,...,...]`

```
* language = ne auto
```

`\setupfontsolution [...1,...] [...2,...,...]`

```
1 NAME OPT
2 goodies = FILE
  solution = NAME
  less = NAME
  more = NAME
  metoda = preroll split normalni reverse nahodny
  kriterium = NUMMER
```

`\setupforms [...*,...,...]`

```
* metoda = XML HTML PDF
  export = ano ne
```

```

\setupformula [...1,...] [...2...,...]
1 NAME OPT
2 misto = vlevo vpravo
   zarovnnani = vlevo nastred vpravo flushleft center flushright normalni
   strut = ano ne
   vzdalenost = DIMENSION
   vlevo = BEFEHL
   vpravo = BEFEHL
   mezerapred = inherits: \preskoc
   mezeraza = inherits: \preskoc
   ciselny prikaz = \...##1
   barva = COLOR
   stylcisla = STYLE BEFEHL
   barvacisla = COLOR
   volba = zhustene tight nastred ramecek inherits: \nastavzakladnifont
   marginalie = ano ne standardni DIMENSION
   levyokraj = DIMENSION
   pravyokraj = DIMENSION
   alternativa = NAME
   odsadpristi = ano ne auto
   mrizka = inherits: \snaptogrid
   ramecek = cislo
   expanzen = ano ne xml
   referenceprefix = + - TEXT
   xmlsetup = NAME
   catcodes = NAME
   split = ano ne
   inherits: \setupcounter

```

```

\setupformulaframed [...1,...] [...2...,...]
1 NAME OPT
2 inherits: \nastavoramovani

```

```

\setupframedcontent [...1,...] [...2...,...]
1 NAME OPT
2 vlevo = BEFEHL
   vpravo = BEFEHL
   leftoffser = DIMENSION
   pravyoffset = DIMENSION
   offsetvrsku = DIMENSION
   offsetspodku = DIMENSION
   korekceradku = ano ne
   inherits: \nastavoramovani

```

```

\setupframedtext [...1,...] [...2...,...]
1 NAME OPT
2 vlevo = BEFEHL
   vpravo = BEFEHL
   vnitrni = BEFEHL
   misto = vlevo vpravo nastred zadny
   korekcehloubky = zap vyp
   zakladnifont = inherits: \nastavzakladnifont
   odsazovani = inherits: \nastavodsazovani
   pismo = STYLE BEFEHL
   barva = COLOR
   inherits: \nastavoramovani inherits: \setupplacement

```

```

\setupglobalreferenceprefix [...]
* + - TEXT

```

```

\setupheadalternative [...1,...] [...2...,...]
1 NAME OPT
2 alternativa = horizontalne vertikalne nekde
   renderingsetup = NAME

```

```

\setuphelp [...1,...] [...2...,...]
1 NAME OPT
2 inherits: \nastavoramovani

```

`\helptext [...]1 {...}2 {...}3`

1 REFERENCE OPT  
2 TEXT  
3 TEXT

`\setuphigh [...]1,... [...]2,...]`

1 NAME OPT  
2 vzdalenost = DIMENSION  
up = DIMENSION  
pismo = STYLE BEFEHL  
barva = COLOR

`\setuphighlight [...]1,... [...]2,...]`

1 NAME OPT  
2 prikaz = ano ne  
pismo = STYLE BEFEHL  
barva = COLOR

`\unitshigh {...}`

\* CONTENT

`\setuphyphenation [...]*,...]`

\* metoda = original tex implicitni hyphenate expanded traditional zadny

`\setupcharacterkerning [...]1,... [...]2,...]`

1 NAME OPT  
2 faktor = max NUMBER  
sirka = DIMENSION  
features = NAME  
pismo = STYLE BEFEHL  
barva = COLOR

`\setupcharacterspacing [...]1 [...]2 [...]3,...]`

1 NAME OPT  
2 NUMMER  
3 vlevo = NUMMER  
vpravo = NUMMER  
alternativa = 0 1

`\setupchemical [...]1,... [...]2,...]`

1 NAME OPT  
2 strut = ano ne auto kap prizpusobive radek implicitni CHARACTER  
sirka = prizpusobive zadny NUMMER  
vyska = prizpusobive zadny NUMMER  
vlevo = prizpusobive zadny NUMMER  
vpravo = prizpusobive zadny NUMMER  
vrsek = prizpusobive zadny NUMMER  
spodek = prizpusobive zadny NUMMER  
meritko = male stredni velke normalni NUMMER  
rotace = NUMMER  
symzarovnani = auto  
osa = zap vyp  
barvamecku = COLOR  
tloustkalinky = DIMENSION  
offset = DIMENSION  
jednotka = DIMENSION  
faktor = NUMMER  
ramecek = zap vyp  
barvalinky = COLOR  
zakladnifont = inherits: \nastavzakladnifont  
velikost = male stredni velke  
pismo = STYLE BEFEHL  
barva = COLOR

`\setupchemicalframed [...]1,... [...]2,...]`

1 NAME OPT  
2 inherits: \nastavoramovani

`\setupindentedtext [...1,...] [...2...,...]`

1 NAME OPT  
2 pred = BEFEHL  
po = BEFEHL  
vzdalenost = DIMENSION  
vzor = TEXT  
text = TEXT  
sirka = prizpusobive siroky DIMENSION  
oddelovac = BEFEHL  
pismo = STYLE BEFEHL  
barva = COLOR  
stylhlavicky = STYLE BEFEHL  
barvahlavicky = COLOR

`\setupinitial [...1,...] [...2...,...]`

1 NAME OPT  
2 n = NUMMER  
m = NUMMER  
pred = BEFEHL  
vzdalenost = DIMENSION  
hoffset = DIMENSION  
voffset = radek DIMENSION  
pismo = STYLE BEFEHL  
barva = COLOR  
font = FONT  
text = TEXT  
misto = marginalie text  
metoda = prvni posledni auto zadny

`\setupinsertion [...1,...] [...2...,...]`

1 NAME OPT  
2 misto = stranka text sloupce firstcolumn lastcolumn

`\setupitaliccorrection [...*,...]`

\* text vzdy globalne zadny

```

\setupitemgroup [...]1 [...]2 [...]3 [...]4
1 NAME OPT OPT OPT
2 kazdy NUMMER
3 uvod nahodny pokrakovat zhustene autouvod siroky text pred po zadnabila marginalie naokraji naokraji dotextu
uvolnene prizpusobive nofit odstavec spojeny semknuto predel rozbalene opakovat norepeat reverse sloupce jedna dve
tri ctyri pet six seven eight nine standardni NUMMER*siroky NUMMER*semknuto horizontalne NAME
4 pred = BEFEHL
po = BEFEHL
mezi = BEFEHL
predhlavickou = BEFEHL
pohlavicce = BEFEHL
textvlevo = BEFEHL
textvpravo = BEFEHL
vlevo = BEFEHL
vpravo = BEFEHL
faktor = NUMMER
krok = DIMENSION
sirka = DIMENSION
vzdalenost = DIMENSION
marginalie = ano ne standardni DIMENSION
levyokraj = ano ne standardni DIMENSION
pravyokraj = ano ne standardni DIMENSION
zarovnani = inherits: \nastavzarovnani
odsazovani = inherits: \nastavodsazovani
start = NUMMER
symzarovnani = vlevo nastred vpravo flushleft center flushright
symbol = NAME
n = NUMMER
odsadpristi = ano ne auto
vnitrni = BEFEHL
prikaz = CSNAME
polozky = NUMMER
maxsirka = DIMENSION
itemalign = vlevo vpravo nastred flushleft flushright uvnitr vnejsi
alignsymbol = ano ne
textdistance = male stredni velke zadny mezera DIMENSION
predelmista = ano ne
pismo = STYLE BEFEHL
barva = COLOR
stylhlavicky = STYLE BEFEHL
barvahlavicky = COLOR
stylsnacky = STYLE BEFEHL
barvaznacky = COLOR
stylsymboly = STYLE BEFEHL
barvasymbolu = COLOR
mrizka = inherits: \definegridsnapping
inherits: \setupcounter

```



**\setupitemgroup** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```

1  NAME NAME:NUMMER OPT
2  pred             = BEFEHL
   po               = BEFEHL
   mezi            = BEFEHL
   predhlavickou   = BEFEHL
   pohlavicce      = BEFEHL
   textvlevo       = BEFEHL
   textvpravo      = BEFEHL
   vlevo           = BEFEHL
   vpravo          = BEFEHL
   faktor          = NUMMER
   krok            = DIMENSION
   sirka           = DIMENSION
   vzdalenost      = DIMENSION
   volba           = uvod nahodny pokracovat zhustene autouvod siroky text pred po zadnabila marginalie naokraji
                    naokraji dotextu uvolnene prizpusobive nofit odstavec spojeno semknuto predel rozbalene opakovat
                    norepeat reverse sloupce jedna dve tri ctyri pet six seven eight nine standardni NUMMER*siroky
                    NUMMER*semknuto horizontalne NAME

   marginalie      = ano ne standardni DIMENSION
   levyokraj       = ano ne standardni DIMENSION
   pravyokraj      = ano ne standardni DIMENSION
   zarovnani       = inherits: \nastavzarovnani
   odsazovani      = inherits: \nastavodsazovani
   start           = NUMMER
   symzarovnani    = vlevo nastred vpravo flushleft center flushright
   symbol          = NAME
   n               = NUMMER
   odsadpristi     = ano ne auto
   vnitri          = BEFEHL
   prikaz          = CSNAME
   polozky         = NUMMER
   maxsirka        = DIMENSION
   itemalign       = vlevo vpravo nastred flushleft flushright uvnitr vnejsi
   alignsymbol     = ano ne
   textdistance    = male stredni velke zadny mezera DIMENSION
   predelmista     = ano ne
   pismo          = STYLE BEFEHL
   barva           = COLOR
   stylhlavicky    = STYLE BEFEHL
   barvahlavicky   = COLOR
   stylsnacky      = STYLE BEFEHL
   barvaznacky     = COLOR
   stylsymboly     = STYLE BEFEHL
   barvasymbolu    = COLOR
   mrizka          = inherits: \definegridsnapping
   inherits: \setupcounter

```

**\nastaveniITEMGROUP** [...<sup>1</sup>,...] [...<sup>2</sup>,...] [...<sup>3</sup>,...]

```

1  kazdy NUMMER OPT
2  inherits: \setupitemgroup OPT
3  inherits: \setupitemgroup OPT
instances: itemize

```

**\setuplabel** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```

1  NAME          OPT
2  titul          = ano ne
   cislo          = ano ne
   ciselnyprikaz  = \...##1
   vzdalenosttitulek = DIMENSION
   styltitulek    = STYLE BEFEHL
   barvatitulek   = COLOR
   titlecommand   = \...##1
   titleleft      = BEFEHL
   titleright     = BEFEHL
   vlevo          = BEFEHL
   vpravo         = BEFEHL
   symbol         = BEFEHL
   starter        = BEFEHL
   predel         = BEFEHL
   propojeni      = NAME
   counter        = NAME
   uroven         = NUMMER
   text           = TEXT
   headcommand    = \...##1
   pred           = BEFEHL
   po             = BEFEHL
   mezi           = BEFEHL
   alternativa    = vlevo vpravo naokraj ivlevo ivpravo marginalie lev yokraj prav yokraj innermargin outermargin
                   semknuto visici vrsek prikaz dotextu NAME
   zarovnani      = inherits: \nastavzarovnani
   headalign      = inherits: \nastavzarovnani
   odsazovani     = inherits: \nastavodsazovani
   obrazovka      = ano ne
   odsadpristi    = ano ne auto
   sirka          = prizpusobive siroky radek DIMENSION
   vzdalenost     = zadny DIMENSION
   zaveseni       = prizpusobive siroky zadny marginalie NUMMER
   closesymbol    = BEFEHL
   closecommand   = \...##1
   expanzen       = ano ne xml
   referenceprefix = + - TEXT
   vzor           = TEXT
   marginalie     = ano ne standardni DIMENSION
   pismo          = STYLE BEFEHL
   barva          = COLOR
   stylhlavicky   = STYLE BEFEHL
   barvahlavicky  = COLOR
   inherits: \setupcounter

```

**\setuplayer** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```

1  NAME          OPT
2  status        = start stop pokracovat dalsi opakovat
   volba         = test
   stranka       = NUMMER
   sirka         = DIMENSION
   vyska         = DIMENSION
   region        = NAME
   rotace        = vlevo vpravo uvnitr vnejsi NUMMER
   position      = ano ne prekryv
   hoffset       = max DIMENSION
   voffset       = max DIMENSION
   offset        = DIMENSION
   dx            = DIMENSION
   dy            = DIMENSION
   sx            = NUMMER
   sy            = NUMMER
   x             = DIMENSION
   y             = DIMENSION
   roh           = vlevo nastred vpravo vrsek spodek
   misto         = mrizka vlevo nastred vpravo vrsek spodek radek l c r m t b g
   radek         = NUMMER
   sloupec       = NUMMER
   smer          = normalni reverse
   oboustranne   = ano ne
   metoda        = prizpusobive prekryv
   opakovat      = ano
   prednastaveni = lefttop righttop leftbottom rightbottom nastred middletop middlebottom middleleft middleright
                   lefttopleft lefttopright NAME

```

`\setuplayeredtext [...,1...] [...,2...,...]`

1 NAME <sup>OPT</sup>  
2 pismoeno = STYLE BEFEHL  
barva = COLOR  
inherits: \nastavoramovani

`\setuplayouttext [...1] [...2] [...,3...,...]`

1 vrsek zahlavi text upati spo<sup>OPT</sup>dek  
2 text marginalie hrana  
3 status = start stop prazdne vysoko zadny normalni zadneznaceni NAME  
pismoeno = STYLE BEFEHL  
barva = COLOR  
strut = ano ne  
n = NUMMER  
pred = BEFEHL  
po = BEFEHL  
stylvlevo = STYLE BEFEHL  
stylvpravo = STYLE BEFEHL  
barvavlevo = COLOR  
barvavpravo = COLOR  
sirka = DIMENSION  
sirkavlevo = DIMENSION  
sirkavpravo = DIMENSION

`\setuplinefiller [...,1...] [...,2...,...]`

1 NAME <sup>OPT</sup>  
2 misto = vlevo vpravo obe  
rozsah = vlevo vpravo lokalne  
mp = NAME  
vyska = DIMENSION  
hloubka = DIMENSION  
vzdalenost = DIMENSION  
threshold = DIMENSION  
tloustkalinky = DIMENSION  
pred = BEFEHL  
po = BEFEHL  
barva = COLOR  
styltextu = STYLE BEFEHL  
barvatextu = COLOR  
zarovnani = inherits: \nastavzarovnani

`\setuplinefillers [...,1...] [...,2...,...]`

1 NAME <sup>OPT</sup>  
2 inherits: \setuplinefiller

`\setuplinenote [...,1...] [...,2...,...]`

1 NAME <sup>OPT</sup>  
2 compress = ano ne  
compressmethod = separator predel mezera  
compressseparator = BEFEHL  
compressdistance = DIMENSION  
inherits: \setupnote

`\linenote {...}`

\* TEXT

**\setuplinetable** [...<sup>1</sup>] [...<sup>2</sup>] [...,<sup>3</sup>...]

```

1  r c                OPT      OPT
2  liche sude zahlavi NUMMER
3  radky              = prizpusobive NUMMER
   pred               = BEFEHL
   po                 = BEFEHL
   mezi              = BEFEHL
   natahnout         = ano ne DIMENSION
   maxsirka          = prizpusobive DIMENSION
   nvlevo            = NUMMER
   n                  = NUMMER
   opakovat         = ano ne
   nx                 = NUMMER
   sirka             = DIMENSION
   vyska             = prizpusobive radek DIMENSION
   vzdalenost        = DIMENSION
   levyoffset        = DIMENSION
   pravyoffset       = DIMENSION
   zarovnani         = inherits: \nastavzarovnani
   pozadi            = barevne
   barvapozadi       = COLOR
   xheight           = max DIMENSION
   xdepth            = max DIMENSION
   pismo             = STYLE BEFEHL
   barva             = COLOR

```

**\setuplistalternative** [...<sup>1</sup>,...] [...,<sup>2</sup>...]

```

1  NAME                OPT
2  pred                = BEFEHL
   po                  = BEFEHL
   prikaz              = \...##1##2##3
   renderingsetup      = NAME
   sirka               = DIMENSION
   vzdalenost          = DIMENSION
   natahnout           = DIMENSION
   filler              = BEFEHL

```

**\setuplistextra** [...<sup>1</sup>,...] [...,<sup>2</sup>...]

```

1  NAME                OPT
2  pred = BEFEHL
   po  = BEFEHL

```

**\setuplocalfloats** [...,<sup>\*</sup>...]

```

*  pred = BEFEHL
   po   = BEFEHL
   mezi = BEFEHL

```

**\setuplocalinterlinespace** [...<sup>1</sup>,...] [...,<sup>2</sup>...]

```

1  NAME                OPT
2  inherits: \nastavmeziradkovoumezeru

```

**\setuplocalinterlinespace** [...,<sup>\*</sup>...]

```

*  zap vyp reset auto male stredni velkeOPT NUMMER DIMENSION

```

**\setuplocalinterlinespace** [...<sup>\*</sup>...]

```

*  NAME

```

**\setuplow** [...<sup>1</sup>,...] [...,<sup>2</sup>...]

```

1  NAME                OPT
2  vzdalenost = DIMENSION
   down       = DIMENSION
   pismo      = STYLE BEFEHL
   barva      = COLOR

```

`\setuplowhigh [...1,...] [...2...,...]`

```
1 NAME OPT
2 vzdalenost = DIMENSION
  up          = DIMENSION
  down        = DIMENSION
  pismo       = STYLE BEFEHL
  barva       = COLOR
```

`\setuplowmidhigh [...1,...] [...2...,...]`

```
1 NAME OPT
2 up      = DIMENSION
  down    = DIMENSION
  pismo   = STYLE BEFEHL
  barva   = COLOR
```

`\unitslow {...}`

\* CONTENT

`\setupMPgraphics [...*...,...]`

```
* barva = lokalne globalne
  mpy    = FILE
```

`\setupMPinstance [...1,...] [...2...,...]`

```
1 NAME OPT
2 formatovat = metafun mpost
  initializations = ano ne
  setups          = NAME
  styltextu       = STYLE BEFEHL
  barvatextu      = COLOR
  extensions      = ano ne
  metoda         = binary decimal double scaled implicitni
```

`\setupMPpage [...*...,...]`

\* inherits: \setupfittingpage

`\setupMPvariables [...1,...] [...2...,...]`

```
1 NAME OPT
2 KEY = VALUE
```

`\setupmarginblock [...1,...] [...2...,...]`

```
1 NAME OPT
2 status = start stop
  sirka   = DIMENSION
  pred    = BEFEHL
  po      = BEFEHL
  mezi    = BEFEHL
  zarovnani = inherits: \nastavzarovnani
  pismo    = STYLE BEFEHL
  barva    = COLOR
  vrsek    = BEFEHL
  spodek   = BEFEHL
  misto    = vlevo vpravo nastred naokraj
  vlevo    = BEFEHL
  vpravo   = BEFEHL
```

```

\setupmargindata [...1...] [...2...]
1 NAME OPT
2 strut = ano ne auto kap prizpusobive radek implicitni CHARACTER
   prikaz = \...#1
   sirka = DIMENSION
   zarovnani = inherits: \nastavzarovnani
   anchor = region text
   misto = vlevo vpravo uvnitr vnejsi
   metoda = vrsek radek prvni podlehloubky vyska
   category = implicitni hrana
   rozsah = lokalne globalne
   volba = text odstavec
   marginalie = lokalne normalni marginalie hrana
   vzdalenost = DIMENSION
   hoffset = DIMENSION
   voffset = DIMENSION
   dy = DIMENSION
   bottomspace = DIMENSION
   threshold = DIMENSION
   radek = NUMMER
   stack = ano pokracovat
   pismo = STYLE BEFEHL
   barva = COLOR

```

```

\setupmarginframed [...1...] [...2...]
1 NAME OPT
2 inherits: \nastavoramovani

```

```

\atleftmargin [...1...] [...2...] {...3}
1 odkaz = REFERENCE OPT OPT
   inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\atrighmargin [...1...] [...2...] {...3}
1 odkaz = REFERENCE OPT OPT
   inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\ininner [...1...] [...2...] {...3}
1 odkaz = REFERENCE OPT
   inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\ininneredge [...1...] [...2...] {...3}
1 odkaz = REFERENCE OPT OPT
   inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\ininnermargin [...1...] [...2...] {...3}
1 odkaz = REFERENCE OPT OPT
   inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inleft [...1...] [...2...] {...3}
1 odkaz = REFERENCE OPT
   inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inleftedge [...1...] [...2...] {...3}
1 odkaz = REFERENCE OPT OPT
   inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inleftmargin [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] {\stackrel{3}{...}}
1 odkaz = REFERENCE OPT OPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inmargin [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] {\stackrel{3}{...}}
1 odkaz = REFERENCE OPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inotherr [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] {\stackrel{3}{...}}
1 odkaz = REFERENCE OPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inouter [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] {\stackrel{3}{...}}
1 odkaz = REFERENCE OPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inouteredge [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] {\stackrel{3}{...}}
1 odkaz = REFERENCE OPT OPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inoutermargin [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] {\stackrel{3}{...}}
1 odkaz = REFERENCE OPT OPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inright [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] {\stackrel{3}{...}}
1 odkaz = REFERENCE OPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inrightedge [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] {\stackrel{3}{...}}
1 odkaz = REFERENCE OPT OPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inrightmargin [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] {\stackrel{3}{...}}
1 odkaz = REFERENCE OPT OPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\margintext [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] {\stackrel{3}{...}}
1 odkaz = REFERENCE OPT OPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\setupmarginrule [\stackrel{1}{...}] [...,\stackrel{2}{=},...]
1 NUMMER OPT
2 inherits: \setupsidebar

```

`\setupmathalignment [...1,...] [...2,...]`

```
1 NAME OPT
2 n = NUMBER
  m = NUMBER
  vzdalenost = DIMENSION
  cislo = auto
  oddelovac = TEXT
  zarovnani = vlevo nastred vpravo normalni
  misto = vrsek center spodek normalni
  mrizka = math ne
```

`\setupmathcases [...1,...] [...2,...]`

```
1 NAME OPT
2 vlevo = BEFEHL
  vpravo = BEFEHL
  strut = ano ne
  pismeno = STYLE BEFEHL
  vzdalenost = DIMENSION
  numberdistance = DIMENSION
```

`\setupmathematics [...1,...] [...2,...]`

```
1 NAME OPT
2 openup = ano ne
  sadasymbolu = NAME
  functionstyle = STYLE BEFEHL
  compact = ano ne
  zarovnani = l2r r2l
  bidi = ano ne
  sygreek = normalni kurziva zadny
  lcgreeek = normalni kurziva zadny
  ucgreeek = normalni kurziva zadny
  italics = 1 2 3 4 zadny reset
  autopunctuation = ano ne vse
  setups = NAME
  domain = NAME reset
  styltextu = STYLE BEFEHL
  barvatextu = COLOR
  functioncolor = COLOR
  integral = limits nolimits autolimits displaylimits zadny
  stylealternative = NAME
  implicitni = normalni kurziva
  fraction = ams ctx
```

`\setupmathfence [...1,...] [...2,...]`

```
1 NAME OPT
2 prikaz = ano ne
  vlevo = NUMBER
  stredni = NUMBER
  vpravo = NUMBER
  mathstyle = obrazovka text script scriptscript cramped uncramped normalni zhustene male velke
  barva = COLOR
  status = auto
  metoda = auto
  faktor = zadny auto NUMBER
```

`\setupmathfraction [...1,...] [...2,...]`

```
1 NAME OPT
2 vzdalenostvrsku = DIMENSION
  vzdalenostspodku = DIMENSION
  marginalie = DIMENSION
  barva = COLOR
  strut = ano ne math tight
  alternativa = uvnitr vnejsi obe
  linka = ano ne auto
  vlevo = NUMBER
  vpravo = NUMBER
  inlinethreshold = NUMBER
  displaythreshold = NUMBER
  fences = CD:STRING
  tloustkalinky = DIMENSION
  mathstyle = STYLE BEFEHL
  vzdalenost = ne zadny prekryv
```



$\backslash\text{setupmathfractions}$ [ $\dots^1\dots$ ] [ $\dots^2\dots$ ] 1 NAME <small>OPT</small> 2 inherits: $\backslash\text{setupmathfraction}$
$\backslash\text{binom}$ $\{\dots^1\}$ $\{\dots^2\}$ 1 CONTENT 2 CONTENT
$\backslash\text{dbinom}$ $\{\dots^1\}$ $\{\dots^2\}$ 1 CONTENT 2 CONTENT
$\backslash\text{dfrac}$ $\{\dots^1\}$ $\{\dots^2\}$ 1 CONTENT 2 CONTENT
$\backslash\text{frac}$ $\{\dots^1\}$ $\{\dots^2\}$ 1 CONTENT 2 CONTENT
$\backslash\text{sfrac}$ $\{\dots^1\}$ $\{\dots^2\}$ 1 CONTENT 2 CONTENT
$\backslash\text{tbinom}$ $\{\dots^1\}$ $\{\dots^2\}$ 1 CONTENT 2 CONTENT
$\backslash\text{xfrac}$ $\{\dots^1\}$ $\{\dots^2\}$ 1 CONTENT 2 CONTENT
$\backslash\text{xxfrac}$ $\{\dots^1\}$ $\{\dots^2\}$ 1 CONTENT 2 CONTENT
$\backslash\text{setupmathframed}$ [ $\dots^1\dots$ ] [ $\dots^2\dots$ ] 1 NAME <small>OPT</small> 2 inherits: $\backslash\text{nastavoramovani}$
$\backslash\text{inmframed}$ [ $\dots^1\dots$ ] $\{\dots^2\}$ 1 inherits: $\backslash\text{setupmathframed}$ <small>OPT</small> 2 CONTENT
$\backslash\text{mcfamed}$ [ $\dots^1\dots$ ] $\{\dots^2\}$ 1 inherits: $\backslash\text{setupmathframed}$ <small>OPT</small> 2 CONTENT
$\backslash\text{mframed}$ [ $\dots^1\dots$ ] $\{\dots^2\}$ 1 inherits: $\backslash\text{setupmathframed}$ <small>OPT</small> 2 CONTENT
$\backslash\text{setupmathmatrix}$ [ $\dots^1\dots$ ] [ $\dots^2\dots$ ] 1 NAME <small>OPT</small> 2 vlevo = BEFEHL vpravo = BEFEHL strut = ano ne NUMMER zarovnani = vlevo nastred vpravo normalni pismo = STYLE BEFEHL vzdalenost = DIMENSION misto = vrsek spodek vysoko nizko nivy normalni

```
\setupmathornament [...1,...] [...2,...]
1 NAME OPT
2 alternativa = mp
   barva      = COLOR
   mpoffset   = DIMENSION
   mp         = NAME
```

```
\setupmathradical [...1,...] [...2,...]
1 NAME OPT
2 alternativa = implicitni normalni mp
   barva      = COLOR
   mpoffset   = DIMENSION
   mp         = NAME
```

```
\setupmathstackers [...1,...] [...2,...]
1 NAME OPT
2 vlevo      = BEFEHL
   vpravo    = BEFEHL
   topcommand = \...##1
   bottomcommand = \...##1
   middlecommand = \...##1
   mp        = NAME
   mpheight  = DIMENSION
   mpdepth   = DIMENSION
   mpoffset  = DIMENSION
   barva     = COLOR
   hoffset   = DIMENSION
   voffset   = DIMENSION
   minvyska  = DIMENSION
   mindepth  = DIMENSION
   mathclass = rel ord
   offset    = min max normalni
   misto     = vrsek spodek vysoko nizko nastred NUMBER
   strut     = ano ne
   alternativa = normalni implicitni mp
   minsirka  = DIMENSION
   vzdalenost = DIMENSION
   moffset   = DIMENSION
   order     = normalni reverse
   mathlimits = ano ne
```

```
\setupmathstyle [...,*...]
* obrazovka text script scriptscript cramped uncramped normalni zhustene male velke NAME
```

```
\setupmixedcolumns [...1,...] [...2,...]
1 NAME OPT
2 mrizka      = inherits: \definegridsnapping
   tloustkalinky = DIMENSION
   metoda     = otr box
   pred       = BEFEHL
   po         = BEFEHL
   vzdalenost  = DIMENSION
   n          = NUMMER
   maxvyska   = DIMENSION
   maxsirka   = DIMENSION
   krok       = DIMENSION
   profile    = NAME
   zarovnani  = inherits: \nastavzarovnani
   setups     = NAME
   rovnovaha  = ano ne
   splitmethod = zadny fixne
   alternativa = lokalne globalne
   internalgrid = radek pulradku
   oddelovac  = linka
   strut      = ano ne
   barva      = COLOR
   barvalinky = COLOR
   smer       = normalni reverse
   inherits: \nastavoramovani
```

```
\setupmodule [...1] [...2,...]
1 FILE OPT
2 test = ano ne
   KEY = VALUE
```

`\setupnotation [...1,...] [...2,...]`

```

1  NAME                OPT
2  titul               = ano ne
   cislo               = ano ne
   typ                = note
   ciselnyprikaz       = \...##1
   vzdalenosttitulek  = DIMENSION
   styltitulek        = STYLE BEFEHL
   barvatitulek       = COLOR
   titlecommand       = \...##1
   titleleft         = BEFEHL
   titleright        = BEFEHL
   vlevo             = BEFEHL
   vpravo            = BEFEHL
   symbol            = BEFEHL
   starter           = BEFEHL
   predel            = BEFEHL
   propojeni         = NAME
   counter           = NAME
   uroven            = NUMBER
   text              = TEXT
   headcommand       = \...##1
   pred              = BEFEHL
   po                 = BEFEHL
   mezi              = BEFEHL
   alternativa       = vlevo vpravo naokraj i vlevo i vpravo
                        marginalie levýokraj pravýokraj innermargin outermargin
                        semknuto visici vrsek prikaz note NAME
   zarovnani          = inherits: \nastavzarovnani
   headalign          = inherits: \nastavzarovnani
   odsazovani         = inherits: \nastavodsazovani
   obrazovka          = ano ne
   odsadpristi        = ano ne auto
   sirka              = prizpusobive široky radek DIMENSION
   vzdalenost         = zadny DIMENSION
   natahnout         = NUMBER
   shrink             = NUMBER
   zaveseni           = prizpusobive široky zadny marginalie NUMBER
   closesymbol        = BEFEHL
   closecommand       = \...##1
   expanzen           = ano ne xml
   referenceprefix    = + - TEXT
   vzor               = TEXT
   marginalie         = ano ne standardni DIMENSION
   pismo              = STYLE BEFEHL
   barva              = COLOR
   stylhlavicky       = STYLE BEFEHL
   barvahlavicky      = COLOR
   inherits: \setupcounter

```

`\setupnotations [...1,...] [...2,...]`

```

1  NAME                OPT
2  inherits: \setupnotation

```

**\setupnote** [<sup>1</sup>...,<sup>2</sup>...] [<sup>1</sup>...,<sup>2</sup>...,...]

```

1  NAME          OPT
2  interakce      = ano ne cislo text vse
   symbolcommand = \...##1
   textovyprikaz = \...##1
   indikator      = ano ne
   oddelovactextu = BEFEHL
   sirka          = DIMENSION
   vyska          = DIMENSION
   vzdalenost     = DIMENSION
   rulecommand    = BEFEHL
   linka          = zap vyp normalni vlevo vpravo prikaz odstavec
   split          = tolerantni striktni velmistriktni NUMMER
   faktor         = NUMMER
   misto          = text stranka vysoko spodek zadny sloupce firstcolumn lastcolumn
   dalsi          = BEFEHL
   n              = NUMMER
   barvalinky     = COLOR
   tloustkalinky  = DIMENSION
   setups         = NAME
   meziradkovamezera = NAME
   odstavec       = ano ne
   pred           = BEFEHL
   po             = BEFEHL
   mezi           = BEFEHL
   rozsah         = stranka
   vzdalenostsloupcu = DIMENSION
   pokracovat     = ano ne
   alternativa    = mrizka fixne sloupce note zadny
   kriterium      = stranka
   zakladnifont   = inherits: \nastavzakladnifont
   zarovnani      = inherits: \nastavzarovnani
   styltextu      = STYLE BEFEHL
   barvatextu     = COLOR
   anchor         = dalsi
   mezerapred     = inherits: \preskoc
   spaceinbetween = inherits: \preskoc
   inherits: \nastavoramovani

```

**\setupnotes** [<sup>1</sup>...,<sup>2</sup>...] [<sup>1</sup>...,<sup>2</sup>...,...]

```

1  NAME          OPT
2  inherits: \setupnote

```

**\setupoffset** [<sup>\*</sup>...,<sup>\*</sup>...] [<sup>\*</sup>...,<sup>\*</sup>...,...]

```

*  inherits: \setupoffsetbox

```

**\setupoffsetbox** [<sup>\*</sup>...,<sup>\*</sup>...,...]

```

*  x              = DIMENSION
   y              = DIMENSION
   levyoffset     = DIMENSION
   pravyoffset    = DIMENSION
   offsetvrsku    = DIMENSION
   offsetspodku   = DIMENSION
   metoda        = fixne
   sirka          = DIMENSION
   vyska          = DIMENSION
   hloubka        = DIMENSION
   misto          = vlevo nastred vpravo vrsek spodek radek l c r m t b g

```

**\setupoutputroutine** [<sup>1</sup>...] [<sup>1</sup>...,<sup>2</sup>...,...]

```

1  NAME          OPT
2  KEY = CSNAME

```

**\setupoutputroutine** [<sup>\*</sup>...]

```

*  NAME

```

`\setuppagegrid [...1,...] [...2,...]`

```
1 NAME OPT
2 n = NUMBER
  nvlevo = NUMBER
  nvpravo = NUMBER
  sirka = DIMENSION auto
  vzdalenost = DIMENSION
  radky = NUMBER
  maxsirka = DIMENSION
  maxvyska = DIMENSION
  smer = normalni reverse
  stranka = inherits: \strana
  inherits: \nastavoramovani
```

`\setuppagegridarea [...1,...] [...2,...]`

```
1 NAME OPT
2 status = start stop opakovat
  x = NUMBER
  y = NUMBER
  nx = NUMBER
  ny = NUMBER
  pismeno = STYLE BEFEHL
  barva = COLOR
  clipoffset = DIMENSION
  pravyoffset = DIMENSION
  inherits: \nastavoramovani
```

`\setuppagegridareatext [...1] [...2]`

```
1 NAME
2 TEXT
```

`\setuppagegridlines [...1] [...2] [...3] [...4]`

```
1 NAME
2 NUMMER
3 NUMMER
4 NUMMER
```

`\setuppagegridspan [...1,...] [...2,...]`

```
1 NAME OPT
2 n = NUMBER
  pismeno = STYLE BEFEHL
  barva = COLOR
  pred = BEFEHL
  po = BEFEHL
  inherits: \nastavoramovani
```

`\setuppagegridstart [...1] [...2] [...3] [...4]`

```
1 NAME
2 NUMMER
3 NUMMER
4 NUMMER
```

`\setuppagechecker [...1,...] [...2,...]`

```
1 NAME OPT
2 radky = NUMBER
  offset = DIMENSION
  metoda = 0 1 2 3
  pred = BEFEHL
  po = BEFEHL
  mezi = BEFEHL
```

`\setuppageinjection [...1,...] [...2,...]`

```
1 NAME OPT
2 status = predchozi dalsi NUMMER
  prodleva = ano ne
  alternativa = obrazek buffer setups zadny NAME
  stranka = inherits: \strana
  pagestate = start stop
  n = NUMBER
  inherits: \nastavoramovani
```

<pre> \setuppageinjectionalternative [...<sup>1</sup>,...] [...<sup>2</sup>,...] 1  NAME                                OPT 2  renderingsetup = NAME </pre>
<pre> \setuppageshift [...<sup>1</sup>] [...<sup>2</sup>] [...<sup>3</sup>] 1  stranka papir      OPT      OPT 2  NAME 3  NAME </pre>
<pre> \setuppagestate [...<sup>1</sup>,...] [...<sup>2</sup>,...] 1  NAME                                OPT 2  prodleva = ano ne </pre>
<pre> \setuppairedbox [...<sup>1</sup>,...] [...<sup>2</sup>,...] 1  NAME                                OPT 2  pred      = BEFEHL    po        = BEFEHL    mezi      = BEFEHL    misto     = vlevo nastred vpravo vrsek spodek vysoko nizko    n         = NUMMER    vzdalenost = DIMENSION    zakladnifont = inherits: \nastavzakladnifont    sirka     = DIMENSION    vyska     = DIMENSION    maxsirka  = DIMENSION    maxvyska  = DIMENSION    zarovnani = inherits: \nastavzarovnani    pismo     = STYLE BEFEHL    barva     = COLOR </pre>
<pre> \nastaveniPAIREDBOX [...<sup>*</sup>,...] * inherits: \setuppairedbox instances: legend </pre>
<pre> \umistilegend [...<sup>1</sup>,...] {...<sup>2</sup>} {...<sup>3</sup>} 1  inherits: \setuppairedbox 2  CONTENT 3  TEXT </pre>
<pre> \setuppaper [...<sup>*</sup>,...] * inherits: \nastavvelikostpapiru </pre>
<pre> \setupparagraph [...<sup>1</sup>,...] [...<sup>2</sup>,...] 1  NAME                                OPT 2  pismo     = STYLE BEFEHL    barva     = COLOR    zarovnani = inherits: \nastavzarovnani    setups    = NAME </pre>
<pre> \setupparagraphintro [...<sup>1</sup>,...] [...<sup>2</sup>] 1  reset kazdy prvni dalsi 2  BEFEHL </pre>
<pre> \setupparallel [...<sup>1</sup>] [...<sup>2</sup>,...] [...<sup>3</sup>,...] 1  NAME 2  NAME 3  setups    = NAME    start     = NUMMER    n         = NUMMER    kriterium = vse </pre>
<pre> \setupperiods [...<sup>*</sup>,...] * n      = NUMMER    sirka  = DIMENSION prizpusobive    vzdalenost = DIMENSION    symbol  = BEFEHL </pre>

`\setupplacement [...1,...] [...2,...]`

```
1 NAME OPT
2 pred = BEFEHL
  po = BEFEHL
  vlevo = BEFEHL
  vpravo = BEFEHL
  mrizka = inherits: \snaptogrid
  korekceradku = zap vyp
  korekcehloubky = zap vyp
  marginalie = ano ne standardni
```

`\setuppositionbar [...*,...]`

```
* pismeno = STYLE BEFEHL
  barva = COLOR
  n = NUMMER
  min = NUMMER
  max = NUMMER
  text = TEXT
  sirka = DIMENSION
  vyska = DIMENSION
  hloubka = DIMENSION
```

`\setupprocessor [...1,...] [...2,...]`

```
1 NAME OPT
2 status = start stop
  vlevo = BEFEHL
  vpravo = BEFEHL
  prikaz = \...##1
  pismeno = STYLE BEFEHL
  barva = COLOR
```

`\setupprofile [...1,...] [...2,...]`

```
1 NAME OPT
2 vyska = DIMENSION
  hloubka = DIMENSION
  vzdalenost = DIMENSION
  faktor = NUMMER
  radky = NUMMER
  metoda = striktni fixne zadny
```

`\setupquotation [...*,...]`

```
* inherits: \setupdelimitedtext
```

`\setuprealpagenumber [...*,...]`

```
* inherits: \setupcounter
```

`\setupreferenceformat [...1,...] [...2,...]`

```
1 NAME OPT
2 popisek = * NAME
  vlevo = BEFEHL
  vpravo = BEFEHL
  typ = implicitni text titul cislo stranka realpage
  setups = NAME
  autocase = ano ne
  text = TEXT
  pismeno = STYLE BEFEHL
  barva = COLOR
```

`\setupreferenceprefix [...]`

```
* + - TEXT
```

```

\setupreferencestructureprefix [...1] [...2] [...,3...,...]
1  NAME ABSCHNITT                                OPT      OPT
2  implicitni
3  prefix = ano ne
    prefixseparatorset = NAME
    prefixconversion = NAME
    prefixconversionset = NAME
    prefixstarter = BEFEHL PROCESSOR->BEFEHL
    prefixstopper = BEFEHL PROCESSOR->BEFEHL
    prefixset = NAME
    prefixsegments = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:* ABSCHNITT:vse
    numberconversion = NAME
    numberconversionset = NAME
    numberstarter = BEFEHL PROCESSOR->BEFEHL
    numberstopper = BEFEHL PROCESSOR->BEFEHL
    numbersegments = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse
    numberseparatorset = NAME
    prefixconnector = BEFEHL PROCESSOR->BEFEHL

```

```

\setupregisters [...1] [...,2...,...]
1  NAME NAME:NUMMER OPT
2  inherits: \nastavrejstrik

```

```

\setupregisters [...,1...] [...,2...] [...,3...,...]
1  NAME OPT OPT
2  NUMMER
3  inherits: \nastavrejstrik

```

```

\index [...1] [...+2+...]
1  TEXT PROCESSOR->TEXT
2  INDEX

```

```

\setuprenderingwindow [...,1...] [...,2...,...]
1  NAME OPT
2  akceotevrenistranky = REFERENCE
    akcezavrenistranky = REFERENCE
    inherits: \nastavoramovani

```

```

\setups [...,*...]
*  NAME

```

```

\setupscale [...,1...] [...,2...,...]
1  NAME OPT
2  meritko = NUMMER
    xmeritko = NUMMER
    ymeritko = NUMMER
    sirka = DIMENSION
    vyska = DIMENSION
    hloubka = ano ne
    radky = NUMMER
    faktor = prizpusobive siroky max auto implicitni
    vfaktor = prizpusobive siroky max auto implicitni
    sfaktor = prizpusobive siroky max auto implicitni
    maxsirka = DIMENSION
    maxvyska = DIMENSION
    s = NUMMER
    sx = NUMMER
    sy = NUMMER
    equalwidth = DIMENSION
    equalheight = DIMENSION
    mrizka = ano prizpusobive vyska podlehloubky pulradku

```

```

\setupscript [...,1...] [...,2...,...]
1  NAME OPT
2  metoda = hangul hanzi nihongo ethiopic thai test
    prednastaveni = NAME
    features = auto

```



**\setupscripts** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME OPT  
2 inherits: \setupscript

**\setupselector** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME  
2 n = NUMBER  
m = NUMBER

**\setupshift** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME OPT  
2 pokracovat = ano ne  
jednotka = ex em pt in cm mm sp bp pc dd cc nc  
metoda = NUMBER  
dy = NUMBER  
zarovnani = inherits: \nastavzarovnani  
pismo = STYLE BEFEHL  
barva = COLOR

**\shiftdown** {...}

\* CONTENT

**\shiftup** {...}

\* CONTENT

**\setupsidebar** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME OPT  
2 tloustkalinky = DIMENSION  
barvalinky = COLOR  
alternativa = NUMBER  
offsetvrsku = DIMENSION  
offsetspodku = DIMENSION  
vzdalenost = DIMENSION  
vzdalenostlevehookraje = DIMENSION  
uroven = NUMBER

**\setupspellchecking** [...,<sup>\*</sup>...,...]

\* status = start stop  
metoda = 1 2 3  
seznam = NAME

**\setupstartstop** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME OPT  
2 pred = BEFEHL  
po = BEFEHL  
mezi = BEFEHL  
setups = NAME  
vlevo = BEFEHL  
vpravo = BEFEHL  
pismo = STYLE BEFEHL  
barva = COLOR

**\setupstretched** [...,<sup>\*</sup>...,...]

\* inherits: \setupcharacterkerning

**\setupstruts** [...]

\* ano ne auto kap<sup>OPT</sup>prizpusobive radek implicitni CHARACTER

**\setupstyle** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME OPT  
2 metoda = prikaz  
pismo = STYLE BEFEHL  
barva = COLOR

`\setupsubformula [...1,...] [...2,...]`

1 NAME OPT  
2 odsadpristi = ano ne auto

`\setupsubformulas [...1,...] [...2,...]`

1 NAME OPT  
2 inherits: \setupsubformula

`\setups {...,*,...}`

\* NAME

`\setupTABLE [...1,...] [...2,...] [...3,...]`

1 r c x y row column OPT prvni posledni start zahlavi kazdy liche sude jedna NUMBER -NUMBER  
2 prvni least kazdy dve liche sude NUMBER -NUMBER  
3 extras = BEFEHL  
vlevo = BEFEHL  
vpravo = BEFEHL  
barvahlavicky = COLOR  
stylhlavicky = STYLE BEFEHL  
vzdalenostlevehookraje = DIMENSION  
vzdalenostpravhookraje = DIMENSION  
vzdalenostsloupcu = DIMENSION  
maxsirka = DIMENSION  
setups = NAME  
sirkatextu = DIMENSION lokalne  
split = ano ne opakovat auto  
zahlavi = opakovat  
volba = natahnout tight  
pred = BEFEHL  
po = BEFEHL  
stejnastranka = pred po obe  
spaceinbetween = inherits: \preskoc  
splitoffset = DIMENSION  
aligncharacter = ano ne  
alignmentcharacter = TEXT number->TEXT text->TEXT  
vzdalenost = DIMENSION  
barva = COLOR  
pismo = math STYLE BEFEHL  
inherits: \nastavoramovani

`\setupTEXpage [...,*,...]`

\* inherits: \setupfittingpage

`\setuptabulation [...1,...] [...2,...]`

1 NAME OPT  
2 formatovat = TEMPLATE zadny  
pred = BEFEHL  
po = BEFEHL  
vzdalenost = male stredni velke zadny prazdny podlehloubky mizka DIMENSION  
zarovnani = vlevo nastred vpravo dimension  
linka = radek normalni  
barvalinky = COLOR  
tloustkalinky = DIMENSION  
zakladnifont = inherits: \nastavzakladnifont  
odsazovani = ano ne  
split = ano ne opakovat auto  
jednotka = DIMENSION  
marginalie = DIMENSION  
vnitrni = BEFEHL  
EQ = BEFEHL  
zahlavi = ano opakovat text  
ramecek = zap vyp  
titul = TEXT  
keeptogether = ano ne

`\setuptagging [...,*,...]`

\* status = start stop  
metoda = auto

**\setuptextbackground** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

```
1 NAME OPT
2 status = start stop
  misto = text odstavec zadny
  alternativa = NUMMER
  mp = NAME
  metoda = NAME
  pozadi = barevne
  barvapozadi = COLOR
  roh = pravouhly zaobleny
  uroven = NUMMER
  offsetpozadi = DIMENSION
  pred = BEFEHL
  po = BEFEHL
  zarovnani = inherits: \nastavzarovnani
  pomlcka = NUMMER
  polomer = DIMENSION
  ramecek = zap vyp
  barvaramecku = COLOR
  tloustkalinky = DIMENSION
  voffset = DIMENSION
  offsetramecku = DIMENSION
  levyoffset = ano ne standardni DIMENSION
  pravyoffset = ano ne standardni DIMENSION
  offsetvrsku = male stredni velke radek DIMENSION
  offsetspodku = male stredni velke radek DIMENSION
  pismo = STYLE BEFEHL
  barva = COLOR
```

**\setuptextflow** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

```
1 NAME OPT
2 sirka = DIMENSION
  pismo = STYLE BEFEHL
  barva = COLOR
```

**\setuptooltip** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

```
1 NAME OPT
2 misto = vlevo nastred vpravo
  inherits: \nastavoramovani
```

**\tooltip** [...,<sup>1</sup>...,...]{...<sup>2</sup>.}{...<sup>3</sup>.}

```
1 inherits: \setupOPTtooltip
2 TEXT
3 TEXT
```

**\setupunit** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

```
1 NAME OPT
2 metoda = 1 2 3 4 5 6
  language = SPRACHE
  alternativa = text matematika
  order = reverse normalni
  oddelovac = male stredni velke normalni zadny NAME
  mezera = male stredni velke normalni zadny NAME
  pismo = STYLE BEFEHL
  barva = COLOR
```

**\unit** {...}

\* CONTENT

**\setupuserpagenumber** [...,<sup>\*</sup>...,...]

```
* viewerprefix = TEXT
  status = start stop zadny drzet prazdne
  inherits: \setupcounter
```

**\setupversion** [...]

\* koncept soubor docasne finalni NAME

**\setupviewerlayer** [...,\*...,...]

\* titul = TEXT  
status = start stop  
export = ano ne  
tisknutelne = ano ne  
rozsah = lokalne globalne  
metoda = zadny prikaz

**\setupvspacing** [...,\*...,...]

\* inherits: \vspacing <sup>OPT</sup>

**\setupwithargument** {...<sup>1</sup>} {...<sup>2</sup>}

1 NAME  
2 CONTENT

**\setupwithargumentswapped** {...<sup>1</sup>} {...<sup>2</sup>}

1 CONTENT  
2 NAME

**\setupxml** [...,\*...,...]

\* implicitni = skryte zadny text  
compress = ano ne

**\setupxtable** [...,<sup>1</sup>...,...<sup>2</sup>...,...]

1 NAME <sup>OPT</sup>  
2 sirkatextu = DIMENSION lokalne  
zakladnifont = inherits: \nastavzakladnifont  
spaceinbetween = inherits: \preskoc  
volba = tight max natahnout sirka vyska fixne  
vyskatextu = DIMENSION  
maxsirka = DIMENSION  
vzdalenostsloupcu = DIMENSION  
vzdalenostlevehookraje = DIMENSION  
vzdalenostpravhookraje = DIMENSION  
zahlavi = opakovat  
upati = opakovat  
tloustkalinky = DIMENSION  
split = ano ne opakovat auto  
splitoffset = DIMENSION  
stejnastranka = pred po obe  
vzdalenost = DIMENSION  
inherits: \nastavoramovani

**\setuvalue** {...<sup>1</sup>} {...<sup>2</sup>}

1 NAME  
2 CONTENT

**\setuxvalue** {...<sup>1</sup>} {...<sup>2</sup>}

1 NAME  
2 CONTENT

**\setvalue** {...<sup>1</sup>} {...<sup>2</sup>}

1 NAME  
2 CONTENT

**\setvariable** {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

1 NAME  
2 KEY  
3 VALUE

**\setvariables** [...<sup>1</sup>] [...,<sup>2</sup>...,...]

1 NAME  
2 set = BEFEHL  
reset = BEFEHL  
KEY = VALUE

<code>\setvboxregister ...<sup>1</sup> {<sup>2</sup>...}</code> 1 CSNAME NUMBER 2 CONTENT
<code>\setvisualizerfont [<sup>*</sup>...]</code> * FONT OPT
<code>\setvtopregister ...<sup>1</sup> {<sup>2</sup>...}</code> 1 CSNAME NUMBER 2 CONTENT
<code>\setwidthof ...<sup>1</sup> \to \to<sup>2</sup>...</code> 1 TEXT 2 CSNAME
<code>\setxmeasure {<sup>1</sup>...} {<sup>2</sup>...}</code> 1 NAME 2 DIMENSION
<code>\setxvalue {<sup>1</sup>...} {<sup>2</sup>...}</code> 1 NAME 2 CONTENT
<code>\setxvariable {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...}</code> 1 NAME 2 KEY 3 VALUE
<code>\setxvariables [<sup>1</sup>...] [...,<sup>2</sup>...,...]</code> 1 NAME 2 set = BEFEHL reset = BEFEHL KEY = VALUE
<code>\shapedhbox {<sup>*</sup>...}</code> * CONTENT
<code>\SHIFT {<sup>*</sup>...}</code> * CONTENT instances: shiftup shiftdown
<code>\showallmakeup</code>
<code>\showattributes</code>
<code>\showboxes</code>
<code>\showbtxdatasetauthors [...,<sup>*</sup>...,...]</code> * specification = NAME OPT dataset = NAME field = address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME
<code>\showbtxdatasetauthors [<sup>*</sup>...]</code> * NAME OPT

<pre> \showbtxdatasetcompleteness [...,.*,...] *  specification = NAME          OPT    dataset       = NAME    field         = address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution                   journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher                   school series titul opis volume rok yearfiled NAME </pre>
<pre> \showbtxdatasetcompleteness [...] *  NAME          OPT </pre>
<pre> \showbtxdatasetfields [...,.*,...] *  specification = NAME          OPT    dataset       = NAME    field         = address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution                   journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher                   school series titul opis volume rok yearfiled NAME </pre>
<pre> \showbtxdatasetfields [...] *  NAME          OPT </pre>
<pre> \showbtxfields [...,.*,...] *  rotace        = NUMMER<sup>OPT</sup>    specification = NAME </pre>
<pre> \showbtxfields [...] *  NAME          OPT </pre>
<pre> \showbtxhashedauthors [...] *  TEXT          OPT </pre>
<pre> \showbtxtables [...] *  TEXT          OPT </pre>
<pre> \showcolorbar [...] *  COLOR </pre>
<pre> \showcolorcomponents [...] *  COLOR </pre>
<pre> \showcolorset [...] *  COLOR </pre>
<pre> \showcolorstruts </pre>
<pre> \showcounter [...] *  NAME </pre>
<pre> \showdirectives </pre>
<pre> \showdirlsinmargin </pre>
<pre> \showedebuginfo </pre>
<pre> \showexperiments </pre>
<pre> \showfont [...<sup>1</sup>] [...,<sup>2</sup>...] 1  FONT          OPT 2  NUMMER </pre>

<code>\showfontdata</code>
<code>\showfontitalics</code>
<code>\showfontkerns</code>
<code>\showfontparameters</code>
<code>\showfontstrip [...,*,...]</code> <code>* inherits: \nastavzakladnifont</code>
<code>\showfontstyle [...,<sup>1</sup>...] [...,<sup>2</sup>...] [...,<sup>3</sup>...] [...,<sup>4</sup>...]</code> <code>1 inherits: \nastavzakladnifont OPT OPT OPT</code> <code>2 rm ss tt mm hw cg</code> <code>3 tf bf it sl bi bs</code> <code>4 vse NUMMER</code>
<code>\showglyphs</code>
<code>\showgridsnapping</code>
<code>\showhelp {...} [...]</code> <code>1 TEXT</code> <code>2 REFERENCE</code>
<code>\showhyphenationtrace [...]<sup>1</sup> [...]<sup>2</sup></code> <code>1 SPRACHE OPT</code> <code>2 TEXT</code>
<code>\showhyphens {...}</code> <code>* TEXT</code>
<code>\showchardata {...}</code> <code>* TEXT</code>
<code>\showcharratio {...}</code> <code>* TEXT</code>
<code>\showinjector [...,*,...]</code> <code>* NAME OPT</code>
<code>\showjustification</code>
<code>\showkerning {...}</code> <code>* TEXT</code>
<code>\showlayoutcomponents</code>
<code>\showligature {...}</code> <code>* TEXT</code>
<code>\showligatures [...]</code> <code>* FONT</code>
<code>\showlogcategories</code>

<code>\showmargins</code>
<code>\showmessage {<sup>1</sup>.} {<sup>2</sup>.} {<sup>3</sup>.,...}</code> 1 NAME 2 NAME NUMBER 3 TEXT
<code>\showminimalbaseline</code>
<code>\shownextbox \<sup>1</sup>. {<sup>2</sup>.}</code> 1 CSNAME 2 CONTENT
<code>\showotfcomposition {<sup>1</sup>.} {<sup>2</sup>.} {<sup>3</sup>.}</code> 1 FONT 2 -1 1 +1 l2r r2l 3 TEXT
<code>\showparentchain \<sup>1</sup>. {<sup>2</sup>.}</code> 1 CSNAME 2 NAME
<code>\showsetupsdefinition [<sup>*</sup>.]</code> * NAME
<code>\showtimer {<sup>*</sup>.}</code> * TEXT
<code>\showtokens [<sup>*</sup>.]</code> * NAME
<code>\showtrackers</code>
<code>\showvalue {<sup>*</sup>.}</code> * NAME
<code>\showvariable {<sup>1</sup>.} {<sup>2</sup>.}</code> 1 NAME 2 KEY
<code>\showwarning {<sup>1</sup>.} {<sup>2</sup>.} {<sup>3</sup>.,...}</code> 1 NAME 2 NAME NUMBER 3 TEXT
<code>\schovejbloky [...,<sup>1</sup>...] [...,<sup>2</sup>...]</code> 1 NAME 2 NAME <small>OPT</small>
<code>\simplealignedbox {<sup>1</sup>.} {<sup>2</sup>.} {<sup>3</sup>.}</code> 1 DIMENSION 2 vlevo vpravo nastred flushleft flushright uvnitr vnejsi 3 CONTENT
<code>\simplealignedboxplus {<sup>1</sup>.} {<sup>2</sup>.} {<sup>3</sup>.} {<sup>4</sup>.}</code> 1 DIMENSION 2 vlevo vpravo nastred flushleft flushright uvnitr vnejsi 3 TEXT 4 CONTENT



`\simplealignedspreadbox {1...} {2...} {3...}`

1 DIMENSION  
2 vlevo vpravo nastred flushleft flushright uvnitr vnejsi  
3 CONTENT

`\simplegroupedcommand {1...} {2...}`

1 BEFEHL  
2 BEFEHL

`\simplereversealignedbox {1...} {2...} {3...}`

1 DIMENSION  
2 vlevo vpravo nastred flushleft flushright uvnitr vnejsi  
3 CONTENT

`\simplereversealignedboxplus {1...} {2...} {3...} {4...}`

1 DIMENSION  
2 vlevo vpravo nastred flushleft flushright uvnitr vnejsi  
3 TEXT  
4 CONTENT

`\singalcharacteralign {1...} {2...}`

1 NUMMER  
2 NUMMER

`\singlebond`

`\sixthofsixarguments {1...} {2...} {3...} {4...} {5...} {6...}`

1 TEXT  
2 TEXT  
3 TEXT  
4 TEXT  
5 TEXT  
6 TEXT

`\sklonene`

`\sklonenetucne`

`\slantedface`

`\slicepages [1...] [...,2...,...] [...,3...,...]`

1 FILE OPT OPT  
2 offset = DIMENSION  
hoffset = DIMENSION  
voffset = DIMENSION  
sirka = DIMENSION  
vyska = DIMENSION  
n = NUMMER  
3 offset = DIMENSION  
hoffset = DIMENSION  
voffset = DIMENSION  
sirka = DIMENSION  
vyska = DIMENSION  
n = NUMMER

`\sloupec [...,*...]`

\* inherits: \columnbreak

`\slovenianNumerals {.*...}`

\* NUMMER

`\sloveniannumerals {.*...}`

\* NUMMER

<code>\slovo {...}</code> * TEXT
<code>\slovovpravo [...] {...}</code> 1 vpravo DIMENSION <sup>PT</sup> 2 CONTENT
<code>\smallbodyfont</code>
<code>\smallcappedcharacters {...}</code> * NUMMER
<code>\smallcappedromannumerals {...}</code> * NUMMER
<code>\smaller</code>
<code>\smallskip</code>
<code>\smash [...] {...}</code> 1 w h d t <sup>OPT</sup> 2 CONTENT
<code>\smashbox ...</code> * CSNAME NUMMER
<code>\smashboxed ...</code> * CSNAME NUMMER
<code>\smashedhbox ... {...}</code> 1 TEXT <sup>OPT</sup> 2 CONTENT
<code>\smashedvbox ... {...}</code> 1 TEXT <sup>OPT</sup> 2 CONTENT
<code>\snaptogrid [...] \^... {...}</code> 1 normalni standardni ano striktni tolerantni vrsek spodek obe široky prizpusobive prvni posledni vysoko jedna nizko zadny radek strut box min max nastred NAME 2 CSNAME 3 CONTENT
<code>\snaptogrid [...<sup>1</sup>,...] \^... {...}</code> 1 inherits: \definegridsnapping <sup>OPT</sup> 2 CSNAME 3 CONTENT
<code>\someheadnumber [...] [...]</code> 1 ABSCHNITT 2 predchozi aktualni dalsi prvni posledni
<code>\somekindoftab [...,<sup>*</sup>...,...]</code> * alternativa = horizont <sup>OPT</sup> alne vertikalne sirka = DIMENSION vyska = DIMENSION n = NUMMER m = NUMMER
<code>\somalocalfloat</code>

<p><code>\somenamedheadnumber {...} {...}</code></p> <p>1    ABSCHNITT</p> <p>2    predchozi aktualni dalsi prvni posledni</p>
<p><code>\someplace {...} {...} {...} {...} {...} [...]</code></p> <p>1    TEXT</p> <p>2    TEXT</p> <p>3    TEXT</p> <p>4    TEXT</p> <p>5    TEXT</p> <p>6    REFERENCE</p>
<p><code>\SORTING [...] {...}</code></p> <p>1    NAME            OPT</p> <p>2    CONTENT</p> <p>instances: logo</p>
<p><code>\spanishNumerals {...}</code></p> <p>*    NUMMER</p>
<p><code>\spanishnumerals {...}</code></p> <p>*    NUMMER</p>
<p><code>\splitatasterisk ... \... \...</code></p> <p>1    TEXT</p> <p>2    CSNAME</p> <p>3    CSNAME</p>
<p><code>\splitatcolon ... \... \...</code></p> <p>1    TEXT</p> <p>2    CSNAME</p> <p>3    CSNAME</p>
<p><code>\splitatcolons ... \... \...</code></p> <p>1    TEXT</p> <p>2    CSNAME</p> <p>3    CSNAME</p>
<p><code>\splitatcomma ... \... \...</code></p> <p>1    TEXT</p> <p>2    CSNAME</p> <p>3    CSNAME</p>
<p><code>\splitatperiod ... \... \...</code></p> <p>1    TEXT</p> <p>2    CSNAME</p> <p>3    CSNAME</p>
<p><code>\splitdfrac {...} {...}</code></p> <p>1    CONTENT</p> <p>2    CONTENT</p>
<p><code>\splitfilename {...}</code></p> <p>*    FILE</p>
<p><code>\splitfrac {...} {...}</code></p> <p>1    CONTENT</p> <p>2    CONTENT</p>
<p><code>\splitoffbase</code></p>
<p><code>\splitofffull</code></p>

<code>\splitoffkind</code>
<code>\splitoffname</code>
<code>\splitoffpath</code>
<code>\splitoffroot</code>
<code>\splitofftokens</code> <sup>1</sup> ... \from <sup>2</sup> ... \to \ <sup>3</sup> ... 1 TEXT 2 TEXT 3 CSNAME
<code>\splitofftype</code>
<code>\splitstring</code> <sup>1</sup> ... \at <sup>2</sup> ... \to \ <sup>3</sup> ... \and \ <sup>4</sup> ... 1 TEXT 2 TEXT 3 CSNAME 4 CSNAME
<code>\spreadhbox</code> <sup>*</sup> ... <sup>*</sup> CSNAME NUMBER
<code>\sqrt</code> [ <sup>1</sup> ...] { <sup>2</sup> ...} 1 TEXT <sup>OPT</sup> 2 CONTENT
<code>\stackrel</code> { <sup>1</sup> ...} { <sup>2</sup> ...} 1 CONTENT 2 CONTENT
<code>\stanovcislodonadpisu</code> [ <sup>*</sup> ...] <sup>*</sup> ABSCHNITT
<code>\stanovcharakteristickuseznamu</code> [..., <sup>1</sup> ...] [..., <sup>2</sup> ...] 1 LISTE <sup>OPT</sup> 2 inherits: \nastavseznam
<code>\startalignment</code> [..., <sup>*</sup> ...] ... \stopalignment <sup>*</sup> inherits: \nastavzarovnani
<code>\startallmodes</code> [..., <sup>*</sup> ...] ... \stopallmodes <sup>*</sup> NAME
<code>\startATTACHMENT</code> [ <sup>1</sup> ...] [..., <sup>2</sup> ...] 1 NAME <sup>OPT</sup> <sup>OPT</sup> 2 inherits: \setupattachment instances: attachment
<code>\startattachment</code> [ <sup>1</sup> ...] [..., <sup>2</sup> ...] 1 NAME <sup>OPT</sup> <sup>OPT</sup> 2 inherits: \setupattachment
<code>\startbar</code> [ <sup>*</sup> ...] ... \stopbar <sup>*</sup> NAME

<pre> \startbarva [...] ... \stopbarva *   COLOR </pre>
<pre> \startbitmapimage [...,.*=...,...] ... \stopbitmapimage *   barva = rgb cmyk seda     sirka = DIMENSION     vyska = DIMENSION     x     = NUMBER     y     = NUMBER </pre>
<pre> \startbtxrenderingdefinitions [...] ... \stopbtxrenderingdefinitions *   NAME </pre>
<pre> \startbuffer [...] ... \stopbuffer *   NAME          OPT </pre>
<pre> \startBUFFER ... \stopBUFFER instances: hiding </pre>
<pre> \startcatcodetable \*... ... \stopcatcodetable *   CSNAME </pre>
<pre> \startcenteraligned ... \stopcenteraligned </pre>
<pre> \startcollect ... \stopcollect </pre>
<pre> \startcollecting ... \stopcollecting </pre>
<pre> \startcolorintent [...] ... \stopcolorintent *   knockout overprint zadny </pre>
<pre> \startcoloronly [...] ... \stopcoloronly *   COLOR </pre>
<pre> \startcolorset [...] ... \stopcolorset *   NAME </pre>
<pre> \startcolumnspan [...,.*=...,...] ... \stopcolumnspan *   inherits: \setupcolumnspan<sup>PT</sup> </pre>
<pre> \startcombination [...<sup>1</sup>] [...,.*<sup>2</sup>=...,...] ... \stopcombination 1   NAME          OPT          OPT 2   inherits: \setupcombination </pre>
<pre> \startcombination [...<sup>1</sup>] [...<sup>2</sup>] ... \stopcombination 1   NAME          OPT          OPT 2   N*M </pre>
<pre> \startcontextcode ... \stopcontextcode </pre>
<pre> \startcontextdefinitioncode ... \stopcontextdefinitioncode </pre>
<pre> \startbtxlabeltext [...<sup>1</sup>] [...<sup>2</sup>] ... \stopbtxlabeltext 1   SPRACHE          OPT 2   KEY </pre>

`\startheadtext [...]1 [...]2 ... \stoptheadtext`

1 SPRACHE

OPT

2 KEY

`\startlabeltext [...]1 [...]2 ... \stoplabeltext`

1 SPRACHE

OPT

2 KEY

`\startmathlabeltext [...]1 [...]2 ... \stopmathlabeltext`

1 SPRACHE

OPT

2 KEY

`\startoperatortext [...]1 [...]2 ... \stopoperatortext`

1 SPRACHE

OPT

2 KEY

`\startprefixtext [...]1 [...]2 ... \stopprefixtext`

1 SPRACHE

OPT

2 KEY

`\startsuffixtext [...]1 [...]2 ... \stopsuffixtext`

1 SPRACHE

OPT

2 KEY

`\starttaglabeltext [...]1 [...]2 ... \stoptaglabeltext`

1 SPRACHE

OPT

2 KEY

`\startunittext [...]1 [...]2 ... \stopunittext`

1 SPRACHE

OPT

2 KEY

`\startctxfunction ... \stopctxfunction`

\* NAME

`\startctxfunctiondefinition ... \stopctxfunctiondefinition`

\* NAME

`\startcurrentcolor ... \stopcurrentcolor`

`\startcurrentlistentrywrapper ... \stopcurrentlistentrywrapper`

`\startdelimited [...]1 [...]2 [...]3,... \stopdelimited`

1 NAME

OPT

OPT

2 SPRACHE

3 inherits: \startzuzeni

`\startdelimitedtext [...]1 [...]2 [...]3,... \stopdelimitedtext`

1 NAME

OPT

OPT

2 SPRACHE

3 inherits: \startzuzeni

`\startDELIMITEDTEXT [...]1 [...]2,... \stopDELIMITEDTEXT`

1 SPRACHE

OPT

OPT

2 inherits: \startzuzeni

instances: quotation quote blockquote speech aside

`\startaside [...]1 [...]2,... \stopaside`

1 SPRACHE

OPT

OPT

2 inherits: \startzuzeni

$\backslash\text{startblockquote}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...,...] ... $\backslash\text{stopblockquote}$ 1 SPRACHE OPT OPT 2 inherits: $\backslash\text{startzuzeni}$
$\backslash\text{startquotation}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...,...] ... $\backslash\text{stopquotation}$ 1 SPRACHE OPT OPT 2 inherits: $\backslash\text{startzuzeni}$
$\backslash\text{startquote}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...,...] ... $\backslash\text{stopquote}$ 1 SPRACHE OPT OPT 2 inherits: $\backslash\text{startzuzeni}$
$\backslash\text{startspeech}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...,...] ... $\backslash\text{stopspeech}$ 1 SPRACHE OPT OPT 2 inherits: $\backslash\text{startzuzeni}$
$\backslash\text{startdisplaymath}$ ... $\backslash\text{stopdisplaymath}$
$\backslash\text{startdmath}$ ... $\backslash\text{stopdmath}$
$\backslash\text{startdocument}$ [... <sup>*</sup> ...,...] ... $\backslash\text{stopdocument}$ * inherits: $\backslash\text{setupdocument}$ <sup>OPT</sup>
$\backslash\text{starteffect}$ [... <sup>*</sup> ] ... $\backslash\text{stopeffect}$ * NAME
$\backslash\text{startEFFECT}$ ... $\backslash\text{stopEFFECT}$
$\backslash\text{startelement}$ { <sup>1</sup> ...} [... <sup>2</sup> ...,...] ... $\backslash\stopelement$ 1 NAME OPT 2 KEY = VALUE
$\backslash\text{startembeddedxtable}$ [... <sup>*</sup> ...,...] ... $\backslash\text{stopembeddedxtable}$ * inherits: $\backslash\text{setupxtable}$ OPT
$\backslash\text{startembeddedxtable}$ [... <sup>*</sup> ] ... $\backslash\text{stopembeddedxtable}$ * NAME OPT
$\backslash\text{startexceptions}$ [... <sup>*</sup> ] ... $\backslash\text{stopexceptions}$ * SPRACHE
$\backslash\text{startexpanded}$ ... $\backslash\text{stopexpanded}$
$\backslash\text{startexpandedcollect}$ ... $\backslash\text{stopexpandedcollect}$
$\backslash\text{startextendedcatcodetable}$ \... ... $\backslash\text{stopextendedcatcodetable}$ * CSNAME
$\backslash\text{startexternalfigurecollection}$ [... <sup>*</sup> ] ... $\backslash\text{stopexternalfigurecollection}$ * NAME
$\backslash\text{startfittingpage}$ [ <sup>1</sup> ...] [... <sup>2</sup> ...,...] ... $\backslash\text{stopfittingpage}$ 1 NAME OPT 2 inherits: $\backslash\text{setupfittingpage}$

<pre> \startFITTINGPAGE [...,*=...,...] ... \stopFITTINGPAGE * inherits: \setupfittingpage<sup>OPT</sup> instances: TEXpage MPpage </pre>
<pre> \startMPpage [...,*=...,...] ... \stopMPpage * inherits: \setupfittingpage<sup>OPT</sup> </pre>
<pre> \startTEXpage [...,*=...,...] ... \stopTEXpage * inherits: \setupfittingpage<sup>OPT</sup> </pre>
<pre> \startfixne [...*] ... \stopfixne * nizko nastred <sup>OPT</sup>vysoko nivy implicitni </pre>
<pre> \startfloatcombination [...,*=...,...] ... \stopfloatcombination * inherits: \setupcombination<sup>OPT</sup> </pre>
<pre> \startfloatcombination [...*] ... \stopfloatcombination * N*M NAME<sup>OPT</sup> </pre>
<pre> \startFLOATtext [...,<sup>1</sup>...,...] [...,<sup>2</sup>...,...] {...<sup>3</sup>} ... \stopFLOATtext 1 split vzdy vlevo vpravo<sup>OPT</sup> uvnitr vnejsi<sup>OPT</sup> zpetnamezera cutspace ivlevo ivpravo naokraji lev yokraj prav yokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective zahlavi upati 2 REFERENCE 3 TEXT instances: chemical figure table intermezzo graphic </pre>
<pre> \startfont [...*] ... \stopfont * FONT<sup>OPT</sup> </pre>
<pre> \startfontclass [...*] ... \stopfontclass * kazdy NAME </pre>
<pre> \startfontsolution [...*] ... \stopfontsolution * NAME </pre>
<pre> \startframedcontent [...*] ... \stopframedcontent * NAME vyp<sup>OPT</sup> </pre>
<pre> \startgridsnapping [...*] ... \stopgridsnapping * normalni standardni and<sup>OPT</sup>striktni tolerantni vrsek spodek obe siroky prizpusobive prvni posledni vysoko jedna nizko zadny radek strut box min max nastred NAME </pre>
<pre> \startgridsnapping [...,*=...,...] ... \stopgridsnapping * inherits: \definegridsnapping<sup>OPT</sup> </pre>
<pre> \starthboxestohbox ... \stophboxestohbox </pre>
<pre> \starthboxregister ...* ... \stophboxregister * CSNAME NUMBER </pre>
<pre> \startHELP [...*] ... \stopHELP * REFERENCE<sup>OPT</sup> instances: helptext </pre>
<pre> \starthelptext [...*] ... \stophelptext * REFERENCE<sup>OPT</sup> </pre>



<code>\starthighlight [...]</code> ... <code>\stophighlight</code> *    NAME
<code>\starthyphenation [...;...]</code> ... <code>\stophyphenation</code> *    original tex implicitni hyphenate expanded traditional zadny
<code>\startcharacteralign [...]</code> ... <code>\stopcharacteralign</code> *    TEXT number->TEXT text->TEXT
<code>\startcheckedfences ... \stopcheckedfences</code>
<code>\startchemical [...]</code> <sup>1</sup> <code>[...]</code> <sup>2</sup> <code>[...]</code> ... <code>\stopchemical</code> 1    NAME                    OPT                    OPT 2    inherits: \setupchemical
<code>\startimath ... \stopimath</code>
<code>\startindentedtext [...]</code> ... <code>\stopindentedtext</code> *    NAME
<code>\startINDENTEDTEXT ... \stopINDENTEDTEXT</code>
<code>\starthiding ... \stophiding</code>
<code>\startinterakce [...]</code> ... <code>\stopinterakce</code> *    skryte NAME
<code>\startinteraktivnimenu [...]</code> ... <code>\stopinteraktivnimenu</code> *    NAME
<code>\startinterface ... \stopinterface</code> *    vse SPRACHE
<code>\startintertext ... \stopintertext</code>
<code>\startitemgroup [...]</code> <sup>1</sup> <code>[...]</code> <sup>2</sup> <code>[...]</code> <sup>3</sup> <code>[...]</code> ... <code>\stopitemgroup</code> 1    NAME                    OPT                    OPT 2    inherits: \setupitemgroup 3    inherits: \setupitemgroup
<code>\startITEMGROUP [...]</code> <sup>1</sup> <code>[...]</code> <sup>2</sup> <code>[...]</code> ... <code>\stopITEMGROUP</code> 1    inherits: \setupitemgroup 2    inherits: \setupitemgroup <b>instances: itemize</b>
<code>\startJScode ... \stopJScode</code> <sup>1</sup> <sup>2</sup> <sup>3</sup> 1    NAME 2    uses 3    NAME
<code>\startJSreamble ... \stopJSreamble</code> <sup>1</sup> <sup>2</sup> <sup>3</sup> 1    NAME 2    uzito 3    now later
<code>\startjdina [...]</code> ... <code>\stopjdina</code> *    REFERENCE

<pre> \startknockout ... \stopknockout </pre>
<pre> \startkomentarstranky ... \stopkomentarstranky </pre>
<pre> \startCOMMENT [<sup>1</sup>...] [...,<sup>2</sup>...,...] ... \stopCOMMENT 1  TEXT                OPT                OPT 2  inherits: \nastavkomentar instances: comment </pre>
<pre> \startcomment [<sup>1</sup>...] [...,<sup>2</sup>...,...] ... \stopcomment 1  TEXT                OPT                OPT 2  inherits: \nastavkomentar </pre>
<pre> \startkomponenta [...] ... \stopkomponenta *  FILE * </pre>
<pre> \startkomponenta .* ... \stopkomponenta *  FILE * </pre>
<pre> \startkonektabulky [...] ... \stopkonektabulky *  NAME </pre>
<pre> \startlayout [...] ... \stoplayout *  NAME </pre>
<pre> \startlinealignment [...] ... \stoplinealignment *  vlevo nastred vpravo max </pre>
<pre> \startlinecorrection [...,*...] ... \stoplinecorrection *  prazdny inherits: \preskoc OPT </pre>
<pre> \startlinefiller [...] [...,<sup>2</sup>...,...] ... \stoplinefiller 1  filler NAME                OPT 2  inherits: \setuplinefiller </pre>
<pre> \startLINENOTE [...] {...<sup>2</sup>} 1  REFERENCE 2  TEXT instances: linenote </pre>
<pre> \stoplinenote [...] *  REFERENCE </pre>
<pre> \startlinenumbering [<sup>1</sup>...] [...,<sup>2</sup>...,...] ... \stoplinenumbering 1  NAME                OPT                OPT 2  pokračovat = ano ne    start      = NUMMER    krok       = NUMMER    metoda     = stranka prvni dalsi </pre>
<pre> \startlinenumbering [<sup>1</sup>...] [<sup>2</sup>...] ... \stoplinenumbering 1  NAME                OPT                OPT 2  pokračovat NUMMER </pre>
<pre> \startlinetable ... \stoplinetable </pre>
<pre> \startlinetablebody ... \stoplinetablebody </pre>

<code>\startlinetablecell [...,*,...] ... \stoplinetablecell</code> <code>* inherits: \setuplinetable      OPT</code>
<code>\startlinetablehead ... \stoplinetablehead</code>
<code>\startlocalfootnotes ... \stoplocalfootnotes</code>
<code>\startlocalheadsetup ... \stoplocalheadsetup</code>
<code>\startlocallinecorrection [...,*,...] ... \stoplocallinecorrection</code> <code>* prazdney inherits: \preskoc      OPT</code>
<code>\startlocalnotes [...,*,...] ... \stoplocalnotes</code> <code>* NAME</code>
<code>\startlocalsetups [...<sup>1</sup>] [...<sup>2</sup>] ... \stoplocalsetups</code> <code>1 mrizka      OPT</code> <code>2 NAME</code>
<code>\startlocalsetups .* ... \stoplocalsetups</code> <code>* NAME</code>
<code>\startlua ... \stoplua</code>
<code>\startluacode ... \stopluacode</code>
<code>\startluaparameterset [...] ... \stopluaparameterset</code> <code>* NAME</code>
<code>\startluasetups [...<sup>1</sup>] [...<sup>2</sup>] ... \stopluasetups</code> <code>1 mrizka      OPT</code> <code>2 NAME</code>
<code>\startluasetups .* ... \stopluasetups</code> <code>* NAME</code>
<code>\startMPclip {...} ... \stopMPclip</code> <code>* NAME</code>
<code>\startMPcode {...} ... \stopMPcode</code> <code>* NAME      OPT</code>
<code>\startMPdefinitions {...} ... \stopMPdefinitions</code> <code>* NAME      OPT</code>
<code>\startMPdrawing [...] ... \stopMPdrawing</code> <code>* -      OPT</code>
<code>\startMPenvironment [...] ... \stopMPenvironment</code> <code>* reset globalne +      OPT</code>
<code>\startMPextensions {...,*,...} ... \stopMPextensions</code> <code>* NAME      OPT</code>

$\backslash\text{startMPinclusions} [\overset{1}{...}] \{\overset{2}{...}\} ... \backslash\text{stopMPinclusions}$ 1 + OPT OPT 2 NAME
$\backslash\text{startMPinitializations} ... \backslash\text{stopMPinitializations}$
$\backslash\text{startMPpositiongraphic} \{\overset{1}{...}\} \{\overset{2}{...},...\} ... \backslash\text{stopMPpositiongraphic}$ 1 NAME OPT 2 KEY
$\backslash\text{startMPpositionmethod} \{...\} ... \backslash\text{stopMPpositionmethod}$ * NAME
$\backslash\text{startMPrun} \{...\} ... \backslash\text{stopMPrun}$ * NAME OPT
$\backslash\text{startmarginalnilinka} [\overset{*}{...}] ... \backslash\text{stopmarginalnilinka}$ * NUMMER OPT
$\backslash\text{startmarginalnilinka} [...,\overset{*}{...},...] ... \backslash\text{stopmarginalnilinka}$ * inherits: \setupmarginrule OPT
$\backslash\text{startmarginblock} [\overset{*}{...}] ... \backslash\text{stopmarginblock}$ * NAME OPT
$\backslash\text{startmarkedcontent} [\overset{*}{...}] ... \backslash\text{stopmarkedcontent}$ * reset vse NAME OPT
$\backslash\text{startMATHALIGNMENT} [...,\overset{*}{...},...] ... \backslash\text{stopMATHALIGNMENT}$ * inherits: \setupmathalignment <sup>OPT</sup> instances: align mathalignment
$\backslash\text{startMATHCASES} [...,\overset{*}{...},...] ... \backslash\text{stopMATHCASES}$ * inherits: \setupmathcases <sup>OPT</sup> instances: cases mathcases
$\backslash\text{startMATHMATRIX} [...,\overset{*}{...},...] ... \backslash\text{stopMATHMATRIX}$ * inherits: \setupmathmatrix <sup>OPT</sup> instances: matrix mathmatrix
$\backslash\text{startmathmode} ... \backslash\text{stopmathmode}$
$\backslash\text{startmathstyle} [...,\overset{*}{...}] ... \backslash\text{stopmathstyle}$ * obrazovka text script scriptscript cramped uncramped normalni zhustene male velke NAME
$\backslash\text{startmatrices} [...,\overset{*}{...},...] ... \backslash\text{stopmatrices}$ * inherits: \setupmathmatrix <sup>OPT</sup>
$\backslash\text{startmaxaligned} ... \backslash\text{stopmaxaligned}$
$\backslash\text{startmiddlealigned} ... \backslash\text{stopmiddlealigned}$
$\backslash\text{startmixedcolumns} [\overset{1}{...}] [...,\overset{2}{...},...] ... \backslash\text{stopmixedcolumns}$ 1 NAME OPT OPT 2 inherits: \setupmixedcolumns

<pre> \startMIXEDCOLUMNS [...,*...] ... \stopMIXEDCOLUMNS * inherits: \setupmixedcolumns<sup>OPT</sup> instances: itemgroupcolumns boxedcolumns </pre>
<pre> \startboxedcolumns [...,*...] ... \stopboxedcolumns * inherits: \setupmixedcolumns<sup>OPT</sup> </pre>
<pre> \startitemgroupcolumns [...,*...] ... \stopitemgroupcolumns * inherits: \setupmixedcolumns<sup>OPT</sup> </pre>
<pre> \startmode [...,*...] ... \stopmode * NAME </pre>
<pre> \startmodeset [...,<sup>1</sup>...] {<sup>2</sup>...} ... \stopmodeset 1 NAME implicitni 2 CONTENT </pre>
<pre> \startmodule [...] ... \stopmodule * FILE </pre>
<pre> \startmoduletestsection ... \stopmoduletestsection </pre>
<pre> \startmodule ...*... \stopmodule * FILE </pre>
<pre> \startnadpis [...,<sup>1</sup>...] {<sup>2</sup>...} ... \stopnadpis 1 REFERENCE<sup>OPT</sup> 2 TEXT </pre>
<pre> \startnamedsection [...<sup>1</sup>] [...,<sup>2</sup>...] [...,<sup>3</sup>...] ... \stopnamedsection 1 ABSCHNITT 2 titul = TEXT zalozka = TEXT znaceni = TEXT seznam = TEXT odkaz = REFERENCE vlastnicislo = TEXT 3 KEY = VALUE </pre>
<pre> \startnamedsubformulas [...,<sup>1</sup>...] {<sup>2</sup>...} ... \stopnamedsubformulas 1 + - REFERENCE<sup>OPT</sup> 2 TEXT </pre>
<pre> \startnaproti ... \stopnaproti </pre>
<pre> \startnarrower [...,*...] ... \stopnarrower * [-+]vlevo [-+]nastred<sup>OPT</sup>[-+]vpravo NUMMER*vlevo NUMMER*nastred NUMMER*vpravo reset </pre>
<pre> \startNARROWER [...,*...] ... \stopNARROWER * [-+]vlevo [-+]nastred<sup>OPT</sup>[-+]vpravo NUMMER*vlevo NUMMER*nastred NUMMER*vpravo reset </pre>
<pre> \startLUA [...,*...] ... \stopLUA * inherits: \nastav<sup>OPT</sup>opis </pre>
<pre> \startMP [...,*...] ... \stopMP * inherits: \nastav<sup>OPT</sup>opis </pre>
<pre> \startPARSEDXML [...,*...] ... \stopPARSEDXML * inherits: \nastav<sup>OPT</sup>opis </pre>

$\backslash startTEX$ [...] $\backslash stopTEX$ * inherits: $\backslash nastavopis$
$\backslash starttyping$ [...] $\backslash stoptyping$ * inherits: $\backslash nastavopis$
$\backslash startXML$ [...] $\backslash stopXML$ * inherits: $\backslash nastavopis$
$\backslash startlines$ [...] $\backslash stoplines$ * inherits: $\backslash nastavradky$
$\backslash startnegativ$ ... $\backslash stopnegativ$
$\backslash startnicelyfilledbox$ [...] $\backslash stopnicelyfilledbox$ * sirka = DIMENSION vyska = DIMENSION offset = DIMENSION strut = ano ne
$\backslash startnointerference$ ... $\backslash stopnointerference$
$\backslash startnotallmodes$ [...] $\backslash stopnotallmodes$ * NAME
$\backslash startnotext$ ... $\backslash stopnotext$
$\backslash startnotmode$ [...] $\backslash stopnotmode$ * NAME
$\backslash startobrazek$ [...] [...] [...] $\backslash stopobrazek$ 1 NAME 2 FILE 3 inherits: $\backslash externiobraz$
$\backslash startodlozit$ [...] $\backslash stopodlozit$ * [-+]NUMBER
$\backslash startodstavec$ [...] [...] $\backslash stopodstavec$ 1 NAME 2 inherits: $\backslash setupparagraph$
$\backslash startoramovani$ [...] [...] $\backslash stoporamovani$ 1 NAME 2 inherits: $\backslash nastavoramovani$
$\backslash startFRAMEDTEXT$ [...] [...] $\backslash stopFRAMEDTEXT$ 1 vlevo vpravo nastred 2 inherits: $\backslash setupframedtext$ instances: framedtext
$\backslash startframedtext$ [...] [...] $\backslash stopframedtext$ 1 vlevo vpravo nastred 2 inherits: $\backslash setupframedtext$
$\backslash startoutputstream$ [...] $\backslash stopoutputstream$ * NAME

\startoverprint ... \stopoverprint	
\startpagefigure [ <sup>1</sup> ...] [ <sub>...</sub> ... <sup>2</sup> ... <sub>...</sub> ] ... \stoppagefigure 1 FILE <small>OPT</small> 2 inherits: \setupexternalfigure	
\startpagegrid [ <sup>1</sup> ...] [ <sub>...</sub> ... <sup>2</sup> ... <sub>...</sub> ] ... \stoppagegrid 1 NAME <small>OPT</small> <small>OPT</small> 2 inherits: \setuppagegrid	
\startpagegridspan [ <sup>1</sup> ...] [ <sub>...</sub> ... <sup>2</sup> ... <sub>...</sub> ] ... \stoppagegridspan 1 NAME <small>OPT</small> 2 inherits: \setuppagegridspan	
\startPAGEGRID [ <sub>...</sub> ... <sup>*</sup> ... <sub>...</sub> ] ... \stopPAGEGRID * inherits: \setuppagegrid <sup>OPT</sup>	
\startpagelayout [...] * stranka levestranka pravastranka	
\startpar [ <sup>1</sup> ...] [ <sub>...</sub> ... <sup>2</sup> ... <sub>...</sub> ] ... \stoppar 1 NAME <small>OPT</small> <small>OPT</small> 2 inherits: \setupparagraph	
\startparagraphs [...] * NAME	
\startparagraphscell ... \stopparagraphscell	
\startPARAGRAPHS ... \stopPARAGRAPHS	
\startPARALLEL ... \stopPARALLEL	
\startparbuilder [...] * implicitni oneline basic NAME	
\startplacefloat [ <sup>1</sup> ...] [ <sub>...</sub> ... <sup>2</sup> ... <sub>...</sub> ] [ <sub>...</sub> ... <sup>3</sup> ... <sub>...</sub> ] ... \stopplacefloat 1 SINGULAR <small>OPT</small> <small>OPT</small> 2 <ul style="list-style-type: none"> <li>titul = TEXT</li> <li>zalozka = TEXT</li> <li>znaceni = TEXT</li> <li>seznam = TEXT</li> <li>misto = split vzdý vlevo vpravo uvnitř vnější zpětnamezera cutspace ivlevo ivpravo naokraj levýokraj pravýokraj              leváhrana praváhrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky              [-+]radek pulradku mřížka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie              [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levestranka pravastranka nekde              effective zahlavi upati</li> <li>odkaz = REFERENCE</li> </ul> 3 KEY = VALUE	
\startumistiFLOAT [ <sub>...</sub> ... <sup>1</sup> ... <sub>...</sub> ] [ <sub>...</sub> ... <sup>2</sup> ... <sub>...</sub> ] ... \stopumistiFLOAT 1 <ul style="list-style-type: none"> <li>titul = TEXT <small>OPT</small> <small>OPT</small></li> <li>zalozka = TEXT</li> <li>znaceni = TEXT</li> <li>seznam = TEXT</li> <li>misto = split vzdý vlevo vpravo uvnitř vnější zpětnamezera cutspace ivlevo ivpravo naokraj levýokraj pravýokraj              leváhrana praváhrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky              [-+]radek pulradku mřížka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie              [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levestranka pravastranka nekde              effective zahlavi upati</li> <li>odkaz = REFERENCE</li> </ul> 2 KEY = VALUE instances: chemical figure table intermezzo graphic	

```

\startumistifigure [...,\sfrac{1}{2}...,...] [...,\sfrac{2}{2}...,...] ... \stopumistifigure
1  titul    = TEXT
    zalozka = TEXT
    znaceni = TEXT
    seznam  = TEXT
    misto   = split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraj levokraj pravokraj
              levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky
              [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie
              [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde
              effective zahlavi upati
    odkaz   = REFERENCE
2  KEY = VALUE

```

```

\startumistigraphic [...,\sfrac{1}{2}...,...] [...,\sfrac{2}{2}...,...] ... \stopumistigraphic
1  titul    = TEXT
    zalozka = TEXT
    znaceni = TEXT
    seznam  = TEXT
    misto   = split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraj levokraj pravokraj
              levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky
              [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie
              [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde
              effective zahlavi upati
    odkaz   = REFERENCE
2  KEY = VALUE

```

```

\startumistichemical [...,\sfrac{1}{2}...,...] [...,\sfrac{2}{2}...,...] ... \stopumistichemical
1  titul    = TEXT
    zalozka = TEXT
    znaceni = TEXT
    seznam  = TEXT
    misto   = split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraj levokraj pravokraj
              levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky
              [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie
              [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde
              effective zahlavi upati
    odkaz   = REFERENCE
2  KEY = VALUE

```

```

\startumistiintermezzo [...,\sfrac{1}{2}...,...] [...,\sfrac{2}{2}...,...] ... \stopumistiintermezzo
1  titul    = TEXT
    zalozka = TEXT
    znaceni = TEXT
    seznam  = TEXT
    misto   = split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraj levokraj pravokraj
              levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky
              [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie
              [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde
              effective zahlavi upati
    odkaz   = REFERENCE
2  KEY = VALUE

```

```

\startumistitable [...,\sfrac{1}{2}...,...] [...,\sfrac{2}{2}...,...] ... \stopumistitable
1  titul    = TEXT
    zalozka = TEXT
    znaceni = TEXT
    seznam  = TEXT
    misto   = split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraj levokraj pravokraj
              levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky
              [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie
              [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde
              effective zahlavi upati
    odkaz   = REFERENCE
2  KEY = VALUE

```

```

\startplacepairedbox [...,\sfrac{1}{2}...,...] [...,\sfrac{2}{2}...,...] ... \stopplacepairedbox
1  NAME
2  inherits: \setuppairedbox

```

```

\startumistiPAIREDBOX [...,\sfrac{1}{2}...,...] ... \stopumistiPAIREDBOX
* inherits: \setuppairedbox
instances: legend

```



<code>\startumistilegend [...,*=,...] ... \stopumistilegend</code> <code>* inherits: \setuppairedbox OPT</code>
<code>\startpolozka [...,*=,...] ... \stoppolozka</code> <code>* REFERENCE OPT</code>
<code>\startPOPIS [...,*=,...] ... \stopPOPIS</code> <code>* titul = TEXT OPT</code> <code>zalozka = TEXT</code> <code>seznam = TEXT</code> <code>odkaz = REFERENCE</code>
<code>\startPOPIS [...,<sup>1</sup>,...] {...<sup>2</sup>} ... \stopPOPIS</code> <code>1 REFERENCE OPT OPT</code> <code>2 TEXT</code>
<code>\startpositioning [...,<sup>1</sup>] [...,<sup>2</sup>,...] ... \stoppositioning</code> <code>1 NAME OPT OPT</code> <code>2 inherits: \nastavumistovani</code>
<code>\startpositionoverlay {...} ... \stoppositionoverlay</code> <code>* NAME</code>
<code>\startpositiv ... \stoppositiv</code>
<code>\startpozadi [...,*=,...] ... \stoppozadi</code> <code>* inherits: \nastavpozadi OPT</code>
<code>\startPOZADI [...,*=,...] ... \stopPOZADI</code> <code>* inherits: \nastavpozadi OPT</code> <code>instances: pozadi</code>
<code>\startNOTE [...,*=,...] ... \stopNOTE</code> <code>* REFERENCE OPT</code> <code>instances: footnote endnote</code>
<code>\startNOTE [...,*=,...] ... \stopNOTE</code> <code>* titul = TEXT OPT</code> <code>zalozka = TEXT</code> <code>seznam = TEXT</code> <code>odkaz = REFERENCE</code> <code>instances: footnote endnote</code>
<code>\startendnote [...,*=,...] ... \stopendnote</code> <code>* REFERENCE OPT</code>
<code>\startfootnote [...,*=,...] ... \stopfootnote</code> <code>* REFERENCE OPT</code>
<code>\startprekryv ... \stopprekryv</code>
<code>\startprocessassignmentcommand [...,*=,...] ... \stopprocessassignmentcommand</code> <code>* KEY = VALUE</code>
<code>\startprocessassignmentlist [...,*=,...] ... \stopprocessassignmentlist</code> <code>* KEY = VALUE</code>
<code>\startprocesscommacommand [...,*=,...] ... \stopprocesscommacommand</code> <code>* BEFEHL</code>

<pre> \startprocesscommalist [...,*...] ... \stopprocesscommalist *   BEFEHL </pre>
<pre> \startprodukt [...] ... \stopprodukt *   FILE * </pre>
<pre> \startprodukt ... ... \stopprodukt *   FILE * </pre>
<pre> \startprojekt [...] ... \stopprojekt *   FILE * </pre>
<pre> \startprojekt ... ... \stopprojekt *   FILE * </pre>
<pre> \startprostredi [...] ... \stopprostredi *   FILE * </pre>
<pre> \startprostredi ... ... \stopprostredi *   FILE * </pre>
<pre> \startprotectedcolors ... \stopprotectedcolors </pre>
<pre> \startpublikace [...] [...] ... \stoppublikace 1  NAME              OPT          OPT 2  tag               = REFERENCE    category          = TEXT    k                  = REFERENCE    t                  = TEXT </pre>
<pre> \startradek [...] *   REFERENCE </pre>
<pre> \startLINES [...,*=...,...] ... \stopLINES *   inherits: \nastavradky instances: lines </pre>
<pre> \startrandomized ... \stoprandomized </pre>
<pre> \startrawsetups [...] [...] ... \stoprawsetups 1  mrizka            OPT 2  NAME </pre>
<pre> \startrawsetups ... ... \stoprawsetups *   NAME </pre>
<pre> \startreadingfile ... \stopreadingfile </pre>
<pre> \startregime [...] ... \stopregime *   inherits: \enableregime </pre>
<pre> \startregister [...] [...] [...] [...] [...] [...] 1  NAME              OPT          OPT 2  NAME 3  TEXT 4  TEXT PROCESSOR-&gt;TEXT 5  INDEX </pre>

<pre> \startreusableMPgraphic {...<sup>1</sup>} {...<sup>2</sup>,...} ... \stopreusableMPgraphic 1  NAME                                OPT 2  KEY </pre>
<pre> \startrovnice [...,*...] ... \stoprovnice *  zhustene tight nast<sup>OPT</sup>red ramecek inherits: \nastavzakladnifont </pre>
<pre> \startFORMULAformula [...,*...] ... \stopFORMULAformula *  zhustene tight nastred ramecek inherits: \nastavzakladnifont instances: sp sd mp md </pre>
<pre> \startrozbalene ... \stoprozbalene </pre>
<pre> \startscript [...] ... \stopscript *  hangul hanzi nihongo ethiopic thai test NAME </pre>
<pre> \startsectionblock [...<sup>1</sup>] [...<sup>2</sup>,...<sup>OPT</sup>] ... \stopsectionblock 1  NAME 2  zalozka = TEXT    inherits: \nastavbloksekce </pre>
<pre> \startsectionblockenvironment [...] ... \stopsectionblockenvironment *  NAME </pre>
<pre> \startSECTIONBLOCK [...<sup>*</sup>,...<sup>OPT</sup>] ... \stopSECTIONBLOCK *  zalozka = TEXT    inherits: \nastavbloksekce instances: frontmatter bodymatter appendices backmatter </pre>
<pre> \startappendices [...<sup>*</sup>,...<sup>OPT</sup>] ... \stopappendices *  zalozka = TEXT    inherits: \nastavbloksekce </pre>
<pre> \startbackmatter [...<sup>*</sup>,...<sup>OPT</sup>] ... \stopbackmatter *  zalozka = TEXT    inherits: \nastavbloksekce </pre>
<pre> \startbodymatter [...<sup>*</sup>,...<sup>OPT</sup>] ... \stopbodymatter *  zalozka = TEXT    inherits: \nastavbloksekce </pre>
<pre> \startfrontmatter [...<sup>*</sup>,...<sup>OPT</sup>] ... \stopfrontmatter *  zalozka = TEXT    inherits: \nastavbloksekce </pre>
<pre> \startsectionlevel [...<sup>1</sup>] [...<sup>2</sup>,...<sup>OPT</sup>] [...<sup>3</sup>,...<sup>OPT</sup>] ... \stopsectionlevel 1  NAME                                OPT      OPT      OPT 2  titul                               = TEXT    zalozka                             = TEXT    znaceni                             = TEXT    seznam                              = TEXT    odkaz                               = REFERENCE    vlastnicislo                        = TEXT 3  KEY = VALUE </pre>

```

\startSECTION [...1...2...] ... \stopSECTION
1  titul          = TEXTOPT
   zalozka       = TEXT
   znaceni       = TEXT
   seznam        = TEXT
   odkaz         = REFERENCE
   vlastnicislo  = TEXT
2  KEY = VALUE
instances: part chapter section subsection subsubsection subsubsubsection
title subject subsubject subsubsubject subsubsubsubject subsubsubsubsubject

```

```

\startchapter [...1...2...] ... \stopchapter
1  titul          = TEXTOPT
   zalozka       = TEXT
   znaceni       = TEXT
   seznam        = TEXT
   odkaz         = REFERENCE
   vlastnicislo  = TEXT
2  KEY = VALUE

```

```

\startpart [...1...2...] ... \stoppart
1  titul          = TEXTOPT
   zalozka       = TEXT
   znaceni       = TEXT
   seznam        = TEXT
   odkaz         = REFERENCE
   vlastnicislo  = TEXT
2  KEY = VALUE

```

```

\startsection [...1...2...] ... \stopsection
1  titul          = TEXTOPT
   zalozka       = TEXT
   znaceni       = TEXT
   seznam        = TEXT
   odkaz         = REFERENCE
   vlastnicislo  = TEXT
2  KEY = VALUE

```

```

\startsubject [...1...2...] ... \stopsubject
1  titul          = TEXTOPT
   zalozka       = TEXT
   znaceni       = TEXT
   seznam        = TEXT
   odkaz         = REFERENCE
   vlastnicislo  = TEXT
2  KEY = VALUE

```

```

\startsubsection [...1...2...] ... \stopsubsection
1  titul          = TEXTOPT
   zalozka       = TEXT
   znaceni       = TEXT
   seznam        = TEXT
   odkaz         = REFERENCE
   vlastnicislo  = TEXT
2  KEY = VALUE

```

```

\startsubsubject [...1...2...] ... \stopsubsubject
1  titul          = TEXTOPT
   zalozka       = TEXT
   znaceni       = TEXT
   seznam        = TEXT
   odkaz         = REFERENCE
   vlastnicislo  = TEXT
2  KEY = VALUE

```

`\startsubsubsection [...,\subsecnum{1}...] [...,\subsecnum{2}...] ... \stopsubsubsection`

1 titul = TEXT OPT OPT  
 zalozka = TEXT  
 znaceni = TEXT  
 seznam = TEXT  
 odkaz = REFERENCE  
 vlastnicislo = TEXT  
 2 KEY = VALUE

`\startsubsubsubject [...,\subsubsecnum{1}...] [...,\subsubsecnum{2}...] ... \stopsubsubsubject`

1 titul = TEXT OPT OPT  
 zalozka = TEXT  
 znaceni = TEXT  
 seznam = TEXT  
 odkaz = REFERENCE  
 vlastnicislo = TEXT  
 2 KEY = VALUE

`\startsubsubsubsection [...,\subsubsubsecnum{1}...] [...,\subsubsubsecnum{2}...] ... \stopsubsubsubsection`

1 titul = TEXT OPT OPT  
 zalozka = TEXT  
 znaceni = TEXT  
 seznam = TEXT  
 odkaz = REFERENCE  
 vlastnicislo = TEXT  
 2 KEY = VALUE

`\startsubsubsubsubject [...,\subsubsubsubsecnum{1}...] [...,\subsubsubsubsecnum{2}...] ... \stopsubsubsubsubject`

1 titul = TEXT OPT OPT  
 zalozka = TEXT  
 znaceni = TEXT  
 seznam = TEXT  
 odkaz = REFERENCE  
 vlastnicislo = TEXT  
 2 KEY = VALUE

`\startsubsubsubsubsection [...,\subsubsubsubsubsecnum{1}...] [...,\subsubsubsubsubsecnum{2}...] ... \stopsubsubsubsubsection`

1 titul = TEXT OPT OPT  
 zalozka = TEXT  
 znaceni = TEXT  
 seznam = TEXT  
 odkaz = REFERENCE  
 vlastnicislo = TEXT  
 2 KEY = VALUE

`\startsubsubsubsubsubject [...,\subsubsubsubsubsubsecnum{1}...] [...,\subsubsubsubsubsubsecnum{2}...] ... \stopsubsubsubsubsubject`

1 titul = TEXT OPT OPT  
 zalozka = TEXT  
 znaceni = TEXT  
 seznam = TEXT  
 odkaz = REFERENCE  
 vlastnicislo = TEXT  
 2 KEY = VALUE

`\starttitle [...,\subtitnum{1}...] [...,\subtitnum{2}...] ... \stoptitle`

1 titul = TEXT OPT  
 zalozka = TEXT  
 znaceni = TEXT  
 seznam = TEXT  
 odkaz = REFERENCE  
 vlastnicislo = TEXT  
 2 KEY = VALUE

`\startitemize [...,\subitemnum{1}...] [...,\subitemnum{2}...] ... \stopitemize`

1 inherits: \setupitemgroup OPT  
 2 inherits: \setupitemgroup

`\startalign [...,\subalignnum{1}...] ... \stopalign`

\* inherits: \setupmathalignment OPT

$\backslash startmathalignment [..., ...^* ..., ...] \dots \backslash stopmathalignment$ <p>* inherits: <math>\backslash setupmathalignment</math><sup>OPT</sup></p>
$\backslash startcases [..., ...^* ..., ...] \dots \backslash stopcases$ <p>* inherits: <math>\backslash setupmathcases</math></p>
$\backslash startmathcases [..., ...^* ..., ...] \dots \backslash stopmathcases$ <p>* inherits: <math>\backslash setupmathcases</math><sup>OPT</sup></p>
$\backslash startmathmatrix [..., ...^* ..., ...] \dots \backslash stopmathmatrix$ <p>* inherits: <math>\backslash setupmathmatrix</math><sup>OPT</sup></p>
$\backslash startmatrix [..., ...^* ..., ...] \dots \backslash stopmatrix$ <p>* inherits: <math>\backslash setupmathmatrix</math><sup>OPT</sup></p>
$\backslash startsetups [^1] [...] \dots \backslash stopsetups$ <p>1 mrizka<sup>OPT</sup> 2 NAME</p>
$\backslash startmdformula [..., ...^* ..., ...] \dots \backslash stopmdformula$ <p>* zhustene tight nastred<sup>OPT</sup>ramecek inherits: <math>\backslash nastavzakladnifont</math></p>
$\backslash startmpformula [..., ...^* ..., ...] \dots \backslash stopmpformula$ <p>* zhustene tight nastred<sup>OPT</sup>ramecek inherits: <math>\backslash nastavzakladnifont</math></p>
$\backslash startsdformula [..., ...^* ..., ...] \dots \backslash stopsdformula$ <p>* zhustene tight nastred<sup>OPT</sup>ramecek inherits: <math>\backslash nastavzakladnifont</math></p>
$\backslash startspformula [..., ...^* ..., ...] \dots \backslash stopspformula$ <p>* zhustene tight nastred<sup>OPT</sup>ramecek inherits: <math>\backslash nastavzakladnifont</math></p>
$\backslash startsetups \dots \dots \backslash stopsetups$ <p>* NAME</p>
$\backslash startshift [...] \dots \backslash stopshift$ <p>* NAME</p>
$\backslash startsidebar [^1] [...] \dots \backslash stopsidebar$ <p>1 NAME<sup>OPT</sup> 2 inherits: <math>\backslash setupsidebar</math><sup>OPT</sup></p>
$\backslash startsimplecolumns [..., ...^* ..., ...] \dots \backslash stopsimplecolumns$ <p>* inherits: <math>\backslash setsimplecolumnnsize</math><sup>OPT</sup></p>
$\backslash startsloupce [..., ...^* ..., ...] \dots \backslash stopsloupce$ <p>* inherits: <math>\backslash nastavsloupce</math><sup>OPT</sup></p>
$\backslash startspecialitem [^1] [...] \dots \backslash stopspecialitem$ <p>1 polozka<sup>OPT</sup> 2 REFERENCE<sup>OPT</sup></p>
$\backslash startspecialitem [...] \dots \backslash stopspecialitem$ <p>* pod pol</p>
$\backslash startspecialitem [^1] \{^2\} \dots \backslash stopspecialitem$ <p>1 sym rozsah mar 2 TEXT</p>

<code>\startspread ... \stopspread</code>
<code>\start [...] ... \stop</code> <code>* NAME OPT</code>
<code>\startSTARTSTOP ... \stopSTARTSTOP</code>
<code>\startstaticMPfigure {...} ... \stopstaticMPfigure</code> <code>* NAME</code>
<code>\startstaticMPgraphic {...} {...,<sup>2</sup>...} ... \stopstaticMPgraphic</code> <code>1 NAME OPT</code> <code>2 KEY</code>
<code>\STARTSTOP {...}</code> <code>* CONTENT</code>
<code>\startstrictinspectnextcharacter ... \stopstrictinspectnextcharacter</code>
<code>\startstructurepageregister [...]<sup>1</sup> [...]<sup>2</sup> [...,<sup>3</sup>...,...] [...,<sup>4</sup>...,...]</code> <code>1 NAME OPT</code> <code>2 NAME</code> <code>3 popisek = NAME</code> <code>keys = TEXT PROCESSOR-&gt;TEXT</code> <code>entries = TEXT PROCESSOR-&gt;TEXT</code> <code>keys:1 = TEXT</code> <code>keys:2 = TEXT</code> <code>keys:3 = TEXT</code> <code>entries:1 = TEXT</code> <code>entries:2 = TEXT</code> <code>entries:3 = TEXT</code> <code>alternativa = TEXT</code> <code>4 KEY = VALUE</code>
<code>\startstyle [...,<sup>*</sup>...,...] ... \stopstyle</code> <code>* inherits: \setupstyle</code>
<code>\startstyle [...] ... \stopstyle</code> <code>* NAME FONT</code>
<code>\startSTYLE ... \stopSTYLE</code>
<code>\startsubformulas [...,<sup>*</sup>...,...] ... \stopsubformulas</code> <code>* + - REFERENCE OPT</code>
<code>\startsubjectlevel [...]<sup>1</sup> [...,<sup>2</sup>...,...]<sup>2</sup> [...,<sup>3</sup>...,...]<sup>3</sup> ... \stopsubjectlevel</code> <code>1 NAME OPT OPT OPT</code> <code>2 titul = TEXT</code> <code>zalozka = TEXT</code> <code>znaceni = TEXT</code> <code>seznam = TEXT</code> <code>odkaz = REFERENCE</code> <code>vlastnicislo = TEXT</code> <code>3 KEY = VALUE</code>
<code>\startsubsentence ... \stopsubsentence</code>
<code>\startsubstack ... \stopsubstack</code>
<code>\startsymbolset [...] ... \stopsymbolset</code> <code>* NAME</code>

<pre> \startTABLE [...,..<sup>*</sup>...,...] ... \stopTABLE * inherits: \setupTABLE </pre>
<pre> \startTABLEbody [...,..<sup>*</sup>...,...] ... \stopTABLEbody * inherits: \setupTABLE OPT </pre>
<pre> \startTABLEfoot [...,..<sup>*</sup>...,...] ... \stopTABLEfoot * inherits: \setupTABLE OPT </pre>
<pre> \startTABLEhead [...,..<sup>*</sup>...,...] ... \stopTABLEhead * inherits: \setupTABLE OPT </pre>
<pre> \startTABLEnext [...,..<sup>*</sup>...,...] ... \stopTABLEnext * inherits: \setupTABLE OPT </pre>
<pre> \starttabelator [ . <sup>1</sup> . ] [...,..<sup>2</sup>...,...] ... \stoptabelator 1  TEMPLATE OPT OPT 2  inherits: \nastvtabelaci </pre>
<pre> \startTABULATE [ . <sup>1</sup> . ] [...,..<sup>2</sup>...,...] ... \stopTABULATE 1  NAME OPT OPT 2  inherits: \nastvtabelaci instances: legend fact </pre>
<pre> \startfact [ . <sup>1</sup> . ] [...,..<sup>2</sup>...,...] ... \stopfact 1  NAME OPT OPT 2  inherits: \nastvtabelaci </pre>
<pre> \startlegend [ . <sup>1</sup> . ] [...,..<sup>2</sup>...,...] ... \stoplegend 1  NAME OPT OPT 2  inherits: \nastvtabelaci </pre>
<pre> \starttabulatehead [...<sup>*</sup>.] ... \stoptabulatehead *  NAME OPT </pre>
<pre> \starttabulatetail [...<sup>*</sup>.] ... \stoptabulatetail *  NAME OPT </pre>
<pre> \startTABULATION [ . <sup>1</sup> . ] [...,..<sup>2</sup>...,...] ... \stopTABULATION 1  NAME OPT OPT 2  inherits: \setuptabulation </pre>
<pre> \starttabulka [ . <sup>1</sup> . ] [...,..<sup>2</sup>...,...] ... \stoptabulka 1  TEMPLATE OPT 2  inherits: \nastvtabulky </pre>
<pre> \starttabulka [ . <sup>1</sup> . ] [...,..<sup>2</sup>...,...] ... \stoptabulka 1  NAME OPT 2  inherits: \nastvtabulky </pre>
<pre> \starttabulky [ . <sup>*</sup> . ] ... \stoptabulky *  TEMPLATE </pre>
<pre> \starttabulky [...<sup>*</sup>.] ... \stoptabulky *  NAME </pre>
<pre> \starttexcode ... \stoptexcode </pre>



```

\starttexdefinition 1... 2... 3... 4... 5... 6... 7... \stoptexdefinition
1  spaces nospaces      OPT  OPT  OPT  OPT  OPT      OPT
2  globalne
3  unexpanded
4  expanded
5  singleempty doubleempty tripleempty quadrupleempty quintupleempty sextupleempty singleargument doubleargument
   tripleargument quadrupleargument quintupleargument sextupleargument
6  NAME
7  TEMPLATE

```

```

\starttext ... \stoptext

```

```

\starttextbackground [...1] [...2...] ... \stoptextbackground
1  NAME                                OPT
2  inherits: \setuptextbackground

```

```

\starttextbackgroundmanual ... \stoptextbackgroundmanual

```

```

\startTEXTBACKGROUND [...*...] ... \stopTEXTBACKGROUND
*  inherits: \setuptextbackgroundOPT

```

```

\starttextcolor [...] ... \stoptextcolor
*  COLOR

```

```

\starttextcolorintent ... \stoptextcolorintent

```

```

\starttextflow [...] ... \stoptextflow
*  NAME

```

```

\starttextnapovedy [...*] ... \stoptextnapovedy
*  REFERENCE      OPT

```

```

\starttextovalinka {...*} ... \stoptextovalinka
*  TEXT

```

```

\startLABELtext [...1] [...2] ... \stopLABELtext
1  SPRACHE      OPT
2  KEY
instances: head label mathlabel taglabel unit operator prefix suffix btxlabel

```

```

\starttokens [...] ... \stoptokens
*  NAME

```

```

\starttransparent [...] ... \stoptransparent
*  COLOR

```

```

\starttypescript [...1...] [...2...] [...3...] ... \stoptypescript
1  serif sans mono math handwriting calligraphy      OPT
2  NAME
3  size jmeno

```

```

\starttypescriptcollection [...] ... \stoptypescriptcollection
*  NAME

```

```

\startTYPING [...*...] ... \stopTYPING
*  inherits: \nastavopisPT
instances: typing LUA MP PARSEDXML TEX XML

```

`\startTYPING [...,*,...] ... \stopTYPING`

\* pokračovat OPT

instances: typing LUA MP PARSEDXML TEX XML

```
\startumistirovnici [.....*=.....] ... \stopumistirovnici
```

```
*   titul   = TEXT
```

```
suffix = TEXT
```

odkaz = + - REFERENCE

```
\startumistirovnici [...,*...] ... \stopumistirovnici
```

\* + - REFERENCE

$$\backslash\mathrm{startuniqueMPgraphic}\ \{...\}^1\ \{...\}^2\ \dots\ \backslash\mathrm{stopuniqueMPgraphic}$$

1 NAME

2 KEY

$$\backslash\mathrm{startuniqueMPpagegraphic} \{...\} \{...\} \dots \backslash\mathrm{stopuniqueMPpagegraphic}$$

1 NAME

2 KEY

`\startusableMPgraphic {...} {...} ... \stopusableMPgraphic`

1 NAME

2 KEY

$$\backslash\mathrm{startuseMPgraphic} \left\{ \begin{smallmatrix} 1 \\ \vdots \end{smallmatrix} \right\} \left\{ \begin{smallmatrix} 2 \\ \vdots \end{smallmatrix} \right\} \dots \backslash\mathrm{stopuseMPgraphic}$$

1 NAME

2 KEY

$$\backslash\mathrm{startusemathstyleparameter} \ \dots \ \dots \ \backslash\mathrm{stopusemathstyleparameter}$$

\* CSNAME

```
\startusingbtxspecification [...] ... \stopusingbtxspecification
```

\* NAME

$$\backslash \text{startuzky } [\dots] [\dots, \dots \overset{2}{=} \dots, \dots] \dots \backslash \text{stopuzky}$$

1 NAME

```
2 inherits: \nastavzuzeni
```

$$\backslash \text{startuzkv} \left[ \dots \overset{1}{=} \dots \right] \left[ \dots \overset{2}{=} \dots \right] \dots \backslash \text{stopuzkv}$$

```
1 inherits: \nastavzuzeniOPT
```

```
2  [-+]vlevo [-+]nastred [-+]vpravo NUMMER*vlevo NUMMER*nastred NUMMER*vpravo reset
```

$$\backslash \text{startuzky} \quad [ \dots ]^1 \quad [ \dots ]^2 \dots \backslash \text{stopuzky}$$

1 NAME

```
2  [-+]vlevo [-+]nastred [-+]vpravo NUMMER*vlevo NUMMER*nastred NUMMER*vpravo reset
```

```
\startvboxregister ... .. \stopvboxregister
```

\* CSNAME NUMMER

\startvboxtohbox ... \stopvboxtohbox

\startvboxtohboxseparator ... \stopvboxtohboxseparator

```
\startviewerlayer [...] ... \stopviewerlayer
```

\* NAME

```
\startVIEWERLAYER ... \stopVIEWERLAYER
```

```

\startvisici [...1...2...] {...} ... \stopvisici
1  vzdalenost = DIMENSION
   n          = NUMBER
   misto      = vlevo vpravo
2  CONTENT

```

```

\startvisici [...1] {...2} ... \stopvisici
1  vlevo vpravo OPT
2  CONTENT

```

```

\startvtopregister ... .. \stopvtopregister
*  CSNAME NUMBER

```

```

\startVYCET [...*...*...] ... \stopVYCET
*  titul      = TEXT OPT
   zalozka    = TEXT
   seznam     = TEXT
   odkaz      = REFERENCE

```

```

\startVYCET [...1...2...] {...} ... \stopVYCET
1  REFERENCE OPT OPT
2  TEXT

```

```

\startxcell [...1] [...2...2...] ... \stopxcell
1  NAME OPT OPT
2  nx = NUMBER
   ny = NUMBER
   nc = NUMBER
   nr = NUMBER
   inherits: \setupxtable

```

```

\startxcellgroup [...1] [...2...2...] ... \stopxcellgroup
1  NAME OPT OPT
2  inherits: \setupxtable

```

```

\startxgroup [...1] [...2...2...] ... \stopxgroup
1  NAME OPT OPT
2  inherits: \setupxtable

```

```

\startxmldisplayverbatim [...*] ... \stopxmldisplayverbatim
*  NAME

```

```

\startxmlinlineverbatim [...*] ... \stopxmlinlineverbatim
*  NAME

```

```

\startxmlraw ... \stopxmlraw

```

```

\startxmlsetups [...1] [...2] ... \stopxmlsetups
1  mrizka OPT
2  NAME

```

```

\startxmlsetups ... .. \stopxmlsetups
*  NAME

```

```

\startxrow [...1] [...2...2...] ... \stopxrow
1  NAME OPT OPT
2  inherits: \setupxtable

```

```

\startxrowgroup [...1] [...2...2...] ... \stopxrowgroup
1  NAME OPT OPT
2  inherits: \setupxtable

```

<code>\startxtable [...,..<sup>*</sup>...,...] ... \stopxtable</code> <code>* inherits: \setupxtable<sup>OPT</sup></code>
<code>\startxtablebody [...,..<sup>*</sup>...,...] ... \stopxtablebody</code> <code>* inherits: \setupxtable<sup>OPT</sup></code>
<code>\startxtablebody [...] ... \stopxtablebody</code> <code>* NAME<sup>OPT</sup></code>
<code>\startxtablefoot [...,..<sup>*</sup>...,...] ... \stopxtablefoot</code> <code>* inherits: \setupxtable<sup>OPT</sup></code>
<code>\startxtablefoot [...] ... \stopxtablefoot</code> <code>* NAME<sup>OPT</sup></code>
<code>\startxtablehead [...,..<sup>*</sup>...,...] ... \stopxtablehead</code> <code>* inherits: \setupxtable<sup>OPT</sup></code>
<code>\startxtablehead [...] ... \stopxtablehead</code> <code>* NAME<sup>OPT</sup></code>
<code>\startxtablenext [...,..<sup>*</sup>...,...] ... \stopxtablenext</code> <code>* inherits: \setupxtable<sup>OPT</sup></code>
<code>\startxtablenext [...] ... \stopxtablenext</code> <code>* NAME<sup>OPT</sup></code>
<code>\startXTABLE [...,..<sup>*</sup>...,...] ... \stopXTABLE</code> <code>* inherits: \setupxtable<sup>OPT</sup></code>
<code>\startxtable [...] ... \stopxtable</code> <code>* NAME<sup>OPT</sup></code>
<code>\startzahlavitabulky [...] ... \stopzahlavitabulky</code> <code>* NAME</code>
<code>\startzarovnanonastred ... \stopzarovnanonastred</code>
<code>\startzarovnanovlevo ... \stopzarovnanovlevo</code>
<code>\startzarovnanovpravo ... \stopzarovnanovpravo</code>
<code>\startzhustene [...] ... \stopzhustene</code> <code>* prazdny<sup>OPT</sup></code>
<code>\startzlom [<sup>1</sup>...] [...,..<sup>2</sup>...,...] ... \stopzlom</code> <code>1 NAME<sup>OPT</sup></code> <code>2 inherits: \nastavupravu</code>
<code>\startMAKEUPzlom [...,..<sup>*</sup>...,...] ... \stopMAKEUPzlom</code> <code>* inherits: \nastavupravu<sup>OPT</sup></code> <code>instances: standard page text middle</code>
<code>\startmiddlezlom [...,..<sup>*</sup>...,...] ... \stopmiddlezlom</code> <code>* inherits: \nastavupravu<sup>OPT</sup></code>

<code>\startpagezlom [...,.*,...] ... \stoppagezlom</code> <code>* inherits: \nastavupravu<sup>OPT</sup></code>
<code>\startstandardzlom [...,.*,...] ... \stopstandardzlom</code> <code>* inherits: \nastavupravu<sup>OPT</sup></code>
<code>\starttextzlom [...,.*,...] ... \stoptextzlom</code> <code>* inherits: \nastavupravu<sup>OPT</sup></code>
<code>\stopLINENOTE [...]</code> <code>* REFERENCE</code> <code>instances: linenote</code>
<code>\stoppradek [...]</code> <code>* REFERENCE</code>
<code>\stopregister [...<sup>1</sup>] [...<sup>2</sup>]</code> <code>1 NAME</code> <code>2 NAME</code>
<code>\stopstructurepageregister [...<sup>1</sup>] [...<sup>2</sup>]</code> <code>1 NAME</code> <code>2 NAME</code>
<code>\strana [...,.*,...]</code> <code>* inherits: \pagebreak<sup>OPT</sup></code>
<code>\strictdoifelsenextoptional {...<sup>1</sup>} {...<sup>2</sup>}</code> <code>1 TRUE</code> <code>2 FALSE</code>
<code>\strictdoifnextoptionalelse {...<sup>1</sup>} {...<sup>2</sup>}</code> <code>1 TRUE</code> <code>2 FALSE</code>
<code>\stripcharacter ... \from ...<sup>2</sup> \to ...<sup>3</sup></code> <code>1 CHARACTER</code> <code>2 TEXT</code> <code>3 CSNAME</code>
<code>\strippedcsname \*...</code> <code>* CSNAME</code>
<code>\strippedcsname ...</code> <code>* TEXT</code>
<code>\stripspaces \from ...<sup>1</sup> \to ...<sup>2</sup></code> <code>1 TEXT</code> <code>2 CSNAME</code>
<code>\structurelistuservariable {...<sup>*</sup>}</code> <code>* KEY</code>
<code>\structurenumber</code>
<code>\structuretitle</code>

<code>\structureuservariable {...}</code> * KEY
<code>\structurevariable {...}</code> * KEY
<code>\strut</code>
<code>\strutdp</code>
<code>\strutht</code>
<code>\struthtdp</code>
<code>\struttedbox {...}</code> * CONTENT
<code>\strutwd</code>
<code>\style [...<sup>1</sup>...<sup>2</sup>...] {...}</code> 1 inherits: \setupstyle 2 TEXT
<code>\styleinstance [...]</code> * NAME
<code>\style [...<sup>1</sup>] {...<sup>2</sup>}</code> 1 NAME FONT 2 TEXT
<code>\STYLE {...}</code> * TEXT
<code>\subpagenumber</code>
<code>\subsentence {...}</code> * CONTENT
<code>\substituteincommalist {...<sup>1</sup>} {...<sup>2</sup>} \...<sup>3</sup></code> 1 TEXT 2 TEXT 3 CSNAME
<code>\subtractfeature [...]</code> * NAME
<code>\subtractfeature {...}</code> * NAME
<code>\swapcounts \...<sup>1</sup> \...<sup>2</sup></code> 1 CSNAME 2 CSNAME
<code>\swapdimens \...<sup>1</sup> \...<sup>2</sup></code> 1 CSNAME 2 CSNAME

<code>\swapface</code>
<code>\swapmacros \<sup>1</sup> \<sup>2</sup></code> 1 CSNAME 2 CSNAME
<code>\swaptypesface</code>
<code>\switchstyleonly [...]</code> * rm ss tt hw cg antikva serif pravidelne sans bezserifu podpora opis strojopis mono rukopisne kaligraficke
<code>\switchstyleonly \...</code> * CSNAME
<code>\switchtocolour [...]</code> * COLOR
<code>\switchtointerlinespace [...,<sup>1</sup>...] [...,<sup>2</sup>...] [...,<sup>2</sup>...] [...]</code> 1 NAME <small>OPT</small> 2 inherits: \nastavmeziradkovoumezeru
<code>\switchtointerlinespace [...,*...] [...]</code> * zap vyp reset auto male stredni $\Psi$ elke NUMMER DIMENSION
<code>\switchtointerlinespace [...]</code> * NAME
<code>\symbol [...<sup>1</sup>] [...<sup>2</sup>]</code> 1 NAME <small>OPT</small> 2 NAME
<code>\symbolreference [...]</code> * REFERENCE
<code>\symbol {...}</code> * NAME
<code>\synchronizeblank</code>
<code>\synchronizeindenting</code>
<code>\synchronizemarking [...<sup>1</sup>] [...<sup>2</sup>] [...<sup>3</sup>]</code> 1 BESCHRIFTUNG <small>OPT</small> 2 NUMMER 3 drzet
<code>\synchronizeoutputstreams [...,*...]</code> * NAME
<code>\synchronizestrut {...}</code> * ano ne auto kap prizpusobive radek implicitni CHARACTER
<code>\synchronizewhitespace</code>

<code>\SYNONYM [...]<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup></code> 1 NAME OPT 2 TEXT 3 CONTENT instances: abbreviation
<code>\systemlog {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup></code> 1 FILE 2 TEXT 3 TEXT
<code>\systemlogfirst [...]<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup></code> 1 FILE 2 TEXT 3 TEXT
<code>\systemloglast {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup></code> 1 FILE 2 TEXT 3 TEXT
<code>\systemsetups {...}</code> * NAME
<code>\TABLE</code>
<code>\TaBlE</code>
<code>\TEX</code>
<code>\TeX</code>
<code>\TheNormalizedFontSize</code>
<code>\TransparencyHack</code>
<code>\tabulateautoline</code>
<code>\tabulateautorule</code>
<code>\tabulateline</code>
<code>\tabulaterule</code>
<code>\taggedctxcommand {...}</code> * BEFEHL
<code>\taggedlabeltexts {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup></code> 1 NAME 2 NAME 3 CONTENT
<code>\tbox {...}</code> * CONTENT
<code>\tecka {...}</code> * CHARACTER



<code>\tecky [...]</code> <code>*    NUMMER    <small>OPT</small></code>
<code>\tecky [...,.*=...,...]</code> <code>*    inherits: \setupperperiods</code>
<code>\tenkalinka</code>
<code>\tenkelinky [...,.*=...,...]</code> <code>*    inherits: \nastavten<sup>OPT</sup>kelinky</code>
<code>\tequal {<sup>1</sup>...} {<sup>2</sup>...}</code> <code>1    TEXT        <small>OPT</small>        <small>OPT</small></code> <code>2    TEXT</code>
<code>\testandsplitstring <sup>1</sup>... \at <sup>2</sup>... \to \<sup>3</sup>... \and \<sup>4</sup>...</code> <code>1    TEXT</code> <code>2    TEXT</code> <code>3    CSNAME</code> <code>4    CSNAME</code>
<code>\testcolumn [<sup>1</sup>...] [<sup>2</sup>...]</code> <code>1    NUMMER                    <small>OPT</small></code> <code>2    DIMENSION</code>
<code>\testfeature {<sup>1</sup>...} {<sup>2</sup>...}</code> <code>1    NUMMER</code> <code>2    CONTENT</code>
<code>\testfeatureonce {<sup>1</sup>...} {<sup>2</sup>...}</code> <code>1    NUMMER</code> <code>2    CONTENT</code>
<code>\testpage [<sup>1</sup>...] [<sup>2</sup>...]</code> <code>1    NUMMER                    <small>OPT</small></code> <code>2    DIMENSION</code>
<code>\testpageonly [<sup>1</sup>...] [<sup>2</sup>...]</code> <code>1    NUMMER                    <small>OPT</small></code> <code>2    DIMENSION</code>
<code>\testpagesync [<sup>1</sup>...] [<sup>2</sup>...]</code> <code>1    NUMMER                    <small>OPT</small></code> <code>2    DIMENSION</code>
<code>\testtokens [...]</code> <code>*    NAME</code>
<code>\tex {.*}</code> <code>*    CONTENT</code>
<code>\texdefinition {.*}</code> <code>*    NAME</code>
<code>\texsetup {.*}</code> <code>*    NAME</code>
<code>\TEXTBACKGROUND {.*}</code> <code>*    CONTENT</code>

`\textcitation [...1...] [...2]`

```
1 odkaz      = REFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
               authornum authoryear
  pred        = BEFEHL
  po          = BEFEHL
  vlevo       = BEFEHL
  vpravo      = BEFEHL
  inherits: \setupbtx
2 REFERENCE
```

`\textcitation [...1] [...2]`

```
1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear
2 REFERENCE
```

`\textcitation [...1...] [...2...]`

```
1 odkaz      = REFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
               authornum authoryear
  pred        = BEFEHL
  po          = BEFEHL
  vlevo       = BEFEHL
  vpravo      = BEFEHL
  inherits: \setupbtx
2 KEY = VALUE
```

`\textcite [...1...] [...2]`

```
1 odkaz      = REFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
               authornum authoryear
  pred        = BEFEHL
  po          = BEFEHL
  vlevo       = BEFEHL
  vpravo      = BEFEHL
  inherits: \setupbtx
2 REFERENCE
```

`\textcite [...1] [...2]`

```
1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear
2 REFERENCE
```

`\textcite [...1...] [...2...]`

```
1 odkaz      = REFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
               authornum authoryear
  pred        = BEFEHL
  po          = BEFEHL
  vlevo       = BEFEHL
  vpravo      = BEFEHL
  inherits: \setupbtx
2 KEY = VALUE
```

`\textcontrolspace`

`\textflowcollector {...}`

`* NAME`

`\textmath {...}`

`* CONTENT`

`\textminus`

`\textnapovedy [...1] {...2} {...3}`

```
1 REFERENCE
2 TEXT
3 TEXT
```

$\backslash\text{textormathchar}$ {...} *    NUMMER
$\backslash\text{textovalinka}$ [ <sup>1</sup> ...] { <sup>2</sup> ...} 1    vrsek nastred spódek    OPT 2    TEXT
$\backslash\text{textplus}$
$\backslash\text{LABELtext}$ {...} *    KEY instances: head label mathlabel taglabel unit operator prefix suffix btxlabel
$\backslash\text{btxlabeljazyk}$
$\backslash\text{headjazyk}$
$\backslash\text{labeljazyk}$
$\backslash\text{mathlabeljazyk}$
$\backslash\text{operatorjazyk}$
$\backslash\text{prefixjazyk}$
$\backslash\text{suffixjazyk}$
$\backslash\text{taglabeljazyk}$
$\backslash\text{unitjazyk}$
$\backslash\text{textvisiblespace}$
$\backslash\text{thainumerals}$ {...} *    NUMMER
$\backslash\text{thefirstcharacter}$ {...} *    TEXT
$\backslash\text{thenormalizedbodyfontsize}$ {...} *    DIMENSION
$\backslash\text{theremainingcharacters}$ {...} *    TEXT
$\backslash\text{thickspace}$
$\backslash\text{thinspace}$
$\backslash\text{thirdoffivearguments}$ { <sup>1</sup> ...} { <sup>2</sup> ...} { <sup>3</sup> ...} { <sup>4</sup> ...} { <sup>5</sup> ...} 1    TEXT 2    TEXT 3    TEXT 4    TEXT 5    TEXT

`\thirdoffourarguments {...} {...} {...} {...}`

1 TEXT  
2 TEXT  
3 TEXT  
4 TEXT

`\thirdofsixarguments {...} {...} {...} {...} {...} {...}`

1 TEXT  
2 TEXT  
3 TEXT  
4 TEXT  
5 TEXT  
6 TEXT

`\thirdofthreearguments {...} {...} {...}`

1 TEXT  
2 TEXT  
3 TEXT

`\thirdofthreeunexpanded {...} {...} {...}`

1 TEXT  
2 TEXT  
3 TEXT

`\thookleftarrow {...} {...}`

1 TEXT  
2 TEXT

OPT OPT

`\thookrightarrow {...} {...}`

1 TEXT  
2 TEXT

OPT OPT

`\threedigitrounding {...}`

\* NUMMER

`\tibetannumerals {...}`

\* NUMMER

`\tightlayer [...]`

\* NAME

`\tilde {...}`

\* CHARACTER

`\tinyfont`

`\tleftarrow {...} {...}`

1 TEXT  
2 TEXT

OPT OPT

`\tleftrightarrow {...} {...}`

1 TEXT  
2 TEXT

OPT OPT

`\tlacitko [...,\frac{...}{...}] {...} [...]`

1 inherits: \setupbutton  
2 TEXT  
3 REFERENCE

$\backslash\mathrm{tlacitkomenu}$ [ $\dots$ , $\dots$ <sup>1</sup> $\dots$ , $\dots$ ] $\{\dots\}$ $\{\dots\}$ 1 inherits: $\backslash\mathrm{setupbutton}$ 2 TEXT 3 REFERENCE
$\backslash\mathrm{tlacitkomenu}$ [ $\dots$ ] <sup>1</sup> [ $\dots$ , $\dots$ <sup>2</sup> $\dots$ , $\dots$ ] $\{\dots\}$ $\{\dots\}$ <sup>4</sup> 1 NAME OPT 2 inherits: $\backslash\mathrm{nastavinterakcnimenu}$ 3 TEXT 4 REFERENCE
$\backslash\mathrm{BUTTON}$ [ $\dots$ , $\dots$ <sup>1</sup> $\dots$ , $\dots$ ] $\{\dots\}$ [ $\dots$ ] <sup>3</sup> 1 inherits: $\backslash\mathrm{setupbutton}$ 2 TEXT 3 REFERENCE instances: button
$\backslash\mathrm{tlap}$ $\{\dots\}$ * CONTENT
$\backslash\mathrm{tleftarrow}$ $\{\dots\}$ <sup>1</sup> $\{\dots\}$ <sup>2</sup> 1 TEXT OPT OPT 2 TEXT
$\backslash\mathrm{tlefttharpoondown}$ $\{\dots\}$ <sup>1</sup> $\{\dots\}$ <sup>2</sup> 1 TEXT OPT OPT 2 TEXT
$\backslash\mathrm{tlefttharpoonup}$ $\{\dots\}$ <sup>1</sup> $\{\dots\}$ <sup>2</sup> 1 TEXT OPT OPT 2 TEXT
$\backslash\mathrm{tleftrightarrow}$ $\{\dots\}$ <sup>1</sup> $\{\dots\}$ <sup>2</sup> 1 TEXT OPT OPT 2 TEXT
$\backslash\mathrm{tlefttrightharpoons}$ $\{\dots\}$ <sup>1</sup> $\{\dots\}$ <sup>2</sup> 1 TEXT OPT OPT 2 TEXT
$\backslash\mathrm{tloustkacary}$
$\backslash\mathrm{tmapsto}$ $\{\dots\}$ <sup>1</sup> $\{\dots\}$ <sup>2</sup> 1 TEXT OPT OPT 2 TEXT
$\backslash\mathrm{tochar}$ $\{\dots\}$ * e:NAME x:NUMMER d:NUMMER s:NUMMER i:NUMMER n:NAME c:NAME u:NAME a:NAME
$\backslash\mathrm{tolinenote}$ [ $\dots$ ] * REFERENCE
$\backslash\mathrm{topbox}$ $\{\dots\}$ * CONTENT
$\backslash\mathrm{topleftbox}$ $\{\dots\}$ * CONTENT
$\backslash\mathrm{toplinebox}$ $\{\dots\}$ * CONTENT

$\backslash\mathrm{toprightbox}\{\dots\}$ *    CONTENT
$\backslash\mathrm{topskippedbox}\{\dots\}$ *    CONTENT
$\backslash\mathrm{tRightarrow}\{\overset{1}{\dots}\}\{\overset{2}{\dots}\}$ 1    TEXT            OPT            OPT 2    TEXT
$\backslash\mathrm{tracecatcodetables}$
$\backslash\mathrm{tracedfontname}\{\dots\}$ *    FONT
$\backslash\mathrm{traceoutputroutines}$
$\backslash\mathrm{tracepositions}$
$\backslash\mathrm{transparencycomponents}\{\dots\}$ *    COLOR
$\backslash\mathrm{transparent}[\overset{1}{\dots}]\{\overset{2}{\dots}\}$ 1    COLOR 2    CONTENT
$\backslash\mathrm{tref}\{\overset{1}{\dots}\}\{\overset{2}{\dots}\}[\overset{3}{\dots}]$ 1    TEXT    OPT            OPT 2    TEXT 3    REFERENCE
$\backslash\mathrm{trel}\{\overset{1}{\dots}\}\{\overset{2}{\dots}\}$ 1    TEXT    OPT            OPT 2    TEXT
$\backslash\mathrm{trightarrow}\{\overset{1}{\dots}\}\{\overset{2}{\dots}\}$ 1    TEXT            OPT            OPT 2    TEXT
$\backslash\mathrm{trightharpoondown}\{\overset{1}{\dots}\}\{\overset{2}{\dots}\}$ 1    TEXT            OPT            OPT 2    TEXT
$\backslash\mathrm{trightharpoonup}\{\overset{1}{\dots}\}\{\overset{2}{\dots}\}$ 1    TEXT            OPT            OPT 2    TEXT
$\backslash\mathrm{trightleftharpoons}\{\overset{1}{\dots}\}\{\overset{2}{\dots}\}$ 1    TEXT            OPT            OPT 2    TEXT
$\backslash\mathrm{trightoverleftarrow}\{\overset{1}{\dots}\}\{\overset{2}{\dots}\}$ 1    TEXT            OPT            OPT 2    TEXT
$\backslash\mathrm{triplebond}$

\truefilename {...} * FILE
\truefontname {...} * FONT
\ttraggedright
\ttriplerel {...} {...} 1 TEXT OPT OPT 2 TEXT
\ttwoheadleftarrow {...} {...} 1 TEXT OPT OPT 2 TEXT
\ttwoheadrightarrow {...} {...} 1 TEXT OPT OPT 2 TEXT
\tucne
\tucnekurzivni
\tucnesklonene
\tvrdamezera
\tvrdemezery
\twodigitrounding {...} * NUMMER
\tx
\txx
\typebuffer [... <sup>1</sup> ,...] [... <sup>2</sup> ,...] 1 BUFFER OPT OPT 2 inherits: \nastavopis
\opisBUFFER [... <sup>*</sup> ,...] * inherits: \nastavopis <sup>OPT</sup>
\typedefinedbuffer [... <sup>1</sup> ] [... <sup>2</sup> ,...] 1 BUFFER OPT 2 inherits: \nastavopis
\typeface
\typeinlinebuffer [... <sup>1</sup> ,...] [... <sup>2</sup> ,...] 1 BUFFER OPT OPT 2 inherits: \nastavtype
\typescriptone

\typecriptprefix {...} * NAME
\typecriptthree
\typecripttwo
\typesetbuffer [...] [...] [...] 1 * BUFFER OPT OPT 2 inherits: \setupexternalfigure
\typesetfile [...] [...] [...] 1 NAME FILE OPT OPT 2 FILE TEXT 3 inherits: \setupexternalfigure
\uconvertnumber {...} {...} 1 inherits: \konvertujcislo 2 NUMMER
\uedcatcodecommand \... \... {...} 1 CSNAME 2 CHARACTER NUMBER 3 BEFEHL
\ukazbarvu [...] * COLOR
\ukazmrizku [...]*...] * reset spodek vrsek zadny vse radky ramecek nonumber vpravo vlevo vnejsi sloupce
\ukaznastaveni [...]*...] * pt bp cm mm dd cc pcOPTkd nc sp in
\ukazpaletu [...] [...] 1 NAME OPT 2 horizontalne vertikalne cislo hodnota jmeno
\ukazpodpery
\ukazpostredizakladnihofontu [...]*...] * inherits: \nastavzakladnifont
\ukazramecek [...] [...] 1 vrsek zahlavi textOPTupati spodekOPT 2 levahrana levyokraj text pravyokraj pravahrana
\ukazsadusymbolu [...] * NAME
\ukazskupinubarev [...] [...] 1 NAME OPT 2 horizontalne vertikalne cislo hodnota jmeno
\ukazupravu [...] * zlom vse boxesOPTglyph fontkern hbox vbox vtop kern glue penalty strut whatsit simple simplehbox simplevbox simplevtop user math kurziva origin reset



<p><b>\ukazvytisk</b> [...<sup>1</sup>,...] [...<sup>2</sup>,...] [...<sup>3</sup>,...] [...<sup>4</sup>,...]</p> <p>1 inherits: \nastavvelikostpapi<u>r</u><sup>OPT</sup></p> <p>2 inherits: \nastavvelikostpapi<u>r</u></p> <p>3 inherits: \nastavvzhled</p>
<p><b>\ukazvzhled</b> [...*,...]</p> <p>* pt bp cm mm dd cc<sup>OPT</sup>pc nd nc sp in</p>
<p><b>\ukazzakladnifont</b> [...*,...]</p> <p>* inherits: \nastavzakladnifont</p>
<p><b>\umistikombinovanyseznam</b> [...<sup>1</sup>,] [...<sup>2</sup>,...] [...<sup>3</sup>,...]</p> <p>1 LISTE</p> <p>2 inherits: \nastavseznam</p>
<p><b>\umistiCOMBINEDLIST</b> [...<sup>1</sup>,...] [...<sup>2</sup>,...] [...<sup>3</sup>,...]</p> <p>* inherits: \nastavseznam<sup>OPT</sup></p> <p>instances: content</p>
<p><b>\nastavenicontent</b> [...<sup>1</sup>,...] [...<sup>2</sup>,...] [...<sup>3</sup>,...]</p> <p>* inherits: \nastavseznam</p>
<p><b>\umistilokalnipoznamkypodcarou</b> [...<sup>1</sup>,...] [...<sup>2</sup>,...] [...<sup>3</sup>,...]</p> <p>* inherits: \setupnote<sup>OPT</sup></p>
<p><b>\umistinadsebe</b> {...<sup>1</sup>} {...<sup>2</sup>}</p> <p>1 CONTENT</p> <p>2 CONTENT</p>
<p><b>\umistinamrizku</b> [...<sup>1</sup>,] {...<sup>2</sup>}</p> <p>1 normalni standardni<sup>OPT</sup>ano striktni tolerantni vrsek spodek obe široky prizpusobive prvni posledni vysoko jedna nizko zadny radek strut box min max nastred NAME</p> <p>2 CONTENT</p>
<p><b>\umistinamrizku</b> [...<sup>1</sup>,...] {...<sup>2</sup>}</p> <p>1 inherits: \definegrids<sup>OPT</sup>apping</p> <p>2 CONTENT</p>
<p><b>\umistipodrovnici</b> [...*,...]</p> <p>* + - REFERENCE<sup>OPT</sup></p>
<p><b>\umistipoznamkypodcarou</b> [...<sup>1</sup>,...] [...<sup>2</sup>,...] [...<sup>3</sup>,...]</p> <p>* inherits: \setupnote<sup>OPT</sup></p>
<p><b>\umistirejstrik</b> [...<sup>1</sup>,] [...<sup>2</sup>,...] [...<sup>3</sup>,...]</p> <p>1 NAME</p> <p>2 inherits: \nastavrejstrik<sup>OPT</sup></p>
<p><b>\umistiREGISTER</b> [...<sup>1</sup>,...] [...<sup>2</sup>,...] [...<sup>3</sup>,...]</p> <p>* inherits: \nastavrejstri<sup>OPT</sup>k</p> <p>instances: index</p>
<p><b>\upl<sub>ny</sub>index</b> [...<sup>1</sup>,...] [...<sup>2</sup>,...] [...<sup>3</sup>,...]</p> <p>* inherits: \nastavrejstri<sup>OPT</sup>k</p>
<p><b>\umistirovnici</b> [...*,...]</p> <p>* + - REFERENCE<sup>OPT</sup></p>

$\backslash\text{umistiseznam} [\dots^1, \dots] [\dots, \dots^2, \dots]$ 1 LISTE 2 inherits: \nastavseznam
$\backslash\text{umistivedlesebe} \{\dots^1\} \{\dots^2\}$ 1 CONTENT 2 CONTENT
$\backslash\text{umistizalozky} [\dots^1, \dots] [\dots, \dots^2, \dots] [\dots, \dots^3, \dots]$ 1 ABSCHNITT LISTE 2 ABSCHNITT LISTE 3 inherits: \setupbookmark
$\backslash\text{undefinevalue} \{.*\}$ * NAME
$\backslash\text{undepthed} \{.*\}$ * CONTENT
$\backslash\text{underbartext} \{\dots^1\} \{\dots^2\}$ 1 TEXT 2 TEXT
$\backslash\text{underbrace} \{.*\}$ * TEXT
$\backslash\text{underbracetext} \{\dots^1\} \{\dots^2\}$ 1 TEXT 2 TEXT
$\backslash\text{underbracket} \{.*\}$ * TEXT
$\backslash\text{underbrackettext} \{\dots^1\} \{\dots^2\}$ 1 TEXT 2 TEXT
$\backslash\text{underleftarrow} \{.*\}$ * TEXT
$\backslash\text{underleftharpoonup} \{.*\}$ * TEXT
$\backslash\text{underleftharpoonup} \{.*\}$ * TEXT
$\backslash\text{underletrightarrow} \{.*\}$ * TEXT
$\backslash\text{underparent} \{.*\}$ * TEXT
$\backslash\text{underparenttext} \{\dots^1\} \{\dots^2\}$ 1 TEXT 2 TEXT
$\backslash\text{underrightarrow} \{.*\}$ * TEXT

$\backslash$ underrightharpoondown {...} * TEXT
$\backslash$ underrightharpoonup {...} * TEXT
$\backslash$ underset {...} {...} 1 TEXT 2 TEXT
$\backslash$ undertwoheadleftarrow {...} * TEXT
$\backslash$ undertwoheadrightarrow {...} * TEXT
$\backslash$ undoassign [... <sup>1</sup> ] [... <sup>2</sup> ...] 1 TEXT 2 KEY = VALUE
$\backslash$ unhhbox ... <sup>1</sup> \with {...} <sup>2</sup> 1 CSNAME NUMBER 2 BEFEHL
$\backslash$ unihex {...} * NUMMER
$\backslash$ uniqueMPgraphic {...} {..., <sup>2</sup> ... <sub>OPT</sub> ,...} 1 NAME 2 KEY = VALUE
$\backslash$ uniqueMPpagegraphic {...} {..., <sup>2</sup> ... <sub>OPT</sub> ,...} 1 NAME 2 KEY = VALUE
$\backslash$ unprotect ... \protect
$\backslash$ unprotected ... \par * CONTENT
$\backslash$ unregisterhyphenationpattern [... <sup>1</sup> ] [... <sup>2</sup> ] 1 SPRACHE 2 TEXT
$\backslash$ unspaceafter \... <sup>1</sup> {...} <sup>2</sup> 1 CSNAME 2 TEXT
$\backslash$ unspaceargument ... <sup>1</sup> \to \... <sup>2</sup> 1 TEXT 2 CSNAME
$\backslash$ unspaced {...} * TEXT
$\backslash$ unspacestring ... <sup>1</sup> \to \... <sup>2</sup> 1 TEXT 2 CSNAME

<code>\untexargument {...} \to \^2...</code> 1 TEXT 2 CSNAME
<code>\untexcommand {...} \to \^2...</code> 1 CSNAME 2 CSNAME
<code>\uppercased {...}</code> * TEXT
<code>\uppercasestring \^1... \to \^2...</code> 1 TEXT 2 CSNAME
<code>\upperlefthdoubleninequote</code>
<code>\upperlefthdoublesixquote</code>
<code>\upperleftsingleninequote</code>
<code>\upperleftsinglesixquote</code>
<code>\upperrighthdoubleninequote</code>
<code>\upperrighthdoublesixquote</code>
<code>\upperrightsingleninequote</code>
<code>\upperrightsinglesixquote</code>
<code>\urcicharakteristikurejstriku [\^1...] [\^2...,\^3...]</code> 1 NAME 2 language = implicitni DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scn SPRACHE metoda = implicitni pred po prvni posledni ch mm zm pm mc zc pc uc numberorder = cisl compress = ano ne vse kriterium = lokalne text aktualni predchozi vse ABSCHNITT
<code>\url [...]</code> * NAME
<code>\usealignparameter \^...</code> * CSNAME
<code>\useblankparameter \^...</code> * CSNAME
<code>\usebodyfont [...,\^*...]</code> * inherits: \nastavzakladnifont
<code>\usebodyfontparameter \^...</code> * CSNAME
<code>\usebtxdataset [\^1...] [\^2...] [\^3...,\^4...]</code> 1 NAME OPT OPT 2 FILE 3 specification = NAME

\usebtdefinitions [...] * FILE
\usecitation [...] * REFERENCE
\usecitation {...} * REFERENCE
\usecolors [...] * FILE
\usecomponent [...] * FILE
\usedummycolorparameter {...} * KEY
\usedummystyleandcolor {...} {...} 1 KEY 2 KEY
\usedummystyleparameter {...} * KEY
\useenvironment [...] * FILE
\useexternalrendering [...] [...] [...] [...] 1 NAME 2 NAME 3 FILE 4 auto embed
\usefigurebase [...] * reset FILE
\usefile [...] [...] [...] 1 NAME 2 FILE 3 TEXT
\usegridparameter \*... * CSNAME
\useindentingparameter \*... * CSNAME
\useindentnextparameter \*... * CSNAME
\useinterlinespaceparameter \*... * CSNAME
\uselanguageparameter \*... * CSNAME

<code>\uselua module [...]</code> <code>* FILE</code>
<code>\useMPenvironmentbuffer [...]</code> <code>* NAME</code>
<code>\useMPgraphic {...} {...,<sup>2</sup>...,...}</code> <code>1 NAME</code> <code>2 KEY = VALUE</code>
<code>\useMPlibrary [...]</code> <code>* FILE</code>
<code>\useMPrun {...} {...}</code> <code>1 NAME</code> <code>2 NUMMER</code>
<code>\useMPvariables [...]<sup>1</sup> [...,<sup>2</sup>,...]</code> <code>1 NAME</code> <code>2 KEY</code>
<code>\usemathstyleparameter \*...</code> <code>* CSNAME</code>
<code>\useproduct [...]</code> <code>* FILE</code>
<code>\useprofileparameter \*...</code> <code>* CSNAME</code>
<code>\useproject [...]</code> <code>* FILE</code>
<code>\userferenceparameter \*...</code> <code>* CSNAME</code>
<code>\userpagenumber</code>
<code>\usesetupparameter \*...</code> <code>* CSNAME</code>
<code>\usestaticMPfigure [...,<sup>1</sup>...,...]<sup>2</sup> [...]</code> <code>1 inherits: \setupscale</code> <code>2 NAME</code>
<code>\usesubpath [...,<sup>*</sup>,...]</code> <code>* PATH</code>
<code>\usetextmodule [...]<sup>1</sup> [...,<sup>2</sup>,...]<sup>3</sup> [...,<sup>3</sup>...,...]</code> <code>1 m p s x t</code> <code>2 FILE</code> <code>3 KEY = VALUE</code>
<code>\usetypescript [...]<sup>1</sup> [...]<sup>2</sup> [...]<sup>3</sup></code> <code>1 serif sans mono <sup>OPT</sup>math handwriting <sup>OPT</sup>calligraphy casual vse</code> <code>2 NAME fallback implicitni dtp simple</code> <code>3 size jmeno</code>

\usetypescriptfile [...] *   reset FILE
\usezipfile [... <sup>1</sup> ] [... <sup>2</sup> ] 1   FILE                   OPT 2   FILE
\utfchar {...} *   NUMMER
\utflower {...} *   TEXT
\utfupper {...} *   TEXT
\utilityregisterlength
\uzijadresar [...*,...] *   PATH
\uzijbloky [... <sup>1</sup> ,...] [... <sup>2</sup> ,...] [... <sup>3</sup> ,... <sup>3</sup> ,...] 1   NAME                   OPT                   OPT 2   NAME 3   kriterium = text ABSCHNITT
\uzijexternidokument [... <sup>1</sup> ] [... <sup>2</sup> ] [... <sup>3</sup> ] 1   NAME                   OPT 2   FILE 3   TEXT
\uzijexterniobraz [... <sup>1</sup> ] [... <sup>2</sup> ] [... <sup>3</sup> ] [... <sup>4</sup> ,... <sup>4</sup> ,...] 1   NAME                   OPT                   OPT 2   FILE 3   NAME 4   inherits: \setupexternalfigure
\uzijexternizvuk [... <sup>1</sup> ] [... <sup>2</sup> ] 1   NAME 2   FILE
\uzijJSscripts [... <sup>1</sup> ] [... <sup>2</sup> ,...] 1   FILE                   OPT 2   NAME
\uzijmodul [... <sup>1</sup> ] [... <sup>2</sup> ,...] [... <sup>3</sup> ,... <sup>3</sup> ,...] 1   m p s x t           OPT                   OPT 2   FILE 3   KEY = VALUE
\uzijsymbol [...*] *   FILE
\uzijURL [... <sup>1</sup> ] [... <sup>2</sup> ] [... <sup>3</sup> ] [... <sup>4</sup> ] 1   NAME                   OPT                   OPT 2   URL 3   FILE 4   TEXT





$\backslash\text{vlevo}$ ... * CHARACTER
$\backslash\text{vphantom}$ {...} * CONTENT
$\backslash\text{vpos}$ {... <sup>1</sup> } {... <sup>2</sup> } 1 NAME 2 CONTENT
$\backslash\text{vpravo}$ ... * CHARACTER
$\backslash\text{vradku}$ {... <sup>1</sup> } [... <sup>2</sup> ] 1 TEXT <small>OPT</small> 2 REFERENCE
$\backslash\text{vsedniden}$ {...} * NUMMER
$\backslash\text{vsmash}$ {...} * CONTENT
$\backslash\text{vsmashbox}$ ... * CSNAME NUMMER
$\backslash\text{vsmashed}$ {...} * CONTENT
$\backslash\text{vspace}$ [... <sup>1</sup> ] [... <sup>2</sup> ] 1 NAME <small>OPT</small> <small>OPT</small> 2 NAME
$\backslash\text{vspacing}$ [... <sup>*</sup> ...] * nastaveni stej <sup>OPT</sup> nastranka max sila enable zablokovat zadnabila zpet prekryv vzdy weak strong implicitni pred mezi po fixne prizpusobive zadny male stredni velke radek pulradku quarterline rovnice bily vyska podlehloubky standardni NUMMER*male NUMMER*stredni NUMMER*velke NUMMER*radek NUMMER*pulradku NUMMER*quarterline NUMMER*rovnice NUMMER*bily NUMMER*vyska NUMMER*podlehloubky category:NUMMER order:NUMMER penalty:NUMMER DIMENSION NAME
$\backslash\text{vyberbloky}$ [... <sup>1</sup> ,...] [... <sup>2</sup> ,...] [... <sup>3</sup> ,...] 1 NAME <small>OPT</small> <small>OPT</small> 2 NAME 3 kriterium = text ABSCHNITT
$\backslash\text{VCET}$ [... <sup>1</sup> ,...] {... <sup>2</sup> } ... <sup>3</sup> \par 1 REFERENCE <small>OPT</small> <small>OPT</small> 2 TEXT 3 CONTENT
$\backslash\text{vyplnenytext}$ [... <sup>1</sup> ,...] {... <sup>2</sup> } {... <sup>3</sup> } 1 inherits: \nastavvypl <sup>OPT</sup> noVelinky <small>OPT</small> <small>OPT</small> 2 TEXT 3 TEXT
$\backslash\text{vyplnovelinky}$ [... <sup>1</sup> ,...] {... <sup>2</sup> } {... <sup>3</sup> } 1 inherits: \nastavvypl <sup>OPT</sup> noVelinky <small>OPT</small> <small>OPT</small> 2 TEXT 3 TEXT

<code>\vyplnovyradek [...,..<sup>*</sup>...,...]</code> <code>* inherits: \nastavvyplnoveradky</code>
<code>\vysoky {...}</code> <code>* CONTENT</code>
<code>\HIGH {...}</code> <code>* CONTENT</code> <code>instances: unitshigh</code>
<code>\WidthSpanningText {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}</code> <code>1 TEXT</code> <code>2 DIMENSION</code> <code>3 FONT</code>
<code>\wdofstring {...}</code> <code>* TEXT</code>
<code>\widthhofstring {...}</code> <code>* TEXT</code>
<code>\widthspanningtext {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}</code> <code>1 TEXT</code> <code>2 DIMENSION</code> <code>3 FONT</code>
<code>\withoutpt {...}</code> <code>* DIMENSION</code>
<code>\words {...}</code> <code>* TEXT</code>
<code>\wordtonumber {...<sup>1</sup>} {...<sup>2</sup>}</code> <code>1 jedna dve tri ctyri pet</code> <code>2 TEXT</code>
<code>\writadatatolist [...<sup>1</sup>] [...,..<sup>2</sup>...,...]<sub>OPT</sub> [...,..<sup>3</sup>...,...]</code> <code>1 LISTE</code> <code>2 inherits: \nastavseznam</code> <code>3 KEY = VALUE</code>
<code>\writestatus {...<sup>1</sup>} {...<sup>2</sup>}</code> <code>1 TEXT</code> <code>2 TEXT</code>
<code>\XETEX</code>
<code>\XeTeX</code>
<code>\xdefconvertedargument \... {...<sup>1</sup>} {...<sup>2</sup>}</code> <code>1 CSNAME</code> <code>2 TEXT</code>
<code>\xequal {...<sup>1</sup>} {...<sup>2</sup>}<sub>OPT</sub> {...<sup>2</sup>}<sub>OPT</sub></code> <code>1 TEXT</code> <code>2 TEXT</code>

`\xhookleftarrow {...} {...}`  
1 TEXT OPT OPT  
2 TEXT

`\xhookrightarrow {...} {...}`  
1 TEXT OPT OPT  
2 TEXT

`\xLeftarrow {...} {...}`  
1 TEXT OPT OPT  
2 TEXT

`\xLeftrightarrow {...} {...}`  
1 TEXT OPT OPT  
2 TEXT

`\xleftarrow {...} {...}`  
1 TEXT OPT OPT  
2 TEXT

`\xleftharpoondown {...} {...}`  
1 TEXT OPT OPT  
2 TEXT

`\xleftharpoonup {...} {...}`  
1 TEXT OPT OPT  
2 TEXT

`\xleftrightharpoonarrow {...} {...}`  
1 TEXT OPT OPT  
2 TEXT

`\xleftrightharpoons {...} {...}`  
1 TEXT OPT OPT  
2 TEXT

`\xmapsto {...} {...}`  
1 TEXT OPT OPT  
2 TEXT

`\xmladdindex {...}`  
\* NODE

`\xmلاfterdocumentsetup {...} {...} {...}`  
1 NAME  
2 SETUP  
3 SETUP

`\xmلاftersetup {...} {...}`  
1 SETUP  
2 SETUP

`\xmlall {...} {...}`  
1 NODE  
2 LPATH

`\xmلاppenddocumentsetup {...} {...}`  
1 NAME  
2 SETUP

\xmlappendsetup {...} *    SETUP
\xmlapplyselectors {...} *    NODE
\xmlatt {...} {...} 1    NODE 2    NAME
\xmlattdef {...} {...} {...} 1    NODE 2    NAME 3    TEXT
\xmlattribute {...} {...} {...} 1    NODE 2    LPATH 3    NAME
\xmlattributedef {...} {...} {...} {...} 1    NODE 2    LPATH 3    NAME 4    TEXT
\xmlbadinclusions {...} *    NODE
\xmlbeforedocumentsetup {...} {...} {...} 1    NAME 2    SETUP 3    SETUP
\xmlbeforesetup {...} {...} 1    SETUP 2    SETUP
\xmlcommand {...} {...} {...} 1    NODE 2    LPATH 3    XMLSETUP
\xmlconcat {...} {...} {...} 1    NODE 2    LPATH 3    TEXT
\xmlconcatrange {...} {...} {...} {...} {...} 1    NODE 2    LPATH 3    TEXT 4    FIRST 5    LAST
\xmlcontext {...} {...} 1    NODE 2    LPATH
\xmlcount {...} *    NODE

\xmldefaulttotext {...} *   NODE
\xmldirectives {...} *   NODE
\xmldirectivesafter {...} *   NODE
\xmldirectivesbefore {...} *   NODE
\xmldisplayverbatim {...} *   NODE
\xmldoif {...} {...} {...} 1   NODE 2   LPATH 3   TRUE
\xmldoifelse {...} {...} {...} {...} 1   NODE 2   LPATH 3   TRUE 4   FALSE
\xmldoifelseempty {...} {...} {...} {...} 1   NODE 2   LPATH 3   TRUE 4   FALSE
\xmldoifelseselfempty {...} {...} {...} 1   NODE 2   TRUE 3   FALSE
\xmldoifelsesetText {...} {...} {...} {...} 1   NODE 2   LPATH 3   TRUE 4   FALSE
\xmldoifelsevalue {...} {...} {...} {...} 1   CATEGORY 2   NAME 3   TRUE 4   FALSE
\xmldoifnot {...} {...} {...} 1   NODE 2   LPATH 3   TRUE
\xmldoifnotselfempty {...} {...} 1   NODE 2   TRUE
\xmldoifnottext {...} {...} {...} 1   NODE 2   LPATH 3   TRUE

<pre> \xmldoifselfempty {...} {...} 1  NODE 2  TRUE </pre>
<pre> \xmldoiftext {...} {...} {...} 1  NODE 2  LPATH 3  TRUE </pre>
<pre> \xmlelement {...} {...} 1  NODE 2  NUMMER </pre>
<pre> \xmlfilter {...} {...} 1  NODE 2  LPATH </pre>
<pre> \xmlfirst {...} {...} 1  NODE 2  LPATH </pre>
<pre> \xmlflush {...} *  NODE </pre>
<pre> \xmlflushcontext {...} *  NODE </pre>
<pre> \xmlflushdocumentsetups {...} {...} 1  NAME 2  SETUP </pre>
<pre> \xmlflushlinewise {...} *  NODE </pre>
<pre> \xmlflushpure {...} *  NODE </pre>
<pre> \xmlflushspacewise {...} *  NODE </pre>
<pre> \xmlflushtext {...} *  NODE </pre>
<pre> \xmlchainatt {...} {...} 1  NODE 2  NAME </pre>
<pre> \xmlchainattdef {...} {...} {...} 1  NODE 2  NAME 3  TEXT </pre>
<pre> \xmlchecknamespace {...} {...} 1  NODE 2  NAME </pre>
<pre> \xmlinclude {...} {...} {...} 1  NODE 2  LPATH 3  NAME </pre>

\xmlinclusion {...} *    NODE
\xmlinclusions {...} *    NODE
\xmlinfo {...} *    NODE
\xmlinjector {...} *    NAME
\xmlinlineverbatim {...} *    NODE
\xmlinstalldirective {...} {...} 1    NAME 2    CSNAME
\xmllast {...} {...} 1    NODE 2    LPATH
\xmllastatt
\xmllastmatch
\xmlloadbuffer {...} {...} {...} 1    BUFFER 2    NAME 3    XMLSETUP
\xmlloaddata {...} {...} {...} 1    NAME 2    TEXT 3    XMLSETUP
\xmlloaddirectives {...} *    FILE
\xmlloadfile {...} {...} {...} 1    NAME 2    FILE 3    XMLSETUP
\xmlloadonly {...} {...} {...} 1    NAME 2    FILE 3    XMLSETUP
\xmlmain {...} *    NAME
\xmlmapvalue {...} {...} {...} 1    CATEGORY 2    NAME 3    TEXT

\xmlname {...} *    NODE
\xmlnamespace {...} *    NODE
\xmlnonspace {...} {...} 1    NODE 2    LPATH
\xmlpath {...} *    NODE
\xmlpos {...} *    NODE
\xmlposition {...} {...} {...} 1    NODE 2    LPATH 3    NUMMER
\xmlprependdocumentsetup {...} {...} 1    NAME 2    SETUP
\xmlprependsetup {...} *    SETUP
\xmlprettyprint {...} {...} 1    NODE 2    NAME
\xmlprocessbuffer {...} {...} {...} 1    BUFFER 2    NAME 3    XMLSETUP
\xmlprocessdata {...} {...} {...} 1    NAME 2    TEXT 3    XMLSETUP
\xmlprocessfile {...} {...} {...} 1    NAME 2    FILE 3    XMLSETUP
\xmlpure {...} {...} 1    NODE 2    LPATH
\xmlraw {...} *    NODE
\xmlrefatt {...} {...} 1    NODE 2    NAME



\xmlregisterdocumentsetups {...} {...} 1 NAME 2 SETUP
\xmlregisteredsetups
\xmlregisterns {...} {...} 1 NAME 2 URL
\xmlremapname {...} {...} {...} {...} 1 NODE 2 LPATH 3 NAME 4 NAME
\xmlremapnamespace {...} {...} {...} 1 NODE 2 NAME 3 NAME
\xmlremoveddocumentsetup {...} {...} 1 NAME 2 SETUP
\xmlremovesetup {...} * SETUP
\xmlresetdocumentsetups {...} * NAME
\xmlresetinjectors
\xmlresetsetups {...} * NAME
\xmlsave {...} {...} 1 NODE 2 FILE
\xmlsetentity {...} {...} 1 NAME 2 TEXT
\xmlsetfunction {...} {...} {...} 1 NODE 2 LPATH 3 LUAFUNCTION
\xmlsetinjectors [...*,...] * NAME
\xmlsetsetup {...} {...} {...} 1 NAME 2 LPATH 3 SETUP
\xmlsetup {...} {...} 1 NODE 2 SETUP

<code>\xmlshow {...}</code> *    NODE
<code>\xmlsnippet {...} {...}</code> 1    NODE 2    NUMMER
<code>\xmlstrip {...} {...}</code> 1    NODE 2    LPATH
<code>\xmlstrippnolines {...} {...}</code> 1    NODE 2    LPATH
<code>\xmlstripped {...} {...}</code> 1    NODE 2    LPATH
<code>\xmlstrippednolines {...} {...}</code> 1    NODE 2    LPATH
<code>\xmltag {...}</code> *    NODE
<code>\xmltexentity {...} {...}</code> 1    NAME 2    TEXT
<code>\xmltext {...} {...}</code> 1    NODE 2    LPATH
<code>\xmltobuffer {...} {...} {...}</code> 1    NODE 2    LPATH 3    BUFFER
<code>\xmltobufferverbose {...} {...} {...}</code> 1    NODE 2    LPATH 3    BUFFER
<code>\xmltofile {...} {...} {...}</code> 1    NODE 2    LPATH 3    FILE
<code>\xmlvalue {...} {...} {...}</code> 1    CATEGORY 2    NAME 3    TEXT
<code>\xmlverbatim {...}</code> *    NODE
<code>\xrightarrow {...} {...}</code> 1    TEXT                    OPT            OPT 2    TEXT

$\backslash\mathrm{xrel}\ \{...\}^1\{...\}^2$ 1    TEXT    OPT    OPT 2    TEXT
$\backslash\mathrm{xrightarrow}\ \{...\}^1\{...\}^2$ 1    TEXT    OPT    OPT 2    TEXT
$\backslash\mathrm{xrightharpoondown}\ \{...\}^1\{...\}^2$ 1    TEXT    OPT    OPT 2    TEXT
$\backslash\mathrm{xrightharpoonup}\ \{...\}^1\{...\}^2$ 1    TEXT    OPT    OPT 2    TEXT
$\backslash\mathrm{xrightleftharpoons}\ \{...\}^1\{...\}^2$ 1    TEXT    OPT    OPT 2    TEXT
$\backslash\mathrm{xrightarrowleftarrow}\ \{...\}^1\{...\}^2$ 1    TEXT    OPT    OPT 2    TEXT
$\backslash\mathrm{xsplitstring}\ \backslash.^1...\{...\}^2$ 1    CSNAME 2    TEXT
$\backslash\mathrm{xtriplerel}\ \{...\}^1\{...\}^2$ 1    TEXT    OPT    OPT 2    TEXT
$\backslash\mathrm{xtwoheadleftarrow}\ \{...\}^1\{...\}^2$ 1    TEXT    OPT    OPT 2    TEXT
$\backslash\mathrm{xtwoheadrightarrow}\ \{...\}^1\{...\}^2$ 1    TEXT    OPT    OPT 2    TEXT
$\backslash\mathrm{xypos}\ \{...\}$ *    NAME
$\backslash\mathrm{Znak}\ \{...\}$ *    NUMMER
$\backslash\mathrm{Znaky}\ \{...\}$ *    NUMMER
$\backslash\mathrm{zadnamezera}$
$\backslash\mathrm{zadnehorniadolniradky}$
$\backslash\mathrm{zadnezahlaviaupati}$
$\backslash\mathrm{zachovejbloky}\ [...]^1,...\ [...]^2,...]$ 1    NAME    OPT 2    NAME

$\backslash\text{zalozka} [\text{...}] \{\text{...}\}$ 1 ABSCHNITT LISTE 2 TEXT
$\backslash\text{zapisdoseznamu} [\text{...}] [\text{...}, \text{...}^{\text{2}} \text{...}] \{\text{...}\} \{\text{...}\}$ 1 LISTE 2 inherits: $\backslash\text{nastavseznam}$ 3 NUMMER 4 TEXT
$\backslash\text{zapismezeznam} [\text{...}] [\text{...}, \text{...}^{\text{2}} \text{...}] \{\text{...}\}$ 1 LISTE 2 inherits: $\backslash\text{nastavseznam}$ 3 BEFEHL
$\backslash\text{zaramovani} [\text{...}, \text{...}^{\text{1}} \text{...}] \{\text{...}\}$ 1 inherits: $\backslash\text{nastavseznam}$ 2 CONTENT
$\backslash\text{zarovnanonastred} \{\text{...}\}$ * CONTENT
$\backslash\text{zarovnanovlevo} \{\text{...}\}$ * CONTENT
$\backslash\text{zarovnanovpravo} \{\text{...}\}$ * CONTENT
$\backslash\text{zasobnikpoli} [\text{...}] [\text{...}, \text{...}^{\text{2}} \text{...}] [\text{...}, \text{...}^{\text{3}} \text{...}]$ 1 NAME 2 NAME 3 inherits: $\backslash\text{setupfieldcategory}$
$\backslash\text{ziskejbuffer} [\text{...}]$ * BUFFER
$\backslash\text{ziskatBUFFER}$
$\backslash\text{ziskejznaceni} [\text{...}] [\text{...}^{\text{2}} \text{...}] [\text{...}^{\text{3}} \text{...}]$ 1 BESCHRIFTUNG 2 stranka NAME 3 prvi posledni aktualni predchozi dalsi vrsek spodek implicitni obe vse first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck
$\backslash\text{FRACTION} \{\text{...}\} \{\text{...}\}$ 1 CONTENT 2 CONTENT instances: xfrac xxfrac frac sfrac dfrac binom dbinom tbinom
$\backslash\text{znaceni} (\text{...}^{\text{1}} \text{...}) (\text{...}^{\text{2}} \text{...}) [\text{...}^{\text{3}} \text{...}]$ 1 POSITION 2 POSITION 3 REFERENCE
$\backslash\text{znak} \{\text{...}\}$ * NUMMER
$\backslash\text{znaky} \{\text{...}\}$ * NUMMER

`\zpracujbloky [...,1...] [...,2...] [...,3...]`

1 NAME

OPT

OPT

2 NAME

3 kriterium = text ABSCHNITT

`\zrcadlit {...}`

\* CONTENT

`\zref [...]`

\* REFERENCE

`\zvysit \.*..`

\* CSNAME

`\zvysit cd:parentheses-1`

\* CSNAME NUMMER







PRAGMA ADE  
Ridderstraat 27  
8061GH Hasselt NL  
[www.pragma-ade.com](http://www.pragma-ade.com)