



ConTExT

přikazy

CS

ConTeXt

příkazy

cs / český
9. dubna 2018

<p><code>\addvalue {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\aftersplitstring ... \at ... \to ...</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 CSNAME</p>
<p><code>\aftertestandsplitstring ... \at ... \to ...</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 CSNAME</p>
<p><code>\aktualnicislonadpisu</code></p>
<p><code>\aktualnidatum [...*...]</code></p> <p>* rok mesec den vsedni^{den} y yy Y m mm M d dd D w W mezera \ month:mnem m:mnem d:ord day:ord dd:ord D:ord TEXT znacka day:+ day:++ d:+ d:++ dd:+ dd:++ D:+ D:++ month:jalali m:jalali jalali:to jalali:from</p>
<p><code>\alignbottom</code></p>
<p><code>\aligned [...¹,...] {...²}</code></p> <p>1 vlevo nastred vpravo vrsek spodek radek l c r m t b g</p> <p>2 CONTENT</p>
<p><code>\alignedbox [...¹,...] ...² {...³}</code></p> <p>1 vlevo nastred vpravo vrsek spodek radek l c r m t b g</p> <p>2 CSNAME</p> <p>3 CONTENT</p>
<p><code>\alignedline {...¹} {...²} {...³}</code></p> <p>1 vlevo vpravo nastred flushleft flushright center max uvnitr vnejsi innermargin outermargin inneredge outeredge zpetnamezera cutspace levyokraj prav yokraj levahrana pravahrana</p> <p>2 vlevo vpravo nastred flushleft flushright center max uvnitr vnejsi innermargin outermargin inneredge outeredge zpetnamezera cutspace levyokraj prav yokraj levahrana pravahrana</p> <p>3 CONTENT</p>
<p><code>\alignhere</code></p>
<p><code>\alignmentcharacter</code></p>
<p><code>\allinputpaths</code></p>
<p><code>\alphabeticnumerals {...[*]}</code></p> <p>* NUMMER</p>
<p><code>\alwayscitation [...¹,...²,...] [...²]</code></p> <p>1 odkaz = REFERENCE^{PT} alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear</p> <p>pred = BEFEHL po = BEFEHL vlevo = BEFEHL vpravo = BEFEHL inherits: \setupbtx</p> <p>2 REFERENCE</p>
<p><code>\alwayscitation [...¹] [...²]</code></p> <p>1 implicitni category^{PT}entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear</p> <p>2 REFERENCE</p>

`\alwayscitation [...1...2...]`

```
1 odkaz = REFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
                authornum authoryear
  pred = BEFEHL
  po = BEFEHL
  vlevo = BEFEHL
  vpravo = BEFEHL
  inherits: \setupbtx
2 KEY = VALUE
```

`\alwayscite [...1...2...]`

```
1 odkaz = REFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
                authornum authoryear
  pred = BEFEHL
  po = BEFEHL
  vlevo = BEFEHL
  vpravo = BEFEHL
  inherits: \setupbtx
2 REFERENCE
```

`\alwayscite [...1...]`

```
1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear
2 REFERENCE
```

`\alwayscite [...1...2...]`

```
1 odkaz = REFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
                authornum authoryear
  pred = BEFEHL
  po = BEFEHL
  vlevo = BEFEHL
  vpravo = BEFEHL
  inherits: \setupbtx
2 KEY = VALUE
```

`\ampersand`

`\anchor [...1...2...3...]{...4...}`

```
1 NAME OPT OPT
2 inherits: \setuplayer
3 inherits: \setuplayerinherits: \nastavoramovani
4 CONTENT
```

`\antikva`

`\appendetoks ... \to \2...`

```
1 BEFEHL
2 CSNAME
```

`\appendgvalue {...1}{...2...}`

```
1 NAME
2 BEFEHL
```

`\appendtocommalist {...1}\2...`

```
1 TEXT
2 CSNAME
```

`\appendtoks ... \to \2...`

```
1 BEFEHL
2 CSNAME
```

`\appendtoksonce ... \to \2...`

```
1 BEFEHL
2 CSNAME
```

\appendvalue {...} {...} 1 NAME 2 BEFEHL
\apply {...} {...} 1 CONTENT 2 CONTENT
\applyalternativestyle {...} * NAME
\applyprocessor {...} {...} 1 NAME 2 CONTENT
\applytofirstcharacter \... {...} 1 CSNAME 2 TEXT
\applytocharacters \... {...} 1 CSNAME 2 TEXT
\applytosplitstringchar \... {...} 1 CSNAME 2 TEXT
\applytosplitstringcharspaced \... {...} 1 CSNAME 2 TEXT
\applytosplitstringline \... {...} 1 CSNAME 2 TEXT
\applytosplitstringlinespaced \... {...} 1 CSNAME 2 TEXT
\applytosplitstringword \... {...} 1 CSNAME 2 TEXT
\applytosplitstringwordspaced \... {...} 1 CSNAME 2 TEXT
\applytowords \... {...} 1 CSNAME 2 TEXT
\arabicdecimals {...} * NUMMER
\arabicexnumerals {...} * NUMMER
\arabicnumerals {...} * NUMMER

<code>\arg {...}</code> * CONTENT
<code>\asciistr {...}</code> * CONTENT
<code>\assignalfadimension {...} \^2... {...} {...} {...}</code> 1 male stredni velke zadny DIMENSION 2 CSNAME 3 DIMENSION 4 DIMENSION 5 DIMENSION
<code>\assigndimen \^1... {...}</code> 1 CSNAME 2 DIMENSION
<code>\assigndimension {...} \^2... {...} {...} {...}</code> 1 [-+]male [-+]stredni [-+]velke zadny DIMENSION 2 CSNAME 3 DIMENSION 4 DIMENSION 5 DIMENSION
<code>\assignifempty \^1... \^2...</code> 1 CSNAME 2 BEFEHL
<code>\assigntranslation [...,\^1...,\^2...]</code> 1 SPRACHE = TEXT 2 CSNAME
<code>\assignvalue {...} \^2... {...} {...} {...}</code> 1 male stredni velke TEXT 2 CSNAME 3 BEFEHL 4 BEFEHL 5 BEFEHL
<code>\assignwidth {...} \^2... {...} {...}</code> 1 prizpusobive siroky DIMENSION 2 CSNAME 3 TEXT 4 DIMENSION
<code>\assumelongusagecs \^1... {...}</code> 1 CSNAME 2 CONTENT
<code>\astype {...}</code> * CONTENT
<code>\ATTACHMENT [...]\^1... \^2...]</code> 1 NAME OPT OPT 2 inherits: \setupattachment instances: attachment
<code>\attachment [...]\^1... \^2...]</code> 1 NAME OPT OPT 2 inherits: \setupattachment
<code>\autocap {...}</code> * TEXT

$\backslash\text{autodirhbox}$ $\overset{1}{\dots}$ $\{\overset{2}{\dots}\}$ 1 TEXT OPT 2 CONTENT
$\backslash\text{autodirvbox}$ $\overset{1}{\dots}$ $\{\overset{2}{\dots}\}$ 1 TEXT OPT 2 CONTENT
$\backslash\text{autodirvtop}$ $\overset{1}{\dots}$ $\{\overset{2}{\dots}\}$ 1 TEXT OPT 2 CONTENT
$\backslash\text{autoinsertnextspace}$
$\backslash\text{autointegral}$ $\{\overset{1}{\dots}\}$ $\{\overset{2}{\dots}\}$ $\{\overset{3}{\dots}\}$ 1 TEXT 2 TEXT 3 TEXT
$\backslash\text{automathematics}$ $\{\dots\}$ * CONTENT
$\backslash\text{autosetups}$ $\{\dots,*,\dots\}$ * NAME
$\backslash\text{autostarttext}$... $\backslash\text{autostoptext}$
$\backslash\text{availablehsize}$
$\backslash\text{averagecharwidth}$
$\backslash\text{BeforePar}$ $\{\dots\}$ * BEFEHL
$\backslash\text{Big}$... * CHARACTER
$\backslash\text{Bigg}$... * CHARACTER
$\backslash\text{Biggl}$... * CHARACTER
$\backslash\text{Biggm}$... * CHARACTER
$\backslash\text{Biggr}$... * CHARACTER
$\backslash\text{Bigl}$... * CHARACTER
$\backslash\text{Bigm}$... * CHARACTER
$\backslash\text{Bigr}$... * CHARACTER

`\backgroundimage {...} {...} {...} {...}`

1 NUMBER
2 DIMENSION
3 DIMENSION
4 BEFEHL

`\backgroundimagefill {...} {...} {...} {...}`

1 NUMBER
2 DIMENSION
3 DIMENSION
4 BEFEHL

`\backgroundline [...] {...}`

1 COLOR
2 CONTENT

`\bar {...}`

* CHARACTER

`\barevnaalista [...*,...]`

* COLOR

`\barva [...] {...}`

1 COLOR
2 CONTENT

`\BAR {...}`

* CONTENT

instances: overbar underbar overstrike understrike overbars underbars overstrikes understrikes
underrandom underrandoms underdash underdashes underdot underdots nobar hiddenbar

`\hiddenbar {...}`

* CONTENT

`\nobar {...}`

* CONTENT

`\overbar {...}`

* CONTENT

`\overbars {...}`

* CONTENT

`\overstrike {...}`

* CONTENT

`\overstrikes {...}`

* CONTENT

`\underbar {...}`

* CONTENT

`\underbars {...}`

* CONTENT

`\underdash {...}`

* CONTENT

<code>\underdashes {...}</code> * CONTENT
<code>\underdot {...}</code> * CONTENT
<code>\underdots {...}</code> * CONTENT
<code>\underrandom {...}</code> * CONTENT
<code>\underrandoms {...}</code> * CONTENT
<code>\understrike {...}</code> * CONTENT
<code>\understrikes {...}</code> * CONTENT
<code>\basegrid [...,...[*]...,...]</code> * nx = NUMMER * ny = NUMMER * dx = NUMMER * dy = NUMMER * faktor = NUMMER * meritko = NUMMER * xkrok = NUMMER * ykrok = NUMMER * offset = DIMENSION * xoffset = DIMENSION * yoffset = DIMENSION * zarovnani = nastred * jednotka = cm mm in pc pt bp * pismo = STYLE BEFEHL * barva = COLOR
<code>\baselinebottom</code>
<code>\baselineleftbox {...}</code> * CONTENT
<code>\baselinemiddlebox {...}</code> * CONTENT
<code>\baselinerightbox {...}</code> * CONTENT
<code>\bbordermatrix {...}</code> * CONTENT
<code>\bbox {...}</code> * CONTENT
<code>\beforesplitstring ¹... \at ²... \to ³...</code> 1 TEXT 2 TEXT 3 CSNAME

<pre> \beforetestandsplitstring ¹... \at ²... \to ³... 1 TEXT 2 TEXT 3 CSNAME </pre>
<pre> \beginBLOCK [...[*]...] ... \endBLOCK * + - NAME ^{OPT} </pre>
<pre> \beginhbox ... \endhbox </pre>
<pre> \beginofshapebox ... \endofshapebox </pre>
<pre> \beginvbox ... \endvbox </pre>
<pre> \beginvtop ... \endvtop </pre>
<pre> \begstrut ... \endstrut </pre>
<pre> \bezserifu </pre>
<pre> \bigbodyfont </pre>
<pre> \bigg [*]... * CHARACTER </pre>
<pre> \bigger </pre>
<pre> \biggl [*]... * CHARACTER </pre>
<pre> \biggm [*]... * CHARACTER </pre>
<pre> \biggr [*]... * CHARACTER </pre>
<pre> \bigl [*]... * CHARACTER </pre>
<pre> \bigm [*]... * CHARACTER </pre>
<pre> \bigR [*]... * CHARACTER </pre>
<pre> \bigskip </pre>
<pre> \bitmapimage [...¹...] {²...} 1 barva = rgb cmyk seda sirka = DIMENSION vyska = DIMENSION x = NUMMER y = NUMMER 2 NUMMER </pre>
<pre> \blap {[*]...} * CONTENT </pre>

<code>\bleed [...,¹...,...]{...}</code> 1 inherits: \setupbleeding 2 CONTENT
<code>\bleedheight</code>
<code>\bleedwidth</code>
<code>\blockligatures [...,*...]</code> * TEXT
<code>\blocksynctexfile [...,*...]</code> * FILE
<code>\bodyfontenvironmentlist</code>
<code>\bodyfontsize</code>
<code>\boldface</code>
<code>\booleanmodevalue {...}</code> * NAME
<code>\bordermatrix {...}</code> * CONTENT
<code>\bottombox {...}</code> * CONTENT
<code>\bottomleftbox {...}</code> * CONTENT
<code>\bottomrightbox {...}</code> * CONTENT
<code>\boxcursor</code>
<code>\boxmarker {...¹}{...²}</code> 1 NAME 2 NUMMER
<code>\boxofsize \...¹...²...³{...}</code> 1 CSNAME OPT 2 DIMENSION 3 CONTENT
<code>\boxreference [...,¹...]\...²{...³}</code> 1 REFERENCE 2 CSNAME 3 CONTENT
<code>\bpar ... \epar</code>
<code>\bpos {...}</code> * NAME
<code>\breakhere</code>

<code>\breve {...}</code> * CHARACTER
<code>\bTABLE [...,.*,...] ... \eTABLE</code> * inherits: \setupTABLE
<code>\bTABLEbody [...,.*,...] ... \eTABLEbody</code> * inherits: \setupTABLE
<code>\bTABLEfoot [...,.*,...] ... \eTABLEfoot</code> * inherits: \setupTABLE
<code>\bTABLEhead [...,.*,...] ... \eTABLEhead</code> * inherits: \setupTABLE
<code>\bTABLEnext [...,.*,...] ... \eTABLEnext</code> * inherits: \setupTABLE
<code>\bTC [...,.*,...] ... \eTC</code> * inherits: \PBD
<code>\bTD [...,.*,...] ... \eTD</code> * nx = NUMBER ny = NUMBER nc = NUMBER nr = NUMBER n = NUMBER m = NUMBER akce = REFERENCE inherits: \setupTABLE
<code>\bTDs [...] ... \eTDs</code> * NAME
<code>\bTH [...,.*,...] ... \eTH</code> * inherits: \PBD
<code>\bTN [...,.*,...] ... \eTN</code> * inherits: \PBD
<code>\bTR [...,.*,...] ... \eTR</code> * inherits: \PBD\setupTABLE
<code>\bTRs [...] ... \eTRs</code> * NAME
<code>\bTX [...,.*,...] ... \eTX</code> * inherits: \PBD
<code>\bTY [...,.*,...] ... \eTY</code> * inherits: \PBD\setupTABLE
<code>\btxabbreviatedjournal {...}</code> * NAME
<code>\btxaddjournal [...] [...]</code> 1 NAME 2 NAME

\btxalwayscitation [...¹...²...] [...]

```
1 odkaz      = REFERENCE OPT
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
               authornum authoryear
  pred        = BEFEHL
  po          = BEFEHL
  vlevo       = BEFEHL
  vpravo      = BEFEHL
  inherits: \setupbtx
2 REFERENCE
```

\btxalwayscitation [...¹...] [...²...]

```
1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear
2 REFERENCE
```

\btxalwayscitation [...¹...²...] [...²...¹...]

```
1 odkaz      = REFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
               authornum authoryear
  pred        = BEFEHL
  po          = BEFEHL
  vlevo       = BEFEHL
  vpravo      = BEFEHL
  inherits: \setupbtx
2 KEY = VALUE
```

\btxauthorfield {...}

* initials firstnames vons surnames juniors

\btxdetail {...}

* address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language
mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok
yearfiled NAME

\btxdirect {...}

* address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language
mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok
yearfiled NAME

\btxdoif {...} {...}

```
1 address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language
  mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok
  yearfiled NAME
2 TRUE
```

\btxdoifcombiinlistelse {...} {...} {...} {...}

```
1 NAME
2 NAME
3 TRUE
4 FALSE
```

\btxdoifelse {...} {...} {...}

```
1 address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language
  mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok
  yearfiled NAME
2 TRUE
3 FALSE
```

\btxdoifelsecombiinlist {...} {...} {...} {...}

```
1 NAME
2 NAME
3 TRUE
4 FALSE
```


\btxdfelselfsameasprevious {...} {...} {...}

1 address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language
mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok
yearfiled NAME
2 TRUE
3 FALSE

\btxdfelselfsameaspreviouschecked {...} {...} {...} {...}

1 vzdy dvoustranny
2 address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language
mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok
yearfiled NAME
3 TRUE
4 FALSE

\btxdfelselfuservariable {...} {...} {...}

1 KEY
2 TRUE
3 FALSE

\btxdfifnot {...} {...}

1 address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language
mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok
yearfiled NAME
2 TRUE

\btxdfifselfsameaspreviouselse {...} {...} {...}

1 address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language
mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok
yearfiled NAME
2 TRUE
3 FALSE

\btxdfifselfsameaspreviouscheckedelse {...} {...} {...} {...}

1 vzdy dvoustranny
2 address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language
mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok
yearfiled NAME
3 TRUE
4 FALSE

\btxdfifuservariableelse {...} {...} {...}

1 KEY
2 TRUE
3 FALSE

\btlexpandedjournal {...}

* NAME

\btxfielf {...}

* address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language
mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok
yearfiled NAME

\btxfielfname {...}

* address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language
mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok
yearfiled NAME

\btxfielftype {...}

* address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language
mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok
yearfiled NAME

\btxfirstofrange {...}

* volume pages

<p><code>\btxflush {...}</code></p> <p>* address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME</p>
<p><code>\btxflushauthor [...¹] {...²}</code></p> <p>1 num normalni normalshort inverted invertedshort</p> <p>2 autor editor</p>
<p><code>\btxflushauthorinverted {...}</code></p> <p>* autor editor</p>
<p><code>\btxflushauthorinvertedshort {...}</code></p> <p>* autor editor</p>
<p><code>\btxflushauthorname {...}</code></p> <p>* autor editor</p>
<p><code>\btxflushauthornormal {...}</code></p> <p>* autor editor</p>
<p><code>\btxflushauthornormalshort {...}</code></p> <p>* autor editor</p>
<p><code>\btxflushsuffix</code></p>
<p><code>\btxfoundname {...}</code></p> <p>* address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME</p>
<p><code>\btxfoundtype {...}</code></p> <p>* address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME</p>
<p><code>\btxhiddencitation [...]</code></p> <p>* REFERENCE</p>
<p><code>\btxhybridcite [...¹...²] [...]</code></p> <p>1 odkaz = REFERENCE</p> <p>alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear</p> <p>pred = BEFEHL</p> <p>po = BEFEHL</p> <p>vlevo = BEFEHL</p> <p>vpravo = BEFEHL</p> <p>inherits: \setupbtx</p> <p>2 REFERENCE</p>
<p><code>\btxhybridcite [...¹] [...²]</code></p> <p>1 implicitni category^{opt} entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear</p> <p>2 REFERENCE</p>
<p><code>\btxhybridcite {...}</code></p> <p>* REFERENCE</p>

\btxhybridcite [...¹...] [...²...]

```
1 odkaz      = REFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
               authornum authoryear
  pred        = BEFEHL
  po          = BEFEHL
  vlevo       = BEFEHL
  vpravo      = BEFEHL
  inherits: \setupbtx
2 KEY = VALUE
```

\btxlistcitation [...¹...] [...²...]

```
1 odkaz      = REFERENCEOPT
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
               authornum authoryear
  pred        = BEFEHL
  po          = BEFEHL
  vlevo       = BEFEHL
  vpravo      = BEFEHL
  inherits: \setupbtx
2 REFERENCE
```

\btxlistcitation [...¹...] [...²...]

```
1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear
2 REFERENCE
```

\btxlistcitation [...¹...] [...²...]

```
1 odkaz      = REFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
               authornum authoryear
  pred        = BEFEHL
  po          = BEFEHL
  vlevo       = BEFEHL
  vpravo      = BEFEHL
  inherits: \setupbtx
2 KEY = VALUE
```

\btxloadjournalist [...]

* FILE

\btxoneorrange {...} {...} {...}

```
1 volume pages
2 TRUE
3 FALSE
```

\btxremapauthor [...¹] [...²...]

```
1 TEXT
2 TEXT
```

\btxsavejournalist [...]

* FILE

\btxsetup {...}

* NAME

\btxsingularorplural {...} {...} {...}

```
1 editor producer director
2 TRUE
3 FALSE
```

\btxsingularplural {...} {...} {...}

```
1 editor producer director
2 TRUE
3 FALSE
```

\btxttextcitation [...¹...²...] [...]

```
1 odkaz      = REFERENCEOPT
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
               authornum authoryear
  pred        = BEFEHL
  po          = BEFEHL
  vlevo       = BEFEHL
  vpravo      = BEFEHL
  inherits: \setupbtx
2 REFERENCE
```

\btxttextcitation [...¹...] [...]

```
1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear
2 REFERENCE
```

\btxttextcitation [...¹...²...] [...²...²...]

```
1 odkaz      = REFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
               authornum authoryear
  pred        = BEFEHL
  po          = BEFEHL
  vlevo       = BEFEHL
  vpravo      = BEFEHL
  inherits: \setupbtx
2 KEY = VALUE
```

\TOOLTIP [...¹...²...] {...} {...}

```
1 inherits: \setupOPTtooltip
2 TEXT
3 TEXT
instances: tooltip
```

\TOOLTIP [...¹...] {...} {...}

```
1 vlevo nastOPTřed vpravo
2 TEXT
3 TEXT
instances: tooltip
```

\tooltip [...¹...] {...} {...}

```
1 vlevo nastOPTřed vpravo
2 TEXT
3 TEXT
```

\tooltip [...¹...²...] {...} {...}

```
1 inherits: \setupOPTtooltip
2 TEXT
3 TEXT
```

\buildmathaccent {...} {...}

```
1 CHARACTER
2 CHARACTER
```

\buildtextaccent {...} {...}

```
1 CHARACTER
2 CHARACTER
```

\buildtextbottomcomma {...}

```
* CHARACTER
```

\buildtextbottomdot {...}

```
* CHARACTER
```

\buildtextcedilla {...}

```
* CHARACTER
```

<code>\buildtextgrave {...}</code> * CHARACTER
<code>\buildtextmacron {...}</code> * CHARACTER
<code>\buildtextognek {...}</code> * CHARACTER
<code>\Caps {...}</code> * TEXT
<code>\Cisla {...}</code> * NUMMER
<code>\CONTEXT</code>
<code>\ConTeXt</code>
<code>\Context</code>
<code>\ConvertConstantAfter \.¹ {...} {³...}</code> 1 CSNAME 2 TEXT 3 TEXT
<code>\ConvertToConstant \.¹ {...} {³...}</code> 1 CSNAME 2 TEXT 3 TEXT
<code>\camel {...}</code> * TEXT
<code>\catcodetablename</code>
<code>\cbox .¹ {...}</code> 1 TEXT <small>OPT</small> 2 CONTENT
<code>\centraligned {...}</code> * CONTENT
<code>\centerbox .¹ {...}</code> 1 TEXT <small>OPT</small> 2 CONTENT
<code>\centeredbox .¹ {...}</code> 1 TEXT <small>OPT</small> 2 CONTENT
<code>\centeredlastline</code>
<code>\centerednextbox .¹ {...}</code> 1 TEXT <small>OPT</small> 2 CONTENT

<pre> \centerline {...} * CONTENT </pre>
<pre> \cernalinka [...,.*=...,...] * inherits: \nastavce^{OPT}helinky </pre>
<pre> \cernelinky [...,.*=...,...] * inherits: \nastavce^{OPT}helinky </pre>
<pre> \cfrac [...¹.] {...} {...³.} 1 l c r l^{PT}lc lr cl cc cr rl rc rr 2 CONTENT 3 CONTENT </pre>
<pre> \cisla {...} * NUMMER </pre>
<pre> \cislondpisu [...¹.] [...².] 1 ABSCHNITT^{OPT} 2 predchozi aktualni dalsi prvni posledni </pre>
<pre> \cislornice [...,*=...,...] * REFERENCE^{OPT} </pre>
<pre> \cislostrany </pre>
<pre> \citation [...,.*¹=...,...] [...².] 1 odkaz = REFERENCE alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear pred = BEFEHL po = BEFEHL vlevo = BEFEHL vpravo = BEFEHL inherits: \setupbtx 2 REFERENCE </pre>
<pre> \citation [...¹.] [...².] 1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear 2 REFERENCE </pre>
<pre> \citation {...} * REFERENCE </pre>
<pre> \citation [...,.*¹=...,...] [...,.*²=...,...] 1 odkaz = REFERENCE alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear pred = BEFEHL po = BEFEHL vlevo = BEFEHL vpravo = BEFEHL inherits: \setupbtx 2 KEY = VALUE </pre>
<pre> \cite [...,.*¹=...,...] [...².] 1 odkaz^{OPT} = REFERENCE alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear pred = BEFEHL po = BEFEHL vlevo = BEFEHL vpravo = BEFEHL inherits: \setupbtx 2 REFERENCE </pre>

<code>\cite [...]¹ [...]²</code> 1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear 2 REFERENCE
<code>\cite {...}</code> * REFERENCE
<code>\cite [...]¹ [...]² [...]³ [...]⁴</code> 1 odkaz = REFERENCE alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear pred = BEFEHL po = BEFEHL vlevo = BEFEHL vpravo = BEFEHL inherits: \setupbtx 2 KEY = VALUE
<code>\clap {...}</code> * CONTENT
<code>\classfont {...}¹ {...}²</code> 1 NAME 2 FONT
<code>\cldcommand {...}</code> * BEFEHL
<code>\cldcontext {...}</code> * BEFEHL
<code>\cldloadfile {...}</code> * FILE
<code>\cldprocessfile {...}</code> * FILE
<code>\collect {...}</code> * CONTENT
<code>\collectedtext [...]¹ [...]² {...}³ {...}⁴</code> 1 inherits: \setupcollect ^{OPT} 2 pismo = STYLE BEFEHL barva = COLOR inherits: \nastavoramovani 3 TEXT 4 CONTENT
<code>\collectexpanded {...}</code> * CONTENT
<code>\colorcomponents {...}</code> * COLOR
<code>\colored [...]¹ {...}²</code> 1 inherits: \definujbarvu 2 CONTENT
<code>\colored [...]¹ {...}²</code> 1 COLOR 2 CONTENT

<code>\coloronly [...]¹ {...}²</code> 1 COLOR 2 CONTENT
<code>\columnbreak [...][*]...</code> * ano ne nastaveni ^{OPT} lokalne sila prvni posledni NUMBER NAME
<code>\combinepages [...]¹ [...]²...</code> 1 FILE ^{OPT} 2 alternativa = a b c horizontalne vertikalne n = NUMMER nx = NUMMER ny = NUMMER start = NUMMER stop = NUMMER vzdalenost = DIMENSION vrsek = BEFEHL spodek = BEFEHL vlevo = BEFEHL vpravo = BEFEHL pred = BEFEHL po = BEFEHL mezi = BEFEHL ramecek = zap vyp pozadi = popredi barevne NAME barvapozadi = COLOR
<code>\commalistelement</code>
<code>\commalistsentence [...]¹ [...]²...</code> 1 TEXT ^{OPT} 2 TEXT
<code>\commalistsize</code>
<code>\comparedimension {...}¹ {...}²</code> 1 DIMENSION 2 DIMENSION
<code>\comparedimensioneps {...}¹ {...}²</code> 1 DIMENSION 2 DIMENSION
<code>\completebtxrendering [...]¹ [...]²...</code> 1 NAME ^{OPT} ^{OPT} 2 inherits: \setupbtxrendering
<code>\uplnyCOMBINEDLIST [...][*]...</code> * inherits: \nastavseznam ^{OPT} instances: content
<code>\uplnycontent [...][*]...</code> * inherits: \nastavseznam ^{OPT}
<code>\completelist [...]¹ [...]²...</code> 1 LISTE ^{OPT} 2 inherits: \nastavseznam
<code>\completelistofFLOATS [...][*]...</code> * inherits: \nastavseznam ^{OPT} instances: chemicals figures tables intermezzi graphics
<code>\completelistoffigures [...][*]...</code> * inherits: \nastavseznam ^{OPT}

$\backslash\text{completelistofgraphics}$ [...,.. [*] ...,...] * inherits: \nastavseznam ^{OPT}
$\backslash\text{completelistofchemicals}$ [...,.. [*] ...,...] * inherits: \nastavseznam ^{OPT}
$\backslash\text{completelistofintermezzi}$ [...,.. [*] ...,...] * inherits: \nastavseznam ^{OPT}
$\backslash\text{completelistoftables}$ [...,.. [*] ...,...] * inherits: \nastavseznam ^{OPT}
$\backslash\text{completelistofpublications}$ [... ¹ .] [...,.. ² ...,...] 1 NAME ^{OPT} ^{OPT} 2 inherits: \setupbtxrendering
$\backslash\text{completelistofsorts}$ [... ¹ .] [...,.. ² ...,...] 1 SINGULAR ^{OPT} 2 inherits: \nastavtrideni
$\backslash\text{completelistofSORTS}$ [...,.. [*] ...,...] * inherits: \nastavtrideni ^{OPT} instances: logos
$\backslash\text{completelistoflogos}$ [...,.. [*] ...,...] * inherits: \nastavtrideni ^{OPT}
$\backslash\text{completelistofsynonyms}$ [... ¹ .] [...,.. ² ...,...] 1 SINGULAR ^{OPT} 2 inherits: \nastavsynonyma
$\backslash\text{completelistofSYNONYMS}$ [...,.. [*] ...,...] * inherits: \nastavsynonyma ^{OPT} instances: abbreviations
$\backslash\text{completelistofabbreviations}$ [...,.. [*] ...,...] * inherits: \nastavsynonyma ^{OPT}
$\backslash\text{completepagenumber}$
$\backslash\text{completeregister}$ [... ¹ .] [...,.. ² ...,...] 1 NAME ^{OPT} 2 inherits: \nastavrejstrik
$\backslash\text{uplNyREGISTER}$ [...,.. [*] ...,...] * inherits: \nastavrejstrik ^{OPT} instances: index
$\backslash\text{uplNyindex}$ [...,.. [*] ...,...] * inherits: \nastavrejstrik ^{OPT}
$\backslash\text{complexorsimple}$ *.. * CSNAME
$\backslash\text{complexorsimpleempty}$ *.. * CSNAME

\complexorsimpleempty {...} * TEXT CSNAME
\complexorsimple {...} * TEXT CSNAME
\composedcollector {...} * NAME
\composedlayer {...} * NAME
\compresult
\constantdimen \... * CSNAME
\constantdimenargument \... * CSNAME
\constantemptyargument \... * CSNAME
\constantnumber \... * CSNAME
\constantnumberargument \... * CSNAME
\contentreference [... ¹ ,...] [... ² ,... ² ,...] {... ³ } 1 REFERENCE 2 inherits: \nastavoramovani 3 CONTENT
\continuednumber {...} * NUMMER
\continueifinputfile {...} * FILE
\convertargument ... ¹ \to ... ² 1 TEXT 2 CSNAME
\convertcommand \... ¹ \to ... ² 1 CSNAME 2 CSNAME
\convertedcounter [... ¹] [... ² ,... ² ,...] 1 NAME 2 inherits: \setupcounter
\converteddimen {... ¹ } {... ² } 1 DIMENSION 2 ex em pt in cm mm sp bp pc dd cc nc

$\backslash\text{convertedsubcounter}$ [¹ ...] [² ...] [³ ... _{...} ...] 1 NAME OPT OPT 2 NUMBER NUMBER:NUMBER NUMBER:* NUMBER:vse 3 inherits: \setupcounter
$\backslash\text{convertmonth}$ {...} * NUMBER
$\backslash\text{convertvalue}$... \to \ ² ... 1 NAME 2 CSNAME
$\backslash\text{convertvboxtohbox}$
$\backslash\text{copyboxfromcache}$ {...} {...} ... ³ 1 NAME 2 NUMBER TEXT 3 CSNAME NUMBER
$\backslash\text{copyLABELtext}$ [¹ ...] [... _{...} ...] ² 1 SPRACHE OPT 2 KEY = KEY instances: head label mathlabel taglabel unit operator prefix suffix btxlabel
$\backslash\text{copybtxlabeltext}$ [¹ ...] [... _{...} ...] ² 1 SPRACHE OPT 2 KEY = KEY
$\backslash\text{copyheadtext}$ [¹ ...] [... _{...} ...] ² 1 SPRACHE OPT 2 KEY = KEY
$\backslash\text{copylabeltext}$ [¹ ...] [... _{...} ...] ² 1 SPRACHE OPT 2 KEY = KEY
$\backslash\text{copymathlabeltext}$ [¹ ...] [... _{...} ...] ² 1 SPRACHE OPT 2 KEY = KEY
$\backslash\text{copyoperatortext}$ [¹ ...] [... _{...} ...] ² 1 SPRACHE OPT 2 KEY = KEY
$\backslash\text{copyprefixtext}$ [¹ ...] [... _{...} ...] ² 1 SPRACHE OPT 2 KEY = KEY
$\backslash\text{copysuffixtext}$ [¹ ...] [... _{...} ...] ² 1 SPRACHE OPT 2 KEY = KEY
$\backslash\text{copytaglabeltext}$ [¹ ...] [... _{...} ...] ² 1 SPRACHE OPT 2 KEY = KEY
$\backslash\text{copyunittext}$ [¹ ...] [... _{...} ...] ² 1 SPRACHE OPT 2 KEY = KEY

$\backslash\text{copypages}$ [¹ ...] [² ... _{OPT} ...] [³ ... _{OPT} ...] 1 FILE 2 $\text{znaceni} = \text{zap vyp}$ $\text{offset} = \text{DIMENSION}$ $n = \text{NUMMER}$ 3 $\text{inherits: \setupexternalfigure}$
$\backslash\text{copyparameters}$ [¹] [²] [³ ...] 1 TEXT 2 TEXT 3 KEY
$\backslash\text{copyposition}$ { ¹ } { ² } 1 NAME 2 NAME
$\backslash\text{countersubs}$ [¹] [² ...] 1 NAME 2 NUMBER
$\backslash\text{counttoken}$ ¹ ... \in ² ... \to \sup{3}... 1 TEXT 2 TEXT 3 CSNAME
$\backslash\text{counttokens}$ ¹ ... \to \sup{2}... 1 TEXT 2 CSNAME
$\backslash\text{cramped}$ { [*] } * CONTENT
$\backslash\text{crampedclap}$ { [*] } * CONTENT
$\backslash\text{crampedllap}$ { [*] } * CONTENT
$\backslash\text{crampedrlap}$ { [*] } * CONTENT
$\backslash\text{ctop}$ ¹ ... { ² } 1 TEXT _{OPT} 2 CONTENT
$\backslash\text{ctxcommand}$ { [*] } * BEFEHL
$\backslash\text{ctxdirectcommand}$ { [*] } * BEFEHL
$\backslash\text{ctxdirectlua}$ { [*] } * BEFEHL
$\backslash\text{ctxfunction}$ { [*] } * NAME
$\backslash\text{CTXFUNCTIONDEFINITION}$
$\backslash\text{CTXFUNCTION}$

\ctxlatecommand {...} * BEFEHL
\ctxlatelua {...} * BEFEHL
\ctxloadluafile {...} * FILE
\ctxlua {...} * BEFEHL
\ctxluabuffer [...] {...} * BUFFER OPT
\ctxluacode {...} * BEFEHL
\ctxreport {...} * BEFEHL
\ctxsprint {...} * BEFEHL
\currentassignmentlistkey
\currentassignmentlistvalue
\currentbtxuservariable {...} * KEY
\currentcommalistitem
\currentcomponent
\currentenvironment
\currentfeaturetest
\currentinterface
\currentPOPISEK [... ¹ ,... ²] {...} 1 REFERENCE OPT OPT 2 TEXT
\currentlanguage
\currentlistentrydestinationattribute
\currentlistentrylimitedtext {...} * TEXT
\currentlistentrynumber
\currentlistentrypagenumber

\currentlistentryreferenceattribute {...} * cislo text cislostranky vse
\currentlistentrytitle
\currentlistentrytitlerendered
\currentlistsymbol
\currentmainlanguage
\currentmessagetext
\currentmoduleparameter {...} * KEY
\currentoutputstream
\currentproduct
\currentproject
\currentregime
\currentregisterpageuserdata {...} * KEY
\currentresponses
\currenttime [...,*,...] * h m TEXT OPT
\currentvalue
\currentxtablecolumn
\currentxtablerow
\d {...} * CHARACTER
\dalsipodstranka
\datasetvariable {... ¹ } {... ² } {... ³ } 1 NAME 2 NAME NUMMER 3 KEY realpage
\datum [...,* ¹ ...,* ² ...] [...,* ² ...] 1 d = NUMMER OPT OPT m = NUMMER y = NUMMER 2 inherits: \aktualnidatum

1	NUMMER
2	NUMMER
3	NUMMER

1	NUMMER
2	NUMMER

* CHARACTER

* CHARACTER

* CSNAME

1	NAME	OPT
2	NUMMER	

* NAME

* NAME

* CSNAME NUMMER

```

1  CSNAME
2  CHARACTER NUMMER
3  BEFEHL

```

```

1 CSNAME
2 TEXT

```

```

1  CSNAME
2  CSNAME

```

```

1  CSNAME
2  NAME

```

\defineactivecharacter ¹... {²...}

- 1 CHARACTER
- 2 BEFEHL

\definealternativestyle [...,¹...] [²...] [³...]

- 1 NAME
- 2 BEFEHL
- 3 BEFEHL

\defineanchor [¹...] [²...] [...,³...,...] [...,⁴...,...]

- 1 NAME
- 2 NAME
- 3 inherits: \setuplayer
- 4 inherits: \setuplayerinherits: \nastavoramovani

\defineattachment [¹...] [²...] [...,³...,...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupattachment

\defineattribute [¹...] [...,²...]

- 1 NAME
- 2 lokalne globalne public private

\definebackground [¹...] [²...] [...,³...,...]

- 1 NAME
- 2 NAME
- 3 inherits: \nastavpozadi

\definebar [¹...] [²...] [...,³...,...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupbar

\definebodyfontswitch [¹...] [...,²...]

- 1 NAME
- 2 inherits: \nastavzakladnifont

\definebreakpoint [¹...] [²...] [...,³...,...]

- 1 NAME
- 2 CHARACTER
- 3 typ = 1 2 3 4 5
- nvlevo = NUMMER
- nvpravo = NUMMER
- vlevo = BEFEHL
- stredni = BEFEHL
- vpravo = BEFEHL
- range = ano ne
- language = SPRACHE

\definebreakpoints [...]

- * NAME

\definebtx [¹...] [²...] [...,³...,...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupbtx

\definebtxdataset [¹...] [²...] [...,³...,...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupbtxdataset


```
\definebtxregister [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupbtxregister
```

```
\definebtxrendering [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupbtxrendering
```

```
\definebutton [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupbutton
```

```
\definecapitals [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \nastavkapitaly
```

```
\definecollector [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupcollector
```

```
\definecolumnbreak [...] [...]
1 NAME
2 ano ne nastaveni lokalne sila prvni posledni NUMMER
```

```
\definecombination [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupcombination
```

```
\definecomment [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \nastavkomentar
```

```
\definecomplexorsimple \*...
* CSNAME
```

```
\definecomplexorsimpleempty \*...
* CSNAME
```

```
\definecomplexorsimpleempty {...}
* TEXT CSNAME
```

```
\definecomplexorsimple {...}
* TEXT CSNAME
```

```
\defineconversionset [...] [...] [...]
1 NAME SECTIONBLOCK:NAME OPT
2 NAME PROCESSOR->NAME
3 NAME PROCESSOR->NAME
```

```
\definecounter [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupcounter
```

`\definedataset [...]1 [...]2 [...,...3...,...]`

1 NAME
2 NAME
3 inherits: \setupdataset

`\definedelimitedtext [...]1 [...]2 [...,...3...,...]`

1 NAME
2 NAME
3 inherits: \setupdelimitedtext

`\definedfont [...]*`

* FONT OPT

`\defineeffect [...]1 [...]2 [...,...3...,...]`

1 NAME
2 NAME
3 inherits: \setupeffect

`\defineexpandable [...]1 [...]2 {...}3`

1 NUMBER
2 CSNAME
3 CONTENT

`\defineexternalfigure [...]1 [...]2 [...,...3...,...]`

1 NAME
2 NAME
3 inherits: \setuexternalfigure

`\definefallbackfamily [...]1 [...]2 [...]3 [...,...4...,...]`

1 NAME
2 rm ss tt mm hw cg antikva serif pravidelne bezserifu sans podpora strojopis opis mono rukopisne kaligraficke math matematika
3 FONT
4 rscale = NUMBER
designsize = implicitni auto
goodies = FILE
range = NUMBER NAME
offset = NUMBER NAME
check = ano ne
sila = ano ne
features = NAME
tf = TEXT
bf = TEXT
it = TEXT
sl = TEXT
bi = TEXT
bs = TEXT
sc = TEXT

`\definefallbackfamily [...]1 [...]2 [...]3 [...,...4...,...]`

1 NAME
2 rm ss tt mm hw cg antikva serif pravidelne bezserifu sans podpora strojopis opis mono rukopisne kaligraficke math matematika
3 FONT
4 NAME

`\definefielddbody [...]1 [...]2 [...,...3...,...]`

1 NAME
2 NAME
3 inherits: \setupfielddbody

`\definefielddbodyset [...]1 [...]2,...]`

1 NAME
2 NAME

<pre> \definefieldcategory [...] [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setupfieldcategory </pre>
<pre> \definefileconstant {...} {...} 1 NAME 2 NAME </pre>
<pre> \definefilefallback [...] [...] 1 NAME 2 FILE </pre>
<pre> \definefilesynonym [...] [...] 1 NAME 2 FILE </pre>
<pre> \definefiller [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setupfiller </pre>
<pre> \definefirstline [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setupfirstline </pre>
<pre> \definefittingpage [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setupfittingpage </pre>
<pre> \definefontalternative [...] * NAME </pre>
<pre> \definefontfallback [...] [...] [...] [...] 1 NAME 2 FONT NAME 3 NAME NUMMER 4 rscale = NUMMER sila = ano ne check = ano ne offset = NUMMER NAME features = NAME faktor = NUMMER </pre>
<pre> \definefontfamily [...] [...] [...] [...] 1 NAME 2 rm ss tt mm hw cg antikva serif pravidelne bezserifu sans podpora strojopis opis mono rukopisne kaligraficke math matematika 3 FONT 4 rscale = NUMMER designsize = implicitni auto goodies = FILE features = NAME tf = TEXT bf = TEXT it = TEXT sl = TEXT bi = TEXT bs = TEXT sc = TEXT </pre>
<pre> \definefontfamilypreset [...] [...] 1 NAME 2 inherits: \definefontfamily </pre>

```
\definefontfamilypreset [...]1 [...]2
```

```
1 NAME
2 NAME
```

```
\definefontfamily [...]1 [...]2 [...]3 [...]4,...]
```

```
1 NAME OPT
2 rm ss tt mm hw cg antikva serif pravidelne bezserifu sans podpora strojopis opis mono rukopisne kaligraficke math
  matematika
3 FONT
4 NAME
```

```
\definefontfeature [...]1 [...]2 [...]3,...]
```

```
1 NAME OPT
2 NAME
3 language = NAME
  script = NAME auto
  mode = node base auto zadny
  liga = ano ne
  kern = ano ne
  extrakerns = ano ne
  tlig = ano ne
  trep = ano ne
  missing = ano ne
  dummies = ano ne
  analyze = ano ne
  unicoding = ano ne
  expanzen = NAME
  protrusion = NAME
  nostackmath = ano ne
  realdimensions = ano ne
  itlc = ano ne
  textitalics = ano ne
  mathitalics = ano ne
  slant = NUMMER
  extend = NUMMER
  dimensions = NUMMER
  boundingbox = ano ne pozadi ramecek prazdne COLOR
  compose = ano ne
  char-ligatures = ano ne
  compat-ligatures = ano ne
  goodies = FILE
  extrafeatures = ano ne
  featureset = NAME
  colorscheme = NAME
  postprocessor = NAME
  mathdimensions = NAME
  keepligatures = ano ne auto
  devanagari = ano ne
  features = ano ne
  tcom = ano ne
  anum = ano ne
  mathsize = ano ne
  decomposehangul = ano ne
  mathalternatives = ano ne
  mathgaps = ano ne
  checkmarks = ano ne
  NAME = ano ne
  mathnolimitsmode = NUMMER
  blockligatures = ano ne
```

```
\definefontfile [...]1 [...]2 [...]3,...]
```

```
1 NAME OPT
2 FILE
3 features = NAME
  fallbacks = NAME
  goodies = NAME
  designsize = auto implicitni
```

```
\definefontsize [...]
```

```
* NAME
```

```
\definefontsolution [...] [...2] [...,3...,...]
1 NAME
2 NAME
3 inherits: \setupfontsolution
```

```
\defineformula [...] [...2] [...,3...,...]
1 NAME
2 NAME
3 inherits: \setupformula
```

```
\defineformulaalternative [...] [...2] [...3]
1 NAME
2 CSNAME
3 CSNAME
```

```
\defineformulaframed [...] [...2] [...,3...,...]
1 NAME
2 NAME
3 inherits: \setupformulaframed
```

```
\defineframedcontent [...] [...2] [...,3...,...]
1 NAME
2 NAME
3 inherits: \setupframedcontent
```

```
\defineframedtable [...1] [...2]
1 NAME
2 NAME
```

```
\definefrozenfont [...1] [...2]
1 NAME
2 FONT
```

```
\defineglobalcolor [...1] [...,2...,...]
1 NAME
2 inherits: \definujbarvu
```

```
\defineglobalcolor [...1] [...2]
1 NAME
2 COLOR
```

```
\definegraphictypesynonym [...1] [...2]
1 NAME
2 NAME
```

```
\definegridsnapping [...1] [...,2...]
1 NAME
2 lokalne globalne noheight nodepth box max min zadny radek pulradku prvni posledni minvyska maxheight mindepth
maxdepth vrsek spodek strut NUMMER minheight:NUMMER maxheight:NUMMER mindepth:NUMMER maxdepth:NUMMER box:NUMMER
top:NUMMER bottom:NUMMER offset:NUMMER
```

```
\defineheadalternative [...1] [...2] [...,3...,...]
1 NAME
2 NAME
3 inherits: \setupheadalternative
```

```
\definehelp [...1] [...2] [...,3...,...]
1 NAME
2 NAME
3 inherits: \setuphelp
```

\definehigh [¹...] [²...] [³...₃...]

1 NAME OPT OPT
2 NAME
3 inherits: \setuphigh

\definehighlight [¹...] [²...] [³...₃...]

1 NAME OPT OPT
2 NAME
3 inherits: \setuphighlight

\definehspace [¹...] [²...] [³...]

1 NAME OPT
2 NAME
3 DIMENSION

\definehyphenationfeatures [¹...] [²...₂...]

1 NAME
2 characters = TEXT
hyphens = ano vse TEXT
joiners = ano vse TEXT
rightwords = NUMMER
hyphenmin = NUMMER
lefthyphenmin = NUMMER
righthyphenmin = NUMMER
lefthyphenchar = NUMMER
righthyphenchar = NUMMER
alternativa = original tex hyphenate expanded traditional zadny
pravahrana = tex
rightchars = slovo NUMMER

\definecharacterkerning [¹...] [²...] [³...₃...]

1 NAME OPT OPT
2 NAME
3 inherits: \setupcharacterkerning

\definecharacterspacing [...]

* NAME

\definechemical [¹...] {...}

1 NAME
2 CONTENT

\definechemicals [¹...] [²...] [³...₃...]

1 NAME OPT OPT
2 NAME
3 inherits: \setupchemical

\definechemicalsymbol [¹...] [²...]

1 NAME
2 TEXT

\defineindentedtext [¹...] [²...] [³...₃...]

1 NAME OPT OPT
2 NAME
3 inherits: \setupindentedtext

\defineindenting [¹...] [...²,...]

1 NAME
2 [-+]male [-+]stredni [-+]velke zadny ne ne prvni dalsi ano vzdy nikdy liche sude normalni reset toggle DIMENSION

\defineinitial [¹...] [²...] [³...₃...]

1 NAME OPT OPT
2 NAME
3 inherits: \setupinitial

<pre> \defineinsertion [¹...] [²...] [³...,...³...,...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupinsertion </pre>
<pre> \defineinteraction [¹...] [²...] [³...,...³...,...] 1 NAME OPT OPT 2 NAME 3 inherits: \nastavinterakci </pre>
<pre> \defineinteractionbar [¹...] [²...] [³...,...³...,...] 1 NAME OPT OPT 2 NAME 3 inherits: \nastavinterakcnilistu </pre>
<pre> \defineinterfaceconstant {¹...} {²...} 1 NAME 2 NAME </pre>
<pre> \defineinterfaceelement {¹...} {²...} 1 NAME 2 NAME </pre>
<pre> \defineinterfacevariable {¹...} {²...} 1 NAME 2 NAME </pre>
<pre> \defineinterlinespace [¹...] [²...] [³...,...³...,...] 1 NAME OPT OPT 2 NAME 3 inherits: \nastavmeziradkovoumezeru </pre>
<pre> \defineintermediatecolor [¹...] [²...,...²...] [³...,...³...,...] 1 NAME OPT OPT 2 COLOR NUMMER 3 a = NUMMER t = NUMMER </pre>
<pre> \defineitemgroup [¹...] [²...] [³...,...³...,...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupitemgroup </pre>
<pre> \defineitems [¹...] [²...] [³...,...³...,...] 1 NAME OPT OPT 2 NAME 3 inherits: \nastavpolozky </pre>
<pre> \definelabelclass [¹...] [²...] 1 NAME OPT 2 NUMMER </pre>
<pre> \definelayer [¹...] [²...] [³...,...³...,...] 1 NAME OPT OPT 2 NAME 3 inherits: \setuplayer </pre>
<pre> \definelayerpreset [¹...] [²...,...²...,...] 1 NAME 2 inherits: \setuplayer </pre>
<pre> \definelayerpreset [¹...] [²...] 1 NAME 2 NAME </pre>

\definelayout [¹...] [²...] [³...,...]

1 NAME OPT OPT
2 NAME
3 inherits: \nastavvzhled

\definelinefiller [¹...] [²...] [³...,...]

1 NAME OPT OPT
2 NAME
3 inherits: \setuplinefiller

\definelinenote [¹...] [²...] [³...,...]

1 NAME OPT OPT
2 NAME
3 inherits: \setuplinenote

\definelinenumbering [¹...] [²...] [³...,...]

1 NAME OPT OPT
2 NAME
3 inherits: \nastavcislovaniradku

\definelines [¹...] [²...] [³...,...]

1 NAME OPT OPT
2 NAME
3 inherits: \nastavradky

\definelistalternative [¹...] [²...] [³...,...]

1 NAME OPT OPT
2 NAME
3 inherits: \setuplistalternative

\definelistextra [¹...] [²...] [³...,...]

1 NAME OPT OPT
2 NAME
3 inherits: \setuplistextra

\definelow [¹...] [²...] [³...,...]

1 NAME OPT OPT
2 NAME
3 inherits: \setuplow

\definelowhigh [¹...] [²...] [³...,...]

1 NAME OPT OPT
2 NAME
3 inherits: \setuplowhigh

\definelowmidhigh [¹...] [²...] [³...,...]

1 NAME OPT OPT
2 NAME
3 inherits: \setuplowmidhigh

\defineMPinstance [¹...] [²...] [³...,...]

1 NAME OPT OPT
2 NAME
3 inherits: \setupMPinstance

\definemarginblock [¹...] [²...] [³...,...]

1 NAME OPT OPT
2 NAME
3 inherits: \setupmarginblock

\definemargindata [¹...] [²...] [³...,...]

1 NAME OPT OPT
2 NAME
3 inherits: \setupmargindata

\backslash definemarker [...] * NAME
\backslash definemathaccent ¹ ... ² ... 1 NAME 2 CHARACTER
\backslash definemathalignment [¹ ...] [² ...] [³ ... ³ ... ³ ...] 1 NAME 2 NAME 3 inherits: \setupmathalignment
\backslash definemathcases [¹ ...] [² ...] [³ ... ³ ... ³ ...] 1 NAME 2 NAME 3 inherits: \setupmathcases
\backslash definemathcommand [¹ ...] [² ...] [³ ...] { ⁴ ...} 1 NAME 2 ord op bin rel open close punct alpha uvnitr nothing limop nolog box 3 jedna dve 4 BEFEHL \...##1 \...##1##2
\backslash definemathdouble [¹ ...] [² ...] [³ ...] [⁴ ...] 1 obe vfenced NAME 2 NAME 3 NUMMER 4 NUMMER
\backslash definemathdoubleextensible [¹ ...] [² ...] [³ ...] [⁴ ...] 1 obe vfenced 2 NAME 3 NUMMER 4 NUMMER
\backslash definematematics [¹ ...] [² ...] [³ ... ³ ... ³ ...] 1 NAME 2 NAME 3 inherits: \setupmathematics
\backslash definemathextensible [¹ ...] [² ...] [³ ...] 1 reverse mathematika text chemistry 2 NAME 3 NUMMER
\backslash definemathfence [¹ ...] [² ...] [³ ... ³ ... ³ ...] 1 NAME 2 NAME 3 inherits: \setupmathfence
\backslash definemathfraction [¹ ...] [² ...] [³ ... ³ ... ³ ...] 1 NAME 2 NAME 3 inherits: \setupmathfraction
\backslash definemathframed [¹ ...] [² ...] [³ ... ³ ... ³ ...] 1 NAME 2 NAME 3 inherits: \setupmathframed
\backslash definemathmatrix [¹ ...] [² ...] [³ ... ³ ... ³ ...] 1 NAME 2 NAME 3 inherits: \setupmathmatrix

```
\definemathornament [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupmathornament
```

```
\definemathover [...] [...] [...]
1 vrsek vfenced NAME
2 NAME
3 NUMMER
```

```
\definemathoverextensible [...] [...] [...]
1 vrsek vfenced
2 NAME
3 NUMMER
```

```
\definemathovertextextensible [...] [...] [...]
1 bothtext
2 NAME
3 NUMMER
```

```
\definemathradical [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupmathradical
```

```
\definemathstackers [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupmathstackers
```

```
\definemathstyle [...] [...]
1 NAME
2 obrazovka text script scriptscript cramped uncramped normalni zhustene male velke
```

```
\definemathtriplet [...] [...] [...]
1 NAME
2 NAME
3 TEXT
```

```
\definemathunder [...] [...] [...]
1 spodek vfenced NAME
2 NAME
3 NUMMER
```

```
\definemathunderextensible [...] [...] [...]
1 spodek vfenced
2 NAME
3 NUMMER
```

```
\definemathundertextextensible [...] [...] [...]
1 bothtext
2 NAME
3 NUMMER
```

```
\definemathunstacked [...] [...] [...]
1 siroce
2 NAME
3 NUMMER
```

```
\definemeasure [...] [...]
1 NAME
2 DIMENSION
```

<pre> \definemessageconstant {...} * NAME </pre>
<pre> \definemixedcolumns [...¹] [...²] [...³...,...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupmixedcolumns </pre>
<pre> \definemode [...¹,...] [...²] 1 NAME OPT 2 ano ne drzet </pre>
<pre> \definemultitonecolor [...¹] [...²...,...] [...³...,...] [...⁴...,...] 1 NAME OPT 2 COLOR = NUMMER 3 inherits: \definujbarvu 4 inherits: \definespotcolor </pre>
<pre> \definenamecolor [...¹] [...²...,...] 1 NAME 2 inherits: \definujbarvu </pre>
<pre> \definenamecolor [...¹] [...²] 1 NAME 2 COLOR </pre>
<pre> \definenamespace [...¹] [...²...,...] 1 NAME 2 jmeno = TEXT parent = TEXT pismo = ano ne prikaz = ano ne seznam setup = ano ne seznam set = ano ne seznam ramecek = ano ne </pre>
<pre> \definearrower [...¹] [...²] [...³...,...] 1 NAME OPT OPT 2 NAME 3 inherits: \nastavzuzeni </pre>
<pre> \definernote [...¹] [...²] [...³...,...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupnote </pre>
<pre> \defineornament [...¹] [...²...,...] [...³...,...] 1 NAME OPT 2 alternativa = a b inherits: \setupcollector 3 pismo = STYLE BEFEHL barva = COLOR inherits: \nastavoramovani </pre>
<pre> \defineornament [...¹] [...²...,...] [...³...,...] 1 NAME OPT 2 alternativa = a b inherits: \setuplayer 3 inherits: \setuplayeredtext </pre>
<pre> \defineoutputroutine [...¹] [...²] [...³...,...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupoutputroutine </pre>

<code>\defineoutputroutinecommand [...,*,...]</code> * KEY
<code>\definepage [...¹] [...²]</code> 1 NAME 2 REFERENCE
<code>\definepagebreak [...¹] [...,²,...]</code> 1 NAME 2 prazdne zahlati upati dummy ramecek NUMBER +NUMBER implicitni reset zablokovat ano ne zlom prazdny nastaveni vysokapriorita vlevo vpravo sude liche ctyrnasobny posledni poslednistrana start stop
<code>\definepagegrid [...¹] [...²] [...,³,...]</code> 1 NAME OPT OPT 2 NAME 3 inherits: \setuppagegrid
<code>\definepagegridarea [...¹] [...²] [...,³,...]</code> 1 NAME OPT OPT 2 NAME 3 inherits: \setuppagegridarea
<code>\definepagegridspan [...¹] [...²] [...,³,...]</code> 1 NAME OPT OPT 2 NAME 3 inherits: \setuppagegridspan
<code>\definepagechecker [...¹] [...²] [...,³,...]</code> 1 NAME OPT OPT 2 NAME 3 inherits: \setuppagechecker
<code>\definepageinjection [...¹] [...²] [...,³,...]</code> 1 NAME OPT OPT 2 NAME 3 inherits: \setuppageinjection
<code>\definepageinjectionalternative [...¹] [...²] [...,³,...]</code> 1 NAME OPT OPT 2 NAME 3 inherits: \setuppageinjectionalternative
<code>\definepageshift [...¹] [...²] [...,³,...]</code> 1 NAME 2 horizontalne vertikalne 3 DIMENSION
<code>\definepagestate [...¹] [...²] [...,³,...]</code> 1 NAME OPT OPT 2 NAME 3 inherits: \setuppagestate
<code>\definepairedbox [...¹] [...²] [...,³,...]</code> 1 NAME OPT OPT 2 NAME 3 inherits: \setuppairedbox
<code>\defineparagraph [...¹] [...²] [...,³,...]</code> 1 NAME OPT OPT 2 NAME 3 inherits: \setupparagraph

<pre> \defineparallel [...] [...²,...] 1 NAME 2 NAME </pre>
<pre> \defineparbuilder [...] * NAME </pre>
<pre> \defineplacement [...] [...²] [...,³...,...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupplacement </pre>
<pre> \definepositioning [...] [...²] [...,³...,...] 1 NAME OPT OPT 2 NAME 3 inherits: \nastavumistovani </pre>
<pre> \defineprefixset [...] [...²,...] [...³] 1 NAME SECTIONBLOCK:NAME OPT 2 ABSCHNITT 3 ABSCHNITT </pre>
<pre> \defineprocesscolor [...] [...²] [...,³...,...] 1 NAME OPT 2 COLOR 3 inherits: \definujbarvu </pre>
<pre> \defineprocessor [...] [...²] [...,³...,...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupprocessor </pre>
<pre> \definepushbutton [...] [...,²...,...] 1 NAME OPT 2 inherits: \setupfieldcontentframed </pre>
<pre> \definepushsymbol [...] [...²] 1 NAME 2 n r d </pre>
<pre> \definerenderingwindow [...] [...²] [...,³...,...] 1 NAME OPT OPT 2 NAME 3 inherits: \setuprenderingwindow </pre>
<pre> \defineresetset [...] [...²,...] [...³] 1 NAME SECTIONBLOCK:NAME OPT 2 NUMMER 3 NUMMER </pre>
<pre> \definescale [...] [...²] [...,³...,...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupscale </pre>
<pre> \definescript [...] [...²] [...,³...,...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupscript </pre>
<pre> \definesectionlevels [...] [...²,...] 1 NAME 2 ABSCHNITT </pre>

<pre> \defineselector [...] [...,²...,...] 1 NAME 2 inherits: \setupselector </pre>
<pre> \defineseparatorset [...] [...,²...,...] [...] 1 NAME SECTIONBLOCK:NAME 2 BEFEHL PROCESSOR->BEFEHL 3 BEFEHL PROCESSOR->BEFEHL </pre>
<pre> \defineshift [...] [...²...] [...,³...,...] 1 NAME 2 NAME 3 inherits: \setupshift </pre>
<pre> \definesidebar [...] [...²...] [...,³...,...] 1 NAME 2 NAME 3 inherits: \setupsidebar </pre>
<pre> \definesort [...] [...²...] [...³...] {⁴...} 1 ano ne 2 SINGULAR 3 NAME 4 CONTENT </pre>
<pre> \definespotcolor [...] [...²...] [...,³...,...] 1 NAME 2 COLOR 3 a = NUMMER zadny normalni multiply rastr prekryv softlight hardlight colordodge colorburn darken lighten difference exclusion hue saturation barevne luminosity t = NUMMER e = TEXT p = NUMMER </pre>
<pre> \definestyleinstance [...] [...²...] [...³...] [...⁴...] 1 NAME 2 rm ss tt mm hw cg 3 tf bf it sl bi bs sc 4 BEFEHL </pre>
<pre> \definesubformula [...] [...²...] [...,³...,...] 1 NAME 2 NAME 3 inherits: \setupsubformula </pre>
<pre> \definesynonym [...] [...²...] [...³...] {⁴...} {⁵...} 1 ano ne 2 SINGULAR 3 NAME 4 TEXT 5 CONTENT </pre>
<pre> \definesystemattribute [...] [...,²...,...] 1 NAME 2 lokalne globalne public private </pre>
<pre> \definesystemconstant {...} * NAME </pre>
<pre> \definesystemvariable {...} * NAME </pre>
<pre> \defineTABLEsetup [...] [...,²...,...] 1 NAME 2 inherits: \setupTABLE </pre>

<pre> \definetabulation [...] [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setuptabulation </pre>
<pre> \definetextbackground [...] [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setuptextbackground </pre>
<pre> \definetextflow [...] [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setuptextflow </pre>
<pre> \definetooltip [...] [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setuptooltip </pre>
<pre> \definetransparency [...] [...] 1 NAME 2 NUMBER </pre>
<pre> \definetransparency [...] [...] 1 NAME 2 a = NUMBER zadny normalni multiply rastr prekryv softlight hardlight colordodge colorburn darken lighten difference exclusion hue saturation barevne luminosity t = NUMBER </pre>
<pre> \definetransparency [...] [...] 1 NAME 2 NAME </pre>
<pre> \definetwopasslist {...} * NAME </pre>
<pre> \definetype [...] [...] [...] [...] 1 NAME 2 NAME 3 inherits: \nastavtype </pre>
<pre> \definetypeface [...] [...] [...] [...] [...] [...] [...] 1 NAME 2 rm ss tt mm hw cg 3 serif sans mono math handwriting calligraphy 4 NAME 5 implicitni dtp 6 rscale = auto NUMBER features = NAME fallbacks = NAME goodies = NAME designsize = auto implicitni smer = obe </pre>
<pre> \definetypescriptprefix [...] [...] 1 NAME 2 TEXT </pre>
<pre> \definetypescriptsynonym [...] [...] 1 NAME 2 TEXT </pre>

\definetypesetting [¹...] [²...] [³...,...]

- 1 NAME
- 2 TEXT
- 3 inherits: \setupexternalfigure

\defineunit [¹...] [²...] [³...,...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupunit

\defineviewerlayer [¹...] [²...] [³...,...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupviewerlayer

\definevspace [¹...] [²...] [³...]

- 1 NAME
- 2 NAME
- 3 DIMENSION

\definevspacing [¹...] [²...]

- 1 NAME
- 2 inherits: \vspacing

\definevspacingamount [¹...] [²...] [³...]

- 1 NAME
- 2 DIMENSION
- 3 DIMENSION

\definetable [¹...] [²...] [³...,...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupxtable

\definuj [¹...] \²... {³...}

- 1 NUMBER
- 2 CSNAME
- 3 CONTENT

\definujakcent ¹... ²... ³...

- 1 CHARACTER
- 2 CHARACTER
- 3 CHARACTER

\definujbarvu [¹...] [²...,...]

- 1 NAME
- 2
 - r = NUMBER
 - g = NUMBER
 - b = NUMBER
 - c = NUMBER
 - m = NUMBER
 - y = NUMBER
 - k = NUMBER
 - h = NUMBER
 - s = NUMBER
 - v = NUMBER
 - x = NUMBER
 - a = NUMBER zadny normalni multiply rastr prekryv softlight hardlight colordodge colorburn darken lighten difference exclusion hue saturation barevne luminosity
 - t = NUMBER

\definujbarvu [¹...] [²...]

- 1 NAME
- 2 COLOR

<pre> \definujblok [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \nastavblok </pre>
<pre> \definujbloksekce [...] [...] [...] 1 NAME OPT 2 NAME 3 inherits: \nastavbloksekce </pre>
<pre> \definujbuffer [...] [...] [...] 1 NAME OPT OPT 2 BUFFER 3 inherits: \nastavbuffer </pre>
<pre> \definujfont [...] [...] [...] 1 NAME OPT 2 FONT 3 inherits: \nastavmeziradkovoumezeru </pre>
<pre> \definujfont [...] [...] [...] 1 NAME OPT 2 FONT 3 NAME </pre>
<pre> \definujformatodkazu [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupreferenceformat </pre>
<pre> \definujhbox [...] [...] 1 NAME 2 DIMENSION </pre>
<pre> \definujinterakcnimenu [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \nastavinterakcnimenu </pre>
<pre> \definujkombinovanyseznam [...] [...] [...] 1 NAME OPT 2 LISTE 3 inherits: \nastavseznam </pre>
<pre> \definujkonverzi [...] [...] [...] 1 SPRACHE OPT 2 NAME 3 CSNAME </pre>
<pre> \definujkonverzi [...] [...] [...] 1 SPRACHE OPT 2 NAME 3 TEXT </pre>
<pre> \definujnadpis [...] [...] [...] 1 NAME OPT OPT 2 ABSCHNITT 3 inherits: \nastavnadpis </pre>
<pre> \definujobrazeksymbol [...] [...] [...] 1 NAME OPT 2 FILE NAME 3 inherits: \externiobraz </pre>

<pre> \definujodkaz [...] [...] 1 NAME 2 REFERENCE </pre>
<pre> \definujodstavce [...] [...] [...] 1 NAME 2 NAME 3 inherits: \nastavodstavce </pre>
<pre> \definujopis [...] [...] [...] 1 NAME 2 NAME 3 inherits: \nastavopis </pre>
<pre> \definujoramovani [...] [...] [...] 1 NAME 2 NAME 3 inherits: \nastavoramovani </pre>
<pre> \definujoramovanytext [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setupframedtext </pre>
<pre> \definujpaletu [...] [...] 1 NAME 2 NAME = COLOR </pre>
<pre> \definujpaletu [...] [...] 1 NAME 2 NAME </pre>
<pre> \definujplvouciobjekt [...] [...] [...] 1 SINGULAR 2 SINGULAR PLURAL 3 inherits: \nastavplvouciobjekt instances: chemical figure table intermezzo graphic </pre>
<pre> \definujplvouciobjekt [...] [...] [...] 1 SINGULAR 2 PLURAL 3 SINGULAR instances: chemical figure table intermezzo graphic </pre>
<pre> \definujpodpole [...] [...] [...] 1 NAME 2 NAME 3 NAME </pre>
<pre> \definujpole [...] [...] [...] [...] [...] 1 NAME 2 radio pod text radek push check signature 3 NAME 4 NAME 5 NAME </pre>
<pre> \definujpopis [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setupdescription </pre>
<pre> \definujpopisek [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setuplabel </pre>

\definujprekryv [...] [¹...] [²] [³]

- 1 NAME OPT
- 2 NAME
- 3 BEFEHL

\definujprikaz ...¹ ...²

- 1 CHARACTER
- 2 BEFEHL

\definujprofil [¹] [²] [...,³...,...]

- 1 NAME OPT OPT
- 2 NAME
- 3 inherits: \setupprofile

\definujprogram [...] [¹] [²] [³]

- 1 NAME OPT
- 2 TEXT
- 3 TEXT

\definujprostredizakladnihofontu [¹] [²] [...,³...,...]

- 1 NAME OPT OPT
- 2 implicitni DIMENSION
- 3 velky = DIMENSION NUMMER
- male = DIMENSION NUMMER
- a = DIMENSION NUMMER
- b = DIMENSION NUMMER
- c = DIMENSION NUMMER
- d = DIMENSION NUMMER
- text = DIMENSION NUMMER
- x = DIMENSION NUMMER
- xx = DIMENSION NUMMER
- script = DIMENSION NUMMER
- scriptscript = DIMENSION NUMMER
- meziradkovamezera = DIMENSION
- em = sklonene kurziva STYLE BEFEHL
- * = NUMMER

\definujrejstrik [¹] [²] [...,³...,...]

- 1 NAME OPT OPT
- 2 NAME
- 3 inherits: \nastavrejstrik

\definujsablonutabulky [...] [|¹...|] [²] [³] [⁴]

- 1 NAME OPT OPT
- 2 TEMPLATE
- 3 NAME
- 4 NAME

\definujsekci [...]

- * NAME

\definujseznam [¹] [²] [...,³...,...]

- 1 NAME OPT OPT
- 2 LISTE
- 3 inherits: \nastavseznam

\definujskupinubarev [¹] [²] [x:y:³z,...]

- 1 NAME OPT
- 2 seda rgb cmyk spot
- 3 TRIPLET

\definujstartstop [¹] [²] [...,³...,...]

- 1 NAME OPT OPT
- 2 NAME
- 3 inherits: \setupstartstop

```
\definujstyl [...]1 [...]2 [...]3...]
```

```
1 NAME OPT OPT
```

```
2 NAME
```

```
3 inherits: \setupstyle
```

```
\definujstylfontu [...]1 [...]2
```

```
1 NAME
```

```
2 NAME
```

```
\definujsymbol [...]1 [...]2 [...]3
```

```
1 NAME OPT
```

```
2 NAME
```

```
3 BEFEHL
```

```
\definujsynonumfontu [...]1 [...]2 [...]3...]
```

```
1 NAME OPT
```

```
2 FONT
```

```
3 features = NAME
```

```
   fallbacks = NAME
```

```
   goodies = NAME
```

```
   designsize = auto implicitni
```

```
\definujsynonyma [...]1 [...]2 [...]3 [...]4
```

```
1 SINGULAR OPT OPT
```

```
2 PLURAL
```

```
3 CSNAME
```

```
4 CSNAME
```

```
\definujtabelaci [...]1 [...]2 [/]3]
```

```
1 NAME OPT OPT
```

```
2 NAME
```

```
3 TEMPLATE
```

```
\definujtext [...]1 [...]2 [...]3 [...]4 [...]5 [...]6 [...]7
```

```
1 NAME OPT OPT OPT OPT
```

```
2 vrsek zahlavi text upati spodek
```

```
3 text marginalie hrana
```

```
4 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
```

```
5 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
```

```
6 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
```

```
7 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
```

```
\definujtrideni [...]1 [...]2 [...]3
```

```
1 SINGULAR OPT
```

```
2 PLURAL
```

```
3 zadny CSNAME
```

```
\definujupravu [...]1 [...]2 [...]3...]
```

```
1 NAME OPT OPT
```

```
2 NAME
```

```
3 inherits: \nastavupravu
```

```
\definujvelikostpapiru [...]1 [...]2...]
```

```
1 NAME
```

```
2 sirka = DIMENSION
```

```
   vyska = DIMENSION
```

```
   vrsek = BEFEHL
```

```
   spodek = BEFEHL
```

```
   vlevo = BEFEHL
```

```
   vpravo = BEFEHL
```

```
   vzdalenost = DIMENSION
```

```
   stranka = inherits: \nastavvelikostpapiru
```

```
   papir = inherits: \nastavvelikostpapiru
```

```
\definujvelikostpapiru [...]1 [...]2 [...]3...]
```

```
1 NAME OPT
```

```
2 inherits: \nastavvelikostpapiru
```

```
3 inherits: \nastavvelikostpapiru
```

\definujvycet [¹...] [²...] [³...³...]

1 NAME OPT OPT
2 NAME
3 inherits: \setupenumeration

\definujzakladnifont [¹...¹...] [²...²...] [³...³...] [⁴...⁴...]

1 NAME implicitni OPT OPT
2 NAME DIMENSION
3 rm ss tt hw cg
4 tf = FILE
bf = FILE
it = FILE
sl = FILE
bi = FILE
bs = FILE
sc = FILE
mr = FILE
mrlr = FILE
mrrl = FILE
mb = FILE
mblr = FILE
mbrl = FILE

\definujzakladnifont [¹...¹...] [²...²...] [³...³...] [⁴...]

1 NAME implicitni OPT OPT
2 NAME DIMENSION
3 rm ss tt hw cg
4 NAME

\definujzasobnikpoli [¹...] [²...²...] [³...³...]

1 NAME OPT
2 NAME
3 inherits: \setupfieldcategory

\definujznaceni [¹...] [²...] [³...³...]

1 NAME OPT OPT
2 BESCHRIFTUNG
3 inherits: \nastavznaceni

\definujznak ¹... ²...

1 CHARACTER
2 NUMMER

\delimited [¹...] [²...] {³...}

1 NAME OPT
2 SPRACHE
3 CONTENT

\delimitedtext [¹...] [²...] {³...}

1 NAME OPT
2 SPRACHE
3 CONTENT

\DELIMITEDTEXT [¹...] {²...}

1 SPRACHE OPT
2 CONTENT
instances: quotation quote blockquote speech aside

\aside [¹...] {²...}

1 SPRACHE OPT
2 CONTENT

\blockquote [¹...] {²...}

1 SPRACHE OPT
2 CONTENT

<code>\quotation [...]{...}</code> 1 SPRACHE <small>OPT</small> 2 CONTENT
<code>\quote [...]{...}</code> 1 SPRACHE ^{OPT} 2 CONTENT
<code>\speech [...]{...}</code> 1 SPRACHE <small>OPT</small> 2 CONTENT
<code>\delkaseznamu</code>
<code>\depthofstring {...}</code> * TEXT
<code>\depthonlybox {...}</code> * CONTENT
<code>\depthspanningtext {...}{...}{...}</code> 1 TEXT 2 DIMENSION 3 FONT
<code>\depthstrut</code>
<code>\determinenoflines {...}</code> * CONTENT
<code>\devanagarinumerals {...}</code> * NUMMER
<code>\digits {...}</code> * NUMMER
<code>\digits ...</code> * NUMMER
<code>\dimensiontocount {...}\²...</code> 1 DIMENSION 2 CSNAME
<code>\directboxfromcache {...}{...}</code> 1 NAME 2 NUMMER TEXT
<code>\directcolor [...]</code> * COLOR
<code>\directcolored [...,...[*]...,...]</code> * inherits: \definujbarvu
<code>\directcolored [...]</code> * COLOR
<code>\directconvertedcounter {...}{...}</code> 1 NAME 2 prvni predchozi dalsi posledni cislo

\directcopyboxfromcache {...} {...} 1 NAME 2 NUMMER TEXT
\directdummysparameter {...} * KEY
\directgetboxllx ... * CSNAME NUMMER
\directgetboxlly ... * CSNAME NUMMER
\directhighlight {...} {...} 1 NAME 2 TEXT
\directlocalframed [...] {...} 1 NAME 2 CONTENT
\directluacode {...} * BEFEHL
\directselect {...} {...} {...} {...} {...} {...} 1 NAME 2 CONTENT 3 CONTENT 4 CONTENT 5 CONTENT 6 CONTENT
\directsetbar {...} * NAME
\directsetup {...} * NAME
\directsymbol {...} {...} 1 NAME 2 NAME
\directvspacing {...,*...} * inherits: \vspacing
\dis {...} * CONTENT
\disabledirectives [...,*...] * NAME
\disableexperiments [...,*...] * NAME
\disablemode [...,*...] * NAME
\disableoutputstream

<code>\disableparpositions</code>
<code>\disableregime</code>
<code>\disabletrackers [...,*,...]</code> <code>* NAME</code>
<code>\displaymath {...}</code> <code>* CONTENT</code>
<code>\displaymathematics {...}</code> <code>* CONTENT</code>
<code>\displaymessage {...}</code> <code>* TEXT</code>
<code>\distributedhsize {...} {...} {...}</code> <code>1 DIMENSION</code> <code>2 DIMENSION</code> <code>3 NUMMER</code>
<code>\dividedsize {...} {...} {...}</code> <code>1 DIMENSION</code> <code>2 DIMENSION</code> <code>3 NUMMER</code>
<code>\loadaptleftskip {...}</code> <code>* ano ne standardni DIMENSION</code>
<code>\loadaptrightskip {...}</code> <code>* ano ne standardni DIMENSION</code>
<code>\doaddfeature {...,*,...}</code> <code>* NAME</code>
<code>\doassign [...¹] [...²...]</code> <code>1 TEXT</code> <code>2 KEY = VALUE</code>
<code>\doassignempty [...¹] [...²...]</code> <code>1 TEXT</code> <code>2 KEY = VALUE</code>
<code>\doboundtext {...¹} {...²} {...³}</code> <code>1 TEXT</code> <code>2 DIMENSION</code> <code>3 BEFEHL</code>
<code>\documentvariable {...}</code> <code>* KEY</code>
<code>\dodoubleargument \... [...²] [...³]</code> <code>1 CSNAME</code> <code>2 TEXT</code> <code>3 TEXT</code>
<code>\dodoubleargumentwithset \... [...²,...] [...³]</code> <code>1 CSNAME</code> <code>2 TEXT</code> <code>3 TEXT</code>

\doDOUBLEempty \ ¹ ... [² ...] [³ ...] 1 CSNAME OPT OPT 2 TEXT 3 TEXT
\doDOUBLEemptywithset \ ¹ ... [² ...; ³ ...] [³ ...] 1 CSNAME OPT OPT 2 TEXT 3 TEXT
\doDOUBLEgroupempty \ ¹ ... { ² ...} { ³ ...} 1 CSNAME OPT OPT 2 TEXT 3 TEXT
\doeassign [¹ ...] [² ...] 1 TEXT 2 KEY = VALUE
\doexpandedrecurse { ¹ ...} { ² ...} 1 NUMMER 2 BEFEHL
\doFASTloopcs { ¹ ...} \ ² .. 1 NUMMER 2 CSNAME
\doGETattribute { [*] ...} * NAME
\doGETattributeid { [*] ...} * NAME
\doGETcommacommandelement ¹ ... \from ² ... \to \ ³ .. 1 NUMMER 2 TEXT 3 CSNAME
\doGOBBLEDdoubleempty [¹ ...] [² ...] 1 TEXT OPT OPT 2 TEXT
\doGOBBLESingleempty [[*] ...] * TEXT OPT
\doCHECKassignment { [*] ...} * TEXT
\doCHECKedpagestate { ¹ ...} { ² ...} { ³ ...} { ⁴ ...} { ⁵ ...} { ⁶ ...} { ⁷ ...} 1 REFERENCE 2 BEFEHL 3 BEFEHL 4 BEFEHL 5 BEFEHL 6 BEFEHL 7 BEFEHL
\doCHECKedpair {...; [*] ...} * TEXT

```
\doif {...} {...} {...}
```

```
1 CONTENT  
2 CONTENT  
3 TRUE
```

```
\doifallcommon {...,1...} {...,2...} {...3}
```

```
1 TEXT  
2 TEXT  
3 TRUE
```

```
\doifallcommonelse {...,1...} {...,2...} {...3} {...4}
```

```
1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE
```

```
\doifalldefinedelse {...,1...} {...2} {...3}
```

```
1 NAME  
2 TRUE  
3 FALSE
```

```
\doifallmodes {...,1...} {...2} {...3}
```

```
1 NAME  
2 TRUE  
3 FALSE
```

```
\doifallmodeselse {...,1...} {...2} {...3}
```

```
1 NAME  
2 TRUE  
3 FALSE
```

```
\doifassignmentelse {...1} {...2} {...3}
```

```
1 TEXT  
2 TRUE  
3 FALSE
```

```
\doifblackelse {...1} {...2} {...3}
```

```
1 COLOR  
2 TRUE  
3 FALSE
```

```
\doifbothsides {...1} {...2} {...3}
```

```
1 BEFEHL  
2 BEFEHL  
3 BEFEHL
```

```
\doifbothsidesoverruled {...1} {...2} {...3}
```

```
1 BEFEHL  
2 BEFEHL  
3 BEFEHL
```

```
\doifboxelse {...1} {...2} {...3} {...4}
```

```
1 NAME  
2 NAME  
3 TRUE  
4 FALSE
```

```
\doifbufferelse {...1} {...2} {...3}
```

```
1 BUFFER  
2 TRUE  
3 FALSE
```

```
\doifcolor {...1} {...2}
```

```
1 COLOR  
2 TRUE
```

`\doifcolorelse {...} {...} {...}`

1 COLOR
2 TRUE
3 FALSE

`\doifcommandhandler \... {...} {...}`

1 CSNAME
2 NAME
3 TRUE

`\doifcommandhandlerelse \... {...} {...} {...}`

1 CSNAME
2 NAME
3 TRUE
4 FALSE

`\doifcommon {...,1...} {...,2...} {...}`

1 TEXT
2 TEXT
3 TRUE

`\doifcommonelse {...,1...} {...,2...} {...} {...}`

1 TEXT
2 TEXT
3 TRUE
4 FALSE

`\doifcontent {...} {...} {...} \...4 {...5}`

1 BEFEHL
2 BEFEHL
3 BEFEHL
4 CSNAME
5 CONTENT

`\doifconversiondefinedelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doifconversionnumberelse {...} {...} {...} {...}`

1 NAME
2 NUMMER
3 TRUE
4 FALSE

`\doifcounter {...} {...}`

1 NAME
2 TRUE

`\doifcounterelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doifcurrentfonthasfeatureelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doifdefined {...} {...}`

1 NAME
2 TRUE

\doifdefinedcounter {...} {...}

1 NAME
2 TRUE

\doifdefinedcounterelse {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifdefinedelse {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifdimensionelse {...} {...} {...}

1 TEXT
2 TRUE
3 FALSE

\doifdimenstringelse {...} {...} {...}

1 TEXT
2 TRUE
3 FALSE

\doifdocumentargument {...} {...}

1 NAME
2 TRUE

\doifdocumentargumentelse {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifdocumentfilename {...} {...}

1 NUMMER
2 TRUE

\doifdocumentfilenameelse {...} {...} {...}

1 NUMMER
2 TRUE
3 FALSE

\doifdrawingblackelse {...} {...}

1 TRUE
2 FALSE

\doifelse {...} {...} {...} {...}

1 CONTENT
2 CONTENT
3 TRUE
4 FALSE

\doifelseallcommon {...,¹...} {...,²...} {...} {...⁴}

1 TEXT
2 TEXT
3 TRUE
4 FALSE

\doifelsealldefined {...,¹...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifelseallmodes {...¹,...} {...²} {...³}

1 NAME
2 TRUE
3 FALSE

\doifelseassignment {...¹} {...²} {...³}

1 TEXT
2 TRUE
3 FALSE

\doifelseblack {...¹} {...²} {...³}

1 COLOR
2 TRUE
3 FALSE

\doifelsebox {...¹} {...²} {...³} {...⁴}

1 NAME
2 NAME
3 TRUE
4 FALSE

\doifelseboxincache {...¹} {...²} {...³} {...⁴}

1 NAME
2 NUMMER TEXT
3 TRUE
4 FALSE

\doifelsebuffer {...¹} {...²} {...³}

1 BUFFER
2 TRUE
3 FALSE

\doifelsecolor {...¹} {...²} {...³}

1 COLOR
2 TRUE
3 FALSE

\doifelsecommandhandler \... {...¹} {...²} {...³} {...⁴}

1 CSNAME
2 NAME
3 TRUE
4 FALSE

\doifelsecommon {...¹,...} {...²,...} {...³} {...⁴}

1 TEXT
2 TEXT
3 TRUE
4 FALSE

\doifelseconversiondefined {...¹} {...²} {...³}

1 NAME
2 TRUE
3 FALSE

\doifelseconversionnumber {...¹} {...²} {...³} {...⁴}

1 NAME
2 NUMMER
3 TRUE
4 FALSE

\doifelsecounter {...¹} {...²} {...³}

1 NAME
2 TRUE
3 FALSE

\doifelsecurrentfonthasfeature {...} {...} {...} 1 NAME 2 TRUE 3 FALSE
\doifelsecurrentsortingingused {...} {...} 1 TRUE 2 FALSE
\doifelsecurrentsynonymshown {...} {...} 1 TRUE 2 FALSE
\doifelsecurrentsynonymused {...} {...} 1 TRUE 2 FALSE
\doifelsedefined {...} {...} {...} 1 NAME 2 TRUE 3 FALSE
\doifelsedefinedcounter {...} {...} {...} 1 NAME 2 TRUE 3 FALSE
\doifelsedimension {...} {...} {...} 1 TEXT 2 TRUE 3 FALSE
\doifelsedimenstring {...} {...} {...} 1 TEXT 2 TRUE 3 FALSE
\doifelsedocumentargument {...} {...} {...} 1 NAME 2 TRUE 3 FALSE
\doifelsedocumentfilename {...} {...} {...} 1 NUMBER 2 TRUE 3 FALSE
\doifelsedrawingblack {...} {...} 1 TRUE 2 FALSE
\doifelseempty {...} {...} {...} 1 CONTENT 2 TRUE 3 FALSE
\doifelseemptyvalue {...} {...} {...} 1 NAME 2 TRUE 3 FALSE

`\doifelseemptyvariable {...} {...} {...} {...}`

1 NAME
2 KEY
3 TRUE
4 FALSE

`\doifelseenv {...} {...} {...}`

1 KEY
2 TRUE
3 FALSE

`\doifelsefastoptionalcheck {...} {...}`

1 TRUE
2 FALSE

`\doifelsefastoptionalcheckcs \^1 \^2`

1 CSNAME
2 CSNAME

`\doifelsefieldbody {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doifelsefieldcategory {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doifelsefigure {...} {...} {...}`

1 FILE
2 TRUE
3 FALSE

`\doifelsefile {...} {...} {...}`

1 FILE
2 TRUE
3 FALSE

`\doifelsefiledefined {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doifelsefileexists {...} {...} {...}`

1 FILE
2 TRUE
3 FALSE

`\doifelsefirstchar {...} {...} {...} {...}`

1 TEXT
2 TEXT
3 TRUE
4 FALSE

`\doifelseflagged {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doifelsefontfeature {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

```
\doifelsefontchar {...} {...} {...} {...}
1  FONT
2  NUMMER
3  TRUE
4  FALSE
```

```
\doifelsefontpresent {...} {...} {...}
1  FONT
2  TRUE
3  FALSE
```

```
\doifelsefontsynonym {...} {...} {...}
1  NAME
2  TRUE
3  FALSE
```

```
\doifelsehasspace {...} {...} {...}
1  TEXT
2  TRUE
3  FALSE
```

```
\doifelsehelp {...} {...}
1  TRUE
2  FALSE
```

```
\doifelseincsname {...} {...} {...} {...}
1  TEXT
2  CSNAME
3  TRUE
4  FALSE
```

```
\doifelseinelement {...} {...} {...}
1  NAME
2  TRUE
3  FALSE
```

```
\doifelseinputfile {...} {...} {...}
1  FILE
2  TRUE
3  FALSE
```

```
\doifelseinsertion {...} {...} {...}
1  NAME
2  TRUE
3  FALSE
```

```
\doifelseinset {...} {...,2...} {...} {...}
1  TEXT
2  TEXT
3  TRUE
4  FALSE
```

```
\doifelseinstring {...} {...} {...} {...}
1  TEXT
2  TEXT
3  TRUE
4  FALSE
```

```
\doifelseinsymbolset {...} {...} {...} {...}
1  NAME
2  NAME
3  TRUE
4  FALSE
```


\doifelseintoks {...} {...} {...} {...}

1 BEFEHL
2 BEFEHL
3 TRUE
4 FALSE

\doifelseintwopassdata {...} {...} {...} {...}

1 NAME
2 NAME
3 TRUE
4 FALSE

\doifelseitalic {...} {...}

1 TRUE
2 FALSE

\doifelselanguage {...} {...} {...}

1 SPRACHE
2 TRUE
3 FALSE

\doifelselayerdata {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifelselayoutdefined {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifelselayoutsomeline {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifelselayouttextline {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifelseleapyear {...} {...} {...}

1 NUMMER
2 TRUE
3 FALSE

\doifelselist {...} {...} {...}

1 LISTE
2 TRUE
3 FALSE

\doifelselocation {...} {...}

1 TRUE
2 FALSE

\doifelselocfile {...} {...} {...}

1 FILE
2 TRUE
3 FALSE

\doifelseMPgraphic {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifelsemainfloatbody {...} {...} 1 TRUE 2 FALSE
\doifelsemarkedpage {...} {...} {...} 1 NAME 2 TRUE 3 FALSE
\doifelsemarking {...} {...} {...} 1 BESCHRIFTUNG 2 TRUE 3 FALSE
\doifelsemeaning \^1... \^2... {...} {...} 1 CSNAME 2 CSNAME 3 TRUE 4 FALSE
\doifelsemessage {...} {...} {...} {...} 1 NAME 2 NAME NUMMER 3 TRUE 4 FALSE
\doifelsemode {..., ¹ ...} {...} {...} 1 NAME 2 TRUE 3 FALSE
\doifelsenextbgroup {...} {...} 1 TRUE 2 FALSE
\doifelsenextbgroupcs \^1... \^2... 1 CSNAME 2 CSNAME
\doifelsenextchar {...} {...} {...} 1 CHARACTER 2 TRUE 3 FALSE
\doifelsenextoptional {...} {...} 1 TRUE 2 FALSE
\doifelsenextoptionalcs \^1... \^2... 1 CSNAME 2 CSNAME
\doifelsenextparenthesis {...} {...} 1 TRUE 2 FALSE
\doifelsenonzeropositive {...} {...} {...} 1 NUMMER 2 TRUE 3 FALSE

\doifelseonpage {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifelsenothing {...} {...} {...}

1 TEXT
2 TRUE
3 FALSE

\doifelsenumber {...} {...} {...}

1 TEXT
2 TRUE
3 FALSE

\doifelseobjectfound {...} {...} {...} {...}

1 NAME
2 NAME
3 TRUE
4 FALSE

\doifelseobjectreferencefound {...} {...} {...} {...}

1 NAME
2 NAME
3 TRUE
4 FALSE

\doifelseoddpage {...} {...}

1 BEFEHL
2 BEFEHL

\doifelseoddpagefloat {...} {...}

1 TRUE
2 FALSE

\doifelseoldercontext {...} {...} {...}

1 NUMMER
2 TRUE
3 FALSE

\doifelseolderversion {...} {...} {...} {...}

1 NUMMER
2 NUMMER
3 TRUE
4 FALSE

\doifelseoverlapping {...} {...} {...} {...}

1 NAME
2 NAME
3 TRUE
4 FALSE

\doifelseoverlay {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifelseparallel {...} {...} {...} {...}

1 NAME
2 NAME vse
3 TRUE
4 FALSE

\doifelseparentfile {...} {...} {...}

1 FILE
2 TRUE
3 FALSE

\doifelsepath {...} {...} {...}

1 PATH
2 TRUE
3 FALSE

\doifelsepathexists {...} {...} {...}

1 PATH
2 TRUE
3 FALSE

\doifelsepatterns {...} {...} {...}

1 SPRACHE
2 TRUE
3 FALSE

\doifelseposition {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifelsepositionaction {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifelsepositiononpage {...} {...} {...} {...}

1 NAME
2 NUMMER
3 TRUE
4 FALSE

\doifelsepositionsonsamepage {...,¹...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifelsepositionsonthispage {...,¹...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifelsepositionsused {...} {...}

1 TRUE
2 FALSE

\doifelserreferencefound {...} {...} {...}

1 REFERENCE
2 TRUE
3 FALSE

\doifelserightpagefloat {...} {...}

1 TRUE
2 FALSE

\doifelserighttopleftinbox ...¹ {...} {...}

1 CSNAME NUMMER
2 TRUE
3 FALSE

\doifelsesamelinereference {...} {...} {...}

1 REFERENCE
2 TRUE
3 FALSE

\doifelsesamestring {...} {...} {...} {...}

1 TEXT
2 TEXT
3 TRUE
4 FALSE

\doifelsesetups {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifelsesomebackground {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifelsesomespace {...} {...} {...}

1 TEXT
2 TRUE
3 FALSE

\doifelsesomething {...} {...} {...}

1 TEXT
2 TRUE
3 FALSE

\doifelsesometoks \... {...} {...}

1 CSNAME
2 TRUE
3 FALSE

\doifelsestringinstring {...} {...} {...} {...}

1 TEXT
2 TEXT
3 TRUE
4 FALSE

\doifelsestructurelisthasnumber {...} {...}

1 TRUE
2 FALSE

\doifelsestructurelisthaspage {...} {...}

1 TRUE
2 FALSE

\doifelsesymboldefined {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifelsesymbolset {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifelsetext {...} {...} {...}

1 TEXT
2 TRUE
3 FALSE

`\doifsettextflow {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doifsettextflowcollector {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doifsettopofpage {...} {...}`

1 TRUE
2 FALSE

`\doifsettypingfile {...} {...} {...}`

1 FILE
2 TRUE
3 FALSE

`\doifelseundefined {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doifelseurldefined {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doifelsevalue {...} {...} {...} {...}`

1 NAME
2 TEXT
3 TRUE
4 FALSE

`\doifelsevaluenothing {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doifelsevariable {...} {...} {...} {...}`

1 NAME
2 KEY
3 TRUE
4 FALSE

`\doifempty {...} {...}`

1 CONTENT
2 TRUE

`\doifemptyelse {...} {...} {...}`

1 CONTENT
2 TRUE
3 FALSE

`\doifemptytoks \^1. {...}`

1 CSNAME
2 TRUE

`\doifemptyvalue {...} {...}`

1 NAME
2 TRUE

\doifemptyvalueelse {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifemptyvariable {...} {...} {...}

1 NAME
2 KEY
3 TRUE

\doifemptyvariableelse {...} {...} {...} {...}

1 NAME
2 KEY
3 TRUE
4 FALSE

\doifenv {...} {...}

1 KEY
2 TRUE

\doifenvelse {...} {...} {...}

1 KEY
2 TRUE
3 FALSE

\doiffastoptionalcheckcselse \¹... \²...

1 CSNAME
2 CSNAME

\doiffastoptionalcheckelse {...} {...}

1 TRUE
2 FALSE

\doiffielddbbodyelse {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doiffielddcategoryelse {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doiffigureelse {...} {...} {...}

1 FILE
2 TRUE
3 FALSE

\doiffile {...} {...}

1 FILE
2 TRUE

\doiffiledefinedelse {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doiffileelse {...} {...} {...}

1 FILE
2 TRUE
3 FALSE

`\doiffileexistselse {...} {...} {...}`

1 FILE
2 TRUE
3 FALSE

`\doiffirstcharelse {...} {...} {...} {...}`

1 TEXT
2 TEXT
3 TRUE
4 FALSE

`\doifflaggedelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doiffontfeatureelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doiffontcharelse {...} {...} {...} {...}`

1 FONT
2 NUMBER
3 TRUE
4 FALSE

`\doiffontpresentelse {...} {...} {...}`

1 FONT
2 TRUE
3 FALSE

`\doiffontsynonymelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doifhasspaceelse {...} {...} {...}`

1 TEXT
2 TRUE
3 FALSE

`\doifhelpelse {...} {...}`

1 TRUE
2 FALSE

`\doifincsnameelse {...} {...} {...} {...}`

1 TEXT
2 CSNAME
3 TRUE
4 FALSE

`\doifinelementelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doifinputfileelse {...} {...} {...}`

1 FILE
2 TRUE
3 FALSE

\doifinsertionelse {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifinset {...} {...,²...} {...³}

1 TEXT
2 TEXT
3 TRUE

\doifinsetelse {...} {...,²...} {...} {...⁴}

1 TEXT
2 TEXT
3 TRUE
4 FALSE

\doifinstring {...} {...²} {...³}

1 TEXT
2 TEXT
3 TRUE

\doifinstringelse {...} {...²} {...³} {...⁴}

1 TEXT
2 TEXT
3 TRUE
4 FALSE

\doifinsymbolset {...} {...} {...} {...⁴}

1 NAME
2 NAME
3 TRUE
4 FALSE

\doifinsymbolsetelse {...} {...} {...} {...⁴}

1 NAME
2 NAME
3 TRUE
4 FALSE

\doifintokselse {...} {...} {...} {...⁴}

1 BEFEHL
2 BEFEHL
3 TRUE
4 FALSE

\doifintwopassdataelse {...} {...} {...} {...⁴}

1 NAME
2 NAME
3 TRUE
4 FALSE

\doifitalicelse {...} {...²}

1 TRUE
2 FALSE

\doiflanguageelse {...} {...²} {...³}

1 SPRACHE
2 TRUE
3 FALSE

\doiflayerdataelse {...} {...²} {...³}

1 NAME
2 TRUE
3 FALSE

`\doiflayoutdefinedelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doiflayoutsomelineelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doiflayouttextlineelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doifleapyearelse {...} {...} {...}`

1 NUMMER
2 TRUE
3 FALSE

`\doiflistelse {...} {...} {...}`

1 LISTE
2 TRUE
3 FALSE

`\doiflocationelse {...} {...}`

1 TRUE
2 FALSE

`\doiflocfileelse {...} {...} {...}`

1 FILE
2 TRUE
3 FALSE

`\doifMPgraphicelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doifmainfloatbodyelse {...} {...}`

1 TRUE
2 FALSE

`\doifmarkingelse {...} {...} {...}`

1 BESCHRIFTUNG
2 TRUE
3 FALSE

`\doifmeaningelse \... \... {...} {...}`

1 CSNAME
2 CSNAME
3 TRUE
4 FALSE

`\doifmessageelse {...} {...} {...} {...}`

1 NAME
2 NAME NUMMER
3 TRUE
4 FALSE

`\doifmode {...,1...} {...2}`

1 NAME
2 TRUE

<pre> \doifmodeelse {...,¹...} {...²} {...³} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifnextbgroupcselse \¹... \²... 1 CSNAME 2 CSNAME </pre>
<pre> \doifnextbgroupelse {...¹} {...²} 1 TRUE 2 FALSE </pre>
<pre> \doifnextcharelse {...¹} {...²} {...³} 1 CHARACTER 2 TRUE 3 FALSE </pre>
<pre> \doifnextoptionalcselse \¹... \²... 1 CSNAME 2 CSNAME </pre>
<pre> \doifnextoptionalelse {...¹} {...²} 1 TRUE 2 FALSE </pre>
<pre> \doifnextparenthesiselse {...¹} {...²} 1 TRUE 2 FALSE </pre>
<pre> \doifnonzeropositiveelse {...¹} {...²} {...³} 1 NUMBER 2 TRUE 3 FALSE </pre>
<pre> \doifnot {...¹} {...²} {...³} 1 CONTENT 2 CONTENT 3 TRUE </pre>
<pre> \doifnotallcommon {...,¹...} {...,²...} {...³} 1 TEXT 2 TEXT 3 TRUE </pre>
<pre> \doifnotallmodes {...,¹...} {...²} {...³} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifnotcommandhandler \¹... {...²} {...³} 1 CSNAME 2 NAME 3 TRUE </pre>
<pre> \doifnotcommon {...,¹...} {...,²...} {...³} 1 TEXT 2 TEXT 3 TRUE </pre>
<pre> \doifnotcounter {...¹} {...²} 1 NAME 2 TRUE </pre>

<pre> \doifnotdocumentargument {...} {...} 1 NAME 2 TRUE </pre>
<pre> \doifnotdocumentfilename {...} {...} 1 NUMMER 2 TRUE </pre>
<pre> \doifnotempty {...} {...} 1 CONTENT 2 TRUE </pre>
<pre> \doifnotemptyvalue {...} {...} 1 NAME 2 TRUE </pre>
<pre> \doifnotemptyvariable {...} {...} {...} 1 NAME 2 KEY 3 TRUE </pre>
<pre> \doifnotenv {...} {...} 1 KEY 2 TRUE </pre>
<pre> \doifnoteonsamepageelse {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifnotescollected {...} {...} 1 NAME 2 TRUE </pre>
<pre> \doifnotfile {...} {...} 1 FILE 2 TRUE </pre>
<pre> \doifnotflagged {...} {...} 1 NAME 2 TRUE </pre>
<pre> \doifnothing {...} {...} 1 TEXT 2 TRUE </pre>
<pre> \doifnothingelse {...} {...} {...} 1 TEXT 2 TRUE 3 FALSE </pre>
<pre> \doifnotinset {...} {...²,...} {...³} 1 TEXT 2 TEXT 3 TRUE </pre>
<pre> \doifnotinsidesplitfloat {...} * TRUE </pre>
<pre> \doifnotinstring {...} {...} {...} 1 TEXT 2 TEXT 3 TRUE </pre>

<pre> \doifnotmode {...¹,...} {...²} 1 NAME 2 TRUE </pre>
<pre> \doifnotnumber {...¹} {...²} 1 TEXT 2 TRUE </pre>
<pre> \doifnotsamestring {...¹} {...²} {...³} 1 TEXT 2 TEXT 3 TRUE </pre>
<pre> \doifnotsetups {...¹} {...²} 1 NAME 2 TRUE </pre>
<pre> \doifnotvalue {...¹} {...²} {...³} 1 NAME 2 TEXT 3 TRUE </pre>
<pre> \doifnotvariable {...¹} {...²} {...³} 1 NAME 2 KEY 3 TRUE </pre>
<pre> \doifnumber {...¹} {...²} 1 TEXT 2 TRUE </pre>
<pre> \doifnumberelse {...¹} {...²} {...³} 1 TEXT 2 TRUE 3 FALSE </pre>
<pre> \doifobjectfoundelse {...¹} {...²} {...³} {...⁴} 1 NAME 2 NAME 3 TRUE 4 FALSE </pre>
<pre> \doifobjectreferencefoundelse {...¹} {...²} {...³} {...⁴} 1 NAME 2 NAME 3 TRUE 4 FALSE </pre>
<pre> \doifoddpagelse {...¹} {...²} 1 BEFEHL 2 BEFEHL </pre>
<pre> \doifoddpagefloatelse {...¹} {...²} 1 TRUE 2 FALSE </pre>
<pre> \doifoldercontextelse {...¹} {...²} {...³} 1 NUMMER 2 TRUE 3 FALSE </pre>

```
\doifolderversionelse {...} {...} {...} {...}
1  NUMMER
2  NUMMER
3  TRUE
4  FALSE
```

```
\doifoverlappingelse {...} {...} {...} {...}
1  NAME
2  NAME
3  TRUE
4  FALSE
```

```
\doifoverlayelse {...} {...} {...}
1  NAME
2  TRUE
3  FALSE
```

```
\doifparallelelse {...} {...,2...} {...} {...}
1  NAME
2  NAME vse
3  TRUE
4  FALSE
```

```
\doifparentfileelse {...} {...} {...}
1  FILE
2  TRUE
3  FALSE
```

```
\doifpathelse {...} {...} {...}
1  PATH
2  TRUE
3  FALSE
```

```
\doifpathexistselse {...} {...} {...}
1  PATH
2  TRUE
3  FALSE
```

```
\doifpatternselse {...} {...} {...}
1  SPRACHE
2  TRUE
3  FALSE
```

```
\doifposition {...} {...} {...}
1  NAME
2  TRUE
3  FALSE
```

```
\doifpositionaction {...} {...} {...}
1  NAME
2  TRUE
3  FALSE
```

```
\doifpositionactionelse {...} {...} {...}
1  NAME
2  TRUE
3  FALSE
```

```
\doifpositionelse {...} {...} {...}
1  NAME
2  TRUE
3  FALSE
```

\doifpositiononpageelse {...} {...} {...} {...}

1 NAME
2 NUMMER
3 TRUE
4 FALSE

\doifpositionsonsamepageelse {...,¹...} {...²} {...³}

1 NAME
2 TRUE
3 FALSE

\doifpositionsonthispageelse {...,¹...} {...²} {...³}

1 NAME
2 TRUE
3 FALSE

\doifpositionsusedelse {...¹} {...²}

1 TRUE
2 FALSE

\doifreferencefoundelse {...¹} {...²} {...³}

1 REFERENCE
2 TRUE
3 FALSE

\doifrightpagefloatelse {...¹} {...²}

1 TRUE
2 FALSE

\doifrighttoleftinboxelse ...¹ {...²} {...³}

1 CSNAME NUMMER
2 TRUE
3 FALSE

\doifsamelinereferenceelse {...¹} {...²} {...³}

1 REFERENCE
2 TRUE
3 FALSE

\doifsamestring {...¹} {...²} {...³}

1 TEXT
2 TEXT
3 TRUE

\doifsamestringelse {...¹} {...²} {...³} {...⁴}

1 TEXT
2 TEXT
3 TRUE
4 FALSE

\doifsetups {...¹} {...²}

1 NAME
2 TRUE

\doifsetupselse {...¹} {...²} {...³}

1 NAME
2 TRUE
3 FALSE

\doifsomebackground {...¹} {...²} {...³}

1 NAME
2 TRUE
3 FALSE

\doifsomebackgroundelse {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifsomespaceelse {...} {...} {...}

1 TEXT
2 TRUE
3 FALSE

\doifsomething {...} {...}

1 TEXT
2 TRUE

\doifsomethingelse {...} {...} {...}

1 TEXT
2 TRUE
3 FALSE

\doifsometoks \... {...}

1 CSNAME
2 TRUE

\doifsometokselse \... {...} {...}

1 CSNAME
2 TRUE
3 FALSE

\doifstringinstringelse {...} {...} {...} {...}

1 TEXT
2 TEXT
3 TRUE
4 FALSE

\doifstructurelisthasnumberelse {...} {...}

1 TRUE
2 FALSE

\doifstructurelisthaspageelse {...} {...}

1 TRUE
2 FALSE

\doifsymboldefinedelse {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifsymbolsetelse {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doiftext {...} {...} {...}

1 TEXT
2 TRUE
3 FALSE

\doiftextelse {...} {...} {...}

1 TEXT
2 TRUE
3 FALSE

`\doiftextflowcollectorelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doiftextflowelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doiftopofpageelse {...} {...}`

1 TRUE
2 FALSE

`\doiftypingfileelse {...} {...} {...}`

1 FILE
2 TRUE
3 FALSE

`\doifundefined {...} {...}`

1 NAME
2 TRUE

`\doifundefinedcounter {...} {...}`

1 NAME
2 TRUE

`\doifundefinedelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doifunknownfontfeature {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doifurldefinedelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doifvalue {...} {...} {...}`

1 NAME
2 TEXT
3 TRUE

`\doifvalueelse {...} {...} {...} {...}`

1 NAME
2 TEXT
3 TRUE
4 FALSE

`\doifvaluenothing {...} {...}`

1 NAME
2 TRUE

`\doifvaluenothingelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

\doifvaluesomething { ¹ ...} { ² ...} 1 NAME 2 TRUE
\doifvariable { ¹ ...} { ² ...} { ³ ...} 1 NAME 2 KEY 3 TRUE
\doifvariableelse { ¹ ...} { ² ...} { ³ ...} { ⁴ ...} 1 NAME 2 KEY 3 TRUE 4 FALSE
\doindentation
\dollar
\doloop { [*] ...} * BEFEHL
\doloopoverlist {..., ¹ ...} { ² ...} 1 TEXT 2 BEFEHL
\donothing
\dontconvertfont
\dontleavehmode
\dontpermitspacesbetweenengroups
\dopositionaction { [*] ...} * NAME
\doprocesslocalsetups {..., [*] ...} * NAME
\doquadrupleargument \ ¹ ... [² ...] [³ ...] [⁴ ...] [⁵ ...] 1 CSNAME 2 TEXT 3 TEXT 4 TEXT 5 TEXT
\doquadrupleempty \ ¹ ... [² ...] _{OPT} [³ ...] _{OPT} [⁴ ...] _{OPT} [⁵ ...] _{OPT} 1 CSNAME 2 TEXT 3 TEXT 4 TEXT 5 TEXT
\doquadruplegroupempty \ ¹ ... { ² ...} _{OPT} { ³ ...} _{OPT} { ⁴ ...} _{OPT} { ⁵ ...} _{OPT} 1 CSNAME 2 TEXT 3 TEXT 4 TEXT 5 TEXT

<p><code>\doquintupleargument \¹... [²...] [³...] [⁴...] [⁵...] [⁶...]</code></p> <p>1 CSNAME 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT</p>
<p><code>\doquintupleempty \¹... [²...] [³...] [⁴...] [⁵...] [⁶...]</code></p> <p>1 CSNAME 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT</p>
<p><code>\doquintuplegroupempty \¹... {²...} {³...} {⁴...} {⁵...} {⁶...}</code></p> <p>1 CSNAME 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT</p>
<p><code>\dorecurse {¹...} {²...}</code></p> <p>1 NUMBER 2 BEFEHL</p>
<p><code>\dorechecknextindentation</code></p>
<p><code>\dorepeatwithcommand [¹...] \²...</code></p> <p>1 TEXT NUMBER*TEXT 2 CSNAME</p>
<p><code>\doreplacefeature {...,*...}</code></p> <p>* NAME</p>
<p><code>\doresetandafffeature {...,*...}</code></p> <p>* NAME</p>
<p><code>\doresetattribute {[*]...}</code></p> <p>* NAME</p>
<p><code>\dorotatebox {¹...} \²... {³...}</code></p> <p>1 NUMBER 2 CSNAME 3 CONTENT</p>
<p><code>\dosetattribute {¹...} {²...}</code></p> <p>1 NAME 2 NUMBER</p>
<p><code>\dosetleftskipadaption {[*]...}</code></p> <p>* ano ne standardni DIMENSION</p>
<p><code>\dosetrighskipadaption {[*]...}</code></p> <p>* ano ne standardni DIMENSION</p>
<p><code>\dosetupcheckedinterlinespace {...,*...,...}</code></p> <p>* inherits: \nastavmeziradkovoumezeru</p>
<p><code>\dosetupcheckedinterlinespace {...,*...,...}</code></p> <p>* zap vyp reset auto male stredni velke NUMBER DIMENSION</p>

<pre> \dosetupcheckedinterlinespace {...} * NAME </pre>
<pre> \doseventupleargument \¹... [²...] [³...] [⁴...] [⁵...] [⁶...] [⁷...] [⁸...] 1 CSNAME 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT 7 TEXT 8 TEXT </pre>
<pre> \doseventupleempty \¹... [²...] [³...] [⁴...] [⁵...] [⁶...] [⁷...] [⁸...] 1 CSNAME 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT 7 TEXT 8 TEXT </pre>
<pre> \dosingleargument \¹... [²...] 1 CSNAME 2 TEXT </pre>
<pre> \dosingleempty \¹... [²...] 1 CSNAME 2 TEXT </pre>
<pre> \dosinglegroupempty \¹... {²...} 1 CSNAME 2 TEXT </pre>
<pre> \dosixtupleargument \¹... [²...] [³...] [⁴...] [⁵...] [⁶...] [⁷...] 1 CSNAME 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT 7 TEXT </pre>
<pre> \dosixtupleempty \¹... [²...] [³...] [⁴...] [⁵...] [⁶...] [⁷...] 1 CSNAME 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT 7 TEXT </pre>
<pre> \dostarttagged {¹...} {²...} ... \dostoptagged 1 NAME 2 NAME </pre>
<pre> \dostepwiserecurse {¹...} {²...} {³...} {⁴...} 1 NUMBER 2 NUMBER 3 [-+]NUMBER 4 BEFEHL </pre>
<pre> \dosubtractfeature {...,*...} * NAME </pre>

`\dotfskip {...}`
* DIMENSION

`\dotoks \...`
* CSNAME

`\dotripleargument \1... [2...] [3] [4]`
1 CSNAME
2 TEXT
3 TEXT
4 TEXT

`\dotripleargumentwithset \1... [2...,...] [3] [4]`
1 CSNAME
2 TEXT
3 TEXT
4 TEXT

`\dotripleempty \1... [2] [3] [4]`
1 CSNAME
2 TEXT
3 TEXT
4 TEXT

`\dotripleemptywithset \1... [2...,...] [3] [4]`
1 CSNAME
2 TEXT
3 TEXT
4 TEXT

`\dotriplegroupempty \1... {2} {3} {4}`
1 CSNAME
2 TEXT
3 TEXT
4 TEXT

`\doublebond`

`\dowith {...1,...} {...2}`
1 BEFEHL
2 BEFEHL

`\dowithnextbox {...1} \2... {...3}`
1 BEFEHL
2 CSNAME
3 CONTENT

`\dowithnextboxcontent {...1} {...2} \3... {...4}`
1 BEFEHL
2 BEFEHL
3 CSNAME
4 CONTENT

`\dowithnextboxcontentcs \1... \2... \3... {...4}`
1 CSNAME
2 CSNAME
3 CSNAME
4 CONTENT

`\dowithnextboxcs \1... \2... {...3}`
1 CSNAME
2 CSNAME
3 CONTENT

<code>\dowithpargument *..</code> <code>* CSNAME</code>
<code>\dowithrange {...¹...} *..</code> <code>1 NUMBER NUMBER:NUMBER</code> <code>2 CSNAME</code>
<code>\dowithwargument *..</code> <code>* CSNAME</code>
<code>\dpofstring {...}</code> <code>* TEXT</code>
<code>\dummydigit</code>
<code>\dummyparameter {...}</code> <code>* KEY</code>
<code>\ETEX</code>
<code>\EveryLine {...}</code> <code>* BEFEHL</code>
<code>\EveryPar {...}</code> <code>* BEFEHL</code>
<code>\edefconvertedargument *¹... {..²..}</code> <code>1 CSNAME</code> <code>2 TEXT</code>
<code>\efcmaxheight {...}</code> <code>* NAME</code>
<code>\efcmaxwidth {...}</code> <code>* NAME</code>
<code>\efcminheight {...}</code> <code>* NAME</code>
<code>\efcminwidth {...}</code> <code>* NAME</code>
<code>\efcparameter {...¹} {...²..}</code> <code>1 NAME</code> <code>2 KEY</code>
<code>\effect [...¹] {...²..}</code> <code>1 NAME</code> <code>2 CONTENT</code>
<code>\elapsedseconds</code>
<code>\elapsedtime</code>
<code>\em</code>
<code>\emphasisboldface</code>

<code>\emphasistypeface</code>
<code>\emptylines [...]</code> * NUMMER OPT
<code>\emspace</code>
<code>\enabledirectives [...,*,...]</code> * NAME
<code>\enableexperiments [...,*,...]</code> * NAME
<code>\enablemode [...,*,...]</code> * NAME
<code>\enableoutputstream [...]</code> * NAME
<code>\enableparpositions</code>
<code>\enableregime [...]</code> * cp1250 cp1251 cp1252 cp1253 cp1254 cp1255 cp1256 cp1257 cp1258 8859-1 8859-2 8859-3 8859-4 8859-9 8859-10 8859-13 8859-14 8859-15 8859-16 utf windows-1250 windows-1251 windows-1252 windows-1253 windows-1254 windows-1255 windows- 1256 windows-1257 windows-1258 il1 il2 il3 il4 il5 il6 il7 il8 il9 il10 iso-8859-1 iso-8859-2 iso-8859-3 iso- 8859-4 iso-8859-9 iso-8859-10 iso-8859-13 iso-8859-14 iso-8859-15 iso-8859-16 latin1 latin2 latin3 latin4 latin5 latin6 latin7 latin8 latin9 latin10 utf-8 utf8 windows
<code>\enabletrackers [...,*,...]</code> * NAME
<code>\enskip</code>
<code>\enspace</code>
<code>\env {...}</code> * KEY
<code>\envvar {...} {...}</code> 1 KEY 2 BEFEHL
<code>\epos {...}</code> * NAME
<code>\equaldigits {...}</code> * TEXT
<code>\eTeX</code>
<code>\executeifdefined {...} {...}</code> 1 NAME 2 BEFEHL
<code>\exitloop</code>
<code>\exitloopnow</code>

<code>\expanded {...}</code> * CONTENT
<code>\expandfontsynonym \¹... {²...}</code> 1 CSNAME 2 NAME
<code>\expandcheckedcsname \¹... {²...} {³...}</code> 1 CSNAME 2 KEY 3 TEXT
<code>\expdoif {¹...} {²...} {³...}</code> 1 CONTENT 2 CONTENT 3 TRUE
<code>\expdoifcommonelse {¹...,...} {²...,...} {³...} {⁴...}</code> 1 TEXT 2 TEXT 3 TRUE 4 FALSE
<code>\expdoifelse {¹...} {²...} {³...} {⁴...}</code> 1 CONTENT 2 CONTENT 3 TRUE 4 FALSE
<code>\expdoifelsecommon {¹...,...} {²...,...} {³...} {⁴...}</code> 1 TEXT 2 TEXT 3 TRUE 4 FALSE
<code>\expdoifelseinset {¹...} {²...,...} {³...} {⁴...}</code> 1 TEXT 2 TEXT 3 TRUE 4 FALSE
<code>\expdoifinsetelse {¹...} {²...,...} {³...} {⁴...}</code> 1 TEXT 2 TEXT 3 TRUE 4 FALSE
<code>\expdoifnot {¹...} {²...} {³...}</code> 1 CONTENT 2 CONTENT 3 TRUE
<code>\externalfigurecollectionmaxheight {...}</code> * NAME
<code>\externalfigurecollectionmaxwidth {...}</code> * NAME
<code>\externalfigurecollectionminheight {...}</code> * NAME
<code>\externalfigurecollectionminwidth {...}</code> * NAME

\externalfigurecollectionparameter {...} {...} 1 NAME 2 KEY
\externiobraz [...] ¹ [...] ² [...,... ³ ...,...] 1 FILE 2 NAME 3 inherits: \setupexternalfigure OPT OPT
\fakebox ... * CSNAME NUMBER
\fastdecrement \... * CSNAME
\fastincrement \... * CSNAME
\fastlocalframed [...] ¹ [...,... ² ...,...] ³ {...} 1 NAME 2 inherits: \nastavoramovani 3 CONTENT
\fastloopfinal
\fastloopindex
\fastscale {...} ¹ {...} ² 1 NUMBER 2 CONTENT
\fastsetup {...} * NAME
\fastsetupwithargument {...} ¹ {...} ² 1 NAME 2 CONTENT
\fastsetupwithargumentswapped {...} ¹ {...} ² 1 CONTENT 2 NAME
\fastswitchtobodyfont {...} * x xx male velke script scriptscript
\fastsxsy {...} ¹ {...} ² {...} ³ 1 NUMBER 2 NUMBER 3 CONTENT
\feature [...] ¹ [..., ² ...] 1 + - = ! > < more less novy reset implicitni old lokalne 2 NAME
\feature {...} ¹ {..., ² ...} 1 + - = ! > < more less novy reset implicitni old lokalne 2 NAME
\fence

<pre> \fenced [...] {...} 1 NAME 2 CONTENT </pre>
<pre> \FENCE {...} * CONTENT </pre>
<pre> \fetchallmarkings [...] [...] 1 BESCHRIFTUNG 2 stranka NAME </pre>
<pre> \fetchallmarks [...] * BESCHRIFTUNG </pre>
<pre> \fetchmark [...] [...] 1 BESCHRIFTUNG OPT 2 prvni posledni aktualni predchozi dalsi vrsek spodek implicitni obe vse first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck </pre>
<pre> \fetchmarking [...] [...] [...] 1 BESCHRIFTUNG 2 stranka NAME 3 prvni posledni aktualni predchozi dalsi vrsek spodek implicitni obe vse first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck </pre>
<pre> \fetchonemark [...] [...] 1 BESCHRIFTUNG OPT 2 prvni posledni aktualni predchozi dalsi vrsek spodek implicitni obe vse first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck </pre>
<pre> \fetchonemarking [...] [...] [...] 1 BESCHRIFTUNG 2 stranka NAME 3 prvni posledni aktualni predchozi dalsi vrsek spodek implicitni obe vse first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck </pre>
<pre> \fetchruntimecommand \... {...} 1 CSNAME 2 FILE </pre>
<pre> \fetchtwomarkings [...] [...] 1 BESCHRIFTUNG 2 stranka NAME </pre>
<pre> \fetchtwomarks [...] * BESCHRIFTUNG </pre>
<pre> \fieldbody [...] [...] [...] 1 NAME OPT 2 inherits: \setupfieldbody </pre>
<pre> \fifthoffivearguments {...} {...} {...} {...} {...} 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT </pre>

<p><code>\fifthofsixarguments {...} {...} {...} {...} {...} {...}</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 TEXT</p> <p>4 TEXT</p> <p>5 TEXT</p> <p>6 TEXT</p>
<code>\figurefilename</code>
<code>\figurefilepath</code>
<code>\figurefiletype</code>
<code>\figurefullname</code>
<code>\figureheight</code>
<code>\figurenaturalheight</code>
<code>\figurenaturalwidth</code>
<p><code>\figuresymbol [...] [...²...]</code></p> <p>1 FILE NAME</p> <p>2 inherits: \externiobraz</p>
<code>\figurewidth</code>
<p><code>\filename {...}</code></p> <p>* FILE</p>
<p><code>\filledhboxb ¹... {...}</code></p> <p>1 TEXT</p> <p>2 CONTENT</p>
<p><code>\filledhboxc ¹... {...}</code></p> <p>1 TEXT</p> <p>2 CONTENT</p>
<p><code>\filledhboxg ¹... {...}</code></p> <p>1 TEXT</p> <p>2 CONTENT</p>
<p><code>\filledhboxk ¹... {...}</code></p> <p>1 TEXT</p> <p>2 CONTENT</p>
<p><code>\filledhboxm ¹... {...}</code></p> <p>1 TEXT</p> <p>2 CONTENT</p>
<p><code>\filledhboxr ¹... {...}</code></p> <p>1 TEXT</p> <p>2 CONTENT</p>
<p><code>\filledhboxy ¹... {...}</code></p> <p>1 TEXT</p> <p>2 CONTENT</p>

\filler [...] * sym symbol linka sirka mezera NAME
\filterfromnext {...} {...} {...} {...} {...} {...} {...} 1 NUMBER OPT OPT OPT OPT OPT 2 NUMBER 3 CONTENT 4 CONTENT 5 CONTENT 6 CONTENT 7 CONTENT
\filterfromvalue {...} {...} {...} 1 NAME 2 NUMBER 3 NUMBER
\filterpages [...] ¹ [..., ² ...] [..., ³ ...,...] OPT 1 FILE 2 sude liche NUMBER NUMBER:NUMBER 3 sirka = DIMENSION n = NUMBER category = NAME
\filterreference {...} * implicitni text titul cislo stranka realpage
\findtwopassdata {...} {...} 1 NAME 2 NAME
\finishregisterentry [...] ¹ [..., ² ...,...] [..., ³ ...,...] OPT 1 NAME 2 popisek = NAME keys = TEXT PROCESSOR->TEXT entries = TEXT PROCESSOR->TEXT alternativa = TEXT 3 KEY = VALUE
\firstcounter [...] ¹ [...] ² OPT 1 NAME 2 NUMBER
\firstcountervalue [...] [*] * NAME
\firstcharacter
\firstoffivearguments {...} {...} {...} {...} {...} 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT
\firstoffourarguments {...} {...} {...} {...} 1 TEXT 2 TEXT 3 TEXT 4 TEXT
\firstofoneargument {...} * TEXT

<code>\firstofoneunexpanded {...}</code> * TEXT
<code>\firstofsixarguments {...} {...} {...} {...} {...} {...}</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT
<code>\firstofthreearguments {...} {...} {...}</code> 1 TEXT 2 TEXT 3 TEXT
<code>\firstofthreeunexpanded {...} {...} {...}</code> 1 TEXT 2 TEXT 3 TEXT
<code>\firstoftwoarguments {...} {...}</code> 1 TEXT 2 TEXT
<code>\firstoftwounexpanded {...} {...}</code> 1 TEXT 2 TEXT
<code>\firstrealpage</code>
<code>\firstrealpagenumber</code>
<code>\firstsubcountervalue [...] [...]</code> 1 NAME 2 NUMMER
<code>\firstsubpagenumber</code>
<code>\firstuserpage</code>
<code>\firstuserpagenumber</code>
<code>\fitfieldframed [...¹..._{OPT}...] {...}</code> 1 inherits: \nastavoramovan ^{OPT} 2 CONTENT
<code>\fittopbaselinegrid {...}</code> * CONTENT
<code>\flag {...}</code> * NAME
<code>\floatuserdataparameter {...}</code> * KEY
<code>\flushbox {...} {...}</code> 1 NAME 2 NAME

\flushboxregister ... * CSNAME NUMMER
\flushcollector [...] * NAME
\flushedrightlastline
\flushlayer [...] * NAME
\flushlocalfloats
\flushnextbox
\flushnotes
\flushoutputstream [...] * NAME
\flushshapebox
\flushtextflow {...} * NAME
\flushtokens [...] * NAME
\flushtoks \... * CSNAME
\fontalternative
\fontbody
\fontclass
\fontclassname {...} {...} 1 NAME 2 FONT
\fontface
\fontfeaturelist [...] ¹ [...] ² 1 NAME 2 TEXT
\fontchar {...} * NAME
\fontcharbyindex {...} * NUMMER
\fontsize
\fontstyle

<code>\footnotetext [...¹,...] {...²}</code> 1 REFERENCE OPT 2 TEXT
<code>\footnotetext [...[*],...] [...[*],...]</code> * titul = TEXT * zalozka = TEXT * seznam = TEXT * odkaz = REFERENCE
<code>\forcecharacterstripping</code>
<code>\forcelocalfloats</code>
<code>\forgeteverypar</code>
<code>\forgetparameters [...¹] [...²,...,...]</code> 1 TEXT 2 KEY = VALUE
<code>\forgetragged</code>
<code>\foundbox {...¹} {...²}</code> 1 NAME 2 NAME
<code>\fourthoffivearguments {...¹} {...²} {...³} {...⁴} {...⁵}</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT
<code>\fourthoffourarguments {...¹} {...²} {...³} {...⁴}</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT
<code>\fourthofsixarguments {...¹} {...²} {...³} {...⁴} {...⁵} {...⁶}</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT
<code>\frameddimension {...[*]}</code> * KEY
<code>\framedparameter {...[*]}</code> * KEY
<code>\freezedimenmacro \.¹ \.²..</code> 1 CSNAME 2 CSNAME
<code>\freezemeasure [...¹] [...²..]</code> 1 NAME 2 DIMENSION
<code>\frenchspacing</code>

<code>\fromlinenote [.¹.] {.².}</code> 1 REFERENCE 2 TEXT
<code>\frozenhbox {.*.}</code> * CONTENT
<code>\frule .. .[*].. .. \relax</code> * width _⌈ DIMENSION height _⌈ DIMENSION depth _⌈ DIMENSION radius _⌈ DIMENSION line _⌈ DIMENSION type _⌈ TEXT data _⌈ TEXT name _⌈ TEXT
<code>\GetPar</code>
<code>\GotoPar</code>
<code>\Greeknumerals {.*.}</code> * NUMMER
<code>\gdefconvertedargument \.¹.. {.².}</code> 1 CSNAME 2 TEXT
<code>\gdefconvertedcommand \.¹.. \.²..</code> 1 CSNAME 2 CSNAME
<code>\getboxfromcache {.¹..} {.².} .³..</code> 1 NAME 2 NUMMER TEXT 3 CSNAME NUMMER
<code>\getboxllx .[*]..</code> * CSNAME NUMMER
<code>\getboxlly .[*]..</code> * CSNAME NUMMER
<code>\getbufferdata [.[*]..]</code> * BUFFER OPT
<code>\getcommacommandsize [...,[*]...]</code> * BEFEHL
<code>\getcommalistsize [...,[*]...]</code> * BEFEHL
<code>\getdayoftheweek {.¹..} {.².} {.³.}</code> 1 NUMMER 2 NUMMER 3 NUMMER
<code>\getdayspermonth {.¹..} {.².}</code> 1 NUMMER 2 NUMMER
<code>\getdefinedbuffer [.[*]..]</code> * BUFFER
<code>\getdocumentargument {.*.}</code> * NAME

<pre> \getdocumentargumentdefault {...} {...} 1 NAME 2 TEXT </pre>
<pre> \getdocumentfilename {...} * NUMMER </pre>
<pre> \getdummyparameters [...,..²...,...] * KEY = VALUE </pre>
<pre> \getemptyparameters [...,..²...,...] 1 TEXT 2 KEY = VALUE </pre>
<pre> \getparameters [...,..²...,...] 1 TEXT 2 KEY = VALUE </pre>
<pre> \getexpandedparameters [...,..²...,...] 1 TEXT 2 KEY = VALUE </pre>
<pre> \getfiguredimensions [...,..²...,...] 1 FILE 2 inherits: \setupexternalfigure OPT </pre>
<pre> \getfirstcharacter {...} * TEXT </pre>
<pre> \getfirsttwopassdata {...} * NAME </pre>
<pre> \getfromcommacommand [...,¹...] [...²] 1 BEFEHL 2 NUMMER </pre>
<pre> \getfromcommalist [...,¹...] [...²] 1 BEFEHL 2 NUMMER </pre>
<pre> \getfromtwopassdata {...} {...} 1 NAME 2 NAME </pre>
<pre> \getglyphdirect {...} {...} 1 FONT 2 NUMMER CHARACTER </pre>
<pre> \getglyphstyled {...} {...} 1 FONT 2 NUMMER CHARACTER </pre>
<pre> \getgparameters [...,..²...,...] 1 TEXT 2 KEY = VALUE </pre>
<pre> \getlasttwopassdata {...} * NAME </pre>

\getlocalfloat {...} * NUMBER
\getlocalfloats
\getMPdrawing
\getMPlayer [...] ¹ [...,... ² ...,...] ² {...} ³ 1 NAME 2 inherits: \nastavoramovani 3 CONTENT
\getmessage {...} ¹ {...} ² 1 NAME 2 NAME NUMBER
\getnamedglyphdirect {...} ¹ {...} ² 1 FONT 2 NAME
\getnamedglyphstyled {...} ¹ {...} ² 1 FONT 2 NAME
\getnamedtwopassdatalist \... {...} ¹ {...} ² 1 CSNAME 2 NAME
\getnaturaldimensions ... * CSNAME NUMBER
\getnoflines {...} * DIMENSION
\getobject {...} ¹ {...} ² 1 NAME 2 NAME
\getobjectdimensions {...} ¹ {...} ² 1 NAME 2 NAME
\getpaletsize [...] * NAME
\getparameters [...] ¹ [...,... ² ...,...] 1 TEXT 2 KEY = VALUE
\getprivatechar {...} * NAME
\getprivateslot {...} * NAME
\getrandomcount \... {...} ¹ {...} ² {...} ³ 1 CSNAME 2 NUMBER 3 NUMBER

\getrandomdimen \ ¹ ... {\ ² ...} {\ ³ ...} 1 CSNAME 2 DIMENSION 3 DIMENSION
\getrandomfloat \ ¹ ... {\ ² ...} {\ ³ ...} 1 CSNAME 2 NUMBER 3 NUMBER
\getrandomnumber \ ¹ ... {\ ² ...} {\ ³ ...} 1 CSNAME 2 NUMBER 3 NUMBER
\getrandomseed *.. * CSNAME
\getraweparameters [¹ ...] [..., ² ...] 1 TEXT 2 KEY = VALUE
\getrawgparameters [¹ ...] [..., ² ...] 1 TEXT 2 KEY = VALUE
\getrawnoflines {*.. * DIMENSION
\getrawparameters [¹ ...] [..., ² ...] 1 TEXT 2 KEY = VALUE
\getrawxparameters [¹ ...] [..., ² ...] 1 TEXT 2 KEY = VALUE
\getreference [¹ ...] [² .. 1 implicitni text titul cislo stranka realpage 2 REFERENCE
\getreferenceentry {*.. * implicitni text titul cislo stranka realpage
\getroundednoflines {*.. * DIMENSION
\getsubstring {\ ¹ ...} {\ ² ...} {\ ³ ...} 1 NUMBER 2 NUMBER 3 TEXT
\gettwopassdata {*.. * NAME
\gettwopassdatalist {*.. * NAME
\getuvalue {*.. * NAME

<pre>\getvalue {...} * NAME</pre>
<pre>\getvariable {...} {...} 1 NAME 2 KEY</pre>
<pre>\getvariabledefault {...} {...} {...} 1 NAME 2 KEY 3 BEFEHL</pre>
<pre>\getxparameters [...] [..., ...²..., ...] 1 TEXT 2 KEY = VALUE</pre>
<pre>\globaldisablemode [..., ...] * NAME</pre>
<pre>\globalenablemode [..., ...] * NAME</pre>
<pre>\globalletempty *.. * CSNAME</pre>
<pre>\globalpopbox ... * CSNAME NUMBER</pre>
<pre>\globalpopmacro *.. * CSNAME</pre>
<pre>\globalpreventmode [..., ...] * NAME</pre>
<pre>\globalprocesscommalist [...] *.. 1 BEFEHL 2 CSNAME</pre>
<pre>\globalpushbox ... * CSNAME NUMBER</pre>
<pre>\globalpushmacro *.. * CSNAME</pre>
<pre>\globalpushreferenceprefix {...} ... \globalpopreferenceprefix * + - TEXT</pre>
<pre>\globalswapcounts *.. *.. 1 CSNAME 2 CSNAME</pre>
<pre>\globalswapdimens *.. *.. 1 CSNAME 2 CSNAME</pre>
<pre>\globalswapmacros *.. *.. 1 CSNAME 2 CSNAME</pre>

`\globalundefine {...}`

* NAME

`\glyphfontfile {...}`

* FONT

`\gobbledoubleempty [...]1 [...]2`

1 TEXT

OPT

OPT

2 TEXT

`\gobbleeightarguments {...}1 {...}2 {...}3 {...}4 {...}5 {...}6 {...}7 {...}8`

1 CONTENT

2 CONTENT

3 CONTENT

4 CONTENT

5 CONTENT

6 CONTENT

7 CONTENT

8 CONTENT

`\gobblefivearguments {...}1 {...}2 {...}3 {...}4 {...}5`

1 CONTENT

2 CONTENT

3 CONTENT

4 CONTENT

5 CONTENT

`\gobblefiveoptionals [...]1 [...]2 [...]3 [...]4 [...]5`

1 TEXT

2 TEXT

3 TEXT

4 TEXT

5 TEXT

`\gobblefourarguments {...}1 {...}2 {...}3 {...}4`

1 CONTENT

2 CONTENT

3 CONTENT

4 CONTENT

`\gobblefouroptionals [...]1 [...]2 [...]3 [...]4`

1 TEXT

2 TEXT

3 TEXT

4 TEXT

`\gobbleninearguments {...}1 {...}2 {...}3 {...}4 {...}5 {...}6 {...}7 {...}8 {...}9`

1 CONTENT

2 CONTENT

3 CONTENT

4 CONTENT

5 CONTENT

6 CONTENT

7 CONTENT

8 CONTENT

9 CONTENT

`\gobbleoneargument {...}`

* CONTENT

`\gobbleoneoptional [...]`

* TEXT

\gobblesevenarguments {...} {...} {...} {...} {...} {...} {...}

1 CONTENT
2 CONTENT
3 CONTENT
4 CONTENT
5 CONTENT
6 CONTENT
7 CONTENT

\gobblesingleempty [...]

* TEXT OPT

\gobblesixarguments {...} {...} {...} {...} {...} {...}

1 CONTENT
2 CONTENT
3 CONTENT
4 CONTENT
5 CONTENT
6 CONTENT

\gobblespacetokens

\gobbletenarguments {...} {...} {...} {...} {...} {...} {...} {...} {...} {...}

1 CONTENT
2 CONTENT
3 CONTENT
4 CONTENT
5 CONTENT
6 CONTENT
7 CONTENT
8 CONTENT
9 CONTENT
10 CONTENT

\gobblethreearguments {...} {...} {...}

1 CONTENT
2 CONTENT
3 CONTENT

\gobblethreeoptionals [...] [...] [...]

1 TEXT
2 TEXT
3 TEXT

\gobbletwoarguments {...} {...}

1 CONTENT
2 CONTENT

\gobbletwooptionals [...] [...]

1 TEXT
2 TEXT

\gobbleuntil \...

* CSNAME

\gobbleuntilrelax ... \relax

* CONTENT

\grabbufferdata [...] [...] [...] [...]

1 CATEGORY OPT
2 NAME
3 NAME
4 NAME

<code>\grabbufferdatadirect {...} {...} {...}</code> 1 NAME 2 NAME 3 NAME
<code>\grabuntil {...} \^2..</code> 1 NAME 2 CSNAME
<code>\grave {...}</code> * CHARACTER
<code>\grayvalue {...}</code> * COLOR
<code>\greedystring ... \at ^2. \to \^3. \and \^4.</code> 1 TEXT 2 TEXT 3 CSNAME 4 CSNAME
<code>\greeknumerals {...}</code> * NUMBER
<code>\groupedcommand {...} {...}</code> 1 BEFEHL 2 BEFEHL
<code>\gsetboxllx ... {...}</code> 1 CSNAME NUMBER 2 DIMENSION
<code>\gsetboxlly ... {...}</code> 1 CSNAME NUMBER 2 DIMENSION
<code>\gujaratinumerals {...}</code> * NUMBER
<code>\gurmukhinumerals {...}</code> * NUMBER
<code>\hairspace</code>
<code>\halflinestrut</code>
<code>\halfstrut</code>
<code>\halfwaybox {...}</code> * CONTENT
<code>\handletokens ... \with \^2.</code> 1 TEXT 2 CSNAME
<code>\hash</code>
<code>\hat {...}</code> * CHARACTER

<code>\hboxofvbox ...</code> <code>* CSNAME NUMBER</code>
<code>\hboxreference [...¹,...] {...²}</code> <code>1 REFERENCE</code> <code>2 CONTENT</code>
<code>\hboxBOX {...}</code> <code>* CONTENT</code>
<code>\hdofstring {...}</code> <code>* TEXT</code>
<code>\headhbox ...¹ {...²}</code> <code>1 TEXT OPT</code> <code>2 CONTENT</code>
<code>\headnumbercontent</code>
<code>\headnumberdistance</code>
<code>\headnumberwidth</code>
<code>\headreferenceattributes</code>
<code>\headsetupspacing</code>
<code>\headtextcontent</code>
<code>\headtextdistance</code>
<code>\headtextwidth</code>
<code>\headvbox ...¹ {...²}</code> <code>1 TEXT OPT</code> <code>2 CONTENT</code>
<code>\headwidth</code>
<code>\heightanddepthofstring {...}</code> <code>* TEXT</code>
<code>\heightofstring {...}</code> <code>* TEXT</code>
<code>\heightspanningtext {...¹} {...²} {...³}</code> <code>1 TEXT</code> <code>2 DIMENSION</code> <code>3 FONT</code>
<code>\HELP [...¹] {...²} {...³}</code> <code>1 REFERENCE</code> <code>2 TEXT</code> <code>3 TEXT</code> <code>instances: helptext</code>

<code>\helptext [...] {...} {...}</code> 1 REFERENCE <small>OPT</small> 2 TEXT 3 TEXT
<code>\hglue ...</code> * DIMENSION
<code>\hiddencitation [...]</code> * REFERENCE
<code>\hiddencite [...]</code> * REFERENCE
<code>\highlight [...]¹ {...}²</code> 1 NAME 2 TEXT
<code>\HIGHLIGHT {...}</code> * TEXT
<code>\highordinalstr {...}</code> * TEXT
<code>\hilo [...]¹ {...}² {...}³</code> 1 <small>vlevo</small> <small>OPT</small> <small>pravo</small> 2 CONTENT 3 CONTENT
<code>\himilo {...}¹ {...}² {...}³</code> 1 CONTENT 2 CONTENT 3 CONTENT
<code>\hl [...]</code> * NUMBER
<code>\hlavnijazyk [...]</code> * SPRACHE
<code>\hodnotabarvy {...}</code> * COLOR
<code>\horizontalgrowingbar [...,[*]...,...]</code> * inherits: \setuppositionbar
<code>\horizontalpositionbar [...,[*]...,...]</code> * inherits: \setuppositionbar
<code>\hphantom {...}</code> * CONTENT
<code>\hpos {...}¹ {...}²</code> 1 NAME 2 CONTENT
<code>\hsizefraction {...}¹ {...}²</code> 1 DIMENSION 2 NUMBER

<code>\hsmash {...}</code> * CONTENT
<code>\hsmashbox ...</code> * CSNAME NUMBER
<code>\hsmashed {...}</code> * CONTENT
<code>\hspace [...]¹ [...]²</code> 1 NAME OPT OPT 2 male sredni velke normalni implicitni zadny .5 1 2 3 speech citovat interquotation citace sentence intersentence NAME
<code>\htdpofstring {...}</code> * TEXT
<code>\htofstring {...}</code> * TEXT
<code>\hyphen</code>
<code>\hyphenatedcoloredword {...}</code> * TEXT
<code>\hyphenatedfile {...}</code> * FILE
<code>\hyphenatedfilename {...}</code> * TEXT
<code>\hyphenatedhbox {...}</code> * CONTENT
<code>\hyphenatedpar {...}</code> * TEXT
<code>\hyphenatedurl {...}</code> * TEXT
<code>\hyphenatedword {...}</code> * TEXT
<code>\CHARACTERKERNING [...]¹ {...}²</code> 1 NUMBER OPT 2 TEXT
<code>\chardescription {...}</code> * NUMBER
<code>\charwidthlanguage</code>
<code>\check {...}</code> * CHARACTER
<code>\checkedfiller {...}</code> * sym symbol linka sirka mezera NAME BEFEHL

\checkedchar {...} {...} 1 NUMMER 2 CHARACTER
\checkedstrippedcsname *.. * CSNAME
\checkedstrippedcsname *.. * TEXT
\checkcharacteralign {...} * CONTENT
\checkinjector [...] * NAME
\checknextindentation [...] * ano ne auto
\checknextinjector [...] * NAME
\checkpage [...] ¹ [...,... ² ...] _{OPT} 1 NAME 2 inherits: \setuppagechecker
\checkparameters [...] * TEXT
\checkpreviousinjector [...] * NAME
\checksoundtrack {...} * NAME
\checktwopassdata {...} * NAME
\checkvariables [...] ¹ [...,... ² ...] 1 NAME 2 set = BEFEHL reset = BEFEHL KEY = VALUE
\chem {...} ¹ {...} ² {...} ³ 1 TEXT 2 TEXT 3 TEXT
\chemical [...] ¹ [...,... ² ...] _{OPT} [...,... ³ ...] _{OPT} 1 NAME 2 TEXT 3 TEXT
\chemicalbottext {...} * TEXT
\chemicalmidtext {...} * TEXT

<code>\chemicalsymbol [...]</code> * NAME
<code>\chemicaltext {...}</code> * TEXT
<code>\chemicaltopertext {...}</code> * TEXT
<code>\chineseallnumerals {...}</code> * NUMMER
<code>\chinesecapnumerals {...}</code> * NUMMER
<code>\chinesenumerals {...}</code> * NUMMER
<code>\INRSTEX</code>
<code>\ibox {...}</code> * CONTENT
<code>\ifassignment ...¹ \else ...² \fi</code> 1 TRUE 2 FALSE
<code>\iff</code>
<code>\ifinobject ...¹ \else ...² \fi</code> 1 TRUE 2 FALSE
<code>\ifinoutputstream ...¹ \else ...² \fi</code> 1 TRUE 2 FALSE
<code>\ifparameters ...¹ \else ...² \fi</code> 1 TRUE 2 FALSE
<code>\iftrialtypesetting ...¹ \else ...² \fi</code> 1 TRUE 2 FALSE
<code>\ignoreimplicitspaces</code>
<code>\ignorevalue {...}</code> * NAME
<code>\immediatesavetwopassdata {...¹} {...²} {...³}</code> 1 NAME 2 NUMMER 3 CONTENT
<code>\impliedby</code>
<code>\implies</code>

<code>\inlineprettyprintbuffer {¹...} {²...}</code> 1 BUFFER 2 mp lua xml parsed-xml nested tex context zadny NAME
<code>\inlinerange [...]</code> * REFERENCE
<code>\innerflushshapebox</code>
<code>\input {[*]...}</code> * FILE
<code>\inputfilebarename</code>
<code>\inputfilename</code>
<code>\inputfilerealsuffix</code>
<code>\inputfilesuffix</code>
<code>\inputgivenfile {[*]...}</code> * FILE
<code>\input [*]...</code> * FILE
<code>\insertpages [¹...] [²...,³...] [³...,³...,³...]</code> 1 FILE 2 NUMBER 3 sirka = DIMENSION n = NUMMER category = NAME
<code>\instalacejazyka [¹...] [²...,²...,²...]</code> 1 NAME 2 inherits: \nastavjazyk
<code>\instalacejazyka [¹...] [²...]</code> 1 NAME 2 SPRACHE
<code>\installactionhandler {[*]...}</code> * NAME
<code>\installactivecharacter [*]...</code> * CHARACTER
<code>\installanddefineactivecharacter ¹... {²...}</code> 1 CHARACTER 2 BEFEHL
<code>\installattributestack \[*]...</code> * CSNAME
<code>\installautocommandhandler \¹... {²...} \³...</code> 1 CSNAME 2 NAME 3 CSNAME

<pre> \installautosetuphandler \... {^2} 1 CSNAME 2 NAME </pre>
<pre> \installbasicautosetuphandler \... {^2} \... 1 CSNAME 2 NAME 3 CSNAME </pre>
<pre> \installbasicparameterhandler \... {^2} 1 CSNAME 2 NAME </pre>
<pre> \installbottomframerenderer {^1} {^2} 1 NAME 2 BEFEHL </pre>
<pre> \installcommandhandler \... {^2} \... 1 CSNAME 2 NAME 3 CSNAME </pre>
<pre> \installcorenamespace {^*} * NAME </pre>
<pre> \installdefinehandler \... {^2} \... 1 CSNAME 2 NAME 3 CSNAME </pre>
<pre> \installdefinitionset \... {^2} 1 CSNAME 2 NAME </pre>
<pre> \installdefinitionsetmember \... {^2} \... {^4} 1 CSNAME 2 NAME 3 CSNAME 4 NAME </pre>
<pre> \installdirectcommandhandler \... {^2} 1 CSNAME 2 NAME </pre>
<pre> \installdirectparameterhandler \... {^2} 1 CSNAME 2 NAME </pre>
<pre> \installdirectparametersethandler \... {^2} 1 CSNAME 2 NAME </pre>
<pre> \installdirectsetuphandler \... {^2} 1 CSNAME 2 NAME </pre>
<pre> \installdirectstyleandcolorhandler \... {^2} 1 CSNAME 2 NAME </pre>

<pre> \installframedautocommandhandler \... {...} \... 1 CSNAME 2 NAME 3 CSNAME </pre>
<pre> \installframedcommandhandler \... {...} \... 1 CSNAME 2 NAME 3 CSNAME </pre>
<pre> \installleftframerenderer {...} {...} 1 NAME 2 BEFEHL </pre>
<pre> \installnamespace {...} * NAME </pre>
<pre> \installoutputroutine \... {...} 1 CSNAME 2 BEFEHL </pre>
<pre> \installpagearrangement ... {...} 1 NAME 2 BEFEHL </pre>
<pre> \installparameterhandler \... {...} 1 CSNAME 2 NAME </pre>
<pre> \installparameterhashhandler \... {...} 1 CSNAME 2 NAME </pre>
<pre> \installparametersethandler \... {...} 1 CSNAME 2 NAME </pre>
<pre> \installparentinjector \... {...} 1 CSNAME 2 NAME </pre>
<pre> \installrightframerenderer {...} {...} 1 NAME 2 BEFEHL </pre>
<pre> \installrootparameterhandler \... {...} 1 CSNAME 2 NAME </pre>
<pre> \installsetuphandler \... {...} 1 CSNAME 2 NAME </pre>
<pre> \installsetuponlycommandhandler \... {...} 1 CSNAME 2 NAME </pre>
<pre> \installshipoutmethod {...} {...} 1 NAME 2 BEFEHL </pre>

<code>\installsimplecommandhandler \¹... {²...} \³...</code> 1 CSNAME 2 NAME 3 CSNAME
<code>\installsimpleframedcommandhandler \¹... {²...} \³...</code> 1 CSNAME 2 NAME 3 CSNAME
<code>\installstyleandcolorhandler \¹... {²...}</code> 1 CSNAME 2 NAME
<code>\installswitchcommandhandler \¹... {²...} \³...</code> 1 CSNAME 2 NAME 3 CSNAME
<code>\installswitchsetuphandler \¹... {²...}</code> 1 CSNAME 2 NAME
<code>\installtexdirective {¹...} {²...} {³...}</code> 1 NAME 2 BEFEHL 3 BEFEHL
<code>\installtextracker {¹...} {²...} {³...}</code> 1 NAME 2 BEFEHL 3 BEFEHL
<code>\installtopframerenderer {¹...} {²...}</code> 1 NAME 2 BEFEHL
<code>\installunitsseparator {¹...} {²...}</code> 1 NAME 2 BEFEHL
<code>\installunitsspace {¹...} {²...}</code> 1 NAME 2 BEFEHL
<code>\installversioninfo {¹...} {²...}</code> 1 NAME 2 BEFEHL
<code>\integerrounding {[*]...}</code> * NUMMER
<code>\interakcnilista [¹...] [²...,...²...,...]</code> 1 NAME OPT OPT 2 inherits: \nastavinterakcnilistu
<code>\interakcnitlacitka [...¹...,...¹...,...] [...²...,...]</code> 1 inherits: \nastavinterakcnilistu 2 stranka podstranka REFERENCE
<code>\interaktivnimenu [¹...] [...²...,...²...,...]</code> 1 NAME OPT 2 inherits: \nastavinterakcnimenu

<code>\intertext {...}</code> * TEXT
<code>\invokepagehandler {...} {...}</code> 1 normalni zadny NAME 2 CONTENT
<code>\istltdir ...</code> * TLT TRT
<code>\istrtdir ...</code> * TLT TRT
<code>\italiccorrection</code>
<code>\italicface</code>
<code>\itemtag [...*,...]</code> * REFERENCE OPT
<code>\jazyk [...]</code> * SPRACHE
<code>\LANGUAGE</code>
<code>\jdidolu [...]</code> * DIMENSION
<code>\jdina {...} [...]</code> 1 CONTENT 2 REFERENCE
<code>\jdinabox {...} [...]</code> 1 CONTENT 2 REFERENCE
<code>\jdinastranu {...} [...]</code> 1 TEXT 2 REFERENCE
<code>\UNIT {...}</code> * CONTENT instances: unit
<code>\unit {...}</code> * CONTENT
<code>\jobfilename</code>
<code>\jobfilesuffix</code>
<code>\Kap {...}</code> * TEXT
<code>\kaligraficke</code>

\kap {...} * TEXT
\keeplinestogether {...} * NUMMER
\keepunwantedspaces
\kerncharacters [...] ¹ {...} ² 1 NUMMER OPT 2 TEXT
\klonujpole [...] ¹ [...] ² [...] ³ [...] ⁴ ,... 1 NAME 2 NAME 3 NAME 4 NAME
\COMMENT [...] ¹ [...] ² ,... {...} ³ 1 TEXT OPT OPT 2 inherits: \nastavkomentar 3 TEXT instances: comment
\comment [...] ¹ [...] ² ,... {...} ³ 1 TEXT OPT OPT 2 inherits: \nastavkomentar 3 TEXT
\komponenta {...} * FILE
\komponenta ... * FILE
\konvertujcisko {...} ¹ {...} ² 1 prazdne implicitni zadny mesic month:mnem pismo Pismo pisma Pisma a A Csla slovo words Slovo Slova n N rimskecislice Rimskecislice i I r R KR RK recky Recky g G abjadnumerals abjadnodotnumerals abjadnaivenumerals thainumerals devanagarinumerals gurmurkhinumerals gujaratinnumerals tibetannumerals greeknumerals Greeknumerals arabicnumerals persiannumerals arabicexnumerals arabicdecimals persiandecimals koreannumerals koreanparentnumerals koreancirclenumerals kr kr-p kr-c chinesenumerals chinesecapnumerals chineseallnumerals cn cn-c cn-a sloveniannumerals slovenianNumerals spanishnumerals spanishNumerals mathgreek set_0 set_1 set_2 set_3 continued NAME 2 NUMBER
\kopirujpole [...] ¹ [...] ² 1 NAME 2 NAME
\koreancirclenumerals {...} * NUMMER
\koreannumerals {...} * NUMMER
\koreannumeralsc {...} * NUMMER
\koreannumeralsp {...} * NUMMER

<code>\koreanparentnumerals {...}</code> * NUMBER
<code>\korekcebilehomista {...}</code> * CONTENT
<code>\kurziva</code>
<code>\kurzivnitucne</code>
<code>\LAMSTEX</code>
<code>\LATEX</code>
<code>\LamSTeX</code>
<code>\LaTeX</code>
<code>\LUAJITTEX</code>
<code>\LUATEX</code>
<code>\Lua</code>
<code>\LuajitTeX</code>
<code>\LuaTeX</code>
<code>\LABELjazyk</code> instances: head label mathlabel taglabel unit operator prefix suffix btxlabel
<code>\btxlabeljazyk</code>
<code>\headjazyk</code>
<code>\labeljazyk</code>
<code>\mathlabeljazyk</code>
<code>\operatorjazyk</code>
<code>\prefixjazyk</code>
<code>\suffixjazyk</code>
<code>\taglabeljazyk</code>
<code>\unitjazyk</code>
<code>\LABELtexts {...} {...}</code> 1 KEY 2 TEXT instances: head label mathlabel

$\backslash\text{headtexts} \{.^1.\} \{.^2.\}$ 1 KEY 2 TEXT
$\backslash\text{labeltexts} \{.^1.\} \{.^2.\}$ 1 KEY 2 TEXT
$\backslash\text{mathlabeltexts} \{.^1.\} \{.^2.\}$ 1 KEY 2 TEXT
$\backslash\text{languageCharacters} \{.*.\}$ * NUMMER
$\backslash\text{languagecharacters} \{.*.\}$ * NUMMER
$\backslash\text{languagecharwidth} \{.*.\}$ * SPRACHE
$\backslash\text{lastcounter} [.^1.] [.^2.]$ 1 NAME OPT 2 NUMMER
$\backslash\text{lastcountervalue} [.*.]$ * NAME
$\backslash\text{lastdigit} \{.*.\}$ * NUMMER
$\backslash\text{lastlinewidth}$
$\backslash\text{lastnaturalboxdp}$
$\backslash\text{lastnaturalboxht}$
$\backslash\text{lastnaturalboxwd}$
$\backslash\text{lastpredefinedsymbol}$
$\backslash\text{lastrealpage}$
$\backslash\text{lastrealpagenumber}$
$\backslash\text{lastsubcountervalue} [.^1.] [.^2.]$ 1 NAME 2 NUMMER
$\backslash\text{lastsubpagenumber}$
$\backslash\text{lasttwodigits} \{.*.\}$ * NUMMER
$\backslash\text{lastuserpage}$
$\backslash\text{lastuserpagenumber}$

<code>\lateluacode {...}</code> * BEFEHL
<code>\layeredtext [...,¹...,...] [...,²...,...] {...} {...}</code> 1 inherits: \setuplayer ^{PT} 2 inherits: \setuplayeredtext 3 TEXT 4 CONTENT
<code>\layerheight</code>
<code>\layerwidth</code>
<code>\lazysavetaggedtwopassdata {...} {...} {...} {...}</code> 1 NAME 2 NUMMER 3 NAME 4 CONTENT
<code>\lazysavetwopassdata {...} {...} {...}</code> 1 NAME 2 NUMMER 3 CONTENT
<code>\lbox ¹... {...}</code> 1 TEXT ^{OPT} 2 CONTENT
<code>\leftbottombox {...}</code> * CONTENT
<code>\leftbox {...}</code> * CONTENT
<code>\lefthbox {...}</code> * CONTENT
<code>\leftLABELtext {...}</code> * KEY instances: head label mathlabel
<code>\leftheadtext {...}</code> * KEY
<code>\leftlabeltext {...}</code> * KEY
<code>\leftmathlabeltext {...}</code> * KEY
<code>\leftline {...}</code> * CONTENT
<code>\lefttorrighthbox ¹... {...}</code> 1 TEXT ^{OPT} 2 CONTENT
<code>\lefttorrightvbox ¹... {...}</code> 1 TEXT ^{OPT} 2 CONTENT

<code>\leftorrightvtop ...¹ {...}</code> 1 TEXT OPT 2 CONTENT
<code>\leftskipadaption</code>
<code>\leftsubguillemot</code>
<code>\lefttopbox {...}</code> * CONTENT
<code>\lefttoright</code>
<code>\lefttorighthbox ...¹ {...}</code> 1 TEXT OPT 2 CONTENT
<code>\lefttorightvbox ...¹ {...}</code> 1 TEXT OPT 2 CONTENT
<code>\lefttorightvtop ...¹ {...}</code> 1 TEXT OPT 2 CONTENT
<code>\letbeundefined {...}</code> * NAME
<code>\letcatcodecommand \...¹ ... \...² \...³</code> 1 CSNAME 2 CHARACTER NUMBER 3 CSNAME
<code>\letcscsname \...¹ \csname ...² \endcsname</code> 1 CSNAME 2 NAME
<code>\letcsnamecs \csname ...¹ \endcsname \...²</code> 1 NAME 2 CSNAME
<code>\letcsnamecsname \csname ...¹ \endcsname \csname ...² \endcsname</code> 1 NAME 2 NAME
<code>\letdummyparameter {...¹} \...²</code> 1 KEY 2 CSNAME
<code>\letempty \...[*]</code> * CSNAME
<code>\letgvalue {...¹} \...²</code> 1 NAME 2 CSNAME
<code>\letgvalueempty {...[*]}</code> * NAME

<code>\letgvalurelax {...}</code> <code>* NAME</code>
<code>\letterampersand</code>
<code>\letterat</code>
<code>\letterbackslash</code>
<code>\letterbar</code>
<code>\letterbgroup</code>
<code>\letterclosebrace</code>
<code>\lettercolon</code>
<code>\letterdollar</code>
<code>\letterdoublequote</code>
<code>\letteregroup</code>
<code>\letterescape</code>
<code>\letterexclamationmark</code>
<code>\letterhash</code>
<code>\letterhat</code>
<code>\letterleftbrace</code>
<code>\letterleftbracket</code>
<code>\letterleftparenthesis</code>
<code>\letterless</code>
<code>\lettermore</code>
<code>\letteropenbrace</code>
<code>\letterpercent</code>
<code>\letterquestionmark</code>
<code>\letterrightbrace</code>
<code>\letterrightbracket</code>
<code>\letterrightparenthesis</code>

<code>\lettersinglequote</code>
<code>\letterslash</code>
<code>\letterspacing</code> [¹ ...] { ² ...} 1 NUMMER OPT 2 TEXT
<code>\lettertilde</code>
<code>\letterunderscore</code>
<code>\letvalue</code> { ¹ ...} \ ² ... 1 NAME 2 CSNAME
<code>\letvalueempty</code> {.*} * NAME
<code>\letvaluerelax</code> {.*} * NAME
<code>\lfence</code> {.*} * CHARACTER
<code>\lhbox</code> {.*} * CONTENT
<code>\limitatefirstline</code> { ¹ ...} { ² ...} { ³ ...} 1 TEXT 2 DIMENSION 3 BEFEHL
<code>\limitatelines</code> { ¹ ...} { ² ...} { ³ ...} 1 NUMMER 2 BEFEHL 3 TEXT
<code>\limitatetext</code> { ¹ ...} { ² ...} { ³ ...} 1 TEXT 2 [-+]DIMENSION 3 BEFEHL
<code>\limitatetext</code> { ¹ ...} {..., ² ...} { ³ ...} 1 TEXT 2 [-+]DIMENSION 3 BEFEHL
<code>\LINENOTE</code> {.*} * TEXT instances: linenote
<code>\linenote</code> {.*} * TEXT
<code>\linespanningtext</code> { ¹ ...} { ² ...} { ³ ...} 1 TEXT 2 DIMENSION 3 FONT

`\listcitation [...1...] [...2]`

```
1 odkaz      = REFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
                authornum authoryear
  pred       = BEFEHL
  po        = BEFEHL
  vlevo     = BEFEHL
  vpravo    = BEFEHL
  inherits: \setupbtx
2 REFERENCE
```

`\listcitation [...1] [...2]`

```
1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear
2 REFERENCE
```

`\listcitation [...1...] [...2...]`

```
1 odkaz      = REFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
                authornum authoryear
  pred       = BEFEHL
  po        = BEFEHL
  vlevo     = BEFEHL
  vpravo    = BEFEHL
  inherits: \setupbtx
2 KEY = VALUE
```

`\listcite [...1...] [...2]`

```
1 odkaz      = REFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
                authornum authoryear
  pred       = BEFEHL
  po        = BEFEHL
  vlevo     = BEFEHL
  vpravo    = BEFEHL
  inherits: \setupbtx
2 REFERENCE
```

`\listcite [...1] [...2]`

```
1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear
2 REFERENCE
```

`\listcite [...1...] [...2...]`

```
1 odkaz      = REFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
                authornum authoryear
  pred       = BEFEHL
  po        = BEFEHL
  vlevo     = BEFEHL
  vpravo    = BEFEHL
  inherits: \setupbtx
2 KEY = VALUE
```

`\listnamespaces`

`\llap {...}`

`* CONTENT`

`\loadanyfile [...]`

`* FILE`

`\loadanyfileonce [...]`

`* FILE`

`\loadbtxdefinitionfile [...]`

`* FILE`

\loadbtxreplacementfile [...] * FILE
\loadcldfile [...] * FILE
\loadcldfileonce [...] * FILE
\loadfontgoodies [...] * FILE
\loadluafile [...] * FILE
\loadluafileonce [...] * FILE
\loadspellchecklist [...] ¹ [...] ² 1 NAME 2 FILE
\loadtexfile [...] * FILE
\loadtexfileonce [...] * FILE
\loadtypescriptfile [...] * FILE
\localframed [...] ¹ [...] ² _{OPT} {...} ³ 1 NAME 2 inherits: \nastavoramovani 3 CONTENT
\localframedwithsettings [...] ¹ [...] ² _{OPT} {...} ³ 1 NAME 2 inherits: \nastavoramovani 3 CONTENT
\localhsize
\localpopbox ... * CSNAME NUMMER
\localpopmacro \... * CSNAME
\localpushbox ... * CSNAME NUMMER
\localpushmacro \... * CSNAME
\localundefine {...} * NAME

<code>\locatedfilepath</code>
<code>\locatefilepath {...}</code> * FILE
<code>\locfilename {...}</code> * FILE
<code>\lomihi {...} {...} {...}</code> 1 CONTENT 2 CONTENT 3 CONTENT
<code>\lowerbox {...} \^2... {...}</code> 1 DIMENSION 2 CSNAME 3 CONTENT
<code>\lowercased {...}</code> * TEXT
<code>\lowercasestring ... \to \^2...</code> 1 TEXT 2 CSNAME
<code>\lowerlefthdoubleninequote</code>
<code>\lowerleftsingleninequote</code>
<code>\lowerrighthdoubleninequote</code>
<code>\lowerrightsingleninequote</code>
<code>\LOWHIGH [...] {...} {...}</code> 1 vleft vpr ⁹⁰ 2 CONTENT 3 CONTENT
<code>\LOWMIDHIGH {...} {...} {...}</code> 1 CONTENT 2 CONTENT 3 CONTENT
<code>\lrbbox {...} {...} {...} {...} {...}</code> 1 DIMENSION 2 DIMENSION 3 DIMENSION 4 DIMENSION 5 CONTENT
<code>\ltop ... {...}</code> 1 TEXT ^{OPT} 2 CONTENT
<code>\luacode {...}</code> * BEFEHL
<code>\luaconditional \^*...</code> * CSNAME

\luaenvironment ... * FILE
\luaexpanded {...} * BEFEHL
\luaexpr {...} * CONTENT
\luafunction {...} * BEFEHL
\luajitTeX
\luamajorversion
\luaminorversion
\luaparameterset {...} {...} 1 NAME 2 CONTENT
\luasetup {...} * NAME
\luaTeX
\luaversion
\MESIC {...} * NUMMER
\METAFONT
\METAFUN
\METAPOST
\MetaFont
\MetaFun
\MetaPost
\MKII
\MKIV
\MKIX
\MKVI
\MKXI

\MONTHLONG {...} * NUMBER
\MONTHSHORT {...} * NUMBER
\MPanchor {...} * NAME
\MPbetex {...} * NAME
\MPc {...} * NAME
\MPcode {... ¹ } {... ² } 1 NAME OPT 2 CONTENT
\MPcolor {...} * COLOR
\MPcoloronly {...} * COLOR
\MPcolumn {...} * NAME
\MPd {...} * NAME
\MPdrawing {...} * CONTENT
\MPfontsizehskip {...} * FONT
\MPgetmultipars {... ¹ } {... ² } 1 NAME 2 NAME
\MPgetmultishape {... ¹ } {... ² } 1 NAME 2 NAME
\MPgetposboxes {... ¹ ,... ² } {... ² } 1 NAME 2 NAME
\MPh {...} * NAME
\MPII
\MPIV

\MPinclusions [¹ ...] { ² ...} { ³ ...} 1 + OPT OPT 2 NAME 3 CONTENT
\MPlleftskip {...} * NAME
\MPl1 {...} * NAME
\MPlr {...} * NAME
\MPls {...} * NAME
\MPmenubuttons {...} * NAME
\MPn {...} * NAME
\MPOptions {...} * COLOR
\MPOverlayanchor {...} * NAME
\MPP {...} * NAME
\MPPage {...} * NAME
\MPPardata {...} * NAME
\MPPplus { ¹ ...} { ² ...} { ³ ...} 1 NAME 2 NUMMER 3 CONTENT
\MPPos {...} * NAME
\MPPositiongraphic { ¹ ...} { ² ...,... _{OPT} ...} 1 NAME 2 KEY = VALUE
\MPPosset {...} * NAME
\MPr {...} * NAME
\MPravvar { ¹ ...} { ² ...} 1 NAME 2 KEY

\MPregion {...} * NAME
\MPrest {...} {...} 1 NAME 2 CONTENT
\MPrightskip {...} * NAME
\MPrs {...} * NAME
\MPstring {...} * NAME
\MPtext {...} * NAME
\MPtransparency {...} * COLOR
\MPul {...} * NAME
\MPur {...} * NAME
\MPVI
\MPv {...} {...} {...} 1 NAME 2 NUMMER 3 CONTENT
\MPvar {...} * KEY
\MPvariable {...} * KEY
\MPvv {...} {...} 1 NAME 2 CONTENT
\MPw {...} * NAME
\MPwhd {...} * NAME
\MPx {...} * NAME
\MPxy {...} * NAME

<code>\MPxywhd {...}</code> * NAME
<code>\MPy {...}</code> * NAME
<code>\m [...¹] {...²}</code> 1 NAME ^{OPT} 2 CONTENT
<code>\makecharacteractive ...</code> * CHARACTER
<code>\makerawcommalist [...¹,...²]</code> 1 BEFEHL 2 CSNAME
<code>\makestrutofbox ...</code> * CSNAME NUMBER
<code>\male</code>
<code>\malekurzivnitucne</code>
<code>\malenormalni</code>
<code>\malesklonene</code>
<code>\malesklonenetucne</code>
<code>\maletucne</code>
<code>\maletucnekurzivni</code>
<code>\maletucnesklonene</code>
<code>\maletype</code>
<code>\mapfontsize [...¹] [...²]</code> 1 DIMENSION 2 DIMENSION
<code>\margindata [...¹] [...²,...³,...⁴]{...}</code> 1 NAME 2 odkaz = REFERENCE ^{OPT} inherits: \setupmargindata 3 inherits: \setupmarginframed ^{OPT} 4 CONTENT
<code>\MARGINDATA [...¹,...²,...³]{...}</code> 1 odkaz = REFERENCE ^{OPT} inherits: \setupmargindata 2 inherits: \setupmarginframed ^{OPT} 3 CONTENT instances: inleftmargin inrightmargin inoutermargin ininnermargin inleftedge inrightedge inouteredge ininneredge atleftmargin atrightmargin inleft inright inouter ininner inmargin inother margintext

```

\atleftmargin [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] {\stackrel{3}{...}}
1 odkaz = REFERENCE OPT OPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\atrightrightmargin [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] {\stackrel{3}{...}}
1 odkaz = REFERENCE OPT OPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\ininner [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] {\stackrel{3}{...}}
1 odkaz = REFERENCE OPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\ininneredge [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] {\stackrel{3}{...}}
1 odkaz = REFERENCE OPT OPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\ininnermargin [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] {\stackrel{3}{...}}
1 odkaz = REFERENCE OPT OPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inleft [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] {\stackrel{3}{...}}
1 odkaz = REFERENCE OPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inleftedge [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] {\stackrel{3}{...}}
1 odkaz = REFERENCE OPT OPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inleftmargin [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] {\stackrel{3}{...}}
1 odkaz = REFERENCE OPT OPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inmargin [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] {\stackrel{3}{...}}
1 odkaz = REFERENCE OPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inothert [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] {\stackrel{3}{...}}
1 odkaz = REFERENCE OPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inouter [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] {\stackrel{3}{...}}
1 odkaz = REFERENCE OPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

$\backslash inouteredge$ [\dots $\overset{1}{=}$ \dots] [\dots $\overset{2}{=}$ \dots] $\{\dots\}$ 1 odkaz = REFERENCE <small>OPT</small> <small>OPT</small> inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT
$\backslash inoutermargin$ [\dots $\overset{1}{=}$ \dots] [\dots $\overset{2}{=}$ \dots] $\{\dots\}$ 1 odkaz = REFERENCE <small>OPT</small> <small>OPT</small> inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT
$\backslash inright$ [\dots $\overset{1}{=}$ \dots] [\dots $\overset{2}{=}$ \dots] $\{\dots\}$ 1 odkaz = REFERENCE <small>OPT</small> inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT
$\backslash inrightedge$ [\dots $\overset{1}{=}$ \dots] [\dots $\overset{2}{=}$ \dots] $\{\dots\}$ 1 odkaz = REFERENCE <small>OPT</small> <small>OPT</small> inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT
$\backslash inrightmargin$ [\dots $\overset{1}{=}$ \dots] [\dots $\overset{2}{=}$ \dots] $\{\dots\}$ 1 odkaz = REFERENCE <small>OPT</small> <small>OPT</small> inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT
$\backslash margintext$ [\dots $\overset{1}{=}$ \dots] [\dots $\overset{2}{=}$ \dots] $\{\dots\}$ 1 odkaz = REFERENCE <small>OPT</small> <small>OPT</small> inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT
$\backslash markcontent$ [\dots] $\{\dots\}$ 1 reset vse NAME <small>OPT</small> 2 CONTENT
$\backslash markinjector$ [\dots] * NAME
$\backslash markpage$ [\dots] [\dots] 1 NAME <small>OPT</small> 2 [-+]NUMBER
$\backslash mat$ $\{\dots\}$ * CONTENT
$\backslash matematika$ [\dots] $\{\dots\}$ 1 NAME <small>OPT</small> 2 CONTENT
$\backslash math$ [\dots] $\{\dots\}$ 1 NAME <small>OPT</small> 2 CONTENT
$\backslash mathbf$
$\backslash mathbi$
$\backslash mathblackboard$

<code>\mathbs</code>
$\backslash\text{MATHCOMMAND}$ $\{.^1..\}$ $\{.^2..\}$ 1 TEXT OPT OPT 2 TEXT
<code>\mathdefault</code>
$\backslash\text{mathdouble}$ $[.^1..]$ $\{.^2..\}$ $\{.^3..\}$ $\{.^4..\}$ 1 obe vfenced OPT 2 NUMBER 3 TEXT 4 TEXT
$\backslash\text{MATHDOUBLEEXTENSIBLE}$ $\{.^1..\}$ $\{.^2..\}$ 1 TEXT 2 TEXT instances: doublebar doublebrace doubleparent doublebracket overbarunderbar overbraceunderbrace overparentunderparent overbracketunderbracket
$\backslash\text{doublebar}$ $\{.^1..\}$ $\{.^2..\}$ 1 TEXT 2 TEXT
$\backslash\text{doublebrace}$ $\{.^1..\}$ $\{.^2..\}$ 1 TEXT 2 TEXT
$\backslash\text{doublebracket}$ $\{.^1..\}$ $\{.^2..\}$ 1 TEXT 2 TEXT
$\backslash\text{doubleparent}$ $\{.^1..\}$ $\{.^2..\}$ 1 TEXT 2 TEXT
$\backslash\text{overbarunderbar}$ $\{.^1..\}$ $\{.^2..\}$ 1 TEXT 2 TEXT
$\backslash\text{overbraceunderbrace}$ $\{.^1..\}$ $\{.^2..\}$ 1 TEXT 2 TEXT
$\backslash\text{overbracketunderbracket}$ $\{.^1..\}$ $\{.^2..\}$ 1 TEXT 2 TEXT
$\backslash\text{overparentunderparent}$ $\{.^1..\}$ $\{.^2..\}$ 1 TEXT 2 TEXT

`\MATHEXTENSIBLE {...} {...}`

1 TEXT

OPT

OPT

2 TEXT

instances: xrel xequal xleftarrow xrightarrow xleftrightharrow xLeftarrow xRightarrow
xleftrightharrow xtwoheadleftarrow xtwoheadrightarrow xmapsto xhookleftarrow xhookrightarrow
xleftharpoondown xleftharpoonup xrightharpoondown xrightarpoonup xrightoverleftarrow
xleftrightharpoons xrightleftharpoons xtriplerel mrel mequal mleftarrow mrightarrow mleftrightharrow
mLeftarrow mRightarrow mLeftrightharrow mtwoheadleftarrow mtwoheadrightarrow mmapsto mhookleftarrow
mhookrightarrow mleftharpoondown mleftharpoonup mrightharpoondown mrightharpoonup mrightoverleftarrow
mleftrightharpoons mrightrightleftharpoons mtriplerel eleftrightarrowfill erightarrowfill eleftrightarrowfill
etwoheadrightarrowfill eleftharpoondownfill eleftharpoonupfill erightharpoondownfill
erightharpoonupfill eoverbarfill eunderbarfill eoverbracefill eunderbracefill eoverparentfill
eunderparentfill eoverbracketfill eunderbracketfill trel tequal tmapsto tleftarrow trightarrow
tleftrightarrow tLeftarrow tRightarrow tLeftrightharrow ttwoheadleftarrow ttwoheadrightarrow
thookleftarrow thookrightarrow tleftharpoondown tleftharpoonup trightharpoondown trightharpoonup
trightoverleftarrow tleftrightharpoons trightleftharpoons ttriplerel cleftarrow crightarrow
crightoverleftarrow

`\cleftarrow {...} {...}`

1 TEXT

OPT

OPT

2 TEXT

`\crightarrow {...} {...}`

1 TEXT

OPT

OPT

2 TEXT

`\crightoverleftarrow {...} {...}`

1 TEXT

OPT

OPT

2 TEXT

`\eleftrightarrowfill {...} {...}`

1 TEXT

OPT

OPT

2 TEXT

`\eleftharpoondownfill {...} {...}`

1 TEXT

OPT

OPT

2 TEXT

`\eleftharpoonupfill {...} {...}`

1 TEXT

OPT

OPT

2 TEXT

`\eleftrightarrowfill {...} {...}`

1 TEXT

OPT

OPT

2 TEXT

`\eoverbarfill {...} {...}`

1 TEXT

OPT

OPT

2 TEXT

`\eoverbracefill {...} {...}`

1 TEXT

OPT

OPT

2 TEXT

`\eoverbracketfill {...} {...}`

1 TEXT

OPT

OPT

2 TEXT

`\eoverparentfill {...} {...}`

1 TEXT

OPT

OPT

2 TEXT

`\erightarrowfill {...} {...}`

1 TEXT OPT OPT
2 TEXT

`\erightharpoondownfill {...} {...}`

1 TEXT OPT OPT
2 TEXT

`\erightharpoonupfill {...} {...}`

1 TEXT OPT OPT
2 TEXT

`\etwoheadrightarrowfill {...} {...}`

1 TEXT OPT OPT
2 TEXT

`\eunderbarfill {...} {...}`

1 TEXT OPT OPT
2 TEXT

`\eunderbracefill {...} {...}`

1 TEXT OPT OPT
2 TEXT

`\eunderbracketfill {...} {...}`

1 TEXT OPT OPT
2 TEXT

`\eunderparentfill {...} {...}`

1 TEXT OPT OPT
2 TEXT

`\mequal {...} {...}`

1 TEXT OPT OPT
2 TEXT

`\mhookleftarrow {...} {...}`

1 TEXT OPT OPT
2 TEXT

`\mhookrightarrow {...} {...}`

1 TEXT OPT OPT
2 TEXT

`\mLeftarrow {...} {...}`

1 TEXT OPT OPT
2 TEXT

`\mLeftrightarrow {...} {...}`

1 TEXT OPT OPT
2 TEXT

`\mleftarrow {...} {...}`

1 TEXT OPT OPT
2 TEXT

`\mleftharpoondown {...} {...}`

1 TEXT OPT OPT
2 TEXT

`\mleftharpoonup {...} {...}`

1 TEXT OPT OPT

2 TEXT

`\mleftrightharpoonup {...} {...}`

1 TEXT OPT OPT

2 TEXT

`\mleftrightharpoons {...} {...}`

1 TEXT OPT OPT

2 TEXT

`\mmapsto {...} {...}`

1 TEXT OPT OPT

2 TEXT

`\mRightharpoonup {...} {...}`

1 TEXT OPT OPT

2 TEXT

`\mrel {...} {...}`

1 TEXT OPT OPT

2 TEXT

`\mrightarrow {...} {...}`

1 TEXT OPT OPT

2 TEXT

`\mrightharpoondown {...} {...}`

1 TEXT OPT OPT

2 TEXT

`\mrightharpoonup {...} {...}`

1 TEXT OPT OPT

2 TEXT

`\mrightharpoons {...} {...}`

1 TEXT OPT OPT

2 TEXT

`\mrightharpoonoverleftarrow {...} {...}`

1 TEXT OPT OPT

2 TEXT

`\mtriplerel {...} {...}`

1 TEXT OPT OPT

2 TEXT

`\mtwoheadleftarrow {...} {...}`

1 TEXT OPT OPT

2 TEXT

`\mtwoheadrightarrow {...} {...}`

1 TEXT OPT OPT

2 TEXT

`\tequal {...} {...}`

1 TEXT OPT OPT

2 TEXT

`\thookleftarrow {...} {...}`

1 TEXT OPT OPT

2 TEXT

`\thookrightarrow {...} {...}`

1 TEXT OPT OPT

2 TEXT

`\tleftarrow {...} {...}`

1 TEXT OPT OPT

2 TEXT

`\tlefttrightharpoonup {...} {...}`

1 TEXT OPT OPT

2 TEXT

`\tleftrightarrow {...} {...}`

1 TEXT OPT OPT

2 TEXT

`\tleftharpoonowdown {...} {...}`

1 TEXT OPT OPT

2 TEXT

`\tleftharpoonoup {...} {...}`

1 TEXT OPT OPT

2 TEXT

`\tleftrightharpoonup {...} {...}`

1 TEXT OPT OPT

2 TEXT

`\tleftrightharpoons {...} {...}`

1 TEXT OPT OPT

2 TEXT

`\tmapsto {...} {...}`

1 TEXT OPT OPT

2 TEXT

`\trightarrow {...} {...}`

1 TEXT OPT OPT

2 TEXT

`\trel {...} {...}`

1 TEXT OPT OPT

2 TEXT

`\rightarrow {...} {...}`

1 TEXT OPT OPT

2 TEXT

`\trightharpoonowdown {...} {...}`

1 TEXT OPT OPT

2 TEXT

`\trightharpoonoup {...} {...}`

1 TEXT OPT OPT

2 TEXT

`\trightharpoons {...} {...}`
1 TEXT OPT OPT
2 TEXT

`\trightoverleftarrow {...} {...}`
1 TEXT OPT OPT
2 TEXT

`\ttriplelrel {...} {...}`
1 TEXT OPT OPT
2 TEXT

`\twoheadleftarrow {...} {...}`
1 TEXT OPT OPT
2 TEXT

`\twoheadrightarrow {...} {...}`
1 TEXT OPT OPT
2 TEXT

`\xequal {...} {...}`
1 TEXT OPT OPT
2 TEXT

`\xhookleftarrow {...} {...}`
1 TEXT OPT OPT
2 TEXT

`\xhookrightarrow {...} {...}`
1 TEXT OPT OPT
2 TEXT

`\xLeftarrow {...} {...}`
1 TEXT OPT OPT
2 TEXT

`\xLeftrightarrow {...} {...}`
1 TEXT OPT OPT
2 TEXT

`\xleftarrow {...} {...}`
1 TEXT OPT OPT
2 TEXT

`\xleftharpoondown {...} {...}`
1 TEXT OPT OPT
2 TEXT

`\xleftharpoonup {...} {...}`
1 TEXT OPT OPT
2 TEXT

`\xleftrightharpoonup {...} {...}`
1 TEXT OPT OPT
2 TEXT

`\xleftrightharpoons {...} {...}`
1 TEXT OPT OPT
2 TEXT

1	TEXT	OPT	OPT
2	TEXT		

1	TEXT	OPT	OPT
2	TEXT		

```

1  TEXT  OPT      OPT
2  TEXT

```

1	TEXT	OPT	OPT
2	TEXT		

1	TEXT	OPT	OPT
2	TEXT		

1	TEXT	OPT	OPT
2	TEXT		

1	TEXT	OPT	OPT
2	TEXT		

1	TEXT	OPT	OPT
2	TEXT		

1	TEXT	OPT	OPT
2	TEXT		

1	TEXT	OPT	OPT
2	TEXT		

1	TEXT	OPT	OPT
2	TEXT		

 \mathfrak{f}

```

1 inherits: \setupmathframed
2 CONTENT

```

```
1 inherits: \setupmathframedOPT
2 CONTENT
```

```
1 inherits: \setupOPTmathframed
2 CONTENT
```

$\mfrac{...}{...}$ $\mfrac{...}{...}$ 1 inherits: \setupmathframed 2 CONTENT
$\mathfunction{...}$ * CONTENT
\mathit
italic
$\mathop{...}$ * CONTENT
$\MATHORNAMENT{...}$ * CONTENT
$\mathover{...}{...}{...}$ 1 vrsek vfenced 2 NUMMER 3 TEXT
$\MATHOVEREXTENSIBLE{...}$ * TEXT
$\MATHOVERTEXTEXTENSIBLE{...}{...}$ 1 TEXT 2 TEXT instances:
$\MATHRADICAL{...}$ 1 TEXT 2 CONTENT
\mathrm
\mathscript
\mathsl
\mathss
$\mathtext{...}$ 1 TEXT 2 TEXT
$\mathtextbf{...}$ 1 TEXT 2 TEXT
$\mathtextbi{...}$ 1 TEXT 2 TEXT
$\mathtextbs{...}$ 1 TEXT 2 TEXT

$\backslash\mathtextit$ $\dots^{.1}\{...\}$ 1 TEXT OPT 2 TEXT
$\backslash\mathtextsl$ $\dots^{.1}\{...\}$ 1 TEXT OPT 2 TEXT
$\backslash\mathtexttf$ $\dots^{.1}\{...\}$ 1 TEXT OPT 2 TEXT
$\backslash\mathtf$
$\backslash\mathtriplet$ $[...]^{.1}\{...\}^{.2}\{...\}^{.3}\{...\}^{.4}$ 1 NAME OPT OPT OPT OPT 2 TEXT 3 TEXT 4 TEXT
$\backslash\mathtriplet$ $[...]^{.1}\{...\}^{.2}\{...\}^{.3}\{...\}^{.4}$ 1 NAME OPT OPT OPT OPT 2 TEXT 3 TEXT 4 TEXT
$\backslash\mathtt$
$\backslash\mathunder$ $[...]^{.1}\{...\}^{.2}\{...\}^{.3}$ 1 spodek vfence \mathbb{F} 2 NUMMER 3 TEXT
$\backslash\mathunderextensible$ $\{...\}^{.*}$ * TEXT
$\backslash\mathunderextextensible$ $\{...\}^{.1}\{...\}^{.2}$ 1 TEXT 2 TEXT instances:
$\backslash\mathunstacked$
$\backslash\mathupright$
$\backslash\mathword$ $\dots^{.1}\{...\}^{.2}$ 1 TEXT OPT 2 TEXT
$\backslash\mathwordbf$ $\dots^{.1}\{...\}^{.2}$ 1 TEXT OPT 2 TEXT
$\backslash\mathwordbi$ $\dots^{.1}\{...\}^{.2}$ 1 TEXT OPT 2 TEXT
$\backslash\mathwordbs$ $\dots^{.1}\{...\}^{.2}$ 1 TEXT OPT 2 TEXT

$\backslash\mathwordit$ $\overset{1}{...}$ $\{...\}$ 1 TEXT OPT 2 TEXT
$\backslash\mathwordsl$ $\overset{1}{...}$ $\{...\}$ 1 TEXT OPT 2 TEXT
$\backslash\mathwordtf$ $\overset{1}{...}$ $\{...\}$ 1 TEXT OPT 2 TEXT
$\backslash\maxaligned$ $\{...\}$ * CONTENT
$\backslash\mbox$ $\{...\}$ * CONTENT
$\backslash\measure$ $\{...\}$ * NAME
$\backslash\measured$ $\{...\}$ * NAME
$\backslash\medskip$
$\backslash\medspace$
$\backslash\meritko$ $[\overset{1}{...}]$ $[\overset{2}{...},\dots,\overset{3}{...}]$ $\{...\}$ 1 NAME OPT OPT 2 inherits: $\backslash\setupscale$ 3 CONTENT
$\backslash\mesic$ $\{...\}$ * NUMMER
$\backslash\message$ $\{...\}$ * TEXT
$\backslash\metaTeX$
$\backslash\mezera$
$\backslash\mfence$ $\{...\}$ * CHARACTER
$\backslash\mfunction$ $\{...\}$ * CONTENT
$\backslash\mfunctionlabeltext$ $\{...\}$ * NAME
$\backslash\mhbox$ $\{...\}$ * CONTENT
$\backslash\middlealigned$ $\{...\}$ * CONTENT

<code>\middlebox {...}</code> * CONTENT
<code>\midhbox {...}</code> * CONTENT
<code>\midsubsentence</code>
<code>\minimalhbox ¹... {²...}</code> 1 TEXT OPT 2 CONTENT
<code>\mixedcaps {...}</code> * TEXT
<code>\mkvibuffer [...]</code> * BUFFER OPT
<code>\moduleparameter {¹...} {²...}</code> 1 FILE 2 KEY
<code>\molecule {...}</code> * CONTENT
<code>\mono</code>
<code>\mononormal</code>
<code>\monotucne</code>
<code>\monthlong {...}</code> * NUMMER
<code>\monthshort {...}</code> * NUMMER
<code>\mprandomnumber</code>
<code>\mrizka [...[*]...]</code> * inherits: \base ^{OPT} grid
<code>\mtext {...}</code> * CONTENT
<code>\NormalizeFontHeight \¹... {²...} {³...} {⁴...}</code> 1 CSNAME 2 TEXT 3 DIMENSION 4 FONT
<code>\NormalizeFontWidth \¹... {²...} {³...} {⁴...}</code> 1 CSNAME 2 TEXT 3 DIMENSION 4 FONT

\NormalizeTextHeight {...} {...} {...} 1 FONT 2 DIMENSION 3 TEXT
\NormalizeTextWidth {...} {...} {...} 1 FONT 2 DIMENSION 3 TEXT
\namedheadnumber {...} * ABSCHNITT
\namedstructureheadlocation {...} * ABSCHNITT
\namedstructureuservariable {...} {...} 1 ABSCHNITT 2 KEY
\namedstructurevariable {...} {...} 1 ABSCHNITT 2 KEY
\namedtaggedlabeltexts {...} {...} {...} {...} {...} 1 NAME 2 NAME 3 NAME 4 NAME 5 CONTENT
\nastavbarvu [...] * FILE
\nastavbarvy [...,... [*] ...,...] * status = start stop spot = ano ne expanzen = ano ne faktor = ano ne rgb = ano ne cmyk = ano ne konverze = ano ne vzdy pagecolormodel = auto zadny NAME barvatextu = COLOR intent = overprint knockout zadny
\nastavbilamista [..., [*] ...] * fixuj fixne prizpusobive ^{OPT} radek pulradku quarterline zadny male stredni velke implicitni DIMENSION
\nastavblok [..., ¹ ...] [..., ² ...,...] 1 NAME ^{OPT} 2 pred = BEFEHL po = BEFEHL vnitrni = BEFEHL pismo = STYLE BEFEHL barva = COLOR
\nastavbloksekce [..., ¹ ...] [..., ² ...,...] 1 NAME ^{OPT} 2 stranka = inherits: \strana pred = BEFEHL po = BEFEHL cislo = ano ne

`\nastavbuffer [...1,...] [...2,...]`

1 BUFFER OPT
2 pred = BEFEHL
po = BEFEHL

`\nastavcernelinky [...*,...]`

* sirka = max DIMENSION
vyska = max DIMENSION
hloubka = max DIMENSION
vzdalenost = DIMENSION
n = NUMMER
alternativa = a b
pismo = STYLE BEFEHL
barva = COLOR
typ = mp ano ne
mp = NAME

`\nastavcislonadpisu [...1] [...2]`

1 ABSCHNITT
2 [-+]NUMMER

`\nastavcislostrany [...*,...]`

* inherits: \setupuserpagenumber

`\nastavcislovaniodstavcu [...*,...]`

* status = start stop radek reset
vzdalenost = DIMENSION
pismo = STYLE BEFEHL
barva = COLOR

`\nastavcislovaniradku [...1,...] [...2,...]`

1 NAME OPT
2 start = NUMMER
krok = NUMMER
metoda = stranka prvni dalsi
konverze = NAME
pokracovat = ano ne
misto = text begin end implicitni vlevo vpravo uvnitr vnejsi ivlevo ivpravo marginalie naokraji
vzdalenost = DIMENSION
zarovnani = uvnitr vnejsi flushleft flushright vlevo vpravo nastred auto
prikaz = \...##1
vlevo = BEFEHL
vpravo = BEFEHL
marginalie = DIMENSION
sirka = marginalie DIMENSION
pismo = STYLE BEFEHL
barva = COLOR

`\nastavcislovanistran [...*,...]`

* alternativa = jednostranne dvoustranny
stranka = inherits: \strana
strut = ano ne
prikaz = \...##1
vlevo = BEFEHL
vpravo = BEFEHL
status = start stop
sirka = DIMENSION
misto = zahlavi upati vlevo nastred vpravo ivlevo ivpravo marginalie naokraji naokraji textovahrana
pismo = STYLE BEFEHL
barva = COLOR

`\nastavcitaci [...*,...]`

* inherits: \setupdelimitedtext

`\nastavdeleniplvoucichobjektu [...*,...]`

* pred = BEFEHL
po = BEFEHL
mezi = BEFEHL
radky = auto NUMMER
konverze = NAME

\nastavdelitko [...,..^{*}...]

* znak = normalni siroce

\nastavdolnitexty [...¹...] [...²...] [...³...] [...⁴...] [...⁵]

1 text marginalie hrana^{OPT} OPT OPT OPT OPT
2 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
3 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
4 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
5 datum cislostranky BESCHRIFTUNG TEXT BEFEHL

\nastaveni [...]

* NAME

\nastaveni {...}

* NAME

\nastavhorejsek [...¹] [...,..²...]

1 text marginalie hrana^{OPT}
2 inherits: \setuplayoutelement

\nastavhornitexty [...¹...] [...²...] [...³...] [...⁴...] [...⁵]

1 text marginalie hrana^{OPT} OPT OPT OPT OPT
2 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
3 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
4 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
5 datum cislostranky BESCHRIFTUNG TEXT BEFEHL

\nastavinterakci [...¹...] [...,..²...]

1 NAME^{OPT}
2 status = start stop
pismo = STYLE BEFEHL
barva = COLOR
kontrastnibarva = COLOR
titul = TEXT
podtitulek = COLOR
autor = TEXT
datum = TEXT
keyword = TEXT
zaostreni = standardni ramecek sirka minsirka vyska minvyska prizpusobive tight
menu = zap vyp
fieldlayer = auto NAME
pocitat = REFERENCE
klik = ano ne
obrazovka = normalni novy
stranka = ano ne stranka jmeno auto
otevriakci = REFERENCE
zavriakci = REFERENCE
akceotevrenistranky = REFERENCE
akcezavrenistranky = REFERENCE
sadasymbolu = NAME
vyska = DIMENSION
hloubka = DIMENSION
focusoffset = DIMENSION

\nastavinterakci [...]

* NAME^{OPT}

\nastavinterakcnilistu [...¹,...] [...²,...]

```

1  NAME                      OPT
2  alternativa              = a b c d e f g
   status                   = start stop
   prikaz                   = CSNAME
   sirka                    = DIMENSION
   vyska                    = DIMENSION max široky
   hloubka                  = DIMENSION max
   vzdalenost               = DIMENSION
   krok                     = male stredni velke
   barvapozadi              = COLOR
   pismeno                  = STYLE BEFEHL
   barva                    = COLOR
   kontrastnibarva         = COLOR
   symbol                   = ano ne
   inherits: \nastavoramovani

```

\nastavinterakcnimenu [...¹,...] [...²,...]

```

1  NAME                      OPT
2  alternativa              = vertikalne horizontalne skryte
   category                 = NAME
   levyoffset               = prekryv ramecek zadny implicitni DIMENSION
   pravyoffset              = prekryv ramecek zadny implicitni DIMENSION
   offsetvrsku              = prekryv ramecek zadny implicitni DIMENSION
   offsetspodku             = prekryv ramecek zadny implicitni DIMENSION
   maxsirka                 = DIMENSION
   maxvyska                 = DIMENSION
   itemalign                = vlevo nastred vpravo flushleft flushright nizko vysoko nivy
   status                   = start prazdne lokalne
   vlevo                    = BEFEHL
   vpravo                   = BEFEHL
   vzdalenost               = prekryv DIMENSION
   pred                     = BEFEHL
   po                       = BEFEHL
   mezi                     = BEFEHL
   position                 = ano ne
   stredni                  = BEFEHL
   pismeno                  = STYLE BEFEHL
   barva                    = COLOR
   stejnastranka            = ano ne prazdne zadny normalni implicitni
   kontrastnibarva         = COLOR
   inherits: \nastavoramovani

```

\nastavinterakcniobrazovku [...^{*},...]

```

*  sirka                    = prizpusobive max tight DIMENSION
   vyska                    = prizpusobive max tight DIMENSION
   zpetnamezera             = DIMENSION
   horoffset                = DIMENSION
   offsethlavicky           = DIMENSION
   svrchnamezera            = DIMENSION
   volba                    = prizpusobive max jednostranne dvoustranny zalozka auto zadny implicitni fixne nasirku portrait
                              stranka papir attachment layer
   copies                   = NUMMER
   print                    = LISTE
   prodleva                 = zadny NUMMER

```

\nastavjazyk [...]¹ [...,...²...,...]

```
1  SPRACHE implicitOPT
2  implicitni      = SPRACHE
    status         = start stop
    datum          = inherits: \aktualnidatum
    patterns       = FILE
    lefthyphenmin  = NUMMER
    righthyphenmin = NUMMER
    lefthyphenchar = NUMMER
    righthyphenchar = NUMMER
    setups         = NAME
    mezerovani     = siroky zhustene
    font           = auto
    bidi           = vlevo vpravo l2r r2l
    text           = TEXT
    limitttext     = TEXT
    hyphen         = TEXT
    compoundhyphen = TEXT
    leftcompoundhyphen = TEXT
    rightcompoundhyphen = TEXT
    citovatvlevo   = BEFEHL
    citovatvpravo  = BEFEHL
    citacevlevo    = BEFEHL
    citacevpravo   = BEFEHL
    leftspeech     = BEFEHL
    rightspeech    = BEFEHL
    vetavlevo      = BEFEHL
    middlespeech   = BEFEHL
    vetavpravo     = BEFEHL
    midsentence    = BEFEHL
    podvetavlevo   = BEFEHL
    podvetavpravo  = BEFEHL
    faktor         = ano ne
```

\nastavkapitalky [...]¹,...² [...,...²...,...]

```
1  NAME OPT
2  titul   = ano ne
    sc     = ano ne
    pismeno = STYLE BEFEHL
```

\nastavkombinovanyseznam [...]¹ [...,...²...,...]

```
1  LISTE
2  inherits: \nastavseznam
```

\nastaveni^{COMBINEDLIST} [...,...^{*}...,...]

```
* inherits: \nastavseznam
instances: content
```

\nastaveni^{content} [...,...^{*}...,...]

```
* inherits: \nastavseznam
```

\nastavkomentar [...]¹,...² [...,...²...,...]

```
1  NAME OPT
2  status      = start stop zadny
    metoda     = normalni skryte
    symbol      = Comment Napoveda Insert Klavesa Newparagraph Note Odstavec Default
    sirka       = prizpusobive DIMENSION
    vyska       = prizpusobive DIMENSION
    hloubka     = prizpusobive DIMENSION
    titul       = TEXT
    podtitulek  = TEXT
    autor       = TEXT
    nx          = NUMMER
    ny          = NUMMER
    barva       = COLOR
    volba       = xml max
    textlayer   = NAME
    misto       = levahrana pravahrana naokraji levyokraj pravyyokraj text vysoko zadny
    vzdalenost  = DIMENSION
    mezera      = ano
    buffer      = BUFFER
```

`\nastavkomentarstrany [...,..1...,...]`

* misto = vlevo vpravo vrsek spodek zadny
status = start stop zadny
offset = DIMENSION
vzdalenost = DIMENSION
sirka = DIMENSION
vyska = DIMENSION

`\nastavmarginalnilinky [...,..1...] [...,..2...,...]`

1 NUMBER ^{OPT}
2 inherits: \setupmarginrule

`\nastavmeziradkovoumezeru [...,..1...] [...,..2...,...]`

1 NAME ^{OPT}
2 radek = DIMENSION
vyska = NUMBER
hloubka = NUMBER
minvyska = NUMBER
mindepth = NUMBER
vzdalenost = DIMENSION
vrsek = NUMBER vyska
spodek = NUMBER
natahnout = NUMBER
shrink = NUMBER

`\nastavmeziradkovoumezeru [...,*,...]`

* zap vyp reset auto male stredni vel^{PKT}ke NUMBER DIMENSION

`\nastavmeziradkovoumezeru [...*]`

* NAME

\nastavnadpis [...¹,...] [...²,...]

```

1  ABSCHNITT OPT
2  frontpartlabel = NAME
   bodypartlabel  = NAME
   appendixlabel  = NAME
   backpartlabel  = NAME
   expanzen       = ano ne xml
   catcodes       = NAME
   sectionresetset = NAME
   sectionseparatorset = NAME
   sectionconversionset = NAME
   konverze       = NAME
   sectionstarter = BEFEHL PROCESSOR->BEFEHL
   sectionstopper = BEFEHL PROCESSOR->BEFEHL
   sectionset      = NAME
   sectionsegments = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:*
                        ABSCHNITT:vse

   referenceprefix = + - TEXT
   pismeno         = STYLE BEFEHL
   barva           = COLOR
   styltextu       = STYLE BEFEHL
   barvatextu      = COLOR
   stylcisla       = STYLE BEFEHL
   barvacisla      = COLOR
   propojeni       = ABSCHNITT
   vlastnicislo    = ano ne
   beforesection   = BEFEHL
   aftersection    = BEFEHL
   insidesection   = BEFEHL
   zvsujicicislo   = ano ne seznam prazdne
   umistihlavicku  = ano ne skryte prazdne sekce
   cislo           = ano ne
   stranka         = inherits: \strana
   znaceni         = stranka reset
   zahlavi         = start stop vysoko zadny normalni prazdne zadneznaceni NAME
   text            = start stop vysoko zadny normalni prazdne zadneznaceni NAME
   upati           = start stop vysoko zadny normalni prazdne zadneznaceni NAME
   pred            = BEFEHL
   po              = BEFEHL
   mezi            = BEFEHL
   pokracovat      = ano ne
   zarovnejtitul   = ano ne plvouciobjekt
   meziradkovamezera = NAME
   interakce       = seznam odkaz
   internalgrid    = NAME
   mrizka          = normalni standardni ano striktni tolerantni vrsek spodek obe široky prizpusobive prvni
                        posledni vysoko jedna nizko zadny radek strut box min max nastred math math:radek math:pulradku
                        math:-line math:-halfline NAME

   zarovnani       = inherits: \nastavzarovnani
   tolerance       = inherits: \nastavtoleranci
   strut           = ano ne
   zaveseni        = radek široky prizpusobive zadny NUMMER
   marginalie      = DIMENSION
   odsadpristi     = ano ne auto
   alternativa     = text odstavec normalni marginalie naokraj vrsek nastred spodek reverse marginalnitext
                        NAME

   sirka           = DIMENSION
   numberwidth     = DIMENSION
   sirkatextu      = DIMENSION
   vzdalenost      = DIMENSION
   textdistance    = DIMENSION
   predchoziprikaz = BEFEHL
   prikazpo        = BEFEHL
   prikaz          = \...##1##2
   textovyprikaz   = \...##1
   deeptextcommand = \...##1
   ciselnyprikaz   = \...##1
   deepnumbercommand = \...##1
   misto           = NAME
   kriterium       = striktni pozitiv vse

```

\nastavnadpisy [...¹,...] [...²,...]

```

1  ABSCHNITT OPT
2  inherits: \nastavnadpis

```

\nastavodkazovani [...,*=...,...]

```
* status      = start stop
  expanzen    = ano ne xml
  autofile    = ano ne
  export      = ano ne
  vlevo       = BEFEHL
  vpravo      = BEFEHL
  sirka       = DIMENSION
  oboustranne = ano ne
  interakce   = popis text symbol vse
  oddelovac   = BEFEHL
  prefix      = + - TEXT
```

\nastavodsazovani [...,*,...]

```
* [-+]male [-+]stredni [-+9Velke zadny ne ne prvni dalsi ano vzdy nikdy liche sude normalni reset toggle DIMENSION
  NAME
```

\nastavodstavce [...¹] [...²,...²] [...³,...³,...]

```
1 NAME      OPT      OPT
2 kazdy NUMMER
3 n          = NUMMER
  pred       = BEFEHL
  po         = BEFEHL
  sirka      = DIMENSION
  vzdalenost = DIMENSION
  vyska      = DIMENSION prizpusobive
  vrsek      = BEFEHL
  spodek     = BEFEHL
  zarovnnani = inherits: \nastavzarovnnani
  vnitrni    = BEFEHL
  prikaz     = BEFEHL
  linka      = zap vyp
  tloustkalinky = DIMENSION
  barvalinky = COLOR
  pismeno    = STYLE BEFEHL
  barva      = COLOR
```

\nastavodstavce [...¹] [...²,...²,...]

```
1 NAME:NUMMER      OPT
2 n                = NUMMER
  pred             = BEFEHL
  po               = BEFEHL
  sirka            = DIMENSION
  vzdalenost       = DIMENSION
  vyska            = DIMENSION prizpusobive
  vrsek            = BEFEHL
  spodek           = BEFEHL
  zarovnnani       = inherits: \nastavzarovnnani
  vnitrni          = BEFEHL
  prikaz           = BEFEHL
  linka            = zap vyp
  tloustkalinky    = DIMENSION
  barvalinky       = COLOR
  pismeno          = STYLE BEFEHL
  barva            = COLOR
```

`\nastavopis [...1,...] [...2,...]`

```

1 NAME OPT
2 lichyokraj = DIMENSION
  sudamarginalie = DIMENSION
  marginalie = ano ne standardni DIMENSION
  volba = mp lua xml parsed-xml nested tex context zadny NAME
  pismeno = STYLE BEFEHL
  barva = COLOR
  zarovnani = inherits: \nastavzarovnani
  radky = ano ne normalni hyphenated
  mezera = zap vyp normalni fixne natahnout
  keeptogether = ano ne
  pred = BEFEHL
  po = BEFEHL
  strip = ano ne NUMMER
  range = NUMMER NAME
  tab = ano ne NUMMER
  escape = ano ne TEXT PROCESSOR->TEXT
  odsadpristi = ano ne auto
  pokračovat = ano ne
  start = NUMMER
  stop = NUMMER
  krok = NUMMER
  cislovani = soubor radek ne
  prazdny = inherits: \preskoc

```

`\nastavoramovanetexty [...1,...] [...2,...]`

```

1 NAME OPT
2 inherits: \setupframedtext

```

`\nastavoramovani [...1,...] [...2,...]`

```

1 NAME OPT
2 roh = pravouhly zaobleny NUMMER
  rohramecku = pravouhly zaobleny NUMMER
  rohpozadi = pravouhly zaobleny NUMMER
  polomer = DIMENSION
  polomerramecku = DIMENSION
  polomerpozadi = DIMENSION
  hloubka = DIMENSION
  hloubkramecku = DIMENSION
  hloubkapozadi = DIMENSION
  barvaramecku = COLOR
  rameceknahore = zap vyp NAME
  ramecekdole = zap vyp NAME
  ramecekvlevo = zap vyp NAME
  ramecekvpravo = zap vyp NAME
  region = ano ne
  tloustkalinky = DIMENSION
  offsetramecku = DIMENSION
  ramecek = zap vyp prekryv zadny
  pozadi = popredi barevne NAME
  offsetpozadi = ramecek DIMENSION
  component = NAME
  extras = BEFEHL
  foregroundstyle = STYLE BEFEHL
  foregroundcolor = COLOR
  setups = NAME
  offset = implicitni prekryv zadny DIMENSION
  sirka = lokalne prizpusobive max siroky fixne DIMENSION
  vyska = prizpusobive max siroky DIMENSION
  zarovnani = inherits: \nastavzarovnani
  strut = ano ne zadny lokalne globalne
  autostrut = ano ne
  misto = vyska podlehloubky vysoko nizko vrsek nastred spodek radek nivy visici drzet rovnice matematika
    normalni
  autosirka = ano ne sila
  radky = NUMMER
  vrsek = BEFEHL
  spodek = BEFEHL
  prazdny = ano ne
  profile = NAME
  prazdne = ano ne
  loffset = DIMENSION
  roffset = DIMENSION
  toffset = DIMENSION
  boffset = DIMENSION
  orientation = NUMMER

```

\nastavorez [...,*...]

```
* status      = start stop
sirka         = DIMENSION
vyska        = DIMENSION
hoffset      = DIMENSION
voffset      = DIMENSION
x            = NUMMER
y            = NUMMER
nx           = NUMMER
ny           = NUMMER
sx           = NUMMER
sy           = NUMMER
levyoffset   = DIMENSION
pravyoffset  = DIMENSION
offsetvrsku  = DIMENSION
offsetspodku = DIMENSION
mp           = NAME
n            = NUMMER
offset       = DIMENSION
```

\nastavotoceni [...,*...]

```
* misto      = prizpusobive široky podlehloubky vysoko nastred implicitni normalni
rotace       = vlevo vpravo uvnitr vnejsi NUMMER
inherits: \nastavoramovani
```

\nastavpaletu [...]

```
* NAME
```

\nastavplvouciobjekt [...,¹...] [...,²...]

```
1 SINGULAR OPT
2 odsadpristi      = ano ne auto
implicitni        = inherits: \placefloat
fallback          = inherits: \placefloat
vnitrni           = BEFEHL
kriterium         = DIMENSION
metoda            = NUMMER
sidemethod        = NUMMER
textmethod        = NUMMER
sidealign         = vyska podlehloubky radek pulradku mrizka normalni
mrizka            = inherits: \snaptogrid
lokalne           = ano ne
prikaz            = \...#1
availablewidth    = DIMENSION
availableheight   = DIMENSION
minsirka          = DIMENSION
maxsirka          = DIMENSION
misto             = vlevo vpravo nastred flushleft flushright center max uvnitr vnejsi innermargin outermargin
                  inneredge outeredge zpetnamezera cutspace levyokraj pravyokraj levahrana pravahrana
vzdalenostlevehookraje = DIMENSION
vzdalenostpravhookraje = DIMENSION
levyokraj         = DIMENSION
pravyokraj       = DIMENSION
innermargin       = DIMENSION
outermargin       = DIMENSION
bottombefore      = BEFEHL
bottomafter       = BEFEHL
expanzen          = ano ne xml
referenceprefix    = + - TEXT
xmlsetup          = NAME
catcodes          = NAME
freeregion        = ano ne
mezerapred        = zadny inherits: \preskoc
mezeraza          = zadny inherits: \preskoc
sirka             = DIMENSION
vyska            = DIMENSION
offset            = DIMENSION zadny prekryv
bocnimezerapred   = zadny inherits: \preskoc
bocnimezeraza     = zadny inherits: \preskoc
spacebeforeside   = zadny inherits: \preskoc
spaceafterside    = zadny inherits: \preskoc
sidethreshold     = old dimension
marginalie        = DIMENSION
nvrsek            = DIMENSION
nspodek           = DIMENSION
krok              = male stredni velke radek podlehloubky
nrady             = NUMMER
cache             = ano ne
```


<p>\nastavplvouciobjekty [...¹,...] [...²,...]</p> <p>1 SINGULAR OPT</p> <p>2 inherits: \nastavplvouciobjekt</p>
<p>\nastavpodcislostrany [...[*],...]</p> <p>* inherits: \setupcounter</p>
<p>\nastavpole [...¹,...] [...²,...] [...³,...] [...⁴,...] [...⁵,...]</p> <p>1 NAME OPT OPT OPT OPT</p> <p>2 reset popisec ramecek horizontalne vertikalne</p> <p>3 inherits: \setupfieldtotalframed</p> <p>4 inherits: \setupfieldlabelframed</p> <p>5 inherits: \setupfieldcontentframed</p>
<p>\nastavpolozky [...¹,...] [...²,...]</p> <p>1 NAME OPT</p> <p>2 alternativa = vlevo vpravo vrsek spodek naokraji</p> <p>sirkatextu = DIMENSION</p> <p>sirka = DIMENSION</p> <p>vzdalenost = DIMENSION</p> <p>symbol = zadny NAME</p> <p>zarovnani = vlevo nastred vpravo flushleft flushright uvnitr vnejsi marginalie</p> <p>textalign = vlevo nastred vpravo flushleft flushright uvnitr vnejsi</p> <p>n = NUMMER</p> <p>pred = BEFEHL</p> <p>po = BEFEHL</p> <p>mezi = BEFEHL</p>
<p>\nastavpopisek [...¹,...] [...²,...]</p> <p>1 NAME OPT</p> <p>2 inherits: \setupfloatcaption</p>
<p>\nastavpopisky [...¹,...] [...²,...]</p> <p>1 NAME OPT</p> <p>2 inherits: \setupfloatcaption</p>
<p>\nastavpozadi [...¹,...] [...²,...]</p> <p>1 NAME OPT</p> <p>2 status = start stop</p> <p>levyoffset = DIMENSION</p> <p>pravyoffset = DIMENSION</p> <p>offsetvrsku = DIMENSION</p> <p>offsetspodku = DIMENSION</p> <p>pred = BEFEHL</p> <p>po = BEFEHL</p> <p>inherits: \nastavoramovani</p>
<p>\nastavpozadi [...¹,...] [...²,...]</p> <p>1 papir stranka levas^{PT}tranka pravastranka text skryte</p> <p>2 status = start stop</p> <p>inherits: \nastavoramovani</p>
<p>\nastavprechodstrany [...]</p> <p>* reset auto start nahodny NUMMER</p>
<p>\nastavpreskok [...[*],...]</p> <p>* inherits: \preskoc OPT</p>
<p>\nastavprogramy [...[*],...]</p> <p>* pismo = STYLE BEFEHL</p> <p>barva = COLOR</p>
<p>\nastavradkovani [...]</p> <p>* fixne zhustene sirok^{PT}y</p>

\nastavradky [...¹,...] [...²,...]

```

1  NAME          OPT
2  volba         = zhustene
   pred          = BEFEHL
   po            = BEFEHL
   mezi          = BEFEHL
   odsazovani    = inherits: \nastavodsazovani
   zarovnani     = inherits: \nastavzarovnani
   mezera        = ano zap vyp fixne implicitni
   prikaz        = BEFEHL
   pismo         = STYLE BEFEHL
   barva         = COLOR
   vlevo         = BEFEHL
   vpravo        = BEFEHL

```

\nastavrejstrik [...¹] [...²,...]

```

1  NAME NAME:NUMMER  OPT
2  referencemethod   = vpred
   expanzen          = ano ne xml
   vlastnicislo      = ano ne
   xmlsetup          = NAME
   alternativa       = a b A B
   metoda            = implicitni pred po prvni posledni ch mm zm pm mc zc pc uc
   compress          = ano ne vse
   kriterium         = lokalne text aktualni predchozi vse ABSCHNITT
   pageprefixseparatorset = BEFEHL
   pageprefixconversionset = NAME
   pageprefixstarter = BEFEHL PROCESSOR->BEFEHL
   pageprefixstopper = BEFEHL PROCESSOR->BEFEHL
   pageprefixset      = NAME
   pageprefixsegments = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:*
                        ABSCHNITT:vse
   pageprefixconnector = BEFEHL
   pageprefix        = ano ne
   pageseparatorset  = NAME
   pageconversionset  = NAME
   pagestarter       = BEFEHL PROCESSOR->BEFEHL
   pagestopper       = BEFEHL PROCESSOR->BEFEHL
   pagesegments      = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse
   maxsirka          = DIMENSION
   indikator         = ano ne
   pred              = BEFEHL
   po                 = BEFEHL
   prikaz            = \...##1
   textovyprikaz     = \...##1
   deeptextcommand   = \...##1
   strankovyprikaz   = \...##1
   vzdalenost        = DIMENSION
   interakce         = text cislostranky
   cislostranky       = ano ne
   symbol            = a n zadny 1 2 BEFEHL
   language           = implicitni DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scn SPRACHE
   pismo             = STYLE BEFEHL
   barva             = COLOR
   styltextu         = STYLE BEFEHL
   barvatextu        = COLOR
   stylstranky       = STYLE BEFEHL
   barvastranky      = COLOR
   n                 = NUMMER
   rovnovaha         = ano ne
   zarovnani         = inherits: \nastavzarovnani
   numberorder       = cisla

```

\nastavrejstrik [...¹,...] [...²,...] [...³,...]

```

1  NAME                OPT      OPT
2  NUMMER
3  referencemethod      = vpred
   expanzen             = ano ne xml
   vlastnicislo         = ano ne
   xmlsetup             = NAME
   alternativa          = a b A B
   metoda               = implicitni pred po prvni posledni ch mm zm pm mc zc pc uc
   compress             = ano ne vse zhustene
   kriterium            = lokalne text aktualni predchozi vse ABSCHNITT
   pageprefixseparatorset = BEFEHL
   pageprefixconversionset = NAME
   pageprefixstarter    = BEFEHL PROCESSOR->BEFEHL
   pageprefixstopper    = BEFEHL PROCESSOR->BEFEHL
   pageprefixset        = NAME
   pageprefixsegments   = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:*
                        ABSCHNITT:vse
   pageprefixconnector  = BEFEHL
   pageprefix           = ano ne
   pageseparatorset     = NAME
   pageconversionset    = NAME
   pagestarter          = BEFEHL PROCESSOR->BEFEHL
   pagestopper          = BEFEHL PROCESSOR->BEFEHL
   pagesegments         = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse
   maxsirka             = DIMENSION
   indikator            = ano ne
   pred                 = BEFEHL
   po                   = BEFEHL
   prikaz               = \...#1
   textovyprikaz        = \...#1
   deeptextcommand      = \...#1
   strankovyprikaz      = \...#1
   vzdalenost           = DIMENSION
   interakce            = text cislostranky
   cislostranky         = ano ne
   symbol               = a n zadny 1 2 BEFEHL
   language             = implicitni DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scn SPRACHE
   pismo                = STYLE BEFEHL
   barva                = COLOR
   styltextu            = STYLE BEFEHL
   barvatextu           = COLOR
   stylstranky          = STYLE BEFEHL
   barvastranky         = COLOR
   n                    = NUMMER
   rovnovaha            = ano ne
   zarovnnani           = inherits: \nastavzarovnnani
   numberorder          = cisla

```

\nastaveniREGISTER [...¹,...] [...²,...]

```

1  NUMMER                OPT
2  inherits: \nastavrejstrik
instances: index

```

\nastaveniindex [...¹,...] [...²,...]

```

1  NUMMER                OPT
2  inherits: \nastavrejstrik

```

\nastavrovnice [...¹,...] [...²,...]

```

1  NAME                OPT
2  inherits: \setupformula

```

\nastavsadusymbolu [...]

```

*  NAME

```

\nastavseznam [...,¹...] [...,²...,...]

1 LISTE OPT
2 status = start stop
misto = zadny zde
typ = simple prikaz userdata
kriterium = lokalne uvod odkaz SECTIONBLOCK:odkaz vse SECTIONBLOCK:vse text SECTIONBLOCK:text
aktualni SECTIONBLOCK:aktualni zde predchozi SECTIONBLOCK:predchozi komponenta ABSCHNITT
SECTIONBLOCK:ABSCHNITT
seznam = NAME
sirka = prizpusobive siroky auto DIMENSION
vyska = prizpusobive siroky DIMENSION
hloubka = prizpusobive siroky DIMENSION
symbol = jedna dve tri zadny implicitni
popisek = ano ne zadny NAME
starter = BEFEHL
predel = BEFEHL
prikaz = \...#1#2#3
ciselnyprikaz = \...#1
textovyprikaz = \...#1
strankovyprikaz = \...#1
cislostranky = ano ne vzdy
cislonadpisu = ano ne vzdy
pred = BEFEHL
po = BEFEHL
mezi = BEFEHL
marginalie = zadny DIMENSION
vzdalenost = zadny DIMENSION
zarovnejtitul = ano ne
numberalign = vlevo vpravo nastred flushleft flushright uvnitr vnejsi
zarovnani = inherits: \nastavzarovnani
zaveseni = ano ne
vlevo = BEFEHL
vpravo = BEFEHL
interakce = ano ne vse cislo text titul stranka cislooddilu cislostranky
limittext = ano ne TEXT
pismeno = STYLE BEFEHL
barva = COLOR
stylcisla = STYLE BEFEHL
barvacisla = COLOR
styltextu = STYLE BEFEHL
barvatextu = COLOR
stylstranky = STYLE BEFEHL
barvastranky = COLOR
odkaz = NUMMER
extras = NAME
order = prikaz vse titul
alternativa = a b c d e f g vlevo vpravo vrsek spodek prikaz zadny interactive odstavec horizontalne
vertikalne NAME
maxsirka = DIMENSION
pageprefix = ano ne
pageprefixseparatorset = NAME
pageprefixconversionset = NAME
pageprefixset = NAME
pageprefixsegments = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:*
ABSCHNITT:vse
pageprefixconnector = BEFEHL PROCESSOR->BEFEHL
pageconversionset = NAME
pagestarter = BEFEHL PROCESSOR->BEFEHL
pagestopper = BEFEHL PROCESSOR->BEFEHL
inherits: \setupcounterinherits: \nastavoramovani

\nastavsirkucary [...]

* male stredni velke DIMENSION

\nastavsloupce [...,*...,...]

* n = NUMMER
vzdalenost = DIMENSION
volba = pozadi
offset = DIMENSION
prikaz = \...#1
vyska = DIMENSION
smer = vlevo vpravo
rovnovaha = ano ne
zarovnani = setupalign
tolerance = setuptolerance
prazdny = inherits: \preskoc
nvrsek = NUMMER
linka = zap vyp BEFEHL

`\nastavspodek [...]1 [...,...2...]`

1 text marginalie^{OPT}hrana
2 inherits: \setuplayoutelement

`\nastavsynonyma [...]1 [...,...2...]`

1 SINGULAR^{OPT}
2 expanden = ano ne xml
alternativa = prvni posledni normalni NAME
dalsi = BEFEHL
prikaz = \...##1##2##3
textovyprikaz = \...##1
synonymcommand = \...##1
language = implicitni DIN_L5007-1 DIN_L5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scn SPRACHE
metoda = implicitni pred po prvni posledni ch mm zm pm mc zc pc uc
kriterium = aktualni predchozi lokalne text vse ABSCHNITT
pismeno = STYLE BEFEHL
barva = COLOR
styltextu = STYLE BEFEHL
barvatextu = COLOR
stylsynonyma = STYLE BEFEHL
barvasynonyma = COLOR

`\nastavtabelaci [...]1 [...]2 [...,...3...]`

1 NAME^{OPT}
2 NAME^{OPT}
3 inherits: \setuptabulation

`\nastavtabulky [...,...*...]`

* text = DIMENSION max
split = ano ne opakovat auto
ramecek = zap vyp
NL = inherits: \preskoc
VL = male stredni velke zadny NUMMER
HL = male stredni velke zadny NUMMER
vzdalenost = male stredni velke zadny
zarovnani = vlevo nastred vpravo
prikazy = BEFEHL
zakladnifont = inherits: \nastavzakladnifont
tloustkalinky = DIMENSION
vyska = strut NUMMER
hloubka = strut NUMMER
openup = DIMENSION

`\nastavtenkelinky [...,...*...]`

* vyska = max DIMENSION
hloubka = max DIMENSION
pozadi = barevne
ramecek = zap vyp
tloustkalinky = DIMENSION
alternativa = a b c zadny
barvapozadi = COLOR
barva = COLOR
meziradkovamezera = male stredni velke NUMMER
pred = BEFEHL
po = BEFEHL
mezi = BEFEHL
n = NUMMER

`\nastavtext [...]1 [...,...2...]`

1 text marginalie^{OPT}hrana
2 inherits: \setuplayoutelement

`\nastavtextovetlinky [...1...2...]`

```
*   pred      = BEFEHL
    po        = BEFEHL
    mezi      = BEFEHL
    tloustkalinky = DIMENSION
    misto     = vlevo naokraji
    pismeno   = STYLE BEFEHL
    barva     = COLOR
    barvalinky = COLOR
    sirka     = DIMENSION
    vyska     = DIMENSION
    vzdalenost = DIMENSION
    korekcehloubky = zap vyp
    zakladnifont = inherits: \nastavzakladnifont
```

`\nastaveniLABELtext [...1...2...]`

```
1   SPRACHE      OPT
2   KEY = VALUE
```

instances: head label mathlabel taglabel unit operator prefix suffix btxlabel

`\nastavenibtxlabeltext [...1...2...]`

```
1   SPRACHE      OPT
2   KEY = VALUE
```

`\nastaveniheadtext [...1...2...]`

```
1   SPRACHE      OPT
2   KEY = VALUE
```

`\nastavenilabeltext [...1...2...]`

```
1   SPRACHE      OPT
2   KEY = VALUE
```

`\nastavenimathlabeltext [...1...2...]`

```
1   SPRACHE      OPT
2   KEY = VALUE
```

`\nastavenioperatortext [...1...2...]`

```
1   SPRACHE      OPT
2   KEY = VALUE
```

`\nastaveniprefixtext [...1...2...]`

```
1   SPRACHE      OPT
2   KEY = VALUE
```

`\nastavenisuffixtext [...1...2...]`

```
1   SPRACHE      OPT
2   KEY = VALUE
```

`\nastavenitaglabeltext [...1...2...]`

```
1   SPRACHE      OPT
2   KEY = VALUE
```

`\nastaveniunittext [...1...2...]`

```
1   SPRACHE      OPT
2   KEY = VALUE
```

`\nastavtexttexty [...1...2...3...4...5...]`

```
1   text marginalie hranPT OPT OPT OPT OPT
2   datum cislostranky BESCHRIFTUNG TEXT BEFEHL
3   datum cislostranky BESCHRIFTUNG TEXT BEFEHL
4   datum cislostranky BESCHRIFTUNG TEXT BEFEHL
5   datum cislostranky BESCHRIFTUNG TEXT BEFEHL
```

`\nastavtextyupati` [¹...] [²...] [³...] [⁴...] [⁵...]

```
1 text marginalie hrana OPT OPT OPT OPT OPT
2 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
3 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
4 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
5 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
```

`\nastavtextyzahlavi` [¹...] [²...] [³...] [⁴...] [⁵...]

```
1 text marginalie hrana OPT OPT OPT OPT OPT
2 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
3 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
4 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
5 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
```

`\nastavtoleranci` [...*...]

* horizontalne vertikalne velmistriktni striktni tolerantni velmitolerantni mezera natahnout

`\nastavtrideni` [...¹,...] [...²,...]

```
1 SINGULAR OPT
2 expanzen = ano ne xml
alternativa = prvni posledni normalni NAME
dalsi = BEFEHL
prikaz = \...##1##2##3
textovyprikaz = \...##1
synonymcommand = \...##1
language = implicitni DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scsc SPRACHE
metoda = implicitni pred po prvni posledni ch mm zm pm mc zc pc uc
kriterium = aktualni predchozi lokalne text vse ABSCHNITT
pismeno = STYLE BEFEHL
barva = COLOR
styltextu = STYLE BEFEHL
barvatextu = COLOR
stylsynonyma = STYLE BEFEHL
barvasynonyma = COLOR
```

`\nastavtype` [...¹,...] [...²,...]

```
1 NAME OPT
2 volba = mp lua xml parsed-xml nested tex context zadny NAME
prikaz = CSNAME
vlevo = BEFEHL
vpravo = BEFEHL
tab = ano ne NUMMER
compact = absolutni posledni vse
escape = ano ne TEXT PROCESSOR->TEXT
pismeno = STYLE BEFEHL
barva = COLOR
radky = ano ne normalni hyphenated
mezera = zap vyp normalni fixne natahnout
```

`\nastavumisteniprotejsku` [...,*...]

```
* status = start stop
pred = BEFEHL
po = BEFEHL
mezi = BEFEHL
```

`\nastavumistovani` [...¹,...] [...²,...]

```
1 NAME OPT
2 offset = ano ne
jednotka = ex em pt in cm mm sp bp pc dd cc nc
status = start prekryv
xoffset = DIMENSION
yoffset = DIMENSION
xkrok = absolutni relativni
ykrok = absolutni relativni
xmeritko = NUMMER
ymeritko = NUMMER
xfaktor = NUMMER
yfaktor = NUMMER
faktor = NUMMER
meritko = NUMMER
```

\nastavupati [...] [...] ²

1 text marginalie^{OPT}strana
2 inherits: \setuplayoutelement

\nastavupravu [...] ¹ [...] [...] ²

1 NAME ^{OPT}
2 stranka = inherits: \strana
prikaz = BEFEHL
sirka = DIMENSION
vyska = DIMENSION
zarovnani = inherits: \nastavzarovnani
setups = NAME
vrsek = BEFEHL
spodek = BEFEHL
pred = BEFEHL
po = BEFEHL
misto = vrsek
odkaz = REFERENCE
pagestate = start stop
statuszahlavi = start stop vysoko prazdne zadny normalni
statusupati = start stop vysoko prazdne zadny normalni
statusvrsku = start stop vysoko prazdne zadny normalni
statusspodku = start stop vysoko prazdne zadny normalni
statustextu = start stop vysoko prazdne zadny normalni
oboustranne = ano ne prazdne
pismo = STYLE BEFEHL
barva = COLOR

\nastavurl [...] ^{*}

* pismo = STYLE BEFEHL
barva = COLOR

\nastavusporadani [...] ^{*}

* zablokovat zrcadleno dvoustranny negativ 90 180 270 reset pozadi normalni 2*16 2*8 2*4 2*2 2**2 2SIDE 2TOP
2UP 2DOWN 2*4*2 2*2*4 2TOPSIDE 2*8*Z 2*6*Z 1*8 1*4 3SIDE TRYPTICHON ZFLYER-8 ZFLYER-10 ZFLYER-12 MAPFLYER-12
DOUBLEWINDOW 1*2-Conference 1*4-Conference 2*2*2 2*2*3 XY NAME

\nastavvelikostpapiru [...] ¹ [...] [...] ²

1 NAME ^{OPT}
2 vrsek = BEFEHL
spodek = BEFEHL
vlevo = BEFEHL
vpravo = BEFEHL
metoda = normalni zadny NAME
meritko = NUMMER
nx = NUMMER
ny = NUMMER
dx = DIMENSION
dy = DIMENSION
sirka = DIMENSION
vyska = DIMENSION
svrchnimezera = DIMENSION
zpetnamezera = DIMENSION
offset = DIMENSION
stranka = reset nasirku zrcadleno negativ otoceno 90 180 270 NAME
papier = reset nasirku zrcadleno negativ otoceno 90 180 270 NAME
volba = prizpusobive max
vzdalenost = DIMENSION

\nastavvelikostpapiru [...] ¹ [...] [...] ²

1 reset nasirku zrcadleno negativ otoceno 90^{OPT}180 270 NAME
2 reset nasirku zrcadleno negativ otoceno 90 180 270 NAME

\nastavvsechnapole [...] ¹ [...] [...] ² [...] [...] ³ [...] [...] ⁴

1 reset popisek ramecek horizontalne vertikálne ^{OPT}
2 inherits: \setupfieldtotalframed
3 inherits: \setupfieldlabelframed
4 inherits: \setupfieldcontentframed

\nastavvycty [...] ¹ [...] [...] ²

1 NAME ^{OPT}
2 inherits: \setupenumeration

\nastavvyplnovelinky [...,*...]

```
*   pred      = BEFEHL
    po        = BEFEHL
    n         = NUMMER
    meziradkovamezera = male stredni velke NUMMER
    vzdalenost = DIMENSION
    sirka      = prizpusobive široky DIMENSION
    oddelovac  = BEFEHL
    pismo      = STYLE BEFEHL
    barva      = COLOR
```

\nastavvyplnoveradky [...,*...]

```
*   pred      = BEFEHL
    po        = BEFEHL
    marginalie = DIMENSION
    sirka      = DIMENSION
    vzdalenost = DIMENSION
    tloustkalinky = DIMENSION
    barva      = COLOR
```

\nastavvzhled [...¹][...²...]

```
1   NAME      OPT
2   status    = start stop normalni opakovat
    marginalie = DIMENSION
    hrana     = DIMENSION
    vzdalenostokraje = DIMENSION
    vzdalenosthrany = DIMENSION
    vzdalenostlevehrany = DIMENSION
    vzdalenostpravehrany = DIMENSION
    vzdalenostlevehookraje = DIMENSION
    vzdalenostpravehookraje = DIMENSION
    vzdalenostvrsku = DIMENSION
    vzdalenostzahlavi = DIMENSION
    vzdalenostupati = DIMENSION
    vzdalenostspodku = DIMENSION
    prednastaveni = NAME
    levyokraj    = DIMENSION
    pravyokraj   = DIMENSION
    levahrana    = DIMENSION
    pravahrana   = DIMENSION
    zahlavi     = DIMENSION
    upati       = DIMENSION
    vrsek       = DIMENSION
    spodek      = DIMENSION
    zpetnamezera = DIMENSION
    svrchnimezera = DIMENSION
    setups      = NAME
    cutspace    = DIMENSION
    sirka      = DIMENSION nastred prizpusobive
    bottomspace = DIMENSION
    radky      = NUMMER
    vyska      = DIMENSION nastred prizpusobive
    horoffset   = DIMENSION
    offsethlavicky = DIMENSION
    sloupce     = NUMMER
    vzdalenostsloupcu = DIMENSION
    metoda     = implicitni normalni NAME
    misto      = vlevo nastred vpravo vrsek spodek jednostranne dvoustranny
    sirkatextu = DIMENSION
    vyskatextu = DIMENSION
    nx         = NUMMER
    ny         = NUMMER
    dx         = DIMENSION
    dy         = DIMENSION
    meritko    = NUMMER
    sx         = NUMMER
    sy         = NUMMER
    znaceni    = zap vyp stranka prazdne barevne jedna dve ctyri
    mrizka     = ano ne vyp
    textdistance = DIMENSION
    alternativa = implicitni normalni zlom NAME
    clipoffset  = DIMENSION
    cropoffset  = DIMENSION
    trimoffset  = DIMENSION
    bleedoffset = DIMENSION
    artoffset   = DIMENSION
```

<p>\nastavvzhled [...] ¹</p> <p>* reset NAME</p>
<p>\nastavzahlavi [...] [...] ²</p> <p>1 text marginalie hr¹ta</p> <p>2 inherits: \setuplayoutelement</p>
<p>\nastavzakladnifont [...] [*]</p> <p>* DIMENSION NAME globalne res¹et x xx male velke script scriptscript rm ss tt hw cg antikva serif pravidelne sans bezserifu podpora opis strojopis mono rukopisne kaligraficke</p>
<p>\nastavzarovnani [...] [*]</p> <p>* široky siroce spodek vyska radek vysoko nizko nivy flushright flushleft nastred ano ne sirka normalni reset uvnitr vnejsi flushinner flushouter vlevo vpravo center zablockovat posledni end odstavec lefttoright righttoleft l2r r2l tabulka lesshyphenation morehyphenation visici nothanging hz fullhz nohz hyphenated nothyphenated tolerantni velmitolerantni natahnout extremestretch finalni 1*final 2*final 3*final 4*final more 1*more 2*more</p>
<p>\nastavznaceni [...] ¹ [...] ²</p> <p>1 BESCHRIFTUNG ^{OPT}</p> <p>2 status = start stop</p> <p>expanzen = ano ne</p> <p>oddelovac = BEFEHL</p> <p>filtercommand = \...##1</p>
<p>\nastavzuzeni [...] ¹ [...] ²</p> <p>1 NAME ^{OPT}</p> <p>2 vlevo = DIMENSION</p> <p>stredni = DIMENSION</p> <p>vpravo = DIMENSION</p> <p>implicitni = [-+]vlevo [-+]nastred [-+]vpravo NUMMER*vlevo NUMMER*nastred NUMMER*vpravo reset</p> <p>pred = BEFEHL</p> <p>po = BEFEHL</p>
<p>\nastrane [...]</p> <p>* REFERENCE</p>
<p>\nastred ...</p> <p>* CHARACTER</p>
<p>\naturalhbox ¹ [...] ²</p> <p>1 TEXT ^{OPT}</p> <p>2 CONTENT</p>
<p>\naturalhpack ¹ [...] ²</p> <p>1 TEXT ^{OPT}</p> <p>2 CONTENT</p>
<p>\naturalvbox ¹ [...] ²</p> <p>1 TEXT ^{OPT}</p> <p>2 CONTENT</p>
<p>\naturalvcenter ¹ [...] ²</p> <p>1 TEXT ^{OPT}</p> <p>2 CONTENT</p>
<p>\naturalvpack ¹ [...] ²</p> <p>1 TEXT ^{OPT}</p> <p>2 CONTENT</p>
<p>\naturalvtop ¹ [...] ²</p> <p>1 TEXT ^{OPT}</p> <p>2 CONTENT</p>

<code>\naturalwd ...</code> * CSNAME NUMMER
<code>\negatecolorbox ...</code> * CSNAME NUMMER
<code>\negated {...}</code> * TEXT
<code>\negthinspace</code>
<code>\nejakyradek [...]</code> * REFERENCE
<code>\nekde {...} {...} [...]</code> 1 TEXT 2 TEXT 3 REFERENCE
<code>\newattribute \...</code> * CSNAME
<code>\newcatcodetable \...</code> * CSNAME
<code>\newcounter \...</code> * CSNAME
<code>\newevery \¹ \²</code> 1 CSNAME 2 CSNAME
<code>\newfrenchspacing</code>
<code>\newmode {...}</code> * NAME
<code>\newsignal \...</code> * CSNAME
<code>\newsystemmode {...}</code> * NAME
<code>\nextbox</code>
<code>\nextboxdp</code>
<code>\nextboxht</code>
<code>\nextboxhtdp</code>
<code>\nextboxwd</code>
<code>\nextcounter [...] [²]</code> 1 NAME OPT 2 NUMMER

<code>\nextcountervalue [...]</code> * NAME
<code>\nextdepth</code>
<code>\nextparagraphs</code>
<code>\dalsiPARAGRAPHS</code>
<code>\nextrealpage</code>
<code>\nextrealpagenumber</code>
<code>\nextsubcountervalue [...]¹ [...]²</code> 1 NAME 2 NUMMER
<code>\nextsubpagenumber</code>
<code>\nextuserpage</code>
<code>\nextuserpagenumber</code>
<code>\neznamo</code>
<code>\nivy [...]¹ {...}² {...}³</code> 1 vlevo pravo 2 CONTENT 3 CONTENT
<code>\nizky {...}</code> * CONTENT
<code>\LOW {...}</code> * CONTENT instances: unitslow
<code>\unitslow {...}</code> * CONTENT
<code>\nocitation [...]</code> * REFERENCE
<code>\nocitation {...}</code> * REFERENCE
<code>\nocite [...]</code> * REFERENCE
<code>\nocite {...}</code> * REFERENCE
<code>\nodetostring \...¹ {...}²</code> 1 CSNAME 2 CONTENT

<code>\nofigurepages</code>
<code>\noflines</code>
<code>\noflocalfloats</code>
<code>\noheightstrut</code>
<code>\noindentation</code>
<code>\noitem</code>
<code>\nokap {...}</code> * TEXT
<code>\nonfrenchspacing</code>
<code>\nonmathematics {...}</code> * CONTENT
<code>\normalboldface</code>
<code>\normalframedwithsettings [...¹...²...] {...}</code> 1 inherits: \nastavoramovani 2 CONTENT
<code>\normalitalicface</code>
<code>\normalizebodyfontsize \...¹ {...²}</code> 1 CSNAME 2 DIMENSION
<code>\normalizedfontsize</code>
<code>\normalizefontdepth \...¹ {...²} {...³} {...⁴}</code> 1 CSNAME 2 TEXT 3 DIMENSION 4 FONT
<code>\normalizefontheight \...¹ {...²} {...³} {...⁴}</code> 1 CSNAME 2 TEXT 3 DIMENSION 4 FONT
<code>\normalizefontline \...¹ {...²} {...³} {...⁴}</code> 1 CSNAME 2 TEXT 3 DIMENSION 4 FONT
<code>\normalizefontwidth \...¹ {...²} {...³} {...⁴}</code> 1 CSNAME 2 TEXT 3 DIMENSION 4 FONT

<code>\normalizetextdepth {...} {...} {...}</code> 1 FONT 2 DIMENSION 3 TEXT
<code>\normalizetextheight {...} {...} {...}</code> 1 FONT 2 DIMENSION 3 TEXT
<code>\normalizetextline {...} {...} {...}</code> 1 FONT 2 DIMENSION 3 TEXT
<code>\normalizetextwidth {...} {...} {...}</code> 1 FONT 2 DIMENSION 3 TEXT
<code>\normalni</code>
<code>\normalslantedface</code>
<code>\normaltypeface</code>
<code>\notesymbol [...] [...]</code> 1 NAME <small>OPT</small> 2 REFERENCE
<code>\notragged</code>
<code>\ntimes {...} {...}</code> 1 TEXT 2 NUMMER
<code>\numberofpoints {...}</code> * DIMENSION
<code>\obeydepth</code>
<code>\objectdepth</code>
<code>\objectheight</code>
<code>\objectmargin</code>
<code>\objectwidth</code>
<code>\obox {...}</code> * CONTENT
<code>\obrazovka [...,*...]</code> * inherits: <code>\strana</code> <small>OPT</small>
<code>\odkaz [...,¹...] {...}</code> 1 REFERENCE 2 TEXT

\odkaznastranu [...,*...] * REFERENCE
\odkaznatekst [..., ¹ ...] { ² .} 1 REFERENCE 2 TEXT
\odkazujici (..., ¹ ...) (..., ² ...) [... ³ .] 1 POSITION 2 POSITION 3 REFERENCE
\offset [..., ¹ ...] { ² .} 1 inherits: \setupoffset 2 CONTENT
\offsetbox [..., ¹ ...] \ ² . { ³ .} 1 inherits: \setupoffsetbox 2 CSNAME 3 CONTENT
\onedigitrounding {.*} * NUMMER
\opis [..., ¹ ...] { ² .} 1 inherits: \fastavtype 2 CONTENT
\opissoubor [... ¹] [..., ² ...] { ³ .} 1 NAME OPT OPT 2 inherits: \nastavopis 3 FILE
\opis [..., ¹ ...] << ² .>> 1 inherits: \fastavtype 2 ANGLES
\OPIS [..., ¹ ...] { ² .} 1 inherits: \fastavtype 2 CONTENT
\OPIS [..., ¹ ...] << ² .>> 1 inherits: \fastavtype 2 ANGLES
\oramovani [..., ¹ ...] { ² .} 1 inherits: \nastavoramovani 2 CONTENT
\FRAMED [..., ¹ ...] { ² .} 1 inherits: \nastavoramovani 2 CONTENT instances: unframed fitfieldframed
\fitfieldframed [..., ¹ ...] { ² .} 1 inherits: \nastavoramovani 2 CONTENT
\unframed [..., ¹ ...] { ² .} 1 inherits: \nastavoramovani 2 CONTENT

\backslash FRAMEDTEXT [... ¹ ... ² ...] {...} 1 inherits: \setupframedtext ^{OPT} 2 CONTENT instances: framedtext
\backslash framedtext [... ¹ ... ² ...] {...} 1 inherits: \setupframedtext ^{OPT} 2 CONTENT
\backslash ordinaldaynumber {...} * NUMMER
\backslash ordinalstr {...} * TEXT
\backslash oref [...] * REFERENCE
\backslash orez [... ¹ ... ² ...] {...} 1 inherits: \hastavorez ^{OPT} 2 CONTENT
\backslash ornamenttext [... ¹ ... ² ...] [... ³ ... ⁴ ...] {...} ^{OPT} 1 alternativa = a b inherits: \setupcollector 2 pismo = STYLE BEFEHL barva = COLOR inherits: \nastavoramovani 3 TEXT 4 CONTENT
\backslash ornamenttext [... ¹ ...] {... ² ... ³ ...} 1 NAME 2 TEXT 3 CONTENT
\backslash ornamenttext [... ¹ ... ² ...] [... ³ ... ⁴ ...] {...} ^{OPT} 1 alternativa = a b inherits: \setupplayer 2 inherits: \setuplayeredtext 3 TEXT 4 CONTENT
\backslash ORNAMENT {... ¹ ... ² ...} 1 TEXT 2 CONTENT
\backslash otocit [... ¹ ... ² ...] {...} 1 inherits: \nastavotoceni ^{OPT} 2 CONTENT
\backslash outputfilename
\backslash outputstreambox [...] * NAME
\backslash outputstreamcopy [...] * NAME
\backslash outputstreamunvbox [...] * NAME

<code>\outputstreamunvcopy [...]</code> * NAME
<code>\over [...]</code> * REFERENCE
<code>\overlaybutton [...]</code> * REFERENCE
<code>\overlaybutton {...}</code> * REFERENCE
<code>\overlaycolor</code>
<code>\overlaydepth</code>
<code>\overlayfigure {...}</code> * FILE
<code>\overlayheight</code>
<code>\overlaylinecolor</code>
<code>\overlaylinewidth</code>
<code>\overlayoffset</code>
<code>\overlayrollbutton [...]¹ [...]²</code> 1 REFERENCE 2 REFERENCE
<code>\overlaywidth</code>
<code>\overloaderror</code>
<code>\overset {...}¹ {...}²</code> 1 TEXT 2 TEXT
<code>\oznaceni (...¹,...) (...²,...) [...,³...³,...] {...⁴}</code> 1 POSITION 2 POSITION 3 inherits: \nastavoramovani 4 TEXT
<code>\PDFcolor {...}</code> * NAME
<code>\PDFETEX</code>
<code>\PDFTEX</code>
<code>\PICTEX</code>
<code>\PiCTeX</code>

\PointsToBigPoints {...} \^{.2}.. 1 DIMENSION 2 CSNAME
\PointsToReal {...} \^{.2}.. 1 DIMENSION 2 CSNAME
\PointsToWholeBigPoints {...} \^{.2}.. 1 DIMENSION 2 CSNAME
\PPCHTEX
\PPCHTeX
\PRAGMA
\PtToCm {...} * DIMENSION
\pagearea [...][...][...] 1 vrsek zahlevi text upati spodek 2 text marginalie hrana 3 vlevo vpravo lefttext middletext righttext
\pagebreak [...,*...] * prazdne zahlevi ^{OPT} upati dummy ramecek NUMMER +NUMMER implicitni reset zablokovat ano ne zlom prazdny nastaveni vysokapriorita vlevo vpravo sude liche cyrnasobny posledni poslednistrana start stop NAME
\pagefigure [...][... ² ...] 1 FILE ^{OPT} 2 offset = implicitni prekryv zadny DIMENSION
\pagegridspanwidth {...} * NUMMER
\pageinjection [...][... ² ...] 1 NAME ^{OPT} 2 KEY = VALUE ^{OPT}
\pageinjection [... ¹ ...][... ² ...] 1 inherits: \setuppageinjection ^{OPT} 2 KEY = VALUE
\pagestaterealpage {...} {...} 1 NAME 2 NAME NUMMER
\paletsize
\PARAGRAPHS
\pdfactualtext {...} {...} 1 CONTENT 2 TEXT
\pdfbackendactualtext {...} {...} 1 CONTENT 2 TEXT

<code>\pdfbackendcurrentresources</code>
<code>\pdfbackendsetcatalog {...} {...}</code> 1 NAME 2 TEXT
<code>\pdfbackendsetcolorspace {...} {...}</code> 1 NAME 2 TEXT
<code>\pdfbackendsettextgstate {...} {...}</code> 1 NAME 2 TEXT
<code>\pdfbackendsetinfo {...} {...}</code> 1 NAME 2 TEXT
<code>\pdfbackendsetname {...} {...}</code> 1 NAME 2 TEXT
<code>\pdfbackendsetpageattribute {...} {...}</code> 1 NAME 2 TEXT
<code>\pdfbackendsetpageresource {...} {...}</code> 1 NAME 2 TEXT
<code>\pdfbackendsetpagesattribute {...} {...}</code> 1 NAME 2 TEXT
<code>\pdfbackendsetpattern {...} {...}</code> 1 NAME 2 TEXT
<code>\pdfbackendsetshade {...} {...}</code> 1 NAME 2 TEXT
<code>\pdfcolor {...}</code> * NAME
<code>\pdfTeX</code>
<code>\pdfTeX</code>
<code>\percent</code>
<code>\percentdimen {...} {...}</code> 1 DIMENSION CSNAME 2 DIMENSION NUMBER
<code>\permitcaretescape</code>
<code>\permitcircumflexescape</code>

<code>\permitspacesbetweengroups</code>
<code>\persiandecimals {...}</code> * NUMMER
<code>\persiannumerals {...}</code> * NUMMER
<code>\phantom {...}</code> * CONTENT
<code>\phantombox [..., ...¹..., ...]</code> * sirka = DIMENSION * vyska = DIMENSION * hloubka = DIMENSION
<code>\pickupgroupedcommand {...} {...¹} {...²} {...³}</code> 1 BEFEHL 2 BEFEHL 3 BEFEHL
<code>\pis [..., ...¹..., ...] {...²}</code> 1 inherits: \ Nastavtype 2 CONTENT
<code>\pis [..., ...¹..., ...] <<...²>></code> 1 inherits: \ Nastavtype 2 ANGLES
<code>\placeattachments</code>
<code>\placebtxrendering [...¹] [..., ...²..., ...]</code> 1 NAME OPT OPT 2 inherits: \setupbtxrendering
<code>\placecitation [...]</code> * REFERENCE
<code>\placecomments</code>
<code>\placecurrentformulanumber</code>
<code>\placedbox {...}</code> * CONTENT
<code>\placefloat [...¹] [..., ...²..., ...] [..., ...³..., ...] {...⁴} {...⁵}</code> 1 SINGULAR OPT OPT 2 split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji lev yokraj prav yokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective zahlavi upati 3 REFERENCE 4 TEXT 5 CONTENT

\placefloatwithsetups [...]¹ [...]²,...] [...]³,...] {...}⁴ {...}⁵

- 1 NAME OPT OPT
- 2 split vzdý vľavo vpravo uvnitř vnějši zpetnamezera cutspace ivľavo ivpravo naokraj levýokraj pravýokraj leváhrana praváhrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mřizka vysoko nízko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective zahľavi upati
- 3 REFERENCE
- 4 TEXT
- 5 CONTENT

\umistiFLOAT [...]¹,...] [...]²,...] {...}³ {...}⁴

- 1 split vzdý vľavo vpravo uvnitř vnějši zpetnamezera cutspace ivľavo ivpravo naokraj levýokraj pravýokraj leváhrana praváhrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mřizka vysoko nízko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective zahľavi upati
- 2 REFERENCE
- 3 TEXT
- 4 CONTENT

instances: chemical figure table intermezzo graphic

\umistifigure [...]¹,...] [...]²,...] {...}³ {...}⁴

- 1 split vzdý vľavo vpravo uvnitř vnějši zpetnamezera cutspace ivľavo ivpravo naokraj levýokraj pravýokraj leváhrana praváhrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mřizka vysoko nízko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective zahľavi upati
- 2 REFERENCE
- 3 TEXT
- 4 CONTENT

\umistigraphic [...]¹,...] [...]²,...] {...}³ {...}⁴

- 1 split vzdý vľavo vpravo uvnitř vnějši zpetnamezera cutspace ivľavo ivpravo naokraj levýokraj pravýokraj leváhrana praváhrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mřizka vysoko nízko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective zahľavi upati
- 2 REFERENCE
- 3 TEXT
- 4 CONTENT

\umistichemical [...]¹,...] [...]²,...] {...}³ {...}⁴

- 1 split vzdý vľavo vpravo uvnitř vnějši zpetnamezera cutspace ivľavo ivpravo naokraj levýokraj pravýokraj leváhrana praváhrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mřizka vysoko nízko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective zahľavi upati
- 2 REFERENCE
- 3 TEXT
- 4 CONTENT

\umistiintermezzo [...]¹,...] [...]²,...] {...}³ {...}⁴

- 1 split vzdý vľavo vpravo uvnitř vnějši zpetnamezera cutspace ivľavo ivpravo naokraj levýokraj pravýokraj leváhrana praváhrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mřizka vysoko nízko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective zahľavi upati
- 2 REFERENCE
- 3 TEXT
- 4 CONTENT

\umistitable [...]¹,...] [...]²,...] {...}³ {...}⁴

- 1 split vzdý vľavo vpravo uvnitř vnějši zpetnamezera cutspace ivľavo ivpravo naokraj levýokraj pravýokraj leváhrana praváhrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mřizka vysoko nízko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective zahľavi upati
- 2 REFERENCE
- 3 TEXT
- 4 CONTENT

\placeframed [...]¹ [...]²,...] {...}³

- 1 NAME OPT
- 2 inherits: \nastavoramovani
- 3 CONTENT

<code>\placeheadnumber [...]</code> * ABSCHNITT
<code>\placeheadtext [...]</code> * ABSCHNITT
<code>\placehelp</code>
<code>\placeinitial [...]</code> * NAME OPT
<code>\placelayer [...]</code> * NAME
<code>\placelayeredtext [¹...] [...,²...,...] [...,³...,...] {⁴...} {⁵...}</code> 1 NAME 2 inherits: \setuplayer 3 inherits: \setuplayeredtext 4 TEXT 5 CONTENT
<code>\placelistofFLOATS [...,[*]...,...]</code> * inherits: \nastavseznam OPT instances: chemicals figures tables intermezzi graphics
<code>\placelistoffigures [...,[*]...,...]</code> * inherits: \nastavseznam OPT
<code>\placelistofgraphics [...,[*]...,...]</code> * inherits: \nastavseznam OPT
<code>\placelistofchemicals [...,[*]...,...]</code> * inherits: \nastavseznam OPT
<code>\placelistofintermezzi [...,[*]...,...]</code> * inherits: \nastavseznam OPT
<code>\placelistoftables [...,[*]...,...]</code> * inherits: \nastavseznam OPT
<code>\placelistofpublications [¹...] [...,²...,...]</code> 1 NAME OPT OPT 2 inherits: \setupbtxrendering
<code>\placelistofsorts [¹...] [...,²...,...]</code> 1 SINGULAR OPT 2 inherits: \nastavtrideni
<code>\placelistofSORTS [...,[*]...,...]</code> * inherits: \nastavtrideni OPT instances: logos
<code>\placelistoflogos [...,[*]...,...]</code> * inherits: \nastavtrideni OPT
<code>\placelistofsynonyms [¹...] [...,²...,...]</code> 1 SINGULAR OPT 2 inherits: \nastavsynonyma

<p><code>\placelistofSYNONYMS [...¹...²...]</code></p> <p>* inherits: \nastavsynonyma <small>OPT</small></p> <p>instances: abbreviations</p>
<p><code>\placelistofabbreviations [...¹...²...]</code></p> <p>* inherits: \nastavsynonyma <small>OPT</small></p>
<p><code>\placelocalnotes [...¹] [...²...]</code></p> <p>1 NAME <small>OPT</small></p> <p>2 inherits: \setupnote</p>
<p><code>\placement [...¹] [...²...]{...³}</code></p> <p>1 NAME <small>OPT</small></p> <p>2 inherits: \setupplacement</p> <p>3 CONTENT</p>
<p><code>\PLACEMENT [...¹...]{...²}</code></p> <p>1 inherits: \setupplacement <small>OPT</small></p> <p>2 CONTENT</p>
<p><code>\placenamefloat [...¹] [...²]</code></p> <p>1 NAME</p> <p>2 REFERENCE</p>
<p><code>\placenameformula [...¹...]{...²}</code></p> <p>1 + - REFERENCE <small>OPT</small></p> <p>2 TEXT</p>
<p><code>\placenotes [...¹...] [...²...]</code></p> <p>1 NAME <small>OPT</small></p> <p>2 inherits: \setupnote</p>
<p><code>\placepagenumber</code></p>
<p><code>\placepairedbox [...¹] [...²...]{...³}{...⁴}</code></p> <p>1 NAME <small>OPT</small></p> <p>2 inherits: \setuppairedbox</p> <p>3 CONTENT</p> <p>4 TEXT</p>
<p><code>\umistiPAIREDBOX [...¹...]{...²}{...³}</code></p> <p>1 inherits: \setuppairedbox <small>OPT</small></p> <p>2 CONTENT</p> <p>3 TEXT</p> <p>instances: legend</p>
<p><code>\umistilegend [...¹...]{...²}{...³}</code></p> <p>1 inherits: \setuppairedbox <small>OPT</small></p> <p>2 CONTENT</p> <p>3 TEXT</p>
<p><code>\placeparallel [...¹] [...²...][...³...]</code></p> <p>1 NAME <small>OPT</small></p> <p>2 NAME</p> <p>3 inherits: \setupparallel</p>
<p><code>\placeraawlist [...¹] [...²...]</code></p> <p>1 LISTE <small>OPT</small></p> <p>2 inherits: \nastavseznam</p>

<p><code>\placereadingwindow [...]</code> ¹ <code>[...]</code> ²</p> <p>1 NAME OPT</p> <p>2 NAME</p>
<p><code>\plnezneni {...}</code></p> <p>* NAME</p>
<p><code>\pole [...]</code> ¹ <code>[...]</code> ²</p> <p>1 NAME OPT</p> <p>2 TEXT</p>
<p><code>\polozka [...,*...]</code></p> <p>* REFERENCE OPT</p>
<p><code>\polozky [...,¹...,...]</code> ² <code>{...}</code></p> <p>1 inherits: \nastavopolozky OPT</p> <p>2 TEXT</p>
<p><code>\popattribute *...</code></p> <p>* CSNAME</p>
<p><code>\POPIS [...,¹...,...]</code> <code>{...}</code> ² <code>...</code> ³ <code>\par</code></p> <p>1 REFERENCE OPT OPT</p> <p>2 TEXT</p> <p>3 CONTENT</p>
<p><code>\popmacro *...</code></p> <p>* CSNAME</p>
<p><code>\popmode [...]</code></p> <p>* NAME</p>
<p><code>\POPISEK [...,¹...,...]</code> <code>{...}</code> ²</p> <p>1 REFERENCE OPT OPT</p> <p>2 TEXT</p>
<p><code>\popsystemmode {...}</code></p> <p>* NAME</p>
<p><code>\porovnejpaletu [...]</code></p> <p>* NAME</p>
<p><code>\porovnejskupinubarev [...]</code></p> <p>* NAME</p>
<p><code>\positionoverlay {...}</code></p> <p>* NAME</p>
<p><code>\positionregionoverlay {...}</code> ¹ <code>{...}</code> ² <code>{...}</code></p> <p>1 NAME</p> <p>2 NAME</p>
<p><code>\poslaednipodstranka</code></p>
<p><code>\postponenotes</code></p>
<p><code>\pozadi {...}</code></p> <p>* CONTENT</p>

<pre> \POZADI {...} * CONTENT instances: pozadi </pre>
<pre> \pozice [...,¹...,²...] {...} 1 inherits: \nasťavumistovani 2 POSITION 3 CONTENT </pre>
<pre> \poznamka [...¹] [...²] 1 NAME OPT 2 REFERENCE </pre>
<pre> \NOTE [...,¹...] {...²} 1 REFERENCE^{PT} 2 TEXT instances: footnote endnote </pre>
<pre> \NOTE [...,[*]...,...] * titul = TEXT zalozka = TEXT seznam = TEXT odkaz = REFERENCE instances: footnote endnote </pre>
<pre> \endnote [...,[*]...,...] * titul = TEXT zalozka = TEXT seznam = TEXT odkaz = REFERENCE </pre>
<pre> \footnote [...,[*]...,...] * titul = TEXT zalozka = TEXT seznam = TEXT odkaz = REFERENCE </pre>
<pre> \endnote [...,¹...] {...²} 1 REFERENCE OPT 2 TEXT </pre>
<pre> \footnote [...,¹...] {...²} 1 REFERENCE OPT 2 TEXT </pre>
<pre> \pravidelne </pre>
<pre> \predefinedfont [...] * FONT </pre>
<pre> \predefinefont [...¹] [...²] 1 NAME 2 FONT </pre>
<pre> \predefinesymbol [...] * NAME </pre>
<pre> \pref {...¹} {...²} [...³] 1 TEXT OPT OPT 2 TEXT 3 REFERENCE </pre>

<code>\prefixedpagenumber</code>
<code>\prelozit [...,*...,...]</code> <code>* SPRACHE = TEXT^{OPT}</code>
<code>\prependetoks ¹... \to \²...</code> <code>1 BEFEHL</code> <code>2 CSNAME</code>
<code>\prependgvalue {...} {...}</code> <code>1 NAME</code> <code>2 BEFEHL</code>
<code>\prependtocommalist {...} \²...</code> <code>1 TEXT</code> <code>2 CSNAME</code>
<code>\prependtoks ¹... \to \²...</code> <code>1 BEFEHL</code> <code>2 CSNAME</code>
<code>\prependtoksonce ¹... \to \²...</code> <code>1 BEFEHL</code> <code>2 CSNAME</code>
<code>\prependvalue {...} {...}</code> <code>1 NAME</code> <code>2 BEFEHL</code>
<code>\prepninazakladnifont [...,*...]</code> <code>* inherits: \nastavzakladnifont</code>
<code>\presetdocument [...,*...,...]</code> <code>* inherits: \setupdocument</code>
<code>\presetfieldsymbols [...,*...]</code> <code>* NAME</code>
<code>\presetLABELtext [...]¹ [...,...²...,...]</code> <code>1 SPRACHE^{OPT}</code> <code>2 KEY = VALUE</code> <code>instances: head label mathlabel taglabel unit operator prefix suffix btxlabel</code>
<code>\presetbtxlabeltext [...]¹ [...,...²...,...]</code> <code>1 SPRACHE^{OPT}</code> <code>2 KEY = VALUE</code>
<code>\presetheadtext [...]¹ [...,...²...,...]</code> <code>1 SPRACHE^{OPT}</code> <code>2 KEY = VALUE</code>
<code>\presetlabeltext [...]¹ [...,...²...,...]</code> <code>1 SPRACHE^{OPT}</code> <code>2 KEY = VALUE</code>
<code>\presetmathlabeltext [...]¹ [...,...²...,...]</code> <code>1 SPRACHE^{OPT}</code> <code>2 KEY = VALUE</code>

<pre> \presetoperatortext [...] [...] 1 SPRACHE 2 KEY = VALUE </pre>
<pre> \presetprefixtext [...] [...] 1 SPRACHE 2 KEY = VALUE </pre>
<pre> \presetsuffixtext [...] [...] 1 SPRACHE 2 KEY = VALUE </pre>
<pre> \presettaglabeltext [...] [...] 1 SPRACHE 2 KEY = VALUE </pre>
<pre> \presetunittext [...] [...] 1 SPRACHE 2 KEY = VALUE </pre>
<pre> \preskoc [...*,...] * nastaveni stejhastranka max sila enable zablockovat zadnabila zpet prekryv vzdy weak strong implicitni pred mezi po fixne prizpusobive zadny male stredni velke radek pulradku quarterline rovnice bily vyska podlehloubky standardni NUMMER*male NUMMER*stredni NUMMER*velke NUMMER*radek NUMMER*pulradku NUMMER*quarterline NUMMER*rovnice NUMMER*bily NUMMER*vyska NUMMER*podlehloubky category:NUMMER order:NUMMER penalty:NUMMER DIMENSION NAME </pre>
<pre> \pretocommalist {...} \^2.. 1 TEXT 2 CSNAME </pre>
<pre> \prettyprintbuffer {...} {...} 1 BUFFER 2 mp lua xml parsed-xml nested tex context zadny NAME </pre>
<pre> \prevcounter [...] [...] 1 NAME 2 NUMMER </pre>
<pre> \prevcountervalue [...] * NAME </pre>
<pre> \preventmode [...*,...] * NAME </pre>
<pre> \prevrealpage </pre>
<pre> \prevrealpagenumber </pre>
<pre> \prevsubcountervalue [...] [...] 1 NAME 2 NUMMER </pre>
<pre> \prevsubpage </pre>
<pre> \prevsubpagenumber </pre>
<pre> \prevuserpage </pre>
<pre> \prevuserpagenumber </pre>

<pre> \prizpusobivepole [...] [...,²...,...] 1 NAME OPT 2 inherits: \setupfieldbody </pre>
<pre> \prizpusobvzhled [...,¹...] [...,²...,...] 1 NUMBER OPT 2 vyska = max DIMENSION radky = NUMBER </pre>
<pre> \procent </pre>
<pre> \processaction [...] [...,²>...,...] 1 BEFEHL 2 APPLY </pre>
<pre> \processallactionsinset [...] [...,²>...,...] 1 BEFEHL 2 APPLY </pre>
<pre> \processassignlist [...,¹...] \²... 1 TEXT 2 CSNAME </pre>
<pre> \processassignmentcommand [...,¹...,...] \²... 1 KEY = VALUE 2 CSNAME </pre>
<pre> \processassignmentlist [...,¹...,...] \²... 1 KEY = VALUE 2 CSNAME </pre>
<pre> \processbetween {...} \²... 1 NAME 2 CSNAME </pre>
<pre> \processbodyfontenvironmentlist *... * CSNAME </pre>
<pre> \processcolorcomponents {...} * COLOR </pre>
<pre> \processcommacommand [...,¹...] \²... 1 BEFEHL 2 CSNAME </pre>
<pre> \processcommalist [...,¹...] \²... 1 BEFEHL 2 CSNAME </pre>
<pre> \processcommalistwithparameters [...,¹...] \²... 1 BEFEHL 2 CSNAME </pre>
<pre> \processcontent {...} \²... 1 NAME 2 CSNAME </pre>
<pre> \processfile {...} * FILE </pre>

<pre>\processfilemany {...} * FILE</pre>
<pre>\processfilenone {...} * FILE</pre>
<pre>\processfileonce {...} * FILE</pre>
<pre>\processfirstactioninset [...] [...=>...,...] 1 BEFEHL 2 APPLY</pre>
<pre>\processisolatedchars {...} \^2.. 1 TEXT 2 CSNAME</pre>
<pre>\processisolatedwords {...} \^2.. 1 TEXT 2 CSNAME</pre>
<pre>\processlinetablebuffer [...] * BUFFER OPT</pre>
<pre>\processlinetablefile {...} * FILE</pre>
<pre>\processlist {...} {...} {...} \^4.. 1 CHARACTER 2 CHARACTER 3 TEXT 4 CSNAME</pre>
<pre>\processMPbuffer [...,*...] * NAME OPT</pre>
<pre>\processMPfigurefile {...} * FILE</pre>
<pre>\processmonth {...} {...} {...} 1 NUMMER 2 NUMMER 3 BEFEHL</pre>
<pre>\processranges [...^1,...] \^2.. 1 NUMMER NUMMER:NUMMER 2 CSNAME</pre>
<pre>\processseparatedlist [...] [...] {...} 1 TEXT 2 TEXT 3 CSNAME BEFEHL</pre>
<pre>\processTEXbuffer [...] * BUFFER OPT</pre>

<pre> \processtokens {...} {...} {...} {...} {...} 1 BEFEHL 2 BEFEHL 3 BEFEHL 4 BEFEHL 5 TEXT </pre>
<pre> \processuntil *. * CSNAME </pre>
<pre> \processxtablebuffer [...] * NAME OPT </pre>
<pre> \processyear {...} {...} {...} {...} 1 NUMMER 2 BEFEHL 3 BEFEHL 4 BEFEHL </pre>
<pre> \produkt [...] * FILE </pre>
<pre> \produkt ... * FILE </pre>
<pre> \profiledbox [...] [...] {...} 1 zadny fixne striktni halffixed quarterfixed eightsfixed NAME 2 inherits: \setupprofile 3 CONTENT </pre>
<pre> \profilegivenbox {...} ... 1 zadny fixne striktni halffixed quarterfixed eightsfixed NAME 2 CSNAME NUMMER </pre>
<pre> \program [...] * NAME </pre>
<pre> \projekt [...] * FILE </pre>
<pre> \projekt ... * FILE </pre>
<pre> \prostredi [...] * FILE </pre>
<pre> \prostredi ... * FILE </pre>
<pre> \prvnipodstranka </pre>
<pre> \pseudoMixedCapped {...} * TEXT </pre>
<pre> \pseudoSmallCapped {...} * TEXT </pre>
<pre> \pseudoSmallcapped {...} * TEXT </pre>

<p><code>\pseudosmallcapped {...}</code></p> <p>* TEXT</p>
<p><code>\purenumber {...}</code></p> <p>* NUMMER</p>
<p><code>\pusharrangedpages ... \poparrangedpages</code></p>
<p><code>\pushattribute *..</code></p> <p>* CSNAME</p>
<p><code>\pushbar [...] ... \popbar</code></p> <p>* NAME</p>
<p><code>\pushbarva [...] ... \popbarva</code></p> <p>* COLOR</p>
<p><code>\pushbutton [¹...] [²...]</code></p> <p>1 NAME</p> <p>2 REFERENCE</p>
<p><code>\pushcatcodetable ... \popcatcodetable</code></p>
<p><code>\pushendoffline ... \popendoffline</code></p>
<p><code>\pushindentation ... \popindentation</code></p>
<p><code>\pushMPdrawing ... \popMPdrawing</code></p>
<p><code>\pushmacro *..</code></p> <p>* CSNAME</p>
<p><code>\pushmathstyle ... \popmathstyle</code></p>
<p><code>\pushmode [...]</code></p> <p>* NAME</p>
<p><code>\pushoutputstream [...]</code></p> <p>* NAME OPT</p>
<p><code>\pushpath [...] ... \poppath</code></p> <p>* PATH</p>
<p><code>\pushpozadi [...] ... \poppozadi</code></p> <p>* NAME</p>
<p><code>\pushpunctuation ... \poppunctuation</code></p>
<p><code>\pushrandomseed ... \poprandomseed</code></p>
<p><code>\pushreferenceprefix {...} ... \popreferenceprefix</code></p> <p>* + - TEXT</p>
<p><code>\pushsystemmode {...}</code></p> <p>* NAME</p>

<p><code>\putboxincache {¹...} {²...} ³...</code></p> <p>1 NAME 2 NUMMER TEXT 3 CSNAME NUMMER</p>
<p><code>\putnextboxincache {¹...} {²...} \³... {⁴...}</code></p> <p>1 NAME 2 NUMMER TEXT 3 CSNAME 4 CONTENT</p>
<p><code>\qqquad</code></p>
<p><code>\quad</code></p>
<p><code>\quads [...]</code></p> <p>* NUMMER <small>OPT</small></p>
<p><code>\quarterstrut</code></p>
<p><code>\quitcommalist</code></p>
<p><code>\quitprevcommalist</code></p>
<p><code>\quittypescriptscanning</code></p>
<p><code>\ReadFile {¹...}</code></p> <p>* FILE</p>
<p><code>\Rimskecislice {¹...}</code></p> <p>* NUMMER</p>
<p><code>\radek {¹...}</code></p> <p>* CONTENT</p>
<p><code>\raggedbottom</code></p>
<p><code>\raggedcenter</code></p>
<p><code>\raggedleft</code></p>
<p><code>\raggedright</code></p>
<p><code>\raggedwidecenter</code></p>
<p><code>\raisebox {¹...} \²... {³...}</code></p> <p>1 DIMENSION 2 CSNAME 3 CONTENT</p>
<p><code>\randomizetext {¹...}</code></p> <p>* TEXT</p>
<p><code>\randomnumber {¹...} {²...}</code></p> <p>1 NUMMER 2 NUMMER</p>

<pre> \rawcounter [...]¹ [...]² 1 NAME OPT 2 NUMMER </pre>
<pre> \rawcountervalue [...] * NAME </pre>
<pre> \rawdate [...,*...] * inherits: \aktualnidatum </pre>
<pre> \rawdoifelseinset {...}¹ {...,²...} {...}³ {...}⁴ 1 TEXT 2 TEXT 3 TRUE 4 FALSE </pre>
<pre> \rawdoifinset {...}¹ {...,²...} {...}³ 1 TEXT 2 TEXT 3 TRUE </pre>
<pre> \rawdoifinsetelse {...}¹ {...,²...} {...}³ {...}⁴ 1 TEXT 2 TEXT 3 TRUE 4 FALSE </pre>
<pre> \rawgetparameters [...]¹ [...,²...,...] 1 TEXT 2 KEY = VALUE </pre>
<pre> \rawprocessaction [...]¹ [...,²...=>...,...] 1 BEFEHL 2 APPLY </pre>
<pre> \rawprocesscommacommand [...]¹,... \²... 1 BEFEHL 2 CSNAME </pre>
<pre> \rawprocesscommalist [...]¹,... \²... 1 BEFEHL 2 CSNAME </pre>
<pre> \rawstructurelistuservariable {...} * KEY </pre>
<pre> \rawsubcountervalue [...]¹ [...]² 1 NAME 2 NUMMER </pre>
<pre> \rbox ...¹ {...}² 1 TEXT^{OPT} 2 CONTENT </pre>
<pre> \readfile {...}¹ {...}² {...}³ 1 FILE 2 TRUE 3 FALSE </pre>

<pre> \readfixfile {...} {...} {...} {...} 1 PATH 2 FILE 3 TRUE 4 FALSE </pre>
<pre> \readjobfile {...} {...} {...} 1 FILE 2 TRUE 3 FALSE </pre>
<pre> \readlocfile {...} {...} {...} 1 FILE 2 TRUE 3 FALSE </pre>
<pre> \readsetfile {...} {...} {...} {...} 1 PATH 2 FILE 3 TRUE 4 FALSE </pre>
<pre> \readsysfile {...} {...} {...} 1 FILE 2 TRUE 3 FALSE </pre>
<pre> \readtexfile {...} {...} {...} 1 FILE 2 TRUE 3 FALSE </pre>
<pre> \readxmlfile {...} {...} {...} 1 FILE 2 TRUE 3 FALSE </pre>
<pre> \realpagenumber </pre>
<pre> \realSmallCapped {...} * TEXT </pre>
<pre> \realSmallcapped {...} * TEXT </pre>
<pre> \realSmallcapped {...} * TEXT </pre>
<pre> \recursedepth </pre>
<pre> \recurselevel </pre>
<pre> \recursestring </pre>
<pre> \redoconvertfont </pre>
<pre> \ref [.^.] [.^.] 1 implicitni text titul cislo stranka realpage 2 REFERENCE </pre>

<code>\REFERENCEFORMAT {...} {...} [...]</code> 1 TEXT OPT OPT 2 TEXT 3 REFERENCE
<code>\referenceprefix</code>
<code>\registerattachment [...][...²...]</code> 1 NAME 2 inherits: \setupattachment
<code>\registercxtluafile {...} {...}</code> 1 FILE 2 NUMMER
<code>\registerexternalfigure [...][...²][...³...]</code> 1 FILE OPT OPT 2 NAME 3 inherits: \setupexternalfigure
<code>\registerfontclass {...}</code> * NAME
<code>\registerhyphenationexception [...][...²]</code> 1 SPRACHE OPT 2 TEXT
<code>\registerhyphenationpattern [...][...²]</code> 1 SPRACHE OPT 2 TEXT
<code>\registermenubuttons [...][...²]</code> 1 NAME 2 TEXT
<code>\registersort [...][...²]</code> 1 SINGULAR 2 NAME
<code>\registersynonym [...][...²]</code> 1 SINGULAR 2 NAME
<code>\registerunit [...][...²...]</code> 1 prefix jednotka ^{OPT} operator suffixe symbol packaged 2 KEY = VALUE
<code>\REGISTER [...][...²...]</code> 1 TEXT PROCESSOR->TEXT 2 INDEX instances: index
<code>\index [...][...²...]</code> 1 TEXT PROCESSOR->TEXT 2 INDEX
<code>\REGISTER [...][...²][...³...]</code> 1 TEXT PROCESSOR->TEXT 2 TEXT 3 INDEX instances: index

<code>\index [...]¹ {...}² [...+...+...]</code> 1 TEXT PR <small>OC</small> ESSOR->TEXT 2 TEXT 3 INDEX
<code>\relatemarking [...]¹ [...]²</code> 1 BESCHRIFTUNG 2 BESCHRIFTUNG
<code>\relateparameterhandlers {...}¹ {...}² {...}³ {...}⁴</code> 1 NAME 2 NAME 3 NAME 4 NAME
<code>\relaxvalueifundefined {...}[*]</code> * NAME
<code>\remainingcharacters</code>
<code>\removebottomthings</code>
<code>\removedepth</code>
<code>\removefromcommalist {...}¹ \...²</code> 1 TEXT 2 CSNAME
<code>\removelastskip</code>
<code>\removelastspace</code>
<code>\removemarkedcontent [...][*]</code> * NAME
<code>\removepunctuation</code>
<code>\removesubstring ...¹ \from ...² \to ...³</code> 1 TEXT 2 TEXT 3 CSNAME
<code>\removetoks ...¹ \from \...²</code> 1 BEFEHL 2 CSNAME
<code>\removeunwantedspaces</code>
<code>\replacefeature [...][*]</code> * NAME
<code>\replacefeature {...}[*]</code> * NAME
<code>\replaceincommalist \...¹ {...}²</code> 1 CSNAME 2 NUMMER

<pre> \replaceword [...] [...] [...] 1 NAME 2 TEXT 3 TEXT </pre>
<pre> \rescan {...} * CONTENT </pre>
<pre> \rescanwithsetup {...} {...} 1 NAME 2 CONTENT </pre>
<pre> \resetallattributes </pre>
<pre> \resetandaddfeature [...] * NAME </pre>
<pre> \resetandaddfeature {...} * NAME </pre>
<pre> \resetbar </pre>
<pre> \resetboxesincache {...} * NAME </pre>
<pre> \resetbreakpoints </pre>
<pre> \resetbuffer [...] * BUFFER </pre>
<pre> \resetcollector [...] * NAME </pre>
<pre> \resetcounter [...] [...] 1 NAME OPT 2 NUMMER </pre>
<pre> \resetdigitsmanipulation </pre>
<pre> \resetdirection </pre>
<pre> \resetfeature </pre>
<pre> \resetflag {...} * NAME </pre>
<pre> \resetfontcolorsheme </pre>
<pre> \resetfontfallback [...] [...] 1 NAME OPT 2 FONT </pre>
<pre> \resetfontsolution </pre>
<pre> \resethyphenationfeatures </pre>
<pre> \resetcharacteralign </pre>

\resetsetups [...] * NAME
\resetshownsynonyms [...] * SINGULAR
\resetsubpagenumber
\resetsymbolset
\resetsystemmode {...} * NAME
\resettimer
\resettrackers
\resettrialtypesetting
\resetusedsortings [...] * SINGULAR
\resetusedsynonyms [...] * SINGULAR
\resetuserpagenumber
\resetvalue {...} * NAME
\resetvisualizers
\resetznaceni [...] * BESCHRIFTUNG
\reshapebox {...} * BEFEHL
\resolvedglyphdirect {...} {...} 1 FONT 2 e:NAME x:NUMMER d:NUMMER s:NUMMER i:NUMMER n:NAME c:NAME u:NAME a:NAME
\resolvedglyphstyled {...} {...} 1 FONT 2 e:NAME x:NUMMER d:NUMMER s:NUMMER i:NUMMER n:NAME c:NAME u:NAME a:NAME
\restartcounter [...] [. ²] [...] 1 NAME 2 NUMMER 3 NUMMER
\restorebox {...} {...} 1 NAME 2 NAME
\restorecatcodes

<code>\restorecounter [...]</code> * NAME
<code>\restorecurrentattributes {...}</code> * NAME
<code>\restoreendofline</code>
<code>\restoreglobalbodyfont</code>
<code>\reusableMPgraphic {...} {...²...}</code> 1 NAME 2 KEY = VALUE <small>OPT</small>
<code>\reuseMPgraphic {...} {...²...}</code> 1 NAME 2 KEY = VALUE <small>OPT</small>
<code>\reuserandomseed</code>
<code>\revivefeature</code>
<code>\rfence {...}</code> * CHARACTER
<code>\rhbox {...}</code> * CONTENT
<code>\rightbottombox {...}</code> * CONTENT
<code>\rightbox {...}</code> * CONTENT
<code>\righthbox {...}</code> * CONTENT
<code>\rightLABELtext {...}</code> * KEY instances: head label mathlabel
<code>\rightheadtext {...}</code> * KEY
<code>\rightlabeltext {...}</code> * KEY
<code>\rightmathlabeltext {...}</code> * KEY
<code>\rightline {...}</code> * CONTENT
<code>\rightorleftpageaction {...} {...²}</code> 1 BEFEHL 2 BEFEHL

<code>\rightskipadaption</code>
<code>\rightsubguillemot</code>
<code>\righttopleft</code>
<code>\righttopleftthbox</code> ¹ ... { ² ...} 1 TEXT <small>OPT</small> 2 CONTENT
<code>\righttopleftvbox</code> ¹ ... { ² ...} 1 TEXT <small>OPT</small> 2 CONTENT
<code>\righttopleftvtop</code> ¹ ... { ² ...} 1 TEXT <small>OPT</small> 2 CONTENT
<code>\righttopbox</code> { [*] ...} * CONTENT
<code>\rimskedislice</code> { [*] ...} * NUMBER
<code>\ring</code> { [*] ...} * CHARACTER
<code>\rlap</code> { [*] ...} * CONTENT
<code>\robustaddtocommalist</code> { ¹ ...} \ ² ... 1 TEXT 2 CSNAME
<code>\robustdoifelseinset</code> { ¹ ...} { ² ...,...} { ³ ...} { ⁴ ...} 1 TEXT 2 TEXT 3 TRUE 4 FALSE
<code>\robustdoifinsetelse</code> { ¹ ...} { ² ...,...} { ³ ...} { ⁴ ...} 1 TEXT 2 TEXT 3 TRUE 4 FALSE
<code>\robustpretocommalist</code> { ¹ ...} \ ² ... 1 TEXT 2 CSNAME
<code>\rollbutton</code> [..., ¹ ...,...] ² ... [³ ...] 1 inherits: \setupbutton 2 TEXT 3 REFERENCE
<code>\rollbutton</code> [¹ ...] [..., ² ...,...] ³ ... [⁴ ...] 1 NAME <small>OPT</small> <small>OPT</small> 2 inherits: \nastavinterakcnimenu 3 TEXT 4 REFERENCE

<code>\rovnice [...¹,...] {...²}</code> 1 zhustene tight ^{OPT} nastred ramecek podlehloubky radek pulradku -radek -pulradku inherits: \nastavzakladnifont 2 CONTENT
<code>\rozdelplovouciobjekt [...¹,...¹,...] {...²} {...³}</code> 1 inherits: \nastavdeleniplvouci ^{OPT} chobjektu 2 BEFEHL 3 CONTENT
<code>\roztazene [...¹,...¹,...] {...²}</code> 1 inherits: \setupst ^{OPT} retched 2 TEXT
<code>\rtop ...¹ {...²}</code> 1 TEXT ^{OPT} 2 CONTENT
<code>\rukopisne</code>
<code>\ruledhbox ...¹ {...²}</code> 1 TEXT ^{OPT} 2 CONTENT
<code>\ruledhpack ...¹ {...²}</code> 1 TEXT ^{OPT} 2 CONTENT
<code>\ruledmbox {...}</code> * CONTENT
<code>\ruledtopv ...¹ {...²}</code> 1 TEXT ^{OPT} 2 CONTENT
<code>\ruledtpack ...¹ {...²}</code> 1 TEXT ^{OPT} 2 CONTENT
<code>\ruledvbox ...¹ {...²}</code> 1 TEXT ^{OPT} 2 CONTENT
<code>\ruledvpack ...¹ {...²}</code> 1 TEXT ^{OPT} 2 CONTENT
<code>\ruledvtop ...¹ {...²}</code> 1 TEXT ^{OPT} 2 CONTENT
<code>\runMPbuffer [...[*],...^{OPT}]</code> * NAME
<code>\runninghbox {...}</code> * CONTENT
<code>\ScaledPointsToBigPoints {...¹} \...²</code> 1 DIMENSION 2 CSNAME

\ScaledPointsToWholeBigPoints {...} \ ² .. 1 DIMENSION 2 CSNAME
\SLOVA {...} * TEXT
\SLOVO {...} * TEXT
\Slova {...} * TEXT
\Slovo {...} * TEXT
\Smallcapped {...} * TEXT
\safechar {...} * NUMMER
\samplefile {...} * FILE
\sans
\sansnormal
\sanstucne
\savebarva ... \restorebarva
\savebox {...} {...} {...} 1 NAME 2 NAME 3 CONTENT
\savebtxdataset [...] ¹ [...] ² [...,...] ³ .. 1 NAME OPT OPT OPT 2 FILE 3 dataset = NAME typ = bib lua xml soubor = FILE kritérium = vse text uvod odkaz aktualni zde predchozi lokalne komponenta SECTIONBLOCK:vse SECTIONBLOCK:odkaz SECTIONBLOCK:aktualni SECTIONBLOCK:predchozi
\savebuffer [...,...] [*] .. * seznam = NAME soubor = FILE prefix = ano ne
\savebuffer [...] ¹ .. 1 BUFFER 2 FILE
\savecounter [...] * NAME

\savecurrentattributes {...} * NAME
\savenormalmeaning *... * CSNAME
\savetaggedtwopassdata {...} {...} {...} {...} 1 NAME 2 NUMMER 3 NAME 4 CONTENT
\savetwopassdata {...} {...} {...} 1 NAME 2 NUMMER 3 CONTENT
\sbox {...} * CONTENT
\SCRIPT instances: hangul hanzi nihongo ethiopic thai latin test
\ethiopic
\hangul
\hanzi
\latin
\nihongo
\test
\thai
\secondoffivearguments {...} {...} {...} {...} {...} 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT
\secondoffourarguments {...} {...} {...} {...} 1 TEXT 2 TEXT 3 TEXT 4 TEXT
\secondofsixarguments {...} {...} {...} {...} {...} {...} 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT

`\secondofthreearguments {...} {...} {...}`

1 TEXT
2 TEXT
3 TEXT

`\secondofthreeunexpanded {...} {...} {...}`

1 TEXT
2 TEXT
3 TEXT

`\secondoftwoarguments {...} {...}`

1 TEXT
2 TEXT

`\secondoftwounexpanded {...} {...}`

1 TEXT
2 TEXT

`\sedabarva [...] {...}`

1 COLOR
2 CONTENT

`\vizREGISTER [...] [...+.+.+] {...}`

1 TEXT PROCESSOR-^{OPT}TEXT
2 INDEX
3 TEXT PROCESSOR->TEXT

instances: index

`\vizindex [...] [...+.+.+] {...}`

1 TEXT PROCESSOR->TEXT
2 INDEX
3 TEXT PROCESSOR->TEXT

`\SECTION [...,1...] {...2}`

1 REFERENCE ^{OPT}
2 TEXT

instances: part chapter section subsection subsubsection subsubsubsection subsubsubsubsection
title subject subsubject subsubsubject subsubsubsubject subsubsubsubsubject

`\SECTION [...,*...] [...,*...]`

* titul = TEXT
zalozka = TEXT
znaceni = TEXT
seznam = TEXT
odkaz = REFERENCE
vlastnicislo = TEXT

instances: part chapter section subsection subsubsection subsubsubsection subsubsubsubsection
title subject subsubject subsubsubject subsubsubsubject subsubsubsubsubject

`\chapter [...,*...] [...,*...]`

* titul = TEXT
zalozka = TEXT
znaceni = TEXT
seznam = TEXT
odkaz = REFERENCE
vlastnicislo = TEXT

`\part [...,*...] [...,*...]`

* titul = TEXT
zalozka = TEXT
znaceni = TEXT
seznam = TEXT
odkaz = REFERENCE
vlastnicislo = TEXT

```
\section [...,.*,..., ...]
*   titul           = TEXT
    zalozka         = TEXT
    znaceni          = TEXT
    seznam           = TEXT
    odkaz            = REFERENCE
    vlastnicislo     = TEXT
```

```
\subject [...,.*,..., ...]
*   titul           = TEXT
    zalozka         = TEXT
    znaceni          = TEXT
    seznam           = TEXT
    odkaz            = REFERENCE
    vlastnicislo     = TEXT
```

```
\subsection [...,.*,..., ...]
*   titul           = TEXT
    zalozka         = TEXT
    znaceni          = TEXT
    seznam           = TEXT
    odkaz            = REFERENCE
    vlastnicislo     = TEXT
```

```
\subsubject [...,.*,..., ...]
*   titul           = TEXT
    zalozka         = TEXT
    znaceni          = TEXT
    seznam           = TEXT
    odkaz            = REFERENCE
    vlastnicislo     = TEXT
```

```
\subsubsection [...,.*,..., ...]
*   titul           = TEXT
    zalozka         = TEXT
    znaceni          = TEXT
    seznam           = TEXT
    odkaz            = REFERENCE
    vlastnicislo     = TEXT
```

```
\subsubsubject [...,.*,..., ...]
*   titul           = TEXT
    zalozka         = TEXT
    znaceni          = TEXT
    seznam           = TEXT
    odkaz            = REFERENCE
    vlastnicislo     = TEXT
```

```
\subsubsubsection [...,.*,..., ...]
*   titul           = TEXT
    zalozka         = TEXT
    znaceni          = TEXT
    seznam           = TEXT
    odkaz            = REFERENCE
    vlastnicislo     = TEXT
```

```
\subsubsubsubject [...,.*,..., ...]
*   titul           = TEXT
    zalozka         = TEXT
    znaceni          = TEXT
    seznam           = TEXT
    odkaz            = REFERENCE
    vlastnicislo     = TEXT
```

`\subsubsubsubsection [...,.*,...]`

* titul = TEXT
 zalozka = TEXT
 znaceni = TEXT
 seznam = TEXT
 odkaz = REFERENCE
 vlastnicislo = TEXT

`\subsubsubsubsubject [...,.*,...]`

* titul = TEXT
 zalozka = TEXT
 znaceni = TEXT
 seznam = TEXT
 odkaz = REFERENCE
 vlastnicislo = TEXT

`\title [...,.*,...]`

* titul = TEXT
 zalozka = TEXT
 znaceni = TEXT
 seznam = TEXT
 odkaz = REFERENCE
 vlastnicislo = TEXT

`\chapter [...,1,...] {..2.}`

1 REFERENCE ^{OPT}
2 TEXT

`\SECTION [...,1,...] {..2.} {..3.}`

1 REFERENCE ^{OPT}
2 NUMMER
3 TEXT

instances: part chapter section subsection subsubsection subsubsubsection subsubsubsubsection
title subject subsubject subsubsubject subsubsubsubject subsubsubsubsubject

`\chapter [...,1,...] {..2.} {..3.}`

1 REFERENCE ^{OPT}
2 NUMMER
3 TEXT

`\part [...,1,...] {..2.} {..3.}`

1 REFERENCE^{OPT}
2 NUMMER
3 TEXT

`\section [...,1,...] {..2.} {..3.}`

1 REFERENCE ^{OPT}
2 NUMMER
3 TEXT

`\subject [...,1,...] {..2.} {..3.}`

1 REFERENCE ^{OPT}
2 NUMMER
3 TEXT

`\subsection [...,1,...] {..2.} {..3.}`

1 REFERENCE ^{OPT}
2 NUMMER
3 TEXT

`\subsubject [...,1,...] {..2.} {..3.}`

1 REFERENCE ^{OPT}
2 NUMMER
3 TEXT

$\backslash\text{subsubsection} [\dots, \dots] \{\dots\} \{\dots\}$ 1 REFERENCE OPT 2 NUMMER 3 TEXT
$\backslash\text{subsubsubject} [\dots, \dots] \{\dots\} \{\dots\}$ 1 REFERENCE OPT 2 NUMMER 3 TEXT
$\backslash\text{subsubsubsection} [\dots, \dots] \{\dots\} \{\dots\}$ 1 REFERENCE OPT 2 NUMMER 3 TEXT
$\backslash\text{subsubsubsubject} [\dots, \dots] \{\dots\} \{\dots\}$ 1 REFERENCE OPT 2 NUMMER 3 TEXT
$\backslash\text{subsubsubsubsection} [\dots, \dots] \{\dots\} \{\dots\}$ 1 REFERENCE OPT 2 NUMMER 3 TEXT
$\backslash\text{subsubsubsubsubject} [\dots, \dots] \{\dots\} \{\dots\}$ 1 REFERENCE OPT 2 NUMMER 3 TEXT
$\backslash\text{title} [\dots, \dots] \{\dots\} \{\dots\}$ 1 REFERENCE OPT 2 NUMMER 3 TEXT
$\backslash\text{part} [\dots, \dots] \{\dots\}$ 1 REFERENCE ^{PT} 2 TEXT
$\backslash\text{section} [\dots, \dots] \{\dots\}$ 1 REFERENCE OPT 2 TEXT
$\backslash\text{subject} [\dots, \dots] \{\dots\}$ 1 REFERENCE OPT 2 TEXT
$\backslash\text{subsection} [\dots, \dots] \{\dots\}$ 1 REFERENCE OPT 2 TEXT
$\backslash\text{subsubject} [\dots, \dots] \{\dots\}$ 1 REFERENCE OPT 2 TEXT
$\backslash\text{subsubsection} [\dots, \dots] \{\dots\}$ 1 REFERENCE OPT 2 TEXT
$\backslash\text{subsubsubject} [\dots, \dots] \{\dots\}$ 1 REFERENCE OPT 2 TEXT

<code>\subsubsection [...,¹...] {...²}</code> 1 REFERENCE OPT 2 TEXT
<code>\subsubsubject [...,¹...] {...²}</code> 1 REFERENCE OPT 2 TEXT
<code>\subsubsubsection [...,¹...] {...²}</code> 1 REFERENCE OPT 2 TEXT
<code>\subsubsubsubject [...,¹...] {...²}</code> 1 REFERENCE OPT 2 TEXT
<code>\title [...,¹...] {...²}</code> 1 REFERENCE OPT 2 TEXT
<code>\select {...¹} {...²} {...³} {...⁴} {...⁵} {...⁶}</code> 1 NAME OPT OPT OPT OPT OPT 2 CONTENT 3 CONTENT 4 CONTENT 5 CONTENT 6 CONTENT
<code>\serializecommalist [...,*...]</code> * BEFEHL
<code>\serializedcommalist</code>
<code>\serif</code>
<code>\serifbold</code>
<code>\serifnormal</code>
<code>\setbar [...]</code> * NAME
<code>\setbigbodyfont</code>
<code>\setboxllx ...¹ {...²}</code> 1 CSNAME NUMMER 2 DIMENSION
<code>\setboxlly ...¹ {...²}</code> 1 CSNAME NUMMER 2 DIMENSION
<code>\setbreakpoints [...]</code> * reset NAME
<code>\setbuffer [...] ... \endbuffer</code> * NAME
<code>\setcapstrut</code>

<pre> \setcatcodetable *... * CSNAME </pre>
<pre> \setcollector [...]¹ [...,...²...,...]² {...}³ 1 NAME OPT 2 inherits: \setupcollector 3 CONTENT </pre>
<pre> \setcolormodel [...]¹ * black bw seda rgb cmyk vse zadny </pre>
<pre> \setcounter [...]¹ [...]² [...]³ 1 NAME OPT 2 NUMMER 3 NUMMER </pre>
<pre> \setcounterown [...]¹ [...]² [...]³ 1 NAME OPT 2 NUMMER 3 TEXT </pre>
<pre> \setcurrentfontclass {...} * NAME </pre>
<pre> \setdataset [...]¹ [...]² [...,...³...,...]³ 1 NAME OPT 2 NAME 3 KEY = VALUE </pre>
<pre> \setdefaultpenalties </pre>
<pre> \setdigitsmanipulation [...]¹ * reset NUMMER </pre>
<pre> \setdirection [...]¹ * NUMMER </pre>
<pre> \setdocumentargument {...}¹ {...}² 1 NAME 2 TEXT </pre>
<pre> \setdocumentargumentdefault {...}¹ {...}² 1 NAME 2 TEXT </pre>
<pre> \setdocumentfilename {...}¹ {...}² 1 NUMMER 2 TEXT </pre>
<pre> \setdummyparameter {...}¹ {...}² 1 KEY 2 BEFEHL </pre>
<pre> \setelementexporttag [...]¹ [...]² [...]³ 1 NAME OPT 2 export nature pdf 3 inline obrazovka mixed </pre>
<pre> \setemeasure {...}¹ {...}² 1 NAME 2 DIMENSION </pre>

`\setevalue {...} {...}`

1 NAME
2 CONTENT

`\setevariable {...} {...} {...}`

1 NAME
2 KEY
3 VALUE

`\setevariables [...]1 [...,2...,...]`

1 NAME
2 set = BEFEHL
reset = BEFEHL
KEY = VALUE

`\setfirstline [...]`

* NAME OPT

`\setflag {...}`

* NAME

`\setfont ...`

* FONT

`\setfontcolorsheme [...]`

* NAME

`\setfontfeature {...}`

* NAME

`\setfontsolution [...]`

* NAME

`\setfontstrut`

`\setgmeasure {...} {...}`

1 NAME
2 DIMENSION

`\setgvalue {...} {...}`

1 NAME
2 CONTENT

`\setgvariable {...} {...} {...}`

1 NAME
2 KEY
3 VALUE

`\setgvariables [...]1 [...,2...,...]`

1 NAME
2 set = BEFEHL
reset = BEFEHL
KEY = VALUE

`\sethboxregister ...1 {...}`

1 CSNAME NUMBER
2 CONTENT

`\sethyphenatedurlafter {...}`

* TEXT

<pre> \sethyphenatedurlbefore {...} * TEXT </pre>
<pre> \sethyphenatedurlnormal {...} * TEXT </pre>
<pre> \sethyphenationfeatures [...,*,...] * NAME reset OPT </pre>
<pre> \setcharacteralign {...} {...} 1 NUMMER 2 TEXT number->TEXT text->TEXT </pre>
<pre> \setcharactercasing [...] * reset SLOVO slovo Slovo Slova kapitalky Kapitalky zadny nahodny mixed camel kap Kap </pre>
<pre> \setcharactercleaning [...] * reset 1 </pre>
<pre> \setcharacterkerning [...] * reset NAME </pre>
<pre> \setcharacterspacing [...] * reset NAME </pre>
<pre> \setcharacterstripping [...] * reset 1 </pre>
<pre> \setcharstrut {...} * TEXT </pre>
<pre> \setinitial [...¹] [...,²...,...³] 1 NAME OPT OPT 2 inherits: \setupinitial </pre>
<pre> \setinjector [...¹] [...,²...,...³] 1 NAME 2 NUMMER 3 BEFEHL </pre>
<pre> \setinteraction [...] * skryte NAME </pre>
<pre> \setinterfacecommand {...} {...} 1 NAME 2 NAME </pre>
<pre> \setinterfaceconstant {...} {...} 1 NAME 2 NAME </pre>
<pre> \setinterfaceelement {...} {...} 1 NAME 2 NAME </pre>
<pre> \setinterfacemessage {...} {...} {...} 1 NAME 2 titul NAME NUMMER 3 TEXT </pre>

1	NAME
2	NAME

```

1  NAME
2  auto embed
3  CONTENT

```

```
* reset 1 2
```

```

1  NAME
2  CONTENT

```

```

1  NAME                                OPT
2  vlevo vpravo sude liche
3  inherits: \setupplayer
4  CONTENT

```

```
1  NAME
2  inherits: \setupplayer
3  inherits: \nastavoramovani
4  CONTENT
```

```

1  NAME                                OPT
2  inherits: \setupplayerinherits: \nastavoramovani
3  CONTENT

```

```

1  NAME                                     OPT
2  inherits: \setupplayer
3  zarovnnani = inherits: \nastavzarovnnani
   sirka      = DIMENSION
   pismo      = STYLE BEFEHL
   barva      = COLOR
4  TEXT

```

```
*  filler NAME
```

* [-+] DIMENSION OPT

```
1  NAME
2  NAME
3  inherits: \setupplayer
4  CONTENT
```

```

1  NAME
2  NAME
3  KEY  =  VALUE

```

```

1  NAME
2  NAME
3  NAME
4  KEY  =  VALUE

```

$\backslash\text{setMPtext}$ $\{.^1.\}$ $\{.^2.\}$ 1 NAME 2 TEXT
$\backslash\text{setMPvariable}$ $[.^1.]$ $[.^2..]$ 1 NAME 2 KEY = VALUE
$\backslash\text{setMPvariables}$ $[.^1.]$ $[.^2..]$ $[.^3..]$ 1 NAME <small>OPT</small> 2 KEY = VALUE
$\backslash\text{setmainbodyfont}$
$\backslash\text{setmainparbuilder}$ $[.^*.]$ * implicitni oneline basic NAME
$\backslash\text{setmarker}$ $[.^1.]$ $[.^2.]$ 1 NAME 2 NUMMER
$\backslash\text{setmarking}$ $[.^1.]$ $\{.^2.\}$ 1 BESCHRIFTUNG 2 TEXT
$\backslash\text{setmathstyle}$ $\{.^*.,.^*\}$ * obrazovka text script scriptscript cramped uncramped normalni zhustene male velke NAME
$\backslash\text{setmeasure}$ $\{.^1.\}$ $\{.^2.\}$ 1 NAME 2 DIMENSION
$\backslash\text{setmessagetext}$ $\{.^1.\}$ $\{.^2.\}$ 1 NAME 2 NAME NUMMER
$\backslash\text{setmode}$ $\{.^*.\}$ * NAME
$\backslash\text{setnostrut}$
$\backslash\text{setnote}$ $[.^1.]$ $[.^2..]$ $\{.^3.\}$ 1 NAME <small>OPT</small> 2 REFERENCE 3 TEXT
$\backslash\text{setnotetext}$ $[.^1.]$ $[.^2..]$ $\{.^3.\}$ 1 NAME <small>OPT</small> 2 REFERENCE 3 TEXT
$\backslash\text{setnotetext}$ $[.^1.]$ $[.^2..]$ $[.^3..]$ 1 NAME 2 titul = TEXT zalozka = TEXT seznam = TEXT odkaz = REFERENCE

\setnote [¹.] [²...,...]

1 NAME
2 titul = TEXT
zalozka = TEXT
seznam = TEXT
odkaz = REFERENCE

\setobject {¹...} {²...} \³... {⁴...}

1 NAME
2 NAME
3 CSNAME
4 CONTENT

\setoldstyle

\setpagegrid [...,...¹...,...] {²...}

1 c = NUMMER ^{OPT}
r = NUMMER
volba = zadny
2 CONTENT

\setpagereference {¹...} {²...,...}

1 NAME
2 REFERENCE

\setpagestate [¹.] [²...]

1 NAME ^{OPT}
2 NAME NUMMER

\setpagestaterealpageno {¹...} {²...}

1 NAME
2 NAME NUMMER

\setpenalties \¹... {²...} {³...}

1 CSNAME
2 NUMMER
3 NUMMER

\setpercentdimen {¹...} {²...}

1 DIMENSION CSNAME
2 DIMENSION NUMMER

\setposition {^{*}...}

* NAME

\setpositionbox {¹...} \²... {³...}

1 NAME
2 CSNAME
3 CONTENT

\setpositiondata {¹...} {²...} {³...} {⁴...}

1 NAME
2 DIMENSION
3 DIMENSION
4 DIMENSION

\setpositiondataplus {¹...} {²...} {³...} {⁴...} {⁵...,...}

1 NAME
2 DIMENSION
3 DIMENSION
4 DIMENSION
5 TEXT

\setpositiononly {...} * NAME
\setpositionplus {... ¹ } {... ² ,...} \... {... ⁴ } 1 NAME 2 TEXT 3 CSNAME 4 CONTENT
\setpositionstrut {...} * NAME
\setprofile [...] * zadny fixne striktni halffixed quarterfixed eightsfixed NAME
\setrandomseed {...} * NUMMER
\setreference [... ¹ ,...] [... ² ,...] 1 REFERENCE 2 KEY = VALUE
\setreferencedobject {... ¹ } {... ² } \... {... ⁴ } 1 NAME 2 NAME 3 CSNAME 4 CONTENT
\setregisterentry [... ¹] [... ² ,... ³ ,...] [... ³ ,... ³ ,...] OPT 1 NAME 2 popisek = NAME keys = TEXT PROCESSOR->TEXT entries = TEXT PROCESSOR->TEXT keys:1 = TEXT keys:2 = TEXT keys:3 = TEXT entries:1 = TEXT entries:2 = TEXT entries:3 = TEXT alternativa = TEXT 3 KEY = VALUE
\setreplacement [...] * reset NAME
\setrigidcolumnbalance ... * CSNAME NUMMER
\setrigidcolumnhsize {... ¹ } {... ² } {... ³ } 1 DIMENSION 2 DIMENSION 3 NUMMER
\setscript [...] * hangul hanzi nihongo ethiopic thai test NAME
\setsectionblock [... ¹] [... ² ,... ³ ,...] OPT 1 NAME 2 zalozka = TEXT

<pre> \setsimplecolumnhsize [...,*...,...] * n = NUMBER sirka = DIMENSION vzdalenost = DIMENSION radky = NUMBER </pre>
<pre> \setsmallbodyfont </pre>
<pre> \setsmallcaps </pre>
<pre> \setstackbox {¹.} {².} {³.} 1 NAME 2 NAME 3 CONTENT </pre>
<pre> \setstructurepageregister [...¹.] [...,²...,...] [...,³...,...] 1 NAME 2 popisek = NAME keys = TEXT PROCESSOR->TEXT entries = TEXT PROCESSOR->TEXT keys:1 = TEXT keys:2 = TEXT keys:3 = TEXT entries:1 = TEXT entries:2 = TEXT entries:3 = TEXT alternativa = TEXT 3 KEY = VALUE </pre>
<pre> \setstrut </pre>
<pre> \setsuperiors </pre>
<pre> \setsystemmode {.*} * NAME </pre>
<pre> \settabular </pre>
<pre> \settaggedmetadata [...,*...,...] * KEY = VALUE </pre>
<pre> \settextcontent [...¹.] [...².] [...³.] [...⁴.] [...⁵.] 1 vrsek zahlavi text upati spodek OPT OPT 2 text marginalie hrana 3 vlevo nastred vpravo 4 datum cislostranky BESCHRIFTUNG TEXT BEFEHL 5 datum cislostranky BESCHRIFTUNG TEXT BEFEHL </pre>
<pre> \settightobject {¹.} {².} \³. {⁴.} 1 NAME 2 NAME 3 CSNAME 4 CONTENT </pre>
<pre> \settightreferencedobject {¹.} {².} \³. {⁴.} 1 NAME 2 NAME 3 CSNAME 4 CONTENT </pre>
<pre> \settightunreferencedobject {¹.} {².} \³. {⁴.} 1 NAME 2 NAME 3 CSNAME 4 CONTENT </pre>

\settrialtypesetting	
\setuevalue {...} {...} 1 NAME 2 CONTENT	
\setugvalue {...} {...} 1 NAME 2 CONTENT	
\setunreferencedobject {...} {...} \^3... {...} 1 NAME 2 NAME 3 CSNAME 4 CONTENT	
\setupalternativestyles [...,...*...,...] * metoda = normalni auto	
\setupattachment [...,...^1,...] [...,...^2,...,...] 1 NAME OPT 2 titul = TEXT podtitulek = TEXT autor = TEXT soubor = FILE jmeno = NAME buffer = BUFFER status = start stop metoda = normalni skryte symbol = Graph Paperclip Pushpin Default sirka = prizpusobive DIMENSION vyska = prizpusobive DIMENSION hloubka = prizpusobive DIMENSION barva = COLOR textlayer = NAME misto = levahrana pravahrana naokraji levvyokraj pravvyokraj text vysoko zadny vzdalenost = DIMENSION	
\setupattachments [...,...^1,...] [...,...^2,...,...] 1 NAME OPT 2 inherits: \setupattachment	
\setupbackend [...,...*...,...] * export = ano FILE xhtml = FILE soubor = FILE intent = Coated FOGRA39 (ISO 12647-2:2004) GRACoL2006_Coated1v2.icc ISO Coated v2 300 ISO Coated v2 (ECI) ISOnewspaper26v4 ISOnewspaper26v4_gr ISO Uncoated ISO Uncoated Yellowish ISO Web Coated Japan Color 2001 Coated Japan Color 2002 Newspaper Japan Web Coated (Ad) SNAP 2007 SWOP2006_Coated3v2.icc SWOP2006_Coated5v2.icc Uncoated FOGRA29 (ISO 12647-2:2004) Web Coated FOGRA28 (ISO 12647-2:2004) PSR_LWC_PLUS_V2_PT PSR_LWC_STD_V2_PT PSR_SC_PLUS_V2_PT PSR_SC_STD_V2_PT PSRgravureMF mezera = ano ne xmpfile = FILE formatovat = version implicitni PDF/X-1a:2001 PDF/X-1a:2003 PDF/X-3:2002 PDF/X-3:2003 PDF/X-4 PDF/X-4p PDF/X-5g PDF/X-5pg PDF/X-5n PDF/A-1a:2005 PDF/A-1b:2005 PDF/A-2a PDF/A-3a PDF/UA-1 uroven = NUMMER volba = vzdy nikdy profile = FILE	

\setupbar [¹...,²...] [¹...,²...,...]

1 NAME OPT
2 barva = COLOR
pokracovat = ano ne vse
prazdne = ano ne
jednotka = ex em pt in cm mm sp bp pc dd cc nc
order = popredi pozadi
tloustkalinky = DIMENSION
metoda = NUMMER
offset = NUMMER
dy = NUMMER
max = NUMMER
foregroundstyle = STYLE BEFEHL
foregroundcolor = COLOR
mp = NAME
vlevo = TEXT
vpravo = TEXT

\setupbars [¹...,²...] [¹...,²...,...]

1 NAME OPT
2 inherits: \setupbar

\setupbleeding [^{*}...,...]

* sirka = DIMENSION
vyska = DIMENSION
offset = DIMENSION
hoffset = DIMENSION
voffset = DIMENSION
misto = t b l r bl lb br rb tl lt tr rt
natahnout = ano ne
stranka = ano ne

\setupbookmark [^{*}...,...]

* sila = ano ne
cislo = ano ne
numberseparatorset = NAME
numberconversionset = NAME
numberstarter = BEFEHL
numberstopper = BEFEHL
numbersegments = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:* ABSCHNITT:vse
sectionblock = ano ne

\setupbtx [¹...] [²...,...]

1 NAME OPT
2 specification = implicitni apa aps NAME
dataset = implicitni NAME
prikaz = \...##1
vlevo = BEFEHL
vpravo = BEFEHL
authorconversion = normalni normalshort normalinverted invertedshort short
etallimit = NUMMER
etaldisplay = NUMMER
etaloption = posledni
predel = initials
interakce = start stop cislo text stranka vse
alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
authornum authoryear
sorttype = normalni reverse
compress = ano ne
implicitni = implicitni NAME
pismo = STYLE BEFEHL
barva = COLOR

\setupbtxdataset [¹...,²...] [¹...,²...,...]

1 NAME OPT
2 language = SPRACHE

\setupbtxlist [¹...] [²...,...]

1 NAME OPT
2 inherits: \nastavseznam

\setupbtregister [...¹,...] [...²,...]

1 NAME OPT
 2 status = start stop
 dataset = NAME
 field = keyword range cislostranky autor
 register = NAME
 metoda = once
 alternativa = normalshort invertedshort
 pismo = STYLE BEFEHL
 barva = COLOR

\setupbtxrendering [...¹,...] [...²,...]

1 NAME OPT
 2 statustextu = start stop
 pagestate = start stop
 oddelevac = BEFEHL
 kriterium = predchozi cite zde vse zadny
 filter = TEXT
 specification = NAME
 titul = TEXT
 pred = BEFEHL
 po = BEFEHL
 dataset = NAME
 metoda = dataset sila lokalne globalne zadny
 sorttype = short dataset seznam odkaz uzito implicitni cite rejstrik
 opakovat = ano ne
 group = NAME
 cislovani = ano ne num rejstrik tag short stranka

\setupbtx [...]

* NAME

\setupbutton [...¹,...] [...²,...]

1 NAME OPT
 2 status = start stop
 stejnastranka = ano ne prazdne zadny normalni implicitni
 pismo = STYLE BEFEHL
 barva = COLOR
 kontrastnibarva = COLOR
 alternativa = skryte
 inherits: \nastavoramovani

\setupcollector [...¹,...] [...²,...]

1 NAME OPT
 2 rotace = vlevo vpravo uvnitr vnejsi NUMMER
 roh = vlevo nastred vpravo vrsek spodek
 x = DIMENSION
 y = DIMENSION
 hoffset = DIMENSION
 voffset = DIMENSION
 misto = vlevo nastred vpravo vrsek spodek radek l c r m t b g
 status = start stop

\setupcolumnspan [...^{*},...]

* n = NUMMER
 inherits: \nastavoramovani

\setupcombination [...¹,...] [...²,...]

1 NAME OPT
 2 nx = NUMMER
 ny = NUMMER
 sirka = prizpusobive DIMENSION
 vyska = prizpusobive DIMENSION
 misto = vlevo nastred vpravo vrsek spodek
 vzdalenost = DIMENSION
 alternativa = popisek text
 zarovnani = inherits: \nastavzarovnani
 pokracovat = ano ne
 pred = BEFEHL
 po = BEFEHL
 mezi = BEFEHL
 pismo = STYLE BEFEHL
 barva = COLOR

\setupcounter [...,¹...] [...,²...,...]

```
1 NAME OPT
2 start = NUMBER
  counter = NAME
  metoda = stranka
  status = start stop
  zpusob = bystranka byblock bytext byhlavicka byABSCHNITT
  prefix = ano ne
  prefixseparatorset = NAME
  prefixconversion = NAME
  prefixconversionset = NAME
  prefixstarter = BEFEHL PROCESSOR->BEFEHL
  prefixstopper = BEFEHL PROCESSOR->BEFEHL
  prefixset = NAME
  prefixsegments = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:* ABSCHNITT:vse
  numberorder = reverse
  numberseparatorset = NAME
  numberconversion = NAME
  numberconversionset = NAME
  numberstarter = BEFEHL PROCESSOR->BEFEHL
  numberstopper = BEFEHL PROCESSOR->BEFEHL
  numbersegments = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:vse
  typ = prvni predchozi dalsi posledni cislo
  kriterium = striktni pozitiv vse
  prefixconnector = BEFEHL PROCESSOR->BEFEHL
```

\setupdataset [...,¹...] [...,²...,...]

```
1 NAME OPT
2 prodleva = ano ne
```

\setupdelimitedtext [...,¹...] [...,²...,...]

```
1 NAME OPT
2 pred = BEFEHL
  po = BEFEHL
  language = lokalne globalne SPRACHE
  metoda = font
  opakovat = ano ne
  misto = text odstavec marginalie
  vlevo = BEFEHL
  stredni = BEFEHL
  vpravo = BEFEHL
  nextleft = BEFEHL
  nextright = BEFEHL
  mezerapred = inherits: \preskoc
  mezeraza = inherits: \preskoc
  levyokraj = ano ne standardni DIMENSION
  pravyokraj = ano ne standardni DIMENSION
  odsazovani = inherits: \nastavodsazovani
  odsadpristi = ano ne auto
  pismeno = STYLE BEFEHL
  barva = COLOR
  stylsymboly = STYLE BEFEHL
  barvasymbolu = COLOR
```

\setupdescription [...¹,...] [...²,...]

1	NAME		OPT
2	titul	=	ano ne
	uroven	=	NUMMER
	text	=	TEXT
	headcommand	=	\...##1
	pred	=	BEFEHL
	po	=	BEFEHL
	mezi	=	BEFEHL
	alternativa	=	vlevo vpravo naokraji ivlevo ivpravo marginalie lev yokraj prav yokraj innermargin outermargin semknuto visici vrsek prikaz NAME
	zarovnani	=	inherits: \nastavzarovnani
	headalign	=	inherits: \nastavzarovnani
	odsazovani	=	inherits: \nastavodsazovani
	obrazovka	=	ano ne
	odsadpristi	=	ano ne auto
	sirka	=	prizpusobive široky radek DIMENSION
	vzdalenost	=	zadny DIMENSION
	natahnout	=	NUMMER
	shrink	=	NUMMER
	zaveseni	=	prizpusobive široky zadny marginalie NUMMER
	closesymbol	=	BEFEHL
	closecommand	=	\...##1
	expanzen	=	ano ne xml
	referenceprefix	=	+ - TEXT
	vzor	=	TEXT
	marginalie	=	ano ne standardni DIMENSION
	pismeno	=	STYLE BEFEHL
	barva	=	COLOR
	stylhlavicky	=	STYLE BEFEHL
	barvahlavicky	=	COLOR

\setupdirections [...^{*},...]

*	bidi	=	zap vyp lokalne globalne
	metoda	=	jedna dve implicitni
	fences	=	ano ne
	break	=	obe pred

\setupdocument [...^{*},...]

*	pred	=	BEFEHL
	po	=	BEFEHL
	metadata:author	=	TEXT
	metadata:title	=	TEXT
	metadata:subject	=	TEXT
	metadata:keywords	=	TEXT
	KEY	=	VALUE

\setupeffect [...¹,...] [...²,...]

1	NAME		OPT
2	metoda	=	zadny prikaz
	natahnout	=	NUMMER
	tloustkalinky	=	NUMMER
	alternativa	=	normalni uvnitr vnejsi obe skryte natahnout

\setupenumeration [$\dots^1\dots$] [$\dots^2\dots$]

```

1  NAME                                OPT
2  titul                             = ano ne
   cislo                             = ano ne
   ciselny prikaz                     = \...##1
   vzdalenost titulek                 = DIMENSION
   styl titulek                       = STYLE BEFEHL
   barva titulek                      = COLOR
   titlecommand                       = \...##1
   titleleft                         = BEFEHL
   titleright                        = BEFEHL
   vlevo                             = BEFEHL
   vpravo                            = BEFEHL
   symbol                            = BEFEHL
   starter                           = BEFEHL
   predel                            = BEFEHL
   propojeni                         = NAME
   counter                           = NAME
   uroven                             = NUMMER
   text                              = TEXT
   headcommand                       = \...##1
   pred                              = BEFEHL
   po                                 = BEFEHL
   mezi                              = BEFEHL
   alternativa                       = vlevo vpravo naokraj i vlevo i vpravo
                                     semknuto visici vrsek prikaz NAME
                                     marginalie levýokraj pravýokraj innermargin outermargin
   zarovnani                         = inherits: \nastavzarovnani
   headalign                         = inherits: \nastavzarovnani
   odsazovani                       = inherits: \nastavodsazovani
   obrazovka                        = ano ne
   odsadpristi                      = ano ne auto
   sirka                             = prizpusobive široky radek DIMENSION
   vzdalenost                       = zadny DIMENSION
   natahnout                        = NUMMER
   shrink                           = NUMMER
   zaveseni                         = prizpusobive široky zadny marginalie NUMMER
   closesymbol                      = BEFEHL
   closecommand                     = \...##1
   expanzen                         = ano ne xml
   referenceprefix                  = + - TEXT
   vzor                             = TEXT
   marginalie                       = ano ne standardni DIMENSION
   pismo                             = STYLE BEFEHL
   barva                             = COLOR
   styl hlavy                       = STYLE BEFEHL
   barva hlavy                      = COLOR
   inherits: \setupcounter

```

\setupenv [$\dots^*\dots$]

```

*  set      = BEFEHL
   reset    = BEFEHL
   KEY      = VALUE

```

\setupexport [$\dots^*\dots$]

```

*  zarovnani      = flushleft nastred flushright normalni
   zakladnifont    = DIMENSION
   sirka           = DIMENSION
   titul          = TEXT
   podtitulek      = TEXT
   autor          = TEXT
   alternativa     = html div
   properties      = ano ne
   hyphen          = ano ne
   cssfile         = FILE
   prvnistranka    = FILE
   poslednistrana  = FILE

```

`\setupexternalfigure [...1,...] [...2,...]`

```
1 NAME OPT
2 sirka = DIMENSION
vyska = DIMENSION
popisek = NAME
stranka = NUMMER
objekt = ano ne
prefix = TEXT
metoda = pdf mps jpg png jp2 jbig svg eps gif tif mov buffer tex cld auto
controls = ano ne
nahled = ano ne
mask = zadny
rozliseni = NUMMER
barva = COLOR
arguments = TEXT
opakovat = ano ne
faktor = prizpusobive siroky max auto implicitni
vfaktor = prizpusobive siroky max auto implicitni
sfaktor = prizpusobive siroky max auto implicitni
maxsirka = DIMENSION
maxvyska = DIMENSION
equalwidth = DIMENSION
equalheight = DIMENSION
meritko = NUMMER
xmeritko = NUMMER
ymeritko = NUMMER
s = NUMMER
sx = NUMMER
sy = NUMMER
radky = NUMMER
misto = lokalne globalne implicitni
adresar = PATH
volba = test ramecek prazdne
foregroundcolor = COLOR
reset = ano ne
pozadi = barevne popredi NAME
ramecek = zap vyp
barvapozadi = COLOR
xmax = NUMMER
ymax = NUMMER
ramecky = zap vyp
interakce = ano vse zadny odkaz layer zalozka
zakladnifont = DIMENSION
comment = BEFEHL TEXT
velikost = zadny media crop trim art
cache = PATH
resources = PATH
obrazovka = FILE
konverze = TEXT
order = LISTE
crossreference = ano ne NUMMER
```

`\setupexternalsoundtracks [...*,...]`

`* volba = opakovat`

`\setupfieldbody [...1,...] [...2,...]`

```
1 NAME OPT
2 category = NAME
inherits: \setupfieldcategory
```


\setupfieldcategory [...¹,...] [...²,...]

```

1  NAME                      OPT
2  start                     = NUMMER
   pismo                     = STYLE BEFEHL
   barva                     = COLOR
   typ                       = radio pod text radek push check signature
   values                    = TEXT
   implicitni                = TEXT
   barvarameckupole          = COLOR
   barvapožadipole           = COLOR
   sirka                     = DIMENSION
   vyska                     = DIMENSION
   hloubka                   = DIMENSION
   zarovnani                 = vlevo nastred vpravo flushleft center flushright
   n                         = NUMMER
   symbol                    = NAME
   fieldlayer                 = NAME
   volba                     = pouze procteni pozadovane chranene tridene nedostupne nocheck fixne soubor skryte tisknutelne
                              auto
   klikuvnitř                = REFERENCE
   klikvne                   = REFERENCE
   oblastuvnitř              = REFERENCE
   oblastvne                 = REFERENCE
   klavesapo                  = REFERENCE
   formatovat                = REFERENCE
   validovat                 = REFERENCE
   pocitat                   = REFERENCE
   focusin                   = REFERENCE
   focusout                   = REFERENCE
   openpage                  = REFERENCE
   closepage                  = REFERENCE

```

\setupfieldcontentframed [...¹,...] [...²,...]

```

1  NAME                      OPT
2  inherits: \nastavoramovaniinherits: \setupfieldcategory

```

\setupfieldlabelframed [...¹,...] [...²,...]

```

1  NAME                      OPT
2  inherits: \nastavoramovani

```

\setupfieldtotalframed [...¹,...] [...²,...]

```

1  NAME                      OPT
2  pred                     = BEFEHL
   po                      = BEFEHL
   mezi                    = BEFEHL
   vzdalenost              = DIMENSION
   alternativa             = reset popisek ramecek horizontalne vertikalne
   inherits: \nastavoramovani

```

\setupfiller [...¹,...] [...²,...]

```

1  NAME                      OPT
2  levyokraj                = DIMENSION
   pravyokraj               = DIMENSION
   vlevo                    = BEFEHL
   vpravo                   = BEFEHL
   alternativa              = symbol natahnout linka mezera
   metoda                   = lokalne globalne nastred siroky
   sirka                    = DIMENSION
   vyska                    = DIMENSION
   hloubka                  = DIMENSION
   offset                   = DIMENSION
   vzdalenost               = DIMENSION
   zarovnani                = vlevo vpravo nastred flushleft flushright uvnitř vnejsi
   symbol                   = BEFEHL
   pismo                    = STYLE BEFEHL
   barva                    = COLOR

```

\setupfirstline [...¹,...] [...²,...]

```

1  NAME                      OPT
2  n                        = NUMMER
   alternativa             = implicitni radek slovo
   pismo                   = STYLE BEFEHL
   barva                   = COLOR

```

`\setupfittingpage [...1,...] [...2,...]`

```
1 NAME OPT
2 pagestate = start stop
  prikaz = \...##1
  marginalie = stranka
  meritko = NUMMER
  papir = auto implicitni NAME
  inherits: \nastavoramovani
```

`\setupfloatcaption [...1,...] [...2,...]`

```
1 NAME OPT
2 suffix = BEFEHL
  suffixseparator = BEFEHL
  suffixstopper = BEFEHL
  misto = vlevo vpravo nastred nizko vysoko mrizka prekryv uvnitr vnejsi innermargin outermargin levyokraj
    pravyyokraj lefthanging righthanging zaveseni vrsek spodek natahnout tolerantni velmitolerantni
    zadny implicitni
  prikaz = \...##1
  ciselnyprikaz = \...##1
  textovyprikaz = \...##1
  mezerapred = inherits: \preskoc
  spaceinbetween = inherits: \preskoc
  mezeraza = inherits: \preskoc
  vzdalenost = DIMENSION
  headseparator = TEXT
  mezi = BEFEHL
  pismo = STYLE BEFEHL
  barva = COLOR
  offsetvrsku = DIMENSION
  offsetspodku = DIMENSION
  cislo = ano ne zadny
  group = TEXT
  levyokraj = DIMENSION
  pravyyokraj = DIMENSION
  innermargin = DIMENSION
  outermargin = DIMENSION
  zarovnnani = inherits: \nastavzarovnnani
  sirka = prizpusobive max DIMENSION
  minsirka = prizpusobive DIMENSION
  maxsirka = DIMENSION
  inherits: \setupcounter
```

`\setupfontexpansion [...1] [...2,...]`

```
1 NAME
2 vector = NAME
  faktor = NUMMER
  natahnout = NUMMER
  shrink = NUMMER
  krok = NUMMER
```

`\setupfontprotrusion [...1] [...2,...]`

```
1 NAME
2 vector = NAME
  faktor = NUMMER
  vlevo = NUMMER
  vpravo = NUMMER
```

`\setupfonts [...*,...]`

```
* language = ne auto
```

`\setupfontsolution [...1,...] [...2,...]`

```
1 NAME OPT
2 goodies = FILE
  solution = NAME
  less = NAME
  more = NAME
  metoda = preroll split normalni reverse nahodny
  kriterium = NUMMER
```

`\setupforms [...*,...]`

```
* metoda = XML HTML PDF
  export = ano ne
```

\setupformula [¹...] [²...]

```

1 NAME OPT
2 misto = vlevo vpravo
  zarovnani = vlevo nastred vpravo flushleft center flushright normalni
  split = ano ne stranka
  strut = ano ne
  vzdalenost = DIMENSION
  vlevo = BEFEHL
  vpravo = BEFEHL
  mezerapred = inherits: \preskoc
  mezeraza = inherits: \preskoc
  ciselny prikaz = \...##1
  barva = COLOR
  styl cisla = STYLE BEFEHL
  barva cisla = COLOR
  volba = zhustene tight nastred ramecek podlehloubky radek pulradku -radek -pulradku inherits: \nastavzakladnifont
  marginalie = ano ne standardni DIMENSION
  levyokraj = DIMENSION
  pravyokraj = DIMENSION
  alternativa = NAME
  odsadpristi = ano ne auto
  mrizka = inherits: \snaptogrid
  ramecek = cislo
  zaveseni = zadny auto
  expanzen = ano ne xml
  referenceprefix = + - TEXT
  xmlsetup = NAME
  catcodes = NAME
  inherits: \setupcounter

```

\setupformulaframed [¹...] [²...]

```

1 NAME OPT
2 inherits: \nastavoramovani

```

\setupframedcontent [¹...] [²...]

```

1 NAME OPT
2 vlevo = BEFEHL
  vpravo = BEFEHL
  leftoffser = DIMENSION
  pravyoffset = DIMENSION
  offsetvrsku = DIMENSION
  offsetspodku = DIMENSION
  korekceradku = ano ne
  inherits: \nastavoramovani

```

\setupframedtable [¹...] [²...]

```

1 NAME OPT
2 pred = BEFEHL
  po = BEFEHL
  mezi = BEFEHL
  vzdalenost = DIMENSION
  inherits: \nastavoramovani

```

\setupframedtablecolumn [¹...] [²...] [³...]

```

1 NAME OPT
2 NUMMER kazdy
3 inherits: \nastavoramovani

```

\setupframedtablerow [¹...] [²...] [³...]

```

1 NAME OPT
2 NUMMER kazdy
3 inherits: \nastavoramovani

```

\setupframedtext [...¹,...] [...²,...]

1 NAME OPT

2 vlevo = BEFEHL
 vpravo = BEFEHL
 vnitrni = BEFEHL
 misto = vlevo vpravo nastred zadny
 korekcehloubky = zap vyp
 zakladnifont = inherits: \nastavzakladnifont
 odsazovani = inherits: \nastavodsazovani
 pismo = STYLE BEFEHL
 barva = COLOR
 inherits: \nastavoramovani inherits: \setupplacement

\setupglobalreferenceprefix [...]

* + - TEXT

\setupheadalternative [...¹,...] [...²,...]

1 NAME OPT

2 alternativa = horizontalne vertikalne nekde
 renderingsetup = NAME

\setuphelp [...¹,...] [...²,...]

1 NAME OPT

2 inherits: \nastavoramovani

\setuphigh [...¹,...] [...²,...]

1 NAME OPT

2 vzdalenost = DIMENSION
 up = DIMENSION
 pismo = STYLE BEFEHL
 barva = COLOR

\setuphighlight [...¹,...] [...²,...]

1 NAME OPT

2 prikaz = ano ne
 pismo = STYLE BEFEHL
 barva = COLOR

\setuphyphenation [...^{*},...]

* metoda = original tex implicitni hyphenate expanded traditional zadny

\setupcharacterkerning [...¹,...] [...²,...]

1 NAME OPT

2 faktor = max NUMMER
 sirka = DIMENSION
 features = NAME
 pismo = STYLE BEFEHL
 barva = COLOR

\setupcharacterspacing [...¹] [...²] [...³,...]

1 NAME OPT

2 NUMMER

3 vlevo = NUMMER
 vpravo = NUMMER
 alternativa = 0 1

```

\setupchemical [...1,...] [...2,...]
1  NAME                      OPT
2  strut                    = ano ne auto kap prizpusobive radek implicitni CHARACTER
   sirka                    = prizpusobive zadny NUMMER
   vyska                    = prizpusobive zadny NUMMER
   vlevo                    = prizpusobive zadny NUMMER
   vpravo                   = prizpusobive zadny NUMMER
   vrsek                   = prizpusobive zadny NUMMER
   spodek                   = prizpusobive zadny NUMMER
   meritko                  = male stredni velke normalni NUMMER
   rotace                   = NUMMER
   symzarovnani             = auto
   osa                      = zap vyp
   barvamecku               = COLOR
   tloustkalinky           = DIMENSION
   offset                   = DIMENSION
   jednotka                 = DIMENSION
   faktor                   = NUMMER
   ramecek                  = zap vyp
   barvalinky               = COLOR
   zakladnifont             = inherits: \nastavzakladnifont
   velikost                 = male stredni velke
   pismo                    = STYLE BEFEHL
   barva                    = COLOR

```

```

\setupchemicalframed [...1,...] [...2,...]
1  NAME                      OPT
2  inherits: \nastavoramovani

```

```

\setupindentedtext [...1,...] [...2,...]
1  NAME                      OPT
2  pred                     = BEFEHL
   po                       = BEFEHL
   vzdalenost               = DIMENSION
   vzor                     = TEXT
   text                     = TEXT
   sirka                    = prizpusobive siroky DIMENSION
   oddelovac                = BEFEHL
   pismo                    = STYLE BEFEHL
   barva                    = COLOR
   stylhlavicky             = STYLE BEFEHL
   barvahlavicky            = COLOR

```

```

\setupinitial [...1,...] [...2,...]
1  NAME                      OPT
2  n                        = NUMMER
   m                        = NUMMER
   pred                     = BEFEHL
   vzdalenost               = DIMENSION
   hoffset                  = DIMENSION
   voffset                  = radek DIMENSION
   pismo                    = STYLE BEFEHL
   barva                    = COLOR
   font                     = FONT
   text                     = TEXT
   misto                    = marginalie text
   metoda                   = prvni posledni auto zadny

```

```

\setupinsertion [...1,...] [...2,...]
1  NAME                      OPT
2  misto                    = stranka text sloupce firstcolumn lastcolumn

```

```

\setupitaliccorrection [...,*...]
*  text vzdy globalne zadny

```

```

\setupitemgroup [...]1 [...]2 [...]3 [...]4
1 NAME OPT OPT OPT
2 kazdy NUMMER
3 uvod nahodny pokracovat zhustene autouvod široky text pred po zadnabila marginalie naokraji naokraji dotextu
uvolnene prizpusobive nofit odstavec spojeno semknuto predel nostopper rozbalene opakovat norepeat reverse sloupce
jedna dve tri ctyri pet six seven eight nine standardni NUMMER*siroky NUMMER*semknuto horizontalne NAME
4 pred = BEFEHL
po = BEFEHL
mezi = BEFEHL
predhlavickou = BEFEHL
pohlavice = BEFEHL
textvlevo = BEFEHL
textvpravo = BEFEHL
vlevo = BEFEHL
vpravo = BEFEHL
faktor = NUMMER
krok = DIMENSION
sirka = DIMENSION
vzdalenost = DIMENSION
marginalie = ano ne standardni DIMENSION
levyokraj = ano ne standardni DIMENSION
pravyokraj = ano ne standardni DIMENSION
zarovnani = inherits: \nastavzarovnani
odsazovani = inherits: \nastavodsazovani
start = NUMMER
symzarovnani = vlevo nastred vpravo flushleft center flushright
symbol = NAME
n = NUMMER
odsadpristi = ano ne auto
vnitrni = BEFEHL
prikaz = CSNAME
polozky = NUMMER
maxsirka = DIMENSION
itemalign = vlevo vpravo nastred flushleft flushright uvnitr vnejsi
alignsymbol = ano ne
textdistance = male stredni velke zadny mezera DIMENSION
predelmista = ano ne
pismo = STYLE BEFEHL
barva = COLOR
stylhlavicky = STYLE BEFEHL
barvahlavicky = COLOR
stylsnacky = STYLE BEFEHL
barvaznacky = COLOR
stylsymboly = STYLE BEFEHL
barvasymbolu = COLOR
mrizka = inherits: \definegridsnapping
inherits: \setupcounter

```

\setupitemgroup [...¹,...] [...²,...]

```

1  NAME NAME:NUMMER OPT
2  pred             = BEFEHL
   po               = BEFEHL
   mezi            = BEFEHL
   predhlavickou   = BEFEHL
   pohlavicce      = BEFEHL
   textvlevo       = BEFEHL
   textvpravo      = BEFEHL
   vlevo           = BEFEHL
   vpravo          = BEFEHL
   faktor          = NUMMER
   krok            = DIMENSION
   sirka           = DIMENSION
   vzdalenost      = DIMENSION
   volba           = uvod nahodny pokracovat zhustene autouvod široky text pred po zadnabila marginalie naokraji
                   naokraji dotextu uvolnene prizpusobive nofit odstavec spojeno semknuto predel rozbalene opakovat
                   norepeat reverse sloupce jedna dve tri ctyri pet six seven eight nine standardni NUMMER*siroky
                   NUMMER*semknuto horizontalne NAME
   marginalie      = ano ne standardni DIMENSION
   levyokraj       = ano ne standardni DIMENSION
   pravyokraj      = ano ne standardni DIMENSION
   zarovnnani      = inherits: \nastavzarovnnani
   odsazovani      = inherits: \nastavodsazovani
   start           = NUMMER
   symzarovnnani   = vlevo nastred vpravo flushleft center flushright
   symbol          = NAME
   n               = NUMMER
   odsadpristi     = ano ne auto
   vnitri          = BEFEHL
   prikaz          = CSNAME
   polozky         = NUMMER
   maxsirka        = DIMENSION
   itemalign       = vlevo vpravo nastred flushleft flushright uvnitr vnejsi
   alignsymbol     = ano ne
   textdistance    = male stredni velke zadny mezera DIMENSION
   predelmista     = ano ne
   pismeno         = STYLE BEFEHL
   barva           = COLOR
   stylhlavicky    = STYLE BEFEHL
   barvahlavicky   = COLOR
   stylsnacky      = STYLE BEFEHL
   barvaznacky     = COLOR
   stylsymboly     = STYLE BEFEHL
   barvasymbolu    = COLOR
   mrizka          = inherits: \definegridsnapping
   inherits: \setupcounter

```

\nastaveniITEMGROUP [...¹,...] [...²,...] [...³,...]

```

1  kazdy NUMMER OPT OPT OPT
2  inherits: \setupitemgroup
3  inherits: \setupitemgroup
instances: itemize

```

\nastaveniitemize [...¹,...] [...²,...] [...³,...]

```

1  kazdy NUMMER OPT OPT OPT
2  inherits: \setupitemgroup
3  inherits: \setupitemgroup

```

\setuplabel [...¹,...] [...²,...]

```

1  NAME          OPT
2  titul         = ano ne
   cislo         = ano ne
   ciselnyprikaz = \...##1
   vzdalenosttitulek = DIMENSION
   styltitulek   = STYLE BEFEHL
   barvatitulek  = COLOR
   titlecommand  = \...##1
   titleleft     = BEFEHL
   titleright    = BEFEHL
   vlevo         = BEFEHL
   vpravo        = BEFEHL
   symbol        = BEFEHL
   starter       = BEFEHL
   predel        = BEFEHL
   propojeni     = NAME
   counter       = NAME
   uroven        = NUMMER
   text          = TEXT
   headcommand   = \...##1
   pred          = BEFEHL
   po            = BEFEHL
   mezi          = BEFEHL
   alternativa   = vlevo vpravo naokrajiv vlevo vpravo marginalie lev yokraj prav yokraj innermargin outermargin
                   semknuto visici vrsek prikaz dotextu NAME
   zarovnani     = inherits: \nastavzarovnani
   headalign     = inherits: \nastavzarovnani
   odsazovani    = inherits: \nastavodsazovani
   obrazovka     = ano ne
   odsadpristi   = ano ne auto
   sirka         = prizpusobive siroky radek DIMENSION
   vzdalenost    = zadny DIMENSION
   natahnout     = NUMMER
   shrink        = NUMMER
   zaveseni      = prizpusobive siroky zadny marginalie NUMMER
   closesymbol   = BEFEHL
   closecommand  = \...##1
   expanzen      = ano ne xml
   referenceprefix = + - TEXT
   vzor          = TEXT
   marginalie    = ano ne standardni DIMENSION
   pismo         = STYLE BEFEHL
   barva         = COLOR
   stylhlavicky  = STYLE BEFEHL
   barvahlavicky = COLOR
   inherits: \setupcounter

```

\setupplayer [...¹,...] [...²,...]

```

1  NAME          OPT
2  status        = start stop pokracovat dalsi opakovat
   volba         = test
   stranka       = NUMMER
   sirka         = DIMENSION
   vyska         = DIMENSION
   region        = NAME
   rotace        = vlevo vpravo uvnitr vnejsi NUMMER
   position      = ano ne prekryv
   hoffset       = max DIMENSION
   voffset       = max DIMENSION
   offset        = DIMENSION
   dx            = DIMENSION
   dy            = DIMENSION
   sx            = NUMMER
   sy            = NUMMER
   x             = DIMENSION
   y             = DIMENSION
   roh           = vlevo nastred vpravo vrsek spodek
   misto         = mrizka vlevo nastred vpravo vrsek spodek radek l c r m t b g
   radek         = NUMMER
   sloupec       = NUMMER
   smer          = normalni reverse
   oboustranne   = ano ne
   metoda        = prizpusobive prekryv
   opakovat      = ano
   prednastaveni = lefttop righttop leftbottom rightbottom nastred middletop middlebottom middleleft middleright
                   lefttopleft lefttopright NAME

```


\setuplayeredtext [...¹,...] [...²,...]

1 NAME OPT
 2 pismo = STYLE BEFEHL
 barva = COLOR
 inherits: \nastavoramovani

\setuplayouttext [...¹.] [...².] [...³,...]

1 vrsek zahlavi text upati spodk
 2 text marginalie hrana
 3 status = start stop prazdne vysoko zadny normalni zadneznaceni NAME
 pismo = STYLE BEFEHL
 barva = COLOR
 strut = ano ne
 n = NUMMER
 pred = BEFEHL
 po = BEFEHL
 stylvlevo = STYLE BEFEHL
 stylvpravo = STYLE BEFEHL
 barvavlevo = COLOR
 barvavpravo = COLOR
 sirka = DIMENSION
 sirkavlevo = DIMENSION
 sirkavpravo = DIMENSION

\setuplinefiller [...¹,...] [...²,...]

1 NAME OPT
 2 misto = vlevo vpravo obe
 rozsah = vlevo vpravo lokalne
 mp = NAME
 vyska = DIMENSION
 hloubka = DIMENSION
 vzdalenost = DIMENSION
 threshold = DIMENSION
 tloustkalinky = DIMENSION
 pred = BEFEHL
 po = BEFEHL
 barva = COLOR
 styltextu = STYLE BEFEHL
 barvatextu = COLOR
 zarovnani = inherits: \nastavzarovnani

\setuplinefillers [...¹,...] [...²,...]

1 NAME OPT
 2 inherits: \setuplinefiller

\setuplinenote [...¹,...] [...²,...]

1 NAME OPT
 2 compress = ano ne
 compressmethod = separator predel mezera
 compressseparator = BEFEHL
 compressdistance = DIMENSION
 inherits: \setupnote

\setuplinetable [¹...] [²...] [³...²...]

```

1  r c          OPT      OPT
2  liche sude zahlavi NUMMER
3  radky        = prizpusobive NUMMER
   pred         = BEFEHL
   po           = BEFEHL
   mezi         = BEFEHL
   natahnout    = ano ne DIMENSION
   maxsirka     = prizpusobive DIMENSION
   nvlevo       = NUMMER
   n            = NUMMER
   opakovat    = ano ne
   nx           = NUMMER
   sirka        = DIMENSION
   vyska       = prizpusobive radek DIMENSION
   vzdalenost   = DIMENSION
   levyoffset   = DIMENSION
   pravyoffset  = DIMENSION
   zarovnani    = inherits: \nastavzarovnani
   pozadi       = barevne
   barvapozadi  = COLOR
   xheight     = max DIMENSION
   xdepth       = max DIMENSION
   pismo       = STYLE BEFEHL
   barva        = COLOR

```

\setuplistalternative [¹...] [²...²...]

```

1  NAME          OPT
2  pred          = BEFEHL
   po            = BEFEHL
   prikaz        = \...##1##2##3
   renderingsetup = NAME
   sirka         = DIMENSION
   vzdalenost    = DIMENSION
   natahnout     = DIMENSION
   filler        = BEFEHL

```

\setuplistextra [¹...] [²...²...]

```

1  NAME          OPT
2  pred = BEFEHL
   po  = BEFEHL

```

\setuplocalfloats [²...²...]

```

*  pred = BEFEHL
   po   = BEFEHL
   mezi = BEFEHL

```

\setuplocalinterlinespace [¹...] [²...²...]

```

1  NAME          OPT
2  inherits: \nastavmeziradkovoumezeru

```

\setuplocalinterlinespace [²...²...]

```

*  zap vyp reset auto male stredni velke NUMMER DIMENSION

```

\setuplocalinterlinespace [²...²...]

```

*  NAME

```

\setuplow [¹...] [²...²...]

```

1  NAME          OPT
2  vzdalenost    = DIMENSION
   down         = DIMENSION
   pismo        = STYLE BEFEHL
   barva        = COLOR

```

`\setuplowhigh [...1,...] [...2...,...]`

```
1  NAME          OPT
2  vzdalenost    = DIMENSION
   up            = DIMENSION
   down          = DIMENSION
   pismo        = STYLE BEFEHL
   barva         = COLOR
```

`\setuplowmidhigh [...1,...] [...2...,...]`

```
1  NAME          OPT
2  up            = DIMENSION
   down          = DIMENSION
   pismo        = STYLE BEFEHL
   barva         = COLOR
```

`\setupMPgraphics [...*...,...]`

```
*  barva = lokalne globalne
   mpy   = FILE
```

`\setupMPinstance [...1,...] [...2...,...]`

```
1  NAME          OPT
2  formatovat     = metafun mpost
   initializations = ano ne
   setups         = NAME
   styltextu      = STYLE BEFEHL
   barvatextu     = COLOR
   extensions     = ano ne
   metoda         = binary decimal double scaled implicitni
```

`\setupMPpage [...*...,...]`

```
*  inherits: \setupfittingpage
```

`\setupMPvariables [...1] [...2...,...]`

```
1  NAME          OPT
2  KEY = VALUE
```

`\setupmarginblock [...1,...] [...2...,...]`

```
1  NAME          OPT
2  status        = start stop
   sirka         = DIMENSION
   pred          = BEFEHL
   po            = BEFEHL
   mezi          = BEFEHL
   zarovnnani    = inherits: \nastavzarovnnani
   pismo        = STYLE BEFEHL
   barva         = COLOR
   vrsek         = BEFEHL
   spodek        = BEFEHL
   misto         = vlevo vpravo nastred naokraji
   vlevo         = BEFEHL
   vpravo        = BEFEHL
```

`\setupmargindata [...1,...] [...2,...]`

```

1  NAME                      OPT
2  strut                    = ano ne auto kap prizpusobive radek implicitni CHARACTER
   prikaz                  = \...#1
   sirka                   = DIMENSION
   zarovnnani              = inherits: \nastavzarovnnani
   anchor                  = region text
   misto                   = vlevo vpravo uvnitr vnejsi
   metoda                  = vrsek radek prvni podlehloubky vyska
   category                = implicitni hrana
   rozsah                  = lokalne globalne
   volba                   = text odstavec
   marginalie              = lokalne normalni marginalie hrana
   vzdalenost              = DIMENSION
   hoffset                 = DIMENSION
   voffset                 = DIMENSION
   dy                      = DIMENSION
   bottomspace             = DIMENSION
   threshold               = DIMENSION
   radek                   = NUMMER
   stack                   = ano pokracovat
   pismoeno                = STYLE BEFEHL
   barva                   = COLOR

```

`\setupmarginframed [...1,...] [...2,...]`

```

1  NAME                      OPT
2  inherits: \nastavoramovani

```

`\setupmarginrule [...1,...] [...2,...]`

```

1  NUMMER                    OPT
2  inherits: \setupsidebar

```

`\setupmathalignment [...1,...] [...2,...]`

```

1  NAME                      OPT
2  n                        = NUMMER
   m                        = NUMMER
   vzdalenost              = DIMENSION
   cislo                   = auto
   oddelovac               = TEXT
   zarovnnani              = vlevo nastred vpravo normalni
   misto                   = vrsek center spodek normalni
   mrizka                  = math ne

```

`\setupmathcases [...1,...] [...2,...]`

```

1  NAME                      OPT
2  vlevo                    = BEFEHL
   vpravo                   = BEFEHL
   strut                    = ano ne
   pismoeno                 = STYLE BEFEHL
   vzdalenost              = DIMENSION
   numberdistance          = DIMENSION

```

`\setupmathematics [...1,...] [...2,...]`

```

1  NAME                      OPT
2  openup                    = ano ne
   sadasymbolu              = NAME
   functionstyle            = STYLE BEFEHL
   compact                  = ano ne
   zarovnani                = l2r r2l
   bidi                     = ano ne
   sygreek                  = normalni kurziva zadny
   lcgreeek                 = normalni kurziva zadny
   ucgreeek                 = normalni kurziva zadny
   italics                  = 1 2 3 4 zadny reset
   autopunctuation         = ano ne vse comma yes,semicolon comma,semicolon all,semicolon
   setups                   = NAME
   domain                   = NAME reset
   styltextu                = STYLE BEFEHL
   barvatextu               = COLOR
   functioncolor            = COLOR
   integral                 = limits nolimits autolimits displaylimits zadny
   stylealternative        = NAME
   implicitni               = normalni kurziva
   fraction                 = ams ctx
   ampersand                = normalni

```

`\setupmathfence [...1,...] [...2,...]`

```

1  NAME                      OPT
2  prikaz                    = ano ne
   vlevo                    = NUMMER
   stredni                  = NUMMER
   vpravo                   = NUMMER
   mathstyle                = obrazovka text script scriptscript cramped uncramped normalni zhustene male velke
   barva                    = COLOR
   status                   = auto
   metoda                   = auto
   faktor                   = zadny auto NUMMER
   mathclass                = NUMMER

```

`\setupmathfraction [...1,...] [...2,...]`

```

1  NAME                      OPT
2  vzdalenostvrsku          = DIMENSION
   vzdalenostspodku         = DIMENSION
   marginalie               = DIMENSION
   barva                    = COLOR
   strut                    = ano ne math tight
   alternativa              = uvnitr vnejsi obe
   linka                    = ano ne auto
   vlevo                    = NUMMER
   vpravo                   = NUMMER
   tloustkalinky            = DIMENSION
   mathstyle                = STYLE BEFEHL
   vzdalenost               = ne zadny prekryv
   inlinethreshold          = auto NUMMER
   displaythreshold         = auto NUMMER
   fences                   = NAME

```

`\setupmathfractions [...1,...] [...2,...]`

```

1  NAME                      OPT
2  inherits: \setupmathfraction

```

`\setupmathframed [...1,...] [...2,...]`

```

1  NAME                      OPT
2  inherits: \nastavoramovani

```

`\setupmathmatrix [...1,...] [...2,...]`

```

1  NAME                      OPT
2  vlevo                    = BEFEHL
   vpravo                   = BEFEHL
   strut                    = ano ne NUMMER
   zarovnani                = vlevo nastred vpravo normalni
   pismeno                  = STYLE BEFEHL
   vzdalenost               = DIMENSION
   simplecommand            = TEXT
   misto                    = vrsek spodek vysoko nizko nivy normalni

```

```
\setupmathornament [...1,...] [...2,...]
1 NAME OPT
2 alternativa = mp
  barva = COLOR
  mpoffset = DIMENSION
  mp = NAME
```

```
\setupmathradical [...1,...] [...2,...]
1 NAME OPT
2 alternativa = implicitni normalni mp
  barva = COLOR
  mpoffset = DIMENSION
  mp = NAME
```

```
\setupmathstackers [...1,...] [...2,...]
1 NAME OPT
2 vlevo = BEFEHL
  vpravo = BEFEHL
  topcommand = \...##1
  bottomcommand = \...##1
  middlecommand = \...##1
  mp = NAME
  mpheight = DIMENSION
  mpdepth = DIMENSION
  mpoffset = DIMENSION
  barva = COLOR
  hoffset = DIMENSION
  voffset = DIMENSION
  minvyska = DIMENSION
  mindepth = DIMENSION
  mathclass = rel ord
  offset = min max normalni
  misto = vrsek spodek vysoko nizko nastred NUMBER
  strut = ano ne
  alternativa = normalni implicitni mp
  minsirka = DIMENSION
  vzdalenost = DIMENSION
  moffset = DIMENSION
  order = normalni reverse
  mathlimits = ano ne
```

```
\setupmathstyle [...,*...]
* obrazovka text script scriptscript cramped uncramped normalni zhustene male velke NAME
```

```
\setupmixedcolumns [...1,...] [...2,...]
1 NAME OPT
2 mrizka = inherits: \definegridsnapping
  tloustkalinky = DIMENSION
  metoda = otr box
  pred = BEFEHL
  po = BEFEHL
  vzdalenost = DIMENSION
  n = NUMBER
  maxvyska = DIMENSION
  maxsirka = DIMENSION
  krok = DIMENSION
  profile = NAME
  zarovnani = inherits: \nastavzarovnani
  setups = NAME
  rovnovaha = ano ne
  splitmethod = zadny fixne
  alternativa = lokalne globalne
  internalgrid = radek pulradku
  oddelovac = linka
  strut = ano ne
  barva = COLOR
  barvalinky = COLOR
  smer = normalni reverse
  inherits: \nastavoramovani
```

```
\setupmodule [...1] [...2,...]
1 FILE OPT
2 test = ano ne
  KEY = VALUE
```

`\setupnotation [...1,...] [...2...]`

```

1 NAME OPT
2 titul = ano ne
  cislo = ano ne
  typ = note
  ciselnyprkaz = \...##1
  vzdalenosttitulek = DIMENSION
  styltitulek = STYLE BEFEHL
  barvatitulek = COLOR
  titlecommand = \...##1
  titleleft = BEFEHL
  titleright = BEFEHL
  vlevo = BEFEHL
  vpravo = BEFEHL
  symbol = BEFEHL
  starter = BEFEHL
  predel = BEFEHL
  propojeni = NAME
  counter = NAME
  uroven = NUMMER
  text = TEXT
  headcommand = \...##1
  pred = BEFEHL
  po = BEFEHL
  mezi = BEFEHL
  alternativa = vlevo vpravo naokrajji ivlevo ivpravo marginalie levyokraj pravyokraj innermargin outermargin
                  semknuto visici vrsek prikaz note NAME
  zarovnani = inherits: \nastavzarovnani
  headalign = inherits: \nastavzarovnani
  odsazovani = inherits: \nastavodsazovani
  obrazovka = ano ne
  odsadpristi = ano ne auto
  sirka = prizpusobive siroky radek DIMENSION
  vzdalenost = zadny DIMENSION
  natahnout = NUMMER
  shrink = NUMMER
  zaveseni = prizpusobive siroky zadny marginalie NUMMER
  closesymbol = BEFEHL
  closecommand = \...##1
  expanzen = ano ne xml
  referenceprefix = + - TEXT
  vzor = TEXT
  marginalie = ano ne standardni DIMENSION
  pismeno = STYLE BEFEHL
  barva = COLOR
  stylhlavicky = STYLE BEFEHL
  barvahlavicky = COLOR
  inherits: \setupcounter

```

`\setupnotations [...1,...] [...2...]`

```

1 NAME OPT
2 inherits: \setupnotation

```

```

\setupnote [...1,...2] [...2,...1,...]
1 NAME OPT
2 interakce = ano ne cislo text vse
symbolcommand = \...##1
textovyprikaz = \...##1
indikator = ano ne
oddelovactextu = BEFEHL
sirka = DIMENSION
vyska = DIMENSION
vzdalenost = DIMENSION
rulecommand = BEFEHL
linka = zap vyp normalni vlevo vpravo prikaz odstavec
split = tolerantni striktni velmistriktni NUMMER
faktor = NUMMER
misto = text stranka vysoko spodek zadny sloupce firstcolumn lastcolumn
dalsi = BEFEHL
n = NUMMER
barvalinky = COLOR
tloustkalinky = DIMENSION
setups = NAME
meziradkovamezera = NAME
odstavec = ano ne
pred = BEFEHL
po = BEFEHL
mezi = BEFEHL
rozsah = stranka
vzdalenostsloupcu = DIMENSION
pokracovat = ano ne
alternativa = mrizka fixne sloupce note zadny
kriterium = stranka
zakladnifont = inherits: \nastavzakladnifont
zarovnani = inherits: \nastavzarovnani
styltextu = STYLE BEFEHL
barvatextu = COLOR
anchor = dalsi
mezerapred = inherits: \preskoc
spaceinbetween = inherits: \preskoc
inherits: \nastavoramovani

```

```

\setupnotes [...1,...2] [...2,...1,...]
1 NAME OPT
2 inherits: \setupnote

```

```

\setupoffset [...*,...*,...]
* inherits: \setupoffsetbox

```

```

\setupoffsetbox [...*,...*,...]
* x = DIMENSION
y = DIMENSION
levyoffset = DIMENSION
pravyoffset = DIMENSION
offsetvrsku = DIMENSION
offsetspodku = DIMENSION
metoda = fixne
sirka = DIMENSION
vyska = DIMENSION
hloubka = DIMENSION
misto = vlevo nastred vpravo vrsek spodek radek l c r m t b g

```

```

\setupoutputroutine [...1,...2,...]
1 NAME OPT
2 KEY = CSNAME

```

```

\setupoutputroutine [...*,...]
* NAME

```


\setuppagegrid [...¹,...] [...²,...]

1 NAME OPT
2 n = NUMBER
nvlevo = NUMBER
nvpravo = NUMBER
sirka = DIMENSION auto
vzdalenost = DIMENSION
radky = NUMBER
maxsirka = DIMENSION
maxvyska = DIMENSION
smer = normalni reverse
stranka = inherits: \strana
inherits: \nastavoramovani

\setuppagegridarea [...¹,...] [...²,...]

1 NAME OPT
2 status = start stop opakovat
x = NUMBER
y = NUMBER
nx = NUMBER
ny = NUMBER
pismo = STYLE BEFEHL
barva = COLOR
clipoffset = DIMENSION
pravyoffset = DIMENSION
inherits: \nastavoramovani

\setuppagegridareatext [...¹] [...²]

1 NAME
2 TEXT

\setuppagegridlines [...¹] [...²] [...³] [...⁴]

1 NAME
2 NUMBER
3 NUMBER
4 NUMBER

\setuppagegridspan [...¹,...] [...²,...]

1 NAME OPT
2 n = NUMBER
pismo = STYLE BEFEHL
barva = COLOR
pred = BEFEHL
po = BEFEHL
inherits: \nastavoramovani

\setuppagegridstart [...¹] [...²] [...³] [...⁴]

1 NAME
2 NUMBER
3 NUMBER
4 NUMBER

\setuppagechecker [...¹,...] [...²,...]

1 NAME OPT
2 radky = NUMBER
offset = DIMENSION
metoda = 0 1 2 3
pred = BEFEHL
po = BEFEHL
mezi = BEFEHL

\setuppageinjection [...¹,...] [...²,...]

1 NAME OPT
2 status = predchozi dalsi NUMBER
prodleva = ano ne
alternativa = obrazek buffer setups zadny NAME
stranka = inherits: \strana
pagestate = start stop
n = NUMBER
inherits: \nastavoramovani

<pre> \setuppageinjectionalternative [...] [¹...] [²...] 1 NAME OPT 2 renderingsetup = NAME </pre>
<pre> \setuppageshift [¹...] [²...] [³...] 1 stranka papir OPT OPT 2 NAME 3 NAME </pre>
<pre> \setuppagestate [¹...] [²...] 1 NAME OPT 2 prodleva = ano ne </pre>
<pre> \setuppairedbox [¹...] [²...] 1 NAME OPT 2 pred = BEFEHL po = BEFEHL mezi = BEFEHL misto = vlevo nastred vpravo vrsek spodek vysoko nizko n = NUMMER vzdalenost = DIMENSION zakladnifont = inherits: \nastavzakladnifont sirka = DIMENSION vyska = DIMENSION maxsirka = DIMENSION maxvyska = DIMENSION zarovnani = inherits: \nastavzarovnani pismeno = STYLE BEFEHL barva = COLOR </pre>
<pre> \nastaveniPAIREDBOX [...[*]...] * inherits: \setuppairedbox instances: legend </pre>
<pre> \nastavenilegend [...[*]...] * inherits: \setuppairedbox </pre>
<pre> \setuppaper [...[*]...] * inherits: \nastavvelikostpapiru </pre>
<pre> \setupparagraph [¹...] [²...] 1 NAME OPT 2 pismeno = STYLE BEFEHL barva = COLOR zarovnani = inherits: \nastavzarovnani setups = NAME </pre>
<pre> \setupparagraphintro [¹...] [²] 1 reset kazdy prvni dalsi 2 BEFEHL </pre>
<pre> \setupparallel [¹...] [²...] [³...] 1 NAME 2 NAME 3 setups = NAME start = NUMMER n = NUMMER kriterium = vse </pre>
<pre> \setupperiods [...[*]...] * n = NUMMER sirka = DIMENSION prizpusobive vzdalenost = DIMENSION symbol = BEFEHL </pre>

`\setupplacement [...1,...] [...2,...]`

```
1 NAME OPT
2 pred = BEFEHL
  po = BEFEHL
  vlevo = BEFEHL
  vpravo = BEFEHL
  mrizka = inherits: \suptogrid
  korekceradku = zap vyp
  korekcehloubky = zap vyp
  marginalie = ano ne standardni
```

`\setuppositionbar [...*,...]`

```
* pismo = STYLE BEFEHL
  barva = COLOR
  n = NUMMER
  min = NUMMER
  max = NUMMER
  text = TEXT
  sirka = DIMENSION
  vyska = DIMENSION
  hloubka = DIMENSION
```

`\setupprocessor [...1,...] [...2,...]`

```
1 NAME OPT
2 status = start stop
  vlevo = BEFEHL
  vpravo = BEFEHL
  prikaz = \...##1
  pismo = STYLE BEFEHL
  barva = COLOR
```

`\setupprofile [...1,...] [...2,...]`

```
1 NAME OPT
2 vyska = DIMENSION
  hloubka = DIMENSION
  vzdalenost = DIMENSION
  faktor = NUMMER
  radky = NUMMER
  metoda = striktni fixne zadny
```

`\setupquotation [...*,...]`

```
* inherits: \setupdelimitedtext
```

`\setuprealpagenumber [...*,...]`

```
* inherits: \setupcounter
```

`\setupreferenceformat [...1,...] [...2,...]`

```
1 NAME OPT
2 popis = * NAME
  vlevo = BEFEHL
  vpravo = BEFEHL
  typ = implicitni text titul cislo stranka realpage
  setups = NAME
  autocase = ano ne
  text = TEXT
  pismo = STYLE BEFEHL
  barva = COLOR
```

`\setupreferenceprefix [...]`

```
* + - TEXT
```

```

\setupreferencestructureprefix [...] [...] [...] [...]
1 NAME ABSCHNITT OPT OPT
2 implicitni
3 prefix = ano ne
  prefixseparatorset = NAME
  prefixconversion = NAME
  prefixconversionset = NAME
  prefixstarter = BEFEHL PROCESSOR->BEFEHL
  prefixstopper = BEFEHL PROCESSOR->BEFEHL
  prefixset = NAME
  prefixsegments = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:* ABSCHNITT:vse
  numberconversion = NAME
  numberconversionset = NAME
  numberstarter = BEFEHL PROCESSOR->BEFEHL
  numberstopper = BEFEHL PROCESSOR->BEFEHL
  numbersegments = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse
  numberseparatorset = NAME
  prefixconnector = BEFEHL PROCESSOR->BEFEHL

```

```

\setupregisters [...] [...]
1 NAME NAME:NUMMER OPT
2 inherits: \nastavrejstrik

```

```

\setupregisters [...] [...] [...]
1 NAME OPT OPT
2 NUMMER
3 inherits: \nastavrejstrik

```

```

\setuprenderingwindow [...] [...]
1 NAME OPT
2 akceotevrenistranky = REFERENCE
  akcezavrenistranky = REFERENCE
  inherits: \nastavoramovani

```

```

\setups [...]
* NAME

```

```

\setupscale [...] [...]
1 NAME OPT
2 meritko = NUMMER
  xmeritko = NUMMER
  ymeritko = NUMMER
  sirka = DIMENSION
  vyska = DIMENSION
  hloubka = ano ne
  radky = NUMMER
  faktor = prizpusobive siroky max auto implicitni
  vfaktor = prizpusobive siroky max auto implicitni
  sfaktor = prizpusobive siroky max auto implicitni
  maxsirka = DIMENSION
  maxvyska = DIMENSION
  s = NUMMER
  sx = NUMMER
  sy = NUMMER
  equalwidth = DIMENSION
  equalheight = DIMENSION
  mrizka = ano prizpusobive vyska podlehloubky pulradku

```

```

\setupscript [...] [...]
1 NAME OPT
2 metoda = hangul hanzi nihongo ethiopic thai test
  prednastaveni = NAME
  features = auto

```

```

\setupscripts [...] [...]
1 NAME OPT
2 inherits: \setupscript

```

`\setupselector [...]1 [...]2...`

1 NAME
2 n = NUMBER
m = NUMBER

`\setupshift [...]1 [...]2...`

1 NAME OPT
2 pokracovat = ano ne
jednotka = ex em pt in cm mm sp bp pc dd cc nc
metoda = NUMBER
dy = NUMBER
zarovnani = inherits: \nastavzarovnani
pismo = STYLE BEFEHL
barva = COLOR

`\setupsidebar [...]1 [...]2...`

1 NAME OPT
2 tloustkalinky = DIMENSION
barvalinky = COLOR
alternativa = NUMBER
offsetvrsku = DIMENSION
offsetspodku = DIMENSION
vzdalenost = DIMENSION
vzdalenostlevehookraje = DIMENSION
uroven = NUMBER

`\setupspellchecking [...]*...`

* status = start stop
metoda = 1 2 3
seznam = NAME

`\setupstartstop [...]1 [...]2...`

1 NAME OPT
2 pred = BEFEHL
po = BEFEHL
mezi = BEFEHL
setups = NAME
vlevo = BEFEHL
vpravo = BEFEHL
pismo = STYLE BEFEHL
barva = COLOR

`\setupstretched [...]*...`

* inherits: \setupcharacterkerning

`\setupstruts [...]*`

* ano ne auto kap^{OPT} prizpusobive radek implicitni CHARACTER

`\setupstyle [...]1 [...]2...`

1 NAME OPT
2 metoda = prikaz
pismo = STYLE BEFEHL
barva = COLOR

`\setupsubformula [...]1 [...]2...`

1 NAME OPT
2 odsadpristi = ano ne auto

`\setupsubformulas [...]1 [...]2...`

1 NAME OPT
2 inherits: \setupsubformula

`\setupsynctex [...]*...`

* status = start stop
metoda = min max

```
\setups {...,*,...}
```

```
* NAME
```

```
\setupTABLE [...,1...] [...,2...] [...,3...,...]
```

```
1 r c x y row columnOPT prvni posledni start zahlavi kazdy liche sude jedna NUMBER -NUMBER
2 prvni least kazdy dve liche sude NUMBER -NUMBER
3 extras = BEFEHL
  vlevo = BEFEHL
  vpravo = BEFEHL
  barvahlavicky = COLOR
  stylhlavicky = STYLE BEFEHL
  vzdalenostlevehookraje = DIMENSION
  vzdalenostpravehookraje = DIMENSION
  vzdalenostsloupcu = DIMENSION
  maxsirka = DIMENSION
  setups = NAME
  sirkatextu = DIMENSION lokalne
  split = ano ne opakovat auto
  zahlavi = opakovat
  volba = natahnout tight
  pred = BEFEHL
  po = BEFEHL
  stejnastranka = pred po obe
  spaceinbetween = inherits: \preskoc
  splitoffset = DIMENSION
  aligncharacter = ano ne
  alignmentcharacter = TEXT number->TEXT text->TEXT
  vzdalenost = DIMENSION
  barva = COLOR
  pismeno = math STYLE BEFEHL
  inherits: \nastavoramovani
```

```
\setupTEXpage [...,*...,...]
```

```
* inherits: \setupfittingpage
```

```
\setuptabulation [...,1...] [...,2...,...]
```

```
1 NAME OPT
2 formatovat = TEMPLATE zadny
  pred = BEFEHL
  po = BEFEHL
  vzdalenost = male stredni velke zadny prazdny podlehloubky mrizka DIMENSION
  zarovnani = vlevo nastred vpravo dimension
  linka = radek normalni
  barvalinky = COLOR
  tloustkalinky = DIMENSION
  zakladnifont = inherits: \nastavzakladnifont
  odsazovani = ano ne
  split = ano ne opakovat auto
  jednotka = DIMENSION
  marginalie = DIMENSION
  vnitri = BEFEHL
  EQ = BEFEHL
  zahlavi = ano opakovat text
  ramecek = zap vyp
  titul = TEXT
  keptogether = ano ne
```

```
\setuptagging [...,*...,...]
```

```
* status = start stop
  metoda = auto
```

\setuptextbackground [...,¹...] [...,²...,...]

1 NAME OPT
2 status = start stop
misto = text odstavec vzdy zadny
kriterium = NUMMER
alternativa = NUMMER
mp = NAME
metoda = NAME
pozadi = barevne
barvapozadi = COLOR
roh = pravouhly zaobleny
uroven = NUMMER
offsetpozadi = DIMENSION
pred = BEFEHL
po = BEFEHL
zarovnani = inherits: \nastavzarovnani
pomlcka = NUMMER
polomer = DIMENSION
ramecek = zap vyp
barvamecku = COLOR
tloustkalinky = DIMENSION
voffset = DIMENSION
offsetramecku = DIMENSION
levyoffset = ano ne standardni DIMENSION
pravyoffset = ano ne standardni DIMENSION
offsetvrsku = male stredni velke radek DIMENSION
offsetspodku = male stredni velke radek DIMENSION
pismo = STYLE BEFEHL
barva = COLOR

\setuptextflow [...,¹...] [...,²...,...]

1 NAME OPT
2 sirka = DIMENSION
pismo = STYLE BEFEHL
barva = COLOR

\setuptooltip [...,¹...] [...,²...,...]

1 NAME OPT
2 misto = vlevo nastred vpravo
inherits: \nastavoramovani

\setupunit [...,¹...] [...,²...,...]

1 NAME OPT
2 metoda = 1 2 3 4 5 6
language = SPRACHE
alternativa = text matematika
order = reverse normalni
oddelovac = male stredni velke normalni zadny NAME
mezera = male stredni velke normalni zadny NAME
pismo = STYLE BEFEHL
barva = COLOR

\setupuserpagenumber [...,^{*}...,...]

* viewerprefix = TEXT
status = start stop zadny drzet prazdne
inherits: \setupcounter

\setupversion [...]

* koncept soubor docasne finalni NAME

\setupviewerlayer [...,^{*}...,...]

* titul = TEXT
status = start stop
export = ano ne
tisknutelne = ano ne
rozsah = lokalne globalne
metoda = zadny prikaz

\setupvspacing [...,^{*}...]

* inherits: \vspacing OPT

\setupwithargument {...} {...}

- 1 NAME
- 2 CONTENT

\setupwithargumentswapped {...} {...}

- 1 CONTENT
- 2 NAME

\setupxml [...]*[...]

- * implicitni = skryte zadny text
- compress = ano ne

\setupxtable [...]¹[...] [...]²[...]

- 1 NAME OPT
- 2 sirkatextu = DIMENSION lokalne
- zakladnifont = inherits: \nastavzakladnifont
- spaceinbetween = inherits: \preskoc
- volba = tight max natahnout sirka vyska fixne
- vyskatextu = DIMENSION
- maxsirka = DIMENSION
- vzdalenostsloupcu = DIMENSION
- vzdalenostlevehookraje = DIMENSION
- vzdalenostpravehookraje = DIMENSION
- zahlavi = opakovat
- upati = opakovat
- tloustkalinky = DIMENSION
- split = ano ne opakovat auto
- splitoffset = DIMENSION
- stejnastranka = pred po obe
- vzdalenost = DIMENSION
- inherits: \nastavoramovani

\setuvalue {...} {...}

- 1 NAME
- 2 CONTENT

\setuxvalue {...} {...}

- 1 NAME
- 2 CONTENT

\setvalue {...} {...}

- 1 NAME
- 2 CONTENT

\setvariable {...} {...} {...}

- 1 NAME
- 2 KEY
- 3 VALUE

\setvariables [...]¹[...] [...]²[...]

- 1 NAME
- 2 set = BEFEHL
- reset = BEFEHL
- KEY = VALUE

\setvboxregister ...¹ {...}

- 1 CSNAME NUMBER
- 2 CONTENT

\setvisualizerfont [...]^{*}

- * FONT OPT

\setvtopregister ...¹ {...}

- 1 CSNAME NUMBER
- 2 CONTENT

<pre> \setwidthof ¹... \to \²... 1 TEXT 2 CSNAME </pre>
<pre> \setxmeasure {...} {...} 1 NAME 2 DIMENSION </pre>
<pre> \setxvalue {...} {...} 1 NAME 2 CONTENT </pre>
<pre> \setxvariable {...} {...} {...} 1 NAME 2 KEY 3 VALUE </pre>
<pre> \setxvariables [¹...] [²...=...,...] 1 NAME 2 set = BEFEHL reset = BEFEHL KEY = VALUE </pre>
<pre> \shapedhbox {...} * CONTENT </pre>
<pre> \SHIFT {...} * CONTENT instances: shiftup shiftdown </pre>
<pre> \shiftdown {...} * CONTENT </pre>
<pre> \shiftup {...} * CONTENT </pre>
<pre> \showallmakeup </pre>
<pre> \showattributes </pre>
<pre> \showboxes </pre>
<pre> \showbtxdatasetauthors [...,[*]...,...] * specification = NAME OPT dataset = NAME field = address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME </pre>
<pre> \showbtxdatasetauthors [...[*]] * NAME OPT </pre>
<pre> \showbtxdatasetcompleteness [...,[*]...,...] * specification = NAME OPT dataset = NAME field = address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME </pre>
<pre> \showbtxdatasetcompleteness [...[*]] * NAME OPT </pre>

<pre> \showbtxdatasetfields [...,.*,...,...] * specification = NAME OPT dataset = NAME field = address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME </pre>
<pre> \showbtxdatasetfields [...] * NAME OPT </pre>
<pre> \showbtxfields [...,.*,...,...] * rotace = NUMMER^{OPT} specification = NAME </pre>
<pre> \showbtxfields [...] * NAME OPT </pre>
<pre> \showbtxhashedauthors [...] * TEXT OPT </pre>
<pre> \showbtxtables [...] * TEXT OPT </pre>
<pre> \showcolorbar [...] * COLOR </pre>
<pre> \showcolorcomponents [...] * COLOR </pre>
<pre> \showcolorset [...] * COLOR </pre>
<pre> \showcolorstruts </pre>
<pre> \showcounter [...] * NAME </pre>
<pre> \showdirectives </pre>
<pre> \showdirsmargin </pre>
<pre> \showedebuginfo </pre>
<pre> \showexperiments </pre>
<pre> \showfont [...¹] [...,²...] 1 FONT OPT 2 NUMMER </pre>
<pre> \showfontdata </pre>
<pre> \showfontitalics </pre>
<pre> \showfontkerns </pre>
<pre> \showfontparameters </pre>

\showfontstrip [...] * inherits: \nastavzakladnifont
\showfontstyle [...] [...] [...] [...] 1 inherits: \nastavzakladnifont OPT OPT OPT OPT 2 rm ss tt mm hw cg 3 tf bf it sl bi bs 4 vse NUMMER
\showglyphs
\showgridsnapping
\showhelp {...} [...] 1 TEXT 2 REFERENCE
\showhyphenationtrace [...] [...] 1 SPRACHE OPT 2 TEXT
\showhyphens {...} * TEXT
\showchardata {...} * TEXT
\showcharratio {...} * TEXT
\showinjector [...] * NAME OPT
\showjustification
\showkerning {...} * TEXT
\showlayoutcomponents
\showligature {...} * TEXT
\showligatures [...] * FONT
\showlogcategories
\showmargins
\showmessage {...} {...} {..., ...} 1 NAME 2 NAME NUMMER 3 TEXT
\showminimalbaseline

\shownextbox \ ¹ ... {\ ² ...} 1 CSNAME 2 CONTENT
\showotfcomposition {\ ¹ ...} {\ ² ...} {\ ³ ...} 1 FONT 2 -1 1 +1 l2r r2l 3 TEXT
\showparentchain \ ¹ ... {\ ² ...} 1 CSNAME 2 NAME
\showsetupsdefinition [...] * NAME
\showtimer {\ [*] ...} * TEXT
\showtokens [... [*] ...] * NAME
\showtrackers
\showvalue {\ [*] ...} * NAME
\showvariable {\ ¹ ...} {\ ² ...} 1 NAME 2 KEY
\showwarning {\ ¹ ...} {\ ² ...} {\ ³ ...,...} 1 NAME 2 NAME NUMBER 3 TEXT
\schovejbloky [..., ¹ ...] [..., ² ...] 1 NAME 2 NAME OPT
\simplealignedbox {\ ¹ ...} {\ ² ...} {\ ³ ...} 1 DIMENSION 2 vlevo vpravo nastred flushleft flushright uvnitr vnejsi 3 CONTENT
\simplealignedboxplus {\ ¹ ...} {\ ² ...} {\ ³ ...} {\ ⁴ ...} 1 DIMENSION 2 vlevo vpravo nastred flushleft flushright uvnitr vnejsi 3 TEXT 4 CONTENT
\simplealignedspreadbox {\ ¹ ...} {\ ² ...} {\ ³ ...} 1 DIMENSION 2 vlevo vpravo nastred flushleft flushright uvnitr vnejsi 3 CONTENT
\simplegroupedcommand {\ ¹ ...} {\ ² ...} 1 BEFEHL 2 BEFEHL

<code>\simplereversealignedbox {...} {...} {...}</code> 1 DIMENSION 2 vlevo vpravo nastred flushleft flushright uvnitr vnejsi 3 CONTENT
<code>\simplereversealignedboxplus {...} {...} {...} {...}</code> 1 DIMENSION 2 vlevo vpravo nastred flushleft flushright uvnitr vnejsi 3 TEXT 4 CONTENT
<code>\singalcharacteralign {...} {...}</code> 1 NUMMER 2 NUMMER
<code>\singlebond</code>
<code>\sixthofsixarguments {...} {...} {...} {...} {...} {...}</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT
<code>\sklonene</code>
<code>\sklonenetucne</code>
<code>\slantedface</code>
<code>\slicepages [...]_{OPT} [...]_{OPT} [...]_{OPT}</code> 1 FILE 2 offset = DIMENSION hoffset = DIMENSION voffset = DIMENSION sirka = DIMENSION vyska = DIMENSION n = NUMMER 3 offset = DIMENSION hoffset = DIMENSION voffset = DIMENSION sirka = DIMENSION vyska = DIMENSION n = NUMMER
<code>\sloupec [...]*...]</code> * inherits: \columnbreak
<code>\slovenianNumerals {...}</code> * NUMMER
<code>\sloveniannumerals {...}</code> * NUMMER
<code>\slovo {...}</code> * TEXT
<code>\slovovpravo [...]_{OPT} {...}</code> 1 vpravo DIMENSION 2 CONTENT
<code>\smallbodyfont</code>

$\backslash\text{smallcappedcharacters}$ {...} * NUMBER
$\backslash\text{smallcappedromannumerals}$ {...} * NUMBER
$\backslash\text{smaller}$
$\backslash\text{smallskip}$
$\backslash\text{smash}$ [¹ ...] { ² ...} 1 w h d t ^{OPT} 2 CONTENT
$\backslash\text{smashbox}$... * CSNAME NUMBER
$\backslash\text{smashboxed}$... * CSNAME NUMBER
$\backslash\text{smashedhbox}$ [¹ ...] { ² ...} 1 TEXT ^{OPT} 2 CONTENT
$\backslash\text{smashedvbox}$ [¹ ...] { ² ...} 1 TEXT ^{OPT} 2 CONTENT
$\backslash\text{snaptogrid}$ [¹ ...] \ ² ... { ³ ...} 1 normalni standardni ano striktni tolerantni vrsek spodek obe široky prizpusobive prvni posledni vysoko jedna nizko zadny radek strut box min max nastred math math:radek math:pulradku math:-line math:-halflne NAME 2 CSNAME 3 CONTENT
$\backslash\text{snaptogrid}$ [..., ¹ ...] \ ² ... { ³ ...} 1 inherits: $\backslash\text{define}$ ^{OPT} gridsnapping 2 CSNAME 3 CONTENT
$\backslash\text{someheadnumber}$ [¹ ...] [² ...] 1 ABSCHNITT 2 predchozi aktualni dalsi prvni posledni
$\backslash\text{somekindoftab}$ [..., [*] ...,...] * alternativa = horizontalne ^{OPT} vertikalne sirka = DIMENSION vyska = DIMENSION n = NUMMER m = NUMMER
$\backslash\text{somelocalfloat}$
$\backslash\text{somenamedheadnumber}$ { ¹ ...} { ² ...} 1 ABSCHNITT 2 predchozi aktualni dalsi prvni posledni

$\backslash\text{someplace}$ ¹ {...} ² {...} ³ {...} ⁴ {...} ⁵ {...} ⁶ [...] 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 REFERENCE
$\backslash\text{SORTING}$ [¹ ...] { ² ...} 1 NAME ^{OPT} 2 CONTENT instances: logo
$\backslash\text{logo}$ [¹ ...] { ² ...} 1 NAME ^{OPT} 2 CONTENT
$\backslash\text{spanishNumerals}$ { [*] ...} * NUMBER
$\backslash\text{spanishnumerals}$ { [*] ...} * NUMBER
$\backslash\text{splitatasterisk}$ ¹ ... \ ² ... \ ³ ... 1 TEXT 2 CSNAME 3 CSNAME
$\backslash\text{splitatcolon}$ ¹ ... \ ² ... \ ³ ... 1 TEXT 2 CSNAME 3 CSNAME
$\backslash\text{splitatcolons}$ ¹ ... \ ² ... \ ³ ... 1 TEXT 2 CSNAME 3 CSNAME
$\backslash\text{splitatcomma}$ ¹ ... \ ² ... \ ³ ... 1 TEXT 2 CSNAME 3 CSNAME
$\backslash\text{splitatperiod}$ ¹ ... \ ² ... \ ³ ... 1 TEXT 2 CSNAME 3 CSNAME
$\backslash\text{splitdfrac}$ { ¹ ...} { ² ...} 1 CONTENT 2 CONTENT
$\backslash\text{splitfilename}$ { [*] ...} * FILE
$\backslash\text{splitfrac}$ { ¹ ...} { ² ...} 1 CONTENT 2 CONTENT
$\backslash\text{splitoffbase}$
$\backslash\text{splitofffull}$

<code>\splitoffkind</code>
<code>\splitoffname</code>
<code>\splitoffpath</code>
<code>\splitoffroot</code>
<code>\splitofftokens</code> ^{1.} ... \from ^{2.} ... \to \ ^{3.} ... 1 TEXT 2 TEXT 3 CSNAME
<code>\splitofftype</code>
<code>\splitstring</code> ^{1.} ... \at ^{2.} ... \to \ ^{3.} ... \and \ ^{4.} ... 1 TEXT 2 TEXT 3 CSNAME 4 CSNAME
<code>\spreadhbox</code> ^{1.} ... * CSNAME NUMBER
<code>\sqrt</code> [^{1.} ...] { ^{2.} ...} 1 TEXT <small>OPT</small> 2 CONTENT
<code>\stackrel{1.}{rel}</code> { ^{1.} ...} { ^{2.} ...} 1 CONTENT 2 CONTENT
<code>\stanovcislonaadpisu</code> [^{1.} ...] * ABSCHNITT
<code>\stanovcharakteristikuseznamu</code> [..., ^{1.} ...] [..., ^{2.} ... _{OPT} ,...] 1 LISTE 2 inherits: \nastavseznam
<code>\startalignment</code> [..., ^{1.} ...] ... \stopalignment * inherits: \nastavzarovnani
<code>\startallmodes</code> [..., ^{1.} ...] ... \stopallmodes * NAME
<code>\startATTACHMENT</code> [^{1.} ...] [..., ^{2.} ... _{OPT} ,...] ... \stopATTACHMENT 1 NAME <small>OPT</small> <small>OPT</small> 2 inherits: \setupattachment instances: attachment
<code>\startattachment</code> [^{1.} ...] [..., ^{2.} ... _{OPT} ,...] ... \stopattachment 1 NAME <small>OPT</small> <small>OPT</small> 2 inherits: \setupattachment
<code>\startbar</code> [^{1.} ...] ... \stopbar * NAME
<code>\startbarva</code> [^{1.} ...] ... \stopbarva * COLOR

<code>\startbbordermatrix ... \stopbbordermatrix</code>
<code>\startbitmapimage [...,.*,...] ... \stopbitmapimage</code> <code>* barva = rgb cmyk seda</code> <code> sirka = DIMENSION</code> <code> vyska = DIMENSION</code> <code> x = NUMMER</code> <code> y = NUMMER</code>
<code>\startbordermatrix ... \stopbordermatrix</code>
<code>\startbtxrenderingdefinitions [...] ... \stopbtxrenderingdefinitions</code> <code>* NAME</code>
<code>\startbuffer [...] ... \stopbuffer</code> <code>* NAME</code> <small>OPT</small>
<code>\startBUFFER ... \stopBUFFER</code> <code>instances: hiding</code>
<code>\starthiding ... \stophiding</code>
<code>\startcatcodetable * ... \stopcatcodetable</code> <code>* CSNAME</code>
<code>\startcenteraligned ... \stopcenteraligned</code>
<code>\startcollect ... \stopcollect</code>
<code>\startcollecting ... \stopcollecting</code>
<code>\startcolorintent [...] ... \stopcolorintent</code> <code>* knockout overprint zadny</code>
<code>\startcoloronly [...] ... \stopcoloronly</code> <code>* COLOR</code>
<code>\startcolorset [...] ... \stopcolorset</code> <code>* NAME</code>
<code>\startcolumnspan [...,.*,...] ... \stopcolumnspan</code> <code>* inherits: \setupcolumnspan^{OPT}</code>
<code>\startcombination [...]¹ [...,.*,...]² ... \stopcombination</code> <code>1 NAME</code> <small>OPT</small> <small>OPT</small> <code>2 inherits: \setupcombination</code>
<code>\startcombination [...]¹ [...]² ... \stopcombination</code> <code>1 NAME</code> <small>OPT</small> <small>OPT</small> <code>2 N*M</code>
<code>\startcontextcode ... \stopcontextcode</code>
<code>\startcontextdefinitioncode ... \stopcontextdefinitioncode</code>
<code>\startctxfunction * ... \stopctxfunction</code> <code>* NAME</code>

$\backslash\text{startcctxfunctiondefinition}$ ¹ ... $\backslash\text{stopcctxfunctiondefinition}$ [*] NAME
$\backslash\text{startcurrentcolor}$... $\backslash\text{stopcurrentcolor}$
$\backslash\text{startcurrentlistentrywrapper}$... $\backslash\text{stopcurrentlistentrywrapper}$
$\backslash\text{startdelimited}$ [¹ ...] [² ...] [³ ...,...] ... $\backslash\text{stopdelimited}$ 1 NAME OPT OPT 2 SPRACHE 3 inherits: $\backslash\text{startzuzeni}$
$\backslash\text{startdelimitedtext}$ [¹ ...] [² ...] [³ ...,...] ... $\backslash\text{stopdelimitedtext}$ 1 NAME OPT OPT 2 SPRACHE 3 inherits: $\backslash\text{startzuzeni}$
$\backslash\text{startDELIMITEDTEXT}$ [¹ ...] [² ...,...] ... $\backslash\text{stopDELIMITEDTEXT}$ 1 SPRACHE OPT OPT 2 inherits: $\backslash\text{startzuzeni}$ instances: quotation quote blockquote speech aside
$\backslash\text{startaside}$ [¹ ...] [² ...,...] ... $\backslash\text{stopaside}$ 1 SPRACHE OPT OPT 2 inherits: $\backslash\text{startzuzeni}$
$\backslash\text{startblockquote}$ [¹ ...] [² ...,...] ... $\backslash\text{stopblockquote}$ 1 SPRACHE OPT OPT 2 inherits: $\backslash\text{startzuzeni}$
$\backslash\text{startquotation}$ [¹ ...] [² ...,...] ... $\backslash\text{stopquotation}$ 1 SPRACHE OPT OPT 2 inherits: $\backslash\text{startzuzeni}$
$\backslash\text{startquote}$ [¹ ...] [² ...,...] ... $\backslash\text{stopquote}$ 1 SPRACHE OPT OPT 2 inherits: $\backslash\text{startzuzeni}$
$\backslash\text{startspeech}$ [¹ ...] [² ...,...] ... $\backslash\text{stopspeech}$ 1 SPRACHE OPT OPT 2 inherits: $\backslash\text{startzuzeni}$
$\backslash\text{startdisplaymath}$... $\backslash\text{stopdisplaymath}$
$\backslash\text{startdmath}$... $\backslash\text{stopdmath}$
$\backslash\text{startdocument}$ [... [*] ...] ... $\backslash\text{stopdocument}$ [*] inherits: $\backslash\text{setupdocument}$ ^{OPT}
$\backslash\text{starteffect}$ [[*] ...] ... $\backslash\text{stopeffect}$ [*] NAME
$\backslash\text{startEFFECT}$... $\backslash\text{stopEFFECT}$
$\backslash\text{startelement}$ { ¹ ...} [² ...,...] ... $\backslash\text{stopelement}$ 1 NAME OPT 2 KEY = VALUE

$\backslash\text{startembeddedxtable} [\dots, \dots, \dots, \dots] \dots \backslash\text{stopembeddedxtable}$ \ast inherits: $\backslash\text{setupxtable}$ <small>OPT</small>
$\backslash\text{startembeddedxtable} [\dots] \dots \backslash\text{stopembeddedxtable}$ \ast NAME <small>OPT</small>
$\backslash\text{startexceptions} [\dots] \dots \backslash\text{stopexceptions}$ \ast SPRACHE
$\backslash\text{startexpanded} \dots \backslash\text{stopexpanded}$
$\backslash\text{startexpandedcollect} \dots \backslash\text{stopexpandedcollect}$
$\backslash\text{startextendedcatcodetable} \backslash\dots \dots \backslash\text{stopextendedcatcodetable}$ \ast CSNAME
$\backslash\text{startexternalfigurecollection} [\dots] \dots \backslash\text{stopexternalfigurecollection}$ \ast NAME
$\backslash\text{startfittingpage} [\dots, \dots, \dots, \dots] \dots \backslash\text{stopfittingpage}$ 1 NAME <small>OPT</small> 2 inherits: $\backslash\text{setupfittingpage}$
$\backslash\text{startFITTINGPAGE} [\dots, \dots, \dots, \dots] \dots \backslash\text{stopFITTINGPAGE}$ \ast inherits: $\backslash\text{setupfittingpage}$ <small>OPT</small> instances: TEXpage MPpage
$\backslash\text{startMPpage} [\dots, \dots, \dots, \dots] \dots \backslash\text{stopMPpage}$ \ast inherits: $\backslash\text{setupfittingpage}$ <small>OPT</small>
$\backslash\text{startTEXpage} [\dots, \dots, \dots, \dots] \dots \backslash\text{stopTEXpage}$ \ast inherits: $\backslash\text{setupfittingpage}$ <small>OPT</small>
$\backslash\text{startfixne} [\dots] \dots \backslash\text{stopfixne}$ \ast nizko nastred <small>OPT</small> vysoko nivy implicitni
$\backslash\text{startfloatcombination} [\dots, \dots, \dots, \dots] \dots \backslash\text{stopfloatcombination}$ \ast inherits: $\backslash\text{setupcombination}$ <small>OPT</small>
$\backslash\text{startfloatcombination} [\dots] \dots \backslash\text{stopfloatcombination}$ \ast N*M NAME <small>OPT</small>
$\backslash\text{startFLOATtext} [\dots, \dots, \dots] [\dots, \dots, \dots] \{\dots\} \dots \backslash\text{stopFLOATtext}$ 1 split vzdy vlevo vpravo uvnitr vnejsi <small>OPT</small> zpetnamezera cutspace ivlevo ivpravo naokraj levokraj pravokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective zahlavi upati 2 REFERENCE 3 TEXT instances: chemical figure table intermezzo graphic
$\backslash\text{startfiguretext} [\dots, \dots, \dots] [\dots, \dots, \dots] \{\dots\} \dots \backslash\text{stopfiguretext}$ 1 split vzdy vlevo vpravo uvnitr vnejsi <small>OPT</small> zpetnamezera cutspace ivlevo ivpravo naokraj levokraj pravokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective zahlavi upati 2 REFERENCE 3 TEXT

`\startgraphicstext [...1,...] [...2,...] {...3} ... \stopgraphicstext`

1 split vzdy vľavo vpravo ^{OPT}uvnitr vnější^{OPT} zpetnamezera cutspace ivľavo ivpravo naokraji levýokraj pravýokraj leváhrana praváhrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective zahľavi upati

2 REFERENCE

3 TEXT

`\startchemicaltext [...1,...] [...2,...] {...3} ... \stopchemicaltext`

1 split vzdy vľavo vpravo ^{OPT}uvnitr vnější^{OPT} zpetnamezera cutspace ivľavo ivpravo naokraji levýokraj pravýokraj leváhrana praváhrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective zahľavi upati

2 REFERENCE

3 TEXT

`\startintermezzotext [...1,...] [...2,...] {...3} ... \stopintermezzotext`

1 split vzdy vľavo vpravo ^{OPT}uvnitr vnější^{OPT} zpetnamezera cutspace ivľavo ivpravo naokraji levýokraj pravýokraj leváhrana praváhrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective zahľavi upati

2 REFERENCE

3 TEXT

`\starttabletext [...1,...] [...2,...] {...3} ... \stoptabletext`

1 split vzdy vľavo vprav^{OPT}u vnitř vnější^{OPT} zpetnamezera cutspace ivľavo ivpravo naokraji levýokraj pravýokraj leváhrana praváhrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective zahľavi upati

2 REFERENCE

3 TEXT

`\startfont [...] ... \stopfont`

* FONT ^{OPT}

`\startfontclass [...] ... \stopfontclass`

* kazdy NAME

`\startfontsolution [...] ... \stopfontsolution`

* NAME

`\startframedcell [...,*...,...] ... \stopframedcell`

* inherits: \nastavoramovani^{OPT}

`\startframedcontent [...] ... \stopframedcontent`

* NAME vyp ^{OPT}

`\startframedrow [...,*...,...] ... \stopframedrow`

* inherits: \nastavoramovani^{OPT}

`\startframedtable [...1] [...,2...,...] ... \stopframedtable`

1 NAME ^{OPT} ^{OPT}

2 inherits: \nastavoramovani

`\startgridsnapping [...] ... \stopgridsnapping`

* normalni standardni ano^{OPT}striktni tolerantni vrsek spodek obe široky prizpusobive prvni posledni vysoko jedna nizko zadny radek strut box min max nastred math math:radek math:pulradku math:-line math:-halflne NAME

`\startgridsnapping [...,*...] ... \stopgridsnapping`

* inherits: \definegridsnapping^{OPT}

`\starthboxestohbox ... \stophboxestohbox`

<code>\starthboxregister ... \stophboxregister</code> * CSNAME NUMBER
<code>\startHELP [...] ... \stopHELP</code> * REFERENCE <small>OPT</small> instances: helptext
<code>\starthelptext [...] ... \stophelptext</code> * REFERENCE <small>OPT</small>
<code>\starthhighlight [...] ... \stophighlight</code> * NAME
<code>\starthyphenation [...,*...] ... \stophyphenation</code> * original tex implicitni hyphenate expanded traditional zadny
<code>\startcharacteralign [...] ... \stopcharacteralign</code> * TEXT number->TEXT text->TEXT
<code>\startcheckedfences ... \stopcheckedfences</code>
<code>\startchemical [¹...] [...,²...,³...,...] ... \stopchemical</code> 1 NAME <small>OPT</small> <small>OPT</small> 2 inherits: \setupchemical
<code>\startimath ... \stopimath</code>
<code>\startindentedtext [...] ... \stopindentedtext</code> * NAME
<code>\startINDENTEDTEXT ... \stopINDENTEDTEXT</code>
<code>\startinterakce [...] ... \stopinterakce</code> * skryte NAME
<code>\startinteraktivnimenu [...] ... \stopinteraktivnimenu</code> * NAME
<code>\startinterface ... \stopinterface</code> * vse SPRACHE
<code>\startintertext ... \stopintertext</code>
<code>\startitemgroup [¹...] [...,²...,³...,...] ... \stopitemgroup</code> 1 NAME <small>OPT</small> <small>OPT</small> 2 inherits: \setupitemgroup 3 inherits: \setupitemgroup
<code>\startITEMGROUP [...,¹...,²...,...] ... \stopITEMGROUP</code> 1 inherits: \setupitemgroup <small>OPT</small> 2 inherits: \setupitemgroup instances: itemize
<code>\startitemize [...,¹...,²...,...] ... \stopitemize</code> 1 inherits: \setupitemgroup <small>OPT</small> 2 inherits: \setupitemgroup

\startJScode ¹ ... ² ... ³ ... \stopJScode 1 NAME 2 uses 3 NAME
\startJSreamble ¹ ... ² ... ³ ... \stopJSreamble 1 NAME 2 uzito 3 now later
\startjdina [...] ... \stopjdina * REFERENCE
\startknockout ... \stopknockout
\startkomentarstranky ... \stopkomentarstranky
\startCOMMENT [¹ ...] [... ² ...] ... \stopCOMMENT 1 TEXT OPT 2 inherits: \nastavkomentar instances: comment
\startcomment [¹ ...] [... ² ...] ... \stopcomment 1 TEXT OPT 2 inherits: \nastavkomentar
\startkomponenta [...] ... \stopkomponenta * FILE *
\startkomponenta .* ... \stopkomponenta * FILE *
\startkonectabulky [...] ... \stopkonectabulky * NAME
\startlayout [...] ... \stoplayout * NAME
\startlinealignment [...] ... \stoplinealignment * vlevo nastred vpravo max
\startlinecorrection [...,*...] ... \stoplinecorrection * prazdny inherits: \preskoc OPT
\startlinefiller [¹ ...] [... ² ...] ... \stoplinefiller 1 filler NAME OPT 2 inherits: \setuplinefiller
\startLINENOTE [¹] {... ² } 1 REFERENCE 2 TEXT instances: linenote
\startlinenote [¹] {... ² } 1 REFERENCE 2 TEXT

<pre> \startlinenumbering [...] [...] ... \stoplinenumbering 1 NAME OPT OPT 2 pokračovat = ano ne start = NUMMER krok = NUMMER metoda = stranka prvni dalsi </pre>
<pre> \startlinenumbering [...] [...] ... \stoplinenumbering 1 NAME OPT OPT 2 pokračovat NUMMER </pre>
<pre> \startlinetable ... \stoplinetable </pre>
<pre> \startlinetablebody ... \stoplinetablebody </pre>
<pre> \startlinetablecell [...] [...] ... \stoplinetablecell * inherits: \setuplinetable OPT </pre>
<pre> \startlinetablehead ... \stoplinetablehead </pre>
<pre> \startlocalfootnotes ... \stoplocalfootnotes </pre>
<pre> \startlocalheadsetup ... \stoplocalheadsetup </pre>
<pre> \startlocallinecorrection [...] [...] ... \stoplocallinecorrection * prazdny inherits: \preskoc OPT </pre>
<pre> \startlocalnotes [...] [...] ... \stoplocalnotes * NAME </pre>
<pre> \startlocalsetups [...] [...] ... \stoplocalsetups 1 mrizka OPT 2 NAME </pre>
<pre> \startlocalsetups \stoplocalsetups * NAME </pre>
<pre> \startlua ... \stoplua </pre>
<pre> \startluacode ... \stopluacode </pre>
<pre> \startluaparameterset [...] ... \stopluaparameterset * NAME </pre>
<pre> \startluasetups [...] [...] ... \stopluasetups 1 mrizka OPT 2 NAME </pre>
<pre> \startluasetups \stopluasetups * NAME </pre>
<pre> \startMPclip {...} ... \stopMPclip * NAME </pre>
<pre> \startMPcode {...} ... \stopMPcode * NAME OPT </pre>

* NAME	OPT
--------	-----

* - OPT

```
* reset globalne + OPT
```

* NAME	OPT
--------	-----

```

1      +                                OPT      OPT
2      NAME

```

```
\startMPinitializations ... \stopMPinitializations
```

```

1  NAME                                OPT
2  KEY

```

* NAME

* NAME	OPT
--------	-----

* NUMMER	OPT
----------	-----

* inherits: \setupmarginrule OPT

* NAME	OPT
--------	-----

```
*      reset vse NAME                                OPT
```

* inherits: \setupmathalignment^{OPT}

```
* inherits: \setupmathalignment
```

```
* inherits: \setupmathalignmentOPT
```

```
* inherits: \setupmathcasesOPT
```

```
* inherits: \setupmathcasesOPT
```


$\backslash\text{startmathcases}$ [...] $\backslash\text{stopmathcases}$ * inherits: $\backslash\text{setupmathcases}$ ^{OPT}
$\backslash\text{startMATHMATRIX}$ [...] $\backslash\text{stopMATHMATRIX}$ * inherits: $\backslash\text{setupmathmatrix}$ ^{OPT} instances: matrix mathmatrix
$\backslash\text{startmathmatrix}$ [...] $\backslash\text{stopmathmatrix}$ * inherits: $\backslash\text{setupmathmatrix}$ ^{OPT}
$\backslash\text{startmatrix}$ [...] $\backslash\text{stopmatrix}$ * inherits: $\backslash\text{setupmathmatrix}$ ^{OPT}
$\backslash\text{startmathmode}$... $\backslash\text{stopmathmode}$
$\backslash\text{startmathstyle}$ [...] $\backslash\text{stopmathstyle}$ * obrazovka text script scriptscript cramped uncramped normalni zhustene male velke NAME
$\backslash\text{startmatrices}$ [...] $\backslash\text{stopmatrices}$ * inherits: $\backslash\text{setupmathmatrix}$ ^{OPT}
$\backslash\text{startmaxaligned}$... $\backslash\text{stopmaxaligned}$
$\backslash\text{startmiddlealigned}$... $\backslash\text{stopmiddlealigned}$
$\backslash\text{startmixedcolumns}$ [¹ ...] [² ...] $\backslash\text{stopmixedcolumns}$ 1 NAME ^{OPT} ^{OPT} 2 inherits: $\backslash\text{setupmixedcolumns}$
$\backslash\text{startMIXEDCOLUMNS}$ [...] $\backslash\text{stopMIXEDCOLUMNS}$ * inherits: $\backslash\text{setupmixedcolumns}$ ^{OPT} instances: itemgroupcolumns boxedcolumns
$\backslash\text{startboxedcolumns}$ [...] $\backslash\text{stopboxedcolumns}$ * inherits: $\backslash\text{setupmixedcolumns}$ ^{OPT}
$\backslash\text{startitemgroupcolumns}$ [...] $\backslash\text{stopitemgroupcolumns}$ * inherits: $\backslash\text{setupmixedcolumns}$ ^{OPT}
$\backslash\text{startmode}$ [...] $\backslash\text{stopmode}$ * NAME
$\backslash\text{startmodeset}$ [... ¹ ,...] {... ² } ... $\backslash\text{stopmodeset}$ 1 NAME implicitni 2 CONTENT
$\backslash\text{startmodule}$ [...] $\backslash\text{stopmodule}$ * FILE
$\backslash\text{startmoduletestsection}$... $\backslash\text{stopmoduletestsection}$
$\backslash\text{startmodule}$... $\backslash\text{stopmodule}$ * FILE
$\backslash\text{startnadpis}$ [... ¹ ,...] {... ² } ... $\backslash\text{stopnadpis}$ 1 REFERENCE ^{OPT} 2 TEXT

<p>\startnamedsection [¹...] [²..._{OPT}...] [³..._{OPT}...] ... \stopnamedsection</p> <p>1 ABSCHNITT</p> <p>2 titul = TEXT</p> <p> zalozka = TEXT</p> <p> znaceni = TEXT</p> <p> seznam = TEXT</p> <p> odkaz = REFERENCE</p> <p> vlastnicislo = TEXT</p> <p>3 KEY = VALUE</p>
<p>\startnamedsubformulas [¹...] {²...} ... \stopnamedsubformulas</p> <p>1 + - REFERENCE</p> <p>2 TEXT</p>
<p>\startnaproti ... \stopnaproti</p>
<p>\startnarrower [...*...] ... \stopnarrower</p> <p>* [-+]vlevo [-+]nastred^{PT}[-+]vpravo NUMMER*vlevo NUMMER*nastred NUMMER*vpravo reset reverse</p>
<p>\startNARROWER [...*...] ... \stopNARROWER</p> <p>* [-+]vlevo [-+]nastred^{PT}[-+]vpravo NUMMER*vlevo NUMMER*nastred NUMMER*vpravo reset reverse</p>
<p>\startnegativ ... \stopnegativ</p>
<p>\startnicelyfilledbox [...*_{OPT}...] ... \stopnicelyfilledbox</p> <p>* sirka = DIMENSION</p> <p> vyska = DIMENSION</p> <p> offset = DIMENSION</p> <p> strut = ano ne</p>
<p>\startnointerference ... \stopnointerference</p>
<p>\startnotallmodes [...*...] ... \stopnotallmodes</p> <p>* NAME</p>
<p>\startnotext ... \stopnotext</p>
<p>\startnotmode [...*...] ... \stopnotmode</p> <p>* NAME</p>
<p>\startobrazek [¹] [²] [³..._{OPT}...] ... \stopobrazek</p> <p>1 NAME</p> <p>2 FILE</p> <p>3 inherits: \externiobraz</p>
<p>\startodlozit [[*]...] ... \stopodlozit</p> <p>* [-+]NUMBER _{OPT}</p>
<p>\startodstavec [¹] [²..._{OPT}...] ... \stopodstavec</p> <p>1 NAME _{OPT}</p> <p>2 inherits: \setupparagraph</p>
<p>\startoramovani [¹] [²..._{OPT}...] ... \stoporamovani</p> <p>1 NAME _{OPT}</p> <p>2 inherits: \nastavoramovani</p>
<p>\startFRAMEDTEXT [¹] [²..._{OPT}...] ... \stopFRAMEDTEXT</p> <p>1 vlevo vpravo nastred_{OPT} zadny _{OPT}</p> <p>2 inherits: \setupframedtext</p> <p>instances: framedtext</p>

<pre> \startframedtext [...] [...] ... \stopframedtext 1 vlevo vpravo nastred^{OPT}zadny^{OPT} 2 inherits: \setupframedtext </pre>
<pre> \startoutputstream [...] ... \stopoutputstream * NAME </pre>
<pre> \startoverprint ... \stopoverprint </pre>
<pre> \startpagefigure [...] [...] ... \stoppagefigure 1 FILE^{OPT} 2 offset = implicitni prekryv zadny DIMENSION </pre>
<pre> \startpagegrid [...] [...] ... \stoppagegrid 1 NAME^{OPT} 2 inherits: \setuppagegrid </pre>
<pre> \startpagegridspan [...] [...] ... \stoppagegridspan 1 NAME^{OPT} 2 inherits: \setuppagegridspan </pre>
<pre> \startPAGEGRID [...] ... \stopPAGEGRID * inherits: \setuppagegrid^{OPT} </pre>
<pre> \startpagelayout [...] ... \stoppagelayout * stranka levastranka pravastranka </pre>
<pre> \startpar [...] [...] ... \stoppar 1 NAME^{OPT} 2 inherits: \setupparagraph </pre>
<pre> \startparagraphs [...] ... \stopparagraphs * NAME </pre>
<pre> \startparagraphscell ... \stopparagraphscell </pre>
<pre> \startPARAGRAPHS ... \stopPARAGRAPHS </pre>
<pre> \startPARALLEL ... \stopPARALLEL </pre>
<pre> \startparbuilder [...] ... \stopparbuilder * implicitni oneline basic NAME </pre>
<pre> \startplacefloat [...] [...] [...] ... \stopplacefloat 1 SINGULAR^{OPT} 2 titul = TEXT zalozka = TEXT znaceni = TEXT seznam = TEXT misto = split vzdy vlevo vpravo uvnitr vnejsi zpenamezera cutspace ivlevo ivpravo naokraji levyokraj pravyokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective zhlavi upati odkaz = REFERENCE 3 KEY = VALUE </pre>

```

\startumistiFLOAT [...,\substack{1}{...},...] [...,\substack{2}{...},...] ... \stopumistiFLOAT
1  titul    = TEXT
   zalozka  = TEXT
   znaceni  = TEXT
   seznam   = TEXT
   misto    = split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraj levokraj pravokraj
              levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky
              [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie
              [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde
              effective zahlavi upati
   odkaz    = REFERENCE
2  KEY = VALUE
instances: chemical figure table intermezzo graphic

```

```

\startumistifigure [...,\substack{1}{...},...] [...,\substack{2}{...},...] ... \stopumistifigure
1  titul    = TEXT
   zalozka  = TEXT
   znaceni  = TEXT
   seznam   = TEXT
   misto    = split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraj levokraj pravokraj
              levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky
              [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie
              [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde
              effective zahlavi upati
   odkaz    = REFERENCE
2  KEY = VALUE

```

```

\startumistigraphic [...,\substack{1}{...},...] [...,\substack{2}{...},...] ... \stopumistigraphic
1  titul    = TEXT
   zalozka  = TEXT
   znaceni  = TEXT
   seznam   = TEXT
   misto    = split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraj levokraj pravokraj
              levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky
              [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie
              [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde
              effective zahlavi upati
   odkaz    = REFERENCE
2  KEY = VALUE

```

```

\startumistichemical [...,\substack{1}{...},...] [...,\substack{2}{...},...] ... \stopumistichemical
1  titul    = TEXT
   zalozka  = TEXT
   znaceni  = TEXT
   seznam   = TEXT
   misto    = split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraj levokraj pravokraj
              levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky
              [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie
              [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde
              effective zahlavi upati
   odkaz    = REFERENCE
2  KEY = VALUE

```

```

\startumistiintermezzo [...,\substack{1}{...},...] [...,\substack{2}{...},...] ... \stopumistiintermezzo
1  titul    = TEXT
   zalozka  = TEXT
   znaceni  = TEXT
   seznam   = TEXT
   misto    = split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraj levokraj pravokraj
              levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky
              [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie
              [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde
              effective zahlavi upati
   odkaz    = REFERENCE
2  KEY = VALUE

```

```

\startumistitable [...,\1...,...] [...,\2...,...] ... \stopumistitable
1  titul    = TEXT          OPT          OPT
   zalozka  = TEXT
   znaceni  = TEXT
   seznam   = TEXT
   misto    = split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraj levokraj pravokraj
             levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky
             [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie
             [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde
             effective zahlavi upati
   odkaz    = REFERENCE
2  KEY     = VALUE

```

```

\startplacepairedbox [...,\1...] [...,\2...,...] ... \stopplacepairedbox
1  NAME          OPT
2  inherits: \setuppairedbox

```

```

\startumistiPAIREDBOX [...,\*...,...] ... \stopumistiPAIREDBOX
*  inherits: \setuppairedbox          OPT
instances: legend

```

```

\startumistilegend [...,\*...,...] ... \stopumistilegend
*  inherits: \setuppairedbox          OPT

```

```

\startpolozka [...,\*...,...] ... \stoppolozka
*  REFERENCE          OPT

```

```

\startPOPIS [...,\*...,...] ... \stopPOPIS
*  titul    = TEXT          OPT
   zalozka  = TEXT
   seznam   = TEXT
   odkaz    = REFERENCE

```

```

\startPOPIS [...,\1...,...] {\2...} ... \stopPOPIS
1  REFERENCE          OPT          OPT
2  TEXT

```

```

\startpositioning [...,\1...] [...,\2...,...] ... \stoppositioning
1  NAME          OPT          OPT
2  inherits: \nastavumistovani

```

```

\startpositionoverlay {...} ... \stoppositionoverlay
*  NAME

```

```

\startpositiv ... \stoppositiv

```

```

\startpozadi [...,\*...,...] ... \stoppozadi
*  inherits: \nastavpozadi

```

```

\startPOZADI [...,\*...,...] ... \stopPOZADI
*  inherits: \nastavpozadi
instances: pozadi

```

```

\startNOTE [...,\*...,...] ... \stopNOTE
*  REFERENCE          OPT
instances: footnote endnote

```

```

\startNOTE [...,\*...,...] ... \stopNOTE
*  titul    = TEXT          OPT
   zalozka  = TEXT
   seznam   = TEXT
   odkaz    = REFERENCE
instances: footnote endnote

```

<pre> \startendnote [...,*,...] ... \stopendnote * titul = TEXT OPT zalozka = TEXT seznam = TEXT odkaz = REFERENCE </pre>
<pre> \startfootnote [...,*,...] ... \stopfootnote * titul = TEXT OPT zalozka = TEXT seznam = TEXT odkaz = REFERENCE </pre>
<pre> \startendnote [...,*,...] ... \stopendnote * REFERENCE OPT </pre>
<pre> \startfootnote [...,*,...] ... \stopfootnote * REFERENCE OPT </pre>
<pre> \startprekryv ... \stopprekryv </pre>
<pre> \startprocessassignmentcommand [...,*,...] ... \stopprocessassignmentcommand * KEY = VALUE </pre>
<pre> \startprocessassignmentlist [...,*,...] ... \stopprocessassignmentlist * KEY = VALUE </pre>
<pre> \startprocesscommacommand [...,*,...] ... \stopprocesscommacommand * BEFEHL </pre>
<pre> \startprocesscommalist [...,*,...] ... \stopprocesscommalist * BEFEHL </pre>
<pre> \startprodukt [...] ... \stopprodukt * FILE * </pre>
<pre> \startprodukt *... ... \stopprodukt * FILE * </pre>
<pre> \startprojekt [...] ... \stopprojekt * FILE * </pre>
<pre> \startprojekt *... ... \stopprojekt * FILE * </pre>
<pre> \startprostredi [...] ... \stopprostredi * FILE * </pre>
<pre> \startprostredi *... ... \stopprostredi * FILE * </pre>
<pre> \startprotectedcolors ... \stopprotectedcolors </pre>
<pre> \startpublikace [.1.] [...,*2,...] ... \stoppublikace 1 NAME OPT OPT 2 tag = REFERENCE category = TEXT k = REFERENCE t = TEXT </pre>

\startradek [...] * REFERENCE
\startLINES [...,*,...] ... \stopLINES * inherits: \nastavrakky instances: lines
\startlines [...,*,...] ... \stoplines * inherits: \nastavrakky
\startrandomized ... \stoprandomized
\startrawsetups [...] [...] ... \stoprawsetups 1 mrizka OPT 2 NAME
\startrawsetups * ... \stoprawsetups * NAME
\startreadingfile ... \stopreadingfile
\startregime [...] ... \stopregime * inherits: \enableregime
\startregister [...] [...] [...] [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 TEXT 4 TEXT PROCESSOR->TEXT 5 INDEX
\startreusableMPgraphic {...} {...} ... \stopreusableMPgraphic 1 NAME OPT 2 KEY
\startrovnice [...,*,...] ... \stoprovnice * zhustene tight nastred ^{OPT} ramecek podlehloubky radek pulradku -radek -pulradku inherits: \nastavzakladnifont
\startrovnice [...,*,...] ... \stoprovnice * volba = zhustene ^{OPT} tight nastred ramecek podlehloubky radek pulradku -radek -pulradku inherits: \nastavzakladnifont marginalie = ano ne standardni DIMENSION mrizka = inherits: \snaptogrid
\startFORMULAformula [...,*,...] ... \stopFORMULAformula * zhustene tight nastred ^{OPT} ramecek podlehloubky radek pulradku -radek -pulradku inherits: \nastavzakladnifont instances: sp sd mp md
\startmdformula [...,*,...] ... \stopmdformula * zhustene tight nastred ^{OPT} ramecek podlehloubky radek pulradku -radek -pulradku inherits: \nastavzakladnifont
\startmpformula [...,*,...] ... \stopmpformula * zhustene tight nastred ^{OPT} ramecek podlehloubky radek pulradku -radek -pulradku inherits: \nastavzakladnifont
\startsdfformula [...,*,...] ... \stopsdfformula * zhustene tight nastred ^{OPT} ramecek podlehloubky radek pulradku -radek -pulradku inherits: \nastavzakladnifont
\startspformula [...,*,...] ... \stopspformula * zhustene tight nastred ^{OPT} ramecek podlehloubky radek pulradku -radek -pulradku inherits: \nastavzakladnifont

\startrozbalene ... \stoprozbalene	
\startscript [...] ... \stopscript * hangul hanzi nihongo ethiopic thai test NAME	
\startsectionblock [...] [...] ... \stopsectionblock 1 NAME OPT 2 zalozka = TEXT inherits: \nastavbloksekce	
\startsectionblockenvironment [...] ... \stopsectionblockenvironment * NAME	
\startSECTIONBLOCK [...] ... \stopSECTIONBLOCK * zalozka = TEXT OPT inherits: \nastavbloksekce instances: frontmatter bodymatter appendices backmatter	
\startappendices [...] ... \stopappendices * zalozka = TEXT OPT inherits: \nastavbloksekce	
\startbackmatter [...] ... \stopbackmatter * zalozka = TEXT OPT inherits: \nastavbloksekce	
\startbodymatter [...] ... \stopbodymatter * zalozka = TEXT OPT inherits: \nastavbloksekce	
\startfrontmatter [...] ... \stopfrontmatter * zalozka = TEXT OPT inherits: \nastavbloksekce	
\startsectionlevel [...] [...] [...] ... \stopsectionlevel 1 NAME OPT OPT OPT 2 titul = TEXT zalozka = TEXT znaceni = TEXT seznam = TEXT odkaz = REFERENCE vlastnicislo = TEXT 3 KEY = VALUE	
\startSECTION [...] [...] ... \stopSECTION 1 titul = TEXT OPT OPT zalozka = TEXT znaceni = TEXT seznam = TEXT odkaz = REFERENCE vlastnicislo = TEXT 2 KEY = VALUE instances: part chapter section subsection subsubsection subsubsubsection subsubsubsubsection title subject subsubject subsubsubject subsubsubsubject subsubsubsubsubject	
\startchapter [...] [...] ... \stopchapter 1 titul = TEXT OPT OPT zalozka = TEXT znaceni = TEXT seznam = TEXT odkaz = REFERENCE vlastnicislo = TEXT 2 KEY = VALUE	

`\startpart [...,\u1...\u2...] ... \stoppart`

1 titul = TEXT OPT
zalozka = TEXT
znaceni = TEXT
seznam = TEXT
odkaz = REFERENCE
vlastnicislo = TEXT
2 KEY = VALUE

`\startsection [...,\u1...\u2...] ... \stopsection`

1 titul = TEXT OPT OPT
zalozka = TEXT
znaceni = TEXT
seznam = TEXT
odkaz = REFERENCE
vlastnicislo = TEXT
2 KEY = VALUE

`\startsubject [...,\u1...\u2...] ... \stopsubject`

1 titul = TEXT OPT OPT
zalozka = TEXT
znaceni = TEXT
seznam = TEXT
odkaz = REFERENCE
vlastnicislo = TEXT
2 KEY = VALUE

`\startsubsection [...,\u1...\u2...] ... \stopsubsection`

1 titul = TEXT OPT OPT
zalozka = TEXT
znaceni = TEXT
seznam = TEXT
odkaz = REFERENCE
vlastnicislo = TEXT
2 KEY = VALUE

`\startsubsubject [...,\u1...\u2...] ... \stopsubsubject`

1 titul = TEXT OPT OPT
zalozka = TEXT
znaceni = TEXT
seznam = TEXT
odkaz = REFERENCE
vlastnicislo = TEXT
2 KEY = VALUE

`\startsubsubsection [...,\u1...\u2...] ... \stopsubsubsection`

1 titul = TEXT OPT OPT
zalozka = TEXT
znaceni = TEXT
seznam = TEXT
odkaz = REFERENCE
vlastnicislo = TEXT
2 KEY = VALUE

`\startsubsubsubject [...,\u1...\u2...] ... \stopsubsubsubject`

1 titul = TEXT OPT OPT
zalozka = TEXT
znaceni = TEXT
seznam = TEXT
odkaz = REFERENCE
vlastnicislo = TEXT
2 KEY = VALUE

`\startsubsubsubsection [...,\u1...\u2...] ... \stopsubsubsubsection`

1 titul = TEXT OPT OPT
zalozka = TEXT
znaceni = TEXT
seznam = TEXT
odkaz = REFERENCE
vlastnicislo = TEXT
2 KEY = VALUE

`\startsubsubsubsubject [...,\overset{1}{=},...] [...,\overset{2}{=},...] ... \stopsubsubsubsubject`

1 titul = TEXT
 zalozka = TEXT
 znaceni = TEXT
 seznam = TEXT
 odkaz = REFERENCE
 vlastnicislo = TEXT
 2 KEY = VALUE

`\startsubsubsubsubsection [...,\overset{1}{=},...] [...,\overset{2}{=},...] ... \stopsubsubsubsubsection`

1 titul = TEXT
 zalozka = TEXT
 znaceni = TEXT
 seznam = TEXT
 odkaz = REFERENCE
 vlastnicislo = TEXT
 2 KEY = VALUE

`\startsubsubsubsubsubject [...,\overset{1}{=},...] [...,\overset{2}{=},...] ... \stopsubsubsubsubsubject`

1 titul = TEXT
 zalozka = TEXT
 znaceni = TEXT
 seznam = TEXT
 odkaz = REFERENCE
 vlastnicislo = TEXT
 2 KEY = VALUE

`\starttitle [...,\overset{1}{=},...] [...,\overset{2}{=},...] ... \stoptitle`

1 titul = TEXT
 zalozka = TEXT
 znaceni = TEXT
 seznam = TEXT
 odkaz = REFERENCE
 vlastnicislo = TEXT
 2 KEY = VALUE

`\startsetups [...]\overset{1}{=}[...] [...]\overset{2}{=}[...] ... \stopsetups`

1 mrizka
 2 NAME

`\startsetups ... \stopsetups`

* NAME

`\startshift [...] ... \stopshift`

* NAME

`\startsidebar [...]\overset{1}{=}[...] [...]\overset{2}{=}[...] ... \stopsidebar`

1 NAME
 2 inherits: \setupsidebar

`\startsimplecolumns [...,\overset{*}{=},...] ... \stopsimplecolumns`

* inherits: \setsimplecolumnsize

`\startsloupce [...,\overset{*}{=},...] ... \stopsloupce`

* inherits: \nastavsloupce

`\startspecialitem [...]\overset{1}{=}[...] [...]\overset{2}{=}[...] ... \stopspecialitem`

1 polozka
 2 REFERENCE

`\startspecialitem [...] ... \stopspecialitem`

* pod pol

$\backslash\text{startspecialitem}$ [¹ ...] { ² ...} ... $\backslash\text{stopspecialitem}$ 1 sym rozsah mar 2 TEXT
$\backslash\text{startsplitformula}$... $\backslash\text{stopsplitformula}$
$\backslash\text{startspread}$... $\backslash\text{stopspread}$
$\backslash\text{start}$ [[*] ...] ... $\backslash\text{stop}$ * NAME OPT
$\backslash\text{startSTARTSTOP}$... $\backslash\text{stopSTARTSTOP}$
$\backslash\text{startstaticMPfigure}$ { [*] ...} ... $\backslash\text{stopstaticMPfigure}$ * NAME
$\backslash\text{startstaticMPgraphic}$ { ¹ ...} { ² ...; ³ ...} ... $\backslash\text{stopstaticMPgraphic}$ 1 NAME 2 KEY OPT
$\backslash\text{STARTSTOP}$ { [*] ...} * CONTENT
$\backslash\text{startstrictinspectnextcharacter}$... $\backslash\text{stopstrictinspectnextcharacter}$
$\backslash\text{startstructurepageregister}$ [¹ ...] [² ...] [..., ³ ...,...] [..., ⁴ ...,...] OPT 1 NAME 2 NAME 3 popisek = NAME keys = TEXT PROCESSOR->TEXT entries = TEXT PROCESSOR->TEXT keys:1 = TEXT keys:2 = TEXT keys:3 = TEXT entries:1 = TEXT entries:2 = TEXT entries:3 = TEXT alternativa = TEXT 4 KEY = VALUE
$\backslash\text{startstyle}$ [..., [*] ...,...] ... $\backslash\text{stopstyle}$ * inherits: \setupstyle
$\backslash\text{startstyle}$ [[*] ...] ... $\backslash\text{stopstyle}$ * NAME FONT
$\backslash\text{startSTYLE}$... $\backslash\text{stopSTYLE}$
$\backslash\text{startsubformulas}$ [..., [*] ...,...] ... $\backslash\text{stopsubformulas}$ OPT * + - REFERENCE
$\backslash\text{startsubjectlevel}$ [¹ ...] [..., ² ...,...] [..., ³ ...,...] ... $\backslash\text{stopsubjectlevel}$ OPT OPT OPT 1 NAME 2 titul = TEXT zalozka = TEXT znaceni = TEXT seznam = TEXT odkaz = REFERENCE vlastnicislo = TEXT 3 KEY = VALUE
$\backslash\text{startsubsentence}$... $\backslash\text{stopsubsentence}$

<code>\startsubstack ... \stopsubstack</code>
<code>\startsymbolset [...] ... \stopsymbolset</code> <code>* NAME</code>
<code>\startTABLE [...,..[*]...,...] ... \stopTABLE</code> <code>* inherits: \setupTABLE^{OPT}</code>
<code>\startTABLEbody [...,..[*]...,...] ... \stopTABLEbody</code> <code>* inherits: \setupTABLE^{OPT}</code>
<code>\startTABLEfoot [...,..[*]...,...] ... \stopTABLEfoot</code> <code>* inherits: \setupTABLE^{OPT}</code>
<code>\startTABLEhead [...,..[*]...,...] ... \stopTABLEhead</code> <code>* inherits: \setupTABLE^{OPT}</code>
<code>\startTABLEnext [...,..[*]...,...] ... \stopTABLEnext</code> <code>* inherits: \setupTABLE^{OPT}</code>
<code>\starttabelator [/.¹/] [...,..²...,...] ... \stoptabelator</code> <code>1 TEMPLATE^{OPT}</code> <code>2 inherits: \nastvtabelaci</code>
<code>\startTABULATE [.¹] [...,..²...,...] ... \stopTABULATE</code> <code>1 NAME^{OPT}</code> <code>2 inherits: \nastvtabelaci</code> <code>instances: legend fact</code>
<code>\startfact [.¹] [...,..²...,...] ... \stopfact</code> <code>1 NAME^{OPT}</code> <code>2 inherits: \nastvtabelaci</code>
<code>\startlegend [.¹] [...,..²...,...] ... \stoplegend</code> <code>1 NAME^{OPT}</code> <code>2 inherits: \nastvtabelaci</code>
<code>\starttabulatehead [...,..[*]] ... \stoptabulatehead</code> <code>* NAME^{OPT}</code>
<code>\starttabulatetail [...,..[*]] ... \stoptabulatetail</code> <code>* NAME^{OPT}</code>
<code>\startTABULATION [.¹] [...,..²...,...] ... \stopTABULATION</code> <code>1 NAME^{OPT}</code> <code>2 inherits: \setuptabulation</code>
<code>\starttabulka [/.¹/] [...,..²...,...] ... \stoptabulka</code> <code>1 TEMPLATE^{OPT}</code> <code>2 inherits: \nastvtabulky</code>
<code>\starttabulka [.¹] [...,..²...,...] ... \stoptabulka</code> <code>1 NAME^{OPT}</code> <code>2 inherits: \nastvtabulky</code>
<code>\starttabulky [/.[*]/] ... \stoptabulky</code> <code>* TEMPLATE</code>

`\starttabulky [...]` ... `\stoptabulky`

* NAME

`\starttexcode ... \stoptexcode`

`\starttexdefinition` ¹... ²... ³... ⁴... ⁵... ⁶... ⁷... `\stoptexdefinition`

1 spaces nospaces

OPT

OPT

OPT

OPT

OPT

OPT

2 globalne

3 unexpanded

4 expanded

5 singleempty doubleempty tripleempty quadrupleempty quintupleempty sextupleempty singleargument doubleargument

tripleargument quadrupleargument quintupleargument sextupleargument

6 NAME

7 TEMPLATE

`\starttext ... \stoptext`

`\starttextbackground` [¹...] [²...²...²...] ... `\stoptextbackground`

1 NAME

OPT

2 inherits: `\setuptextbackground`

`\starttextbackgroundmanual ... \stoptextbackgroundmanual`

`\startTEXTBACKGROUND` [¹...^{*}...^{*}...^{*}...] ... `\stopTEXTBACKGROUND`

* inherits: `\setuptextbackground` ^{OPT}

`\starttextcolor [...]` ... `\stoptextcolor`

* COLOR

`\starttextcolorintent ... \stoptextcolorintent`

`\starttextflow [...]` ... `\stoptextflow`

* NAME

`\starttextnapovedy` [^{*}...] ... `\stoptextnapovedy`

* REFERENCE

OPT

`\starttextovalinka {...}` ... `\stoptextovalinka`

* TEXT

`\startLABELtext` [¹...] [²...] ... `\stopLABELtext`

OPT

1 SPRACHE

2 KEY

instances: head label mathlabel taglabel unit operator prefix suffix btxlabel

`\startbtxlabeltext` [¹...] [²...] ... `\stopbtxlabeltext`

1 SPRACHE

OPT

2 KEY

`\startheadtext` [¹...] [²...] ... `\stopheadtext`

OPT

1 SPRACHE

2 KEY

`\startlabeltext` [¹...] [²...] ... `\stoplabeltext`

OPT

1 SPRACHE

2 KEY

`\startmathlabeltext` [¹...] [²...] ... `\stopmathlabeltext`

OPT

1 SPRACHE

2 KEY

$\backslash\text{startoperator}\textit{text} [\dots]^{1} [\dots]^{2} \dots \backslash\text{stopoperator}\textit{text}$ 1 SPRACHE OPT 2 KEY
$\backslash\text{startprefix}\textit{text} [\dots]^{1} [\dots]^{2} \dots \backslash\text{stopprefix}\textit{text}$ 1 SPRACHE OPT 2 KEY
$\backslash\text{startsuffix}\textit{text} [\dots]^{1} [\dots]^{2} \dots \backslash\text{stopsuffix}\textit{text}$ 1 SPRACHE OPT 2 KEY
$\backslash\text{starttaglabel}\textit{text} [\dots]^{1} [\dots]^{2} \dots \backslash\text{stoptaglabel}\textit{text}$ 1 SPRACHE OPT 2 KEY
$\backslash\text{startunit}\textit{text} [\dots]^{1} [\dots]^{2} \dots \backslash\text{stopunit}\textit{text}$ 1 SPRACHE OPT 2 KEY
$\backslash\text{starttokens} [\dots] \dots \backslash\text{stoptokens}$ * NAME
$\backslash\text{starttransparent} [\dots] \dots \backslash\text{stoptransparent}$ * COLOR
$\backslash\text{starttypescript} [\dots]^{1}, \dots [\dots]^{2}, \dots [\dots]^{3}, \dots \backslash\text{stoptypescript}$ 1 serif sans mono math handwriting calligraphy OPT 2 NAME 3 size jmeno
$\backslash\text{starttypescriptcollection} [\dots] \dots \backslash\text{stoptypescriptcollection}$ * NAME
$\backslash\text{startTYPING} [\dots]^{*}, \dots \backslash\text{stopTYPING}$ * inherits: $\backslash\text{nastavopis}$ OPT instances: typing LUA MP PARSEDXML TEX XML
$\backslash\text{startTYPING} [\dots]^{*}, \dots \backslash\text{stopTYPING}$ * pokračovat OPT instances: typing LUA MP PARSEDXML TEX XML
$\backslash\text{startLUA} [\dots]^{*}, \dots \backslash\text{stopLUA}$ * pokračovat OPT
$\backslash\text{startMP} [\dots]^{*}, \dots \backslash\text{stopMP}$ * pokračovat OPT
$\backslash\text{startPARSEDXML} [\dots]^{*}, \dots \backslash\text{stopPARSEDXML}$ * pokračovat OPT
$\backslash\text{startTEX} [\dots]^{*}, \dots \backslash\text{stopTEX}$ * pokračovat OPT
$\backslash\text{starttyping} [\dots]^{*}, \dots \backslash\text{stoptyping}$ * pokračovat OPT
$\backslash\text{startXML} [\dots]^{*}, \dots \backslash\text{stopXML}$ * pokračovat OPT

<pre> \startLUA [...,*=...,...] ... \stopLUA * inherits: \nastavopis^{OPT} </pre>
<pre> \startMP [...,*=...,...] ... \stopMP * inherits: \nastavopis^{OPT} </pre>
<pre> \startPARSEDXML [...,*=...,...] ... \stopPARSEDXML * inherits: \nastavopis^{OPT} </pre>
<pre> \startTEX [...,*=...,...] ... \stopTEX * inherits: \nastavopis^{OPT} </pre>
<pre> \starttyping [...,*=...,...] ... \stoptyping * inherits: \nastavopis^{OPT} </pre>
<pre> \startXML [...,*=...,...] ... \stopXML * inherits: \nastavopis^{OPT} </pre>
<pre> \startumistirovnici [...,*=...,...] ... \stopumistirovnici * titul = TEXT OPT * suffix = TEXT * odkaz = + - REFERENCE </pre>
<pre> \startumistirovnici [...,*=...,...] ... \stopumistirovnici * + - REFERENCE OPT </pre>
<pre> \startuniqueMPgraphic {...} {...,²...,...} ... \stopuniqueMPgraphic 1 NAME OPT 2 KEY </pre>
<pre> \startuniqueMPpagegraphic {...} {...,²...,...} ... \stopuniqueMPpagegraphic 1 NAME OPT 2 KEY </pre>
<pre> \startusableMPgraphic {...} {...,²...,...} ... \stopusableMPgraphic 1 NAME OPT 2 KEY </pre>
<pre> \startuseMPgraphic {...} {...,²...,...} ... \stopuseMPgraphic 1 NAME OPT 2 KEY </pre>
<pre> \startusemathstyleparameter \... ... \stopusemathstyleparameter * CSNAME </pre>
<pre> \startusingbtxs specification [...*] ... \stopusingbtxs specification * NAME </pre>
<pre> \startuzky [...¹] [...,*=...,...²] ... \stopuzky 1 NAME OPT OPT 2 inherits: \nastavuzeni </pre>
<pre> \startuzky [...,*=...,...¹] [...,²...,...] ... \stopuzky 1 inherits: \nastavuzeni^{OPT} OPT 2 [-+]vlevo [-+]nastred [-+]vpravo NUMMER*vlevo NUMMER*nastred NUMMER*vpravo reset reverse </pre>
<pre> \startuzky [...¹] [...,²...,...] ... \stopuzky 1 NAME OPT OPT 2 [-+]vlevo [-+]nastred [-+]vpravo NUMMER*vlevo NUMMER*nastred NUMMER*vpravo reset reverse </pre>

$\backslash\text{startvboxregister}$ \dots \dots $\backslash\text{stopvboxregister}$ \ast CSNAME NUMMER
$\backslash\text{startvboxtohbox}$ \dots $\backslash\text{stopvboxtohbox}$
$\backslash\text{startvboxtohboxseparator}$ \dots $\backslash\text{stopvboxtohboxseparator}$
$\backslash\text{startviewerlayer}$ [\dots] \dots $\backslash\text{stopviewerlayer}$ \ast NAME
$\backslash\text{startVIEWERLAYER}$ \dots $\backslash\text{stopVIEWERLAYER}$
$\backslash\text{startvisici}$ [$\dots,\dots,\overset{1}{\dots},\dots$] $\{\dots\}$ \dots $\backslash\text{stopvisici}$ 1 vzdalenost = DIMENSION n = NUMMER misto = vlevo vpravo 2 CONTENT
$\backslash\text{startvisici}$ [$\overset{1}{\dots}$] $\{\overset{2}{\dots}\}$ \dots $\backslash\text{stopvisici}$ 1 vlevo vpravo OPT 2 CONTENT
$\backslash\text{startvtopregister}$ \dots \dots $\backslash\text{stopvtopregister}$ \ast CSNAME NUMMER
$\backslash\text{startVYCET}$ [$\dots,\dots,\overset{\ast}{\dots},\dots$] \dots $\backslash\text{stopVYCET}$ \ast titul = TEXT OPT zalozka = TEXT seznam = TEXT odkaz = REFERENCE
$\backslash\text{startVYCET}$ [$\dots,\overset{1}{\dots},\dots$] $\{\overset{2}{\dots}\}$ \dots $\backslash\text{stopVYCET}$ 1 REFERENCE OPT OPT 2 TEXT
$\backslash\text{startxcell}$ [$\overset{1}{\dots}$] [$\dots,\dots,\overset{2}{\dots},\dots$] \dots $\backslash\text{stopxcell}$ 1 NAME OPT OPT 2 nx = NUMMER ny = NUMMER nc = NUMMER nr = NUMMER inherits: \setupxtable
$\backslash\text{startxcellgroup}$ [$\overset{1}{\dots}$] [$\dots,\dots,\overset{2}{\dots},\dots$] \dots $\backslash\text{stopxcellgroup}$ 1 NAME OPT OPT 2 inherits: \setupxtable
$\backslash\text{startxgroup}$ [$\overset{1}{\dots}$] [$\dots,\dots,\overset{2}{\dots},\dots$] \dots $\backslash\text{stopxgroup}$ 1 NAME OPT OPT 2 inherits: \setupxtable
$\backslash\text{startxmldisplayverbatim}$ [\dots] \dots $\backslash\text{stopxmldisplayverbatim}$ \ast NAME
$\backslash\text{startxmllineverbatim}$ [\dots] \dots $\backslash\text{stopxmllineverbatim}$ \ast NAME
$\backslash\text{startxmlraw}$ \dots $\backslash\text{stopxmlraw}$


```
1  mrizka                                OPT
2  NAME
```

* NAME

```
1  NAME          OPT          OPT
2  inherits: \setupxtable
```

```
1 NAME OPT OPT
2 inherits: \setupxtable
```

```
* inherits: \setupxtableOPT
```

```
* inherits: \setupxtable OPT
```

* NAME	OPT
--------	-----

```
* inherits: \setupxtable OPT
```

* NAME	OPT
--------	-----

```
* inherits: \setupxtable OPT
```

* NAME	OPT
--------	-----

```
* inherits: \setupxtable OPT
```

* NAME	OPT
--------	-----

```
* inherits: \setupxtableOPT
```

* NAME	OPT
--------	-----

* NAME

\startzhustene [...] ... \stopzhustene * prazdny ^{OPT}
\startzlom [¹ ...] [² ...,...] ... \stopzlom 1 NAME ^{OPT} 2 inherits: \nastavupravu
\startMAKEUPzlom [[*] ...,...] ... \stopMAKEUPzlom * inherits: \nastavupravu ^{OPT} instances: standard page text middle
\startmiddlezlom [[*] ...,...] ... \stopmiddlezlom * inherits: \nastavupravu ^{OPT}
\startpagezlom [[*] ...,...] ... \stoppagezlom * inherits: \nastavupravu ^{OPT}
\startstandardzlom [[*] ...,...] ... \stopstandardzlom * inherits: \nastavupravu ^{OPT}
\starttextzlom [[*] ...,...] ... \stoptextzlom * inherits: \nastavupravu ^{OPT}
\stopLINENOTE [...] * REFERENCE instances: linenote
\stoplinenote [...] * REFERENCE
\stopradek [...] * REFERENCE
\stopregister [¹ ...] [² ...] 1 NAME 2 NAME
\stopstructurepageregister [¹ ...] [² ...] 1 NAME 2 NAME
\strana [..., [*] ...] * inherits: \ ^{OPT} pagebreak
\strictdoifelsenextoptional { ¹ ...} { ² ...} 1 TRUE 2 FALSE
\strictdoifnextoptionalelse { ¹ ...} { ² ...} 1 TRUE 2 FALSE
\stripcharacter ¹ ... \from ² ... \to \ ³ ... 1 CHARACTER 2 TEXT 3 CSNAME
\strippedcsname \ [*] ... * CSNAME

<code>\strippedcsname ...</code> <code>* TEXT</code>
<code>\stripspaces \from ... \to ...</code> <code>1 TEXT</code> <code>2 CSNAME</code>
<code>\structurelistuservariable {...}</code> <code>* KEY</code>
<code>\structurenumber</code>
<code>\structuretitle</code>
<code>\structureuservariable {...}</code> <code>* KEY</code>
<code>\structurevariable {...}</code> <code>* KEY</code>
<code>\strut</code>
<code>\strutdp</code>
<code>\strutgap</code>
<code>\strutht</code>
<code>\struthtdp</code>
<code>\struttedbox {...}</code> <code>* CONTENT</code>
<code>\strutwd</code>
<code>\style [...¹...] {...²}</code> <code>1 inherits: \setupstyle</code> <code>2 TEXT</code>
<code>\styleinstance [...]</code> <code>* NAME</code>
<code>\style [...¹] {...²}</code> <code>1 NAME FONT</code> <code>2 TEXT</code>
<code>\STYLE {...}</code> <code>* TEXT</code>
<code>\subpagenumber</code>
<code>\subsentence {...}</code> <code>* CONTENT</code>

<code>\substituteincommalist {...} {...} \...</code> 1 TEXT 2 TEXT 3 CSNAME
<code>\subtractfeature [...]</code> * NAME
<code>\subtractfeature {...}</code> * NAME
<code>\swapcounts \... \...</code> 1 CSNAME 2 CSNAME
<code>\swapdimens \... \...</code> 1 CSNAME 2 CSNAME
<code>\swapface</code>
<code>\swapmacros \... \...</code> 1 CSNAME 2 CSNAME
<code>\swaptypesface</code>
<code>\switchstyleonly [...]</code> * rm ss tt hw cg antikva serif pravidelne sans bezserifu podpora opis strojopis mono rukopisne kaligraficke
<code>\switchstyleonly \...</code> * CSNAME
<code>\switchtocolour [...]</code> * COLOR
<code>\switchtointerlinespace [...¹,...] [...²,...]</code> 1 NAME <small>OPT</small> 2 inherits: \nastavmeziradkovoumezeru
<code>\switchtointerlinespace [...[*],...]</code> * zap vyp reset auto male stredni ^{OPT} Velke NUMMER DIMENSION
<code>\switchtointerlinespace [...]</code> * NAME
<code>\symbol [...¹] [...²]</code> 1 NAME <small>OPT</small> 2 NAME
<code>\symbolreference [...]</code> * REFERENCE
<code>\symbol {...}</code> * NAME
<code>\synctexblockfilename {...}</code> * FILE

<code>\TheNormalizedFontSize</code>
<code>\TransparencyHack</code>
<code>\tabulateautoline</code>
<code>\tabulateautorule</code>
<code>\tabulateline</code>
<code>\tabulaterule</code>
<code>\taggedctxcommand {...}</code> * BEFEHL
<code>\taggedlabeltexts {¹...} {²...} {³...}</code> 1 NAME 2 NAME 3 CONTENT
<code>\tbox {...}</code> * CONTENT
<code>\tecka {...}</code> * CHARACTER
<code>\tecky [...]</code> * NUMMER ^{OPT}
<code>\tecky [...,...[*]...,...]</code> * inherits: \setupperperiods
<code>\tenkalinka</code>
<code>\tenkelinky [...,...[*]...,...]</code> * inherits: \nastavtenkelinky ^{OPT}
<code>\testandsplitstring ¹... \at ²... \to ³... \and ⁴...</code> 1 TEXT 2 TEXT 3 CSNAME 4 CSNAME
<code>\testcolumn [¹...] [²...]</code> 1 NUMMER ^{OPT} 2 DIMENSION
<code>\testfeature {¹...} {²...}</code> 1 NUMMER 2 CONTENT
<code>\testfeatureonce {¹...} {²...}</code> 1 NUMMER 2 CONTENT
<code>\testpage [¹...] [²...]</code> 1 NUMMER ^{OPT} 2 DIMENSION

<pre> \testpageonly [...] [²] 1 NUMBER OPT 2 DIMENSION </pre>
<pre> \testpagesync [...] [²] 1 NUMBER OPT 2 DIMENSION </pre>
<pre> \testtokens [...] * NAME </pre>
<pre> \tex {...} * CONTENT </pre>
<pre> \texdefinition {...} * NAME </pre>
<pre> \texsetup {...} * NAME </pre>
<pre> \TEXTBACKGROUND {...} * CONTENT </pre>
<pre> \textcitation [...,¹...,...] [²] 1 odkaz = REFERENCE alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear pred = BEFEHL po = BEFEHL vlevo = BEFEHL vpravo = BEFEHL inherits: \setupbtx 2 REFERENCE </pre>
<pre> \textcitation [¹] [²] 1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear 2 REFERENCE </pre>
<pre> \textcitation [...,¹...,...] [...,²...,...] 1 odkaz = REFERENCE alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear pred = BEFEHL po = BEFEHL vlevo = BEFEHL vpravo = BEFEHL inherits: \setupbtx 2 KEY = VALUE </pre>
<pre> \textcite [...,¹...,...] [²] 1 odkaz = REFERENCE alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear pred = BEFEHL po = BEFEHL vlevo = BEFEHL vpravo = BEFEHL inherits: \setupbtx 2 REFERENCE </pre>
<pre> \textcite [¹] [²] 1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear 2 REFERENCE </pre>

$\backslash\text{textcite}$ [\dots , \dots ¹ \dots , \dots] [\dots , \dots ² \dots , \dots] 1 odkaz = REFERENCE alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear pred = BEFEHL po = BEFEHL vlevo = BEFEHL vpravo = BEFEHL inherits: \setupbtx 2 KEY = VALUE
$\backslash\text{textcontrolspace}$
$\backslash\text{textflowcollector}$ {...} * NAME
$\backslash\text{textmath}$ {...} * CONTENT
$\backslash\text{textminus}$
$\backslash\text{textnapovedy}$ [\dots] ¹ {...} ² {...} ³ 1 REFERENCE OPT 2 TEXT 3 TEXT
$\backslash\text{textormathchar}$ {...} * NUMMER
$\backslash\text{textovalinka}$ [\dots] ¹ {...} ² 1 vrsek nastred spodek OPT OPT 2 TEXT
$\backslash\text{textplus}$
$\backslash\text{LABELtext}$ {...} * KEY instances: head label mathlabel taglabel unit operator prefix suffix btxlabel
$\backslash\text{btxlabeltext}$ {...} * KEY
$\backslash\text{headtext}$ {...} * KEY
$\backslash\text{labeltext}$ {...} * KEY
$\backslash\text{mathlabeltext}$ {...} * KEY
$\backslash\text{operatortext}$ {...} * KEY
$\backslash\text{prefixtext}$ {...} * KEY
$\backslash\text{suffixtext}$ {...} * KEY

<code>\taglabeltext {...}</code> * KEY
<code>\unittext {...}</code> * KEY
<code>\textvisiblespace</code>
<code>\thainumerals {...}</code> * NUMBER
<code>\thefirstcharacter {...}</code> * TEXT
<code>\thenormalizedbodyfontsize {...}</code> * DIMENSION
<code>\theremainingcharacters {...}</code> * TEXT
<code>\thickspace</code>
<code>\thinspace</code>
<code>\thirddoffivearguments {...} {...} {...} {...} {...}</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT
<code>\thirddoffourarguments {...} {...} {...} {...}</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT
<code>\thirddofsixarguments {...} {...} {...} {...} {...} {...}</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT
<code>\thirddofthreearguments {...} {...} {...}</code> 1 TEXT 2 TEXT 3 TEXT
<code>\thirddofthreeunexpanded {...} {...} {...}</code> 1 TEXT 2 TEXT 3 TEXT
<code>\threedigitrounding {...}</code> * NUMBER
<code>\tibetannumerals {...}</code> * NUMBER

<code>\tightlayer [...]</code> * NAME
<code>\tilde {...}</code> * CHARACTER
<code>\tinyfont</code>
<code>\tlacitko [...¹...²...] {...³} [...]</code> 1 inherits: \setupbutton 2 TEXT 3 REFERENCE
<code>\tlacitkomenu [...¹...²...] {...³} {...}</code> 1 inherits: \setupbutton 2 TEXT 3 REFERENCE
<code>\tlacitkomenu [...¹] [...²...³...] {...⁴} {...}</code> 1 NAME 2 inherits: \nastavinterakcnimenu 3 TEXT 4 REFERENCE
<code>\BUTTON [...¹...²...] {...³} [...]</code> 1 inherits: \setupbutton 2 TEXT 3 REFERENCE instances: button
<code>\tlap {...}</code> * CONTENT
<code>\tloustkacary</code>
<code>\tochar {...}</code> * e:NAME x:NUMMER d:NUMMER s:NUMMER i:NUMMER n:NAME c:NAME u:NAME a:NAME
<code>\tolinenote [...]</code> * REFERENCE
<code>\topbox {...}</code> * CONTENT
<code>\topleftbox {...}</code> * CONTENT
<code>\toplinebox {...}</code> * CONTENT
<code>\toprightbox {...}</code> * CONTENT
<code>\topskippedbox {...}</code> * CONTENT
<code>\tracecatcodetables</code>

\tracedfontname {...} * FONT
\traceoutputroutines
\tracepositions
\transparencycomponents {...} * COLOR
\transparent [¹ ...] { ² ...} 1 COLOR 2 CONTENT
\tref { ¹ ...} { ² ...} [³ ...] 1 TEXT OPT OPT 2 TEXT 3 REFERENCE
\triplebond
\truefilename {...} * FILE
\truefontname {...} * FONT
\ttraggedright
\tucne
\tucnekurzivni
\tucnesklonene
\tvrdamezera
\tvrdemezery
\twodigitrounding {...} * NUMMER
\tx
\txx
\typebuffer [..., ¹ ...] [..., ² ...,...] 1 BUFFER OPT OPT 2 inherits: \nastavopis
\opisBUFFER [..., [*] ...,...] * inherits: \nastavopis ^{FF}
\typedefinedbuffer [¹ ...] [..., ² ...,...] 1 BUFFER OPT 2 inherits: \nastavopis

<code>\typeface</code>
<code>\typeinlinebuffer [...¹,...] [...²,...]</code> 1 BUFFER OPT OPT 2 inherits: \nastavtype
<code>\typescriptone</code>
<code>\typescriptprefix {.*}</code> * NAME
<code>\typescriptthree</code>
<code>\typescripttwo</code>
<code>\typesetbuffer [...¹] [...²,...]</code> 1 * BUFFER OPT OPT 2 inherits: \setupexternalfigure
<code>\typesetfile [...¹] [...²] [...³,...]</code> 1 NAME FILE OPT OPT 2 FILE TEXT 3 inherits: \setupexternalfigure
<code>\uconvertnumber {...¹} {...²}</code> 1 inherits: \konvertujcislo 2 NUMMER
<code>\uedcatcodecommand \...¹ ...² {...³}</code> 1 CSNAME 2 CHARACTER NUMBER 3 BEFEHL
<code>\ukazbarvu [...]</code> * COLOR
<code>\ukazmrizku [...[*],...]</code> * reset spodek vrsek ^{OPT} zadny vse radky ramecek nonumber vpravo vlevo vnejsi sloupce
<code>\ukaznastaveni [...[*],...]</code> * pt bp cm mm dd cc pc ^{OPT} hd nc sp in
<code>\ukazpaletu [...¹] [...²,...]</code> 1 NAME OPT 2 horizontalne vertikalne cislo hodnota jmeno
<code>\ukazpodpery</code>
<code>\ukazpostredizakladnihofontu [...[*],...]</code> * inherits: \nastavzakladnifont
<code>\ukazramecek [...¹,...] [...²,...]</code> 1 vrsek zhlavi text ^{OPT} upati spodek ^{OPT} 2 levahrana levyokraj text pravyyokraj pravahrana
<code>\ukazsadasymbolu [...]</code> * NAME

\backslash ukazskupinubarev [...] ¹ [...] ² ,...] 1 NAME OPT 2 horizontalne vertikalne cislo hodnota jmeno
\backslash ukazupravu [...] [*] * zlom vse boxes ^{OPT} radek glyph fontkern hbox vbox vtop kern glue penalty strut whatsit simple simplehbox simplevbox simplevtop user math kurziva origin reset
\backslash ukazvytisk [...] ¹ ,... [...] ² ,... [...] ³ ,... ^{OPT} 1 inherits: \nastav ^{OPT} velikostpapi ^{OPT} ru 2 inherits: \nastavvelikostpapi ^{OPT} ru 3 inherits: \nastavvzhled
\backslash ukazvzhled [...] [*] ,... 1 pt bp cm mm dd c ^{OPT} pc nd nc sp in
\backslash ukazzakladnifont [...] [*] ,... 1 inherits: \nastavzakladnifont
\backslash umistikombinovanyseznam [...] ¹ [...] ² ,... ^{OPT} 1 LISTE 2 inherits: \nastavseznam
\backslash umistiCOMBINEDLIST [...] [*] ,... ^{OPT} * inherits: \nastavseznam instances: content
\backslash umisticontent [...] [*] ,... ^{OPT} * inherits: \nastavseznam
\backslash umistilokalnipoznamkypodcarou [...] [*] ,... ^{OPT} * inherits: \setupnote
\backslash umistinadsebe {...} ¹ {...} ² 1 CONTENT 2 CONTENT
\backslash umistinamrizku [...] ¹ {...} ² 1 normalni standardni ^{OPT} ano striktni tolerantni vrsek spodek obe široky prizpusobive prvni posledni vysoko jedna nizko zadny radek strut box min max nastred math math:radek math:pulradku math:-line math:-halfline NAME 2 CONTENT
\backslash umistinamrizku [...] ¹ ,... {...} ² 1 inherits: \definegrids ^{OPT} mapping 2 CONTENT
\backslash umistipodrovnici [...] [*] ,... ^{OPT} * + - REFERENCE
\backslash umistipoznamkypodcarou [...] [*] ,... ^{OPT} * inherits: \setupnote
\backslash umistirejstrik [...] ¹ [...] ² ,... ^{OPT} 1 NAME 2 inherits: \nastavrejstrik
\backslash umistiREGISTER [...] [*] ,... ^{OPT} * inherits: \nastavrejstri ^{OPT} k instances: index

$\backslash umistiindex [\dots, \dots, \dots]$ * inherits: $\backslash nastavrejstrik$
$\backslash umistirovnici [\dots, \dots]$ * + - REFERENCE OPT
$\backslash umistiseznam [\dots, \dots] [\dots, \dots, \dots]$ 1 LISTE OPT 2 inherits: $\backslash nastavseznam$
$\backslash umistivedlesebe \{ \dots \} \{ \dots \}$ 1 CONTENT 2 CONTENT
$\backslash umistizalozky [\dots, \dots] [\dots, \dots] [\dots, \dots, \dots]$ 1 ABSCHNITT LISTE OPT OPT OPT 2 ABSCHNITT LISTE 3 inherits: $\backslash setupbookmark$
$\backslash undefinevalue \{ \dots \}$ * NAME
$\backslash undepted \{ \dots \}$ * CONTENT
$\backslash underset \{ \dots \} \{ \dots \}$ 1 TEXT 2 TEXT
$\backslash undoassign [\dots] [\dots]$ 1 TEXT 2 KEY = VALUE
$\backslash unexpandeddocumentvariable \{ \dots \}$ * KEY
$\backslash unhhbox \dots \backslash with \{ \dots \}$ 1 CSNAME NUMBER 2 BEFEHL
$\backslash unihex \{ \dots \}$ * NUMMER
$\backslash uniqueMPgraphic \{ \dots \} \{ \dots, \dots, \dots \}$ 1 NAME OPT 2 KEY = VALUE
$\backslash uniqueMPpagegraphic \{ \dots \} \{ \dots, \dots, \dots \}$ 1 NAME OPT 2 KEY = VALUE
$\backslash unprotect \dots \backslash protect$
$\backslash unprotected \dots \backslash par$ * CONTENT
$\backslash unregisterhyphenationpattern [\dots] [\dots]$ 1 SPRACHE OPT 2 TEXT

$\backslash\text{unspaceafter } \dots \{ \dots \}$ 1 CSNAME 2 TEXT
$\backslash\text{unspaceargument } \dots \backslash\text{to } \dots$ 1 TEXT 2 CSNAME
$\backslash\text{unspaced } \{ \dots \}$ * TEXT
$\backslash\text{unspacestring } \dots \backslash\text{to } \dots$ 1 TEXT 2 CSNAME
$\backslash\text{untexargument } \{ \dots \} \backslash\text{to } \dots$ 1 TEXT 2 CSNAME
$\backslash\text{untexcommand } \{ \dots \} \backslash\text{to } \dots$ 1 CSNAME 2 CSNAME
$\backslash\text{uppercased } \{ \dots \}$ * TEXT
$\backslash\text{uppercasestring } \dots \backslash\text{to } \dots$ 1 TEXT 2 CSNAME
$\backslash\text{upperlefthdoubleninequote}$
$\backslash\text{upperlefthdoublesixquote}$
$\backslash\text{upperleftsingleninequote}$
$\backslash\text{upperleftsinglesixquote}$
$\backslash\text{upperrighthdoubleninequote}$
$\backslash\text{upperrighthdoublesixquote}$
$\backslash\text{upperrightsingleninequote}$
$\backslash\text{upperrightsinglesixquote}$
$\backslash\text{urc} \text{charakteristikurejstriku } [\dots] [\dots, \dots, \dots]$ 1 NAME 2 language = implicitni DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scen SPRACHE metoda = implicitni pred po prvni posledni ch mm zm pm mc zc pc uc numberorder = cisla compress = ano ne vse kriterium = lokalne text aktualni predchozi vse ABSCHNITT
$\backslash\text{url } [\dots]$ * NAME
$\backslash\text{usealignparameter } \dots$ * CSNAME

\useblankparameter *... * CSNAME
\usebodyfont [...*,...] * inherits: \nastavzakladnifont
\usebodyfontparameter *... * CSNAME
\usebtxdataset [¹ ...] [²] [... ³ ...] 1 NAME OPT OPT 2 FILE 3 specification = NAME
\usebtxdefinitions [...*] * FILE
\usecitation [...*] * REFERENCE
\usecitation {...*} * REFERENCE
\usecolors [...*] * FILE
\usecomponent [...*] * FILE
\usedummycolorparameter {...*} * KEY
\usedummystyleandcolor {... ¹ } {... ² } 1 KEY 2 KEY
\usedummystyleparameter {...*} * KEY
\useenvironment [...*] * FILE
\useexternalrendering [... ¹] [... ²] [... ³] [... ⁴] 1 NAME 2 NAME 3 FILE 4 auto embed
\usefigurebase [...*] * reset FILE
\usefile [... ¹] [... ²] [... ³] 1 NAME OPT 2 FILE 3 TEXT
\usegridparameter *... * CSNAME

<code>\useindentingparameter \...</code> <code>* CSNAME</code>
<code>\useindentnextparameter \...</code> <code>* CSNAME</code>
<code>\useinterlinespaceparameter \...</code> <code>* CSNAME</code>
<code>\uselanguageparameter \...</code> <code>* CSNAME</code>
<code>\uselua module [...]</code> <code>* FILE</code>
<code>\useMPenvironmentbuffer [...]</code> <code>* NAME</code>
<code>\useMPgraphic {...} {...,<u>2</u>...,...}</code> <code>1 NAME</code> <code>2 KEY = VALUE</code>
<code>\useMPlibrary [...]</code> <code>* FILE</code>
<code>\useMPrun {...} {...}</code> <code>1 NAME</code> <code>2 NUMMER</code>
<code>\useMPvariables [...¹] [...²,...]</code> <code>1 NAME</code> <code>2 KEY</code>
<code>\usemathstyleparameter \...</code> <code>* CSNAME</code>
<code>\useproduct [...]</code> <code>* FILE</code>
<code>\useprofileparameter \...</code> <code>* CSNAME</code>
<code>\useproject [...]</code> <code>* FILE</code>
<code>\userreferenceparameter \...</code> <code>* CSNAME</code>
<code>\userpagenumber</code>
<code>\usesetupparameter \...</code> <code>* CSNAME</code>
<code>\usestaticMPfigure [...,<u>1</u>...,...][²]</code> <code>1 inherits: \setupscale</code> <code>2 NAME</code>

\usesubpath [...,*...] * PATH
\usetexmodule [... ¹ ...] [... ² ,...] [... ³ ,... ³ ...] 1 m p s x t OPT OPT 2 FILE 3 KEY = VALUE
\usetypescript [... ¹ ...] [... ² ...] [... ³ ...] 1 serif sans mono math ^{OPT} handwriting ^{OPT} calligraphy casual vse 2 NAME fallback implicitni dtp simple 3 size jmeno
\usetypescriptfile [...*...] * reset FILE
\usezipfile [... ¹ ...] [... ² ...] 1 FILE OPT 2 FILE
\utfchar {...} * NUMMER
\utflower {...} * TEXT
\utfupper {...} * TEXT
\utilityregisterlength
\uzijadresar [...,*...] * PATH
\uzijbloky [... ¹ ,...] [... ² ,...] [... ³ ,... ³ ...] 1 NAME OPT OPT 2 NAME 3 kriterium = text ABSCHNITT
\uzijexternidokument [... ¹ ...] [... ² ...] [... ³ ...] 1 NAME OPT 2 FILE 3 TEXT
\uzijexterniobraz [... ¹ ...] [... ² ...] [... ³ ...] [... ⁴ ,... ⁴ ...] 1 NAME OPT OPT 2 FILE 3 NAME 4 inherits: \setupexternalfigure
\uzijexternizvuk [... ¹ ...] [... ² ...] 1 NAME 2 FILE
\uzijJSscripts [... ¹ ...] [... ² ,...] 1 FILE OPT 2 NAME

\uzijmodul [¹ ...] [² ...,...] [³ ...,...] 1 m p s x t <small>OPT</small> <small>OPT</small> 2 FILE 3 KEY = VALUE
\uzijsymbol [...] * FILE
\uzijURL [¹] [²] [³] [⁴] 1 NAME <small>OPT</small> <small>OPT</small> 2 URL 3 FILE 4 TEXT
\uzijurl [...] [²] [³] [⁴] 1 NAME <small>OPT</small> <small>OPT</small> 2 URL 3 FILE 4 TEXT
\VerboseNumber {...} * NUMMER
\VSEDNIDEN {...} * NUMMER
\ vboxreference [... ¹ ,...] {... ² } 1 REFERENCE 2 CONTENT
\vec {...} * CHARACTER
\velke ... * CHARACTER
\verbatim {...} * CONTENT
\verbatimstring {...} * CONTENT
\verbosenummer {...} * NUMMER
\verticalgrowingbar [..., [*] ...,...] * inherits: \setuppositionbar
\verticalpositionbar [..., [*] ...,...] * inherits: \setuppositionbar
\veryraggedcenter
\veryraggedleft
\veryraggedright
\verze [...] * koncept soubor docasne finalni NAME

$\backslash\mathrm{v}\mathrm{g}\mathrm{l}\mathrm{u}\mathrm{e}$... * DIMENSION
$\backslash\mathrm{v}\mathrm{i}\mathrm{e}\mathrm{w}\mathrm{e}\mathrm{r}\mathrm{l}\mathrm{a}\mathrm{y}\mathrm{e}\mathrm{r}$ [...] {...} 1 NAME 2 CONTENT
$\backslash\mathrm{v}\mathrm{l}$ [...] * NUMBER
$\backslash\mathrm{v}\mathrm{l}\mathrm{a}\mathrm{s}\mathrm{o}\mathrm{v}\mathrm{a}\mathrm{l}\mathrm{i}\mathrm{n}\mathrm{k}\mathrm{a}$
$\backslash\mathrm{v}\mathrm{l}\mathrm{e}\mathrm{v}\mathrm{o}$... * CHARACTER
$\backslash\mathrm{v}\mathrm{p}\mathrm{h}\mathrm{a}\mathrm{n}\mathrm{t}\mathrm{o}\mathrm{m}$ {...} * CONTENT
$\backslash\mathrm{v}\mathrm{p}\mathrm{o}\mathrm{s}$ [...] {...} 1 NAME 2 CONTENT
$\backslash\mathrm{v}\mathrm{p}\mathrm{r}\mathrm{a}\mathrm{v}\mathrm{o}$... * CHARACTER
$\backslash\mathrm{v}\mathrm{r}\mathrm{a}\mathrm{d}\mathrm{k}\mathrm{u}$ [...] [...] [...] 1 TEXT OPT 2 REFERENCE
$\backslash\mathrm{v}\mathrm{s}\mathrm{e}\mathrm{d}\mathrm{n}\mathrm{i}\mathrm{d}\mathrm{e}\mathrm{n}$ {...} * NUMBER
$\backslash\mathrm{v}\mathrm{s}\mathrm{m}\mathrm{a}\mathrm{s}\mathrm{h}$ {...} * CONTENT
$\backslash\mathrm{v}\mathrm{s}\mathrm{m}\mathrm{a}\mathrm{s}\mathrm{h}\mathrm{b}\mathrm{o}\mathrm{x}$... * CSNAME NUMBER
$\backslash\mathrm{v}\mathrm{s}\mathrm{m}\mathrm{a}\mathrm{s}\mathrm{h}\mathrm{e}\mathrm{d}$ {...} * CONTENT
$\backslash\mathrm{v}\mathrm{s}\mathrm{p}\mathrm{a}\mathrm{c}\mathrm{e}$ [...] [...] [...] 1 NAME OPT OPT 2 NAME
$\backslash\mathrm{v}\mathrm{s}\mathrm{p}\mathrm{a}\mathrm{c}\mathrm{i}\mathrm{n}\mathrm{g}$ [...]*[...] * nastaveni stejnastranka max sila enable zablokovat zadnabila zhustene zpet prekryv vzdy weak strong implicitni pred mezi po fixne prizpusobive zadny male stredni velke radek pulradku quarterline rovnice bily vyska podlehloubky standardni NUMBER*male NUMBER*stredni NUMBER*velke NUMBER*radek NUMBER*pulradku NUMBER*quarterline NUMBER*rovnice NUMBER*bily NUMBER*vyska NUMBER*podlehloubky category:NUMBER order:NUMBER penalty:NUMBER DIMENSION NAME
$\backslash\mathrm{v}\mathrm{y}\mathrm{b}\mathrm{e}\mathrm{r}\mathrm{b}\mathrm{l}\mathrm{o}\mathrm{k}\mathrm{y}$ [...] ¹ [...] [...] ² [...] [...] [...] ³ [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 kriterium = text ABSCHNITT
$\backslash\mathrm{V}\mathrm{Y}\mathrm{C}\mathrm{E}\mathrm{T}$ [...] ¹ [...] [...] {...} ² [...] [...] ³ \par 1 REFERENCE OPT OPT 2 TEXT 3 CONTENT

$\backslash\text{vyplnenytext}$ [$\dots\overset{1}{=}\dots$] $\{\dots\}^2$ $\{\dots\}^3$ 1 inherits: $\backslash\text{nastavvyplnovelinky}$ OPT OPT 2 TEXT 3 TEXT
$\backslash\text{vyplnovelinky}$ [$\dots\overset{1}{=}\dots$] $\{\dots\}^2$ $\{\dots\}^3$ 1 inherits: $\backslash\text{nastavvyplnovelinky}$ OPT OPT 2 TEXT 3 TEXT
$\backslash\text{vyplnovyradek}$ [$\dots\overset{*}{=}\dots$] * inherits: $\backslash\text{nastavvyplnoveradky}$
$\backslash\text{vysoky}$ $\{\dots\}$ * CONTENT
$\backslash\text{HIGH}$ $\{\dots\}$ * CONTENT instances: unitshigh
$\backslash\text{unitshigh}$ $\{\dots\}$ * CONTENT
$\backslash\text{WidthSpanningText}$ $\{\dots\}^1$ $\{\dots\}^2$ $\{\dots\}^3$ 1 TEXT 2 DIMENSION 3 FONT
$\backslash\text{wdofstring}$ $\{\dots\}$ * TEXT
$\backslash\text{widthhofstring}$ $\{\dots\}$ * TEXT
$\backslash\text{widthspanningtext}$ $\{\dots\}^1$ $\{\dots\}^2$ $\{\dots\}^3$ 1 TEXT 2 DIMENSION 3 FONT
$\backslash\text{withoutpt}$ $\{\dots\}$ * DIMENSION
$\backslash\text{words}$ $\{\dots\}$ * TEXT
$\backslash\text{wordtonumber}$ $\{\dots\}^1$ $\{\dots\}^2$ 1 jedna dve tri ctyri pet 2 TEXT
$\backslash\text{writadatolist}$ [\dots] [$\dots\overset{2}{=}\dots$] [$\dots\overset{3}{=}\dots$] 1 LISTE 2 inherits: $\backslash\text{nastavseznam}$ 3 KEY = VALUE
$\backslash\text{writestatus}$ $\{\dots\}^1$ $\{\dots\}^2$ 1 TEXT 2 TEXT
$\backslash\text{XETEX}$

<code>\XeTeX</code>
<code>\xdefconvertedargument \¹... \²...</code> 1 CSNAME 2 TEXT
<code>\xmladdindex {...}</code> * NODE
<code>\xmlafterdocumentsetup {\¹...} {\²...} {\³...}</code> 1 NAME 2 SETUP 3 SETUP
<code>\xmlaftersetup {\¹...} {\²...}</code> 1 SETUP 2 SETUP
<code>\xmlall {\¹...} {\²...}</code> 1 NODE 2 LPATH
<code>\xmlappenddocumentsetup {\¹...} {\²...}</code> 1 NAME 2 SETUP
<code>\xmlappendsetup {...}</code> * SETUP
<code>\xmlapplyselectors {...}</code> * NODE
<code>\xmlatt {\¹...} {\²...}</code> 1 NODE 2 NAME
<code>\xmlattdef {\¹...} {\²...} {\³...}</code> 1 NODE 2 NAME 3 TEXT
<code>\xmlattribute {\¹...} {\²...} {\³...}</code> 1 NODE 2 LPATH 3 NAME
<code>\xmlattributedef {\¹...} {\²...} {\³...} {\⁴...}</code> 1 NODE 2 LPATH 3 NAME 4 TEXT
<code>\xmlbadinclusions {...}</code> * NODE
<code>\xmlbeforedocumentsetup {\¹...} {\²...} {\³...}</code> 1 NAME 2 SETUP 3 SETUP

<code>\xmlbeforesetup {...} {...}</code> 1 SETUP 2 SETUP
<code>\xmlcommand {...} {...} {...}</code> 1 NODE 2 LPATH 3 XMLSETUP
<code>\xmlconcat {...} {...} {...}</code> 1 NODE 2 LPATH 3 TEXT
<code>\xmlconcatrange {...} {...} {...} {...} {...}</code> 1 NODE 2 LPATH 3 TEXT 4 FIRST 5 LAST
<code>\xmlcontext {...} {...}</code> 1 NODE 2 LPATH
<code>\xmlcount {...}</code> * NODE
<code>\xmldefaulttotext {...}</code> * NODE
<code>\xmldirectives {...}</code> * NODE
<code>\xmldirectivesafter {...}</code> * NODE
<code>\xmldirectivesbefore {...}</code> * NODE
<code>\xmldisplayverbatim {...}</code> * NODE
<code>\xmldoif {...} {...} {...}</code> 1 NODE 2 LPATH 3 TRUE
<code>\xmldoifatt {...} {...}</code> 1 NODE 2 TRUE
<code>\xmldoifelse {...} {...} {...} {...}</code> 1 NODE 2 LPATH 3 TRUE 4 FALSE
<code>\xmldoifelseatt {...} {...} {...}</code> 1 NODE 2 TRUE 3 FALSE

`\xmldoifelseempty {...} {...} {...} {...}`

1 NODE
2 LPATH
3 TRUE
4 FALSE

`\xmldoifelseempty {...} {...} {...}`

1 NODE
2 TRUE
3 FALSE

`\xmldoifelsetext {...} {...} {...} {...}`

1 NODE
2 LPATH
3 TRUE
4 FALSE

`\xmldoifelsevalue {...} {...} {...} {...}`

1 CATEGORY
2 NAME
3 TRUE
4 FALSE

`\xmldoifnot {...} {...} {...}`

1 NODE
2 LPATH
3 TRUE

`\xmldoifnotatt {...} {...}`

1 NODE
2 TRUE

`\xmldoifnotselfempty {...} {...}`

1 NODE
2 TRUE

`\xmldoifnottext {...} {...} {...}`

1 NODE
2 LPATH
3 TRUE

`\xmldoifselfempty {...} {...}`

1 NODE
2 TRUE

`\xmldoiftext {...} {...} {...}`

1 NODE
2 LPATH
3 TRUE

`\xmlelement {...} {...}`

1 NODE
2 NUMMER

`\xmlfilter {...} {...}`

1 NODE
2 LPATH

`\xmlfirst {...} {...}`

1 NODE
2 LPATH

`\xmlflush {...}`

* NODE

<code>\xmlflushcontext {...}</code> * NODE
<code>\xmlflushdocumentsetups {...} {...}</code> 1 NAME 2 SETUP
<code>\xmlflushlinewise {...}</code> * NODE
<code>\xmlflushpure {...}</code> * NODE
<code>\xmlflushspacewise {...}</code> * NODE
<code>\xmlflushtext {...}</code> * NODE
<code>\xmlchainatt {...} {...}</code> 1 NODE 2 NAME
<code>\xmlchainattdef {...} {...} {...}</code> 1 NODE 2 NAME 3 TEXT
<code>\xmlchecknamespace {...} {...}</code> 1 NODE 2 NAME
<code>\xmlinclude {...} {...} {...}</code> 1 NODE 2 LPATH 3 NAME
<code>\xmlinclusion {...}</code> * NODE
<code>\xmlinclusions {...}</code> * NODE
<code>\xmlinfo {...}</code> * NODE
<code>\xmlinjector {...}</code> * NAME
<code>\xmlinlineprettyprint {...} {...}</code> 1 NODE 2 mp lua xml parsed-xml nested tex context zadny NAME
<code>\xmlinlineprettyprinttext {...} {...}</code> 1 NODE 2 mp lua xml parsed-xml nested tex context zadny NAME
<code>\xmlinlineverbatim {...}</code> * NODE

\xmlinstalldirective {...} {...} 1 NAME 2 CSNAME
\xmllast {...} {...} 1 NODE 2 LPATH
\xmllastatt
\xmllastmatch
\xmllastpar
\xmlloadbuffer {...} {...} {...} 1 BUFFER 2 NAME 3 XMLSETUP
\xmlloaddata {...} {...} {...} 1 NAME 2 TEXT 3 XMLSETUP
\xmlloaddirectives {...} * FILE
\xmlloadfile {...} {...} {...} 1 NAME 2 FILE 3 XMLSETUP
\xmlloadonly {...} {...} {...} 1 NAME 2 FILE 3 XMLSETUP
\xmlmain {...} * NAME
\xmlmapvalue {...} {...} {...} 1 CATEGORY 2 NAME 3 TEXT
\xmlname {...} * NODE
\xmlnamespace {...} * NODE
\xmlnonspace {...} {...} 1 NODE 2 LPATH
\xmlpar {...} {...} 1 NODE 2 NAME

<code>\xmlparam {...} {...} {...}</code> 1 NODE 2 LPATH 3 NAME
<code>\xmlpath {...}</code> * NODE
<code>\xmlpos {...}</code> * NODE
<code>\xmlposition {...} {...} {...}</code> 1 NODE 2 LPATH 3 NUMMER
<code>\xmlprependdocumentsetup {...} {...}</code> 1 NAME 2 SETUP
<code>\xmlprependsetup {...}</code> * SETUP
<code>\xmlprettyprint {...} {...}</code> 1 NODE 2 mp lua xml parsed-xml nested tex context zadny NAME
<code>\xmlprettyprinttext {...} {...}</code> 1 NODE 2 mp lua xml parsed-xml nested tex context zadny NAME
<code>\xmlprocessbuffer {...} {...} {...}</code> 1 BUFFER 2 NAME 3 XMLSETUP
<code>\xmlprocessdata {...} {...} {...}</code> 1 NAME 2 TEXT 3 XMLSETUP
<code>\xmlprocessfile {...} {...} {...}</code> 1 NAME 2 FILE 3 XMLSETUP
<code>\xmlpure {...} {...}</code> 1 NODE 2 LPATH
<code>\xmlraw {...}</code> * NODE
<code>\xmlrefatt {...} {...}</code> 1 NODE 2 NAME
<code>\xmlregistereddokumentsetups {...} {...}</code> 1 NAME 2 SETUP

<code>\xmlregisteredsetups</code>
<code>\xmlregisterns {...} {...}</code> 1 NAME 2 URL
<code>\xmlremapname {...} {...} {...} {...}</code> 1 NODE 2 LPATH 3 NAME 4 NAME
<code>\xmlremapnamespace {...} {...} {...}</code> 1 NODE 2 NAME 3 NAME
<code>\xmlremoveddocumentsetup {...} {...}</code> 1 NAME 2 SETUP
<code>\xmlremovesetup {...}</code> * SETUP
<code>\xmlresetdocumentsetups {...}</code> * NAME
<code>\xmlresetinjectors</code>
<code>\xmlresetsetups {...}</code> * NAME
<code>\xmlsave {...} {...}</code> 1 NODE 2 FILE
<code>\xmlsetatt {...} {...} {...}</code> 1 NODE 2 NAME 3 TEXT
<code>\xmlsetAttribute {...} {...} {...} {...}</code> 1 NODE 2 LPATH 3 NAME 4 TEXT
<code>\xmlsetentity {...} {...}</code> 1 NAME 2 TEXT
<code>\xmlsetfunction {...} {...} {...}</code> 1 NODE 2 LPATH 3 LUAFUNCTION
<code>\xmlsetinjectors [...,*,...]</code> * NAME

\xmlsetpar {...} {...} {...}

1 NODE
2 NAME
3 TEXT

\xmlsetparam {...} {...} {...} {...}

1 NODE
2 LPATH
3 NAME
4 TEXT

\xmlsetsetup {...} {...} {...}

1 NAME
2 LPATH
3 SETUP

\xmlsetup {...} {...}

1 NODE
2 SETUP

\xmlshow {...}

* NODE

\xmlsnippet {...} {...}

1 NODE
2 NUMMER

\xmlstrip {...} {...}

1 NODE
2 LPATH

\xmlstripnolines {...} {...}

1 NODE
2 LPATH

\xmlstripped {...} {...}

1 NODE
2 LPATH

\xmlstrippednolines {...} {...}

1 NODE
2 LPATH

\xmltag {...}

* NODE

\xmltexentity {...} {...}

1 NAME
2 TEXT

\xmltext {...} {...}

1 NODE
2 LPATH

\xmltobuffer {...} {...} {...}

1 NODE
2 LPATH
3 BUFFER

\xmltobufferverbose {...} {...} {...}

1 NODE
2 LPATH
3 BUFFER

\xmltofile {...} {...} {...} 1 NODE 2 LPATH 3 FILE
\xmlvalue {...} {...} {...} 1 CATEGORY 2 NAME 3 TEXT
\xmlverbatim {...} * NODE
\xsplitstring \... {...} 1 CSNAME 2 TEXT
\xypos {...} * NAME
\Znak {...} * NUMMER
\Znaky {...} * NUMMER
\zadnamezera
\zadnehorniadolniradky
\zadnezahlaviaupati
\zachovejbloky [... ¹ ,...] [... ² ,...] <small>OPT</small> 1 NAME 2 NAME
\zalozka [... ¹] {... ² } 1 ABSCHNITT <small>OPT</small> LISTE 2 TEXT
\zapisdoseznam [... ¹] [... ² ,... ² ,...] {... ³ } {... ⁴ } <small>OPT</small> 1 LISTE 2 inherits: \nastavseznam 3 NUMMER 4 TEXT
\zapismeziseznam [... ¹] [... ² ,... ² ,...] {... ³ } <small>OPT</small> 1 LISTE 2 inherits: \nastavseznam 3 BEFEHL
\zaramovani [... ¹ ,... ¹ ,...] {... ² } <small>OPT</small> 1 inherits: \nastavor ^{OPT} amovani 2 CONTENT
\zarovnanonastred {...} * CONTENT
\zarovnanovlevo {...} * CONTENT

$\backslash\text{zarovnanovpravo}$ {...} * CONTENT
$\backslash\text{zasobnikpoli}$ [...] ¹ [..., ² ...] [..., ³ ...] 1 NAME 2 NAME 3 inherits: \setupfieldcategory
$\backslash\text{ziskejbuffer}$ [...] * BUFFER OPT
$\backslash\text{ziskatBUFFER}$
$\backslash\text{ziskejznaceni}$ [...] ¹ [...] ² [...] ³ 1 BESCHRIFTUNG OPT OPT 2 stranka NAME 3 prvi posledni aktualni predchozi dalsi vrsek spodek implicitni obe vse first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck
$\backslash\text{FRACTION}$ {...} ¹ {...} ² 1 CONTENT 2 CONTENT instances: xfrac xxfrac frac sfrac dfrac binom dbinom tbinom
$\backslash\text{binom}$ {...} ¹ {...} ² 1 CONTENT 2 CONTENT
$\backslash\text{dbinom}$ {...} ¹ {...} ² 1 CONTENT 2 CONTENT
$\backslash\text{dfrac}$ {...} ¹ {...} ² 1 CONTENT 2 CONTENT
$\backslash\text{frac}$ {...} ¹ {...} ² 1 CONTENT 2 CONTENT
$\backslash\text{sfrac}$ {...} ¹ {...} ² 1 CONTENT 2 CONTENT
$\backslash\text{tbinom}$ {...} ¹ {...} ² 1 CONTENT 2 CONTENT
$\backslash\text{xfrac}$ {...} ¹ {...} ² 1 CONTENT 2 CONTENT
$\backslash\text{xxfrac}$ {...} ¹ {...} ² 1 CONTENT 2 CONTENT
$\backslash\text{znaceni}$ (..., ¹ ...) (..., ² ...) [...] ³ 1 POSITION 2 POSITION 3 REFERENCE

$$\backslash \text{znak} \{ \dots \}$$

* NUMMER

\znaky {.*.}

* NUMMER

$$\backslash\text{zpracujbloky } [\dots^1, \dots] [\dots^2, \dots] [\dots^3 = \dots, \dots]$$

1 NAME

1	NAME
2	NAME

```
3 kriterium = text ABSCHNITT
```

```
\zrcadlit {...}
```

* CONTENT

\zref [...*...]

* REFERENCE

\zvysit \.*..

* CSNAME

`\zvysit cd:parentheses-1`

* CSNAME NUMMER



PRAGMA ADE
Ridderstraat 27
8061GH Hasselt NL
www.pragma-ade.com